

BOOK 5162

FIELD NOTES

PAGE 01

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,

A PORTION OF THE SOUTH BOUNDARY OF TOWNSHIP 7 SOUTH, RANGE 21 WEST

(THE NORTH BOUNDARY OF SECTION 1, TOWNSHIP 8 SOUTH, RANGE 21 WEST),

A PORTION OF THE SUBDIVISIONAL LINES;

THE SURVEY OF A PORTION OF THE SUBDIVISION LINES

WITHIN SECTIONS 1, 3, 4, 5, AND 8,

THE METES AND BOUNDS SURVEY OF LOT 26 AND PARCEL A WITHIN SECTION 1,

LOT 16 OF SECTION 4, LOT 6 OF SECTION 5, AND LOTS 13 AND 14,

PARCELS A, B, C, D, AND E, WITHIN SECTION 8;

THE METES AND BOUNDS SURVEY OF TRACTS 37 THROUGH 42 INCLUSIVE

TOWNSHIP 8 SOUTH, RANGE 21 WEST

Of the _____ GILA AND SALT RIVER _____ Meridian,

In the State of _____ ARIZONA _____

EXECUTED BY

RAY HARPIN

CADASTRAL SURVEYOR

DOUGLAS A. CODY

CADASTRAL SURVEYOR

SANTIAGO T. CHAVEZ

CADASTRAL SURVEYOR

Under special instructions dated OCTOBER 14, 1969, approved OCTOBER 27, 1969,
SUPPLEMENTAL SPECIAL INSTRUCTIONS DATED NOVEMBER 20, 1969, APPROVED NOVEMBER 21,
1969, SUPPLEMENTAL SPECIAL INSTRUCTIONS DATED SEPTEMBER 5, 1979, APPROVED SEPTEMBER
13, 1979, AND SUPPLEMENTAL SPECIAL INSTRUCTIONS DATED OCTOBER 20, 1980, APPROVED
OCTOBER 27, 1980, which provided for the surveys included under ~~XXXX Survey~~ Group
Number 517, and assignment instructions dated OCTOBER 14, 1969.
AND OCTOBER 14, 1980

Survey commenced FEBRUARY 18, 1970

Survey completed DECEMBER 4, 1980

INDEX DIAGRAM

Township 8 SOUTH, Range 21 WEST,

6	5 21 25	4 15 19	3 12 13	2 10	6 1 3 8
7 24	8 17 22	9	10	11	2 12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Survey of Subdivision Lines

- Section 1 . . . p. 26
- Section 3 . . . p. 35
- Section 4 . . . p. 42
- Section 5 . . . p. 46
- Section 8 . . . p. 48

Metes and Bounds Surveys within Sections

- Lot 26, Sec. 1 . . . p. 32
- Parcel A, Sec. 1 . . . p. 33
- Lot 16, Sec. 4 . . . p. 45
- Lot 6, Sec. 5 . . . p. 47
- Lot 13, Sec. 8 . . . p. 54
- Lot 14, Sec. 8 . . . p. 55
- Parcel A, Sec. 8 . . . p. 56
- Parcel B, Sec. 8 . . . p. 57
- Parcel C, Sec. 8 . . . p. 59
- Parcel D, Sec. 8 . . . p. 61
- Parcel E, Sec. 8 . . . p. 63

Metes and Bounds Surveys

- Tract 37 . . . p. 66
- Tract 38 . . . p. 68
- Tract 39 . . . p. 72
- Tract 40 . . . p. 75
- Tract 41 . . . p. 76
- Tract 42 . . . p. 78

Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of the dependent resurvey of a portion of the east boundary of the township, a portion of the south boundary of Tp. 7 S., R. 21 W. (the north boundary of section 1, Tp. 8 S., R. 21 W.), and a portion of the subdivisional lines; survey of a portion of the subdivision lines within sections 1, 3, 4, 5, and 8; the metes and bounds survey of Lot 26, and Parcel A within section 1, lot 16 of section 4, lot 6 of section 5, and lots 13 and 14, Parcels A, B, C, D, and E within section 8; and the metes and bounds survey of Tracts 37 through 42 inclusive, Township 8 South, Range 21 West, of the Gila and Salt River Meridian, Arizona.

History of Previous Surveys: A portion of the south and east boundaries, the west and the north boundaries, and a portion of the subdivisional lines were originally surveyed by James H. Martineau, U.S. Deputy Surveyor, in 1890, as shown upon the official plat approved December 18, 1890. The east boundary of the township, a portion was resurveyed and a portion was surveyed as the west boundary of Tp. 8 S., R. 20 W. by William B. Kimmel, U.S. Surveyor, in 1915 and 1916, as shown upon the official plat of that township, approved March 20, 1918. The north boundary of the township was resurveyed as the south boundary of Tp. 7 S., R. 21 W. by Francis E. Joy, U.S. Cadastral Engineer, in 1930, as shown upon the official plat of that township, approved December 14, 1931 and accepted May 9, 1932. A portion of the south and west boundaries, and a portion of the subdivisional lines were dependently resurveyed by Robert S. Kaiser, Cadastral Surveyor, in 1960 and 1961, as shown upon the official plat, accepted, January 24, 1962. A portion of the east boundary was dependently resurveyed; a portion of the south boundary and a portion of the subdivisional lines were surveyed by Phil D. Smith, Cadastral Surveyor, in 1957, and Paul G. Bauer, Surveying Technician, in 1962, as shown upon the official plat accepted May 9, 1962.

These dependent resurveys and surveys were executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947 and 1973 Editions, and the Special Instructions dated October 14, 1969, Supplemental Special Instructions dated November 20, 1969, Supplemental Special Instructions dated September 5, 1979, and Supplemental Special Instructions dated October 20, 1980.

The direction of all lines of these surveys were determined from direct altitude observations on the sun for azimuth, and these directions refer to the true meridian. The lines were carried forward by normal transit traverse. Distances are expressed in chains and reduced to horizontal equivalents.

Prior to the restoration of any corner, all necessary lines of the original surveys were retraced and a diligent search was made for any evidence of the original record. Identified corners were remonumented in their original positions. Lost corners were reestablished at proportionate positions, but not until exhausting every reasonable possibility of finding direct evidence for the control of each corner.

Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS

The geographic position of the corner of secs. 8, 9, 16, and 17, determined by scaling from an U.S. Geological Survey Quadrangle Map, 7 1/2 minute series "Fortuna, Arizona, 1965", is as follows: Latitude 32° 44.6' N. and Longitude 114° 25.6' W. The mean magnetic declination 14° East.

Dependent Resurvey of a Portion of the East Boundary
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

The east 1/4 sec. cor. of sec. 12, Tp. 8 S., R. 21 W., which is monumented with an iron post, 2 1/2 ins. in diam., firmly set in a small mound of stone, projecting 9 ins. above the surface of the ground, with brass cap mkd.

T8S
R21W|
1/4|
S 12|

1962

The above corner was remonumented by Paul G. Bauer, Surveying Technican, in 1962; as described in the official field-note record of the dependent resurvey of a portion of the east boundary and shown upon the official plat of Tp. 8 S., R. 21 W., accepted May 9, 1962.

Restoring the Resurvey Executed
by William B. Kimmel, U.S. Surveyor
1915 and 1916

N. 0° 05' W., on the east boundary of Tp. 8 S., R. 21 W., and on the east boundary of sec. 12.

Descend over gently rolling northeast slope.

1.74

The closing corner of secs. 6 and 7 on the west boundary of Tp. 8 S., R. 20 W., which is monumented with an iron post, 2 ins. in diam., firmly set, projecting 9 ins. above the surface of the ground, with regulation General Land Office brass cap mkd.

Dependent Resurvey of a Portion of the East Boundary
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">T8S T8S R21W S 6 CC S 12 S 7 R20W</p> <p style="text-align: center;">1916</p> <p>Substantiated by:</p> <p style="padding-left: 40px;">A mound of stone, 4 ft. base, 2 1/2 ft. high, west of the corner.</p> <p>Continue with course and measurement.</p> <p>40.035 The cor. of secs. 1 and 12 is marked with an iron pipe, 30 ins. long, 2 ins. in diam., with brass cap loose alongside, mkd. for the corner of secs. 1 and 12, 1939, with the top of the iron pipe, 9 ins. below the surface of the road, and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 8 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">T8S R21W R20W S 1 S 6 S 12 </p> <p style="text-align: center;">1970</p> <p>Deposit the iron pipe corner marker and brass cap alongside the iron post.</p>	
1.745	<hr/> <p>N. 0° 05' W., along the east boundary of sec. 1</p> <p>Over nearly level land, along north and south road.</p> <p>The west 1/4 sec. cor. of sec. 6, Tp. 8 S., R. 20 W., is monumented with an iron post, 2 1/2 ins. in diam., with brass cap 7 ins. below the surface of the road, and is marked as described in the official field-note record of the dependent resurvey of a portion of the subdivision lines within sec. 6, Tp. 8 S., R. 20 W., executed concurrently with this group.</p> <p style="text-align: center;">Restoring the Survey Executed by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954</p> <hr/> <p>Continue with the above course and measurement.</p>	

Dependent Resurvey of a Portion of the East Boundary
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS	
3.92	<p>The point for the meander corner of sec. 1, on the right bank of the Gila River is determined at proportionate distance; there is no evidence of the original corner. I did not remonument this corner point.</p>
15.54	<p>The point for Corner No. 1, Lot 26, sec. 1</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R21W R20W S 1 COR 1 S 6 L 26 </p> </div> <p style="text-align: center;">1980</p>
19.195	<p>The point for Angle Point No. 7, Tract 40, Tp. 8 S., R. 21 W.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 8 ins. below the surface of the road, mkd.</p> <div style="text-align: center;"> <p>TR 40 AP 7 — S 1 S 6 R21W R20W T8S</p> </div> <p style="text-align: center;">1970</p>
20.06	<p>The south 1/16 sec. cor. of sec. 1 on the east boundary of the township, is marked with an iron pipe, 1-inch in diam., with brass cap 8 ins. below the surface of the road, mkd.</p> <div style="text-align: center;"> <p>BUREAU OF RECLAMATION S 1/16 — S 1 — </p> </div> <p style="text-align: center;">1952</p> <p>The above corner marker is accepted as the position of the corner. I did not remonument this corner.</p> <hr style="width: 20%; margin: 10px auto;"/>
1.685	<p>N. 0° 05' W., beginning new measurement.</p> <p>The north 1/16 sec. cor. of sec. 6, which is designated to function for Angle Point No. 7, Tract 37, Tp. 8 S., R. 20 W., is located on the west boundary of the above township, and is monumented with an iron post, 2 1/2 ins. in diam., with brass cap 8 ins. below the surface of the road, is marked as described in the official field-note record of the dependent resurvey of a portion of the subdivision lines within sec. 6, Tp. 8 S., R. 20 W., executed concurrently with this group.</p> <p>Continue with course and measurement.</p>

Dependent Resurvey of a Portion of the East Boundary
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS			
11.985		<p>Angle Point No. 3, lot 11 of sec. 6, which is identical with Angle Point No. 6, Tract 37, Tp. 8 S., R. 20 W., is monumented with an iron post, 2 1/2 ins. in diam., with brass cap 6 ins. below the surface of the road, and is marked as described in the official field-note record of the dependent resurvey of a portion of the subdivision lines within sec. 6, Tp. 8 S., R. 20 W., executed concurrently with this group.</p> <p>Continue with course and measurement</p>	
14.31		<p>The point for Angle Point No. 1, Tract 40, Tp. 8 S., R. 21 W.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 8 ins. below the surface of the road, mkd.</p> <div style="text-align: center;"> <p>T8S R21W R20W S 1 S 6 / AP 1 TR 40 </p> <p>1970</p> </div> <p>There are no suitable accessories nor locations available for reference monuments.</p>	
20.055		<p>The east 1/4 sec. cor. of sec. 1, is marked with an iron pipe, 1-inch in diam., with brass cap 29 ins. below the surface of the road, mkd.</p> <div style="text-align: center;"> <p>BUREAU OF RECLAMATION 1/4 S 1 </p> <p>1952</p> </div> <p>The above corner marker is accepted as the best available evidence of the position of the original corner. This corner was not remonumented.</p> <hr style="width: 20%; margin: 20px auto;"/>	
2.00		<p>N. 0° 05' W., beginning new measurement</p> <p>The closing corner of secs. 6 and 31, Tps. 7 and 8 S., R. 20 W., which is marked with an iron pipe, 2 ins. in diam., with brass cap 20 ins. below the surface of the road, and is marked as described in the official field-note record of the dependent resurvey of a portion of the north boundary of Tp. 8 S., R. 20 W., executed concurrently with this group.</p> <p>Continue with course and measurement</p>	
20.07		<p>The point for the north 1/16 sec. cor. of sec. 1 on the east boundary of the township. I did not monument this corner point.</p>	

08

Dependent Resurvey of a Portion of the East Boundary
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

<p>CHAINS 29.535</p>	<p>The point for Angle Point No. 7, Tract 41, Tp. 8 S., R. 21 W.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 12 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">T8S T7S R21W R20W TR 41 S 31 <u>AP 7 </u> S 1 </p> <p style="text-align: center;">1980</p>	
<p>40.14</p>	<p>The corner of Tps. 7 and 8 S., R. 21 W. (secs. 1 and 36) is monumented with an iron post, 3 ins. in diam., with regulation (G.L.O.) brass cap 7 ins. below the surface of the road; the marking on this brass cap had been destroyed and I marked, as:</p> <p style="text-align: center;">T7S R21W R20W <u>S 36 S 31</u> S 1 T8S </p> <p style="text-align: center;">1980</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the South Boundary Township 7 South, Range 21 West (The north Boundary of Tp. 8 S., R. 21 W.) Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Restoring the Dependent Resurvey executed by Francis E. Joy, U.S. Cadastral Engineer in 1930</p> <hr/> <p>N. 88° 52' W., along the south boundary of Tp. 7 S., R. 21 W. (the north boundary of sec. 1, Tp. 8 S., R. 21 W.).</p>	
<p>20.01</p>	<p>The east 1/16 sec. cor. of sec. 36 (only) is marked with an iron pipe, 1-inch in diam., with brass cap 15 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION E 1/16 <u>S 36</u></p> <p style="text-align: center;">1952</p> <p>This corner marker is accepted as the position of the corner. This corner was not remonumented.</p> <hr/> <p>S. 89° 07' W., beginning new measurement</p>	

Dependent Resurvey of a Portion of the South Boundary
 Township 7 South, Range 21 West
 (The north Boundary of Tp. 8 S., R. 21 W.)
 Gila and Salt River Meridian, Arizona

CHAINS	
0.085	<p>The east 1/16 sec. cor. of sec. 1 (only) Tp. 8 S., R. 21 W. is marked with an iron pipe, 1-inch in diam., with brass cap 15 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION</p> <p style="text-align: center;"><u>E 1/16</u> S 1</p> <p style="text-align: center;">1952</p> <p>This corner marker is accepted as the position of the corner. This corner was not remonumented.</p> <p>Continue with course and measurement</p>
19.985	<p>The south 1/4 sec. cor. of sec. 36 is marked with an iron pipe, 1-inch in diam., with brass cap 15 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION</p> <p style="text-align: center;"><u>1/4 S 36</u></p> <p style="text-align: center;">1952</p> <p>This corner marker is accepted as the best available evidence of the position of the original corner. This corner was not remonumented.</p> <p style="text-align: center;">_____</p> <p>N. 89° 52' W., beginning new measurement</p>
0.17	<p>The north 1/4 sec. cor. of sec. 1, Tp. 8 S., R. 21 W. is marked with an iron pipe, 1-inch in diam., with brass cap 15 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION</p> <p style="text-align: center;"><u>1/4 S 1</u></p> <p style="text-align: center;">1952</p> <p>This corner marker is accepted as the best available evidence of the position of the original corner. This corner was not remonumented.</p> <p>Continue with course and measurement</p>
19.99	<p>The west 1/16 sec. cor. of sec. 36 (only) is marked with an iron pipe, 1-inch in diam., with brass cap 15 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION</p> <p style="text-align: center;">W 1/16 <u>S 36</u></p> <p style="text-align: center;">1952</p> <p>This corner marker is accepted as the position of the corner. This corner was not remonumented.</p> <p style="text-align: center;">_____</p>

Dependent Resurvey of a Portion of the South Boundary
 Township 7 South, Range 21 West
 (The north Boundary of Tp. 8 S., R. 21 W.)
 Gila and Salt River Meridian, Arizona

CHAINS

N. 89° 53' W., beginning new measurement

0.255

The west 1/16 sec. cor. of sec. 1 (only) Tp. 8 S., R. 21 W. is marked with an iron pipe, 1-inch in diam., with brass cap 15 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION

W 1/16 S 1

1952

This corner marker is accepted as the position of the corner. This corner was not remonumented.

Continue with course and measurement

19.995

The corner of secs. 35 and 36 is monumented with an iron post, 2 ins. in diam., with regulation (G.L.O.) brass cap 12 ins. below the surface of the road, mkd.

T7S R21W
S 35 | S 36
 T8S R21W
 S 1

1930

Discontinue the dependent resurvey of this township line at this corner.

Dependent Resurvey of a Portion of the
 Subdivisional Lines
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

Restoring the Survey Executed
 by James H. Martineau,
 U.S. Deputy Surveyor,
 in 1890

From the corner of secs. 1 and 12 on the east boundary of the township, heretofore described.

N. 89° 57' W., between secs. 1 and 12

Over nearly level land.

1.17

Intersect the medial line of the abandoned (1890) Gila River channel. The point for the Special Meander Corner of secs. 1 and 12.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R21W
S 1 / S 12 SMC

1980

Dependent Resurvey of a Portion of the
Subdivisional Lines
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS	
8.20	The northern bank of the Wellton-Mohawk Canal, flows on curve to the southeast.
8.965	The point for the meander corner of secs. 1 and 12 on the left bank of the Gila River is determined at proportionate distance; this corner point is located within the bed of the canal, where it is impracticable to establish a permanent monument.
10.10	The southern bank of the Wellton-Mohawk Canal.
10.90	Road, bears parallel to the above canal.
19.92	The east 1/16 sec. cor. of secs. 1 and 12 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 13 ins. above the surface of the ground, with brass cap mkd.
BUREAU OF RECLAMATION E 1/16 S 1 <hr style="width: 10%; margin: 0 auto;"/> S 12 1952	
The above corner marker is accepted as the position of the corner. I did not remonument this corner.	
<hr style="width: 20%; margin: 0 auto;"/>	
N. 89° 54' W., beginning new measurement	
19.92	The 1/4 sec. cor. of secs. 1 and 12 is marked with an iron pipe, 36 ins. long, 1-inch in diam., firmly set 26 ins. in the ground, with brass cap mkd.
BUREAU OF RECLAMATION 1/4 $\frac{S 1}{S 12}$ 1941	
The above corner marker is accepted as the best available evidence of the position of the original corner.	
At the corner point	
Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 24 ins. in the ground, with brass cap mkd.	
T8S R21W 1/4 $\frac{S 1}{S 12}$ 1977	
Deposit the iron pipe corner marker alongside the iron post.	
Discontinue the regular order of survey at this corner.	

Dependent Resurvey of a Portion of the
Subdivisional Lines
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS

The corner of secs. 1, 2, 11, and 12 is marked with an iron pipe, 2 ins. in diam., firmly set, projecting 10 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

T8S R21W

S 2 | S 1

S 11 | S 12

1941

The above corner marker is accepted as the best available evidence of the position of the original corner. I did not remonument this corner.

N. 0° 35' W., between secs. 1 and 2

Over rolling land.

10.70 The center line of the Southern Pacific Railroad, bears N. 84° 22' E. and S. 84° 22' W.

Thence, over nearly level land.

15.40 Road, bears parallel to the hereinafter described canal.

15.95 The southern bank of the Wellton-Mohawk Canal, flows N. 80° 45' E.

16.52 The point for the meander corner of secs. 1 and 2, on the left bank of the Gila River is determined at proportionate distance; this corner point is located within the bed of the canal, where it is impracticable to establish a permanent monument.

17.20 The northern bank of the Wellton-Mohawk Canal,

17.70 Road, bears parallel to the heretofore described canal.

20.072 The point for the south 1/16 sec. cor. of secs. 1 and 2

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

S 1/16

S 2 | S 1

1970

23.432 The point for Angle Point No. 3, Tract 40

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

| TR 40

| AP 3

S 2 | S 1
T8S R21W

1970

Dependent Resurvey of a Portion of the
 Subdivisional Lines
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS	
24.25	The point for the meander corner of secs. 1 and 2 on the right bank of the Gila River is determined at proportionate distance; there is no evidence of the original corner. I did not monument this corner point.
38.615	The point for Angle Point No. 2, Tract 40 Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T8S R21W S 2 S 1 AP 2 TR 40 1970 </div>
39.545	Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, for the witness 1/4 sec. cor. of secs. 1 and 2, with brass cap mkd. <div style="text-align: center;"> W C T8S R21W ↑ 1/4 S 2 S 1 1970 </div>
40.145	The true point for the 1/4 sec. cor. of secs. 1 and 2 is determined at proportionate distance; this true corner point is located within a lateral, where it is impracticable to establish a permanent monument.
60.217	The point for the north 1/16 sec. cor. of secs. 1 and 2. I did not monument this corner point.
80.33	The corner of secs. 1 and 2 on the north boundary of the township, is monumented with an iron post, 2 ins. in diam., with regulation General Land Office brass cap 12 ins. below the surface of the road, mkd. <div style="text-align: center;"> T7S R21W S 35 <hr style="width: 50px; margin: 0 auto;"/> S 2 S 1 T8S R21W 1930 </div> <p>The above corner was reestablished by Francis E. Joy, U.S. Cadastral Engineer, in 1930, and is described in the official field-note record of the resurvey of the south boundary of Tp. 7 S., R. 21 W., approved December 14, 1931 and accepted May 9, 1932.</p> <p>From this corner, the corner of secs. 35 and 36 on the south boundary of Tp 7 S., R. 21 W., heretofore described, bears S. 89° 30' E., 0.345 chs. distant.</p> <p>Discontinue the regular order of survey at this corner.</p>

Dependent Resurvey of a Portion of the
Subdivisional Lines
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS

The corner of secs. 2, 3, 10, and 11, which is designated to function for the meander corner for the left bank of the Gila River, is marked with an iron pipe, 2 ins. in diam., firmly set, projecting 3 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION
T8S R21W
S 3 | S 2
S 10 | S 11

1941

From this corner, a witness corner to this corner bears S. 1° 00' E., 6.14 chs. distant, and is marked with an iron pipe, 2 ins. in diam., firmly set, projecting 10 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION
W C
T8S R21W
S 3 | S 2
S 10 | S 11
405 - N

1949

The above corner marker is accepted as the best available evidence of the position of the original corner. I did not remonument this corner.

N. 1° 00' W., between secs. 2 and 3

Over nearly level land.

- | | |
|--------|---|
| 2.35 | Road, bears parallel to the hereinafter described canal. |
| 2.75 | The southern bank of the Wellton-Mohawk Canal, flows N. 80° 20' E. |
| 3.72 | Intersect the medial line of the abandoned (1890) Gila River channel. The point for the Special Meander Corner of secs. 2 and 3; this corner point is located within the bed of the above canal, where it is impracticable to establish a permanent monument. |
| 4.00 | The northern bank of the Wellton-Mohawk Canal. |
| 4.50 | Road, bears parallel to the heretofore described canal. |
| 7.44 | The point for the meander corner of secs. 2 and 3 on the right bank of the abandoned (1890) Gila River is determined at proportionate distance; there is no evidence of the original corner. I did not monument this corner point. |
| 20.105 | The point for the south 1/16 sec. cor. of secs. 2 and 3. I did not monument this corner point. |
| 40.21 | The point for the 1/4 sec. cor. of secs. 2 and 3 is determined at proportionate distance; there is no evidence of the original corner. |

Dependent Resurvey of a Portion of the
Subdivisional Lines
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R21W

1/4

S 3 | S 2

1970

80.54

The corner of secs. 2 and 3 on the north boundary of the township, which is monumented with an iron post, 2 ins. in diam., firmly set, projecting 8 ins. above the surface of the ground, with regulation General Land Office brass cap mkd.

T7S R21W

S 34

S 3 | S 2

T8S R21W

1930

substantiated by:

A mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, north of the corner.

The above corner was reestablished by Francis E. Joy, U.S. Cadastral Engineer, in 1930, and is described in the official field-note record of the resurvey of the south boundary of Tp. 7 S., R. 21 W., approved December 14, 1931 and accepted May 9, 1932.

From this same corner, the corner of secs. 34 and 35 on the south boundary of Tp. 7 S., R. 21 W., bears S. 89° 49' E., 0.70 chs. distant, and is monumented with an iron post, 2 ins. in diam., firmly set, projecting 10 ins. above the surface of the ground, with regulation General Land Office brass cap mkd.

T7S R21W

S 34 | S 35

T8S R21W

S 2

1930

substantiated by:

A mound of stone, 3 ft. base, 2 ft. high, east of the corner.

The above corner was established by Francis E. Joy, U.S. Cadastral Engineer, in 1930, and is described in the official field-note record of the resurvey of the south boundary of Tp. 7 S., R. 21 W., approved December 14, 1931 and accepted May 9, 1932.

Discontinue the regular order of survey at this corner.

From the corner of secs. 2, 3, 10, and 11, which is designated to function for the meander corner for the left bank of the Gila River, heretofore described.

N. 89° 56' W., between secs. 3 and 10

Dependent Resurvey of a Portion of the
Subdivisional Lines
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS		
	Over nearly level land.	
1.85	A Bureau of Reclamation bench mark, a regulation brass tablet seated on top of a concrete cylinder, 6 ins. in diam., firmly set, projecting 4 ins. above the surface of the ground, with brass tablet mkd. 166.178	
32.00	The center line of the Southern Pacific Railroad (northern tract), bears N. 71° 00' W. and S. 71° 00' E.	
32.75	The center line of the Southern Pacific Railroad (southern tract), bears parallel to the above tract.	
39.85	The 1/4 sec. cor. of secs. 3 and 10 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 12 ins. above the surface of the ground, with brass cap mkd.	
	BUREAU OF RECLAMATION $1/4 \frac{S \ 3}{S \ 10}$ 1941	
	The above corner marker is accepted as the best available evidence of the position of the original corner. I did not remonument this corner.	

	N. 89° 56' W., beginning new measurement	
19.92	The west 1/16 sec. cor. of secs. 3 and 10 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 15 ins. above the surface of the ground, with brass cap mkd.	
	BUREAU OF RECLAMATION $W \ 1/16$ $\frac{S \ 3}{S \ 10}$ 1952	
	The above corner marker is accepted as the position of the corner. I did not remonument this corner.	

	N. 89° 56' W., beginning new measurement	
1.50	Spur, slopes north.	
4.20	Wash, drains north.	
14.55	The center line of the Southern Pacific Railroad (southern tract), bears on curve to the northeast and southwest.	
14.85	The center line of the Southern Pacific Railroad (northern track), bears parallel to the above track.	
19.93	The corner of secs. 3, 4, 9, and 10 is marked with an iron pipe, 2 ins. in diam., firmly set, projecting 8 ins. above the surface of the ground, with brass cap mkd.	

Dependent Resurvey of a Portion of the
Subdivisional Lines
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS

BUREAU OF RECLAMATION

T8S R21W

S 4 | S 3

S 9 | S 10

1941

The above corner marker is accepted as the best available evidence of the position of the original corner. I did not remonument this corner.

N. 0° 56' W., between secs. 3 and 4

Over nearly level land.

- 3.50 Road, bears parallel to the hereinafter described canal.
- 4.00 The southern bank of the Wellton-Mohawk Canal, flows N. 62° 30' E.
- 5.35 The northern bank of the Wellton-Mohawk Canal.
- 5.85 Road, bears parallel to the heretofore described canal.
- 7.25 Lateral, bears parallel to the above canal.
- 17.36 The point for Angle Point No. 18, Tract 38 and Angle Point No. 4, Tract 39.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R21W

TR 38 | TR 39

AP 18 | AP 4

S 4 | S 3

1970

- 20.12 The south 1/16 sec. cor. of secs. 3 and 4 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 14 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

S 1/16

S 4 | S 3



1952

The above corner marker is accepted as the position of the corner. I did not remonument this corner.

N. 0° 56' W., beginning new measurement

- 8.70 The center line of U.S. Highway No. 95, bears N. 47° 40' E. and S. 47° 40' W.
- 13.06 The point for Angle Point No. 1, Tract 38 and Angle Point No. 3, Tract 39.

Dependent Resurvey of a Portion of the
Subdivisional Lines
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R21W S 4 S 3  AP 1 AP 3 TR 38 TR 39</p> <p style="text-align: center;">1970</p>
13.275	The point for the meander corner of secs. 3 and 4, on the left bank of the Gila River is determined at proportionate distance; there is no evidence of the original corner. I did not monument this corner point.
16.105	<p>Intersect the medial line of the abandoned (1890) Gila River channel. The point for the Special Meander Corner of secs. 3 and 4.</p> <p>Set an iron post, 28 ins. long 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R21W S 4 S 3  SMC</p> <p style="text-align: center;">1980</p>
18.935	The point for the meander corner of secs 3. and 4, on the right bank of the Gila River is determined at proportionate distance; there is no evidence of the original corner. I did not monument this corner point.
20.11	<p>The point for the 1/4 sec. cor. of secs. 3 and 4 is determined at proportionate distance; there is no evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R21W 1/4 S 4 S 3</p> <p style="text-align: center;">1980</p>
40.22	<p>The north 1/16 sec. cor. of secs. 3 and 4 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 11 ins. above the surface of the ground, mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION N 1/16 S 4 S 3</p> <p style="text-align: center;">1952</p> <p>The above corner marker is accepted as the position of the corner. I did not remonument this corner.</p> <p>Discontinue the regular order of survey at this corner.</p> <hr/>

Dependent Resurvey of a Portion of the
Subdivisional Lines
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS

The corner of secs 8, 9, 16, and 17 is marked with an iron pipe, 2 ins. in diam., with brass cap flush with the surface of the ground, mkd.

US RECLAMATION SERVICE

T8S R21W

S 8 | S 9

S 17 | S 16

1914

The above corner marker is accepted as the best available evidence of the position of the original corner.

N. 0° 09.5' E., between secs. 8 and 9.

Through an area of excavation of gravel pit.

19.985

The south 1/16 sec. cor. of secs. 8 and 9 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 14 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

S 1/16

S 8 | S 9

1954

The above corner marker is accepted as the position of the corner. I did not remonument this corner.

N. 0° 09.5' E. beginning new measurement

Over nearly level land.

4.09

The point for the meander corner of secs. 8 and 9 on the left bank of the Gila River is determined at proportionate distance; there is no evidence of the original corner. I did not monument this corner point.

8.69

Intersect the medial line of the abandoned (1890) Gila River channel. The point for the Special Meander Corner of secs. 8 and 9.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R21W

S 8 | S 9

COR 1 | SMC

PAR E |

1970

This corner is designated to function for Corner No. 1, Parcel E of sec. 8.

Dependent Resurvey of a Portion of the
Subdivisional Lines
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS	
10.40	Road, bears parallel to the hereinafter described canal.
11.25	The southern bank of the Wellton-Mohawk Canal, flows N. 51° 50' E.
12.50	The northern bank of the Wellton-Mohawk Canal.
13.29	The point for the meander corner of secs. 8 and 9 on the right bank of the Gila River is determined at proportionate distance; there is no evidence of the original corner. I did not monument this corner point.
13.55	Road, bears parallel to the heretofore described canal.
14.00	Lateral, bears parallel to the above canal.
15.15	Lateral, flows S. 51° 50' W.
15.27	Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, for a Witness Point for secs. 8 and 9, with brass cap mkd. <div style="text-align: center;"> W P T8S R21W S 8 S 9 1970 </div>
19.97	The point for the 1/4 sec. cor. of secs. 8 and 9 is determined at proportionate distance; there is no evidence of the original corner. Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 28 ins. below the surface of the ground, mkd. <div style="text-align: center;"> T8S R21W 1/4 S 8 S 9 1980 </div> <p>There are no suitable accessories nor locations available for reference monuments.</p>
39.94	The point for the north 1/16 sec. cor. of secs. 8 and 9. Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 28 ins. below the surface of the ground, mkd. <div style="text-align: center;"> N 1/16 S 8 S 9 1980 </div> <p>There are no suitable accessories nor locations available for reference monuments.</p>
49.90	The point for Angle Point No. 11, Tract 37

Dependent Resurvey of a Portion of the
 Subdivisional Lines
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 9 ins. below the surface of the ground, mkd.</p> <div style="text-align: center;"> <p>T8S R21W TR 37 S 9 AP 11 S 8 </p> </div> <p>1970</p> <p>There are no suitable accessories nor locations available for reference monuments.</p>	
59.91	<p>The corner of secs, 4, 5, 8, and 9 is marked with an iron pipe, 2 ins. in diam., with brass cap flush with the surface of the ground, mkd.</p> <div style="text-align: center;"> <p>BUREAU OF RECLAMATION T8S R21W <u>S 5 S 4</u> S 8 S 9</p> </div> <p>1941</p> <p>The above corner marker is accepted as the best available evidence of the position of the original corner. I did not remonument this corner.</p>	
	<p>From the corner of secs. 3, 4, 9, and 10, heretofore described</p> <p>S. 89° 14' W., between secs. 4 and 9</p> <p>Along rolling north to northwest slope.</p>	
7.575	<p>The point for the corner of lots 15 and 16 of sec. 4</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R21W S 4 <u>L 15 L 16</u> S 9</p> </div> <p>1980</p>	
8.95	<p>Road, bears parallel to the hereinafter described canal.</p>	
9.75	<p>The southern bank of the Wellton-Mohawk Canal, flows N. 66° 30' E.</p>	
13.40	<p>The northern bank of the Wellton-Mohawk Canal.</p>	
14.20	<p>Road, bears parallel to the heretofore described canal.</p> <p>Thence, over nearly level land.</p>	
17.50	<p>Lateral, bears parallel to the above canal, but flows to the southwest.</p>	

22

Dependent Resurvey of a Portion of the
Subdivisional Lines
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS	
17.85	Road, bears parallel to the above canal.
20.165	<p>The east 1/16 sec. cor. of secs. 4 and 9 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 9 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION E 1/16 <u> S 4 </u> S 9</p> <p style="text-align: center;">1952</p> <p>The above corner marker is accepted as the position of the corner. I did not remonument this corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 14' W., beginning new measurement</p>
10.155	<p>Intersect the eastern right-of-way of U.S. Highway No. 95. The point for Angle Point No. 14, Tract 38.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R21W TR 38 <u>AP 14 / S 4</u> S 9</p> <p style="text-align: center;">1970</p>
12.44	Intersect the center line of U.S. Highway No. 95, bears N. 47° 42' E. and S. 47° 42' W.
14.725	<p>Intersect the western right-of-way of U.S. Highway No. 95. The point for Angle Point No. 13, Tract 38.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with the brass cap mkd.</p> <p style="text-align: center;">T8S R21W TR 38 <u>S 4 / AP 13</u> S 9</p> <p style="text-align: center;">1970</p>
20.13	<p>The 1/4 sec. cor. of secs. 4 and 9 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 13 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION</p> <p style="text-align: center;">1/4 <u> S 4 </u> S 9</p> <p style="text-align: center;">1941</p> <p>The above corner marker is accepted as the best available evidence of the position of the original corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 14' W., beginning new measurement</p>


Dependent Resurvey of a Portion of the
Subdivisional Lines
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS											
5.235	The point for the meander corner of secs. 4 and 9 on the left bank of the Gila River is determined at proportionate distance; there is no evidence of the original corner. I did not monument this corner point.										
	Thence, over the abandoned (1890) Gila River channel										
10.89	The point for the meander corner of secs. 4 and 9 on the right bank of the Gila River is determined at proportionate distance; there is no evidence of the original corner. I did not monument this corner point.										
13.00	Ascend over broken east to northeast slope.										
16.86	The point for Angle Point No. 10, Tract 38. Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 14 ins. in the ground, and in a small mound of stone, with brass cap mkd.										
	<table style="margin: auto;"> <tr><td>T8S</td><td>R21W</td></tr> <tr><td>TR 38</td><td></td></tr> <tr><td>AP 10</td><td>S 4</td></tr> <tr><td>S 9</td><td></td></tr> </table>	T8S	R21W	TR 38		AP 10	S 4	S 9			
T8S	R21W										
TR 38											
AP 10	S 4										
S 9											
	1970										
	Thence, descend over broken northwest slope.										
19.40	Base of descent, bears northeast and southwest; thence, over nearly level land.										
40.285	The corner of secs. 4, 5, 8, and 9, heretofore described.										
	N. 0° 09' E., between secs. 4 and 5										
	Over nearly level land.										
7.285	The point for Angle Point No. 8, Tract 38 and Corner No. 1, lot 6 of sec. 5. Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.										
	<table style="margin: auto;"> <tr><td>T8S</td><td>R21W</td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td></td><td>AP 8</td></tr> <tr><td>COR 1</td><td>TR 38</td></tr> <tr><td>LOT 6</td><td></td></tr> </table>	T8S	R21W	S 5	S 4		AP 8	COR 1	TR 38	LOT 6	
T8S	R21W										
S 5	S 4										
	AP 8										
COR 1	TR 38										
LOT 6											
	1970										
10.45	Road, bears N. 84° E. and S. 84° W.										
19.975	The point for the south 1/16 sec. cor. of secs. 4 and 5. I did not monument this corner point.										
39.95	The 1/4 sec. cor. of secs. 4 and 5 is marked with an iron pipe, 36 ins. long 1-inch in diam., firmly set 18 ins. in the ground, with brass cap mkd.										

Dependent Resurvey of a Portion of the
Subdivisional Lines
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">BUREAU OF RECLAMATION 1/4 S 5 S 4 1952</p> <p>The above corner marker is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 18 ins. in the ground, and in a small mound of stone, with brass cap mkd.</p> <p style="text-align: center;">T8S R21W 1/4 S 5 S 4 1970</p> <p>Deposit the iron pipe corner marker alongside the iron post.</p> <p>Discontinue the regular order of survey at this corner.</p> <hr/> <p style="text-align: center;">Restoring the Dependent Resurvey Executed by Robert S. Kaiser, Cadastral Surveyor. in 1960</p> <hr/> <p>From the corner of secs. 8, 9, 16, and 17, heretofore described.</p> <p>N. 86° 03' W., between secs. 8 and 17</p> <p>Over rolling land.</p>	
25.84	The eastern bank of the Wellton-Mohawk Canal, flows N. 21° 02' E.	
26.245	Intersect the center line of the Wellton-Mohawk Canal. The point for Corner No. 16, Parcel E and Corner No. 5, Parcel D of sec. 8. This corner point is located within the bed of the above canal, where it is impracticable to establish a permanent monument.	
26.65	The western bank of the Wellton-Mohawk Canal. Thence, over nearly level land.	
31.00	Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, for a witness corner for Corner No. 16, Parcel E and Corner No. 5, Parcel D of sec. 8, with brass cap mkd.	

Dependent Resurvey of a Portion of the
Subdivisional Lines
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS	
40.38	<p style="text-align: center;"> W C T8S R21W S 8 PAR D / PAR E COR 5 / COR 16 S 17  </p> <p style="text-align: center;">1970</p> <p>The 1/4 sec. cor. of secs. 8 and 17 is marked with a mound of stone, 2 ft. base, 1 1/2 ft. high; and is accepted as the best available evidence of the position of the corner.</p> <p>At the corner point, the center of the above mound of stone.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;"> T8S R21W 1/4 $\frac{S 8}{S 17}$ 1980 </p> <hr style="width: 20%; margin: 20px auto;"/>
5.57	<p>N. 86° 03' W., beginning new measurement</p> <p>The point for Corner No. 5, Parcel B and Corner No. 4, Parcel D of sec. 8.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T8S R21W S 8 PAR B / PAR D COR 5 / COR 4 S 17 </p> <p style="text-align: center;">1970</p>
20.82	<p>The point for Corner No. 4, Parcel A and Corner No. 4, Parcel B of sec. 8.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T8S R21W S 8 PAR A / PAR B COR 4 / COR 4 S 17 </p> <p style="text-align: center;">1970</p>
24.33	<p>The witness meander corner of secs. 8 and 17, for the left bank of the Gila River, which is monumented with an iron post, 2 1/2 ins. in diam., firmly set, projecting 5 ins. above the surface of the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the
Subdivisional Lines
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS

T8S
 S 8
 WMC ← S 17
 R21W

1960

N. 86° 03' W., beginning new measurement

1.03 The true point for the meander corner of secs. 8 and 17, on the left bank of the Gila River.

6.00 The meander corner of secs. 8 and 17, on the right bank of the Gila River, which is monumented with an iron post, 2 1/2 ins. in diam., firmly set in a mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd.

T8S
 S 8 / MC
 S 17
 R21W

1960

N. 86° 03' W., beginning new measurement

10.05 The corner of secs. 7, 8, 17, and 18 is marked with an iron pipe, 2 ins. in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.

U S RECLAMATION SERVICE

T8S
 S 7 | S 8
 S 18 | S 17
 R21W

1914

The above corner marker was accepted and included in the official field-note record of the dependent resurvey of a portion of the subdivisional line by Robert S. Kaiser, Cadastral Surveyor, in 1960

Discontinue the regular order of survey at this corner.

Restoring the Survey Executed
by James H. Martineau
U.S. Deputy Surveyor,
in 1890

N. 0° 20' W., between secs. 7 and 8

Over rough and broken terrain.

19.065 The point for the south 1/16 sec. cor. of secs. 7 and 8. I did not monument this corner point.

38.13 The 1/4 sec. cor. of secs. 7 and 8 is monumented with a stone, firmly set, 12x12 ins. base, projecting 8 ins. above the surface of the ground, mkd. 1/4 on the east. I did not remonument this corner.

Dependent Resurvey of a Portion of the
Subdivisional Lines
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

27

CHAINS

This corner is located on the east slope of rocky ridge spur, that slopes south.

Discontinue the regular order of survey at this corner.

From the corner of secs. 4, 5, 8, and 9 heretofore described.

N. 87° 38' W., between secs. 5 and 8

Over nearly level land.

11.77

The point for Angle Point No. 2, Tract 37 and Corner No. 2, lot 6 of sec. 5.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R21W
S 5
/ LOT 6
COR 2
S 8 / AP 2
TR 37

1970

20.27

The east 1/16 sec. cor. of secs. 5 and 8 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 3 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

E 1/16

S 5

S 8

1952

The above corner marker is accepted as the position of the corner. I did not remonument this corner.

N. 87° 38' W., beginning new measurement

20.27

The 1/4 sec. cor. of secs. 5 and 8 is marked with an iron pipe, 36 ins. long, 1-inch in diam., firmly set 30 ins. in the ground, with brass cap mkd.

BUREAU OF RECLAMATION

1/4 S 5

S 8

1952

The above corner marker is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the
Subdivisional Lines
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T8S R21W 1/4 $\frac{S 5}{S 8}$ 1970</p> <p>Deposit the iron pipe corner marker inside the iron post.</p> <p>Discontinue the dependent resurvey of the township at this corner.</p> <hr/> <p style="text-align: center;">Survey of a Portion of the Subdivision Lines Within Sections 1, 3, 4, 5, and 8 Township 8 South, Range 21 West Gila and Salt River Meridian, Arizona</p> <hr/> <p>Thence, in section 1</p> <p>From the 1/4 sec. cor. of secs. 1 and 12, heretofore described</p> <p>N. 0° 20' W., on the north and south center line of sec. 1</p> <p>20.055 The center-south 1/16 sec. cor. of sec. 1 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 3 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION C S 1/16 S 1 1954</p> <p>The above corner marker is accepted as the position of the corner. I did not remonument this corner.</p> <hr/> <p>N. 0° 18' W., beginning new measurement</p> <p>1.24 Intersect line 3 - 4, Tract 40, hereinafter described. I did not monument this point of intersection.</p> <p>Thence, on a blank line across Tract 40.</p> <p>16.405 Intersect line 1 - 2, Tract 40, hereinafter described. I did not monument this point of intersection.</p> <p>20.045 The center 1/4 sec. cor. of sec. 1 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 5 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION C 1/4 S 1 1954</p>

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p>The above corner marker is accepted as the position of the corner. I did not remonument this corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 18' W., beginning new measurement</p>
10.055	<p>The C-S-N 1/64 sec. cor. of sec. 1 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 12 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION C S N 1/64 S 1 1954</p> <p>The above corner marker is accepted as the position of the corner. I did not remonument this corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 23' W., beginning new measurement</p>
10.04	<p>The center-north 1/16 sec. cor. of sec. 1 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION C N 1/16 S 1 1954</p> <p>The above corner marker is accepted as the position of the corner. I did not remonument this corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 19.5' W., beginning new measurement</p>
9.45	<p>Intersect (hereinafter described) line 6 - 7, Tract 41.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R21W TR 41 C <hr style="width: 10%; margin: 0 auto;"/> S 1 C 1980</p> <p>Thence, on a blank line across Tract 41.</p>
20.055	<p>The north 1/4 sec. cor. of sec. 1 on the north boundary of the township, heretofore described.</p>

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the east 1/4 sec. cor. of sec. 1 on the east boundary of the township, heretofore described.</p>
	<p>N. 89° 56' W., on the east and west center line of sec. 1</p>
19.99	<p>The point for the center-east 1/16 sec. cor. of sec. 1. I did not monument this corner point.</p>
39.98	<p>The center 1/4 sec. cor. of sec. 1, heretofore described.</p>
	<hr/>
	<p>N. 89° 56' W., beginning new measurement</p>
20.005	<p>The point for the center-west 1/16 sec. cor. of sec. 1. I did not monument this corner point.</p>
40.01	<p>The true point for the 1/4 sec. cor. of secs. 1 and 2, heretofore described.</p>
	<p>Discontinue the regular order of survey at this corner.</p>
	<hr/>
	<p>The northeast 1/16 sec. cor. of sec. 1 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 5 ins. above the surface of the ground, with brass cap mkd.</p>
	<p style="text-align: center;">BUREAU OF RECLAMATION NE 1/16 S 1 1954</p>
	<p>The above corner marker is accepted as the position of the corner. I did not remonument this corner.</p>
	<hr/>
	<p>N. 0° 12.5' W., on the north and south center line of the northeast quarter of sec. 1</p>
9.455	<p>Intersect (hereinafter described) line 6 - 7, Tract 41.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T8S R21W TR 41 E S 1 E</p>
	<p style="text-align: center;">1980</p>
	<p>Thence, on a blank line across Tract 41.</p>

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS	
20.41	<p>The east 1/16 sec. cor. of sec. 1 on the north boundary of the township, heretofore described.</p> <p>Discontinue the regular order of survey at this corner.</p> <hr/> <p>The northwest 1/16 sec. cor. of sec. 1 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 6 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION NW 1/16 S 1 1954</p> <p>The above corner marker is accepted as the position of the corner. I did not remonument this corner.</p> <hr/> <p>N. 0° 24.5' W., on the north and south center line of the northwest quarter of sec. 1</p>
9.49	<p>The point for Angle Point No. 6, Tract 41</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R21W W TR 41 AP 6 S 1 W 1980</p> <p>Thence, continue on the north and south center line of the northwest quarter of sec. 1, which is identical with (hereinafter described) line 6 - 5 of Tract 41.</p>
20.095	<p>The west 1/16 sec. cor. of sec. 1 on the north boundary of the township, heretofore described.</p> <p>Discontinue the regular order of survey at this corner.</p> <hr/> <p>From the south 1/16 sec. cor. of sec. 1 on the east boundary of the township, heretofore described.</p> <p>N. 89° 55.5' W., on the east and west center line of the southeast quarter of sec. 1. Thence, on a blank line across Tract 40</p>
16.445	<p>Intersect line 6 - 7, Tract 40, hereinafter described. I did not monument this point of intersection.</p>
19.995	<p>The southeast 1/16 sec. cor. of sec. 1 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.</p>

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS

BUREAU OF RECLAMATION
 SE 1/16
 S 1

1954

The above corner marker is accepted as the position of the corner. I did not remonument this corner.

N. 89° 56' W., beginning new measurement


8.135 Intersect the medial line of the abandoned (1890) Gila River Channel, hereinafter described. The point for the Special Meander Corner of sec. 1.

Set a steel shaft, 6 ft. long, 1-inch in diam., 4.5 ft in the ground.

N. 50° 00' W., on the partition line, along the medial line of the abandoned (1890) Gila River Channel.

1.02 The point for Angle Point No. 6, Tract 40


Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 25 ins. in the ground, with brass cap mkd.



1977

3.105 The calculated position, the point for the Special Meander Corner of sec. 1

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 25 ins. in the ground, with brass cap mkd.






1977

This corner is designated to function for Angle Point No. 5, Tract 40.



S. 40° 00' W., continue on the partition line, on a calculated bearing across the abandoned (1890) Gila River Channel.

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

33

CHAINS	
1.595	<p>The point for Angle Point No. 4, Tract 40</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>1977</p> </div>
2.625	<p>Intersect the east and west center line of the southeast quarter and the calculated position for the left bank of the abandoned (1890) Gila River channel. The point for the Special Meander Corner of sec. 1.</p> <p>Set an iron, 28 ins. long, 2 1/2 ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>1977</p> </div> <p>This corner is designated to function for Corner No. 1, Parcel A of sec. 1.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 56' W., on the east and west center line of the southeast quarter, which is identical with line 1 - 2, Parcel A of sec. 1.</p>
1.305	<p>The point for Corner No. 2, Parcel A of sec. 1</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>1977</p> </div>
7.775	<p>The center-south 1/16 sec. cor. of sec. 1, heretofore described.</p> <p>Discontinue the regular order of survey at this corner.</p> <hr style="width: 40%; margin: 10px auto;"/> <p>Thence, with the survey of the Fixed and Limiting Boundary of the medial line of the abandoned (1890) Gila River channel, the partition line between an area of patented (private ownership) and vacant (United States ownership).</p> <hr style="width: 40%; margin: 10px auto;"/> <p>From the Special Meander Corner of secs. 1 and 12, heretofore described.</p>

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS		
	<p>N. 59° 22.5' W., on a calculated bearing for the medial line of the abandoned (1890) Gila River channel through sec. 1.</p>	
4.09	<p>The point for Corner No. 3, lot 26 of sec. 1</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>	
	<div style="text-align: center;"> <p>T8S R21W L 26 /COR 3 S 1</p>  <p>1980</p> </div>	
10.765	<p>The calculated position, the point for Angle Point No. 1 of sec. 1, I did not monument this corner point.</p>	
4.99	<p>N. 52° 09' W., beginning new measurement</p> <p>The calculated position, the point for Angle Point No. 2 of sec. 1, I did not monument this corner point.</p>	
17.97	<p>N. 50° 00' W., beginning new measurement</p> <p>Intersect the east and west center line of the south-east quarter of sec. 1, heretofore described.</p>	
18.99	<p>Angle Point No. 6, Tract 40, heretofore described.</p>	
21.075	<p>Angle Point No. 5, Tract 40, heretofore described.</p>	
21.455	<p>The calculated position, the point for Angle Point No. 3 of sec. 1.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 25 ins. in the ground, with brass cap mkd.</p>	
	<div style="text-align: center;"> <p>T8S R21W S 1</p>  <p>1977</p> </div>	
	<p>Discontinue the survey of the medial line of the abandoned (1890) Gila River channel at this corner.</p>	
	<p style="text-align: center;">The metes and Bounds Survey of Lot 26, Section 1</p>	
	<p>Beginning at Corner No. 1, lot 26 of sec. 1, on the east boundary of the township, heretofore described.</p>	
	<p>N. 89° 57' W., on line 1 - 2, lot 26 of sec. 1</p>	

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

35

CHAINS	
4.685	<p>The point for Corner No. 2, lot 26 of sec. 1</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R21W S 1 COR 2 L 26</p> <p style="text-align: center;">1980</p> <hr/>
13.46	<p>S. 0° 05' E., on line 2 - 3, lot 26 of sec. 1</p> <p>Intersect the medial line of the abandoned (1890) Gila River Channel, Corner No. 3, lot 26 of sec. 1, heretofore described.</p> <hr/> <p>S. 59° 22.5' E., on line 3 - 4, lot 26 of sec. 1, which is identical with the medial line of the abandoned (1890) Gila River channel.</p>
4.09	<p>The Special Meander Corner of secs. 1 and 12, heretofore described. This corner is designated to function for Corner No. 4, lot 26 of sec. 1.</p> <hr/> <p>S. 89° 57' E., on line 4 - 5, lot 26 of sec. 1, which is identical with the section line between secs. 1 and 12</p>
1.17	<p>The corner of secs. 1 and 12 on the east boundary of the township, heretofore described. This corner is designated to function for Corner No. 5, lot 26 of sec. 1.</p> <hr/> <p>N. 0° 05' W., on line 5 - 1, lot 26 of sec. 1, which is identical with the east boundary of section 1.</p>
1.745	<p>The west 1/4 sec. cor. of sec. 6, Tp. 8 S., R. 20 W., heretofore described.</p>
3.92	<p>The point for the meander corner of sec. 1, on the right bank of the Gila River, heretofore described.</p>
15.54	<p>Corner No. 1, lot 26 of sec. 1, and the place of beginning.</p> <hr/>
<p>The Metes and Bounds Survey of Parcel A. Section 1</p> <p>The area of Parcel A of section 1 having been acquired (United States ownership) is taken from a portion of the patented (private ownership) original lot 14 of section 1.</p>	

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS

Beginning at Corner No. 1 Parcel A of section 1, heretofore described.

N. 89° 56' W., on line 1 - 2, Parcel A of sec. 1, which is identical with the east and west center line of the southeast quarter of sec. 1.

1.305 Corner No. 2, Parcel A of sec. 1, heretofore described.

S. 12° 40' W., on line 2 - 3, Parcel A of sec. 1

7.805 The calculated position, the point for Corner No. 3, Parcel A of sec. 1.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 25 ins. in the ground, with brass cap mkd.

T8S R21W
 S 1
 / PAR A
 \ COR 3
 1977

S. 76° 36.5' E., on line 3 - 4, Parcel A of sec. 1

3.94 The calculated position, the point for Corner No. 4, Parcel A of sec. 1

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 25 ins. in the ground, with brass cap mkd.

T8S R21W
 S 1
 / PAR A
 \ COR 4
 1977

N. 13° 23.7' E., on line 4 - 5, Parcel A of sec. 1

5.78 The calculated position for the left bank of the abandoned (1890) Gila River channel and the point for Corner No. 5, Parcel A of sec. 1.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 25 ins. in the ground, with brass cap mkd.

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T8S R21W S 1</p> <p style="text-align: center;">COR 5 PAR A</p> <p style="text-align: center;">1977</p> <hr style="width: 20%; margin: auto;"/> <p>N. 49° 52' W., on line 5 - 6, Parcel A, which is the calculated bearing for the position of the left bank of the abandoned (1890) Gila River channel through sec. 1.</p>
1.742	<p>The calculated position, the point for Corner No. 6, Parcel A of sec. 1</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T8S R21W S 1</p> <p style="text-align: center;">PAR A COR 6</p> <p style="text-align: center;">1977</p> <hr style="width: 20%; margin: auto;"/> <p>N. 24° 50' W., on line 6 - 1, Parcel A, continue on a calculated bearing for the position of the left bank of the abandoned (1890) Gila River channel through sec. 1.</p>
1.962	<p>Corner No. 1, Parcel A of sec. 1, and the place of beginning.</p>
	<p>Thence, in section 3</p> <p>From the 1/4 sec. cor. of secs. 3 and 10, heretofore described</p> <p>N. 1° 06.5' W., on the north and south center line of sec. 3</p>
20.11	<p>The point for the center-south 1/16 sec. cor. of sec. 3</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 26 ins. below the surface of the ground, mkd.</p> <p style="text-align: center;">C S 1/16 S 3 C</p> <p style="text-align: center;">1980</p> <p>There are no suitable accessories nor locations available for reference monuments.</p>

38

Survey of a Portion of the Subdivision Lines
Within Sections 1, 3, 4, 5, and 8
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS	
34.98	Intersect the (hereinafter described) reestablished meanders of the left bank of the abandoned (1890) Gila River channel. The point for the Special Meander Corner of sec. 3. This corner point is not monumented.
37.88	Intersect the (hereinafter described) medial line of the abandoned (1890) Gila River channel. This point of intersection is not monumented.
40.22	Intersect the east and west center line, the point for the center 1/4 sec. cor. of sec. 3 Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 26 ins. below the surface of the ground, mkd. T8S R21W C 1/4 S 3 1980 There are no suitable accessories nor locations available for reference monuments.
80.71	The north 1/4 sec. cor. of sec. 3 on the north boundary of the township, which is monumented with an iron post, 1-inch in diam., firmly set, projecting 8 ins. above the surface of the ground, with regulation (G.L.O.) brass cap mkd. <u>1/4 S 3</u> 1930 The above corner was reestablished by Francis E. Joy, U.S. Cadastral Engineer, in 1930, and is described in the official field-note record of the resurvey of the south boundary of Tp. 7 S., R. 21 W., approved December 14, 1931 and accepted May 9, 1932. From this corner, the south 1/4 sec. cor. of sec. 34, Tp. 7 S., R. 21 W. bears S. 89° 43' E., 0.54 chs. dist., and is monumented with an iron post, 1-inch in diam., firmly set, projecting 12 ins. above the surface of the ground, with regulation (G.L.O.) brass cap mkd. <u>1/4 S 34</u> 1930 The above corner was reestablished by Francis E. Joy, U.S. Cadastral Engineer, in 1930, and is described in the official field-note records of the resurvey of the south boundary of Tp. 7 S., R. 21 W., approved December 14, 1931 and accepted May 9, 1932. From this same corner, the corner of secs. 33 and 34 Tp. 7 S., R. 21 W. bears N. 89° 43' W., 39.20 chs. dist., and is monumented with an iron post, 2 ins. in diam., firmly set, projecting 14 ins. above the surface of the ground, and in a mound of stone, 3 ft. base, to the top, with regulation (G.L.O.) brass cap mkd.


Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	T7S R21W S 33 S 34 <hr style="width: 50%; margin: auto;"/> T8S R21W S 3 1930 The above corner was reestablished by Francis E. Joy, U.S. Cadastral Engineer, in 1930, and is described in the official field-note record of the resurvey of the south boundary of Tp. 7 S., R. 21 W., approved December 14, 1931 and accepted May 9, 1932.
	<hr/> From the 1/4 sec. cor. of secs. 2 and 3, heretofore described N. 89° 54' W., on the east and west center line of sec. 3
39.91	Intersect the north and south center line, the center 1/4 sec. cor. of sec. 3, heretofore described.
44.68	Intersect the (hereinafter described) medial line of the abandoned (1890) Gila River channel. This point of intersection is not monumented.
50.235	Intersect the (hereinafter described) reestablished meanders of the left bank of the abandoned (1890) Gila River channel. The point for the Special Meander Corner of sec. 3. This corner point is not monumented.
	Thence, on a blank line across (hereinafter described) Tract 42.
64.60	Intersect line 3 - 4 Tract 42, hereinafter described. This point of intersection is not monumented.
	Thence, on a blank line across lot 16 of sec. 3.
69.41	Intersect the (hereinafter described) medial line of the abandoned (1890) Gila River channel. This point of intersection is not monumented.
79.63	The 1/4 sec. cor. of secs. 3 and 4, heretofore described. Discontinue the regular order of survey at this corner.
	<hr/> From the center-south 1/16 sec. cor. of sec. 3, heretofore described. N. 89° 55' W., on the east and west center line of the southwest quarter of sec. 3
3.605	The point for Angle Point No. 9, Tract 42. Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

40

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS



1980

31.13 Intersect (hereinafter described) line 4 - 5, Tract 39. From this point of intersection Angle Point No. 5, bears N. 72° 19.5' E., 1.815 chs. distant.

Thence, on a blank line across Tract 39.

39.79 The south 1/16 sec. cor. of secs. 3 and 4, heretofore described.

Discontinue the regular order of survey at this corner.

From the point for the south 1/16 sec. cor. of secs. 2 and 3, heretofore described.


N. 89° 56' W., on the east and west center line of the southeast quarter of sec. 3

18.12 Intersect the (hereinafter described) medial line of the abandoned (1890) Gila River channel. This point of intersection is not monumented.

21.625 Intersect the (hereinafter described) reestablished meanders of the left bank of the abandoned (1890) Gila River channel. The point for the Special Meander Corner of sec. 3. This corner point is not monumented.

26.99 The point for Angle Point No. 11, Tract 42

Set an aluminum rod, 48 ins. long, 1/2-inch in diam., 36 ins. in the ground, with aluminum cap, 3 ins. in diam., mkd.



1980

39.89 Intersect the north and south center line, the center-south 1/16 sec. cor. of sec. 3, heretofore described.

Discontinue the regular order of survey at this corner.

The Reestablishment of the Meanders of the
 Left Bank of the Abandoned (1890) Gila River
 Channel, as a Fixed and Limiting Boundary

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS

MEMORANDUM


The record courses of the meanders of the left bank of the abandoned (1890) Gila River channel, were calculated between two known corners. The meanders were retraced; the residual or closing errors were ascertained and the recorded courses were calculated and adjusted to a closing, by the broken boundary method, adopting new courses to the nearest minute and lengths to the nearest link, as follows:

From the corner of secs. 2, 3, 10, and 11, which is designated to function for the meander corner for the left bank of the (1890) Gila River, heretofore described.


N. 47° 30' W., on a calculated bearing, fixed and limiting boundary of the meanders of the left bank of the abandoned (1890) Gila River channel.

29.80 Intersect the east and west center line of the south-east quarter; the point for the Special Meander Corner of sec. 3. This corner point is not monumented.

33.90 The point for Angle Point No. 12, Tract 42
 Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.



48.02 Adjusted position for Angle Point No. 1 of sec. 3 on the reestablished left bank of the abandoned (1890) Gila River channel.
 Set an iron, 28 ins. long, 2 1/2 ins. in diam., with brass cap 26 ins. below the surface of the ground, mkd.



This corner is designated to function for Angle Point No. 13, Tract 42.




There are no suitable accessories nor locations available for reference monuments.

N. 63° 15' W.,




5.73 Intersect the north and south center line, the point for the Special Meander Corner of sec. 3, heretofore described.

17.41 Intersect the east and west center line, the point for the Special Meander Corner of sec. 3, heretofore described.

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona


CHAINS		
18.16	<p>The point for Angle Point No. 14, Tract 42</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 26 ins. below the surface of the ground, mkd.</p> <div data-bbox="763 537 941 698" style="text-align: center;"> <p>T8S R21W</p>  <p>AP 14 TR 42</p> </div> <p>1980</p> <p>There are no suitable accessories nor locations available for references monuments.</p>	
18.99	<p>Adjusted position for Angle Point No. 2 of sec. 3 on the reestablished left bank of the abandoned (1890) Gila River channel</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 26 ins. below the surface of the ground, mkd.</p> <div data-bbox="747 1142 941 1303" style="text-align: center;"> <p>T8S R21W</p>  <p>AP 2</p> </div> <p>1980</p> <p>There are no suitable accessories nor locations available for reference monuments.</p> <p>Discontinue the on the ground resurvey of this meander line of the left bank of the abandoned (1890) Gila River channel at this corner.</p>	
	<p>The survey of the Fixed and Limiting Boundary of the medial line of the abandoned (1890) Gila River channel, partition line between an area of patented (private ownership) and vacant (United States ownership).</p> <p>From the point for the Special Meander Corner of secs. 2 and 3, heretofore described.</p> <p>N. 48° 17.5' W., on a calculated bearing, fixed and limiting boundary of the medial line of the abandoned (1890) Gila River channel through sec. 3.</p>	
24.66	<p>Intersect the east and west center line of the south-east quarter of sec. 3, heretofore described.</p>	
47.96	<p>The calculated position, the point for Angle Point No. 1 of sec. 3</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 26 ins. below the surface of the ground, mkd.</p> <div data-bbox="779 2419 974 2553" style="text-align: center;"> <p>T8S R21W</p>  <p>AP 1</p> </div> <p>1980</p>	

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p>There are no suitable accessories nor locations available for reference monuments.</p>
	<p>N. 64° 04' W., continue with the survey of the medial line through section 3,</p>
5.24	<p>Intersect the north and south center line of sec. 3, heretofore described.</p>
10.60	<p>Intersect the east and west center line of sec. 3, heretofore described.</p>
12.83	<p>The point for Angle Point No. 15, Tract 42</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 26 ins. below the surface of the ground, mkd.</p>
	<div style="text-align: center;"> <p>T8S R21W S 3</p>  <p>TR 42 AP 15</p> <p>1980</p> </div>
	<p>Continue with the course and measurement on the medial line through section 3.</p>
19.58	<p>The calculated position, the point for Angle Point No. 2 of sec. 3.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 26 ins. in the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T8S R21W S 3 AP 2</p>  <p>AP 1 TR 42</p> <p>1970</p> </div>
	<p>This corner is designated to function for Angle Point No. 1, Tract 42</p>
	<p>S. 76° 51' W., continue with the survey of the medial line through section 3.</p>
10.36	<p>The point for Angle Point No. 2, Tract 42</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 22 ins. in the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T8S R21W S 3</p>  <p>AP 2 TR 42</p> <p>1980</p> </div>

44

Survey of a Portion of the Subdivision Lines
Within Sections 1, 3, 4, 5, and 8
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS	
17.105	Intersect the east and west center line of sec. 3, heretofore described.
17.52	The calculated position, the point for Angle Point No. 3 of sec. 3. Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T8S R21W S 3 AP 3  1970 </div>
10.51	S. 68° 15.5' W., continue with the survey of the medial line through section 3. The Special Meander Corner of secs. 3 and 4, heretofore described.
5.13	Thence, in section 4 From the 1/4 sec. cor. of secs. 4 and 9, heretofore described. N. 0° 38' W., on the north and south center line of sec. 4. Intersect line 10 - 11, Tract 38, hereinafter described, I did not monument this point of intersection. From this point of intersection Angle Point No. 11, Tract 38 bears N. 72° 19.5' E., 15.965 chs. distant. Thence, on a blank line across Tract 38
11.35	The calculated position for the left bank of the abandoned (1890) Gila River channel. I did not monument this point.
16.37	The calculated position for the right bank of the abandoned (1890) Gila River channel. I did not monument this point.
20.05	The point for the center-south 1/16 sec. cor. of sec. 4, Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> C S 1/16 S 4 1970 </div>
20.975	This corner is designated to function for Angle Point No. 5, Tract 38 The point for Angle Point No. 6, Tract 38

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

45

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R21W S 4 AP 6 TR 38 </p> <p>1970</p> </div>
40.10	<p>The center 1/4 sec. cor. of sec. 4 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 14 ins. above the surface of the ground, and in a small mound of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>1/4 S 4</p> <p>1952</p> </div> <p>The above corner marker is accepted as the position of the corner. I did not remonument this corner.</p> <p>Discontinue the regular order of survey at this corner.</p> <hr/>
40.08	<p>From the 1/4 sec. cor. of secs. 3 and 4, heretofore described.</p> <p>S. 89° 03' W., on the east and west center line of sec. 4</p>
39.74	<p>The center 1/4 sec. cor. of sec. 4, heretofore described.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89° 00.5' W., beginning new measurement</p> <p>The 1/4 sec. cor. of secs. 4 and 5, heretofore described.</p> <p>Discontinue the regular order of survey at this corner.</p> <hr/>
24.30	<p>From the south 1/16 sec. cor. of secs. 3 and 4, heretofore described.</p> <p>S. 89° 08' W., on the east and west center line of the southeast quarter of sec. 4; thence, on a blank line across Tract 38.</p> <p>The calculated position for the left bank of the abandoned (1890) Gila River channel. No permanent monument established.</p>
29.13	<p>The calculated position for the medial line (hereinafter described) of the abandoned (1890) Gila River channel, the partition line between an area of patented (private ownership) and vacant (United States ownership), which is also designated to function for line 2-3, Tract 38. From this point, Angle Point No. 3, Tract 38 bears S. 59° 48' W., 4.06 chs. distant. Thence, on a blank line across lot No. 5 of sec. 4</p>

46

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS

33.815

The calculated position for the right bank of the abandoned (1890) Gila River channel, the point for a Special Meander Corner of Sec. 4, which is designated to function for Angle Point No. 4, Tract 38.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 24 ins. in the ground, with brass cap mkd.

T8S R21W
 S 4
 AP 4 S
 TR 38 M
 C

1970

40.185

Intersect the north and south center line, the center-south 1/16 sec. cor. of sec. 4, which is designated to function for Angle Point No. 5, Tract 38, heretofore described.

Discontinue the regular order of survey at this corner.

Thence, with the survey of the Fixed and Limiting Boundary of the medial line of the abandoned (1890) Gila River channel, the partition line between an area of patented (private ownership) and vacant (United States ownership).

From the Special Meander Corner of secs. 3 and 4, heretofore described.

S. 64° 42' W., on a calculated bearing for the medial line of the abandoned (1890) Gila River channel through sec. 4.

2.595

The calculated position, the point for Angle Point No. 1 of sec. 4. I did not monument this corner point.

S. 59° 48' W., continue with the survey of the medial line through section 4.

11.86

The point for Angle Point No. 2, Tract 38

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 25 ins. in the ground, with brass cap mkd.


T8S R21W
 S 4
 AP 2
 TR 38

1970

Continue with the course and measurement on the medial line through section 4, which is now identical with line 2 - 3, Tract 38

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

47

CHAINS	
30.685	Intersect the east and west center line of the south-east quarter of sec. 4, heretofore described.
34.745	The calculated position, the point for Special Meander Corner of sec. 4, which is designated to function for Angle Point No. 3, Tract 38
	Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.
	
	Discontinue the survey of the medial line of the abandoned (1890) Gila River channel.
	<hr/> <p>Thence, with the survey of the Fixed and Limiting Boundary, the partition line between an area of patented (private ownership) and vacant (United States ownership).</p>
	N. 30° 50' W., on a calculated bearing across the abandoned (1890) Gila River channel.
2.295	Intersect the east and west center line of the south-east quarter, the Special Meander Corner of sec. 4, which is designated to function for Angle Point No. 4, Tract 38, heretofore described.
	<hr/> <p>Thence, with the metes and bounds survey of lot 16, sec. 4</p>
	<hr/> <p>From Angle Point No. 18, Tract 38, which is identical with Angle Point No. 4, Tract 39, heretofore described, and is identical with the northeast corner of lot 16, sec. 4</p>
	S. 72° 19.5' W., along the northern boundary of lot 16, sec. 4, which is identical with line 18 - 17, Tract 38.
7.935	The true point for Angle Point No. 17, Tract 38, hereinafter described, which is designated to function for the corner of lots 15 and 16 of sec. 4.
	<hr/> <p>S. 1° 01' E., along the western boundary of lot 16, which is identical with the eastern boundary of lot 15 of sec. 4.</p>

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS	
15.05	Intersect the section line between secs. 4 and 9, the southwest corner of lot 16, which is identical with the southeast corner of lot 15 of sec. 4, heretofore described.

	N. 89° 14' E., along the southern boundary of lot 16, sec. 4, which is identical with the section line between secs. 4 and 9.
7.575	The corner of secs. 3, 4, 9, and 10, heretofore described, which is designated to function for the southeast corner of lot 16, sec. 4.

	N. 0° 56' W., along the eastern boundary of lot 16, sec. 4, which is identical with the section line between secs. 3 and 4.
17.36	The northeast corner of lot 16, sec. 4, which is identical with Angle Point No. 18, Tract 38 and Angle Point No. 4, Tract 39, and the place of beginning.

	Thence, in section 5
	From the 1/4 sec. cor. of secs. 5 and 8, heretofore described.
	N. 0° 20.5' W., on the north and south center line of sec. 5
19.845	The point for the center-south 1/16 sec. cor. of sec. 5. I did not monument this corner point.
39.69	The center 1/4 sec. cor. of sec. 5 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 11 ins. above the surface of the ground, and in a small mound of stone, with brass cap mkd.
	BUREAU OF RECLAMATION C 1/4 S 5 1952
	The above corner marker is accepted as the position of the corner. I did not remonument this corner.
	Discontinue the regular order of survey at this corner.

	From the 1/4 sec. cor. of secs. 4 and 5, heretofore described.
	N. 88° 01' W., on the east and west center line of sec. 5.
20.435	The point for the center-east 1/16 sec. cor. of sec. 5. I did not monument this corner point.

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

49

CHAINS	
40.87	The center 1/4 sec. cor. of sec. 5, heretofore described.
	Discontinue the regular order of survey at this corner.
	From the east 1/16 sec. cor. of secs. 5 and 8, heretofore described.
	N. 0° 05.5' W., on the north and south center line of the southeast quarter of sec. 5.
19.91	Intersect the east and west center line of the southeast quarter, the point for the southeast 1/16 sec. cor. of sec. 5. I did not monument this corner point.
39.82	Intersect the east and west center line, the point for the center-east 1/16 sec. cor. of sec. 5, heretofore described.
	From the point for the south 1/16 sec. cor. of secs. 4 and 5, heretofore described.
	N. 87° 49.5' W., on the east and west center line of the southeast quarter of sec. 5.
20.35	Intersect the north and south center line of the southeast quarter, the point for the southeast 1/16 sec. cor. of sec. 5, heretofore described.
40.705	Intersect the north and south center line, the point for the center-south 1/16 sec. cor. of sec. 5, heretofore described.
	Thence, with the metes and bounds survey of lot 6, sec. 5
	Beginning at Corner No. 1, lot 6, sec. 5, which is identical with Angle Point No. 8, Tract 38, heretofore described.
	Thence, on line 1 - 2, lot 6 of sec. 5, along the arc of a curve, curve data:
	Chord bears S. 60° 00' W. Chord length 13.60 chs. distant Radius 113.635 chs. distant Length of arc 13.61 chs. distant
	At the end of the arc of the curve, Corner No. 2, lot 6 of sec. 5, which is identical with Angle Point No. 2, Tract 37, heretofore described.

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS		
	<p>S. 87° 38' E., on line 2 - 3, lot 6 of sec. 5, which is identical with line 2 - 1, Tract 37, and is identical with the section line between secs. 5 and 8.</p>	
11.77	<p>The corner of secs. 4, 5, 8, and 9, heretofore described, which is designated to function for Corner No. 3, lot 6 of sec. 5.</p>	
	<p>N. 0° 09' E., on line 3 - 1, lot 6 of sec. 5, which is identical with the section line between secs. 4 and 5.</p>	
7.285	<p>Corner No. 1, lot 6 of sec. 5, which is identical with Angle Point No. 8, Tract 38, and the place of beginning.</p>	
	<p>Thence, in section 8</p>	
	<p>From the 1/4 sec. cor. of secs. 8 and 17, heretofore described</p>	
	<p>NORTH, on the north and south center line of sec. 8; thence, on a blank line across Parcel D of sec. 8.</p>	
5.62	<p>Intersect line 1 - 2, Parcel D, which is identical with line 14 and 15, Parcel E of sec. 8, hereinafter described. I did not monument this point of intersection. From this point of intersection Corner No. 2, Parcel D and Corner No. 14, Parcel E of sec. 8 bears N. 87° 15' W., 4.405 chs. distant.</p>	
	<p>Thence, on a blank line across Parcel E of sec. 8.</p>	
13.445	<p>The calculated position, the point for the Special Meander Corner of sec. 8, on the left bank of the abandoned (1890) Gila River channel. I did not monument this corner point.</p>	
14.705	<p>The point for Corner No. 3, Parcel C and Corner No. 9, Parcel E of sec. 8.</p>	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T8S R21W C S 8 PAR E PAR C COR 9 COR 3 C</p>	
	<p style="text-align: center;">1980</p>	
16.36	<p>The calculated position for the medial line of the abandoned (1890) Gila River channel; the point for Corner No. 2, Parcel C and Corner No. 10, Parcel E of sec. 8.</p>	
	<p>Set an iron post, 28 ins. long 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>	

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">T8S R21W C S 8 COR 10 PAR E COR 2 PAR C C</p> <p style="text-align: center;">1980</p>	
19.275	<p>The calculated position, the point for the Special Meander Corner of sec. 8, on the right bank of the abandoned (1890) Gila River channel.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T8S R21W C S 8 C SMC</p> <p style="text-align: center;">1970</p> <p>This corner is designated to function for Corner No. 12, Parcel E, sec. 8, hereinafter described.</p>	
19.51	<p>The point for the center-south 1/16 sec. cor. of sec. 8</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C S 1/16 S 8</p> <p style="text-align: center;">1970</p>	
19.57	<p>Intersect the arc of a (hereinafter described) curve, the point for Corner No. 13, Parcel E of sec. 8, which is identical with Angle Point No. 5, Tract 37.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>	
39.02	<p style="text-align: center;">T8S R21W C TR 37 AP 5 13 COR PAR E S 8 C</p> <p style="text-align: center;">1970</p> <p>The center 1/4 sec. cor. of sec. 8 is marked with an iron pipe, 36 ins. long, 1-inch in diam., firmly set 30 ins. in the ground, with brass cap mkd.</p>	

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS

BUREAU OF RECLAMATION
 C 1/4 S 8

1952

The above corner marker is accepted as the position of the corner.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R21W
 C 1/4
 S 8

1970

Deposit the iron pipe corner marker alongside the iron post.

N. 0° 01' W., beginning new measurement; thence, on a blank line across Tract 37.

11.31 Intersect the arc of a curve, hereinafter described; line 2 - 3, Tract 37.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R21W
 C
 S | 8
 |
 C
 TR 37

1970

19.87 The center-north 1/16 sec. cor. of sec. 8 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION
 C N
 1/16
 S 8

1954

The above corner marker is accepted as the position of the corner. I did not remonument this corner.

N. 0° 01' W., beginning new measurement

19.88 The 1/4 sec. cor. of secs. 5 and 8, heretofore described.

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 8 and 9, heretofore described.</p> <p>N. 87° 22' W., on the east and west center line of sec. 8</p>
20.215	<p>The center-east 1/16 sec. cor. of sec. 8 is marked with an iron pipe, 1-inch in diam., with brass cap 6 ins. below the surface of the ground, mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION C E 1/16 S 8</p> <p style="text-align: center;">19</p> <p>The above corner marker is accepted as the position of the corner. I did not remonument this corner.</p> <hr style="width: 20%; margin: 10px auto;"/>
10.005	<p>N. 87° 22' W., beginning new measurement</p> <p>The point for Corner No. 2, lot 13 and Corner No. 3, lot 14 of sec. 8.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 26 ins. below the surface of the ground, mkd.</p> <p style="text-align: center;">T8S R21W S 8 L 14 / L 13 <u>COR 3 / COR 2</u></p> <p style="text-align: center;">1980</p> <p>There are no suitable accessories nor locations available for reference monuments</p>
17.23	<p>The point for Angle Point No. 7, Tract 37 and Corner No. 2 of lot 14 of sec. 8.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R21W TR 37 / Lot 14 <u>AP 7 / COR 2</u> S 8</p> <p style="text-align: center;">1980</p>
20.215	<p>The center 1/4 sec. cor. of sec. 8, heretofore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 87° 21' W., beginning new measurement; thence, on a blank line across Tract 37.</p>

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS


- 7.205 Intersect the arc of a curve, line 2 - 3, Tract 37, hereinafter described. From this point of intersection Angle Point No. 3 bears along the arc of the above curve 28.825 chs. distant.
- 20.28 The point for the center-west 1/16 sec. cor. of sec. 8. I did not monument this corner point.
- 40.56 The 1/4 sec. cor. of secs. 7 and 8, heretofore described.

From the center-east 1/16 sec. cor. of sec. 8, heretofore described

N. 0° 05' E., on the north and south center line of the northeast quarter of sec. 8

- 12.76 The point for Corner No. 1, lot 13 and Corner No. 4, lot 14 of sec. 8.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 26 ins. below the surface of the ground, mkd.




1980

There are no suitable accessories nor locations available for reference monuments.

- 14.905 The point for Corner No. 1, lot 14 of sec. 8 and Angle Point No. 8, Tract 37

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 22 ins. in the ground, with brass cap mkd.



1980

- 19.90 The northeast 1/16 sec. cor. of sec. 8 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION
 NE
 1/16
 S 8

1954

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

55

CHAINS	
	<p>The above corner marker is accepted as the position of the corner. I did not remonument this corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 03' E., beginning new measurement; thence, on a blank line across Tract 37.</p>
13.40	Intersect the arc of a curve, line 2 - 3, Tract 37, hereinafter described. From this point of intersection Angle Point No. 2 bears along the arc of the above curve 10.52 chs. distant.
19.94	The east 1/16 sec. cor. of secs. 8 and 9 heretofore described.
	<hr style="width: 80%; margin: 10px auto;"/> <p>From the north 1/16 sec. cor. of secs. 8 and 9, heretofore described</p> <p>N. 87° 30' W., on the east and west center line of the northeast quarter of sec. 8</p>
13.01	Intersect the arc of a curve, hereinafter described, the point for Angle Point No. 10, Tract 37
	Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 25 ins. in the ground, with brass cap mkd.
	<p>T8S R21W TR 37 <u>AP 10 / S 8</u></p> <p>1970</p>
20.24	The northeast 1/16 sec. cor. of sec. 8, heretofore described.
	<hr style="width: 20%; margin: 10px auto;"/> <p>N. 87° 27.5' W., beginning new measurement; thence, on a blank line across Tract 37.</p>
13.52	Intersect the arc of a curve, line 2 - 3, Tract 37, hereinafter described. From this point of intersection Angle Point No. 2 bears along the arc of the above curve 29.16 chs. distant.
20.25	The center-north 1/16 sec. cor. of sec. 8 heretofore described.
	Discontinue the regular order of survey at this corner.
	<hr style="width: 80%; margin: 10px auto;"/> <p>From the center-south 1/16 sec. cor. of sec. 8, heretofore described.</p> <p>N. 86° 46.5' W., on the east and west center line of the southwest quarter of sec. 8.</p>


Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS

0.01

Intersect the arc of a curve, hereinafter described, the point for Corner No. 1, Parcel B of sec. 8, and Angle Point No. 4, Tract 37

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.




1970

15.885

Intersect the arc of a curve, hereinafter described, the point for Corner No. 1, Parcel A, Corner No. 2, Parcel B of sec. 8, and Angle Point No. 3, Tract 37.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.



1970

40.46

The point for the south 1/16 sec. cor. of secs. 7 and 8, heretofore described.

The Metes and Bounds Survey
 of Lots 13 and 14 within section 8

Thence, with lot 13, section 8

Beginning at Corner No. 1, lot 13, which is identical with Corner No. 4, lot 14, and is located on the north and south center line of the northeast quarter of sec. 8, heretofore described.

S. 39° 08' W., on line 1 - 2, lot 13, which is identical with line 4 - 3, lot 14, of sec. 8.

15.86

Intersect the east and west center line, Corner No. 2, lot 13, which is identical with Corner No. 3, lot 14 of sec. 8, heretofore described.

S. 87° 22' E., on line 2 - 3, lot 13, which is identical with the east and west center line of the northeast quarter of sec. 8.

Survey of a Portion of the Subdivision Lines
 Within Sections 1, 3, 4, 5, and 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

57

CHAINS	
10.005	<p>The center-east 1/16 sec. cor. of sec. 8, heretofore described; this corner is designated to function for Corner No. 3, lot 13 of sec. 8.</p> <hr/>
	<p>N. 0° 05' E., on line 3 - 1, lot 13, which is identical with the north and south center line of the northeast quarter of sec. 8.</p>
12.76	<p>Corner No. 1, lot 13, which is identical with Corner No. 4, lot 14 of sec. 8, and the place of beginning.</p> <hr/>
	<p>Thence, with lot 14, section 8</p>
	<p>Beginning at Corner No. 1, lot 14, sec. 8, which is identical with Angle Point No. 8, Tract 37, heretofore described.</p>
	<p>S. 50° 41' W., on line 1 - 2, lot 14, sec. 8, which is identical with line 8 - 7, Tract 37.</p>
22.275	<p>Intersect with east and west center line, Corner No. 2, lot 14, sec. 8, which is identical with Angle Point No. 7, Tract 37, heretofore described.</p> <hr/>
	<p>S. 87° 22' E., on line 2 - 3, lot 14, which is identical with the east and west center line of sec. 8.</p>
7.225	<p>Corner No. 3, lot 14, which is identical with Corner No. 2, lot 13 of sec. 8, heretofore described.</p> <hr/>
	<p>N. 39° 08' E., on line 3 - 4, lot 14, which is identical with line 2 - 1, lot 13 of sec. 8.</p>
15.86	<p>Corner No. 4, lot 14, which is identical with Corner No. 1, lot 13, of sec. 8, heretofore described.</p> <hr/>
	<p>N. 0° 05' E., on line 4 - 1, lot 14, which is identical with the north and south center line of the northeast quarter of sec. 8.</p>
2.145	<p>Corner No. 1, lot 14, which is identical with Angle Point No. 8, Tract 37, and the place of beginning.</p> <hr/>
	<p>Metes and Bounds Survey of Parcel A, B, C, D, and E within Section 8 Township 8 South, Range 21 West Gila and Salt River Meridian, Arizona</p> <hr/>

Metes and Bounds Survey of Parcel A, B, C, D, and E
within Section 8
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Thence, with the metes and bounds survey of Parcel A of sec. 8</p>
	<p>Beginning at Corner No. 1, Parcel A, which is identical with Corner No. 2, Parcel B of sec. 8, and is identical with Angle Point No. 3, Tract 37, heretofore described.</p>
	<p>N. 86° 46.5' W., on line 1 - 2, Parcel A, which is identical with the east and west center line of the southwest quarter of sec. 8.</p>
24.575	<p>The point for the south 1/16 sec. cor. of secs. 7 and 8, heretofore described, which is designated to function for Corner No. 2, Parcel A of sec. 8.</p> <hr/>
	<p>S. 0° 20' E., on line 2 - 3, Parcel A of sec. 8, which is identical with the section line between secs. 7 and 8.</p>
19.065	<p>The corner of secs 7, 8, 17, and 18, heretofore described, which is designated to function for Corner No. 3, Parcel A of sec. 8.</p> <hr/>
	<p>S. 86° 03' E., on line 3 - 4, Parcel A of sec. 8, which is identical with the section line between secs. 8 and 17</p>
10.05	<p>The meander corner of secs. 8 and 17, on the right bank of the Gila River, heretofore described.</p>
	<p>Continue with course and measurement</p>
15.02	<p>The true point for the meander corner of secs. 8 and 17, on the left bank of the Gila River, heretofore described.</p>
16.05	<p>The witness meander corner of secs. 8 and 17, for the left bank of the Gila River, heretofore described.</p>
	<p>Continue with course and measurement</p>
19.56	<p>Corner No. 4, Parcel A, which is identical with Corner No. 4, Parcel B of sec. 8, heretofore described.</p> <hr/>
	<p>N. 10° 35' E., on line 4 - 5, Parcel A, which is identical with line 4 - 3, Parcel B of sec. 8</p>
2.235	<p>The point for Corner No. 5, Parcel A and Corner No. 3, Parcel B of sec. 8</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins in diam., 23 ins. in the ground, with brass cap mkd.</p>

Metes and Bounds Survey of Parcel A, B, C, D, and E
 Within Section 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

59

CHAINS

T8S R21W
 S / 8
 PAR A / PAR B
 COR 5 / COR 3
 1970

Thence, on line 5 - 1, Parcel A, which is identical with line 3 - 2, Parcel B of sec. 8, along the arc of a curve, curve data:

Chord bears N. 14° 59' E.
 Chord length 17.425 chs. distant
 Radius 113.635 chs. distant
 Length of arc 17.44 chs. distant

At the end of the arc of the curve, Corner No. 1, Parcel A, which is identical with Corner No. 2, Parcel B of sec. 8, and is identical with Angle Point No. 3, Tract 37, and the place of beginning.

Thence, with the metes and bounds survey of Parcel B of sec. 8

Beginning at Corner No. 1, Parcel B of sec. 8, which is identical with Angle Point No. 4, Tract 37, heretofore described.

N. 86° 46.5' W., on line 1 - 2, Parcel B of sec. 8, which is identical with line 4 - 3, Tract 37, and is identical with the east and west center line of the southwest quarter of sec. 8

15.875 Corner No. 2, Parcel B, which is identical with Corner No. 1, Parcel A of sec. 8, and is identical with Angle Point No. 3, Tract 37, heretofore described.

Thence, on line 2 - 3, Parcel B, which is identical with line 1 - 5, Parcel A of sec. 8, along the arc of a curve, curve data:

Chord bears S. 14° 59' W
 Chord length 17.425 chs. distant
 Radius 113.635 chs. distant
 Length of arc 17.44 chs. distant

At the end of the arc of the curve, Corner No. 3, Parcel B, which is identical with Corner No. 5, Parcel A of sec. 8, heretofore described.

S. 10° 35' W., on line 3 - 4, Parcel B which is identical with line 5 - 4, Parcel A of sec. 8.

Metes and Bounds Survey of Parcel A, B, C, D, and E
 Within Section 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS		
2.235	Corner No. 4, Parcel B, which is identical with Corner No. 4, Parcel A of sec. 8, heretofore described. <hr/>	
	S. 86° 03' E., on line 4 - 5, Parcel B of sec. 8, which is identical with the section line between secs. 8 and 17.	
15.25	Corner No. 5, Parcel B, which is identical with Corner No. 4, Parcel D of sec. 8, heretofore described. <hr/>	
	N. 10° 35' E., on line 5 - 6, Parcel B, which is identical with line 4 - 3, Parcel D of sec. 8.	
0.47	The point for Corner No. 6, Parcel B and Corner No. 3, Parcel D of sec. 8. Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center; margin: 10px 0;"> T8S R21W S 8 PAR B / PAR D COR 6 / COR 3 1970 </div> <hr/>	
	Thence, on line 6 - 1, Parcel B, which is identical with line 3 - 2, Parcel D of sec. 8, along the arc of a curve, curve data: Chord bears N. 16° 16' E. Chord length 19.445 chs. distant Radius 98.485 chs. distant Length of arc 19.48 chs. distant At 5.10 chs. distant on the arc of the curve, the point for Corner No. 2, Parcel D and Corner No. 14, Parcel E. of sec. 8. Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center; margin: 10px 0;"> T8S R21W S 8 PAR E COR 14 PAR B / COR 2 PAR D 1970 </div> <hr/>	
	Thence, continue on line 6 - 1, Parcel B, which is now identical with line 14 - 13, Parcel E of sec. 8, and along the arc of the above curve. At the end of the arc of the curve, Corner No. 1, Parcel B of sec. 8, which is identical with Angle Point No. 4, Tract 37, and the place of beginning. <hr/>	

Metes and Bounds Survey of Parcel A, B, C, D, and E
 Within Section 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona


CHAINS

Thence, with metes and bounds survey of Parcel C of sec. 8

The survey of the Fixed and Limiting Boundary of the medial line of the abandoned (1890) Gila River channel, partition line between an area of patented (private ownership) and vacant (United States ownership).

Beginning at a calculated position on the Fixed and Limiting Boundary of the medial line of the abandoned (1890) Gila River channel; this point is designated as Corner No. 1, Parcel C and Corner No. 3, Parcel E of sec. 8.


Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.



S. 72° 55' W., on a calculated bearing, the Fixed and Limiting Boundary of the medial line of the abandoned (1890) Gila River channel, through section 8, which is designated line 1 - 2, Parcel C of sec. 8.

28.38 The point for the Special Meander Corner of sec. 8.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 22 ins. in the ground, with brass cap mkd.



This corner is designated to function for Corner No. 11, Parcel E of sec. 8.

29.38 Intersect the north and south center line of sec. 8; Corner No. 2, Parcel C which is identical with Corner No. 10, Parcel E of sec. 8, heretofore described.

Discontinue the survey of the medial line of the abandoned (1890) Gila River channel at this corner.

SOUTH., on line 2 - 3, Parcel C of sec. 8, which is identical with the north and south center line of sec. 8.

Metes and Bounds Survey of Parcel A, B, C, D, and E
 Within Section 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS		
1.655	Corner No. 3, Parcel C which is identical with Corner No. 9, Parcel E of sec. 8, heretofore described.	
17.53	<p>S. 86° 46.5' E., on line 3 - 4, Parcel C, which is identical with line 9 - 8, Parcel E of sec. 8.</p> <p>The point for Corner No. 4, Parcel C and Corner No. 8, Parcel E of sec. 8.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 22 ins. in the ground, with brass cap mkd.</p> <div data-bbox="730 819 950 981" style="text-align: center;"> <p>T8S R21W S 8 PAR C COR 4 / COR 8 PAR E</p> </div> <p>1980</p>	
4.26	<p>N. 45° 01' E., on line 4 - 5, Parcel C, which is identical with line 8 - 7, Parcel E of sec. 8.</p> <p>The point for Corner No. 5, Parcel C and Corner No. 7, Parcel E of sec. 8.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 22 ins. in the ground, with brass cap mkd.</p> <div data-bbox="706 1464 950 1626" style="text-align: center;"> <p>T8S R21W S 8 PAR C COR 7 / COR 5 PAR E</p> </div> <p>1980</p>	
0.30	<p>S. 38° 09' E., on line 5 - 6, Parcel C, which is identical with line 7 - 6, Parcel E of sec. 8.</p> <p>The point for Corner No. 6, Parcel C and Corner No. 6, Parcel E of sec. 8.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 6 ins. below the surface of the ground, mkd.</p> <div data-bbox="763 2136 974 2325" style="text-align: center;"> <p>T8S R21W S 8 PAR C COR 6 / COR 6 PAR E</p> </div> <p>1980</p>	

Metes and Bounds Survey of Parcel A, B, C, D, and E
 Within Section 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS


There are no suitable accessories nor locations available for reference monuments.

4.755

N. 51° 51' E., on line 6 - 7, Parcel C, which is identical with line 6 - 5, Parcel E of sec. 8

The point for Corner No. 7, Parcel C and Corner No. 5, Parcel E of sec. 8.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 4 ins. below the surface of the ground, mkd.



1980


There are no suitable accessories nor locations available for reference monuments.

5.205

S. 75° 53.5' W., on line 7 - 8, Parcel C, which is identical with line 5 - 4, Parcel E of sec. 8

The point for Corner No. 8, Parcel C and Corner No. 4, Parcel E of sec. 8

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 22 ins. in the ground, with brass cap mkd.



1980

11.05

N. 51° 51' E., on line 8 - 1, Parcel C, which is identical with line 4 - 3, Parcel E of sec. 8

Corner No. 1, Parcel C, which is identical with Corner No. 3, Parcel E of sec. 8, and the place of beginning.

Thence, with the metes and bounds survey of Parcel D of sec. 8

The point for Corner No. 1, Parcel D, which is identical with Corner No. 15, Parcel E of sec. 8; this corner point is located on the center line of the Wellton-Mohawk Canal where it is impracticable to establish a permanent monument.

N. 87° 15' W., on line 1 - 2, Parcel D, which is identical with line 15 - 14, Parcel E of sec. 8


64

Metes and Bounds Survey of Parcel A, B, C, D, and E
 Within Section 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

CHAINS	
4.785	<p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, for the witness corner of Corner No. 1, Parcel D and Corner No. 15, Parcel E of sec. 8, with brass cap mkd.</p> <p style="text-align: center;"> W C T8S R21W S 8 PAR E COR 15 PAR D COR 1 → </p> <p style="text-align: center;">1970</p>
16.355	Intersect the north and south center line of sec. 8, heretofore described.
20.76	Corner No. 2, Parcel D, which is identical with Corner No. 14, Parcel E of sec. 8, heretofore described.
	<hr/> <p>Thence, on line 2 - 3, Parcel D, which is identical with a portion of line 1 - 6, Parcel B of sec. 8, along the arc of a curve, curve data:</p> <p>Chord bears S. 12° 04' W. Chord length 5.10 chs. distant Radius 98.485 chs. distant Length of arc 5.10 chs. distant</p> <p>At the end of the arc of the curve, Corner No. 3, Parcel D, which is identical with Corner No. 6, Parcel B of sec. 8, heretofore described.</p> <hr/> <p>S. 10° 35' W., on line 3 - 4, Parcel D, which is identical with line 6 - 5, Parcel B of sec. 8</p>
0.47	Corner No. 4, Parcel D, which is identical with Corner No. 5, Parcel B of sec. 8, heretofore described.
	<hr/> <p>S. 86° 03' E., on line 4 - 5, Parcel D of sec 8, which is identical with the section line between secs. 8 and 17.</p>
5.57	<p>The 1/4 sec. cor. of secs. 8 and 17, heretofore described.</p> <p>Continue with course and measurement</p>
14.95	The witness corner for Corner No. 5, Parcel D, which is identical with Corner No. 16, Parcel E of sec. 8, heretofore described.
19.705	<p>Intersect the center line of the Wellton-Mohawk Canal, the true point for Corner No. 5, Parcel D, which is identical with Corner No. 16, Parcel E of sec. 8, heretofore described.</p> <hr/>

Metes and Bounds Survey of Parcel A, B, C, D, and E
within Section 8
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

65

CHAINS		
	<p>N. 21° 02' E., on line 5 - 1, Parcel D, which is identical with line 16 - 15, Parcel E. of sec. 8, and along the center line of the Wellton-Mohawk Canal.</p>	
6.225	<p>The true point for Corner No. 1, Parcel D, which is identical with Corner No. 15, Parcel E of sec. 8, and the place of beginning.</p> <hr/> <p>Thence, with the metes and bounds survey of Parcel E of sec. 8</p> <p>The survey of the Fixed and Limiting Boundary of the medial line of the abandoned (1890) Gila River channel, partition line between an area of patented (private ownership) and vacant (United States ownership).</p> <p>Beginning at the Special Meander Corner of secs. 8 and 9, heretofore described, which is designated to function for Corner No. 1, Parcel E of sec. 8.</p> <p>N. 84° 49.5' W., on a calculated bearing, the fixed and limiting boundary of the medial line of the abandoned (1890) Gila River channel, through section 8, which is designated line 1 - 2, Parcel E of sec. 8.</p>	
7.225	<p>The calculated position, the point for Angle Point No. 1, sec. 8,</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 9 ins. below the surface of the ground, mkd.</p> <div style="text-align: center;"> <p>T8S R21W S 8 AP 1</p>  <p>COR 2 PAR E</p> <p>1970</p> </div> <p>The above corner is designated to function for Corner No. 2, Parcel E of sec. 8.</p> <p>There are no suitable accessories nor locations available for reference monuments.</p> <hr/>	
5.36	<p>S. 72° 55' W., continue with the survey of the medial line through section 8, which is designated line 2 - 3, Parcel E of sec. 8.</p> <p>Corner No. 3, Parcel E, which is identical with Corner No. 1, Parcel C of sec. 8, heretofore described.</p> <hr/>	
11.05	<p>S. 51° 51' W., on line 3 - 4, Parcel E, which is identical with line 1 - 8, Parcel C of sec. 8</p> <p>Corner No. 4, Parcel E which is identical with Corner No. 8, Parcel C of sec. 8, heretofore described.</p> <hr/>	

66

Metes and Bounds Survey of Parcel A, B, C, D, and E
within Section 8
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS		
	N. 75° 53.5' E., on line 4 - 5, Parcel E, which is identical with line 8 - 7, Parcel C of sec. 8	
5.205	Corner No. 5, Parcel E, which is identical with Corner No. 7, Parcel C of sec. 8, heretofore described.	
	S. 51° 51' W., on line 5 - 6, Parcel E, which is identical with line 7 - 6, Parcel C of sec. 8	
4.755	Corner No. 6, Parcel E, which is identical with Corner No. 6, Parcel C of sec. 8, heretofore described.	
	N. 38° 09' W., on line 6 - 7, Parcel E, which is identical with line 6 - 5, Parcel C of sec. 8	
0.30	Corner No. 7, Parcel E, which is identical with Corner No. 5, Parcel C of sec. 8, heretofore described.	
	S. 45° 01' W., on line 7 - 8, Parcel E, which is identical with line 5 - 4, Parcel C of sec. 8	
4.26	Corner No. 8, Parcel E, which is identical with Corner No. 4, Parcel C of sec. 8, heretofore described.	
	N. 86° 46.5' W., on line 8 - 9, Parcel E, which is identical with line 4 - 3, Parcel C of sec. 8	
17.53	Intersect the north and south center line, Corner No. 9, Parcel E, which is identical with Corner No. 3, Parcel C of sec. 8, heretofore described.	
	NORTH, on line 9 - 10, Parcel E., which is identical with line 3 - 2, Parcel C of sec. 8, and is identical with the north and south center line of sec. 8.	
1.655	Corner No. 10, Parcel E, which is identical with Corner No. 2, Parcel C of sec. 8, heretofore described.	
	N. 72° 55' E., on line 10 - 11, Parcel E, which is identical with a portion of line 2 - 1, Parcel C of sec. 8; and is the Fixed and Limiting Boundary of the medial line of the abandoned (1890) Gila River channel, through section 8.	
1.00	The Special Meander Corner of sec. 8, heretofore described. This corner is designated to function for Corner No. 11, Parcel E of sec. 8.	

Metes and Bounds Survey of Parcel A, B, C, D, and E
 Within Section 8
 Township 8 South, Range 21 West
 Gila and Salt River Meridian, Arizona

67

CHAINS	
	<p>Thence, with the survey of the Fixed and Limiting Boundary, the partition line between an area of patented (private ownership) and vacant (United States owner- ship).</p>
	<p>N. 19° 50' W., on a calculated bearing across the abandoned (1890) Gila River channel.</p>
2.83	<p>Intersect the north and south center line, the Special Meander Corner of sec. 8, which is designated to function for Corner No. 12, Parcel E of sec. 8, heretofore described.</p> <hr/>
	<p>NORTH, on line 12 - 13, Parcel E of sec. 8, which is identical with the north and south center line of sec. 8</p>
0.235	<p>The center-south 1/16 sec. cor. of sec. 8, heretofore described.</p>
	<p>Continue with line 12 - 13, Parcel E of sec. 8, and course and measurement.</p>
0.295	<p>Corner No. 13, Parcel E of sec. 8, which is identical with Angle Point No. 5, Tract 37, heretofore described.</p> <hr/>
	<p>Thence, on line 13 - 14, Parcel E of sec. 8, which is identical with line 5 - 4, Tract 37, along the arc of a curve, curve data:</p>
	<p>Chord bears S. 17° 45' W. Chord length 14.425 chs. distant Radius 98.485 chs. distant Length of arc 14.44 chs. distant.</p>
	<p>At 0.06 chs. distant on the arc of the curve, intersect the east and west center line of the southwest quarter, Corner No. 1, Parcel B of sec. 8, which is identical with Angle Point No. 4, Tract 37.</p>
	<p>Thence, continue on line 13 - 14, Parcel E, which is now identical with line 1 - 6, Parcel B of sec. 8, and along the arc of the above curve.</p>
	<p>At the end of arc of the curve, Corner No. 14, Parcel E, which is identical with Corner No. 2, Parcel D of sec. 8, heretofore described.</p> <hr/>
	<p>S. 87° 15' E., on line 14 - 15, Parcel E, which is identical with line 2 - 1, Parcel D of sec. 8</p>
4.405	<p>Intersect the north and south center line of sec. 8, heretofore described.</p>
15.975	<p>The witness corner for Corner No. 15, Parcel E, and Corner No. 1, Parcel D of sec. 8, heretofore described.</p>

Metes and Bounds Survey of Parcel A, B, C, D, and E
Within Section 8
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS	
20.76	<p>The true point for Corner No. 15, Parcel E, and Corner No. 1, Parcel D of sec. 8, heretofore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 21° 02' W., on line 15 - 16, Parcel E, which is identical with line 1 - 5, Parcel D of sec. 8</p>
6.225	<p>The true point for Corner No. 16, Parcel E, and Corner No. 5, Parcel D of sec. 8, heretofore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 86° 03' E., on line 16 - 17, Parcel E of sec. 8, which is identical with the section line between secs. 8 and 17.</p>
26.245	<p>The corner of secs. 8, 9, 16, and 17, heretofore described. This corner is designated to function for Corner No. 17, Parcel E of sec. 8.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 09.5' E., on line 17 - 1, Parcel E of sec. 8, which is identical with the section line between secs. 8 and 9.</p>
19.985	<p>The south 1/16 sec. cor. of secs. 8 and 9, heretofore described.</p> <p>Continue with course and measurement</p>
24.075	<p>The point for the meander corner of secs. 8 and 9, on the left bank of the abandoned (1890) Gila River channel, heretofore described.</p>
28.675	<p>Intersect the medial line of the abandoned (1890) Gila River channel, the Special Meander Corner of secs. 8 and 9, which is designated to function for Corner No. 1, Parcel E of sec. 8, and the place of beginning.</p> <hr style="width: 60%; margin: 10px auto;"/> <p style="text-align: center;">The Metes and Bounds Survey of Tracts 37 through 42 inclusive Township 8 South, Range 21 West Gila and Salt River Meridian, Arizona</p> <hr style="width: 60%; margin: 10px auto;"/> <p>Thence, with the metes and bounds survey of Tract 37</p> <p>Beginning at the corner of secs. 4, 5, 8, and 9, heretofore described, which is designated to function for Angle Point No. 1, Tract 37 and Corner No. 3, lot 6 of sec. 5.</p> <p>N. 87° 38' W., on line 1 - 2, Tract 37, which is identical with line 3 - 2, lot 6 of sec. 5, and is identical with the section line between sec. 5 and 8</p>
11.77	<p>Angle Point No. 2, Tract 37, which is identical with Corner No. 2, lot 6 of sec. 5, heretofore described.</p> <hr style="width: 20%; margin: 10px auto;"/>

The Metes and Bounds Survey of Tracts
37 through 42 inclusive
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

69

CHAINS		
	<p>Thence, on line 2 - 3, Tract 37, along the arc of a curve, curve data:</p> <p>Chord bears S. 37° 58.5' W. Chord length 72.485 chs. distant Radius 113.635 chs. distant Length of arc 73.77 chs. distant</p> <p>At 10.52 chs. distant on the arc of the curve, intersect the north and south center line of the northeast quarter of sec. 8, heretofore described.</p> <p>At 29.16 chs. distant on the arc of the curve, intersect the east and west center line of the northeast quarter of sec. 8, heretofore described.</p> <p>At 39.795 chs. distant on the arc of the curve, intersect the north and south center line of sec. 8, heretofore described.</p> <p>At 52.945 chs. distant on the arc of the curve, intersect the east and west center line of sec. 8, heretofore described.</p> <p>At the end of the arc of the curve, Angle Point No. 3, Tract 37, which is identical with Corner No. 1, Parcel A and Corner No. 2, Parcel B of sec. 8, heretofore described.</p> <hr/> <p>S. 86° 46.5' E., on line 3 - 4, Tract 37, which is identical with line 2 - 1, Parcel B of sec. 8, and is identical with the east and west center line of the southwest quarter of sec. 8.</p>	
15.875	<p>Angle Point No. 4, Tract 37, which is identical with Corner No. 1, Parcel B of sec. 8, heretofore described.</p> <hr/> <p>Thence, on line 4 - 5, Tract 37, which is identical with a portion of line 14 - 13, Parcel E of sec. 8, along the arc of a curve, curve data:</p> <p>Chord bears N. 9° 28' E. Chord length 0.06 chs. distant Radius 98.485 chs. distant Length of arc 0.06 chs. distant</p> <p>At the end of the arc of the curve, Angle Point No. 5, Tract 37, which is identical with Corner No. 13, Parcel E of sec. 8, heretofore described.</p> <hr/> <p>NORTH, on line 5 - 6, Tract 37, which is identical with the north and south center line of sec. 8</p>	
19.45	<p>The center 1/4 sec. cor. of sec. 8, heretofore described, which is designated to function for Angle Point No. 6, Tract 37.</p> <hr/>	

The Metes and Bounds Survey of Tracts
37 through 42 inclusive
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona



CHAINS		
	S. 87° 22' E., on line 6 - 7, Tract 37, which is identical with the east and west center line of sec. 8	
2.985	Angle Point No. 7, Tract 37, which is identical with Corner No. 2, lot 14 of sec. 8, heretofore described.	
	<hr/> N. 50° 41' E., on line 7 - 8, Tract 37, which is identical with line 2 - 1, lot 14 of sec. 8.	
22.275	Angle Point No. 8, Tract 37, which is identical with Corner No. 1, lot 14 of sec. 8, heretofore described.	
	<hr/> N. 0° 05' E., on line 8 - 9, Tract 37, which is identical with the north and south center line of the northeast quarter of sec. 8.	
4.995	The northeast 1/16 sec. cor. of sec. 8, heretofore described, which is designated to function for Angle Point No. 9, Tract 37.	
	<hr/> S. 87° 30' E., on line 9 - 10, Tract 37, which is identical with the east and west center line of the northeast quarter of sec. 8.	
7.23	Angle Point No. 10, Tract 37, heretofore described.	
	<hr/> Thence, on line 10 - 11, Tract 37, along the arc of a curve, curve data: Chord bears N. 54° 13' E. Chord length 16.065 chs. distant Radius 98.485 chs. distant Length of arc 16.085 chs. distant At the end of the arc of the curve, Angle Point No. 11, Tract 37, heretofore described.	
10.01	<hr/> N. 0° 09.5' E., on line 11 - 1, Tract 37, which is identical with the section line between secs. 8 and 9. The corner of secs. 4, 5, 8, and 9, which is designated to function for Angle Point No. 1, Tract 37 and Corner No. 3, lot 6 of sec. 5, and the place of beginning.	
	<hr/> Thence, with the metes and bounds survey of Tract 38 Beginning at Angle Point No. 1, Tract 38, which is identical with Angle Point No. 3, Tract 39, heretofore described.	

The Metes and Bounds Survey of Tracts
37 through 42 inclusive
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

71

CHAINS	
13.27	<p>S. 72° 19.5' W., on line 1 - 2, Tract 38</p> <p>Angle Point No. 2, Tract 38, heretofore described.</p> <hr/>
18.825	<p>S. 59° 48' W., on line 2 - 3, Tract 38, which is identical with the medial line of the abandoned (1890) Gila River channel, and is the partition line between an area of patented (private ownership) and vacant (United States ownership).</p> <p>Intersect the east and west center line of the south-east quarter of sec. 4, heretofore described.</p>
22.885	<p>The Special Meander Corner of sec. 8, which is designated to function for Angle Point No. 3, Tract 38, heretofore described.</p> <hr/>
2.295	<p>N. 30° 50' W., on line 3 - 4, Tract 38, which is the partition line between an area of patented (private ownership) and vacant (United State ownership).</p> <p>The Special Meander Corner of sec. 8, which is designated to function for Angle Point No. 4, Tract 38, heretofore described.</p> <hr/>
6.37	<p>S. 89° 08' W., on line 4 - 5, Tract 38, which is identical with the east and west center line of the south-east quarter of sec. 4.</p> <p>The center-south 1/16 sec. cor. of sec. 4, heretofore described, which is designated to function for Angle Point No. 5, Tract 38.</p> <hr/>
0.925	<p>N. 0° 38' W., on line 5 - 6, Tract 38, which is identical with the north and south center line of sec. 4.</p> <p>Angle Point No. 6, Tract 38, heretofore described.</p> <hr/>
24.885	<p>S. 72° 19.5' W., on line 6 - 7, Tract 38</p> <p>The point for Angle Point No. 7, Tract 38</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>

The Metes and Bounds Survey of Tracts
37 through 42 inclusive
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<div style="text-align: center;">  <p>T8S R21W S 4 AP 7 TR 38</p> </div> <p style="text-align: center;">1970</p> <hr/> <p>Thence, on line 7 - 8, Tract 38, along the arc of a curve, curve data:</p> <p>Chord bears S. 67° 53' W. Chord length 17.62 chs. distant Radius 113.635 chs. distant Length of arc 17.64 chs. distant</p> <p>At the end of the arc of the curve, Angle Point No. 8, Tract 38, which is identical with Corner No. 1, lot 6, sec. 5, heretofore described.</p> <hr/> <p>S. 0° 09' W., on line 8 - 9, Tract 38, which is identical with line 1 - 3, lot 6 of sec. 5, and is identical with the section line between secs. 4 and 5</p> <p>7.285 The corner of secs. 4, 5, 8, and 9, heretofore described, which is designated to function for Angle Point No. 9, Tract 38, Angle Point No. 1, Tract 37, and Corner No. 3, lot 6 of sec. 5.</p> <hr/> <p>N. 89° 14' E., on line 9 - 10, Tract 38, which is identical with the section line between secs. 4 and 9</p> <p>23.425 Angle Point No. 10, Tract 38, heretofore described.</p> <hr/> <p>N. 72° 19.5' E., on line 10 - 11, Tract 38</p> <p>17.635 Intersect the north and south center line of sec. 4, heretofore described.</p> <p>33.60 The point for Angle Point No. 11, Tract 38</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>T8S R21W TR 38 AP 11 S 4</p> </div> <p style="text-align: center;">1970</p> <hr/>


The Metes and Bounds Survey of Tracts
37 through 42 inclusive
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

73

CHAINS		
9.665	<p>S. 43° 10' W., on line 11 - 12, Tract 38</p> <p>The point for Angle Point No. 12, Tract 38</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R21W</p> <p style="text-align: center;">S 4 / AP 12 TR 38</p> <p style="text-align: center;">1970</p> <hr/>	
4.235	<p>S. 47° 42' W., on line 12 - 13, Tract 38</p> <p>Angle Point No. 13, Tract 38, heretofore described.</p> <hr/>	
4.57	<p>N. 89° 14' E., on line 13 - 14, Tract 38, which is identical with the section line between secs. 4 and 9</p> <p>Angle Point No. 14, Tract 38, heretofore described.</p> <hr/>	
0.815	<p>N. 47° 42' E., on line 14 - 15, Tract 38</p> <p>The point for Angle Point No. 15, Tract 38</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R21W</p> <p style="text-align: center;">TR 38 AP 15 / S 4</p> <p style="text-align: center;">1970</p> <hr/>	
19.33	<p>N. 53° 21' E., on line 15 - 16, Tract 38</p> <p>The point for Angle Point No. 16, Tract 38</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R21W</p> <p style="text-align: center;">TR 38 AP 16 / S 4</p> <p style="text-align: center;">1970</p> <hr/>	
	<p>N. 62° 50' E., on line 16 - 17, Tract 38</p>	

74


The Metes and Bounds Survey of Tracts
37 through 42 inclusive
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS		
7.155	<p>The point for Angle Point No. 17, Tract 38; this corner point is located within the bed of the Gila River, where it is impracticable to establish a permanent monument. This true corner point is designated to function for the corner of lots 15 and 16 of sec. 4.</p> <p>From this point, the point for the witness cor. to the cor. for Angle Point No. 17, Tract 38 bears S. 72° 19.5' W., 2.93 chs. dist.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>	
	<div style="text-align: center;"> <p>W C T8S R21W TR 38 AP 17 → S 4 1970</p>  </div>	
	<p>Thence, continue from the true point for Angle Point No. 17, Tract 38.</p> <p>N. 72° 19.5' E., on line 17 - 18, Tract 38, which is identical with the northern boundary of lot 16 of sec. 4.</p>	
7.935	<p>Angle Point No. 18, Tract 38, which is identical with Angle Point No. 4, Tract 39, and the northeast corner of lot 16 of sec. 4, heretofore described.</p>	
	<p>N. 0° 56' W., on line 18 - 1, Tract 38, which is identical with line 4 - 3, Tract 39, and is identical with the section line between secs. 3 and 4.</p>	
2.76	<p>The south 1/16 sec. cor. of secs. 3 and 4, heretofore described.</p> <p>Continue with course and measurement</p>	
15.82	<p>Angle Point No. 1, Tract 38, which is identical with Angle Point No. 3, Tract 39, and the place of beginning.</p>	
	<p>Thence, with the metes and bounds survey of Tract 39</p> <p>Beginning at a calculated position of (hereinafter described) line 4 - 5, Tract 42; this position is designated the point for Angle Point No. 1, Tract 39.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 22 ins. in the ground, with brass cap mkd.</p>	

The Metes and Bounds Survey of Tracts
37 through 42 inclusive
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

75

CHAINS




1980

Thence, on line 1 - 2, Tract 39, along the arc of a curve, curve data:

Chord bears S. 73° 14' W.
Chord length 5.05 chs. distant
Radius 159.09 chs. distant
Length of arc 5.05 chs. distant

At the end of the arc of the curve, the point for Angle Point No. 2, Tract 39

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.



1970

S. 72° 19.5' W., on line 2 - 3, Tract 39

6.305 Angle Point No. 3, Tract 39, which is identical with Angle Point No. 1, Tract 38, heretofore described.

S. 0° 56' E., on line 3 - 4, Tract 39, which is identical with line 1 - 18, Tract 38, and is identical with the section line between secs. 3 and 4.

13.06 The south 1/16 sec. cor. of secs. 3 and 4, heretofore described.

Continue with course and measurement

15.82 Angle Point No. 4, Tract 39, which is identical with Angle Point No. 18, Tract 38, heretofore described.

N. 72° 19.5' E., on line 4 - 5, Tract 39

9.045 Intersect the east and west center line of the south-west quarter of sec. 3, heretofore described.

10.86 The point for Angle Point No. 5, Tract 39

The Metes and Bounds Survey of Tracts
37 through 42 inclusive
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R21W
TR 39
AP 5
S 3

1970

Thence, on line 5 - 6, Tract 39, along the arc of a curve, curve data:

Chord bears N. 74° 11.5' E.
Chord length 9.39 chs. distant
Radius 143.94 chs. distant
Length of arc 9.39 chs. distant

At the end of the arc of the curve; the point for Angle Point No. 6, Tract 39 is determined at the intersection of the above curve (hereinafter described) line 7 - 8, Tract 42.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R21W
TR 42
AP 6
TR 39 S 3

1980

N. 88° 24' W., on line 6 - 7, Tract 39, which is identical with a portion of line 7 - 8, Tract 42

6.36 The point for Angle Point No. 7, Tract 39, which is identical with Angle Point No. 7, Tract 42.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 22 ins. in the ground, with brass cap mkd.

T8S R21W
TR 42
AP 7



AP 7
TR 39

1980

N. 81° 29' W., on line 7 - 8, Tract 39, which is identical with line 7 - 6, Tract 42

11.16 The point for Angle Point No. 8, Tract 39, which is identical with Angle Point No. 6, Tract 42

The Metes and Bounds Survey of Tracts
37 through 42 inclusive
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R21W TR 39 TR 42 AP 8 AP 6</p>  <p>1980</p> </div> <hr/> <p>N. 5° 14.5' W., on line 8 - 9, Tract 39, which is identical with line 6 - 5, Tract 42</p>
3.43	<p>The point for Angle Point No. 9, Tract 39, which is identical with Angle Point No. 5, Tract 42</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R21W AP 9 AP 5 TR 39 TR 42</p>  <p>1980</p> </div> <hr/> <p>N. 47° 45.5' E., on line 9 - 1, Tract 39, which is identical with a portion of line 5 - 4, Tract 42</p>
12.04	<p>Angle Point No. 1, Tract 39, and the place of beginning.</p> <hr/> <p>Thence, with the metes and bounds survey of Tract 40.</p> <p>Beginning at Angle Point No. 1, Tract 40 on the east bdy. of the Tp., heretofore described.</p> <p>N. 86° 55' W., on line 1 - 2, Tract 40</p>
40.025	<p>Intersect the north and south center line of sec. 1, heretofore described.</p>
80.10	<p>Angle Point No. 2, Tract 40, heretofore described.</p> <hr/>
15.183	<p>S. 0° 35' E., on line 2 - 3, Tract 40, which is identical with the section line between secs. 1 and 2</p> <p>Angle Point No. 3, Tract 40, heretofore described.</p> <hr/>
39.95	<p>S. 86° 55' E., on line 3 - 4, Tract 40</p> <p>Intersect the north and south center line of sec. 1, heretofore described.</p>

The Metes and Bounds Survey of Tracts
37 through 42 inclusive
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

<p>CHAINS 48.425</p>	<p>Angle Point No. 4, Tract 40, heretofore described.</p> <hr/>	
	<p>N. 40° 00' E., on line 4 - 5, Tract 40, which is the partition line between an area of patented (private ownership) and vacant (United States ownership).</p>	
<p>1.595</p>	<p>The Special Meander Corner of sec. 1, which is designated to function for Angle Point No. 5, Tract 40, heretofore described.</p> <hr/>	
	<p>S. 50° 00' E., on line 5 - 6, Tract 40, continue on the partition line between an area of patented (private ownership) and vacant (United States ownership).</p>	
<p>2.085</p>	<p>Angle Point No. 6, Tract 40, heretofore described.</p> <hr/>	
	<p>S. 86° 55' E., on line 6 - 7, Tract 40</p>	
<p>12.46</p>	<p>Intersect the east and west center line of the south-east quarter of sec. 1, heretofore described.</p>	
<p>28.93</p>	<p>Angle Point No. 7, Tract 40 on the east boundary of the township, heretofore described.</p> <hr/>	
	<p>N. 0° 05' W., on line 7 - 1, Tract 40, which is identical with the east boundary of the township</p>	
<p>0.865</p>	<p>The south 1/16 sec. cor. of sec. 1, heretofore described.</p>	
	<p>Continue with course and measurement</p>	
<p>2.55</p>	<p>The north 1/16 sec. cor. of sec. 6, on the west boundary of Tp. 8 S., R. 20 W., heretofore described.</p>	
	<p>Continue with course and measurement</p>	
<p>12.85</p>	<p>Angle Point No. 3, lot 11 of sec. 6, which is identical with Angle Point No. 6, Tract 37, Tp. 8 S., R. 20 W., heretofore described.</p>	
	<p>Continue with course and measurement</p>	
<p>15.175</p>	<p>Angle Point No. 1, Tract 40, and the place of beginning.</p> <hr/>	
	<p>Thence, with the metes and bounds survey of Tract 41 Beginning at the corner of Tps. 7 and 8 S., R. 21 W. (secs. 1 and 36), heretofore described. This corner is designated to function for Angle Point No. 1, Tract 41.</p>	

The Metes and Bounds Survey of Tracts
37 through 42 inclusive
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

79

CHAINS	
	N. 88° 52' W., on line 1 - 2, Tract 41, which is identical with the south boundary of Tp. 7 S., R. 21 W., and being the north boundary of Tp. 8 S., R. 21 W.
20.01	The east 1/16 sec. cor. of sec. 36 (only), Tp. 7 S. R. 21 W., heretofore described. This corner is designated to function for Angle Point No. 2, Tract 41, Tp. 8 S., R. 21 W.
	S. 89° 07' W., on line 2 - 3, Tract 41, continue along the above described township line.
0.085	The east 1/16 sec. cor. of sec. 1 (only), Tp. 8 S., R. 21 W., heretofore described.
	Continue with course and measurement
19.985	The south 1/4 sec. cor. of sec. 36, Tp. 7 S., R. 21 W., heretofore described. This corner is designated to function for Angle Point No. 3, Tract 41, Tp. 8 S., R. 21 W.
	N. 89° 52' W., on line 3 - 4, Tract 41, continue along the above described township line.
0.17	The north 1/4 sec. cor. of sec. 1, Tp. 8 S., R. 21 W., heretofore described.
	Continue with course and measurement
19.99	The west 1/16 sec. cor. of sec. 36 (only), Tp. 7 S., R. 21 W., heretofore described. This corner is designated to function for Angle Point No. 4, Tract 41, Tp. 8 S., R. 21 W.
	N. 89° 53' W., on line 4 - 5, Tract 41, continue along the above described township line.
0.255	The west 1/16 sec. cor. of sec. 1 (only) Tp. 8 S., R. 21 W., heretofore described. This corner is designated to function for Angle Point No. 5, Tract 41, Tp. 8 S., R. 21 W.
	S. 0° 24.5' E., on line 5 - 6, Tract 41, which is identical with the north and south center line of the northwest quarter of sec. 1, Tp. 8 S., R. 21 W.
10.605	Angle Point No. 6, Tract 41, heretofore described.
	S. 89° 52.3' E., on line 6 - 7, Tract 41
20.06	Intersect the north and south center line of sec. 1, heretofore described.

The Metes and Bounds Survey of Tracts
37 through 42 inclusive
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS

40.104 Intersect the north and south center line of the north-east quarter of sec. 1, heretofore described.

60.174 Intersect the east boundary of the township, Angle Point No. 7, Tract 41, heretofore described.

N. 0° 05' W., on line 7 - 1, Tract 41, which is identical with the east boundary of the township.

10.605 The corner of Tps. 7 and 8 S., R. 21 W., which is designated to function for Angle Point No. 1, Tract 41, and the place of beginning.

Thence, with the metes and bounds survey of Tract 42

Beginning at Angle Point No. 1, Tract 42, which is identical with Angle Point No. 2 of sec. 3, located on the reestablished medial line of the abandoned (1890) Gila River channel, heretofore described.

S. 76° 51' W., on line 1 - 2, Tract 42, which is identical with the medial line of the abandoned (1890) Gila River channel, through section 3.

10.36 Angle Point No. 2, Tract 42, heretofore described.

Thence, on line 2 - 3, Tract 42, along the arc of a curve, curve data:

Chord bears S. 49° 38' W.
Chord length 1.07 chs. distant
Radius 85.30 chs. distant
Length of arc 1.07 chs. distant

At the end of the arc of the curve; the point for Angle Point No. 3, Tract 42

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 22 ins. in the ground, with brass cap mkd.

T8S R21W
S 3
X AP 3
TR 42

1980

The Metes and Bounds Survey of Tracts
37 through 42 inclusive
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

81

CHAINS

Thence, on line 3 - 4, Tract 42, along the arc of a curve, curve data:

Chord bears S. 48° 18' W.
Chord length 4.51 chs. distant
Radius 85.30 chs. distant
Length of arc 4.51 chs. distant

At 1.245 chs. distant on the arc of the curve, intersect the east and west center line of section 3, heretofore described.

At the end of the arc of the curve; the point for Angle Point No. 4, Tract 42

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R21W

AP 4
S 3 TR 42
1980

S. 47° 45.5' W., on line 4 - 5, Tract 42

2.24 Angle Point No. 1, Tract 39, heretofore described.

Continue on line 4 - 5, Tract 42, which is now identical with line 1 - 9, Tract 39.

14.28 Angle Point No. 5, Tract 42, which is identical with Angle Point No. 9, Tract 39, heretofore described.

S. 5° 14.5' E., on line 5 - 6, Tract 42, which is identical with line 9 - 8, Tract 39

3.43 Angle Point No. 6, Tract 42, which is identical with Angle Point No. 8, Tract 39, heretofore described.

S. 81° 29' E., on line 6 - 7, Tract 42, which is identical with line 8 - 7, Tract 39

11.16 Angle Point No. 7, Tract 42, which is identical with Angle Point No. 7, Tract 39, heretofore described.

S. 88° 24' E., on line 7 - 8, Tract 42, which is identical with line 7 - 6, Tract 39

6.36 Angle Point No. 6, Tract 39, heretofore described.

Continue with course and measurement

15.94 The point for Angle Point No. 8, Tract 42

The Metes and Bounds Survey of Tracts
37 through 42 inclusive
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R21W TR 42 AP 8 S 3 1980</p> <hr/> <p>S. 68° 08' E., on line 8 - 9, Tract 42</p>	
7.74	<p>Intersect the east and west center line of the south-west quarter of sec. 3, Angle Point No. 9, Tract 42, heretofore described.</p> <hr/> <p>S. 89° 55' E., on line 9 - 10, Tract 42, which is identical with the east and west center line of the south-west quarter of sec. 3</p>	
3.605	<p>Intersect the north and south center line, the center-south 1/16 sec. cor. of sec. 3, heretofore described; this corner is designated to function for Angle Point No. 10, Tract 42</p> <hr/> <p>S. 89° 56' E., on line 10 - 11, Tract 42, which is identical with the east and west center line of the southeast quarter of sec. 3</p>	
12.90	<p>Angle Point No. 11, Tract 42, heretofore described.</p> <hr/> <p>N. 40° 13.5' E., on line 11 - 12, Tract 42</p>	
3.62	<p>Intersect the reestablished meanders of the left bank of the abandoned (1890) Gila River channel; Angle Point No. 12, Tract 42, heretofore described.</p> <hr/> <p>N. 47° 30' W., on line 12 - 13, Tract 42, which is identical with the reestablished meanders of the left bank of the abandoned (1890) Gila River channel</p>	
14.12	<p>Angle Point No. 13, Tract 42, which is identical with Angle Point No. 1, sec. 3, on the reestablished meanders of the left bank of the abandoned (1890) Gila River channel, heretofore described.</p> <hr/> <p>N. 63° 15' W., on line 13 - 14, Tract 42, which is identical with the reestablished meanders of the left bank of the abandoned (1890) Gila River channel.</p>	

The Metes and Bounds Survey of Tracts
37 through 42 inclusive
Township 8 South, Range 21 West
Gila and Salt River Meridian, Arizona

83

CHAINS	
5.73	Intersect the north and south center line, the point for the Special Meander Corner of sec. 3, heretofore described.
17.41	Intersect the east and west center line, the point for the Special Meander Corner of sec. 3, heretofore described
18.16	Angle Point No. 14, Tract 42, heretofore described.
	<hr/> <p>Thence, on line 14 - 15, Tract 42, along the arc of a curve, curve data:</p> <p>Chord bears N. 81° 26' E. Chord length 4.27 chs. distant Radius 159.09 chs. distant Length of arc 4.27 chs. distant</p> <p>At the end of the arc of the curve; Intersect reestablished medial line of the abandoned (1890) Gila River channel, Angle Point No. 15, Tract 42, heretofore described.</p> <hr/>
6.75	<p>N. 64° 04' W., on line 15 - 1, Tract 42, which is identical with the reestablished medial line of the abandoned (1890) Gila River channel.</p> <p>Angle Point No. 1, Tract 42, which is identical with Angle Point No. 2 of sec. 3, located on the reestablished medial line of the abandoned (1890) Gila River channel, and the place of beginning.</p> <hr/>
	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The land area within these surveys is nearly level to rolling. Drainage is to the west through sections 1, 3, and 4, thence, to the southwest through section 5 and 8. The soil consists of sandy clay loam, the land area is under cultivation, with the exception of the federally controlled lands, which are undeveloped; with French tamarish, mesquite, and paloverde trees; undergrowth, young trees, cacti, arrow weed, and creosote brush (shrub).</p> <p>Improvements located throughout the area, are: The Wellton-Mohawk Canal, and numerous canals and laterals for irrigation and/or drainage purposes; Two tracks of the Southern Pacific railroad, U.S. Highway No. 95, Yuma County and farm roads.</p> <hr/>

CHAINS		
--------	--	--

Form 9600-11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Victor E. Templeton	Surveying Aid
Dale E. Phillips	Surveying Aid
Ernest E. Hurtado	Surveying Aid
Fordner Van Fleet, Jr.	Surveying Aid
Gilbert V. Olson	Cadastral Surveyor
Donald C. Beecroft, Jr.	Surveying Aid
William C. Gabonay	Surveying Aid
Troy D. Hudspeth	Surveying Aid
Terry E. Northup	Surveying Aid
Richard J. Teiper	Surveying Aid
Paul J. Fisher	Surveying Technician
Richard H. Gingerich	Surveying Technician
Douglas A. Spence	Surveying Aid
Thomas G. Boehm	Surveying Aid
Brian K. Logsdon	Surveying Aid




CERTIFICATE OF SURVEY

~~XX~~ (We), Ray Harpin, Douglas A. Cody, and Santiago T. Chavez , HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 14th day

of October , 1969 , ~~XXXXXX~~ Supplemental Special Instructions dated November 20, 1969, Supplemental Special Instructions dated September 5, 1979, and Supplemental Special Instructions dated October 20, 1980, (We) have de-
pendently resurveyed a portion of the east boundary of the township, a por-
tion of the south boundary of Township 7 South, Range 21 West (the north
boundary of section 1, Township 8 South, Range 21 West), and a portion of
the subdivisional lines; surveyed a portion of the subdivision lines within
sections 1, 3, 4, 5, and 8; the metes and bounds survey of lot 26 and Parcel
A within section 1, lot 16 of section 4, lot 6 of section 5, and lots 13 and
14, Parcels A, B, C, D, and E, within section 8; and the metes and bounds
survey of Tracts 37 through 42 inclusive, Township 8 South, Range 21 West,

of the Gila and Salt River Meridian, in the State of Arizona , which
are represented in the foregoing field notes as having been executed by ~~XXX~~, (us) and under ~~XXXX~~
(our) direction; and that said survey has been made in strict conformity with said special instruc-
tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in
specific manner described in the foregoing field notes.

March 3, 1981 _____ (Date)	 _____ (Cadastral Surveyor)
March 5, 1981 _____ (Date)	 _____ (Cadastral Surveyor)
March 3, 1981 _____ (Date)	 _____ (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the east boundary
of the township, a portion of the south boundary of Tp. 7 S., R. 21 W. (the
north boundary of section 1, Tp. 8 S., R. 21 W.), and a portion of the sub-
divisional lines; survey of a portion of the subdivision lines with sections
1, 3, 4, 5, and 8; the metes and bounds survey of lot 26 and Parcel A within
section 1, lot 16 of section 4, lot 6 of section 5, and lots 13 and 14, Parcels
A, B, C, D, and E, within section 8; and the metes and bounds survey of Tracts 37
through 42 inclusive, Tp. 8 S., R. 21 W., of the Gila and Salt River Meridian, AZ
executed by Ray Harpin, Douglas A. Cody, and Santiago T. Chavez, Cadastral
Surveyors
having been critically examined and found correct, are hereby approved.

NOV 23 1981

(Date) 
ACTING (Chief, Cadastral Survey Examination and Approval Staff)

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
_____, is a true copy of the original field notes.

(Date) _____
(Chief, Cadastral Survey Examination and Approval Staff)