

Form 9600-9
(December 1979)
(formerly 9180-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

B00 K5 173

FIELD NOTES

ORIGINAL

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE

FIRST STANDARD PARALLEL SOUTH,

SOUTH BOUNDARY OF TOWNSHIP 5 SOUTH, RANGE 30 EAST,

A PORTION OF THE EAST BOUNDARY

AND

SUBDIVISIONAL LINES,

A CORRECTIVE DEPENDENT RESURVEY

BETWEEN SECTIONS 1 AND 2,

THE SURVEY OF THE SUBDIVISION

AND A

METES-AND-BOUNDS SURVEY OF CERTAIN SMALL LOTS

IN SECTION 1

OF

TOWNSHIP 6 SOUTH, RANGE 30 EAST

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

EXECUTED BY

PAUL L. REEVES SUPERVISORY CADASTRAL SURVEYOR

Under special instructions dated JANUARY 4, 1982, approved JANUARY 4, 1982,

AND SUPPLEMENTAL SPECIAL INSTRUCTIONS DATED APRIL 1, 1982, APPROVED APRIL 1,

1982, which provided for the surveys included under ~~XXX Survey~~ Group

Number 628, and assignment instructions dated JANUARY 4, 1982.

Survey commenced JANUARY 7, 1982

Survey completed APRIL 7, 1982

INDEX DIAGRAM

Township 6 SOUTH, Range 30 EAST,

3

6	5	4	3	2	8 1
					7
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

7

Subdivision of Section 1.....pp. 11-17
 Metes-and-bounds survey of certain small lots.....pp. 17-20

T. 6 S., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS

The north boundary of section 1 (First Standard Parallel South) was surveyed in 1882 by Theodore F. White, re-surveyed in 1891 by Daniel Drummond and again in 1968 by Gary T. Oviatt. The east boundary of section 1 was surveyed in 1891 by Daniel Drummond and resurveyed in 1968-1969 by Louis D. Gilbert. The south and west boundaries of section 1 and the meander lines of the Gila River through section 1 were surveyed in 1891 by Daniel Drummond. Louis D. Gilbert resurveyed the south and west boundaries of section 1 in 1968-1969.

The following field notes are those of a dependent re-survey of a portion of the First Standard Parallel South, south boundary of Township 5 South, Range 30 East; a portion of the east boundary and subdivisional lines, a corrective dependent resurvey between secs. 1 and 2, the survey of the subdivision and a metes-and-bounds survey of certain small lots in sec. 1, Township 6 South, Range 30 East, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 628, Arizona, dated January 4, 1982, and Supplemental Special Instructions dated April 1, 1982.

The directions of lines were determined from triangulation stations of the horizontal control network and refer to the true meridian. Distances and angles were measured with a Hewlett Packard 3820A total station.

In initiating the resurvey, retracements of the previous surveys were performed and a diligent search made to identify evidence of all previously established corner monuments. Identified corners are remonumented in their original positions; where available, collateral evidence is used to reestablish obliterated corners; and lost corners are reestablished by the rules of proportionate measurement.

In the 1968 resurvey, the original 1/4 sec. cor. of secs. 1 and 2 was not recovered and was reestablished by proportionate measurement. During the resurvey of section 1, under Group No. 628, the original 1/4 sec. cor. of sec. 1 and 2, was recovered in place, N. 82°58' E., 3.485 chs. dist., from the 1968 proportioned cor. In view of the existing condition, a corrective dependent resurvey was made of the line between secs. 1 and 2, using the found original 1/4 sec. cor. of secs. 1 and 2. The locations of the 1968 iron posts (1/4 sec. cor. and closing cor. of secs 1 and 2) with respect to the corrected locations were noted and then moved to their new locations. The old dates were removed and new dates added.

The geographic position of the southeast cor. of sec. 1, as determined from a tie made to the U.S.C.&G.S. triangulation station "SIDE", is as follows:

Latitude: 32°55'59.82" N. Longitude: 109°13'07.60" W.

The mean magnetic declination is 13°00' E.

Dependent Resurvey of a Portion of First Standard
Parallel South, S. Bdy. of T. 5 S., R. 30 E., Gila and
Salt River Meridian, Arizona

CHAINS		
	(Restoring the 1968 Resurvey by Gary T. Oviatt)	
	<p>Beginning at the standard 1/4 sec. cor. of sec. 36, monumented with an iron post, 2½ ins. diam., projecting 6 ins. above the ground, with brass cap mkd.</p>	
	<p>S C T5S R30E <u>1/4 S 36</u> 1968</p>	
	<p>Cor. is witnessed with a mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor.</p> <p>Cor. is located 10 lks. S of an E and W fence line.</p> <p>N. 89°54' W., on the S bdy. of sec. 36.</p> <p>Over rolling land, through medium creosote.</p>	
34.09	The closing cor. of Tps. 6 S., Rs. 30 and 31 E., hereinafter described.	
40.01	<p>The standard cor. of secs. 35 and 36. monumented with an iron post, 2½ ins. diam., projecting 24 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>	
	<p>S C T5S R30W <u>S 35 S 36</u> 1968</p>	
	<p>Cor. is located 14 lks. S. of and E and W fence line.</p>	
	<p>N. 89°56' W., on the S. bdy. of sec. 35.</p> <p>Over gently rolling land, through scattered creosote, sage brush and mesquite.</p>	
14.12	<p>Point for the E 1/16 sec. cor. of sec. 1 only.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p>	
	<p><u>E1/16 S1</u> T6S R30E 1982</p>	
	<p>Cor. is located 3 lks. S. of an E and W fence line, in the E. edge of a wash, in a draw, 50 lks. wide, drains SW.</p>	
24.14	<p>Point for the W-E 1/64 sec. cor. of sec. 1 only, identical with cor. 1, lot 14, sec. 1.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p>	

Dependent Survey of a Portion of First Standard
Parallel South, S. Bdy. of T. 5 S., R. 30 E., Gila and
Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">W-E 1/64 S 1 1982</p> <p>Cor. is located 4.5 lks. S. of an E and W fence line.</p>	
34.16	<p>The 1/4 sec. cor. of sec. 1 only, monumented with an iron post, 2½ ins. diam., projecting 12 ins. above the ground, with brass cap mkd.</p>	
39.97	<p style="text-align: center;">1/4 S1 T6S R30E 1968</p> <p>The standard 1/4 sec. cor. of sec. 35, identical with cor. 2, lot 14, sec. 1, monumented with an iron post, 2½ ins. projecting 5 ins. above the ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S C T5S R30E 1/4 S35 1968</p> <p>From this point, U.S.C.&G.S. Triangulation Station "Side" bears N. 83°10' E., 13.15 chs. dist., monumented with a brass tablet, 3 ins. diam., in a base of concrete, 12 x 12 ins., projecting 4 ins. above the ground, mkd. Side 1945, and a triangle. The geographic position as published by U.S.C.&G.S. is:</p> <p style="text-align: center;">Latitude: 32°56'52.443" N. Longitude: 109°13'32.217" W.</p> <p style="text-align: center;">N. 89°51' W., beginning new measurement.</p>	
4.13	<p>Point for cor. no. 3 of lot 14, sec. 1, at intersection with the center line of State Highway No. 75.</p> <p>Set a railroad spike, with top mkd.</p> <p style="text-align: center;">Cor 3 Lot 14 S 1 1982</p> <p>from which</p> <p>A highway marker bears N. 85°43' E., 151.3 lks. dist., monumented with a brass tablet 2½ ins. diam., set in a 6 ins. diam. concrete cylinder, projecting 4 ins. above the ground, mkd. Arizona Highway Dept. STA 1025+29.69 Elev. 3527.30.</p>	

Dependent Resurvey of a Portion of First Standard
 Parallel South, S. Bdy. of T. 5 S., R. 30 E., Gila and
 Salt River Meridian, Arizona

CHAINS										
10.63	Intersect the center line of State Highway No. 666, not monumented.									
14.19	Point for the W 1/16 sec. cor. of sec. 1 only.									
	Set an aluminum post, 30 ins. long, $\frac{3}{4}$ ins. diam., 24 ins. in the ground, with cap mkd.									
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td>W 1/16</td><td>S1</td></tr> <tr><td>T6S</td><td>R30E</td></tr> <tr><td colspan="2" style="text-align: center;">1982</td></tr> </table>	W 1/16	S1	T6S	R30E	1982				
W 1/16	S1									
T6S	R30E									
1982										
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, S. of the cor.									
	Cor. is located 59 lks. S. of an E and W fence line.									
14.583	Point for cor. no. 1 of lot 19, sec. 1, at intersection with the westerly 200 ft. right-of-way of State Highway No. 666.									
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.									
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td>Cor 1</td><td></td></tr> <tr><td>Lot 19</td><td></td></tr> <tr><td>S 1</td><td></td></tr> <tr><td colspan="2" style="text-align: center;">1982</td></tr> </table>	Cor 1		Lot 19		S 1		1982		
Cor 1										
Lot 19										
S 1										
1982										
	Cor. is located 61 lks. S. of an E and W fence line.									
27.885	Point for cor. no. 2, of lot 19, sec. 1.									
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.									
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td>Cor 2</td><td></td></tr> <tr><td>Lot 19</td><td></td></tr> <tr><td>S 1</td><td></td></tr> <tr><td colspan="2" style="text-align: center;">1982</td></tr> </table>	Cor 2		Lot 19		S 1		1982		
Cor 2										
Lot 19										
S 1										
1982										
34.19	Point for the closing cor. of secs. 1 and 2, T. 6 S., R. 30 E., hereinafter described.									
39.96	The standard cor. of secs. 34 and 35, monumented with an iron post, $2\frac{1}{2}$ ins. diam., projecting 28 ins. above the ground, in a mound of stone, $4\frac{1}{2}$ ft. base, to top, with brass cap mkd.									
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td>S C</td><td></td></tr> <tr><td>T5S</td><td>R30E</td></tr> <tr><td>S34</td><td>S35</td></tr> <tr><td colspan="2" style="text-align: center;">1968</td></tr> </table>	S C		T5S	R30E	S34	S35	1968		
S C										
T5S	R30E									
S34	S35									
1968										

Dependent Resurvey of a Portion of the East Bdy.
T. 6 S., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS

(Restoring the 1968 Resurvey by Louis D. Gilbert)

From the 1/4 sec. cor. of secs. 1 and 6, monumented with an iron post, 2½ ins. diam., projecting 7 ins. above the ground, with brass cap mkd.

T6S
R30E R31E
1/4
S1 | S6
1968

Cor. is witnessed with a mound of stone, 2½ ft. base, 1 ft. high, W. of the cor.

N. 1°12' W., bet. secs. 1 and 6.

Over rolling land, through medium creosote.

19.82 Point for the N 1/16 sec. cor. of secs. 1 and 6, set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.

T6S
R30E R31E
N 1/16
S1 | S6
1982

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.

39.03 The closing cor. of secs. 1 and 6, Tps. 6 S., Rs. 30 and 31 E., on the First Standard Parallel South, monumented with an iron post, 2½ ins. diam., projecting 16 ins. above the ground, in a mound of stone, 3½ ft. base, to top, with brass cap mkd.

T5S R30E
S36
S1 | S6
C C
R30E R31E
T6S
1968

Cor. is located 16 lks. S. of an E and W fence line.

Dependent Resurvey of a Portion of Subdivisional Lines
T. 6 S. R. 30 E., Gila and Salt River Meridian, Arizona

(Restoring the 1968 Resurvey by Louis D. Gilbert)

From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of Tp., monumented with an iron post, 2½ ins. diam., projecting 12 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

Dependent Resurvey of a Portion of Subdivisional Lines
T. 6 S., R. 30 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>35.49</p> <p>43.75</p>	<p style="text-align: center;">T6S R30E R31E $\frac{S1}{S12} \frac{S6}{S7}$ 1968</p> <p>N. 89°33' W., bet. secs. 1 and 12.</p> <p>Over gently rolling land, through scattered mesquite and creosote.</p> <p>The 1/4 sec. cor. of secs. 1 and 12, monumented with a lava stone, 14 x 8 x 6 ins., projecting 8 ins. above the ground, mkd. 1/4 on N. face and a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <p>At the cor. point.</p> <p>Set an aluminum post, 30 ins. long, $\frac{3}{4}$ ins. diam., 8 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T6S R30E $\frac{1}{4} \frac{S1}{S12}$ 1982</p> <p>Deposit the original cor. in the mound of stone around the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89°32' W., beginning new measurement.</p> <p>The cor. of secs. 1, 2, 11 and 12, monumented with an iron post, 2½ ins. diam., projecting 24 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R30E $\frac{S2}{S11} \frac{S1}{S12}$ 1968</p> <hr/> <p style="text-align: center;">Corrective Dependent Resurvey of a Portion of Subdivisional Lines, T. 6 S., R. 30 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>Correction of a portion of the resurvey executed by Louis D. Gilbert in 1968, reestablishing the survey executed by Daniel Drummond in 1891.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12, heretofore described.</p> <p>N. 5°01' E., bet. secs. 1 and 2.</p> <p>Over rolling land, through scattered mesquite and creosote.</p>	
---	---	--

Corrective Dependent Resurvey of a Portion of
Subdivisional Lines, T. 6 S., R. 30 E., Gila and Salt
River Meridian, Arizona

CHAINS		
6.28	Point for the 1891 meander cor. of secs. 1 and 2, on the left bank of the Gila River, at proportionate dist., there is no remaining evidence of the original cor., not monumented.	
17.13	Point for the 1891 meander cor. of secs. 1 and 2, on the right bank of the Gila River, at proportionate dist., there is no remaining evidence of the original cor., not monumented.	
40.54	<p>The 1/4 sec. cor. of secs. 1 and 2, monumented with a malipase stone 14 x 11 x 7 ins., loosely set at a scattered mound of stone, mkd. 1/4 on one side. From this point, an iron post, 2½ ins. diam., projecting 14 ins. above the ground, in a mound of stone, 2½ ft. base, to top, bears S. 82°58' W., 3.485 chs. dist., with brass cap mkd.</p> <p style="text-align: center;">T6S R30E 1/4 S2 S1 1968</p> <p>I removed the iron post from its found position and at the original cor. point.</p> <p>Reset the iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground.</p> <p>Removed the 1968 date from the cap and redated it to read 1982.</p> <p>Deposit the original stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <p>Cor. is located at east edge of a wash, 5 lks. wide, 2½ ft. deep, drains southerly.</p> <p style="text-align: center;">_____</p> <p>N. 4°55' W., beginning new measurement.</p>	
9.93	<p>Point for the S-N 1/64 sec. cor. of secs. 1 and 2.</p> <p>Set an aluminum post, 30 ins. long, ¾ ins. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S-N 1/64 S2 S1 1982</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.</p>	
19.86	<p>Point for the N 1/16 sec. cor. of secs. 1 and 2.</p> <p>Set an aluminum post, 30 ins. long, ¾ ins. diam., 2 ins. in the ground, in a mound of stone, 4 ft. base, to top, with cap mkd.</p>	

Corrective Dependent Resurvey of a Portion of
Subdivisional Lines, T. 6 S., R. 30 E., Gila and Salt
River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">T6S R30E N 1/16 S2 S1 1982</p>	
	<p>Cor. is located in the E. edge of a draw, drains SW.</p>	
	<p>From this point a local cor. bears N. 82°10' W., 1.60 chs. dist., monumented with a reinforcement rod, ½ in. diam., projecting 12 ins. above the ground, with tag attached and mkd. LS 7498.</p>	
29.79	<p>Point for the N-N 1/64 sec. cor. of secs. 1 and 2.</p>	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">N-N 1/64 S2 S1 1982</p>	
	<p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.</p>	
38.97	<p>Point for the closing cor. of secs. 1 and 2, at inter-</p>	
	<p>section with the First Standard Parallel South. From this point an iron post, 2½ ins. diam., projecting 3 ins. above the ground, bears N. 36°28' W., 2.9 lks. dist., with brass cap mkd.</p>	
	<p style="text-align: center;">T5S S35 S2 S1 C' C T6S R30E 1968</p>	
	<p>I removed the iron post from its found position and at the intersection point.</p>	
	<p>Reset the iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with the brass cap remarked.</p>	
	<p style="text-align: center;">T5S R30E S35 S2 S1 T6S R30E CC 1982</p>	
	<p>Cor. is located on the NW face of a steep canyon wall.</p>	
	<p>From this point the original closing cor. of secs. 1 and 2, bears N. 4°55' W., 17 lks. dist., monumented with a sandstone, 8 x 6 x 6 ins. above the ground, mkd. A M CC on S. face and 5 notches on the W.</p>	
	<p>From this same point the standard cor. of secs. 34 and 35, T. 5 S., R. 30 E., bears N. 89°51' W., 5.77 chs. dist., heretofore described.</p>	

Subdivision of Sec. 1, T. 6 S., R. 30 E.,
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>From the 1/4 sec. cor. of 1 and 12.</p> <p>N. 2°34'30" W., on the N and S center line of sec. 1.</p> <p>Over rolling land, through medium creosote and scattered mesquite.</p>	
39.88	<p>Point for the C 1/4 sec. cor. of sec. 1, at intersection with the E and W center line.</p> <p>Set an aluminum post, 30 ins. long, $\frac{3}{4}$ ins. diam., 25 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T6S R30E C1/4 S1 1982</p>	
	<p>Raise a mound of stone, 2 ft. base, 1 ft. high, W. of the cor.</p> <p>Cor. is located 10 lks. S. of a fence line, bears S. 70° E., and N. 70° W.</p>	
59.70	<p>Point for the C-N 1/16 sec. cor. of sec. 1, identical with cor. 5, lot 14.</p> <p>Set an aluminum post, 30 ins. long, $\frac{3}{4}$ ins. diam., 22 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T6S R30E C N1/16 S1 C 1982</p>	
78.82	<p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.</p> <p>The 1/4 sec. cor. of sec. 1 only, heretofore described.</p>	
19.58	<p>From the 1/4 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp., heretofore described.</p> <p>N. 89°43'30" W., on the E and W center line of sec. 1.</p> <p>Over rolling land, through scattered creosote and mesquite.</p> <p>Point for the C-E 1/16 sec. cor. of sec. 1.</p> <p>Set an aluminum post, 28 ins. long, 1 ins. diam., 22 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T6S R30E E 1/16 C ——— C S1 1982</p>	



Subdivision of Sec. 1, T. 6 S., R 30 E.,
Gila and Salt River Meridian, Arizona

CHAINS	<p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor.</p> <p>From this point a local cor. bears S. 1°04' E., 10.7 lks. dist., monumented with an iron rod, ¾ in. diam., flush with ground in a collar of stone. The position of this cor. is unacceptable due to the corrective dependent resurvey bet. secs. 1 and 2.</p>
39.16	The C 1/4 sec. cor. of sec. 1.
58.36	<p>Point for the C-W 1/16 sec. cor. of sec. 1.</p> <p>Set an aluminum post, 30 ins. long, ¾ ins. diam., 18 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T6S R30E W 1/16 C———C S 1 1982</p> </div> <p>From this point a local cor. bears S. 79°31' W., 1.76 chs. dist., monumented with an iron rod, 1 in. diam., projecting 3 ins. above the ground.</p>
67.96	Point for the C-W-W 1/64 sec. cor. of sec. 1, not monumented.
71.255	Intersect the center line of State Highway No. 666.
77.56	The 1/4 sec. cor. of secs. 1 and 2.
19.82	<p>From the C-E 1/16 sec. cor. of sec. 1.</p> <p>N. 1°53' W., on the N and S center line of the NE 1/4 of sec 1.</p> <p>Over rolling land, through medium creosote.</p> <p>Point for the NE 1/16 sec. cor. of sec. 1, at intersection with the E and W center line of the NE 1/4.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T6S R30E NE 1/16 S1 1982</p> </div> <p>Raise a mound of stone, 2½ ft. high, W. of the cor.</p> <p>Cor. is located on the W. bank of a wash, 1 ch. wide, 3 ft. deep, drains SW.</p>
38.99	The E 1/16 sec. cor of sec. 1 only.
	<p>From the N 1/16 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp.</p> <p>N. 89°46' W., on the E and W center line of the NE 1/4 of sec. 1.</p> <p>Over rolling land, through medium creosote.</p>

Subdivision of Sec. 1, T. 6 S., R 30 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
19.82	The NE 1/16 sec. cor. of sec. 1.
29.73	<p>Point for the C-W-NE 1/64 sec. cor. of sec. 1, identical with cor. 6, lot 14.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S1 C-W-NE 1/64 1982</p> <p>Cor. is located on the E. side of a steep slope.</p>
39.64	<p>The C-N 1/16 sec. cor. of sec. 1.</p> <hr/> <p>From the C-W-NE 1/64 sec. cor. of sec. 1, identical with cor. 6, lot 14.</p> <p>N. 2°14' W., on the N and S center line of the NW 1/4 NE 1/4 of sec. 1, identical with line 6-1, lot 14.</p>
19.15	<p>The W-E 1/64 sec. cor. of sec. 1 only, identical with cor. 1, lot 14.</p> <hr/> <p>From the C-W 1/16 sec. cor. of sec. 1.</p> <p>N. 3°45' W., on the N and S center line of the NW 1/4 of sec. 1.</p> <p>Over rolling land, through scattered mesquite and creosote.</p>
9.915	<p>Point for the C-S-NW 1/64 sec. cor. of sec. 1.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 6 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S1 C-S-NW 1/64 1982</p> <p>Cor. is located in the E. edge of a wash, 20 lks. wide, 3 ft. deep, drains SW.</p>
19.83	<p>Point for the NW 1/16 sec. cor. of sec. 1, at intersection with the E and W center line of NW 1/4.</p> <p>Set an aluminum post, 30 ins. long, ¾ in. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T6S R30E NW 1/16 S1 1982</p> <p>Cor. is located 48 lks. W. of center of a wash, 70 lks. wide, drains S. 55° W.</p>
29.75	<p>Point for the C-N-NW 1/64 sec. cor of sec. 1.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with cap mkd.</p>

Subdivision of Sec. 1, T. 6 S., R 30 E.,
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>S1 C-N-NW 1/64 1982</p>	
	<p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.</p>	
34.779	<p>Intersect the center line of State Highway No. 666, not monumented.</p>	
38.94	<p>The W 1/16 sec. cor. of sec. 1 only.</p>	
	<hr/> <p>From the C-N 1/16 sec. cor. of sec. 1, identical with cor 5, lot 14.</p> <p>N. 89°45' W., on the E and W center line of the NW 1/4, sec. 1, identical with line 5-4, lot 14.</p> <p>Over rolling land, through medium creosote.</p>	
3.19	<p>Point for cor. no. 4, of lot 14, at intersection with the center line of State Highway No. 75.</p> <p>Set a railroad spike, flush with surface of road, with top mkd.</p> <div style="text-align: center;">  <p>Cor 4 Lot 14 S1</p> </div> <p>1982</p> <p>from which</p> <p>An aluminum post, 28 ins. long, 1 in. diam. set 22 ins. in the ground for a reference monument, bears N. 55°03' E., 71.8 lks. dist., with cap mkd. T6S R30E S1 RM 47.4 ft. Cor 4 Lot 14 1982 and an arrow pointing to the cor.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, E. of the cor.</p> <p>An aluminum post, 28 ins. long, 1 in. diam., set 20 ins. in the ground, in a mound of stone, 2 ft. base, to top, for a reference monument, bears S. 55°03' W., 67 lks. dist., with cap mkd. T6S R30E S1 RM 44.2 ft. 1982 and an arrow pointing to the cor.</p>	
19.61	<p>The NW 1/16 sec. cor. of sec. 1.</p>	
27.29	<p>Intersect the center line of State Highway No. 666, not monumented.</p>	
28.84	<p>Point for cor. 1 of lot 22, sec. 1, at the intersection with the westerly 100 ft. right-of-way of State Highway No. 666,</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p> <div style="text-align: center;">  <p>Cor 1 Lot 22 S1</p> </div> <p>1982</p>	

Subdivision of Sec. 1, T. 6 S., R 30 E.,
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.</p> <p>Cor. is located in a 100 ft. right-of-way fence.</p>	
30.395	<p>Point for cor. 4 of lot 18, sec. 1, at intersection with the westerly 200 ft. right-of-way of State Highway No. 666</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>Cor 4 / Lot 18 / S1 / ----- 1982</p> </div>	
34.325	<p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.</p> <p>Point for the C-W-W-NW 1/256 sec. cor. of sec. 1, identical with cor. 3, lot 18 and cor. 2, lot 22.</p> <p>Set an aluminum post, 30 ins. long, ¾ in. diam., 24 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>S1 C-W-W-NW 1/256 1982</p> </div>	
39.23	<p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor.</p> <p>The N 1/16 sec. cor. of secs. 1 and 2.</p> <hr/> <p>From the C-S-NW 1/64 sec. cor. of sec. 1.</p> <p>N. 89°44' W., on the E and W center line of the SW 1/4 NW 1/4 of sec. 1.</p>	
10.305	<p>Intersect the center line of State Highway No. 666, not monumented.</p>	
11.85	<p>Point for cor. 4, lot 22, sec. 1, at intersection with the westerly 100 ft. right-of-way of State Highway No. 666.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <div style="text-align: center;"> <p>Cor 4 / Lot 22 / S1 / ----- 1982</p> </div> <p>Cor. is located in a 100 ft. right-of-way fence.</p>	
14.555	<p>Point for the C-W-SW-NW 1/256 sec. cor. of sec. 1, identical with cor. 3, lot 22</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 19 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p>	

Subdivision of Sec. 1, T. 6 S., R. 30 E.,
Gila and Salt River Meridian, ARIZONA

CHAINS		
	<p style="text-align: center;">S1 C-W-SW-NW 1/256 1982</p>	
19.41	<p>The S-N 1/64 sec. cor. of secs. 1 and 2.</p>	
	<hr/> <p>From the C-W-SW-NW 1/256 sec. cor. of sec. 1, identical with cor. 3, lot 22.</p> <p>N. 4°37'30" W., on the N and S center line of the NW 1/4 SW 1/4 NW 1/4 of sec. 1, identical with line 3-2, lot 22.</p>	
9.925	<p>The C-W-W-NW 1/156 sec. cor. of sec. 1, identical with cor. 2, lot 22, and cor. 3, lot 18.</p>	
	<hr/> <p>From the C-N-NW 1/64 sec. cor. of sec. 1.</p> <p>N. 89°46' W., on the E and W center line of the NW 1/4 NW 1/4 of sec. 1.</p>	
3.36	<p>Intersect the center line of State Highway No. 666, not monumented.</p>	
6.735	<p>Point for cor. 1 of lot 18, identical with cor. 4 of lot 19, sec. 1, at intersection with the westerly 200 ft. right-of-way of State Highway No. 666.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p>	
	<div style="text-align: center;"> <p style="margin-left: 100px;">Cor 4 Lot 19 Cor 1 S1 Lot 18 1982</p> </div>	
13.70	<p>Point for cor. 3, lot 19, sec. 1.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p>	
	<div style="text-align: center;"> <p style="margin-left: 100px;">Cor 3 Lot 19 S1 1982</p> </div>	
14.856	<p>Point for the C-W-NW-NW 1/256 sec. cor. of sec. 1, identical with cor. 2, lot 18.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p>	
	<p style="text-align: center;">S1 C-W-NW-NW 1/256 1982</p>	

Subdivision of Sec. 1, T. 6 S., R. 30 E.,
Gila and Salt River Meridian, Arizona

<p>CHAINS 19.82</p>	<p>The N-N 1/64 sec. cor. of secs. 1 and 2.</p> <hr/> <p>From the C-W-W-NW 1/256 sec. cor. of sec. 1, identical with cor. 3, lot 18, and cor. 2, lot 22.</p> <p>N. 4°38' W., on the N and S center line of the SW 1/4 NW 1/4 NW 1/4 of sec. 1, identical with line 3-2, lot 18.</p>
<p>9.925</p>	<p>The C-W-NW-NW 1/256 sec. cor. of sec. 1, identical with cor. 2, lot 18.</p> <hr/> <p>Metes-and-Bounds Survey of Certain Small Lots in Section 1, T. 6 S., R. 30 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;"><u>Lot 14</u></p> <p>From cor. 1, lot 14, sec. 1, identical with the W-E 1/64 sec. cor. of sec. 1 only, heretofore described.</p> <p>N. 89°56' W., on line 1-2 of lot 14, identical with the N. bdy. of sec. 1.</p>
<p>10.02</p>	<p>The 1/4 sec. cor. of sec. 1 only, heretofore described.</p>
<p>15.83</p>	<p>Cor. 2, lot 14, identical with the standard 1/4 sec. cor. of sec. 35, T. 5 S., R. 30 E., heretofore described.</p> <hr/> <p>N. 89°51' W., beginning new measurement, on line 2-3 of lot 14, identical with the N. bdy of sec. 1.</p>
<p>4.13</p>	<p>Cor. 3 of lot 14, sec. 1, at intersection with the center line of State Highway No. 75, heretofore described.</p> <hr/> <p>Thence, on line 3-4 of lot 14 of sec 1, along a 3°00'00" circular curve to the left, having a radius of 28.937 chs., the chord of said arc bears S. 21°43'22" E., 20.567 chs. dist.</p> <p>Along the center line of State Highway No. 75.</p>
<p>21.027</p>	<p>Cor. 4 of lot 14, at intersection with the E and W center line of the NW 1/4, sec. 1, heretofore described.</p> <hr/> <p>S. 89°45' E., on line 4-5 of lot 14, identical with the E and W center line of NW 1/4, sec. 1.</p>
<p>3.19</p>	<p>Cor. 5 of lot 14, identical with the C-N 1/16 sec. cor. of sec. 1, heretofore described.</p> <hr/> <p>S. 89°46' E., on line 5-6 of lot 14, identical with the E and W center line of the NE 1/4, sec. 1.</p>
<p>9.91</p>	<p>Cor. 6 of lot 14, identical with the C-W-NE 1/64 sec. cor. of sec. 1, heretofore described.</p> <hr/> <p>N. 2°14' W., on line 6-1 of lot 14, identical with the N and S center line of the NW 1/4 NE 1/4, sec. 1.</p>

Metes-and-Bounds Survey of Certain Small Lots in Section 1,
T. 6 S., R 30 E., Gila and Salt River Meridian, Arizona

<p>19415</p> <hr/> <p>6.965</p> <p>8.13</p> <hr/> <p>9.925</p> <hr/> <p>3.93</p> <hr/> <p>.492</p>	<p>Cor. 1 of lot 14, identical with the W-E 1/64 sec. cor. of sec. 1 only, and place of beginning, heretofore described.</p> <hr/> <p style="text-align: center;"><u>Lot 18</u></p> <p>From cor. 1 of lot 18, identical with cor. 4 of lot 19, sec. 1, on the westerly 200 ft. right-of-way of State Highway No. 666, heretofore described.</p> <p>N. 89°46' W., on line 1-2 of lot 18, identical with line 4-3, lot 19, and with the E and W center line of the NW 1/4 NW 1/4, sec. 1.</p> <p>Cor. 3 of lot 19, sec. 1, heretofore described.</p> <p>Cor. 2 of lot 18, identical with the C-W-NW-NW 1/256 sec. cor. of sec. 1, heretofore described.</p> <hr/> <p>S. 4°38' E., on line 2-3 of lot 18, identical with the N and S center line of the SW 1/4 NW 1/4 NW 1/4 of sec. 1.</p> <p>Cor. 3 of lot 18, identical with cor. 2 of lot 22 and the C-W-W-NW 1/256 sec. cor. of sec 1., heretofore described.</p> <hr/> <p>S. 89°45' E., on line 3-4 of lot 18, identical with a portion of line 2-1, lot 22, and with the E and W center line of the NW 1/4. sec. 1.</p> <p>Cor. 4 of lot 18, sec. 1, at intersection with the westerly 200 ft. right-of-way of State Highway No. 666, heretofore described.</p> <hr/> <p>Thence, on line 4-5 of lot 18, sec. 1, along the arc of a spiral curve to the right; the chord of which bears N. 12°10'27" E., 49.2 lks. dist.</p> <p>Along the westerly 200 ft. right-of-way of State Highway No. 666.</p> <p>Point for cor. 5 of lot 18, at the point of spiral to curve, on the 200 ft. westerly right-of-way of State Highway No. 666.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <div style="text-align: center;"> <p>Cor 5 Lot 18 S1 1982</p> </div> <hr/> <p>Thence, on line 5-1 of lot 18, sec. 1, along a 1°52' 10" circular curve to the right, having a radius of 46.436 chs., the chord of said arc bears N. 19°17'02" E., 9.956 chs. dist.</p> <p>Along the westerly 200 ft. right-of-way of State Highway No. 666.</p>	
--	--	--

Metes-and-Bounds Survey of Certain Small Lots in Section 1,
T. 6 S., R. 30 E., Gila and Salt River Mer., Arizona

CHAINS	
9.976	<p>Cor. 1 of lot 18, identical with cor. 4 of lot 19, and place of beginning, heretofore described.</p> <hr/> <p style="text-align: center;"><u>Lot 19</u></p> <p>From cor. 1 of lot 19, sec. 1, on the westerly 200 ft. right-of-way of State Highway No. 666, heretofore described.</p> <p>N. 89°51' W., on line 1-2 of lot 19, identical with the N. bdy. of sec. 1.</p>
13.302	<p>Cor. 2 of lot 19, sec. 1, heretofore described.</p> <hr/> <p>S. 3°45' E., on line 2-3 of lot 19, sec. 1.</p>
9.17	<p>Cor. 3 of lot 19, sec. 1, heretofore described.</p> <hr/> <p>S. 89°46' E., on line 3-4 of lot 19, identical with line 2-1, lot 18, and with the E and W center line of the NW 1/4 NW 1/4, sec. 1.</p>
6.965	<p>Cor. 4 of lot 19, identical with cor. 1 of lot 18, sec. 1, at intersection with the westerly 200 ft. right-of-way of State Highway No. 666, heretofore described.</p> <hr/> <p>Thence, on line 4-1 of lot 19, sec. 1, along a 1°52'10" circular curve to the right, having a radius of 46.436 chs., the chord of said arc bears N. 32°06'47" E., 10.795 chs. dist.</p> <p>Along the westerly 200 ft. right-of-way of State Highway No. 666.</p>
10.82	<p>Cor. 1 of lot 19, sec. 1, and place of beginning, heretofore described.</p> <hr/> <p style="text-align: center;"><u>Lot 22</u></p> <p>From cor. 1 of lot 22, sec. 1, on the westerly 100 ft. right-of-way of State Highway No. 666, heretofore described.</p> <p>N. 89°45' W., on line 1-2 of lot 22, identical with the E and W center line of the NW 1/4, sec. 1.</p>
1.555	<p>Cor. 4 of lot 18, sec. 1, heretofore described.</p> <p>Continue along line 1-2, lot 22, identical with line 4-5, lot 18.</p>
5.485	<p>Cor. 2 of lot 22, identical with cor. 3, lot 18, and with the C-W-W-NW 1/256 sec. cor. of sec. 1, heretofore described.</p> <hr/> <p>S. 4°37'30" E., on line 2-3 of lot 22, sec. 1.</p>

Metes-and-Bounds Survey of Certain Small Lots in Section 1,
T. 6 S., R. 30. E., Gila and Salt River Meridian, Arizona

<p>CHAINS 9.925</p>	<p>Cor. 3 of lot 22, identical with the C-W-SW-NW 1/256 sec. cor. of sec. 1, heretofore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°44' E., on line 3-4 of lot 22, identical with the E and W center line of the SW 1/4 NW 1/4, sec. 1.</p>
<p>2.705</p>	<p>Cor. 4 of lot 22, sec. 1, at intersection with the westerly 100 ft. right-of-way of State Highway No. 666, heretofore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 11°08' E., on line 4-5 of lot 22, sec. 1.</p> <p>Along the westerly 100 ft. right-of-way of State Highway No. 666.</p>
<p>7.14</p>	<p>Point for cor. 5 of lot 22, sec. 1, at the point of curve to spiral, on the 100 ft. westerly right-of-way of State Highway No. 666.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>Cor 5 / Lot 22 / S1 / 1982</p> </div> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.</p> <p>Cor. is located in the westerly 100 ft. right-of-way fence.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence, on line 5-1 of lot 22, sec. 1, along the arc of a spiral curve to the right; the chord of which bears N. 11°44'46" E., 2.938 chs. dist.</p> <p>Along the westerly 100 ft. right-of-way of State Highway No. 666.</p>
<p>2.938</p>	<p>Cor. 1 of lot 22, and place of beginning, heretofore described.</p> <hr style="width: 100%; margin: 10px 0;"/> <p style="text-align: center;">General Description</p> <p>The land encompassed in this survey is located about 10 miles SSE of Clifton, Arizona. The average elevation is about 3500 ft. above sea level. The Gila River drains westerly through the lower portion of sec. 1.</p> <p>Access is by way of Arizona State Highways 75 and 666.</p> <p>The vegetation consists of creosote, mesquite, sage brush and cacti.</p> <hr style="width: 100%; margin: 10px 0;"/>

CERTIFICATE OF SURVEY

(I) ~~XXX~~, Paul L. Reeves, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 4th day of January, 1982, ~~(XXXXXX)~~ and Supplemental Special Instructions dated April 1, 1982, (I) have dependently resurveyed a portion of the First Standard Parallel South, south boundary of Township 5 South, Range 30 East, a portion of the east boundary and subdivisional lines, performed a corrective dependent resurvey of the section line between sections 1 and 2, and surveyed the subdivision and a metes-and-bounds survey of certain small lots in section 1 of Township 6 South, Range 30 East

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(XXX)~~ and under (my) ~~(XXX)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

8/24/82 (Date) Paul L. Reeves (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
~~XXXXXXXXXXXXXXXXXXXX~~
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the First Standard Parallel South, south boundary of Township 5 South, Range 30 East, a portion of the east boundary and subdivisional lines, a corrective dependent resurvey between sections 1 and 2, the survey of the subdivision and a metes-and-bounds survey of certain small lots in section 1 of Township 6 South, Range 30 East, Gila and Salt River Meridian, Arizona

executed by Paul L. Reeves, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

8-24-82 (Date) James P. Kelley (Chief, Cadastral Survey Examination and Approval Staff) Chief Cadastral Surveyor of Arizona

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.~~

~~(Date) (Chief, Cadastral Survey Examination and Approval Staff)~~