



UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE _____

DEPENDENT RESURVEY OF A PORTION _____

OF THE SUBDIVISIONAL LINES _____

AND THE _____

SURVEY OF SUBDIVISIONS IN SECTIONS _____

10, 11, 14, 15, 22, 23, 26 AND 27, _____

TOWNSHIP 7 NORTH, RANGE 10 EAST _____

Of the _____ GILA AND SALT RIVER _____ Meridian,

In the State of _____ ARIZONA _____

EXECUTED BY

HARRY K. SMITH _____ CADASTRAL SURVEYOR

JOHN P. BENNETT III _____ CADASTRAL SURVEYOR

Under special instructions dated MARCH 5, 1980, approved MARCH 13, 1980,

_____, which provided for the surveys included under ~~XXXX Survey~~/Group
Number 618, and assignment instructions dated APRIL 2, 1980.

Survey commenced APRIL 7, 1980

Survey completed JUNE 5, 1980

INDEX DIAGRAM

Township 7 NORTH, Range 10 EAST,

6	5	4	3	2	1
			21	13	
7	8	9	21 10	12 11	4 12
			19	11	
18	17	16	19 15	10 14	3 13
			18	9	
19	20	21	17 22	8 23	2 24
			16	7	
30	29	28	15 27	6 26	2 25
			14	5	
31	32	33	34	35	36

SUBDIVISION OF SECTIONS

- Sec. 10.....p. 22
- Sec. 11.....p. 26
- Sec. 14.....p. 29
- Sec. 15.....p. 31
- Sec. 22.....p. 34
- Sec. 23.....p. 36
- Sec. 26.....p. 39
- Sec. 27.....p. 41



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

9600 (942)
Group No. 618, Arizona

ARIZONA STATE OFFICE
2400 VALLEY BANK CENTER
PHOENIX, ARIZONA 85073

April 8, 1983

Memorandum

To : Christine M. Pitcairn, Legal Clerk

From : Chief Cadastral Surveyor of Arizona

Subject : Corrections to Original Field Notes, Pages 34 and 39, Book 5176, T. 7 N., R. 10 E., Gila and Salt River Meridian, Arizona, Group No. 618, Approved November 16, 1982

On March 30, 1983, Paul L. Reeves, Supervisory Cadastral Surveyor, performed a field investigation involving the witness point on the E and W center line of the NW1/4 of section 15, of the subject township. The brass cap was marked for section 23 and was corrected to read S 15 and the date 1983, was added. The field notes on page 34, book No. 5176, mistakenly refer to section 23.

On page 39 of the same field notes all ties to reference monuments at the SW 1/16 section cor. of section 23 should refer to feet.

You are hereby directed to make pen and ink additions and corrections as indicated above and shown on enclosures 1 and 2, and reference this memorandum in the margin of both pages. Provide the records section in the Public Room on the 24th floor with a zerox copy of each of the pages affected, to replace their existing record.

Indicate that the changes have been made by signing below.

James P. Kelley

James P. Kelley

Enclosures

4-8-83
Christine M. Pitcairn

Dependent Resurvey of T. 7 N., R. 10 E.,
Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the subdivisional lines and the survey of subdivisions in sections 10, 11, 14, 15, 22, 23, 26 and 27 of Township 7 North, Range 10 East, Gila and Salt River Meridian, Arizona.

A portion of the subdivisional lines was surveyed by Albert T. Colton, U.S. Deputy Surveyor, in 1899 with the remainder of the subdivisional lines still being unsurveyed. Certain corners were remonumented by Louis D. Gilbert, in 1970.

The resurvey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 618, Arizona, dated March 5, 1980.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of lines were determined from the United States Coast and Geodetic Survey triangulation station "REED" and refer to the true meridian. Distances were measured electronically with Zeiss SM-4 and Hewlett Packard 3820 instruments.

The geographic position of the corner of sections 25, 26, 35 and 36, determined by a tie to triangulation station "REED" is as follows:

Latitude 33°54'49.380" N. Longitude 111°17'41.439" W.

The mean magnetic declination is 14°00' E.

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

(Restoring the survey executed by Albert T. Colton
in 1899)

Beginning at the cor. of secs. 25, 26, 35 and 36, monumented with a granite stone, 11 x 8 x 5 ins., set in a mound of stone, 3½ ft. base, 1 ft. high, mkd. with 1 notch on the E and S edges.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with aluminum cap mkd.

T7N R10E
S26 | S25
S35 | S36
1980

Deposit the mkd. stone alongside the aluminum post.

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS		
	<p>Rebuild the mound of stone, 4 ft. base, 2½ ft. high, W of the cor.</p> <p>N. 0°04' W., bet. secs. 25 and 26.</p> <p>Over broken mesa land, through scattering undergrowth.</p> <p>40.30 The 1/4 sec. cor. of secs. 25 and 26, monumented with a granite stone, 12 x 12 x 8 ins., firmly set 9 ins. in the ground, mkd. 1/4 S on the W face, with a scattered mound of stone, W of the cor.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground and in a mound of stone, 2½ ft. base, to top, with aluminum cap mkd.</p> <p style="text-align: center;">T7N R10E 1/4 S26 S25 1980</p> <p>Deposit the mkd. stone alongside the aluminum post.</p>	
	<p>N. 0°05' W., beginning new measurement.</p> <p>40.27 The cor. of secs. 23, 24, 25 and 26, monumented with a granite stone, 10 x 8 x 7 ins., firmly set 7 ins. in the ground, mkd. with 1 groove on the E and 2 grooves on the S faces, with a scattered mound of stone, NE of the cor.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground and in a mound of stone, 2½ ft. base to top, with aluminum cap mkd.</p> <p style="text-align: center;">T7N R10E S23 S24 S26 S25 1980</p> <p>Deposit the mkd. stone alongside the aluminum post.</p>	
	<p>N. 0°16' W., bet. secs. 23 and 24.</p> <p>Over broken mesa and mountainous land, through scattering undergrowth.</p> <p>40.05 The 1/4 sec. cor. of secs. 23 and 24, monumented with a granite stone, 11 x 7 x 5 ins., firmly set 7 ins. in the ground, mkd. 1/4 S on the W face, with a mound of stone, 2½ ft. base, 1 ft. high, NE of the cor.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T7N R10E 1/4 S23 S24 1980</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS	
	<p>Deposit the mkd. stone alongside the aluminum post.</p> <p>Rebuild the mound of stone, 3 ft. base, 1 ft. high, W of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°02' W., beginning new measurement.</p>
19.895	<p>Point for the N 1/16 sec. cor. of secs. 23 and 24.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T7N R10E N 1/16 S23 S24 1980</p>
	<p>Raise a mound of stone, 3½ ft. base, 1½ ft. high, W of the cor.</p>
39.79	<p>The cor. of secs. 13, 14, 23 and 24, monumented with a granite boulder, 30 x 22 x 12 ins., projecting 3 ins. above ground, mkd. with an X on top, with 1 groove E of the X and 3 grooves S of the X.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. in the ground, to solid rock and in a mound of stone, 4 ft. base, to top, with aluminum cap mkd.</p> <p style="text-align: center;">T7N R10E S14 S13 S23 S24 1980</p> <p>from which</p> <p style="padding-left: 40px;">A granite boulder, 3 x 2½ x 2 ft. above ground, bears S. 87¾° E., 85 lks. dist., mkd. XBO on top.</p> <p style="padding-left: 40px;">A granite boulder, 2½ x 1½ x 1 ft. above ground, bears S. 46¾° W., 40 lks. dist., mkd. XBO on top.</p> <p>Deposit the mkd. boulder in the mound around the aluminum post.</p> <p>The cor. is about 1.50 chs. W of the top of the southern end of Kayler Butte.</p> <hr/> <p>N. 0°03' E., bet. secs. 13 and 14.</p> <p>Over rolling land, through medium undergrowth.</p>
2.30	The top of Kayler Butte.
12.90	Fence, bears E and W.
40.11	<p>The 1/4 sec. cor. of secs. 13 and 14, monumented with a granite stone, 11 x 11 x 8 ins., firmly set 8 ins. in the ground, mkd. 1/4 S on the W face, with a mound of stone, 2 ft. base, 1 ft. high, 10 ft. W of the cor.</p> <p>At the cor. point</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS		
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 8 ins. in the ground, to solid rock and in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.</p> <p style="text-align: center;">T7N R10E 1/4 S14 S13 1980</p>	
	<p>Deposit the mkd. stone alongside the aluminum post.</p> <hr style="width: 20%; margin: auto;"/>	
	<p>N. 0°11' E., beginning new measurement.</p>	
<p>39.00</p>	<p>Track road, bears S. 65° E. and N. 65° W.</p>	
<p>39.86</p>	<p>Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor. This point falls in a railed area.</p>	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with aluminum cap mkd.</p>	
	<p style="text-align: center;">T7N R10E S11 S12 S14 S13 1980</p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">The center shaft of a windmill, bears S. 60°22' E., 14.92 chs. dist.</p>	
	<p style="padding-left: 40px;">An earth stock pond, 2 chs. diam., bears S. 54° E., 16.00 chs. dist.</p>	
	<p style="padding-left: 40px;">A metal water tank, bears S. 31½° E., 6.10 chs. dist.</p>	
	<p>Raise a mound of stone, 4 ft. base, 3 ft. high, W of the cor.</p>	
	<p>From this point the 1/4 sec. cor. of secs. 12 and 13, bears S. 89°13' E., 40.235 chs. dist., monumented with a granite stone, 21 x 12 x 10 ins., firmly set 6 ins. in the ground, mkd. X on top and 1/4 S on the N face, with a mound of stone, 2½ ft. base, 1 ft. high, N of the cor.</p>	
	<p>At the cor. point</p>	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 6 ins. in the ground, to solid rock and in a mound of stone, with aluminum cap mkd.</p>	
	<p style="text-align: center;">T7N R10E 1 S12 4 S13 1980</p>	
	<p>Deposit the mkd. stone in the mound around the aluminum post.</p> <hr style="width: 50%; margin: auto;"/>	
	<p>N. 0°23' W., bet. secs. 11 and 12.</p>	
	<p>Over rolling land, through scattering undergrowth.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS		
32.40	Fence, bears E and W.	
34.65	Track road, bears N. 60° E. and S. 60° W.	
39.86	The 1/4 sec. cor. of secs. 11 and 12, monumented with a granite stone, 15 x 12 x 10 ins., firmly set 12 ins. in the ground, mkd. 1/4 S on the W face, with a scattered mound of stone, W of the cor.	
	At the cor. point	
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.	
	T7N R10E 1/4 S11 S12 1980	
	Deposit the mkd. stone alongside the iron post.	
	Rebuild the mound of stone, 3 ft. base, 2 ft. high, W of the cor.	
	<hr style="width: 20%; margin: auto;"/> N. 0°11' W., beginning new measurement.	
40.20	The cor. of secs. 1, 2, 11 and 12, monumented with a granite stone, 24 x 5 x 5 ins., firmly set 12 ins. in the ground, mkd. with 1 notch on the E and 5 notches on the S edges, with a mound of stone, 2 ft. base, 6 ins. high, W of the cor.	
	At the cor. point	
	Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with aluminum cap mkd.	
	T7N R10E S 2 S 1 S11 S12 1980	
	Deposit the mkd. stone alongside the aluminum post.	
	Rebuild the mound of stone, 3 ft. base, 1½ ft. high, W of the cor.	
	<hr style="width: 100%;"/> From the cor. of secs. 25, 26, 35 and 36.	
	S. 89°42' W., bet. secs. 26 and 35.	
	Over rolling broken land, through scattering to medium undergrowth.	
40.23	The 1/4 sec. cor. of secs. 26 and 35, monumented with a granite stone, 12 x 10 x 4 ins., firmly set 9 ins. in the ground, mkd. 1/4 S on the N face, with a mound of stone, 3 ft. base, 1 ft. high, N of the cor.	
	At the cor. point	
	Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with aluminum cap mkd.	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS		
	<p>T7N R10E $\frac{1}{4}$ S26 $\frac{1}{4}$ S35 1980</p>	
	<p>Deposit the mkd. stone alongside the aluminum post.</p> <p>Rebuild the mound of stone, 3½ ft. base, 2 ft. high, N of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°20' W., beginning new measurement.</p>	
2.70	Enter Tonto Creek bottom, edge bears N and S.	
21.40	Leave Tonto Creek bottom, edge bears N and S.	
40.36	The cor. of secs. 26, 27, 34 and 35, monumented with an iron post, 2½ ins. diam., set in a mound of stone, 4 ft. base, 6 ins. high, to top of brass cap which is mkd. as described in the official record of the 1970 remonumentation notes by Louis D. Gilbert, Cadastral Surveyor.	
	<hr/> <p>N. 0°11' W., bet. secs. 26 and 27.</p> <p>Over rolling land, through scattering undergrowth.</p>	
8.50	Fence, bears S. 30° E. and N. 30° W.	
30.92	Point selected for the witness 1/4 sec. cor. of secs. 26 and 27.	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>W C T7N R10E 1/4 ↑ S27 S26 1980</p> </div>	
	<p>Raise a mound of stone, 4 ft. base, 3 ft. high, W of the cor.</p>	
31.00	Descend into Tonto Creek bottom.	
33.20	Enter Tonto Creek bottom, edge bears S. 75° E. and N. 75° W.	
40.22	True point for the 1/4 sec. cor. of secs. 26 and 27 falls in Tonto Creek bottom where it is impractical to set a permanent monument.	
50.275	Point for the S-N 1/64 sec. cor. of secs. 26 and 27, falls in Tonto Creek bottom where it is impractical to set a permanent monument.	
60.00	Leave Tonto Creek bottom, edge bears N. 70° E. and S. 70° W.	
60.33	Point for the N 1/16 sec. cor. of secs. 26 and 27.	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T7N R10E N 1/16 S27 S26 1980</p> <p>Raise a mound of stone, 3½ ft. base, 1½ ft. high, W of the cor.</p>
80.44	<p>The cor. of secs. 22, 23, 26 and 27, monumented with an open end pipe, ¾ in. diam., buried 12 ins. under ground. This position is shown as the cor. on the Arizona State Highway Department's plats of Construction Project S-456-506 on Highway 188 and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set an aluminum post, 30 ins. long, ¾ in. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T7N R10E S22 S23 S27 S26 1980</p> <p>from which</p> <p style="padding-left: 40px;">An aluminum post, 30 ins. long, ¾ in. diam., set 18 ins. in the ground, for a reference monument, bears N. 80°38' E., 53.2 ft. dist., with aluminum cap mkd. T7N R10E S23 RM 53.2 FT. 1980 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An aluminum post, 30 ins. long, ¾ in. diam., set 20 ins. in the ground, for a reference monument, bears S. 33°06' E., 47.25 ft. dist., with aluminum cap mkd. T7N R10E S26 RM 47.25 FT. 1980 and an arrow pointing to the cor.</p> <p>Reset the open end pipe alongside the aluminum post.</p> <p>The cor. is near the E edge of the pavement of Arizona State Highway No. 188.</p>
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°25' W., bet. secs. 23 and 26.</p> <p>Over rolling land, through medium undergrowth.</p>
30.00	<p>Descend into Tonto Creek bottom.</p>
34.00	<p>Enter Tonto Creek bottom, edge bears NE and SW.</p>
40.36	<p>True point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the original cor. This point falls in Tonto Creek bottom where it is impractical to set a permanent monument.</p> <p>From this point the point selected for the witness 1/4 sec. cor. of secs. 23 and 26, bears S. 0°10'30" E., 7.00 chs. dist.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">W C T7N R10E $\frac{1}{4}$ ↑ $\frac{S23}{S26}$ 1980</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of the cor.</p> <p>60.54 Point for the W 1/16 sec. cor. of secs. 23 and 26, falls on high land in Tonto Creek bottom.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T7N R10E W 1/16 $\frac{S23}{S26}$ 1980</p> <p>From this point an open end pipe of unknown origin, 1 in. diam., buried 6 ins. under ground, bears S. 43° W., 36.2 lks. dist.</p> <p>80.50 Leave Tonto Creek bottom, edge bears NE and SW.</p> <p>80.72 The cor. of secs. 22, 23, 26 and 27.</p>	
	<p>N. 0°09' E., bet. secs. 22 and 23.</p> <p>Over rolling land, through scattering to medium undergrowth.</p> <p>.54 Arizona State Highway No. 188, asphalt surfaced, bears N. 25° E. and S. 25° W.</p> <p>20.05 The S 1/16 sec. cor. of secs. 22 and 23, monumented with an open end pipe of unknown origin, 1 in. diam., projecting 8 ins. above ground. This position is harmoniously related to identified original cors. and is accepted as the cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7N R10E S 1/16 S22 S23 1980</p> <p>Reset the open end pipe alongside the aluminum post.</p> <p>Set a steel fence post alongside the cor.</p> <p>From the cor. an aluminum cap, 3 ins. diam., set in a concrete base, flush with the ground, bears N. 3°04' E., 6.307 chs. dist., mkd. ADOT Highway Division 100' POC 490+85.83 EL 2508.95 1977.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°11' E., beginning new measurement.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS	
20.00	<p>The 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 2½ ins. diam., projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1970 remonumentation notes by Louis D. Gilbert, Cadastral Surveyor.</p> <p>The cor. is located at the SE edge of a bladed road which extends E and S.</p> <p>From this point an aluminum post, 30 ins. long, ¾ in. diam., set 18 ins. in the ground, for a reference monument, bears S. 17° E., 16.88 ft. dist., with aluminum cap mkd. T7N R10E 1/4 S23 RM 16.88 FT. 1980 and an arrow pointing to the cor.</p> <p>From this same point an aluminum post, 30 ins. long, ¾ in. diam., set 18 ins. in the ground, for a reference monument, bears N. 17° W., 42.3 ft. dist., with aluminum cap mkd. T7N R10E 1/4 S22 RM 42.3 FT. 1980 and an arrow pointing to the cor.</p> <p>Add the date 1980 on the brass cap set in 1970.</p> <hr/> <p>N. 0°09' E., beginning new measurement.</p>
10.40	<p>Edge of a high bluff, edge bears E and W; descend into Tonto Creek bottom.</p>
15.00	<p>Enter Tonto Creek bottom, edge bears SE and NW.</p>
20.11	<p>True point for the N 1/16 sec. cor. of secs. 22 and 23 falls in Tonto Creek bottom where it is impractical to set a permanent monument.</p> <p>From this point the point selected for the witness N 1/16 sec. cor. of secs. 22 and 23, bears S. 89°44' W., 3.70 chs. dist.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>W C T7N R10E N 1/16 S22 S23 → 1980</p> </div> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, W of the witness cor.</p>
40.22	<p>The cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2½ ins. diam., projecting 5 ins. above ground, with brass cap mkd. as described in the official record of the 1970 remonumentation notes by Louis D. Gilbert, Cadastral Surveyor.</p> <p>The cor. is located on the left bank of Tonto Creek, 25 ft. high, bears N and S.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°43' W., bet. secs. 14 and 23.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS		
	<p>Over rolling broken land, through scattering to medium undergrowth.</p>	
19.98	<p>Point for the E 1/16 sec. cor. of secs. 14 and 23.</p>	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with aluminum cap mkd.</p>	
	<p style="text-align: center;">T7N R10E E 1/16 $\frac{S14}{S23}$ 1980</p>	
	<p>Raise a mound of stone, 3 ft. base, 1 ft. high, N of the cor.</p>	
23.50	<p>Fence, bears NE and SW.</p>	
39.96	<p>The 1/4 sec. cor. of secs. 14 and 23, monumented with a granite stone, 15 x 12 x 6 ins., firmly set 12 ins. in the ground, mkd. 1/4 S on the N face, with a mound of stone, 2½ ft. base, 1½ ft. high, N of the cor.</p>	
	<p>At the cor. point</p>	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with aluminum cap mkd.</p>	
	<p style="text-align: center;">T7N R10E $\frac{1}{4} \frac{S14}{S23}$ 1980</p>	
	<p>Deposit the mkd. stone alongside the aluminum post.</p>	
	<p>Rebuild the mound of stone, 3½ ft. base, 1½ ft. high, N of the cor.</p>	
	<p>From this point Kayler Spring, bears N. 85°02' E., 12.90 chs. dist. Water flows from several holes in a boulder forming a stream of water which flows S. 60° W., down the bottom of a draw into Tonto Creek.</p>	
	<p style="text-align: center;">—————</p> <p>S. 89°44' W., beginning new measurement.</p>	
20.15	<p>Point for the W 1/16 sec. cor. of secs. 14 and 23.</p>	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with aluminum cap mkd.</p>	
	<p style="text-align: center;">T7N R10E W 1/16 $\frac{S14}{S23}$ 1980</p>	
	<p>Raise a mound of stone, 3 ft. base, 1 ft. high, N of the cor.</p>	
40.30	<p>The cor. of secs. 14, 15, 22 and 23.</p>	
	<p>N. 0°02' E., bet. secs. 14 and 15.</p>	
	<p>Over rolling land, through scattering to medium undergrowth.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS		
10.60	Power line, bears S. 80° E. and N. 80° W.	
11.50	Enter Tonto Creek bottom, edge bears N. 65° E. and S. 65° W.	
20.08	Point for the S 1/16 sec. cor. of secs. 14 and 15, falls in Tonto Creek bottom where it is impractical to set a permanent monument.	
	From this point an aluminum post, 28 ins. long, 1 in. diam., set 20 ins. in the ground, for a reference monument, bears N. 55°50' E., 171.8 ft. dist., with aluminum cap mkd. T7N R10E S 1/16 S14 RM 171.8 FT. 1980 and an arrow pointing to the cor.	
	From this same point an aluminum post, 28 ins. long, 1 in. diam., set 20 ins. in the ground, for a reference monument, bears S. 38°57' E., 232.39 ft. dist., with aluminum cap mkd. T7N R10E S 1/16 S14 RM 232.39 FT. 1980 and an arrow pointing to the cor.	
23.40	Leave Tonto Creek bottom, edge bears SE and NW.	
35.30	Fence, bears N. 55° E. and S. 55° W.	
40.16	Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground and in a mound of stone, 3 ft. base, to top, with brass cap mkd.	
	T7N R10E 1/4 S15 S14 1980	
	from which A granite boulder, 3 x 3 x 2 ft. above ground, bears N. 72° E., 46.3 lks. dist., mkd. XBO on top. A granite boulder, 3 x 2 x 1½ ft. above ground, bears S. 40° E., 64.4 lks. dist., mkd. XBO on top. The cor. is on a W slope, about 50 lks. S of a ravine, drains SW.	
80.32	The cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2½ ins. diam., set in a mound of stone, 4 ft. base, 1 ft. high, to top, with brass cap mkd. as described in the official record of the 1970 remonumentation notes by Louis D. Gilbert, Cadastral Surveyor.	
	The cor. is 155 lks. E of a N-S fence.	
	From the cor. of secs. 11, 12, 13 and 14.	
	West, bet. secs. 11 and 14.	
	Over gently rolling land, through scattering undergrowth.	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS	
40.18	<p>Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p>T7N R10E 1 S11 4 S14 1980</p>
	<p>Raise a mound of stone, 3 ft. base, 1½ ft. high, N of the cor.</p>
60.27	<p>Point for the W 1/16 sec. cor. of secs. 11 and 14.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p>T7N R10E W 1/16 S11 S14 1980</p>
	<p>Raise a mound of stone, 3 ft. base, 1½ ft. high, N of the cor.</p>
66.90	<p>Track road, bears S. 5° E. and N. 5° W.</p>
69.30	<p>Power line, bears N. 5° E. and S. 5° W.</p>
80.36	<p>The cor. of secs. 10, 11, 14 and 15.</p>
	<p>N. 0°15' W., bet. secs. 10 and 11.</p>
	<p>Over rolling land, through medium undergrowth.</p>
11.70	<p>Fence bears N. 25° E. and S. 25° W.; enter open pasture, bears N. 25° E. and S. 25° W.</p>
19.96	<p>Point for the S 1/16 sec. cor. of secs. 10 and 11.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p>
	<p>T7N R10E S 1/16 S10 S11 1980</p>
	<p>Cor. is 2 lks. N of an E-W fence.</p>
39.92	<p>Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with aluminum cap mkd.</p>
	<p>T7N R10E 1/4 S10 S11 1980</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS	
	Cor. is located in open pasture.
59.88	Point for the N 1/16 sec. cor. of secs. 10 and 11.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T7N R10E N 1/16 S10 S11 1980</p>
	Set a steel fence post, 5 ft. long, 2 ft. in the ground, W of the cor.
	From this point an irrigation well, 16 ins. diam., bears N. 36°36' E., 4.81 chs. dist.
63.70	Power line, bears E and W; enter medium to dense undergrowth, bears E and W.
79.10	Track road, bears S. 50° E. and N. 50° W.
79.84	The cor. of secs. 2, 3, 10 and 11, monumented with a scattering mound of stone and a steel fence post set alongside. This position is shown as being the cor. on an application for right-of-way plat by the Arizona Public Service Company, dated 9-04-69, is related to identified original cors. and is accepted as the best available evidence of the original cor. position.
	At the center of the mound of stone.
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T7N R10E S 3 S 2 S10 S11 1980</p>
	Raise a mound of stone, 3½ ft. base, 2 ft. high, W of the cor.
	From this cor. U.S.C.&G.S. triangulation station "REED 1946," bears N. 36°02'13" E., 66.597 chs. dist., a brass tablet, 3 ins. diam., seated in a concrete form, 12 ins. square, projecting 12 ins. above ground. The geographic position as published by U.S.C.&G.S. is as follows:
	<p style="text-align: center;">Latitude 33°58'53.807" N. Longitude 111°18'15.216" W.</p>
	From this triangulation station, the U.S.C.&G.S. azimuth mark, bears S. 46°48'02.7" W., 83.471 chs. dist., a brass tablet, 3 ins. diam., seated in a concrete form, 12 ins. square, projecting 12 ins. above ground with the tablet mkd. N 20 2544.841 FT. 1933.
	From the cor. of secs. 1, 2, 11 and 12.
	N. 89°59' W., bet. secs. 2 and 11.
	Over rolling land, through scattering undergrowth.
11.60	Fence, bears N. 80° E. and S. 80° W.

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS 40.06	<p>The 1/4 sec. cor. of secs. 2 and 11, monumented with a granite boulder 30 x 24 x 10 ins. above ground, mkd. X on top and 1/4 S on the W face, with a scattered mound of stone, N of the cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., over the X chiseled on the original stone and in a mound of stone, 5½ ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T7N R10E</p> <table style="margin: auto;"> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">S 2</td> </tr> <tr> <td style="text-align: center;">4</td> <td style="text-align: center;">S11</td> </tr> </table> <p>1980</p> </div> <p>from which</p> <div style="text-align: center;"> <p>A juniper, 7 ins. diam., bears N. 18° E., 28 lks. dist., mkd. 1/4 S2 BT at chest height due to the growth of the tree.</p> </div> <p>The cor. is on a W slope.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°40' W., beginning new measurement.</p>	1	S 2	4	S11
1	S 2				
4	S11				
20.13	<p>Point for the W 1/16 sec. cor. of secs. 2 and 11.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T7N R10E</p> <table style="margin: auto;"> <tr> <td style="text-align: center;">W 1/16</td> <td style="text-align: center;">S 2</td> </tr> <tr> <td></td> <td style="text-align: center;">S11</td> </tr> </table> <p>1980</p> </div> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of the cor.</p>	W 1/16	S 2		S11
W 1/16	S 2				
	S11				
40.26	<p>The cor. of secs. 2, 3, 10 and 11.</p> <hr style="width: 100%;"/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°51' W., bet. secs. 27 and 34.</p> <p>Over rolling land, through scattering to medium undergrowth.</p>				
1.30	<p>Arizona State Highway No. 188, asphalt surfaced, bears S. 30° E. and N. 30° W.</p>				
5.90	<p>Power and telephone lines, bear SE and NW.</p>				
39.74	<p>Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T7N R10E</p> <table style="margin: auto;"> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">S27</td> </tr> <tr> <td style="text-align: center;">4</td> <td style="text-align: center;">S34</td> </tr> </table> <p>1980</p> </div>	1	S27	4	S34
1	S27				
4	S34				

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS		
79.48	<p>Raise a mound of stone, 3 ft. base, 1½ ft. high, E of the cor. for support.</p> <p>The cor. is on a NW slope, 20 lks. E of a wash, 10 lks. wide, 2 feet deep, drains N. 20° E.</p> <p>The cor. of secs. 27, 28, 33 and 34, monumented with a granite stone, 16 x 9 x 5 ins., firmly set 4 ins. in the ground, mkd. with 3 grooves on the E and 1 groove on the S faces, with a mound of stone, 2½ ft. base, 1 ft. high, W of the cor.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. in the ground and in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T7N R10E S28 S27 S33 S34 1980</p> </div> <p>Deposit the mkd. stone in the mound alongside the aluminum post.</p> <p>The cor. is on a low ridge, bears E and W.</p>	
39.94	<p>N. 0°16' W., bet. secs. 27 and 28.</p> <p>Over broken rolling land, through scattering to medium undergrowth.</p> <p>The ¼ sec. cor. of secs. 27 and 28, monumented with a quartz stone, 12 x 8 x 6 ins., firmly set 5 ins. in the ground, mkd. ¼ on the W face, with a mound of stone, 2½ ft. base, 1½ ft. high, W of the cor.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T7N R10E ¼ S28 S27 1980</p> </div> <p>Deposit the mkd. stone alongside the aluminum post.</p> <p>Rebuild the mound of stone, 3 ft. base, 1½ ft. high, W of the cor.</p> <p>The cor. is 1.00 ch. N of a draw, drains easterly.</p>	
40.30	<p>N. 0°17' E., beginning new measurement.</p> <p>The cor. of secs. 21, 22, 27 and 28, monumented with a granite stone, 14 x 8 x 6 ins., firmly set 10 ins. in the ground, mkd. with 3 grooves on the E and 2 grooves on the S faces, with a mound of stone, 3 ft. base, 1 ft. high, SW of the cor.</p> <p>At the cor. point</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7N R10E S21 S22 S28 S27 1980</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, SW of the cor.</p>	
.34	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89°34' W., bet. secs. 22 and 27.</p> <p>Over rolling land, through scattering to medium undergrowth.</p> <p>Arizona State Highway No. 188, asphalt surfaced, bears N. 25° E. and S. 25° W.</p>	
19.65	<p>Point for the E 1/16 sec. cor. of secs. 22 and 27.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7N R10E E 1/16 S22 S27 1980</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, N of the cor.</p> <p>From this point a local cor. of unknown origin, bears N. 80°24' W., 35.3 lks. dist., monumented with an open end pipe, 1½ ins. diam., projecting 12 ins. above a mound of stone, 2 ft. base, 1½ ft. high.</p>	
39.30	<p>The 1/4 sec. cor. of secs. 22 and 27, monumented with a quartz stone, 18 x 8 x 7 ins., firmly set 12 ins. in the ground, mkd. 1/4 S on the N face, with a scattered mound of stone, N of the cor.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T7N R10E 1 S22 4 S27 1980</p> <p>Deposit the mkd. stone alongside the aluminum post.</p> <p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, SW of the cor. for support.</p> <p>The cor. is 50 lks. S of a wash, 30 lks. wide, 3 ft. deep, drains E, curving SE.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS		
	<p>N. 89°34' W., beginning new measurement.</p>	
39.89	<p>The cor. of secs. 21, 22, 27 and 28.</p>	
	<p>N. 0°11' E., bet. secs. 21 and 22.</p>	
	<p>Over rolling land, through scattering to medium undergrowth.</p>	
2.30	<p>Ridge, bears E and W.</p>	
34.40	<p>Fence, bears N. 65° E. and S. 65° W.</p>	
40.60	<p>The 1/4 sec. cor. of secs. 21 and 22, monumented with a granite stone, 16 x 6 x 4 ins., firmly set 8 ins. in the ground, mkd. 1/4 S on the W face.</p>	
	<p>At the cor. point</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T7N R10E 1/4 S21 S22 1980</p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">A juniper, 10 ins. diam., bears S. 55° E., 104 lks. dist., mkd. 1/4 S22 BT.</p>	
	<p style="padding-left: 40px;">A juniper, 12 ins. diam., bears N. 63° W., 104.5 lks. dist., mkd. 1/4 S21 BT.</p>	
	<p>Deposit the mkd. stone alongside the iron post.</p>	
	<p>Raise a mound of stone, 3 ft. base, 1 ft. high, W of the cor.</p>	
	<p>N. 0°13' E., beginning new measurement.</p>	
38.36	<p>Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor.</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T7N R10E S16 S15 S21 S22 1980</p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">A juniper, 5 ins. diam., bears N. 65° E., 85 lks. dist., mkd. T7N R10E S15 BT.</p>	
	<p style="padding-left: 40px;">A juniper, 4 ins. diam., bears S. 66° E., 114.5 lks. dist., mkd. T7N R10E S22 BT.</p>	
	<p>Raise a mound of stone, 3½ ft. base, 2 ft. high, W of the cor.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS

From this point the 1/4 sec. cor. of secs. 16 and 21, bears S. 89°58' W., 39.555 chs. dist., monumented with a granite stone, 18 x 18 x 7 ins., firmly set 8 ins. in the ground, mkd. X on top and 1/4 on the W face, with a scattered mound of stone, N of the cor.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T7N R10E
1 S16
4 S21
1980

from which

A juniper, 8 ins. diam., bears S. 60° E.,
62 lks. dist., mkd. X BT at the base.

A mesquite, 8 ins. diam., bears S. 88° W.,
46 lks. dist., mkd. 1/4 S21 BT.

Rebuild the mound of stone, 3 ft. base, 1½ ft. high, N of the cor. and deposit the mkd. stone in this mound.

From the cor. of secs. 14, 15, 22 and 23.

S. 89°02' W., bet. secs. 15 and 22.

Over rolling land, through medium undergrowth.

- .50 Enter Tonto Creek bottom, edge bears N and S.
- 8.00 Leave Tonto Creek bottom, edge bears N and S.
- 13.10 Power line, bears S. 5° E. and N. 5° W.
- 14.30 Arizona State Highway No. 188, asphalt surfaced, bears S. 5° E. and N. 5° W.
- 19.78 Point for the E 1/16 sec. cor. of secs. 15 and 22.
Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T7N R10E
E 1/16 S15
S22
1980

Raise a mound of stone, 3½ ft. base, 2 ft. high, N of the cor.

- 39.56 Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate dist.; there is no remaining evidence of the original cor.
Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS	
79.12	<p style="text-align: center;">T7N R10E $\frac{1}{4}$ S15 $\frac{4}{4}$ S22 1980</p> <p>Raise a mound of stone, 4 ft. base, 3 ft. high, N of the cor.</p> <p>The cor. is on a steep W slope.</p> <p>The cor. of secs. 15, 16, 21 and 22.</p>
38.36	<p>N. 1°01' W., bet. secs. 15 and 16.</p> <p>Over rolling land, through medium undergrowth.</p> <p>The 1/4 sec. cor. of secs. 15 and 16, monumented with a granite stone, 12 x 12 x 8 ins., firmly set 4 ins. in the ground, mkd. 1/4 S on top.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, with aluminum cap mkd.</p>
20.24	<p style="text-align: center;">T7N R10E $\frac{1}{4}$ S16 S15 1980</p> <p>Deposit the mkd. stone alongside the aluminum post.</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, W of the cor.</p> <hr/> <p>N. 1°30' W., beginning new measurement.</p> <p>Point for the N 1/16 sec. cor. of secs. 15 and 16.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 19 ins. in the ground and in a mound of stone, 4 ft. base, to top, with aluminum cap mkd.</p>
40.48	<p style="text-align: center;">T7N R10E N 1/16 S16 S15 1980</p> <p>The cor. is 50 lks. W of a spur sloping N.</p> <p>The cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2½ ins. diam., projecting 7 ins. above ground, with brass cap mkd. as described in the official record of the 1970 remonumentation notes by Louis D. Gilbert, Cadastral Surveyor. A mound of stone, 2 ft. base, 1 ft. high, is W of the cor.</p>
	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 88°01' W., bet. secs. 10 and 15.</p> <p>Over rolling land, through scattering to medium undergrowth.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS	
13.50	Enter Tonto Creek bottom, edge bears NE and SW.
20.23	Point for the E 1/16 sec. cor. of secs. 10 and 15, falls in the Tonto Creek overflow area where it is impractical to set a permanent monument.
40.46	True point for the 1/4 sec. cor. of secs. 10 and 15 falls in the Tonto Creek overflow area where it is impractical to set a permanent monument.
42.70	Leave Tonto Creek bottom, edge bears irregularly N and S.
43.56	Point selected for the witness 1/4 sec. cor. of secs. 10 and 15.
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with aluminum cap mkd.
	<p style="text-align: center;">W C T7N R10E $\frac{1}{4}$ S10 → S15 > 1980</p>
	from which
	A mesquite, 7 ins. diam., bears N. 70° E., 8.5 lks. dist., mkd. X BT at the base.
	A mesquite, 8 ins. diam., bears S. 34° W., 14 lks. dist., mkd. X BT at the base.
	Raise a mound of stone, 3 ft. base, 1½ ft. high, N of the cor.
	The witness cor. is 24 lks. E of a fence, bears NE and SW.
49.20	Power line, bears S. 15° E. and N. 15° W.
60.69	The W 1/16 sec. cor. of secs. 10 and 15, monumented with a re-bar of unknown origin, 3/8 in. diam., set flush with the pavement in the center of Arizona State Highway No. 188, which bears S. 20° E. and N. 20° W. This position was shown to me by an interested private landowner in the area, is harmoniously related to identified original cors. and is accepted as the cor. position; not remonumented.
	From this point an iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground for a reference monument, bears N. 85°50' E., 44.16 ft. dist., with brass cap mkd. T7N R10E W 1/16 S10 RM 44.16 FT. 1980 and an arrow pointing to the cor.
	An iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground, for a reference monument, bears S. 85°50' W., 54.07 ft. dist., with brass cap mkd. T7N R10E W 1/16 S15 RM 54.07 FT. and an arrow pointing to the cor.

	S. 87°59' W., beginning new measurement.
20.23	The cor. of secs. 9, 10, 15 and 16.

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS	
	N. 0°18' W., bet. secs. 9 and 10.
	Over rolling land, through medium undergrowth.
19.75	Point for the S 1/16 sec. cor. of secs. 9 and 10.
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T7N R10E S 1/16 S 9 S10 1980</p>
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W of the cor.
	The cor. is in a small draw, drains SE.
39.50	The 1/4 sec. cor. of secs. 9 and 10, monumented with a granite stone, 10 x 7 x 6 ins., set in a mound of stone, 2 ft. base, 1 ft. high, mkd. 1/4 S on the W face.
	At the cor. point
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T7N R10E 1/4 S 9 S10 1980</p>
	from which
	<p style="text-align: center;">A juniper, 18 ins. diam., bears S. 4° E., 28 lks. dist., mkd. 1/4 S10 BT.</p>
	<p style="text-align: center;">A juniper, 14 ins. diam., bears N. 33° W., 43 lks. dist., mkd. 1/4 S9 BT.</p>
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W of the cor.
	From the cor. of secs. 2, 3, 10 and 11.
	N. 89°39' W., bet. secs. 3 and 10.
	Over Tonto Creek bottom.
.90	Track road, bears S. 50° E. and N. 50° W.
16.80	Leave Tonto Creek bottom, edge bears N. 10° E. and S. 10° W.; enter rolling land with a scattering to medium cover of undergrowth.
20.05	Point for the E 1/16 sec. cor. of secs. 3 and 10.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS	
	<p>T7N R10E E 1/16 $\frac{S\ 3}{S10}$ 1980</p>
	<p>Raise a mound of stone, 3 ft. base, 1 ft. high, N of the cor.</p>
21.60	Power line, bears N. 30° E. and S. 30° W.
33.10	Arizona State Highway No. 188, bears N. 25° E. and S. 25° W.
40.10	The 1/4 sec. cor. of secs. 3 and 10, monumented with an iron post, 2½ ins. diam., set in a mound of stone, 2 ft. base, 6 ins. high, to top, with brass cap mkd. as described in the official record of the 1970 remonumentation notes by Louis D. Gilbert, Cadastral Surveyor.
<p>Subdivision of Section 10, T. 7 N., R. 10 E., Gila and Salt River Mer., Arizona</p>	
	<p>From the true point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>N. 0°01' W., on the N and S center line of sec. 10.</p> <p>Over Tonto Creek bottom.</p>
7.00	Enter dense undergrowth, edge bears N. 15° E. and S. 15° W.
19.855	<p>Point for the center S 1/16 sec. cor. of sec. 10, falls in the Tonto Creek overflow area where it is impractical to set a permanent monument.</p> <p>From this point an iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground and in a mound of stone, 2½ ft. base, to top, for a reference monument, bears S. 66½° W., 26.7 ft. dist., with brass cap mkd. T7N R10E C-S 1/16 S10 RM 26.7 FT. 1980 and an arrow pointing to the cor.</p> <p>From this same point an iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground and in a mound of stone, 2½ ft. base, to top, for a reference monument, bears N. 38° W., 32.5 ft. dist., with brass cap mkd. T7N R10E C-S 1/16 S10 RM 32.5 FT. 1980 and an arrow pointing to the cor.</p>
21.10	Leave Tonto Creek bottom, edge bears N curving E and S curving E.
39.71	<p>Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E and W center line of sec. 10.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p>T7N R10E C 1/4 S10 1980</p>

Subdivision of Section 10,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A mesquite, 7 ins. diam., bears N. 67° W., 91 lks. dist., mkd. C 1/4 S10 BT.</p> <p>A mesquite, 7 ins. diam., bears N. 12° W., 95.5 lks. dist., mkd. C 1/4 S10 BT.</p>
39.94	Power line, bears E and W.
60.59	<p>Point for the center N 1/16 sec. cor. of sec. 10.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7N R10E C N 1/16 S10 C 1980</p> <p>Raise a mound of stone, 3½ ft. base, 2 ft. high, W of the cor.</p> <p>Cor. is 230 lks. E of Arizona State Highway No. 188, asphalt surfaced, bears N. 25° E., and S. 25° W.</p> <p>Cor. is 105 lks. W of a fence, bears N. 25° E., and S. 25° W.</p>
81.47	The 1/4 sec. cor. of secs. 3 and 10.
	<p>From the 1/4 sec. cor. of secs. 10 and 11.</p> <p>S. 87°43' W., on the E and W center line of sec. 10.</p> <p>Over level pasture.</p>
7.60	Fence, bears S. 10° E. and N. 10° W.
7.90	Enter Tonto Creek bottom, edge bears S. 10° E. and N. 10° W.
20.15	Point for the center E 1/16 sec. cor of sec. 10, falls in Tonto Creek bottom where it is impracticable to set a permanent monument.
28.20	Leave Tonto Creek bottom, edge bears N. 15° E. and S. 15° W.
40.30	The center 1/4 sec. cor. of sec. 10.
53.55	Fence, bears N. 22° E. and S. 22° W.
53.65	Power line, bears N. 22° E. and S. 22° W.
60.63	<p>Point for the center W 1/16 sec. cor. of sec. 10.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7N R10E C W 1/16 C S10 1980</p>

Subdivision of Section 10,
T. 7 N., R. 10 E. Gila & Salt River Mer., Arizona

CHAINS	
	<p>Raise a mound of stone, 3½ ft. base, 2½ ft. high, N of the cor.</p> <p>From this point an open end pipe of unknown origin, ¾ in. diam., projecting 5 ins. above ground, bears N. 76°05' W., 152.8 lks. dist.</p>
61.50	<p>Arizona State Highway No. 188, asphalt surfaced, bears N. 25° E., curving NE and S. 25° W., curving SW.</p>
80.96	<p>The 1/4 sec. cor. of secs. 9 and 10.</p>
	<p>NE 1/4, Section 10</p> <hr style="width: 20%; margin: auto;"/>
	<p>From the point for the center E 1/16 sec. cor. of sec. 10.</p> <p>N. 0°08' W., on the N and S center line of the NE 1/4 of sec. 10.</p> <p>Over Tonto Creek bottom.</p>
20.42	<p>True point for the NE 1/16 sec. cor. of sec. 10, at intersection with the E and W center line of the NE 1/4 of sec. 10, falls in Tonto Creek bottom where it is impracticable to set a permanent monument.</p>
23.90	<p>Leave Tonto Creek bottom, edge bears S. 70° W. and N. 70° E. curving northerly.</p>
24.65	<p>Power line, bears E and W.</p>
24.82	<p>Point selected for the witness NE 1/16 sec. cor. of sec. 10.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>W C T7N R10E NE 1/16 ↓ S10 1980</p> </div>
40.84	<p>Raise a mound of stone, 3½ ft. base, 2½ ft. high, W of the cor.</p> <p>The E 1/16 sec. cor. of secs. 3 and 10.</p>
	<p>From the N 1/16 sec. cor. of secs. 10 and 11.</p> <p>S. 89°01' W., on the E and W center line of the NE 1/4 of sec. 10.</p> <p>Over Tonto Creek bottom.</p>
20.095	<p>True point for the NE 1/16 sec. cor. of sec. 10.</p>
40.19	<p>The center N 1/16 sec. cor. of sec. 10.</p>

Subdivision of Section 10,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS	
	SE 1/4, Section 10
	From the point for the E 1/16 sec. cor. of secs. 10 and 15.
	N. 0°08' W., on the N and S center line of the SE 1/4 of sec. 10.
	Over Tonto Creek bottom.
19.905	Point for the SE 1/16 sec. cor. of sec. 10, at intersection with the E and W center line of the SE 1/4 of sec. 10, falls in the Tonto Creek bottom.
	Set a re-bar, 48 ins. long, 5/8 in. diam., 3 ft. in the ground, with aluminum cap mkd.
	BLM SE 1/16 S10 1980
39.81	Point for the center E 1/16 sec. cor. of sec. 10.
	From the S 1/16 sec. cor. of secs. 10 and 11.
	S. 87°52' W., on the E and W center line of the SE 1/4 of sec. 10.
	Over level pasture.
3.30	Enter Tonto Creek bottom, edge bears NE and SW.
20.19	The SE 1/16 sec. cor. of sec. 10.
40.38	Point for the center S 1/16 sec. cor. of sec. 10.
	SW 1/4, Section 10
	From the W 1/16 sec. cor. of secs. 10 and 15.
	N. 0°09' W., on the N and S center line of the SW 1/4 of sec. 10.
	Over rolling land, through medium to scattering brush and undergrowth.
19.80	Point for the SW 1/16 sec. cor. of sec. 10, at intersection with the E and W center line of the SW 1/4 of sec. 10.
	Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with aluminum cap mkd.
	T7N R10E SW 1/16 S10 1980
	Raise a mound of stone, 3½ ft. base, 2 ft. high, W of the cor.
39.60	The center W 1/16 sec. cor. of sec. 10.

Subdivision of Section 10,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS	
	<p>From the point for the center S 1/16 sec. cor. of sec. 10.</p> <p>S. 87°52' W., on the E and W center line of the SW 1/4 of sec. 10.</p> <p>0.20 Leave Tonto Creek bottom, edge bears N curving E and S curving E.</p> <p>20.28 The SW 1/16 sec. cor. of sec. 10.</p> <p>40.56 The S 1/16 sec. cor. of secs. 9 and 10.</p>
	<p style="text-align: center;">Subdivision of Section 11, T. 7 N., R. 10 E., Gila and Salt River Mer., Arizona</p>
	<p>From the 1/4 sec. cor. of secs. 11 and 14.</p> <p>N. 0°12' W., on the N and S center line of sec. 11.</p> <p>Over gently rolling land, through scattering undergrowth.</p> <p>8.90 Track road, bears NE and SW.</p> <p>18.20 Track road, bears N. 55° E. and S. 55° W.</p> <p>19.945 Point for the center S 1/16 sec. cor. of sec. 11.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7N R10E C S 1/16 S11 C 1980</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, W of the cor.</p> <p>34.60 Fence, bears S. 85° E. and N. 85° W.</p> <p>39.89 Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E and W center line of sec. 11.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7N R10E C 1/4 S11 1980</p> <p>from which</p> <p style="text-align: center;">A juniper, 4 ins. diam., bears S. 26½° W., 103 lks. dist., mkd. X BT at the base.</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, W of the cor.</p> <p>The cor. is about 2.00 chs. N of a draw, drains NW from NE.</p> <p>59.98 Point for the center N 1/16 sec. cor. of sec. 11.</p>

Subdivision of Section 11,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T7N R10E C N 1/16 S11 C 1980</p> <p>from which</p> <p style="text-align: center;">A juniper, 12 ins. diam., bears N. 61½° E., 238 lks. dist., mkd. C-N 1/16 S11 BT.</p>
80.07	The 1/4 sec. cor. of secs. 2 and 11.
	<hr/> <p>From the 1/4 sec. cor. of secs. 11 and 12.</p> <p>N. 89°58' W., on the E and W center line of sec. 11.</p> <p>Over rolling land, through medium undergrowth.</p>
27.25	Fence, bears S. 5° E. and N. 5° W.
40.06	The center 1/4 sec. cor. of sec. 11.
60.17	Point for the center W 1/16 sec. cor. of sec. 11.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7N R10E C W 1/16 C S11 1980</p>
60.38	Raise a mound of stone, 3 ft. base, 2 ft. high, N of the cor. Fence, bears N and S.
80.28	The 1/4 sec. cor. of secs. 10 and 11.
	<hr/> <p style="text-align: center;">SW 1/4, Section 11</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 11 and 14.</p> <p>N. 0°13' W., on the N and S center line of the SW 1/4 of sec. 11.</p> <p>Over rolling land, through medium undergrowth.</p>
10.30	Track road, bears SE and NW.
19.75	Track road, bears E and W.
19.95	Point for the SW 1/16 sec. cor. of sec. 11, at intersection with the E and W center line of the SW 1/4 of sec. 11.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 11,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS		
	<p>T7N R10E SW 1/16 S11 1980</p>	
	<p>Raise a mound of stone, 3½ ft. base, 1½ ft. high, E of the cor., on public land.</p> <p>From this point an open end pipe of unknown origin, ¾ in. diam., projecting 5 ins. above ground, bears N. 51° W., 14.2 lks. dist.</p> <p>From this same point a fence cor., bears N. 49° W., 21 lks. dist., from which fences extend N and W.</p>	
39.90	The center W 1/16 sec. cor. of sec. 11.	
	<hr/> <p>From the center S 1/16 sec. cor. of sec. 11.</p> <p>N. 89°59' W. on the E and W center line of the SW 1/4 of sec. 11.</p> <p>Over rolling land, through medium undergrowth.</p>	
20.10	The SW 1/16 sec. cor. of sec. 11.	
27.30	Track road, bears irregularly N and S.	
27.80	Power line, bears N. 5° E. and S. 5° W.	
29.70	Center of Indian ruins, 5 chs. diam.	
40.20	The S 1/16 sec. cor. of secs. 10 and 11.	
	<hr/> <p>NW 1/4, Section 11</p> <hr/>	
	<p>From the center W 1/16 sec. cor. of sec. 11.</p> <p>N. 0°14' W., on the N and S center line of the NW 1/4 of sec. 11.</p> <p>Over rolling land, through scattering to medium undergrowth.</p>	
20.025	<p>Point for the NW 1/16 sec. cor. of sec. 11, at intersection with the E and W center line of the NW 1/4 of sec. 11.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p>	
	<p>T7N R10E NW 1/16 S11 1980</p>	
	<p>From this point a fence cor., bears S. 83° W., 25 lks. dist., from which fences extend S and W.</p> <p>From this same point an open end pipe of unknown origin, ¾ in. diam., projecting 10 ins. above ground, bears W, 20.8 lks. dist.</p>	

Subdivision of Section 11,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS	
40.05	<p>The W 1/6 sec. cor. of secs. 2 and 11.</p> <hr/> <p>From the center N 1/16 sec. cor. of sec. 11.</p> <p>S. 89°51' W., on the E and W center line of the NW 1/4 of sec. 11.</p> <p>Over rolling land.</p>
20.12	<p>The NW 1/16 sec. cor. of sec. 11.</p>
40.24	<p>The N 1/16 sec. cor. of secs. 10 and 11.</p>
<p>Subdivision of Section 14, T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona</p>	
	<p>From the 1/4 sec. cor. of secs. 14 and 23.</p> <p>N. 0°03' W., on the N and S center line of sec. 14.</p> <p>Over rolling land, through medium to scattering undergrowth.</p>
20.07	<p>Point for the center S 1/16 sec. cor. of sec. 14.</p> <p>Set a fiberglass post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, and in a mound of stone, 3½ ft. base, to top, with brass cap mkd.</p>
<p>T7N R10E C S 1/16 S14 C 1980</p>	
40.14	<p>Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E and W center line of sec. 14, falls in a wash where it is impractical to set a permanent monument.</p> <p>From this point a granite stone, 24 x 12 x 10 ins. above ground, bears S. 67½° E., 24 lks. dist., mkd. X B0 on top.</p> <p>From this same point an iron post, 28 ins. long, 2½ ins. diam., set 8 ins. in the ground and in a mound of stone, 4½ ft. base, to top, for a reference monument, bears S. 8¾° E., 15.71 ft. dist., with brass cap mkd. T7N R10E C 1/4 S14 RM 15.71 FT. 1980 and an arrow pointing to the cor.</p> <p>The cor. point is 75 lks. S of the center of a wash, 150 lks. wide, 10 ft. deep, drains SW.</p>
47.35	<p>Fence, bears SE and NW.</p>
80.15	<p>The 1/4 sec. cor. of secs. 11 and 14.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 14.</p> <p>S. 89°46' W., on the E and W center line of sec. 14.</p>

Subdivision of Section 14,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS	<p>Over rolling land, through scattering to medium undergrowth.</p> <p>9.60 Fence, bears SE and NW.</p> <p>40.03 The point for the center 1/4 sec. cor. of sec. 14.</p> <p>60.15 Point for the center W 1/16 sec. cor. of sec. 14.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T7N R10E C W 1/16 C S14 1980</p> <p>71.60 Fence, bears N and S.</p> <p>72.70 Track road and power line, bear N and S.</p> <p>73.60 Fence, bears NE and SW.</p> <p>80.27 The 1/4 sec. cor. of secs. 14 and 15.</p> <hr/> <p style="text-align: center;">SW 1/4, Section 14</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 14 and 23.</p> <p>North, on the N and S center line of the SW 1/4 of sec. 14.</p> <p>Over rolling land, through dense undergrowth and cacti.</p> <p>20.08 Point for the SW 1/16 sec. cor. of sec. 14, at intersection with the E and W center line of the SW 1/4 of sec. 14.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7N R10E SW 1/16 S14 1980</p> <p>Raise a mound of stone, 3½ ft. base, 2 ft. high, W of the cor.</p> <p>40.16 The center W 1/16 sec. cor. of sec. 14.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 14.</p> <p>S. 89°45' W., on the E and W center line of the SW 1/4 of sec. 14.</p> <p>Over rolling land, through medium undergrowth.</p> <p>20.14 The SW 1/16 sec. cor. of sec. 14.</p> <p>32.70 Fence, bears N. 5° E., and S. 5° W.</p> <p>33.20 Track road, bears N curving NW and S curving SW.</p>
--------	--

Subdivision of Section 14,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS	
34.25	Power line, bears N. 5° E. and S. 5° W.
37.30	Enter Tonto Creek bottom, edge bears S. 15° E. and N. 30° W.
40.28	Point for the S 1/16 sec. cor. of secs. 14 and 15.
Subdivision of Section 15, T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona	
	From the 1/4 sec. cor. of secs. 15 and 22.
	N. 0°37' W., on the N and S center line of sec. 15.
	Over rolling land, through medium to scattering undergrowth.
19.63	Point for the center S 1/16 sec. cor. of sec. 15.
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.
	T7N R10E C S 1/16 S15 C 1980
	from which
	A juniper, 6 ins. diam., bears N. 14° E., 31.5 lks. dist., mkd. C S 1/16 S15 BT.
	Raise a mound of stone, 3½ ft. base, 2 ft. high, W of the cor.
39.26	True point for the center 1/4 sec. cor. of sec. 15, at intersection with the E and W center line of sec. 15, falls in Tonto Creek bottom where it is impractical to set a permanent monument.
59.425	Point for the center N 1/16 sec. cor. of sec. 15, falls in Tonto Creek bottom where it is impractical to set a permanent monument.
79.59	True point for the 1/4 sec. cor. of secs. 10 and 15.
	From the 1/4 sec. cor. of secs. 14 and 15.
	S. 87°45'30" W., on the E and W center line of sec. 15.
	Over rolling land, through scattering to medium undergrowth.
20.015	Point for the center E 1/16 sec. cor. of sec. 15.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T7N R10E C E 1/16 C S15 1980

Subdivision of Section 15,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS		
	<p>from which</p> <p>A mesquite, 20 ins. diam., bears S. 68° E., 101 lks. dist., mkd. C-E 1/16 S15 BT.</p> <p>A walnut tree, 15 ins. diam., bears N. 72½° W., 59 lks. dist., mkd. C-E 1/16 S15 BT.</p>	
25.60	Enter Tonto Creek bottom, edge bears S. 50° E. and N. 70° W.	
40.03	True point for the center 1/4 sec. cor. of sec. 15.	
40.80	Leave Tonto Creek bottom, edge bears irregularly N and S.	
41.86	<p>Point selected for the witness center 1/4 sec. cor. of sec. 15.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">W C T7N R10E C 1/4 S15</p> <p style="text-align: center;">→ 1980</p>	
	Raise a mound of stone, 3½ ft. base, 1½ ft. high, W of the cor.	
42.60	Arizona State Highway No. 188, asphalt surfaced, bears S. 15° E. and N. 15° W.	
45.00	Fence, bears NE and SW.	
59.95	<p>Point for the center W 1/16 sec. cor. of sec. 15, falls in a wash, 15 lks. wide, 1 ft. deep, draining NE, where it is impractical to set a permanent monument.</p> <p>From this point an aluminum post, 28 ins. long, 1 in. diam., set 19 ins. in the ground, for a reference monument, bears S. 62° E., 10.48 ft. dist., with aluminum cap mkd. T7N R10E C-W 1/16 S15 RM 10.48 FT. 1980 and an arrow pointing to the cor.</p> <p>From this same point a granite boulder, 24 x 18 x 18 ins. above ground, bears N. 19° W., 30.4 lks. dist., mkd. XBO on top.</p>	
79.87	The 1/4 sec. cor. of secs. 15 and 16.	
	<hr/> <p>SE 1/4, Section 15</p> <hr/>	
	<p>From the E 1/16 sec. cor. of secs. 15 and 22.</p> <p>N. 0°18' W., on the N and S center line of the SE 1/4 of sec. 15.</p> <p>Over rolling land, through scattering undergrowth.</p>	
19.855	Point for the SE 1/16 sec. cor. of sec. 15, at intersection with the E and W center line of the SE 1/4 of sec. 15.	

Subdivision of Section 15,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 19 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T7N R10E SE 1/16 S15 1980</p> <p>Raise a mound of stone, 3½ ft. base, 2 ft. high, N of the cor.</p> <p>The cor. is 4 lks. E of a fence, bears SE and NW.</p>
21.05	Arizona State Highway No. 188, asphalt surfaced, bears SE and NW.
39.71	The center E 1/16 sec. cor. of sec. 15.
	<hr/> <p>From the point for the S 1/16 sec. cor. of secs. 14 and 15.</p> <p>S. 88°23' W., on the E and W center line of the SE 1/4 of sec. 15.</p> <p>Over Tonto Creek bottom.</p>
11.30	Leave Tonto Creek bottom, edge bears S. 25° E. and N. 25° W.; thence over rolling land, through scattering undergrowth.
19.00	Arizona State Highway No. 188, asphalt surfaced, bears SE and NW.
19.90	The SE 1/16 sec. cor. of sec. 15.
39.80	The center S 1/16 sec. cor. of sec. 15.
	<hr/> <p style="text-align: center;">NW 1/4, Section 15</p> <hr/> <p>From the point for the center W 1/16 sec. cor. of sec. 15.</p> <p>N. 1°04'30" W., on the N and S center line of the NW 1/4 of sec. 15.</p> <p>Over rolling land, through scattering undergrowth.</p>
20.20	<p>Point for the NW 1/16 sec. cor. of sec. 15, at intersection with the E and W center line of the NW 1/4 of sec. 15, falls in a wash, 60 lks. wide, 3 ft. deep, draining NE, where it is impracticable to set a permanent monument.</p> <p>From this point a metal post of unknown origin, projecting 3 ft. above ground, bears N. 32¾° E., 35.8 lks. dist.</p> <p>From this same point an aluminum post, 28 ins. long, 1 in. diam., set 19 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, for a reference monument, bears S. 74° E., 40.47 ft. dist., with aluminum cap mkd. T7N R10E NW 1/16 S15 RM 40.47 FT. 1980 and an arrow pointing to the cor.</p>

Subdivision of Section 15,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS	<p>From this same point an aluminum post, 28 ins. long, 1 in. diam., set 20 ins. in the ground, and in a mound of stone, 2 ft. base, to top, for a reference monument, bears S. 83°06' W., 26.57 ft. dist., with aluminum cap mkd. T7N R10E NW 1/16 S15 RM 26.57 FT. 1980 and an arrow pointing to the cor.</p>
40.41	<p>The W 1/16 sec. cor. of secs. 10 and 15.</p> <hr/> <p>From the point for the center N 1/16 sec. cor. of sec. 15.</p> <p>S. 87°52' W., on the E and W center line of the NW 1/4 of sec. 15.</p> <p>Over Tonto Creek bottom.</p>
6.70	<p>Leave Tonto Creek bottom, edge bears N. 10 E. and S. 10° E.</p>
7.50	<p>Arizona State Highway No. 188, asphalt surfaced, bears S. 35° E. and N. 35° W.</p>
9.20	<p>Point for a witness point on the E and W center line of the NW 1/4 of sec. 15.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T7N R10E W P S29 15 1980 1983</p>
20.075	<p>The cor. is on a steep NE slope.</p>
40.15	<p>The point for the NW 1/16 sec. cor. of sec. 15.</p> <p>The N 1/16 sec. cor. of secs. 15 and 16</p> <hr/> <p style="text-align: center;">Subdivision of Section 22, T. 7 N., R. 10 E., Gila and Salt River Mer., Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 22 and 27.</p> <p>N. 0°03' W., on the N and S center line of sec. 22.</p> <p>Over rolling land, through scattering undergrowth.</p>
29.10	<p>Fence, bears S. 70° E. and N. 70° W.</p>
40.63	<p>Point for the center 1/4 sec. cor. of sec. 22, at intersection with the E and W center line of sec. 22.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 19 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T7N R10E C 1/4 S22 1980</p> <p>from which</p> <p style="text-align: center;">A juniper, 7 ins. diam., bears S. 32° W., 51.5 lks. dist., mkd. C 1/4 S22 BT.</p>

*Ref. memo
7600-992
Gyazo No. 618,
Arizona,
dated April 8,
1983*

Subdivision of Section 22,
T. 7 N., R. 10 E., Gila & Salt River Mer., Arizona

CHAINS	
	<p>Raise a mound of stone, 3 ft. base, 1½ ft. high, W of the cor.</p>
60.275	<p>Point for the center N 1/16 sec. cor. of sec. 22.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T7N R10E C N 1/16 S22 C 1980</p>
62.40	Track road, bears S. 75° E. and N. 75° W.
79.92	The 1/4 sec. cor. of secs. 15 and 22.
<p>From the 1/4 sec. cor. of secs. 22 and 23.</p> <p>N. 89°36' W., on the E and W center line of sec. 22.</p> <p>Over rolling land, through scattering to medium undergrowth.</p>	
7.20	Arizona State Highway No. 188, asphalt surfaced, bears S. 20° E. and N. 20° W.
8.80	Telephone line, bears S. 15° E. and N. 15° W.
10.60	Power line, bears N and S.
19.715	<p>Point for the center E 1/16 sec. cor. of sec. 22.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T7N R10E C E 1/16 C S22 1980</p>
	<p>Raise a mound of stone, 3 ft. base, 1½ ft. high, N of the cor.</p> <p>From this point an Arizona State Highway monument, bears N. 81°30' E., 4.83 chs. dist., a brass tablet, 3 ins. diam., set flush in a granite stone, 24 x 18 x 6 ins. above ground, mkd. P&M 1328-21 dated 1974.</p>
39.43	The center 1/4 sec. cor. of sec. 22.
79.17	The 1/4 sec. cor. of secs. 21 and 22.
<p style="text-align: center;">NE 1/4, Section 22</p> <hr style="width: 20%; margin: auto;"/>	
	<p>From the center E 1/16 sec. cor. of sec. 22.</p> <p>N. 0°03'30" E. on the N and S center line of the NE 1/4 of sec. 22.</p> <p>Over rolling land, through scattering to medium undergrowth.</p>

Subdivision of Section 22,
T. 7 N., R. 10 E., Gila and Salt River Mer., Arizona

CHAINS	
14.98	<p>Point selected for the witness NE 1/16 sec. cor. of sec. 22 is in an abandoned road, which bears S. 80° E. and N. 80° W.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W C T7N R10E NE 1/16 S22 1980</p> <p>Raise a mound of stone, 5 ft. base, 3 ft. high, W of the cor.</p>
19.88	<p>True point for the NE 1/16 sec. cor. of sec. 22, at intersection with the E and W center line of the NE 1/4 of sec. 22, falls in Slate Creek, where it is impracticable to set a permanent monument. Set a steel fence post.</p>
39.76	<p>The E 1/16 sec. cor. of secs. 15 and 22.</p>
3.20	<p>Leave Tonto Creek bottom, edge bears N and S; enter rolling land, with scattering undergrowth.</p>
3.70	<p>The witness N 1/16 sec. cor. of secs. 22 and 23, heretofore described.</p>
14.10	<p>Arizona State Highway No. 188, asphalt surfaced, bears N. 10° E. and S.</p>
19.745	<p>The NE 1/16 sec. cor. of sec. 22.</p>
39.49	<p>The center N 1/16 sec. cor. of sec. 22.</p>
	<p style="text-align: center;">Subdivision of Section 23, T. 7 N., R. 10 E., Gila and Salt River mer., Arizona</p>
20.025	<p>Point for the center S 1/16 sec. cor. of sec. 23, falls in Tonto Creek bottom where it is impracticable to set a permanent monument.</p>
23.30	<p>Leave Tonto Creek bottom, edge bears N. 60° E. and S. 60° W.</p>
23.50	<p>Fence, bears N. 60° E. and S. 60° W.</p>
40.05	<p>Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E and W center line of sec. 23.</p>

Subdivision of Section 23
T. 7 N., R. 10 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7N R10E C 1/4 S23 1980</p>	
	<p>Raise a mound of stone, 3 ft. base, 1 ft. high, W of the cor.</p>	
57.55	<p>Point selected for the witness center N 1/16 sec. cor. of sec. 23.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground with brass cap mkd.</p> <p style="text-align: center;">T7N WC R10E C N 1/16 ↑ S23 C 1980</p>	
	<p>Raise a mound of stone, 3½ ft. base, 2 ft. high, N of the cor. for support.</p>	
58.10	<p>Enter Tonto Creek bottom, edge bears E and W.</p>	
60.05	<p>True point for the center N 1/16 sec. cor. of sec. 23, falls in Tonto Creek bottom where it is impracticable to set a permanent monument.</p>	
80.05	<p>The 1/4 sec. cor. of secs. 14 and 23.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 23 and 24.</p> <p>S. 89°25' W., on the E and W center line of sec. 23.</p> <p>Over rolling land, through scattering undergrowth.</p>	
20.04	<p>Point for the center E 1/16 sec. cor. of sec. 23.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T7N R10E C E 1/16 C S23 1980</p> <p>from which</p> <p style="text-align: center;">A juniper, 12 ins. diam., bears N. 80° E., 9 lks. dist., mkd. C E 1/16 S23 BT.</p> <p>Cor. is on a steep N slope.</p>	
40.08	<p>The center 1/4 sec. cor. of sec. 23.</p>	
60.245	<p>Point for the center W 1/16 sec. cor. of sec. 23, falls on the N edge of a bladed road, bears E and W.</p> <p>Set an iron post, 14 ins. long, 2½ ins. diam., 16 ins. in the ground, to solid rock with brass cap mkd.</p>	

Subdivision of Section 23
T. 7 N., R. 10 E., Gila and Salt River Mer., Arizona

CHAINS	
80.41	<p style="text-align: center;">T7N R10E C W 1/16 C S23 1980</p> <p>From this point an aluminum post, 28 ins. long, 1 in. diam., set 20 ins. in the ground, for a reference monument, bears S. 21°26' W., 60.79 ft. dist., with aluminum cap mkd. T7N R10E C-W 1/16 S23 RM 60.79 FT. 1980 and an arrow pointing to the cor.</p> <p>From this same point an open end pipe of unknown origin, 1 1/4 ins. diam., projecting 6 ins. above ground, bears S. 31°12' W., 29.3 lks. dist.</p> <p>From the same point an aluminum post, 28 ins. long, 1 in. diam., set 20 ins. in the ground, for a reference monument, bears S. 62°04' W., 75.38 ft. dist., with aluminum cap mkd. T7N R10E C-W 1/16 S23 RM 75.38 FT. 1980 and an arrow pointing to the cor.</p> <p>The cor. is 12 lks. S of a power line, bears E and W.</p> <p>The 1/4 sec. cor. of secs. 22 and 23.</p>
19.95	<p style="text-align: center;">NE 1/4, Section 23</p> <hr/> <p>From the center E 1/16 sec. cor. of sec. 23.</p> <p>N. 0°02' E., on the N and S center line of the NE 1/4 of sec. 23.</p> <p>Over broken rolling land, through scattering undergrowth.</p> <p>True point for the NE 1/16 sec. cor. of sec. 23, at intersection with the E and W center line of the NE 1/4 of sec. 23, falls on a steep crumbly W slope where it is impracticable to set a permanent monument.</p> <p>From this point the point selected for the witness NE 1/16 sec. cor. of sec. 23, bears N. 61°30' E., 44 lks. dist.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">WC T7N R10E NE 1/16 S23 ↙ 1980</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor.</p> <p>The witness cor. is 20 lks. E of a steep bluff.</p>
39.90	<p>The E 1/16 sec. cor. of secs. 14 and 23.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 23 and 24.</p> <p>S. 89°34' W., on the E and W center line of the NE 1/4 of sec. 23.</p>

Subdivision of Section 22
T. 7 N., R. 10 E., Gila and Salt River Mer., Arizona

CHAINS	
20.01	True point for the NE 1/16 sec. cor. of sec. 23.
40.02	True point for the center N 1/16 sec. cor. of sec. 23.
	SW 1/14, Section 23
	From the W 1/16 sec. cor. of sec. 23 and 26.
	N. 0°08' E., on the N and S center line of the SW 1/14 of sec. 23.
	Over Tonto Creek bottom.
20.04	Point for the SW 1/16 sec. cor. of sec. 23, at intersection with the E and W center line of the SW 1/14 of sec. 23, falls in the center of a newly bladed road which bears N and S, 40 lks. dist., thence E.
	Set an aluminum post, 30 ins. long, $\frac{3}{4}$ in. diam., 38 ins. in the ground, with aluminum cap mkd.
	T7N R10E SW 1/16 S23 1980
	From this point an open end pipe, of unknown origin, 1 1/4 in. diam. set in a mound of stone, 2 ft. base, 6 ins. high, to top, bears S. 32° W., 28.7 lks. dist.
	From this same point an aluminum post, 30 ins. long, $\frac{3}{4}$ in. diam., set 16 ins. in the ground, for a reference monument, bears N. 62°15' W., 27.62 lks. dist., with aluminum cap mkd. T7N R10E SW 1/16 S23 RM 27.62 FT. 1980 and an arrow pointing to the cor.
	From this same point an aluminum post, 30 ins. long, $\frac{3}{4}$ in diam., set 18 ins. in the ground, for a reference monument, bears N. 27°42' W., 44.67 ft. dist., with aluminum cap mkd. T7N R10E SW 1/16 S23 RM 44.67 FT. 1980 and an arrow pointing to the cor.
40.05	The center W 1/16 sec. cor. of sec. 23.
	From the point for the center S 1/16 sec. cor. of sec. 23.
	S. 89°27' W., on the E and W center line of the SW 1/4 of sec. 23.
	Over Tonto Creek bottom.
20.17	The SW 1/16 sec. cor. of sec. 23.
40.35	The S 1/16 sec. cor. of sec. 22 and 23.
	Subdivision of Section 26, T. 7 N., R. 10 E., Gila and Salt River Mer., Arizona
	From the 1/4 sec. cor. of sec. 26 and 35.
	N. 0°10'30" W., on the N and S center line of sec. 26.

*Ref. Memo
9600-942
Group No. 618,
Arizona,
dated April 8,
1983*

Subdivision of Section 26,
T. 7 N., R. 10 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>N. 0°10'30" W., on the N and S center line of sec. 26.</p> <p>Over rolling broken land, through scattering undergrowth.</p>
40.13	<p>Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E and W center line of sec. 26.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T7N R10E C 1/4 S26 1980</p>
	<p>Raise a mound of stone, 5 ft. base, 3 ft. high, W of the cor.</p>
60.25	<p>Point for the center N 1/16 sec. cor. of sec. 26.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T7N R10E C N 1/16 S26 C 1980</p>
	<p>Raise a mound of stone, 5 ft. base, 3 ft. high, W of the cor.</p>
73.37	<p>The witness 1/4 sec. cor. of secs. 23 and 26, heretofore described.</p>
74.50	<p>Enter Tonto Creek bottom, edge bears NE and SW.</p>
80.37	<p>True point for the 1/4 sec. cor. of secs. 23 and 26.</p>
	<hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26.</p>
	<p>S. 89°26'30" W., on the E and W center line of sec. 26.</p>
	<p>Over gently rolling mesa, through scattering to medium undergrowth.</p>
40.30	<p>The center 1/4 sec. cor. of sec. 26.</p>
52.50	<p>Enter Tonto Creek bottom, edge bears SE and NW.</p>
60.48	<p>Point for the center W 1/16 sec. cor. of sec. 26 falls in Tonto Creek bottom where it is impracticable to set a permanent monument.</p>
80.66	<p>True point for the 1/4 sec. cor. of secs. 26 and 27.</p>
	<hr/> <p style="text-align: center;">NW 1/4, Section 26</p> <hr/>
	<p>From the point for the center W 1/16 sec. cor. of sec. 26.</p>
	<p>N. 0°10' W., on the N and S center line of the NW 1/4 of sec. 26.</p>
	<p>Over Tonto Creek bottom.</p>

Subdivision of Section 26,
T. 7 N., R. 10 E., Gila and Salt River Mer., Arizona

CHAINS	
20.115	True point for the NW 1/16 sec. cor. of sec. 26, at intersection with the E and W center line of the NW 1/4 of sec. 26, falls in Tonto Creek bottom where it is impractical to set a permanent monument.
40.23	The W 1/16 sec. cor. of secs. 23 and 26.
<hr/>	
From the center N 1/16 sec. cor. of sec. 26.	
S. 89°26' W , on the E and W center line of the NW 1/4 of sec. 26.	
Over rolling land, through medium undergrowth.	
14.78	Point selected for the witness NW 1/16 sec. cor. of sec. 26.
Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.	
<p>WC T7N R10E ← NW 1/16 S26 1980</p>	
Raise a mound of stone, 4 ft. base, 1½ ft. high, W of the cor.	
15.60	Enter Tonto Creek bottom, edge bears N and S.
20.18	True point for the NW 1/16 sec. cor. of sec. 26.
30.27	Point for the center W-NW 1/64 sec. cor. of sec. 26, falls in Tonto Creek bottom where it is impractical to set a permanent monument.
40.36	The N 1/16 sec. cor. of secs. 26 and 27.
<hr/>	
From the point for the center W-NW 1/64 sec. cor. of sec. 26.	
S. 0°10'30" E., on the N and S center line of the SW 1/4 of the NW 1/4 of sec. 26.	
Over Tonto Creek bottom.	
10.055	Point for the SW-NW 1/64 sec. cor. of sec. 26, falls in Tonto Creek bottom where it is impracticable to set a permanent monument.
<hr/>	
S. 89°26' W , on the E and W center line of the SW 1/4 of the NW 1/4 of sec. 26.	
Over Tonto Creek bottom.	
10.09	Point for the S-N 1/64 sec. cor. of secs. 26 and 27.
<hr/>	
<p>Subdivision of Section 27, T. 7 N., R. 10 E., Gila and Salt River Mer., Arizona</p>	
<hr/>	
From the 1/4 sec. cor. of secs. 27 and 34.	

Subdivision of Section 27,
T. 7 N. R. 10 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>N. 0°07' E., on the N and S center line of sec. 27. Over rolling land, through scattering undergrowth.</p>	
32.40	<p>Fence, bears S. 80° E. and N. 80° W</p>	
40.10	<p>Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E and W center line of sec. 27.</p>	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with aluminum cap mkd.</p>	
	<p style="text-align: center;">T7N R10E C 1/4 S27 1980</p>	
	<p>Raise a mound of stone, 3 ft. base, 1 ft. high, W of the cor.</p>	
60.07	<p>Point for the center N 1/16 sec. cor. of sec. 27.</p>	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 14 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>	
	<p style="text-align: center;">T7N R10E C N 1/16 S27 C 1980</p>	
	<p>The cor. is on level ground on a small mesa.</p>	
80.04	<p>The 1/4 sec. cor. of secs. 22 and 27.</p>	
	<p>From the true point for the 1/4 sec. cor. of sec. 26 and 27.</p>	
	<p>N. 89°58' W., on the E and W center line of sec. 27.</p>	
7.10	<p>Over Tonto Creek bottom.</p>	
	<p>Leave Tonto Creek bottom, edge bears S. 35° E. and N. 35° W., curving W; enter rolling land with a scattering cover of undergrowth.</p>	
19.80	<p>The center E 1/16 sec. cor. of sec. 27, monumented with an open end pipe of unknown origin, 3/4 in. diam., projecting 4 ins. above ground. This position is accepted as a careful and faithful determination for the center E 1/16 sec. cor. of sec. 27.</p>	
	<p>At the cor. point</p>	
	<p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T7N R10E C E 1/16 C S27 1980</p>	
	<p>Reset the local cor. alongside the iron post.</p>	
	<p>The cor. is 1 lk. S of a fence cor.; fences extend N and W.</p>	

Subdivision of Section 27,
T. 7 N., R. 10 E., Gila and Salt River Mer., Arizona

CHAINS		
	S. 89°55'30" W., beginning new measurement.	
5.00	Power line, bears N. 10° E. and S. 10° W.	
8.50	Arizona State Highway No. 188, asphalt surfaced, bears N. 30° E. and S. 30° W., curving SE.	
9.40	Telephone line, bears N. 30° E. and S. 30° W.	
19.72	The center 1/4 sec. cor. of sec. 27.	
59.74	The 1/4 sec. cor. of secs. 27 and 28.	
NE 1/4, Section 27		
	From the center E 1/16 sec. cor. of sec. 27.	
	N. 0°01' E., on the N and S center line of the NE 1/4 of sec. 27.	
	Over rolling land, through scattering to medium undergrowth.	
16.50	Arizona State Highway No. 188, asphalt surfaced, bears N. 30° E. and S. 30° W.	
20.02	Point for the NE 1/16 sec. cor. of sec. 27, at intersection with the E and W center line of the NE 1/4 of sec. 27.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.	
	T7N R10E NE 1/16 S27 1980	
	Raise a mound of stone, 3 ft. base, 1 ft. high, W of the cor.	
	The cor. is 23 lks. W of power and telephone lines, bears N. 20° E. and S. 20° W.	
40.06	The E 1/16 sec. cor. of secs. 22 and 27.	
	From the N 1/16 sec. cor. of secs. 26 and 27.	
	S. 89°45' W., on the E and W center line of the NE 1/4 of sec. 27.	
17.50	Arizona State Highway No. 188, asphalt surfaced, bears N. 35° E. and S. 35° W.	
19.725	The NE 1/16 sec. cor. of sec. 27.	
28.70	Fence, bears S. 15° E. and N. 15° W.	
39.405	The center N 1/16 sec. cor. of sec. 27.	

T. 7 N., R. 10 E., Gila and Salt River Mer., Arizona

CHAINS

GENERAL DESCRIPTION

The land encompassed in this survey is located about 5 miles north of Tonto Basin, Arizona, commonly referred to as Punkin Center. The area is drained by Tonto Creek which flows southerly into Roosevelt Lake. Elevation ranges from about 2,400 to 2,900 feet above sea level. The terrain varies from rolling to nearly level in the Tonto Creek bottom and on some of the mesas overlooking the creek. Vegetation consists of cat claw, palo verde, mesquite, creosote and cacti with juniper on some of the northern slopes and salt cedar and a few cottonwood trees along Tonto Creek.

Access is by way of Arizona State Highway No. 188 asphalt surfaced, which enters the area on the north boundary of section 10, traverses southerly and exits at the south boundary of section 27. Further access is provided by numerous dirt roads.

Kayler Spring is located in section 14. H Four Cemetary is located in the NW 1/4 of the SE 1/4 of section 15. Residences are located on patented land in sections 10, 11, 15 and 23.

Indian ruins are common on much of the mesa land east of Tonto Creek. The remains include scattered large stones that were used for dwellings, broken metates, pottery and flint chippings. Ruins are also present at Kayler Butte, the witness 1/4 sec. cor. of secs. 26 and 27 and at the center N 1/16 section cor. of section 22.

There is no evidence of mineral deposits or any active mining.

An average number of readings throughout the area surveyed gives a mean magnetic declination of 14° E., with a variation of 4° in local attraction.

CERTIFICATE OF SURVEY

(We), Harry K. Smith, Cadastral Surveyor, and John P. Bennett III, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 5th day of March, 1980, (We) have dependently resurveyed a portion of the subdivisional lines and surveyed subdivisions in sections 10, 11, 14, 15, 22, 23, 26 and 27 of Township 7 North, Range 10 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), (us) and under (my) (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 20, 1981 (Date)

Harry K. Smith (Cadastral Surveyor)

April 20, 1981 (Date)

John P. Bennett III (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Denver, Colorado Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and the survey of subdivisions in sections 10, 11, 14, 15, 22, 23, 26 and 27, of T. 7 N., R. 10 E., of the Gila and Salt River Meridian, Arizona,

executed by Harry K. Smith, Cadastral Surveyor, and John P. Bennett III, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

November 16, 1982 (Date)

James P. Kelley Chief Cadastral Survey Examination and Approval Staff Chief Cadastral Surveyor of Arizona

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date)

(Chief, Cadastral Survey Examination and Approval Staff)