

ORIGINAL

Form 9600-9
(December 1979)
(formerly 9180-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE EAST AND WEST BOUNDARIES

A PORTION OF THE SUBDIVISIONAL LINES

AND

THE SURVEY OF SUBDIVISIONS IN SECTIONS

1, 6, 7, 11, 12 AND 19

TOWNSHIP 5 SOUTH, RANGE 9 WEST

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

EXECUTED BY

Paul L. Reeves

Cadastral Surveyor

Under special instructions dated November 6, 19 78, approved November 7, 1978,

and Supplemental Special Instructions dated October 19, 1979 and approved

October 22, 1979, which provided for the surveys included under ~~U.S. Survey~~ XXXXXXXX Group
Number 608, and assignment instructions dated December 12, 19 78.

Survey commenced December 12, 19 78

Survey completed March 2, 19 82

INDEX DIAGRAM

Township 5 south, Range 9 west,

	6 16	5 15	4	3	2 12	1 11 11 10	5
7	7 14	15 8 14	9	10	11 12 11	10 12 4 9 8	
6	18 13	17	16	15	14	13	
5	19 13 12	20	21	22	23	24	
	30	29	28	27	26	25	
	31	32	33	34	35	36	

Section Subdivision

- Section 1 -- pp 16 to 17
- Section 6 -- pp 17 to 19
- Section 7 -- pp 19 to 20
- Section 11-- pp 20 to 23
- Section 12-- pp 23 to 26
- Section 19-- pp 26 to 28

T. 5 S., R. 9 W., Gila and Salt River Mer., Arizona

CHAINS

The history of surveys of Township 5 South, Range 9 West, Gila and Salt River Meridian, Arizona, is as follows:

The south boundary, (First Standard Parallel South) was surveyed by Theodore F. White in 1874, resurveyed by Lewis Wolfley in 1892 and resurveyed again by Anthony C. Kimmell in 1934.

The east and west boundaries were surveyed by Theodore F. White in 1877 and resurveyed by Anthony C. Kimmell and Daniel M. Wier in 1934.

The north boundary was surveyed by Theodore F. White in 1877 and resurveyed by Jesse B. Wright in 1914.

The subdivisional lines were surveyed by Theodore F. White in 1877. Sidney E. Blout resurveyed the boundaries of section 11, the S 1/2 mile between secs. 1 and 2, and the line between secs. 1 and 12 and lot 2 in sec. 11 in 1926. The subdivisional lines were resurveyed by William M. Heina, Daniel M. Wier and Jess R. Horak in 1934.

The following field notes are those of the dependent re-survey of a portion of the east and west boundaries, a portion of the subdivisional lines and the survey of subdivisions in sections 1, 6, 7, 11, 12 and 19, Township 5 South, Range 9 West, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 608, Arizona, dated November 6, 1978, and Supplemental Special Instructions dated October 19, 1979.

The directions of lines were determined by direct solar observations and refer to the true meridian.

Prior to restoration of any corners, the lines of the original survey were retraced and diligent search was made for any evidence of the original monuments and other calls of the official record. Identified corners were remonumented in their original positions. Lost corners were reestablished at proportionate positions based on the original record but not until exhausting every reasonable possibility of finding direct evidence for the control of each corner. The retracement data were thoroughly verified and only the true line field notes are given herein.

The survey was done with a Wild T-16 theodolite, Hewlett Packard 3805A Electronic distance meter and a Hewlett Packard 3820A total station instrument.

The geographic position of the SE corner of section 12, as scaled from the U.S. Geological Survey Quadrangle Map, "Sentinel, Arizona", prepared in 1950, is as follows:

Latitude: 32°59.9' N. Longitude: 113°08' W.

The mean magnetic declination is 14°30' E.

Dependent Resurvey of a Portion of the E Bdy.
T. 5 S., R. 9 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p>(Restoring the 1934 resurvey by Anthony C. Kimmell and Daniel M. Wier)</p> <hr/> <p>Beginning at the cor. of secs. 7, 12, 13, 18, monumented with an iron post, 2 ins. diam., projecting 36 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5S R9W R8W S12 S 7 S13 S18 1934</p> <p>N. 0°06' W., bet. secs. 7 and 12.</p> <p>Over rolling land, through medium creosote and scattered palo verde and cacti.</p>	
19.965	<p>Point for the S 1/16 sec. cor. of secs. 7 and 12.</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T5S R9W R8W S 1/16 S12 S7 1982</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p>	
39.93	<p>The 1/4 of secs. 7 and 12, monumented with an iron post, 1 in. diam., projecting 12 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S12 S7 1934</p> <p>Mound of stone, 2½ ft. base, 2 ft. high, W of cor.</p> <hr/> <p>N. 0°07' W., beginning new measurement.</p>	
20.06	<p>Point for the N 1/16 sec. cor. of secs. 7 and 12.</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T5S R9W R8W N 1/16 S12 S7 1982</p>	

Dependent Resurvey of a Portion of the E Bdy.
T. 5 S., R. 9 W., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p> <p>Cor. is located on a steep N slope, desc. into river bottom land.</p>
40.12	<p>Point for the cor. of secs. 1, 6, 7 and 12, at proportionate dist.; not monumented in the 1934 resurvey.</p> <p>Set an aluminum post, 72 ins. long, ¾ in. diam., 68 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>T5S R9W R8W S 1 S 6 S12 S 7 1982</p> </div> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in river bottom in dense salt cedar</p>
	<p>N. 0°07' W., bet. secs. 1 and 6.</p> <p>Over river bottom land, through dense salt cedar and weeds.</p>
2.885	<p>Point for the witness cor. of secs. 1, 6, 7 and 12, at proportionate dist.; there is no remaining evidence of the original cor., not remonumented.</p>
40.12	<p>Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate dist., falls on side of right bank of the Gila River, impracticable to monument.</p>
40.22	<p>The witness 1/4 sec. cor. of secs. 1 and 6, monumented with an iron post, 1 in. diam., projecting 10 ins. above ground, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>1/4 S1 S6 WC 1934</p> </div> <p>Cor. is located in an E and W fence line.</p>
	<p style="text-align: center;">Dependent Resurvey of a Portion of the W Bdy. T. 5 S., R. 9 W., Gila and Salt River Mer., Arizona</p>
	<p style="text-align: center;">(Restoring the 1934 resurvey by Anthony C. Kimmell and Daniel M. Wier)</p>
	<p>From the 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., projecting 13 ins. above ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the W Bdy.
T. 5 S., R. 9 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">1/4 S24 S19 1934</p>	
	<p>from which an 1877 bearing tree</p>	
	<p style="padding-left: 40px;">A mesquite, 5 ins. diam., bears West, 8 lks. dist., open blaze, no marks visible. (Record: 10 lks. dist.)</p>	
	<p>from which the 1934 bearing trees</p>	
	<p style="padding-left: 40px;">A mesquite, 12 ins. diam., bears S. 27½° E., 88 lks. dist., marks visible 19 BT. (Record: 86 lks. dist.)</p>	
	<p style="padding-left: 40px;">A mesquite, 10 ins. diam., bears S. 69° W., 164 lks. dist., marks visible 1/4 4 BT.</p>	
	<p>Cor. is located in a N and S fence line.</p>	
	<p>N. 0°07' W., bet. secs. 19 and 24.</p>	
	<p>Over gently rolling land, along a fence line, through medium creosote, sage brush and scattered mesquite.</p>	
20.33	<p>Point for the N 1/16 sec. cor. of secs. 19 and 24.</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T5S N 1/16 R10W R9W S24 S19 1979</p>	
	<p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W of cor</p>	
	<p>Cor. is located in a N and S fence line.</p>	
40.66	<p>The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2 ins. diam., projecting 8 ins. above ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T5S R10W R9W S13 S18 S24 S19 1934</p>	
	<p>Cor. is located at a fence cor., fences extend E and S.</p>	
	<p>From the 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., projecting 36 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of the W Bdy.
T. 5 S., R. 9 W., Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">1/4 S13 S18 1934</p>
	<p>from which</p>
	<p>A palo verde, 7 ins. diam., bears N. 74° E., 74 lks. dist., partly rotted blaze, illegible scribed marks visible.</p>
	<p>A palo verde, 9 ins. diam., bears S. 66° W., 164 lks. dist., no marks visible.</p>
	<p>N. 0°37' W., bet. secs. 13 and 18.</p>
	<p>Over rocky rolling land, through medium creosote.</p>
20.21	<p>Point for the N 1/16 sec. cor. of secs. 13 and 18.</p>
	<p>Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 28 ins. in the ground, with cap mkd.</p>
	<p style="text-align: center;">T5S</p>
	<p style="text-align: center;">R10S R9W</p>
	<p style="text-align: center;">N 1/16</p>
	<p style="text-align: center;">S13 S18</p>
	<p style="text-align: center;">1982</p>
	<p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p>
29.20	<p>Bluff, bears S. 85° E. and N. 85° W., with numerous Indian markings on face of bluff, thence over river bottom land, through dense salt cedar and mesquite.</p>
40.42	<p>Point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, with cap mkd.</p>
	<p style="text-align: center;">T5S</p>
	<p style="text-align: center;">R10W R9W</p>
	<p style="text-align: center;">S12 S 7</p>
	<p style="text-align: center;">S13 S18</p>
	<p style="text-align: center;">1982</p>
	<p>Cor. is located 6 lks. W of a N and S fence line.</p>
	<p>N. 0°37' W., bet. secs. 7 and 12.</p>
	<p>Over river bottom land, through medium salt cedar and mesquite.</p>
40.42	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented with an iron post, 1 in. diam., projecting 8 ins. above ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the W Bdy.
T. 5 S., R. 9 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">1/4 S12 S 7 1934</p> <p>from which</p> <p style="padding-left: 40px;">A stump hole of the remains of a palo verde, 10 ins. diam. bears N. 61½° E., 91 lks. dist., mkd. BT.</p> <p>Cor. is located 2 lks. S of a fence cor., fences extend N, S and W.</p> <hr/> <p>Dependent Resurvey, a Portion of the Subdivisional Lines, T. 5 S., R. 9 W., Gila and Salt River Mer., Arizona</p> <hr/> <p style="text-align: center;">(Restoring the 1934 resurvey by William M. Heina, Daniel M. Wier and Jess R. Horak)</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E bdy. of Tp., heretofore described</p> <p>N. 89°01' W., bet. secs. 12 and 13.</p> <p>Over nearly level mesa, through medium creosote, scattered palo verde and ironwood.</p>	
12.20	Desc. from mesa.	
19.945	<p>Point for the E 1/16 sec. cor. of secs. 12 and 13.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T5S R9W E 1/16 $\frac{S12}{S13}$ 1982</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.</p>	
39.89	<p>The 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 1 in. diam., projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 $\frac{S12}{S13}$ 1934</p> <p>Mound of stone, 2½ ft. base, 2½ ft. high, N of cor.</p> <p>from which</p> <p style="padding-left: 40px;">A power pole, bears N. ½° W., 113 lks. dist., powerline extends N. 1½° E.</p> <p style="padding-left: 40px;">A fence cor., bears N. 77° E., 44 lks. dist., fences extend N and W.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 5 S., R. 9 W., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Center of pump over well, bears N. 67° W., 42 lks. dist.</p> <hr/> <p>N. 89°10' W., beginning new measurement.</p>
19.97	<p>Point for the W 1/16 sec. cor. of secs. 12 and 13.</p> <p>Set an aluminum post, 30 ins. long, $\frac{3}{4}$ in. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T5S R9W W 1/16 $\frac{S12}{S13}$ 1982</p> <p>Cor. is located 3 lks. S of an E and W fence line.</p>
39.94	<p>The cor. of secs. 11, 12, 13 and 14, monumented with an iron post, 2 ins. diam., projecting 15 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R9W $\frac{S11}{S14} \frac{S12}{S13}$ 1926</p> <p>Mound of stone, $1\frac{1}{2}$ ft. base, 1 ft. high, N of cor.</p> <hr/> <p>N. 0°05' E., bet. secs. 11 and 12.</p> <p>Over bottom land, through dense mesquite.</p>
17.00	<p>Leave dense brush, edge bears E and W, thence over cultivated field.</p>
20.03	<p>Point for the S 1/16 sec. cor. of secs. 11 and 12.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R9W S 1/16 S11 S12 1982</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 8 lks. E of center of a concrete lined irrigation ditch, bears S. 3° E. and N. 3° W., bet. cultivated fields.</p>
40.06	<p>Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 24 ins. below surface of cultivated field, with cap mkd.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 5 S., R. 9 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T5S R9W 1/4 S11 S12 1982</p> <p>from which</p> <p style="text-align: center;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 60° W., 186.7 lks. dist., with brass cap mkd. T5S R9W 1/4 S11 RM 123.2 ft. 1982 and an arrow pointing to the cor.</p> <p>Set a steel fence post alongside the reference monument.</p>	
42.20	<p>Leave cultivated field, edge bears E and W, thence through dense weeds, creosote and scattered mesquite.</p>	
60.08	<p>Point for the N 1/16 sec. cor. of secs. 11 and 12.</p> <p>Set an iron post 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R9W N 1/16 S11 S12 1982</p> <p>Set a steel fence post alongside the cor.</p> <p>Continue over river bottom land, through dense weeds and salt cedar.</p>	
80.10	<p>Point for the cor. of secs. 1, 2, 11 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 72 ins. long, ¾ in. diam., 68 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T5S R9W S 2 S 1 S11 S12 1982</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located on a sandbar in river bottom.</p>	
19.885	<p>From the cor. of secs. 1, 6, 7 and 12, on the E bdy. of Tp., heretofore described.</p> <p>N. 89°03' W., bet. secs. 1 and 12.</p> <p>Over river bottom land, through dense salt cedar.</p> <p>Point for the E 1/16 sec. cor. of secs. 1 and 12.</p> <p>Set an aluminum post, 72 ins. long, ¾ in. diam., 68 ins. in the ground, with cap mkd.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 5 S., R. 9 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T5S R9W E 1/16 $\frac{S 1}{S 12}$ 1982</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in river bottom in dense salt cedar.</p>	
39.77	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 72 ins. long, $\frac{3}{4}$ in. diam., 68 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">T5S R9W 1/4 $\frac{S 1}{S 12}$ 1982</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in river bottom in dense salt cedar.</p>	
79.54	<p>The cor. of secs. 1, 2, 11 and 12.</p> <hr/> <p>N. 0°42' W., bet. secs. 1 and 2.</p> <p>Over river bottom land, through dense salt cedar.</p>	
40.04	<p>The 1/4 sec. cor. of secs. 1 and 2, monumented with the rusted remains of an iron post, 1 in. diam., firmly set flush with the ground. A 12 in. long sec. of the iron post was found lying loose alongside, with brass cap mkd.</p> <p style="text-align: center;">1/4 S 2 S 1 1926</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T5S R9W 1/4 S 2 S 1 1978</p> <p>Deposit the remains of the iron post alongside the cor.</p> <p>Raise a mound of stone $2\frac{1}{2}$ ft. base, 1 ft. high, W of cor.</p>	
	<hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89°21' W., bet. secs. 11 and 14.</p> <p>Over rolling land, through scattered palo verde and creosote.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 5 S., R. 9 W., Gila and Salt River Mer., Arizona

CHAINS		
19.95	<p>Point for the E 1/16 sec. cor. of secs. 11 and 14.</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 28 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T5S R9W E 1/16 $\frac{S11}{S14}$ 1982</p>	
39.90	<p>Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, N of cor.</p> <p>The 1/4 sec. cor. of secs. 11 and 14, monumented with an iron post, 1 in. diam., projecting 36 ins. above ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S11}{S14}$ 1926</p>	
39.97	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. $89^{\circ}01'$ W., bet. secs. 2 and 11.</p> <p>Over river bottom land, through dense salt cedar.</p> <p>The 1/4 sec. cor. of secs. 2 and 11, monumented with an iron post, 1 in. diam., projecting 15 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S 2}{S11}$ 1926</p> <p>Mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N of cor.</p>	
39.96	<p>From the cor. of secs. 19, 20, 29 and 30, monumented with an iron post, 2 ins. diam., projecting 30 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5S R9W S19 S20 S30 S29 1934</p> <p>S. $87^{\circ}55'$ W., bet. secs. 19 and 30.</p> <p>Over rolling land, through scattered palo verde, creosote and saguaro.</p> <p>The 1/4 sec. cor. of secs. 19 and 30, monumented with an iron post, 1 in. diam., projecting 24 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 5 S., R. 9 W., Gila and Salt River Mer., Arizona

CHAINS	
	$\frac{1}{4} \frac{S19}{S30}$ <p style="text-align: center;">1934</p> <hr/> <p>N. 85°11' W., beginning new measurement.</p>
20.01	<p>Point for the W 1/16 sec. cor. of secs. 19 and 30.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> $\begin{array}{c} T5S R9W \\ W 1/16 \frac{S19}{S30} \\ 1979 \end{array}$
39.83	<p>The cor. of secs. 19, 24, 25 and 30, on the W bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 24 ins. above ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p> $\begin{array}{c} T5S \\ R10W \quad \quad R9W \\ \frac{S24}{S25} \quad \quad \frac{S19}{S30} \\ 1934 \end{array}$ <p>from which</p> <p style="padding-left: 40px;">A dead palo verde, 6 ins. diam., bears N. 49½° E., 272 lks. dist., rotted blaze, no marks visible.</p> <p style="padding-left: 40px;">A dead palo verde, 10 ins. diam., bears N. 58½° W., 230 lks. dist., rotted blaze, no marks visible.</p> <p>Cor. is located in a N and S fence line.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 18 and 19, monumented with an iron post, 1 in. diam., projecting 36 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> $\frac{1}{4} \frac{S18}{S19}$ <p style="text-align: center;">1934</p> <p>from which</p> <p style="padding-left: 40px;">A palo verde, 11 ins. diam., bears S. 37° E., 242 lks. dist., decayed blaze, no marks visible. (Record: 237 lks. dist.)</p> <p>N. 89°09' W., bet. secs. 18 and 19.</p> <p>Over gently rolling land, through medium creosote, sage brush and scattered mesquite.</p>
20.02	<p>Point for the W 1/16 sec. cor. of secs. 18 and 19.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 5 S., R 9 W., Gila and Salt River Mer., Arizona

CHAINS		
40.15	<p style="text-align: center;">T5S R9W W 1/16 $\frac{S18}{S19}$ 1979</p> <p>Deposit broken glass at base of iron post.</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N of cor.</p> <p>A fence cor., bears N. 57° W., 61 lks. dist., fences extend NE and W.</p> <p>The cor. of secs. 13, 18, 19 and 24, on the W bdy. of the Tp., heretofore described.</p>	
40.20	<p>From the 1/4 sec. cor. of secs. 7 and 18, monumented with an iron post, 1 in. diam., projecting 2 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">$\frac{S 7}{1/4 S18}$ 1934</p> <p>N. 89°01' W., bet. secs. 7 and 18.</p> <p>Over river bottom land, through dense salt cedar.</p> <p>The cor. of secs. 7, 12, 13 and 18, on the W bdy. of Tp., heretofore described.</p>	
40.30	<p>From the cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 2 ins. diam., 2 ins. below ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R9W $\frac{S 7 S 8}{S18 S17}$ 1934</p> <p>Cor. is located in flow area of river bottom.</p> <p>N. 0°10' W., bet. secs. 7 and 8.</p> <p>Over river bottom land, through medium weeds and salt cedar.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, ¼ in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T5S R9W 1/4 S 7 S 8 1982</p> <p>Raise a mound of stone, 2½ ft. base, 1 ft. high, W of cor.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 5 S., R. 9 W., Gila and Salt River Mer., Arizona

CHAINS	
	Cor. is located in flood area of river bottom.
49.20	Right bank of Gila River, bears N. 75° E. and S. 75° W., thence over nearly level land, through medium creosote, palo verde and mesquite.
60.445	Point for the N 1/16 sec. cor. of secs. 7 and 8.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T5S R9W N 1/16 S 7 S 8 1982 </div>
	Set a mesquite post, 5 ins. diam., 6½ ft. long, alongside the cor.
80.59	The cor. of secs. 5, 6, 7 and 8, monumented with an iron post, 2 ins. diam., projecting 18 ins. above ground, with brass cap mkd.
	<div style="text-align: center;"> T5S R9W S 6 S 5 S 7 S 8 1934 </div>
	N. 88°48' W., bet. secs. 6 and 7.
	Over gently rolling land, through medium creosote and mesquite.
20.34	Point for the E 1/16 sec. cor. of secs. 6 and 7.
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T5S R9W E 1/16 $\frac{S 6}{S 7}$ 1979 </div>
	Set a mesquite post, 4 ins. diam., 6 ft. long, alongside the cor.
40.68	The 1/4 sec. cor. of secs. 6 and 7, monumented with an iron post, 1 in. diam., 36 ins. long, buried 24 ins. below ground, with brass cap erroneously mkd.
	<div style="text-align: center;"> W. C. 1/4 $\frac{S 6}{S 7}$ 1934 </div>
	Reset the iron post, 26 ins. in the ground.
	Remove the marks W.C. from the brass cap and add the marks 1979.

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 5 S., R. 9 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p>from which new bearing trees</p> <p>A palo verde, 7 ins. diam., bears N. 72° E., 79 lks. dist., mkd. 1/4 S6 BT.</p> <p>A mesquite, 13 ins. diam., bears S. 11° E., 22 lks. dist., mkd. 1/4 S7 BT.</p> <p>Set a mesquite post, 6 ins. diam., 5½ ft. long, alongside the cor.</p>	
	<p>N. 88°49' W., beginning new measurement.</p>	
40.24	<p>The cor. of secs. 1, 6, 7 and 12, on the W bdy. of the Tp., monumented with an iron post, 2 ins. diam, projecting 14 ins. above ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T5S R10W R9W S 1 S 6 S12 S 7 1934</p>	
	<p>Cor. is located 2 lks. N of a fence cor., fences extend N, S and W.</p>	
	<p style="text-align: center;">Subdivision of Section 1, T. 5 S., R. 9 W. Gila and Salt River Mer., Arizona</p>	
	<p>From the 1/4 sec. cor. of secs. 1 and 12.</p>	
	<p>N. 0°15' W., on the N and S center line of sec. 1.</p>	
	<p>Over river bottom land, through dense salt cedar.</p>	
23.60	<p>Right bank of Gila River, bears E and W, thence over level land, through dense weeds and scattered mesquite.</p>	
40.08	<p>Point for the center 1/4 sec. cor., at intersection with the E and W center line of sec. 1.</p>	
	<p>Set an aluminum post, 30 ins. long, ¾ in. diam., 26 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">T5S R9W C 1/4 S1 1982</p>	
	<p>Set a steel fence post alongside the cor.</p>	
	<p>Fence cor. bears N. 80° W., 40 lks. dist., fences extend N and E.</p>	
	<p>Cor. is located 100 lks. E of a track road, bears N and S, and 245 lks. E of a power line, bears S. 10° E. and N. 10° W.</p>	
	<p>Thence along W edge of a cultivated field.</p>	

Subdivision of Section 1, T. 5 S., R. 9 W.
Gila and Salt River Mer., Arizona

CHAINS	
80.34	<p>The 1/4 sec. cor. of secs. 1 and 36, on the N bdy. of Tp., monumented with an iron post, 1 in. diam., projecting 15 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"> $\frac{S36}{1/4 S 1}$ 1914 </p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, N of cor.</p> <p>Add the marks 1982 to the cap.</p> <p>Cor. is located in a N and S fence line.</p>
39.86	<p>From the true point for the 1/4 sec. cor. of secs. 1 and 6, on the E bdy. of the Tp.</p> <p>N. 89°06' W., on the E and W center line of sec. 1.</p> <p>Over level land, along a fence line, with a cultivated field to N and dense mesquite to S.</p> <p>The center 1/4 sec. cor. of sec. 1.</p> <p>Continue over nearly level land, through scattered mesquite and sage brush.</p>
79.94	<p>The 1/4 sec. cor. of secs. 1 and 2.</p>
<p>Subdivision of Section 6, T. 5 S., R. 9 W. Gila and Salt River Mer., Arizona</p>	
40.05	<p>From the 1/4 sec. cor. of secs. 6 and 7.</p> <p>N. 0°14' E., on the N and S center line of sec. 6.</p> <p>Over gently rolling land, through medium creosote and mesquite.</p> <p>Point for the center 1/4 sec. cor., at intersection with the E and W center line of sec. 6.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T5S R9W C 1/4 S6 1979 </p> <p>from which</p> <p style="text-align: center;"> A palo verde, 9 ins. diam., bears S. 84° E., 18 lks. dist., mkd. C 1/4 S6 BT. </p> <p>Set an ironwood post, 4 ins. diam., 8 ft. long, alongside the cor.</p>

Subdivision of Section 6, T. 5 S., R. 9 W.
Gila and Salt River Mer., Arizona

CHAINS

80.29

The 1/4 sec. cor. of sec. 6 only, on the N bdy. of the Tp., monumented with the rusted remains of an iron post, 1 in. diam., projecting 10 ins. above ground, with brass cap mkd.

1/4
S6
1914

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.

T4S R9W
1/4 S6
T5S R9W
1979

Deposit the remains of the iron post alongside the cor.

Set an ironwood post, 4 ins. diam., 6 ft. long, alongside the cor.

Cor. is located 42 lks. N of a powerline, bears E and W, and 125 lks. N of a track road, bears E and W.

From the 1/4 sec. cor. of secs. 5 and 6, monumented with the rusted remains of an iron post, 1 in. diam., projecting 10 ins. above ground, with brass cap mkd.

1/4
S 6 | S 5
1934

from which an 1877 bearing tree

An ironwood, 10 ins. diam., bears S. 32° E., 182 lks. dist., no marks visible. (1934 record 180 lks. dist., 14 ins. diam.)

Found clear glass jar at base of iron post.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.

T5S R9W
1/4
S 6 | S 5
1979

Deposit the remains of the iron post and glass jar alongside the cor.

Set an ironwood post, 5 ins. diam., 5½ ft. long, alongside the cor.

N. 89°01' W., on the E and W center line of sec. 6.

Subdivision of Section 6, T. 5 S., R. 9 W.
Gila and Salt River Mer., Arizona

CHAINS		
	<p>Over rolling land, through medium creosote and scattered ironwood, palo verde and mesquite.</p>	
20.25	<p>Point for the center E 1/16 sec. cor. of sec. 6.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R9W E 1/16 G-----C S6 1979</p> <p>from which</p> <p style="text-align: center;">A palo verde, 14 ins. diam., bears S. 80° W., 228 lks. dist., mkd. C-E 1/16 S6 BT.</p> <p>Raise a mound of stone, 2 ft. base, 1½ ft. high, N of cor.</p>	
40.50	<p>The center 1/4 sec. cor. of sec. 6.</p>	
80.42	<p>The 1/4 sec. cor. of secs. 1 and 6, on the W bdy. of the Tp., monumented with an iron post, 1 in. diam., projecting 5 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S 1 S 6 1934</p> <p>from which</p> <p style="text-align: center;">A mesquite, 14 ins. diam., bears N. 76 1/4° E., 223 lks. dist., marks visible 6 BT.</p> <p>Cor. is located in a N and S fence line.</p>	
	<p>Subdivision of Section 7, T. 5 S., R. 9 W. Gila and Salt River Mer., Arizona</p>	
40.34	<p>From the 1/4 sec. cor. of secs. 7 and 18.</p> <p>N. 0°34' W., on the N and S center line of sec. 7.</p> <p>Over river bottom land, through dense salt cedar and scattered mesquite.</p> <p>Point for the center 1/4 sec. cor., at intersection with the E and W center line of sec. 7.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R9W C 1/4 S7 1982</p>	

Subdivision of Section 7, T. 5 S., R. 9 W.
Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T5S R9W C 1/4 S7 1982</p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">A mesquite, 16 ins. diam., bears S. 28° W., 107 lks. dist., mkd. C 1/4 S7 BT.</p>	
	<p style="padding-left: 40px;">A mesquite, 8 ins. diam., bears N. 32° W., 129 lks. dist., mkd. C 1/4 S7 BT.</p>	
	<p>Continue over level land through dense mesquite, palo verde and creosote.</p>	
60.53	<p>Point for the center N 1/16 sec. cor. of sec. 7.</p>	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">T5S R9W C N 1/16 S 7 C 1982</p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">A mesquite, 7 ins. diam., bears S. 71° E., 54 lks. dist., mkd. C-N 1/16 S7 BT.</p>	
	<p>Set a mesquite post, 6 ft. long, 4 ins. diam., alongside the cor.</p>	
80.72	<p>The 1/4 sec. cor. of secs. 6 and 7.</p>	
	<p>From the 1/4 sec. cor. of secs. 7 and 8.</p>	
	<p>N. 88°56' W., on the E and W center line of sec. 7.</p>	
	<p>Over river bottom land, through medium salt cedar.</p>	
17.00	<p>Right bank of Gila River, bears N. 55° E. and S. 55° W., thence through dense mesquite, palo verde and creosote.</p>	
40.39	<p>The center 1/4 sec. cor. of sec. 7.</p>	
80.62	<p>The 1/4 sec. cor. of secs. 7 and 12, on the W bdy. of Tp.</p>	
<p>Subdivision of Section 11, T. 5 S., R. 9 W. Gila and Salt River Mer., Arizona</p>		
	<p>From the 1/4 sec. cor. of secs. 11 and 14.</p>	
	<p>N. 0°02.5' E., on the N and S center line of sec. 11.</p>	
	<p>Over rolling land, through medium creosote, palo verde and scattered cacti.</p>	

Subdivision of Section 7, T. 5 S., R. 9 W.
Gila and Salt River Mer., Arizona

CHAINS	
16.00	Begin desc. along E face of slope.
16.50	Old wagon road, bears E and W.
20.055	Point for the center S 1/16 sec. cor. of sec. 11.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, with cap mkd.
	<p style="text-align: center;">T5S R9W C S 1/16 S11 C 1982</p>
	Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, W of cor.
	Cor. is located on E face of steep slope.
28.00	Enter river bottom land, edge bears S and NW, thence through dense salt cedar.
40.11	Point for the center 1/4 sec. cor., at intersection with the E and W center line of sec. 11.
	Set an aluminum post, 72 ins. long, $\frac{3}{4}$ in diam., 68 ins. in the ground, with cap mkd.
	<p style="text-align: center;">T5S R9W C 1/4 S11 1982</p>
	Set a steel fence post alongside the cor.
80.33	The 1/4 sec. cor. of secs. 2 and 11.
	From the 1/4 sec. cor. of secs. 11 and 12.
	N. $89^{\circ}17'$ W., on the E and W center line of sec. 11.
	Over cultivated field.
1.20	W edge of cultivated field bears N and S, thence through dense mesquite and weeds.
19.96	Point for the center E 1/16 sec. cor. of sec. 11.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T5S R9W E 1/16 G-----C S11 1982</p>
	Set a steel fence post alongside the cor.
25.90	Fence line, bears N and S.

Subdivision of Section 11, T. 5 S., R. 9 W.
Gila and Salt River Mer., Arizona

CHAINS		
26.90	Enter river bottom, edge bears NE and SW, thence through dense salt cedar.	
39.92	The center 1/4 sec. cor. of sec. 11.	
79.85	The 1/4 sec. cor. of secs. 10 and 11, monumented with an iron post, 1 in. diam., projecting 3 ins. above ground, with brass cap mkd.	
	1/4 S10 S11 1926	
	Mound of stone, 3 ft. base, 2 ft. high, W of cor.	
	SE 1/4 of Section 11 <hr style="width: 20%; margin: auto;"/>	
	From the E 1/16 sec. cor. of secs. 11 and 14.	
	N. 0°03.5' E., on the N and S center line of the SE 1/4 of sec. 11.	
	Over rolling land, through scattered creosote.	
20.05	Point for the SE 1/16 sec. cor., at intersection with the E and W center line of the SE 1/4 of sec. 11.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	T5S R9W SE 1/16 S11 1982	
	Set a steel fence post alongside the cor.	
	From this point Cor. 3 of Lot 2, bears N. 40°52' W., 5.33 chs. dist., monumented with an iron post, 1 in. diam., projecting 18 ins. above ground, with brass cap mkd.	
	3 OF └─── 1926	
	Steel fence post alongside the cor.	
40.09	The center E 1/16 sec. cor. of sec. 11.	
	From the S 1/16 sec. cor. of secs. 11 and 12,	
	N. 89°19.5' W., on the E and W center line of the SE 1/4 of sec. 11.	
	Over cultivated land.	
9.50	Leave cultivated field, edge bears S. 35° E. and N. 35° W., thence through dense mesquite.	

Subdivision of Section 11, T. 5 S., R. 9 W.
Gila and Salt River Mer., Arizona

CHAINS	
19.955	The SE 1/16 sec. cor. of sec. 11.
39.91	The center S 1/16 sec. cor. of sec. 11.
Subdivision of Section 12, T. 5 S., R. 9 W. Gila and Salt River Mer., Arizona	
From the 1/4 sec. cor. of secs. 12 and 13.	
N. 0°02' W., on the N and S center line of sec. 12.	
Over level land, along W edge of track road.	
19.70	Track roads, extend E, S and W.
19.97	Point for the center S 1/16 sec. cor. of sec. 12.
Chiseled a cross on N side of a concrete lined irrigation ditch, bears E and W.	
from which	
An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 34½° E., 86.8 lks. dist., with brass cap mkd. T 5 S R 9 W C-S 1/16 S12 RM 57.3 FT. 1982 and an arrow pointing to the cor.	
A powerpole, bears S. 34° E., 90 lks. dist., power line, extends N. 60° E. and S. 1½° W.	
Continue over cultivated field.	
39.94	Point for the center 1/4 sec. cor., at intersection with the E and W center line of sec. 12.
Set an aluminum post, 36 ins. long, ¾ in. diam., 24 ins. below surface of cultivated field, with cap mkd.	
T5S R9W C 1/4 S12 1982	
53.40	Leave cultivated field, edge bears E and W, thence over river bottom land through weeds, salt cedar and scattered mesquite.
59.98	Point for the center N 1/16 sec. cor. of sec. 12.
Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.	
T5S R9W C N 1/16 S12 C 1982	
Set a steel fence post alongside the cor.	

Subdivision of Section 12, T. 5 S., R. 9 W.
Gila and Salt River Mer., Arizona

CHAINS	
	A fence cor., bears N. 29° E., 189 lks. dist., fences extend S and W.
80.02	The 1/4 sec. cor. of secs. 1 and 12.
	From the 1/4 sec. cor. of secs. 7 and 12, on the E bdy. of Tp.
	N. 89°00' W., on the E and W center line of sec. 12.
	Over rolling land, through medium creosote and scattered palo verde and cacti.
19.30	Desc. over steep NW slope.
19.915	Point for the center E 1/16 sec. cor. of sec. 12.
	Set an iron post, 28 ins. long, 2½ ins. diam., on exposed rock, in a mound of stone, 2½ ft. base, to top, against a rock ledge, with brass cap mkd.
	T5S R9W E 1/16 C-----C S12 1982
	Cor. is located on a steep NW face of a slope.
26.20	Base of desc.
29.00	Track road, bears N and S. 20° W.
29.20	Concrete lined irrigation ditch, bears N and S. 20° W., thence over cultivated field.
39.83	The center 1/4 sec. cor. of sec. 12.
59.755	Point for the center W 1/16 sec. cor. of sec. 21, not monumented.
79.68	The 1/4 sec. cor. of secs. 11 and 12.
	NE 1/4 of Section 12
	From the center E 1/16 sec. cor. of sec. 12.
	N. 0°04' W., on the N and S center line of the NE 1/4 of sec. 12.
	Over rolling land, through medium creosote, scattered palo verde and cacti.
16.20	Desc. from mesa, edge bears NE and SW.
20.05	Point for the NE 1/16 sec. cor., at intersection with the E and W center line of the NE 1/4 of sec. 12.

Subdivision of Section 12, T. 5 S., R. 9 W.
Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T5S R9W NE 1/16 S12 1982</p>	
40.10	<p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W of cor.</p> <p>Cor. is located at base of a steep NW slope.</p> <p>The E 1/16 sec. cor. of secs. 1 and 12.</p>	
19.90	<p>From the N 1/16 sec. cor. of secs. 7 and 12, on the E bdy. of Tp.</p> <p>N. $89^{\circ}01'$ W., on the E and W center line of the NE 1/4 of sec. 12.</p> <p>Along N slope of mesa.</p> <p>The E 1/16 sec. cor. of secs. 1 and 12.</p>	
39.80	<p>Continue over nearly level land, through dense weeds and scattered mesquite.</p> <p>The center N 1/16 sec. cor. of sec. 12.</p>	
19.97	<p style="text-align: center;">SE 1/4 of Section 12</p> <p>From the E 1/16 sec. cor. of secs. 12 and 13.</p> <p>N. $0^{\circ}04'$ W., on the N and S center line of the SE 1/4 of sec. 12.</p> <p>Over rolling land, through medium creosote, scattered palo verde and cacti.</p> <p>Point for the SE 1/16 sec. cor., at intersection with the E and W center line of the SE 1/4 of sec. 12.</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T5S R9W SE 1/16 S12 1982</p>	
39.94	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Cor. is located on a small spur, sloping E.</p> <p>The center E 1/16 sec. cor. of sec. 12.</p> <p>From the S 1/16 sec. cor. of secs. 7 and 12, on the E bdy. of Tp.</p>	

Subdivision of Section 12, T. 5 S., R. 9 W.
Gila and Salt River Mer., Arizona

CHAINS	
	N. 89°00' W., on the E and W center line of the SE 1/4 of sec. 12.
	Over rolling land, through medium creosote, scattered palo verde and cacti.
19.93	The SE 1/16 sec. cor. of sec. 12.
39.86	The center S 1/16 sec. cor. of secs. 12.
SW 1/4 of Section 12	
	From the W 1/16 sec. cor. of secs. 12 and 13.
	N. 0°01' E., on the N and S center line of the SW 1/4 of sec. 12.
	Over level open land.
15.60	Fence line, bears N. 70° E. and W., thence over cultivated field.
20.00	Point for the SW 1/16 sec. cor., at intersection with the E and W center line of the SW 1/4 of sec. 12.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 24 ins. below surface of cultivated field, with cap mkd.
T5S R9W SW 1/16 S12 1982	
40.00	The center W 1/16 sec. cor. point of sec. 12.
From the center S 1/16 sec. cor. of sec. 12.	
	N. 89°05' W , on the E and W center line of the SW 1/4 of sec. 12.
	Over cultivated field.
19.95	The SW 1/16 sec. cor. of sec. 12.
39.90	The S 1/16 sec. cor. of secs. 11 and 12.
Subdivision of Section 19, T. 5 S., R. 9 W., Gila and Salt River Mer., Arizona	
From the 1/4 sec. cor. of secs. 19 and 30.	
	N. 0°17' E., on the N and S center line of sec. 19.
	Over rolling land, through medium creosote and scattered cacti.
43.25	Point for the center 1/4 sec. cor., at intersection with the E and W center line of sec. 19.

Subdivision of Section 19, T. 5 S., R. 9 W.
Gila and Salt River Mer., Arizona

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T5S R9W C 1/4 S19 1979</p>
	Set a mesquite post, 4 ins. diam., 6 ft. long, alongside the cor.
63.68	Point for the center N 1/16 sec. cor. of sec. 19.
	Set an iron post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T5S R9W C N 1/16 S19 C 1979</p>
	Raise a mound of stone, 2½ ft. base, 2½ ft. high, W of cor.
84.11	The 1/4 sec. cor. of secs. 18 and 19.
	From the 1/4 sec. cor. of secs. 19 and 20, monumented with an iron post, 1 in. diam., projecting 15 ins. above ground, with brass cap mkd.
	<p style="text-align: center;">1/4 S19 S20 1934</p>
	Mound of stone, 3 ft. base, 2½ ft. high, W of cor.
	N. 88°50' W., on the E and W center line of sec. 19.
	Over rolling land, through medium creosote and scattered mesquite.
40.07	The center 1/4 sec. cor. of sec. 19.
60.04	Point for the center W 1/16 sec. cor. of sec. 19.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T5S R9W W 1/16 C—C S19 1979</p>
	Set a mesquite post, 4 ins. diam., 6½ ft. long, alongside the cor.
79.96	The 1/4 sec. cor. of secs. 19 and 24, on the W bdy. of the Tp.
	<p style="text-align: center;">NW 1/4 of Section 19</p> <hr style="width: 20%; margin: auto;"/>

Subdivision of Section 19, T. 5 S., R. 9 W.
Gila and Salt River Mer., Arizona

CHAINS		
	<p>From the center W 1/16 sec. cor. of sec. 19.</p> <p>N. 0°12' E., on the N and S center line of the NW 1/4 of sec. 19.</p> <p>Over gently rolling land, through medium creosote and scattered mesquite.</p>	
20.38	<p>Point for the NW 1/16 sec. cor., at intersection with the E and W center line of the NW 1/4 of sec. 19.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R9W NW 1/16 S19 1979</p>	
40.76	<p>Set a mesquite post, 4 ins. diam., 6½ ft. long, alongside the cor.</p> <p>The W 1/16 sec. cor. of secs. 18 and 19.</p> <hr style="width: 20%; margin: 10px auto;"/>	
20.00	<p>From the center N 1/16 sec. cor. of sec. 19.</p> <p>N. 89°00' W., on the E and W center line of the NW 1/4 of sec. 19.</p> <p>Over gently rolling land, through medium creosote and scattered mesquite.</p>	
40.03	<p>The NW 1/16 sec. cor. of sec. 19.</p> <p>The N 1/16 sec. cor. of secs. 19 and 24, on the W bdy. of the Tp.</p>	
GENERAL DESCRIPTION		
<p>The land encompassed in this survey is located approximately 8 miles southeast of the small farm community of Hyder, Arizona. Elevation ranges from 460 to 630 feet above sea level.</p>		
<p>The Gila River drains through the north portion of the township in a westerly direction.</p>		
<p>Access is by way of numerous unimproved or lightly gravelled roads.</p>		
<p>The vegetation consists of creosote, palo verde, mesquite and cacti, with dense salt cedar in the river bottom. Most of the private land in sections 1, 11 and 12, is under cultivation.</p>		
<p>There is no evidence of mining activity in the area</p>		

Form 9600-11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
John P. Bennett III	Surveying Technician
John J. Bulinski	Survey Aid
William Anderson	Survey Aid
Dan Simpson	Survey Aid
Victor A. Hansen	Survey Aid
Donald L. Brewer	Survey Aid
Delbert L. Bybee	Survey Aid

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Paul L. Reeves, Cadastral Surveyor, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 6th day of November, 1978, ~~(by special)~~ and supplemental special instructions dated October 19, 1979, I have dependently resurveyed a portion of the east and west boundaries, a portion of the subdivisional lines and surveyed subdivisions in sections 1, 6, 7, 11, 12 and 19, Township 5 South, Range 9 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

2/03/83
(Date)

Paul L. Reeves
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
~~Denver, Colorado~~
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the east and west boundaries, a portion of the subdivisional lines and a survey of subdivisions in sections 1, 6, 7, 11, 12 and 19, Township 5 South, Range 9 West, Gila and Salt River Meridian, Arizona,

executed by Paul L. Reeves, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

FEB 04 1983
(Date)

James P. Kelley
~~(Chief, Cadastral Survey Examination and Approval Staff)~~
(Chief, Cadastral Surveyor of Arizona)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

~~(Chief, Cadastral Survey Examination and Approval Staff)~~
(Chief, Cadastral Surveyor of Arizona)