

ORIGINAL
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A PORTION OF THE SOUTH BOUNDARY

(BLACK MESA FOREST RESERVE)

TOWNSHIP 12 NORTH, RANGE 11 EAST

AND

A PORTION OF THE EAST BOUNDARY

AND

SUBDIVISIONAL LINES

AND

A SURVEY OF SUBDIVISIONS IN

SECTIONS 24, 25 AND 26

TOWNSHIP 11½ NORTH, RANGE 11 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Paul L. Reeves, Supervisory Cadastral Surveyor

John P. Bennett III, Supervisory Cadastral Surveyor

Under special instructions dated October 2, 19 81, approved October 2, 1981,

, which provided for the surveys included under U.S. Survey/Group
Number 625, and assignment instructions dated October 2, 19 81.

Survey commenced November 10, 19 81

Survey completed March 30, 19 83

INDEX DIAGRAM

Township 11½ North, Range 11 East,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13 Sec. 34 4
19	20	21	22	23	16 24 9 21 14
30	29	28	27	20 26	11 25 6 10
31	32	33	34	35	36

Subdivision of sec. 24 ----- p. 23
 Subdivision of sec. 25 ----- p. 36
 Subdivision of sec. 26 ----- p. 42

T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary (Black Mesa Forest Reserve), Township 12 North, Range 11 East. A dependent resurvey of a portion of the east boundary and subdivisional lines and a survey of subdivisions in sections 24, 25 and 26, Township 11½ North, Range 11 East, Gila and Salt River Meridian, Arizona.

The south boundary (Black Mesa Forest Reserve), Township 12 North, Range 11 East, was surveyed in 1902-03 by W.H. Thorn. In 1933 a dependent resurvey of this south boundary was executed by Theodore Vander Meer. The east, west, and south boundaries, and the subdivisional lines of Township 11½ North, Range 11 East, were surveyed in 1904 by Charles L. Campbell.

Patterson and Associates, Inc., Mesa, Arizona, surveyed the boundaries and subdivided sections 24, 25 and 26, under U.S. Forest Service contract. The Forest Service requested this dependent resurvey and subdivision of sections 24, 25 and 26 in order to verify and to delineate the National Forest boundary lines and to resolve conflicts of ownership and prevent future trespass.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 625, Arizona, dated October 2, 1981.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of record. Identified corners were re-monumented in their original positions. Lost corners were restored and monumented in a proportionate position based on original records. All evidence of private surveys was evaluated and considered and was accepted if the evidence indicated that the survey was properly executed. The retracement data were thoroughly verified and only the true line field notes are given herein.

The direction of lines were determined from triangulation stations of the horizontal control network and direct solar observations and refer to the true meridian. Angles and distances were measured electronically with a Hewlett-Packard 3820 instrument.

The geographic position of the southeast corner of section 25, as determined by a tie to triangulation station "MYRTLE POINT" (U.S.F.S.), located in sec. 36, T. 12 N., R. 11 E., is as follows:

Latitude: 34°20'57.22" N Longitude: 111°10'06.82" W

The mean magnetic declination is 13½° E.

Dependent Resurvey of a Portion of the S Bdy.
T. 12 N., R. 11 E., Gila and Salt River Mer., Arizona

(Restoring the 1933 resurvey by Theodore Vander Meer)

Beginning at the 1/4 sec. cor. of sec. 35, on the S bdy. of the Tp., monumented with an iron post, 1 in. diam., projecting 6 ins. above ground, with brass cap mkd. as described in the 1933 official record.

Dependent Resurvey of a Portion of the S Bdy.
T. 12 N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which bearing trees mkd. in 1933</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears N. 69° E., 24 lks. dist., healed blaze.</p> <p style="padding-left: 40px;">A dead oak, 8 ins. diam., bears N. 60½° W., 35 lks. dist., no marks visible.</p> <p>From this point, an angle point on the S bdy. of sec. 35, bears S. 89°55' E., 2.14 chs. dist., monumented with a sandstone, 6 x 9 x 19 ins., firmly set 10 ins. in the ground, mkd. 1/4 AP on N face.</p> <p>from which bearing trees mkd. in 1903</p> <p style="padding-left: 40px;">A dead oak, 8 ins. diam., bears N. 48° E., 48 lks. dist., rotted blaze. (Record: 44 lks. dist.)</p> <p style="padding-left: 40px;">A pine, 26 ins. diam., bears S. 83½° E., 28 lks. dist., healed blaze. (Record: 26 lks. dist.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>AP T12N R11E <u>S35</u> 1982</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°55' W., on the S bdy. of sec. 35.</p> <p>Over rolling land, through medium to dense timber.</p>
35.81	The closing cor. of secs. 19 and 24, Tps. 11½ N., Rs. 11 and 11½ E., hereinafter described.
37.77	<p>Angle point on the S bdy. of sec. 35, monumented with an iron post, 4 ins. diam., projecting 24 ins. above ground, in a mound of stone, 4½ ft. base, 1½ ft. high, mkd. as described in the 1903 and 1933 official record.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°51' W., beginning new measurement.</p>
2.23	<p>The cor. of secs. 34 and 35, monumented with an iron post, 2 ins. diam., projecting 18 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R11E <u>S34 S35</u> 1933</p> </div> <p>from which bearing trees mkd. in 1937</p> <p style="padding-left: 40px;">A juniper, 20 ins. diam., bears N. 35° E., 35 lks. dist., mkd. T12N R11E BT. (Record: N. 28° E.)</p>

Dependent Resurvey of a Portion of the S Bdy.
T. 12 N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>A pine stump, 20 ins. diam., bears N. 40° W., 17 lks. dist., no marks visible.</p> <hr/> <p>S. 89°53' W., on the S bdy. of sec. 34, through medium to dense timber.</p>
15.79	Point for the E 1/16 sec. cor. of sec. 24, T. 11½ N., R. 11 E., hereinafter described.
25.78	Point for the W-E 1/64 sec. cor. of sec. 24, T. 11½ N., R. 11 E., hereinafter described.
26.59	Ellison Creek, 20 lks. wide, 1 ft. deep, course southerly.
33.80	Track road, bears N. 40° E. and S. 50° W.
35.77	Point for the 1/4 sec. cor. of sec. 24, T. 11½ N., R. 11 E., hereinafter described.
37.60	<p>Angle point on S bdy. of sec. 34, monumented with a sand- stone, 16 x 18 x 12 ins., firmly set 8 ins. in the ground, mkd. 1/4 AP on N face, and in a mound of stone, 4½ ft. base, 1 ft. high.</p> <p>from which the remains of a bearing tree mkd. in 1903</p> <p>A pine stump, 24 ins. diam., bears N. 2° E., 99 lks. dist., mkd. BT.</p> <p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 24 ins. in the ground, and in a mound of stone, 4½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">AP T12N R11E S34 ----- 1982</p> <p>Deposit the mkd. stone alongside the aluminum post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89°36' W., beginning new measurement.</p>
2.40	<p>The 1/4 sec. cor. of sec. 34 only, monumented with an iron post, 1 in. diam., projecting 30 ins. above ground, in a mound of stone, 3½ ft. base, to top, with brass cap mkd. as described in the 1933 official record.</p> <p>from which the bearing trees mkd. in 1933</p> <p>A juniper, 22 ins. diam., bears N. 14° E., 16 lks. dist., mkd. 1/4 S34 BT.</p> <p>A pine, 16 ins. diam., bears N. 88 1/4° W., 124 lks. dist., healed blaze. (There is no record dist.)</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89°50' W., beginning new measurement.</p>

Dependent Resurvey of a Portion of the S Bdy.
T. 12 N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS
15.75

Point for the W 1/16 sec. cor. of sec. 24, T. 11½ N., R. 11 E., hereinafter described.

35.73

Point for the closing cor. of secs. 23 and 24, T. 11½ N., R. 11 E., hereinafter described.

37.57

Angle point on the S bdy. of sec. 34, monumented with an iron post, 4 ins. diam., projecting 18 ins. above ground, in a mound of stone, 4 ft. base, 1 ft. high, with brass cap mkd. as described in the 1933 official record.

from which bearing trees mkd. in 1903

A dead oak, 12 ins. diam., bears N. 14½° E.,
34 lks. dist., healed blaze.
(Record: 44 lks. dist.)

An oak stump, 10 ins. diam., bears S. 85° E.,
43 lks. dist., no marks visible.

A dead oak, 12 ins. diam., bears S. 85°50' W.,
65 lks. dist., healed blaze.

A dead oak, 12 ins. diam., bears N. 19° W.,
29 lks. dist., rotted blaze.

Dependent Resurvey of a Portion of the E Bdy.
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

(Restoring the 1904 Survey by Charles L. Campbell)

From the cor. of secs. 25, 30, 31 and 36, on the E bdy. of the Tp., determined from the original bearing trees

A ponderosa pine, 28 ins. diam., bears N. 34° E.,
54 lks. dist., healed blaze. (Record: N. 32° E.)

An oak, 30 ins. diam., bears S. 40° E., 10 lks.
dist., marks visible 11½ N R11E 36.


A ponderosa pine, 30 ins. diam., bears S. 54° W.,
77 lks. dist., marks visible 11½. (Record:
S. 44° W., 70 lks. dist.)

An oak, 17 ins. diam., bears N. 7° W., 51 lks.
dist., healed blaze.

The original standstone, 13 x 8 x 3 ins., with 5 grooves on one side, and 1 groove on another, was found lying loose.

At the cor. point

Set an aluminum post, 36 ins. long, ¾ in. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.



Dependent Resurvey of a Portion of the E Bdy.
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS

from which a new bearing tree

A ponderosa pine, 6 ins. diam., bears
S. 65° E., 20.5 lks. dist., mkd. T11½N
R11½E S36 BT.

Bury the mkd. stone in the mound of stone.

Cor is located 25 lks. S of a fence line, bears
N. 54° E. and S. 54° W.

From this point a Forest Service aluminum post, 2½ ins.
diam., projecting 20 ins. above ground, in a mound of
stone, 2 ft. base, 1 ft. high, bears N. 43°00' E., 20.8
lks. dist., with cap mkd.

T11½N	T11½N
R11E	R11½E
S25	S30
S36	S31

RLS 13056 1980

This monument was established by Patterson and Associates
under Forest Service contract using improper procedures
and not utilized in the course of this survey.

N. 0°07' E., bet. secs. 25 and 30.

Over rolling land, through medium ponderosa pine,
scattered juniper and oak.

40.08 The 1/4 sec. cor. of secs. 25 and 30, monumented with a
sandstone, 17 x 10 x 6 ins., projecting 6 ins. above
ground, mkd. 1/4 on W face.

from which the original bearing trees

An alligator juniper, 35 ins. diam., bears
N. 14° E., 32 lks. dist., mkd. 1/4 S30 BT.
(Record: 23 lks. dist.)

An oak, 14 ins. diam., bears S. 89° W., 36 lks.
dist., healed blaze. (Record: S. 85° W.)

At the cor. point

Set an aluminum post, 30 ins. long, ¾ in. diam., 20 ins.
in the ground, in a mound of stone, 4 ft. base, to top,
with cap mkd.

T11½N	
1/4	
R11E	R11½E
S25	S30

1981

from which new bearing trees

A ponderosa pine, 11 ins. diam., bears
S. 88° E., 23 lks. dist., mkd. 1/4 S30 BT.

A ponderosa pine, 15 ins. diam., bears
S. 51° W., 49 lks. dist., mkd. 1/4 S25 BT.

Bury the original stone in the mound.

Dependent Resurvey of a Portion of the E Bdy.
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS

From this point a Forest Service aluminum post, 2½ ins. diam., projecting 16 ins. above ground, in a mound of stone, 3 ft. base, to top, bears N. 24°00' E., 12 lks. dist., with cap mkd.

T11½N	T11½N
R11E	R11½E
S25	S30
1/4	
RLS 13056 1980	

This monument was established by Patterson and Associates under Forest Service contract using improper procedures and is not utilized in the course of this survey.

N. 0°11' E., beginning new measurement.

39.82 The cor. of secs. 19, 24, 25 and 30, monumented with a sandstone, 15 x 10 x 7 ins., projecting 6 ins. above ground, mkd. with 2 grooves on the S face, and 1 groove on the N face, with a mound of stone, 2 ft. base, 1 ft. high, S of cor.

from which the original bearing trees

An oak snag, 7 ins. diam., bears N. 37° E., 17 lks. dist., mkd. T11½N R11½E S19 BT.
(Record: N. 40° E.)

A black oak, 9 ins. diam., bears S. 82° E., 30 lks. dist., healed blaze.

A black oak, 11 ins. diam., bears S. 14° W., 53 lks. dist., healed blaze.

A white oak, 7 ins. diam., bears N. 48° W., 32 lks. dist., healed blaze.

At the cor. point

Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, with cap mkd.

T11½N	
R11E	R11½E
S24	S19
S25	S30
1982	

from which new bearing trees

A ponderosa pine, 7 ins. diam., bears N. 63° E., 10 lks. dist., mkd. T11½N R11½E S19 BT.

A ponderosa pine, 7 ins. diam., bears S. 6° E., 42.5 lks. dist., mkd. T11½N R11½E S30 BT.

A ponderosa pine, 8 ins. diam., bears S. 16° W., 39 lks. dist., mkd. T11½N R11E S25 BT.

Rebuilt mound of stone, 3 ft. base, 1½ ft. high, W of cor.

Bury mkd. stone in the mound.

Dependent Resurvey of a Portion of the E Bdy.
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS			
	<p>N. 0°31' E., bet. secs. 19 and 24.</p> <p>Over rolling land, through medium to dense timber.</p> <p>39.84 The 1/4 sec. cor. of secs. 19 and 24, monumented with a sandstone, 10 x 18 x 4 ins., firmly set 8 ins. in the ground, mkd. 1/4 on W face, and in a scattered mound of stone.</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">An oak, 10 ins. diam., bears S. 70° E., 45 lks. dist., healed blaze.</p> <p style="padding-left: 40px;">A dead and down oak, bears S. 62° W., 48 lks. dist., no marks visible on open blaze.</p> <p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 24 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <div style="text-align: center;"> <p>T11½N 1/4 R11E R11½E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S24</td> <td style="padding: 0 5px;">S19</td> </tr> </table> <p>1982</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A juniper, 24 ins. diam., bears S. 60° E., 64 lks. dist., mkd. 1/4 S19 BT.</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears N. 20° W., 66½ lks. dist., mkd. 1/4 S24 BT.</p> <p>Deposit the mkd. stone alongside the aluminum post.</p>	S24	S19
S24	S19		
<p>19.84</p>	<p>N. 0°08' E., beginning new measurement.</p> <p>Point for the N 1/16 sec. cor. of secs. 19 and 24, at proportionate dist.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 24 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <div style="text-align: center;"> <p>T11½N N 1/16 R11E R11½E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S24</td> <td style="padding: 0 5px;">S19</td> </tr> </table> <p>1982</p> </div> <p>from which</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears S. 71° E., 55½ lks. dist., mkd. N 1/16 S19 BT.</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears N. 12° W., 34½ lks. dist., mkd. N 1/16 S24 BT.</p>	S24	S19
S24	S19		

Dependent Resurvey of a Portion of the E Bdy.
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS	
32.73	<p>The original closing cor. of T. 11½ N., Rs. 11 and 11½ E., monumented with a sandstone, 24 x 16 x 4 ins., firmly set 10 ins. in the ground, mkd. with 6 grooves on E and W faces, 3 grooves and CC on S face.</p> <p>from which the original bearing trees</p> <p>A juniper, 24 ins. diam., bears S. 35° E., 54 lks. dist., mkd. CC T11½N R11½E S19 BT.</p> <p>A dead oak, 8 ins. diam., bears S 44° W., 30 lks. dist., mkd. with illegible scribe marks.</p> <p>Add the marks AM and bury the stone 6 ins. below ground.</p>
32.75	<p>The closing cor. of T. 11½ N., Rs. 11 and 11½ E., monumented with an iron post, 3 ins. diam., projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R11E S35 ----- S24 S19 R11E R11½E CC T11½N 1933</p> </div> <p>From this point an angle point on the S bdy. of sec. 35, T. 12 N., R. 11 E., bears N. 89°55' W., 1.96 chs. dist., heretofore described.</p>
<p>Dependent Resurvey of a Portion of Subdivisional Lines, T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona</p>	
<p>(Restoring the 1904 Survey by Charles L. Campbell)</p>	
40.02	<p>From the cor. of secs. 25, 30, 31 and 36, on the E bdy., heretofore described.</p> <p>N. 89°29' W., bet. secs. 25 and 36.</p> <p>Over rolling land, through medium ponderosa pine, juniper and oak.</p> <p>The 1/4 sec. cor. of secs. 25 and 36, monumented with an iron stone, 13 x 9 x 6 ins., projecting 5 ins. above ground, mkd. 1/4 on N face.</p> <p>from which</p> <p>A ponderosa pine, 22 ins. diam., bears N. 89½° E., 86 lks. dist., mkd. 1/4 S25 BT. (Record: juniper, 84 lks. dist.)</p> <p>A pine stump, 25 ins. diam., bears S. 30° E., 21 lks. dist., no marks visible.</p> <p>At the cor. point</p> <p>Set an aluminum post, 30 ins. long, ¾ in. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p>

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T11½N R11E 1/4 $\frac{S25}{S36}$ 1981</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N. 14° E., 20 lks. dist., mkd. 1/4 S25 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears S. 35½° E., 39 lks. dist., mkd. 1/4 S36 BT.</p> <p>Bury the mkd. stone in the mound.</p> <p style="text-align: center;">_____</p> <p>S. 89°59' W., beginning new measurement.</p>	
39.99	<p>The cor. of secs. 25, 26, 35 and 36, monumented with a sandstone, 13 x 12 x 4 ins., projecting 5 ins. above ground, in a scattered mound of stone, mkd. with 1 groove on the E and 1 groove on the S.</p> <p>from which a bearing tree not of record</p> <p style="padding-left: 40px;">A ponderosa pine, 29 ins. diam., bears S. 89° W., 97 lks. dist., marks visible 11½N 11E 35.</p> <p>At the cor. point</p> <p>Set an aluminum post, 30 ins. long, ¾ in. diam., 10 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T11½N R11E S26 S25 S35 S36 1981</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears N. 33° E., 44 lks. dist., mkd. T11½N R11E S25 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S. 53° E., 24 lks. dist., mkd. T11½N R11 E S36 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S. 52° W., 29 lks. dist., mkd. T11½N R11E S35 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 44° W., 31.5 lks. dist., mkd. T11½N R11E S26 BT.</p> <p>Bury the mkd. stone in the mound.</p>	
39.74	<p>N. 0°04' W., bet. secs. 25 and 26.</p> <p>Over rolling land, through medium ponderosa pine, oak, juniper and manzanita.</p> <p>The 1/4 sec. cor. of secs. 25 and 26, monumented with a sandstone, 12 x 10 x 8 ins., projecting 7 ins. above ground, with scattered mound of stone S, mkd. 1/4 on W face.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS	<p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 24 ins. diam., bears N. 84° E., 99 lks. dist., marks visible 2 BT. (Record: N. 81° E., 100 lks. dist.)</p> <p style="padding-left: 40px;">An alligator juniper, 22 ins. diam., bears S. 30° W., 134 lks. dist., marks visible S26 BT. (Record: S. 29° W., 136 lks. dist.)</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, ¾ in. diam., 23 ins. in the ground, with cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T11½N R11E</p> <p>1/4</p> <p>S26 S25</p> <p>1981</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N. 43° E., 61 lks. dist., mkd. 1/4 S25 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears N. 35° W., 64 lks. dist., mkd. 1/4 S26 BT.</p> <p>Rebuild a mound of stone, 2½ ft. base, 1 ft. high, W of cor.</p> <p>Bury the mkd. stone in the mound.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°18' E., beginning new measurement.</p> <p>10.02 Point for the S-N 1/64 sec. cor. of secs. 25 and 26.</p> <p>Set an aluminum post, 30 ins. long, ¾ in. diam., 24 ins. in the ground, with cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S-N</p> <p>1/64</p> <p>S26 S25</p> <p>1981</p> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears S. 35° E., 61 lks. dist., mkd. S-N 1/64 S25 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears S. 49° W., 63 lks. dist., mkd. S-N 1/64 S26 BT.</p> <p>Raise a mound of stone, 2 ft. base, 1½ ft. high, W of cor.</p> <p>Cor. is located 13 lks. S of an E and W fence line.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 24 ins. above ground, in a mound of stone, 2 ft. base, 1 ft. high, bears East, 1.6 lks. dist., with cap mkd.</p>
--------	--

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T11½N R11E S-N S26 S25 1/64 RLS 13056 1980</p> <p>This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	
20.04	<p>Point for the N 1/16 sec. cor. of secs. 25 and 26.</p> <p>Set an aluminum post, 30 ins. long, ¾ in. diam., 24 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">T11½N R11E N 1/16 S26 S25 1981</p> <p>Raise a mound of stone, 1½ ft. base, 1½ ft. high, W of cor.</p> <p>From this point a ½ in. diam. rebar, projecting 1 in. above ground, bears East, .3 lks. dist. This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	
30.06	<p>Point for the N-N 1/64 sec. cor. of secs. 25 and 26.</p> <p>Set an aluminum post, 30 ins. long, ¾ in. diam., 24 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">N-N 1/64 S26 S25 1981</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears N. 45° W., 41 lks. dist., mkd. N-N 1/64 S26 BT.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.</p> <p>Cor. is located 60 lks. N of a graded dirt road, bears N. 60° E., curving northerly and S. 80° W.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 5 ins. above ground, in a collar of stone, bears N. 56°19' E., .4 lk. dist., with cap mkd.</p>	
	<p style="text-align: center;">T11½N R11E N—N S26 S25 1/64 RLS 13056 1980</p> <p>This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>40.08 The cor. of secs. 23, 24, 25 and 26, monumented with a sandstone, 12 x 10 x 8 ins., projecting 10 ins. above ground, in a scattered mound of stone, with 2 grooves on the E face and 2 grooves on the S face.</p> <p>from which</p> <p>An alligator juniper, 16 ins. diam., bears N. 43° E., 33 lks. dist., mkd. T11½N R11E S24 BT.</p> <p>An alligator juniper, 40 ins. diam., bears S. 7° E., 67 lks. dist., mkd. T11½N R11E S25 BT. (Record: S. 13½° E.)</p> <p>A pine stump, 24 ins. diam., bears S. 72½° W., 113 lks. dist., marks visible T.</p> <p>An oak stump, 16 ins. diam., bears N. 34½° W., 32 lks. dist., no marks visible. (Record: N. 36½° W., 34 lks. dist.)</p> <p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 6 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td colspan="2">T11½N R11E</td> </tr> <tr> <td>S23</td> <td>S24</td> </tr> <tr> <td>S26</td> <td>S25</td> </tr> <tr> <td colspan="2">1982</td> </tr> </table> </div> <p>from which new bearing trees</p> <p>An alligator juniper, 13 ins. diam., bears S. 73½° W., 99 lks. dist., mkd. T11½N R11E S26 BT</p> <p>A ponderosa pine, 7 ins. diam., bears N. 41° W., 77 lks. dist., mkd. T11½N R11E S23 BT.</p> <p>Bury the mkd. stone in the mound.</p>	T11½N R11E		S23	S24	S26	S25	1982		
T11½N R11E										
S23	S24									
S26	S25									
1982										
	<p>From the cor. of secs. 19, 24, 25 and 30, on the E bdy., heretofore described.</p> <p>N. 89°52' W., bet. secs. 24 and 25.</p> <p>Over rolling land, through dense ponderosa pine, oak, juniper and manzanita.</p>									
<p>40.08</p>	<p>The 1/4 sec. cor. of secs. 24 and 25, monumented with a sandstone, 15 x 9 x 6 ins., projecting 4 ins. above ground, in a scattered mound of stone, mkd. 1/4 on the N face.</p> <p>from which</p> <p>A ponderosa pine, 20 ins. diam., bears N. 54½° E., 39 lks. dist., healed blaze. (Record: N. 52° E.)</p> <p>A ponderosa pine, 13 ins. diam., bears S. 42° W., 27 lks. dist., healed blaze.</p>									

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T11½N R11E 1/4 $\frac{S24}{S25}$ 1982</p> <p>from which a new bearing tree</p> <p style="text-align: center;">A ponderosa pine, 7 ins. diam., bears N. 30° W., 32 lks. dist., mkd. 1/4 S24 BT.</p> <p>Raise a mound of stone, 2½ ft. base, to top, N of cor.</p> <p>Bury the mkd. stone in the mound.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89°42' W., beginning new measurement.</p>	
10.00	<p>Point for the E-W 1/64 sec. cor. of secs. 24 and 25.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 18 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S24 E-W 1/64 S25 1982</p> <p>from which</p> <p style="text-align: center;">A ponderosa pine, 7 ins. diam., bears N. 41° E., 54 lks. dist., mkd. E-W 1/64 S24 BT.</p> <p style="text-align: center;">A ponderosa pine, 12 ins. diam., bears S. 12° E., 77.5 lks. dist., mkd. E-W 1/64 S25 BT.</p> <p>Cor. is located 1 lk. E of a N and S fence line.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 24 ins. above ground, in a mound of stone, 3½ ft. base, 1 ft. high, bears N. 38°40' W., .6 lk. dist., with cap mkd.</p> <p style="text-align: center;">T11½N R11E S24 $\frac{E-W}{1/64}$ S25 RLS 13056 1980</p> <p>This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	
20.00	<p>Point for the W 1/16 sec. cor. of secs. 24 and 25.</p> <p>Set an aluminum post, 30 ins. long, ¾ in. diam., 27 ins. in the ground, with cap mkd.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T11½N R11E W 1/16 $\frac{S24}{S25}$ 1981</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 6 ins. above ground, in a mound of stone, 2 ft. base, to top, bears N. 11°19' W., 2 lks. dist., with cap mkd.</p> <p style="text-align: center;">T11½N R11E S24 W 1/16 S 25 RLS 13056 1980</p> <p>This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	
40.00	<p>The cor. of secs. 23, 24, 25 and 26.</p> <hr/> <p>N. 0°27' E., bet. secs. 23 and 24.</p> <p>Over rolling land, through medium timber.</p>	
19.97	<p>Point for the S 1/16 sec. cor. of secs. 23 and 24.</p> <p>The point is monumented with a Forest Service aluminum post, 28 ins. long, 2½ ins. diam., projecting 8 ins. above ground, with cap mkd.</p> <p style="text-align: center;">T11½ R11E S23 S24 S 1/16 RLS 13056 1980</p> <p>This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p> <p>Removed the Forest Service aluminum post.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, in a mound of stone, 1½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T11½N R11E S 1/16 S23 S24 1982</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 13 ins. diam., bears N. 39° E., 37½ lks. dist., mkd. S 1/16 S24 BT.</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 34° W., 65 lks. dist., mkd. S 1/16 S23 BT.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Cor is located 3 lks. W of fence cor., fence extends S and W.</p> <p>39.94 The 1/4 sec. cor. of secs. 23 and 24, monumented with a sandstone, 16 x 8 x 6 ins., set 12 ins. in the ground, mkd. 1/4 on W face.</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 36 ins. diam., bears S. 47½° E., 96 lks. dist., mkd. 1/4 S24 BT.</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears S. 79° W., 68 lks. dist., healed blaze.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 26 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T11½N R11E 1/4 S23 S24 1982</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A juniper, 9 ins. diam., bears N. 45° W., 39 lks. dist., mkd. 1/4 S23 BT.</p> <p>Bury the mkd. stone alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°33' E., beginning new measurement.</p>
19.79	<p>Point for the N 1/16 sec. cor. of secs. 23 and 24, at proportionate dist.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 18 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with aluminum cap mkd.</p> <p style="text-align: center;">T11½N R11E N 1/16 S23 S24 1982</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears S. 66° E., 13 lks. dist., mkd. N 1/16 S24 BT.</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears N. 60° W., 30½ lks. dist., mkd. N 1/16 S23 BT.</p> <p>From this point a ½ in. diam. rebar, projecting 4 ins. above ground, bears N. 1°39' E., 20.2 lks. dist. This monument was established using improper procedures by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>
32.20	<p>The original closing cor. of secs. 23 and 24, monumented with a sandstone, 18 x 12 x 6 ins., firmly set 15 ins. in the ground, mkd. with 1 groove on the E face, CC on the S face, and 5 grooves on the W face.</p>

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

<p>CHAINS</p> <p>32.22</p>	<p>from which the remaining original bearing tree</p> <p>An oak, 18 ins. diam., bears S. 70° W., 45 lks. dist., mkd. 1½N 11 23 on partially healed blaze.</p> <p>Add the marks AM and bury the stone in place, 6 ins. below ground.</p> <p>Intersect the S bdy. of sec. 34, T. 12 N., R. 11 E.</p> <p>Point for the closing cor. of secs. 23 and 24.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 24 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with cap mkd.</p> <div style="text-align: center;"> <p>T12N R11E S34 ----- S23 S24 T11½N R11E CC 1982</p> </div> <p>from which</p> <p>A pine, 11 ins. diam., bears S. 9° E., 47½ lks. dist., mkd. T11½N R11E S24 CC BT.</p> <p>A pine, 6 ins. diam., bears S. 84° W., 30½ lks. dist., mkd. T11½N R11E S23 CC BT.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 24 ins. above ground, in a mound of stone, 2½ ft. base, to top, bears N. 82° E., 1½ lks. dist., with cap mkd.</p> <div style="text-align: center;"> <p>T12N R11E S34 ----- 23 24 T11½N R11E CC RLS 13056 1980</p> </div> <p>This monument was established using improper procedures by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p> <p>From the same point an angle point on the S bdy. of sec. 34, T. 12 N., R. 11 E., bears S. 89°50' W., 1.84 chs. dist., heretofore described.</p>
<p>40.02</p>	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89°43' W., bet. secs. 26 and 35.</p> <p>Over gently rolling land, through dense ponderosa pine, oak and juniper.</p> <p>The ¼ sec. cor. of secs. 26 and 35, determined from remains of original bearing trees.</p>

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS

A ponderosa pine, 20 ins. diam., bears
N. 5½° E., 54 lks. dist., mkd. B on
partly healed blaze. (Record: N. 8° E.)

The remains of a pine stump, bears S. 21° E.,
47 lks. dist., no marks visible. (Record:
S. 29½° E.)

The original sandstone, 14 x 10 x 3 ins., mkd. 1/4, was
found lying loose.

At the cor. point

Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins.
in the ground, with cap mkd.

T11½N R11E
1/4 $\frac{S26}{S35}$
1982

from which new bearing trees

An alligator juniper, 6 ins. diam., bears
N. 28° E., 46 lks. dist., mkd. 1/4 S26 BT.

A ponderosa pine, 7 ins. diam., bears S. 7° E.,
34 lks. dist., mkd. 1/4 S35 BT.

Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of
cor.

Bury the mkd. stone in the mound.

Cor. is located 15 lks. S of center of an E and W track
road.

From this point a Forest Service aluminum post, 2½ ins.
diam., projecting 20 ins. above ground, in a mound of
stone, 3 ft. base, 1 ft. high, bears S. 12°37' W., 6.9
lks. dist., with cap mkd.

T11½N R11E
1/4 $\frac{S26}{S35}$
RLS 13056 1980

This monument was established by Patterson and Associates
under Forest Service contract using improper procedures
and is not utilized in the course of this survey.

N. 89°53' W., beginning new measurement.

40.05 The cor. of secs. 26, 27, 34 and 35, monumented with a
Forest Service aluminum post, 2½ ins. diam., projecting
26 ins. above ground, in a mound of stone, 4 ft. base, 1½
ft. high, with cap mkd.

T11½N R11E
 $\frac{S27}{S34} \mid \frac{S26}{S35}$
RLS 13056 1980

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS	<p>from which the original bearing trees</p> <p>A fallen pine, 32 ins. diam., bears N. 70° E., 52 lks. dist., no marks visible.</p> <p>An oak, 42 ins. diam., bears S. 60° E., 15 lks. dist., healed blaze.</p> <p>The stump hole of an oak, 24 ins. diam., bears S. 60° W., 85 lks. dist., no marks visible.</p> <p>An alligator juniper, 34 ins. diam., bears N. 41° W., 95 lks. dist., marks visible 11½N 11E S27 BT.</p> <p>This monument was set by Patterson and Associates under Forest Service contract and is not used in the course of this survey.</p> <p>Removed the Forest Service aluminum post.</p> <p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 28 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td colspan="2">T11½N R11E</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S27</td> <td style="padding-left: 5px;">S26</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S34</td> <td style="padding-left: 5px;">S35</td> </tr> <tr> <td colspan="2">1982</td> </tr> </table> </div> <p>from which new bearing trees</p> <p>A ponderosa pine, 9 ins. diam., bears N. 38° E., 31 lks. dist., mkd. T11½N R11E S26 BT.</p> <p>A ponderosa pine, 11 ins. diam., bears S. 89½° E., 30 lks. dist., mkd. T11½N R11E S35 BT.</p> <p>A ponderosa pine, 10 ins. diam., bears S. 15° W., 11 lks. dist., mkd. T11½N R11E S34 BT.</p> <p>A ponderosa pine, 10 ins. diam., bears N. 75° W., 26 lks. dist., mkd. T11½N R11E S27 BT.</p> <hr/> <p>N. 0°02' W., bet. secs. 26 and 27.</p> <p>Over rolling land, through dense ponderosa pine, juniper, oak and manzanita.</p> <p>39.96 The ¼ sec. cor. of secs. 26 and 27, monumented with an iron stone, 14 x 10 x 6 ins., projecting 8 ins. above ground, mkd. ¼ on W face.</p> <p>from which</p> <p>A pine stump, 16 ins. diam., bears N. 74° E., 19 lks. dist., no marks visible. (Record: N. 60° E.)</p> <p>A ponderosa pine, 21 ins. diam., bears N. 49½° W., 93 lks. dist., healed blaze. (Record: N. 65° W., 95 lks. dist.)</p>	T11½N R11E		S27	S26	S34	S35	1982	
T11½N R11E									
S27	S26								
S34	S35								
1982									

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 28 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T11½N R11E 1/4 S27 S26 1982</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S. 62° E., 86 lks. dist., mkd. 1/4 S26 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S. 29° W., 16.5 lks. dist., mkd. 1/4 S27 BT.</p> <p>Bury the mkd. stone alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°49' E., beginning new measurement.</p>	
40.08	<p>The cor. of secs. 22, 23, 26 and 27, monumented with a slate stone, 18 x 10 x 4 ins., projecting 4 ins. above ground, with a scattered mound of stone W, mkd. with 2 grooves on the E face, and 2 grooves on the S face.</p> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 22 ins. diam., bears N. 8° E., 42 lks. dist., healed blaze.</p> <p style="padding-left: 40px;">An alligator juniper, 26 ins. diam., bears N. 43° W., 123 lks. dist., mkd. T11½N R11E S22 BT.</p> <p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 24 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T11½N R11E S22 S23 S27 S26 1982</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">An alligator juniper, 14 ins. diam., bears S. 26½° E., 88 lks. dist., mkd. T11½N R11E S26 BT.</p> <p style="padding-left: 40px;">An alligator juniper, 16 ins. diam., bears S. 84° W., 33 lks. dist., mkd. T11½N R11E.</p> <p>Bury the mkd. stone in the mound.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°54' W., bet. secs. 23 and 26.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS		
9.97	<p>Over rolling land, through dense ponderosa pine, juniper, oak and manzanita.</p> <p>Point for the E-E 1/64 sec. cor. of secs. 23 and 26.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S23 E-E 1/64 S26 1982</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears N. 54° E., 16.5 lks. dist., mkd. E-E 1/64 S23 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears S. 12° E., 37 lks. dist., mkd. E-E 1/64 S26 BT.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.</p> <p>From this point a ¾ in. diam. rebar, projecting 6 ins. above ground, bears S. 45°00' W., .8 lk. dist. This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	
19.94	<p>Point for the E 1/16 sec. cor. of secs. 23 and 26.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 28 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T11½N R11E E 1/16 $\frac{S23}{S26}$ 1982</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears S. 58° W., 23.5 lks. dist., mkd. E 1/16 S26 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N. 15° W., 35.5 lks. dist., mkd. E 1/16 S23 BT.</p> <p>From this point a ½ in. diam. rebar, projecting 1 in. above ground, bears S. 26°34' W., .9 lk. dist.</p> <p>This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	
39.88	<p>The 1/4 sec. cor. of secs. 23 and 26, monumented with a 2 x 2 ft. ledge, projecting 1 ft. above ground, mkd. with a cross on top, and 1/4 on the E face.</p> <p>from which</p> <p style="padding-left: 40px;">An oak, 16 ins. diam., bears S. 22½° W., 20 lks. dist., healed blaze. (Record: S. 20° W.)</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>An oak snag, 19 ins. diam., bears N. 15° W., 17 lks. dist., marks visible 1/4 S26. (Record: N. 13° W.)</p> <p>Broke the ledge off and at the cor. point</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 28 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T11½N R11E 1/4 $\frac{S23}{S26}$ 1982</p> <p>from which</p> <p>An alligator juniper, 6 ins. diam., bears S. 15° E., 28 lks. dist., mkd. 1/4 S26 BT.</p> <p>A ponderosa pine, 10 ins. diam., bears N. 36° W., 23.5 lks. dist., mkd. 1/4 S23 BT.</p> <p>Bury the broken piece of cor. in the mound.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89°20' W., beginning new measurement.</p>	
39.80	<p>The cor. of secs. 22, 23, 26 and 27.</p> <hr/> <p style="text-align: center;">Subdivision of Section 24 T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona</p>	
19.97	<p>From the 1/4 sec. cor. of secs. 24 and 25.</p> <p>N. 0°26' E., on the N and S center line of sec. 24.</p> <p>Over rolling land, through medium timber.</p> <p>Point for the center S 1/16 sec. cor. of sec. 24.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 28 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T11½N R11E C S 1/16 S24 C 1982</p> <p>from which</p> <p>A pine, 10 ins. diam., bears N. 45° E., 14 lks. dist., mkd. CS 1/16 S24 BT.</p> <p>A pine, 10 ins. diam., bears S. 49° W., 22 lks. dist., mkd. CS 1/16 S24 BT.</p> <p>From this point a ½ in. diam. rebar, projecting 4 ins. above ground, bears N. 89°54' E., 54 lks. dist. This monument was established using improper procedures by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	

Subdivision of Section 24
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS		
39.94	<p>Point for the center 1/4 sec. cor., at intersection with the E and W center line of sec. 24.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 26 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T11½N R11E C 1/4 S24 1982</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 79° E., 15½ lks. dist., mkd. C 1/4 S24 BT.</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 12° W., 42 lks. dist., mkd. C 1/4 S24 BT.</p> <p>Cor. is located 10 lks. N of fence, bears E and W.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 12 ins. above ground, in a mound of stone, 2½ ft. base, to top, bears N. 89°53' W., 1.06 lks. dist., with cap mkd.</p> <p style="text-align: center;">T11½N R11E C 1/4 S24 RLS 13056 1980</p> <p>This monument was established using improper procedures by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	
49.85	<p>Point for the center S-N 1/64 sec. cor. of sec. 24, falls in a barn yard area where it is impractical to establish a permanent monument.</p>	
54.81	<p>Point for the center N-S-N 1/256 sec. cor. of sec. 24.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 28 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">C N-S-N 1/256 S24 C 1982</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears North, 6 lks. dist., mkd. X BT at the base.</p> <p>From this point a sandstone, projecting 18 x 15 x 6 ins. above ground, mkd. H 4 on S face, bears N. 15° W., 9.7 lks. dist. This monument is of unknown origin, and is not utilized in the course of this survey.</p>	
59.76	<p>Point for the center N 1/16 sec. cor. of sec. 24, at proportionate dist.</p>	

Subdivision of Section 24
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

	CHAINS		
		<p>Set an aluminum post, 36 ins. long, ¾ in. diam., 25 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T11½N R11E C N 1/16 S24 C 1982</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears S. 55° W., 3 lks. dist., mkd. X BT at the base.</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 9° W., 18½ lks. dist., mkd. CN 1/16 S24 BT.</p> <p>Cor. is located 57 lks. E of a fence, bears N. 32° E. and S. 32° W.; and 45 lks. W of Ellison Creek, 20 lks. wide, 1 ft. deep, course SW.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 8 ins. above ground, in a mound of stone, 2 ft. base, 6 ins. high, bears N. 82°54' W., 1.51 chs. dist., with aluminum cap mkd.</p> <p style="text-align: center;">S24 C N 1/16 C RLS 13056 1980</p> <p>This monument was established using improper procedures by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	
	69.67	<p>Point for the center N-N 1/64 sec. cor. of sec. 24, at proportionate dist.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 26 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">C N-N 1/64 S24 C 1982</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 17 ins. diam., bears N. 35° E., 67 lks. dist., mkd. C-N-N 1/64 S24 BT.</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears N. 32° W., 53 lks. dist., mkd. X BT at the base.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 4 ins. above ground, in a mound of stone, 2½ ft. base, to top, bears S. 26°03' W., 3.87 chs. dist., with cap mkd.</p>	

Subdivision of Section 24
 T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">S24 C N-N 1/64 C RLS 13056 1982</p> <p>From this same point a Forest Service aluminum post, 2½ ins. diam., projecting 24 ins. above ground, in a mound of stone, 2½ ft. base, 1 ft. high, bears S. 89°03' W., 1.76 chs. dist., with cap mkd.</p> <div style="text-align: center;"> <p>T11½N R11E</p> <p>S24</p> <hr style="width: 50px; margin: 0 auto;"/> <p style="margin: 0 auto 10px auto;">NW COR</p> <p style="margin: 0 auto 10px auto;"> </p> <p style="margin: 0 auto 10px auto;">LOT 5</p> </div> <p style="text-align: center;">RLS 13056 1980</p> <p>These monuments were established using improper procedures by Patterson and Associates under Forest Service contract and are not utilized in the course of this survey.</p> <p>From this same point a sandstone, 11 x 4 x 15 ins. above ground, in a scattered mound of stone, bears N. 25° W., 15.8 lks. dist., mkd. H 5 on S face, from which a juniper 21 ins. diam., bears 54° E., 26 lks. dist., mkd. W H 5. This monument is of unknown origin and is not utilized in the course of this survey.</p>
72.45	<p>Intersect the S bdy. of sec. 34, T. 12 N., R. 11 E.</p> <p>Point for the 1/4 sec. cor. of sec. 24, is at midpoint on the N bdy. of sec. 24.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 24 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <div style="text-align: center;"> <p><u>T12N R11E</u></p> <p><u>1/4 S24</u></p> <p>T11½N R11E</p> <p>1982</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears S. 39° E., 32 lks. dist., mkd. 1/4 S24 BT.</p> <p>From this point an angle point on the S bdy. of sec. 34, T. 12 N., R. 11 E., bears S. 89°53' W., 1.83 chs. dist., heretofore described.</p>
	<p>From the 1/4 sec. cor. of secs. 19 and 24, T. 11½ N., Rs. 11 and 11½ E.</p> <p>N. 89°46' W., on the E and W center line of sec. 24.</p> <p>Over rolling land, through medium to dense timber.</p>
17.81	Creek, 10 lks. wide, 1 ft. deep, course SW.
19.82	Track road, bears N. 30° E. and S. 30° W.
20.07	Point for the center E 1/16 sec. cor. of sec. 24.

Subdivision of Section 24
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an aluminum post, 36 ins. long, ¾ in. diam., 26 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T11½N R11E C $\frac{E\ 1/16}{S24}$ C 1982</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 4 ins. diam., bears S. 28° E., 37½ lks. dist., mkd. X BT at the base.</p> <p style="padding-left: 40px;">A juniper, 7 ins. diam., bears S. 79° W., 34½ lks. dist., mkd. CE 1/16 S24 BT.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 3 ins. above ground, bears N. 89°59' W., 51.5 lks. dist., with cap mkd.</p> <p style="text-align: center;">C $\frac{E\ 1/16}{S24}$ C RLS 13056 1980</p> <p>This monument was established using improper procedures by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p> <p>From this same point a triangular shaped sandstone, projecting 12 x 4 ins. above ground, mkd. H 9 on E face, bears S. 51°36' W., 16.7 lks. dist., from which a pine, 25 ins. diam., bears N. 39° W., 58 lks. dist., mkd. 9 through a partially healed blaze. This monument is of unknown origin, and is not utilized in the course of this survey.</p>	
40.14	The center 1/4 sec. cor. of sec. 24.	
49.44	Ellison Creek, 20 lks. wide, 1 ft. deep, course southerly.	
50.14	<p>Point for the center E-W 1/64 sec. cor. of sec. 24.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 24 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">C $\frac{E-W\ 1/64}{S24}$ C 1982</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears S. 13° E., 5 lks. dist., mkd. X BT at the base.</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears S. 40° W., 38½ lks. dist., mkd. C-E-W 1/64 S24 BT.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 8 ins. above ground, bears S. 89°30' W., 78 lks. dist., with cap mkd.</p>	

Subdivision of Section 24
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS	
	S24 E-W C ————— C 1/64 RLS 13056 1980
	This monument was established using improper procedures by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.
	From this same point a sandstone, 12 x 6 x 10 ins. above ground, mkd. H 2 on E face, bears S. 71°34' E., 5.4 lks. dist., from which a pine, 24 ins. diam., bears East, 22 lks. dist., mkd. W 2. This monument is of unknown origin, and is not utilized in the course of this survey.
55.88	Track road, bears N. 30° E. and S. 30° W.
60.14	Point for the center W 1/16 sec. cor. of sec. 24. Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.
	T11½N R11E W 1/16 C ————— C S24 1982
	from which A pine, 8 ins. diam., bears S. 61° W., 25 lks. dist., mkd. CW 1/16 S24 BT. A juniper, 7 ins. diam., bears N. 15° W., 7½ lks. dist., mkd. CW 1/16 S24 BT.
	From this same point a ½ in. diam. rebar, projecting 3 ins. above ground, bears S. 88°43' W., 51.7 lks. dist. This monument was established using improper procedures by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.
80.14	The 1/4 sec. cor. of secs. 23 and 24.
	NE 1/4 of Section 24 _____
	From the center E 1/16 sec. cor. of sec. 24. N. 0°15' E., on the N and S center line of the NE 1/4 of sec. 24.
19.82	Point for the NE 1/16 sec. cor., at intersection with the E and W center line of the NE 1/4 of sec. 24. Set an aluminum post, 36 ins. long, ¾ in. diam., 24 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.
	T11½N R11E NE 1/16 S24 1982

Subdivision of Section 24
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>from which</p> <p>A pine, 9 ins. diam., bears N. 32° E., 40 lks. dist., mkd. X BT at the base.</p> <p>A pine, 11 ins. diam., bears S. 27° E., 22 lks. dist., mkd. NE 1/4 S24 BT.</p> <p>Cor. is located 5 lks. E of a fence, bears N and S.</p> <p>29.74 Point for the center N-NE 1/64 sec. cor. of sec. 24, at proportionate dist.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 26 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S24 C-N-NE 1/64 1982</p>	
	<p>from which</p> <p>A pine, 5 ins. diam., bears N. 7° E., 23 lks. dist., mkd. X BT at the base.</p> <p>A pine, 10 ins. diam., bears S. 41° E., 49 lks. dist., mkd. C-N-NE 1/64 S24 BT.</p> <p>Cor. is located 10 lks. E of fence, bears N and S.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 5 ins. above ground, bears S. 25°48' W., 3.76 chs. dist., with cap mkd.</p> <p style="text-align: center;">C-N-NE 1/64 — S24 RLS 13056 1980</p> <p>This monument was established using improper procedures by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	
32.63	<p>Intersect the S bdy. of sec. 34, T. 12 N., R. 11 E.</p> <p>Point for the E 1/16 sec. cor. of sec. 24, at proportionate dist., on the N bdy. of sec. 24.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 26 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R11E — E 1/16 S24 T11½N R11E 1982</p> <p>from which</p> <p>A pine, 18 ins. diam., bears S. 4° E., 40½ lks. dist., mkd. E 1/16 S24 BT.</p>	

Subdivision of Section 24
 T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>A fence cor., bears West, 13½ lks. dist., fence extending S and N. 80° W., with a sandstone, 12 x 16 x 4 ins., mkd. H 8, lying loose along-side.</p> <p>From this point the cor. of secs. 34 and 35, T. 12 N., R. 11 E., bears N. 89°53' E., 15.79 chs. dist., heretofore described.</p> <p>From this same point a Forest Service aluminum post, 2½ ins. diam., projecting 5 ins. above ground, bears N. 89°17' W., 2.09 chs. dist., with cap mkd.</p> <p style="text-align: center;">T12N R11E S34 <hr style="width: 50px; margin: 0 auto;"/> E 1/16 S24 T11½N R11E RLS 13056 1980</p> <p>This monument was established using improper procedures by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p> <hr style="width: 200px; margin: 10px auto;"/> <p>From the N 1/16 sec. cor. of secs. 19 and 24, on the E bdy. of the Tp., heretofore described.</p> <p>N. 89°48' W., on the E and W center line of the NE 1/4 of sec. 24.</p>	
20.01	The NE 1/16 sec. cor. of sec. 24.	
30.01	<p>Point for the center W-NE 1/64 sec. cor. of sec. 24.</p> <p>Set an aluminum post, 36 ins. diam., 30 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S24 C-W-NE 1/64 1982</p>	
40.02	<p>The center N 1/16 sec. cor. of sec. 24.</p> <hr style="width: 200px; margin: 10px auto;"/> <p>From the center W-NE 1/64 sec. cor. of sec. 24.</p> <p>N. 0°21' E., on the N and S center line of the NW 1/4 of the NE 1/4 of sec. 24.</p>	
9.92	<p>Point for the NW-NE 1/64 sec. cor., at intersection with the E and W center line of the NW 1/4 of the NE 1/4 of sec. 24.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S24 NW-NE 1/64 1982</p>	

Subdivision of Section 24
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>from which</p> <p>A pine, 11 ins. diam., bears N. 40° W., 24 lks. dist., mkd. NW-NE 1/64 S24 BT.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 24 ins. above ground, in a mound of stone, 2½ ft. base, 1 ft. high, bears N. 88°07' W., 1.77 chs. dist., with cap mkd.</p> <p style="text-align: center;">T11½N R11E S24 NE COR LOT 5 RLS 13056 1980</p> <p>This monument was established using improper procedures by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p> <p>From this same point a sandstone, 14 x 16 x 8 ins. above ground, mkd. H 6 on S face, bears N. 58° W., 15.5 lks. dist. This monument is of unknown origin and is not utilized in the course of this survey.</p>	
12.59	Fence, bears E and W.	
12.75	<p>Intersect the S bdy. of sec. 34, T. 12 N., R. 11 E.</p> <p>Point for the W-E 1/64 sec. cor. of sec. 24, at proportionate dist., on the N bdy. of sec. 24.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R11E W-E 1/64 S24 T11½N R11E 1982</p> <p>from which</p> <p>A pine, 12 ins. diam., bears S. 40° W., 29½ lks. dist., mkd. WE 1/64 S24 BT.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 24 ins. above ground, in a mound of stone, 2 ft. base, 1 ft. high, bears N. 89°02' W., 1.86 chs. dist., with cap mkd.</p> <p style="text-align: center;">T12N R11E S34 WE 1/64 S24 T11½N R11E RLS 13056 1980</p> <p>This monument was established using improper procedures by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	

Subdivision of Section 24
 T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>From this same point a sandstone, 16 x 10 x 4 ins. above ground, mkd. H 7 on S face, bears N. 78° W., 14 lks. dist. This monument is of unknown origin and is not utilized in the course of this survey.</p> <hr/> <p>From the center N-NE 1/64 sec. cor. of sec. 24.</p> <p>N. 89°48' W., on the E and W center line of the NW 1/4 of the NE 1/4 of sec. 24.</p>
9.99	The NW-NE 1/64 sec. cor. of sec. 24.
11.30	Ellison Creek, 15 lks. wide, 1 ft. deep, course southerly.
19.98	The center N-N 1/64 sec. cor of sec. 24.
	<hr/> <p style="text-align: center;">SW 1/4 of Section 24</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 24 and 25.</p> <p>N. 0°23.5' E., on the N and S center line of the SW 1/4 of sec. 24.</p>
13.07	Ellison Creek, 20 lks. wide, 1 ft. deep, course S. 20° W.
19.97	<p>Point for the SW 1/16 sec. cor., at intersection with the E and W center line of the SW 1/4 of sec. 24.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T11½N R11E SW 1/16 S24 1982</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 15° E., 8½ lks. dist., mkd. X BT at the base.</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears N. 85° W., 9½ lks. dist., mkd. SW 1/16 S24 BT.</p> <p>Cor. is located on a steep eastern slope.</p> <p>From this same point a Forest Service aluminum post, 2½ ins. diam., projecting 6 ins. above ground, bears S. 87°39' W., 27 lks. dist., with cap mkd.</p> <p style="text-align: center;">SW 1/16 S24 _____ RLS 13056 1980</p>
31.13	Track road, bears N. 15° E. and S. 15° W.
39.94	The center W 1/16 sec. cor. of sec. 24.

Subdivision of Section 24
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>From the center S 1/16 sec. cor. of sec. 24.</p> <p>N. 89°47' W., on the E and W center line of the SW 1/4 of sec. 24.</p>	
10.00	<p>Point for the center E-SW 1/64 sec. cor. of sec. 24.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 28 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S24 C-E-SW 1/64 1982</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 15 ins. diam., bears S. 76° E., 11½ lks. dist., mkd. C-E-SW 1/64 S24 BT.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 12 ins. above ground, in a mound of stone, 1 ft. base, 6 ins. high, bears S. 89°02' W., 41.2 lks. dist., with cap mkd.</p> <p style="text-align: center;">S24 C-E-SW</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1/64 RLS 13056 1980</p> <p>This monument was established using improper procedures by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	
10.20	Track road, bears S. 35° E. and N. 35° W.	
20.00	The SW 1/16 sec. cor. of sec. 24.	
22.74	Track road, bears N. 30° E. and S. 30° W.	
40.00	The S 1/16 sec. cor. of secs. 23 and 24.	
19.97	<p>From the E-W 1/64 sec. cor. of secs. 24 and 25.</p> <p>N. 0°25' E., on the N and S center line of the SE 1/4 of the SW 1/4 of sec. 24.</p> <p>The center E-SW 1/64 sec. cor. of sec. 24.</p> <hr style="width: 50%; margin: auto;"/> <p style="text-align: center;">NW 1/4 of Section 24</p> <hr style="width: 50%; margin: auto;"/> <p>From the center W 1/16 sec. cor. of sec. 24.</p> <p>N. 0°28' E., on the N and S center line of the NW 1/4 of sec. 24.</p>	
9.91	<p>Point for the center S-NW 1/64 sec. cor. of sec. 24.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 24 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p>	

Subdivision of Section 24
 T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">S24 C-S-NW 1/64 1982</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 20 ins. diam., bears S. 44° W., 24½ lks. dist., mkd. X BT at the base.</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears N. 45° W., 32½ lks. dist., mkd. C-S-NW 1/64 BT.</p>	
<p>19.81</p>	<p>Point for the NW 1/16 sec. cor., at intersection with the E and W center line of the NW 1/4 of sec. 24.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 26 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T11½N R11E NW 1/16 S24 1982</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 89° E., 14 lks. dist., mkd. NW 1/16 S24 BT.</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears S. 29° W., 4 lks. dist., mkd. NW 1/16 S24 BT.</p> <p>From this point a ½ in. diam. rebar, projecting 4 ins. above ground, bears N. 80°27' W., 76.6 lks. dist. This monument was established using improper procedures by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	
<p>32.39</p>	<p>Intersect the S bdy. of sec. 34, T. 12 N., R. 11 E.</p> <p>Point for the W 1/16 sec. cor. of sec. 24, at proportionate dist., on the N bdy. of sec. 24.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 25 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R11E <hr style="width: 10%; margin: auto;"/> W 1/16 S24 T11½N R11E 1982</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 16 ins. diam., bears S. 39° E., 42 lks. dist., mkd. W 1/16 S24 BT.</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 37° W., 17½ lks. dist., mkd. W 1/16 S24 BT.</p> <p>From this point the 1/4 sec. cor. of sec. 34, T. 12 N., R. 11 E., bears N. 89°50' E., 15.75 chs. dist., heretofore described.</p> <hr style="width: 20%; margin: auto;"/>	

Subdivision of Section 24
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS	
	From the center N 1/16 sec. cor. of sec. 24.
	N. 89°47' W., on the E and W center line of the NW 1/4 of sec. 24.
9.50	Track road, bears N. 15° E. and S. 15° W.
10.00	Point for the center E-NW 1/64 sec. cor. of sec. 24.
	Set an aluminum post, 36 ins. long, ¾ in. diam., 22 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.
	S24
	C-E-NW
	1/64
	1982
	from which
	A forked juniper, 24 ins. diam., bears N. 31° E., 22 lks. dist., mkd. X BT at the base.
	A pine, 8 ins. diam., bears S. 60° W., 46½ lks. dist., mkd. C-E-NW 1/64 S24 BT.
	From this point a Forest Service aluminum post, 2½ ins. diam., projecting 8 ins. above ground, in a mound of stone, 3 ft. base, to top, bears N. 82°01' W., 1.14 chs. dist., with cap mkd.
	C-E-NW
	1/64
	S24
	RLS 13056 1980
	This monument was established using improper procedures by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.
19.99	The NW 1/16 sec. cor. of sec. 24.
39.98	The N 1/16 sec. cor. of secs. 23 and 24.

	From the center E-W 1/64 sec. cor. of sec. 24.
	N. 0°27' E., on the N and S center line of the SE 1/4 of the NW 1/4 of sec. 24.
9.91	Point for the SE-NW 1/64 sec. cor., at intersection with the E and W center line of the SE 1/4 of the NW 1/4 of sec. 24.
	Set an aluminum post, 36 ins. long, ¾ in. diam., 16 ins. in the ground, in a mound of stone, 4 ft. base, to top, with cap mkd.
	S24
	SE-NW
	1/64
	1982
	from which

Subdivision of Section 24
 T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS	<p>A pine, 13 ins. diam., bears S. 19° E., 22 lks. dist., mkd. SE-NW 1/64 S24 BT.</p> <p>A pine, 5 ins. diam., bears N. 69° W., 23½ lks. dist., mkd. X BT at the base.</p>
14.87	<p>Point for the center N-SE-NW 1/256 sec. cor. of sec. 24.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 26 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S24 C-N-SE-NW 1/256 1982</p> <p>from which</p> <p>A pine, 10 ins. diam., bears S. 70° W., 21 lks. dist., mkd. C-N-SE-NW 1/256 S24 BT.</p> <p>A pine, 7 ins. diam., bears N. 15° W., 15½ lks. dist., mkd. X BT at the base.</p> <p>From this point a sandstone, projecting 13 x 5 x 16 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, mkd. H 3 on S face, bears N. 28°24' E., 12.6 lks. dist. This monument is of unknown origin and is not utilized in the course of this survey.</p>
19.82	<p>The center E-NW 1/64 sec. cor. of sec. 24.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the point for the center S-N 1/64 sec. cor. of sec. 24.</p> <p>N. 89°46' W., on the E and W center line of the SE 1/4 of the NW 1/4 of sec. 24.</p>
10.00	<p>The SE-NW 1/64 sec. cor. of sec. 24.</p>
20.00	<p>The center S-NW 1/64 sec. cor. of sec. 24.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center N-S-N 1/256 sec. cor. of sec. 24.</p> <p>N. 89°46.5' W., on the E and W center line of the NE 1/4 of the SE 1/4 of the NW 1/4 of sec. 24.</p>
10.00	<p>The center N-SE-NW 1/256 sec. cor. of sec. 24.</p>
<p>Subdivision of Section 25 T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona</p>	
39.72	<p>From the 1/4 sec. cor. of secs. 25 and 36.</p> <p>N. 0°06' E., on the N and S center line of sec. 25.</p> <p>Over rolling land, through dense ponderosa pine, juniper and oak.</p> <p>Point for the center 1/4 sec. cor., at intersection with the E and W center line of sec. 25.</p>

Subdivision of Section 25
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an aluminum post, 30 ins. long, ¾ in. diam., 23 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T11½N R11E C 1/4 S25 1981</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S. 31½° W., 18 lks. dist., mkd. C 1/4 S25 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears N. 42° W., 22.5 lks. dist., mkd. C 1/4 S25 BT.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 16 ins. above ground, in a mound of stone, 2½ ft. base, to top, bears North, 2.1 lks. dist., with cap mkd.</p> <p style="text-align: center;">T11½N R11E C 1/4 S 25 RLS 13056 1980</p> <p>This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	
59.67	<p>Point for the center N 1/16 sec. cor. of sec. 25.</p> <p>Set an aluminum post, 30 ins. long, ¾ in. diam., 22 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T11½N R11E C N 1/16 S25 C 1981</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears N. 54° E., 21.5 lks. dist., mkd. C-N 1/16 S25 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S. 88° W., 30 lks. dist., mkd. C-N 1/16 S25 BT.</p> <p>Raise a mound of stone, 4 ft. base, 2½ ft. high, W of cor.</p> <p>From this point a ½ in. diam. rebar, projecting 6 ins. above ground, bears S. 17°37' W., 6.6 lks dist. This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	
69.645	<p>Point for the center N-N 1/64 sec. cor. of sec. 25, falls on a sandstone outcropping, 6 x 3 ft., projecting 9 ins. above ground.</p>	

Subdivision of Section 25
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

<p>CHAINS</p> <p>79.62</p> <p>40.08</p> <p>60.14</p> <p>80.20</p>	<p>Set a brass tablet, 3 1/4 ins. diam., 3½ in. stem, in a drill hole, in concrete, with top mkd.</p> <p style="text-align: center;">S25 C-N-N 1/64 1981</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S. 84° E., 31 lks. dist., mkd. C-N-N 1/64 S25 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S. 44° W., 13 lks. dist., mkd. C-N-N 1/64 S25 BT.</p> <p>From this point a ½ in. diam. rebar, projecting 2 ins. above ground, bears N. 23°12' W., 4.6 lks. dist. This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p> <hr/> <p>The 1/4 sec. cor. of secs. 24 and 25.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 30.</p> <p>West, on the E and W center line of sec. 25.</p> <p>Over rolling land, through dense ponderosa pine, juniper, oak and manzanita.</p> <p>The center 1/4 sec. cor. of sec. 25.</p> <p>Point for the center W 1/16 sec. cor. of sec. 25.</p> <p>Set an aluminum post, 30 ins. long, ¾ in. diam., 8 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T11½N R11E W 1/16 C ————— C S25 1981</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 35° E., 72 lks. dist., mkd. C-W 1/16 S25 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears S. 28° E., 49 lks. dist., mkd. C-W 1/16 S25 BT.</p> <p>From this point a ½ in. diam. rebar, projecting 1 in. above ground, bears N. 9°28' E., 1.2 lks. dist. This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p> <hr/> <p>The 1/4 sec. cor. of secs. 25 and 26.</p> <hr/> <p style="text-align: center;">NW 1/4, Section 25</p> <hr/> <p>From the center W 1/16 sec. cor. of sec. 25.</p>	
---	--	--

Subdivision of Section 25
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>N. 0°11' E., on the N and S center line of the NW 1/4 of sec. 25.</p> <p>Over rolling land, through dense ponderosa pine, juniper and oak.</p> <p>10.00 Point for the center S-NW 1/64 sec. cor. of sec. 25.</p> <p>Set an aluminum post, 30 ins. long, ¾ in. diam., 22 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S25 C-S-NW 1/64 1981</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears S. 88° E., 33 lks. dist. mkd. C-S-NW 1/64 S25 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S. 16° E., 23 lks. dist., mkd. C-S-NW 1/64 S25 BT.</p> <p style="padding-left: 40px;">A fence cor., bears N. 66° W., 44 lks. dist., fences extend N. 20° E., S. 35° E. and W.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 12 ins. above ground, in a mound of stone, 2 ft. base, to top, bears S. 60°57' E., 1 lk. dist., with cap mkd.</p> <p style="text-align: center;">C-S-NW 1/64 —+— S 25 RLS 13056 1980</p> <p>This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>
<p>20.00</p>	<p>Point for the NW 1/16 sec. cor., at intersection with the E and W center line of the NW 1/4 of sec. 25.</p> <p>Set an aluminum post, 30 ins. long, ¾ in. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T11½N R11E NW 1/16 S25 1981</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears N. 29° E., 44 lks. dist., mkd. NW 1/16 S25 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears S. 64° E., 56 lks. dist., mkd. NW 1/16 S25 BT.</p> <p>Raise a mound of stone, 1½ ft. base, 1½ ft. high, W of cor.</p>

Subdivision of Section 25
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 12 ins. above ground, in a mound of stone, 2½ ft. base, to top, bears S. 17°56' E., 3.6 lks. dist., with cap mkd.</p> <p style="text-align: center;">NW 1/16 $\begin{array}{c} \\ \hline S \quad \quad 25 \\ \end{array}$ RLS 13056 1980</p>	
<p>30.00</p>	<p>This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p> <p>Point for the center N-NW 1/64 sec. cor. of sec. 25.</p> <p>Set an aluminum post, 30 ins. long, ¾ in. diam., 25 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S25 C-N-NW 1/64 1981</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S. 4° E., 34 lks. dist., mkd. C-N-NW 1/64 S25 BT.</p> <p style="padding-left: 40px;">A fence post at the W end of a fence line, extending E only, bears S. 40° E., 4 lks. dist.</p> <p>Raise a mound of stone, 2 ft. base, 1½ ft. high, W of cor.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 8 ins. above ground, bears S. 20°26' E., 5.4 lks. dist., with cap mkd.</p> <p style="text-align: center;">C-N-NW 1/64 $\begin{array}{c} \\ \hline S \quad \quad 25 \\ \end{array}$ RLS 13056 1980</p>	
<p>40.00</p>	<p>The W 1/16 sec. cor. of secs. 24 and 25.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center N 1/16 sec. cor. of sec. 25.</p> <p>N. 89°52' W., on the E and W center line of the NW 1/4 of sec. 25.</p> <p>Over rolling land, through dense ponderosa pine, juniper and oak.</p>	
<p>10.01</p>	<p>Point for the center E-NW 1/64 sec. cor. of sec. 25.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, with cap mkd.</p>	

Subdivision of Section 25
 T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">S25 C-E-NW 1/64 1982</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S. 34° E., 27 lks. dist., mkd. C-E-NW 1/64 S25 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S. 39½° W., 29.5 lks. dist., mkd. C-E-NW 1/64 S25 BT.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.</p> <p>From this point a ½ in. diam. rebar, projecting 2 ins. above ground, bears S. 17°06' E., 2.7 lks. dist. This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	
20.02	The NW 1/16 sec. cor. of sec. 25.	
40.05	The N 1/16 sec. cor. of secs. 25 and 26.	
	<p style="text-align: center;">—————</p> <p>From the center E-NW 1/64 sec. cor. of sec. 25.</p> <p>N. 0°08' E., on the N and S center line of the NE 1/4 of the NW 1/4 of sec. 25.</p> <p>Over rolling land, through dense ponderosa pine, juniper and oak.</p>	
9.99	<p>Point for the NE-NW 1/64 sec. cor., at intersection with the E and W center line of the NE 1/4 of the NW 1/4 of sec. 25.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 26 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p>	
	<p style="text-align: center;">S25 NE-NW 1/64 1982</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears N. 55° E., 45.5 lks. dist., mkd. NE-NW 1/64 S25 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears S. 25° W., 41 lks. dist., mkd. NE-NW 1/64 S25 BT.</p> <p>Cor. is located 4 lks. S of a fence cor., fences extend N and W.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 18 ins. above ground, in a mound of stone, 2½ ft. base, 1 ft. high, bears N. 19°59' E., 1.2 lks. dist., with cap mkd.</p>	

Subdivision of Section 25
 T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>NE-NW</p> <p>┌</p> <p>1/64</p> <p>S25</p> <p>RLS 13056 1980</p>	
	<p>This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	
19.98	<p>The E-W 1/64 sec. cor. of secs. 24 and 25.</p> <hr/> <p>From the center N-N 1/64 sec. cor. of sec. 25.</p> <p>N. 89°48' W., on the E and W center line of the NE 1/4 of the NW 1/4 of sec. 25.</p> <p>Over rolling land, through dense ponderosa pine, juniper and oak.</p>	
10.00	<p>The NE-NW 1/64 sec. cor. of sec. 25.</p>	
20.00	<p>The center N-NW 1/64 sec. cor. of sec. 25.</p> <hr/> <p>From the center S-NW 1/64 sec. cor. of sec. 25.</p> <p>N. 89°56' W., on the E and W center line of the SW 1/4 of the NW 1/4 of sec. 25.</p> <p>Over rolling land, through dense ponderosa pine, juniper and oak.</p>	
20.05	<p>The S-N 1/64 sec. cor. of secs. 25 and 26.</p> <hr/> <p style="text-align: center;">Subdivision of Section 26 T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 35.</p> <p>N. 0°12' E., on the N and S center line of sec. 26.</p> <p>Over rolling land, through dense ponderosa pine, juniper and oak.</p>	
39.79	<p>Point for the center 1/4 sec. cor., at intersection with the E and W center line of sec. 26.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T11½N R11E C 1/4 S26 1982</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N. 59° E., 61.5 lks. dist., mkd. C 1/4 S26 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S. 4° W., 30 lks. dist., mkd. C 1/4 S26 BT.</p>	

Subdivision of Section 26
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 6 ins. above ground, bears S. 15°15' E., 3.4 lks. dist., with cap mkd.</p> <p style="text-align: center;">T11½N R11E C 1/4 S 26 1980</p> <p>This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	
59.735	<p>Point for the center N 1/16 sec. cor. of sec. 26, falls on limestone bedrock.</p> <p>Set aluminum tablet, 3 1/4 ins. diam., 3½ in. stem, in a drill hole, in concrete, with top mkd.</p> <p style="text-align: center;">T11½N R11E C N 1/16 S26 C 1982</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears N. 79° E., 34.5 lks. dist., mkd. C-N 1/16 S26 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 5 ins. diam., bears S. 8° E., 60 lks. dist., mkd. C-N 1/16 S26 BT.</p> <p>From this point a ½ in. diam. rebar, projecting 1 in. above ground, bears S. 40°22' E., 2.6 lks. dist. This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	
79.68	<p>The 1/4 sec. cor. of secs. 23 and 26.</p>	
9.955	<p>From the 1/4 sec. cor. of secs. 25 and 26.</p> <p>N. 89°36' W., on the E and W center line of sec. 26.</p> <p>Over rolling land, through dense ponderosa pine, juniper and oak.</p> <p>Point for the center E-E 1/64 sec. cor. of sec. 26.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 28 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S26 C-E-E 1/64 1982</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S. 63° W., 82 lks. dist., mkd. C-E-E 1/64 S26 BT.</p> <p style="padding-left: 40px;">An alligator juniper, 6 ins. diam., bears N. 28° W., 41 lks. dist., mkd. C-E-E 1/64 S26 BT.</p>	

Subdivision of Section 26
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>From this point a ½ in. diam. rebar, projectin 2 ins. above ground, bears N. 63°26' E., .2 lk. dist. This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	
19.91	<p>Point for the center E 1/16 sec. cor. of sec. 26.</p>	
	<p>Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">T11½N R11E E 1/16 C ————— C S26 1982</p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">An alligator juniper, 6 ins. diam., bears S. 53° E., 15 lks. dist., mkd. C-E 1/16 S26 BT.</p>	
	<p style="padding-left: 40px;">An alligator juniper, 10 ins. diam., bears S. 46° W., 31.5 lks. dist., mkd. C-E 1/16 S26 BT.</p>	
	<p>Raise a mound of stone, 2½ ft. base, 1 ft. high, N of cor.</p>	
	<p>From this point a ½ in. diam. rebar, projecting 2 ins. above ground, bears S. 29°45' E., .8 lk. dist. This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	
39.82	<p>The center 1/4 sec. cor. of sec. 26.</p>	
80.04	<p>The 1/4 sec. cor. of secs. 26 and 27.</p>	
	<p style="text-align: center;">NE 1/4, Section 26</p> <hr style="width: 20%; margin: auto;"/>	
	<p>From the center E 1/16 sec. cor. of sec. 26.</p>	
	<p>N. 0°15' E., on the N and S center line of the NE 1/4 of sec. 26.</p>	
	<p>Over rolling land, through dense ponderosa pine, juniper and oak.</p>	
9.995	<p>Point for the center S-NE 1/64 sec. cor. of sec. 26.</p>	
	<p>Set an aluminum post, 36 ins. long, ¾ in. diam., 29 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p>	
	<p style="text-align: center;">S26 C-S-NE 1/64 1982</p>	
	<p>from which</p>	

Subdivision of Section 26
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

	CHAINS		
		<p>A ponderosa pine, 9 ins. diam., bears N. 15½° E., 28 lks. dist., mkd. C-S-NE 1/64 S26 BT.</p> <p>A ponderosa pine, 12 ins. diam., bears S. 54° E., 18 lks. dist., mkd. C-S-NE 1/64 S26 BT.</p> <p>From this point a ½ in. diam. rebar, projecting 1 in. above ground, bears S. 27°54' E., 1.9 lks. dist. This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	
	19.99	<p>Point for the NE 1/16 sec. cor., at intersection with the E and W center line of the NE 1/4 of sec. 26.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 28 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T11½N R11E NE 1/16 S26 1982</p> <p>from which</p> <p>A ponderosa pine, 7 ins. diam., bears N. 27° E., 17 lks. dist., mkd. NE 1/16 S26 BT.</p> <p>A ponderosa pine, 9 ins. diam., bears S. 60° E., 17.5 lks. dist., mkd. NE 1/16 S26 BT.</p> <p>From this point a ½ in. diam. rebar, projecting 1 in. above ground, bears S. 85°55' E., 2.8 lks. dist. This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	
	29.99	<p>Point for the center N-NE 1/64 sec. cor. of sec. 26.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S26 C-N-NE 1/64 1982</p> <p>from which</p> <p>A ponderosa 8 ins. diam., bears S. 75° E., 44 lks. dist., mkd. C-N-NE 1/64 S26 BT.</p> <p>An alligator juniper, 10 ins. diam., bears N. 13° W., 54 lks. dist., mkd. C-N-NE 1/64 S26 BT.</p> <p>From this point a ½ in. diam. rebar, projecting 2 ins. above ground, bears N. 84°17' E., 2 lks. dist. This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	

Subdivision of Section 26
 T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS		
39.99	<p>The E 1/16 sec. cor. of secs. 23 and 26.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 25 and 26.</p> <p>N. 89°45' W., on the E and W center line of the NE 1/4 of sec. 26.</p> <p>Over rolling land, through dense ponderosa pine, juniper and oak.</p>	
9.96	<p>Point for the center E-NE 1/64 sec. cor. of sec. 26.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 28 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S26 C-E-NE 1/64 1982</p> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 9 ins. diam., bears S. 30° W., 49 lks. dist., mkd. C-E-NE 1/64 S26 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears N. 75° W., 35 lks. dist., mkd. C-E-NE 1/64 S26 BT.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, N of cor.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 28 ins. above ground, in a mound of stone, 3 ft. base, 2 ft. high, bears S. 56°19' W., .4 lk. dist., with cap mkd.</p> <p style="text-align: center;">C-E-NE 1/64 S 26 RLS 13056 1980</p> <p>This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	
19.92	<p>The NE 1/16 sec. cor. of sec. 26.</p>	
39.84	<p>The center N 1/16 sec. cor. of sec. 26.</p> <hr/> <p>From the center E-NE 1/64 sec. cor. of sec. 26.</p> <p>N. 0°17' E., on the N and S center line of the NE 1/4 of the NE 1/4 of sec. 26.</p> <p>Over rolling land, through dense ponderosa pine, juniper and oak.</p>	
10.01	<p>Point for the NE-NE 1/64 sec. cor., at intersection with the E and W center line of the NW 1/4 of the NE 1/4 of sec. 26.</p>	

Subdivision of Section 26
 T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an aluminum post, 36 ins. long, ¾ in. diam., 28 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S26 NE-NE 1/64 1982</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S. 20° W., 68 lks. dist., mkd. NE-NE 1/64 S26 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 64° W., 12 lks. dist., mkd. NE-NE 1/64 S26 BT.</p> <p>Cor. is located 60 lks. W of a wash in a small canyon, drains southerly.</p> <p>From this point a Forest Service aluminum post, 2½ ins. diam., projecting 24 ins. above ground, in a mound of stone, 3½ ft. base, to top, bears S. 63°26' W., .7 lk. dist., with cap mkd.</p> <p style="text-align: center;">NE-NE 1/64 S 26 RLS 13056 1980</p> <p>This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey.</p>	
20.02	<p>The E-E 1/64 sec. cor. of secs. 23 and 26.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the N-N 1/64 sec. cor. of secs. 25 and 26.</p> <p>N. 89°49.5' W., on the E and W center line of the NE 1/4 of the NE 1/4 of sec. 26.</p> <p>Over rolling land, through dense ponderosa pine, juniper and oak.</p>	
9.965	<p>The NE-NE 1/64 sec. cor. of sec. 26.</p>	
19.93	<p>The center N-NE 1/64 sec. cor. of sec. 26.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center E-E 1/64 sec. cor. of sec. 26.</p> <p>N. 0°17' E., on the N and S center line of the SE 1/4 of the NE 1/4 of sec. 26.</p> <p>Over rolling land, through dense ponderosa pine, juniper and oak.</p>	
10.01	<p>Point for the SE-NE 1/64 sec. cor., at intersection with the E and W center line of the SE 1/4 of the NE 1/4 of sec. 26.</p> <p>This point is monumented with a Forest Service aluminum post, 2½ ins. diam., projecting 20 ins. above ground, in a mound of stone, 2 ft. base, 1½ ft. high, with cap mkd.</p>	

Subdivision of Section 26
T. 11½ N., R. 11 E., Gila and Salt River Mer., Arizona

CHAINS	SE-NE 1/64 <hr style="width: 10%; margin: 0 auto;"/> S 26 RLS 13056 1980
	<p>This monument was established by Patterson and Associates under Forest Service contract and is not utilized in the course of this survey, and was removed.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 18 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S26 SE-NE 1/64 1982</p> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 4 ins. diam., bears S. 56½° E., 100 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">An alligator juniper, 10 ins. diam., bears S. 33½° W., 70 lks. dist., mkd. SE-NE 1/64 S26 BT.</p>
20.02	<p>The center E-NE 1/64 sec. cor. of sec. 26.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the N-S 1/64 sec. cor. of secs. 25 and 26.</p> <p>N. 89°41' W., on the E and W center line of the SE 1/4 of the NE 1/4 of sec. 26.</p> <p>Over rolling land, through dense ponderosa pine, juniper and oak.</p>
9.96	<p>The SE-NE 1/64 sec. cor. of sec. 26.</p>
19.92	<p>The center S-NE 1/64 sec. cor. of sec. 26.</p>
	<p>GENERAL DESCRIPTION</p> <p>The land encompassed in this survey is located approximately 20 miles northeasterly of Payson, Arizona. The elevation ranges from about 5,600 to 6,250 ft. above sea level.</p> <p>The vegetation consists of ponderosa pine, juniper, oak and manzanita.</p> <p>Access is by way of a graded gravel road and numerous unimproved track roads.</p>

Form 9600-11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
William C. Gabonay	Cadastral Surveyor
Kevin L. Miller	Survey Technician
Donald L. Brewer	Survey Aid
Delbert L. Bybee	Survey Aid
Neil A. Hemminger	Survey Aid

CERTIFICATE OF SURVEY

Paul L. Reeves,
 (We), John P. Bennett III, Supervisory Cadastral Surveyors, HEREBY
 CERTIFY upon honor that, in pursuance of special instructions bearing date of the 2nd day
 of October, 1981, (We) have dependently resurveyed a portion of
 the south boundary (Black Mesa Forest Reserve) Township 12 North,
 Range 11 East, dependently resurveyed a portion of the east boundary and
 subdivisional lines and surveyed subdivisions in secs. 24, 25 and 26,
 Township 11½ North, Range 11 East,

of the Gila and Salt River Meridian, in the State of Arizona, which
 are represented in the foregoing field notes as having been executed by (me), (us) and under (my)
 (our) direction; and that said survey has been made in strict conformity with said special instruc-
 tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in
 specific manner described in the foregoing field notes.

4/04/83 (Date) Paul L. Reeves (Cadastral Surveyor)
4-4-83 (Date) John P. Bennett III (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
 Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the south boundary
 (Black Mesa Forest Reserve) Township 12 North, Range 11 East, a dependent
 resurvey of a portion of the east boundary and subdivisional lines and survey
 of subdivisions in sections 24, 25 and 26, Township 11½ North, Range 11 East,
 Gila and Salt River Meridian, Arizona

executed by Paul L. Reeves, and John P. Bennett III, Cadastral Surveyors
 having been critically examined and found correct, are hereby approved.

APR 04 1983 (Date) James P. Kelley
 Chief, Cadastral Surveyor of Arizona

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
 T. 11½ N., R. 11 E., G&SRM, Arizona, is a true copy of the original field notes.

(Date) Chief, Cadastral Surveyor of Arizona