

Form 9600-9
(December 1979)
(formerly 9180-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

of the

Dependent Resurvey of a Portion

of the North, East and South Boundaries

and Subdivisional Lines

and the

Survey of Subdivisions in Sections

2, 10, 11, 13, 14, 23, 24, 25, 26, and 36

Township 6 North, Range 10 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

John P. Bennett, Cadastral Surveyor

Under special instructions dated March 5, 19 80, approved March 13, 1980

and Supplemental Special Instructions dated October 7, 1980, approved

October 8, 1980, which provided for the surveys included under U.S. Survey/Group

Number 618, and assignment instructions dated October 9, 19 80.

Survey commenced October 14, 19 80

Survey completed March 4, 19 81

INDEX DIAGRAM

Township 6 North, Range 10 East,

6	5	4	3 42 41	12 11 39 2 38 37	24 1 23
7	8	9	41 40 10 40 39	37 35 11 35 33	23 22 12 22 21
18	17	16	15	33 14 32 31 30	21 11 18 20 10 20 19
19	20	21	22	30 29 28 29 26	19 10 17 24 17 9 16
30	29	28	27	26 26 25 25 24	16 9 25 15 8 15 14
31	32	33	34 6 5	35 5	13 8 12 36 6 5 3

Subdivision of Sections

- Sec. 2 ----- pp. 42 - 44
- Sec. 10 ----- pp. 44 - 49
- Sec. 11 ----- pp. 49 - 55
- Sec. 13 ----- pp. 55 - 58
- Sec. 14 ----- pp. 58 - 66
- Sec. 23 ----- pp. 66 - 71
- Sec. 24 ----- pp. 71 - 72
- Sec. 25 ----- pp. 72 - 75
- Sec. 26 ----- pp. 75 - 78
- Sec. 36 ----- pp. 78 - 84

T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS

The following field notes are those of the dependent re-survey of portions of the north, south and east boundaries and subdivisional lines and the survey of subdivision in sections 2, 10, 11, 13, 14, 23, 24, 25, 26 and 36, of Township 6 North, Range 10 East, Gila and Salt River Meridian, Arizona.

The north and east boundaries and portions of the south boundary and subdivisional lines were surveyed by Theodore F. White, U.S. Deputy Surveyor, in 1881. The east boundary was resurveyed by Jesse B. Wright, U.S. Deputy Surveyor, in 1908. Certain corners were remonumented by Louis D. Gilbert in 1970.

The survey and resurvey were executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instruction for Group No. 618, Arizona, dated March 5, 1980, and Supplemental Special Instructions, dated October 7, 1980.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of lines were determined from the U.S.C. & G.S. triangulation station "RENO", and refer to the true meridian. Distances were measured electronically with Zeiss SM-4 and Hewlett Packard 3820 instruments.

The geographic position of the corner of Tps. 5 and 6 N, Rs. 10 and 11 E, determined by traverse to triangulation station "RENO", is as follows:

Latitude: 33°48'42.73" N Longitude: 111°16'39.24" W

The mean magnetic declination is 14°00' E.

Dependent Resurvey of a Portion of the S Bdy.,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

Restoring the Survey by Theodore F. White in 1881

Beginning at the cor. of Tps. 5 and 6 N, Rs. 10 and 11 E, remonumented by Louis D. Gilbert, Cadastral Surveyor in 1970, with an iron post, 2½ ins. diam., projecting 2 ins. above ground, with brass cap mkd.

T6N	
R10E	R11E
S36	S31
S 1	S 6
T5N	
1970	

from which bearing trees mkd. in 1908

Dependent Resurvey of a Portion of the S Bdy.,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>A mesquite, 12 ins. diam., bears S 47° W, 23 lks. dist., with a healed blaze. (Record: S 35$\frac{3}{4}$° W.)</p> <p>A mesquite, 6 ins. diam., bears N 33° W, 59 lks. dist., with a healed blaze. (Record: N 34$\frac{3}{4}$° W.)</p> <p>Cor. of fences, bears N 85° W, 55$\frac{1}{2}$ lks. dist., fences extend N 24° E and W.</p> <p>S 89°55.5' W, bet. secs. 1 and 36.</p> <p>Over rolling land through dense mesquite and sage brush.</p>	
19.945	<p>Point for the E 1/16 sec. cor. of secs. 1 and 36.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T6N R10E E 1/16 $\frac{S36}{S 1}$ T5N 1980</p>	
39.89	<p>Raise a mound of stone, 2$\frac{1}{2}$ ft. base, 1$\frac{1}{2}$ ft. high, N of cor.</p> <p>Cor. is located 50 lks. N of graded gravel road, bears N 55° E and S 55° W.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone, 3$\frac{1}{2}$ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E $\frac{1}{4}$ $\frac{S36}{S 1}$ T5N 1980</p>	
49.50	<p>Cor. is located on N bank of a wash, 75 lks. wide, 5 ft. deep, drains N 35° E.</p> <p>Center of Highway No. 188, asphalt surfaced, bears S 10° E, curving to SE and N 5° W, curving to NE.</p>	
79.78	<p>The cor. of secs. 1, 2, 35 and 36, monumented with a granite stone, 14 x 14 x 8 ins., loosely set in a scattered mound of stone, mkd. with 1 notch on E, and 5 notches on W.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of the S Bdy.,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
40.93	<p style="text-align: center;">T6N R10E S35 S36 S 2 S 1 T5N 1980</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, W of cor.</p> <hr/> <p>N 89°50' W, bet. secs. 2 and 35.</p> <p>Over rolling, rocky, broken land, through scattering scrub brush.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.</p>	
81.86	<p style="text-align: center;">T6N R10E $\frac{1}{4}$ S35 S 2 T5N 1980</p> <p>The cor. of secs. 2, 3, 34 and 35, monumented with a scattered mound of painted rocks.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E S34 S35 S 3 S 2 T5N 1980</p> <p>from which</p> <p style="padding-left: 40px;">A granite boulder, 2½ x 4½ x 2½ ft. above ground, mkd. X BO on NE face, bears S 5½° W, 131½ lks. dist.</p> <p>Raise a mound of stone, 4 ft. base, 2½ ft. high, W of cor.</p>	
40.82	<p>N 89°29' W, bet. secs. 3 and 34.</p> <p>Over rolling, rocky land, through medium scrub brush.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>At the cor. point</p>	

Dependent Resurvey of a Portion of the S Bdy.,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.

T6N R10E
¼ S34
S 3
T5N
1980

81.64 The cor. of secs. 3, 4, 33 and 34, monumented with a mound of stone, 2½ ft. base, 1 ft. high.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T6N R10E
S33 | S34
S 4 | S 3
T5N
1980

Raise a mound of stone, 3 ft. high, W of cor.

Dependent Resurvey of a Portion of the E Bdy.,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

Restoring the resurvey by Jesse B. Wright in 1908

From the cor. of Tps. 5 and 6 N, Rs. 10 and 11 E, heretofore described.

N 0°09.5' W, bet. secs. 31 and 36.

Over bottom of Tonto Creek, through mesquite, cottonwood and undergrowth.

20.045 Point for the S 1/16 sec. cor. of secs. 31 and 36.

Set a rebar, 48 ins. long, ⅝ in. diam., 42 ins. in the ground, with aluminum cap attached and mkd.

T6N
R10E R11E
S 1/16
S36 | S31
1980

Cor. is located in Tonto Creek bottom, drains southerly, subject to seasonal floodings.

40.09 Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor.

Set a rebar, 48 ins. long, ⅝ in. diam., 42 ins. in the ground, with aluminum cap attached and mkd.

Dependent Resurvey of a Portion of the E Bdy.,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

	CHAINS		
		<p style="text-align: center;">T6N R10E R11E 1/4 S36 S31 1980</p> <p>from which</p> <p>A willow, 12 ins. diam., bears N 41° E, 48 lks. dist., mkd. 1/4 S31 BT.</p> <p>A willow, 12 ins. diam., bears S 86° W, 73 lks. dist., mkd. 1/4 S36 BT.</p> <p>Cor. is located in Tonto Creek bottom, drains southerly, subject to seasonal flooding.</p>	
	55.00	Leave creek bottom, edge bears SE and NW.	
	60.135	Point for the N 1/16 sec. cor. of secs. 31 and 36.	
		Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top, with cap mkd.	
		<p style="text-align: center;">T6N R10E R11E N 1/16 S36 S31 1980</p> <p>Cor. is located in a horse corral.</p>	
	63.15	Graded road, bears S 60° E curving to SE, and N 75° W curving to SW.	
	80.18	<p>The cor. of secs. 25, 30, 31 and 36, monumented with a rebar, 5/8 in. diam., projecting 12 ins. above ground, in a scattered mound of stone. A volcanic stone, 20 x 12 x 7 ins., mkd. with 5 notches on a side and 1 notch on opposite side, was found lying loose near the rebar.</p> <p>from which a bearing tree mkd. in 1908</p> <p>A mesquite, 9 ins. diam., bears N 69° E, 73 lks. dist., with rotted center and illegible scribe marks. (Record: N 61° E)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
		<p style="text-align: center;">T6N R10E R11E S25 S30 S36 S31 1980</p> <p>Deposit the rebar alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W of cor.</p>	

Dependent Resurvey of a Portion of the E Bdy.,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Deposit the mkd. stone in the mound of stone.</p> <p>Cor. is located on edge of bluff, bears N 20° E and S 20° W.</p>	
	<p>N 0°11.5' W, bet. secs. 25 and 30.</p> <p>Over gently rolling land, through medium to dense mesquite and cacti.</p>	
<p>20.045</p>	<p>Point for the S 1/16 sec. cor. of secs. 25 and 30.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6N S 1/16 R10E R11E S25 S30 1980</p> </div> <p>Cor. is located 8½ lks. W of fence, bears S 5° E and N 5° W.</p> <p>From this point a 4 x 4 in. wood post, projecting 3½ ft. above ground, in a mound of stone, 3½ ft. base, 1½ ft. high, bears N 80° W, 11 lks. dist.</p>	
<p>40.09</p>	<p>The ¼ sec. cor. of secs. 25 and 30, monumented with an imbedded mound of stone, 4 ft. base, 1 ft. high.</p> <p>A 4 x 4 in. wood post, 4½ ft. long, was lying loose near mound of stone.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6N ¼ R10E R11E S25 S30 1980</p> </div> <p>Raise a mound of stone, 4½ ft. base, 2 ft. high, W of cor.</p> <p>Deposit wood post in mound of stone.</p> <p>Cor. of fences, bears South, 42 lks. dist., fences extend S and N 20° W.</p> <p>Cor. of fences, bears West, 21 lks. dist., fences extend S 20° E and N 70° W.</p> <p>N 0°02.5' E, beginning new measurement.</p>	
<p>40.145</p>	<p>The cor. of secs. 19, 24, 25 and 30, remonumented by Louis D. Gilbert, Cadastral Surveyor in 1970, with an iron post, 2½ ins. diam., projecting 3 ins. above ground, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of the E Bdy.,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS

T6N	
R10E	R11E
S24	S19
S25	S30
1970	

from which the only remaining bearing tree mkd. in 1881

A mesquite snag, 12 ins. diam., bears S $19\frac{1}{4}^{\circ}$ E, 341 lks. dist., with old blaze, no marks visible. (Record: S 15° E, 338 lks. dist.)

and from which bearing trees mkd. in 1908

A mesquite snag, 15 ins. diam., bears S $38\frac{1}{4}^{\circ}$ W, 254 lks. dist., no marks visible. (Record: S $36\frac{1}{2}^{\circ}$ W, 251 lks. dist.)

A mesquite snag, 8 ins. diam., bears N $79\frac{1}{4}^{\circ}$ W, 261 lks. dist., no marks visible. (Record: 252 lks. dist.)

A 4 x 4 in. wood post, projecting 4 ft. above ground, is set alongside the cor.

Mound of stone, 3 ft. base, 1 ft. high, is W of cor.

N $0^{\circ}03'$ W, bet. secs. 19 and 24.

Over gently rolling land, through medium mesquite and cacti.

40.16 The $\frac{1}{4}$ sec. cor. of secs. 19 and 24, monumented with an imbedded mound of stone, 3 ft. base, 6 ins. high.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T6N	
R10E	R11E
S24	S19
1980	

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

N $0^{\circ}11'$ W, beginning new measurement.

40.25 The cor. of secs. 13, 18, 19 and 24, monumented with a granite stone, 18 x 11 x 10 ins., firmly set 10 ins. in the ground, mkd. with 3 notches on N edge, 3 notches on S edge; a $\frac{3}{4}$ in. diam. open end pipe, 18 ins. long, projecting 2 ins. above ground, with a copper tag attached and mkd. LS 4083, set alongside cor. stone, with a mound of stone, 4 ft. base, 2 ft. high, E of cor.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the E Bdy.,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS

T6N
R10E R11E
S13 | S18
S24 | S19
1980

Deposit the mkd. stone and pipe alongside the iron post.

Rebuilt mound of stone, 4 ft. base, 2½ ft. high, E of cor. (impracticable to W)

Cor. is located 20 lks. E of dry wash, 10 lks. wide, 2 ft. deep, drains S.

N 0°01.5' W, bet. secs. 13 and 18.

Over gently rolling land, through medium mesquite and cresote.

40.15 The ¼ sec. cor. of secs. 13 and 18, monumented with a granite stone, 10 x 10 x 18 ins., firmly set 8 ins. in the ground, mkd. ¼ on top, with mound of stone, 4 ft. base, 2 ft. high, N of cor.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with brass cap mkd.

T6N
¼
R10E | R11E
S13 | S18
1980

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 4 ft. base, 3 ft. high, W of cor.

N 0°06' W, beginning new measurement.

40.31 The cor. of secs. 7, 12, 13 and 18, monumented with a breccia stone, 18 x 12 x 12 ins., firmly set 12 ins. in the ground, mkd. with 2 notches on N edge and 4 notches on S edge; ¾ in. diam. open end pipe, 18 ins. long, projecting 3 ins. above ground, set alongside cor. stone, with a mound of stone, 3½ ft. base, 2 ft. high, W of cor.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T6N
R10E R11E
S12 | S 7
S13 | S18
1981

from which

Dependent Resurvey of a Portion of the E Bdy.,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS

A mesquite, 5 ins. diam., bears S 34° E, 170½
lks. dist., mkd. T6N R10E S18 BT.

Deposit the mkd. stone and open end pipe alongside the
iron post.

Rebuilt mound of stone, 3½ ft. base, 2½ ft. high, W of
cor.

Cor. is located 174 lks. N of a dry wash, 120 lks. wide,
4 ft. deep, drains S 80° E.

Dependent Resurvey of a Portion of the N Bdy.,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

Restoring the survey by Theodore F. White in 1881

From the cor. of secs. 1, 2, 35 and 36, remonumented by -
Louis D. Gilbert, Cadastral Surveyor, in 1970, with an
iron post, 2½ ins. diam., projecting 4 ins. above a mound
of stone, 5 ft. base, 2 ft. high, with brass cap mkd.

T7N R10E	
S35	S36
S 2	S 1
T6N	
1970	

S 89°56.5' W, bet. secs. 2 and 35.

Over rolling land, through medium mesquite and cacti.

20.00 Point for the E 1/16 sec. cor. of secs. 2 and 35.

Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins.
in the ground, with cap mkd.

T7N R10E	
E 1/16	S35
	S 2
T6N	
1981	

Raise a mound of stone, 3½ ft. base, 2½ ft. high, N of
cor.

Cor. is located 83 lks. S of a track road, bears S 70° W.

38.10 Point selected for the witness ¼ sec. cor. of secs. 2 and
35.

Set an aluminum post, 36 ins. long, ¾ in. diam., 28 ins.
in the ground, with cap mkd.

W C	
T7N R10E	
← S35	
S 2	
T6N	
1981	

Dependent Resurvey of a Portion of the N Bdy.,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
	Raise a mound of stone, 2½ ft. base, 2 ft. high, N of cor.	
38.40	Enter Tonto Creek bottom, edge bears N and S.	
40.00	True point for the ¼ sec. cor. of secs. 2 and 35, at proportionate dist., falls in Tonto Creek bottom, drains southerly, where it is impracticable to establish a permanent monument; there is no remaining evidence of the original cor.	
57.00	Asc. bluff, 50 ft. high, edge bears N and S, leave Tonto Creek bottom.	
60.00	Point for the W 1/16 sec. cor. of secs. 2 and 35. Set an aluminum post, 36 ins. long, ¾ in. diam., 32 ins. in the ground, with cap mkd. <div style="text-align: center;"> T7N R10E W 1/16 $\frac{S35}{S 2}$ T6N 1981 </div>	
	Raise a mound of stone, 2½ ft. base, 2 ft. high, N of cor.	
63.10	Center of Highway No. 188, asphalt surfaced, bears S 35° E and N 35° W.	
80.00	The cor. of secs. 2, 3, 34 and 35, remonumented by Louis D. Gilbert, Cadastral Surveyor in 1970, with an iron post, 2½ ins. diam., projecting 6 ins. above ground, with a mound of stone, 4 ft. base, 1½ ft. high, to the E, with brass cap mkd. <div style="text-align: center;"> T7N R10E S34 S35 S 3 S 2 T6N 1970 </div>	
	from which the remains of the original bearing trees mkd. in 1881 A mesquite stump, 6 ins. diam., bears N 30° E, 25 lks. dist., no marks. A rotted mesquite stump, size indeterminate, bears S 10° E, 20 lks. dist., no marks.	
<hr/> Dependent Resurvey, a Portion of the Subdivisional Lines, T 6 N, R 10 E, Gila and Salt River Mer., Arizona		
<hr/> Restoring the survey executed by T.F. White in 1881		
From the cor. of secs. 1, 2, 35 and 36, on the S bdy. of the Tp., heretofore described. N 1°03.5' W, bet. secs. 35 and 36.		

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	
	Over rolling land, through medium mesquite and cacti.
39.73	Track road, bears N 50° E and S 50° W.
40.22	The $\frac{1}{4}$ sec. cor. of secs. 35 and 36, monumented with the remains of a cut wood post, 3 ft. long, 3 ins. diam., with no discernable marks, lying loose.
	from which the original bearing trees
	A burnt mesquite snag, size indeterminate, bears S 85° E, 72 lks. dist., no marks.
	A mesquite, 8 ins. diam., bears N 5° W, 42 lks. dist., with rotted blaze, no marks. (Record: N 12° W)
	At the cor. point
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T6N R10E $\frac{1}{4}$ S35 S36 1980</p>
	Deposit the original post alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 1½ ft high, W of cor.

	N 0°03' E, beginning new measurement.
20.06	Point for the N 1/16 sec. cor. of secs. 35 and 36.
	Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with cap mkd.
	<p style="text-align: center;">T6N R10E N 1/16 S35 S36 1980</p>
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
40.12	The cor. at secs. 25, 26, 35 and 36, as shown on Map 413, recorded with Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., is accepted as a careful and faithful perpetuation of the position of the original cor., monumented with an iron post, 2½ ins. diam., projecting 6 ins. above ground, and in a mound of stone, 2½ ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T6N R10E S26 S25 S35 S36 LS6713 1969</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>From the cor. of secs. 25, 30, 31 and 36, on the E bdy. of the Tp., heretofore described.</p>	
	<p>N 89°59' W, bet. secs. 25 and 36.</p>	
	<p>Over rolling land, through medium mesquite and cacti.</p>	
0.44	<p>Fence, bears S 35° E and N 35° W.</p>	
20.06	<p>Point for the E 1/16 sec. cor. of secs. 25 and 36.</p>	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, and in a mound of stone, 1½ ft. base, to top, with cap mkd.</p>	
	<p style="text-align: center;">T6N R10E E 1/16 $\frac{S25}{S36}$ 1980</p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">The NW cor. of a block house, 66 x 25 ft., bears S 88½° E, 7.58 chs. dist., long side bears S 45° E.</p>	
	<p style="padding-left: 40px;">The NW cor. of a metal storage shed, 19 x 12 ft., bears S 81½° E, 8.83 chs. dist., long side bears S 50° E.</p>	
	<p style="padding-left: 40px;">The NW cor. of a metal hay barn, 50 x 29 ft., bears S 76¼° E, 9.61 chs. dist., long side bears S 40° E.</p>	
34.00	<p>Enter Tonto Creek bottom, edge bears S 20° E and N 20° W.</p>	
40.12	<p>Point for the ¼ sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p>	
	<p>Set a rebar, 48 ins. long, ⅝ in. diam., 42 ins. in the ground, with aluminum cap attached and mkd.</p>	
	<p style="text-align: center;">T6N R10E ¼ $\frac{S25}{S36}$ 1980</p>	
	<p>Cor. falls in Tonto Creek bottom, drains southeasterly, subject to seasonal flooding.</p>	
44.75	<p>Leave Tonto Creek bottom, edge bears S 60° E and N 35° W.</p>	
60.185	<p>Point for the W 1/16 sec. cor. of secs. 25 and 36.</p>	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">T6N R10E W 1/16 $\frac{S25}{S36}$ 1980</p>	
	<p>from which</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A mesquite, 7 ins. diam., bears S 62° E, 20 lks. dist., mkd. W 1/16 S36 BT.</p> <p>Cor. is located 21 lks. N of a fence, bears S 88° E and N 88° W.</p> <p>78.81 Center of Highway No. 188, asphalt surfaced, bears S 25° E and N 25° W.</p> <p>80.25 The cor. of secs. 25, 26, 35 and 36.</p>
	<p>N 0°18' E, bet. secs. 25 and 26.</p> <p>Over nearly level land, through medium mesquite and creosote.</p> <p>2.45 Center of Highway No. 188, asphalt surfaced, bears S 30° E and N 30° W.</p> <p>5.05 Power line, bears S 35° E and N 35° W.</p> <p>20.03 Point for the S 1/16 sec. cor. of secs. 25 and 26.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T6N R10E S 1/16 S26 S25 1980</p> <p>from which</p> <p>A mesquite, 6 ins. diam., bears S 58° W, 48 lks. dist., mkd. X BT at the base.</p> <p>A mesquite, 8 ins. diam., bears S 80° W, 53 lks. dist., mkd. S 1/16 S26 BT.</p> <p>Cor. is located on the E edge of a track road, bears N and S, and 13 lks. W of a concrete irrigation ditch, bears N and S.</p> <p>40.06 The ¼ sec. cor. of secs. 25 and 26, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., is accepted as a careful and faithful reestablishment at the position of the original cor., monumented with an iron post, 2½ ins. diam., projecting 2 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E ¼ S26 S25 LS6713 1969</p> <p>from which a bearing tree mkd. by G. H. Long in 1969</p> <p>An ash, 30 ins. diam., bears N 66° E, 4.05 chs. dist., mkd. X BT at the base. (Record: N 46½° E, 4.32 chs. dist.)</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS

Cor. is located 1 lk. E of fence, bears N and S.

N 0°14' E, beginning new measurement.

20.015 Point for the N 1/16 sec. cor. of secs. 25 and 26.

Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, and in a mound of stone, 1½ ft. base, to top, with cap mkd.

T6N R10E
N 1/16
S26 | S25
1980

from which

A mesquite, 11 ins. diam., bears N 20° E, 75½ lks. dist., mkd. N 1/16 S25 BT.

A mesquite, 12 ins. diam., bears N 58° W, 41½ lks. dist., mkd. N 1/16 S26 BT.

40.03 The cor. of secs. 23, 24, 25 and 26, determined from record bearing and dist. from bearing trees as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., is accepted as a careful and faithful reestablishment of the position of the original cor. A permanent monument was not established at the cor. point by G. H. Long.

from which bearing trees mkd. by G. H. Long in 1969

A willow, 16 ins. diam., bears N 39° E, 1.31 chs. dist., with a healed blaze.

A fallen willow, 12 ins. diam., bears S 85° E, 1.93 chs. dist., with a rotted blaze.

At the cor. point

Set a rebar, 48 ins. long, ½ in. diam., 3 ft. in the ground, with aluminum cap attached and mkd.

T6N R10E
S23 | S24
S26 | S25
1980

Cor. is located in Tonto Creek bottom, drains southerly, subject to seasonal flooding.

From the cor. of secs. 19, 24, 25 and 30, on the E bdy. of the Tp., heretofore described.

N 89°55.5' W, bet. secs. 24 and 25.

Over nearly level land, through dense mesquite.

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
40.09	<p>The $\frac{1}{4}$ sec. cor. of secs. 24 and 25, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., is accepted as a careful and faithful perpetuation of the position of the original cor., monumented with an iron post, $2\frac{1}{2}$ ins. diam., projecting 14 ins. above ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>	
	<p>T6N R10E $\frac{1}{4}$ $\frac{S24}{S25}$ LS6713 1969</p>	
	<p>S 89°47' W, beginning new measurement.</p>	
17.00	<p>Edge of bluff, bears N and S, desc. into Tonto Creek bottom.</p>	
18.97	<p>Point selected for the witness W $\frac{1}{16}$ sec. cor. of secs. 24 and 25.</p>	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.</p>	
	<p>W C T6N R10E W $\frac{1}{16}$ $\frac{S24}{S25}$ 1980</p>	
	<p>Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N of cor.</p>	
19.27	<p>Left bank of Tonto Creek, 8 ft. high, bears N and S.</p>	
19.97	<p>True point for the W $\frac{1}{16}$ sec. cor. of secs. 24 and 25, falls in the Tonto Creek bottom, drains southerly, where it is impracticable to set a permanent monument.</p>	
39.94	<p>The cor. of secs. 23, 24, 25 and 26.</p>	
	<p>N 0°34.5' W, bet. secs. 23 and 24.</p>	
	<p>Over Tonto Creek bottom.</p>	
10.09	<p>The S S $\frac{1}{64}$ sec. cor. of secs. 23 and 24, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., is accepted as a careful and faithful determination of the position of the cor., monumented with an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., buried 18 ins. below ground, with brass cap mkd.</p>	
	<p>T6N R10E S S $\frac{1}{64}$ S23 S24 LS6713 1969</p>	
	<p>from which a bearing tree mkd. by G. H. Long in 1969</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS

A cottonwood, 20 ins. diam., bears S 35° E,
7 lks. dist., mkd. S. (Record: 6 lks. dist.)

Reset the iron post 22 ins. in the ground.

N 0°28' W, beginning new measurement.

9.97 The S 1/16 sec. cor. of secs. 23 and 24, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., is accepted as a careful and faithful determination of the position of the cor., monumented with an iron post, 2½ ins. diam., projecting 10 ins. above ground, with brass cap mkd.

T6N R10E
S 1/16
S23 | S24
LS6713
1969

from which a bearing tree mkd. by G. H. Long in 1969

A willow, 10 ins. diam., bears N 81° E, 23 lks. dist., with a healed blaze.

N 0°24.5' W, beginning new measurement.

20.06 Point for the ¼ sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor.

Set a rebar, 48 ins. long, ½ in. diam., 42 ins. in the ground, with aluminum cap attached and mkd.

T6N R10E
¼
S23 | S24
1981

Cor. is located in Tonto Creek bottom, drains southeasterly, subject to seasonal flooding.

40.12 True point for the N 1/16 sec. cor. of secs. 23 and 24, falls in Tonto Creek bottom where it is impracticable to set a permanent monument.

40.42 Point selected for the witness N 1/16 sec. cor. of secs. 23 and 24.

Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.

W C
T6N R10E
N 1/16
S23 | S24
↓
1980

from which

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	
60.18	<p>A mesquite, 12 ins. diam., bears N 20° E, 36½ lks. dist., mkd. X BT at the base.</p> <p>The cor. of secs. 13, 14, 23 and 24, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., is accepted as a careful and faithful reestablishment of the position of the original cor., monumented with an iron post, 2½ ins. diam., projecting 12 ins. above ground, and in a mound of stone, 2½ ft. base, 6 ins. high, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E S14 S13 S23 S24 LS6713 1969</p> <p>from which a bearing tree mkd. by G. H. Long in 1969</p> <p>A cottonwood, 36 ins. diam., bears S 48° E, 95 lks. dist., with a healed blaze. (Record: S 45° E, 93½ lks. dist.)</p> <p>An axle, 1½ ins. diam., projecting 16 ins. above ground, of unknown origin, bears S 83¾° W, 1.655 chs. dist.</p>
40.605	<p>From the cor. of secs. 13, 18, 19 and 24, on the E bdy. of the Tp., heretofore described.</p> <p>S 89°42' W, bet. secs. 13 and 24.</p> <p>Over gently rolling land, through medium mesquite and cacti.</p> <p>The ¼ sec. cor. of secs. 13 and 24, remonumented by Louis D. Gilbert, Cadastral Surveyor in 1970, with an iron post, 2½ ins. diam., projecting 12 ins. above ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E ¼ S13 S24 1970</p> <p>S 89°55.5' W, beginning new measurement.</p>
2.66	Center of graded road, bears S 15° E and N 15° W.
6.94	Power line, bears S 15° E and N 15° W.
19.94	<p>Point for the W 1/16 sec. cor. of secs. 13 and 24.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone, 1½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E W 1/16 S13 S24 1980</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Raise a mound of stone, 2 ft. base, 1½ ft. high, N of cor.</p>	
29.50	<p>Edge of bluff, bears N and S, desc.</p>	
39.88	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/> <p>N 1°11' W, bet. secs. 13 and 14.</p> <p>Over rolling land, through mesquite and cottonwood.</p>	
20.015	<p>Point for the S 1/16 sec. cor. of secs. 13 and 24.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E S 1/16 S14 S13 1981</p>	
40.03	<p>Raise a mound of stone, 2 ft. base, 2 ft. high, W of cor.</p> <p>The ¼ sec. cor. of secs. 13 and 24, as shown on Map 368, recorded with the Gila County Recorder, Globe, AZ., by Donald M. Wiley, Reg. Land Surveyor No. 4083 AZ., is accepted as a careful and faithful reestablishment of the position of the orig. cor., monumented with an open end pipe, 1 in. diam., 12 ins. long, buried 6 ins. below ground, in a scattered mound of stone.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E ¼ S14 S13 1981</p> <p>Deposit the open end pipe in the iron post.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p> <p>Cor. is located S 45° W, 25 lks. dist. from the corner of a graded road, extending N and E.</p> <hr style="width: 20%; margin: auto;"/>	
20.12	<p>N 1°12' E, beginning new measurement.</p> <p>Along graded road.</p> <p>The N 1/16 sec. cor. of secs. 13 and 14, as shown on Map 368, recorded with the Gila County Recorder, Globe, AZ., by Donald M. Wiley, Reg. Land Surveyor No. 4083 AZ., is accepted as a careful and faithful determination of the position of the cor., monumented with a rebar, 12 ins. long, ¾ in. diam., set flush with surface of abandoned graded road.</p> <p>At the cor. point</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E N 1/16 S14 S13 1981</p> <p>from which</p> <p style="padding-left: 40px;">A power pole, bears N 82° W, 38 lks. dist., lines extend N and W.</p> <p>Deposit the rebar alongside the iron post.</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W of cor.</p> <p>Cor. is located on N edge of abandoned graded road, bears S 30° E and N 30° W, for 50 lks., thence W along graded road in use.</p> <hr style="width: 20%; margin: auto;"/> <p>N 1°09.5' E, beginning new measurement.</p> <p>Over rolling land, through medium mesquite and cacti.</p>	
20.065	<p>The cor. of secs. 11, 12, 13 and 14, remonumented by Louis D. Gilbert, Cadastral Surveyor in 1970, with an iron post, 2½ ins. diam., projecting 12 ins. above ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E S11 S12 S14 S13 1970</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A rotted mesquite stump, size indeterminate, bears N 3° E, 247 lks. dist., no marks.</p> <p>Mound of stone, 3 ft. base, 1 ft. high, N of cor.</p>	
40.33	<p>From the cor. of secs. 7, 12, 13 and 18, on the E bdy. of the Tp., heretofore described.</p> <p>S 89°05' W, bet. secs. 12 and 13.</p> <p>Over gently rolling land, through medium mesquite and cacti.</p> <p>The ¼ sec. cor. of secs. 12 and 13, remonumented by Louis D. Gilbert, Cadastral Surveyor in 1970, with an iron post, 2½ ins. diam., projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E ¼ S12 S13 1970</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Mound of stone, 3½ ft. base, 1½ ft. high, W of cor.</p> <hr/> <p>N 89°51' W, beginning new measurement.</p>	
20.015	<p>Point for the W 1/16 sec. cor. of secs. 12 and 13.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone, 3½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E W 1/16 $\frac{S12}{S13}$ 1981</p>	
20.84	<p>Center of graded road, bears S 20° E and N 25° W.</p>	
30.025	<p>The W W 1/64 sec. cor. of secs. 12 and 13, as shown on Map 512, recorded with the Gila County Recorder, Globe, AZ., by Samuel Tucker, Reg. Professional Engineer No. 2242 AZ., monumented with an open end pipe, 1 in. diam., 18 ins. long, projecting 4 ins. above ground, and in a mound of stone, 1½ ft. base, 6 ins. high, with a copper tag attached and mkd. 4083.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E S12 W-W 1/64 S13 1981</p> <p>Deposit the open end pipe alongside the iron post.</p> <p>Cor. is 2 lks. W of a fence, bears S and N 18° W.</p> <hr/> <p>N 89°51' W, beginning new measurement.</p>	
10.005	<p>The cor. of secs. 11, 12, 13 and 14.</p> <hr/> <p>N 0°07' E, bet. secs. 11 and 12.</p> <p>Over gently rolling land, through medium mesquite, palo verde and cacti.</p>	
19.765	<p>Point for the S 1/16 sec. cor. of secs. 11 and 12.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 26 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T6N R10E S 1/16 S11 S12 1981</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	
39.53	<p>The $\frac{1}{4}$ sec. cor. of secs. 11 and 12, monumented with a mound of stone, 3 ft. base, 2 ft. high.</p> <p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{8}$ in. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <div style="text-align: center;"> <p>T6N R10E</p> <p>$\frac{1}{4}$</p> <p>S11 S12</p> <p>1981</p> </div> <hr/> <p>N 0°54' W, beginning new measurement.</p>
0.30	<p>Abandoned fence, bears N 78° E and S 78° W.</p>
41.64	<p>The cor. of secs. 1, 2, 11 and 12, remonumented by Louis D. Gilbert, Cadastral Surveyor, in 1970, with an iron post, 2½ ins. diam., projecting 12 ins. above ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6N R10E</p> <p>S 2 S 1</p> <p>S11 S12</p> <p>1970</p> </div> <hr/> <p>N 0°51' E, bet. secs. 1 and 2.</p> <p>Over rolling land, through medium mesquite and cacti.</p>
40.34	<p>The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, monumented with a mound of stone, 3 ft. base, 1½ ft. high.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6N R10E</p> <p>$\frac{1}{4}$</p> <p>S 2 S 1</p> <p>1981</p> </div> <hr/> <p>Raise a mound of stone, 3½ ft. base, 2 ft. high, W of cor.</p> <hr/> <p>N 0°23' W, beginning new measurement.</p>
19.70	<p>Point for the N 1/16 sec. cor. of secs. 1 and 2.</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{8}$ in. diam., 28 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>T6N R10E</p> <p>N 1/16</p> <p>S 2 S 1</p> <p>1981</p> </div>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS

39.29

The cor. of secs. 1, 2, 35 and 36, on the N bdy. of the Tp., heretofore described.

From the cor. of secs. 2, 3, 34 and 35, on the S bdy. of the Tp., heretofore described.

N 0°56.5' E, bet. secs. 34 and 35.

Over rolling broken land, through medium mesquite and juniper.

40.12

Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 28 ins. long, 1 in. diam., 8 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with cap mkd.

T6N R10E
S34 | $\frac{1}{4}$ | S35
1980

Cor. is located on the N edge of a flat ridge, bears N 70° E and S 70° W.

80.24

Point for the cor. of secs. 26, 27, 34 and 35, determined latitudinally by proportionate measurement, and longitudinally at record dist. from the cor. of secs. 25, 26, 35 and 36. All control lines to the W were fully retraced and careful search was made for evidence of intervening cors., none of which were recovered.

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T6N R10E
S27 | S26
S34 | S35
1980

from which

A juniper, 8 ins. diam., bears N 70° E, 6½ lks. dist., mkd. T6N R10E S26 BT.

A juniper, 8 ins. diam., bears S 34° E, 29 lks. dist., mkd. T6N R10E S35 BT.

A juniper, 5 ins. diam., bears N 52° W, 16 lks. dist., mkd. X BT at the base.

From the cor. of secs. 25, 26, 35 and 36.

N 89°54' W, bet. secs. 26 and 35.

Over rolling land, through medium mesquite, creosote, jojoba and scattered juniper.

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	
19.95	True point for the E 1/16 sec. cor. of secs. 26 and 35, falls in a dry wash, 75 lks. wide, 10 ft. deep, drains easterly, where it is impracticable to set a permanent monument.
21.45	Point selected for the witness E 1/16 sec. cor. of secs. 26 and 35. Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.
	<p style="text-align: center;">W C T6N R10E E 1/16 $\frac{S26}{S35}$ → 1980</p>
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
39.90	The $\frac{1}{4}$ sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T6N R10E $\frac{1}{4}$ $\frac{S26}{S35}$ 1980</p>
	<p>from which</p> <p style="padding-left: 40px;">A mesquite, 12 ins. diam., bears S 1° E, 74 lks. dist., mkd. $\frac{1}{4}$ S35 BT.</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N 73° W, 67 lks. dist., mkd. $\frac{1}{4}$ S26 BT.</p>
79.81	The cor. of secs. 26, 27, 34 and 35.
	N 0°03' E, bet. secs. 26 and 27.
	Over rolling land, through medium mesquite and juniper.
40.115	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27, at proportionate dist.; there is no remaining evidence of the original cor. Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with cap mkd.
	<p style="text-align: center;">T6N R10E $\frac{1}{4}$ S27 S26 1980</p>
	<p>from which</p> <p style="padding-left: 40px;">A mesquite, 10 ins. diam., bears N 80° W, 49½ lks. dist., mkd. $\frac{1}{4}$ S27 BT.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS

Cor. is located 25 lks. E of a dry wash, 50 lks. wide, 8 ft. deep, drains N 20° E, curving easterly, and 60 lks. S of same wash, drains easterly.

80.23

The cor. of secs. 22, 23, 26 and 27, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., is accepted as a careful and faithful reestablishment of the position of the original cor., monumented with an iron post, 2½ ins. diam., projecting 12 ins. above ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T6N R10E
S22 | S23
S27 | S26
LS6713
1969

from which a tree and boulder mkd. by G. H. Long in 1969

A juniper, dead and down, 7 ins. diam., bears S 72° W, 159 lks. dist., mkd. X BT.

A granite boulder, 3 x 2 x 1 ft. above ground, bears N 5° W, 29 lks. dist., mkd. X BR on top.

From the cor. of secs. 23, 24, 25 and 26.

N 89°40.5' W, bet. secs. 23 and 26.

Over Tonto Creek bottom, drains southerly.

9.97

The E E 1/64 sec. cor. of secs. 23 and 26, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., is accepted as a careful and faithful determination of the position of the cor., monumented with an iron post, 2½ ins. diam., projecting 10 ins. above ground, with brass cap mkd.

T6N R10E
E E
S23 1/64
LS6713
1969

from which bearing trees mkd. by G. H. Long in 1969

A cottonwood, 48 ins. diam., bears N 13° E, 51½ lks. dist., with a healed blaze. (Record: N 9½° E, 49 lks. dist.)

A cottonwood, 42 ins. diam., bears N 28° E, 47 lks. dist., with a healed blaze. (Record: N 24° E, 45 lks. dist.)

Remarked the brass cap to read

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T6N R10E S23 E-E 1/64 S26 LS6713 1980 1969</p>	
	<p>Cor. is located in a fence line, bears N 15° E and S 15° W.</p>	
	<hr style="width: 20%; margin: auto;"/>	
	<p>N 89°44' W, beginning new measurement.</p>	
	<p>Over gently rolling land, through dense mesquite.</p>	
<p>10.005</p>	<p>The E 1/16 sec. cor. of secs. 23 and 26, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., is accepted as a careful and faithful determination of the position of the cor., monumented with an iron post, 2½ ins. diam., projecting 12 ins. above ground, with brass cap mkd.</p>	
	<p style="text-align: center;">E 1/16 S23 LS6713 1969</p>	
	<p>Remarked the brass cap to read</p>	
	<p style="text-align: center;">T6N R10E E 1/16 $\frac{S23}{S26}$ 1980 1969</p>	
	<hr style="width: 20%; margin: auto;"/> <p>N 89°48' W, beginning new measurement.</p>	
<p>20.24</p>	<p>The ¼ sec. cor. of secs. 23 and 26, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., is accepted as a careful and faithful reestablishment of the position of the original cor., monumented with an iron post, 2½ ins. diam., projecting 12 ins. above ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>	
	<p style="text-align: center;">T6N R10E ¼ $\frac{S23}{S26}$ 1969</p>	
	<hr style="width: 20%; margin: auto;"/> <p>N 89°52' W, beginning new measurement.</p>	
	<p>Over rolling land, through medium mesquite, palo verde and cacti.</p>	
<p>1.30</p>	<p>Highway No. 188, asphalt surfaced, bears S 26° E and N 26° W.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS

4.97

The E-E-W 1/256 sec. cor. of secs. 23 and 26, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., is accepted as a careful and faithful determination of the position of the cor., monumented with an iron post, 2½ ins. diam., projecting 18 ins. above ground, in a scattered mound of stone, with brass cap mkd.

E-E-W
1/256
S23
LS6713
1969

Remarked the brass cap to read

S23
E-E-W
1/256
S26
LS6713
1980
1969

N 89°45' W, beginning new measurement.

4.99

The E-W 1/64 sec. cor. of secs. 23 and 26, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., is accepted as a careful and faithful determination of the position of the cor., monumented with an iron post, 2½ ins. diam., projecting 10 ins. above ground, in a scattered mound of stone, with brass cap mkd.

E-W
1/64
S23
LS6713
1969

Remarked the brass cap to read

T6N R10E
S23
E-W 1/64
S26
LS6713
1980
1969

N 89°51' W, beginning new measurement.

9.97

Point for the W 1/16 sec. cor. of secs. 23 and 26.

Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.

T6N R10E
W 1/16 $\frac{S23}{S26}$
1980

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
29.91	<p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.</p> <p>The cor. of secs. 22, 23, 26 and 27.</p>	
20.01	<p>N 0°31' W, bet. secs. 22 and 23.</p> <p>Over rolling land, through medium mesquite and cacti.</p> <p>The S 1/16 sec. cor. of secs. 22 and 23, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., is accepted as a careful and faithful determination of the position of the cor., monumented with an iron post, 2½ ins. diam., projecting 28 ins. above ground, and in a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd.</p> <p style="text-align: center;">W-S 1/16 LS6713 1967</p> <p>Remarked the brass cap to read</p> <p style="text-align: center;">T6N R10E S 1/16 S22 S23 LS6713 1980 1969</p>	
19.935	<p>N 0°33'W, beginning new measurement.</p> <p>The ¼ sec. cor. of secs. 22 and 23, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., is accepted as a careful and faithful reestablishment of the position of the original cor., monumented with an iron post, 2½ ins. diam., projecting 16 ins. above ground, and in a mound of stone, 2½ ft. base, 8 ins. high, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E ¼ S22 S23 LS6713 1969</p> <p>Mound of stone, 2½ ft. base, 1 ft. high, is W of cor.</p> <p style="text-align: center;">T6N R10E ¼ S22 S23 LS6713 1969</p>	
39.975	<p>N 0°34' W, beginning new measurement.</p> <p>The cor. of secs. 14, 15, 22 and 23, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., is accepted as a careful and faithful perpetuation of the position of the original cor., monumented with an iron post, 2½ ins. diam., projecting 8 ins. above ground, with brass cap mkd.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T6N R10E S15 S14 S22 S23 LS6713 1969</p> <p>from which the remains of a bearing tree mkd. in 1881</p> <p style="padding-left: 40px;">A juniper stump, 18 ins. diam., bears N 37½° W, 85 lks. dist., no marks visible. (Record: N 30° W, 90 lks. dist.)</p>	
	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S 89°57.5' W, bet. secs. 14 and 23.</p> <p>Over nearly level land, through dense mesquite and cottonwood.</p>	
13.78	<p>Point selected for the witness E 1/16 sec. cor. of secs. 14 and 23.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">W C T6N R10E E 1/16 ← S14 S23 1980</p>	
	<p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.</p>	
14.28	<p>Left bank of Tonto Creek, 6 ft. high, bears N and S.</p>	
20.03	<p>True point for the E 1/16 sec. cor. of secs. 14 and 23, falls in Tonto Creek bottom, drains southerly, where it is impracticable to establish a permanent monument.</p>	
40.06	<p>True point for the ¼ sec. cor. of secs. 14 and 23, at proportionate dist., falls in Tonto Creek bottom, drains southerly, where it is impracticable to establish a permanent monument; there is no remaining evidence of the original cor.</p>	
41.25	<p>Right bank of Tonto creek, 10 ft. high, bears S 60° E and N 60° W.</p>	
41.36	<p>Point selected for the witness ¼ sec. cor. of secs. 14 and 23.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">W C T6N R10E ¼ S14 S23 1980</p>	
	<p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	
	Cor. is located 1 lk. E of a fence line, bears S 60° E and N 60° W.
50.075	The E-W 1/64 sec. cor. of secs. 14 and 23, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., is accepted as a careful and faithful determination of the position of the original cor., monumented with an iron post, 2½ ins. diam., projecting 12 ins. above ground, and in a mound of stone, 1½ ft. base, 6 ins. high, with brass cap mkd.
	<p style="text-align: center;">E-W 1/64 S23 LS6713 1969</p>
	Remarked the brass cap to read
	<p style="text-align: center;">T6N R10E S14 E-W 1/64 S23 LS6713 1980 1969</p>
	N 89°58' W, beginning new measurement.
4.67	Power line, bears S 10° E and N 10° W.
9.99	The W 1/16 sec. cor. of secs. 14 and 23, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., is accepted as a careful and faithful determination of the position of the cor., monumented with an iron post, 2½ ins. diam., projecting 10 ins. above ground, with brass cap mkd.
	<p style="text-align: center;">W 1/16 S23 LS6713 1969</p>
	Remarked the brass cap to read
	<p style="text-align: center;">T6N R10E W 1/16 $\frac{S14}{S23}$ 1980 1969</p>
	Cor. is located at cor. of fences, extending N and E.
	S 89°56.5' W, beginning new measurement.
0.95	Dirt airstrip, bears S 20° E and N 20° W.
7.42	Highway No. 188, asphalt surfaced, bears N 10° E and S 10° W.
20.17	The cor. of secs. 14, 15, 22 and 23.

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>N 0°03' E, bet. secs. 14 and 15.</p>	
	<p>Over rolling land, through medium mesquite, crucifixion trees, jojoba, and cacti.</p>	
7.25	<p>Fence, bears N 70° E and SW.</p>	
39.52	<p>Center of Highway No. 188, asphalt surfaced, bears S 20° E and N 20° W.</p>	
40.05	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15, at proportionate dist.; there is no remaining evidence of the original cor.</p>	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 8 ins. below surface of Highway No. 188, asphalt surfaced, 24 lks. E of center, bears S 20° E and N 20° W, with cap mkd.</p>	
	<p style="text-align: center;">T6N R10E</p>	
	<p style="text-align: center;"> $\frac{1}{4}$ S15 S14 1981 </p>	
	<p>from which</p>	
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 20 ins. in the ground, for a reference monument, bears N 45° E, 136½ lks. dist., with brass cap mkd. T6N R10E S14 RM 90 FT 1981, and an arrow pointing to the cor.</p>	
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, for a reference monument, bears S 80° E, 150 lks. dist., with brass cap mkd. T6N R10E S14 RM 99 FT 1981, and an arrow pointing to the cor.</p>	
59.575	<p>Point selected for the witness cor. to the N 1/16 sec. cor. of secs. 14 and 15.</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">W C</p>	
	<p style="text-align: center;">T6N R10E</p>	
	<p style="text-align: center;">N 1/16</p>	
	<p style="text-align: center;">S15 ↑ S14</p>	
	<p style="text-align: center;">1981</p>	
	<p>Raise a mound of stone, 4 ft. base, 3½ ft. high, W of cor.</p>	
60.075	<p>True point for the N 1/16 sec. cor. of secs. 14 and 15, falls in Park Creek (dry), 80 lks. wide, 2 ft. deep, drains N 40° E, where it is impracticable to establish a permanent monument.</p>	
66.40	<p>Asphalt surfaced road, bears S 85° E, curving northerly and N 85° W.</p>	
78.68	<p>Asphalt surfaced road, bears S 60° E and N 65° W.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS									
80.10	<p>The cor. of secs. 10, 11, 14 and 15, remonumented by Louis D. Gilbert, Cadastral Surveyor in 1970, with an iron post, 2½ ins. diam., projecting 24 ins. above ground, and in a mound of stone, 3 ft. base, 18 ins. high, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T6N</td><td>R10E</td></tr> <tr><td>S10</td><td>S11</td></tr> <tr><td>S15</td><td>S14</td></tr> <tr><td colspan="2">1970</td></tr> </table> </div> <p>from which bearing trees mkd. in 1881</p> <p>A mesquite, 8 ins. diam., bears N 50° E, 221 lks. dist., with a blaze, no marks visible. (Record: N 48° E, 225 lks. dist.)</p> <p>A mesquite, 18 ins. diam., bears N 65° W, 117 lks. dist., with a blaze, no marks visible. (Record: 120 lks. dist.)</p> <p>From this same point, U.S.G.S. triangulation station "RENO", bears S 4°25'42" E, 9.415 chs. dist., monumented with a stan. brass tablet set in a concrete base, 12 x 12 ins., projecting 2 ins. above ground, mkd. RENO 1946 and a triangle.</p>	T6N	R10E	S10	S11	S15	S14	1970	
T6N	R10E								
S10	S11								
S15	S14								
1970									
	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S 89°52' W, bet. secs. 11 and 14.</p> <p>Over rolling land, through medium mesquite.</p>								
18.65	<p>Graded gravel road, bears N 35° E curving E, and S 45° W curving W.</p>								
20.045	<p>The E 1/16 sec. cor. of secs. 11 and 14, monumented with an open end pipe, 18 ins. long, 1 in. diam., projecting 18 ins. above ground, and in a mound of stone, 3 ft. base, 1 ft. high, of unknown origin, is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T6N</td><td>R10E</td></tr> <tr><td>E 1/16</td><td>S11</td></tr> <tr><td></td><td>S14</td></tr> <tr><td colspan="2">1981</td></tr> </table> </div> <p>from which</p> <p>A power pole, bears S 86° E, 39 lks. dist., lines extending S and W.</p> <p>Deposit the open end pipe alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Cor. is 90 lks. N of a graded road, bears N 70° E, curving S and W, and 30 lks. S of a dry wash, 50 lks. wide, 3 ft. deep, drains S 75° W.</p>	T6N	R10E	E 1/16	S11		S14	1981	
T6N	R10E								
E 1/16	S11								
	S14								
1981									

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>S 89°52' W, beginning new measurement.</p> <p>10.00 The W-E 1/64 sec. cor. of secs. 11 and 14, monumented with an open end pipe, 18 ins. long, $\frac{3}{4}$ in. diam., set flush with surface of graded road, bears N and S, is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 3 ins. below surface of road, 4 lks. W of center, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E S11 W-E 1/64 S14 1981</p> <p>from which</p> <p style="padding-left: 40px;">A power pole, bears S 82° E, 44 lks. dist., lines extend E, S and W.</p> <p style="padding-left: 40px;">A mesquite, 6 ins. diam., bears S 68° W, 107$\frac{1}{2}$ lks. dist., mkd. W-E 1/64 S14 BT.</p> <p>Deposit the open end pipe alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>S 89°53.5' W, beginning new measurement.</p>	
	<p>10.02 Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E $\frac{1}{4}$ S11 $\frac{1}{4}$ S14 1981</p> <p>An open end pipe, $\frac{1}{2}$ in. diam., lying horizontal, 12 ins. below ground, bears S 10° W, 18 lks. dist.</p> <p>Cor. is located 1.90 chs. N of a telephone line, bears E and W.</p> <p>Enter Tonto Creek bottom, edge bears N and S.</p>	
	<p>25.045 Point for the W-E-W 1/256 sec. cor. bet. secs. 11 and 14.</p> <p>Set a rebar, 42 ins. long, $\frac{5}{8}$ in. diam., 30 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with aluminum cap attached and mkd.</p> <p style="text-align: center;">S11 W-E-W 1/256 S14 1981</p> <p>Cor. is located in Tonto Creek bottom, drains southerly, subject to seasonal flooding.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
30.055	<p>Point for the W 1/16 sec. cor. of secs. 11 and 14.</p> <p>Set a rebar, 48 ins. long, $\frac{5}{8}$ in. diam., 42 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with aluminum cap attached and mkd.</p> <p style="text-align: center;">T6N R10E W 1/16 $\frac{S11}{S14}$ 1981</p> <p>Cor. is located in Tonto Creek bottom, drains southerly, subject to seasonal flooding.</p>	
32.00	<p>Right bank of Tonto Creek, 6 ft. high, bears N and S.</p>	
35.06	<p>Point for the E-W-W 1/256 sec. cor. of secs. 11 and 14.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S11 E-W-W 1/256 S14 1981</p>	
40.07	<p>Point for the W-W 1/64 sec. cor. of secs. 11 and 14.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S11 W-W 1/64 S14 1981</p> <p>Cor. is located 75 lks. N of Reno Creek (dry), 150 lks. wide, 5 ft. deep, flows SE.</p>	
45.075	<p>Point for the W-W-W 1/256 sec. cor. of secs. 11 and 14.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S11 W-W-W 1/256 S14 1981</p> <p>from which</p> <p style="text-align: center;">A well casing, 7 ins. diam., bears N 70° W, 15 lks. dist.</p> <p>Cor. is located 1 ch. N of a track road, bears E and N 70° W.</p>	
50.058	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/> <p>N 0°02.5' E, bet. secs. 10 and 11.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
19.93	<p>Over rolling land, through medium to dense mesquite.</p> <p>The S 1/16 sec. cor. of secs. 10 and 11, monumented with an axle, 30 ins. long, $\frac{3}{4}$ in. diam., projecting 12 ins. above ground, of unknown origin, is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E S 1/16 S10 S11 1981</p> <p>Deposit the axle in the iron post.</p> <p>Cor. is located 70 lks. S of a chain link fence, bears E and W.</p> <hr style="width: 20%; margin: auto;"/> <p>N 0°13' E, beginning new measurement.</p>	
19.985	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E $\frac{1}{4}$ S10 S11 1981</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears S 89° E, $43\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S11 BT.</p>	
24.98	<p>Point for the S-S-N 1/256 sec. cor. of secs. 10 and 11.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, and in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S-S-N 1/256 S10 S11 1981</p> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 10 ins. diam., bears N $6\frac{1}{2}$° W, $51\frac{1}{2}$ lks. dist., mkd. SSN 1/256 S10 BT.</p>	
39.97	<p>Point for the N 1/16 sec. cor. of secs. 10 and 11.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T6N R10E N 1/16 S10 S11 1981</p> <p>Raise a mound of stone, 4 ft. base, 2½ ft. high, W of cor.</p> <p>Cor. is located 45½ lks. N and 33 lks. W of Highway No. 188, asphalt surfaced, bears N 40° E and S 40° W.</p> <p>From this point, a brass tablet, 3 ins. diam., set in a concrete form, bears N 86½° W, 4.17 chs. dist., mkd.</p> <p style="text-align: center;">ARIZONA HIGHWAY DEPT. P&M 1368-27 1974</p>
59.955	<p>The cor. of secs. 2, 3, 10 and 11, remonumented by Louis D. Gilbert, Cadastral Surveyor in 1970, with an iron post, 2½ ins. diam., projecting 8 ins. above ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E S 3 S 2 S10 S11 1970</p> <p>from which the only remaining bearing tree mkd. in 1881</p> <p style="text-align: center;">A mesquite, 8 ins. diam., bears N 71½° E, 153 lks. dist., no marks visible.</p> <p>Mound of stone, 2½ ft. base, 1½ ft. high, is NW of cor.</p> <p>Cor. is located 3 lks. W of power line, bears N 10° E and S 10° W.</p>
	<p>From the cor. of secs. 1, 2, 11 and 12, heretofore described.</p> <p>S 88°55.5' W, bet. secs. 2 and 11.</p> <p>Over rolling land, through medium mesquite and creosote bush.</p>
19.825	<p>Point for the E 1/16 sec. cor. of secs. 2 and 11.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 18 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T6N R10E E 1/16 S 2 S11 1981</p>
32.00	<p>Left bank Tonto Creek, 10 ft. high, bears N and S, enter creek bottom.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
39.65	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a rebar, 42 ins. long, $\frac{5}{8}$ in. diam., 26 ins. in the ground, and in a mound of stone, 2$\frac{1}{2}$ ft. base, to top, with aluminum cap attached and mkd.</p> <p style="text-align: center;">T6N R10E $\frac{1}{4}$ $\frac{S 2}{S11}$ 1981</p> <p>Cor. falls in Tonto Creek bottom, drains southerly, subject to seasonal flooding.</p>	
59.48	<p>Point for the W $\frac{1}{16}$ sec. cor. of secs. 2 and 11.</p> <p>Set a rebar, 42 ins. long, $\frac{5}{8}$ in. diam., 28 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with aluminum cap attached and mkd.</p> <p style="text-align: center;">T6N R10E W $\frac{1}{16}$ $\frac{S 2}{S11}$ 1981</p> <p>Cor. falls in Tonto Creek bottom, drains southerly, subject to seasonal flooding.</p>	
63.50	<p>Right bank Tonto Creek, 5 ft. high, bears N 20° E and S 20° W.</p> <p>Enter medium mesquite and creosote brush.</p>	
79.31	<p>The cor. of secs. 2, 3, 10 and 11.</p> <hr/> <p>N 0°07' W, bet. secs. 2 and 3.</p> <p>Over rolling land, through medium mesquite, creosote and cacti.</p>	
39.86	<p>The $\frac{1}{4}$ sec. cor. of secs. 2 and 3, monumented with a granite stone, 15 x 13 x 12 ins., set 10 ins. in the ground, mkd. $\frac{1}{4}$ on the top.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T6N R10E S 3 $\frac{1}{4}$ S 2 1981</p> <p>Deposit the mkd. stone alongside the aluminum post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Cor. is located 70 lks. N of spur, slopes S 70° E.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	
	N 0°23' W, beginning new measurement.
20.66	Point for the N 1/16 sec. cor. of secs. 2 and 3.
	Set an aluminum post, 36 ins. long, $\frac{3}{8}$ in. diam., 30 ins. in the ground, with cap mkd.
	<p style="text-align: center;">T6N R10E N 1/16 S 3 S 2 1981</p>
	from which
	<p style="text-align: center;">A juniper, 5 ins. diam., bears N 61½° W, 27 lks. dist., mkd. N 1/16 S3 BT.</p>
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.
41.22	The cor. of secs. 2, 3, 34 and 35, on the N bdy. of the Tp., heretofore described.
	<hr/> <p>From the cor. of secs. 10, 11, 14 and 15, heretofore described.</p>
	S 89°47' W, bet. secs. 10 and 15.
	Over rolling land, through medium mesquite and juniper.
5.005	Point for the E-E-E 1/256 sec. cor. of secs. 10 and 15.
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with cap mkd.
	<p style="text-align: center;">S10 E-E-E 1/256 S15 1981</p>
8.13	Highway No. 188, asphalt surfaced, bears S 10° E and N 10° W.
20.02	Point for the E 1/16 sec. cor. of secs. 10 and 15.
	Set an aluminum post, 36 ins. long, $\frac{3}{8}$ in. diam., 18 ins. in the ground, and in a mound of stone, 3½ ft. base, to top, with cap mkd.
	<p style="text-align: center;">T6N R10E E 1/16 $\frac{S10}{S15}$ 1981</p>
	A $\frac{3}{8}$ in. diam. steel rod, projecting 3 ins. above ground, of unknown origin, bears S 84° W, 2 lks. dist.
	Cor. is located 22½ lks. W of fence line, bears S 35° E and N 35° W.

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS

40.04

The $\frac{1}{4}$ sec. cor. of secs. 10 and 15, monumented with an open end pipe, 20 ins. long, $\frac{3}{4}$ in. diam., projecting 3 ins. above ground, in a scattered mound of stone, and is accepted as the best available evidence of the position of the original cor.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.

T6N R10E
 $\frac{1}{4}$ $\frac{S10}{S15}$
1981

Deposit the pipe in the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

Cor. is located 26 lks. S of fence line, bears S 75° E and N 75° W.

S 89°55' W, beginning new measurement.

40.00

The cor. of secs. 9, 10, 15 and 16, remonumented by Louis D. Gilbert, Cadastral Surveyor in 1970, with an iron post, $2\frac{1}{2}$ ins. diam., projecting 12 ins. above ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T6N R10E
S 9 | S10
S16 | S15
1970

A 1 in. diam. pipe, set flush in a mound of stone, 2 ft. base, 20 ins. high, of unknown origin, bears N 3°30' W, 2.56 chs. dist.

N 0°22.5' E, bet. secs. 9 and 10.

Over rolling land, through medium mesquite and juniper.

5.85

Track road, bears E and W.

39.91

The $\frac{1}{4}$ sec. cor. of secs. 9 and 10, monumented with an imbedded mound of stone, 3 ft. base, 1 ft. high, and is accepted as the best available evidence of the position of the original cor.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with cap mkd.

T6N R10E
 $\frac{1}{4}$ S 9 | S10
1981

from which

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS											
40.09	<p>A juniper, 12 ins. diam., bears N 30° E, 55½ lks. dist., mkd. ¼ S10 BT.</p> <p>A mesquite, 18 ins. diam., bears N 80° E, 88 lks. dist., mkd. ¼ S10 BT.</p> <p>Rebuilt mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <hr/> <p>N 0°40.5' E, beginning new measurement.</p> <p>The cor. of secs. 3, 4, 9 and 10, monumented with the remains of a juniper post, 3 ft. long, 3 ins. diam., flattened on 2 sides, no marks visible, loosely set in a mound of stone, 2½ ft. base, 1 ft. high, and is accepted as the best available evidence of the position of the original cor.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T6N R10E</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td>S 9</td><td>S10</td></tr> <tr><td colspan="2">1981</td></tr> </table> </div> <p>from which</p> <p>A juniper, 12 ins. diam., bears S 26° E, 77 lks. dist., mkd. T6N R10E S10 BT.</p> <p>A juniper, 8 ins. diam., bears N 89° W, 36 lks. dist., mkd. T6N R10E S4 BT.</p> <p>Deposit the post in the mound of stone.</p> <p>Cor. is located on broken E slope, and 90 lks. N of a steep ridge, bears S 30° E and W.</p>	T6N R10E		S 4	S 3	S 9	S10	1981			
T6N R10E											
S 4	S 3										
S 9	S10										
1981											
18.39	<p>From the cor. of secs. 2, 3, 10 and 11, heretofore described.</p> <p>S 89°55' W, bet. secs. 3 and 10.</p> <p>Over rolling broken land, through mesquite and creosote bush.</p> <p>Point selected for the witness E 1/16 sec. cor. of secs. 3 and 10.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">W C</td></tr> <tr><td colspan="2">T6N R10E</td></tr> <tr><td>E 1/16</td><td>← S 3</td></tr> <tr><td></td><td>S10</td></tr> <tr><td colspan="2">1981</td></tr> </table> </div>	W C		T6N R10E		E 1/16	← S 3		S10	1981	
W C											
T6N R10E											
E 1/16	← S 3										
	S10										
1981											

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
19.89	True point for the E 1/16 sec. cor. of secs. 3 and 10, falls on steep southern slope, where it is impracticable to set a permanent monument.	
39.78	<p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.</p>	
<p>T6N R10E 1/4 S 3 S10 1981</p>		
79.56	The cor. of secs. 3, 4, 9 and 10.	
<p>Subdivision of Section 2 T 6 N, R 10 E, Gila and Salt River Mer., Arizona</p>		
<p>From the 1/4 sec. cor. of secs. 2 and 11.</p>		
<p>N 0°01' W, on the N and S center line of sec. 2.</p>		
<p>Over Tonto Creek bottom.</p>		
40.09	Point for the center 1/4 sec. cor., at intersection with the E and W center line of sec. 2, falls in Tonto Creek bottom where it is impracticable to set a permanent monument.	
60.28	<p>Point for the center N 1/16 sec. cor. of sec. 2.</p> <p>Set a rebar, 42 ins. long, 5/8 in. diam., 28 ins. in the ground, and in a mound of stone, 3 1/2 ft. base, to top, with aluminum cap attached and mkd.</p>	
<p>T6N R10E C N 1/16 S 2 C 1981</p>		
<p>Cor. falls in Tonto Creek bottom, drains southerly, subject to seasonal flooding.</p>		
80.365	True point for the 1/4 sec. cor. of secs. 2 and 35, on the N bdy. of the Tp.	
<p>From the 1/4 sec. cor. of secs. 1 and 2.</p>		
<p>S 88°36' W, on the E and W center line of sec. 2.</p>		
<p>Over gently rolling land, through medium mesquite.</p>		
19.78	Fence, bears S 10° E and N 10° W.	
20.135	Point for the center E 1/16 sec. cor. of sec. 2.	

Subdivision of Section 2
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 28 ins. in the ground, and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T6N R10E E 1/16 C-----C S 2 1981</p>
27.00	Desc. into Tonto Creek bottom.
40.27	The true point for the center $\frac{1}{4}$ sec. cor. of sec. 2.
60.14	Point for the center W 1/16 sec. cor. of sec. 2.
	<p>Set a rebar, 36 ins. long, $\frac{5}{8}$ in. diam., 26 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with aluminum cap attached and mkd.</p> <p style="text-align: center;">T6N R10E W 1/16 C-----C S 2 1981</p>
	Cor. falls in Tonto Creek bottom, drains southerly, subject to seasonal flooding.
65.65	Right bank of Tonto Creek, 35 ft. high, bears N and S.
80.01	The $\frac{1}{4}$ sec. cor. of secs. 2 and 3.
	<p style="text-align: center;"><u>NE $\frac{1}{4}$, Section 2</u></p> <p>From the center E 1/16 sec. cor. of sec. 2.</p> <p>N 0°12' W, on the N and S center line of the NE$\frac{1}{4}$ of sec. 2.</p> <p>Over rolling land, through medium mesquite.</p>
19.95	<p>Point for the NE 1/16 sec. cor., at intersection with the E and W center line of the NE$\frac{1}{4}$ of sec. 2.</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 26 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T6N R10E NE 1/16 S 2 1981</p>
39.79	<p>The E 1/16 sec. cor. of secs. 2 and 35, on the N bdy. of the Tp.</p> <p style="text-align: center;"><u>NE $\frac{1}{4}$, Section 2</u></p> <p>From the N 1/16 sec. cor. of secs. 1 and 2.</p> <p>S 89°15' W, on the E and W center line of the NE$\frac{1}{4}$ of sec. 2.</p>

Subdivision of Section 2
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	
	Over rolling land, through medium mesquite.
20.065	The NE 1/16 sec. cor. of sec. 2.
34.15	The left bank of Tonto Creek, 2 ft. high, bears N and SW.
40.13	The center N 1/16 sec. cor. of sec. 2.
<hr/> <p>NW ¼, Section 2</p> <hr/>	
	From the center W 1/16 sec. cor. of sec. 2.
	N 0°12' W, on the N and S center line of the NW¼ of sec. 2.
	Over Tonto Creek bottom.
19.13	Highway No. 188, asphalt surfaced, bears N 45° E and S 45° W.
20.43	Point for the NW 1/16 sec. cor., at intersection with the E and W center line of the NW¼ of sec. 2.
	Set an aluminum post, 36 ins. long, ¾ in. diam., 24 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with cap mkd.
<p>T6N R10E NW 1/16 S 2 1981</p>	
	An iron rod, 5/8 in. diam., projecting 1 in. above ground, of unknown origin, bears S 6°45' W, 46 lks. dist.
36.30	Highway No. 188, asphalt surfaced, bears S 35° E and N 35° W.
40.75	The W 1/16 sec. cor. of secs. 2 and 35, on the N bdy. of the Tp.
<hr/>	
	From the center N 1/16 sec. cor. of sec. 2.
	S 89°16' W, on the E and W center line of the NW¼ of sec. 2.
	Over Tonto Creek bottom.
19.17	Highway No. 188, asphalt surfaced, bears N 20° E and S 45° W.
19.93	The NW 1/16 sec. cor of sec. 2.
39.86	The N 1/16 sec. cor. of secs. 2 and 3.
<hr/> <p>Subdivision of Section 10 T 6 N, R 10 E, Gila and Salt River Mer., Arizona</p> <hr/>	
	From the ¼ sec. cor. of secs. 10 and 15.

Subdivision of Section 10
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>N 0°22.5' E, on the N and S center line of sec. 10.</p>
12.75	<p>Fence, bears N 80° E and S 50° W.</p>
19.985	<p>Point for the center S 1/16 sec. cor. of sec. 10.</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{8}$ in. diam., 30 ins. in the ground, with cap mkd.</p>
	<p style="text-align: center;">T6N R10E C S 1/16 S10 C 1981</p> <p>Cor. is located in a wash, 40 lks. wide, 7 ft. deep, drains easterly; on high ground.</p>
39.97	<p>Point for the center $\frac{1}{4}$ sec. cor., at intersection with the E and W center line of sec. 10.</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{8}$ in. diam., 27 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with cap mkd.</p>
	<p style="text-align: center;">T6N R10E C $\frac{1}{4}$ S10 1981</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 18 ins. diam., bears S 14° W, 65$\frac{1}{2}$ lks. dist., mkd. C $\frac{1}{4}$ S10 BT.</p> <p style="padding-left: 40px;">A juniper, 18 ins. diam., bears N 2° W, 142$\frac{1}{2}$ lks. dist., mkd. C $\frac{1}{4}$ S10 BT.</p>
40.42	<p>Reno Creek (dry), 60 lks. wide, 5 ft. deep, drains S 60° E.</p>
53.70	<p>Reno Pass road, dirt track, bears S 75° E and N 75° W.</p>
59.98	<p>Point for the center N 1/16 sec. cor. of sec. 10.</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{8}$ in. diam., 30 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with cap mkd.</p>
	<p style="text-align: center;">T6N R10E C N 1/16 S10 C 1981</p> <p>from which</p> <p style="padding-left: 40px;">The SW cor. of a chain link fence, 6 ft. high, around the Tonto Basin refuse dump, bears S 75°45' E, 4.52 chs. dist.</p>
79.99	<p>The $\frac{1}{4}$ sec. cor. of secs. 3 and 10.</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.</p>

Subdivision of Section 10
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS

S 89°57' W, on the E and W center line of sec. 10.

Over rolling land through medium mesquite.

9.945 The center E-E 1/64 sec. cor. of sec. 10, monumented with a pipe, 3½ ft. long, 1 in. diam., projecting 18 ins. above ground, and is accepted as a careful and faithful determination of the position of the cor., and has long been recognized as the cor. by adjacent landowners.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.

T6N R10E
E-E 1/64
C———C
S10
1981

Deposit the local monument alongside the iron post.

Cor. is located 9½ lks. W of a fence line, bears N 20° E curving E, and S 20° W curving S.

S 89°50' W, beginning new measurement.

1.42 Highway No. 188, asphalt surfaced, bears N 30° E and S 5° W.

3.58 Graded road, bears N 10° E and S 10° W.

9.98 Point for the center E 1/16 sec. cor. of sec. 10.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T6N R10E
E 1/16
C———C
S10
1981

Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.

29.94 The center ¼ sec. cor. of sec. 10.

55.37 Fence, bears N 60° E and S 60° W.

69.93 The ¼ sec. cor. of secs. 9 and 10.

NE ¼, Section 10

From the center E 1/16 sec. cor. of sec. 10.

N 0°17' E, on the N and S center line of the NE¼ of sec. 10.

Over gently rolling land, through medium mesquite and creosote bush.

Subdivision of Section 10
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	
19.99	<p>Point for the NE 1/16 sec. cor., at intersection with the E and W center line of the NE$\frac{1}{4}$ of sec. 10.</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 36 ins. in the ground, and in a mound of stone, 2$\frac{1}{2}$ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T6N R10E NE 1/16 S10 1981</p>
39.985	<p>True point for the E 1/16 sec. cor. of secs. 3 and 10.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 10 and 11.</p> <p>S 89°54' W, on the E and W center line of the NE$\frac{1}{4}$ of sec. 10.</p> <p>Over gently rolling land, through medium mesquite and creosote.</p>
19.91	<p>The NE 1/16 sec. cor. of sec. 10.</p>
39.84	<p>The center N 1/16 sec. cor. of sec. 10.</p> <hr/> <p>From the center E-E 1/64 sec. cor. of sec. 10.</p> <p>N 0°15' E, on the N and S center line of the SE$\frac{1}{4}$ of the NE$\frac{1}{4}$ of sec. 10.</p>
4.995	<p>Point for the center S-SE-NE 1/256 sec. cor. of sec. 10.</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., flush with the ground, with cap mkd.</p> <p style="text-align: center;">S10 C-S-SE-NE 1/256 1981</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located along W edge of Highway No. 188, asphalt surfaced, 53 lks. W of center. Road, bears N 35° E and S 35° W.</p> <hr/> <p>N 89°56' E, on the E and W center line of the SE$\frac{1}{4}$ of the NE$\frac{1}{4}$ of the NE$\frac{1}{4}$ of sec. 10.</p>
9.95	<p>The S-S-N 1/256 sec. cor. of secs. 10 and 11.</p> <hr/> <p style="text-align: center;">SE $\frac{1}{4}$, Section 10</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 10 and 15.</p> <p>N 0°17.5' E, on the N and S center line of the SE$\frac{1}{4}$ of sec. 10.</p> <p>Over rolling land, through medium mesquite and juniper.</p>

Subdivision of Section 10
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
19.98	<p>Point for the SE 1/16 sec. cor., at intersection with the E and W center line of the SE$\frac{1}{4}$ of sec. 10.</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{8}$ in. diam., 28 ins. in the ground, and in a mound of stone, 2$\frac{1}{2}$ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T6N R10E SE 1/16 S10 1981</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears N 51° E, 23$\frac{1}{2}$ lks. dist., mkd. SE 1/16 S10 BT.</p> <p style="padding-left: 40px;">A mesquite, 18 ins. diam., bears S 42° E, 16 lks. dist., mkd. SE 1/16 S10 BT.</p>	
39.96	<p>The center E 1/16 sec. cor. of sec. 10.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>From the S 1/16 sec. cor. of secs. 10 and 11.</p> <p>N 89°54.5' W, on the E and W center line of the SE$\frac{1}{4}$ of sec. 10.</p>	
9.935	<p>The center E-SE 1/64 sec. cor. of sec. 10, monumented with a rebar, 18 ins. long, $\frac{3}{8}$ in. diam., projecting 3 ins. above ground, is accepted as a careful and faithful determination of the position of the cor., and has long been recognized as the cor. by adjacent landowners.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S10 C-E-SE 1/64 1981</p> <p>Cor. is located 1 lk. W of fence, bears N and S.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>S 89°48.5' W, beginning new measurement.</p>	
1.82	<p>Highway No. 188, asphalt surfaced, bears N and S.</p>	
10.01	<p>The SE 1/16 sec. cor. of sec. 10.</p>	
30.005	<p>The center S 1/16 sec. cor. of sec. 10.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>From the E-E-E 1/256 sec. cor. of secs. 10 and 15.</p> <p>N 0°16' E, on the N and S center line of the SE$\frac{1}{4}$ of the SE$\frac{1}{4}$ of the SE$\frac{1}{4}$ of sec. 10.</p> <p>9.98 The center E-SE-SE 1/256 sec. cor. of sec. 10, monumented with a rebar, 18 ins. long, $\frac{3}{8}$ in. diam., set flush with the ground, is accepted as a careful and faithful determination of the position of the cor., and has long been recognized as the cor. by adjacent landowners.</p>	

Subdivision of Section 10
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{8}$ in. diam., 26 ins. in the ground, and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S10 C-E-SE-SE 1/256 1981</p> <p>Deposit the rebar alongside the aluminum post.</p> <p>Cor. is located 75 lks. S of Reno Creek (dry), 75 lks. wide, 5 ft. deep, drains S 35° E.</p> <hr/> <p>S $89^{\circ}40'$ W, on the E and W center line of the $SE\frac{1}{4}$ of the $SE\frac{1}{4}$ of sec. 10.</p> <p>0.88 Road, asphalt surfaced, bears N and S.</p> <p>4.995 The SE-SE $\frac{1}{64}$ sec. cor. of sec. 10, monumented with a rebar, 24 ins. long, $\frac{5}{8}$ in. diam., projecting 3 ins. above ground, is accepted as a careful and faithful determination of the position of the cor., and has long been recognized as the cor. by adjacent landowners.</p> <p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{8}$ in. diam., 28 ins. in the ground, and in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S10 SE-SE 1/64 1981</p> <p>Deposit the rebar alongside the aluminum post.</p> <p>Cor. is located 130 lks. E of Highway No. 188, asphalt surfaced, bears S 15° E and N 10° W, curving to E.</p> <hr/> <p>N $0^{\circ}14.5'$ E, on the N and S center line of the $SE\frac{1}{4}$ of the $SE\frac{1}{4}$ of sec. 10.</p> <p>6.40 Reno Creek (dry), 100 lks. wide, 6 ft. deep, drains S 35° E.</p> <p>9.99 The center E-SE $\frac{1}{64}$ sec. cor. of sec. 10.</p> <hr/> <p style="text-align: center;">Subdivision of Section 11 T 6 N, R 10 E, Gila and Salt River Mer., Arizona</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.</p> <p>N $0^{\circ}05.5'$ W, on the N and S center line of sec. 11.</p> <p>Over Tonto Creek bottom.</p>

Subdivision of Section 11
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
19.865	<p>Point for the center S 1/16 sec. cor. of sec. 11.</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{8}$ in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T6N R10E C S 1/16 S11 C 1981</p> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 14 ins. diam., bears N 1° W, 43 lks. dist., mkd. CS 1/16 S11 BT.</p> <p>Cor. is located 100 lks. E of a track road, bears NW and SW.</p>	
39.73	<p>Point for the center $\frac{1}{4}$ sec. cor., at intersection with the E and W center line of sec. 11.</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{8}$ in. diam., 28 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T6N R10E C $\frac{1}{4}$ S11 1981</p> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 4 ins. diam., bears S 7½° W, 8½ lks. dist., mkd. X BT at the base.</p> <p style="padding-left: 40px;">A mesquite, 14 ins. diam., bears S 74° W, 69½ lks. dist., mkd. C $\frac{1}{4}$ S11 BT.</p>	
60.145	<p>Point for the center N 1/16 sec. cor. of sec. 11.</p> <p>Set a rebar, 42 ins. long, $\frac{5}{8}$ in. diam., 25 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with aluminum cap attached and mkd.</p> <p style="text-align: center;">T6N R10E C N 1/16 S11 C 1981</p> <p>Cor. is located in Tonto Creek bottom, 40 lks. W of left bank, 4 ft. high, bears N and S 20° W, subject to seasonal flooding.</p>	
80.56	<p>The $\frac{1}{4}$ sec. cor. of secs. 2 and 11.</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 11 and 12.</p> <p>N 89°50' W, on the E and W center line of sec. 11.</p> <p>Over rolling land, through medium mesquite.</p>	
20.115	<p>Point for the center E 1/16 sec. cor. of sec. 11.</p>	

Subdivision of Section 11
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS

Set an aluminum post, 36 ins. long, $\frac{3}{8}$ in. diam., 24 ins. in the ground, and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with cap mkd.

T6N R10E
E 1/16
C-----C
S11
1981

40.23 The center $\frac{1}{4}$ sec. cor. of sec. 11.

43.25 The left bank of Tonto Creek, 4 ft. high, bears N and S.

60.175 Point for the center W 1/16 sec. cor. of sec. 11.

Set a rebar, $3\frac{1}{2}$ ft. long, $\frac{5}{8}$ in. diam., 28 ins. in the ground, and in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with aluminum cap attached and mkd.

T6N R10E
W 1/16
C-----C
S11
1981

Cor. is located in Tonto Creek, drains southerly, subject to seasonal flooding.

68.00 The right bank of Tonto Creek, bears N and S.

75.13 The center W-W-W 1/256 sec. cor. of sec. 11.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.

W-W-W 1/256
C-----C
S11
1981

from which

A mesquite, 4 ins. diam., bears N 82° E, 29 lks. dist., mkd. X BT at the base.

A mesquite, 4 ins. diam., bears S 55° W, 58 lks. dist., mkd. X BT at the base.

80.115 The $\frac{1}{4}$ sec. cor. of secs. 10 and 11.

SE $\frac{1}{4}$, Section 11

From the E 1/16 sec. cor. of secs. 11 and 14.

N $0^\circ 02.5'$ E, on the N and S center line of the SE $\frac{1}{4}$ of sec. 11.

19.83 Point for the SE 1/16 sec. cor., at intersection with the E and W center line of the SE $\frac{1}{4}$ of sec. 11.

Subdivision of Section 11
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set an aluminum post, 36 ins. long, $\frac{3}{8}$ in. diam., 26 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T6N R10E SE 1/16 S11 1981</p> <p>Cor. is located 7 lks. E of a fence, bears S and N, 120 lks. dist., thence W.</p>
39.66	<p>The center E 1/16 sec. cor. of sec. 11.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the S 1/16 sec. cor. of secs. 11 and 12.</p> <p>N 89°57.5' W, on the E and W center line of the SE$\frac{1}{4}$ of sec. 11.</p>
3.00	<p>Lambing Creek (dry), 1.50 chs. wide, 6 ft. deep, drains S 30° W.</p>
20.075	<p>The SE 1/16 sec. cor. of sec. 11.</p>
40.14	<p>The center S 1/16 sec. cor. of sec. 11.</p> <hr style="width: 60%; margin: 10px auto;"/> <p style="text-align: center;">SW $\frac{1}{4}$, Section 11</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the W 1/16 sec. cor. of secs. 11 and 14.</p> <p>N 0°02' E, on the N and S center line of the SW$\frac{1}{4}$ of sec. 11.</p>
19.895	<p>Point for the SW 1/16 sec. cor., at intersection with the E and W center line of the SW$\frac{1}{4}$ of sec. 11.</p> <p>Set a rebar, 42 ins. long, $\frac{5}{8}$ in. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with aluminum cap attached and mkd.</p> <p style="text-align: center;">T6N R10E SW 1/16 S11 1981</p> <p>Cor. falls in Tonto Creek bottom, drains southerly, subject to seasonal flooding.</p>
39.82	<p>The center W 1/16 sec. cor. of sec. 11.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center S 1/16 sec. cor. of sec. 11.</p> <p>S 89°59' W, on the E and W center line of the SW$\frac{1}{4}$ of sec. 11.</p>
19.985	<p>The SW 1/16 sec. cor. of sec. 11.</p>
24.99	<p>Point for the center E-W-SW 1/256 sec. cor. of sec. 11.</p> <p>Set a rebar, 42 ins. long, $\frac{5}{8}$ in. diam., 26 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with aluminum cap attached and mkd.</p>

Subdivision of Section 11
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">S11 C-E-W-SW 1/256 1981</p> <p>Cor. is located in Tonto Creek bottom, drains southerly, subject to seasonal flooding.</p>
27.75	Right bank of Tonto Creek, 4 ft. high, bears N and S.
29.995	<p>Point for the center W-SW 1/64 sec. cor. of sec. 11.</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{8}$ in. diam., 30 ins. in the ground, with cap mkd.</p>
	<p style="text-align: center;">S11 C-W-SW 1/64 1981</p> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 9 ins. diam., bears N $76\frac{1}{2}^{\circ}$ E, 45 lks. dist., mkd. C-W-SW 1/64 S11 BT.</p> <p style="padding-left: 40px;">A mesquite, 4 ins. diam., bears N 1° W, $12\frac{1}{2}$ lks. dist., mkd. X BT at the base.</p> <p>Cor. is located 2 lks. W of a fence, bears S 10° E and N 10° W.</p>
40.005	<p>The S 1/16 sec. cor. of secs. 10 and 11.</p> <hr style="width: 20%; margin: auto;"/> <p>From the center W-SW 1/64 sec. cor. of sec. 11.</p> <p>N $0^{\circ}07.5'$ E, on the N and S center line of the NW$\frac{1}{4}$ of the SW$\frac{1}{4}$ of sec. 11.</p>
4.99	<p>Point for the center S-NW-SW 1/256 sec. cor. of sec. 11.</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{8}$ in. diam., 30 ins. in the ground, with cap mkd.</p>
	<p style="text-align: center;">S11 C-S-NW-SW 1/256 1981</p> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 10 ins. diam., bears N 60° W, 54 lks. dist., mkd. C-S-NW-SW 1/256 S11 BT.</p> <hr style="width: 20%; margin: auto;"/> <p>N $89^{\circ}58'$ W, on the E and W center line of the SW$\frac{1}{4}$ of the NW$\frac{1}{4}$ of the SW$\frac{1}{4}$ of sec. 11.</p>
5.00	<p>Point for the SW-NW-SW 1/256 sec. cor. of sec. 11.</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{8}$ in. diam., 30 ins. in the ground, with cap mkd.</p>

Subdivision of Section 11
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">S11 SW-NW-SW 1/256 1981</p> <p>from which</p> <p style="text-align: center;">A mesquite, 4 ins. diam., bears N 5° W, 56½ lks. dist., mkd. X BT at the base.</p> <hr/> <p>N 0°10.5' E, on the N and S center line of the SW¼ of the NW¼ of the SW¼ of sec. 11.</p>	
4.995	<p>Point for the center W-NW-SW 1/256 sec. cor. of sec. 11, not monumented.</p> <p>Continuing measurement on the N and S center line of the NW¼ of the NW¼ of the SW¼ of sec. 11.</p>	
14.98	<p>The center W-W-W 1/256 sec. cor. of sec. 11.</p> <hr/> <p style="text-align: center;">NW ¼, Section 11</p> <hr/> <p>From the center W 1/16 sec. cor. of sec. 11.</p> <p>N 0°04' E, on the N and S center line of the NW¼ of sec. 11.</p> <p>Over Tonto Creek bottom.</p>	
20.20	<p>Point for the NW 1/16 sec. cor., at intersection with the E and W center line of the NW¼ of sec. 11.</p> <p>Set a rebar, 42 ins. long, ½ in. diam., 24 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with aluminum cap attached and mkd.</p> <p style="text-align: center;">T6N R10E NW 1/16 S11 1981</p> <p>Cor. is located in Tonto Creek bottom, drains southerly, subject to seasonal flooding.</p>	
40.40	<p>The W 1/16 sec. cor. of secs. 2 and 11.</p> <hr/> <p>From the center N 1/16 sec. cor. of sec. 11.</p> <p>S 89°33' W, on the E and W center line of the NW¼ of sec. 11.</p> <p>Over Tonto Creek bottom, drains southerly.</p>	
19.885	<p>The NW 1/16 sec. cor. of sec. 11.</p>	
24.90	<p>Right bank of Tonto Creek, 5 ft. high, bears N and S.</p>	
39.77	<p>The N 1/16 sec. cor. of secs. 10 and 11.</p> <hr/>	

Subdivision of Section 11
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	
<p>5.01</p>	<p>From the center W-W-W 1/256 sec. cor. of sec. 11.</p> <p>N 0°11' E, on the N and S center line of the SW$\frac{1}{4}$ of the SW$\frac{1}{4}$ of the NW$\frac{1}{4}$ of sec. 11.</p> <p>Point for the SW-SW-NW 1/256 sec. cor. of sec. 11.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S11 SW-SW-NW 1/256 1981</p> <hr/> <p>N 89°59' W, on the E and W center line of the SW$\frac{1}{4}$ of the SW$\frac{1}{4}$ of the NW$\frac{1}{4}$ of sec. 11.</p> <p>The S-S-N 1/256 sec. cor. of secs. 10 and 11.</p>
<p>Subdivision of Section 13 T 6 N, R 10 E, Gila and Salt River Mer., Arizona</p>	
<p>40.16</p> <p>57.73</p> <p>60.08</p>	<p>From the $\frac{1}{4}$ sec. cor. of secs. 13 and 24.</p> <p>N 0°07.5' E, on the N and S center line of sec. 13.</p> <p>Over gently rolling land, through medium mesquite, cacti and creosote.</p> <p>Point for the center $\frac{1}{4}$ sec. cor., at intersection with the E and W center line of sec. 13.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E C $\frac{1}{4}$ S13 1981</p> <p>Raise a mound of stone, 2$\frac{1}{2}$ ft. base, 1$\frac{1}{2}$ ft. high, W of cor.</p> <p>A mound of stone, 4 ft. base, 1 ft. high, of unknown origin, bears N 2° E, 85 lks. dist.</p> <p>Fence, bears E and W.</p> <p>Point for the center N 1/16 sec. cor. of sec. 13.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 19 ins. in the ground, and in a mound of stone, 2$\frac{1}{2}$ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T6N R10E C N 1/16 S13 C 1981</p>
<p>80.00</p>	<p>The $\frac{1}{4}$ sec. cor. of secs. 12 and 13.</p>

Subdivision of Section 13
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, on the E bdy. of the Tp.</p>	
	<p>S 89°44.5' W, on the E and W center line of sec. 13.</p>	
40.485	<p>The center $\frac{1}{4}$ sec. cor. of sec. 13.</p>	
46.70	<p>Graded road, bears S 35° E and N 20° W.</p>	
50.76	<p>Point for the center E-W $\frac{1}{64}$ sec. cor. of sec. 13.</p>	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, and in a mound of stone, 3½ ft. base, to top, with cap mkd.</p>	
	<p style="text-align: center;">E-W $\frac{1}{64}$ C———C S13 1981</p>	
51.25	<p>Fence, bears N 2° E and S 2° W.</p>	
60.04	<p>Power line, bears S 15° E and N 15° W.</p>	
61.035	<p>Point for the center W $\frac{1}{16}$ sec. cor. of sec. 13.</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T6N R10E W $\frac{1}{16}$ C———C 1981</p>	
	<p>from which</p>	
	<p style="text-align: center;">The SW cor. of a steel workshop, 40 x 80 ft., bears N 1°51' E, 398 lks. dist., long side bears N 10° E.</p>	
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p>	
	<p>Cor. is located 106 lks. N of power line and fence, bears E and W.</p>	
71.31	<p>The center W-W $\frac{1}{64}$ sec. cor. of sec. 13, as shown on Map 368, recorded with the Gila County Recorder, Globe, AZ., by Donald M. Wiley, Reg. Land Surveyor No. 4083 AZ., is accepted as a careful and faithful determination of the position of the cor., monumented with an open end pipe, 16 ins. long, 1 in. diam., firmly set 10 ins. in the ground, and in a mound of stone, 2 ft. base, to top.</p>	
	<p>At the cor. point</p>	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.</p>	
	<p style="text-align: center;">T6N R10E S13 C-W-W $\frac{1}{64}$ 1981</p>	
	<p>Deposit open end pipe alongside cor., in the mound of stone.</p>	

Subdivision of Section 13
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Cor. is located in a fence, bears N and S.</p> <hr/>
	<p>S 89°38.5' W, beginning new measurement.</p>
9.98	<p>The $\frac{1}{4}$ sec. cor. of secs. 13 and 14.</p> <hr/>
	<p style="text-align: center;">NW $\frac{1}{4}$, Section 13</p> <hr/>
	<p>From the center W $\frac{1}{16}$ sec. cor. of sec. 13.</p>
	<p>N 0°53' E, on the N and S center line of the NW$\frac{1}{4}$ of sec. 13.</p>
14.63	<p>Fence, bears S 88° E and N 88° W.</p>
15.00	<p>Point for the center N-S-NW $\frac{1}{256}$ sec. cor. of sec. 13.</p>
	<p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a mound of stone, 2$\frac{1}{2}$ ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">S13 C-N-S-NW $\frac{1}{256}$ 1981</p>
	<p>A tailings pond, approximately 4 chs. diam., bears S 60° W, 3 chs. dist.</p>
20.00	<p>Point for the NW $\frac{1}{16}$ sec. cor., at intersection with the E and W center line of the NW$\frac{1}{4}$ of sec. 13.</p>
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.</p>
	<p style="text-align: center;">T6N R10E NW $\frac{1}{16}$ S13 1981</p>
39.98	<p>The W $\frac{1}{16}$ sec. cor. of secs. 12 and 13.</p> <hr/>
	<p>From the center N $\frac{1}{16}$ sec. cor. of sec. 13.</p>
	<p>S 89°59.5' W, on the E and W center line of the NW$\frac{1}{4}$ of sec. 13.</p>
17.70	<p>Graded road, bears S 45° E curving S, and N 20° W curving N.</p>
20.285	<p>The NW $\frac{1}{16}$ sec. cor. of sec. 13.</p>
30.35	<p>Point for the center W-NW $\frac{1}{64}$ sec. cor. of sec. 13.</p>
	<p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a mound of stone, 2$\frac{1}{2}$ ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">S13 C-W-NW $\frac{1}{64}$ 1981</p>

Subdivision of Section 13
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	<p>30.40 Fence, bears N and S.</p> <p>40.415 The N 1/16 sec. cor. of secs. 13 and 14.</p> <hr style="width: 20%; margin: 5px auto;"/> <p>From the center E-W 1/64 sec. cor. of sec. 13.</p> <p>N 0°30' E, on the N and S center line of the SE$\frac{1}{4}$ of the NW$\frac{1}{4}$ of sec. 13.</p> <p>14.97 Point for the center N-SE-NW 1/256 sec. cor. of sec. 13.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 19 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S13 C-N-SE-NW 1/256 1981</p> <p>Cor. is located 133 lks. S of fence, bears S 88° E and N 88° W.</p> <hr style="width: 20%; margin: 5px auto;"/> <p>S 89°55.5' W, on the E and W center line of the NW$\frac{1}{4}$ of the SE$\frac{1}{4}$ of the NW$\frac{1}{4}$ of sec. 13.</p> <p>1.80 Graded road, bears S 20° E curving S, and N 40° W.</p> <p>10.175 The center N-S-NW 1/256 sec. cor. of sec. 13.</p> <hr style="width: 20%; margin: 5px auto;"/> <p>From the center W-W 1/64 sec. cor. of sec. 13.</p> <p>N 1°28' E, on the N and S center line of the SW$\frac{1}{4}$ of the NW$\frac{1}{4}$ of sec. 13.</p> <p>15.050 Point for the center N-SW-NW 1/256 sec. cor. of sec. 13.</p> <p>Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 26 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S13 C-N-SW-NW 1/256 1981</p> <p>Cor. of fences, bears S 45° W, 7 lks. dist., fences extend N, E, and S.</p> <hr style="width: 20%; margin: 5px auto;"/> <p>N 89°56' E, on the E and W center line of the NE$\frac{1}{4}$ of the SW$\frac{1}{4}$ of the NW$\frac{1}{4}$ of sec. 13.</p> <p>10.12 The center N-S-NW 1/256 sec. cor. of sec. 13.</p> <hr style="width: 100%; margin: 5px 0;"/> <p style="text-align: center;">Subdivision of Section 14 T 6 N, R 10 E, Gila and Salt River Mer., Arizona</p> <hr style="width: 100%; margin: 5px 0;"/> <p>From the true point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23.</p>
--------	---

Subdivision of Section 14
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>N 0°01.5' W, on the N and S center line of sec. 14. Over Tonto Creek bottom, drains southerly.</p>	
20.00	<p>Point for the center S 1/16 sec. cor. of sec. 14. Set a rebar, 42 ins. long, $\frac{5}{8}$ in. diam., 24 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with aluminum cap attached and mkd.</p>	
40.00	<p style="text-align: center;">T6N R10E C S 1/16 S14 C 1981</p> <p>Cor. falls in Tonto Creek bottom, drains southerly, subject to seasonal flooding. Point for the center $\frac{1}{4}$ sec. cor., at intersection with the E and W center line of sec. 14. Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T6N R10E C $\frac{1}{4}$ S14 1981</p> <p>from which A mesquite, 6 ins. diam., bears S 53° E, 78 lks. dist., mkd. C $\frac{1}{4}$ S14 BT.</p> <p>Cor. is located on sand bar in Tonto Creek bottom, drains southerly.</p>	
60.075	<p>Point for the center N 1/16 sec. cor. of sec. 14. Set a rebar, 48 ins. long, $\frac{5}{8}$ in. diam., 42 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with aluminum cap attached and mkd.</p>	
80.15	<p style="text-align: center;">T6N R10E C N 1/16 S14 C 1981</p> <p>Cor. falls in Tonto Creek bottom, drains southerly, subject to seasonal flooding. The $\frac{1}{4}$ sec. cor. of secs. 11 and 14. <hr style="width: 20%; margin: auto;"/>From the $\frac{1}{4}$ sec. cor. of secs. 13 and 14. S 89°50' W, on the E and W center line of sec. 14. Over bottom land, through medium to dense mesquite.</p>	

Subdivision of Section 14
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
20.055	<p>The center E 1/16 sec. cor. of sec. 14, as shown on Map 368, recorded with the Gila County Recorder, Globe, AZ., by Donald M. Wiley, Reg. Land Surveyor No. 4083 AZ., is accepted as a careful and faithful determination of the position of the cor., perpetuated by adjacent landowners, with a $\frac{3}{4}$ in. diam. steel rod, indeterminate length, 2 ft. below ground.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, over the steel rod, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6N R10E E 1/16 C-----C S14 1981</p> </div> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 12 ins. diam., bears S 68° E, 155 lks. dist., mkd. X BT at the base.</p> <p style="padding-left: 40px;">A mesquite, 17 ins. diam., bears N 5° W, 168 lks. dist., mkd. CE 1/16 S14 BT.</p> <p>Cor. is located at fence cor., fence extends N and E.</p> <p>Cor. is on left bank of Tonto Creek, 8 ft. high, bears S 45° E and N 45° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 89°57' W, beginning new measurement.</p> <p>Over Tonto Creek bottom, drains southerly.</p>	
19.19	<p>The center $\frac{1}{4}$ sec. cor. of sec. 14.</p>	
29.22	<p>Point for the center E-W 1/64 sec. cor. of sec. 14.</p> <p>Set a rebar, 48 ins. long, $\frac{5}{8}$ in. diam., 36 ins. in the ground, and in a mound of stone, 3 ft. base, to top.</p> <p>Cor. falls in Tonto Creek bottom, drains southerly, subject to seasonal flooding.</p>	
35.00	<p>Right bank Tonto Creek, 50 ft. high, bears N and S, thence through medium mesquite.</p>	
39.25	<p>Point for the center W 1/16 sec. cor. of sec. 14.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6N R10E W 1/16 C-----C S14 1981</p> </div>	
49.28	<p>Point for the center W-W 1/64 sec. cor. of sec. 14, falls on W edge of asphalt surfaced road, bears N and S.</p> <p>Set an aluminum post, 30 ins. long, $\frac{3}{4}$ in. diam., 6 ins. below surface of road, with cap mkd.</p>	

Subdivision of Section 14
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">W-W 1/64 C-----C S14 1981</p> <p>from which</p> <p>An aluminum post, 28 ins. long, 1 in. diam., set 10 ins. in the ground, and in a mound of stone, 4 ft. base, to top, for a reference monument, bears S 30° W, 50 lks. dist., with cap mkd. C-W-W 1/64 S14 RM 33 FT 1981, and an arrow pointing to the cor.</p> <p>An aluminum post, 28 ins. long, 1 in. diam., set 20 ins. in the ground, for a reference monument, bears N 68° W, 41.6 lks. dist., with cap mkd. C-W-W 1/64 S14 RM 27.45 FT 1981, and an arrow pointing to the cor.</p>	
59.31	<p>The ¼ sec. cor. of secs. 14 and 15.</p>	
	<p style="text-align: center;">NE ¼, Section 14</p> <hr/> <p>From the center E 1/16 sec. cor. of sec. 14.</p> <p>N 1°13' E, on the N and S center line of the NE¼ of sec. 14.</p> <p>10.07 Point for the center S-NE 1/64 sec. cor. of sec. 14, falls in intersection of graded roads, bearing N and E.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 8 ins. below surface of road, with cap mkd.</p> <p style="text-align: center;">S14 C-S-NE 1/64 1981</p> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground, for a reference monument, bears S 14° W, 40 lks. dist., with brass cap mkd. C-S-NE 1/64 S14 RM 26.4 FT 1981, and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 20 ins. in the ground, for a reference monument, bears S 85° W, 45 lks. dist., with brass cap mkd. C-S-NE 1/64 S14 RM 29.7 FT 1981, and an arrow pointing to the cor.</p> <p>Thence along graded road.</p> <p>20.14 The NE 1/16 sec. cor. of sec. 14, as shown on Map 395, recorded with the Gila County Recorder, Globe, AZ., by Ralph B. Nunnolley, Reg. Civil Engineer No. 4901 AZ., and also shown on Map 512, recorded with the Gila County Recorder, Globe, AZ., by Samuel Tucker, Reg. Civil Engineer No. 2242 AZ., is accepted as a careful and faithful determination of the position of the cor., monumented with an open end pipe, 18 ins. long, 1¼ ins. diam., set flush with the ground.</p>	

Subdivision of Section 14,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T6N R10E
NE 1/16 S13
1981

Deposit open end pipe in the iron post.

Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.

Cor. is set alongside power pole, lines extend N, E, S, and W; and located 25 lks. E of graded road, bears N and S.

N $1^{\circ}08.5'$ E, beginning new measurement.

20.07 The E 1/16 sec. cor. of secs. 11 and 14.

From the N 1/16 sec. cor. of secs. 13 and 14.

S $89^{\circ}54'$ W, on the E and W center line of the NE $\frac{1}{4}$ of sec. 14.

20.04 The NE 1/16 sec. cor. of sec. 14.

S $89^{\circ}41.5'$ W, beginning new measurement.

10.03 The center W-NE 1/64 sec. cor. of sec. 14, as shown on Map 395, recorded with the Gila County Recorder, Globe, AZ., by Ralph B. Nunnelley, Reg. Civil Engineer No. 4901 AZ., is accepted as a careful and faithful determination of the position of the cor., monumented with an open end pipe, 18 ins. long, $\frac{3}{4}$ in. diam., set 3 ins. below ground.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap mkd.

S14
C-W-NE
1/64
1981

Deposit the open end pipe in the iron post.

Cor. is located 114 lks. S of fence, bears S 45° E and N 40° W.

N $89^{\circ}56'$ W, beginning new measurement.

5.09 Left bank of Tonto Creek, bears S 25° E and N 40° W.

9.59 The center N 1/16 sec. cor. of sec. 14.

Subdivision of Section 14,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	
	From the center S-NE 1/64 sec. cor. of sec. 14.
	S 89°49' W, on the E and W center line of the SW $\frac{1}{4}$ of the NE $\frac{1}{4}$ of sec. 14.
9.40	Left bank of Tonto Creek, 4 ft. high, bears S 20° E and N 20° W.
10.02	<p>The locally accepted SW-NE 1/64 sec. cor. of sec. 14, as shown on Map 395, recorded with the Gila County Recorder, Globe, AZ., by Ralph B. Nunnolley, Reg. Civil Engineer No. 4901 AZ., has been destroyed by flood waters. Local residents identified the position of the cor. being at the cor. of fences extending N and E, which have been partially destroyed by flooding. I reestablished this position at the intersection of a projection of existing fence lines from the N and E. This position closely matches the record of the aforementioned map.</p> <p>At the cor. point</p> <p>Set a rebar, 42 ins. long, $\frac{5}{8}$ in. diam., 24 ins. in the ground, and in a mound of stone, 2$\frac{1}{2}$ ft. base, to top, with aluminum cap attached and mkd.</p> <p style="text-align: center;">S14 SW-NE 1/64 1981</p> <p>from which</p> <p>An iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., set 21 ins. in the ground, for a reference monument, bears S 88° E, 150 lks. dist., with brass cap mkd. SW-NE 1/64 S14 RM 99 FT 1981, and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., set 20 ins. in the ground, for a reference monument, bears N 1°30' W, 150 lks. dist., with brass cap mkd. SW-NE 1/64 S14 RM 99 FT 1981, and an arrow pointing to the cor.</p>
10.045	<p>N 1°10.5' E, on the N and S center line of the SW$\frac{1}{4}$ of the NE$\frac{1}{4}$ of sec. 14.</p> <p>The center W-NE 1/64 sec. cor. of sec. 14.</p> <hr/> <p style="text-align: center;">SE $\frac{1}{4}$, Section 14</p> <hr/> <p>From the true point for the E 1/16 sec. cor. of secs. 14 and 23.</p> <p>N 1°13' W, on the N and S center line of the SE$\frac{1}{4}$ of sec. 14.</p> <p>Over Tonto Creek bottom, drains southerly.</p>
20.015	Point for the SE 1/16 sec. cor. of sec. 14, at intersection with the E and W center line of the SE $\frac{1}{4}$ of sec. 14.

Subdivision of Section 14,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 19 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T6N R10E SE 1/16 S14 1981</p> <p>Cor. is located on sand bar in Tonto Creek bottom, drains southerly, subject to seasonal flooding.</p>	
39.995	<p>The center E 1/16 sec. cor. of sec. 14.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 13 and 14.</p> <p>S 89°58' W, on the E and W center line of the SE¼ of sec. 14.</p>	
8.00	<p>Left bank of Tonto Creek, 3 ft. high, bears N and S.</p> <p>Thence over creek bottom.</p>	
20.035	<p>The SE 1/16 sec. cor. of sec. 14.</p>	
39.64	<p>The center S 1/16 sec. cor. of sec. 14.</p> <hr/> <p style="text-align: center;">NW ¼, Section 14</p> <hr/> <p>From the center W 1/16 sec. cor. of sec. 14.</p> <p>N 0°01' E, on the N and S center line of the NW¼ of sec. 14.</p>	
20.05	<p>Point for the NW 1/16 sec. cor., at intersection with the E and W center line of the NW¼ of sec. 14.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T6N R10E NW 1/16 S14 1981</p>	
40.10	<p>The W 1/16 sec. cor. of secs. 11 and 14.</p> <hr/> <p>From the center N 1/16 sec. cor. of sec. 14.</p> <p>S 89°58' W, on the E and W center line of the NW¼ of sec. 14.</p>	
10.024	<p>Point for the center E-NW 1/64 sec. cor. of sec. 14.</p> <p>Set a rebar, 48 ins. long, ⅝ in. diam., 42 ins. in the ground, and in a mound of stone, 2½ ft. base, to top.</p> <p>Cor. falls in Tonto Creek bottom, drains southerly, subject to seasonal flooding.</p>	
15.036	<p>Point for the center W-E-NW 1/256 sec. cor. of sec. 14.</p>	

Subdivision of Section 14,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set a rebar, 48 ins. long, $\frac{5}{8}$ in. diam., 42 ins. in the ground, and in a mound of stone, 2$\frac{1}{2}$ ft. base, to top.</p> <p>Cor. falls in Tonto Creek bottom, drains southerly, subject to seasonal flooding.</p>	
19.80	Right bank of Tonto Creek, 20 ft. high, bears N and S.	
20.048	The NW 1/16 sec. cor. of sec. 14.	
25.060	Point for the center E-W-NW 1/256 sec. cor. of sec. 14.	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, and in a mound of stone, 2$\frac{1}{2}$ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S14 C-E-W-NW 1/256 1981</p>	
	<p>Cor. is located on steep N slope, 1 ch. S of Park Creek (dry), 1 ch. wide, 4 ft. deep, course easterly.</p>	
30.072	Point for the center W-NW 1/64 sec. cor. of sec. 14.	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, and in a mound of stone, 2$\frac{1}{2}$ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S14 C-W-NW 1/64 1981</p>	
	<p>Cor. is located 160 lks. S of main channel of Park Creek (dry), 1 ch. wide, 4 ft. deep, course easterly.</p>	
40.096	True point for the N 1/16 sec. cor. of secs. 14 and 15.	
	<p style="text-align: center;">_____</p>	
	<p>From the center E-W-NW 1/256 sec. cor. of sec. 14.</p> <p>N 0°01.5' E, on the N and S center line of the SE$\frac{1}{4}$ of the NW$\frac{1}{4}$ of the NW$\frac{1}{4}$ of sec. 14.</p>	
5.01	Point for the SE-NW-NW 1/256 sec. cor. of sec. 14.	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, and in a mound of stone, 2$\frac{1}{2}$ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S14 SE-NW-NW 1/256 1981</p>	
	<p style="text-align: center;">_____</p> <p>S 89°57' W, on the E and W center line of the SE$\frac{1}{4}$ of the NW$\frac{1}{4}$ of the NW$\frac{1}{4}$ of sec. 14.</p>	
5.01	Point for the center S-NW-NW 1/256 sec. cor. of sec. 14, not monumented.	

Subdivision of Section 14,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
	Continuing measurement on the E and W center line of the SW $\frac{1}{4}$ of the NW $\frac{1}{4}$ of the NW $\frac{1}{4}$ of sec. 14.	
10.02	Point for the SW-NW-NW 1/256 sec. cor. of sec. 14.	
	Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, and in a mound of stone, 2 $\frac{1}{2}$ ft. base, to top, with cap mkd.	
	S14 SW-NW-NW 1/256 1981	
	Cor. is located 45 lks. E of a track road, bears N 35° E curving N, and S 65° W.	
	N 0°02.5' E, on the N and S center line of the SW $\frac{1}{4}$ of the NW $\frac{1}{4}$ of the NW $\frac{1}{4}$ of sec. 14.	
5.01	Point for the center W-NW-NW 1/256 sec. cor. of sec. 14, not monumented.	
	Continuing measurement on the N and S center line of the NW $\frac{1}{4}$ of the NW $\frac{1}{4}$ of the NW $\frac{1}{4}$ of sec. 14.	
15.025	The W-W-W 1/256 sec. cor. of secs. 11 and 14.	
	Subdivision of Section 23, T 6 N, R 10 E, Gila and Salt River Mer., Arizona	
	From the $\frac{1}{4}$ sec. cor. of secs. 23 and 26.	
	N 0°20' W, on the N and S center line of sec. 23.	
	Over rolling land, through medium creosote and mesquite.	
20.01	The center S 1/16 sec. cor. of sec. 23, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., and incorporated in other private surveys of record, is accepted as a careful and faithful determination of the position of the cor., monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., projecting 16 ins. above ground, in a mound of stone, 2 ft. base, 10 ins. high, with brass cap mkd.	
	T6N R10E C-S 1/16 S23 LS 6713 1969	
	Cor. is located 6 lks. W of fence cor., fence extending N and E.	
	N 0°15' W, beginning new measurement.	
	Along fence line and graded road.	

Subdivision of Section 23,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	
20.02	<p>The center $\frac{1}{4}$ sec. cor. of sec. 23, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., and incorporated in other private surveys of record, is accepted as a careful and faithful determination of the position of the cor., monumented with an iron post, $2\frac{1}{2}$ ins. diam., projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E C $\frac{1}{4}$ S23 LS6713 1969</p> <p>Cor. is located at cor. of fences, extending E, S and W.</p> <hr style="width: 20%; margin: auto;"/> <p>N $0^{\circ}22.5'$ W, beginning new measurement.</p>
20.035	<p>The center N $\frac{1}{16}$ sec. cor. of sec. 23, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., and incorporated in other private surveys of record, is accepted as a careful and faithful determination of the position of the cor., monumented with an iron post, $2\frac{1}{2}$ ins. diam., projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E CN 1/16 S23 LS6713 1969</p> <p>Cor. is located 1 lk. N of a fence cor., fences extending N, E and W.</p> <hr style="width: 20%; margin: auto;"/> <p>N $0^{\circ}23'$ W, beginning new measurement.</p>
19.975	<p>True point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23.</p> <hr style="width: 80%; margin: auto;"/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 23 and 24.</p> <p>N $89^{\circ}50.5'$ W, on the E and W center line of sec. 23.</p> <p>Over Tonto Creek bottom, drains southerly.</p>
20.035	<p>Point for the center E $\frac{1}{16}$ sec. cor. of sec. 23, at proportionate dist.; falls in irrigation ditch, bears N and S, where it is impracticable to establish a permanent monument.</p>
20.235	<p>The witness center E $\frac{1}{16}$ sec. cor. of sec. 23, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., and incorporated in other private surveys of record, monumented with an iron post, $2\frac{1}{2}$ ins. diam., projecting 8 ins. above ground, with brass cap mkd.</p>

Subdivision of Section 23,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T6N R10E C-E 1/16 WC S23 LS6713 1969</p> <hr/> <p>N 89°58' W, beginning new measurement.</p> <p>Over nearly level pasture.</p>	
19.865	<p>The center $\frac{1}{4}$ sec. cor. of sec. 23.</p> <hr/> <p>N 89°56' W, beginning new measurement.</p> <p>Over gently rolling land, along fence line.</p>	
10.02	<p>The center E-W 1/64 sec. cor. of sec. 23, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., and incorporated in other private surveys of record, is accepted as a careful and faithful determination of the position of the cor., monumented with an iron post, 2½ ins. diam., projecting 8 ins. above ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T6N R10E C-E-W 1/64 S23 LS6713 1969</p> <hr/> <p>Cor. is located 3 lks. S of cor. of fences, extending N and E.</p> <hr/> <p>N 89°56' W, beginning new measurement.</p>	
10.01	<p>The center W 1/16 sec. cor. of sec. 23, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., is accepted as a careful and faithful determination of the position of the cor., monumented with an iron post, 2½ ins. diam., projecting 6 ins. above ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T6N R10E C-W 1/16 S23 LS6713 1969</p> <hr/> <p>N 89°56.5' W, beginning new measurement.</p>	
2.93	<p>Center of Highway No. 188, asphalt surfaced, bears S 25° E and N 25° W.</p>	
20.01	<p>The $\frac{1}{4}$ sec. cor. of secs. 22 and 23.</p> <hr/>	

Subdivision of Section 23
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>SE $\frac{1}{4}$, Section 23</p> <hr/>	
	<p>From the E 1/16 sec. cor. of secs. 23 and 26.</p> <p>N 0°39.5' W, on the N and S center line of the SE$\frac{1}{4}$ of sec. 23.</p>	
10.025	<p>The center S-SE 1/64 sec. cor. of sec. 23, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., is accepted as a careful and faithful determination of the position of the cor., monumented with an iron post, 2½ ins. diam., projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E C-S-SE 1/64 S23 LS6713 1969</p> <p>Cor. is located 2 lks. E of cor. of fences, extending N and W.</p> <hr/> <p>N 0°31' W, beginning new measurement.</p>	
10.01	<p>The SE 1/16 sec. cor. of sec. 23, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., and incorporated in other private surveys of record, is accepted as a careful and faithful determination of the position of the cor., monumented with an iron post, 2½ ins. diam., projecting 10 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E SE 1/16 S23 LS6713 1969</p> <p>Cor. is located 2 lks. S of fence, bears E and W.</p> <hr/> <p>N 0°31.5' W, beginning new measurement.</p>	
20.03	<p>True point for the center E 1/16 sec. cor. of sec. 23.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 23 and 24.</p> <p>N 89°46' W, on the E and W center line of SE$\frac{1}{4}$, sec. 23.</p>	
19.995	<p>The SE 1/16 sec. cor. of sec. 23.</p> <hr/> <p>N 89°53.5' W, beginning new measurement.</p>	
20.145	<p>The center S 1/16 sec. cor. of sec. 23.</p> <hr/>	

Subdivision of Section 23,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>From the E-E 1/64 sec. cor. of secs. 23 and 26.</p> <p>N 0°47.5' W, on the N and S center line of the SE$\frac{1}{4}$ of the SE$\frac{1}{4}$ of sec. 23.</p> <p>10.05 The SE-SE 1/64 sec. cor. of sec. 23, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., is accepted as a careful and faithful determination of the position of the cor., monumented with an iron post, 2$\frac{1}{2}$ ins. diam., projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E SE-SE 1/64 S23 LS6713 1969</p> <p>Cor. of fences, extending N and W, bears N 25° E, 26 lks. dist.</p>	
	<p>N 89°54.5' W, on the E and W center line of the SE$\frac{1}{4}$ of the SE$\frac{1}{4}$ of sec. 23.</p> <p>9.99 The center S-SE 1/64 sec. cor. of sec. 23.</p>	
	<p style="text-align: center;"><u>SW $\frac{1}{4}$, Section 23</u></p> <p>From the W 1/16 sec. cor. of secs. 23 and 26.</p> <p>N 0°27' W, on the N and S center line of the SW$\frac{1}{4}$ of sec. 23.</p> <p>20.00 Point for the SW 1/16 sec. cor., at intersection with the E and W center line of the SW$\frac{1}{4}$ of sec. 23.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E SW 1/16 S23 1980</p> <p>Raise a mound of stone, 2$\frac{1}{2}$ ft. base, 2 ft. high, W of cor.</p>	
	<p>34.68 Center of Highway No. 188, asphalt surfaced, bears S 28° E and N 28° W.</p>	
	<p>39.97 The center W 1/16 sec. cor. of sec. 23.</p> <p style="text-align: center;"><u>From the center S 1/16 sec. cor. of sec. 23.</u></p> <p>N 89°51' W, on the E and W center line of the SW$\frac{1}{4}$ of sec. 23.</p>	

Subdivision of Section 23,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	
4.995	<p>The center E-E-SW 1/256 sec. cor. of sec. 23, as shown on Map 413, recorded with the Gila County Recorder, Globe, AZ., by Gordon H. Long, Reg. Land Surveyor No. 6713 AZ., and incorporated in other private surveys of record, is accepted as a careful and faithful determination of the position of the cor., monumented with an iron post, 2½ ins. diam., projecting 10 ins. above ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T6N R10E C-E-E-SW 1/256 S23 LS6713 1969</p>
	<p>N 89°51' W, beginning new measurement.</p>
7.10	<p>Center of Highway No. 188, asphalt surfaced, bears S 28° E and N 28° W.</p>
14.985	<p>The SW 1/16 sec. cor. of sec. 23.</p>
34.955	<p>The S 1/16 sec. cor. of secs. 22 and 23.</p>
<p>Subdivision of Section 24, T 6 N, R 10 E, Gila and Salt River Mer., Arizona</p>	
	<p>From the ¼ sec. cor. of secs. 24 and 25.</p>
	<p>N 0°28.5' W, on the N and S center line of sec. 24.</p>
	<p>Over gently rolling land, through dense mesquite.</p>
40.02	<p>Point for the center ¼ sec. cor. of sec. 24, at intersection with the E and W center line of sec. 24.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T6N R10E C ¼ S24 1980</p>
	<p>Raise a mound of stone, 2½ ft. base, 1 ft. high, W of cor.</p>
	<p>A mound of stone, of unknown origin, 4½ ft. base, 1½ ft. high, bears N 33° E, 94 lks. dist.</p>
60.085	<p>Point for the center N 1/16 sec. cor. of sec. 24.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T6N R10E C N 1/16 S24 C 1980</p>

Subdivision of Section 24,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS

Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor.
Cor. is located 36 lks. E of graded road, bears S 10° E
and N 10° W.

80.15 The ¼ sec. cor. of secs. 13 and 24.

From the ¼ sec. cor. of secs. 19 and 24, on the E bdy. of
the Tp.

S 89°55' W, on the E and W center line of sec. 24.

Over gently rolling land, through medium to dense
mesquite.

33.30 Graded road, bears S 10° E and N 15° W.

35.30 Power line, bears S 15° E and N 15° W.

35.40 Fence, bears S 15° E and N 15° W.

40.39 The center ¼ sec. cor. of sec. 24.

60.355 Point for the center W 1/16 sec. cor. of sec. 24.

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in
the ground, with brass cap mkd.

T6N R10E
W. 1/16
C—C
S24
1980

Raise a mound of stone, 2½ ft. base, 2 ft. high, N of
cor.

Center of an Indian ruin, approximately 3 chs. in diam.,
bears N 30° W, 175 lks. dist.

80.32 The ¼ sec. cor. of secs. 23 and 24.

Subdivision of Section 25,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

From the ¼ sec. cor. of secs. 25 and 36.

N 0°08' E, on the N and S center line of sec. 25.

19.00 Left bank of Tonto Creek, 4 ft. high, bears SE and NW.

20.03 Point for the center S 1/16 sec. cor. of sec. 25.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in
the ground, with brass cap mkd.

T6N R10E
C
S 1/16 | S25
C
1980

Subdivision of Section 25,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A mesquite, 8 ins. diam., bears S 72° E, 50 lks. dist., mkd. C S 1/16 S25 BT.</p> <p>Thence through medium mesquite.</p>
40.06	<p>Point for the center 1/4 sec. cor., at intersection with the E and W center line of sec. 25.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E C 1/4 S25 1980</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>Cor. is located in a fence line, bears N 30° E, for 44 lks. dist., thence N 85° E and S 30° W.</p> <p>A mound of stone, of unknown origin, 4 ft. base, 2 ft. high, bears N 34° W, 62 lks. dist.</p>
60.16	<p>Point for the center N 1/16 sec. cor. of sec. 25.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E C N 1/16 S25 C 1980</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>A 4 in. sq. wood post, of unknown origin, projecting 2 1/2 ft. above a mound of stone, 4 ft. base, 2 ft. high, bears S 48° W, 16 lks. dist.</p>
78.90	<p>Fence, bears S 65° E and N 65° W.</p>
80.26	<p>The 1/4 sec. cor. of secs. 24 and 25.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 30, on the E bdy. of the Tp.</p> <p>N 89°59' W, on the E and W center line of sec. 25.</p> <p>Over gently rolling land, through dense mesquite.</p>
9.06	<p>Power line, bears N 18° E and S 18° W.</p>
40.16	<p>The center 1/4 sec. cor. of sec. 25.</p>
42.25	<p>Edge of steep bluff, bears S 30° E and N 30° W, desc. into Tonto Creek bottom.</p>

Subdivision of Section 25,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
60.17	True point for the center W 1/16 sec. cor. of sec. 25, falls in Tonto Creek, where it is impracticable to set a permanent monument.	
62.15	Right bank of Tonto Creek, 2 ft. high, bears irregularly N and S.	
64.17	<p>Point selected for the witness center W 1/16 sec. cor. of sec. 25.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <div style="text-align: center;"> <p>W C T6N R10E W 1/16 C → C S25 1980</p> </div>	
80.18	<p>The $\frac{1}{4}$ sec. cor. of secs. 25 and 26.</p> <hr/> <p style="text-align: center;">NW $\frac{1}{4}$, Section 25</p> <hr/> <p>From the true point for the center W 1/16 sec. cor. of sec. 25.</p> <p>N 0°11.5' E, on the N and S center line of the NW$\frac{1}{4}$ of sec. 25.</p> <p>Over Tonto Creek bottom.</p>	
20.06	<p>True point for the NW 1/16 sec. cor., at intersection with the E and W center line of the NW$\frac{1}{4}$ of sec. 25, falls in Tonto Creek bottom, where it is impracticable to establish a permanent monument. The witness NW 1/16 sec. cor. of sec. 25, hereinafter described, bears N 89°55' E, 6.35 chs. dist.</p>	
40.115	<p>The true point for the W 1/16 sec. cor. of secs. 24 and 25.</p> <hr/> <p>From the center N 1/16 sec. cor. of sec. 25.</p> <p>S 89°55' W, on the E and W center line of the NW$\frac{1}{4}$ of sec. 25.</p>	
13.64	<p>Point selected for the witness NW 1/16 sec. cor. of sec. 25.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>W C T6N R10E ← NW 1/16 S25 1980</p> </div> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, N of cor.</p>	

Subdivision of Section 25,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	
13.75	Edge of steep bluff, bears irregularly N and S, desc. into Tonto Creek bottom.
19.99	True point for the NW 1/16 sec. cor. of sec. 25.
29.40	Leave Tonto Creek bottom, edge bears irregularly N and S.
39.985	The N 1/16 sec. cor. of secs. 25 and 26.
<p>Subdivision of Section 26, T 6 N, R 10 E, Gila and Salt River Mer., Arizona</p>	
<p>From the $\frac{1}{4}$ sec. cor. of secs. 26 and 35.</p>	
<p>N 0°02.5' E, on the N and S center line of sec. 26.</p>	
<p>Over rolling land, through medium to dense mesquite.</p>	
1.86	Fence, bears S 55° E and N 55° W.
20.06	True point for the center S 1/16 sec. cor. of sec. 26, falls in a steep draw where a permanent monument would be subject to being buried by slides. Draw is 50 lks. wide and drains easterly.
20.56	Point selected for the witness center S 1/16 sec. cor. of sec. 26.
<p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.</p>	
<pre> W C T6N R10E C S 1/16 S26 C 1980 </pre>	
40.12	Point for the center $\frac{1}{4}$ sec. cor., at intersection with the E and W center line of sec. 26.
<p>Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with cap mkd.</p>	
<pre> T6N R10E C ¼ S26 1981 </pre>	
<p>Raise a mound of stone, 3 ft. base, 3 ft. high, W of cor.</p>	
60.16	Point for the center N 1/16 sec. cor. of sec. 26.
<p>Set an aluminum post, 28 ins. long, 1 in. diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.</p>	
<pre> T6N R10E C N 1/16 S26 C 1981 </pre>	

Subdivision of Section 26,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
70.18	<p>Raise a mound of stone, 3 ft. base, 3 ft. high, W of cor.</p> <p>Point for the center N-N 1/64 sec. cor. of sec. 26.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, and in a mound of stone, 1 ft. base, to top, with cap mkd.</p>	
80.20	<p style="text-align: center;">T6N R10E S26 C-N-N 1/64 1980</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W of cor.</p> <p>Cor. is located 4.25 chs. W of Highway No. 188, asphalt surfaced, bears S 25° E and N 25° W.</p> <p>The ¼ sec. cor. of secs. 23 and 26.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>From the ¼ sec. cor. of secs. 25 and 26.</p> <p>N 89°45.5' W, on the E and W center line of sec. 26.</p> <p>Over rolling land, through medium to dense mesquite.</p>	
19.96	<p>The center E 1/16 sec. cor. of sec. 26, as shown on Map 492, recorded with the Gila County Recorder, Globe, AZ., by James D. King, Reg. Land Surveyor No. 1574 AZ., is accepted as a careful and faithful determination of the position of the cor., monumented with a rebar, 18 ins. long, ⅜ in. diam., firmly set 15 ins. in the ground.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E E 1/16 C—C S26 1980</p> <p>from which</p> <p style="padding-left: 40px;">A steel telephone pole, bears N 9½° W, 48 lks. dist., with lines extending S 15° E and N 15° W.</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W of cor. It would be impracticable to raise mound to N.</p> <p>Deposit the rebar in the iron post.</p> <p>Cor. is located 15 lks. S of dry wash, 25 lks. wide, 8 ft. deep, drains easterly.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>N 89°54' W, beginning new measurement.</p>	
2.57	<p>Highway No. 188, asphalt surfaced, bears N and S.</p>	

Subdivision of Section 26,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	
20.125	The center $\frac{1}{4}$ sec. cor. of sec. 26.
60.02	The $\frac{1}{4}$ sec. cor. of secs. 26 and 27.
<p><u>NE $\frac{1}{4}$, Section 26</u></p>	
<p>From the center E 1/16 sec. cor. of sec. 26.</p>	
<p>N 0°11.5' E, on the N and S center line of the NE $\frac{1}{4}$ of sec. 26.</p>	
20.00	Point for the NE 1/16 sec. cor., at intersection with the E and W center line of the NE $\frac{1}{4}$ of sec. 26.
<p>Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with cap mkd.</p>	
<p>T6N R10E NE 1/16 S26 1981</p>	
<p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p>	
30.02	Point for the center N-NE 1/64 sec. cor. of sec. 26.
<p>Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with cap mkd.</p>	
<p>T6N R10E S26 C-N-NE 1/64 1981</p>	
<p>Raise a mound of stone, 2½ ft. base, 1 ft. high, W of cor.</p>	
<p>Cor. is located in a fence line, bears N and S.</p>	
40.04	The E 1/16 sec. cor. of secs. 23 and 26.
<p>From the N 1/16 sec. cor. of secs. 25 and 26.</p>	
<p>N 89°47.5' W, on the E and W center line of the NE $\frac{1}{4}$ of sec. 26.</p>	
19.97	The NE 1/16 sec. cor. of sec. 26.
31.35	Highway No. 188, asphalt surfaced, bears S 25° E and N 25° W, as scaled from U.S.G.S. topographic map "TONTIO BASIN, AZ.".
40.15	The center N 1/16 sec. cor. of sec. 26.
<p><u>SE $\frac{1}{4}$, Section 26</u></p>	
<p>From the true point for the E 1/16 sec. cor. of secs. 26 and 35.</p>	

Subdivision of Section 26,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>N 0°16' E, on the N and S center line of the SE$\frac{1}{4}$ of sec. 26.</p>	
19.07	<p>Track road, bears E and W.</p>	
20.08	<p>The SE 1/16 sec. cor. of sec. 26, as shown on Map 492, recorded with the Gila County Recorder, Globe, AZ., by James D. King, Reg. Land Surveyor No. 1574 AZ., is accepted as a careful and faithful determination of the position of the cor., monumented with a rebar, 18 ins. long, $\frac{3}{8}$ in. diam., firmly set 16 ins. in the ground, and in a scattered mound of stone.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E SE 1/16 S26 1980</p> <p>Raise a mound of stone, 2$\frac{1}{2}$ ft. base, 1$\frac{1}{2}$ ft. high, W of cor.</p> <p>Deposit the rebar in the iron post.</p> <p>From this point, a rebar, $\frac{3}{8}$ in. diam., of unknown origin, projecting 8 ins. above ground, bears S 32°52' W, 1.70 lks. dist.</p> <hr style="width: 20%; margin: auto;"/> <p>N 0°18.5' E, beginning new measurement.</p>	
20.035	<p>The center E 1/16 sec. cor. of sec. 26.</p> <hr style="width: 20%; margin: auto;"/> <p>From the S 1/16 sec. cor. of secs. 25 and 26.</p> <p>N 89°46.5' W, on the E and W center line of the SE$\frac{1}{4}$ of sec. 26.</p>	
15.90	<p>Highway No. 188, asphalt surfaced, bears S 36° E and N 36° W.</p>	
19.96	<p>The SE 1/16 sec. cor. of sec. 26.</p> <hr style="width: 20%; margin: auto;"/> <p>N 89°57' W, beginning new measurement.</p>	
20.035	<p>True point for the center S 1/16 sec. cor. of sec. 26.</p>	
<p>Subdivision of Section 36, T 6 N, R 10 E, Gila and Salt River Mer., Arizona</p>		
<p>From the $\frac{1}{4}$ sec. cor. of secs. 1 and 36, on th S bdy. of the Tp.</p> <p>N 0°19.5' W, on the N and S center line of sec. 36.</p> <p>Over rolling land, through dense mesquite and scattered hackberry.</p>		

Subdivision of Section 36,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
10.04	<p>Point for the center S-S 1/64 sec. cor. of sec. 36.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S36 C-S-S 1/64 1980</p> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 8 ins. diam., bears S 38° E, 15 lks. dist., mkd. C-S-S 1/64 S36 BT.</p> <p style="padding-left: 40px;">A mesquite, 12 ins. diam., bears N 81° W, 56½ lks. dist., mkd. C-S-S 1/64 S36 BT.</p> <p>A rebar, ½ in. diam., projecting 4 ins. above ground, of unknown origin, bears N 12°44' W, 35½ lks. dist.</p>	
20.08	<p>Point for the center S 1/16 sec. cor. of sec. 36.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, and in a mound of stone, 1½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T6N R10E C S 1/16 S36 C 1980</p> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 6 ins. diam., bears N 45° W, 95 lks. dist., mkd. C-S 1/16 S36 BT.</p>	
40.16	<p>Point for the center ¼ sec. cor. of sec. 36, at intersection with the E and W center line of sec. 36.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, and in a mound of stone, 1½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E C ¼ S36 1980</p> <p>From this point, a copperweld, ½ in. diam., projecting 10 ins. above ground, and in a mound of stone, 1½ ft. base, to top, bears S 42°56' W, 10 lks. dist. There are no marks and is of unknown origin.</p> <p>Thence over Tonto Creek bottom.</p>	
60.14	<p>Fence, bears E and W.</p>	
60.215	<p>Point for the center N 1/16 sec. cor. of sec. 36.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p>	

Subdivision of Section 36,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T6N R10E C N 1/16 S36 C 1980</p> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 7 ins. diam., bears N 66° W, 52 lks. dist., mkd. C-N 1/16 S36 BT.</p>	
80.27	<p>The 1/4 sec. cor. of secs. 25 and 36.</p>	
	<hr/> <p>From the 1/4 sec. cor. of secs. 31 and 36, on the E bdy. of the Tp.</p> <p>N 89°59.5' W, on the E and W center line of sec. 36.</p> <p>Over Tonto Creek bottom, through dense willow, cottonwood and mesquite.</p>	
19.10	<p>Right bank of Tonto Creek, bears N and S.</p>	
20.01	<p>Point for the center E 1/16 sec. cor. of sec. 36.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 23 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">T6N R10E E 1/16 C———C S36 1980</p> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 6 ins. diam., bears N 34° E, 34 lks. dist., mkd. C-E 1/16 S36 BT.</p> <p style="padding-left: 40px;">A mesquite, 6 ins. diam., bears S 41° E, 51 lks. dist., mkd. C-E 1/16 S36 BT.</p>	
30.015	<p>Point for the center W-E 1/64 sec. cor. of sec. 36.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">S36 C-W-E 1/64 1980</p>	
40.02	<p>The center 1/4 sec. cor. of sec. 36.</p>	
45.90	<p>Power line, bears S 40° E and N 40° W.</p>	
49.67	<p>Fence, bears S 5° E and N 5° W.</p>	
50.01	<p>Telephone line, bears S 35° E and N 35° W.</p>	
50.12	<p>Point for the center E-W 1/64 sec. cor. of sec. 36.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with cap mkd.</p>	

Subdivision of Section 36,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS

- 30.05 Point for the center W-NE 1/64 sec. cor. of sec. 36.
- Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with cap mkd.
- S36
C-W-NE
1/64
1980
- 40.06 The center N 1/16 sec. cor. of sec. 36.
-
- SE ¼, Section 36
- From the E 1/16 sec. cor. of secs. 1 and 36, on the S bdy. of the Tp.
- N 0°15.5' W, on the N and S center line of the SE¼ of sec. 36.
- 10.03 Point for the center S-SE 1/64 sec. cor. of sec. 36.
- Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with cap mkd.
- S36
C-S-SE
1/64
1980
- from which
- The NE cor. of a travel trailer, 8 x 23 ft. (in place), bears S 53°36' W, 2.11 chs. dist., long side bears S 43° W.
- The NE cor. of a metal storage shed, 6 x 8 ft., bears S 61°43' W, 2.97 chs. dist., long side bears N 80° W.
- The SE cor. of a travel trailer, 8 x 23 ft. (in place), bears S 62°16' W, 2.86 chs. dist., long side bears N 12° E.
- The SE cor. of a trailer house, 14 x 64 ft., bears S 79°10' W, 7.51 chs. dist., long side bears N 55° W.
- The SE cor. of a trailer house, 12 x 48 ft., bears S 88°44' W, 4.32 chs. dist., long side bears N 50° W.
- 20.06 Point for the SE 1/16 sec. cor., at intersection with the E and W center line of the SE¼ of sec. 36.
- Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with cap mkd.

Subdivision of Section 36,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T6N R10E SE 1/16 S36 1980</p> <p>From this point, a granite stone, projecting 11 x 9 x 8 ins. above ground, and in a mound of stone, 2 ft. base, 6 ins. high, bears S 15°48' E, 30 lks. dist. There are no marks and is of unknown origin.</p> <p>From this same point, a rebar, $\frac{3}{8}$ in. diam., of unknown origin, projecting 6 ins. above ground, and in a mound of stone, 1½ ft. base, 6 ins. high, bears N 15°47' W, 15 lks. dist.</p>
40.12	<p>The center E 1/16 sec. cor. of sec. 36.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 31 and 36, on the E bdy. of the Tp.</p> <p>S 89°58' W, on the E and W center line of the SE¼ of sec. 36.</p>
19.985	The SE 1/16 sec. cor. of sec. 36.
39.965	The center S 1/16 sec. cor. of sec. 36.
	<p style="text-align: center;">NW ¼, Section 36</p> <hr/> <p>From the center W 1/16 sec. cor. of sec. 36.</p> <p>N 0°08.5' W, on the N and S center line of the NW¼ of sec. 36.</p>
11.10	Highway No. 188, asphalt surfaced, bears S 35° E and N 35° W, (calculated).
20.055	<p>Point for the NW 1/16 sec. cor., at intersection with the E and W center line of the NW¼ of sec. 36.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p>
	<p style="text-align: center;">T6N R10E NW 1/16 S36 1980</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p>
20.08	Fence, bears N 70° E and S 70° W.
40.115	The W 1/16 sec. cor. of secs. 25 and 36.
	<hr/> <p>From the center N 1/16 sec. cor. of sec. 36.</p> <p>N 89°59' W, on the E and W center line of the NW¼ of sec. 36.</p>
10.07	Point for the center E-NW 1/64 sec. cor. of sec. 36.

Subdivision of Section 36,
T 6 N, R 10 E, Gila and Salt River Mer., Arizona

CHAINS

Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.

S36
C-E-NW
1/64
1980

from which

A mesquite, 7 ins. diam., bears N 71° W, 82 lks. dist., mkd. C-E-NW 1/64 S36 BT.

- 10.80 Fence, bears S 25° E and N 25° W.
- 11.15 Graded road, bears S 25° E and N 25° W.
- 20.14 The NW 1/16 sec. cor. of sec. 36.
- 27.45 Highway No. 188, asphalt surfaced, bears S 35° E and N 35° W.
- 40.27 The N 1/16 sec. cor. of secs. 35 and 36.

GENERAL DESCRIPTION

The land encompassed in this survey is generally located in the Tonto Basin, with the community of Punkin Center, Arizona, lying in sections 10 and 11. Tonto Creek flows southerly through the township and drains the area into Roosevelt Lake. Elevations range from 2,400 to 3,200 feet above sea level. The western portion of the township is mountainous with the eastern portion being rolling and nearly level in the Tonto Creek bottom. Vegetation consists of juniper, palo verde, cat claw acacia, creosote bush and cacti. There are scattered stands of cottonwood, hackberry and willow along Tonto Creek.

Access is by way of Arizona State Highway No. 188, asphalt surfaced, which enters the township in section 2, traverses southerly and exits the township in section 36. Further access is provided by numerous dirt roads.

Residences are located in all sections surveyed, except section 2. A school and several small businesses are located in the SW $\frac{1}{4}$ of section 10. Intermittent springs and seeps were noted in section 26.

The location of uranium claims in the eastern portion of the township is the only evidence of mineralization. A hardrock mill is in operation in the NW $\frac{1}{4}$ of section 13.

An average number of readings throughout the surveyed area gives a mean magnetic declination of 14° E, with a variation of 4° in local attraction.

CERTIFICATE OF SURVEY

(I) (~~We~~), John P. Bennett, Cadastral Surveyor, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 5th day

of March, 19 80, ~~(XXXXXX)~~ and the supplemental special instructions dated October 7, 1980, I have dependently resurveyed portions of the North, East and South boundaries and subdivisional lines, and surveyed subdivisions in sections 2, 10, 11, 13, 14, 23, 24, 25, 26 and 36, Township 6 North, Range 10 East.

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(US)~~ and under (my) ~~XXX~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

JAN 11 1984

(Date)

John P. Bennett

(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

Arizona State Office
BUREAU OF LAND MANAGEMENT
~~Denver, Colorado~~
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of portions of the North, East, and South boundaries and subdivisional lines, and the survey of subdivisions in sections 2, 10, 11, 13, 14, 23, 24, 25, 26 and 36, Township 6 North, Range 10 East, Gila and Salt River Meridian, Arizona

executed by John P. Bennett, Cadastral Surveyor
having been critically examined and found correct, are hereby approved.

JAN 12 1984

(Date)

James P. Kelley

~~XXXXXX Cadastral Survey Examination and Approval Staff~~
Chief Cadastral Surveyor of Arizona

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in T. 6 N., R. 10 E., G&SRM, Arizona, is a true copy of the original field notes.

(Date)

~~XXXXXX Cadastral Survey Examination and Approval Staff~~

Chief Cadastral Surveyor of Arizona