

ORIGINAL

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE

NORTH AND WEST BOUNDARIES

AND THE SUBDIVISIONAL LINES

AND THE

SURVEY OF SUBDIVISIONS IN

SECTIONS 5 AND 30

OF

TOWNSHIP 17 NORTH, RANGE 6 EAST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

Paul L. Reeves, Cadastral Surveyor

Under special instructions dated September 20, 1984, approved September 20, 1984
and Supplemental Special Instructions dated November 23, 1984, approved
November 23, 1984, which provided for the surveys included under Group Number
658 and assignment instructions dated October 3, 1984.

Survey commenced October 25, 1984

Survey completed June 5, 1985

BOOK 5219

2

INDEX DIAGRAM

TOWNSHIP 17 NORTH, RANGE 6 EAST,

	3				
6	9 5	6 4	3	2	1
	7				
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
13					
4 30	12 29	28	27	26	25
10					
31	32	33	34	35	36

Subdivision of section 5 pp 15-25
 Subdivision of section 30 pp 25-36

T 17 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS

The following field notes are those of the dependent resurvey of portions of the north and west boundaries and subdivisional lines and the survey of subdivisions in sections 5 and 30, Township 17 North, Range 6 East, Gila and Salt River Meridian, Arizona.

The history of the pertinent surveys is as follows:
The north boundary was surveyed by John C. Smith, in 1885, resurveyed by W.O. Secor, in 1902, and partially resurveyed by Donald E. Harding, in 1957.

The west boundary was surveyed by John C. Smith, in 1885, partially resurveyed by W.O. Secor, in 1902, and partially resurveyed by Leslie H. Godwin and Donald E. Harding, in 1956.

The subdivisional lines were partially surveyed by R.C. Power, in 1885, partially surveyed by W.O. Secor, in 1902, who also resurveyed some of Power's work. Donald E. Harding resurveyed portions of the subdivisional lines, in 1957.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated September 20, 1984, and the Supplemental Instructions dated November 23, 1984, for Group No. 658, Arizona.

The direction of the lines of this survey was determined by altitude observations on the sun and refers to the true meridian. Distances were measured with a Hewlett Packard 3820A Total Station instrument.

Preliminary to the resurvey, the lines of prior surveys were retraced and search was made for all corners and other calls of the record. All corners were found in good condition. All evidence of private surveys was evaluated and considered and was accepted if evidence indicated that the survey was properly executed. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the following listed points, as determined by a tie to U.S. Geological Survey triangulation station "MUNDS, 1930", located in section 15, T 17 N, R 6 E, is as follows:

Southeast Corner of Section 5

Latitude: 34°52'34.59" N Longitude: 111°44'32.51" W

Southeast Corner of Section 30

Latitude: 34°49'04.93" N Longitude: 111°45'34.64" W

The mean magnetic declination is 14° E.

Dependent Resurvey of a Portion of the North Boundary
T 17 N, R 6 E, Gila and Salt River Mer., Arizona

Reestablishment of the resurvey executed
by Donald E. Harding, in 1957

Beginning at the cor. of secs. 4 and 5 only, on the N bdy. of the Tp., monumented with an iron post, 2½ ins. diam., projecting 14 ins. above ground, in a mound of stone, 3 ft. base, 14 ins. high, with brass cap mkd.

Dependent Resurvey of a Portion of the North Boundary
T 17 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T18N S33 S 5 S 4 T17N R6E 1957</p> <p>from which a 1957 bearing tree</p> <p style="padding-left: 40px;">A pinyon, 9 ins. diam., bears S 54° E, 128 lks. dist., mkd. T17N R6E S4 BT.</p> <p>and from which a 1902 bearing tree</p> <p style="padding-left: 40px;">A pinyon, 14 ins. diam., bears S 32° W, 105 lks. dist., with illegible scribe marks visible through a partially healed blaze. (Record: 103 lks. dist.)</p> <p>S 88°51' W, on the North bdy. of sec. 5.</p> <p>Over rugged, mountainous land, through medium pinyon pine, juniper, yew and mountain mahogany.</p>	
38.65	<p>The ¼ sec. cor. of sec. 5 only, monumented with an iron post, 2½ ins. diam., projecting 18 ins. above ground, in a mound of stone, 2½ ft. base, 1 ft. high, with brass cap mkd.</p> <p style="text-align: center;">T18N ----- ¼ S5 T17N R6E 1957</p> <p>from which a 1902 bearing tree</p> <p style="padding-left: 40px;">A yew, 18 ins. diam., bears N 15° W, 39 lks. dist., mkd. ¼ S32 BT. (Reportedly destroyed in 1957)</p> <p>and from which a 1957 bearing tree</p> <p style="padding-left: 40px;">A pinyon, 6 ins. diam., bears S 27¾° E, 82 lks. dist., mkd. ¼ S5 BT. (Record: S 29° E, 81 lks. dist.)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S 89°55' W, beginning new measurement.</p>	
39.87	<p>The cor. of secs. 5 and 6 only, monumented with an iron post, 2½ ins. diam., projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T18N ----- S 6 S 5 T17N R6E 1957</p> <p>from which a 1902 bearing tree</p> <p style="padding-left: 40px;">A pinyon, 12 ins. diam., bears S 47° W, 45 lks. dist., mkd. T17N R6E S6 BT.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">Dependent Resurvey of a Portion of the West Boundary T 17 N, R 6 E, Gila and Salt River Mer., Arizona</p>	

Dependent Resurvey of a Portion of the West Boundary
T 17 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS

Reestablishment of the resurvey executed
by Donald E. Harding, in 1956

From the cor. of secs. 25, 30, 31 and 36, on the W bdy.
of the Tp., monumented with an iron post, 2½ ins. diam.,
firmly set, projecting 12 ins. above ground, and in a
mound of stone, 3 ft. base, to top, with brass cap mkd.

T17N
R 5 E | R 6 E
S25 | S30
S36 | S31
1956

N 1°17' E, bet. secs. 25 and 30.

Over rolling land, through medium juniper and pinyon.

20.52 Point for the S 1/16 sec. cor. of secs. 25 and 30.

Set an aluminum tablet, 2½ ins. diam., 2½ in. stem, in
a drill hole in a sandstone outcrop, with top mkd.

T17N
R5E R6E
S 1/16
S25 | S30
1985

from which

A pinyon, 5 ins. diam., bears S 35° E, 81
lks. dist., mkd. X at breast height and
BT at base.

A point on a sandstone outcrop, bears N 12° W,
15 lks. dist., mkd. X BO.

41.04 The ¼ sec. cor. of secs. 25 and 30, monumented with an
iron post, 2½ ins. diam., projecting 24 ins. above
ground, in a mound of stone, 3½ ft. base, to top, with
brass cap mkd.

T17N
R5E R6E
¼
S25 | S30
1956

from which a 1902 bearing tree

A juniper limb, 8 ins. diam., bears S 70½° E,
21 lks. dist., mkd. ¼ S30 BT.

and from which a 1956 bearing tree

A pinyon, 10 ins. diam., bears N 61½° W,
77 lks. dist., mkd. ¼ S25 BT.

N 1°17' E, beginning new measurement.

39.99 The cor. of secs. 19, 24, 25 and 30, monumented with an
iron post, 2½ ins. diam., firmly set, projecting 18 ins.
above ground, and in a mound of stone, 3½ ft. base, to
top, with brass cap mkd.

Dependent Resurvey of a Portion of the West Boundary
T 17 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS

T17N
R5E | R6E
S24 | S19

S25 | S30
1956

from which the remaining 1902 bearing trees

A pinyon, 8 ins. diam., bears N 59° E, 87 lks. dist., mkd. T17N R6E S19 BT.

A juniper, 14 ins. diam., bears N 21½° W, 104 lks. dist., mkd. T17N R5E S24 BT.

and from which the 1956 bearing trees

A pinyon, 7 ins. diam., bears S 21° E, 15 lks. dist., mkd. T17N R6E S30 BT.

A juniper, 9 ins. diam., bears S 84° W, 71 lks. dist., mkd. T17N R5E S25 BT.
(Record: pinyon)

Dependent Resurvey, a Portion of the Subdivisional Lines
T 17 N, R 6 E, Gila and Salt River Mer., Arizona

Reestablishment of the resurvey executed
by Donald E. Harding, in 1957

From the cor. of secs. 4, 5, 8, 9, monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T17N R6E
S 5 | S 4

S 8 | S 9
1957

from which the 1902 bearing trees

A pinyon, 7 ins. diam., bears S 41° E, 35 lks. dist., mkd. T17N R6E S9 BT.
(Record: S 28¼° E)

A pinyon, 8 ins. diam., bears S 21° W, 33 lks. dist., mkd. T17N R6E S8 BT.
(Record: S 15¼° W, 36 lks. dist.)

and from which a 1957 bearing tree

A pinyon, 11 ins. diam., bears N 34½° W, 113 lks. dist., mkd. T17N R6E S5 BT.
(Record: N 32¼° W, 110 lks. dist.)

N 0°51' W, bet. secs. 4 and 5.

Over mountainous land, through medium juniper, pinyon, yew, oak brush and mountain mahogany.

19.86

Point for the S 1/16 sec. cor. of secs. 4 and 5.

Dependent Resurvey, a Portion of the Subdivisional Lines
T 17 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T17N R6E S 1/16 S 5 S 4 1984</p> <p>from which</p> <p style="padding-left: 40px;">A yew, 6 ins. diam., bears N 20° E, 30 lks. dist., mkd. S 1/16 S4 BT.</p> <p style="padding-left: 40px;">A yew, 8 ins. diam., bears N 55° W, 65 lks. dist., mkd. S 1/16 S5 BT.</p> <p>Set a steel fence post alongside the cor.</p>	
39.72	<p>The ¼ sec. cor. of secs. 4 and 5, monumented with an iron post, 2½ ins. diam., projecting 12 ins. above ground, and in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T17N R6E ¼ S 5 S 4 1957</p> <p>from which the 1957 bearing trees</p> <p style="padding-left: 40px;">A yew, 7 ins. diam., bears S 23° E, 18 lks. dist., mkd. ¼ S4 BT. (Record: S 50° E)</p> <p style="padding-left: 40px;">A yew, 6 ins. diam., bears N 32° W, 21 lks. dist., mkd. ¼ S5 BT. (Record: N 34° W, 22 lks. dist.)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°44' W, beginning new measurement.</p>	
39.01	<p>The cor. of secs. 4 and 5 only, on the N bdy. of the Tp., heretofore described.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S 89°51' W, bet. secs. 5 and 8.</p> <p>Over rolling land, through medium pinyon, scattered mesquite and mountain mahogany.</p>	
21.46	<p>Point for the E 1/16 sec. cor. of secs. 5 and 8.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 8 ins. in the ground, in a mound of stone, 4 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T17N R6E E 1/16 S 5 S 8 1984</p> <p>from which</p> <p style="padding-left: 40px;">A point on a sandstone ledge, 35 x 8 x 8 ft., bears S 88° E, 21 lks. dist., mkd. X BO.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines
T 17 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A pinyon, 6 ins. diam., bears N 13° W, 33 lks. dist., mkd. E 1/16 S5 BT.</p> <p>Set a steel fence post alongside the cor.</p> <p>32.19 Point for the W-E 1/64 sec. cor. of secs. 5 and 8.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S 5 W E 1/64 S 8 1984</p> <p>from which</p> <p>A pinyon, 6 ins. diam., bears N 50° E, 11 lks. dist., mkd. W-E 1/64 S5 BT.</p> <p>A pinyon, 6 ins. diam., bears S 7½° E, 31 lks. dist., mkd. W-E 1/64 S8 BT.</p> <p>Set a steel fence post alongside the cor.</p>
	<p>37.555 Point for the W-W-E 1/256 sec. cor. of secs. 5 and 8.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S 5 W W E 1/256 S 8 1984</p> <p>from which</p> <p>A sycamore, 4 ins. diam., bears N 43° E, 82 lks. dist., mkd. X at breast height and BT at base.</p> <p>A point on a basalt stone, 5 x 4 x 4 ft., bears S 88° W, 87 lks. dist., mkd. X BO.</p> <p>A point on a basalt stone, 2 x 2 x ½ ft., bears N 8° W, 23 lks. dist., mkd. X BO.</p> <p>Cor. is located at W edge of Oak Creek, 120 lks. wide, course S 65° W.</p> <p>Set a steel fence post alongside the cor.</p>
	<p>42.92 The ¼ sec. cor. of secs. 5 and 8, monumented with an iron post, 2½ ins. diam., projecting 3 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T17N R6E ¼ S 5 S 8 1957</p> <p>from which</p>

Dependent Resurvey, a Portion of the Subdivisional Lines
T 17 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>An oak, 14 ins. diam., bears S 63° E, 38 lks. dist., mkd. ¼ S8 BT. (Record: N 60° E)</p> <hr/> <p>S 88°47' W, beginning new measurement.</p>	
19.63	Point for the W 1/16 sec. cor. of secs. 5 and 8; not monumented.	
39.26	<p>The cor. of secs. 5, 6, 7 and 8, monumented with a local brass cap, 2½ ins. diam., flush with surface of paved road, with top incorrectly mkd. for R5E.</p> <p style="text-align: center;">SEC COR S 6 S 5 S 7 S 8 T17N R5E</p> <p>This is accepted as a careful perpetuation of the position of the original cor.</p> <p>Cor. is located in Navahopi Street, 37 lks. W of Jordan Road, bears N and S.</p> <hr/> <p>N 1°50' E, bet. secs. 5 and 6.</p>	
20.00	Point for the S 1/16 sec. cor. of secs. 5 and 6; not monumented.	
30.00	<p>Point for the N-S 1/64 sec. cor. of secs. 5 and 6.</p> <p>Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 6 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N S 1/64 S 6 S 5 1984</p> <p>from which</p> <p style="text-align: center;">A pinyon, 4 ins. diam., bears N 22° W, 38 lks. dist., mkd. X at breast height and BT at base.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. falls 32 lks. N of an E and W track road and 1.5 lks. E of a N and S fence.</p>	
35.00	<p>The N-N-S 1/256 sec. cor. of secs. 5 and 6, monumented with a pipe, 1 in. diam., projecting 5 ins. above ground, with brass cap attached and mkd. COR 6 X. This is accepted as a careful and faithful determination of the cor. position.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines
T 17 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">N N S 1/256 S 6 S 5 1984</p> <p>from which</p> <p style="padding-left: 40px;">A yew, 8 ins. diam., bears N 43° E, 17 lks. dist., mkd. N-N-S 1/256 S5 BT.</p> <p style="padding-left: 40px;">A yew, 8 ins. diam., bears S 64° W, 15 lks. dist., mkd. N-N-S 1/256 S6 BT.</p> <p>Drove the local cor. alongside the aluminum post.</p> <p>From this point, another local cor. bears N 40° E, 1.5 lks. dist., monumented with an open end iron pipe, 1 in. diam., projecting 4 ins. above ground.</p> <p>A fence cor., bears N 12° E, 7 lks. dist., fences extend N, E and S.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N 1°50' E, beginning new measurement.</p>
5.00	<p>The ¼ sec. cor. of secs. 5 and 6, monumented with an iron post, 2½ ins. diam., projecting 12 ins. above ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T17N R6E ¼ S 6 S 5 1957</p> <p>from which</p> <p style="padding-left: 40px;">A yew, 8 ins. diam., bears N 51¼° E, 14 lks. dist., mkd. ¼ S5 BT.</p> <p style="padding-left: 40px;">A yew, 6 ins. diam., bears N 60° W, 8 lks. dist., mkd. ¼ S6 BT. (Record: N 71¼° W)</p> <p>Cor. is located in a barbed wire fence line, bears N and S.</p> <p>From this cor., U.S. Geological Survey triangulation station "MUNDS, 1930" bears S 54°10'26" E, 273.81 chs. dist., monumented with a brass tablet, 3½ ins. diam., set in a boulder, 2½ x 1½ x ½ ft., with top mkd. TT NO. Y1930 and a cross in the center.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N 1°54' E, beginning new measurement.</p>
38.87	<p>The cor. of secs. 5 and 6 only, on the N bdy. of the Tp., heretofore described.</p> <hr style="width: 80%; margin: 20px auto;"/> <p>From the cor. of secs. 29, 30, 31 and 32, monumented with a brass tablet, 3½ ins. diam., set in sandstone outcrop, with top mkd.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines
T 17 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS

T17N R6E
S30 | S29
S31 | S32
1957

from which the bearing trees mkd. in 1887

A pinyon, 6 ins. diam., bears S 78½° E,
42 lks. dist., mkd. T17N R6E S32 BT.

A pinyon, 8 ins. diam., bears S 12¾° E,
60 lks. dist., no marks visible.

A pinyon, 8 ins. diam., bears S 86½° W,
63 lks. dist., mkd. T17N R6E S31 BT.

and from which the 1957 bearing trees

A pinyon, 10 ins. diam., bears N 43¼° E,
81 lks. dist., mkd. T17N R6E S29 BT.

A pinyon, 8 ins. diam., bears N 41½° W,
25 lks. dist., mkd. T17N R6E S30 BT.
(Record: 24 lks. dist.)

N 89°49' W, bet. secs. 30 and 31.

Over rolling land, through medium juniper, pinyon and oak brush.

43.27 The ¼ sec. cor. of secs. 30 and 31, monumented with an iron post, 2½ ins. diam., projecting 10 ins. above ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.

T17N R6E
¼ S30
S31
1957

from which the 1957 bearing trees

A juniper, 10 ins. diam., bears N 68¼° E,
96 lks. dist., mkd. ¼ S30 BT.

A juniper, 10 ins. diam., bears S 2¼° E,
80 lks. dist., mkd. ¼ S31 BT.

N 89°50' W, beginning new measurement.

22.98 Point for the W 1/16 sec. cor. of secs. 30 and 31.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T17N R6E
W 1/16 S30
S31
1985

from which

A juniper, 16 ins. diam., bears N 19° E,
36 lks. dist., mkd. W 1/16 S30 BT.

Dependent Resurvey, a Portion of the Subdivisional Lines
T 17 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS		
46.13	<p>A yew, 14 ins. diam., bears S 7° E, 9 lks. dist., mkd. W 1/16 S31 BT.</p> <p>Set a steel fence post alongside the cor.</p> <p>The cor. of secs. 25, 30, 31 and 36, on the W bdy. of the Tp., heretofore described.</p>	
39.88	<p>From the cor. of secs. 29, 30, 31 and 32, heretofore described.</p> <p>N 0°23' W, bet. secs. 29 and 30.</p> <p>Over rolling land, through medium juniper and pinyon.</p> <p>The ¼ sec. cor. of secs. 29 and 30, monumented with an iron post, 2½ ins. diam., projecting 10 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T17N R6E ¼ S30 S29 1957</p> <p>from which the 1957 bearing trees</p> <p>A pinyon, 8 ins. diam., bears N 22¼° E, 92 lks. dist., mkd. ¼ S29 BT.</p> <p>A dead standing pinyon, 6 ins. diam., bears S 57° W, 60 lks. dist., mkd. ¼ S30 BT.</p> <p>A mound of stone, 2½ ft. base, 1 ft. high, is W of cor.</p> <p style="text-align: center;">_____</p> <p>N 0°31' E, beginning new measurement.</p>	
20.49	<p>Point for the N 1/16 sec. cor. of secs. 29 and 30.</p> <p>Set an aluminum tablet, 2½ ins. diam., 2½ in. stem, in a drill hole in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T17N R6E N 1/16 S30 S29 1985</p> <p>from which</p> <p>A pinyon, 6 ins. diam., bears S 3½° E, 76 lks. dist., mkd. N 1/16 S29 BT.</p> <p>A juniper, 8 ins. diam., bears S 67° W, 99 lks. dist., mkd. N 1/16 S30 BT.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p>	
30.735	<p>Point for the N-N 1/64 sec. cor. of secs. 29 and 30.</p> <p>Set an aluminum post, 10 ins. long, 1 in. diam., in a drill hole on top of a sandstone ledge, with cap mkd.</p> <p style="text-align: center;">N N 1/64 S30 S29 1985</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines
T 17 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS		
40.98	<p>from which</p> <p>A point on a sandstone ledge, 6 ft. high, bears N 53° E, 9 lks. dist., mkd. X BO.</p> <p>A point on the same ledge, bears N 52½° W, 28 lks. dist., mkd. X BO.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.</p> <p>The cor. of secs. 19, 20, 29 and 30, monumented with an iron post, 2½ ins. diam., firmly set, projecting 24 ins. above ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T17N R6E S19 S20 S30 S29 1957</p> <p>from which the 1957 bearing trees</p> <p>A pinyon, 8 ins. diam., bears S 83° W, 30 lks. dist., mkd. T17N R6E S30 BT.</p> <p>A pinyon, 10 ins. diam., bears N 32½° W, 78 lks. dist., mkd. T17N R6E S19 BT. (Record: N 30° W, 75 lks. dist.)</p>	
10.96	<p>N 89°42' W, bet. secs. 19 and 30.</p> <p>Over mountainous land, through medium pinyon, juniper and oak brush.</p> <p>Point for the E-E 1/64 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S19 E E 1/64 S30 1985</p> <p>from which</p> <p>A juniper, 4 ins. diam., bears S 68° E, 26 lks. dist., mkd. X at breast height and BT at base.</p> <p>A point on a malpais boulder, 6 x 4 x 4 ft., bears N 67° W, 22 lks. dist., mkd. X BO.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>Point for the E 1/16 sec. cor. of secs. 19 and 30.</p> <p>Set an aluminum tablet, 2½ ins. diam., 2½ in. stem, cemented in a drill hole in sandstone bedrock, with cap mkd.</p>	
21.92		

Dependent Resurvey, a Portion of the Subdivisional Lines
T 17 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T17N R6E E 1/16 $\frac{S19}{S30}$ 1985</p> <p>from which</p> <p style="text-align: center;">A pinyon, 8 ins. diam., bears S 71° W, 42 lks. dist., mkd. E 1/16 S30 BT.</p> <p>Set a steel fence post alongside the cor.</p>	
<p>32.88</p>	<p>The W-E 1/64 sec. cor. of secs. 19 and 30, monumented with a rebar, ½ in. diam., projecting 2 ins. above ground. This point is accepted as a careful and faithful determination of the cor. position.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S19 W E 1/64 S30 1985</p> <p>from which</p> <p style="text-align: center;">A point at the base of a sandstone bluff, bears N 29° E, 16 lks. dist., mkd. X BO.</p> <p>From this point the SE cor. of the roof of a carport, 27 x 23 ft., bears S 3°49' E, 2.884 chs. dist., long side bears N 57° E and S 57° W.</p> <p>Drove local cor. alongside the aluminum post.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 89°42' W, beginning new measurement.</p>	
<p>10.985</p>	<p>The ¼ sec. cor. of secs. 19 and 30, monumented with an iron post, 2½ ins. diam., flush with the ground, with brass cap mkd.</p> <p style="text-align: center;">T17N R6E ¼ $\frac{S19}{S30}$ 1957</p> <p>from which</p> <p style="text-align: center;">A fire hydrant, bears S 67° W, 11.7 lks. dist.</p> <p>Add the marks 1984 to the brass cap.</p> <p>Cor. is located 33 lks. S of center of Chapel Road, bears N 85° W, curving W and S 85° E, curving SE, and 42 lks. W of Cathedral Lane, extends S from Chapel Road.</p> <p>From this cor., U.S. Geological Survey triangulation station "MUNDS" bears N 65°42'10" E, 288.92 chs. dist., heretofore described.</p> <hr style="width: 50%; margin: 10px auto;"/>	

Dependent Resurvey, a Portion of the Subdivisional Lines
T 17 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS		
43.82	<p>N 89°43' W, beginning new measurement.</p> <p>The cor. of secs. 19, 24, 25 and 30, on the W bdy. of the Tp., heretofore described.</p>	
<hr/> <p>Subdivision of Section 5, T 17 N, R 6 E, Gila and Salt River Mer., Arizona</p> <hr/>		
9.875	<p>From the ¼ sec. cor. of secs. 5 and 8.</p> <p>N 2°21' E, on the N and S center line of sec. 5.</p> <p>Over rolling land, through medium juniper and oak brush.</p> <p>Point for the center S-S 1/64 sec. cor. of sec. 5.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <div style="text-align: center;"> <p>C S S 1/64 S 5 C 1984</p> </div> <p>from which</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N 11° E, 32 lks. dist., mkd. C-S-S 1/64 S5 BT.</p> <p style="padding-left: 40px;">A pinyon, 4 ins. diam., bears N 51° W, 28 lks. dist., mkd. X at breast height and BT at base.</p> <p>Cor. is located 5 lks. S of an abandoned E and W fence.</p> <p>Set a steel fence post alongside the cor.</p>	
19.75	<p>Point for the center S 1/16 sec. cor. of sec. 5.</p> <p>Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 20 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T17N R6E C S 1/16 S 5 C 1984</p> </div> <p>from which</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N 3½° E, 41 lks. dist., mkd. C S 1/16 S5 BT.</p> <p style="padding-left: 40px;">A pinyon, 4 ins. diam., bears S 71° W, 30 lks. dist., mkd. X at breast height and BT at base.</p> <p>Set a steel fence post alongside the cor.</p> <p>From this point a fence cor., bears N 75° E, 33 lks. dist., fence extends N, S 65° E and W.</p>	

Subdivision of Section 5, T 17 N, R 6 E,
Gila and Salt River Mer., Arizona

CHAINS		
39.50	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 5, at intersection with the E and W center line of sec. 5.</p> <p>Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 14 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T17N R6E C $\frac{1}{4}$ S5 1984</p> <p>from which</p> <p style="padding-left: 40px;">A pinyon, 8 ins. diam., bears S 50° E, 6 lks. dist., mkd. C $\frac{1}{4}$ S5 BT.</p> <p style="padding-left: 40px;">A pinyon, 6 ins. diam., bears S $78\frac{1}{2}^\circ$ W, 33 lks. dist., mkd. C $\frac{1}{4}$ S5 BT.</p> <p>Set a steel fence post alongside the cor.</p>	
78.11	<p>The $\frac{1}{4}$ sec. cor. of sec. 5 only, on the N bdy. of the Tp., heretofore described.</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 4 and 5.</p> <p>S $89^\circ 31'$ W, on the E and W center line of sec. 5.</p> <p>Over rolling land, through medium juniper, pinyon, yew and oak brush.</p>	
20.36	<p>Point for the center E $\frac{1}{16}$ sec. cor. of sec. 5.</p> <p>Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 6 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T17N R6E C $\frac{E \frac{1}{16}}$ C S 5 1984</p> <p>from which</p> <p style="padding-left: 40px;">A pinyon, 7 ins. diam., bears N $28\frac{1}{2}^\circ$ E, 39 lks. dist., mkd. C-E $\frac{1}{16}$ S5 BT.</p> <p style="padding-left: 40px;">A pinyon, 8 ins. diam., bears S $83\frac{1}{2}^\circ$ W, 66 lks. dist., mkd. C-E $\frac{1}{16}$ S5 BT.</p> <p>Set a steel fence post alongside the cor.</p>	
40.72	<p>The center $\frac{1}{4}$ sec. cor. of sec. 5.</p>	
60.505	<p>Point for the center W $\frac{1}{16}$ sec. cor. of sec. 5.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. in the ground, and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with cap mkd.</p>	

Subdivision of Section 5, T 17 N, R 6 E,
Gila and Salt River Mer., Arizona

CHAINS

T17N R6E
C $\frac{W 1/16}{S 5}$ C
1984

from which

A pinyon, 4 ins. diam., bears N 69° E, 32 lks. dist., mkd. X at breast height and BT at base.

A pinyon, 7 ins. diam., bears N 14° W, 40 lks. dist., mkd. C-W 1/16 S5 BT.

Set a steel fence post alongside the cor.

Cor. is located 160 lks. N of an E and W fence.

80.29 The $\frac{1}{4}$ sec. cor. of secs. 5 and 6.

SE $\frac{1}{4}$ of Section 5

From the E 1/16 sec. cor. of secs. 5 and 8.

N 0°45.5' E, on the N and S center line of the SE $\frac{1}{4}$ of sec. 5.

Over mountainous land, through medium pinyon, juniper, yew and oak brush.

9.90 Point for the center S-SE 1/64 sec. cor. of sec. 5.

Set an aluminum post, 28 ins. long, 1 in. diam., 26 ins. in the ground, with cap mkd.

S 5
C S SE
1/64
1984

from which

A point on a sandstone boulder, 8 x 4 x 4 ft., bears S 66° E, 44 lks. dist., mkd. X BO.

A point on a sandstone boulder, 10 x 6 x 6 ft., bears S 60° W, 16 lks. dist., mkd. X BO.

Cor. is located in a wash, 30 lks. wide, in the bottom of a canyon, drains N 60° W.

19.80 Point for the SE 1/16 sec. cor. of sec. 5, at intersection with the E and W center line of the SE $\frac{1}{4}$ of sec. 5.

Set an aluminum post, 28 ins. long, 1 in. diam., 4 ins. in the ground, in a mound of stone, 4 ft. base, to top, with cap mkd.

T17N R6E
SE 1/16 S5
1984

Subdivision of Section 5, T 17 N, R 6 E,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A ponderosa pine, 8 ins. diam., bears S 72° E, 98 lks. dist., mkd. X at breast height and BT at base.</p> <p>A ponderosa pine, 16 ins. diam., bears S 6½° E, 108 lks. dist., mkd. SE 1/16 S5 BT.</p> <p>Cor. is located 130 lks. E of Oak Creek, 70 lks. wide, flows S 40° W.</p>
39.60	<p>The center E 1/16 sec. cor. of sec. 5.</p> <hr/>
	<p>From the S 1/16 sec. cor. of secs. 4 and 5.</p> <p>S 89°41.5' W, on the E and W center line of the SE¼ of sec. 5.</p> <p>Over mountainous land, through medium juniper and pinyon.</p>
20.91	<p>The SE 1/16 sec. cor. of sec. 5.</p>
31.365	<p>Point for the center W-SE 1/64 sec. cor. of sec. 5.</p> <p>Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 12 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S 5 C W SE 1/64 1984</p>
	<p>from which</p> <p>A juniper, 12 ins. diam., bears S 62° W, 30 lks. dist., mkd. C-W-SE 1/64 S5 BT.</p> <p>A pinyon, 9 ins. diam., bears N 13° W, 69 lks. dist., mkd. C-W-SE 1/64 S5 BT.</p> <p>Set a steel fence post alongside the cor.</p>
41.82	<p>The center S 1/16 sec. cor. of sec. 5.</p> <hr/>
	<p>From the W-E 1/64 sec. cor. of secs. 5 and 8.</p> <p>N 1°31.5' E, on the N and S center line of the SW¼ of the SE¼ of sec. 5.</p>
7.415	<p>Point for the 1/1024 sec. cor. of sec. 5.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S 5 1/1024 1984</p>

Subdivision of Section 5, T 17 N, R 6 E,
Gila and Salt River Mer., Arizona

CHAINS

- Set a steel fence post alongside the cor.
- 9.885 Point for the SW-SE 1/64 sec. cor. of sec. 5, at intersection with the E and W center line of the SW $\frac{1}{4}$ of the SE $\frac{1}{4}$ of sec. 5.
- Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2 $\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 20 ins. in the ground, in a mound of stone, 2 $\frac{1}{2}$ ft. base, to top, with brass cap mkd.
- S 5
SW SE
1/64
1984
- from which
- An ash, 10 ins. diam., bears S 3° E, 42 lks. dist., mkd. SW-SE 1/64 S5 BT.
- Set a steel fence post alongside the cor.
- 12.355 Point for the 1/1024 sec. cor. of sec. 5.
- Set a rebar, 12 ins. long, $\frac{3}{4}$ in. diam., 2 ins. below the surface of a dirt road, with aluminum cap attached and mkd.
- S 5
1/1024
1984
- from which
- A pinyon, 6 ins. diam., bears N 40° E, 32 lks. dist., mkd. 1/1024 S5 BT.
- A power pole, bears N 70 $\frac{1}{2}$ ° E, 27.5 lks. dist.
- A local survey cor., bears S 41° E, 13.2 lks. dist., monumented with a rebar, $\frac{1}{2}$ in. diam., set flush in driveway.
- A point on a sandstone outcrop, 2 x 1 $\frac{1}{2}$ x $\frac{1}{2}$ ft., bears N 43° W, 49 lks. dist., mkd. X B0.
- The SW cor. of a trailer house, 8 x 26.5 ft., bears N 65°27' E, 1.227 chs. dist., long side bears N 70° E and S 70° W.
- The SW cor. of a trailer house, 8 x 32 ft., bears N 78°25' E, 58.8 lks. dist., long side bears N 66° E and S 66° W.
- The northerly cor. of a metal storage shed, 9.3 x 10.3 ft., bears N 81°16' E, 1.635 chs. dist., long side bears N 45° E and S 45° W.
- The northerly cor. of a partly constructed wood frame house, 16 x 24 ft., bears N 89°37' E, 1.618 chs. dist., long side bears S 42° E and N 42° W.
- The NE cor. of a wood frame house, bears S 10° W, 64 lks. dist.

Subdivision of Section 5, T 17 N, R 6 E,
Gila and Salt River Mer., Arizona

CHAINS	
19.77	<p>The center W-SE 1/64 sec. cor. of sec. 5.</p> <hr/> <p>From the center S-SE 1/64 sec. cor. of sec. 5.</p> <p>S 89°45.5' W, on the E and W center line of the SW$\frac{1}{4}$ of the SE$\frac{1}{4}$ of sec. 5.</p>
7.945	<p>True point for the 1/1024 sec. cor. of sec. 5, falls in Oak Creek, 150 lks. wide, flows S 30° W, where it is impractical to monument.</p> <p>from which</p> <p style="padding-left: 40px;">An aluminum post, 28 ins. long, 1 in. diam., set 20 ins. in the ground, for a reference monument, bears S 69°22' E, 90.7 ft. dist., with cap mkd. 1/1024 RM 90.4 FT. 1984 and an arrow pointing to the true point.</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears S 43$\frac{1}{4}$° E, 126 lks. dist., mkd. 1/1024 S5 BT.</p>
10.595	<p>The SW-SE 1/64 sec. cor. of sec. 5.</p>
15.895	<p>Point for the center W-SW-SE 1/256 sec. cor. of sec. 5.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S 5 C W SW SE 1/256 1984</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 5 lks. S of an old fence, bears N 40° E and S 40° W.</p>
21.195	<p>The center S-S 1/64 sec. cor. of sec. 5.</p> <hr/> <p>From the true point for the 1/1024 sec. cor. of sec. 5, on the E and W center line of the SW$\frac{1}{4}$ of the SE$\frac{1}{4}$ of sec. 5.</p> <p>N 1°20.5' E, on the N and S center line of the SW$\frac{1}{4}$ of the NE$\frac{1}{4}$ of the SW$\frac{1}{4}$ of the SE$\frac{1}{4}$ of sec. 5.</p>
2.473	<p>Point for the 1/1024 sec. cor. of sec. 5.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, 2$\frac{1}{2}$ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S 5 1/1024 1984</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 33 lks. S of a dirt canal, flows S 30° W.</p> <hr/>

Subdivision of Section 5, T 17 N, R 6 E,
Gila and Salt River Mer., Arizona

CHAINS		
	<p>S 89°44.5' W, on the E and W center line of the SW$\frac{1}{4}$ of the NE$\frac{1}{4}$ of the SW$\frac{1}{4}$ of the SE$\frac{1}{4}$ of sec. 5.</p>	
2.64	<p>The 1/1024 sec. cor. of sec. 5, at 12.355 chs., on the N and S center line of the SW$\frac{1}{4}$ of the SE$\frac{1}{4}$ of sec. 5.</p> <hr/> <p>From the W-W-E 1/256 sec. cor. of secs. 5 and 8.</p> <p>N 1°57' E, on the N and S center line of the SW$\frac{1}{4}$ of the SW$\frac{1}{4}$ of the SE$\frac{1}{4}$ of sec. 5.</p> <p>Through Oak Creek bottom land.</p>	
1.00	<p>Right bank of Oak Creek, bears NE and SW, thence over leveled area along the W side of an orchard.</p>	
2.47	<p>Point for the 1/1024 sec. cor. of sec. 5.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S 5 1/1024 1984</p> <p>from which</p> <p style="padding-left: 40px;">A yew, 12 ins. diam., bears S 89° E, 60 lks. dist., mkd. 1/1024 S5 BT.</p> <p>From this point, a local survey cor., bears S 72°19' W, 14.5 lks. dist., monumented with an open end pipe, 1 in. diam., projecting 10 ins. above ground.</p> <hr/> <p>N 89°51' E, on the E and W center line of the SE$\frac{1}{4}$ of the SW$\frac{1}{4}$ of the SW$\frac{1}{4}$ of the SE$\frac{1}{4}$ of sec. 5.</p> <p>Through Oak Creek bottom, along the N side of an orchard and across a horse shoe court.</p>	
1.50	<p>Rail fence on the right bank of Oak Creek, bears N 40° E and S 40° W, leave orchard.</p>	
2.675	<p>Point for the 1/1024 sec. cor. of sec. 5.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S 5 1/1024 1984</p> <p>from which</p> <p style="padding-left: 40px;">An elm, 16 ins. diam., bears N 51½° E, 21 lks. dist., mkd. 1/1024 S5 BT.</p> <p style="padding-left: 40px;">A point on a basalt stone, 2½ x 3½ x 1½ ft., bears N 6° W, 67 lks. dist., mkd. X BO.</p>	

Subdivision of Section 5, T 17 N, R 6 E,
Gila and Salt River Mer., Arizona

CHAINS		
	<p>From this point, a local survey cor., bears S 56°23' W, 19.2 lks. dist., monumented with an open end iron pipe, 1 in. diam., projecting 3 ins. above ground.</p> <p>Cor. is located 26 lks. N of right bank of main channel of Oak Creek, 100 lks. wide, course S 45° W.</p> <hr/> <p>N 1°43.5' E, on the N and S center line of the SE$\frac{1}{4}$ of the SW$\frac{1}{4}$ of the SW$\frac{1}{4}$ of the SE$\frac{1}{4}$ of sec. 5.</p> <p>Through Oak Creek bottom.</p>	
2.47	<p>Point for the 1/1024 sec. cor. of sec. 5; not monumented.</p> <p>Continue measurement on the N and S center line of the NE$\frac{1}{4}$ of the SW$\frac{1}{4}$ of the SW$\frac{1}{4}$ of the SE$\frac{1}{4}$ of sec. 5.</p>	
4.94	<p>Point for the 1/1024 sec. cor. of sec. 5.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 2$\frac{1}{2}$ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S 5 1/1024 1984</p> <p>from which</p> <p style="text-align: center;">A ponderosa pine, 26 ins. diam., bears S 37° E, 132 lks. dist., mkd. 1/1024 S5 BT.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>N 89°47' E, on the E and W center line of the NE$\frac{1}{4}$ of the SW$\frac{1}{4}$ of the SW$\frac{1}{4}$ of the SE$\frac{1}{4}$ of sec. 5.</p> <p>Through Oak Creek bottom.</p>	
2.66	<p>The 1/1024 sec. cor. of sec. 5, at 7.415 chs., on the N and S center line of the SW$\frac{1}{4}$ of the SE$\frac{1}{4}$ of sec. 5.</p> <hr/> <p>From the center W-SW-SE 1/256 sec. cor. of sec. 5.</p> <p>N 1°57' E, on the N and S center line of the NW$\frac{1}{4}$ of the SW$\frac{1}{4}$ of the SE$\frac{1}{4}$ of sec. 5.</p>	
2.00	<p>Center of Highway No. 89A, bears N 50° E and S 50° W.</p>	
2.47	<p>Point for the 1/1024 sec. cor. of sec. 5.</p> <p>Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2$\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S 5 1/1024 1984</p>	

Subdivision of Section 5, T 17 N, R 6 E,
Gila and Salt River Mer., Arizona

CHAINS

from which

A point on a concrete abutment, bears S 50° W,
26 lks. dist., mkd. X BO.

A pinyon, 4 ins. diam., bears N 11½° W, 21
lks. dist., mkd. X at breast height and
BT at base.

Set a steel fence post alongside the cor.

N 89°44.5' E, on the E and W center line of the SE¼ of
the NW¼ of the SW¼ of the SE¼ of sec. 5.

5.28 The 1/1024 sec. cor. of sec. 5, at 12.355 chs., on the
N and S center line of the SW¼ of the SE¼ of sec. 5.

SW¼ of Section 5

From the point for the W 1/16 sec. cor. of secs. 5 and
8.

N 2°04.5' E, on the N and S center line of the SW¼ of
sec. 5.

Over rolling land, through medium juniper, pinyon,
manzanita and oak brush.

9.935 Point for the center S-SW 1/64 sec. cor. of sec. 5.

Set a monument, 30 ins. long, composed of a stainless
steel post, 25 ins. long, 2½ ins. diam., bonded to a
magnetic poly breakaway base, 12 ins. in the ground, in
a mound of stone, 4½ ft. base, to top, with brass cap
mkd.

S 5
C S SW
1/64
1984

from which

A pinyon, 8 ins. diam., bears N 26° E,
45 lks. dist., mkd. C S SW 1/64 S5 BT.

Set a steel fence post alongside the cor.

From this point, a local survey cor., bears East, 5.5
lks. dist., monumented with an iron pipe, 1 in. diam.,
projecting 12 ins. above ground, with brass cap mkd.
COR 4 X.

19.87 Point for the SW 1/16 sec. cor. of sec. 5, at intersec-
tion with the E and W center line of the SW¼ of sec. 5.

Set a monument, 30 ins. long, composed of a stainless
steel post, 25 ins. long, 2½ ins. diam., bonded to a
magnetic poly breakaway base, 10 ins. in the ground, in
a mound of stone, 3½ ft. base, to top, with brass cap
mkd.

Subdivision of Section 5, T 17 N, R 6 E,
Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T17N R6E SW 1/16 S5 1984</p> <p>from which</p> <p style="text-align: center;">A pinyon, 8 ins. diam., bears N 55° E, 13 lks. dist., mkd. SW 1/16 S5 BT.</p> <p>Set a steel fence post alongside the cor.</p>	
34.78	<p>Point for the center N-N-SW 1/256 sec. cor. of sec. 5.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. in the ground, in a mound of stone, 4 ft. base, to top, with cap mkd.</p>	
	<p style="text-align: center;">S 5 C N N SW 1/256 1984</p> <p>from which</p> <p style="text-align: center;">A yew, 16 ins. diam., bears N 32° W, 11 lks. dist., mkd. C-N-N-SW 1/256 S5 BT.</p> <p>Set a steel fence post alongside the cor.</p> <p>From this point, a local survey cor. bears S 88°48' E, 19 lks. dist., monumented with a rebar, $\frac{3}{4}$ in. diam., projecting 4 ins. above ground, with a plastic cap attached and mkd. J & G ENGINEERING LS2049.</p> <p>Cor. is located 19 lks. E of a wash, 30 lks. wide, drains S 10° W.</p>	
39.75	<p>The center W 1/16 sec. cor. of sec. 5.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center S 1/16 sec. cor. of sec. 5.</p> <p>S 89°09' W, on the E and W center line of the SW$\frac{1}{4}$ of sec. 5.</p> <p>Over rolling land, through medium juniper, pinyon and manzanita.</p>	
19.705	<p>The SW 1/16 sec. cor. of sec. 5.</p>	
39.41	<p>The point for the S 1/16 sec. cor. of secs. 5 and 6, hereinbefore called for.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center S-S 1/64 sec. cor. of sec. 5.</p> <p>S 88°57' W, on the E and W center line of the SE$\frac{1}{4}$ of the SW$\frac{1}{4}$ of sec. 5.</p> <p>Over rolling land, through medium to dense pinyon and juniper.</p>	
19.665	<p>The center S-SW 1/64 sec. cor. of sec. 5.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center N-N-SW 1/256 sec. cor. of sec. 5.</p>	

Subdivision of Section 5, T 17 N, R 6 E,
Gila and Salt River Mer., Arizona

CHAINS		
19.765	<p>S 89°24' W, on the E and W center line of the N$\frac{1}{2}$ of the NW$\frac{1}{4}$ of the SW$\frac{1}{4}$ of sec. 5.</p> <p>Over rolling land, through medium to dense pinyon, yew and juniper.</p> <p>The N-N-S 1/256 sec. cor. of secs. 5 and 6.</p>	
<p>Subdivision of Section 30, T 17 N, R 6 E, Gila and Salt River Mer., Arizona</p>		
20.22	<p>From the $\frac{1}{4}$ sec. cor. of secs. 30 and 31.</p> <p>N 0°22' W, on the N and S center line of sec. 30.</p> <p>Over rolling land, through medium juniper and pinyon.</p> <p>Point for the center S 1/16 sec. cor. of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 14 ins. in the ground, and in a mound of stone, 3$\frac{1}{2}$ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T17N R6E C S 1/16 S30 C 1985</p> <p>from which</p> <p style="padding-left: 40px;">A pinyon, 10 ins. diam., bears N 65° E, 70 lks. dist., mkd. C-S 1/16 S30 BT.</p> <p style="padding-left: 40px;">A pinyon, 6 ins. diam., bears N 32° W, 31 lks. dist., mkd. C-S 1/16 S30 BT.</p> <p>Set a steel fence post alongside the cor.</p>	
40.44	<p>The center $\frac{1}{4}$ sec. cor. of sec. 30, monumented with a red sandstone, 16 x 10 x 6 ins., firmly set 8 ins. in the ground, mkd. $\frac{1}{4}$ on four sides and a cross on top. This point was monumented by Clyde M. Etter, Registered Highway Engineer No. 977, AZ, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T17N R6E C $\frac{1}{4}$ S30 1985</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N 33$\frac{1}{2}$° E, 64 lks. dist., mkd. C $\frac{1}{4}$ S30 BT.</p> <p style="padding-left: 40px;">A juniper, 10 ins. diam., bears S 27° E, 80 lks. dist., mkd. C $\frac{1}{4}$ S30 BT.</p>	

Subdivision of Section 30, T 17 N, R 6 E,
Gila and Salt River Mer., Arizona

CHAINS

Deposit the mkd. stone alongside the cor.

Set a steel fence post alongside the cor.

Cor. is located 5 lks. SE of a power pole and 1.5 lks. SE of a chain link fence cor., fences extend N and W.

N 0°27' W, beginning new measurement.

5.055 The center S-S-N 1/256 sec. cor. of sec. 30, monumented with an iron pipe, of unknown origin, 1½ ins. diam., projecting 8 ins. above ground This position is accepted as a careful and faithful determination of the position of the cor.

At the cor. point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

S30
C S S N
1/256
1985

from which

A pinyon, 8 ins. diam., bears S 51° E, 75 lks. dist., mkd. C-S-S-N 1/256 S30 BT.

Bury the local monument alongside the cor.

Set a steel fence post alongside the cor.

Cor. is located 1 lk. E of a N and S chain lk. fence and in an old fence extending E.

N 0°26.5' W, beginning new measurement.

5.065 The center S-N 1/64 sec. cor. of sec. 30, monumented with a rebar, 16 ins. long, 3/8 in. diam., projecting 1 in. above ground. This point was established by Harold Hallett, Civil Engineer No. 4335, and is accepted as a careful and faithful determination of the position of the cor.

At the cor. point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, with brass cap mkd.

S30
C S N
1/64
1985

Bury the local monument alongside the cor.

Cor. is located in a N and S fence.

N 0°24.5' W, beginning new measurement.

Subdivision of Section 30, T 17 N, R 6 E,
Gila and Salt River Mer., Arizona

CHAINS		
10.125	<p>The center N 1/16 sec. cor. of sec. 30, monumented with an iron pipe, 12 ins. long, 1 in. diam., projecting 1 in. above ground. This point was established by Harold Hallett, Civil Engineer No. 4335, AZ, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 26 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T17N R6E C N 1/16 S30 C 1985</p> <p>Bury the local monument alongside the cor.</p> <p>Cor. is located 1 lk. S of a fence cor., fences extend N, E, S and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°17' W, beginning new measurement.</p>	
10.105	<p>The center N-N 1/64 sec. cor. of sec. 30, monumented with a rebar, of unknown origin, ½ in. diam., loosely set. This cor. is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">C N N 1/64 S30 C 1985</p> <p>Bury the local monument alongside the cor.</p> <p>Cor. is located 1 lk. N of a fence cor., fences extend S and W.</p> <p>Cor. is also 33 lks. W of center of Cathedral Road, bears N and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°14.5' W, beginning new measurement.</p>	
10.14	<p>The ¼ sec. cor. of secs. 19 and 30.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the ¼ sec. cor. of secs. 29 and 30.</p> <p>N 89°04.5' W, on the E and W center line of sec. 30.</p> <p>Over rolling land, through medium to dense juniper and pinyon.</p>	
21.62	<p>The center E 1/16 sec. cor. of sec. 30, monumented with an open end iron pipe, of unknown origin, 12 ins. long, 1 in. diam., projecting 8 ins. above ground. This position is accepted as a careful and faithful determination of the position of the cor.</p>	

Subdivision of Section 30, T 17 N, R 6 E,
Gila and Salt River Mer., Arizona

CHAINS

At the cor. point

Set a stainless steel post, 28 ins. long, 2½ ins. diam.,
14 ins. in the ground, and in a mound of stone, 3 ft.
base, to top, with brass cap mkd.

T17N R6E
E 1/16
C ————— C
S30
1985

from which

A juniper, 8 ins. diam., bears N 23° E, 68
lks. dist., mkd. C-E 1/16 S30 BT.

A juniper, 7 ins. diam., bears S 49° W, 32
lks. dist., mkd. C-E 1/16 S30 BT.

Bury the local monument alongside the cor.

Set a steel fence post alongside the cor.

—————
N 89°04.5' W, beginning new measurement.

10.825

Point for the center W-E 1/64 sec. cor. of sec. 30.

Set a stainless steel post, 28 ins. long, 2½ ins. diam.,
22 ins. in the ground, with brass cap mkd.

S30
C W E
1/64
1985

from which

A yew, 12 ins. diam., bears S 20° W, 16 lks.
dist., mkd. C-W-E 1/64 S30 BT.

A pinyon, 8 ins. diam., bears N 72° W,
55 lks. dist., mkd. C-W-E 1/64 S30 BT.

Raise a mound of stone, 2½ ft. base, 1 ft. high, N of
cor.

Set a steel fence post alongside the cor.

Cor. is located 38 lks. S of a wash, 20 lks. wide,
drains N 80° W.

21.65

The center ¼ sec. cor. of sec. 30.

—————
N 89°01.5' W, beginning new measurement.

11.22

The center E-W 1/64 sec. cor. of sec. 30, monumented
with a rebar, 24 ins. long, ½ in. diam., projecting 4
ins. above ground. This point was established by
Harold Hallett, Civil Engineer, No. 4335, and is
accepted as a careful and faithful determination of the
position of the cor.

At the cor. point

Subdivision of Section 30, T 17 N, R 6 E,
Gila and Salt River Mer., Arizona

CHAINS

Set an aluminum post, 72 ins. long, $\frac{3}{4}$ in. diam., flush with the ground, with cap mkd.

S30
C E W
1/64
1985

from which

A juniper, 14 ins. diam., bears S 30° E,
82 lks. dist., mkd. C-E-W 1/64 S30 BT.

A point on the SE cor. of a cattle guard,
made of railroad rails, bears S 79 $\frac{1}{2}$ ° W,
22 lks. dist., mkd. X BO.

Bury local monument alongside the cor.

Set a steel fence post alongside the cor.

Cor. is located 2 lks. S of a powerline, bears E and W.

N 89°07' W, beginning new measurement.

11.21

The center W 1/16 sec. cor. of sec. 30, monumented with a rebar, of unknown origin, 24 ins. long, $\frac{1}{2}$ in. diam., projecting 4 ins. above ground. This position is accepted as a careful and faithful determination of the position of the cor.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T17N R6E
C $\frac{W 1/16}{S30}$ C
1985

from which

A juniper, 16 ins. diam., bears S 37° W,
40 lks. dist., mkd. C W 1/16 S30 BT.

A pinyon, 6 ins. diam., bears N 50° W,
53 lks. dist., mkd. C W 1/16 S30 BT.

Bury local monument alongside the cor.

Set a steel fence post alongside the cor.

Cor. is located at a fence cor., fences extend E and S.
Cor. is also 2 lks. S of a powerline, bears E and W.

N 89°04' W, beginning new measurement.

22.53

The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, on the W bdy. of the Tp.

NE $\frac{1}{4}$ of Section 30

Subdivision of Section 30, T 17 N, R 6 E,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>From the center E 1/16 sec. cor. of sec. 30.</p> <p>N 0°01' W, on the N and S center line of the NE$\frac{1}{4}$ of sec. 30.</p> <p>Over rolling land, through medium pinyon, juniper and oak brush.</p>
10.18	<p>Point for the center S-NE 1/64 sec. cor. of sec. 30; not monumented.</p>
15.27	<p>The center N-S-NE 1/256 sec. cor. of sec. 30, monumented with a rebar, of unknown origin, 14 ins. long, 5/8 in. diam., projecting 1 in. above ground. This position is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S30 C N S NE 1/256 1985</p> <p>from which</p> <p style="padding-left: 40px;">A pinyon, 10 ins. diam., bears N 48° E, 59 lks. dist., mkd. C-N-S-NE 1/256 S30 BT.</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears S 77° W, 40 lks. dist., mkd. C-N-S-NE 1/256 S30 BT.</p> <p>Bury local monument alongside the cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 1 lk. NW of a fence cor., fences extend N and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°09' E, beginning new measurement.</p>
5.085	<p>The NE 1/16 sec. cor. of sec. 30, monumented with a rebar, of unknown origin, 5/8 in. diam., projecting 1 in. above ground. This position is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T17N R6E NE 1/16 S30 1985</p> <p>Raise a mound of stone, 2$\frac{1}{2}$ ft. base, 1$\frac{1}{2}$ ft. high, SE of cor.</p> <p>Bury local monument alongside the cor.</p> <p>Set a steel fence post alongside the cor.</p>

Subdivision of Section 30, T 17 N, R 6 E,
Gila and Salt River Mer., Arizona

CHAINS		
	<p>Cor. is located 1.5 lks. N of a fence cor., fences extend E and S.</p> <hr style="width: 20%; margin: 10px auto;"/>	
	<p>N 0°08' E, beginning new measurement.</p>	
10.185	<p>Point for the center N-NE 1/64 sec. cor. of sec. 30.</p>	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">S30 C N NE 1/64 1985</p>	
	<p>Set a steel fence post alongside the cor.</p>	
	<p>Cor. is located in an E and W fence.</p>	
	<p>From this point, a local survey cor., bears S 88°26' W, 7.3 lks. dist., monumented with a rebar, of unknown origin, ½ in. diam., projecting 1 in. above ground.</p>	
20.37	<p>The E 1/16 sec. cor. of secs. 19 and 30.</p> <hr style="width: 20%; margin: 10px auto;"/>	
	<p>From the N 1/16 sec. cor. of secs. 29 and 30.</p>	
	<p>N 89°24' W, on the E and W center line of the NE¼ of sec. 30.</p>	
	<p>Over rolling land, through medium juniper, pinyon and oak brush.</p>	
10.895	<p>Point for the center E-NE 1/64 sec. cor. of sec. 30.</p>	
	<p>Set an aluminum tablet, 2½ ins. diam., 2½ in. stem, cemented in a drill hole in sandstone bedrock, with top mkd.</p>	
	<p style="text-align: center;">S30 C E NE 1/64 1985</p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">A pinyon, 4 ins. diam., bears N 54° E, 10 lks. dist., mkd. X at breast height and BT at base.</p>	
	<p style="padding-left: 40px;">A juniper, 10 ins. diam., bears S 29° W, 71 lks. dist., mkd. C-E-NE 1/64 S30 BT.</p>	
	<p>Cor. is located 3 lks. E of a fence cor., fences extend N and W.</p>	
21.79	<p>The NE 1/16 sec. cor. of sec. 30.</p> <hr style="width: 20%; margin: 10px auto;"/>	
	<p>N 89°22.5' W, beginning new measurement.</p>	
10.905	<p>Point for the center W-NE 1/64 sec. cor. of sec. 30; not monumented.</p>	
21.81	<p>The center N 1/16 sec. cor. of sec. 30.</p> <hr style="width: 20%; margin: 10px auto;"/>	

Subdivision of Section 30, T 17 N, R 6 E,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>From the center E-NE 1/64 sec. cor. of sec. 30.</p> <p>N 0°19.5' E, on the N and S center line of the NE¹/₄ of the NE¹/₄ of sec. 30.</p> <p>Over rolling land, through medium juniper, pinyon and oak brush.</p>
10.215	<p>Point for the NE-NE 1/64 sec. cor. of sec. 30, at intersection with the E and W center line of the NE¹/₄ of the NE¹/₄ of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 12 ins. in the ground, and in a mound of stone, 3¹/₂ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S30 NE NE 1/64 1985</p> <p>from which</p> <p style="padding-left: 40px;">A point on a sandstone boulder, 4 x 3 x 2 ft., bears N 17° E, 38 lks. dist., mkd. X BO.</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears S 75° E, 40 lks. dist., mkd. NE-NE 1/64 S30 BT.</p>
20.43	<p>The E-E 1/64 sec. cor. of secs. 19 and 30.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the N-N 1/64 sec. cor. of secs. 29 and 30.</p> <p>N 89°34.5' W, on the E and W center line of the NE¹/₄ of the NE¹/₄ of sec. 30.</p> <p>Over rolling land, through medium pinyon, juniper and oak brush.</p>
10.925	<p>The NE-NE 1/64 sec. cor. of sec. 30.</p>
21.855	<p>The center N-NE 1/64 sec. cor. of sec. 30.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center W-E 1/64 sec. cor. of sec. 30.</p> <p>N 0°18' W, on the N and S center line of the SW¹/₄ of the NE¹/₄ of sec. 30.</p> <p>Over nearly level land, through medium pinyon, juniper and oak brush.</p>
5.08	<p>The center S-SW-NE-1/256 sec. cor. of sec. 30, monumented with a rebar, of unknown origin, 12 ins. long, ¹/₂ in. diam., projecting 1 in. above ground. This position is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p>

Subdivision of Section 30, T 17 N, R 6 E,
Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">S30 C S SW NE 1/256 1985</p> <p>from which</p> <p style="text-align: center;">A pinyon, 10 ins. diam., bears S 23° W, 44 lks. dist., mkd. C-S-SW-NE 1/256 S30 BT.</p> <p>Bury the local monument alongside the cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 1 lk. N of a fence cor., fences extend N and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°09' W, beginning new measurement.</p>	
5.08	Point for the SW-NE 1/64 sec. cor. of sec. 30, at inter- section with the E and W center line of the SW $\frac{1}{4}$ of the NE $\frac{1}{4}$ of sec. 30; not monumented.	
10.155	Point for the center N-SW-NE 1/256 sec. cor. of sec. 30. Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.	
	<p style="text-align: center;">S30 C N SW NE 1/256 1985</p> <p>from which</p> <p style="text-align: center;">A juniper, 12 ins. diam., bears S 21° E, 30 lks. dist., mkd. C-N-SW-NE 1/256 S30 BT.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 3 lks. W of a fence cor., fences extend E and S.</p>	
15.23	The point for the center W-NE 1/64 sec. cor. of sec. 30. <hr style="width: 20%; margin: 10px auto;"/> From the point for the center S-NE 1/64 sec. cor. of sec. 30. N 89°14.5' W, on the E and W center line of the SW $\frac{1}{4}$ of the NE $\frac{1}{4}$ of sec. 30.	
10.865	The point for the SW-NE 1/64 sec. cor. of sec. 30.	
21.725	The center S-N 1/64 sec. cor. of sec. 30. <hr style="width: 20%; margin: 10px auto;"/> From the center N-S-NE 1/256 sec. cor. of sec. 30. N 89°18.5' W, on the E and W center line of the NE $\frac{1}{4}$ of the SW $\frac{1}{4}$ of the NE $\frac{1}{4}$ of sec. 30.	
10.88	The center N-SW-NE 1/256 sec. cor. of sec. 30. <hr style="width: 20%; margin: 10px auto;"/>	

Subdivision of Section 30, T 17 N, R 6 E,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>From the center S-SW-NE 1/256 sec. cor. of sec. 30.</p> <p>N 89°10.5' W, on the E and W center line of the SW$\frac{1}{4}$ of the SW$\frac{1}{4}$ of the NE$\frac{1}{4}$ of sec. 30.</p>
10.84	<p>The center S-S-N 1/256 sec. cor. of sec. 30.</p> <hr/>
	<p>From the point for the center W-NE 1/64 sec. cor. of sec. 30.</p> <p>N 0°02' W, on the N and S center line of the NW$\frac{1}{4}$ of the NE$\frac{1}{4}$ of sec. 30.</p>
10.14	<p>Point for the NW-NE 1/64 sec. cor. of sec. 30, at intersection with the E and W center line of the NW$\frac{1}{4}$ of the NE$\frac{1}{4}$ of sec. 30.</p>
	<p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S30 NW-NE 1/64 1985</p>
	<p>Set a steel fence post alongside the cor.</p>
	<p>A fence cor., bears N 70° W, 3 lks. dist., fences extend N and E.</p>
	<p>Cor. is located 45 lks. E of center of Fox Road.</p>
20.30	<p>The W-E 1/64 sec. cor. of secs. 19 and 30.</p> <hr/>
	<p>From the center N-NE 1/64 sec. cor. of sec. 30.</p> <p>N 89°36' W, on the E and W center line of the NW$\frac{1}{4}$ of the NE$\frac{1}{4}$ of sec. 30.</p>
10.935	<p>The NW-NE 1/64 sec. cor. of sec. 30.</p>
21.88	<p>The center N-N 1/64 sec. cor. of sec. 30.</p> <hr/>
	<p style="text-align: center;">SW$\frac{1}{4}$ of Section 30</p> <hr/>
	<p>From the W 1/16 sec. cor. of secs. 30 and 31.</p>
	<p>N 0°23.5' E, on the N and S center line of the SW$\frac{1}{4}$ of sec. 30.</p>
	<p>Over rolling land, through medium pinyon, juniper and manzanita.</p>
20.37	<p>Point for the SW 1/16 sec. cor. of sec. 30, at intersection with the E and W center line of the SW$\frac{1}{4}$ of sec. 30.</p>
	<p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

Subdivision of Section 30, T 17 N, R 6 E,
Gila and Salt River Mer., Arizona

CHAINS

T17N R6E
SW 1/16 S30
1985

from which

A juniper, 6 ins. diam., bears S 28° E,
18 lks. dist., mkd. SW 1/16 S30 BT.

A pinyon, 4 ins. diam., bears S 33° W, 26
lks. dist., mkd. X at breast height and
BT at base.

Set a steel fence post alongside the cor.

35.645

The center N-N-SW 1/256 sec. cor. of sec. 30, monumented
with a rebar, 16 ins. long, 1/2 in. diam., projecting 3
ins. above ground, with plastic cap attached and mkd.
MKJ LS 4491. Copy of survey plat is located at the
office of Joseph Jones and Asso., Cottonwood, AZ. This
position is accepted as a careful and faithful deter-
mination of the position of the cor.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
20 ins. in the ground, with brass cap mkd.

S30
C N N SW
1/256
1985

from which

A pinyon, 8 ins. diam., bears S 17° W, 52
lks. dist., mkd. C N N SW 1/256 S30 BT.

A pinyon, 8 ins. diam., bears N 73° W, 84
lks. dist., mkd. C N N SW 1/256 S30 BT.

Bury local monument alongside the cor.

Set a steel fence post alongside the cor.

Cor. is located 1 lk. SW of a fence cor., fences extend
N and E.

N 0°26' E, beginning new measurement.

5.085

The center W 1/16 sec. cor. of sec. 30.

From the center S 1/16 sec. cor. of sec. 30.

N 89°28' W, on the E and W center line of the SW 1/4 of
sec. 30.

Over rolling land, through medium juniper and pinyon.

22.71

The SW 1/16 sec. cor. of sec. 30.

45.55

The S 1/16 sec. cor. of secs. 25 and 30, on the W bdy,
of the Tp.

Subdivision of Section 30, T 17 N, R 6 E,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>From the center E-W 1/64 sec. cor. of sec. 30.</p> <p>S 0°03' W, on the N$\frac{1}{2}$ of the N$\frac{1}{2}$ of the N and S center line of the NE$\frac{1}{4}$ of the SW$\frac{1}{4}$ of sec. 30.</p> <p>5.07 The center N-NE-SW 1/256 sec. cor. of sec. 30, monumented with a rebar, 24 ins. long, $\frac{1}{2}$ in. diam., projecting 6 ins. above ground. This point was established by Harold Hallett, Civil Engineer No. 4335, AZ, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S30 C N NE SW 1/256 1985</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears N 38$\frac{1}{2}$° E, 56 lks. dist., mkd. C-N-NE-SW 1/256 S30 BT.</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears S 53$\frac{1}{2}$° E, 10 lks. dist., mkd. C-N-NE-SW 1/256 S30 BT.</p> <p>Bury local monument alongside the cor.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 89°13' W, on the E and W center line of the NW$\frac{1}{4}$ of the NE$\frac{1}{4}$ of the SW$\frac{1}{4}$ of sec. 30.</p>
<p>11.245</p>	<p>The center N-N-SW 1/256 sec. cor. of sec. 30.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>Section 5 of this survey is located at the NE edge of Sedona, Arizona. Section 30 is located about 3 miles south of Sedona, Arizona. The elevation ranges from about 4,200 to 5,300 feet above sea level.</p> <p>There are two trailer houses, a metal storage shed and part of an unfinished house located in lot 5, section 5, and a carport is located in lot 10, section 30, which lots are U.S. National Forest Lands.</p> <p>The land varies from gently rolling to high rolling ridges, higher sandstone and limestone buttes, cliffs and pinnacles. The U.S. Forest Service land is covered with medium to dense timber and undergrowth. Oak Creek flows through the southeastern portion of section 5 in a southwesterly direction.</p> <p>Access is by way of Highways 89A and 179. There are numerous other paved and gravel roads in the area.</p> <p>The mean magnetic declination is 14° E.</p> <hr/>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Delbert L. Bybee	Surveying Technician
Ronald D. Williams	Survey Aid
Tracy J. Eaves	Survey Aid

CERTIFICATE OF SURVEY

I, Paul L. Reeves, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 20th day of September, 1984, and supplemental special instructions dated November 23, 1984, I have dependently resurveyed a portion of the north and west boundaries and the subdivisional lines and surveyed subdivisions in sections 5 and 30, Township 17 North, Range 6 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

SEP 20 1985

(Date)

Paul L. Reeves
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

Arizona State Office
Bureau of Land Management
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the north and west boundaries and the subdivisional lines and surveyed subdivisions in sections 5 and 30, Township 17 North, Range 6 East, Gila and Salt River Meridian, Arizona, executed by Paul L. Reeves, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

SEP 23 1985

(Date)

James P. Kelley
(Chief Cadastral Surveyor of Arizona)