

ORIGINAL  
BOOK 5225  
1

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A PORTION OF THE SUBDIVISIONAL LINES

AND

SURVEY OF TRACT NOS. 37 THROUGH 42

IN

TOWNSHIP 4 SOUTH, RANGE 3 EAST

Of the Gila and Salt River Meridian,  
In the State of Arizona

EXECUTED BY

Paul L. Reeves, Cadastral Surveyor

Stephen J. Malloy, Cadastral Surveyor

Under special instructions dated March 18, 1985, approved March 18, 1985

and supplemental special instructions dated and approved July 18, 1985

, which provided for the surveys included under Group Number

663 and assignment instructions dated March 18 and May 13, 1985.

Survey commenced April 24, 1985

Survey completed August 19, 1985

INDEX DIAGRAM

TOWNSHIP 4 SOUTH, RANGE 3 EAST,

6	5	4	3	2	1
7	8	9	10	11	12
23	21	19	17	14	12
11	9	8	6	5	3
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

T 4 S, R 3 E, Gila and Salt River Mer., Arizona

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and the survey of Tract Nos. 37 through 42, Township 4 South, Range 3 East, Gila and Salt River Meridian, Arizona.

The purpose of this survey is to determine the true position of the south boundary of the Gila River Indian Reservation along the north boundary of sections 13, 14, 15, 16, 17 and 18, as originally established by George P. Ingalls, in 1868, as shown on the plat approved April 16, 1869.

The exterior boundaries and subdivisional lines were surveyed by G.P. and W.F. Ingalls, in 1868. Portions of the north, east and west boundaries were independently resurveyed and the erroneous south boundary of the Gila River Indian Reservation was independently resurveyed by Guy P. Harrington and Robert A. Farmer, in 1910-12. The sections north of the erroneous Gila River Indian Reservation were independently resurveyed and subdivided by Robert A. Farmer, in 1911. The south boundary, a portion of the west boundary and portions of the subdivisional lines were dependently resurveyed and certain sections were subdivided by Roger F. Wilson, in 1936.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated March 18, 1985, and the Supplemental Instructions dated July 18, 1985, for Group No. 663, Arizona.

Preliminary to the resurvey, the necessary lines of the original 1868 survey and the 1910-12 independent resurvey and the 1936 survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions or the evidence was buried in place; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The direction of all lines was determined by altitude observations on the sun and refers to the true meridian. Distances and angles were measured with a Zeiss Total Station instrument.

The geographic position of the southeast corner of section 12, as determined from a tie made to U.S.C.&G.S. triangulation station "ENID 1936", located in the NW $\frac{1}{4}$  of section 18, T. 4 S., R. 2 E., is as follows:

Latitude: 33°05'16.43" N Longitude: 111°59'43.76" W

The mean magnetic declination is 14° E.

---

Dependent Resurvey of the True South Boundary of the  
Gila River Indian Reservation  
T 4 S, R 3 E, Gila and Salt River Mer., Arizona

---

Reestablishment of the survey executed by  
G.P. and W.F. Ingalls, U.S. Deputy Surveyors, in 1868

---

Dependent Resurvey of the True S Bdy. of the GRIR,  
T 4 S, R 3 E, Gila and Salt River Mer., Arizona

CHAINS

Beginning at the cor. of secs. 13 and 18, Tps. 4 S, Rs. 3 and 4 E, and AP 1, Tract 42, originally established by Ingalls in 1868, as the cor. of secs. 7, 12, 13 and 18, Tps. 4 S., Rs. 3 and 4 E, as heretofore described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T 4 S, R 4 E, surveyed concurrently under this same group.

From this point the U.S.C. & G.S. triangulation station "ENID, 1936", bears S 89°27'39" W, 484.06 chs. dist., marked with a drill hole in rock outcropping. Point was verified by ties to reference monuments.

S 89°47' W, bet. sec. 13 and Tract 42.

Desc. over nearly level ground, through cultivated fields.

40.24

Point for the 1/4 sec. cor. of sec. 13 only, originally established by Ingalls in 1868 as the 1/4 sec. cor. of secs. 12 and 13, at proportionate dist.; there is no evidence of the original cor. This cor. now also stands for AP 7, Tract 42, T 4 S, R 3 E.

Set an aluminum post, 36 ins. long, 3 ins. diam., 64 ins. in the ground, with cap; and directly atop, set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap; both caps mkd.

T4S R3E  
TR 42 AP 7  
GRIR  
1/4 S13  
1985

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Set a fiberglass marker alongside the cor.

Cor. is located 39 lks. S of a dirt road, 25 lks. wide, bears E and W, and on the N edge of a cultivated field.

79.70

Graded, gravel road, 25 lks. wide, bears N and S.

80.48

Point for the cor. of secs. 13 and 14 only, originally established by Ingalls in 1868 as the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no evidence of the original cor. This cor. now also stands for AP 8, Tract 41 and AP 6, Tract 42, T 4 S, R 3 E.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T4S R3E  
GRIR  
TR41 / TR42  
AP8 / AP6  
S14 | S13  
1985

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Set a fiberglass marker alongside the cor.


Dependent Resurvey of the True S Bdy. of the GRIR,  
T 4 S, R 3 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>From this point, the cor. of secs. 13, 14, 23 and 24, originally established by Ingalls in 1868, perpetuated by Sheldon K. Baker, Civil Engineer, in 1923, and further accepted by the County Highway Department, as recorded in book 4-3B, and further utilized by U.S. Department of the Interior, Bureau of Reclamation, in 1946 and 1985, bears S 0°10' E, 80.78 chs. dist., monumented with the remains of an iron post, 1 in. diam., firmly set, 8 ins. below the surface; this cor. is accepted as a careful and faithful perpetuation of the original cor.</p> <p>From this same point, the ¼ sec. cor. of secs. 11 and 12, originally established by Ingalls in 1868, and superseded by R.A. Farmer in 1910-12, bears N 0°19' E, 40.39 chs. dist., monumented with a hewn mesquite post, 4 ins. long, 2 ins. sq., with axe marks on end and side; I buried the hewn post in place 6 ins. below the ground; from which the N 1/16 sec. cor. of secs. 11 and 12, established by R.A. Farmer in 1910-12, bears N 5°48' E, 23.57 chs. dist., hereinafter described.</p> <p>The control lines were fully retraced and no evidence of the intervening cors. was found.</p>	
	<p>S 86°34' W, bet. sec. 14 and Tract 41.</p> <p>Desc. over nearly level land, through cultivated fields.</p>	
40.08	<p>Point for the ¼ sec. cor. of sec. 14 only, originally established by Ingalls in 1868 as the ¼ sec. cor. of secs. 11 and 14, at proportionate dist.; there is no evidence of the original cor. This cor. now also stands for AP 7, Tract 41, T 4 S, R 3 E.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T4S R3E TR41 AP7 GRIR — ¼ S14 1985</p>	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a fiberglass marker alongside the cor.</p>	
	<p>This cor. is located West, 5 lks. dist. from an irrigation canal, 9 lks. wide, extending N and S. In the course of setting this cor., I found fragments of Indian pottery along the canal around the cor. location. The original notes called for this cor. to be in a deserted Indian Village.</p>	
79.80	<p>Dirt road, 30 lks. wide, bears N and S.</p>	
80.16	<p>Point for the cor. of secs. 14 and 15 only, originally established by Ingalls in 1868 as the cor. of secs. 10, 11, 14 and 15, at proportionate dist.; there is no evidence of the original cor. This cor. now also stands for AP 8, Tract 40, and AP 6, Tract 41, T 4 S, R 3 E.</p>	

Dependent Resurvey of the True S Bdy. of the GRIR,  
T 4 S, R 3 E, Gila and Salt River Mer., Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2½ ins. diam.,  
26 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored  
plastic case beneath the stainless steel post.

Set a fiberglass marker alongside the cor.

From this point, the original cor. of secs. 2, 3, 34  
and 35, Tps. 4 and 5 S, R 3 E, perpetuated by Lynn Ames  
Winkler, Jr., Registered Land Surveyor, No. 11898, AZ,  
bears S 0°02' E, 319.47 chs. dist., monumented with a  
steel rebar, ½ in. diam., 3 ins. below the ground, with  
tag mkd. 11898, from which bearing objects mkd. by  
Wilson, in 1936.

A power pole, bears N 59° E, 77 lks. dist.,  
lines extend E and W. (Record: N 57½° E)

A power pole, bears N 84° W, 398 lks. dist.,  
lines extend E and W. (Record: 395 lks. dist.)

A well head, bears N 60° W, 375 lks. dist.  
(Record: N 64½° W, 379 lks. dist.)

From this same point, the ¼ sec. cor. of secs. 2 and 3,  
originally established by Ingalls in 1868 and  
superseded by R.A. Farmer in 1910-12, bears N 0°19' W,  
119.79 chs. dist., monumented with a hewn mesquite  
post, 24 ins. long, 2½ ins. sq., lying loose on ground,  
no marks visible. I buried the post in place, 6 ins.  
below the ground, from which the cor. of secs. 2, 3, 10  
and 11, established by R.A. Farmer in 1910-12, bears  
S 6°01' E, 31.17 chs. dist., hereinafter described.

The control lines were fully retraced and no evidence  
of the intervening cors. was found.

---

N 88°21' W, bet. sec. 15 and Tract 40.

Continue over nearly level land, through cultivated  
fields.

1.50 Flood control canal, 175 lks. wide, 15 ft. deep, bears  
N and S.

28.20 Maricopa Road, asphalt surfaced, bears N 26° E and  
S 26° W.

40.39 Point for the ¼ sec. cor. of sec. 15 only, originally  
established by Ingalls in 1868 as the ¼ sec. cor. of  
secs. 10 and 15, at proportionate dist.; there is no  
evidence of the original cor. This cor. now also  
stands for AP 7, Tract 40, T 4 S, R 3 E.

Dependent Resurvey of the True S Bdy. of the GRIR,  
T 4 S, R 3 E, Gila and Salt River Mer., Arizona

CHAINS

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 64 ins. in the ground, with cap; and directly atop, set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap; both caps mkd.

T4S R3E  
GRIR  
AP7 TR40  
      
 $\frac{1}{4}$  S15  
1985

Deposit a magnet in a 1 x 1 x  $2\frac{5}{8}$  in. white colored plastic case beneath the stainless steel post.

Set a fiberglass marker alongside the cor.

The cor. is located in a cultivated field.

80.78

Point for the cor. of secs. 15 and 16 only, originally established by Ingalls in 1868 as the cor. of secs. 9, 10, 15 and 16, at proportionate dist.; there is no remaining evidence of the original cor. This cor. now also stands for AP 8, Tract 39 and AP 6, Tract 40, T 4 S, R 3 E.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 64 ins. in the ground, with cap; and directly atop, set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap; both caps mkd.

T4S R3E  
GRIR  
AP8 / AP6  
TR39 / TR40  
      
S16 | S15  
1985

Deposit a magnet in a 1 x 1 x  $2\frac{5}{8}$  in. white colored plastic case beneath the stainless steel post.

Set a fiberglass marker alongside the cor.

The cor. is located in a cultivated field.

From this point, the cor. of secs. 21, 22, 27 and 28, originally established by Ingalls in 1868 and perpetuated by Wilson in 1936, bears S  $0^{\circ}09'$  E, 162.25 chs. dist., monumented with a cement column, 4 ins. sq., 4 ins. below the surface of the ground, in a surveyors well. The cor. is located in the road intersection, asphalt surfaced, bears N, S and E.

From this same cor., the point for the cor. of secs. 3, 4, 33 and 34, Tps. 3 and 4 S, R 3 E, originally established by Ingalls in 1868 and superseded by R.A. Farmer in 1910-12, bears N  $0^{\circ}30'$  W, 162.86 chs. dist. This point was determined at proportionate dist.; there is no remaining evidence of the original cor. position. No permanent monument was established.

From the point for the 1868 cor. of secs. 3, 4, 33 and 34, Tps. 3 and 4 S, R 3 E, the cor. of Tps. 3 and 4 S, Rs. 2 and 3 E, originally established by Ingalls in

Dependent Resurvey of the True S Bdy. of the GRIR,  
T 4 S, R 3 E, Gila and Salt River Mer., Arizona

CHAINS

1868 and superseded by R.A. Farmer in 1910-12, bears S 88°57' W, 243.38 chs. dist., monumented with the remains of a hewn post and post hole, 3 ins. sq., no marks visible on fragmentary piece, from which an iron post set by Farmer in 1910-12

An iron post, 3 ins. diam., firmly set, projecting 8 ins. above ground, bears N 43°22' E 11.32 chs., dist., with brass cap mkd. T3S T4S R2E R3E S1 S6 S31 S36 BM 1118 1119 and a cross in the center.

Also from the point for the 1868 cor. of secs. 3, 4, 33 and 34, Tps. 3 and 4 S, R 3 E, the ¼ sec. cor. of secs. 1 and 36, Tps. 3 and 4 S, R 3 E, originally established by Ingalls in 1868 and superseded by R.A. Farmer in 1910-12, bears N 88°57' E, 200.97 chs. dist., monumented with the remains of a hewn post, 18 ins. long, 2 ins. sq., lying loose on top of ground, with axe marks on edge, which I buried in place, from which an Indian allotment monument

An iron post, 2 ins. diam., firmly set, projecting 16 ins. above ground, bears S 72°42' E, 3.01 chs., dist., with brass cap mkd. INDIAN ALLOTMENT ¼ S36 S1 REF 50 FT.

The control lines were fully retraced and no evidence of the intervening cors. was found.

S 88°49' W, bet. sec. 16 and Tract 39.

Continue over rolling land, through irrigated fields.

40.03

Point for the ¼ sec. cor. of sec. 16 only, originally established by Ingalls in 1868 as the ¼ sec. cor. of secs. 9 and 16, at proportionate dist.; there is no evidence of the original cor. This cor. now also stands for AP 7, Tract 39, T 4 S, R 3 E.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T4S R3E  
GRIR  
AP7 TR39  
¼ S16  
1985

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Set a fiberglass marker alongside the cor.

From this cor., a point established by Pinal County Engineer, bears S 7°55' E, 1.64 chs. dist., monumented with an open end pipe, 1½ ins. diam., firmly set, projecting 12 ins. above ground. This monument was set using improper controls and is not utilized in the course of this survey.

Continue over rolling land, along south edge of Maricopa Sanitary Land Fill.




Dependent Resurvey of the True S Bdy. of the GRIR,  
T 4 S, R 3 E, Gila and Salt River Mer., Arizona

CHAINS

54.10 Leave Maricopa Sanitary Land Fill.

80.06 Point for the cor. of secs. 16 and 17 only, originally established by Ingalls in 1868 as the cor. of secs. 8, 9, 16 and 17, at proportionate dist.; there is no evidence of the original cor. This cor. now also stands for AP 8, Tract 38 and AP 6, Tract 39, T 4 S, R 3 E.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 64 ins. in the ground, with a cap; and directly atop, set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap; both caps mkd.




Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Set a fiberglass marker alongside the cor.

The cor. is located on the E edge of a cultivated field, edge bears N and S.

From this point, the cor. of secs. 16, 17, 20 and 21, originally established by Ingalls in 1868 and perpetuated by Wilson in 1936, bears S 0°35' W, 81.34 chs. dist., monumented with an iron post, . 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.



From this same cor., the point for the cor. of secs. 4, 5, 32 and 33, Tps. 3 and 4 S, R 3 E, originally established by Ingalls in 1868 and superseded by R.A. Farmer in 1910-12, bears N 0°14' W, 163.05 chs. dist. This point was determined at proportionate dist.; there is no remaining evidence of the original cor. position. No permanent monument established.

From the point for the 1868 cor. of secs. 4, 5, 32 and 33, Tps. 3 and 4 S, R 3 E, the 1868 cor. of Tps. 3 and 4 S, Rs. 2 and 3 E, bears S 88°57' W, 162.99 chs. dist., hereinbefore described.

From the point for the 1868 cor. of secs. 4, 5, 32 and 33, Tps. 3 and 4 S, R 3 E, the 1868  $\frac{1}{4}$  sec. cor. of secs. 1 and 36, Tps. 3 and 4 S, R 3 E, bears N 88°57' E, 281.36 chs. dist., hereinbefore described.

The control lines were fully retraced and no evidence of the intervening cors. was found.

S 89°52' W, bet. sec. 17 and Tract 38.

Continue over rolling land, through irrigated fields.

Dependent Resurvey of the True S Bdy. of the GRIR,  
T 4 S, R 3 E, Gila and Salt River Mer., Arizona

CHAINS

40.29

Point for  $\frac{1}{4}$  sec. cor. of sec. 17 only, originally established by Ingalls in 1868 as the  $\frac{1}{4}$  sec. cor. of secs. 8 and 17, at proportionate dist.; there is no evidence of the original cor. This cor. now also stands for AP 7, Tract 38, T 4 S, R 3 E.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 64 ins. in the ground, with cap; and directly atop, set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap; both caps mkd.

T4S R3E  
GRIR  
AP7 TR38  
            
 $\frac{1}{4}$  S17  
1985

Deposit a magnet in a 1 x 1 x 2  $\frac{5}{8}$  in. white colored plastic case beneath the stainless steel post.

Set a fiberglass marker alongside the cor.

Continue over rolling land, through irrigated fields.

80.58

Point for the cor. of secs. 17 and 18, only, originally established by Ingalls in 1868 and perpetuated by Wilson in 1936 as the cor. of secs. 7, 8, 17 and 18, at proportionate dist.; there is no evidence of the original cor. This cor. now also stands for AP 8, Tract 37 and AP 6, Tract 38, T 4 S, R 3 E.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 64 ins. in the ground, with cap; and directly atop, set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap; both caps mkd.

T4S R3E  
GRIR  
AP8 / AP6  
TR37 / TR38  
        
S18 | S17  
1985

Deposit a magnet in a 1 x 1 x 2  $\frac{5}{8}$  in. white colored plastic case beneath the stainless steel post.

Set a fiberglass marker alongside the cor.

From this point, the 1936 S  $\frac{1}{16}$  sec. cor. of secs. 17 and 18, bears S  $0^{\circ}14'$  W, 60.20 chs. dist., monumented with an iron post, 1 in. diam., firmly set, flush in the the ground, with brass cap mkd.

S  $\frac{1}{16}$   
S18 | S17  
MIR |  
1936

This cor. is located in a fence cor.; fences extend S and E.

From this same cor., the  $\frac{1}{4}$  sec. cor. of secs. 7 and 8, originally established by Ingalls in 1868 and superseded by R.A. Farmer in 1910-12, bears N  $0^{\circ}48'$  E, 40.13 chs. dist., monumented with the remains of an original hewn post, 12 ins. long, 3 ins. sq., projecting 3 ins. above ground, no marks visible;

Dependent Resurvey of the True S Bdy. of the GRIR,  
T 4 S, R 3 E, Gila and Salt River Mer., Arizona

CHAINS

buried the original post in place 6 ins. below the surface of the ground. From which the cor. of secs. 7 and 8 only, established by R.A. Farmer in 1910-12, bears S 5°47' E, 35.39 chs. dist., hereinafter described.

The control lines were fully retraced and no evidence of the intervening cors. was found.

N 89°57' W, bet. sec. 18 and Tract 37.

Continue over rolling land, through irrigated fields.

40.20

Point for the ¼ sec. cor. of sec. 18 only, originally established by Ingalls in 1868 and reestablished by Wilson in 1936, as the ¼ sec. cor. of secs. 7 and 18, at proportionate dist.; there is no evidence of the original cor. This cor. now also stands for AP 7, Tract 37, T 4 S, R 3 E.

Set an aluminum post, 36 ins. long, ¾ in. diam., 64 ins. in the ground, with cap; and directly atop, set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap; both caps mkd.

T4S R3E  
GRIR  
AP7 TR37  
¼ S18  
1985

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Set a fiberglass marker alongside the cor.

Continue over rolling land, through irrigated fields.

60.30

Leave irrigated field, enter desert edge, bears N and S.

82.17

The cor. of secs. 13 and 18, only, originally established by Ingalls in 1868 and reestablished by Wilson in 1936 as the cor. of secs. 7, 12, 13 and 18, Tps. 4 S, Rs. 2 and 3 E, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

T4S  
R2E | R3E  
S12 | S 7  
S13 | S18  
1936

I remarked the brass cap to read

GRIR  
AP8 / AP6  
TR42 / TR37  
S13 | S18  
R2E | R3E  
T4S  
1985  
1936

Dependent Resurvey of the True S Bdy. of the GRIR,  
T 4 S, R 3 E, Gila and Salt River Mer., Arizona

CHAINS	<p>This cor. now also stands for AP 6, Tract 37, T 4 S, R 3 E, and AP 8, Tract 42, T 4 S, R 2 E.</p> <p>Set a fiberglass marker alongside the cor.</p> <hr/> <p>Dependent Resurvey of the Erroneous S Bdy. of the GRIR T 4 S, R 3 E, Gila and Salt River Mer., Arizona.</p> <hr/> <p style="text-align: center;">Reestablishment of the survey executed by Robert A. Farmer, Topographer, and Guy P. Harrington, Cadastral Engineer, in 1910-12</p> <hr/> <p>From the cor. of secs. 7 and 12, only, Tps. 4 S, Rs. 3 and 4 E, established by R.A. Farmer in 1910-12 heretofore described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T 4 S, R 4 E, surveyed concurrently under this same group.</p> <p>N 89°32' W, bet. sec. 12, T 4 S, R 3 E, and sec. 18, T 4 S, R 4 E.</p> <p>Desc. over W slope, through rolling, broken land.</p> <p>1.30 Power line, extends N and S.</p> <p>2.20 The cor. of secs. 13 and 18, only, Tps. 4 S, Rs. 3 and 4 E, and also AP 1, Tract 42, heretofore described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T 4 S, R 4 E, surveyed concurrently under this same group.</p> <hr/> <p>West, beginning new measurement. between sec. 12 and Tract 42.</p> <p>Continue over rolling land, along S edge of a dirt road, 25 lks. wide, bears N 89° W, and E.</p> <p>17.80 Point for the E 1/16 sec. cor. of sec. 12 only, established by R.A. Farmer in 1910-12, at proportionate dist.; there is no evidence of the cor. This cor. now also stands for AP 2, Tract 42, T 4 S, R 3 E.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R3E GRIR <u>E 1/16 S12</u> GRIR TR42 AP2 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>This cor. is located on S edge of dirt road, 25 lks. wide, bears E and W.</p> <p>Continue over rolling land, along E edge of dirt road.</p>
--------	---

Dependent Resurvey of the Erroneous S Bdy. of the GRIR  
T 4 S, R 3 E, Gila and Salt River Mer., Arizona

CHAINS		
37.80	<p>The <math>\frac{1}{4}</math> sec. cor. of sec. 12 only, established by R.A. Farmer in 1910-12, monumented with the remains of an iron post, filled with cement, 1 in. diam., firmly set 8 ins. below the surface of the ground. This cor. now also stands for AP 3, Tract 42, T 4 S, R 3 E.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R3E GRIR <u><math>\frac{1}{4}</math> S12</u> GRIR TR42 AP3 1985</p> <p>Deposit the remains of the iron post beneath the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x <math>2\frac{5}{8}</math> in. white colored plastic case beneath the stainless steel post.</p> <p>Set a fiberglass marker alongside the cor.</p> <p>This cor. is located on the S edge of a dirt road, 25 lks. wide, bears E and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N <math>89^{\circ}53'</math> W, beginning new measurement.</p> <p>Continue over rolling land, along the S edge of a dirt road, 25 lks. wide, bears E and W.</p>	
20.02	<p>The W <math>\frac{1}{16}</math> sec. cor. of sec. 12 only, established by R.A. Farmer in 1910-12, monumented with the remains of an iron post, 1 in. diam., filled with cement, firmly set 12 ins. below the ground. This cor. now also stands for AP 4, Tract 42, T 4 S, R 3 E.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R3E GRIR <u>W <math>\frac{1}{16}</math> S12</u> GRIR TR42 AP4 1985</p> <p>Deposit the remains of the iron post beneath the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x <math>2\frac{5}{8}</math> in. white colored plastic case beneath the stainless steel post.</p> <p>Set a fiberglass marker alongside the cor.</p> <p>The cor. is located on S edge of a dirt road, 25 lks. wide, bears E and S.</p> <hr style="width: 20%; margin: 10px auto;"/>	

Dependent Resurvey of the Erroneous S Bdy. of the GRIR  
T 4 S, R 3 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>N 89°55' W, beginning new measurement.</p> <p>Continue over rolling land, along S edge of a dirt road, 25 lks. wide, bears E and W.</p> <p>20.01 Point for the cor. of secs. 11 and 12 only, established by R.A. Farmer in 1910-12, at proportionate dist.; using a three way proportion there is no evidence of the cor. This cor. now also stands for AP 1, Tract 41 and AP 5, Tract 42, T 4 S, R 3 E.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T4S R3E GRIR S11   S12 TR 41   TR 42 AP 1   AP 5 1985</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a fiberglass marker alongside the cor.</p> <p>This cor. is located on the S edge of a dirt road, 25 lks. wide, bears N, E and W.</p> <p>From this point, the N 1/16 sec. cor. of secs. 11 and 12, established by R.A. Farmer in 1910-12, bears N 0°02'W, 63.50 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>N   12 1/16   S11   S12 1911</p> </div> <p>This control line was fully retraced and no evidence of the intervening cors. was found.</p> <p>From this same point, an open end pipe, of unknown origin, 12 ins. long, ½ in. diam., projecting 1 in. above ground, bears S 34°36' W, 0.19 chs. dist.</p> <p>Also from this same point, the cor. of secs. 13 and 14 only, and also AP 8, Tract 41 and AP 6, Tract 42, bears S 81°53' W, 2.67 chs. dist., hereinbefore described.</p> <hr/> <p>N 89°56' W, bet. sec. 11 and Tract 41.</p> <p>Continue over rolling land, along S edge of dirt road, 25 lks. wide, bears E and curving S.</p> <p>2.20 Dirt road, 25 lks. wide, bears NE and S, continue along old fence, extending W.</p> <p>20.00 The E 1/16 sec. cor. of sec. 11 only, established by R.A. Farmer in 1910-12, monumented with the remains of an iron post, 1 in. diam., filled with cement, firmly set, 6 ins. below the ground. This cor. now also stands for AP 2, Tract 41, T 4 S, R 3 E.</p>	

Dependent Resurvey of the Erroneous S Bdy. of the GRIR  
T 4 S, R 3 E, Gila and Salt River Mer., Arizona

CHAINS

At the cor. point

Set a stainless steel post, 28 ins. long, 2½ ins. diam.,  
27 ins. in the ground, with brass cap mkd.

T4S R3E  
GRIR  
E 1/16 S11  
GRIR  
TR41 AP2  
1985

Deposit the remains of the iron post beneath the  
stainless steel post.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored  
plastic case beneath the stainless steel post.

Set a fiberglass marker alongside the cor.

The cor. is located under old fence, extends E and W.

---

N 89°57' W, beginning new measurement.

Continue over rolling land, along old fence, extends E  
and W.

20.00

The ¼ sec. cor. of sec. 11 only, established by R.A.  
Farmer in 1910-12, and which now also stands for AP 3,  
Tract 41, T 4 S, R 3 E, monumented with an iron post, 1  
in. diam., projecting 6 ins. above ground, with brass  
cap mkd.

GRIR  
¼ S11  
1911

Add marks to brass cap to read

GRIR  
¼ S11  
TR41 AP3  
1985  
1911

Set a fiberglass marker alongside the cor.

This cor. is located under an old fence, extending E  
and W.

---

N 89°45' W, beginning new measurement.

Continue over rolling land, along an old fence,  
extending E and W.

19.875

The W 1/16 sec. cor. of sec. 11 only, established by  
R.A. Farmer in 1910-12, and which now also stands for  
AP 4, Tract 41, T 4 S, R 3 E, monumented with an iron  
post, 1 in. diam., projecting 6 ins. above ground, with  
brass cap mkd.

Dependent Resurvey of the Erroneous S Bdy. of the GRIR  
T 4 S, R 3 E, Gila and Salt River Mer., Arizona

CHAINS

GRIR  
1/16 N 2 S11  
1911

Add marks to cap to read

GRIR  
W 1/16 N 2 S11  
GRIR  
TR41 AP4  
1985  
1911

Set a fiberglass marker alongside the cor.

S 89°36' W, beginning new measurement.

Continue over rolling land, along the N edge of a dirt road, 15 lks. wide, bears E and W.

20.02 Point for the cor. of secs. 10 and 11 only, established by R.A. Farmer in 1910-12, at proportionate dist.; using a three way proportion; there is no evidence of the cor. This cor. now also stands for AP 1, Tract 40 and AP 5, Tract 41, T 4 S, R 3 E.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T4S R3E  
GRIR  
S10 | S11  
AP1 / AP5  
TR40 / TR41  
GRIR  
1985

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Set a fiberglass marker alongside the cor.

The cor. is located on the E side of a flood control canal.

From this point, the cor. of secs. 14 and 15 only, and also AP 8, Tract 40 and AP 6, Tract 41, bears S 28°12' W, 5.85 chs. dist., hereinbefore described.

From this same point, the cor. of secs. 2, 3, 10 and 11, established by R.A. Farmer in 1910-12, bears N 0°06' W, 83.60 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

S 3 | S 2  
| R3E  
T4S |  
S10 | S11  
1911

This control line was fully retraced and no evidence of the intervening cors. was found.



Dependent Resurvey of the Erroneous S Bdy. of the GRIR  
T 4 S, R 3 E, Gila and Salt River Mer., Arizona

CHAINS	
	N 89°51' W, bet. sec. 10 and Tract 40.
	Continue over rolling land.
1.10	Canal, 115 ft. wide, 15 ft. deep, extends N and S.
20.02	The E 1/16 sec. cor. of sec. 10 only, established by R.A. Farmer in 1910-12, and which now also stands for AP 2, Tract 40, T 4 S, R 3 E., monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.
	GRIR <u>1/16 N 1 S10</u> 1911
	Add marks to cap to read
	GRIR <u>E 1/16 N 1 S10</u> AP2 TR40 GRIR 1985 1911
	Set a fiberglass marker alongside the cor.
	S 89°59' W, beginning new measurement.
	Continue over rolling land, along the N edge of a dirt road, 15 lks. wide, bears E and W.
8.30	Maricopa Road, 50 lks wide, bears N 26° E and S 26° W.
20.00	The 1/4 sec. cor. of sec. 10 only, established by R.A. Farmer in 1910-12, and which now also stands for AP 3, Tract 40, T 4 S, R 3 E, monumented with the remains of an iron post, 1 in. diam., filled with cement, firmly set 6 ins. below the ground.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T4S R3E GRIR <u>1/4 S10</u> AP3 TR40 GRIR 1985
	Deposit the remains of the iron post beneath the stainless steel post.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Set a fiberglass marker alongside the cor.
	This cor. is located on the N side of a dirt road, 25 lks. wide, bears E and W.

Dependent Resurvey of the Erroneous S Bdy. of the GRIR  
T 4 S, R 3 E, Gila and Salt River Mer., Arizona

CHAINS		
20.00	<p>N 89°59' W, beginning new measurement.</p> <p>The W 1/16 sec. cor. of sec. 10 only, established by R.A. Farmer in 1910-12, and which now also stands for AP 4, Tract 40, T 4 S, R 3 E, monumented with the remains of an iron post, 1 in. diam., filled with cement, firmly set 6 ins. below the surface.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R3E GRIR <u>W 1/16 S10</u> AP4 TR40 GRIR 1985</p> <p>Deposit the remains of the iron post beneath the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a fiberglass marker alongside the cor.</p> <p>The cor. is located on the N side of a dirt road, 25 lks. wide, bears E and W.</p>	
20.00	<p>West, beginning new measurement.</p> <p>The cor. of secs. 9 and 10 only, established by R.A. Farmer in 1910-12, and which now also stands for AP 5, Tract 40, T 4 S, R 3 E, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">GRIR S 9   S 10 <u>T4S   R3E</u> 1911</p> <p>Add marks to brass cap to now read</p> <p style="text-align: center;">GRIR S 9   S10 T4S   R3E <u>AP1 / AP5</u> TR39 / TR40 1985 1911</p> <p>Set a fiberglass marker alongside the cor.</p> <p>This cor. is located at the end of an old fence, extending westerly.</p> <p>From this point, the cor. of secs. 15 and 16 only, and also AP 8, Tract 39 and AP 6, Tract 40, bears S 50°07' W, 4.58 chs. dist., hereinbefore described.</p>	

Dependent Resurvey of the Erroneous S Bdy. of the GRIR  
T 4 S, R 3 E, Gila and Salt River Mer., Arizona

CHAINS

S 89°59' W, bet. sec. 9 and Tract 39.

Continue over rolling land, along an old fence,  
extending westerly.

20.01

The E 1/16 sec. cor. of sec. 9 only, established by  
R.A. Farmer in 1910-12, and which now also stands for  
AP 2, Tract 39, T 4 S, R 3 E, monumented with the  
remains of an iron post, 1 in. diam., filled with  
cement, firmly set, flush with the surface, with brass  
cap mkd.

GRIR  
E 1/16 NO 1 S 9  
1911

At the cor. point

Set a stainless steel post, 28 ins. long, 2½ ins. diam.,  
27 ins. in the ground, with brass cap mkd.

T4S R3E  
GRIR  
E 1/16 S 9  
AP2 TR39  
GRIR  
1985

Deposit the remains of the iron post beneath the  
stainless steel post.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored  
plastic case beneath the stainless steel post.

Set a fiberglass marker alongside the cor.

N 89°57' W, beginning new measurement.

Continue over rolling land, along an old fence,  
extending E and W.

20.01

The ¼ sec. cor. of sec. 9 only, established by R.A.  
Farmer in 1910-12, and which now also stands for AP 3,  
Tract 39, T 4 S, R 3 E, monumented with the remains of  
an iron post, 1 in. diam., filled with cement, 6 ins.  
below the surface.

At the cor. point

Set a stainless steel post, 28 ins. long, 2½ ins.  
diam., 24 ins. in the ground, with brass cap mkd.

T4S R3E  
GRIR  
¼ S 9  
AP3 TR39  
GRIR  
1985

Deposit the remains of the iron post beneath the  
stainless steel post.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored  
plastic case beneath the stainless steel post.

Dependent Resurvey of the Erroneous S Bdy. of the GRIR  
T 4 S, R 3 E, Gila and Salt River Mer., Arizona

CHAINS

Set a fiberglass marker alongside the cor.

S 89°59' W, beginning new measurement.

Continue over rolling land, along an old fence,  
extending E and W.

20.01

The W 1/16 sec. cor. of sec. 9 only, established by  
R.A. Farmer in 1910-12, and which now also stands for  
AP 4, Tract 39, T 4 S, R 3 E, monumented with an iron  
post, 1 in. diam., firmly set, flush with the ground,  
with brass cap mkd.

GRIR  
1/16 NO 2 S9  
1911

At the cor. point

Set a stainless steel post, 28 ins. long, 2½ ins. diam.,  
24 ins. in the ground, with brass cap mkd.

T4S R3E  
GRIR  
W 1/16 S9  
AP4 TR39  
GRIR  
1985

Deposit the remains of the iron post beneath the  
stainless steel post.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored  
plastic case beneath the stainless steel post.

Set a fiberglass marker alongside the cor.

N 89°57' W, beginning new measurement.

Continue over rolling land, along an old fence,  
extending E and W.

20.00

The cor. of secs. 8 and 9 only, established by R.A.  
Farmer in 1910-12, and which now also stands for AP 1,  
Tract 38, and AP 5, Tract 39, T 4 S, R 3 E, monumented  
with the remains of an iron post., 1 in. diam., 12 ins.  
below the ground, no brass cap, an open end pipe, of  
unknown origin, 10 ins. long, 1 in. diam., projecting 3  
ins. above the ground, is atop the iron post.

At the cor. point

Set a stainless steel post, 28 ins. long, 2½ ins. diam.,  
26 ins. in the ground, with brass cap mkd.

T4S R3E  
GRIR  
S 8 | S 9  
AP1 / AP5  
TR38 / TR39  
GRIR  
1985

Deposit the remains of the iron post and the open end  
pipe beneath the stainless steel post.

Dependent Resurvey of the Erroneous S Bdy. of the GRIR  
T 4 S, R 3 E, Gila and Salt River Mer., Arizona

CHAINS

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Set a fiberglass marker alongside the cor.

From this point, the cor. of secs. 16 and 17 only, and also AP 8, Tract 38 and AP 6, Tract 39, bears S 37°16' W, 5.84 chs. dist., hereinbefore described.

N 89°58' W, bet. sec. 8 and Tract 38.

Continue over rolling land, along an old fence, extending E and W.

20.00

Point for the E 1/16 sec. cor. of sec. 8 only, established by R.A. Farmer in 1910-12, at proportionate dist.; there is no evidence of the cor. This cor. now also stands for AP 2, Tract 38, T 4 S, R 3 E,

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T4S R3E  
GRIR  
E 1/16 S 8  
AP2 TR38  
GRIR  
1985

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Set a fiberglass marker alongside the cor.

Continue over rolling land, bet. fences extending E and W and a dirt road, 15 lks. wide, bears E and W.

40.00

The 1/4 sec. cor. of sec. 8 only, established by R.A. Farmer in 1910-12, and which now also stands for AP 3, Tract 38, T 4 S, R 3 E, monumented with the remains of an iron post, 1 in. diam., filled with cement, firmly set 6 ins. below the ground.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T4S R3E  
GRIR  
1/4 S 8  
AP3 TR38  
GRIR  
1985

Deposit the remains of the iron post beneath the stainless steel post.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Set a fiberglass marker alongside the cor.

Dependent Resurvey of the Erroneous S Bdy. of the GRIR  
T 4 S, R 3 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>N 89°59' W, beginning new measurement.</p> <p>Continue over rolling land, bet. a fence to the N, extending E and W, and a dirt road to the S, bearing E and W.</p> <p>19.98 The W 1/16 sec. cor. of sec. 8 only, established by R.A. Farmer in 1910-12, and which now also stands for AP 4, Tract 38, T 4 S, R 3 E, monumented with the remains of an iron post, 1 in. diam., filled with cement, firmly set, 38 ins. below the ground.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T4S R3E GRIR W 1/16 S 8 AP4 TR38 GRIR 1985</p> </div> <p>Deposit the remains of the iron post beneath the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a fiberglass marker alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 89°58' W, beginning new measurement.</p> <p>Continue over rolling land, bet. a fence to the N, extending E and W and a dirt road to the S, 15 lks. wide, bearing E and W.</p>	
<p>20.00</p>	<p>The cor. of secs. 7 and 8, established by R.A. Farmer in 1910-12, and which now also stands for AP 1, Tract 37, and AP 5, Tract 38, T 4 S, R 3 E, monumented with the remains of an iron post. 1 in. diam., filled with cement, firmly set 2 ins. below the ground.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T4S R3E GRIR S 7   S 8 AP1 / AP5 TR37 / TR38 GRIR 1985</p> </div> <p>Deposit the remains of the iron post beneath the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a fiberglass marker alongside the cor.</p>	

Dependent Resurvey of the Erroneous S Bdy. of the GRIR  
T 4 S, R 3 E, Gila and Salt River Mer., Arizona

CHAINS

From this point, the cor. of secs. 17 and 18 only, and also AP 8, Tract 37 and AP 6, Tract 38, bears S 40°04' W, 6.42 chs. dist., hereinbefore described.

N 89°59' W, bet. sec. 7 and Tract 37.

Continue over rolling land, bet. a fence to the N, extending E and WSW, and a dirt road, to the S, 15 lks. wide, bearing E and W.

1.90 Intersect an old fence and a newer fence, extending W and ENE. respectively.

19.99 The E 1/16 sec. cor. of sec. 7 only, established by R.A. Farmer in 1910-12, and which now also stands for AP 2, Tract 37, T 4 S, R 3 E, monumented with the remains of an iron post, 1 in. diam., filled with cement, firmly set 12 ins. below the ground.

At the cor. point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T4S R3E  
GRIR  
E 1/16 S 7  
AP2  
TR37  
GRIR  
1985

Deposit the remains of the iron post beneath the stainless steel post.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Set a fiberglass marker alongside the cor.

N 89°55' W, beginning new measurement.

Continue over rolling land, along an old fence line, extending E and W.

19.98 The ¼ sec. cor. of sec. 7 only, established by R.A. Farmer in 1910-12, and which now also stands for AP 3, Tract 37, T 4 S, R 3 E, monumented with the remains of an iron post, 1 in. diam., filled with cement, firmly set 30 ins. below the ground.

At the cor. point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T4S R3E  
GRIR  
¼ S 7  
AP3  
TR37  
GRIR  
1985

Dependent Resurvey of the Erroneous S Bdy. of the GRIR  
T 4 S, R 3 E, Gila and Salt River Mer., Arizona

CHAINS

Deposit the remains of the iron post beneath the stainless steel post.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Set a fiberglass marker alongside the cor.

---

N 89°59' W, beginning new measurement.

Continue over rolling land, along an old fence, extending E and W.

19.99 The W 1/16 sec. cor. of sec. 7 only, established by R.A. Farmer in 1910-12, and which now also stands for AP 4, Tract 37, T 4 S, R 3 E, monumented with the remains of an iron post, 1 in. diam., filled with cement, firmly set 18 ins. below the ground.

At the cor. point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T4S R3E  
GRIR  
W 1/16 S 7  
AP4  
TR37  
GRIR  
1985

Deposit the remains of the iron post beneath the stainless steel post.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Set a fiberglass marker alongside the cor.

---

N 89°58' W, beginning new measurement.

Continue over rolling land, along old fence extending E and W.

19.41 The cor. of secs. 7 and 12, established by R.A. Farmer in 1910-12, and which now also stands for AP 1, Tract 42, and AP 5, Tract 37, Tps. 4 S, Rs. 2 and 3 E, monumented with the remains of an iron post, 3 ins. diam., 4 ins. below the ground.

At the cor. point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T4S  
R2E GRIR R3E  
S12 | S 7  
AP1 / AP5  
TR42 / TR37  
GRIR  
1985



Dependent Resurvey of the Erroneous S Bdy. of the GRIR  
T 4 S, R 3 E, Gila and Salt River Mer., Arizona

## CHAINS

Deposit the remains of the iron post beneath the stainless steel post.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Set a fiberglass marker alongside the cor.

From this point the cor. of secs. 13 and 18 only, and also AP 8, Tract 42 and AP 6, Tract 37, Tps. 4 S, Rs. 2 and 3 E, bears S 54°43' W, 8.495 chs. dist., hereinbefore described.

## GENERAL DESCRIPTION

The area in this survey is located about 2 miles N of Maricopa, Arizona. The elevation is about 1150 feet above sea level.

The access is by way of Maricopa Road to many dirt and gravel roads.

The soil is irrigated clay loam and supports a healthy crop of cotton. Where it is not irrigated it is desert.

There were no minerals of value noted on the lines of this survey.

The mean magnetic declination is 14° E, with a range of 1° in local attraction.



## CERTIFICATE OF SURVEY

We, Paul L. Reeves and Stephen J. Malloy, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 18th day of March 1985, and the supplemental special instructions dated July 18, 1985, we have dependently resurveyed a portion of the subdivisional lines and surveyed Tract Nos. 37 through 42, Township 4 South, Range 3 East, of the Gila and Salt River Meridian, in the State of Arizona which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

APR 03 1986

(Date)

*Paul L. Reeves*  
(Cadastral Surveyor)

APR 23 1986

(Date)

*Stephen J. Malloy*  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

Arizona State Office  
Bureau of Land Management  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and the survey of Tract Nos. 37 through 42, Township 4 South, Range 3 East, Gila and Salt River Meridian, Arizona, executed by Paul L. Reeves and Stephen J. Malloy, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

APR 30 1986

(Date)

*James P. Kelley*  
(Chief Cadastral Surveyor of Arizona)