

ORIGINAL

1

BOOK 5229

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF PORTIONS OF THE

NORTH BOUNDARY (THIRD STANDARD PARALLEL NORTH),

EAST AND SOUTH BOUNDARIES,

AND PORTIONS OF THE SUBDIVISIONAL LINES,

THE SURVEY OF SUBDIVISIONS IN CERTAIN SECTIONS

AND

METES-AND-BOUNDS SURVEYS IN

SECTIONS 28, 32 AND 35

TOWNSHIP 12 NORTH, RANGE 18 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Will C. Gabonay, Cadastral Surveyor

Paul L. Reeves, Cadastral Surveyor

Under special instructions dated May 27, 1981, approved May 28 1981

and Supplemental Special Instructions dated December 16, 1983, approved

December 16, 1983, which provided for the surveys included under Group Number

623 and assignment instructions dated May 27,, 1981

and October 7, 1982.

Survey commenced June 3, 1981

Survey completed June 20, 1986

INDEX DIAGRAM

TOWNSHIP 12 NORTH, RANGE 18 EAST,

Third Standard Parallel North

			7			6			5			5			3
6			5			4	43	3	31	2	20	1	12		
									42		30		20		
7			8			9	41	10	29	11	19	12			
63									40		19				
18	61	17			16	39	15	29	14	18	13	11			
60			59			51	38		28		17				
19	57	20	50	21	35	22	27	23	17	24	10				
56			55		49		35		26						
30	54	29	48	28	33	27	25	26	15	25					
53			52		47		33		23						
31	51	32	43	33	32	34	21	35	14	36					
			9						8						

Subdivision of Section

- Section 2 ---pp. 64 - 67
- Section 10 ---pp. 67 - 69
- Section 13 ---pp. 69 - 70
- Section 18 ---pp. 70 - 74
- Section 19 ---pp. 74 - 77
- Section 20 ---pp. 77 - 82
- Section 21 ---pp. 82 - 85
- Section 22 ---pp. 85 - 98
- Section 26 ---pp. 98 - 106

Subdivision of Section

- Section 28 ---pp. 106 - 110
- Section 32 ---pp. 111 - 121
- Section 35 ---pp. 123 - 133

Metes-and-Bounds Survey

- Section 28 ---pp. 110 - 111
- Section 32 ---pp. 121 - 122
- Section 35 ---pp. 133 - 134

T 12 N, R 18 E, Gila and Salt River Mer., Arizona

## CHAINS

The following field notes are those of the dependent resurvey of portions of the north boundary (Third Standard Parallel North) east and south boundaries, and portions of the sudivisional lines; the survey of subdivisions in certain sections and metes-and-bounds surveys in sections 28, 32 and 35, Township 12 North, Range 18 East, Gila and Salt River Meridian, Arizona.

C. Burton Foster surveyed the north boundary (Third Standard Parallel North), in 1874. H.A. Coe resurveyed the north boundary and surveyed the remainder of the township, in 1883. Thomas B. Matthews resurveyed the west boundary and a portion of the north boundary of section 6, in 1917. Albinus N. Kimmell, Roger F. Wilson, Benjamin J. Mollette, Carroll I. Parkman and John Boggs resurveyed a portion of the west boundary, in 1935-36. Harry K. Smith and Paul L. Reeves resurveyed a portion of the south boundary, in 1977.

The survey was executed in accordance with specifications as set forth in the Manual of Surveying Instructions, 1973, and the special instructions dated May 27, 1981, and supplemental special instructions dated December 16, 1983, for Group No. 623, Arizona.

The directions of lines were determined by direct solar observations and refer to the true meridian. Angles and distances were measured electronically using a Hewlett Packard 3820 Total Station instrument.

Preliminary to the resurvey the lines of prior official surveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of section 35 of this township, as determined by a tie to the point for U.S. Coast and Geodetic triangulation station "DECKER", is as follows:

Latitude: 34°23'12.8" N Longitude: 110°23'27.5" W

The mean magnetic declination taken from U.S. Geological Survey quadrangle map CLAY SPRINGS, ARIZ., published in 1961 is 14° E.

---

Dependent Resurvey of the Third Stan. Par. N,  
Through a Portion of R 19 E,  
Gila and Salt River Mer., Arizona

---

Reestablishment of the Resurvey Executed by  
H. A. Coe in 1883.

---

Beginning at the stan. cor. of secs. 31 and 32,  
T 13 N, R 19 E, monumented with a mound of stone,  
2½ ft. base, projecting 1 ft. above ground, from which

Dependent Resurvey of the Third Stan. Par. N, Through  
a Portion of R 19 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A juniper, 16 ins. diam., bears S 31° E, 54 lks. dist., mkd. TXIIN RXIXE, with other illegible scribe marks. (1883 Record: S 24° E)</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S C T13N R19E S31   S32 <u>1981</u></p>
	<p>from which a new bearing tree</p>
	<p>A juniper, 7 ins. diam., bears N 3° E, 20.5 lks. dist., mkd. T13N R19E SC S32 BT.</p>
	<p>Raise a mound of stone, 2½ ft. base, 1 ft. high, N of cor.</p>
	<p>S 89°39' W, on the S bdy. of sec. 31.</p>
	<p>Over relatively level terrain, through medium to dense juniper.</p>
<p>37.30</p>	<p>Highway No. 277, asphalt surfaced, bears N 65° E and S 65° W.</p>
<p>40.05</p>	<p>Point for the stan. ¼ sec. cor. of sec. 31, at pro- portionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p>
	<p style="text-align: center;">S C T13N R19E ¼ S31 <u>1982</u></p>
	<p>Raise a mound of stone, 2½ ft. base, 1½ ft. high N of cor.</p>
	<p>Cor. is 98 lks. N of the center of Highway No. 277, asphalt surfaced, bears N 65° E and S 65° W.</p>
	<p>S 89°29' W, beginning new measurement.</p>
<p>17.30</p>	<p>Point for the closing cor. of secs. 1 and 6 only, Tps. 12 N, Rs. 18 and 19 E, hereinafter described.</p>
<p>40.47</p>	<p>Point for the stan. cor. of Tps. 13 N, Rs. 18 and 19 E, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 1½ ft. base, to top, with cap mkd.</p>

Dependent Resurvey of the Third Stan. Par. N, Through  
a Portion of R 19 E, Gila and Salt River Mer., Arizona

CHAINS

S C  
T13N  
R18E | R19E  
S36 | S31  
1982

A fence cor., bears N 28½° E, 92 lks. dist., fence  
extends N and S 68° E.

---

Dependent Resurvey of the Third Stan. Par. N,  
Through a Portion of R 18 E,  
Gila and Salt River Mer., Arizona

---

S 89°22' W, on the S bdy. of sec. 36.

Through dense juniper.

40.54

Point for the stan. ¼ sec. cor. of sec. 36, at propor-  
tionate dist.; there is no remaining evidence of the  
original cor.

Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins.  
in the ground, with cap mkd.

S C  
T13N R18E  
¼ S36  
1982

from which

A juniper, 11 ins. diam., bears N 25½° E,  
48 lks. dist., mkd. ¼ S36 SC BT.

---

S 89°24' W, beginning new measurement.

18.32

Point for the closing cor. of secs. 1 and 2 only,  
T 12 N, R 18 E, hereinafter described.

Through dense juniper.

40.18

Point for the stan. cor. of secs. 35 and 36, at  
proportionate dist.; there is no remaining evidence of  
the original cor.

Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins.  
in the ground, in a mound of stone, 2½ ft. base, to  
top, with cap mkd.

S C  
T13N R18E  
S35 | S36  
1982

Cor. is located 10 lks. S of an E-W abandoned fence  
line.

---

S 89°34' W, on the S bdy. of sec. 35.

Through sparse juniper.

Dependent Resurvey of the Third Stan. Par. N, Through  
a Portion of R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
18.32	Point for the $\frac{1}{4}$ sec. cor. of sec. 2 only, T 12 N, R 18 E, hereinafter described.
38.41	Point for the W $\frac{1}{16}$ sec. cor. of sec. 2 only, T 12 N, R 18 E, hereinafter described.
40.58	Point for the stan. $\frac{1}{4}$ sec. cor. of sec. 35, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, $1\frac{1}{2}$ ft. base, to top, with cap mkd.
	<p>S C T13N R18E <math>\frac{1}{4}</math> S35 ----- 1982</p>
	from which
	<p>A juniper, 6 ins. diam., bears N <math>26^\circ</math> W, 64.5 lks. dist., mkd. <math>\frac{1}{4}</math> S35 SC BT.</p>
	Cor. is located 23 lks. W of a N-S fence line.
	<p>-----</p> <p>S <math>89^\circ 21'</math> W, beginning new measurement.</p>
	Through dense juniper.
17.92	Point for the closing cor. of secs. 2 and 3 only, T 12 N, R 18 E, hereinafter described.
40.48	Point for the stan. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 28 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base to top with cap mkd.
	<p>S C T13N R18E S34   S35 ----- 1981</p>
	An abandoned fence cor., bears N $87^\circ$ E, 1.465 chs. dist., fence extends N and E.
	<p>-----</p> <p>S <math>89^\circ 55'</math> W, on the S bdy. of sec. 34.</p>
	Through open field.
40.47	Point for the stan. $\frac{1}{4}$ sec. cor. of sec. 34, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground with cap mkd.
	<p>S C T13N R18E <math>\frac{1}{4}</math> S34 ----- 1982</p>

Dependent Resurvey of the Third Stan. Par. N, Through  
a Portion of R 18 E, Gila and Salt River Mer., Arizona

CHAINS

from which

A juniper, 12 ins. diam., bears N 11° W,  
73 lks. dist., mkd. ¼ S34 SC BT.

Raise a mound of stone, 2 ft. base, 1 ft. high, N of  
cor.

---

S 89°11' W, beginning new measurement.

17.46 Point for the closing cor. of secs. 3 and 4 only,  
T 12 N, R 18 E, hereinafter described.

40.48 Point for the stan. cor. of secs. 33 and 34, at  
proportionate dist.; there is no remaining evidence of  
the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.  
in the ground, with brass cap mkd.

S C  
T13N R18E  
S33 | S34  
-----  
1981

from which

A juniper, 4 ins. diam., bears N 87½° E, 60  
lks. dist., mkd. X at breast height and  
BT at base.

---

S 89°23' W, on the S bdy. of sec. 33.

Over rolling land, through dense juniper.

40.65 Point for the stan. ¼ sec. cor. of sec. 33, at propor-  
tionate dist.; there is no remaining evidence of the  
original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins.  
in the ground, with brass cap mkd.

S C  
T13N R18E  
¼ S33  
-----  
1981

from which

A juniper, 14 ins. diam., bears N 73½° E,  
3.5 lks. dist., mkd. ¼ S33 SC BT.

---

S 89°29' W, beginning new measurement.

16.30 Point for the closing cor. of secs. 4 and 5 only,  
T 12 N, R 18 E, at proportionate dist; there in no  
remaining evidence of the original cor., not monumented.

40.38 The stan. cor. of secs. 32 and 33, monumented with a  
juniper post, 4 ins. diam., 40 ins. long, lying on the  
ground, with illegible scribe marks on one side, from  
which the bearing trees reported in 1883.

Dependent Resurvey of the Third Stan. Par. N, Through  
a Portion of R 18 E, Gila and Salt River Mer., Arizona

CHAINS

A juniper, 10 ins. diam., bears N 63° E,  
55 lks. dist., mkd. TXIIIN RXVIIIE SXXXIII,  
other scribe marks are illegible.

A juniper, 4 ins. diam., bears S ¾° W,  
16 lks. dist., mkd. TXIIN RXVIIIE, other scribe  
marks are illegible.

A pinyon, 8 ins. diam., bears N 6° W,  
26 lks. dist., mkd. TXIIIN RXVIIIE, other scribe  
marks are illegible.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.  
in the ground, with brass cap mkd.

S C  
T13N R18E  
S32 | S33  
1981

Bury original post alongside the cor.

Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of  
cor.

---

Dependent Resurvey, Portions of the South Boundary of  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

---

Reestablishment of the Resurvey Executed by  
Harry K. Smith and Paul L. Reeves, in 1977

---

From the cor. of secs. 1, 2, 35 and 36, on the S bdy.  
of the Tp., monumented with an iron post, 2½ ins.  
diam., projecting 6 ins. above the ground, with brass  
cap mkd. as described in the official record of the  
1977 resurvey, from which accessories recorded in 1977

A juniper, 12 ins. diam., bears N 25° E, 9 lks.  
dist., mkd. T12N R18E S36 BT.

A fence cor., bears S 40° E, 1.15 chs. dist.;  
fences extend N and E.

An alligator juniper, 18 ins. diam., bears  
S 12° E, 98 lks. dist., mkd. T11N R18E S1 BT, on  
a partially healed blaze.

A juniper, 13 ins. diam., bears S 29° W,  
74 lks. dist., mkd. T11N R18E S2 BT.

An alligator juniper, 18 ins. diam., bears  
N 68½° W, 96 lks. dist., mkd. T12N R18E  
S35 BT.

A local cor., bears N 17°09' W, 1.77 chs. dist.,  
monumented with an open end metal pipe, 1½ ins.  
diam., projecting 15 ins. above ground.

Cor. is 30 lks. N of a dirt road, bears irregularly E  
and W.



Dependent Resurvey, Portions of the South Boundary of  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

S 89°55' W, bet. secs. 2 and 35.

Through dense juniper, over rolling land.

20.01 Point for the E 1/16 sec. cor. of secs. 2 and 35.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 28 ins. in the ground, in a mound of stone, 2 $\frac{1}{2}$  ft. base, to top, with cap mkd.

T12N R18E  
E 1/16  $\frac{S35}{S 2}$   
T11N  
1981

from which

A juniper, 10 ins. diam., bears S 45° W,  
78 lks. dist., mkd. E 1/16 S2 BT.

A juniper, 8 ins. diam., bears N 25° W,  
64 lks. dist., mkd. E 1/16 S35 BT.

40.02 The  $\frac{1}{4}$  sec. cor. of secs. 2 and 35, monumented with an iron post, 2 $\frac{1}{2}$  ins. diam., projecting 6 ins. above the ground, with a mound of stone, 3 ft. base, 1 ft. high, N of cor., with brass cap mkd. as described in the official record of the 1977 resurvey, from which bearing trees recorded in 1977

A ponderosa pine, 10 ins. diam., bears  
S 78 $\frac{1}{4}$ ° E, 3.61 chs. dist., mkd. X at  
breast height and BT at base.

A ponderosa pine, 12 ins. diam., bears  
S 26° W, 3.61 chs. dist., mkd.  $\frac{1}{4}$  S2 BT.

From the E 1/16 sec. cor. of secs. 5 and 32, on the S bdy. of the Tp., monumented with an iron post, 2 $\frac{1}{2}$  ins. diam., projecting 6 ins. above the ground, with brass cap mkd. as described in the official record of the 1977 resurvey, from which accessories recorded in 1977

A ponderosa pine, 14 ins. diam., bears S 83° W,  
72 lks. dist., mkd. E 1/16 S5 BT.

A fence cor., bears S 66° E, 6 lks. dist.,  
fence extends S and W.

N 89°51' W, bet. secs. 5 and 32.

10.00 Point for the W-E 1/64 sec. cor. of secs. 5 and 32.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.

S32  
W-E 1/64  
S5  
1982

Dependent Resurvey, Portions of the South Boundary of  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS																
	<p>from which</p> <p>A ponderosa pine, 8 ins. diam., bears N 9½° W, 55 lks. dist., mkd. W-E 1/64 S32 BT.</p> <p>A fence cor., bears N 61° W, 11.5 lks. dist., fences extend N, E and W.</p> <p>Cor. is located 4 lks. S of an E and W fence and 64 lks. N of a track road, 15 lks. wide, bears and S 70° E and N 85° W.</p>															
20.00	<p>The ¼ sec. cor. of secs. 5 and 32, monumented with an iron post, 2½ ins. diam., projecting 6 ins. above the ground, with a mound of stone, 2½ ft. base, 1 ft. high, N of cor., with brass cap mkd. as described in the official record of the 1977 resurvey, from which bearing trees recorded in 1977</p> <p>An alligator juniper, 8 ins. diam., bears N 58½° E, 20 lks. dist., mkd. ¼ S32 BT.</p> <p>A ponderosa pine, 10 ins. diam., bears S 12° W, 38 lks. dist., mkd. ¼ S5 BT.</p> <p>Cor. is 3 lks. S of an E-W fence.</p> <hr/> <p>Dependent Resurvey of a Portion of the East Boundary of T 12 N, R 18 E, Gila and Salt River Mer., Arizona</p> <hr/> <p>Reestablishment of the Survey Executed by H.A. Coe, in 1883</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E bdy. of the Tp., monumented with a mound of stone, 1 ft. base, from which original bearing trees</p> <p>An alligator juniper, 11 ins. diam., bears N 1½° E, 76 lks. dist., opened healed blaze mkd. T12N R19E S19 BT, (Record: 78 lks. dist.)</p> <p>An alligator juniper snag, 6 ins. diam., bears S 53° W, 43 lks. dist., mkd. T12N R18E S25 BT. (Record: 41 lks. dist.)</p> <p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T12N</td><td></td><td></td></tr> <tr><td>R18E</td><td> </td><td>R19E</td></tr> <tr><td>S24</td><td> </td><td>S19</td></tr> <tr><td>S25</td><td> </td><td>S30</td></tr> <tr><td colspan="3">1981</td></tr> </table> </div> <p>from which new bearing trees</p> <p>A juniper, 5 ins. diam., bears N 27½° E, 43 lks. dist., mkd. X at breast height and BT at base.</p>	T12N			R18E		R19E	S24		S19	S25		S30	1981		
T12N																
R18E		R19E														
S24		S19														
S25		S30														
1981																

Dependent Resurvey of a Portion of the East Boundary of  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

A juniper, 4 ins. diam., bears S 37° E,  
38 lks. dist., mkd. X at breast height and  
BT at base.

An alligator juniper, 8 ins. diam., bears  
S 68° W, 71.5 lks. dist., mkd. T12N R18E  
S25 BT.

A juniper, 6 ins. diam., bears N 62° W, 60  
lks. dist., mkd. T12N R18E S24 BT.

N 0°19' E, bet. secs. 19 and 24.

Over mildly rolling hills.

39.83 Point for the ¼ sec. cor. of secs. 19 and 24, at  
proportionate dist; there is no remaining evidence of  
the original cor.

Set an aluminum post, 36 ins. long, ¾ in. diam., 28 ins.  
in the ground, in a mound of stone, 2 ft. base, to top,  
with cap mkd.

T12N  
¼  
R18E | R19E  
S24 | S19  
1981

from which

A juniper, 8 ins. diam., bears N 45° E,  
72.5 lks. dist., mkd. ¼ S19 BT.

A juniper, 14 ins. diam., bears N 2° W,  
56.5 lks. dist., mkd. ¼ S24 BT.

79.66 Point for the cor. of secs. 13, 18, 19 and 24, at pro-  
portionate dist.; there is no remaining evidence of the  
original cor.

Set a finned aluminum post, 24 ins. long, ¾ in. diam.,  
18 ins. in the ground, in a mound of stone, 2½ ft.  
base, to top, with cap mkd.

T12N  
R18E R19E  
S13 | S18  
S24 | S19  
1986

Set a steel fence post alongside the cor.

N 0°19' E, bet. secs. 13 and 18.

Over railed area.

39.83 Point for the ¼ sec. cor. of secs. 13 and 18, at pro-  
portionate dist.; there is no remaining evidence of the  
original cor.

Set an aluminum post, 36 ins. long, ¾ in. diam., 28 ins.  
in the ground, in a mound of stone, 1½ ft. base, to top,  
with cap mkd.

Dependent Resurvey of a Portion of the East Boundary of  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T12N  <math>\frac{1}{4}</math>  R18E   R19E  S13   S18  1981</p>
59.745	<p>Point for the N 1/16 sec. cor. of secs. 13 and 18.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 28 ins. in the ground, with cap mkd.</p>
	<p style="text-align: center;">T12N  N 1/16  R18E   R19E  S13   S18  1981</p>
79.66	<p>The cor. of secs. 7, 12, 13 and 18, monumented with a mound of stone, 2<math>\frac{1}{2}</math> ft. base, from which original bearing trees</p> <p style="padding-left: 40px;">A juniper stump, bears N 15° E,  1.20 chs. dist. (Record: N 13° E)</p> <p style="padding-left: 40px;">A juniper, 17 ins. diam., bears S 58° E,  71 lks. dist., mkd. T12N R19E S18. (Record:  S 60° E)</p> <p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 28 ins. in the ground, in a mound of stone, 2<math>\frac{1}{2}</math> ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N  R18E R19E  S12   S 7  S13   S18  1981</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E bdy. of the Tp., monumented with a limestone, 16 x 14 x 11 ins., loosely set and mkd. with 5 grooves on one side, 1 groove on another, with a mound of stone, 1<math>\frac{1}{2}</math> ft. base, 6 ins. high, S of cor., from which an original bearing tree</p> <p style="padding-left: 40px;">The stump hole of a fallen pinyon, 16 ins. diam., bears S 87° W, 32 lks. dist., marks visible are T and S, with other illegible scribe marks.</p> <p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 28 ins. in the ground, in a mound of stone, 1<math>\frac{1}{2}</math> ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N  R18E R19E  S 1   S 6  S12   S 7  1981</p> <p>from which a new bearing tree</p>

Dependent Resurvey of a Portion of the East Boundary of  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

A juniper, 18 ins. diam., bears S 48° W,  
1.005 ch. dist., mkd. T12N R18E S12 BT.

Bury the mkd. stone alongside the aluminum post.

Cor. is located 1 lk. S of an E-W fence and 10 lks. E  
of fence cor., fences extend N an E.

N 0°10' E, bet. secs. 1 and 6.

Over gently rolling land, through scattered juniper.

35.70 Highway No. 277, asphalt surfaced, bears N 65° E and  
S 65° W.

42.18 Point for the ¼ sec. cor. of secs. 1 and 6, at propor-  
tionate dist.; there is no remaining evidence of the  
original cor.

Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins.  
in the ground, with cap mkd.

T12N  
R18E | R19E  
      ¼  
S 1 | S 6  
      1982

from which

A juniper, 10 ins. diam., bears N 78½° W,  
1.83 chs. dist., mkd. ¼ S1 BT.

Cor. is located in abandoned N-S fence.

45.19 Point for the closing cor. of secs. 1 and 6 only, on  
the Third Stan. Par. North.

Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins.  
in the ground, with cap mkd.

T13N R19E  
      S31  
-----  
S 1 | S 6  
R18E | R19E  
      T12N  
      CC  
      1982

from which

A juniper, 8 ins. diam., bears S 61¾° W,  
44 lks. dist., mkd. T12N R18E S1 CC BT.

From this point, the original closing cor. of secs. 1  
and 6, bears N 0°10' E, 15 lks. dist., monumented with  
a wooden post, 32 ins. long, 4 ins. diam., lying loose  
at a fence cor., mkd. CC T12N on one side, R19E S6 on  
one side and R18E S1 on another side, from which  
original bearing trees

The remains of a pine, 5 ins. diam., bears  
N 37° E, 71 lks. dist., rotted out blaze  
and no marks visible.

A fallen pine, 6 ins. diam., mkd. T12N, R18E S1  
BT, is in the SW quadrant: It is impossible to  
determine exactly where this tree grew.

Dependent Resurvey of a Portion of the East Boundary of  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Add the marks AM to the original cor. post and bury it horizontally at the fence cor.</p> <p>From this same point, the stan. <math>\frac{1}{4}</math> sec. cor. of sec. 31, T 13 N, R 19 E, bears N <math>89^{\circ}29'</math> E, 17.30 chs. dist., hereinbefore described.</p>
	<p>Dependent Resurvey, Portions of the Subdivisional Lines T 12 N, R 18 E, Gila and Salt River Mer., Arizona</p>
	<p>Reestablishment of the Survey Executed by H.A. Coe, in 1883</p>
	<p>From the cor. of secs. 1, 2, 35 and 36, on the S bdy. of the Tp., hereinbefore described.</p> <p>N <math>1^{\circ}52'</math> E, bet. secs. 35 and 36.</p> <p>Over rolling land through dense juniper</p>
<p>19.86</p>	<p>Point for the S <math>1/16</math> sec. cor. of secs. 35 and 36.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, in a mound of stone, <math>2\frac{1}{2}</math> ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E S <math>1/16</math> S35   S36 1981</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears N <math>48^{\circ}</math> W, 93 lks. dist., mkd. S <math>1/16</math> S35 BT.</p> <p>Cor. is located 39 lks. E of a fence, bears N and S.</p>
<p>39.72</p>	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E <math>\frac{1}{4}</math> S35   S36 1981</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N <math>86\frac{1}{2}^{\circ}</math> E, 1.07 chs. dist., mkd. <math>\frac{1}{4}</math> S36 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S <math>49^{\circ}</math> W, 66 lks. dist., mkd. <math>\frac{1}{4}</math> S35 BT.</p> <p>Cor. is located 5 lks. W of a wash, 6 lks. wide, <math>1\frac{1}{2}</math> ft. deep, drains N <math>40^{\circ}</math> E.</p>
<p>59.58</p>	<p>Point for the N <math>1/16</math> sec. cor. of secs. 35 and 36.</p>

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 30 ins. in the ground, with cap mkd.

T12N R18E  
N 1/16  
S35 | S36  
1981

from which

An alligator juniper, 6 ins. diam., bears S 74° E, 33.5 lks. dist., mkd. N 1/16 S36 BT.

A ponderosa pine, 14 ins. diam., bears S 40° W, 68 lks. dist., mkd. N 1/16 S35 BT.

79.44

The cor. of secs. 25, 26, 35 and 36, monumented with a sandstone, 14 x 8 x 8 ins., loosely set, mkd.  $\frac{1}{4}$  on top, with a scattered mound of stone N of cor., from which the remains of an original bearing tree

A stump hole, bears S 84° E, 56 lks. dist., the stump of a rotted fallen pine lying alongside is mkd. with illegible scribe marks.

At the cor. point

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 22 ins. in the ground, in a mound of stone, 1 $\frac{1}{2}$  ft. base, to top, with cap mkd.

T12N R18E  
S26 | S25  
S35 | S36  
1981

from which new bearing trees

A ponderosa pine, 10 ins. diam., bears S 41° E, 95 lks. dist., mkd. T12N R18E S36 BT.

A pinyon pine, 8 ins. diam., bears S 71° W, 1.03 chs. dist., mkd. T12N R18E S35 BT.

A juniper, 8 ins. diam., bears N 68° W, 1.34 chs. dist., mkd. T12N R18E S26 BT.

Deposit the mkd. stone in the mound of stone around the cor.

North, bet. secs. 25 and 26.

Over rolling land, through juniper, pinyon, ponderosa pine and oak.

20.05

Point for the S 1/16 sec. cor. of secs. 25 and 26.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 30 ins. in the ground, in a mound of stone, 2 $\frac{1}{2}$  ft. base, to top, with cap mkd.

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

	CHAINS		
		<p>T12N R18E S 1/16 S26   S25 1981</p> <p>from which</p> <p>A ponderosa pine, 8 ins. diam., bears N 29° W, 98 lks. dist., mkd. S 1/16 S26 BT.</p>	
40.10		<p>The 1/4 sec. cor. of secs. 25 and 26, monumented with a mound of stone, 3 ft. base, 6 ins. high, from which the remains of an original bearing tree</p> <p>The stump hole of a fallen pine, 8 ins. diam., bears N 55° W, 33 lks. dist., the tree is mkd. 1/4 S BT.</p> <p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p>	
		<p>T12N R18E 1/4 S26   S25 1981</p> <p>from which new bearing trees</p> <p>A ponderosa pine, 14 ins. diam., bears N 72° E, 35.5 lks. dist., mkd. 1/4 S25 BT.</p> <p>A ponderosa pine, 8 ins. diam., bears S 53° W, 15 lks. dist., mkd. 1/4 S26 BT.</p>	
		<p>N 0°34' E, beginning new measurement.</p>	
20.38		<p>Point for the N 1/16 sec. cor. of secs. 25 and 26.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p>	
		<p>T12N R18E N 1/16 S26   S25 1981</p> <p>from which</p> <p>A ponderosa pine, 8 ins. diam., bears S 14° E, 1.715 chs. dist., mkd. N 1/16 S25 BT.</p> <p>Cor. is located 30 lks. W of a N and S fence.</p>	
40.76		<p>The cor. of secs. 23, 24, 25 and 26, monumented with a mound of earth, with the remains of a cedar post, 4 ins. diam., 3 ft. long, lying alongside, illegible scribe marks on one side, from which an original bearing tree</p> <p>A fallen ponderosa pine, 32 ins. diam., bears N 38 1/2° E, 70 lks. dist., mkd. T12NR18E S24 BT.</p>	



Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E S23   S24 S26   S25 1981</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S 75° E, 33 lks. dist., mkd. T12N R18E S25 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N 18° W, 84 lks. dist., mkd. T12N R18E S23 BT.</p> <p>From the cor., a fence cor. bears S 5° W, 28 lks. dist.; fences extend N, S and W.</p>	
	<p>N 0°51' W, bet. secs. 23 and 24.</p>	
	<p>Over rolling land, through dense juniper and scattered pinyon and ponderosa pine.</p>	
40.80	<p>Point for the ¼ sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E ¼ S23   S24 1981</p> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears N 19° E, 48 lks. dist., fences extend N, E, and S.</p>	
81.60	<p>Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 28 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E S14   S13 S23   S24 1981</p> <p>Cor. is located 62 lks. W of a N-S fence.</p>	
	<p>From the cor. of secs. 13, 18, 19 and 24, on the E bdy. of the Tp., hereinbefore described.</p>	
	<p>N 89°18' W, bet. secs. 13 and 24.</p>	

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
39.57	<p>Over mildly rolling hills, with area ranging from railed to dense juniper.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 28 ins. in the ground, in a mound of stone, <math>2\frac{1}{2}</math> ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E <math>\frac{1}{4}</math> S13 S24 1981</p> <p>from which</p> <p style="padding-left: 40px;">A pinyon, 8 ins. diam., bears N <math>42^\circ</math> E, 58.5 lks. dist., mkd. <math>\frac{1}{4}</math> S13 BT.</p> <p style="padding-left: 40px;">A fence cor., bears S <math>77^\circ</math> E, 1.98 chs. dist., fences extend S and W.</p>
79.15	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/> <p>N <math>0^\circ 31'</math> E, bet. secs. 13 and 14.</p> <p>Over rolling hills, with dense juniper, scattered pinyon and ponderosa pine.</p>
40.80	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 24 ins. in the ground, in a mound of stone, <math>2\frac{1}{2}</math> ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E <math>\frac{1}{4}</math> S14   S13 1981</p> <p>Cor. is located 18 lks. W of a N and S fence.</p>
81.60	<p>The cor. of secs. 11, 12, 13 and 14, monumented with a mound of stone, <math>1\frac{1}{2}</math> ft. base, alongside of which was lying a juniper post, 4 ft. long, squared, with illegible scribe marks.</p> <p>At the cor. point in the center of the mound</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, in a mound of stone, <math>2\frac{1}{2}</math> ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E S11   S12 S14   S13 1981</p> <p>from which</p>

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>A fence cor., bears S 6° W, 1.37 chs. dist., fence extends E, S and W.</p> <p>The juniper post was placed in the mound of stone alongside the cor.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E bdy. of the Tp., hereinbefore described.</p> <p>N 87°52' W, bet. secs. 12 and 13.</p> <p>Through a valley of dense to scattered juniper.</p> <p>19.72 Point for the E 1/16 sec. cor. of secs. 12 and 13.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E E 1/16 <math>\frac{S12}{S13}</math> 1981</p> <p>from which</p> <p>A fence cor., bears N 60° W, 41 lks. dist., fences extend E, S and W.</p>	
	<p>39.44 Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12NR18E 1/4 <math>\frac{S12}{S13}</math> 1981</p> <p>from which</p> <p>A fence cor., bears S 62° W, 81 lks. dist., fences extend N, E, S and W.</p>	
	<p>78.88 The cor. of secs. 11, 12, 13 and 14.</p>	
	<hr/> <p>N 0°51' W, bet. secs. 11 and 12.</p> <p>Through dense juniper.</p> <p>39.80 Point for the 1/4 sec. cor. of secs. 11 and 12, at pro- portionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E 1/4 S11   S12 1982</p>	

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>from which</p> <p>A juniper, 5 ins. diam., bears N <math>55\frac{3}{4}^{\circ}</math> E, 28 lks. dist., mkd. <math>\frac{1}{4}</math> S12 BT.</p> <p>A pinyon, 12 ins. diam., bears S <math>11\frac{3}{4}^{\circ}</math> W, 88 lks. dist., mkd. <math>\frac{1}{4}</math> S11 BT.</p> <p>79.60 Point for the cor. of secs. 1, 2, 11 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>T12N R18E S 2   S 1 S11   S12 1982</p> </div> <p>from which</p> <p>A pinyon, 8 ins. diam., bears N <math>10\frac{3}{4}^{\circ}</math> E, 35.5 lks. dist., mkd. T12N R18E S1 BT.</p> <p>A pinyon, 9 ins. diam., bears S <math>26^{\circ}</math> W, 46.5 lks. dist., mkd. T12N R18E S11 BT.</p> <p>A juniper, 12 ins. diam., bears N <math>24\frac{3}{4}^{\circ}</math> W, 45 lks. dist., mkd. T12N R18E S2 BT.</p>	
	<p>From the cor. of secs. 1, 6, 7 and 12, on the E bdy. of the Tp., hereinbefore described.</p> <p>Over gently rolling land.</p> <p>N <math>88^{\circ}26'</math> W, bet. secs. 1 and 12.</p> <p>40.21 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>T12N R18E <math>\frac{1}{4}</math> S 1 S12 1982</p> </div> <p>from which</p> <p>A juniper, 7 ins. diam., bears S <math>56\frac{1}{2}^{\circ}</math> W, 52.5 lks. dist., mkd. <math>\frac{1}{4}</math> S12 BT.</p> <p>A juniper, 12 ins. diam., bears N <math>45^{\circ}</math> W, 65.5 lks. dist., mkd. <math>\frac{1}{4}</math> S1 BT.</p>	
	<p>80.42 The cor. of secs. 1, 2, 11 and 12.</p> <hr/> <p>N <math>2^{\circ}02'</math> W, bet. secs. 1 and 2.</p> <p>Over gently rolling land, through dense juniper.</p> <p>5.20 Highway No. 277, asphalt surfaced, bears N <math>85^{\circ}</math> E and S <math>85^{\circ}</math> W.</p>	

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

39.82

Point for the  $\frac{1}{4}$  sec. cor. of secs. 1 and 2, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 24 ins. in the ground, with cap mkd.

T12N R18E

$\frac{1}{4}$   
S 2 | S 1  
1982

from which

A juniper, 8 ins. diam., bears S 40° E,  
97 lks. dist., mkd.  $\frac{1}{4}$  S1 BT.

A juniper, 4 ins. diam., bears S 14° W,  
59.5 lks. dist., mkd. X at breast height and  
BT at base.

42.17

Point for the closing cor. of secs. 1 and 2, only, at proportionate dist. on the Third Stan. Parallel North; there is no remaining evidence of the original cor.

Set an aluminum post, 28 ins. long, 1 in. diam., 16 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.

T13N R18E

S36  
S 2 | S 1  
T12N | R18E  
C C  
1982

from which

A pinyon, 9 ins. diam., bears S 88° E,  
78 lks. dist., mkd. T12N R18E S1 CC BT.

A pinyon, 8 ins. diam., bears S 14° W,  
45 lks. dist., mkd. T12N R18E S2 CC BT.

From this cor., the stan.  $\frac{1}{4}$  sec. cor. of sec. 36,  
T 13 N, R 18 E, bears N 89°24' E, 18.32 chs. dist.,  
hereinbefore described.

From the cor. of secs. 2, 3, 34 and 35, on the S bdy.  
of the Tp., monumented with an iron post, 2 $\frac{1}{2}$  ins.  
diam., projecting 6 ins. above ground, with brass cap  
mkd. as described in the official record of the 1977  
resurvey, from which the accessories recorded in 1977

A ponderosa pine, 7 ins. diam., bears N 22° E  
42 lks. dist., mkd. T12N R18E S35 BT.

A ponderosa pine, 9 ins. diam., bears S 50° E  
42 lks. dist., mkd. T11N R18E S2 BT.

A ponderosa pine, 9 ins. diam., bears S 38 $\frac{1}{2}$ ° W,  
41 lks. dist., mkd. T11N R18E S3 BT.

An open end pipe, projecting 18 ins. above a mound  
of stone, 1 $\frac{1}{2}$  ft. base, 6 ins. high, bears  
S 51° W, 94 lks. dist.

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>A dead pine, 32 ins. diam., bears S 63½° W, 205 lks. dist., mkd. T11N R18E S3 BT.</p> <p>A ponderosa pine, 8 ins. diam., bears N 62½° W, 47 lks. dist., mkd. T12N R18E S34 BT.</p> <p>N 0°54' E, bet. secs. 34 and 35.</p> <p>Through medium timber.</p> <p>40.66 The ¼ sec. cor. of secs. 34 and 35, monumented with an unmarked sandstone, 21 x 12 x 6 ins. in a mound of stone, 2½ ft. base, ½ ft. high.</p> <p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 22 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E ¼ S34   S35 1981</p> <p>from which</p> <p>A ponderosa pine, 10 ins. diam., bears S 29° E, 71 lks. dist., mkd. ¼ S35 BT.</p> <p>A pinyon, 8 ins. diam., bears N 73° W, 37 lks. dist., mkd. ¼ S34 BT.</p> <p>Bury the stone in the mound of stone.</p> <p>Cor. is located 46 lks. S of a fence, bears E and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°33' E, beginning new measurement.</p>	
0.80	Powerline and access road, bears S 85° E and N 85° W.	
19.59	<p>Point for the N 1/16 sec. cor. of secs. 34 and 35.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E N 1/16 S34   S35 1981</p> <p>from which</p> <p>A ponderosa pine, 6 ins. diam., bears S 39° E, 34.5 lks. dist., mkd. N 1/16 S35 BT.</p> <p>A ponderosa pine, 7 ins. diam., bears N 83° W, 66 lks. dist., mkd. N 1/16 S34 BT.</p> <p>Cor. is approximately 1 ch. N of a wash, 50 lks. wide, 4 ft. deep drains S 65° E.</p> <p>29.385 Point for the N-N 1/64 sec. cor. of secs. 34 and 35; not monumented.</p>	

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

39.18

The cor. of secs. 26, 27, 34 and 35, monumented with a mound of stone, 2 ft. base, 6 ins. high, from which an original bearing tree

A rotted pine, 14 ins. diam., bears S 9° W,  
46 lks. dist., mkd. T12N R18E S34 BT.  
(Record: S 20° W)

At the cor. point

Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.

T12N	R18E
S27	S26
S34	S35
1981	

from which new bearing trees

A ponderosa pine, 8 ins. diam., bears N 33° E,  
42.5 lks. dist., mkd. T12N R18E S26 BT.

An alligator juniper, 18 ins. diam., bears  
S 49° E, 1.25 chs. dist., mkd. T12N R18E  
S35 BT.

A ponderosa pine, 10 ins. diam., bears  
S 78° W, 76 lks. dist., mkd. T12N R18E  
S34 BT.

A ponderosa pine, 11 ins. diam., bears  
N 32° W, 86 lks. dist., mkd. T12N R18E  
S27 BT.

From the cor. of secs. 25, 26, 35 and 36.

N 89°48' W, bet. secs. 26 and 35.

Over rolling land, through dense juniper and pinyon pine.

20.38

Point for the E 1/16 sec. cor. of secs. 26 and 35.

Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.

T12N	R18E
E 1/16	S26
	S35
1981	

from which

A ponderosa pine, 14 ins. diam., bears S 42° E,  
57 lks. dist., mkd. E 1/16 S35 BT.

A ponderosa pine, 12 ins. diam., bears N 36° W,  
58 lks. dist., mkd. E 1/16 S26 BT.

35.35

Fence bears N and S.

35.665

Point for the W-W-E 1/256 sec. cor. of secs. 26 and 35.

Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">S26 W-W-E 1/256 S35 1981</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 4 ins. diam., bears N 83° E, 40 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S 30° E, 73 lks. dist., mkd. W W E 1/256 S35 BT.</p>	
40.76	<p>Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E 1/4 <math>\frac{S26}{S35}</math> 1981</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, N of cor.</p> <p>Set a steel fence post alongside the cor.</p>	
41.90	<p>Wash, drains N 60° W.</p>	
50.95	<p>Point for the E-W 1/64 sec. cor. of secs. 26 and 35, not monumented.</p>	
61.14	<p>Point for the W 1/16 sec. cor. of secs. 26 and 35.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E W 1/16 <math>\frac{S26}{S35}</math> 1981</p> <p>Cor. is located 90 lks. N of a wash, 30 lks. wide, 4 ft. deep, drains easterly.</p>	
70.05	<p>Fence, bears N 40° E and S 40° W.</p>	
71.33	<p>Point for the W-W 1/64 sec. cor. of secs. 26 and 35.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S26 W-W 1/64 S35 1981</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears S 49° W, 72 lks. dist., mkd. W W 1/64 S35 BT.</p>	



Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>A ponderosa pine, 14 ins. diam., bears N 64° W, 23.5 lks. dist., mkd. W W 1/64 S26 BT.</p>	
80.50	<p>Enter rolling hills, with dense juniper and pinyon pine.</p>	
81.52	<p>The cor. of secs. 26, 27, 34 and 35.</p>	
	<p>N 0°14' E, bet. secs. 26 and 27.</p>	
	<p>Through medium timber.</p>	
10.15	<p>Point for the S-S 1/64 sec. cor. of secs. 26 and 27; not monumented.</p>	
20.30	<p>Point for the S 1/16 sec. cor. of secs. 26 and 27.</p>	
	<p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with cap mkd.</p>	
	<p style="text-align: center;">T12N R18E S 1/16 S27   S26 1981</p>	
	<p>from which</p>	
	<p>A pinyon pine, 8 ins. diam., bears S 55° E, 54 lks. dist., mkd. S 1/16 S26 BT.</p>	
	<p>A pinyon pine, 8 ins. diam., bears N 68° W, 86 lks. dist., mkd. S 1/16 S27 BT.</p>	
40.60	<p>Point for the 1/4 sec. cor. of secs. 26 and 27, at pro- portionate dist.; there is no remaining evidence of the original cor.</p>	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p>	
	<p style="text-align: center;">T12N R18E 1/4 S27   S26 1981</p>	
	<p>from which</p>	
	<p>A juniper, 16 ins. diam., bears N 51° E, 87 lks. dist., mkd. 1/4 S26 BT.</p>	
	<p>A juniper, 14 ins. diam., bears S 39° W, 17.5 lks. dist., mkd. 1/4 S27 BT.</p>	
81.20	<p>Point for the cor. of secs. 22, 23, 26 and 27, at pro- portionate dist.; there is no remaining evidence of the original cor.</p>	

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 20 ins. in the ground, in a mound of stone and earth, 4 ft. base, 10 ins. high, with cap mkd.</p> <p style="text-align: center;">T12N R18E S22   S23 S27   S26 1981</p> <p>from which</p> <p style="text-align: center;">An old leaning fence cor. post bears S 48° E, 46 lks. dist., fence extends S and E.</p>	
20.39	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N 89°34' W, bet. secs. 23 and 26.</p> <p>Through dense timber, along N side of a fence.</p> <p>Point for the E 1/16 sec. cor. of secs. 23 and 26, falls in a wash, 70 lks. wide, 4 to 8 ft. deep, drains S 15° E.</p> <p>Set an aluminum post, 72 ins. long, <math>\frac{3}{4}</math> in. diam., 66 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E E 1/16 S23 S26 1981</p> <p>from which</p> <p style="text-align: center;">A ponderosa pine, 8 ins. diam., bears N 40° E, 70.5 lks. dist., mkd. E 1/16 S23 BT.</p> <p style="text-align: center;">A ponderosa pine, 8 ins. diam., bears N 8° W, 1.33 chs. dist., mkd. X at breast height and BT at base.</p>	
40.78	<p>Cor. is located 41 lks. N of an E and W fence.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 26 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E <math>\frac{1}{4}</math> S23 S26 1981</p> <p>from which</p> <p style="text-align: center;">A fence cor., bears S 36° E, 98 lks. dist., fences extend E and S.</p> <p style="text-align: center;">A juniper, 4 ins. diam., bears S 80° W, 91.5 lks. dist., mkd. X at breast height, and BT at base.</p>	

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
81.57	<p>An alligator juniper, 8 ins. diam., bears N 3° W, 1.765 chs. dist., mkd. <math>\frac{1}{4}</math> S23 BT.</p> <p>The cor. of secs. 22, 23, 26 and 27.</p>	
40.60	<p>N 0°37' E, bet. secs. 22 and 23.</p> <p>Over rolling hills, with dense juniper and pine.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 22 and 23, monumented with a mound of stone, 1<math>\frac{1}{2}</math> ft. base, and the remains of a wood post lying alongside, 3<math>\frac{1}{2}</math> ft. long, 3 ins. diam., no marks visible.</p> <p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E <math>\frac{1}{4}</math> S22   S23 1981</p> <p>Bury the wooden post in the mound of stone.</p>	
20.32	<p>N 0°08' W, beginning new measurement.</p> <p>Point for the N 1/16 sec. cor. of secs. 22 and 23.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 31 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E N 1/16 S22   S23 1983</p>	
30.48	<p>Set a steel fence post alongside the cor.</p> <p>Point for the N-N 1/64 sec. cor. of secs. 22 and 23.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 29 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">N-N 1/64 S22   S23 1983</p>	
35.56	<p>Set a steel fence post alongside the cor.</p> <p>Point for the N-N-N 1/256 sec. cor. of secs. 22 and 23.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">N-N-N 1/256 S22   S23 1983</p>	

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
40.64	<p>Set a steel fence post alongside the cor.</p> <p>Point for the cor. of secs. 14, 15, 22 and 23, at proportionate dist. falls in graded road No. 332; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 6 ins. below the road's surface, with cap mkd.</p> <div style="text-align: center;"> <p>T12N R18E S15   S14 S22   S23 1983</p> </div> <p>from which</p> <p>An aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., set 32 ins. in the ground, for a reference monument, bears S <math>83^{\circ}</math> W, 33.00 ft. dist., with cap mkd. T12N R18E S22 RM 33.00 FT. 1983, and an arrow pointing to the cor.</p> <p>A fence cor. post, bears N <math>21^{\circ}</math> W, 1.40 chs. dist., fences extend N and W.</p> <p>An aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., set 31 ins. in the ground, for a reference monument, bears N <math>5^{\circ}</math> W, 32.80 ft. dist., with cap mkd. T12N R18E S15 RM 32.80 FT, 1983, and an arrow pointing to the cor.</p> <p>Cor. is 10 lks. W of the center of road No. 332, which is 44 lks. wide and bears N <math>35^{\circ}</math> E and S <math>35^{\circ}</math> W.</p>	
39.39	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N <math>88^{\circ}32'</math> W, bet. secs. 14 and 23.</p> <p>Over mildly rolling hills, with railed areas.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 14 and 23, monumented with a mound of stone, <math>1\frac{1}{2}</math> ft. base, with remains of an old cedar post, 30 ins. long, 3 ins. diam., lying alongside, no marks visible, from which the remains of an original bearing tree</p> <p>A stump hole, bears S <math>10^{\circ}</math> W, 57 lks. dist., a badly rotted pine lying on the ground alongside is mkd. BT. (Record calls for a juniper)</p> <p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

T12N R18E

$\frac{1}{4}$  S14

S23

1981

from which a new bearing tree

A pinyon, 10 ins. diam., bears N 2° W, 43.5  
lks. dist., mkd.  $\frac{1}{4}$  S14 BT.

S 88°57' W, beginning new measurement.

Over gently rolling land, through medium to dense  
juniper and scattered pinyon.

40.73 The cor. of secs. 14, 15, 22 and 23.

N 0°25' W, bet. secs. 14 and 15.

Over rolling hills, through dense timber.

40.65 Point for the  $\frac{1}{4}$  sec. cor. of secs. 14 and 15, at pro-  
portionate dist.; there is no remaining evidence of the  
original cor.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 32 ins.  
in the ground, with cap mkd.

T12N R18E

$\frac{1}{4}$

S15 | S14

1983

Set a steel fence post alongside the cor.

Cor. is located 67 lks. E of a N and S fence.

81.30 The cor. of secs. 10, 11, 14 and 15, monumented with a  
mound of sandstone, 2 ft. base, 6 ins. high.

At the cor. point

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 26 ins.  
in the ground, in a mound of stone, 2 $\frac{1}{2}$  ft. base, 6 ins.  
high, with cap mkd.

T12N R18E

S10 | S11

S15 | S14

1982

Set a steel fence post alongside the cor.

Cor. is located 26.5 lks. N of an E and W fence.

N 0°09' W, bet. secs. 10 and 11.

Through scattered juniper.

19.895 Point for the S 1/16 sec. cor. of secs. 10 and 11.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 30 ins.  
in the ground, with cap mkd.

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T12N R18E S 1/16 S10   S11 1982</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears S 21° E, 11.5 lks. dist., mkd. S 1/16 S11 BT.</p> <p>Cor. is located 6 lks. W of a N-S fence.</p>
39.79	<p>Point for the ¼ sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, in a mound of stone, 1½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E ¼ S10   S11 1982</p> <p>from which</p> <p style="padding-left: 40px;">A juniper 4 ins. diam., bears N 18¾° E, 64 lks. dist., mkd. X at breast height and BT at base.</p> <p>Cor. is located 3 lks. E of a N-S fence.</p>
79.58	<p>Point for the cor. of secs. 2, 3, 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 26 ins. in the ground, in a mound of stone, 3 ft. base, to top with cap mkd.</p> <p style="text-align: center;">T12N R18E S 3   S 2 S10   S11 1982</p> <p>Cor. is located 1 lk. W of a N-S fence.</p> <p>From this point, the point for the U.S.C. &amp; G.S. triangulation station "DECKER", determined from its reference monuments, bears N 61°44'32" E, (forward bearing), 288.76 chs. dist.</p>
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N 89°57' W, bet. secs. 2 and 11.</p> <p>Through sparse juniper.</p>
40.21	<p>Fence, bears N 20° E and S 20° W.</p>
40.29	<p>Point for the ¼ sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, with cap mkd.</p>

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T12N R18E  <math>\frac{1}{4}</math> <math>\frac{S 2}{S11}</math>                      1982</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears N 34½° E, 47.5 lks. dist., mkd. ¼ S2 BT.</p> <p style="padding-left: 40px;">A pinyon, 14 ins. diam., bears S 36½° E, 1.06 chs. dist., mkd. ¼ S11 BT.</p> <p>Cor. is 92 lks. S of a right-of-way fence, bearing E and W, and 2.44 chs. S of the center of Highway No. 277, asphalt surfaced, bears E and W.</p>
60.435	<p>Point for the W 1/16 sec. cor. of secs. 2 and 11.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E                      W 1/16 <math>\frac{S 2}{S11}</math>                      1982</p> <p>Cor. is located 86 lks. S of a highway right-of-way fence, bears E and W, and 2.37 chs. S of the center of Highway No. 277, asphalt surfaced, bears E and W.</p>
80.58	<p>The cor. of secs. 2, 3, 10 and 11.</p>
	<p>N 1°48' W, bet. secs. 2 and 3.</p> <p>Through sparse juniper.</p>
0.80	<p>Right-of-way fence, bears E and W.</p>
2.30	<p>Highway No. 277, asphalt surfaced, bears E and W.</p>
19.905	<p>Point for the S 1/16 sec. cor. of secs. 2 and 3.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 18 ins. in the ground, in a mound of stone, 2½ ft. base, to top with cap mkd.</p>
	<p style="text-align: center;">T12N R18E                      S 1/16                      S 3   S 2                      1982</p> <p>Cor. is located 77 lks. W of a N-S fence.</p>
39.81	<p>Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, with cap mkd.</p>
	<p style="text-align: center;">T12N R18E  <math>\frac{1}{4}</math> S 3   S 2                      1981</p>

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
41.37	<p>Point for the closing cor. of secs. 2 and 3 only, at proportionate dist. on the Third Stan. Parallel North; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 26 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T13N R18E S35 ----- S 3   S 2 C C T12N R18E 1981</p> <p>Cor. is located 25 lks. S of an abandoned E-W fence.</p> <p>From this point a fence cor., bears N 77° E 1.475 chs. dist., fences extend N 45° E, S and W.</p> <p>From this same point, the stan. <math>\frac{1}{4}</math> sec. cor. of sec. 35, T 13 N, R 18 E, bears N 89°21' E, 17.92 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S bdy. of the Tp., monumented with an iron post, 2<math>\frac{1}{2}</math> ins. diam., projecting 10 ins. above ground, in a mound of stone, 1<math>\frac{1}{2}</math> ft. base, 6 ins. high, with brass cap mkd. as described in the official record of the 1977 resurvey.</p> <p>from which</p> <ul style="list-style-type: none"> <li>A ponderosa pine, 6 ins. diam., bears N 60<math>\frac{1}{2}</math>° E, 72 lks. dist., mkd. T12N R18E S34 BT.</li> <li>A ponderosa pine, 5 ins. diam., bears S 50° E, 23 lks. dist., mkd. T11N R18E S3 BT.</li> <li>A ponderosa pine, 6 ins. diam., bears S 34<math>\frac{1}{2}</math>° W, 60 lks. dist., mkd. T11N R18E S4 BT.</li> <li>A ponderosa pine, 6 ins. diam., bears N 53<math>\frac{1}{2}</math>° W, 73 lks. dist., mkd. T12N R18E S33 BT.</li> </ul> <p>Cor. is in a fence cor., fences extend N and W, with an abandoned fence E.</p> <p>N 0°05' E, bet. secs. 33 and 34.</p> <p>Over rolling hills, through dense timber of juniper, pinyon and ponderosa pine, along a fence.</p>
40.20	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E <math>\frac{1}{4}</math> S33   S34 1981</p> <p>from which</p>



Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

- 80.40 A juniper, 16 ins. diam., bears S 21° E, 66.5 lks. dist., mkd.  $\frac{1}{4}$  S34 BT.  
Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.  
Cor. is located 1.15 chs. E of a N and S fence.  
Point for the cor. of secs. 27, 28, 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.  
Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.
- |      |      |
|------|------|
| T12N | R18E |
| S28  | S27  |
| S33  | S34  |
| 1981 |      |
- from which  
A fence cor., bears N 88° W, 2.415 chs. dist.
- 
- 40.73 From the cor. of secs. 26, 27, 34 and 35.  
S 89°47' W, bet. secs. 27 and 34.  
Over rolling land, through dense timber of alligator juniper, pinyon pine and ponderosa pine.  
The  $\frac{1}{4}$  sec. cor. of secs. 27 and 34, monumented with a mound of stone, 1 ft. base, 5 ins. high, from which the remains of an original bearing tree  
A stump hole bears N 20° E, 1.23 chs. dist., a badly rotted juniper lying alongside is mkd.  $\frac{1}{4}$  S.  
At the cor. point  
Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, 2 $\frac{1}{2}$  ft. base, to top, with cap mkd.
- |                   |      |
|-------------------|------|
| T12N              | R18E |
| $\frac{1}{4}$ S27 |      |
| S34               |      |
| 1981              |      |
- from which a new bearing tree  
A juniper, 15 ins. diam., bears S 61° W, 2.39 chs. dist., mkd.  $\frac{1}{4}$  S34 BT.
- 
- 40.17 N 89°13' W, beginning new measurement.  
The cor. of secs. 27, 28, 33 and 34.
- 
- 20.10 N 0°04' W, bet. secs. 27 and 28.  
Through dense timber of juniper, alligator juniper, pinyon and ponderosa pine.  
Point for the S 1/16 sec. cor. of secs. 27 and 28.

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 28 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E S 1/16 S28   S27 1981</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears N <math>67\frac{1}{2}^\circ</math> E, 94 lks. dist., mkd. S 1/16 S27 BT.</p> <p style="padding-left: 40px;">A juniper, 13 ins. diam., bears N <math>45\frac{3}{4}^\circ</math> W, 95.5 lks. dist., mkd. S 1/16 S28 BT.</p>	
40.20	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 22 ins. in the ground, in a mound of stone, <math>2\frac{1}{2}</math> ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E <math>\frac{1}{4}</math> S28   S27 1981</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 16 ins. diam., bears S <math>44\frac{1}{2}^\circ</math> E, 89.5 lks. dist., mkd. <math>\frac{1}{4}</math> S27 BT.</p>	
60.30	<p>Point for the N 1/16 sec. cor. of secs. 27 and 28.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, in a mound of stone, <math>1\frac{1}{2}</math> ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E N 1/16 S28   S27 1981</p> <p>from which</p> <p style="padding-left: 40px;">A pinyon, 12 ins. diam., bears S <math>46^\circ</math> E, 34.5 lks. dist., mkd. N 1/16 S27 BT.</p>	
80.40	<p>The cor. of secs. 21, 22, 27 and 28, determined from an original bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 32 ins. diam., bears N <math>30^\circ</math> E, 54 lks. dist., mkd. T12N R18E S22 BT.</p> <p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E S21   S22 S28   S27 1981</p>	

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

from which a new bearing tree

A ponderosa pine, 14 ins. diam., bears N 48° E,  
2.00 chs. dist., mkd. T12N R18E S22 BT.

Cor. is located at the W edge of a wash, 50 lks. wide,  
4 to 10 ft. deep, drains N 25° E.

From the cor. of secs. 22, 23, 26 and 27.

S 89°49' W, bet. secs. 22 and 27.

Over rolling hills, through scattered to dense juniper.

40.635

Point for the 1/4 sec. cor. of secs. 22 and 27, at pro-  
portionate dist.; there is no remaining evidence of the  
original cor.

Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins.  
in the ground, with cap mkd.

T12N R18E  
1/4 S22  
S27  
1981

50.794

Point for the E-W 1/64 sec. cor. of secs. 22 and 27.

Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins.  
in the ground, with cap mkd.

S22  
E-W 1/64  
S27  
1983

Set a steel fence post alongside the cor.

60.953

Point for the W 1/16 sec. cor. of secs. 22 and 27.

Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins.  
in the ground, in a mound of stone, 2 ft. base, to top,  
with cap mkd.

T12N R18E  
W 1/16 S22  
S27  
1981

from which

A pinyon, 5 ins. diam., bears N 75° E, 30  
lks. dist., mkd. W 1/16 S22 BT.

An alligator juniper, 12 ins. diam., bears  
S 73° W, 33 lks. dist., mkd. W 1/16 S27 BT.

Cor. is located 20 lks. N of an abandoned fence,  
extends E and W.

81.270

The cor. of secs. 21, 22, 27 and 28.

N 0°12' W, bet. secs. 21 and 22.

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	Over level terrain, through scattered timber.	
15.27	Point for the N-S-S 1/256 sec. cor. of secs. 21 and 22.	
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, with cap mkd.	
	N-S-S	
	1/256	
	S21   S22	
	1983	
	from which	
	A ponderosa pine, 9 ins. diam., bears S 22° W,	
	96.5 lks. dist., mkd. N S S 1/256 S21 BT.	
	Set a steel fence post alongside the cor.	
	Cor. is located 92 lks. N of an E and W fence.	
20.36	Point for the S 1/16 sec. cor. of secs. 21 and 22.	
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, with cap mkd.	
	T12N R18E	
	S 1/16	
	S21   S22	
	1983	
	Set a steel fence post alongside the cor.	
30.54	Point for the N-S 1/64 sec. cor. of secs. 21 and 22.	
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, with cap mkd.	
	N-S	
	1/64	
	S21   S22	
	1983	
	Set a steel fence post alongside the cor.	
40.72	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 32 ins. in the ground, with cap mkd.	
	T12N R18E	
	$\frac{1}{4}$	
	S21   S22	
	1983	
	from which	
	A juniper, 8 ins. diam., bears S 44° E,	
	78 lks. dist., mkd. $\frac{1}{4}$ S22 BT.	

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

Set a steel fence post alongside the cor.

Cor. is located 44 lks. S of an E and W fence.

50.90 Point for the S-N 1/64 sec. cor. of secs. 21 and 22.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 32 ins. in the ground, with cap mkd.

S-N  
1/64  
S21 | S22  
1983

Set a steel fence post alongside the cor.

55.99 Point for the N-S-N 1/256 sec. cor. of secs. 21 and 22.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 32 ins. in the ground, with cap mkd.

N-S-N  
1/256  
S21 | S22  
1983

from which

A ponderosa pine, 8 ins. diam., bears S 10° E,  
2.19 chs. dist., mkd. N S N 1/256 S22 BT.

Set a steel fence post alongside the cor.

61.08 Point for the N 1/16 sec. cor. of secs. 21 and 22.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 24 ins. in the ground, in a mound of stone, 2 ft. base, 1 ft. high, with cap mkd.

T12N R18E  
N 1/16  
S21 | S22  
1983

Set a steel fence post alongside the cor.

71.26 Point for the N-N 1/64 sec. cor. of secs. 21 and 22.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 32 ins. in the ground, with cap mkd.

N-N  
1/64  
S21 | S22  
1983

Set a steel fence post alongside the cor.

81.44 The cor. of secs. 15, 16, 21 and 22, monumented with a mound of stone, 1½ ft. base, 6 ins. high.

At the cor. point.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 28 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T12N R18E S16   S15 S21   S22 1981</p> <p>from which</p> <p style="text-align: center;">A fence cor., bears N 42° E, 63 lks. dist., fences extend N and E.</p> <p>Cor. is in a railed area.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S 89°56' W, bet. secs. 15 and 22.</p> <p>Over open, hilly terrain.</p>
5.118	<p>Point for the E-E-E 1/256 sec. cor. of secs. 15 and 22.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S15 E-E-E 1/256 S22 1983</p> <p>Set a steel fence post alongside the cor.</p>
10.235	<p>Point for the E-E 1/64 sec. cor. of secs. 15 and 22.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S15 E-E 1/64 S22 1983</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 1.15 chs. S of an E and W fence.</p>
20.47	<p>Point for the E 1/16 sec. cor. of secs. 15 and 22.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E E 1/16 S15 S22 1983</p> <p>Set a steel fence post alongside the cor.</p>
40.94	<p>Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E 1/4 S15 S22 1983</p>

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
61.415	<p>Cor. is located 93 lks. S of an E and W fence.</p> <p>Point for the W 1/16 sec. cor. of secs. 15 and 22.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E W 1/16 <math>\frac{S15}{S22}</math> 1983</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 10 ins. diam., bears S <math>45\frac{1}{2}^\circ</math> E, 1.11 chs. dist., mkd. W 1/16 S22 BT.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 15.5 lks. W of a N and S fence.</p>	
71.653	<p>Point for the W-W 1/64 sec. cor. of secs. 15 and 22.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S15 W-W 1/64 S22 1983</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 63.5 lks. S of an E and W fence.</p>	
81.89	<p>The cor. of secs. 15, 16, 21 and 22.</p> <hr/> <p>N <math>0^\circ 01'</math> W, bet. secs. 15 and 16.</p> <p>Over gently rolling land, through medium to dense juniper.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 15 and 16, determined at record bearing and dist. from an original bearing tree</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears S <math>63^\circ</math> E, 96 lks. dist., mkd. <math>\frac{1}{4}</math> S BT, tree is partially dead.</p> <p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 29 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E <math>\frac{1}{4}</math> S16   S15 1981</p> <p>Cor. falls in railed area 57 lks. W of an abandoned fence line, bears N and S.</p> <hr/> <p>N <math>1^\circ 05'</math> E, beginning new measurement.</p>	
40.19	<p>Point for the cor. of secs. 9, 10, 15 and 16, at proportionate dist.; there is no remaining evidence of the original cor.</p>	

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E S 9   S10 S16   S15 1982</p> <p>from which</p> <p>A pinyon, 6 ins. diam., bears N <math>4\frac{3}{4}^{\circ}</math> E, 99 lks. dist., mkd. T12N R18E S10 BT.</p> <p>A juniper, 8 ins. diam., bears S <math>54\frac{1}{4}^{\circ}</math> E, 59 lks. dist., mkd. T12N R18E S15 BT.</p> <p>A juniper, 4 ins. diam., bears N <math>34^{\circ}</math> W, 1.05 chs. dist., mkd. X at breast height and BT at base.</p> <p>Cor. is located 6 lks. E of an abandoned fence, bears N and S, and 46 lks. S of a fence, bears E and W.</p> <p>From this point, the cor. of secs. 7, 8, 17 and 18, bears N <math>89^{\circ}59'</math> W, 161.56 chs. dist., hereinafter described.</p> <p>The control line was fully retraced and no evidence of the intervening cors. was found.</p>	
	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S <math>89^{\circ}37'</math> W, bet. secs. 10 and 15.</p> <p>Through dense juniper, along a fence line.</p>	
9.76	<p>Point selected for the witness E-E 1/64 sec. cor. of secs. 10 and 15.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, in a mound of stone, 1 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">WC E-E 1/64 ← <math>\frac{S10}{S15}</math> 1982</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 47 lks. N of an E and W fence.</p>	
10.06	<p>True point for the E-E 1/64 sec. cor. of secs. 10 and 15, falls in a wash, 90 lks. wide, 4 ft. deep, drains N <math>5^{\circ}</math> W, impracticable to monument.</p>	
10.40	<p>Center of wash described above.</p>	
20.12	<p>Point for the E 1/16 sec. cor. of secs. 10 and 15.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 28 ins. in the ground, in a mound of stone, <math>2\frac{1}{2}</math> ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E E 1/16 <math>\frac{S10}{S15}</math> 1982</p>	



Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Cor. is located 26 lks. N of an E and W fence.</p>	
30.18	<p>Point for the W-E 1/64 sec. cor. of secs. 10 and 15.</p>	
	<p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 28 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p>	
	<p style="text-align: center;">S10 W-E 1/64 S15 1982</p>	
	<p>Cor. is located 21 lks. N of an E and W fence.</p>	
40.24	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the original cor.</p>	
	<p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">T12N R18E <math>\frac{1}{4}</math> <u>S10</u> S15 1982</p>	
	<p>from which</p>	
	<p style="text-align: center;">A juniper, 6 ins. diam., bears N <math>51\frac{3}{4}^{\circ}</math> E, 5.5 lks. dist., mkd. <math>\frac{1}{4}</math> S10 BT.</p>	
	<p>Cor. is located 9.5 lks. N of a fence, bears E and W.</p>	
80.48	<p>The cor. of secs. 9, 10, 15 and 16.</p>	
	<p>N <math>0^{\circ}19'</math> W, bet. secs. 9 and 10.</p>	
	<p>Through dense juniper.</p>	
40.19	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p>	
	<p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">T12N R18E <math>\frac{1}{4}</math> S 9   S10 1982</p>	
	<p>from which</p>	
	<p style="text-align: center;">A juniper, 5 ins. diam., bears S <math>36^{\circ}</math> E, 5 lks. dist., mkd. <math>\frac{1}{4}</math> S10 BT.</p>	
	<p style="text-align: center;">A juniper, 10 ins. diam., bears N <math>30^{\circ}</math> W, 12 lks. dist., mkd. <math>\frac{1}{4}</math> S9 BT.</p>	
80.38	<p>Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p>	
	<p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 32 ins. in the ground, with cap mkd.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

T12N R18E	
S 4   S 3	
S 9   S10	
1982	

from which

A juniper, 6 ins. diam., bears S 5° E, 63 lks.  
dist., mkd. T12N R18E S10 BT.

A juniper, 4 ins. diam., bears S 21 $\frac{3}{4}$ ° W, 75 lks.  
dist., mkd. X at breast height and BT at base.

Cor. is located 6.5 lks. dist., S of the highway No. 277 right-of-way fence, bears E and W, and 22 lks. S of a telephone line, bears E and W, and 1.78 chs. S of the center of highway No. 277, asphalt surfaced, bears E and W.

From this point, the cor. of secs. 5, 6, 7 and 8, bears N 89°24' W, 161.33 chs. dist., monumented with a sandstone, 10 x 6 x 6 ins., projecting 4 ins. above ground, in a mound of stone, 2 ft. base, 6 ins. high, stone mkd. with 5 grooves on the E and S faces; no remaining evidence of the original bearing trees.

At the cor. point

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 28 ins. in the ground, in a mound of stone, 2 $\frac{1}{2}$  ft. base, to top, with cap mkd.

T12N R18E	
S 6   S 5	
S 7   S 8	
1981	

from which

A pinyon, 9 ins. diam., bears N 60° E, 16 lks.  
dist., mkd. T12N R18E S5 BT.

A juniper, 8 ins. diam., bears S 39° E, 37.5  
lks. dist., mkd. T12N R18E S8 BT.

A pinyon, 9 ins. diam., bears S 31° W, 43 lks.  
dist., mkd. T12N R18E S7 BT.

Bury the mkd. stone alongside the aluminum post.

The control line was fully retraced and no evidence of the intervening cors. was found.

---

From the cor. of secs. 2, 3, 10 and 11.

N 89°48' W, bet. secs. 3 and 10.

Through sparse juniper.

40.33

Point for the  $\frac{1}{4}$  sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 30 ins. in the ground, with cap mkd.

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

T12N R18E

$\frac{1}{4}$  S 3  
S10

1982

from which

A juniper, 6 ins. diam., bears N  $81\frac{1}{4}^{\circ}$  E,  
96 lks. dist., mkd.  $\frac{1}{4}$  S3 BT.

Cor. is located 49 lks. S of highway No. 277,  
right-of-way fence line, bears E and W, and 70 lks. S  
of a telephone line, bears E and W, and 2.07 chs. S of  
the center line of highway No. 277, asphalt surfaced,  
bears E and W.

80.66 The cor. of secs. 3, 4, 9 and 10.

N  $1^{\circ}39'$  W, bet. secs. 3 and 4.

Through dense juniper.

40.20 Point for the  $\frac{1}{4}$  sec. cor. of secs. 3 and 4, at pro-  
portionate dist.; there is no remaining evidence of the  
original cor.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 30 ins.  
in the ground, with cap mkd.

T12N R18E

$\frac{1}{4}$   
S 4 | S 3

1981

Raise a mound of stone, 2 ft. base, 1 ft. high, W of  
cor.

40.53 Point for the closing cor. of secs. 3 and 4 only, at  
proportionate dist., on the Third Stan. Parallel North;  
there is no remaining evidence of the original cor.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 28 ins.  
in the ground, with cap mkd.

T13N R18E

S34  
S 4 | S 3

C C

T12N R18E

1981

From this point, the stan.  $\frac{1}{4}$  sec. cor. of sec. 34,  
T 13 N, R 18 E, bears N  $89^{\circ}11'$  E, 17.46 chs. dist.,  
hereinbefore described.

From the cor. of secs. 4, 5, 32 and 33, on the S bdy. of  
the Tp., monumented with an iron post,  $2\frac{1}{2}$  ins. diam.,  
projecting 10 ins. above ground, in a mound of stone, 2  
ft. base, to top, with brass cap mkd. as described in  
the official record of the 1977 dependent resurvey,  
from which bearing trees recorded in 1977

A ponderosa pine, 7 ins. diam., bears N  $54^{\circ}$  E,  
1.08 chs. dist., mkd. T12N R18E S33 BT.

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

A ponderosa pine, 10 ins. diam., bears S 59° E,  
15 lks. dist., mkd. T11N R18E S4 BT.

A pinyon, 9 ins. diam., bears S 45° W, 29  
lks. dist., mkd. T11N R18E S5 BT.

A ponderosa pine, 20 ins. diam., bears N 37½° W,  
53 lks. dist., mkd. T12N R18E S32 BT.

Cor. is located in an E-W fence.

N 0°26' W, bet. secs. 32 and 33.

Over gently rolling land, through medium timber.

10.05 Point for the S-S 1/64 sec. cor. of secs. 32 and 33.

Set an aluminum post, 36 ins. long, ¾ in. diam., 24 ins.  
in the ground, in a mound of stone, 2 ft. base, to top,  
with cap mkd.

S-S  
1/64  
S32 | S33  
1982

from which

A rebar of unknown origin, ¼ in. diam., projecting  
4 ins. above ground, bears N 5°40' E, 1.073 chs.  
dist.

A ponderosa pine, 8 ins. diam., bears S 78° W,  
46 lks. dist., mkd. S-S 1/64 S32 BT.

Cor. falls in a wash, 15 lks. wide, drains N 70° W.

17.10 Point for AP 4, lot 1, sec. 32.

Set an aluminum post, 28 ins. long, 1 in. diam., 20  
ins. in the ground, with cap mkd.

T12N R18E  
AP4 |  
LOT 1 | S33  
S32 |  
1983

20.10 Point for the S 1/16 sec. cor. of secs. 32 and 33,  
identical with AP 1, lot 1, sec. 32, intersects the  
door on the SE side of a house, 26 x 42 ft., the long  
side bears N 22° E and S 22° W, 19 lks. dist. to the SE  
cor., where it is impractical to set a permanent  
monument, from which

An aluminum post, 36 ins. long, ¾ in. diam., set  
35 ins. in the ground, for a reference  
monument, bears S 6°16' W, 56.83 ft. dist.,  
with cap mkd. T12N R18E S32 S 1/16 RM 56.83  
FT 1982, and an arrow pointing to the true point.

An aluminum post, 36 ins. long, ¾ in. diam., set  
35 ins. in the ground, for a reference  
monument, bears S 18°11' W, 53.06 ft. dist.,  
with cap mkd. T12N R18E S32 S 1/16 RM 53.06  
FT 1982, and an arrow pointing to the true point.

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

20.63 The NE side of the same house.

30.15 The N-S 1/64 sec. cor. of secs. 32 and 33, monumented with a rebar, 10 ins. long, 5/8 in. diam., projecting 4 ins. above ground, tagged PE 5047, with a steel fence post alongside, and is accepted as a careful and faithful determination of the position of the cor.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over the rebar, with brass cap mkd.

N-S  
1/64  
S32 | S33  
1982

Set a steel fence post alongside the cor.

Cor. is located in a cultivated field.

---

N 0°26' W, beginning new measurement.

10.05 The ¼ sec. cor. of secs. 32 and 33, monumented with a rebar, 5/8 in. diam., 4 ins. above ground, with an aluminum cap, 1¼ ins. diam., mkd. ¼ 32|33 5047, and is accepted as a careful and faithful reestablishment of the position of the original cor.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, over the rebar, with brass cap mkd.

T12N R18E  
¼  
S32 | S33  
1982

Set a steel fence post alongside the cor.

Cor. is located in a cultivated field.

---

N 0°27' W, beginning new measurement.

5.02 The S-S-N 1/256 sec. cor. of secs. 32 and 33, monumented with a rebar, 5/8 in. diam., projecting 3 ins. above ground, tagged PE 5047, with a steel fence post alongside, and is accepted as a careful and faithful determination of the position of the cor.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with cap mkd.

S-S-N  
1/256  
S32 | S33  
1982

from which

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A juniper, 22 ins. diam., bears N 62° W, 1.95 chs. dist., mkd. SSN 1/256 S32 BT.</p> <p>The rebar is inside the aluminum post.</p> <p>Cor. falls in a cultivated field, 1.20 chs. E of a track road, bears N 40° E and S 40° W.</p> <hr/> <p>N 0°27' W, beginning new measurement.</p>
4.20	Leave cultivated field.
5.02	<p>The S-N 1/64 sec. cor. of secs. 32 and 33, monumented with a rebar, 5/8 in. diam., tagged PE 5047, with a steel fence post alongside, and is accepted as a care- ful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S-N 1/64 S32   S33 1982</p> <p>from which</p> <p>A ponderosa pine, 16 ins. diam., bears S 8° W, 35 lks. dist., mkd. S-N 1/64 S32 BT.</p> <p>The rebar is inside the aluminum post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 1.10 chs. S of a creek 30 lks. wide, drains N 45° E, and 1.60 chs. N of a track road, bears N 50° E and S 35° W.</p> <hr/> <p>N 0°27' W, beginning new measurement.</p>
10.053	<p>Point for the N 1/16 sec. cor. of secs. 32 and 33.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E N 1/16 S32   S33 1982</p> <p>from which</p> <p>A juniper, 8 ins. diam., bears N 76° E, 61 lks. dist., mkd. N 1/16 S33 BT.</p> <p>A juniper, 10 ins. diam., bears S 79° W, 11.5 lks. dist., mkd. N 1/16 S32 BT.</p>

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

30.16 Cor. is located 22 lks. E of a N and S fence and 70 lks. N of a wash, 30 lks. wide, drains S 65° E.

The cor. of secs. 28, 29, 32 and 33, monumented with a scattered mound of stone, from which an original bearing tree

An alligator juniper stump, 20 ins. diam., bears N 41° W, 1.35 chs. dist., mkd. S29 BT.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 14 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.

T12N	R18E
S29	S28
S32	S33
1981	

from which new bearing trees

A ponderosa pine, 12 ins. diam., bears N 41° E, 1.34 chs. dist., mkd. T12N R18E S28 BT.

An alligator juniper, 4 ins. diam., bears S 61° W, 65 lks. dist., mkd. X BT at base.

An alligator juniper, 6 ins. diam., bears N 67° W, 72.5 lks. dist., mkd. T12N R18E S29 BT.

A fence cor., bears N 25° W, 44 lks. dist., fence extends E and S.

20.22 From the cor. of secs. 27, 28, 33 and 34.

S 89°34' W, bet. secs. 28 and 33.

Along a fence line, through medium timber.

Point for the E 1/16 sec. cor. of secs. 28 and 33.

Set an aluminum post, 36 ins. long, ¾ in. diam., 28 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.

T12N	R18E
E 1/16	S28
	S33
1981	

from which

A ponderosa pine, 6 ins. diam., bears N 14° E, 1.04 chs. dist., mkd. E 1/16 S28 BT.

A water tank, 2.50 chs. diam., bears N 80° E, 3.50 chs. dist.

A fence cor., bears N 89° W, 1.04 chs. dist., fence extends N and W.

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
40.44	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 2 ins. below the surface of a track road on pond bank, with cap mkd.	
	T12N R18E $\frac{1}{4}$ $\frac{S28}{S33}$ 1982	
	Cor. is located in a track road bears E and W, and 24.5 lks. S of an E and W fence.	
60.66	Point for the W $\frac{1}{16}$ sec. cor. of secs. 28 and 33.	
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.	
	T12N R18E W $\frac{1}{16}$ $\frac{S28}{S33}$ 1981	
	from which	
	A ponderosa pine, 6 ins. diam., bears N $44\frac{1}{2}^\circ$ W, 44 lks. dist., mkd. W $\frac{1}{16}$ S28 BT.	
	A fence cor., bears N $31^\circ$ W, 78 lks. dist.; fences extend N, E and W.	
80.88	The cor. of secs. 28, 29, 32 and 33.	
	N $0^\circ 39'$ W, bet. secs. 28 and 29.	
	Over rolling land, through dense juniper and scattered pine.	
20.245	Point for the S $\frac{1}{16}$ sec. cor. of secs. 28 and 29.	
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 28 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.	
	T12N R18E S $\frac{1}{16}$ S29   S28 1981	
	from which	
	An alligator juniper, 6 ins. diam., bears N $55^\circ$ E, 58 lks. dist., mkd. S $\frac{1}{16}$ S28 BT.	
31.00	Graded gravel road, bears SW and NE, curving easterly.	
40.49	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.	



Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 26 ins. in the ground, in a mound of stone,  $2\frac{1}{2}$  ft. base, to top, with cap mkd.

T12N R18E  
 $\frac{1}{4}$   
S29 | S28  
1981

80.98

The cor. of secs. 20, 21, 28 and 29, monumented with a mound of stone,  $2\frac{1}{2}$  ft. base,  $\frac{1}{2}$  ft. high.

At the cor. point

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.

T12N R18E  
S20 | S21  
S29 | S28  
1981

from which

A pinyon, 9 ins. diam., bears S  $11^\circ$  E, 26.5 lks. dist., mkd. T12N R18E S28 BT.

A pinyon, 8 ins. diam., bears S  $89^\circ$  W, 78 lks. dist., mkd. T12N R18E S29 BT.

A pinyon, 6 ins. diam., bears N  $58^\circ$  W, 64 lks. dist., mkd. T12N R18E S20 BT.

From the cor. of secs. 21, 22, 27 and 28.

N  $89^\circ 56'$  W, bet. secs. 21 and 28.

Over rolling land, through juniper, pinyon and ponderosa pine.

20.46

Point for the E 1/16 sec. cor. of secs. 21 and 28.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 28 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.

T12N R18E  
E 1/16  $\frac{S21}{S28}$   
1981

Cor. is located 10.5 lks. E of a N and S fence and 20 lks. W of a power line, bears N and S.

40.92

The  $\frac{1}{4}$  sec. cor. of secs. 21 and 28, determined from an original bearing tree

An alligator juniper, 32 ins. diam., bears S  $2\frac{1}{2}^\circ$  E, 1.40 chs. dist., mkd.  $\frac{1}{4}$  S BT.

At the cor. point

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 28 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E <math>\frac{1}{4}</math> <u>S21</u> S28 1981</p> <p>from which a new bearing tree</p> <p style="text-align: center;">A pinyon, 8 ins. diam., bears N <math>13\frac{1}{2}^{\circ}</math> E, 77 lks. dist., mkd. <math>\frac{1}{4}</math> S21 BT.</p> <hr/> <p>S <math>89^{\circ}56'</math> W, beginning new measurement.</p>	
40.79	<p>The cor. of secs. 20, 21, 28 and 29.</p> <hr/> <p>N <math>0^{\circ}01'</math> E, bet. secs. 20 and 21.</p>	
40.11	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E <math>\frac{1}{4}</math> S20   S21 1982</p> <p>from which</p> <p style="text-align: center;">A juniper, 6 ins. diam., bears East, 99.5 lks. dist., mkd. <math>\frac{1}{4}</math> S21 BT.</p> <p style="text-align: center;">A juniper, 10 ins. diam., bears S <math>62^{\circ}</math> W, 1.33 chs. dist., mkd. <math>\frac{1}{4}</math> S20 BT.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 60 lks. E of a wash, 40 lks. wide, drains N <math>15^{\circ}</math> W.</p>	
80.22	<p>The cor. of secs. 16, 17, 20 and 21, monumented with an imbedded mound of stone, 2 ft. base, 6 ins. high;</p> <p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 32 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E S17   S16 S20   S21 1981</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 1.30 chs. E of a wash, 50 lks. wide, drains N <math>15^{\circ}</math> E.</p> <hr/>	

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
40.71	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S 89°14' W, bet. secs. 16 and 21.</p> <p>Over hilly terrain, through juniper and pinyon pine.</p> <p>Point for the ¼ sec. cor. of secs. 16 and 21, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E ¼ <u>S16</u> S21 1982</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located at the edge of a cleared area, bears S 45° E and N 45° W.</p>	
81.43	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S bdy. of the Tp., monumented with an iron post, 2½ ins. diam., projecting 3 ins. above ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd. as described in the official record of the 1977 resurvey.</p> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 10 ins. diam., bears N 40° E, 1.09 chs. dist., mkd. T12N R18E S32 BT. (Record: N 39° E)</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears S 33¼° E, 2.25 chs. dist., mkd. T11N R18E S5 BT. (Record: S 34½° E, 2.24 chs. dist.)</p> <p style="padding-left: 40px;">An alligator juniper, 12 ins. diam., bears S 73¾° W, 98 lks. dist., mkd. T11N R18E S6 BT. (Record: S 73° W)</p> <p style="padding-left: 40px;">An alligator juniper, 12 ins. diam., bears N 12½° W, 1.21 chs. dist., mkd. T12N R18E S31 BT.</p> <p>Cor. is located 1.30 chs. E of a dirt road, bears N 35° E and S 35° W, and 19 lks. S of a fence, bears E and W.</p> <p>N 0°22' W, bet. secs. 31 and 32.</p> <p>Over gently rolling land, through juniper and scrub pine.</p>	
2.10	<p>Dirt road, bears N 35° E and S 35° W.</p>	
40.36	<p>Point for the ¼ sec. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p>	

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T12N R18E  <math>\frac{1}{4}</math>            S31   S32            1982</p> <p>from which</p> <p style="padding-left: 40px;">A pinyon, 7 ins. diam., bears N 8° E, 49.5 lks. dist., mkd. <math>\frac{1}{4}</math> S32 BT.</p> <p style="padding-left: 40px;">An alligator juniper, 6 ins. diam., bears N 89° W, 45 lks. dist., mkd. <math>\frac{1}{4}</math> S31 BT.</p> <p>Set a steel fence post alongside the cor.</p>	
80.72	<p>Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E            S30   S29            S31   S32            1982</p> <p>from which</p> <p style="padding-left: 40px;">A pinyon, 6 ins. diam., bears N 25° E, 94.5 lks. dist., mkd. T12N R18E S29 BT.</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears S 11° E, 1.18 chs. dist., mkd. T12N R18E S32 BT.</p> <p style="padding-left: 40px;">An alligator juniper, 7 ins. diam., bears S 12° W, 88 lks. dist., mkd. T12N R18E S31 BT.</p> <p style="padding-left: 40px;">A pinyon, 6 ins. diam., bears N 40° W, 72 lks. dist., mkd. T12N R18E S30 BT.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor is located 1.60 chs. S of abandoned gravel road No. 160, bears S 75° E and N 75° W.</p>	
20.02	<p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N 89°45' W, bet. secs. 29 and 32.</p> <p>Through cleared area.</p> <p>Point for the E 1/16 sec. cor. of secs. 29 and 32.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E            E 1/16 <math>\frac{S29}{S32}</math>            1982</p>	

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

from which

A power pole, bears S  $31\frac{1}{2}^{\circ}$  E, 3.54 chs. dist.,  
power line bears S  $70^{\circ}$  E and N  $70^{\circ}$  W.

A power pole, bears S  $42^{\circ}$  W, 2.70 chs. dist.,  
power line bears S  $70^{\circ}$  E and N  $70^{\circ}$  W.

Set a steel fence post alongside the cor.

40.04

Point for the  $\frac{1}{4}$  sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 28 ins. long, 1 in. diam., 25 ins. in the ground, with cap mkd.

T12N R18E  
 $\frac{1}{4}$  S29  
S32  
1982

from which

A power pole, bears N  $10^{\circ}$  E, 2.87 chs. dist.,  
power line bears S  $70^{\circ}$  E and N  $70^{\circ}$  W, paralleled  
by a service road.

Set a steel fence post alongside the cor.

Cor. is located in a cleared area, 1.50 chs. N of  
abandoned gravel road, bears N  $80^{\circ}$  E and S  $80^{\circ}$  W.

80.08

The cor. of secs. 29, 30, 31 and 32.

N  $89^{\circ}50'$  W, bet. secs. 30 and 31.

Through medium timber.

40.13

Point for the  $\frac{1}{4}$  sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.

T12N R18E  
 $\frac{1}{4}$  S30  
S31  
1982

from which

A ponderosa pine, 8 ins. diam., bears N  $62^{\circ}$  E,  
37.5 lks. dist., mkd.  $\frac{1}{4}$  S30 BT.

A ponderosa pine, 6 ins. diam., bears S  $63^{\circ}$  E,  
22 lks. dist., mkd.  $\frac{1}{4}$  S31 BT.

Set a steel fence post alongside the cor.

Cor. is 30 lks. E of a fence, bears S  $25^{\circ}$  E and N  $25^{\circ}$  W.

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
80.41	<p>The cor. of secs. 30 and 31 only, on the W bdy. of the Tp., determined from the remains of the bearing trees as described in the official record of the 1935-36 resurvey of a portion of the W bdy., T12N, R18E.</p> <p>A pine stump, 24 ins. diam., bears N 36½° E, 4.27 chs. dist., mkd. T12N R18E S30 BT.</p> <p>A pine stump, 18 ins. diam., bears S 61° E, 1.36 chs. dist., marks visible 31 BT. (Record: S 56½° E)</p> <p>A pine stump, 26 ins. diam., bears S 6½° W, 89 lks. dist., no marks visible.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, and in a mound of stone, 4 ft. base, 16 ins. high, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R17E R18E S25   S30        S31 1982</p> </div> <p>from which</p> <p>An aluminum post, 28 ins. long, 1 in. diam., set 16 ins. in the ground, in a mound of stone, 2½ ft. base, to top, for a reference monument, bears S 76°58' E, 124.40 ft. dist., with cap mkd. T12N R18E S31 RM 124.40 FT 1982, and an arrow pointing to the cor.</p> <p>An aluminum post, 28 ins. long, 1 in. diam., set 22 ins. in the ground, in a mound of stone, 2½ ft. base, to top, for a reference monument, bears S 35°12' E, 84.75 ft. dist., with cap mkd. T12N R18E S31 RM 84.75 FT 1982, and an arrow pointing to the cor.</p> <p>Cor falls in a wash, 1.00 ch. wide, drains N 70° E.</p>
40.36	<hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N 0°26' W, bet. secs. 29 and 30.</p> <p>Over level terrain, through area ranging from juniper covered to cleared.</p> <p>Point for the ¼ sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 32 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>T12N R18E       ¼ S30   S29 1982</p> </div>

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

from which

A pinyon, 5 ins. diam., bears N 52° E, 76.5  
lks. dist., mkd.  $\frac{1}{4}$  S29 BT.

A pinyon, 8 ins. diam., bears S 35° W,  
1.17 chs. dist., mkd.  $\frac{1}{4}$  S30 BT.

Set a steel fence post alongside the cor.

80.72

Point for the cor. of secs. 19, 20, 29 and 30, at pro-  
portionate dist.; there is no remaining evidence of the  
original cor.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 28 ins.  
in the ground, with cap mkd.

T12N R18E  
S19 | S20  
S30 | S29  
1982

from which

A pinyon, 6 ins. diam., bears N 58 $\frac{1}{2}$ ° E,  
1.295 chs. dist., mkd. T12N R18E S20 BT.

A pinyon, 5 ins. diam., bears S 10° E,  
1.30 chs. dist., mkd. T12N R18E S29 BT.

A pinyon, 10 ins. diam., bears S 62° W,  
1.825 chs. dist., mkd. T12N R18E S30 BT.

A juniper, 9 ins. diam., bears N 6 $\frac{1}{2}$ ° W,  
1.93 chs. dist., mkd. T12N R18E S19 BT.

Set a steel fence post alongside the cor.

Cor. is located 1.37 chs. N of a fence, bears N 55° E  
and S 55° W.

From the cor. of secs. 20, 21, 28 and 29.

N 89°54' W, bet. secs. 20 and 29.

Over areas ranging from cleared to dense juniper.

39.91

Point for the  $\frac{1}{4}$  sec. cor. of secs. 20 and 29, at pro-  
portionate dist.; there is no remaining evidence of the  
original cor.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 32 ins.  
in the ground, with cap mkd.

T12N R18E  
 $\frac{1}{4}$  S20  
S29  
1982

from which

A pinyon, 6 ins. diam., bears N 21 $\frac{1}{2}$ ° E,  
1.00 ch. dist., mkd. X at breast height and BT  
at base.

A juniper, 9 ins. diam., bears S 82° W, 90.5 lks.  
dist., mkd.  $\frac{1}{4}$  S29 BT.

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
	Set a steel fence post alongside the cor.
59.87	Point for the W 1/16 sec. cor. of secs. 20 and 29.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.
	<p style="text-align: center;">T12N R18E W 1/16 <math>\frac{S20}{S29}</math> 1982</p>
	from which
	<p style="text-align: center;">A pine, 10 ins. diam., bears S 53° W, 1.935 chs. dist., mkd. W 1/16 S29 BT.</p>
	Set a steel fence post alongside the cor.
	Cor. falls in cleared area.
79.83	The cor. of secs. 19, 20, 29 and 30.
	<hr/> <p>N 89°42' W, bet. secs. 19 and 30.</p>
	Over nearly level land, through thick juniper and pine.
39.92	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 16 ins. in the ground, in a mound of stone, 2½ ft. base, to top with cap mkd.
	<p style="text-align: center;">T12N R18E <math>\frac{1}{4}</math> <math>\frac{S19}{S30}</math> 1982</p>
	from which
	<p style="text-align: center;">A pine, 5 ins. diam., bears N 61° E, 55 lks. dist., mkd. <math>\frac{1}{4}</math> S19 BT.</p>
	<p style="text-align: center;">A pine, 8 ins. diam., bears S 11° E, 33 lks. dist., mkd. <math>\frac{1}{4}</math> S30 BT.</p>
	Set a steel fence post alongside the cor.
	Cor is located 1.85 chs. E of a track road, bears N 20° E and S 20° W.
80.02	The cor. of secs. 19 and 30 only, on the W bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 14 ins. above the ground, in a mound of stone, 2½ ft. base, 1 ft. high, with brass cap mkd. as described in the official record of the 1935-36 resurvey of a portion of the W bdy., T12N, R18E.
	from which the 1935-36 bearing trees
	<p style="text-align: center;">An alligator juniper, 18 ins. diam., bears N 38° E, 63 lks. dist., mkd. T12N R18E S19 BT. (Record: N 33½° E)</p>



Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>A juniper, 8 ins. diam., bears S 21° E, 24 lks. dist., mkd. T12N R18E S30 BT. (Record: S 25° E, 23 lks. dist.)</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30. N 3°02' E, bet. secs. 19 and 20. Over level land, through medium juniper.</p>	
20.205	<p>Point for the S 1/16 sec. cor. of secs. 19 and 20. Set an aluminum post, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E S 1/16 S19   S20 1982</p>	
	<p>from which</p> <p>A juniper, 6 ins. diam., bears S 49° E, 47 lks. dist., mkd. S 1/16 S20 BT.</p> <p>A juniper, 6 ins. diam., bears N 65½° W, 32 lks. dist., mkd. S 1/16 S19 BT.</p> <p>Set a steel fence post alongside the cor.</p>	
30.308	<p>Point for the N-S 1/64 sec. cor. of secs. 19 and 20. Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">N-S 1/64 S19   S20 1982</p>	
	<p>from which</p> <p>A fence cor., bears East, 57.5 lks. dist., fences extend N and E.</p> <p>A juniper, 13 ins. diam., bears S 23° W, 45 lks. dist., mkd. N S 1/64 S19 BT.</p> <p>Set a steel fence post alongside the cor.</p>	
40.41	<p>The 1/4 sec. cor. of secs. 19 and 20, monumented with a stone, 8 x 6 x 4 ins., loosely set in a mound of stone, 2½ ft. base, 6 ins. high, mkd. 1/4 on a face.</p> <p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E 1/4 S19   S20 1982</p>	

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

from which

A pinyon, 8 ins. diam., bears S 18° E,  
62.5 lks. dist., mkd. ¼ S20 BT.

A juniper, 14 ins. diam., bears N 22° W,  
24 lks. dist., mkd. ¼ S19 BT.

Deposit the mkd. stone alongside the cor.

Set a steel fence post alongside the cor.

Cor. is 2 lks. W of a fence, bears N and S.

N 3°32' W, beginning new measurement.

Over hilly terrain.

20.34

Point for the N 1/16 sec. cor. of secs. 19 and 20.

Set an aluminum post, 36 ins. long, ¾ in. diam., 32 ins.  
in the ground, with cap mkd.

T12N R18E  
N 1/16  
S19 | S20  
1982

from which

A forked juniper, 10 ins. diam., bears S 81° E,  
2.025 chs. dist., mkd. N 1/16 S20 BT.

A forked juniper, 8 ins. diam., bears N 60° W,  
1.79 chs. dist., mkd. N 1/16 S19 BT.

Set a steel fence post alongside the cor.

Raise a mound of stone, 2 ft. base, 8 ins. high, W of  
cor.

Cor. is located 1.81 chs. W of a N and S fence.

40.68

Point for the cor. of secs. 17, 18, 19 and 20, at pro-  
portionate dist.; there is no remaining evidence of the  
original cor.

Set an aluminum post, 36 ins. long, ¾ in. diam., 32 ins.  
in the ground, with cap mkd.

T12N R18E  
S18 | S17  
S19 | S20  
1982

from which

A forked juniper, 9 ins. diam., bears N 34° E,  
95 lks. dist., mkd. T12N R18E S17 BT.

A pinyon, 6 ins. diam., bears S 72° W, 68 lks.  
dist., mkd. T12N R18E S19 BT.

Set a steel fence post alongside the cor.

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

Raise a mound of stone,  $2\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W of cor.

Cor. is located 97 lks. N of a track road, bears N  $75^\circ$  E and W.

From the cor. of secs. 16, 17, 20 and 21.

N  $89^\circ 21'$  W, bet. secs. 17 and 20.

Over nearly level land, through medium juniper.

40.09

Point for the  $\frac{1}{4}$  sec. cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 31 ins. in the ground, with cap mkd.

T12N R18E  
 $\frac{1}{4}$  S17  
S20  
1982

from which

A forked pinyon, 12 ins. diam., bears N  $48\frac{1}{2}^\circ$  E, 1.455 chs. dist., mkd.  $\frac{1}{4}$  S17 BT.

A forked alligator juniper, 12 ins. diam., bears S  $21^\circ$  W, 2.185 chs. dist., mkd.  $\frac{1}{4}$  S20 BT.

50.113

Point for the E-W  $\frac{1}{64}$  sec. cor. of secs. 17 and 20.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.

S17  
E-W  $\frac{1}{64}$   
S20  
1982

from which

A forked juniper, 6 ins. diam., bears N  $69^\circ$  E, 64.5 lks. dist., mkd. E W  $\frac{1}{64}$  S17 BT.

A pinyon, 8 ins. diam., bears S  $84^\circ$  W, 58 lks. dist., mkd. E W  $\frac{1}{64}$  S20 BT.

Cor. is located 67 lks. S of a track road, bears S  $70^\circ$  E and N  $70^\circ$  W, and 54 lks. N of an E and W fence.

60.135

Point for the W  $\frac{1}{16}$  sec. cor. of secs. 17 and 20.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.

T12N R18E  
W  $\frac{1}{16}$  S17  
S20  
1982

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>from which</p> <p>A pine, 4 ins. diam., bears N 25° E, 34 lks. dist., mkd. X at breast hight, and BT at base.</p> <p>A pinyon, 10 ins. diam., bears N 75° W, 2.075 chs. dist., mkd. W 1/16 S17 BT.</p> <p>The NE cor. of an abandoned house, 28 x 24 ft., bears S 59° W, 3.10 chs. dist., long side bears N and S.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 60 lks. N of an E and W fence and 10 lks. N of an E and W track road.</p>	
80.18	<p>The cor. of secs. 17, 18, 19 and 20.</p>	
	<p>N 89°34' W, bet. secs. 18 and 19.</p> <p>Over rolling land, through medium juniper and pine.</p>	
9.985	<p>Point for E-E 1/64 sec. cor. of secs. 18 and 19.</p>	
	<p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">E-E 1/64 S18 S19 1982</p>	
	<p>from which</p>	
	<p>A pine, 8 ins. diam., bears N 42° W, 1.52 chs. dist., mkd. E E 1/64 S18 BT.</p>	
	<p>A pine, 7 ins. diam., bears N 17° W, 25 lks. dist., mkd. E E 1/64 S18 BT.</p>	
	<p>Set a steel fence post alongside the cor.</p>	
	<p>Cor. is located 80 lks. N of a track road, bears N 80° E and S 80° W.</p>	
19.97	<p>Point for the E 1/16 sec. cor. of secs. 18 and 19.</p>	
	<p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p>	
	<p style="text-align: center;">T12N R18E E 1/16 S18 S19 1982</p>	
	<p>from which</p>	
	<p>A ponderosa pine, 24 ins. diam., bears N 22° E, 76.5 lks. dist., mkd. E 1/16 S18 BT.</p>	
	<p>A pinyon, 6 ins. diam., bears S 12° E, 20.5 lks. dist., mkd. E 1/16 S19 BT.</p>	
	<p>Set a steel fence post alongside the cor.</p>	

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Cor. is 2.30 chs. E of Phoenix Park Wash, 1.50 chs. wide, drains N 35° E.</p>	
39.94	<p>Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 28 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E ¼ S18 S19 1982</p> <p>from which</p> <p style="padding-left: 40px;">A pinyon, 8 ins. diam., bears N 66° E, 61 lks. dist., mkd. ¼ S18 BT.</p> <p style="padding-left: 40px;">A pinyon, 8 ins. diam., bears N 65° W, 31 lks. dist., mkd. ¼ S18 BT.</p> <p>Set a steel fence post alongside the cor.</p>	
79.83	<p>The cor. of secs. 18 and 19 only, on the W bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 16 ins. above ground, in a scattered mound of stone, with brass cap mkd. as described in the official record of the 1935-36 resurvey of a portion of the W bdy., T12N, R18E.</p> <p>from which the 1935-36 bearing trees</p> <p style="padding-left: 40px;">A dead pinyon, 7 ins. diam., bears N 36° E, 21 lks. dist., mkd. T12N R18E S18 BT.</p> <p style="padding-left: 40px;">A dead pinyon, 6 ins. diam., bears S 28° E, 66 lks. dist., mkd. T12N R18E S19 BT.</p> <p>and from which new bearing trees</p> <p style="padding-left: 40px;">A juniper, 15 ins. diam., bears N 32° E, 30.5 lks. dist., mkd. T12N R18E S18 BT.</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears S 20° E, 50 lks. dist., mkd. T12N R18E S19 BT.</p> <p>Add the date 1982 to the cap.</p> <p>Rebuild mound of stone, 2 ft. base, 1 ft. high, around the cor.</p>	
10.15	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N 0°34' E, bet. secs. 17 and 18.</p> <p>Over rolling land, through medium juniper and scattering pine.</p> <p>Point for the S-S 1/64 sec. cor. of secs. 17 and 18.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p>	

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">S-S 1/64 S18   S17 1982</p> <p>from which</p> <p>A pinyon, 12 ins. diam., bears N 52° E, 22 lks. dist., mkd. S S 1/64 S17 BT.</p> <p>A pinyon, 8 ins. diam., bears S 14° W, 68.5 lks. dist., mkd. S S 1/64 S18 BT.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located on a spur, slopes W.</p>	
20.30	<p>Point for the S 1/16 sec. cor. of secs. 17 and 18.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 33 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E S 1/16 S18   S17 1982</p> <p>from which</p> <p>A fence cor., bears N 63° E, 95 lks. dist., abandoned fences extend N 4° E and N 87° W.</p> <p>A pinyon, 8 ins. diam., bears N 4° W, 45 lks. dist., mkd. S 1/16 S18 BT.</p> <p>Cor. is located 11 lks. W of an abandoned N and S fence.</p>	
40.60	<p>Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, in a mound of stone and earth, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E 1/4 S18   S17 1982</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 45 lks. W of a N and S fence, and 1.30 chs. E of a bladed road, bears N and S.</p>	
60.90	<p>Point for the N 1/16 sec. cor. of secs. 17 and 18.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 33 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E N 1/16 S18   S17 1982</p>	

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>from which</p> <p>A pine, 14 ins. diam., bears N 75° E, 1.075 chs. dist., mkd. N 1/16 S17 BT.</p> <p>A pine, 22 ins. diam., bears S 64° E, 1.04 chs. dist., mkd. X at breast height and BT at base.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 30 lks. W of an abandoned N and S fence.</p> <p>Cor. falls in a wash, 60 lks. wide, drains N 25° E.</p>	
81.20	<p>The cor. of secs. 7, 8, 17 and 18, monumented with a sandstone, 8 x 7 x 3 ins. mkd. with 5 grooves on one side and 4 grooves on another, loosely set in a mound of stone, 2 ft. base.</p> <p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 32 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>T12N R18E S 7   S 8 S18   S17 1981</p> </div> <p>from which</p> <p>A ponderosa pine, 10 ins. diam., bears N 46° E, 1.22 chs. dist., mkd. T12N R18E S8 BT.</p> <p>A ponderosa pine, 6 ins. diam., bears S 6° E, 59 lks. dist., mkd. T12N R18E S17 BT.</p> <p>A ponderosa pine, 10 ins. diam., bears N 63° W, 73 lks. dist., mkd. T12N R18E S7 BT.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W of the cor.</p> <p>Bury the mkd. stone alongside the aluminum post.</p> <p>Cor. is located at a fence cor.; fences extend E, S and W.</p>	
20.29	<p>S 89°52' W, bet. secs. 7 and 18.</p> <p>Over rolling land, through medium juniper.</p> <p>Point for the E 1/16 sec. cor. of secs. 7 and 18.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 14 ins. in the ground, in a mound of stone, <math>2\frac{1}{2}</math> ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R18E E 1/16   S 7 S18 1981</p> </div>	

Dependent Resurvey, Portions of the Subdivisional Lines  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>from which</p> <p>A juniper, 5 ins. diam., bears S 71° E, 45.5 lks. dist., mkd. E 1/16 S18 BT.</p> <p>A fence cor. post, bears S 42° E, 41 lks. dist., fence extends E, S and W.</p> <p>A juniper, 4 ins. diam., bears S 88° W, 53.5 lks. dist., mkd. X at breast height and BT at base.</p> <p>40.58 Point for the 1/4 sec. cor. of secs. 7 and 18, at pro- portionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E 1/4 S 7 S18 1981</p> <p>from which</p> <p>A juniper, 14 ins. diam., bears S 69° W, 24.5 lks. dist., mkd. 1/4 S18 BT.</p> <p>A pinyon, 12 ins. diam., bears N 13° W, 78 lks. dist., mkd. 1/4 S7 BT.</p> <p>Raise a mound of stone, 1 1/2 ft. base, 1 1/2 ft. high, N of cor.</p> <p>Cor. is located 1.30 chs. N of a fence, bears E and W.</p>	
80.99	<p>The cor. of secs. 7 and 18 only, on the W bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 12 ins. above the ground, with a wood post 4 ins. diam., projecting 2 ft. above ground along side the cor., with brass cap mkd. as described in the official record of the 1935-36 resurvey of a portion of the W bdy., T 12 N, R 18 E.</p> <p>from which the 1935-36 bearing trees</p> <p>A pinyon, 12 ins. diam., bears N 26 3/4° E, 1.07 chs. dist., mkd. T12N R18E S7 BT.</p> <p>A pinyon snag, 6 ins. diam., bears S 41 1/4° E, 2.08 chs. dist., mkd. T12N R18E S18 BT.</p> <p>Cor. is located 41 lks. E of a N and S fence.</p>	
19.92	<p style="text-align: center;">Subdivision of Section 2 T 12 N, R 18 E, Gila and Salt River Mer., Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 2 and 11.</p> <p>N 1°56' W, on the N and S center line of sec. 2.</p> <p>Point for the center S 1/16 sec. cor. of sec. 2.</p>	



Subdivision of Section 2  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 12 ins. in the ground, in a mound of stone, <math>3\frac{1}{2}</math> ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E C S 1/16   S 2 C 1983</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 1.43 chs. W of a N and S fence and 32 lks. E of a graded road, bears N and S.</p>
39.84	<p>Point for the center <math>\frac{1}{4}</math> sec. cor., at intersection with the E and W center line of sec. 2.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 28 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T12N R18E C <math>\frac{1}{4}</math> S2 1983</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 1.81 chs. W of a N and S fence.</p>
41.80	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of sec. 2 only, at proportionate dist., on the Third Stan. Par. North.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, <math>2\frac{1}{2}</math> ft. base, to top, with cap mkd.</p> <p style="text-align: center;"><u>T13N R18E</u> <math>\frac{1}{4}</math> S 2 T12N R18E 1982</p> <p>From this point a fence cor., bears S <math>68^\circ</math> E, 2.055 chs. dist., fence extends N, E and S.</p> <p>From this same point, the stan. cor. of secs. 35 and 36, T 13 N, R 18 E, bears N <math>89^\circ 34'</math> E, 18.32 chs. dist., hereinbefore described.</p>
40.20	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 2.</p> <p>N <math>89^\circ 58'</math> W, on the E and W center line of sec. 2.</p>
60.30	<p>The center <math>\frac{1}{4}</math> sec. cor. of sec. 2.</p>
60.30	<p>Point for the center W 1/16 sec. cor. of sec. 2.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 26 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E C <math>\frac{W 1/16}{S 2}</math> C 1983</p>

Subdivision of Section 2  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
80.40	<p>Set a steel fence post alongside the cor. Cor. is located 1.07 chs. S of an E and W fence. The <math>\frac{1}{4}</math> sec. cor. of secs. 2 and 3.</p>	
	<hr/> <p style="text-align: center;">SW<math>\frac{1}{4}</math> of Section 2</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 2 and 11. N 1°52' W, on the N and S center line of the SW<math>\frac{1}{4}</math> of sec. 2.</p> <p>19.91 Point for the SW 1/16 sec. cor., at intersection with the E and W center line of the SW<math>\frac{1}{4}</math> of sec. 2. Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12NR18E SW 1/16 S 2 1983</p> <p>Raise a mound of stone, 2<math>\frac{1}{2}</math> ft. base, 1<math>\frac{1}{2}</math> ft. high, W of cor. Cor. is located 90 lks. W of a wash, 95 lks. wide, drains N 10° W from S 30° E, and 16 lks. W of a power line, bears N and S.</p> <p>39.82 The center W 1/16 sec. cor. of sec. 2.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 2. N 89°57' W, on the E and W center line of the SW<math>\frac{1}{4}</math> of sec. 2.</p> <p>20.12 The SW 1/16 sec. cor. of sec. 2.</p> <p>40.24 The S 1/16 sec. cor. of secs. 2 and 3.</p>	
1.795	<hr/> <p style="text-align: center;">NW<math>\frac{1}{4}</math> of Section 2</p> <hr/> <p>From the center W 1/16 sec. cor. of sec. 2. N 1°52' W, on the N and S center line of the NW<math>\frac{1}{4}</math> of sec. 2.</p> <p>Point for the W 1/16 sec. cor. of sec. 2 only, at proportionate dist., on the Third Stan. Par. North. Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T13N R18E W 1/16 S 2 T12N R18E 1983</p> <p>Cor. is located 72 lks. N of a fence, bears E and W.</p>	

Subdivision of Section 2  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

From this point, the stan.  $\frac{1}{4}$  sec. cor. of sec. 35,  
T 13 N, R 18 E, bears S  $89^{\circ}34'$  W, 2.17 chs. dist.,  
hereinbefore described.

Subdivision of Section 10  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

From the  $\frac{1}{4}$  sec. cor. of secs. 10 and 15.

N  $0^{\circ}15'$  W, on the N and S center line of sec. 10.

19.995 Point for the center S  $\frac{1}{16}$  sec. cor. of sec. 10.

Set an aluminum post, 28 ins. long, 1 in. diam., 24  
ins. in the ground, with cap mkd.

T12NR18E  
C  
S  $\frac{1}{16}$  | S10  
C  
1982

from which

A juniper, 8 ins. diam., bears N  $65\frac{1}{2}^{\circ}$  E,  
51 lks. dist., mkd. C S  $\frac{1}{16}$  S10 BT.

Set a steel fence post alongside the cor.

39.99 Point for the center  $\frac{1}{4}$  sec. cor., at intersection with  
the E and W center line of sec. 10.

Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins.  
in the ground, with cap mkd.

T12N R18E  
C  $\frac{1}{4}$  S10  
1982

Set a steel fence post alongside the cor.

79.97 The  $\frac{1}{4}$  sec. cor. of secs. 3 and 10.

From the  $\frac{1}{4}$  sec. cor. of secs. 10 and 11.

S  $89^{\circ}54'$  W, on the E and W center line of sec. 10.

20.145 Point for the center E  $\frac{1}{16}$  sec. cor. of sec. 10.

Set an aluminum post, 28 ins. long, 1 in. diam., 24  
ins. in the ground, with cap mkd.

T12N R18E  
C  $\frac{E \frac{1}{16}}$  C  
S10  
1982

from which

A fence cor., bears N  $6\frac{1}{2}^{\circ}$  W, 1.71 chs.  
dist., fence extends N and W.

40.29 The center  $\frac{1}{4}$  sec. cor. of sec. 10.

Subdivision of Section 10  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
80.57	The $\frac{1}{4}$ sec. cor. of secs. 9 and 10.
	<hr/> $SE\frac{1}{4}$ of Section 10 <hr/>
	From the E $\frac{1}{16}$ sec. cor. of secs. 10 and 15.
	N $0^{\circ}13'$ W, on the N and S center line of the $SE\frac{1}{4}$ of sec. 10.
19.95	Point for the SE $\frac{1}{16}$ sec. cor. at intersection with the E and W center line of the $SE\frac{1}{4}$ sec. 10.
	Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, in a mound of stone, $1\frac{1}{2}$ ft. base, to top, with cap mkd.
	T12NR18E SE $\frac{1}{16}$ S10 1982
	Set a steel fence post alongside the cor.
	Cor. is located 68 lks. W of a track road, bears N $15^{\circ}$ E and S $15^{\circ}$ W, and 95 lks. W of an abandoned N and S fence.
39.90	The center E $\frac{1}{16}$ sec. cor. of sec. 10.
	<hr/> From the S $\frac{1}{16}$ sec. cor. of secs. 10 and 11.
	S $89^{\circ}46'$ W, on the E and W center line of the $SE\frac{1}{4}$ of sec. 10.
10.065	Point for the center E-SE $\frac{1}{64}$ sec. cor. of sec. 10.
	Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, in a mound of earth and stone, $1\frac{1}{2}$ ft. base, to top, with cap mkd.
	S10 C-E-SE $\frac{1}{64}$ 1982
	Set a steel fence post alongside the cor.
	Cor. is located 94.5 lks. S of an abandoned E and W fence.
20.13	The SE $\frac{1}{16}$ sec. cor. of sec. 10.
30.195	Point for the center W-SE $\frac{1}{64}$ sec. cor. of sec. 10.
	Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.
	S10 C-W-SE $\frac{1}{64}$ 1982
	Set a steel fence post alongside the cor.
31.05	Fence, bears N and S.
40.26	The center S $\frac{1}{16}$ sec. cor. of sec. 10.

Subdivision of Section 10  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

From the true point for the E-E 1/64 sec. cor. of secs. 10 and 15.

N 0°12' W, on the N and S center line of the SE $\frac{1}{4}$  of the SE $\frac{1}{4}$  of sec. 10.

19.92 The center E-SE 1/64 sec. cor. of sec. 10.

From the W-E 1/64 sec. cor. of secs. 10 and 15.

N 0°14' W, on the N and S center line of the SW $\frac{1}{4}$  of the SE $\frac{1}{4}$  of sec. 10.

19.97 The center W-SE 1/64 sec. cor. of sec. 10.

Subdivision of Section 13  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

From the  $\frac{1}{4}$  sec. cor. of secs. 13 and 24.

N 0°25' E, on the N and S center line of sec. 13.

40.32 Point for the center  $\frac{1}{4}$  sec. cor., at intersection with the E and W center line of sec. 13.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 23 ins. in the ground, with cap mkd.

T12N R18E  
C  $\frac{1}{4}$  S13  
1981

From this point, a fence cor., bears N 80° W, 1.51 chs. dist.; abandoned fences extend N and W.

60.48 Point for the center N 1/16 sec. cor. of sec. 13.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 28 ins. in the ground, with cap mkd.

T12NR18E  
C  
N 1/16 | S13  
C  
1981

From this point a fence cor., bears S 46° W, 1.91 chs. dist., fences extend N, E and S.

80.64 The  $\frac{1}{4}$  sec. cor. of secs. 12 and 13.

From the  $\frac{1}{4}$  sec. cor. of secs. 13 and 18, on the E bdy. of the Tp., hereinbefore described.

N 88°35' W, on the E and W center line of sec. 13.

19.75 Point for the center E 1/16 sec. cor. of sec. 13.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 26 ins. in the ground, in a mound of stone, 1 $\frac{1}{2}$  ft. base, to top, with cap mkd.

Subdivision of Section 13  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>T12N R18E E 1/16 C ————— C S13 1981</p>
39.50	The center 1/4 sec. cor. of sec. 13.
79.01	The 1/4 sec. cor. of secs. 13 and 14.
	<p>NE 1/4 of Section 13</p> <hr/>
	<p>From the center E 1/16 sec. cor. of sec. 13.</p> <p>N 0°21' E, on the N and S center line of the NE 1/4 of sec. 13.</p>
20.04	<p>Point for the NE 1/16 sec. cor., at intersection with the E and W center line of the NE 1/4 of sec. 13.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with cap mkd.</p>
	<p>T12N R18E NE 1/16 S13 1981</p>
	<p>from which</p> <p style="padding-left: 40px;">A juniper, 4 ins. diam., bears S 54° E, 73 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S 5° E, 2.32 chs. dist., mkd. NE 1/16 S13 BT.</p> <p style="padding-left: 40px;">A fence cor., bears S 55° W, 1.52 chs. dist., fences extend N and W.</p> <p>Cor. is located in the center of a wash, 70 lks. wide, 5 ft. deep, drains N 60° E.</p>
40.08	The E 1/16 sec. cor. of secs. 12 and 13.
	<hr/>
	<p>From the N 1/16 sec. cor. of secs. 13 and 18, on the E bdy. of the Tp., hereinbefore described.</p> <p>N 88°14' W, on the E and W center line of the NE 1/4 of sec. 13.</p>
19.73	The NE 1/16 sec. cor. of sec. 13.
39.47	The center N 1/16 sec. cor. of sec. 13.
	<hr/>
	<p>Subdivision of Section 18 T 12 N, R 18 E, Gila and Salt River Mer., Arizona</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 18 and 19.</p> <p>N 0°06' E, on the N and S center line of sec. 18.</p>
20.27	Point for the center S 1/16 sec. cor. of sec. 18.

Subdivision of Section 18  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 31 ins. in the ground, with cap mkd.

C  
S 1/16 | S18  
C  
1982

from which

A pinyon, 4 ins. diam., bears S 13° E, 78 lks. dist., mkd. X at breast height and BT at base.

A pinyon, 10 ins. diam., bears N 59° W, 51 lks. dist., mkd. C S 1/16 S18 BT.

Raise a mound of stone, 2 ft. base, 5 ins. high, W of cor.

Set a steel fence post alongside the cor.

40.54

Point for the center  $\frac{1}{4}$  sec. cor., at intersection with the E and W center line of sec. 18.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 32 ins. in the ground, with cap mkd.

T12N R18E  
C  $\frac{1}{4}$  S18  
1982

from which

A pinyon, 8 ins. diam., bears S 24° W, 42 lks. dist., mkd. C  $\frac{1}{4}$  S18 BT.

A juniper, 6 ins. diam., bears N 59° W, 46.5 lks. dist., mkd. X at breast height and BT at base.

Set a steel fence post alongside the cor.

60.69

Point for the center N 1/16 sec. cor. of sec. 18.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 28 ins. in the ground, in a mound of stone, 2 $\frac{1}{2}$  ft. base, to top, with cap mkd.

C  
N 1/16 | S18  
C  
1982

from which

A juniper, 8 ins. diam., bears East, 21.5 lks. dist., mkd. C N 1/16 S18 BT.

A pine, 5 ins. diam., bears S 12° W, 1.40 chs. dist., mkd. X at breast height and BT at base.

Set a steel fence post alongside the cor.

80.84

The  $\frac{1}{4}$  sec. cor. of secs. 7 and 18.

Subdivision of Section 18  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
20.13	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 17 and 18.</p> <p>N <math>89^{\circ}40'</math> W, on the E and W center line of sec. 18.</p> <p>Point for the center E <math>\frac{1}{16}</math> sec. cor. of sec. 18.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">C <math>\frac{E \frac{1}{16}}{S18}</math> C 1982</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears S <math>50^{\circ}</math> W, 98 lks. dist., mkd. C E <math>\frac{1}{16}</math> S18 BT.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 39 lks. W of a N and S fence.</p>
40.26	<p>The center <math>\frac{1}{4}</math> sec. cor. of sec. 18.</p>
80.42	<p>The <math>\frac{1}{4}</math> sec. cor. of sec. 18 only, on the W bdy. of the Tp., monumented with an iron post, 1 in. diam., projecting 8 ins. above ground in a mound of stone, 2 ft. base, to top, with brass cap mkd. as described in the official record of the 1935-36 resurvey of a portion of the W bdy., T 12 N, R 18 E.</p> <p>from which the 1935-36 bearing trees</p> <p style="padding-left: 40px;">A pinyon, 10 ins. diam., bears N <math>40^{\circ}</math> E, 98 lks. dist., marks visible are <math>\frac{1}{4}</math> S18. (Record: 1.00 ch. dist.)</p> <p style="padding-left: 40px;">A pinyon, 8 ins. diam., bears S <math>70^{\circ}</math> E, 30 lks. dist., marks visible are BT.</p>
<p>NE<math>\frac{1}{4}</math> of Section 18</p> <hr style="width: 20%; margin: auto;"/>	
20.23	<p>From the center E <math>\frac{1}{16}</math> sec. cor. of sec. 18.</p> <p>N <math>0^{\circ}20'</math> E, on the N and S center line of the NE<math>\frac{1}{4}</math> of sec. 18.</p> <p>Point for the NE <math>\frac{1}{16}</math> sec. cor., at intersection with the E and W center line of the NE<math>\frac{1}{4}</math> of sec. 18.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">NE <math>\frac{1}{16}</math> S18 1982</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears S <math>65\frac{1}{2}^{\circ}</math> W, 42.5 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N <math>72\frac{1}{2}^{\circ}</math> W, 42 lks. dist., mkd. NE <math>\frac{1}{16}</math> S18 BT.</p> <p>Set a steel fence post alongside the cor.</p>



Subdivision of Section 18  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

- Cor. is located 43 lks. W of a N and S fence.
- 40.46 The E 1/16 sec. cor. of secs. 7 and 18.
- 
- From the N 1/16 sec. cor. of secs. 17 and 18.
- N 89° 53' W, on the E and W center line of the NE<sup>1</sup>/<sub>4</sub> of sec. 18.
- 20.21 The NE 1/16 sec. cor. of sec. 18.
- 40.42 The center N 1/16 sec. cor. of sec. 18.
- 
- SE<sup>1</sup>/<sub>4</sub> of Section 18
- 
- From the E 1/16 sec. cor. of secs. 18 and 19.
- N 0° 20' E, on the N and S center line of the SE<sup>1</sup>/<sub>4</sub> of sec. 18.
- 10.14 Point for the center S-SE 1/64 sec. cor. of sec. 18.
- Set an aluminum post, 36 ins. long, <sup>3</sup>/<sub>4</sub> in. diam., 30 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.
- S18  
C-S-SE  
1/64  
1982
- from which
- A ponderosa pine, 10 ins. diam., bears S 85° W,  
1.18 chs. dist., mkd. C S SE 1/64 S18 BT.
- Set a steel fence post alongside the cor.
- Cor. is located 55 lks. E of Phoenix Park Wash, drains N.
- 20.28 Point for the SE 1/16 sec. cor., at intersection with the E and W center line of the SE<sup>1</sup>/<sub>4</sub> of sec. 18.
- Set an aluminum post, 15 ins. long, <sup>3</sup>/<sub>4</sub> in. diam., 3 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.
- SE 1/16 S18  
1982
- from which
- A pine, 15 ins. diam., bears S 3° E, 34.5  
lks. dist., mkd. SE 1/16 S18 BT.
- A pine, 16 ins. diam., bears N 21° W, 54.5  
lks. dist., mkd. SE 1/16 S18 BT.
- Set a steel fence post alongside the cor.
- Cor. is located 1.55 chs. W of Phoenix Park Wash,  
125 lks. wide, drains N 30° E.

Subdivision of Section 18  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
40.56	<p>The center E 1/16 sec. cor. of sec. 18.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 17 and 18.</p> <p>N 89°37' W, on the E and W center line of the SE<sup>1</sup>/<sub>4</sub> of sec. 18.</p>
10.02	<p>Point for the center E-SE 1/64 sec. cor. of sec. 18; not monumented.</p>
20.04	<p>The SE 1/16 sec. cor. of sec. 18.</p>
40.09	<p>The center S 1/16 sec. cor. of sec. 18.</p> <hr/> <p>From the E-E 1/64 sec. cor. of secs. 18 and 19.</p> <p>N 0°26' E, on the N and S center line of the SE<sup>1</sup>/<sub>4</sub> of the SE<sup>1</sup>/<sub>4</sub> of sec. 18.</p>
10.15	<p>Point for the SE-SE 1/64 sec. cor. of sec. 18.</p> <p>Set an aluminum post, 36 ins. long, <sup>3</sup>/<sub>4</sub> in. diam., 32 ins. in the ground, with cap mkd.</p>
	<p>S18 SE-SE 1/64 1982</p>
	<p>from which</p> <p style="padding-left: 40px;">A forked pine, 6 ins. diam., bears S 5° W, 57 lks. dist., mkd. SE SE 1/64 S18 BT.</p>
	<p>Set a steel fence post alongside the cor.</p>
20.30	<p>The point for the center E-SE 1/64 sec. cor. of sec. 18.</p> <hr/> <p>From the S-S 1/64 sec. cor. of secs. 17 and 18.</p> <p>N 89°35' W, on the E and W center line of the SE<sup>1</sup>/<sub>4</sub> of the SE<sup>1</sup>/<sub>4</sub> of sec. 18.</p>
10.00	<p>The SE-SE 1/64 sec. cor. of sec. 18.</p>
20.00	<p>The center S-SE 1/64 sec. cor. of sec. 18.</p>
<p>Subdivision of Section 19 T 12 N, R 18 E, Gila and Salt River Mer., Arizona</p>	
	<p>From the <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 19 and 30.</p> <p>N 0°16' W, on the N and S center line of sec. 19.</p>
40.47	<p>Point for the center <sup>1</sup>/<sub>4</sub> sec. cor., at intersection with the E and W center line of sec. 19.</p> <p>Set an aluminum post, 36 ins. long, <sup>3</sup>/<sub>4</sub> in. diam., 31 ins. in the ground, with cap mkd.</p>

Subdivision of Section 19  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T12N R18E C ¼ S19 1982</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears N 52° E, 29 lks. dist., mkd. C ¼ S19 BT.</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears S 59° W, 1.07 chs. dist., mkd. C ¼ S19 BT.</p> <p>Set a steel fence post alongside the cor.</p>	
60.75	<p>Point for the center N 1/16 sec. cor. of sec. 19.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 31 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">C N 1/16   S19 C 1982</p> <p>from which</p> <p style="padding-left: 40px;">A pinyon, 4 ins. diam., bears N 25° E, 22.5 lks. dist., mkd. X at breast height, and BT at base.</p> <p style="padding-left: 40px;">A forked juniper, 10 ins. diam., bears N 61° W, 34 lks. dist., mkd. C N 1/16 S19 BT.</p> <p>Set a steel fence post alongside the cor.</p>	
81.03	<p>The ¼ sec. cor. of secs. 18 and 19.</p> <hr/> <p>From the ¼ sec. cor. of secs. 19 and 20.</p> <p>N 89°32' W, on the E and W center line of sec. 19.</p>	
10.565	<p>Point for the center E-E 1/64 sec. cor. of sec. 19.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 20 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">C <u>E-E 1/64</u> C S19 1982</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N 4° E, 9.5 lks. dist., mkd. C E E 1/64 S19 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S 24° W, 18 lks. dist., mkd. C E E 1/64 S19 BT.</p> <p>Set a steel fence post alongside the cor.</p>	
21.13	<p>Point for the center E 1/16 sec. cor. of sec. 19.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 30 ins. in the ground, with cap mkd.</p>	

Subdivision of Section 19  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

C  $\frac{E 1/16}{S19}$  C  
1982

from which

A ponderosa pine, 8 ins. diam., bears S 89° E, 32 lks. dist., mkd. C E 1/16 S19 BT.

A ponderosa pine, 5 ins. diam., bears S 54° W, 6.5 lks. dist., mkd. X at breast height and BT at base.

Set a steel fence post alongside the cor.

42.26 The center  $\frac{1}{4}$  sec. cor. of sec. 19.

82.26 The  $\frac{1}{4}$  sec. cor. of sec. 19 only on the W bdy. of the Tp., monumented with an iron post, 1 in. diam., projecting 10 ins. above a mound of stone, 4 ft. base, 18 ins. high, with brass cap mkd. as described in the official record of the 1935-36 resurvey of a portion of the W bdy., T 12 N, R 18 E.

from which the bearing trees described in 1935-36

A juniper, 10 ins. diam., bears N 19° E, 69 lks. dist., mkd.  $\frac{1}{4}$  S19 BT. (Record: N 22° E)

A pinyon, 10 ins. diam., bears S 56° E, 1.82 chs. dist., mkd.  $\frac{1}{4}$  S19 BT. (Record: S 50° E)

An alligator juniper, 10 ins. diam., bears S 89° W, 1.96 chs. dist., scribe marks had been removed as noted in the record.

NE $\frac{1}{4}$  of Section 19

From the center E 1/16 sec. cor. of sec. 19.

N 1°54' W, on the N and S center line of the NE $\frac{1}{4}$  of sec. 19.

20.30 Point for the NE 1/16 sec. cor., at intersection with the E and W center line of the NE $\frac{1}{4}$  of sec. 19.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 28 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.

NE 1/16 S19  
1982

from which

A ponderosa pine, 10 ins. diam., bears N 35° E, 56 lks. dist., mkd. NE 1/16 S19 BT.

A pine, 8 ins. diam., bears N 74° W, 1.10 chs. dist., mkd. NE 1/16 S19 BT.

Cor. is located 10 lks. N of a wash, 15 lks. wide, drains W.

Subdivision of Section 19  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

40.61

The E 1/16 sec. cor. of secs. 18 and 19.

From the N 1/16 sec. cor. of secs. 19 and 20.

N 89°33' W, on the E and W center line of the NE<sup>1</sup>/<sub>4</sub> of sec. 19.

10.28

Point for the center E-NE 1/64 sec. cor. of sec. 19.

Set an aluminum post, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with cap mkd.

S19  
C-E-NE  
1/64  
1982

from which

A ponderosa pine, 6 ins. diam., bears S 15° E, 81 lks. dist., mkd. C E NE 1/64 S19 BT.

A ponderosa pine, 6 ins. diam., bears N 56° W, 61.5 lks. dist., mkd. C E NE 1/64 S19 BT.

Set a steel fence post alongside the cor.

20.56

The NE 1/16 sec. cor. of sec. 19.

41.11

The center N 1/16 sec. cor. of sec. 19.

From the center E-E 1/64 sec. cor. of sec. 19.

N 2°43' W, on the N and S center line of the SE<sup>1</sup>/<sub>4</sub> of the NE<sup>1</sup>/<sub>4</sub> of sec. 19.

20.32

The center E-NE 1/64 sec. cor. of sec. 19.

Subdivision of Section 20  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

From the 1/4 sec. cor. of secs. 20 and 29.

N 0°08' W, on the N and S center line of sec. 20.

20.12

Point for the center S 1/16 sec. cor. of sec. 20.

Set an aluminum post, 36 ins. long, 3/4 in. diam., 33 ins. in the ground, with cap mkd.

C  
S 1/16 | S20  
C  
1982

from which

A pine, 6 ins. diam., bears N 40° E, 1.055 chs. dist., mkd. C S 1/16 S20 BT.

A pine, 8 ins. diam., bears S 51° W, 57 lks. dist., mkd. C S 1/16 S20 BT.

Set a steel fence post alongside the cor.

Subdivision of Section 20  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
40.24	<p>Point for the center <math>\frac{1}{4}</math> sec. cor., at intersection with the E and W center line of sec. 20.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E C <math>\frac{1}{4}</math> S20 1982</p> <p>from which</p> <p style="padding-left: 40px;">A pinyon, 6 ins. diam., bears N <math>88^\circ</math> E, 47.5 lks. dist., mkd. C <math>\frac{1}{4}</math> S20 BT.</p> <p style="padding-left: 40px;">A pinyon, 9 ins. diam., bears N <math>2^\circ</math> W, 62.5 lks. dist., mkd. X at breast height and BT at base.</p> <p>Set a steel fence post alongside the cor.</p>	
50.33	<p>Point for the center S-N <math>\frac{1}{64}</math> sec. cor. of sec. 20.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 33 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">C S-N <math>\frac{1}{64}</math>   S20 C 1982</p> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 29 ins. diam., bears N <math>7^\circ</math> E, 1.49 chs. dist., mkd. C S N <math>\frac{1}{64}</math> S20 BT.</p> <p style="padding-left: 40px;">An alligator juniper, 8 ins. diam., bears N <math>49^\circ</math> W, 1.49 chs. dist., mkd. C S N <math>\frac{1}{64}</math> S20 BT.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 98 lks. E of a track road, bears N <math>30^\circ</math> E and S <math>30^\circ</math> W.</p>	
60.42	<p>Point for the center N <math>\frac{1}{16}</math> sec. cor. of sec. 20.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 33 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">C N <math>\frac{1}{16}</math>   S20 C 1982</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 19 ins. diam., bears S <math>54^\circ</math> E, 75 lks. dist., mkd. C N <math>\frac{1}{16}</math> S20 BT.</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears S <math>74^\circ</math> W, 28 lks. dist., mkd. C N <math>\frac{1}{16}</math> S20 BT.</p> <p>Set a steel fence post alongside the cor.</p>	
80.60	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 17 and 20.</p>	

Subdivision of Section 20  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	From the $\frac{1}{4}$ sec. cor. of secs. 20 and 21.	
	N $89^{\circ}41'$ W, on the E and W center line of sec. 20.	
40.00	The center $\frac{1}{4}$ sec. cor. of sec. 20.	
49.42	Point for the center E-W $\frac{1}{64}$ sec. cor. of sec. 20; not monumented.	
58.84	Point for the center W $\frac{1}{16}$ sec. cor. of sec. 20.	
	Set an aluminum post, 72 ins. long, $\frac{3}{4}$ in. diam., 66 ins. in the ground, with cap mkd.	
	$C \frac{W \frac{1}{16}}{S20} C$	
	1982	
	Set a steel fence post alongside the cor.	
	Cor. is located 1.75 chs. W of a N and S fence.	
	Cor. falls on the W edge of a wash, 30 lks. wide, drains N $15^{\circ}$ E.	
68.26	Point for the center W-W $\frac{1}{64}$ sec. cor. of sec. 20; not monumented.	
77.68	The $\frac{1}{4}$ sec. cor. of secs. 19 and 20.	
	<hr/> SW $\frac{1}{4}$ of Section 20	
	From the W $\frac{1}{16}$ sec. cor. of secs. 20 and 29.	
	N $1^{\circ}28'$ E, on the N and S center line of the SW $\frac{1}{4}$ of sec. 20.	
20.16	Point for the SW $\frac{1}{16}$ sec. cor., at intersection with the E and W center line of the SW $\frac{1}{4}$ of sec. 20.	
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 32 ins. in the ground, with cap mkd.	
	SW $\frac{1}{16}$ S20	
	1982	
	from which	
	A fence cor., bears East, 1.67 chs. dist., fence extends N and W.	
	Cor. is located 26 lks. S of an E and W fence.	
30.24	Point for the center N-SW $\frac{1}{64}$ sec. cor. of sec. 20; not monumented.	
40.32	The center W $\frac{1}{16}$ sec. cor. of sec. 20.	
	<hr/> From the center S $\frac{1}{16}$ sec. cor. of sec. 20.	
	N $89^{\circ}47'$ W, on the E and W center line of the SW $\frac{1}{4}$ of sec. 20.	
19.40	The SW $\frac{1}{16}$ sec. cor. of sec. 20.	

Subdivision of Section 20  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
29.10	<p>Point for the center W-SW 1/64 sec. cor. of sec. 20.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S20 C-W-SW 1/64 1982</p> <p>from which</p> <p>An alligator juniper, 10 ins. diam., bears S <math>36^{\circ}</math> E, 49 lks. dist., mkd. C W SW 1/64 S20 BT.</p> <p>A pinyon, 9 ins. diam., bears N <math>67\frac{1}{2}^{\circ}</math> W, 2.02 chs. dist., mkd. C W SW 1/64 S20 BT.</p> <p>Set a steel fence post alongside the cor.</p>
38.80	<p>The S 1/16 sec. cor. of secs. 19 and 20.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center W-SW 1/64 sec. cor. of sec. 20.</p> <p>N <math>2^{\circ}15'</math> E, on the N and S center line of the NW<math>\frac{1}{4}</math> of the SW<math>\frac{1}{4}</math> of sec. 20.</p>
10.09	<p>Point for the NW-SW 1/64 sec. cor., at intersection with the E and W center line of the NW<math>\frac{1}{4}</math> of the SW<math>\frac{1}{4}</math> of sec. 20.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S20 NW-SW 1/64 1982</p> <p>from which</p> <p>A fence cor., bears N <math>82^{\circ}</math> E, 92 lks. dist., fence extends S and W.</p> <p>An alligator juniper, 12 ins. diam., bears S <math>28^{\circ}</math> W, 19 lks. dist., mkd. NW SW 1/64 S20 BT.</p> <p>Set a steel fence post alongside the cor.</p>
20.18	<p>Point for the center W-W 1/64 sec. cor. of sec. 20.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the point for the center N-SW 1/64 sec. cor. of sec. 20.</p> <p>N <math>89^{\circ}47'</math> W, on the E and W center line of the NW<math>\frac{1}{4}</math> of the SW<math>\frac{1}{4}</math> of sec. 20.</p>
9.56	<p>The NW-SW 1/64 sec. cor. of sec. 20.</p>
19.12	<p>The N-S 1/64 sec. cor. of secs. 19 and 20.</p>



Subdivision of Section 20  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

NW $\frac{1}{4}$  of Section 20

From the center W 1/16 sec. cor. of sec. 20.

N 1°49' W, on the N and S center line of the NW $\frac{1}{4}$  of sec. 20.

10.12 Point for the center S-NW 1/64 sec. cor. of sec. 20.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 32 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.

S20  
C-S-NW  
1/64  
1982

from which

A spike in a fence cor., bears S 83° E,  
2.465 chs. dist., fence extends S and W.

Set a steel fence post alongside the cor.

Cor. falls in an open field, 2.30 chs. W of a wash,  
40 lks. wide, drains N 15° E.

20.24 Point for the NW 1/16 sec. cor., at intersection with  
the E and W center line of the NW $\frac{1}{4}$  of sec. 20.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 32 ins. in the ground, with cap mkd.

NW 1/16 S20  
1982

Set a steel fence post alongside the cor.

Cor. falls in a cleared area.

40.48 The W 1/16 sec. cor. of secs. 17 and 20.

From the center N 1/16 sec. cor. of sec. 20.

N 89°30' W, on the E and W center line of the NW $\frac{1}{4}$  of sec. 20.

9.72 Point for the center E-NW 1/64 sec. cor. of sec. 20.

Set a finned aluminum post, 28 ins. long,  $\frac{3}{4}$  in. diam., 14 ins. in the ground, in a mound of stone, 2 $\frac{1}{2}$  ft. base, to top, with cap mkd.

S20  
C-E-NW  
1/64  
1986

from which

A pinyon, 4 ins. diam., bears N 35° E, 95.5 lks. dist., mkd. X at breast height and BT at the base.

Subdivision of Section 20  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
	Set a steel fence post alongside the cor.
19.44	The NW 1/16 sec. cor. of sec. 20.
38.88	The N 1/16 sec. cor. of secs. 19 and 20.
	<hr/> From the center E-NW 1/64 sec. cor. of sec. 20. N 0°59' W, on the N and S center line of the NE <sup>1</sup> / <sub>4</sub> of the NW <sup>1</sup> / <sub>4</sub> of sec. 20.
20.21	The E-W 1/64 sec. cor. of secs. 17 and 20.
	<hr/> From the point for the center E-W 1/64 sec. cor. of sec. 20. N 0°59' W, on the N and S center line of the SE <sup>1</sup> / <sub>4</sub> of the NW <sup>1</sup> / <sub>4</sub> of sec. 20.
10.10	Point for the SE-NW 1/64 sec. cor., at intersection with the E and W center line of the SE <sup>1</sup> / <sub>4</sub> of the NW <sup>1</sup> / <sub>4</sub> of sec. 20.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.
	S20 SE-NW 1/64 1982
	from which
	A pine, 5 ins. diam., bears S 36° E, 81 lks. dist., mkd. X at breast height and BT at base.
	A fence cor., bears S 87° E, 1.90 chs. dist., fence extends N and W.
	Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.
20.21	The center E-NW 1/64 sec. cor. of sec. 20.
	<hr/> From the center S-N 1/64 sec. cor. of sec. 20. N 89°35' W, on the E and W center line of the SE <sup>1</sup> / <sub>4</sub> of the NW <sup>1</sup> / <sub>4</sub> of sec. 20.
9.57	The SE-NW 1/64 sec. cor. of sec. 20.
19.14	The center S-NW 1/64 sec. cor. of sec. 20.
	<hr/> Subdivision of Section 21 T 12 N, R 18 E, Gila and Salt River Mer., Arizona
	From the 1/4 sec. cor. of secs. 21 and 28.
	N 0°03' W, on the N and S center line of sec. 21.
20.18	Point for the center S 1/16 sec. cor. of sec. 21.

Subdivision of Section 21  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 32 ins. in the ground, with cap mkd.

C  
S 1/16 | S21  
C  
1983

Set a steel fence post alongside the cor.

40.36 Point for the center  $\frac{1}{4}$  sec. cor., at intersection with the E and W center line of sec. 21.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 32 ins. in the ground, with cap mkd.

T12N R18E  
C  $\frac{1}{4}$  S21  
1983

Set a steel fence post alongside the cor.

80.77 The  $\frac{1}{4}$  sec. cor. of secs. 16 and 21.

From the  $\frac{1}{4}$  sec. cor. of secs. 21 and 22.

S 89°39' W, on the E and W center line of sec. 21.

Over open terrain.

10.205 Point for the center E-E 1/64 sec. cor. of sec. 21.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 30 ins. in the ground, with cap mkd.

C  $\frac{E-E 1/64}{S21}$  C  
1983

Set a steel fence post alongside the cor.

Cor. is located 54 lks. S of an E and W fence.

20.41 Point for the center E 1/16 sec. cor. of sec. 21.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 28 ins. in the ground, in a mound of stone, 2 $\frac{1}{2}$  ft. base, to top, with cap mkd.

C  $\frac{E 1/16}{S21}$  C  
1983

from which

A fence cor., bears N 17 $\frac{1}{2}$ ° W, 62 lks. dist.,  
fences extend E and S.

Set a steel fence post alongside the cor.

40.82 The center  $\frac{1}{4}$  sec. cor. of sec. 21.

81.57 The  $\frac{1}{4}$  sec. cor. of secs. 20 and 21.

SE $\frac{1}{4}$  of Section 21

Subdivision of Section 21  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>From the E 1/16 sec. cor. of secs. 21 and 28.</p>	
	<p>N 0°08' W, on the N and S center line of the SE<math>\frac{1}{4}</math> of sec. 21.</p>	
20.28	<p>Point for the SE 1/16 sec. cor., at intersection with the E and W center line of the SE<math>\frac{1}{4}</math> of sec. 21.</p>	
	<p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, 6 ins. high, with cap mkd.</p>	
	<p style="text-align: center;">SE 1/16 S21 1983</p>	
	<p>Set a steel fence post alongside the cor.</p>	
	<p>Cor. is located 15 lks. E of a N and S fence.</p>	
30.42	<p>Point for the center N-SE 1/64 sec. cor. of sec. 21.</p>	
	<p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 28 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">S21 C-N-SE 1/64 1983</p>	
	<p>Set a steel fence post alongside the cor.</p>	
	<p>Cor. is located 18 lks. E of a N and S fence.</p>	
40.56	<p>The center E 1/16 sec. cor. of sec. 21.</p>	
	<hr style="width: 20%; margin: auto;"/> <p>From the S 1/16 sec. cor. of secs. 21 and 22.</p>	
	<p>S 89°54' W, on the E and W center line of the SE<math>\frac{1}{4}</math> of sec. 21.</p>	
10.22	<p>Point for the center E-SE 1/64 sec. cor. of sec. 21.</p>	
	<p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 31 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">S21 C-E-SE 1/64 1983</p>	
	<p>Set a steel fence post alongside the cor.</p>	
15.33	<p>Point for the center W-E-SE 1/256 sec. cor. of sec. 21.</p>	
	<p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p>	
	<p style="text-align: center;">S21 C-W-E-SE 1/256 1983</p>	
	<p>Set a steel fence post alongside the cor.</p>	
20.44	<p>The SE 1/16 sec. cor. of sec. 21.</p>	

Subdivision of Section 21  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
40.87	<p>The center S 1/16 sec. cor. of sec. 21.</p> <hr/> <p>From the center E-SE 1/64 sec. cor. of sec. 21.</p> <p>N 0°10' W, on the N and S center line of the NE<sup>1</sup>/<sub>4</sub> of the SE<sup>1</sup>/<sub>4</sub> of sec. 21.</p>
10.16	<p>Point for the NE-SE 1/64 sec. cor., at intersection with the E and W center line of the NE<sup>1</sup>/<sub>4</sub> of the SE<sup>1</sup>/<sub>4</sub> of sec. 21.</p> <p>Set an aluminum post, 36 ins. long, <sup>3</sup>/<sub>4</sub> in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S21 NE-SE 1/64 1983</p> <p>Set a steel fence post alongside the cor.</p>
20.32	<p>The center E-E 1/64 sec. cor. of sec. 21.</p> <hr/> <p>From the N-S 1/64 sec. cor. of secs. 21 and 22.</p> <p>S 89°46' W, on the E and W center line of the NE<sup>1</sup>/<sub>4</sub> of the SE<sup>1</sup>/<sub>4</sub> of sec. 21.</p>
10.21	<p>The NE-SE 1/64 sec. cor. of sec. 21.</p>
15.32	<p>Point for the center W-NE-SE 1/256 sec. cor. of sec. 21.</p> <p>Set an aluminum post, 36 ins. long, <sup>3</sup>/<sub>4</sub> in. diam., 26 ins. in the ground, in a mound of stone, 2<sup>1</sup>/<sub>2</sub> ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S21 C-W-NE-SE 1/256 1983</p> <p>Set a steel fence post alongside the cor.</p>
20.43	<p>The center N-SE 1/64 sec. cor. of sec. 21.</p> <hr/> <p>From the center W-E-SE 1/256 sec. cor. of sec. 21.</p> <p>N 0°09' W, on the N and S center line of the SW<sup>1</sup>/<sub>4</sub> of the NE<sup>1</sup>/<sub>4</sub> of the SE<sup>1</sup>/<sub>4</sub> of sec. 21.</p>
10.15	<p>The center W-NE-SE 1/256 sec. cor. of sec. 21.</p>
<p>Subdivision of Section 22 T 12 N, R 18 E, Gila and Salt River Mer., Arizona</p>	
10.16	<p>From the <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 22 and 27.</p> <p>N 0°02' E, on the N and S center line of sec. 22.</p> <p>Point for the center S-S 1/64 sec. cor. of sec. 22.</p>

Subdivision of Section 22  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

## CHAINS

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 32 ins. in the ground, with cap mkd.

C  
S-S 1/64 | S22  
C  
1983

Set a steel fence post alongside the cor.

20.32 Point for the center S 1/16 sec. cor. of sec. 22, falls at the W edge of graded road No. 332.

Set a rebar, 12 ins. long,  $\frac{1}{2}$  in. diam., 12 ins. under the surface of the road and over the rebar set a brass tablet,  $3\frac{1}{4}$  ins. diam., with a  $3\frac{1}{2}$  in. stem, in concrete, mkd.

C  
S 1/16 | S22  
C  
1983

from which

An aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., set 30 ins. in the ground, for a reference monument, bears S  $85^\circ$  W, 22.24 ft. dist., with cap mkd. C S 1/16 S22 RM 22.24 FT 1983, and an arrow pointing to the cor.

An aluminum post, 28 ins. long, 1 in. diam., set 20 ins. in the ground, for a reference monument, bears N  $7\frac{1}{2}^\circ$  W, 23.50 ft. dist., with cap mkd. C S 1/16 S22 RM 23.50 FT 1983, and an arrow pointing to the cor.

Cor is 10 lks. W of the center of graded road No. 332, bears NE and SW.

30.48 Point for the center N-S 1/64 sec. cor. of sec. 22.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 30 ins. in the ground, with cap mkd.

C  
N-S 1/64 | S22  
C  
1983

Set a steel fence post alongside the cor.

35.56 Point for the center N-N-S 1/256 sec. cor. of sec. 22.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 30 ins. in the ground, with cap mkd.

C  
N-N-S | S22  
1/256 |  
C  
1983

from which

A ponderosa pine, 8 ins. diam., bears N  $56^\circ$  W, 64.5 lks. dist., mkd. C N N S 1/256 S22 BT.

Subdivision of Section 22  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
40.64	<p>A fence cor. bears N 51° W, 72.5 lks. dist., fence extends N and W.</p> <p>Set a steel fence post alongside the cor.</p> <p>Point for the center ¼ sec. cor., at intersection with the E and W center line of sec. 22.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 31 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E C ¼ S22 1983</p> <p>from which</p> <p>A pine, 4 ins. diam., bears N 6½° W, 93.5 lks. dist., mkd. X at breast height and BT at base.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 39 lks. E of a N and S fence.</p>
60.98	<p>Point for the center N 1/16 sec. cor. of sec. 22.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">C N 1/16   S22 C 1983</p> <p>from which</p> <p>A pine, 4 ins. diam., bears S 32° W, 76 lks. dist., mkd. X at breast height and BT at base.</p> <p>Set a steel fence post alongside the cor.</p>
76.24	<p>Point for the center N-N-N 1/256 sec. cor. of sec. 22.</p> <p>Set an aluminum post, 36 ins. long, ¾ in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">C N-N-N   S22 1/256   C 1983</p> <p>Set a steel fence post alongside the cor.</p>
81.32	<p>The ¼ sec. cor. of secs. 15 and 22.</p> <hr/> <p>From the ¼ sec. cor. of secs. 22 and 23.</p> <p>S 89°54' W, on the E and W center line of sec. 22.</p>
20.53	<p>Point for the center E 1/16 sec. cor. of sec. 22.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 16 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p>

Subdivision of Section 22  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	$C \frac{E \ 1/16}{S22} C$ <p style="text-align: center;">1983</p> <p>Set a steel fence post alongside the cor.</p>	
41.06	The center $\frac{1}{4}$ sec. cor. of sec. 22.	
51.26	<p>Point for the center E-W 1/64 sec. cor. of sec. 22.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 32 ins. in the ground, with cap mkd.</p> $C \frac{E-W \ 1/64}{S22} C$ <p style="text-align: center;">1983</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S <math>34\frac{1}{2}^\circ</math> W, 86.5 lks. dist., mkd. C E W 1/64 S22 BT.</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears N <math>14^\circ</math> W, 55 lks. dist., mkd. X at breast height and BT at base.</p> <p>Set a steel fence post alongside the cor.</p>	
61.46	<p>Point for the center W 1/16 sec. cor. of sec. 22.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 32 ins. in the ground, with cap mkd.</p> $C \frac{W \ 1/16}{S22} C$ <p style="text-align: center;">1983</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N <math>22^\circ</math> E, 1.20 chs. dist., mkd. C W 1/16 S22 BT.</p> <p>Set a steel fence post alongside the cor.</p>	
71.66	Point for the center W-W 1/64 sec. cor. of sec. 22; not monumented.	
81.86	The $\frac{1}{4}$ sec. cor. of secs. 21 and 22.	
	<hr/> <p>NE<math>\frac{1}{4}</math> of Section 22</p> <hr/>	
20.33	<p>From the center E 1/16 sec. cor. of sec. 22.</p> <p>N <math>0^\circ 03'</math> W, on the N and S center line of the NE<math>\frac{1}{4}</math> of sec. 22.</p> <p>Point for the NE 1/16 sec. cor., at intersection with the E and W center line of the NE<math>\frac{1}{4}</math> of sec. 22.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 31 ins. in the ground, with cap mkd.</p> $NE \ 1/16 \ S22$ <p style="text-align: center;">1983</p> <p>Set a steel fence post alongside the cor.</p>	



Subdivision of Section 22  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
30.50	Point for the center N-NE 1/64 sec. cor. of sec. 22, not monumented.	
35.585	Point for the center N-N-NE 1/256 sec. cor. of sec. 22.  Set a finned aluminum post, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, with cap mkd.	
	S22 C-N-N-NE 1/256 1986	
	Set a steel fence post alongside the cor.	
40.67	The E 1/16 sec. cor. of secs. 15 and 22.	
	_____	
	From the N 1/16 sec. cor. of secs. 22 and 23.	
	S 89°53' W, on the E and W center line of the NE 1/4 of sec. 22.	
5.125	Point for the center E-E-NE 1/256 sec. cor. of sec. 22.	
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with cap mkd.	
	S22 C-E-E-NE 1/256 1983	
	Set a steel fence post alongside the cor.	
10.25	Point for the center E-NE 1/64 sec. cor. of sec. 22; not monumented.	
20.50	The NE 1/16 sec. cor. of sec. 22.	
41.00	The center N 1/16 sec. cor. of sec. 22.	
	_____	
	From the point for the center E-NE 1/64 sec. cor. of sec. 22.	
	N 0°06' W, on the N and S center line of the NE 1/4 of the NE 1/4 of sec. 22.	
10.16	Point for the NE-NE 1/64 sec. cor., at intersection with the E and W center line of the NE 1/4 of the NE 1/4 of sec. 22; not monumented.	
15.24	Point for the center N-NE-NE 1/256 sec. cor. of sec. 22; not monumented.	
20.32	The E-E 1/64 sec. cor. of secs. 15 and 22.	
	_____	
	From the N-N 1/64 sec. cor. of secs. 22 and 23.	
	S 89°54' W, on the E and W center line of the NE 1/4 of the NE 1/4 of sec. 22.	
5.12	Point for the center E-NE-NE 1/256 sec. cor. of sec. 22; not monumented.	

Subdivision of Section 22  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
10.24	The point for the NE-NE 1/64 sec. cor. of sec. 22.
20.48	The point for the center N-NE 1/64 sec. cor. of sec. 22.
	<hr/> From the point for the center E-NE-NE 1/256 sec. cor. of sec. 22.
	N 0°07' W, on the N and S center line of the NE <sup>1</sup> / <sub>4</sub> of the NE <sup>1</sup> / <sub>4</sub> of the NE <sup>1</sup> / <sub>4</sub> of sec. 22.
5.08	Point for the NE-NE-NE 1/256 sec. cor., at intersection with the E and W center line of the NE <sup>1</sup> / <sub>4</sub> of the NE <sup>1</sup> / <sub>4</sub> of the NE <sup>1</sup> / <sub>4</sub> of sec. 22.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	S22 NE-NE-NE 1/256 1983
	Deposit broken glass at the base of the iron post.
	Set a steel fence post alongside the cor.
10.16	The E-E-E 1/256 sec. cor. of secs. 15 and 22.
	<hr/> From the N-N-N 1/256 sec. cor. of secs. 22 and 23.
	S 89°55' W, on the E and W center line of the NE <sup>1</sup> / <sub>4</sub> of the NE <sup>1</sup> / <sub>4</sub> of the NE <sup>1</sup> / <sub>4</sub> of sec. 22.
5.12	The NE-NE-NE 1/256 sec. cor. of sec. 22.
10.24	The point for the center N-NE-NE 1/256 sec. cor. of sec. 22.
	<hr/> SW <sup>1</sup> / <sub>4</sub> of Section 22
	<hr/> From the W 1/16 sec. cor. of secs. 22 and 27.
	N 0°04' W, on the N and S center line of the SW <sup>1</sup> / <sub>4</sub> of sec. 22.
10.17	Point for the center S-SW 1/64 sec. cor. of sec. 22.
	Set an aluminum post, 36 ins. long, ¾ in. diam., 32 ins. in the ground, with cap mkd.
	S22 C-S-SW 1/64 1983
	Set a steel fence post alongside the cor.
15.255	Point for the center N-S-SW 1/256 sec. cor. of sec. 22.
	Set an aluminum post, 36 ins. long, ¾ in. diam., 32 ins. in the ground, with cap mkd.

Subdivision of Section 22  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

S22  
C-N-S-SW  
1/256  
1983

from which

A juniper, 8 ins. diam., bears N 42° E, 50 lks.  
dist., mkd. C N S SW 1/256 S22 BT.

Set a steel fence post alongside the cor.

Cor. is located 73 lks. S of an E and W fence.

20.34 Point for the SW 1/16 sec. cor., at intersection with  
the E and W center line of the SW 1/4 of sec. 22.

Set an aluminum post, 36 ins. long, 3/4 in. diam., 24 ins.  
in the ground, in a mound of stone, 3 ft. base, to top,  
with cap mkd.

SW 1/16 S22  
1983

from which

A juniper, 8 ins. diam., bears S 7° E,  
1.445 chs. dist., mkd. SW 1/16 S22 BT.

Set a steel fence post alongside the cor.

30.51 Point for the center N-SW 1/64 sec. cor. of sec. 22.

Set an aluminum post, 36 ins. long, 3/4 in. diam., 20 ins.  
in the ground, in a mound of stone, 2 1/2 ft. base, to  
top, with cap mkd.

S22  
C-N-SW  
1/64  
1983

from which

A ponderosa pine, 4 ins. diam., bears N 38° E,  
33 lks. dist., mkd. X at breast height and  
BT at base.

40.68 The center W 1/16 sec. cor. of sec. 22.

From the center S 1/16 sec. cor. of sec. 22.

S 89° 52' W, on the E and W center line of the SW 1/4 of  
sec. 22.

10.18 Point for the center E-SW 1/64 sec. cor. of sec. 22.

Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins.  
in the ground, with cap mkd.

S22  
C-E-SW  
1/64  
1983

Set a steel fence post alongside the cor.

Subdivision of Section 22  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
15.27	<p>Point for the center W-E-SW 1/256 sec. cor. of sec. 22.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S22 C-W-E-SW 1/256 1983</p> <p>from which</p> <p style="text-align: center;">An alligator juniper, 14 ins. diam., bears S 60° W, 1.675 chs. dist., mkd. C W E SW 1/256 S22 BT.</p> <p>Set a steel fence post alongside the cor.</p>
20.36	The SW 1/16 sec. cor. of sec. 22.
40.72	The S 1/16 sec. cor. of secs. 21 and 22.
	<p style="text-align: center;">_____</p> <p>From the center E-SW 1/64 sec. cor. of sec. 22.</p> <p>N 0°01' W, on the N and S center line of the NE<math>\frac{1}{4}</math> of the SW<math>\frac{1}{4}</math> of sec. 22.</p>
5.08	<p>Point for the center S-NE-SW 1/256 sec. cor. of sec. 22.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S22 C-S-NE-SW 1/256 1983</p> <p>from which</p> <p style="text-align: center;">A juniper, 6 ins. diam., bears N 38° W, 68 lks. dist., mkd. C S NE SW 1/256 S22 BT.</p> <p>Set a steel fence post alongside the cor.</p>
10.16	<p>Point for the NE-SW 1/64 sec. cor., at intersection with the E and W center line of the NE<math>\frac{1}{4}</math> of the SW<math>\frac{1}{4}</math> of sec. 22.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S22 NE-SW 1/64 1983</p> <p>from which</p> <p style="text-align: center;">An alligator juniper, 8 ins. diam., bears S 21° W, 94.5 lks. dist., mkd. NE SW 1/64 S22 BT.</p> <p>Set a steel fence post alongside the cor.</p>
15.24	Point for the center N-NE-SW 1/256 sec. cor. of sec. 22.

Subdivision of Section 22  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

## CHAINS

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 32 ins. in the ground, with cap mkd.

S22  
C-N-NE-SW  
1/256  
1983

from which

A fence cor., bears S  $86^{\circ}$  E, 46.5 lks. dist., fences extend E and S  $20^{\circ}$  W.

A juniper, 8 ins. diam., bears S  $40^{\circ}$  W, 1.09 chs. dist., mkd. C N NE SW 1/256 S22 BT.

20.32 The center E-W 1/64 sec. cor. of sec. 22.

From the center N-S 1/64 sec. cor. of sec. 22.

S  $89^{\circ}52'$  W, on the E and W center line of the NE $\frac{1}{4}$  of the SW $\frac{1}{4}$  of sec. 22.

10.19 The NE-SW 1/64 sec. cor. of sec. 22.

20.38 The center N-SW 1/64 sec. cor. of sec. 22.

From the center N-N-S 1/256 sec. cor. of sec. 22.

S  $89^{\circ}53'$  W, on the E and W center line of the NE $\frac{1}{4}$  of the SW $\frac{1}{4}$  of the SW $\frac{1}{4}$  of sec. 22.

10.19 The center N-NE-SW 1/256 sec. cor. of sec. 22.

From the center W-E-SW 1/256 sec. cor. of sec. 22.

N  $0^{\circ}03'$  W, on the N and S center line of the SW $\frac{1}{4}$  of the NE $\frac{1}{4}$  of the SW $\frac{1}{4}$  of sec. 22.

5.08 Point for the SW-NE-SW 1/256 sec. cor. of sec. 22.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 30 ins. in the ground, with cap mkd.

S22  
SW-NE-SW  
1/256  
1983

from which

A juniper, 8 ins. diam., bears S  $71^{\circ}$  W, 30.5 lks. dist., mkd. SW NE SW 1/256 S22 BT.

Set a steel fence post alongside the cor.

N  $89^{\circ}52'$  E, on the E and W center line of the SW $\frac{1}{4}$  of the NE $\frac{1}{4}$  of the SW $\frac{1}{4}$  of sec. 22.

5.09 The center S-NE-SW 1/256 sec. cor. of sec. 22.

From the E-W 1/64 sec. cor. of secs. 22 and 27.

Subdivision of Section 22  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>N 0°01' W, on the N and S center line of the SE<sup>1</sup>/<sub>4</sub> of the SW<sup>1</sup>/<sub>4</sub> of sec. 22.</p>
10.17	<p>Point for the SE-SW 1/64 sec. cor., at intersection with the E and W center line of the SE<sup>1</sup>/<sub>4</sub> of the SW<sup>1</sup>/<sub>4</sub> of sec. 22.</p>
	<p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S22 SE-SW 1/64 1983</p>
20.33	<p>Set a steel fence post alongside the cor.</p> <p>The center E-SW 1/64 sec. cor. of sec. 22</p> <hr style="width: 20%; margin: 0 auto;"/>
	<p>From the center S-S 1/64 sec. cor. of sec. 22.</p> <p>S 89°50' W, on the E and W center line of the SE<sup>1</sup>/<sub>4</sub> of the SW<sup>1</sup>/<sub>4</sub> of sec. 22.</p>
10.17	<p>The SE-SW 1/64 sec. cor. of sec. 22.</p>
20.33	<p>The center S-SW 1/64 sec. cor. of sec. 22.</p> <hr style="width: 20%; margin: 0 auto;"/>
	<p>From the center W-E-SW 1/256 sec. cor. of sec. 22.</p> <p>S 0°02' E, on the N and S center line of the NW<sup>1</sup>/<sub>4</sub> of the SE<sup>1</sup>/<sub>4</sub> of the SW<sup>1</sup>/<sub>4</sub> of sec. 22.</p>
5.08	<p>Point for the NW-SE-SW 1/256 sec. cor. of sec. 22.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S22 NW-SE-SW 1/256 1983</p>
	<p>from which</p> <p style="padding-left: 40px;">A fence cor., bears N 36° W, 54 lks. dist., fence extends N and W.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 1.80 chs. N of graded road No. 332, bears N 80° E and S 80° W.</p> <hr style="width: 20%; margin: 0 auto;"/>
	<p>S 89°51' W, on the E and W center line of the NW<sup>1</sup>/<sub>4</sub> of the SE<sup>1</sup>/<sub>4</sub> of the SW<sup>1</sup>/<sub>4</sub> of sec. 22.</p>
5.09	<p>The center N-S-SW 1/256 sec. cor. of sec. 22.</p> <hr style="width: 20%; margin: 0 auto;"/> <p style="text-align: center;">NW<sup>1</sup>/<sub>4</sub> of Section 22</p> <hr style="width: 20%; margin: 0 auto;"/> <p>From the center W 1/16 sec. cor. of sec. 22.</p>

Subdivision of Section 22  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	N 0°04' W, on the N and S center line of the NW $\frac{1}{4}$ of sec. 22.	
10.18	Point for the center S-NW 1/64 sec. cor. of sec. 22.	
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 32 ins. in the ground, with cap mkd.	
	<p style="text-align: center;">S22 C-S-NW 1/64 1983</p>	
	Set a steel fence post alongside the cor.	
20.36	Point for the NW 1/16 sec. cor., at intersection with the E and W center line of the NW $\frac{1}{4}$ of sec. 22.	
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 32 ins. in the ground, with cap mkd.	
	<p style="text-align: center;">NW 1/16 S22 1983</p>	
	Set a steel fence post alongside the cor.	
	Cor. is located 80 lks. N of a wash, 60 lks. wide, drains S 80° E from S 55° W.	
30.54	Point for the center N-NW 1/64 sec. cor. of sec. 22.	
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 32 ins. in the ground, with cap mkd.	
	<p style="text-align: center;">S22 C-N-NW 1/64 1983</p>	
	Set a steel fence post alongside the cor.	
35.63	Point for the center N-N-NW 1/256 sec. cor. of sec. 22.	
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 31 ins. in the ground, with cap mkd.	
	<p style="text-align: center;">S22 C-N-N-NW 1/256 1983</p>	
	Set a steel fence post alongside the cor.	
	Cor. is located 1.05 chs. E of a track road, bears N 15° E and S 15° W, and 1.93 chs. E of a fence, bears N 30° E and S 30° W.	
40.72	The W 1/16 sec. cor. of secs. 15 and 22.	
	<p style="text-align: center;">_____</p>	
	From the center N 1/16 sec. cor. of sec. 22.	
	S 89°55' W, on the E and W center line of the NW $\frac{1}{4}$ of sec. 22.	
20.43	The NW 1/16 sec. cor. of sec. 22.	

Subdivision of Section 22  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
28.90	Powerline and new fence, bear N 20° E and S 20° W, approximately 90 lks., thence S 35° W.	
30.65	Point for the center W-NW 1/64 sec. cor. of sec. 22.	
	Set a finned aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, with cap mkd.	
	S22 C-W-NW 1/64 1986	
	Set a steel fence post alongside the cor.	
40.87	The N 1/16 sec. cor. of secs. 21 and 22.	
	From the point for the center W-W 1/64 sec. cor. of sec. 22.	
	N 0°08' W, on the N and S center line of the SW 1/4 of the NW 1/4 of sec. 22.	
10.18	Point for the SW-NW 1/64 sec. cor., at intersection with the E and W center line of the SW 1/4 of the NW 1/4 of sec. 22; not monumented.	
15.27	Point for the center N-SW-NW 1/256 sec. cor. of sec. 22.	
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 33 ins. in the ground, with cap mkd.	
	S22 C-N-SW-NW 1/256 1983	
	Set a steel fence post alongside the cor.	
	Cor. is located 20 lks. E of a track road, bears N 50° E and S 50° W, and 1.02 chs. E of a fence, bears N 35° E and S 35° W.	
20.36	The center W-NW 1/64 sec. cor. of sec. 22.	
	From the center S-NW 1/64 sec. cor. of sec. 22.	
	S 89°54' W, on the E and W center line of the SW 1/4 of the NW 1/4 of sec. 22.	
10.20	The point for the SW-NW 1/64 sec. cor. of sec. 22.	
20.41	The S-N 1/64 sec. cor. of secs. 21 and 22.	
	From the center N-SW-NW 1/256 sec. cor. of sec. 22.	
	S 89°55' W, on the E and W center line of the NW 1/4 of the SW 1/4 of the NW 1/4 of sec. 22.	
10.21	The N-S-N 1/256 sec. cor. of secs. 21 and 22.	
	From the center W-NW 1/64 sec. cor. of sec. 22.	



Subdivision of Section 22  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

N 0°07' W, on the N and S center line of the NW<sup>1</sup>/<sub>4</sub> of the NW<sup>1</sup>/<sub>4</sub> of sec. 22.

5.09 Point for the center S-NW-NW 1/256 sec. cor. of sec. 22.

Set an aluminum post, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with cap mkd.

S22  
C-S-NW-NW  
1/256  
1983

Set a steel fence post alongside the cor.

10.18 Point for the NW-NW 1/64 sec. cor., at intersection with the E and W center line of the NW<sup>1</sup>/<sub>4</sub> of the NW<sup>1</sup>/<sub>4</sub> of sec. 22; not monumented.

20.36 The W-W 1/64 sec. cor. of secs. 15 and 22.

From the center N-NW 1/64 sec. cor. of sec. 22.

S 89°55' W, on the E and W center line of the NW<sup>1</sup>/<sub>4</sub> of the NW<sup>1</sup>/<sub>4</sub> of sec. 22.

5.11 Point for the center E-NW-NW 1/256 sec. cor. of sec. 22, not monumented.

10.22 The point for the NW-NW 1/64 sec. cor. of sec. 22.

20.45 The N-N 1/64 sec. cor. of secs. 21 and 22.

From the point for the center E-NW-NW 1/256 sec. cor. of sec. 22.

N 0°05' W, on the N and S center line of the NE<sup>1</sup>/<sub>4</sub> of the NW<sup>1</sup>/<sub>4</sub> of the NW<sup>1</sup>/<sub>4</sub> of sec. 22.

5.09 Point for the NE-NW-NW 1/256 sec. cor. of sec. 22.

Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.

S22  
NE-NW-NW  
1/256  
1983

Set a steel fence post alongside the cor.

N 89°55' E, on the E and W center line of the NE<sup>1</sup>/<sub>4</sub> of the NW<sup>1</sup>/<sub>4</sub> of the NW<sup>1</sup>/<sub>4</sub> of sec. 22.

5.12 The center N-N-NW 1/256 sec. cor. of sec. 22.

From the point for the center E-NW-NW 1/256 sec. cor. of sec. 22.

S 0°05' E, on the N and S center line of the SE<sup>1</sup>/<sub>4</sub> of the NW<sup>1</sup>/<sub>4</sub> of the NW<sup>1</sup>/<sub>4</sub> of sec. 22.


Subdivision of Section 22  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
5.09	<p>Point for the SE-NW-NW 1/256 sec. cor. of sec. 22.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S22 SE-NW-NW 1/256 1983</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 60 lks. E of a track road, bears N 20° E and S 15° W, and 1.17 chs. E of a fence, bears N 25° E and S 25° W.</p> <hr/> <p>S 89°55' W, on the E and W center line of the SE<math>\frac{1}{4}</math> of the NW<math>\frac{1}{4}</math> of the NW<math>\frac{1}{4}</math> of sec. 22.</p>	
5.11	<p>The center S-NW-NW 1/256 sec. cor. of sec. 22.</p> <hr/> <p style="text-align: center;">Subdivision of Section 26 T 12 N, R 18 E, Gila and Salt River Mer., Arizona</p> <hr/>	
20.17	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 26 and 35.</p> <p>N 0°16' E, on the N and S center line of sec. 26.</p> <p>Point for the center S 1/16 sec. cor. of sec. 26.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E C S 1/16   S26 C 1981</p>	
25.213	<p>Point for the center S-N-S 1/256 sec. cor. of sec. 26, falls in the W track of a dirt road which bears N and S.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 6 ins. below the surface of the road, with cap mkd.</p> <p style="text-align: center;">T12N R18E C S-N-S   S26 1/256   C 1981</p> <p>from which</p> <p>A ponderosa pine, 23 ins. diam., bears N 43° E, 1.58 chs. dist., mkd. C S N S 1/256 S26 BT.</p> <p>A fence cor., bears S 45° W, 44 lks. dist., fences extend N, E and W.</p>	
30.255	<p>Point for the center N-S 1/64 sec. cor. of sec. 26.</p>	

Subdivision of Section 26  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.



from which


A ponderosa pine, 10 ins. diam., bears  
S 33° W, 1.185 chs. dist., mkd. C N S  
1/64 S26 BT.

Cor. is located 81 lks. W of a N and S fence.

40.34

Point for the center 1/4 sec. cor., at intersection with the E and W center line of sec. 26.

Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.




from which

A pinyon, 6 ins. diam., bears N 5° W, 81.5  
lks. dist., mkd. C 1/4 S26 BT.

60.68

Point for the center N 1/16 sec. cor. of sec. 26.

Set an aluminum post, 28 ins. long, 1 in. diam., 16 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with cap mkd.



from which

A juniper, 8 ins. diam., bears N 64° W,  
1.28 chs. dist., mkd. C N 1/16 S26 BT.

Cor. is located 56 lks. W of a N and S fence.

81.02

The 1/4 sec. cor. of secs. 23 and 26.


From the 1/4 sec. cor. of secs. 25 and 26.

N 89°28' W, on the E and W center line of sec. 26.

10.14

Point for the center E-E 1/64 sec. cor. of sec. 26.

Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.



Subdivision of Section 26  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>from which</p> <p>A fence cor., bears N 14° E, 78 lks. dist., fences extend N and W.</p> <p>A ponderosa pine, 8 ins. diam., bears N 85° E, 55 lks. dist., mkd. C E E 1/64 S26 BT.</p> <p>A ponderosa pine, 9 ins. diam., bears S 57° W, 93 lks. dist., mkd. C E E 1/64 S26 BT.</p>	
20.28	<p>Point for the center E 1/16 sec. cor. of sec. 26.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with cap mkd.</p> $  \begin{array}{c}  \text{T12N R18E} \\  \text{C } \frac{\text{E } 1/16}{\text{S26}} \text{ C} \\  1981  \end{array}  $	
	<p>from which</p> <p>A fence cor., bears S 82° E, 1.05 chs. dist., fence extends E and S.</p> <p>A ponderosa pine, 12 ins. diam., bears S 85 1/2° E, 41 lks. dist., mkd. C E 1/16 S26 BT.</p>	
40.56	<p>The center 1/4 sec. cor. of sec. 26.</p>	
60.95	<p>Point for the center W 1/16 sec. cor. of sec. 26.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with cap mkd.</p> $  \begin{array}{c}  \text{T12N R18E} \\  \text{C } \frac{\text{W } 1/16}{\text{S26}} \text{ C} \\  1981  \end{array}  $	
	<p>from which</p> <p>An alligator juniper, 12 ins. diam., bears N 4° E, 96 lks. dist., mkd. C W 1/16 S26 BT.</p> <p>A juniper, 14 ins. diam., bears S 28° W, 39 lks. dist., mkd. C W 1/16 S26 BT.</p>	
81.34	<p>The 1/4 sec. cor. of secs. 26 and 27.</p> <hr/> <p style="text-align: center;">NE 1/4 of Section 26</p> <hr/> <p>From the center E 1/16 sec. cor. of sec. 26.</p> <p>N 0°24' E, on the N and S center line of the NE 1/4 of sec. 26.</p>	
20.36	<p>Point for the NE 1/16 sec. cor., at intersection with the E and W center line of the NE 1/4 of sec. 26.</p>	

Subdivision of Section 26  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

## CHAINS

Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.

T12N R18E  
NE 1/16 S26  
1981

40.71 The E 1/16 sec. cor. of secs. 23 and 26.

From the N 1/16 sec. cor. of secs. 25 and 26.

N 89°32' W, on the E and W center line of the NE $\frac{1}{4}$  of sec. 26.

10.17 Point for the center E-NE 1/64 sec. cor. of sec. 26.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 30 ins. in the ground, with cap mkd.

S26  
C-E-NE  
1/64  
1981

from which

A ponderosa pine, 7 ins. diam., bears S 78° E,  
44 lks. dist., mkd. C E NE 1/64 S26 BT.

20.34 The NE 1/16 sec. cor. of sec. 26.

40.68 The center N 1/16 sec. cor. of sec. 26.

SE $\frac{1}{4}$  of Section 26

From the E 1/16 sec. cor. of secs. 26 and 35.

N 0°07' E, on the N and S center line of the SE $\frac{1}{4}$  of sec. 26.

20.12 Point for the SE 1/16 sec. cor., at intersection with the E and W center line of the SE $\frac{1}{4}$  of sec. 26.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 30 ins. in the ground, in a mound of stone, 2 $\frac{1}{2}$  ft. base, to top, with cap mkd.

T12N R18E  
SE 1/16 S26  
1981

from which

A ponderosa pine, 8 ins. diam., bears N 12° E,  
26.5 lks. dist., mkd. SE 1/16 S26 BT.

A ponderosa pine, 8 ins. diam., bears S 83° W,  
63.5 lks. dist., mkd. SE 1/16 S26 BT.

30.18 Point for the center N-SE 1/64 sec. cor. of sec. 26.

Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 2 $\frac{1}{2}$  ft. base, to top, with cap mkd.

Subdivision of Section 26  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">S26 C-N-SE 1/64 1981</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N 40° E, 43 lks. dist., mkd. C N SE 1/64 S26 BT.</p> <p style="padding-left: 40px;">A fence cor., bears N 85° E, 1.11 chs. dist., fences extend N and W.</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears S 55° E, 58.5 lks. dist., mkd. C N SE 1/64 S26 BT.</p>	
40.24	<p>The center E 1/16 sec. cor. of sec. 26.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the S 1/16 sec. cor. of secs. 25 and 26.</p> <p>N 89°38' W, on the E and W center line of the SE<sup>1</sup>/<sub>4</sub> of sec. 26.</p>	
20.34	<p>The SE 1/16 sec. cor. of sec. 26.</p>	
35.595	<p>Point for the center W-W-SE 1/256 sec. cor. of sec. 26.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S26 C-W-W-SE 1/256 1981</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N 71° E, 41 lks. dist., mkd. C W W SE 1/256 S26 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S 38° E, 78 lks. dist., mkd. C W W SE 1/256 S26 BT.</p>	
35.65	<p>A fence, bears N and S.</p>	
40.68	<p>The center S 1/16 sec. cor. of sec. 26.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center N-SE 1/64 sec. cor. of sec. 26.</p> <p>N 89°34' W, on the E and W center line of the NW<sup>1</sup>/<sub>4</sub> of the SE<sup>1</sup>/<sub>4</sub> of sec. 26.</p>	
20.31	<p>The center N-S 1/64 sec. cor. of sec. 26.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center W-W-SE 1/256 sec. cor. of sec. 26.</p> <p>N 0°14' E, on the N and S center line of the SW<sup>1</sup>/<sub>4</sub> of the NW<sup>1</sup>/<sub>4</sub> of the SE<sup>1</sup>/<sub>4</sub> of sec. 26.</p>	
5.04	<p>Point for the SW-NW-SE 1/256 sec. cor. of sec. 26.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p>	

Subdivision of Section 26  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

S26  
SW-NW-SE  
1/256  
1981

from which

A ponderosa pine, 18 ins. diam., bears N 71° E,  
58.5 lks. dist., mkd. SW NW SE 1/256 S26 BT.

A fence cor., bears S 25° W, 1.155 chs. dist.,  
fences extend N 10° E, S 5° E and N 80° W.

A ponderosa pine, 15 ins. diam., bears N 17° W,  
29.5 lks. dist., mkd. SW NW SE 1/256 S26 BT.

N 89°36' W, on the E and W center line of the SW $\frac{1}{4}$  of  
the NW $\frac{1}{4}$  of the SE $\frac{1}{4}$  of sec. 26.

5.08 The center S-N-S 1/256 sec. cor. of sec. 26.

SW $\frac{1}{4}$  of Section 26

From the W 1/16 sec. cor. of secs. 26 and 35.

N 0°16' E, on the N and S center line of the SW $\frac{1}{4}$  of  
sec. 26.

10.12 Point for the center S-SW 1/64 sec. cor. of sec. 26.

Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins.  
in the ground, with cap mkd.

S26  
C-S-SW  
1/64  
1981

from which

A ponderosa pine, 13 ins. diam., bears N 80° W,  
1.15 chs. dist., mkd. C S SW 1/64 S26 BT.

Cor. is located 95 lks. E of a fence, bears N 40° E  
and S 40° W.

20.24 Point for the SW 1/16 sec. cor., at intersection with  
the E and W center line of the SW $\frac{1}{4}$  of sec. 26.

Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins.  
in the ground, with cap mkd.

T12N R18E  
SW 1/16 S26  
1981

from which

A ponderosa pine, 16 ins. diam., bears N 44° E,  
84.5 lks. dist., mkd. SW 1/16 S26 BT.

A ponderosa pine, 8 ins. diam., bears S 77° W,  
63 lks. dist., mkd. SW 1/16 S26 BT.

Subdivision of Section 26  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
40.48	<p>The center W 1/16 sec. cor. of sec. 26.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 26.</p> <p>N 89°37' W, on the E and W center line of the SW<sup>1</sup>/<sub>4</sub> of sec. 26.</p>
10.19	<p>Point for the center E-SW 1/64 sec. cor. of sec. 26.</p> <p>Set an aluminum post, 36 ins. long, <sup>3</sup>/<sub>4</sub> in. diam., 34 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S26 C-E-SW 1/64 1981</p>
20.38	<p>The SW 1/16 sec. cor. of sec. 26.</p>
30.57	<p>Point for the center W-SW 1/64 sec. cor. of sec. 26; not monumented.</p>
40.76	<p>The S 1/16 sec. cor. of secs. 26 and 27.</p> <hr/> <p>From the center E-SW 1/64 sec. cor. of sec. 26.</p> <p>N 0°16' E, on the N and S center line of the NE<sup>1</sup>/<sub>4</sub> of the SW<sup>1</sup>/<sub>4</sub> of sec. 26.</p>
5.05	<p>Point for the center S-NE-SW 1/256 sec. cor. of sec. 26.</p> <p>Set an aluminum post, 36 ins. long, <sup>3</sup>/<sub>4</sub> in. diam., 30 ins. in the ground, in a mound of stone, 1<sup>1</sup>/<sub>2</sub> ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S26 C-S-NE-SW 1/256 1981</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, which is used as a fence cor., 8 ins. diam., bears N 30° E, 9 lks. dist., mkd. C S NE SW 1/256 S26 BT; fences extend E and S.</p> <hr/> <p>S 89°35' E, on the E and W center line of the SE<sup>1</sup>/<sub>4</sub> of the NE<sup>1</sup>/<sub>4</sub> of the SW<sup>1</sup>/<sub>4</sub> of sec. 26.</p>
10.19	<p>The center S-N-S 1/256 sec. cor. of sec. 26.</p> <hr/> <p>From the W-W 1/64 sec. cor. of secs. 26 and 35.</p> <p>N 0°15' E, on the N and S center line of the SW<sup>1</sup>/<sub>4</sub> of the SW<sup>1</sup>/<sub>4</sub> of sec. 26.</p>
5.065	<p>Point for the center S-SW-SW 1/256 sec. cor. of sec. 26.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.</p>



Subdivision of Section 26  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">S26 C-S-SW-SW 1/256 1981</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 4 ins. diam., bears N 11° E, 59 lks. dist., mkd. X at breast height and BT at base.</p>
10.13	Point for the SW-SW 1/64 sec. cor., at intersection with the E and W center line of the SW <sup>1</sup> / <sub>4</sub> of the SW <sup>1</sup> / <sub>4</sub> of sec. 26, not monumented.
20.26	The point for the center W-SW 1/64 sec. cor. of sec. 26.
	<hr style="width: 20%; margin: 10px auto;"/> <p>From the center S-SW 1/64 sec. cor. of sec. 26.</p> <p>N 89°42' W, on the E and W center line of the SW<sup>1</sup>/<sub>4</sub> of the SW<sup>1</sup>/<sub>4</sub> of sec. 26.</p>
5.10	Point for the center E-SW-SW 1/256 sec. cor. of sec. 26.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.
	<p style="text-align: center;">S26 C-E-SW-SW 1/256 1981</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N 29° E, 1.265 chs. dist., mkd. C E SW SW 1/256 S26 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N 19° W, 1.21 chs. dist., mkd. C E SW SW 1/256 S26 BT.</p>
10.20	The point for the SW-SW 1/64 sec. cor. of sec. 26.
20.39	The point for the S-S 1/64 sec. cor. of secs. 26 and 27.
	<hr style="width: 20%; margin: 10px auto;"/> <p>From the center E-SW-SW 1/256 sec. cor. of sec. 26.</p> <p>S 0°16' W, on the N and S center line of the SE<sup>1</sup>/<sub>4</sub> of the SW<sup>1</sup>/<sub>4</sub> of the SW<sup>1</sup>/<sub>4</sub> of sec. 26.</p>
5.06	Point for the SE-SW-SW 1/256 sec. cor. of sec. 26, falls in the W track of a dirt road, which bears N 40° E and S 40° W.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 2 ins. below the surface of the road, with cap mkd.
	<p style="text-align: center;">S26 SE-SW-SW 1/256 1981</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N 53° W, 74.5 lks. dist., mkd. SE SW SW 1/256 S26 BT.</p>

Subdivision of Section 26  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

Cor. is located 29 lks. W of a fence, bears  
N 40° E and S 40° W.

N 89°45' W, on the E and W center line of the SE<sup>1</sup>/<sub>4</sub> of  
the SW<sup>1</sup>/<sub>4</sub> of the SW<sup>1</sup>/<sub>4</sub> of sec. 26.

5.10 The center S-SW-SW 1/256 sec. cor. of sec. 26.

Subdivision of Section 28  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

From the 1/4 sec. cor. of secs. 28 and 33.

N 0°25' W, on the N and S center line of sec. 28.

Over rolling land, through medium timber.

20.17 Point for the center S 1/16 sec. cor. of sec. 28.

Set an aluminum post, 36 ins. long, 3/4 in. diam., 26 ins.  
in the ground, in a mound of stone, 2 1/2 ft. base, to top,  
with cap mkd.

T12N R18E  
C  
S 1/16 | S28  
C  
1981

from which

An abandoned fence cor., bears S 58° E, 73.5  
lks. dist.

A ponderosa pine, 11 ins. diam., bears N 50° W,  
1.235 chs. dist., mkd. C S 1/16 S28 BT.

40.34 Point for the center 1/4 sec. cor., at intersection with  
the E and W center line of sec. 28.

Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins.  
in the ground, in a mound of stone, 3 ft. base, to top,  
with cap mkd.

T12N R18E  
C 1/4 S28  
1981

Cor. is located 15 lks. W of a N-S fence and 1.54 chs.  
N of an E-W road.

60.54 Point for the center N 1/16 sec. cor. of sec. 28.

Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins.  
in the ground, in a mound of stone, 1 ft. base, to top,  
with cap mkd.

T12N R18E  
C  
N 1/16 | S28  
C  
1981

from which

Subdivision of Section 28  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

A fence cor., bears N 12° E, 10 lks. dist.,  
fences extend E and S.

A juniper, 8 ins. diam., bears S 50° W  
91 lks. dist., mkd. C N 1/16 S28 BT.

A juniper, 6 ins. diam., bears N 29° W,  
1.29 chs. dist., mkd. C N 1/16 S28 BT.

80.74 The 1/4 sec. cor. of secs. 21 and 28.


From the 1/4 sec. cor. of secs. 27 and 28.

S 89°47' W, on the E and W center line of sec. 28.

15.19 Point for AP 1, lot 1, sec. 28.

Set an aluminum post, 28 ins. long, 1 in. diam., 24  
ins. in the ground, with cap mkd.

T12N R18E




Set a steel fence post alongside the cor.

Cor. is located 33 lks. W of a graded road, bears  
N 45° E curving northerly and S 45° W curving westerly.

20.34 Point for the center E 1/16 sec. cor. of sec. 28, iden-  
tical with AP 2, lot 1.

Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins.  
in the ground, in a mound of stone, 2 ft. base, to top,  
with cap mkd.



from which

The NW cor. of a rock house, bears S 77° E,  
1.27 chs. dist.


The SW cor. of a rock garage, bears S 28° E,  
1.39 chs. dist.

Cor. is located 1.66 chs. N of an E-W road.

40.68 The center 1/4 sec. cor. of sec. 28.

60.98 Point for the center W 1/16 sec. cor. of sec. 28.

Set an aluminum post, 36 ins. long, 3/4 in. diam., 26 ins.  
in the ground, in a mound of stone, 3 ft. base, to top,  
with cap mkd.



Subdivision of Section 28  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A juniper, 6 ins. diam., bears S 26° E, 12.5 lks. dist., mkd. C W 1/16 S28 BT.</p> <p>A juniper, 5 ins. diam., bears N 5° W, 28 lks. dist., mkd. X at breast height and BT at base.</p>
81.28	<p>The ¼ sec. cor. of secs. 28 and 29.</p>
	<p style="text-align: center;">NE¼ of Section 28</p> <hr style="width: 20%; margin: auto;"/>
	<p>From the center E 1/16 sec. cor. of sec. 28, identical with AP 2, lot 1, sec. 28.</p>
	<p>N 0°16' W, on the N and S center line of the NE¼ of sec. 28.</p>
20.15	<p>Point for the NE 1/16 sec. cor., at intersection with the E and W center line of the NE¼ of sec. 28.</p>
	<p>Set an aluminum post, 36 ins. long, ¾ in. diam., 28 ins. in the ground, with cap mkd.</p>
	<p style="text-align: center;">T12N R18E NE 1/16 S28 1981</p>
	<p>from which</p>
	<p>A fence cor., bears S 3° W, 68 lks. dist., fences extend N, S 10° W and W.</p>
	<p>A ponderosa pine, 16 ins. diam., bears N 6° W, 78 lks. dist., mkd. NE 1/16 S28 BT.</p>
40.30	<p>The E 1/16 sec. cor. of secs. 21 and 28.</p>
	<p>From the N 1/16 sec. cor. of secs. 27 and 28.</p>
	<p>S 89°55' W, on the E and W center line of sec. 28.</p>
20.41	<p>The NE 1/16 sec. cor. of sec. 28.</p>
40.81	<p>The center N 1/16 sec. cor. of sec. 28.</p>
	<p style="text-align: center;">SE¼ of Section 28</p> <hr style="width: 20%; margin: auto;"/>
	<p>From the E 1/16 sec. cor. of secs. 28 and 33.</p>
	<p>N 0°14' W, on the N and S center line of the SE¼ of sec. 28.</p>
20.13	<p>Point for the SE 1/16 sec. cor., at intersection with the E and W center line of the SE¼ of sec. 28.</p>
	<p>Set an aluminum post, 36 ins. long, ¾ in. diam., 28 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p>

Subdivision of Section 28  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

T12N R18E  
SE 1/16 S28  
1981

from which

A ponderosa pine, 16 ins. diam., bears N 64° E,  
55 lks. dist., mkd. SE 1/16 S28 BT.

A ponderosa pine, 10 ins. diam., bears S 24¼° E,  
98 lks. dist., mkd. SE 1/16 S28 BT.

Cor. is located 49 lks. E of a N-S fence.

31.66 Point for AP 3, lot 1, sec. 28.

Set an aluminum post, 28 ins. long, 1 in. diam., 24  
ins. in the ground with cap mkd.

T12N R18E  
| AP3  
S28 | LOT 1

1985

Set a steel fence post alongside cor.

Cor. is located 2 lks. E of a N and S fence and 41 lks.  
S of a track road, bears W and E curving N.

40.26 The center E 1/16 sec. cor. of sec. 28, identical with  
AP 2, lot 1, sec. 28.

From the S 1/16 sec. cor. of secs. 27 and 28.

S 89°41' W, on the E and W center line of the SE¼ of  
sec. 28.

20.28 The SE 1/16 sec. cor. of sec. 28.

40.56 The center S 1/16 sec. cor. of sec. 28.

SW¼ of Section 28

From the W 1/16 sec. cor. of secs. 28 and 33.

N 0°32' W, on the N and S center line of the SW ¼ of  
sec. 28.

20.21 Point for the SW 1/16 sec. cor., at intersection with  
the E and W center line of the SW¼, sec. 28.

Set an aluminum post, 36 ins. long, ¾ in. diam., 20 ins.  
in the ground, in a mound of stone, 3 ft. base, to top,  
with cap mkd.

T12N R18E  
SW 1/16 S28  
1981

from which


A fence cor., bears S 9° E, 9.5 lks. dist.,  
fences extend S and E.

Subdivision of Section 28  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A juniper, 5 ins. diam., bears S 89° W, 61.5 lks. dist., mkd. SW 1/16 S28 BT.</p> <p>A juniper, 8 ins. diam., bears N 1° W, 87 lks. dist., mkd. SW 1/16 S28 BT.</p>
40.41	<p>The center W 1/16 sec. cor. of sec. 28.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 28.</p> <p>S 89°41' W, on the E and W center line of the SW<sup>1</sup>/<sub>4</sub> of sec. 28.</p>
20.26	<p>The SW 1/16 sec. cor. of sec. 28.</p>
40.52	<p>The S 1/16 sec. cor. of secs. 28 and 29.</p> <hr/> <p style="text-align: center;">Metes-and-Bounds Survey of Lot 1, Section 28 T 12 N, R 18 E, Gila and Salt River Mer., Arizona</p> <hr/> <p>From AP 1, lot 1, sec. 28, on the E and W center line of sec. 28, hereinbefore described.</p> <p>S 89°47' W, on line 1-2, lot 1, identical with a portion of the E and W center line of sec. 28.</p>
5.15	<p>AP 2, lot 1, sec. 28, identical with the center E 1/16 sec. cor. of sec. 28, hereinbefore described.</p> <hr/> <p>S 0°14' E, on line 2-3, lot 1, sec. 28, identical with a portion of the N and S center line of the SE<sup>1</sup>/<sub>4</sub> of sec. 28.</p>
1.27	<p>Fence cor., fences extend N and E.</p>
1.70	<p>Center of graded road No. 916, bears E and W.</p>
8.60	<p>AP 3, lot 1, sec. 28, hereinbefore described.</p> <hr/> <p>N 89°46' E, on line 3-4, lot 1, sec. 28.</p>
1.00	<p>Point for AP 4, lot 1, sec. 28.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>T12N R18E AP4 LOT 1 / S28 1985</p> </div> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>N 12°08' E, on line 4-5, lot 1, sec. 28.</p>
5.90	<p>Graded road, bears S 40° E and N 40° W.</p>
6.34	<p>Point for AP 5, lot 1, sec. 28.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p>

Metes-and-Bounds Survey of Lot 1, Section 28  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS



Set a steel fence post alongside the cor.

Cor. is located 40 lks. W of a graded road in a curve, bears NE and SE, and 100 lks. E of a track road, extending southerly from graded road.

N 49°01' E, on line 5-1, lot 1, sec. 28.

1.45 Graded road, bears N 55° E curving northerly and S 55° W curving westerly.

3.68 AP 1, lot 1, sec. 28.


Subdivision of Section 32  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

From the  $\frac{1}{4}$  sec. cor. of secs. 5 and 32, on the S bdy. of the Tp.

N 0°29' W, on the N and S center line of sec. 32.

20.10 Point for the center S  $\frac{1}{16}$  sec. cor. of sec. 32.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 29 ins. in the ground, in a mound of stone, 2 $\frac{1}{2}$  ft. base, to top, with cap mkd.



from which


A ponderosa pine, 8 ins. diam., bears N 57° E, 63.5 lks. dist., mkd. C S 1/16 S32 BT.

A ponderosa pine, 8 ins. diam., bears N 85° W, 63 lks. dist., mkd. C S 1/16 S32 BT.

Set a steel fence post alongside the cor.

40.20 Point for the center  $\frac{1}{4}$  sec. cor., at intersection with the E and W center line of sec. 32.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.



from which

A pine, 12 ins. diam., bears N 40° E, 1.50 chs. dist., mkd. C  $\frac{1}{4}$  S32 BT.

Subdivision of Section 32  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A pinyon, 6 ins. diam., bears S 18° E, 87.5 lks. dist., mkd. C<math>\frac{1}{4}</math> S32 BT.</p> <p>Set a steel fence post alongside the cor.</p>
60.34	<p>Point for the center N 1/16 sec. cor. of sec. 32.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 32 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>C   N 1/16   S32   C 1982</p> </div> <p>from which</p> <p>A forked juniper, 22 ins. diam., bears S 32° W, 1.79 chs. dist., mkd. C N 1/16 S32 BT</p> <p>A juniper, 8 ins. diam., bears S 83° W, 85.5 lks. dist., mkd. C N 1/16 S32 BT.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. falls in cleared area.</p>
69.00	<p>Graded U.S. Forest Service Road No. 916, bears N 40° E and S 40° W.</p>
80.48	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 29 and 32.</p> <hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 32 and 33.</p> <p>N 89°51' W, on the E and W center line of sec. 32.</p> <p>Over open cultivated land.</p>
3.80	<p>Track road, 15 lks. wide, bears N 25° E and S 15° E, thence through medium juniper and pine.</p>
5.002	<p>Point for the center E-E-E 1/256 sec. cor. of sec. 32.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 28 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <div style="text-align: center;"> <p>C <math>\frac{E-E-E 1/256}{S32}</math> C 1982</p> </div> <p>from which</p> <p>A rebar, <math>\frac{1}{2}</math> in. diam., projecting 6 ins. above ground, bears S 62° E, 48 lks. dist.</p> <p>A ponderosa pine, 12 ins. diam., bears N 42° W, 1.225 chs. dist., mkd. C E E E 1/256 S32 BT.</p> <p>A ponderosa pine, 4 ins. diam., bears N 9° W, 2.27 chs. dist., mkd. X at breast height and BT at base.</p> <p>Set a steel fence post alongside the cor.</p>



Subdivision of Section 32  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
	Cor. falls in a wash, 1.30 chs. wide, drains N 15° E.
10.005	Point for the center E-E 1/64 sec. cor. of sec. 32.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.
	$C \frac{E-E \ 1/64}{S32} C$
	1982
	from which
	A ponderosa pine, 4 ins. diam., bears North, 58.5 lks. dist., mkd. X at breast height and BT at base.
	A ponderosa pine, 7 ins. diam., bears S 23° W, 20 lks. dist., mkd. C E E 1/64 S32 BT.
	Set a steel fence post alongside the cor.
	Cor. is located 1.10 chs. W of a wash, 40 lks. wide, drains S 20° W.
10.68	A fence, bears N 25° E and S 25° W.
20.01	Point for the center E 1/16 sec. cor. of sec. 32.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.
	$C \frac{T12N \ R18E}{E \ 1/16} C$
	S32
	1982
	from which
	A ponderosa pine, 8 ins. diam., bears N 30° E, 46 lks. dist., mkd. C E 1/16 S32 BT.
	A pine, 8 ins. diam., bears N 69° W, 37.5 lks. dist., mkd. C E 1/16 S32 BT.
	Set a steel fence post alongside the cor.
40.02	The center 1/4 sec. cor. of sec. 32.
80.20	The 1/4 sec. cor. of secs. 31 and 32.
	<hr/> NE 1/4 of Section 32 <hr/>
	From the center E 1/16 sec. cor. of sec. 32.
	N 0°28' W, on the N and S center line of the NE 1/4 of sec. 32.
10.06	Point for the center S-NE 1/64 sec. cor. of sec. 32; not monumented.
20.12	Point for the NE 1/16 sec. cor., at intersection with the E and W center line of the NE 1/4 of sec. 32.

Subdivision of Section 32  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">NE 1/16 S32 1982</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S 38° E, 96 lks. dist., mkd. NE 1/16 S32 BT.</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears N 47° W, 1.47 chs. dist., mkd. NE 1/16 S32 BT.</p> <p>Set a steel fence post alongside the cor.</p>	
40.25	<p>The E 1/16 sec. cor. of secs. 29 and 32.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the N 1/16 sec. cor. of secs. 32 and 33.</p> <p>N 89°47' W, on the E and W center line of the NE<math>\frac{1}{4}</math> of sec. 32.</p>	
10.01	<p>Point for the center E-NE 1/64 sec. cor. of sec. 32; not monumented.</p>	
20.02	<p>The NE 1/16 sec. cor. of sec. 32.</p>	
20.40	<p>Wash, 30 lks. wide, drains S.</p>	
40.04	<p>The center N 1/16 sec. cor. of sec. 32.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center E-E 1/64 sec. cor. of sec. 32.</p> <p>N 0°28' W, on the N and S center line of the SE<math>\frac{1}{4}</math> of the NE<math>\frac{1}{4}</math> of sec. 32.</p>	
5.025	<p>Point for the center S-SE-NE 1/256 sec. cor. of sec. 32; not monumented.</p>	
10.05	<p>Point for the SE-NE 1/64 sec. cor., at intersection with the E and W center line of the SE<math>\frac{1}{4}</math> of the NE<math>\frac{1}{4}</math> of sec. 32.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S32 SE-NE 1/64 1982</p> <p>from which</p> <p style="padding-left: 40px;">A pinyon, 4 ins. diam., bears S 80° W, 87.5 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">An alligator juniper, 28 ins. diam., bears N 40° W, 99 lks. dist., mkd. SE NE 1/64 S32 BT.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 80 lks. W of a creek, 10 lks. wide, drains S 30° E.</p>	

Subdivision of Section 32  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

- 20.11 The center E-NE 1/64 sec. cor. point of sec. 32.
- 
- From the S-N 1/64 sec. cor. of secs. 32 and 33.
- N 89°48' W, on the E and W center line of the SE<sup>1</sup>/<sub>4</sub> of the NE<sup>1</sup>/<sub>4</sub> of sec. 32.
- 5.005 Point for the center E-SE-NE 1/256 sec. cor. of sec. 32; not monumented.
- 10.01 The SE-NE 1/64 sec. cor. of sec. 32.
- 20.02 The point for the center S-NE 1/64 sec. cor. of sec. 32.
- 
- From the center E-E-E 1/256 sec. cor. of sec. 32.
- N 0°26' W, on the N and S center line of the SE<sup>1</sup>/<sub>4</sub> of the SE<sup>1</sup>/<sub>4</sub> of the NE<sup>1</sup>/<sub>4</sub> of sec. 32.
- 5.02 Point for the SE-SE-NE 1/256 sec. cor., at intersection with the E and W center line of the SE<sup>1</sup>/<sub>4</sub> of the SE<sup>1</sup>/<sub>4</sub> of the NE<sup>1</sup>/<sub>4</sub> of sec. 32.
- Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with cap mkd.
- S32  
SE-SE-NE  
1/256  
1982
- from which
- A pine, 16 ins. diam., bears N 79 1/2° E,  
1.635 chs. dist., mkd. SE SE NE 1/256 S32 BT.
- A pine, 8 ins. diam., bears N 70° W,  
1.91 chs. dist., mkd. SE SE NE 1/256 S32 BT.
- Set a steel fence post alongside the cor.
- Cor. is located 68 lks. E of a dike, bears NE and SW.
- Cor. falls in a wash area, 3.35 chs. wide, bears N 50° E and S 20° W.
- 10.04 The point for the center E-SE-NE 1/256 sec. cor. of sec. 32.
- 
- From the S-S-N 1/256 sec. cor. of secs. 32 and 33.
- N 89°50' W, on the E and W center line of the SE<sup>1</sup>/<sub>4</sub> of the SE<sup>1</sup>/<sub>4</sub> of the NE<sup>1</sup>/<sub>4</sub> of sec. 32.
- 5.00 The SE-SE-NE 1/256 sec. cor. of sec. 32.
- 10.00 The point for the center S-SE-NE 1/256 sec. cor. of sec. 32.

SE<sup>1</sup>/<sub>4</sub> of Section 32

---

From the E 1/16 sec. cor. of secs. 5 and 32, on the S bdy. of the Tp.

Subdivision of Section 32  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>N 0°27' W, on the N and S center line of the SE<math>\frac{1}{4}</math> of sec. 32.</p>	
10.05	<p>Point for the center S-SE 1/64 sec. cor. of sec. 32.</p>	
	<p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 32 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">S32 C-S-SE 1/64 1982</p>	
	<p>Set a steel fence post alongside the cor.</p>	
20.10	<p>Point for the SE 1/16 sec. cor., at intersection with the E and W center line of the SE<math>\frac{1}{4}</math> of sec. 32.</p>	
	<p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 6 ins. below the surface in the center of a track road, with cap mkd.</p>	
	<p style="text-align: center;">SE 1/16 S32 1982</p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N 26° E, 2.065 chs. dist., mkd. SE 1/16 S32 BT.</p>	
	<p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears N 68° W, 33 lks. dist., mkd. SE 1/16 S32 BT.</p>	
25.125	<p>Point for the center S-N-SE 1/256 sec. cor. of sec. 32.</p>	
	<p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 32 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">S32 C-S-N-SE 1/256 1982</p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">A pine, 10 ins. diam., bears S 86° E, 62.5 lks. dist., mkd. C S N SE 1/256 S32 BT.</p>	
	<p style="padding-left: 40px;">A pine, 12 ins. diam., bears S 47° W, 67.5 lks. dist., mkd. C S N SE 1/256 S32 BT.</p>	
	<p>Set a steel fence post alongside the cor.</p>	
30.15	<p>Point for the center N-SE 1/64 sec. cor. of sec. 32.</p>	
	<p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">S32 C-N-SE 1/64 1982</p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">A pine, 8 ins. diam., bears S 57° E, 31.5 lks. dist., mkd. C N SE 1/64 S32 BT.</p>	

Subdivision of Section 32  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>A pine, 8 ins. diam., bears N 87° W, 34 lks. dist., mkd. C N SE 1/64 S32 BT.</p>	
	<p>Set a steel fence post alongside the cor.</p>	
40.20	<p>The center E 1/16 sec. cor. of sec. 32.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the point for the S 1/16 sec. cor. of secs. 32 and 33, identical with AP 1, lot 1, sec. 32.</p> <p>N 89° 52' W, on the E and W center line of the SE<sup>1</sup>/<sub>4</sub> of sec. 32, identical with line 1-2, lot 1, sec. 32.</p> <p>Through a frame house.</p>	
0.35	<p>Intersect the SW side of a frame house, 26 x 30 ft., the SE cor. bears S 57° E, 29.4 lks. dist., the long side bears N 22° E.</p>	
5.00	<p>Point for the center E-E-SE 1/256 sec. cor. of sec. 32, identical with AP 2, lot 1, sec. 32.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S32 C-E-E-SE 1/256 1982</p>	
	<p>Set a steel fence post alongside the cor.</p> <p>Cor. falls in an open field.</p>	
9.80	<p>Fence, bears N and S.</p>	
10.00	<p>Point for the center E-SE 1/64 sec. cor. of sec. 32.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 24 ins. below the ground, with cap mkd.</p> <p style="text-align: center;">S32 C-E-SE 1/64 1982</p>	
	<p>from which</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 32 ins. in the ground, in a N-S fence line, for a reference monument, bears N 45° E, 18.87 ft. dist., with cap mkd. C E SE 1/64 S32 RM 18.87 FT 1982, and an arrow pointing to the cor.</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 32 ins. in the ground, in a N-S fence line, for a reference monument, bears S 52° E, 17.55 ft. dist., with cap mkd. C E SE 1/64 S32 RM 17.55 FT 1982, and an arrow pointing to the cor.</p>	
	<p>Cor. falls in a cultivated field.</p>	
15.00	<p>Point for the center W-E-SE 1/256 sec. cor. of sec. 32.</p>	

Subdivision of Section 32  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S32 C-W-E-SE 1/256 1982</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. falls in a cultivated field.</p>	
20.00	The SE 1/16 sec. cor. of sec. 32.	
30.00	<p>Point for the center W-SE 1/64 sec. cor. of sec. 32.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S32 C-W-SE 1/64 1982</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S 67° W, 23.5 lks. dist., mkd. C W SE 1/64 S32 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N 55° W, 49 lks. dist., mkd. C W SE 1/64 S32 BT.</p>	
40.00	<p>Set a steel fence post alongside the cor.</p> <p>The center S 1/16 sec. cor. of sec. 32.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center E-SE 1/64 sec. cor. of sec. 32.</p> <p>N 0°27' W, on the N and S center line of the NE<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math> of sec. 32.</p>	
5.02	<p>Point for the center S-NE-SE 1/256 sec. cor. of sec. 32.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S32 C-S-NE-SE 1/256 1982</p>	
10.04	<p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 26 lks. W of a N and S fence.</p> <p>Point for the NE-SE 1/64 sec. cor., at intersection with the E and W center line of the NE<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math> of sec. 32.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 32 ins. in the ground, with cap mkd.</p>	

Subdivision of Section 32  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

S32  
NE-SE  
1/64  
1982

from which

A pine, 6 ins. diam., bears S 12° W, 49 lks.  
dist., mkd. NE SE 1/64 S32 BT.

A pine, 10 ins. diam., bears N 52° W, 72 lks.  
dist., mkd. NE SE 1/64 S32 BT.

Raise a mound of stone, 2½ ft. base, 1 ft. high, N of  
the cor.

Set a steel fence post alongside the cor.

Cor. is located 19 lks. W of a N and S fence, and  
1.10 chs. N of a track road, bears N 65° E and S 65° W.

Cor. falls in a wash, 50 lks. wide, drains N 65° E.

20.09 The center E-E 1/64 sec. cor. of sec. 32.

---

From the N-S 1/64 sec. cor. of secs. 32 and 33.

N 89° 50' W, on the E and W center line of the NE¼ of  
the SE¼ of sec. 32.

10.00 The NE-SE 1/64 sec. cor. of sec. 32.

15.00 Point for the center W-NE-SE 1/256 sec. cor. of sec. 32.

Set an aluminum post, 36 ins. long, ¾ in. diam., 32 ins.  
in the ground, in a mound of stone, 2 ft. base, to top,  
with cap mkd.

S32  
C-W-NE-SE  
1/256  
1982

from which

A pine, 14 ins. diam., bears S 4½° W, 1.26 chs.  
dist., mkd. C W NE SE 1/256 S32 BT.

A pine, 9 ins. diam., bears N 37½° W, 33.5 lks.  
dist., mkd. C W NE SE 1/256 S32 BT.

Set a steel fence post alongside the cor.

Cor. falls on N edge of a wash, 1.00 ch. wide.

15.42 Track road, bears S and N 15° W.

20.00 The center N-SE 1/64 sec. cor. of sec. 32.

---

From the center W-E-SE 1/256 sec. cor. of sec. 32.

N 0° 27' W, on the N and S center line of the SW¼ of the  
NE¼ of the SE¼ of sec. 32.

Subdivision of Section 32  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
5.02	<p>Point for the SW-NE-SE 1/256 sec. cor., at intersection with the E and W center line of the SW<math>\frac{1}{4}</math> of the NE<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math> of sec. 32.</p> <p>Set an aluminum post, 36 ins. long, <math>\frac{3}{4}</math> in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S32 SW-NE-SE 1/256 1982</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears N 36° E, 2.11 chs. dist., mkd. SW NE SE 1/256 S32 BT.</p> <p style="padding-left: 40px;">A pine, 13 ins. diam., bears N 1<math>\frac{1}{2}</math>° W, 2.17 chs. dist., mkd. SW NE SE 1/256 S32 BT.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. falls in a ditch on the S edge of a track road, 20 lks. E of the center of road which bears N 55° E and S 55° W.</p>
10.04	<p>The center W-NE-SE 1/256 sec. cor. of sec. 32.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center S-NE-SE 1/256 sec. cor. of sec. 32.</p> <p>N 89°51' W, on the E and W center line of the SW<math>\frac{1}{4}</math> of the NE<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math> of sec. 32.</p>
5.00	<p>The SW-NE-SE 1/256 sec. cor. of sec. 32.</p>
10.00	<p>The center S-N-SE 1/256 sec. cor. of sec. 32.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the E-E 1/64 sec. cor. of secs. 5 and 32, on the S bdy. of the Tp., monumented with an iron post, 2<math>\frac{1}{2}</math> ins. diam., projecting 5 ins. above ground, with brass cap mkd. as described in the official record of the 1977 resurvey.</p> <p>from which the accessories described in 1977</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N 41° E, 21 lks. dist., mkd. E E 1/64 S32 BT</p> <p style="padding-left: 40px;">A fence cor., bears S 49° E, 5 lks. dist.; fences extend easterly and southerly.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S 6° E, 28 lks. dist., mkd. E E 1/64 S5 BT.</p> <p>A mound of stone, 2<math>\frac{1}{2}</math> ft. base, 6 ins. high is N of the cor.</p> <p>N 0°27' W, on the N and S center line of the SE<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math> of sec. 32.</p>
10.05	<p>Point for the SE-SE 1/64 sec. cor., at intersection with the E and W center line of the SE<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math> of sec. 32.</p>



Subdivision of Section 32  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 32 ins. in the ground, with cap mkd.

S32  
SE-SE  
1/64  
1982

from which

A ponderosa pine, 8 ins. diam., bears S  $73\frac{1}{2}^\circ$  E, 1.015 chs. dist., mkd. SE SE 1/64 S32 BT.

A ponderosa pine, 12 ins. diam., bears S  $27^\circ$  E, 1.045 chs. dist., mkd. SE SE 1/64 S32 BT.

Set a steel fence post alongside the cor.

Cor. is located in an open field.

20.10 The center E-SE 1/64 sec. cor. of sec. 32.

From the S-S 1/64 sec. cor. of secs. 32 and 33.

N  $89^\circ 53'$  W, on the E and W center line of the SE  $\frac{1}{4}$  of the SE  $\frac{1}{4}$  of sec. 32.

5.00 Point for the center E-SE-SE 1/256 sec. cor. of sec. 32.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 32 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.

S32  
C-E-SE-SE  
1/256  
1982

from which

A ponderosa pine, 8 ins. diam., bears S  $14^\circ$  E, 30 lks. dist., mkd. C E SE SE 1/256 S32 BT.

A ponderosa pine, 9 ins. diam., bears S  $34^\circ$  W, 60 lks. dist., mkd. C E SE SE 1/256 S32 BT.

Cor. is located 70 lks. S of a track road, bears NE and SW.

10.00 The SE-SE 1/64 sec. cor. of sec. 32.

20.00 The center S-SE 1/64 sec. cor. of sec. 32.

Metes-and-Bounds Survey of Lot 1, Section 32  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

From the point for AP 1, lot 1, sec. 32, identical with the S 1/16 sec. cor. of secs. 32 and 33, hereinbefore described.

N  $89^\circ 52'$  W, on line 1-2, lot 1, sec. 32, identical with a portion of the E and W center line of the SE  $\frac{1}{4}$  of sec. 32.

Metes-and-Bounds Survey of Lot 1, Section 32  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
5.00	<p>AP 2, lot 1, sec. 32, identical with the center E-E-SE 1/256 sec. cor. of sec. 32, hereinbefore described.</p> <hr/> <p>S 0°26' E, on line 2-3, lot 1, sec. 32, identical with a portion of the N and S center line of the NE<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math> of sec. 32.</p>
3.00	<p>Point for AP 3, lot 1, sec. 32.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>T12N R18E   AP 3 S32   LOT 1 1983</p> </div> <p>Cor. is located in an open field.</p> <hr/> <p>S 89°52' E, on line 3-4, lot 1, sec. 32.</p>
5.00	<p>AP 4, lot 1, sec. 32, on the line bet. secs. 32 and 33 hereinbefore described.</p> <hr/> <p>N 0°26' W, on line 4-1, lot 1, sec. 32, identical with a portion of the line bet. secs. 32 and 33.</p>
3.00	<p>The point for AP 1, lot 1, sec. 32, identical with the S 1/16 sec. cor. of secs. 32 and 33, hereinbefore described.</p>
<p>Subdivision of Section 34 T 12 N, R 18 E, Gila and Salt River Mer., Arizona</p> <hr/>	
<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 3 and 34, on the S bdy. of the Tp., monumented with an iron post, 2<math>\frac{1}{2}</math> ins. diam., projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1977 resurvey.</p>	
<p>from which the accessories described in 1977</p>	
<p>A fence cor., bears N 75° E, 36 lks. dist.; fences extend S and W.</p>	
<p>A ponderosa pine, 9 ins. diam., bears N 81° E, 1.65 chs. dist., mkd. X at breast height and BT at the base.</p>	
<p>A ponderosa pine, 9 ins. diam., bears N 18° W, 29 lks. dist., mkd. <math>\frac{1}{4}</math> S34 BT.</p>	
<p>N 0°12' E, on the N and S center line of sec. 34.</p>	
<p>Over rolling land, with dense juniper.</p>	
40.41	<p>Point for the center <math>\frac{1}{4}</math> sec. cor., at intersection with the E and W center line of sec. 34.</p>

Subdivision of Section 34  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 30 ins. in the ground, in a mound of stone,  $1\frac{1}{2}$  ft. base, to top, with cap mkd.

T12N R18E  
C  $\frac{1}{4}$  S34  
1981

from which

A juniper, 6 ins. diam., bears S  $74^\circ$  W, 89 lks. dist., mkd. X at breast height and BT at base.

A juniper, 6 ins. diam., bears N  $39^\circ$  W, 26.5 lks. dist., mkd. C  $\frac{1}{4}$  S34 BT.

Cor. is located 23 lks. W of a N and S fence.

79.74 The  $\frac{1}{4}$  sec. cor. of secs. 28 and 33.

From the  $\frac{1}{4}$  sec. cor. of secs. 34 and 35.

S  $89^\circ 33'$  W, on the E and W center line of sec. 34.

Over mildly rolling hills with dense juniper.

40.50 The center  $\frac{1}{4}$  sec. cor. of sec. 34.

80.59 The  $\frac{1}{4}$  sec. cor. of secs. 33 and 34.

Subdivision of Section 35  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

From the  $\frac{1}{4}$  sec. cor. of secs. 2 and 35, on the S bdy. of the Tp.

N  $1^\circ 16'$  E, on the N and S center line of sec. 35.

20.08 Point for the center S  $\frac{1}{16}$  sec. cor. of sec. 35.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.

T12N R18E  
C  
S  $\frac{1}{16}$  | S35  
C  
1981

from which

A ponderosa pine, 6 ins. diam., bears S  $27^\circ$  E, 12 lks. dist., mkd. C S  $\frac{1}{16}$  S35 BT.

A ponderosa pine, 4 ins. diam., bears N  $73^\circ$  W, 20.5 lks. dist., mkd. X at breast height and BT at base.

24.31 Point for AP 3, lot 1, sec. 35.

Subdivision of Section 35  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E   AP 3 S35   LOT 1 1983</p> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears N 15° E, 2.5 lks. dist., fences extend E and N 5° W.</p> <p>Cor. is located 40 lks. W of a fence, bears N 15° E and S 15° W.</p>
25.10	<p>Point for the center S-N-S 1/256 sec. cor. of sec. 35.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">C S-N-S   S35 1/256   C 1981</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S 3° W, 10.5 lks. dist., mkd. C S N S 1/256 S35 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears N 82° W, 42 lks. dist., mkd. C S N S 1/256 S35 BT.</p> <p style="padding-left: 40px;">The SW cor. of an LDS Ranch House, 39 x 46 ft., bears S 82°57' E, 1.83 chs. dist., long side bears S 86°58' E.</p>
30.12	<p>Point for the center N-S 1/64 sec. cor. of sec. 35; not monumented.</p>
40.16	<p>Point for the center 1/4 sec. cor., at intersection with the E and W center line of sec. 35.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T12N R18E C 1/4 S35 1981</p> <p>Cor. is located 64 lks. E of a track road, bears S 15° E and N 15° W.</p>
45.09	<p>Point for the center S-S-N 1/256 sec. cor. of sec. 35; not monumented.</p>
50.02	<p>Point for the center S-N 1/64 sec. cor. of sec. 35; not monumented.</p>
59.88	<p>Point for the center N 1/16 sec. cor. of sec. 35.</p>

Subdivision of Section 35  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 28 ins. in the ground, with cap mkd.

T12N R18E  
C  
N 1/16 | S35  
C  
1981

- 69.74 Point for the center N-N 1/64 sec. cor. of sec. 35; not monumented.
- 79.60 The  $\frac{1}{4}$  sec. cor. of secs. 26 and 35.

From the  $\frac{1}{4}$  sec. cor. of secs. 35 and 36.

N 89°26' W, on the E and W center line of sec. 35.

Over rolling hills with dense ponderosa pine.

- 20.20 Point for the center E 1/16 sec. cor. of sec. 35.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 24 ins. in the ground, in a mound of stone, 2 $\frac{1}{2}$  ft. base, to top, with cap mkd.

T12N R18E  
C E 1/16 C  
S35  
1981

from which

A ponderosa pine, 5 ins. diam., bears S 40° W, 26 lks. dist., mkd. C E 1/16 S35 BT.

A ponderosa pine, 4 ins. diam., bears N 63° W, 26.5 lks. dist., mkd. X at breast height and BT at base.

- 30.30 Point for the center W-E 1/64 sec. cor. of sec. 35; not monumented.

- 34.38 Point selected for a witness point.

Set a finned aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 28 ins. in the ground, with cap mkd.

WP  
C ——— C  
S35  
1986

Set a steel fence post alongside the aluminum post.

- 34.45 Fence, bears N and S.

- 35.00 Center of wash, 90 lks. wide, 6 ft. deep, drains N 20° W.

- 35.35 Point for the center W-W-E 1/256 sec. cor. of sec. 35, falls in a wash, 90 lks. wide, 6 ft. deep, drains N 20° W, where it is impractical to set a permanent monument.

Set a spike nail flush with the ground.

Subdivision of Section 35  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>from which</p> <p>A ponderosa pine, 18 ins. diam., bears N 36° E, 92 lks. dist., mkd. CWWE 1/256 S35 BT.</p>	
35.66	<p>Point selected for a witness point.</p> <p>Set a finned aluminum post, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, with cap mkd.</p> $C \frac{WP}{S35} C$ <p style="text-align: center;">1986</p> <p>Set a steel fence post alongside the aluminum post.</p>	
40.40	<p>The center 1/4 sec. cor. of sec. 35.</p>	
45.435	<p>Point for the center E-E-W 1/256 sec. cor. of sec. 35.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, with cap mkd.</p> $C \frac{E-E-W \ 1/256}{S35} C$ <p style="text-align: center;">1981</p> <p>from which</p> <p>A ponderosa pine, 5 ins. diam., bears S 39° W, 50 lks. dist., mkd. C E E W 1/256 S35 BT.</p>	
50.47	<p>Point for the center E-W 1/64 sec. cor. of sec. 35; not monumented.</p>	
60.54	<p>Point for the center W 1/16 sec. cor. of sec. 35.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with cap mkd.</p> $C \frac{T12N \ R18E}{W \ 1/16} C$ <p style="text-align: center;">S35 1981</p> <p>from which</p> <p>An alligator juniper, 12 ins. diam., bears N 41° E, 26 lks. dist., mkd. C W 1/16 S35 BT.</p> <p>A ponderosa pine, 8 ins. diam., bears S 62° E, 55.5 lks. dist., mkd. C W 1/16 S35 BT.</p> <p>Cor. is located 89 lks. N of a fence, bears E and W.</p>	
80.68	<p>The 1/4 sec. cor. of secs. 32 and 33.</p> <hr/> <p style="text-align: center;">NE 1/4 of Section 35</p> <hr/> <p>From the center E 1/16 sec. cor. of sec. 35.</p>	

Subdivision of Section 35  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>N 1°33' E, on the N and S center line of the NE<sup>1</sup>/<sub>4</sub> of sec. 35.</p>	
19.79	<p>Point for the NE 1/16 sec. cor., at intersection with the E and W center line of the NE<sup>1</sup>/<sub>4</sub> of sec. 35.</p> <p>Set an aluminum post, 36 ins. long, <sup>3</sup>/<sub>4</sub> in. diam., 18 ins. in the ground, in a mound of stone, 2<sup>1</sup>/<sub>2</sub> ft. base, to top with cap mkd.</p>	
	<p style="text-align: center;">T12N R18E NE 1/16 S35 1981</p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S 85<sup>1</sup>/<sub>2</sub>° E, 48.5 lks. dist., mkd. NE 1/16 S35 BT.</p>	
	<p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N 13° W, 64.5 lks. dist., mkd. NE 1/16 S35 BT.</p>	
39.58	<p>The E 1/16 sec. cor. of secs. 26 and 35.</p>	
	<hr style="width: 20%; margin: auto;"/> <p>From the N 1/16 sec. cor. of secs. 35 and 36.</p>	
	<p>N 89°39' W, on the E and W center line of the NE<sup>1</sup>/<sub>4</sub> of sec. 35.</p>	
20.28	<p>The NE 1/16 sec. cor. of sec. 35.</p>	
35.25	<p>Fence, bears N and S.</p>	
35.498	<p>Point for the center W-W-NE 1/256 sec. cor. of sec. 35.</p> <p>Set an aluminum post, 36 ins. long, <sup>3</sup>/<sub>4</sub> in. diam., 26 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">S35 C-W-W-NE 1/256 1981</p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S 79° E, 78.5 lks. dist., mkd. C W W NE 1/256 S35 BT.</p>	
40.57	<p>The center N 1/16 sec. cor. of sec. 35.</p>	
	<hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">SE<sup>1</sup>/<sub>4</sub> of Section 35</p>	
	<p>From the E 1/16 sec. cor. of secs. 2 and 35, on the S bdy. of the Tp.</p>	
	<p>N 1°35' E, on the N and S center line of the SE<sup>1</sup>/<sub>4</sub> of sec. 35.</p>	
19.97	<p>Point for the SE 1/16 sec. cor., at intersection with the E and W center line of the SE<sup>1</sup>/<sub>4</sub> of sec. 35.</p> <p>Set an aluminum post, 36 ins. long, <sup>3</sup>/<sub>4</sub> in. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p>	

Subdivision of Section 35  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	T12N R18E SE 1/16 S35 1981	
	from which	
	A ponderosa pine, 8 ins. diam., bears N 27° E, 38.5 lks. dist., mkd. SE 1/16 S35 BT.	
	A ponderosa pine, 6 ins. diam., bears S 36° E, 68 lks. dist., mkd. SE 1/16 S35 BT.	
29.965	Point for the center N-SE 1/64 sec. cor. of sec. 35; not monumented.	
39.96	The center E 1/16 sec. cor. of sec. 35.	
	_____	
	From the S 1/16 sec. cor. of secs. 35 and 36.	
	N 89°45' W, on the E and W center line of the SE <sup>1</sup> / <sub>4</sub> of sec. 35.	
20.10	The SE 1/16 sec. cor. of sec. 35.	
30.15	Point for the center W-SE 1/64 sec. cor. of sec. 35; not monumented.	
35.175	Point for the center W-W-SE 1/256 sec. cor. of sec. 35; not monumented.	
40.20	The center S 1/16 sec. cor. of sec. 35.	
	_____	
	From the point for the center W-SE 1/64 sec. cor. of sec. 35.	
	N 1°24' E, on the N and S center line of the NW <sup>1</sup> / <sub>4</sub> of the SE <sup>1</sup> / <sub>4</sub> of sec. 35.	
5.005	Point for the center S-NW-SE 1/256 sec. cor. of sec. 35; not monumented.	
10.01	Point for the NW-SE 1/64 sec. cor., at intersection with the E and W center line of the NW <sup>1</sup> / <sub>4</sub> of the SE <sup>1</sup> / <sub>4</sub> of sec. 35; not monumented.	
20.03	The point for the center W-E 1/64 sec. cor. of sec. 35.	
	_____	
	From the point for the center N-SE 1/64 sec. cor. of sec. 35.	
	N 89°36' W, on the E and W center line of the NW <sup>1</sup> / <sub>4</sub> of the SE <sup>1</sup> / <sub>4</sub> of sec. 35.	
10.07	The point for the NW-SE 1/64 sec. cor. of sec. 35.	
15.11	Point for the center W-NW-SE 1/256 sec. cor. of sec. 35; not monumented.	
20.15	The point for the center N-S 1/64 sec. cor. of sec. 35.	
	_____	
	From the point for the center W-W-SE 1/256 sec. cor. of sec. 35.	



Subdivision of Section 35  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS

N 1°20' E, on the N and S center line of the SW $\frac{1}{4}$  of the NW $\frac{1}{4}$  of the SE $\frac{1}{4}$  of sec. 35.

4.22 Fence, bears E and W.

4.24 Point for AP 4, lot 1, sec. 35.

Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with cap mkd.

T12N R18E  
AP4 |  
LOT 1 | S35  
1983

Cor. is located 1.60 chs. E of a road, bears N 15° E and S 15° W.

5.01 Point for the SW-NW-SE 1/256 sec. cor. of sec. 35, identical with AP 1, lot 1, sec. 35, at intersection with the E and W center line of the SW $\frac{1}{4}$  of the NW $\frac{1}{4}$  of the SE $\frac{1}{4}$  of sec. 35.

Set an aluminum post, 36 ins. long,  $\frac{3}{4}$  in. diam., 28 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.

S35  
SW-NW-SE  
1/256  
1981

from which

A ponderosa pine, 6 ins. diam., bears S 62° E,  
89.5 lks. dist., mkd. SW NW SE 1/256 S35 BT.

10.02 The point for the center W-NW-SE 1/256 sec. cor. of sec. 35.

From the point for the center S-NW-SE 1/256 sec. cor. of sec. 35.

N 89°42' W, on the E and W center line of the SW $\frac{1}{4}$  of the NW $\frac{1}{4}$  of the SE $\frac{1}{4}$  of sec. 35.

5.03 The SW-NW-SE 1/256 sec. cor. of sec. 35, identical with AP 1, lot 1, sec. 35.

7.56 Intersect the E side of an LDS Ranch House, 39 x 46 ft., the SE porch cor. bears S 3°02' W, 23.4 lks. dist., the long side bears N 86°58' W.

Through the house.

8.23 Intersect the West side of an LDS Ranch House, the SW porch cor. bears S 3°02' W, 20.7 lks. dist.

10.06 The center S-N-S 1/256 sec. cor. of sec. 35, identical with AP 2, lot 1, sec. 35.

NW $\frac{1}{4}$  of Section 35

From the center W 1/16 sec. cor. of sec. 35.

Subdivision of Section 35  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>N 0°53' E, on the N and S center line of the NW<sup>1</sup>/<sub>4</sub> of sec. 35.</p>	
	<p>Over rolling hills with dense juniper, pinyon and ponderosa pine.</p>	
9.83	<p>Point for the center S-NW 1/64 sec. cor. of sec. 35; not monumented.</p>	
19.66	<p>Point for the NW 1/16 sec. cor., at intersection with the E and W center line of the NW<sup>1</sup>/<sub>4</sub> of sec. 35.</p> <p>Set an aluminum post, 36 ins. long, <sup>3</sup>/<sub>4</sub> in. diam., 26 ins. in the ground, in a mound of stone, 2<sup>1</sup>/<sub>2</sub> ft. base, to top, with cap mkd.</p>	
	<p style="text-align: center;">T12N R18E NW 1/16 S35 1981</p>	
	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears N 87° E, 1.165 chs. dist., mkd. NW 1/16 S35 BT.</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears S 13° W, 75 lks. dist., mkd. NW 1/16 S35 BT.</p>	
23.42	<p>Fence, bears E and W.</p>	
24.575	<p>Point for the center S-N-NW 1/256 sec. cor. of sec. 35.</p> <p>Set an aluminum post, 36 ins. long, <sup>3</sup>/<sub>4</sub> in. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p>	
	<p style="text-align: center;">S35 C-S-N-NW 1/256 1981</p>	
	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S 88° W, 1.61 chs. dist., mkd. C S N NW 1/256 S35 BT.</p>	
29.49	<p>Point for the center N-NW 1/64 sec. cor. of sec. 35; not monumented.</p>	
39.32	<p>The W 1/16 sec. cor. of secs. 26 and 35.</p>	
	<hr style="width: 20%; margin: 0 auto;"/> <p>From the center N 1/16 sec. cor. of sec. 35.</p> <p>N 89°38' W, on the E and W center line of the NW<sup>1</sup>/<sub>4</sub> of sec. 35.</p> <p>Over rolling hills with dense juniper, pinyon and ponderosa pine.</p>	
10.13	<p>Point for the center E-NW 1/64 sec. cor. of sec. 35.</p> <p>Set an aluminum post, 36 ins. long, <sup>3</sup>/<sub>4</sub> in. diam., 26 ins. in the ground, in a mound of stone, 2<sup>1</sup>/<sub>2</sub> ft. base, to top, with cap mkd.</p>	

Subdivision of Section 35  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	S35 C-E-NW 1/64 1981	
10.18	Fence, bears N and S.	
20.26	The NW 1/16 sec. cor. of sec. 35.	
30.39	Point for the center W-NW 1/64 sec. cor. of sec. 35; not monumented.	
40.52	The N 1/16 sec. cor. of secs. 34 and 35.	
	<hr/> From the center E-NW 1/64 sec. cor. of sec. 35.  N 1°05' E, on the N and S center line of the NE <sup>1</sup> / <sub>4</sub> of the NW <sup>1</sup> / <sub>4</sub> of sec. 35.  Over rolling hills with scattered to dense juniper and ponderosa pine.	
4.92	Point for the center S-NE-NW 1/256 sec. cor. of sec. 35.  Set an aluminum post, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with cap mkd.	
	S35 C-S-NE-NW 1/256 1981	
	from which  A fence cor., bears S 10° W, 1.105 chs. dist., fence extends S and W.	
9.84	Point for the NE-NW 1/64 sec. cor., at intersection with the E and W center line of the NE <sup>1</sup> / <sub>4</sub> of the NW <sup>1</sup> / <sub>4</sub> of sec. 35; not monumented.	
19.69	The point for the E-W 1/64 sec. cor. of secs. 26 and 35.  <hr/> From the point for the center N-N 1/64 sec. cor. of sec. 35.  N 89°44' W, on the E and W center line of the NE <sup>1</sup> / <sub>4</sub> of the NW <sup>1</sup> / <sub>4</sub> of sec. 35.	
10.16	The point for the NE-NW 1/64 sec. cor. of sec. 35.	
20.32	The point for the center N-NW 1/64 sec. cor. of sec. 35.  <hr/> From the point for the center E-W 1/64 sec. cor. of sec. 35.  N 1°04' E, on the N and S center line of the SE <sup>1</sup> / <sub>4</sub> of the NW <sup>1</sup> / <sub>4</sub> of sec. 35.	
4.92	Point for the center S-SE-NW 1/256 sec. cor. of sec. 35.  Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, with cap mkd.	

Subdivision of Section 35  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">S35 C-S-SE-NW 1/256 1981</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S 87° E, 42 lks. dist., mkd. C S SE NW 1/256 S35 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S 12° W, 37.5 lks. dist., mkd. C S SE NW 1/256 S35 BT.</p> <p>Cor. is located 4.5 lks. W of a N-S fence.</p>	
9.84	Point for the SE-NW 1/64 sec. cor., at intersection with the E and W center line of the SE <sup>1</sup> / <sub>4</sub> of the NW <sup>1</sup> / <sub>4</sub> of sec. 35; not monumented.	
19.68	The center E-NW 1/64 sec. cor. of sec. 35.	
	<hr style="width: 20%; margin: 10px auto;"/> <p>From the point for the center S-N 1/64 sec. cor. of sec. 35.</p> <p>N 89°32' W, on the E and W center line of the SE<sup>1</sup>/<sub>4</sub> of the NW<sup>1</sup>/<sub>4</sub> of sec. 35.</p>	
5.05	Point for the center E-SE-NW 1/256 sec. cor. of sec. 35; not monumented.	
10.10	The point for the SE-NW 1/64 sec. cor. of sec. 35.	
20.19	The point for the center S-NW 1/64 sec. cor. of sec. 35.	
	<hr style="width: 20%; margin: 10px auto;"/> <p>From the center E-E-W 1/256 sec. cor. of sec. 35.</p> <p>N 1°10' E, on the N and S center line of the SE<sup>1</sup>/<sub>4</sub> of the SE<sup>1</sup>/<sub>4</sub> of the NW<sup>1</sup>/<sub>4</sub> of sec. 35.</p>	
4.925	Point for the SE-SE-NW 1/256 sec. cor., at intersection with the E and W center line of the SE <sup>1</sup> / <sub>4</sub> of the SE <sup>1</sup> / <sub>4</sub> of the NW <sup>1</sup> / <sub>4</sub> of sec. 35.	
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, with cap mkd.	
	<p style="text-align: center;">S35 SE-SE-NW 1/256 1981</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S 18° W, 39.5 lks. dist., mkd. SE SE NW 1/256 S35 BT.</p>	
9.85	The point for the center E-SE-NW 1/256 sec. cor. of sec. 35.	
	<hr style="width: 20%; margin: 10px auto;"/> <p>From the point for the center S-S-N 1/256 sec. cor. of sec. 35.</p> <p>N 89°29' W, on the E and W center line of the SE<sup>1</sup>/<sub>4</sub> of the SE<sup>1</sup>/<sub>4</sub> of the NW<sup>1</sup>/<sub>4</sub> of sec. 35.</p>	
5.04	The SE-SE-NW 1/256 sec. cor. of sec. 35.	

Subdivision of Section 35  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
10.08	<p>The center S-SE-NW 1/256 sec. cor. of sec. 35.</p> <hr/> <p>From the point for the center W-NW 1/64 sec. cor. of sec. 35.</p> <p>N 0°43' E, on the N and S center line of the NW<sup>1</sup>/<sub>4</sub> of the NW<sup>1</sup>/<sub>4</sub> of sec. 35.</p>
4.90	<p>Point for the center S-NW-NW 1/256 sec. cor. of sec. 35.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S35 C-S-NW-NW 1/256 1981</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S 11° E, 1.45 chs. dist., mkd. C S NW NW 1/256 S35 BT.</p> <p style="padding-left: 40px;">A fence cor., bears S 22° W, 1.37 chs. dist., fences extend N and E.</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears S 54° W, 65.5 lks. dist., mkd. C S NW NW 1/256 S35 BT.</p>
5.65	<p>Wash, 1 ch. wide, 5 ft. deep, drains E curving N.</p>
9.80	<p>Point for the NW-NW 1/64 sec. cor., at intersection with the E and W center line of the NW<sup>1</sup>/<sub>4</sub> of the NW<sup>1</sup>/<sub>4</sub> of sec. 35; not monumented.</p>
19.61	<p>The W-W 1/64 sec. cor. of secs. 26 and 35.</p> <hr/> <p>From the point for the center N-NW 1/64 sec. cor. of sec. 35.</p> <p>N 89°43' W, on the E and W center line of the NW<sup>1</sup>/<sub>4</sub> of the NW<sup>1</sup>/<sub>4</sub> of sec. 35.</p>
10.16	<p>The point for the NW-NW 1/64 sec. cor. of sec. 35.</p>
20.32	<p>The point for the N-N 1/64 sec. cor. of secs. 34 and 35.</p> <hr/> <p style="text-align: center;">Metes-and-Bounds Survey of Lot 1, Section 35 T 12 N, R 18 E, Gila and Salt River Mer., Arizona</p> <hr/> <p>From AP 1, lot 1, sec. 35, identical with the SW-NW-SE 1/256 sec. cor. of sec. 35, hereinbefore described.</p> <p>N 89°42' W, on line 1-2, lot 1, sec. 35, identical with the W<sup>1</sup>/<sub>2</sub> of the E and W center line of the SW<sup>1</sup>/<sub>4</sub> of the NW<sup>1</sup>/<sub>4</sub> of the SE<sup>1</sup>/<sub>4</sub> of sec. 35.</p>
5.03	<p>AP 2, lot 1, sec. 35, identical with the center S-N-S 1/256 sec. cor. of sec. 35, hereinbefore described.</p> <hr/> <p>S 1°16' W, on line 2-3, lot 1, sec. 35, identical with a portion of the N and S center line of sec. 35.</p>

Metes-and-Bounds Survey of Lot 1, Section 35  
T 12 N, R 18 E, Gila and Salt River Mer., Arizona

CHAINS	
0.79	AP 3, lot 1, sec. 35, hereinbefore described.
	<hr/> <p>S 89°52' E, on line 3-4, lot 1, sec. 35.</p>
3.34	Fence cor., bears North, 4 lks. dist., fences extend N 30° E and W.
3.46	Track road, bears N 15° E and S 15° W.
5.03	Point for AP 4, lot 1, sec. 35, on the N and S center line of the SW <sup>1</sup> / <sub>4</sub> of the NW <sup>1</sup> / <sub>4</sub> of the SE <sup>1</sup> / <sub>4</sub> , sec. 35, hereinbefore described.
	<hr/> <p>N 1°20' E, on line 4-1, lot 1, sec. 35, identical with a portion of the N and S center line of the SW<sup>1</sup>/<sub>4</sub> of the NW<sup>1</sup>/<sub>4</sub> of the SE<sup>1</sup>/<sub>4</sub> of sec. 35.</p>
0.77	AP 1, lot 1, sec. 35, identical with the SE-NW-SE 1/256 sec. cor. of sec. 35, hereinbefore described.
GENERAL DESCRIPTION	
<p>The land encompassed in this survey is located about 5½ miles east of Overgaard, Arizona. The elevation ranges from about 6,300 to 6,500 ft. above sea level.</p>	
<p>The land ranges from cultivated and open to forested consisting of juniper and pines scattered throughout the township and in many areas are of dense concentration. There are also chained-cleared areas scattered throughout the township and grazing is evident.</p>	
<p>Access is by means of Arizona State Highway No. 277 which crosses the Northern portion of the township and numerous U.S. Forest Service roads.</p>	
<p>The mean magnetic declination is 14° E.</p>	



CERTIFICATE OF SURVEY

We, Will C. Gabonay and Paul L. Reeves, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 27th day of May 1981, and supplemental special instructions dated December 16, 1983, we have dependently resurveyed portions of the North boundary (Third Standard Parallel North), East and South boundaries and portions of the subdivisional lines and surveyed subdivisions in certain sections and metes-and-bounds surveys in sections 28, 32 and 35, T 12 N, R 18 E of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

AUG 21 1986

(Date)

*Paul L. Reeves*  
 (Cadastral Surveyor)

Will C. Gabonay is no longer assigned to this office and is not available for signature.

AUG 21 1986

(Date)

*Harry K. Smith*  
 (Cadastral Surveyor)

Harry K. Smith, Chief Field Section

CERTIFICATE OF APPROVAL

Arizona State Office  
 Bureau of Land Management  
 Phoenix, Arizona

The foregoing field notes of the dependent resurvey of portions of the North boundary (Third Standard Parallel North), East and South boundaries, and portions of the subdivisional lines, and survey of subdivisions in certain sections, and metes-and-bounds surveys in sections 28, 32 and 35, T 12 N, R 18 E, Gila and Salt River Meridian, Arizona, executed by Will C. Gabonay and Paul L. Reeves, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

AUG 22 1986

(Date)

*James P. Kelley*

(Chief Cadastral Surveyor of Arizona)