

ORIGINAL

1

BOOK 5234

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE

EAST BOUNDARY,

AND

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SURVEY OF SUBDIVISIONS IN SECTIONS 21 AND 28,

TOWNSHIP 13 NORTH, RANGE 2 EAST

Of the Gila and Salt River Meridian,  
In the State of Arizona

EXECUTED BY

Will C. Gabonay, Cadastral Surveyor, under the supervision of Harry K. Smith,  
Chief, Field Section.

Under special instructions dated April 24, 1984, approved April 24, 1984

   which provided for the surveys included under Group Number  
656 and assignment instructions dated April 26, 1984, and  
October 7, 1986.

Survey commenced May 3, 1984

Survey completed October 8, 1986

BOOK 5234

INDEX DIAGRAM

TOWNSHIP 13 NORTH, RANGE 2 EAST,

6	5	4	3	2	1
7	8	9	11 10	11	12
		19	10		
18	17	16	10 15	7 14	5 13
		18	9	6	5
19	20	15 21	9 22	23	4 24 3
		14			
30	29	13 28	7 27	26	25
		12			
31	32	33	34	35	36

Subdivision of Section 21.....pps. 20-30

Subdivision of Section 28.....pps. 30-36

T 13 N, R 2 E, Gila and Salt River Mer., Arizona

## CHAINS

The following field notes describe the dependent resurvey of a portion of the east boundary and a portion of the subdivisional lines, and the survey of subdivisions in sections 21 and 28, Township 13 North, Range 2 East, Gila and Salt River Meridian, Arizona.

The east boundary of the township was surveyed by C.B. Foster in 1874. The subdivisional lines of the east four tiers of sections were surveyed by C.B. Foster, in 1877. A portion of the subdivisional lines were retraced and/or resurveyed in 1915 by R.P.A. Johnson, while executing Homestead Entry Survey No. 327. The east boundary from the cor. of secs. 19, 24, 25, and 30, to the  $\frac{1}{4}$  sec. cor. of secs. 13 and 18 was resurveyed in 1915 by Charles D. Hodson, while executing Homestead Entry Survey No. 89. The west boundary and a portion of the subdivisional lines were resurveyed and the west two tiers of sections surveyed by Benjamin J. Kinsey and Ty White in 1923. The east boundary was resurveyed by Benjamin J. Kinsey and Leroy R. Hanson in 1928.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated April 24, 1984 for Group No. 656, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced. Due to the extensive distortion found in the original survey, extra effort was taken to ensure that all possible locations for corners were calculated and an exhaustive search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of all lines were determined by observations on the U.S. Geological Survey triangulation network, confirmed by altitude observations on the sun, and refer to the true meridian. Distances and angles were measured with a Zeiss Elta 46 Total Station Instrument.

The geographic position of the southeast corner of section 28, T 13 N, R 2 E, as determined from a tie made to U.S. Geological Survey triangulation station "ROUND", located in the SE quarter of section 12, T 13 N, R 1 $\frac{1}{2}$  E, is as follows:

Latitude: 34°28'20.19" N Longitude: 112°07'40.32" W

The mean magnetic declination taken from "MAYER, ARIZ.," quadrangle map, published by U.S. Geological Survey in 1974, is 13 $\frac{1}{2}$ ° E.

---

Dependent Resurvey of a Portion of the E Bdy.,  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

---

(Restoring the resurvey executed by Benjamin J. Kinsey and Leroy R. Hanson in 1928.)

Dependent Resurvey of a Portion of the E Bdy.,  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS

Beginning at the  $\frac{1}{4}$  sec. cor. of secs. 19 and 24, Tps. 13 N, Rs. 2 and 3 E, monumented with a granite stone, 20 x 10 x 8 ins., firmly set 14 ins. in the ground, mkd.  $\frac{1}{4}$  on the W face, with an iron post, 36 ins. long, 1 in. diam., projecting 24 ins. above ground, in a mound of stone, 3 ft. base, 18 ins. high, set adjacent to the stone, with brass cap mkd.

$\frac{1}{4}$   
S24 | S19  
1928

from which

A juniper, 4 ins. diam., bears S  $31\frac{1}{2}^\circ$  E,  
2.05 chs. dist., mkd. BT at base.

A juniper stump, 15 ins. diam., bears  
S  $66\frac{1}{2}^\circ$  W, 3.53 chs. dist., mkd. BT at  
base.

At the cor. point

Reset the iron post, 15 ins. in the ground, in a mound of stone, 3 ft. base to top, and add the date 1986 to the brass cap.

Deposit the mkd. stone alongside the iron post.

N  $0^\circ 26'$  E, bet. secs. 19 and 24.

Over open, hilly terrain.

39.45 Wash, 20 lks. wide, drains S  $10^\circ$  W.

40.19 The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

T13N  
R2E | R3E  
S13 | S18  
S24 | S19  
1928

A mound of stone, 3 ft. base, 18 ins. high, is W of the cor.

---

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

---

(Restoring the survey executed by C. B. Foster in 1877.)

From the  $\frac{1}{4}$  sec. cor. of secs. 23 and 24, monumented with a basalt stone, 16 x 12 x 6 ins., firmly set 10 ins. in the ground, mkd.  $\frac{1}{4}$  on S face, surrounded by a scattered mound of stone.

At the cor. point

Set a stainless steel post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, and in a mound of stone,  $2\frac{1}{2}$  ft. base, to top, with brass cap mkd.

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS

T13N R2E  
 $\frac{1}{4}$   
 S23 | S24  
 1984

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Deposit the mkd. stone alongside the stainless steel post.

N 3°05' E, bet. secs. 23 and 24.

Over hilly, open terrain.

40.39 Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist.; there is no evidence of the original cor. and none was found in the 1915 retracement by R.P.A. Johnson while executing Homestead Entry Survey No. 327.

Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.

T13N R2E  
 S14 | S13  
 S23 | S24  
 1984

From this point, the center of a circular steel tank, 12 ft. high, 25 ft. diam., bears S 48°19' E, 22.07 chs. dist.

From the cor. of secs. 13, 18, 19 and 24, on the E bdy. of the Tp.

N 89°21' W, bet. secs. 13 and 24.

Over open, hilly terrain.

37.43 Point for the  $\frac{1}{4}$  sec. cor. of secs. 13 and 24, at proportionate dist.; there is no evidence of the original cor.

Set an aluminum post, 28 ins. long, 1 in. diam., 25 ins. in the ground, with cap mkd.

T13N R2E  
 $\frac{1}{4}$  S13  
 S24  
 1984

Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.

Set a steel fence post alongside the cor.

74.40 Track road, 15 lks. wide, bears N 15° E and S 15° W.

74.86 The cor. of secs. 13, 14, 23 and 24.

N 1°29' E, bet. secs. 13 and 14.

Over rolling, open terrain.

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS	
40.35	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 13 and 14, monumented with a volcanic stone, 12 x 12 x 6 ins., firmly set 6 ins. in the ground, mkd. <math>\frac{1}{4}</math> on S face, with a mound of stone, 3 ft. base, 1 ft. high, to W.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T13N R2E <math>\frac{1}{4}</math> S14   S13 1984</p> <p>Deposit the mkd. stone alongside the aluminum post.</p> <p>Rebuild the mound of stone, 2<math>\frac{1}{2}</math> ft. base, 1<math>\frac{1}{2}</math> ft. high, W of the cor.</p> <p>Set a steel fence post alongside the cor.</p>
	<hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N 87°39' W, bet. secs. 14 and 23.</p> <p>Over hilly, open terrain.</p>
37.36	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 14 and 23, at proportionate dist.; there is no evidence of the original cor. and none was found in the 1915 retracement by R.P.A. Johnson while executing Homestead Entry Survey No. 327.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T13N R2E <math>\frac{1}{4}</math> <math>\frac{S14}{S23}</math> 1984</p> <p>Set a steel fence post alongside the cor.</p>
70.00	<p>Top of ascent of easterly slope.</p>
74.72	<p>The cor. of secs. 14, 15, 22 and 23, monumented with a mound of stone, 2 ft. base, 6 ins. high. This mound was described in the 1915 Homestead Entry Survey No. 327, by R.P.A. Johnson; is harmonious with topographic calls of the original survey, in which the corner is reported to be 5 chs. W of a descent, 3 chs. S of a descent and 2.20 chs. E of the summit of N end of hills; and is accepted as the original cor. position.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 8 ins. in the ground, and in a mound of stone, 2<math>\frac{1}{2}</math> ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T13N R2E S15   S14 S22   S23 1984</p>

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A fence cor., bears N 26½° E, 4.60 chs. dist.; fences extend North, and S 35° E.</p> <p>Cor. is located at top of hill.</p>
3.00	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N 0°33' E, bet. secs. 14 and 15.</p> <p>Over hilly, open terrain.</p>
40.33	<p>Descend NW slope.</p> <p>Point for the ¼ sec. cor. of secs. 14 and 15, at proportionate dist.; there is no evidence of the original cor. and none was found in the 1915 retracement by R.P.A. Johnson while executing Homestead Entry Survey No. 327.</p> <p>Set an aluminum post, 24 ins. long, ¾ ins. diam., 18 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T13N R2E ¼ S15   S14 1986</p>
80.66	<p>Set a steel fence post alongside the cor.</p> <p>The cor. of secs. 10, 11, 14 and 15, monumented with a volcanic stone, 22 x 10 x 9 ins., firmly set 4 ins. in the ground and in a mound of stone, 1½ ft. base, 2 ins. high, mkd. with 2 grooves on the E face, 4 grooves on the S face and X on top, with a mound of stone, 3½ ft. base, 1 ft. high, W of the cor. This monument was also recovered in the 1915 retracement by R.P.A. Johnson while executing Homestead Entry Survey No. 327.</p> <p>At the cor. point</p> <p>Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 4 ins. in the ground, over a rebar, 12 ins. long, ½ in. diam., and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T13N R2E S10   S11 S15   S14 1984</p> <p>Deposit the original stone in mound alongside the iron post.</p>
	<p>From the cor. of secs. 27, 28, 33 and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 13 ins. above ground, with a mound of stone, 2½ ft. base, 6 ins. high, West, with brass cap mkd.</p> <p style="text-align: center;">T13N R2E S28   S27 S33   S34 1923</p>

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set a steel fence post alongside the cor.</p> <p>From this point, U.S. Geological Survey triangulation station "ROUND", bears N 45°34' W (forward bearing), 379.26 chs. dist., monumented with a brass disk, 3½ ins. diam., set flush in a drill hole in a granite rock, 20 x 20 x 12 ins., mkd. ROUND 1943.</p> <p>N 0°30' E, bet. secs. 27 and 28.</p> <p>Over rolling land, mostly open.</p>	
20.05	<p>Point for the S 1/16 sec. cor. of secs. 27 and 28.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T13N R2E S 1/16 S28   S27 1984</p>	
40.10	<p>Set a steel fence post alongside the cor.</p> <p>The ¼ sec. cor. of secs. 27 and 28, monumented with a granite stone, 8 x 12 x 16 ins., firmly set 8 ins. in the ground, mkd. ¼ on S face.</p> <p>At the cor. point</p> <p>Set a monument, 30 ins. long, composed of an iron post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 20 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T13N R2E ¼ S28   S27 1984</p> <p>from which</p> <p style="text-align: center;">A juniper, 16 ins. diam., bears S 73° W, 4.33 chs. dist., mkd. ¼ S28 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/>	
20.07	<p>N 0°54' E, beginning new measurement.</p> <p>Over rolling hills, through catclaw and sparse juniper.</p> <p>Point for the N 1/16 sec. cor. of secs. 27 and 28.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T13N R2E N 1/16 S28   S27 1984</p>	
21.30	<p>Set a steel fence post alongside the cor.</p> <p>Dirt road, 30 lks. wide, bears SE and NW.</p>	



Dependent Resurvey, a Portion of the Subdivisional Lines  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS		
40.14	<p>The cor. of secs. 21, 22, 27 and 28, monumented with a granite stone, 11 x 15 x 16 ins., firmly set 10 ins. in the ground, mkd. with 3 grooves on the E and 2 grooves on the S faces, with a mound of stone, 2 ft. base, 6 ins. high, W, and an iron post, 36 ins. long, 2 ins. diam., projecting 14 ins. above ground, set adjacent to the stone, with brass cap mkd.</p> <p style="text-align: center;">T13N R2E S21   S22 S28   S27 1923</p> <p>At the cor. point</p> <p>Reset the iron post, 22 ins. in the ground and add the date, 1984, to the brass cap.</p> <p>Deposit the mkd. stone alongside the iron post.</p>	
40.94	<p>N 5°06' E, bet. secs. 21 and 22.</p> <p>Over hilly terrain, mostly open.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 21 and 22, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T13N R2E <math>\frac{1}{4}</math> S21   S22 1984</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 180 lks. West of a dirt road, bears N 10° E and S 10° W.</p>	
81.88	<p>Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T13N R2E S16   S15 S21   S22 1984</p> <p>Set a steel fence post alongside the cor.</p>	
2.00	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N 87°31' W, bet. secs. 15 and 22.</p> <p>Over rolling terrain, mostly open.</p> <p>Descend WNW slope.</p>	

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS	
43.07	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 15 and 22, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 16 ins. in the ground, and in a mound of stone, <math>2\frac{1}{2}</math> ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T13N R2E <math>\frac{1}{4}</math> <u>S15</u> S22 1984</p> <p>Set a steel fence post alongside the cor.</p>
86.14	<p>The cor. of secs. 15, 16, 21 and 22.</p> <hr/>
	<p>N <math>2^{\circ}13'</math> W, bet. secs. 15 and 16.</p> <p>Over hilly, open terrain.</p>
40.80	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 15 and 16, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, <math>2\frac{1}{2}</math> ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T13N R2E <math>\frac{1}{4}</math> S16   S15 1984</p> <p>Set a steel fence post alongside the cor.</p>
81.60	<p>The cor. of secs. 9, 10, 15 and 16, monumented with a malpais stone, 20 x 15 x 10 ins., firmly set 6 ins. in the ground, mkd. with 3 grooves on the E and 4 grooves on the S faces, surrounded by 4 large stones.</p> <p>At the cor. point</p> <p>Set a monument, 30 ins. long, composed of an iron post, 25 ins. long, <math>2\frac{1}{2}</math> ins. diam., bonded to a magnetic poly breakaway base, 4 ins. in the ground and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T13N R2E S 9   S10 S16   S15 1984</p> <p>from which</p> <p style="text-align: center;">A basalt stone, 30 x 24 x 15 ins., bears N <math>62\frac{1}{2}^{\circ}</math> E, 35 lks. dist., mkd. XBO on top.</p> <p>Deposit the mkd. stone in the mound alongside the iron post.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N <math>87^{\circ}03'</math> W, bet. secs. 10 and 15.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS		
	Over open rolling terrain.	
45.06	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15, at proportionate dist.; there is no evidence of the original cor.	
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.	
	T13N R2E $\frac{1}{4}$ <u>S10</u> S15 1986	
	Set a steel fence post alongside the cor.	
90.12	The cor. of secs. 9, 10, 15 and 16.	
	N 1°53' E, bet. secs. 9 and 10.	
	Over hilly, open terrain.	
26.80	Track road, bears N 75° E and S 75° W.	
29.20	Dim road, bears NE and SW.	
40.09	The $\frac{1}{4}$ sec. cor. of secs. 9 and 10, monumented with a basalt stone, 18 x 15 x 8 ins., firmly set 10 ins. in the ground, mkd. $\frac{1}{4}$ on the S face, surrounded by three large stones.	
	At the cor. point	
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap mkd.	
	T13N R2E $\frac{1}{4}$ S 9   S10 1986	
	Deposit a magnet in a 1 x 1 x $2\frac{5}{8}$ in. white colored plastic case beneath the stainless steel post.	
	Deposit the mkd. stone alongside the stainless steel monument.	
	Set a steel fence post alongside the cor.	
40.19	N 1°41' E, beginning new measurement.  The cor. of secs. 3, 4, 9, and 10, monumented with a granite stone, 26 x 20 x 6 ins., firmly set 15 ins. in a mound of stone, 4 ft. base, 15 ins. high, mkd. with 3 grooves on the E and 5 grooves on the S faces, with an iron post, 36 ins. long, 2 ins. diam., projecting 15 ins. above the ground, adjacent to the mkd. stone, in the same mound of stone, to top, with brass cap mkd.	
	T13N R2E S 4   S 3 S 9   S10 1923	

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>At the cor. point</p> <p>Reset the iron post, 22 ins. in the ground, in a mound of stone, 4 ft. base, to top, and add the date, 1986, to the brass cap.</p> <p>Deposit the mkd. stone in the mound alongside the iron post.</p> <p>A mound of stone, 3 ft. base, 2 ft. high, is W of the cor.</p>
19.99	<p>(Restoring the resurvey by Benjamin J. Kinsey and Ty White, in 1923.)</p> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N 87°33' W, bet. secs. 28 and 33.</p> <p>Over open, rolling hills, with scattered catclaw.</p> <p>Point for the E 1/16 sec. cor. of secs. 28 and 33.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>T13N R2E E 1/16 <math>\frac{S28}{S33}</math> 1984</p> </div>
24.00	<p>Set a steel fence post alongside the cor.</p> <p>Dirt road, bears S 20° E and N 20° W.</p>
39.98	<p>Point for the ¼ sec. cor. of secs. 28 and 33, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <div style="text-align: center;"> <p>T13N R2E ¼ <math>\frac{S28}{S33}</math> 1984</p> </div>
54.00	<p>from which</p> <p style="padding-left: 40px;">A juniper, 15 ins. diam., bears S 7° E, 25 lks. dist., mkd. ¼ S33 BT.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 50 lks. N of a dirt road, 18 lks. wide, bears N 70° E and S 70° W.</p> <p>Cor. is located 1.50 chs. N of a wash, 30 lks. wide, 5 ft. deep, drains N 65° E.</p>
55.90	<p>Easterly transmission line, bears S 20½° E and N 20½° W.</p>
	<p>Westerly transmission line, bears S 20½° E and N 20½° W.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS	
79.96	<p>The cor. of secs. 28 and 33 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 3 ins. above a mound of stone, 3 ft. base, 18 ins. high; add 1986 to the brass cap which is now mkd.</p> <p style="text-align: center;">           T13N R2E            S29   S28                S33            1986            1923         </p> <p>Cor. is located in fence line, bears N and S.</p> <hr/> <p>N 0°34' E, on the W bdy. of sec. 28.</p> <p>Over hilly, open terrain.</p>
35.15	<p>The <math>\frac{1}{4}</math> sec. cor. of sec. 29 only, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with a mound of stone, 3 ft. base, 1 ft. high, to the W, with brass cap mkd.</p> <p style="text-align: center;"> <math>\frac{1}{4}</math>              S29              1923         </p> <p>Cor. is located in a fence line, bears N and S.</p> <hr/> <p>N 0°50' E, beginning new measurement.</p>
4.63	<p>The <math>\frac{1}{4}</math> sec. cor. of sec. 28 only, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above a mound of stone, 2½ ft. base, 6 ins. high, with brass cap mkd.</p> <p style="text-align: center;">             <math>\frac{1}{4}</math>              S28            1923         </p> <p>Cor. is located 1.5 lks. East of a fence line, bears N and S.</p> <hr/> <p>N 0°36' E, beginning new measurement.</p>
19.91	<p>Point for the N 1/16 sec. cor. of sec. 28 only.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 25 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">           T13N R2E                N 1/16                S28            1984         </p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 5 lks. East of a N and S fence line, and falls on a N slope underneath a power line.</p>
21.30	<p>Westerly transmission line, bears S 20½° E and N 20½° W.</p>
27.30	<p>Easterly transmission line, bears S 20½° E and N 20½° W.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS	
35.47	<p>The closing cor. of secs. 20 and 29, monumented with an iron post, 2 ins. diam., firmly set, projecting 13 ins. above ground, and in a collar of stone, with a mound of stone, 2½ ft. base, 1 ft. high, W of cor.; add 1986 to the brass cap which is now mkd.</p>
	$\begin{array}{r} \text{T13N R2E} \\ \text{S20} \mid \text{S28} \\ \text{CC} \frac{\text{S29}}{\text{S20}} \mid \\ \text{1986} \\ \text{1923} \end{array}$
	<p>Cor. is located in a fence line, bears N and S.</p>
	<p>N 0°45' E, beginning new measurement.</p>
4.35	<p>The cor. of secs. 21 and 28 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above a mound of stone, 3 ft. base, 1 ft. high; add 1986 to the brass cap which is now mkd.</p>
	$\begin{array}{r} \text{T13N R2E} \\ \text{S20} \mid \text{S21} \\ \mid \text{S28} \\ \text{1986} \\ \text{1923} \end{array}$
	<p>Cor. is located in a fence line, bears N and S.</p>
	<p>From the cor. of secs. 21, 22, 27 and 28.</p>
	<p>N 88°00' W, bet. secs. 21 and 28.</p>
	<p>Over rolling, open hills.</p>
15.00	<p>Dirt road, 30 lks. wide, bears southeasterly and northwesterly.</p>
20.015	<p>Point for the E 1/16 sec. cor. of secs. 21 and 28.</p>
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 16 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p>
	$\begin{array}{r} \text{T13N R2E} \\ \text{E 1/16} \frac{\text{S21}}{\text{S28}} \\ \text{1984} \end{array}$
	<p>Set a steel fence post alongside the cor.</p>
40.03	<p>Point for the ¼ sec. cor. of secs. 21 and 28, at proportionate dist.; there is no evidence of the original cor.</p>
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 16 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.</p>
	$\begin{array}{r} \text{T13N R2E} \\ \frac{1}{4} \frac{\text{S21}}{\text{S28}} \\ \text{1984} \end{array}$

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A rebar of unknown origin, 1 in. diam., projecting 2 ins. above ground, bears S 81°41' W, 2.04 chs. dist.</p> <p>Set a steel fence post alongside the cor.</p>
50.037	Point for the E-W 1/64 sec. cor. of secs. 21 and 28; not monumented.
53.80	Power lines, bear S 25° E and N 25° W.
55.041	Point for the W-E-W 1/256 sec. cor. of secs. 21 and 28.
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S21 W-E-W 1/256 S28 1984</p>
	<p>from which</p> <p>A fence cor., bears S 8¾° W, 1.76 chs. dist.; fences extend S 35° E and S 60° W.</p> <p>Set a steel fence post alongside the cor.</p>
56.20	Dirt road, 14 lks. wide, bears S 40° E and N 30° W.
60.045	Point for the W 1/16 sec. cor. of secs. 21 and 28.
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T13N R2E W 1/16 <u>S21</u> S28 1984</p>
	<p>Set a steel fence post alongside the cor.</p>
64.50	A wash, 90 lks. wide, 3 to 15 ft. deep, drains S 25° E.
65.049	Point for the E-W-W 1/256 sec. cor. of secs. 21 and 28.
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 25 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S21 E-W-W 1/256 S28 1984</p>
	<p>Set a steel fence post alongside the cor.</p>
70.053	Point for the W-W 1/64 sec. cor. of secs. 21 and 28; not monumented.
80.06	The cor. of secs. 21 and 28 only.
	<hr/> <p>N 1°03' E, on the W bdy. of sec. 21.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS		
	Over open, hilly terrain.	
9.98	Point for the S-S 1/64 sec. cor. of sec. 21 only.	
	Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.	
	<p style="text-align: center;">  S-S 1/64   S21 1984</p>	
	Cor. is located 5 lks. W of a N and S fence.	
19.96	Point for the S 1/16 sec. cor. of sec. 21 only.	
	Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.	
	<p style="text-align: center;">T13N R2E   S 1/16   S21 1984</p>	
	Cor. is located 1 lk. E of a N and S fence line.	
29.94	Point for the N-S 1/64 sec. cor. of sec. 21 only.	
	Set an aluminum post, 28 ins. long, 1 in. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.	
	<p style="text-align: center;">  N-S 1/64   S21 1984</p>	
	Cor. is located 2 lks. E of a N and S fence line.	
35.67	The ¼ sec. cor. of sec. 20 only, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above a mound of stone, 2 ft. base, 6 ins. high, with brass cap mkd.	
	<p style="text-align: center;">¼   S20   1923</p>	
	Cor. is located in a N and S fence line.	
	_____	
	N 1°00' E, beginning new measurement.	
4.25	The ¼ sec. cor. of sec. 21 only, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with a mound of stone, 3 ft. base, 1 ft. high, to the E, with brass cap mkd.	
	<p style="text-align: center;">  ¼   S21 1923</p>	
	Cor. is located in a N and S fence line.	
	_____	
	N 0°54' E, beginning new measurement.	



Dependent Resurvey, a Portion of the Subdivisional Lines  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS	
9.97	<p>Point for the S-N 1/64 sec. cor. of sec. 21 only.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">  S-N 1/64   S21 1984</p> <p>from which</p> <p style="padding-left: 40px;">A rebar, 3/8 in. diam., bears North, 32 lks. dist.</p> <p>Cor. is located 2 lks. E of a N and S fence line.</p>
19.94	<p>Point for the N 1/16 sec. cor. of sec. 21 only.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T13N R2E   N 1/16   S21 1984</p> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears N 55° E, 40 lks. dist.; fences extend N, S and W.</p> <p style="padding-left: 40px;">NW cor. of a wood building, 40 x 20 ft., bears N 65° E, 82 lks. dist., long side bears N 65° E.</p> <p>Cor. is located 3 lks. N of a fence, bears N 50° E and S 50° W.</p>
24.925	<p>Point for the S-N-N 1/256 sec. cor. of sec. 21 only falls on a granite outcropping, 4 x 8 x 4 ft. high.</p> <p>Mkd. an X at the cor. point on the NW top of the rock.</p> <p>from which</p> <p style="padding-left: 40px;">A rebar, 1/2 in. diam., projecting 3 ins. above ground, mkd. RCE 2398, bears N 1° E, 76.5 lks. dist.</p> <p style="padding-left: 40px;">A granite rock outcropping, 4 x 6 x 4 ft. high, bears N 89½° E, 41.5 lks. dist., mkd. X BO on W face.</p> <p style="padding-left: 40px;">An aluminum post, 28 ins. long, 1 in. diam., set 18 ins. in the ground, and in a mound of stone, 2 ft. base to top, for a reference monument, bears S 37° E, 29.78 ft. dist., with cap mkd. RM S21 S-N-N 1/256 29.78 FT 1984, and an arrow pointing to the cor. point.</p> <p>Cor. is located 33 lks. East of a N and S fence line and 20 lks. West of a wash, drains South.</p>
25.07	<p>Fence line, bears SE and W.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS	
35.79	<p>The closing cor. of secs. 17 and 20 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground; add 1986 to the brass cap which is now mkd.</p> $\begin{array}{r} \text{T13N R2E} \\ \text{CC } \frac{\text{S17}}{\text{S20}} \mid \text{S21} \\ \text{1986} \\ \text{1923} \end{array}$ <p>Cor. is located at the intersection of fence lines extending N, S and W.</p> <hr style="width: 20%; margin: auto;"/> <p>N 1°54' E, beginning new measurement.</p>
4.09	<p>The cor. of secs. 16 and 21 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 3 ins. above a scattered mound of stone, 4 ft. base, 1 ft. high; add 1986 to the brass cap which is now mkd.</p> $\begin{array}{r} \text{T13N} \\ \text{S17} \mid \frac{\text{R2E}}{\text{S16}} \\ \mid \text{S21} \\ \text{1986} \\ \text{1923} \end{array}$ <p>Cor. is located 2 lks. W of a N and S fence line.</p> <hr/> <p>(Restoring the survey executed by C.B. Foster, in 1877.)</p> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N 89°21' W, bet. secs. 16 and 21.</p> <p>Over rolling land, through scattering undergrowth.</p>
42.92	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 16 and 21, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set an aluminum post, 60 ins. long, <math>\frac{3}{4}</math> in. diam., 54 ins. in the ground, with cap mkd.</p> $\begin{array}{r} \text{T13N R2E} \\ \frac{1}{4} \frac{\text{S16}}{\text{S21}} \\ \text{1984} \end{array}$ <p>Set a steel fence post alongside the cor.</p> <p>Cor. falls on N bank of a wash.</p>
43.70	<p>Wash, 140 lks. wide, 2½ ft. deep, drains S.</p>
64.38	<p>Point for the W 1/16 sec. cor. of secs. 16 and 21.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.</p> $\begin{array}{r} \text{T13N R2E} \\ \text{W } \frac{1}{16} \frac{\text{S16}}{\text{S21}} \\ \text{1984} \end{array}$

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS	
75.11	<p>Point for the W-W 1/64 sec. cor. of secs. 16 and 21.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 14 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S16 W-W 1/64 S21 1984</p>
85.84	<p>The cor. of secs. 16 and 21 only.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N 89°07' W, bet. secs. 9 and 16.</p> <p>Over hilly terrain, mostly open.</p>
40.28	<p>The ¼ sec. cor. of secs. 9 and 16, monumented with a granite stone, 18 x 12 x 10 ins., firmly set 8 ins. in the ground, mkd. ¼ on S face.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T13N R2E ¼ <math>\frac{S\ 9}{S16}</math> 1984</p> <p>from which</p> <p style="padding-left: 40px;">A basalt stone, 14 x 10 x 7 ins., bears S 82° E, 3 lks. dist., mkd. X on W face.</p> <p style="padding-left: 40px;">A granite boulder, 4½ x 2½ x 2 ft., bears N 24¼° W, 56 lks. dist., mkd. X BO on top.</p> <p>Deposit the original stone alongside the aluminum post. Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>S 89°00' W, beginning new measurement.</p>
39.99	<p>The cor. of secs. 9 and 16 only, monumented with a granite stone, 20 x 14 x 10 ins., firmly set 12 ins. in the ground, mkd. with 4 grooves on the E face, no marks on the S, with an iron post, 36 ins. long, 2 ins. diam., projecting 16 ins. above ground, set adjacent to the stone, with brass cap mkd.</p> <p style="text-align: center;">T13N   S 9   S16   R2E 1923</p> <p>Both monuments are surrounded by a scattering mound of stone.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A mound of stone, 4 ft. base, 1½ ft. high, is E of the cor.</p> <p>At the cor. point</p> <p>Reset the iron post 22 ins. in the ground and in a mound of stone, 3 ft. base, to top, and changed the markings on the brass cap to read</p> <div style="text-align: center;"> <p>T13N R2E S 8   S 9             S16 1984 1923</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <hr/> <p style="text-align: center;">Subdivision of Section 21 T 13 N, R 2 E, Gila and Salt River Mer., Arizona</p> <hr/> <p>From the ¼ sec. cor. of secs. 21 and 28.</p> <p>N 3°06' E, on the N and S center line of sec. 21.</p> <p>10.10 Point for the center S-S 1/64 sec. cor. of sec. 21; not monumented.</p> <p>20.20 Point for the center S 1/16 sec. cor. of sec. 21.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <div style="text-align: center;"> <p>T13N R2E C S 1/16   S21 C 1984</p> </div> <p>Set a steel fence post alongside the cor.</p> <p>30.30 Point for the center N-S 1/64 sec. cor. of sec. 21; not monumented.</p> <p>40.40 Point for the center ¼ sec. cor. of sec. 21, at intersection with the E and W center line of sec. 21.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <div style="text-align: center;"> <p>T13N R2E C¼ S21 1984</p> </div> <p>Set a steel fence post alongside the cor.</p> <p>50.49 Point for the center S-N 1/64 sec. cor. of sec. 21; not monumented.</p> <p>60.58 Point for the center N 1/16 sec. cor. of sec. 21.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p>

Subdivision of Section 21  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>T13N R2E C N 1/16   S21 C 1984</p>	
	<p>Cor. is located 30 lks. W of a wash, 20 lks. wide, 3 ft. deep, drains S 35° E, and 90 lks. W of a dirt road, bears S 25° E and N 25° W.</p>	
80.76	<p>The ¼ sec. cor. of secs. 16 and 21.</p> <hr/> <p>From the ¼ sec. cor. of secs. 21 and 22. N 88°41' W, on the E and W center line of sec. 21. Over hilly terrain, mostly open.</p>	
9.20	<p>Wash, 50 lks. wide, 3 ft. deep, drains S 65° E.</p>	
41.48	<p>The center ¼ sec. cor. of sec. 21.</p>	
51.84	<p>Point for the center E-W 1/64 sec. cor. of sec. 21. Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">C <math>\frac{E-W 1/64}{S21}</math> C 1984</p>	
53.00	<p>Dirt road, bears N and S.</p>	
53.30	<p>Fence line, bears N and S.</p>	
62.20	<p>Point for the center W 1/16 sec. cor. of sec. 21. Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T13N R2E C <math>\frac{W 1/16}{S21}</math> C 1984</p>	
	<p>Set a steel fence post alongside the cor.</p>	
72.56	<p>Point for the center W-W 1/64 sec. cor. of sec. 21. Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">C <math>\frac{W-W 1/64}{S21}</math> C 1984</p>	
	<p>from which</p> <p style="text-align: center;">A rebar, ½ in. diam., projecting 1 in. above ground, bears S 86° W, 37.5 lks. dist.</p>	
	<p>Set a steel fence post alongside the cor.</p>	

Subdivision of Section 21  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS	
82.92	The $\frac{1}{4}$ sec. cor. of sec. 21 only.
	<hr/> SW $\frac{1}{4}$ of Section 21 <hr/>
	From the W $\frac{1}{16}$ sec. cor. of secs. 21 and 28.
	N $2^{\circ}05'$ E, on the N and S center line of the SW $\frac{1}{4}$ of sec. 21.
8.18	A wash, 61 lks. wide, 3 ft. deep, drains S $40^{\circ}$ W.
10.04	Point for the center S-SW $\frac{1}{64}$ sec. cor. of sec. 21.
	Set an aluminum post, 60 ins. long, $\frac{3}{4}$ in. diam., 58 ins. in the ground, with cap mkd.
	S21 C-S-SW $\frac{1}{64}$ 1984
	from which
	A cattleguard iron post, 4 ins. diam., 5 ft. high, bears N $33^{\circ}$ E, 6.8 lks. dist., stamped X BO.
	The SE cor. of a cattleguard rail, bears N $72^{\circ}$ W, 3.5 lks. dist., stamped X BO.
20.08	Point for the SW $\frac{1}{16}$ sec. cor. of sec. 21, at intersection with the E and W center line of the SW $\frac{1}{4}$ of sec. 21.
	Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	T13N R2E SW $\frac{1}{16}$ S21 1984
	from which
	A granite stone, $2\frac{1}{2} \times 2\frac{1}{2} \times 1\frac{1}{2}$ ft. high, bears N $75^{\circ}$ E, 37.5 lks. dist., mkd. X BO.
	Set a steel fence post alongside the cor.
25.10	Point for the center S-N-SW $\frac{1}{256}$ sec. cor. of sec. 21.
	Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	S21 C-S-N-SW $\frac{1}{256}$ 1984
	from which
	A rebar, $\frac{1}{2}$ in. diam., projecting 1 in. above ground, tagged R C E 2398, bears S $86\frac{1}{4}^{\circ}$ W, 47 lks. dist.

Subdivision of Section 21  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS	
	Set a steel fence post alongside the cor.
	Cor. is located 3.20 chs. W of a wash, 150 lks. wide, drains S 20° E.
30.12	Point for the center N-SW 1/64 sec. cor. of sec. 21.
	Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.
	S21
	C-N-SW
	1/64
	1984
	from which
	A rebar, 1/2 in. diam., projecting 2 ins. above
	ground, tagged R C E 2398, bears S 86° W, 55.5
	lks. dist.
	Set a steel fence post alongside the cor.
40.16	The center W 1/16 sec. cor. of sec. 21.
	From the center S 1/16 sec. cor. of sec. 21.
	N 88° 21' W, on the E and W center line of the SW 1/4 of
	sec. 21.
10.18	Point for the center E-SW 1/64 sec. cor. of sec. 21;
	not monumented.
20.36	The SW 1/16 sec. cor. of sec. 21.
30.54	Point for the center W-SW 1/64 sec. cor. of sec. 21;
	not monumented.
40.72	The S 1/16 sec. cor. of sec. 21 only.
	From the point for the center E-SW 1/64 sec. cor. of
	sec. 21.
	N 2° 35' E, on the N and S center line of the NE 1/4 of the
	SW 1/4 of sec. 21.
5.035	Point for the center S-NE-SW 1/256 sec. cor. of sec. 21.
	Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins.
	in the ground, in a mound of stone, 2 ft. base, to top,
	with cap mkd.
	S21
	C-S-NE-SW
	1/256
	1984
	Set a steel fence post alongside the cor.
	Cor. is located 1.25 chs. E of a fence line that bears
	N 20° E and S 20° W, and 80 lks. E of a dirt road,
	bears N and S.

Subdivision of Section 21  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS		
10.07	Point for the NE-SW 1/64 sec. cor. of sec. 21, at the intersection with the E and W center line of the NE $\frac{1}{4}$ of the SW $\frac{1}{4}$ of sec. 21.	
	Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.	
	S21 NE-SW 1/64 1984	
	Set a steel fence post alongside the cor.	
20.14	The center E-W 1/64 sec. cor. of sec. 21.	
	From the point for the center N-S 1/64 sec. cor. of sec. 21.	
	N 88°31' W, on the E and W center line of the NE $\frac{1}{4}$ of the SW $\frac{1}{4}$ of sec. 21.	
10.27	The NE-SW 1/64 sec. cor. of sec. 21.	
10.80	Dirt road, bears N and S.	
11.55	Fence line, bears N 20° E and S 20° W.	
20.54	The center N-SW 1/64 sec. cor. of sec. 21.	
	From the center S-NE-SW 1/256 sec. cor. of sec. 21.	
	N 88°26' W, on the E and W center line of the SW $\frac{1}{4}$ of the NE $\frac{1}{4}$ of the SW $\frac{1}{4}$ of sec. 21.	
10.21	The center S-N-SW 1/256 sec. cor. of sec. 21.	
	From the point for the E-W 1/64 sec. cor. of secs. 21 and 28.	
	N 2°36' E, on the N and S center line of the SE $\frac{1}{4}$ of the SW $\frac{1}{4}$ of sec. 21.	
10.07	Point for the SE-SW 1/64 sec. cor. of sec. 21, at intersection with the E and W center line of the SE $\frac{1}{4}$ of the SW $\frac{1}{4}$ of sec. 21; not monumented.	
20.14	The point for the center E-SW 1/64 sec. cor. of sec. 21.	
	From the point for the center S-S 1/64 sec. cor. of sec. 21.	
	N 88°11' W, on the E and W center line of the SE $\frac{1}{4}$ of the SW $\frac{1}{4}$ of sec. 21.	
10.10	The point for the SE-SW 1/64 sec. cor. of sec. 21.	
15.15	Point for the center W-SE-SW 1/256 sec. cor. of sec. 21.	
	Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.	



Subdivision of Section 21  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>S21 C-W-SE-SW 1/256 1984</p>	
	<p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 11 lks. S of a fence line, bears E and W.</p>	
20.20	<p>The center S-SW 1/64 sec. cor. of sec. 21.</p> <hr/> <p>From the W-E-W 1/256 sec. cor. of secs. 21 and 28.</p> <p>N 2°22' E, on the N and S center line of the SW<sup>1</sup>/<sub>4</sub> of the SE<sup>1</sup>/<sub>4</sub> of the SW<sup>1</sup>/<sub>4</sub> of sec. 21.</p>	
10.055	<p>The center W-SE-SW 1/256 sec. cor. of sec. 21.</p> <hr/> <p>From the point for the W-W 1/64 sec. cor. of secs. 21 and 28.</p> <p>N 1°35' E, on the N and S center line of the SW<sup>1</sup>/<sub>4</sub> of the SW<sup>1</sup>/<sub>4</sub> of sec. 21.</p>	
10.01	<p>Point for the SW-SW 1/64 sec. cor. of sec. 21, at the intersection with the E and W center line of the SW<sup>1</sup>/<sub>4</sub> of the SW<sup>1</sup>/<sub>4</sub> of sec. 21; not monumented.</p>	
20.02	<p>The point for the center W-SW 1/64 sec. cor. of sec. 21.</p> <hr/> <p>From the center S-SW 1/64 sec. cor. of sec. 21.</p> <p>N 88°12' W, on the E and W center line of the SW<sup>1</sup>/<sub>4</sub> of the SW<sup>1</sup>/<sub>4</sub> of sec. 21.</p>	
0.10	<p>Dirt road, bears S and curves N 45° E.</p>	
5.05	<p>Point for the center E-SW-SW 1/256 sec. cor. of sec. 21.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 26 ins. in the ground, with cap mkd.</p>	
	<p>S21 C-E-SW-SW 1/256 1984</p>	
	<p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 2 lks. N of an E and W fence line.</p>	
10.10	<p>The point for the SW-SW 1/64 sec. cor. of sec. 21.</p>	
20.195	<p>The S-S 1/64 sec. cor. of sec. 21 only.</p> <hr/> <p>From the E-W-W 1/256 sec. cor. of secs. 21 and 28.</p> <p>N 1°49' E, on the N and S center line of the SE<sup>1</sup>/<sub>4</sub> of the SW<sup>1</sup>/<sub>4</sub> of the SW<sup>1</sup>/<sub>4</sub> of sec. 21.</p>	
10.03	<p>The center E-SW-SW 1/256 sec. cor. of sec. 21.</p> <hr/>	

Subdivision of Section 21  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>From the point for the center W-SW 1/64 sec. cor. of sec. 21.</p>
	<p>N 1°33' E, on the N and S center line of the NW<math>\frac{1}{4}</math> of the SW<math>\frac{1}{4}</math> of sec. 21.</p>
10.01	<p>Point for the NW-SW 1/64 sec. cor. of sec. 21, at the intersection with the E and W center line of sec. 21; not monumented.</p>
15.015	<p>Point for the center N-NW-SW 1/256 sec. cor. of sec. 21.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p>
	<p style="text-align: center;">S21 C-N-NW-SW 1/256 1984</p>
	<p>from which</p> <p style="padding-left: 40px;">A rebar, <math>\frac{1}{2}</math> in. diam., projecting 1 in. above ground, bears N 83° W, 33 lks. dist.</p>
	<p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 132 lks. E of a power line, bears S 25° E and N 25° W.</p>
20.02	<p>The center W-W 1/64 sec. cor. of sec. 21.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center N-SW 1/64 sec. cor. of sec. 21.</p>
	<p>N 88°32' W, on the E and W center line of the NW<math>\frac{1}{4}</math> of the SW<math>\frac{1}{4}</math> of sec. 21.</p>
5.135	<p>Point for the center E-NW-SW 1/256 sec. cor. of sec. 21.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 2<math>\frac{1}{2}</math> ft. base, to top, with cap mkd.</p>
	<p style="text-align: center;">S21 C-E-NW-SW 1/256 1984</p>
	<p>from which</p> <p style="padding-left: 40px;">A rebar, <math>\frac{1}{2}</math> in. diam., projecting 2 ins. above ground, tagged R C E 2398, bears S 85<math>\frac{3}{4}</math>° W, 43 lks. dist.</p>
	<p>Set a steel fence post alongside the cor.</p>
10.27	<p>The point for the NW-SW 1/64 sec. cor. of sec. 21.</p>
20.54	<p>The N-S 1/64 sec. cor. of sec. 21 only.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center E-NW-SW 1/256 sec. cor. of sec. 21.</p>
	<p>N 1°49' E, on the N and S center line of the NE<math>\frac{1}{4}</math> of the NW<math>\frac{1}{4}</math> of the SW<math>\frac{1}{4}</math> of sec. 21.</p>

Subdivision of Section 21  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS	
5.01	<p>Point for the NE-NW-SW 1/256 sec. cor. of sec. 21.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S21 NE-NW-SW 1/256 1984</p> <p>from which</p> <p style="padding-left: 40px;">A rebar, ½ in. diam., projecting 3 ins. above ground, bears S 85¾° W, 49.5 lks. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 88°36.5' W, on the E and W center line of the NE¼ of the NW¼ of the SW¼ of sec. 21.</p>
5.16	<p>The center N-NW-SW 1/256 sec. cor. of sec. 21.</p> <hr style="width: 60%; margin: 10px auto;"/> <p style="text-align: center;">NW ¼ of Section 21</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the center W 1/16 sec. cor. of sec. 21.</p> <p>N 2°04' E, on the N and S center line of the NW¼ of sec. 21.</p>
10.03	<p>Point for the center S-NW 1/64 sec. cor. of sec. 21; not monumented.</p>
20.06	<p>Point for the NW 1/16 sec. cor. of sec. 21, at the intersection with the E and W center line of the NW¼ of sec. 21.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T13N R2E NW 1/16 S21 1984</p> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears N 82° W, 1.83 chs. dist., fences extend S and W.</p> <p style="padding-left: 40px;">A rebar, ½ in. diam., projecting 1 in. above ground, bears N 72¼° W, 1.235 chs. dist.</p>
25.075	<p>Point for the center S-N-NW 1/256 sec. cor. of sec. 21.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S21 C-S-N-NW 1/256 1984</p>

Subdivision of Section 21  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS		
	Set a steel fence post alongside the cor.	
25.30	Dirt road, bears E and W.	
25.55	Fence line, bears S 85° E and N 85° W.	
40.12	The W 1/16 sec. cor. of secs. 16 and 21.	
	<hr/> From the center N 1/16 sec. cor. of sec. 21.	
	N 89°01' W, on the E and W center line of the NW <sup>1</sup> / <sub>4</sub> of sec. 21.	
10.54	Point for the center E-NW 1/64 sec. cor. of sec. 21; not monumented.	
14.30	Fence line, bears S 15° E and N 15° W.	
15.81	Point for the center W-E-NW 1/256 sec. cor. of sec. 21.	
	Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.	
	<p style="text-align: center;">S21 C-W-E-NW 1/256 1984</p>	
	from which	
	<p style="text-align: center;">A rebar, ½ in. diam., projecting 1 in. above ground, bears N 77½° W, 1.475 chs. dist.</p>	
	Set a steel fence post alongside the cor.	
21.08	The NW 1/16 sec. cor. of sec. 21.	
31.643	Point for the center W-NW 1/64 sec. cor. of sec. 21; not monumented.	
42.206	The N 1/16 sec. cor. of sec. 21 only.	
	<hr/> From the center E-W 1/64 sec. cor. of sec. 21.	
	N 2°35' E, on the N and S center line of the SE <sup>1</sup> / <sub>4</sub> of the NW <sup>1</sup> / <sub>4</sub> of sec. 21.	
10.06	Point for the SE-NW 1/64 sec. cor. of sec. 21, at intersection with the E and W center line of sec. 21.	
	Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.	
	<p style="text-align: center;">S21 SE-NW 1/64 1984</p>	
	Set a steel fence post alongside the cor.	
15.09	Point for the center N-SE-NW 1/256 sec. cor. of sec. 21.	

Subdivision of Section 21  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p>	
	<p style="text-align: center;">S21 C-N-SE-NW 1/256 1984</p>	
20.12	<p>The point for the center E-NW 1/64 sec. cor. of sec. 21.</p> <hr style="width: 20%; margin: 0 auto;"/>	
	<p>From the point for the center S-N 1/64 sec. cor. of sec. 21.</p>	
	<p>N 88°52' W, on the E and W center line of the SE<sup>1</sup>/<sub>4</sub> of the NW<sup>1</sup>/<sub>4</sub> of sec. 21.</p>	
10.45	<p>The SE-NW 1/64 sec. cor. of sec. 21.</p>	
11.90	<p>Road, bears N 5° E and S 5° W.</p>	
12.10	<p>Fence, bears N 5° E and S 5° W.</p>	
20.90	<p>The point for the center S-NW 1/64 sec. cor. of sec. 21.</p> <hr style="width: 20%; margin: 0 auto;"/>	
	<p>From the center N-SE-NW 1/256 sec. cor. of sec. 21.</p>	
	<p>N 88°56.5' W, on the E and W center line of the NW<sup>1</sup>/<sub>4</sub> of the SE<sup>1</sup>/<sub>4</sub> of the NW<sup>1</sup>/<sub>4</sub> of sec. 21.</p>	
1.65	<p>Dirt road, bears N 10° W and South.</p>	
5.25	<p>Point for the NW-SE-NW 1/256 sec. cor. of sec. 21.</p>	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with cap mkd.</p>	
	<p style="text-align: center;">S21 NW-SE-NW 1/256 1984</p>	
	<p>from which</p>	
	<p style="text-align: center;">A rebar, ½ in. diam., projecting 2 ins. above ground, bears N 80½° W, 1.335 chs. dist.</p>	
	<p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 0 auto;"/>	
	<p>N 2°19.5' E, on the N and S center line of the NW<sup>1</sup>/<sub>4</sub> of the SE<sup>1</sup>/<sub>4</sub> of the NW<sup>1</sup>/<sub>4</sub> of sec. 21.</p>	
5.02	<p>The center W-E-NW 1/256 sec. cor. of sec. 21.</p> <hr style="width: 20%; margin: 0 auto;"/>	
	<p>From the center W-W 1/64 sec. cor. of sec. 21.</p>	
	<p>N 1°29' E, on the N and S center line of the SW<sup>1</sup>/<sub>4</sub> of the NW<sup>1</sup>/<sub>4</sub> of sec. 21.</p>	
10.00	<p>Point for the SW-NW 1/64 sec. cor. of sec. 21 at intersection with the E and W center line of the SW<sup>1</sup>/<sub>4</sub> of the NW<sup>1</sup>/<sub>4</sub> of sec. 21.</p>	

Subdivision of Section 21  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.</p>	
	<p style="text-align: center;">S21 SW-NW 1/64 1984</p>	
	<p>from which</p>	
	<p style="text-align: center;">A rebar, ½ in. diam., projecting 1 in. above ground, bears N 64° W, 53.5 lks. dist.</p>	
	<p>Set a steel fence post alongside the cor.</p>	
20.00	<p>The point for the center W-NW 1/64 sec. cor. of sec. 21</p> <hr style="width: 20%; margin: 0 auto;"/>	
	<p>From the point for the center S-NW 1/64 sec. cor. of sec. 21.</p>	
	<p>N 88°51' W, on the E and W center line of the SW¼ of the NW¼ of sec. 21.</p>	
10.46	<p>The SW-NW 1/64 sec. cor. of sec. 21.</p>	
19.35	<p>Power line, bears S 25° E and N 25° W.</p>	
20.92	<p>The S-N 1/64 sec. cor. of sec. 21 only.</p> <hr style="width: 20%; margin: 0 auto;"/>	
	<p>From the center S-N-NW 1/256 sec. cor. of sec. 21.</p>	
	<p>N 89°06' W, on the E and W center line of the S½ of the NW¼ of the NW¼ of sec. 21.</p>	
21.24	<p>The S-N-N 1/256 sec. cor. of sec. 21 only.</p> <hr style="width: 100%;"/>	
	<p style="text-align: center;">Subdivision of Section 28 T 13 N, R 2 E, Gila and Salt River Mer., Arizona</p> <hr style="width: 100%;"/>	
	<p>From the ¼ sec. cor. of secs. 28 and 33.</p>	
	<p>N 0°39' E, on the N and S center line of sec. 28.</p>	
	<p>Over hilly, mostly open terrain.</p>	
19.97	<p>Point for the center S 1/16 sec. cor. of sec. 28.</p>	
	<p>Set a monument, 30 ins. long, composed of an iron post, 24 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T13N R2E C S 1/16   S28 C 1984</p>	
	<p>from which</p>	

Subdivision of Section 28  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A forked cottonwood, with S fork 18 ins. diam., bears N 17° W, 43.5 lks. dist., mkd. C S 1/16 S28 BT and is in an E-W fence line.</p>
	<p>Set a steel fence post alongside the cor.</p>
39.94	<p>Point for the center 1/4 sec. cor. of sec. 28, at the intersection with the E and W center line of sec. 28.</p>
	<p>Set a monument, 30 ins. long, composed of an iron post, 25 ins. long, 2 1/2 ins. diam., bonded to a magnetic poly breakaway base, 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T13N R2E C 1/4 S28 1984</p>
	<p>from which</p>
	<p>A power pole, No. 123, bears S 59 1/4° E, 1.915 chs. dist.; lines extend S 20° E and N 20° W.</p>
	<p>Set a steel fence post alongside the cor.</p>
49.94	<p>Point for the center S-N 1/64 sec. cor. of sec. 28; not monumented.</p>
59.94	<p>Point for the center N 1/16 sec. cor. of sec. 28.</p>
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p>
	<p style="text-align: center;">T13N R2E C N 1/16   S28 C 1984</p>
	<p>from which</p>
	<p>NW cor. of a house, 56 x 28 ft., bears S 64° E, 4.27 chs. dist., the long side bears N and S.</p>
	<p>NE cor. of a mobile home, bears S 18° W, 1.93 chs. dist.</p>
	<p>A fence corner, bears N 13° W, 41 lks. dist; fences extend N and E.</p>
	<p>Set a steel fence post alongside the cor.</p>
79.94	<p>The 1/4 sec. cor. of secs. 21 and 28.</p>
	<p>From the 1/4 sec. cor. of secs. 27 and 28.</p>
	<p>N 87°46' W, on the E and W center line of sec. 28.</p>
	<p>Over hilly, open terrain.</p>
19.93	<p>Point for the center E 1/16 sec. cor. of sec. 28.</p>
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p>

Subdivision of Section 28  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS		
	$C \frac{T13N R2E}{E 1/16} C$ <p style="text-align: center;">S28 1984</p>	
	Set a steel fence post alongside the cor.	
29.895	Point for the center W-E 1/64 sec. cor. of sec. 28.	
	Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.	
	$C \frac{W-E 1/64}{S28} C$ <p style="text-align: center;">1984</p>	
32.58	Fence line, bears N and S.	
39.10	Wash, 30 lks. wide, drains S 30° W.	
39.86	The center 1/4 sec. cor. of sec. 28.	
48.08	Fence line, bears S 33° E and N 33° W.	
49.86	Point for the center E-W 1/64 sec. cor. of sec. 28.	
	Set an aluminum post, 28 ins. long, 1 in. diam., 23 ins. in the ground, with cap mkd.	
	$C \frac{E-W 1/64}{S28} C$ <p style="text-align: center;">1984</p>	
	Raise a mound of stone, 2 ft. base, 18 ins. high, N of cor.	
	Set a steel fence post alongside the cor.	
	Cor. is located 40 lks. N of a wash, 20 lks. wide, 5 ft. deep, drains S 60° E.	
59.86	Point for the center W 1/16 sec. cor. of sec. 28.	
	Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.	
	$C \frac{T13N R2E}{W 1/16} C$ <p style="text-align: center;">S28 1984</p>	
	Set a steel fence post alongside the cor.	
69.30	Easterly transmission line, bears S 20½° E and N 20½° W.	
71.20	Westerly transmission line, bears S 20½° E and N 20½° W.	
79.86	The 1/4 sec. cor. of sec. 28 only.	
<hr/> <p>NE 1/4 of Section 28</p> <hr/>		
	From the center E 1/16 sec. cor. of sec. 28.	
	N 0°47' E, on the N and S center line of the NE 1/4 of sec. 28.	



Subdivision of Section 28  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS		
20.03	<p>Point for the NE 1/16 sec. cor. of sec. 28, at the intersection with the E and W center line of the NE<math>\frac{1}{4}</math> of sec. 28.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 25 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T13N R2E NE 1/16 S28 1984</p> <p>Set a steel fence post alongside the cor.</p>	
40.06	<p>The E 1/16 sec. cor. of secs. 21 and 28.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the N 1/16 sec. cor. of secs. 27 and 28.</p> <p>N 87°53' W, on the E and W center line of the NE<math>\frac{1}{4}</math> of sec. 28.</p>	
19.97	<p>The NE 1/16 sec. cor. of sec. 28.</p>	
29.40	<p>Wash, 15 lks. wide, drains S 10° W.</p>	
29.955	<p>Point for the center W-NE 1/64 sec. cor. of sec. 28.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S28 C-W-NE 1/64 1984</p> <p>from which</p> <p style="padding-left: 40px;">A sandstone of unknown origin, 7 x 7 x 7 ins. above ground, in a mound of stone, 2 ft. base, 6 ins. high, mkd. H, with 2 grooves below on W face; bears N 75° W, 2.46 chs. dist.; stone is located in a fence cor. from which fences extend S and W.</p> <p>Set a steel fence post alongside the cor.</p>	
39.94	<p>The center N 1/16 sec. cor. of sec. 28.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center W-E 1/64 sec. cor. of sec. 28.</p> <p>N 0°43' E, on the N and S center line of the SW<math>\frac{1}{4}</math> of the NE<math>\frac{1}{4}</math> of sec. 28.</p>	
20.015	<p>The center W-NE 1/64 sec. cor. of sec. 28.</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="text-align: center;">SE <math>\frac{1}{4}</math> of Section 28</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the E 1/16 sec. cor. of secs. 28 and 33.</p> <p>N 0°34' E, on the N and S center line of the SE<math>\frac{1}{4}</math> of sec. 28.</p>	

Subdivision of Section 28  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS	
20.01	<p>Point for the SE 1/16 sec. cor. of sec. 28, at the intersection with the E and W center line of the SE<math>\frac{1}{4}</math> of sec. 28.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T13N R2E SE 1/16 S28 1984</p> <p>Set a steel fence post alongside the cor.</p>
40.02	<p>The center E 1/16 sec. cor. of sec. 28.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the S 1/16 sec. cor. of secs. 27 and 28.</p> <p>N 87°40' W, on the E and W center line of the SE<math>\frac{1}{4}</math> of sec. 28.</p>
1.45	<p>Dirt road, 20 lks. wide, bears N 35° E and S 35° W.</p>
19.96	<p>The SE 1/16 sec. cor. of sec. 28.</p>
29.94	<p>Point for the center W-SE 1/64 sec. cor. of sec. 28.</p> <p>Set a monument, 30 ins. long, composed of an iron post, 25 ins. long, 2<math>\frac{1}{2}</math> ins. diam., bonded to a magnetic poly breakaway base, 4 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S28 C-W-SE 1/64 1984</p> <p>from which</p> <ul style="list-style-type: none"> <li>A rock, 30 x 20 x 6 ins. high, bears N 42<math>\frac{1}{2}</math>° E, 57 lks. dist., mkd. X BO.</li> <li>A power pole, bears S 13° W, 4.18 chs. dist., lines extend S 20° E and N 20° W.</li> <li>A power pole, bears N 48° E, 4.69 chs. dist., lines extend S 20° E and N 20° W.</li> <li>A fence cor., bears N 81<math>\frac{1}{2}</math>° W, 4.00 chs. dist; fences extend N and W.</li> </ul>
	<p>Cor. is located 35 lks. S of a wash, 10 lks. wide, drains West.</p>
39.92	<p>Set a steel fence post alongside the cor.</p> <p>The center S 1/16 sec. cor. of sec. 28.</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="text-align: center;">NW <math>\frac{1}{4}</math> of Section 28</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center W 1/16 sec. cor. of sec. 28.</p> <p>N 0°38' E, on the N and S center line of the NW<math>\frac{1}{4}</math> of sec. 28.</p>

Subdivision of Section 28  
T 13. N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS	
9.98	<p>Point for the center S-NW 1/64 sec. cor. of sec. 28.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S28 C-S-NW 1/64 1984</p> <p>from which</p> <p style="text-align: center;">A rebar, 1 in. diam., projecting 2 ins. above ground, bears N 25<math>\frac{3}{4}</math>° W, 45.5 lks. dist.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.</p> <p>Set a steel fence post alongside the cor.</p>
19.96	<p>Point for the NW 1/16 sec. cor. of sec. 28, at intersection with the E and W center line of the NW<math>\frac{1}{4}</math> of sec. 28..</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T13N R2E NW 1/16 S28 1984</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.</p> <p>Set a steel fence post alongside the cor.</p>
39.91	<p>The W 1/16 sec. cor. of secs. 21 and 28.</p> <hr/> <p>From the center N 1/16 sec. cor. of sec. 28.</p> <p>N 87°52' W, on the E and W center line of the NW<math>\frac{1}{4}</math> of sec. 28.</p>
10.005	<p>Point for the center E-NW 1/64 sec. cor. of sec. 28; not monumented.</p>
20.01	<p>The NW 1/16 sec. cor. of sec. 28.</p>
37.40	<p>Easterly transmission line, bears S 20<math>\frac{1}{2}</math>° E and N 20<math>\frac{1}{2}</math>° W.</p>
39.30	<p>Westerly transmission line, bears S 20<math>\frac{1}{2}</math>° E and N 20<math>\frac{1}{2}</math>° W.</p>
40.02	<p>The N 1/16 sec. cor. of sec. 28 only.</p> <hr/> <p>From the center E-W 1/64 sec. cor. of sec. 28.</p> <p>N 0°38' E, on the N and S center line of the SE<math>\frac{1}{4}</math> of the NW<math>\frac{1}{4}</math> of sec. 28.</p>
9.99	<p>Point for the SE-NW 1/64 sec. cor. of sec. 28, at the intersection with the E and W center line of the SE<math>\frac{1}{4}</math> of the NW<math>\frac{1}{4}</math> of sec. 28.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p>

Subdivision of Section 28  
T 13 N, R 2 E, Gila and Salt River Mer., Arizona

CHAINS		
	S28 SE-NW 1/64 1984	
	Raise a mound of stone, 2 ft. base, 1½ ft. high, W of cor.	
	Set a steel fence post alongside the cor.	
19.98	The point for the center E-NW 1/64 sec. cor. of sec. 28.	
	<hr/> From the point for the center S-N 1/64 sec. cor. of sec. 28.	
	N 87°49' W, on the E and W center line of the SE¼ of the NW¼ of sec. 28.	
10.00	The SE-NW 1/64 sec. cor. of sec. 28.	
20.00	The center S-NW 1/64 sec. cor. of sec. 28.	
	<hr/> GENERAL DESCRIPTION	
	The land encompassed in this survey is located about 10 miles north of Cordes Junction. Unimproved roads provide access to the area. The average elevation is about 4400 feet above sea level, with the terrain hilly and mostly open. The vegetation consist of grass, brush, scattered cacti, with mesquite, sparse oak and cottonwood.	
	The area is used principally for livestock grazing. No mineral formations of consequence were noted during the survey.	
	The mean magnetic declination is 13½° E, with negligible local attraction.	



CERTIFICATE OF SURVEY

I, Will C. Gabonay, Cadastral Surveyor, under the supervision of Harry K. Smith, Chief, Field Section, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 24th day of April 1984, I have dependently resurveyed a portion of the East boundary and a portion of the subdivisional lines, and have surveyed subdivisions in sections 21 and 28, Township 13 North, Range 2 East, of the Gila and Salt River Meridian, in the State of Arizona which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Will C. Gabonay is no longer assigned to this office and is not available for signature.

JAN 14 1987

(Date)

*Harry K. Smith*

Harry K. Smith, Chief, Field Section

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

Bureau of Land Management

The foregoing field notes of the dependent resurvey of a portion of the east boundary and a portion of the subdivisional lines, and the survey of subdivisions in sections 21 and 28, T 13 N, R 2 E, Gila and Salt River Meridian, Arizona, executed by Will C. Gabonay, Cadastral Surveyor, under the supervision of Harry K. Smith, Chief, Field Section, having been critically examined and found correct, are hereby approved.

FEB 05 1987

(Date)

*James P. Kelley*  
(Chief Cadastral Surveyor for Arizona)