

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE

SUBDIVISIONAL LINES

AND A

SURVEY OF SUBDIVISIONS IN SECTION 28,

A SURVEY OF LOT 1, SECTION 28,

AND

A SURVEY OF LOT 7, SECTION 30

TOWNSHIP 11 NORTH, RANGE 21 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Paul L. Reeves, Cadastral Surveyor

Under special instructions dated September 18, 1985, approved September 18, 1985
and supplemental special instructions dated October 3, 1986, approved October 3,
1986, which provided for the surveys included under Group Number
671 and assignment instructions dated October 3, 1986.

Survey commenced October 7, 1986

Survey completed October 10, 1986

INDEX DIAGRAM

TOWNSHIP 11 NORTH , RANGE 21 EAST ,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	5 29	28	27	26	25
		3			
31	32	33	34	35	36

Subdivision of Section 28.....pp. 7-10.
Survey of lot 1, Section 28.....pp. 10-12.
Survey of lot 7, Section 30.....pp. 12-13.

T 11 N, R 21 E, Gila and Salt River Mer., Arizona

CHAINS

The subdivisional lines were surveyed by Benjamin J. Kinsey and Sidney E. Blout in 1920 and 1921. Ronald E. Stoll, Arizona Registered Land Surveyor No. 11758, resurveyed a portion of subdivisional lines and surveyed subdivisions in certain sections under a Forest Service contract in 1981 and 1985.

The following field notes are those of a dependent resurvey of a portion of the subdivisional lines and a survey of subdivisions in sec. 28, survey of lot 1, sec. 28, and a survey of lot 7, sec. 30, Township 11 North, Range 21 East, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, the Special Instructions dated September 18, 1985, and the Supplemental Special Instructions dated October 3, 1986, for Group 671, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of all lines were determined by direct observations on the sun and refer to the true meridian. Distances and angles were measured electronically with a Zeiss Elta 46 instrument.

The geographic position of the southeast cor. of section 28, Township 11 North, Range 21 East, as scaled from U.S. Geological Survey quadrangle map, "SHOW LOW NORTH, ARIZ.," prepared in 1970, is as follows:

Latitude: 34°18'52" N. Longitude: 110°06'41" W.

The mean magnetic declination is 13½° E.

Dependent Resurvey
of a Portion of Subdivisional Lines,
T 11 N, R 21 E, Gila and Salt River Mer., Arizona

Restoring the survey by Benjamin J. Kinsey and
Sidney E. Blout in 1920 and 1921.

Beginning at the cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 2 ins. diam., projecting 2 ins. above the ground, with brass cap mkd.

T11N R21E
S28 | S27
S33 | S34
1920

A mound of stone, 2½ ft. base, 1½ ft. high, is W of cor.

A steel fence post is alongside the cor.

Cor. is located 111 lks. N of a graded gravel road, bears N 70° E and W.

Dependent Resurvey of a Portion of Subdivisional Lines,
T 11 N, R 21 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>S 89°43' W, bet. secs. 28 and 33.</p> <p>Over gently rolling open land.</p>	
40.14	<p>The ¼ sec. cor. of secs. 28 and 33, monumented with a ¾ in. steel "T" post, 12 ins. below ground, with an aluminum cap attached and is accepted as a careful and faithful reestablishment of the position of the original cor., cap is mkd.</p> <p style="text-align: center;"> $\frac{1}{4} \frac{S28}{S33}$ LS 11758 </p>	
	<p>S 89°44' W, beginning new measurement.</p>	
19.00	<p>Enter timber, edge bears N and S.</p>	
20.07	<p>The W 1/16 sec. cor. of secs. 28 and 33, monumented with a U.S. Department of Agriculture aluminum post, 2½ ins. diam., projecting 5 ins. above the ground and is accepted as a careful and faithful determination of the position of the corner, with aluminum cap attached and mkd.</p> <p style="text-align: center;"> T11N R21E W 1/16 $\frac{S28}{S33}$ RLS 11758 1981 </p>	
	<p>A steel fence post is alongside the cor.</p> <p>Cor. is located in a N and S fence.</p>	
	<p>S 89°43' W, beginning new measurement.</p>	
20.07	<p>The cor. of secs. 28, 29, 32, and 33, monumented with an iron post, 2 ins. diam., projecting 14 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"> T11N R21E S29 S28 S32 S33 1920 </p> <p>from which the original bearing trees</p> <p>A stump hole, bears N 72° E, 149 lks. dist.; a bulldozed out juniper, 18 ins. diam, no marks visible, is alongside (Record: N 79° E).</p> <p>A juniper, 15 ins. diam., bears S 61° E, 261 lks. dist., mkd. T11N R21E S33 BT.</p> <p>A juniper stump, 18 ins. diam., bears S 59° W, 326.5 lks. dist., no marks visible (Record: 329 lks. dist.).</p> <p>A juniper, 18 ins. diam., bears N 6° W, 244 lks. dist., mkd. T11N R21E S29 BT (Record: N 10° W, 242 lks. dist.).</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T 11 N, R 21 E, Gila and Salt River Mer., Arizona

CHAINS

from which new bearing trees

A pinyon, 5 ins. diam., bears N 82° E, 94.5
lks. dist., mkd. T11N R21E S28 BT.

A juniper, 8 ins. diam., bears S 41 $\frac{3}{4}$ ° W, 35
lks. dist., mkd. T11N R21E S32 BT.

Add the marks 1986 to the brass cap.

A steel fence post is alongside the cor.

From the $\frac{1}{4}$ sec. cor. of secs. 29 and 30, monumented
with an iron post, 1 in. diam., projecting 18 ins.
above the ground, with brass cap mkd.

$\frac{1}{4}$
S30 | S29
1920

from which the original bearing trees

A dead and down oak, 10 ins. diam., bears
S 80 $\frac{1}{2}$ ° E, 63 lks. dist., mkd. $\frac{1}{4}$ S29 BT (Record:
S 81° E, 65 lks. dist.).

A juniper, 11 ins. diam., bears S 35 $\frac{1}{2}$ ° W, 14.5
lks. dist., mkd. $\frac{1}{4}$ S30 BT (Record: S 33° W, 15
lks. dist.).

from which a new bearing tree

A juniper, 6 ins. diam., bears N 68 $\frac{1}{4}$ ° E, 56
lks. dist., mkd. $\frac{1}{4}$ S29 BT.

Add the marks 1986 to the brass cap.

N 0°01' E, bet. secs. 29 and 30.

Over rolling land, through dense pinyon, juniper, oak,
and scattered ponderosa pine.

9.99 The S-N 1/64 sec. cor. of secs. 29 and 30, identical
with cor. 4, lot 7, sec. 30, monumented with U.S.
Department of Agriculture aluminum post, 2 $\frac{1}{2}$ ins. diam.,
projecting 6 ins. above the ground and is accepted as a
careful and faithful determination of the position of
the corner, with aluminum cap attached and mkd.

T11N R21E
S-N 1/64
S30 | S29
RLS 11758 1985

from which bearing trees, mkd. by Ronald E. Stoll,
R.L.S. No. 11758, in 1985

A juniper, 9 ins. diam., bears S 80° E, 36
lks. dist., mkd. X BT at base.

A juniper, 16 ins. diam., bears S 29° E, 52.5
lks. dist., mkd. X BT at base.

A fence cor., bears N 8° W, 145.5 lks. dist., fences
extend N and S 30° E, 54.5 lks. dist., thence E.

Dependent Resurvey of a Portion of Subdivisional Lines,
T 11 N, R 21 E, Gila and Salt River Mer., Arizona

CHAINS												
	<p>N 0°01' E, beginning new measurement.</p>											
9.99	<p>The N 1/16 sec. cor. of secs. 29 and 30, monumented with a rebar, ½ in. diam., projecting 2 ins. above the ground, with tag attached and mkd. 11758 and is accepted as a careful and faithful determination of the position of the corner. Cor. falls in a garage under construction where it is impractical to monument.</p>											
	<p>N 0°01' E, beginning new measurement.</p>											
0.42	<p>Point for cor. 1, lot 7, sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T11N</td><td>R21E</td></tr> <tr><td>S30</td><td> S29</td></tr> <tr><td>COR 1</td><td> </td></tr> <tr><td>LOT 7</td><td> </td></tr> <tr><td></td><td>1986</td></tr> </table> </div> <p>from which</p> <p>The NW cor. of a garage under construction, bears S 21°25' W, 41.8 lks. dist., garage is 22 x 58 ft., long side, bears N and S.</p> <p>A pinyon, 6 ins. diam., bears N 77½° W, 31.5 lks. dist., mkd. COR 1 LOT 7 S30 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>	T11N	R21E	S30	S29	COR 1		LOT 7			1986	
T11N	R21E											
S30	S29											
COR 1												
LOT 7												
	1986											
19.98	<p>The cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2 ins. diam., projecting 12 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T11N</td><td>R21E</td></tr> <tr><td>S19</td><td> S20</td></tr> <tr><td>S30</td><td> S29</td></tr> <tr><td></td><td>1920</td></tr> </table> </div> <p>from which the original bearing trees</p> <p>An alligator juniper stump, 30 ins. diam., bears N 15° E, 85 lks. dist., marks visible BT.</p> <p>An alligator juniper stump, 30 ins. diam., bears S 57° W, 78 lks. dist., mkd. T11N R21E S30 BT.</p> <p>An alligator juniper, 9 ins. diam., bears N 83° W, 110 lks. dist., mkd. T11N R21E S19 BT.</p> <p>from which new bearing trees</p> <p>A juniper, 6 ins. diam., bears N 38° E, 28 lks. dist., mkd. T11N R21E S20 BT.</p> <p>A juniper, 6 ins. diam., bears S 63¼° W, 110 lks. dist., mkd. T11N R21E S30 BT.</p>	T11N	R21E	S19	S20	S30	S29		1920			
T11N	R21E											
S19	S20											
S30	S29											
	1920											

Dependent Resurvey of a Portion of Subdivisional Lines,
T 11 N, R 21 E, Gila and Salt River Mer., Arizona

CHAINS

Cor. is located 2 lks. E of a fence cor., fences extend N 45° E and W and 79 lks. N of a graded dirt road, bears NE and SW.

Add the marks 1986 to the brass cap.

Subdivision of Section 28, T 11 N, R 21 E,
Gila and Salt River Mer., Arizona

From the ¼ sec. cor. of secs. 28 and 33.

N 0°03' W, on the N and S center line of sec. 28.

Over rolling open land.

5.00 Enter timber, juniper, and pinyon, edge, bears E and W.

14.99 The center N-S-S 1/256 sec. cor. of sec. 28, monumented with a U.S. Department of Agriculture aluminum post, 2½ ins. diam., projecting 4 ins. above ground in a mound of stone, 2 ft. base, to top, and is accepted as a careful and faithful determination of the position of the corner, with aluminum cap attached and mkd.

T11N R21E
C-N-S-S 1/256
S28
RLS 11758 1981

from which a bearing tree mkd. by Ronald E. Stoll, R.L.S. No. 11758, in 1981

A juniper, 15 ins. diam., bears N ¾° W, 87.5 lks. dist., mkd. X BT at base.

N 0°03' W, beginning new measurement.

4.995 The center S 1/16 sec. cor. of sec. 28, monumented with a U.S. Department of Agriculture aluminum post, 2½ ins. diam., projecting 6 ins. above the ground in a mound of stone, 2 ft. base, to top and is accepted as a careful and faithful determination of the position of the corner, with aluminum cap attached and mkd.

T11N R21E
C-S 1/16
S28
11758 1981

from which bearing trees mkd. by Ronald E. Stoll, R.L.S. No. 11758; in 1981

A juniper, 15 ins. diam., bears South, 191 lks. dist., mkd. X BT at base.

A juniper, 16 ins. diam., bears S 79½° W, 143 lks. dist., mkd. X BT at base.

N 0°03' W, beginning new measurement.

19.985 Point for the center ¼ sec. cor., at intersection with the E and W center line of sec. 28.

Subdivision of Section 28, T 11 N, R 21 E,
Gila and Salt River Mer., Arizona

CHAINS

Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with aluminum cap mkd.

T11N R21E
C $\frac{1}{4}$ S28
1986

from which

A juniper, 7 ins. diam., bears N 73 $\frac{3}{4}$ ° E, 20.5 lks. dist., mkd. C $\frac{1}{4}$ S28 BT.

A juniper, 6 ins. diam., bears S 6 $\frac{3}{4}$ ° E, 27 lks. dist., mkd. X BT at base.

Set a steel fence post alongside the cor.

59.945

The $\frac{1}{4}$ sec. cor. of secs. 21 and 28, monumented with an iron post, 1 in. diam., projecting 14 ins. above the ground, with brass cap mkd.

$\frac{1}{4}$ S21
S28
1920

from which the original bearing trees

A juniper stump, 18 ins. diam., bears North, 7.5 lks. dist., no marks visible (Record: 10 lks. dist.).

A pinyon, 10 ins. diam., bears S 1° W, 37 lks. dist., healed blaze.

from which a new bearing tree

A juniper, 22 ins. diam., bears N 47 $\frac{1}{4}$ ° W, 145 lks. dist., mkd. $\frac{1}{4}$ S21 BT.

Cor. is located 3 lks. S of a fence cor., fences extend N and W.

Add the marks 1986 to the brass cap.

From the $\frac{1}{4}$ sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., projecting 8 ins. above the ground, with brass cap mkd.

$\frac{1}{4}$
S28 | S27
1920

from which the original bearing trees

A juniper, 15 ins. diam., bears N 38 $\frac{1}{2}$ ° E, 92 lks. dist., mkd. $\frac{1}{4}$ S27 BT (Record: N 39° E, 95 lks. dist.).

A juniper, 22 ins. diam., bears N 39° W, 46 lks. dist., illegible scribe marks visible through partly healed blaze.

A steel fence post is alongside the cor.

Subdivision of Section 28, T 11 N, R 21 E,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>S 89°41' W, on the E and W center line of sec. 28. Over nearly level land, through juniper and pinyon timber.</p>
10.015	<p>A 5/8 in. rebar, projecting 3 ins. above ground, with a yellow plastic cap attached and mkd. NAVAJO COUNTY.</p>
10.03	<p>Point for the center E-E 1/64 sec. cor. of sec. 28, identical with cor. 1, lot 1, sec. 28. Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">C $\frac{E-E\ 1/64}{S28}$ C 1986</p>
	<p>from which A juniper, 5 ins. diam., bears S 34 3/4° E, 75 lks. dist., mkd. C-E-E 1/64 S28 BT. Cor. is located in cyclone fence, bears N and S.</p>
18.565	<p>Point for cor. 2, lot 1, sec. 28, monumented with a 5/8 in. rebar, projecting 3 ins. above ground, with a yellow plastic cap attached and mkd. NAVAJO COUNTY. At the cor. point Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T11N R21E S28 $\left\{ \begin{array}{l} \text{COR 2} \\ \text{LOT 1} \end{array} \right.$ 1986</p>
	<p>from which A juniper, 12 ins. diam., bears S 40 1/4° W, 122 lks. dist., mkd. COR 2 LOT 1 S28 BT. Reset the 18 in. long county survey cor. alongside the aluminum post under the ground. Cor. is located 35 lks. E of center of a Lone Pine Dam road, 40 lks. wide, bears N 5° W and S 8° E, curving southeasterly and in a cyclone fence, bears N and S 11°23'30" E.</p>
20.06	<p>The center E 1/16 sec. cor. of sec. 28, monumented with a U.S. Department of Agriculture aluminum post, 2 1/2 ins. diam., projecting 15 ins. above the ground, in a mound of stone, 2 1/2 ft. base, to top, and is accepted as a careful and faithful determination of the position of the cor., with aluminum cap attached and mkd.</p> <p style="text-align: center;">T11N R21E C-E 1/16 S28 1981</p>

Subdivision of Section 28, T 11 N, R 21 E,
Gila and Salt River Mer., Arizona

CHAINS		
	<p>from which the bearing trees mkd. by Ronald E. Stoll, R.L.S. No. 11758, in 1981</p> <p>A juniper, 5 ins. diam., bears N 74½° W, 24 lks. dist., mkd. X BT at base.</p> <p>A juniper, 8 ins. diam., bears N 4¼° W, 89.5 lks. dist., mkd. X BT at base.</p> <hr/> <p>S 89°41' W, beginning new measurement.</p>	
20.06	<p>The center ¼ sec. cor. of sec. 28.</p>	
60.20	<p>The ¼ sec. cor. of secs. 28 and 29, monumented with an iron post, 1 in. diam., projecting 18 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>¼</p> <p>S S</p> <p>29 28</p> <p>1920</p> </div> <p>from which the original bearing trees</p> <p>A juniper, 10 ins. diam., bears N 71¼° E, 54 lks. dist., marks visible ¼ S28 (Record: S 82° E).</p> <p>The remains of a pinyon, 8 ins. diam., bears S 72° W, 41 lks. dist., mkd. ¼ S29 BT (Record: N 88° W, 42 lks. dist.).</p> <p>from which new bearing trees</p> <p>A juniper, 6 ins. diam., bears N 82½° E, 47 lks. dist., mkd. ¼ S28 BT.</p> <p>A juniper, 5 ins. diam., bears N 66° W, 40 lks. dist., mkd. X BT at base.</p> <p>Add the marks 1986 to the brass cap.</p> <hr/> <p style="text-align: center;">Metes-and-Bounds Survey of Lot 1, Sec. 28, T 11 N, R 21 E, Gila and Salt River Mer., Arizona</p> <hr/> <p>From cor. 1, lot 1, identical with the center E-E 1/64 sec. cor. of sec. 28, hereinbefore described.</p> <p>S 89°41' W, on line 1-2, lot 1, identical with a portion of the E and W center line of sec. 28.</p>	
8.535	<p>Cor. 2, lot 1, sec. 28, hereinbefore described.</p> <hr/> <p>Thence along a 11°05'59" circular curve to the left, having a radius 7.821 chs., the chord of said arc bears S 11°23'30" E, 2.081 chs. dist.</p> <p>Along the east right-of-way of Lone Pine Dam road.</p>	


Metes-and-Bounds Survey of Lot 1, Sec. 28,
T 11 N, R 21 E, Gila and Salt River Mer., Arizona

CHAINS

2.087 Point for cor. 3, lot 1, sec. 28, monumented with a 5/8 in. rebar, projecting 3 ins. above the ground, with a yellow plastic cap attached and mkd. NAVAJO COUNTY.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with aluminum cap mkd.



from which

A juniper, 25 ins. diam., bears S 83 $\frac{3}{4}$ ° W, 140.5 lks. dist., mkd. COR 3 LOT 1 S28 BT.

Reset the 18 in. long county survey cor. alongside the aluminum post and below the ground.

Set a steel fence post alongside the cor.


Cor. is located at the cor. of a cyclone fence, fence extends E and N 11°23'30" W and 45 lks. E of center of Lone Pine Dam road, 40 lks. wide, bears N 5° W and S 20° E curving southeasterly.

N 89°45' E, on line 3-4, lot 1, sec. 28.

8.125 Point for cor. 4, lot 1, sec. 28, monumented with a 5/8 in. rebar, projecting 3 ins. above the ground, with a yellow cap attached and mkd. NAVAJO COUNTY.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with aluminum cap mkd.



1986

from which

A juniper, 10 ins. diam., bears S 4° W, 73 lks. dist., mkd. COR 4 LOT 1 S28 BT.

Reset the 18 in. long county survey cor. alongside the aluminum post and below the ground.

Set a steel fence post alongside the cor.

Cor. is located at the cor. of a cyclone fence, fence extends N and W.

N 0°05' W, on line 4-1, lot 1, sec. 28.

Metes-and-Bounds Survey of Lot 1, Sec. 28,
T 11 N, R 21 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>2.055 Cor. 1, lot 1, sec. 28 and point of beginning.</p> <hr/> <p style="text-align: center;">Metes-and-Bounds Survey of Lot 7, Sec. 30 T 11 N, R 21 E, Gila and Salt River Mer., Arizona</p> <hr/> <p>From cor. 1, lot 7, sec. 30, hereinbefore described. N 89°59' W, on line 1-2, lot 7, sec. 30.</p> <p>0.60 Point for cor. 2, lot 7, sec. 30</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R21E S30 COR 2 LOT 7 1986</p> </div> <p>from which</p> <p style="padding-left: 40px;">The NW cor. of a garage under construction, bears S 49°05' E, 59 lks. dist., garage is 22 x 58 ft., long side bears N and S.</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears S 75¾° W, 42 lks. dist., mkd. COR 2 LOT 7 S30 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in a N and S fence.</p> <hr style="width: 20%; margin: auto;"/> <p>S 0°01' W, on line 2-3, lot 7, sec. 30.</p> <p>10.41 Point for cor. 3, lot 7, sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R21E COR 3 LOT 7 S30 1986</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pinyon, 10 ins. diam., bears S 9° W, 28 lks. dist., mkd. COR 3 LOT 7 S30 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>S 89°59' E, on line 3-4, lot 7, sec. 30.</p>	
---------------	---	--

Metes-and-Bounds Survey of Lot 7, Sec. 30,
T 11 N, R 21 E, Gila and Salt River Mer., Arizona

CHAINS	
0.60	Cor. 4, of lot 7, identical with the S-N 1/64 sec. cor. of secs. 29 and 30, hereinbefore described.
	<hr/> <p>N 0°01' E, on line 4-1, lot 7, identical with a portion of the line bet. secs. 29 and 30.</p>
9.99	The N 1/16 sec. cor. of secs. 29 and 30.
10.41	Cor. 1, lot 7, sec. 30 and point of beginning.
	<hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p>
	<p>The land encompassed in this survey is located about 10 miles northwest of Show Low, Arizona. The elevation is about 6,200 ft. above sea level.</p>
	<p>The land is gently rolling, covered with medium to dense juniper, pinyon, and oak.</p>
	<p>Access is by way of Lone Pine Dam road, which is a graded, gravel road.</p>

CERTIFICATE OF SURVEY

I, Paul L. Reeves, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 18th day of September 1985, and the supplemental special instructions bearing date of the 3rd day of October 1986, I have dependently resurveyed a portion of the subdivisional lines and surveyed subdivisions in Sec. 28, surveyed Lot 1, Sec. 28, and surveyed Lot 7, Sec. 30, Township 11 North, Range 21 East, of the Gila and Salt River Meridian, in the State of Arizona which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

MAR 23 1987

(Date)

Paul L. Reeves
 (Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

Bureau of Land Management

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and the survey of subdivisions in Sec. 28, a survey of Lot 1, Sec. 28, and a survey of Lot 7, Sec. 30, T 11 N, R 21 E, Gila and Salt River Meridian, Arizona, executed by Paul L. Reeves, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

APR 01 1987

(Date)

Arnold E. Knight
 (Chief Cadastral Surveyor for Arizona)
acting