

INDEX DIAGRAM

TOWNSHIP 16 NORTH , RANGE 9 EAST ,

6	5	4	3	2	1
7	8	9	10	11	12
18 14	17 13	16	15	14	13
3 19 10	10 20 7	6 21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 19.....pp. 15-18.
 Subdivision of Section 20.....pp. 18-25.

T 16 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS

The following field notes are those of the dependent resurvey of a portion of the west boundary and a portion of the subdivisional lines, and the survey of the subdivision of sections 19 and 20, Township 16 North, Range 9 East, Gila and Salt River Meridian, Arizona.

The boundaries of sections 19 and 20 were surveyed in 1881 by Theodore F. White. Certain corners were remonumented in 1966 by Wallace R. Ott.

In 1973, R. James Smets, Registered Land Surveyor, No. 6975, Arizona, performed a section breakdown in sections 19 and 20 of this township for Mr. James Benedict, under job No. 721016, a copy of which is in the file for this group. During the course of this survey, original evidence was found at the $\frac{1}{4}$ section corners on the N, S, and W boundaries of section 19 and on the E boundary of section 20. This original evidence was not used by Mr. Smets in 1973 which resulted in erroneously positioned monuments that could not be used for this survey.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated September 20, 1984, for Group No. 658, Arizona.

The direction of the lines of this survey was determined by direct solar observations and refer to the true meridian. Angles and distances were measured using a Zeiss Elta 46S Total Station Instrument.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of section 20, as determined from a tie made to U.S. Coast and Geodetic Survey triangulation station "APACHE MAID, 1959", is as follows:

Latitude: $34^{\circ}45'08.94''$ N Longitude: $111^{\circ}24'40.77''$ W

The mean magnetic declination, taken from HUTCH MTN., ARIZ. quadrangle map, published in 1965 by the U.S. Geological Survey, is 14° E.

Dependent Resurvey of a Portion of the W Bdy. of
T 16 N, R 9 E, Gila and Salt River Mer., Arizona

Restoring the survey executed by
Theodore F. White in 1881.

Beginning at the cor. of secs. 19, 24, 25 and 30,
Tps. 16 N, Rs. 8 and 9 E, determined at record dist.
from the remains of the original bearing trees

Dependent Resurvey of a Portion of the W Bdy. of
T 16 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS

A pine stump, 30 ins. diam., bears N 64° E,
1.16 chs. dist., no visible marks.

A pine stump, 26 ins. diam., bears S 28½° E,
1.28 chs. dist., no visible marks.

A pine stump, 28 ins. diam., bears S 7° W,
53 lks. dist., mkd. TXVIN RVIIIIE XXV.

A pine stump, 24 ins. diam., bears N 74° W,
19 lks. dist., mkd. TXVIN RVIIIIE XXIV.

At the cor. point

Set a stainless steel post, 28 ins. long, 2½ ins.
diam., 26 ins. in the ground, with brass cap mkd.

T16N	
R8E	R9E
S24	S19
S25	S30
1984	

from which new bearing trees

A pine, 12 ins. diam., bears N 27° E, 24
lks. dist., mkd. T16N R9E S19 BT.

A pine, 12 ins. diam., bears S 44½° E,
66 lks. dist., mkd. T16N R9E S30 BT.

A pine, 8 ins. diam., bears S 33¾° W,
89 lks. dist., mkd. T16N R8E S25 BT.

A pine, 8 ins. diam., bears N 49¾° W,
62 lks. dist., mkd. T16N R8E S24 BT.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored
plastic case beneath the stainless steel post.

A steel fence post is located alongside the cor.

From this point, U.S. Coast and Geodetic Survey
triangulation station APACHE MAID, bears
S 72°54.1' W (forward bearing), 496.32 chs. dist.,
monumented with standard brass disk, mkd. APACHE MAID
1959.

N 0°04' W, bet. secs. 19 and 24.

Over hilly terrain, through dense forest of ponderosa
pine.

39.89

The ¼ sec. cor. of secs. 19 and 24, monumented with a
mound of stone, 3 ft. base, 1 ft. high, from which the
remains of an original bearing tree

A pine stump, 28 ins. diam., bears N 7° E,
35 lks. dist., alongside which is lying the
remainder of the tree, mkd. ¼ S on open blaze.

At the cor. point

Dependent Resurvey of a Portion of the W Bdy. of
T 16 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS

Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base to top, with cap mkd.

T16N
 $\frac{1}{4}$
 R8E | R9E
 S24 | S19
 1984

from which new bearing trees

A ponderosa pine, 7 ins. diam., bears N 63° E, 44 lks. dist., mkd. $\frac{1}{4}$ S19 BT.

A ponderosa pine, 12 ins. diam., bears N 71 $\frac{1}{2}$ ° W, 10 lks. dist., mkd. $\frac{1}{4}$ S24 BT.

Set a steel fence post alongside the cor.

N 0°08' W, beginning new measurement.

Over hilly terrain, through dense forest of ponderosa pine.

39.86

The cor. of secs. 13, 18, 19 and 24, determined at record dist. from the remains of the original bearing trees.

A ponderosa pine, 25 ins. diam., bears N 76 $\frac{1}{2}$ ° E, 34 lks. dist., mkd. with a blaze, but no visible scribe marks. (Record: N 72 $\frac{1}{2}$ ° E)

A ponderosa pine stump, 24 ins. diam., bears S 11 $\frac{3}{4}$ ° E, 38 lks. dist., mkd. IX E. (Record: S 10° E)

A ponderosa pine stump, 24 ins. diam., bears N 65° W, 1.04 chs. dist., with no visible marks. (Record: N 64° W)

At the cor. point

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T16N
 R8E | R9E
 S13 | S18
 S24 | S19
 1984

from which new bearing trees

A ponderosa pine, 8 ins. diam., bears N 45 $\frac{3}{4}$ ° E, 49 lks. dist., mkd. T16N R9E S18 BT.

A ponderosa pine, 10 ins. diam., bears S 74 $\frac{1}{2}$ ° E, 58 lks. dist., mkd. T16N R9E S19 BT.

A ponderosa pine, 12 ins. diam., bears S 42 $\frac{1}{2}$ ° W, 64 lks. dist., mkd. T16N R8E S24 BT.

A ponderosa pine, 13 ins. diam., bears N 62° W, 41 lks. dist., T16N R8E S13 BT.

Dependent Resurvey of a Portion of the W Bdy. of
T 16 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Set a steel fence post alongside the cor.

Dependent Resurvey of a Portion of the
Subdivisional Lines, T 16 N, R 9 E,
Gila and Salt River Mer., Arizona

Restoring the survey executed by
Theodore F. White in 1881.

From the cor. of secs. 20, 21, 28 and 29, T 16 N,
R 9 E, monumented with an iron post, 2 1/2 ins. diam.,
projecting 4 ins. above a mound of stone, 4 ft. base,
18 ins. high, with brass cap mkd.

T16N R9E	
S20 S21	
S29 S28	
1966	

from which the remains of original bearing trees

A burned stump, 12 ins. diam., bears N 68° E,
60 lks. dist., no marks visible.

A stump, 36 ins. diam., bears S 50 1/2° E, 1.41 chs.
dist., mkd. TXVIN RIXE. (Record: 1.39 chs.)

and a bearing tree mkd. in 1966

A ponderosa pine, 15 ins. diam., bears S 42° W,
1.09 chs. dist., with scribe marks S29 BT
visible on nearly healed blaze. (Record:
S 43 1/2° W, 26 lks.)

and a tree not of record

A ponderosa pine, 20 ins. diam., bears N 20° W,
9 lks. dist., with healed over blaze.

and new bearing trees

A ponderosa pine, 13 ins. diam., bears N 89 3/4° E,
16 lks. dist., mkd. T16N R9E S21 BT.

A ponderosa pine, 9 ins. diam., bears N 18 1/4° W,
20 lks. dist., mkd. T16N R9E S20 BT.

Add the date 1984 to the brass cap.

N 0°22.5' W, bet. secs. 20 and 21.

Over relatively level terrain, through dense forest of
ponderosa pine.

39.90

The 1/4 sec. cor. of secs. 20 and 21, monumented with a
wood post, 3 ins. diam., 3 ft. long, in a mound of
stone, 3 ft. base, 18 ins. high, no mkd. stone.

At the cor. point

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 16 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T16N R9E

½
S20 | S21
1984

from which

A ponderosa pine, 13 ins. diam., bears S 79½° E,
57 lks. dist., mkd. ¼ S21 BT.

A ponderosa pine, 11 ins. diam., bears S 85½° W,
19 lks. dist., mkd. ¼ S20 BT.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Deposit the wood post alongside the cor.

Set a steel fence post alongside the cor.

N 0°33.5' E, beginning new measurement.

Over hilly terrain, through dense forest of ponderosa pine.

1.04 Barbed wire fence, 3 strand, extends E and W.

40.03 The cor. of secs. 16, 17, 20 and 21, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above a mound of stone, 4 ft. base, 18 ins. high, with brass cap mkd.

T16N R9E

S17 | S16
S20 | S21
1966

from which the remains of original bearing trees

A burned stump, 14 ins. diam., bears N 42° E,
22 lks. dist., mkd. TXVI.

A pine stump, 26 ins. diam., bears N 55° W,
37 lks. dist., with healed blaze.

and a bearing tree mkd. in 1966

A ponderosa pine, 9 ins. diam., bears S 16° W,
35 lks. dist., with illegible scribe marks.

and new bearing trees

A ponderosa pine, 8 ins. diam., bears N 87° E,
56 lks. dist., mkd. T16N R9E S16 BT.

A ponderosa pine, 10 ins. diam., bears S 33° E,
52½ lks. dist., mkd. T16N R9E S21 BT.

Add the date 1984 to brass cap.

From the cor. of secs. 20, 21, 28 and 29.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 16 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS		
	S 89°36' W, bet. secs. 20 and 29.	
	Over rolling terrain, through ponderosa pine and scattered oak.	
39.42	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29 at proportionate dist.; there is no remaining evidence of the original cor.	
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	T16N R9E $\frac{1}{4}$ $\frac{S20}{S29}$ 1984	
	from which	
	A ponderosa pine, 14 ins. diam., bears S 48 $\frac{1}{4}$ ° E, 28 lks. dist., mkd. $\frac{1}{4}$ S29 BT.	
	A power pole, bears S 64 $\frac{3}{4}$ ° W, 32 lks. dist., mkd. with an aluminum tag mkd. 15 on the S side.	
	Deposit a magnet in a 1 x 1 x 2 $\frac{5}{8}$ in. white colored plastic case beneath the stainless steel post.	
49.27	The E-W $\frac{1}{64}$ sec. cor. of secs. 20 and 29, monumented with a rebar, $\frac{5}{8}$ in. diam., projecting 2 ins. above a concrete block, 5 ins. square, 5 ins. high, and is accepted as a careful and faithful determination of the cor. position.	
	At the cor. point	
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	S20 E-W $\frac{1}{64}$ S29 1984	
	from which	
	A ponderosa pine stump, 18 ins. diam., 6 ft. high, bears S 16 $\frac{1}{4}$ ° E, 1.70 chs. dist., mkd. WM 6.	
	A ponderosa pine, 19 ins. diam., bears S 45 $\frac{1}{4}$ ° E, 74 lks. dist., mkd. E-W $\frac{1}{64}$ S29 BT.	
	Reset the rebar alongside the stainless steel post.	
	From this point, the SE cor. of a log house, 24 x 36 ft., bears N 7 $\frac{3}{4}$ ° W, 3.31 chs. dist.	

	S 89°33' W, beginning new measurement.	
9.84	The W $\frac{1}{16}$ sec. cor. of secs. 20 and 29, monumented with a rebar, $\frac{5}{8}$ in. diam., projecting 2 ins. above a concrete block, 5 ins. square, 5 ins. high, and is accepted as a careful and faithful determination of the cor. position.	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 16 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS

At the cor. point

Set a stainless steel post, 28 ins. long, 2½ ins. diam.,
24 ins. in the ground, with brass cap mkd.

T16N R9E
W 1/16 $\frac{S20}{S29}$
1984

from which

A ponderosa pine, 19 ins. diam., bears S 14¼° E,
39 lks. dist., mkd. W 1/16 S29 BT.

A ponderosa pine, 7 ins. diam., bears N 64° W,
50 lks. dist., mkd. W 1/16 S20 BT.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored
plastic case beneath the stainless steel post.

Reset the rebar alongside the stainless steel post.

S 89°31' W, beginning new measurement.

1.05 Lower Lake Mary Highway, 50 lks. wide, bears S 4° E and
N 7° W.

19.69 The cor. of secs. 19, 20, 29 and 30, monumented with an
iron post, 2½ ins. diam., projecting 4 ins. above a
mound of stone, 3 ft. base, 18 ins. high, with brass cap
mkd.

T16N R9E
S19 | S20
S30 | S29
1966

from which the remaining original bearing trees

A pine, 30 ins. diam., bears N 48° E, 75 lks.
dist., mkd. TXVI RIXE XX.

An oak, 14 ins. diam., bears S 79° E, 32 lks.
dist., with visible blaze but no
scribe marks.

and bearing trees mkd. in 1966

A pine, 13 ins. diam., bears N 59¾° E, 31 lks.
dist., mkd. T16N R9E S20 BT. (Record:
N 61¾° E, 32 lks.)

A ponderosa pine, 14 ins. diam., bears N 58° W,
29 lks. dist., mkd. T16N R9E S19 BT. (Record:
N 55° W, 28 lks.)

and new bearing trees

A ponderosa pine, 13 ins. diam., bears S 44¼° E,
41 lks. dist., mkd. T16N R9E S29 BT.

A ponderosa pine, 11 ins. diam., bears S 68½° W,
33 lks. dist., mkd. T16N R9E S30 BT.

Add the date 1984 to the brass cap.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 16 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>S 88°55' W, bet. secs. 19 and 30.</p> <p>Over hilly terrain, through forest of pine.</p> <p>39.86 The ¼ sec. cor. of secs. 19 and 30, monumented with a pine post, 3 ins. diam., 2 ft. long, firmly set in a mound of stone, 2½ ft. base, 1 ft. high, no visible marks on post, from which</p> <p style="padding-left: 40px;">A pine stump, 26 ins. diam., bears N 34° E, 38 lks. dist., alongside which is lying the remainder of the tree with blaze mkd. ¼ S. (Record: 36 lks.).</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 2½ ft. base to top, with cap mkd.</p> <div style="text-align: center;"> <p>T16N R9E ¼ S19 S30 1984</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N 54° W, 96 lks. dist., mkd. ¼ S19 BT.</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears S 51° W, 92 lks. dist., mkd. ¼ S30 BT.</p> <p>Deposit the post alongside, in the mound of stone.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>N 88°19' W, beginning new measurement.</p> <p>Over hilly terrain, through forest of pine.</p>	
<p>40.05</p> <p>14.85</p>	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N 0°03' E, bet. secs. 19 and 20.</p> <p>Over hilly terrain, through forest of ponderosa pine.</p> <p>The N-S-S 1/256 sec. cor. of secs. 19 and 20, monumented with a rebar, 5/8" diam., projecting 1 in. above ground, and is accepted as a careful and faithful determination of the cor. position.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 27 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>N-S-S 1/256 S19 S20 1984</p> </div>	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 16 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS

from which

A ponderosa pine, 14 ins. diam., bears N $64\frac{1}{2}^{\circ}$ E,
17 lks. dist., mkd. NSS 1/256 S20 BT.

A ponderosa pine, 16 ins. diam., bears S 85° W,
45 lks. dist., mkd. NSS 1/256 S19 BT.

Reset the rebar alongside the aluminum post.

N $0^{\circ}03'$ E, beginning new measurement.

4.95 Point for the S 1/16 sec. cor. of secs. 19 and 20.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ in. diam.,
26 ins. in the ground, with brass cap mkd.

S 1/16
S19 | S20
1984

from which

A power pole, bears N $75\frac{1}{2}^{\circ}$ E, 2.30 chs. dist.

A ponderosa pine, 22 ins. diam., bears S $27\frac{1}{2}^{\circ}$ W,
2.46 chs. dist., mkd. S 1/16 S19 BT.

Set a steel fence post alongside the cor.

16.95 Center of Lake Mary Road, asphalt surface, 50 lks.
wide, bears S 42° E and N 42° W.

18.21 From this point on line, a highway right-of-way marker,
bears west, 0.015 chs. dist., monumented with a
concrete post, 6 x 6 ins., projecting 4 ins. above the
ground, no marks. This monument fits the position as
shown on Federal Highway Construction plat ARIZ. F.H.
3-2(1) and 3(2), Sheet 13, dated August 15, 1966, a
copy of which is on file at the U.S. Department of
Transportation, Federal Highway Administration, Central
Direct Federal Division, 555 Zang St., P.O. Box 25246,
Denver, Colorado 80225.

24.75 The $\frac{1}{4}$ sec. cor. of secs. 19 and 20, monumented with a
stone, 6 x 6 x 6 ins. above a collar of stone, firmly
set, mkd. $\frac{1}{4}$ on S face, and an X on top, from which an
original bearing tree

A dead standing ponderosa pine, 36 ins. diam.,
bears S $47\frac{3}{4}^{\circ}$ W, 39 lks. dist., mkd. $\frac{1}{4}$ S
(Record: S 17° W, 66 lks. dist.).

At the cor. point

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam.,
24 ins. in the ground, with brass cap mkd.

T16N R9E
 $\frac{1}{4}$
S19 | S20
1984

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 16 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which new bearing trees</p> <p>A ponderosa pine, 16 ins. diam., bears S 6¼° E, 1.80 chs. dist., mkd. ¼ S20 BT.</p> <p>A ponderosa pine, 16 ins. diam., bears N 86½° W, 1.29 chs. dist., mkd. ¼ S19 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>From this point, a 1936 Bureau of Public Roads, Station and Elevation marker, bears S 27°04' W, 4.60 chs. dist., monumented with an iron post, 2½ ins. diam., projecting 3 ins. above ground, with a brass cap attached and mkd. 880+97.96 Elevation 7568.39 Feet 1936.</p> <hr/> <p>N 1°41' W, beginning new measurement.</p> <p>Over hilly terrain, through forest of ponderosa pine.</p>
15.275	<p>The N-S-N 1/256 sec. cor. of secs. 20 and 29, monumented with a rebar, 5/8 in. diam., projecting 2½ ins. above a concrete block, 5 ins. square, 5 ins. high, and is accepted as a careful and faithful determination of the cor. position.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">N-S-N 1/256 S19 S20 1984</p>
5.09	<p>from which</p> <p>A ponderosa pine, 22 ins. diam., bears S 77½° E, 1.48 chs. dist., mkd. NSN 1/256 S20 BT.</p> <p>A ponderosa pine, 23 ins. diam., bears N 88¾° W, 1.47 chs. dist., mkd. NSN 1/256 S19 BT.</p> <p>Reset the rebar alongside the cor.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>N 1°41' W, beginning new measurement.</p> <p>The N 1/16 sec. cor. of secs. 19 and 20, monumented with a rebar, 5/8 in. diam., projecting 2½ ins. above a concrete block, 5 ins. square, 5 ins. high, and is accepted as a careful and faithful determination of the cor. position.</p> <p>At the cor. point</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 16 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS

Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with cap mkd.

T16N R9E
N 1/16
S19 | S20
1984

from which

A ponderosa pine, 9 ins. diam., bears East, 7 lks. dist., mkd. N 1/16 S20 BT.

A ponderosa pine, 13 ins. diam., bears N 87¾° W, 8 lks. dist., mkd. N 1/16 S19 BT.

Reset the rebar in cement block alongside the cor.

Set a steel fence post alongside the cor.

N 1°41' W, beginning new measurement.

20.37

The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2½ ins. diam., projecting 3 ins. above a mound of stone, 2 ft. base, to top, with brass cap mkd.

T16N R9E
S18 | S17
S19 | S20
1966

from which the remains of original bearing trees

A burned stump, 24 ins. diam., bears N 56¾° E, 1.67 chs. dist., marks visible VII. (Record: N 56° E, 1.64 chs. dist.)

A ponderosa pine stump, 12 ins. diam., bears S 59½° E, 1.36 chs. dist., mkd. T16N R9E S20 BT. (Record: S 61° E, 1.34 chs. dist.)

and a bearing tree mkd. in 1966

A ponderosa pine, 15 ins. diam., bears S 18½° W, 21 lks. dist., mkd. T16N R9E S19 BT. (Record: S 21° W)

and new bearing trees

A ponderosa pine, 12 ins. diam., bears N 29½° E, 37 lks. dist., mkd. T16N R9E S17 BT.

A ponderosa pine, 9 ins. diam., bears N 61¾° W, 33 lks. dist., mkd. T16N R9E S18 BT.

Add the date 1984 to the brass cap.

A steel fence post is alongside the cor.

From the cor. of secs. 16, 17, 20 and 21.

S 89°50' W, bet. secs. 17 and 20.

Over hilly terrain, through dense pine.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 16 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS	
40.03	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20 at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T16N R9E $\frac{1}{4}$ <u>S17</u> S20 1984</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 5 ins. diam., bears N 13° E, 41 lks. dist., mkd. $\frac{1}{4}$ S17 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 5 ins. diam., bears S 47° W, 27 lks. dist., mkd. $\frac{1}{4}$ S20 BT.</p> <p>Deposit a magnet in a 1 x 1 x $2\frac{5}{8}$ in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
60.045	<p>Point for the W $\frac{1}{16}$ sec. cor. of secs. 17 and 20.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">W $\frac{1}{16}$ <u>S17</u> S20 1984</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N $24\frac{1}{4}^\circ$ E, 36 lks. dist., mkd. W $\frac{1}{16}$ S17 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears S 26° E, 38 lks. dist., mkd. W $\frac{1}{16}$ S20 BT.</p> <p>Set a steel fence post alongside the cor.</p>
80.06	<p>The cor. of secs. 17, 18, 19 and 20.</p> <hr/> <p>S $89^\circ 56'$ W, bet. secs. 18 and 19.</p> <p>Over hilly terrain, through forest of pine.</p>
19.91	<p>Point for the E $\frac{1}{16}$ sec. cor. of secs. 18 and 19.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T16N R9E E $\frac{1}{16}$ <u>S18</u> S19 1984</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N 13° E, 16 lks. dist., mkd. E $\frac{1}{16}$ S18 BT.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 16 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>A ponderosa pine, 12 ins. diam., bears S 58° E, 53 lks. dist., mkd. E 1/16 S19 BT.</p> <p>Set a steel fence post alongside the cor.</p>	
20.80	<p>Center of Lake Mary Road, 50 lks. wide, bears N and S.</p>	
39.82	<p>The ¼ sec. cor. of secs. 18 and 19, monumented with a mound of stone, 3 ft. base, 2 ft. high, from which the remains of an original bearing tree</p> <p>A pine stump, bears S 63° W, 50 lks. dist., with remains of blaze alongside stump, mkd. ¼ S.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, and in a mound of stone, 3½ ft. base, to top, with cap mkd.</p> <p style="text-align: center;">T16N R9E ¼ S18 S19 1984</p> <p>from which new bearing trees</p> <p>A ponderosa pine, 10 ins. diam., bears N 10° E, 51 lks. dist., mkd. ¼ S18 BT.</p> <p>A ponderosa pine, 11 ins. diam., bears S 20¼° E, 48 lks. dist., mkd. ¼ S19 BT.</p> <p>Set a steel fence post alongside the cor.</p>	
39.04	<p>S 89°51' W, beginning new measurement.</p> <p>Over hilly terrain, through forest of pine.</p> <p>The cor. of secs. 13, 18, 19 and 24, on the W Bdy. of the Tp., hereinbefore described.</p> <hr/> <p style="text-align: center;">Survey of the Subdivision of Section 19, T 16 N, R 9 E, Gila and Salt River Mer., Arizona</p> <hr/> <p>From the ¼ sec. cor. of secs. 19 and 30.</p> <p>N 0°47' W, on the N and S center line of sec. 19.</p> <p>Over rolling, mountainous land, through dense ponderosa pine.</p>	
40.72	<p>Point for the center ¼ sec. cor. of sec. 19 at the intersection with the E and W center line of sec. 19.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T16N R9E C ¼ S19 1984</p>	

Survey of the Subdivision of Section 19,
T 16 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>from which</p>	
	<p>A ponderosa pine, 7 ins. diam., bears S 56½° E, 27 lks. dist., mkd. C ¼ S19 BT.</p>	
	<p>A ponderosa pine, 8 ins. diam., bears S 10¼° W, 40 lks. dist., mkd. C ¼ S19 BT.</p>	
	<p>Set a steel fence post alongside the cor.</p>	
48.15	<p>Center of dirt road, 25 lks. wide, bears S 86° E and S 86° W.</p>	
60.88	<p>Point for the center N 1/16 sec. cor. of sec. 19.</p>	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 27 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">T16N R9E C N 1/16 S19 C 1984</p>	
	<p>from which</p>	
	<p>A ponderosa pine, 8 ins. diam., bears S 84° W, 77 lks. dist., mkd. CN 1/16 S19 BT.</p>	
	<p>A ponderosa pine, 9 ins. diam., bears N 17° W, 83 lks. dist., mkd. CN 1/16 S19 BT.</p>	
	<p>Set a steel fence post alongside the cor.</p>	
81.04	<p>The ¼ sec. cor. of secs. 18 and 19.</p>	
	<p>From the ¼ sec. cor. of secs. 19 and 20.</p>	
	<p>N 89°29' W, on the E and W center line of sec. 19.</p>	
	<p>Over hilly terrain, through dense ponderosa pine.</p>	
5.057	<p>Point for the center E-E-E 1/256 sec. cor. of sec. 19.</p>	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p>	
	<p style="text-align: center;">C E-E-E 1/256 C S19 1984</p>	
	<p>from which</p>	
	<p>A ponderosa pine, 11 ins. diam., bears S 20° E, 80 lks. dist., mkd. CEEE 1/256 S19 BT.</p>	
	<p>A ponderosa pine, 5 ins. diam., bears S 87½° W, 84 lks. dist., mkd. X BT.</p>	
	<p>Set a steel fence post alongside the cor.</p>	
	<p>Cor. is located 2.20 chs. N of Lake Mary Road, 50 lks. wide, bears S 35° E and N 45° W; 11 lks. W of a fence line that bears S 60° E and N 60° W; and S 20° E, 17 lks. dist. from cor. of fences, extending S 60° E and N 4° W, and N 60° W.</p>	

Survey of the Subdivision of Section 19,
T 16 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>From this point, a rebar, 5/8 in. diam., bears N 87° W, 5 lks. dist.</p>	
7.25	Lake Mary Road, 50 lks. wide, bears S 45° E and N 45° W.	
13.40	Barbed wire fence, 4 strand, extends N 20° E and S 20° W.	
20.23	<p>Point for the center E 1/16 sec. cor. of sec. 19.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>T16N R9E E 1/16 C S19 1984</p> </div> <p>from which</p> <p>A power pole, bears S 24° E, 3.04 chs. dist., lines extend S 20³/₄° E and N 20³/₄° W.</p> <p>A ponderosa pine, 9 ins. diam., bears S 48¹/₂° W, 60 lks. dist., mkd. CE 1/16 S19 BT.</p> <p>A ponderosa pine, 6 ins. diam., bears N 42¹/₂° W, 76 lks. dist., mkd. X BT.</p> <p>A power pole, bears N 16³/₄° W, 2.25 chs. dist., lines extend S 20³/₄° E and N 20³/₄° W.</p> <p>Set a steel fence post alongside the cor.</p>	
40.46	The center 1/4 sec. cor. of sec. 19.	
79.98	The 1/4 sec. cor. of secs. 19 and 24 on the W bdy. of the Township.	
<p>NE¹/₄ of Section 19</p> <hr/>		
20.26	<p>From the center E 1/16 sec. cor. of sec. 19.</p> <p>N 1°14' W, on the N and S center line of the NE 1/4 of sec. 19.</p> <p>Point for the NE 1/16 sec. cor. of sec. 19, at intersection with the E and W center line of the NE¹/₄ of sec. 19.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>T16N R9E NE 1/16 1984</p> </div> <p>from which</p> <p>A ponderosa pine, 8 ins. diam., bears N 59° E, 31 lks. dist., mkd. NE 1/16 S19 BT.</p> <p>A ponderosa pine, 9 ins. diam., bears N 80¹/₂° W, 46 lks. dist., mkd. NE 1/16 S19 BT.</p>	

Survey of the Subdivision of Section 19,
T 16 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS		
	Set a steel fence post near the cor.	
40.52	The E 1/16 sec. cor. of secs. 18 and 19.	
	From the N 1/16 sec. cor. of secs. 19 and 20.	
	N 89°46' W, on the E and W center line of the NE $\frac{1}{4}$ of sec. 19.	
	Over rolling land, through dense ponderosa pine.	
20.07	The NE 1/16 sec. cor. of sec. 19.	
20.81	Fence line, bears N and S.	
22.40	Lake Mary Road, 50 lks. wide, bears N and S.	
40.14	The center N 1/16 sec. cor. of sec. 19.	
	From the center E-E-E 1/256 sec. cor. of sec. 19.	
	N 1°34' W, on the N and S center line of the E $\frac{1}{2}$ of the SE $\frac{1}{4}$ of the NE $\frac{1}{4}$ of sec. 19.	
15.255	Point for the NE-SE-NE 1/256 sec. cor. of sec. 19.	
	Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ in. diam., 26 ins. in the ground, with brass cap mkd.	
	S19	
	NE-SE-NE	
	1/256	
	1984	
	from which	
	A ponderosa pine, 15 ins. diam., bears N 21 $\frac{1}{2}$ ° E, 1.12 chs. dist., mkd. NE SE NE 1/256 S19 BT.	
	From this point, a rebar, 5/8 in. diam., 2 ins. above ground, established by Russel James Smets, RLS 6975, in 1973, bears S 50° W, 6 lks. dist., located at the cor. of fences extending S and E. This point was established for the NE-SE-NE 1/256 sec. cor. of sec. 19 using improper procedures and is rejected and not utilized in the course of this survey.	
	Cor. is located 4 lks. N of fence line, bears E and W.	
	From the N-S-N 1/256 sec. cor. of secs. 19 and 20.	
	N 89°41.7' W on the E $\frac{1}{2}$ of the E and W center line of the NE $\frac{1}{4}$ of the SE $\frac{1}{4}$ of the NE $\frac{1}{4}$ of sec. 19.	
5.027	The NE-SE-NE 1/256 sec. cor. of sec. 19.	
	Survey of the Subdivision of Section 20, T 16 N, R 9 E, Gila and Salt River Mer., Arizona	
	From the $\frac{1}{4}$ sec. cor. of secs. 20 and 29.	

Survey of the Subdivision of Section 20,
T 16 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>N 0°21' W, on the N and S center line of sec. 20. Over hilly terrain, through ponderosa pine.</p>
14.80	<p>Center of dirt road, 25 lks. wide, bears S 54° E and N 52° W.</p>
19.865	<p>Point for the center S 1/16 sec. cor. of sec. 20. Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.</p>
	<p style="text-align: center;">T16N R9E C S 1/16 S20. C 1984</p>
	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N 57½° E, 46 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears S 82½° W, 25 lks. dist., mkd. CS 1/16 S20 BT.</p> <p>Set a steel fence post alongside the cor.</p>
39.73	<p>Point for the center ¼ sec. cor. of sec. 20, at intersection with the E and W center line of sec. 20. Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p>
	<p style="text-align: center;">T16N R9E C ¼ S20 1984</p>
	<p>from which</p> <p style="padding-left: 40px;">An oak, 12 ins. diam., bears N 10¾° W, 14 lks. dist., mkd. C ¼ S20 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears N 5° W, 67 lks. dist., mkd. C ¼ S20 BT.</p> <p>Set a steel fence post alongside the cor.</p>
59.92	<p>Point for the center N 1/16 sec. cor. of sec. 20. Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.</p>
	<p style="text-align: center;">T16N R9E C N 1/16 S20 C 1984</p>
	<p>from which</p> <p style="padding-left: 40px;">An oak, 6 ins. diam., bears S 32° E, 48 lks. dist., mkd. C N 1/16 S20 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N 47½° W, 65 lks. dist., mkd. C N 1/16 S20 BT.</p>

Survey of the Subdivision of Section 20,
T 16 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS	
	Set a steel fence post alongside the cor.
80.11	The $\frac{1}{4}$ sec. cor. of secs. 17 and 20.
	From the $\frac{1}{4}$ sec. cor. of secs. 20 and 21:
	S 89°20' W, on the E and W center line of sec. 20.
	Over rolling land, through dense ponderosa pine and scattered oak, asc. SE slope.
28.50	Top of asc., desc. NW slope.
39.39	The center $\frac{1}{4}$ sec. cor. of sec. 20.
47.40	Center of dirt road, 25 lks. wide, bears N 16° E and S 10° W.
54.049	Point for the center W-E-W 1/256 sec. cor. of sec. 20.
	Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.
	$C \frac{W-E-W \ 1/256}{S20} C$
	1984
	from which
	A ponderosa pine, 10 ins. diam., bears N 30 $\frac{1}{4}$ ° E,
	72 lks. dist., mkd. C W E W 1/256 S20 BT.
	A ponderosa pine, 8 ins. diam., bears S 49 $\frac{3}{4}$ ° E,
	44 lks. dist., mkd. X BT.
	Cor. is located in a fence line, bears N and S.
	From this point, a rebar, 5/8 in. diam., 2 in. above ground, bears North, 6 lks. dist. This point was established by Russel James Smets, RLS 6975, in 1973, for the center W-E-W 1/256 sec. cor. of sec. 20, using improper procedures and is rejected and not utilized in the course of this survey. The rebar is set at a cor. of fences extending S and W.
58.935	Point for the center W 1/16 sec. cor. of sec. 20.
	Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ in. diam., 26 ins. in the ground, with brass cap mkd.
	$C \frac{T16N \ R9E \ W \ 1/16}{S20} C$
	1984
	From this point, two rebars alongside each other, both 5/8 in. diam., 2 ins. above ground, bear N 8° E, 5 lks. dist. The rebars are set at the cor. of fences extending N and E and were established by Russel James Smets, RLS 6975, in 1973, for the center W 1/16 sec. cor. of sec. 20, using improper procedures and are rejected and not utilized in the course of this survey.
	Set a steel fence post alongside the cor.

Survey of the Subdivision of Section 20,
T 16 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS	
78.48	The $\frac{1}{4}$ sec. cor. of secs. 19 and 20.
	<hr/> $SW\frac{1}{4}$ of Section 20 <hr/>
	From the W $\frac{1}{16}$ sec. cor. of secs. 20 and 29.
	N $0^{\circ}09'$ W, on the N and S center line of the $SW\frac{1}{4}$ of sec. 20.
9.915	Point for the center S-SW $\frac{1}{64}$ sec. cor. of sec. 20.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ in. diam., 26 ins. in the ground, with brass cap mkd.
	S20 C-S-SW $\frac{1}{64}$ 1984
	from which
	A power pole, bears N $84\frac{3}{4}^{\circ}$ E, 1.57 chs. dist., mkd. 57671; lines extend S $61\frac{1}{2}^{\circ}$ E and N $61\frac{1}{2}^{\circ}$ W.
	A power pole, bears N $45\frac{1}{2}^{\circ}$ W, 3.15 chs. dist., mkd. 106917; lines extend S $61\frac{1}{2}^{\circ}$ E and N $61\frac{1}{2}^{\circ}$ W.
	Cor. falls 1 lk. S of an E-W fence line.
	From this point, a rebar, $\frac{5}{8}$ in. diam., 2 ins. above ground, bears N 18° W, 2.6 lks. dist., established by Russel James Smets, RLS 6975, in 1973, for the center S-SW $\frac{1}{64}$ sec. cor. of sec. 20, using improper procedures and is rejected and not utilized in the course of this survey.
19.83	Point for the SW $\frac{1}{16}$ sec. cor. of sec. 20, at intersection with the E and W center line of the $SW\frac{1}{4}$ of sec. 20.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ in. diam., 26 ins. in the ground, with brass cap mkd.
	T16N R9E SW $\frac{1}{16}$ S20 1984
	from which
	The SW cor. of a house foundation, 28 x 40 ft., bears N $33\frac{3}{4}^{\circ}$ E, 7.06 chs. dist.
39.66	The center W $\frac{1}{16}$ sec. cor. of sec. 20.
	<hr/> From the center S $\frac{1}{16}$ sec. cor. of sec. 20.
	S $89^{\circ}27'$ W, on the E and W center line of the $SW\frac{1}{4}$ of sec. 20.
	Through dense ponderosa pine.
14.715	Point for the center W-E-SW $\frac{1}{256}$ sec. cor. of sec. 20.

Survey of the Subdivision of Section 20,
T 16 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S20 C-W-E-SW 1/256 1984</p>	
19.62	The SW 1/16 sec. cor. of sec. 20.	
39.24	The S 1/16 sec. cor. of secs. 19 and 20.	
	<p style="text-align: center;">_____</p> <p>From the center W-E-SW 1/256 sec. cor. of sec. 20.</p> <p>N 0°12.6' W, on the N and S center line of the W¹/₂ of the NE¹/₄ of the SW¹/₄ of sec. 20.</p>	
19.84	The center W-E-W 1/256 sec. cor. of sec. 20.	
	<p style="text-align: center;">_____</p> <p>From the E-W 1/64 sec. cor. of secs. 20 and 29.</p> <p>N 0°14' W, on the N and S center line of the SE¹/₄ of the SW¹/₄ of sec. 20.</p>	
9.92	Point for the SE-SW 1/64 sec. cor. of sec. 20.	
	<p>Set a stainless steel post, 28 ins. long, 2¹/₂ in. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S20 SE-SW 1/64 1984</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears N 68³/₄° E, 1.75 chs. dist., mkd. SE SW 1/64 S20 BT.</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears S 31¹/₄° E, 1.105 chs. dist., mkd. SE SW 1/64 S20 BT.</p> <p>From this point, a rebar, 5/8 in. diam., 3 ins. above ground, set in concrete, 12 ins. diam., bears N 22° W, 2 lks. dist., and was established by Russel James Smets, RLS 6975, in 1973, using improper procedures and was not utilized in the course of this survey.</p> <p>Cor. falls 1 lk. S of an E-W fence line.</p> <p style="text-align: center;">_____</p> <p>S 89°30.6' W on the E and W center line of the SE¹/₄ of the SW¹/₄ of sec. 20.</p>	
4.913	Point for the center W-SE-SW 1/256 sec. cor. of sec. 20.	
	<p>Set a stainless steel post, 28 ins. long, 2¹/₂ in. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S20 C-W-SE-SW 1/256 1984</p>	

Survey of the Subdivision of Section 20,
T 16 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A ponderosa pine, 14 ins. diam., bears N 15° E, 1.62 chs. dist., mkd. X BT.</p> <p>A ponderosa pine, 10 ins. diam., bears N 67° E, 1.99 chs. dist., mkd. C W SE SW 1/256 S20 BT.</p> <p>From this point, a rebar, 5/8 in. diam., 3 ins. above ground, bears N 21° W, 1.4 lks. dist., established by Russel James Smets, RLS 6975, in 1973, for the center W-SE-SW 1/256 sec. cor. of sec. 20, using improper procedures and is rejected and not utilized in the course of this survey.</p>
9.92	<p>N 0°11.5' W on the N and S center line of the NW¹/₄ of the SE¹/₄ of the SW¹/₄ of sec. 20.</p> <p>The center W-E-SW 1/256 sec. cor. of sec. 20.</p> <p>From the center S-SW 1/64 sec. cor. of sec. 20.</p> <p>S 89°29' W, on the E and W center line of the SW¹/₄ of the SW¹/₄ of sec. 20.</p>
4.914	<p>Point for the center E-SW-SW 1/256 sec. cor. of sec. 20.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. the ground, with cap mkd.</p> <p style="text-align: center;">S20 C-E-SW-SW 1/256 1984</p>
4.955	<p>from which</p> <p>A ponderosa pine, 21 ins. diam., bears S 30° E, 91 lks. dist., mkd. X BT.</p> <p>A ponderosa pine, 7 ins. diam., bears S 64³/₄° W, 54 lks. dist., mkd. C E SW SW 1/256 S20 BT.</p> <p>Cor. is located 2.60 chs., W of Lake Mary Road, bears S 20° E and N 35° W.</p> <p>N 0°06' W, on the N and S center line of the NE¹/₄ of the SW¹/₄ of the SW¹/₄ of sec. 20.</p> <p>Point for the NE-SW-SW 1/256 sec. cor. of sec. 20.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ in. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S20 NE-SW-SW 1/256 1984</p> <p>from which</p> <p>A ponderosa pine, 26 ins. diam., bears S 70° E, 68 lks. dist., mkd. NE SW SW 1/256 S20 BT.</p>

Survey of the Subdivision of Section 20,
T 16 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS	Cor. is 40 lks. E of Lake Mary Road, bears S 35° E and N 35° W.
14.728	S 89°28' W, on the E and W center line of the N $\frac{1}{2}$ of the SW $\frac{1}{4}$ of the SW $\frac{1}{4}$ of sec. 20. The N-S-S 1/256 sec. cor. of secs. 19 and 20.
15.206	<p style="text-align: center;">NW$\frac{1}{4}$ of Section 20</p> <hr/> <p>From the center W 1/16 sec. cor. of sec. 20. N 1°02' W, on the N and S center line of the NW$\frac{1}{4}$ of sec. 20.</p> <p>Point for the center N-S-NW 1/256 sec. cor. of sec. 20. Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S20 C-N-S-NW 1/256 1984</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears S 16$\frac{3}{4}$° E, 21 lks. dist., mkd. CNS NW 1/256 S20 BT</p> <p style="padding-left: 40px;">A well casing, 9 ins. diam., bears S 41° W, 5.46 chs. dist.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N 43° W, 1.03 chs. dist., mkd. X BT.</p> <p>From this point, a rebar, 5/8 in. diam., 2 ins. above ground, bears N 6$\frac{3}{4}$° W, 5.7 lks. dist., established for the center N-S-NW 1/256 sec. cor. of sec. 20, using improper procedures and is rejected and not utilized in the course of this survey.</p>
20.275	<p>Point for the NW 1/16 sec. cor. of sec. 20, at intersection with the E and W center line of the NW$\frac{1}{4}$ of sec. 20.</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ in. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T16N R9E NW 1/16 S20 1984</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears N 78$\frac{3}{4}$° E, 67 lks. dist., mkd. NW 1/16 S20 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears S 7$\frac{3}{4}$° W, 72 lks. dist., mkd. X BT.</p>
40.555	The W 1/16 sec. cor. of secs. 17 and 20.

Survey of the Subdivision of Section 20,
T 16 N, R 9 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>From the center N 1/16 sec. cor. of sec. 20.</p> <p>S 89°35' W, on the E and W center line of the NW$\frac{1}{4}$ of sec. 20.</p>
19.78	<p>The NW 1/16 sec. cor. of sec. 20.</p>
39.56	<p>The N 1/16 sec. cor. of secs. 19 and 20.</p>
19.725	<p>From the center N-S-NW 1/256 sec. cor. of sec. 20.</p> <p>S 89°31' W, on the E and W center line of the N$\frac{1}{2}$ of the SW$\frac{1}{4}$ of the NW$\frac{1}{4}$ of sec. 20.</p> <p>The N-S-N 1/256 sec. cor. of secs. 19 and 20.</p>
	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The land encompassed in this survey is located about 40 miles southeast of Flagstaff, Arizona, and 2 miles northwest of Happy Jack. Lake Mary Road is a paved highway and runs through the center of the survey. Mule Park is the predominant open meadow park located in the west half of section 20. The average elevation is about 7700 feet above sea level, with the terrain mostly mountainous with dense ponderosa pine.</p> <p>The area is used principally for livestock grazing.</p> <p>The mean magnetic declination for the area is 14° E, with negligible local attraction.</p>

CERTIFICATE OF SURVEY

I, Will C. Gabonay, Cadastral Surveyor, under the supervision of Harry K. Smith, Chief, Field Section, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 20th day of September 1984, I have dependently resurveyed a portion of the west boundary and a portion of the subdivisional lines, and surveyed subdivisions in sections 19 and 20, Township 16 North, Range 9 East, of the Gila and Salt River Meridian, in the State of Arizona which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Will C. Gabonay is no longer assigned to this office and is not available for signature.

MAY 26 1987

(Date)

Harry K. Smith

Harry K. Smith, Chief, Field Section

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

Bureau of Land Management

The foregoing field notes of the dependent resurvey of a portion of the west boundary and a portion of the subdivisional lines, and the survey of subdivisions in sections 19 and 20, Township 16 North, Range 9 East, Gila and Salt River Meridian, Arizona, executed by Will C. Gabonay, Cadastral Surveyor, under the supervision of Harry K. Smith, Chief, Field Section, having been critically examined and found correct, are hereby approved.

MAY 28 1987

(Date)

James P. Kelley
(Chief Cadastral Surveyor of Arizona)