

INDEX DIAGRAM

TOWNSHIP 5 NORTH, RANGE 1 WEST,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 14 pp. 14-17.

T 5 N, R 1 W, Gila and Salt River Mer., Arizona

CHAINS	<p>The following field notes are those of the dependent resurvey of a portion of the east boundary (Gila and Salt River Meridian), and a portion of the subdivisional lines, and the survey of subdivisions in section 14, Township 5 North, Range 1 West, Gila and Salt River Meridian, Arizona.</p> <p>The east boundary (Gila and Salt River Meridian) was surveyed by J.B. McLaughlin in 1883. The east boundary was resurveyed and the subdivisional lines were surveyed by William H. Thorn and Ty White in 1922.</p> <p>The survey was executed in accordance with the specifications as set forth in the <u>Manual of Surveying Instructions, 1973</u>, the special instructions dated March 9, 1988, and the supplemental special instructions dated March 23, 1988, for Group No. 705, Arizona.</p> <p>Preliminary to the resurvey, the lines of the original survey were retraced and all needed corners were recovered and remonumented in their original positions as required by deterioration of the original monuments. The retracement data were thoroughly verified and only the true line field notes are given herein.</p> <p>Positions for angle points on the south right-of-way line of the Central Arizona Project Canal when needed to establish intersections with section lines were determined based on information shown on Bureau of Reclamation's survey diagram No. 344-330-3071, dated February 4, 1981, revised May 20, 1986.</p> <p>The directions of all lines were determined by hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with a Zeiss Elta 46 total station.</p> <p>The geographic position of the southeast corner of section 14, as determined from a tie made to U.S. Geological Survey triangulation station "AGUA 1956", located in the NE quarter of section 30, Township 5 North, Range 1 East, is as follows:</p> <p style="text-align: center;">Latitude: 33°46'02.94" N Longitude: 112°19'28.44" W</p> <p>The magnetic declination from U.S. Geological Survey quadrangle map "BALDY MT., ARIZ.", published in 1964, revised in 1981, is 13° E.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the E Bdy., (Gila and Salt River Mer.) T 5 N, R 1 W, Gila and Salt River Mer., Arizona</p> <hr/> <p style="text-align: center;">Reestablishment of the resurvey executed by William H. Thorn and Ty White, in 1922</p>
--------	---

Dependent Resurvey of a Portion of the E Bdy.,
 (Gila and Salt River Meridian)
 T 5 N, R 1 W, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Beginning at the 1/4 sec. cor. of sec. 13 only, on the E bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 21 ins. above ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">1/4 S13 PM 1922</p> <p>A mound of stone, 4 ft. base, 3 ft. high, is W of cor.</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T5N R1W R1E 1/4 S13 P M 1988 1922</p> <p>North, bet. secs. 13 and 18.</p>
<p>3.86</p>	<p>The 1/4 sec. cor. of sec. 18 only, T 5 N, R 1 E, monumented with a malpais stone, 12 x 10 x 8 ins., mkd. 1/4 on the W face, loosely set, 2 ins. in the ground.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5N R1W R1E 1/4 1/4 S18 1988</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Rebuild the mound of stone, 3 ft. base, 3 ft. high, E of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°13' W, beginning new measurement.</p>
<p>14.59</p>	<p>Point for a witness point on line bet. secs. 13 and 18 on the southerly right-of-way line of the Central Arizona Project Canal.</p>


Dependent Resurvey of a Portion of the E Bdy.,
 (Gila and Salt River Mer.)
 T 5 N, R 1 W, Gila and Salt River Mer., Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>W P T5N R1W R1E S13 / S18 1988</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. A.F.T. 685+75.20 CL P.O.T., bears N 64°27.2' E, 10.903 chs. dist. This point was established by the Bureau of Reclamation on the center line of the Central Arizona Project Canal.</p> <p>A steel fence post is alongside the cor.</p> <p>From this same point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. A.F.T. 673+74.21 CL P.O.T., bears N 77°59.6' W, 8.296 chs. dist. This point was established by the Bureau of Reclamation on the center line of the Central Arizona Project Canal.</p> <p>36.07 The cor. of secs. 12 and 13 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, with brass cap mkd. as described in the official notes of the 1922 resurvey of the Gila and Salt River Mer. through T 5 N. Add marks to the brass cap so that it now reads</p> <div style="text-align: center; margin: 10px 0;"> <p>T5N T5N S12 R1E ——— PM S13 S18 R1W 1988 1922</p> </div> <p>A mound of stone, 3 ft. base, 2 ft. high, is W of cor.</p> <hr style="width: 100%; margin-top: 20px;"/>
--------	--

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 1 W, Gila and Salt River Mer., Arizona

CHAINS	<p style="text-align: center;">Reestablishment of the survey executed by William H. Thorn and Ty White, in 1922</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2 ins. diam., projecting 13 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td colspan="2">T5N R1W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S14</td> <td style="padding: 0 5px;">S13</td> </tr> <tr> <td colspan="2"><hr style="width: 50%; margin: auto;"/></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S23</td> <td style="padding: 0 5px;">S24</td> </tr> <tr> <td colspan="2">1922</td> </tr> </table> </div> <p>A mound of stone, 2 1/2 ft. base, 2 ft. high, is W of cor.</p> <p>Cor. is located 15 lks. N of a track road, 20 lks. wide, bears E and W.</p> <p>From this cor. U.S.G.S. triangulation station "AGUA 1956," bears S 57°55.9' E (forward bearing), 149.025 chs. dist., a standard brass tablet, 3 1/2 ins. diam., cemented in top of large, flat rock.</p> <p>N 0°09' E, bet. secs. 13 and 14, on a Sectional Guide Meridian.</p> <p>Over rolling land.</p> <p>40.09 The 1/4 sec. cor. of secs. 13 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td colspan="2">1/4</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S14</td> <td style="padding: 0 5px;">S13</td> </tr> <tr> <td colspan="2">1912</td> </tr> </table> </div> <p>from which the original bearing trees</p> <p style="margin-left: 40px;">An ironwood, 8 ins. diam., bears N 4 1/2° E, 1.10 chs. dist., mkd. 1/4 S13 BT on partly healed blaze. (Record: palo verde, N 5 1/4° E, 1.09 chs.).</p> <p style="margin-left: 40px;">An ironwood, 10 ins. diam., bears N 33 1/4° W, 1.18 chs. dist., mkd. 1/4 S14 BT on partly healed blaze. (Record: palo verde, 1.16 chs.).</p>	T5N R1W		S14	S13	<hr style="width: 50%; margin: auto;"/>		S23	S24	1922		1/4		S14	S13	1912	
T5N R1W																	
S14	S13																
<hr style="width: 50%; margin: auto;"/>																	
S23	S24																
1922																	
1/4																	
S14	S13																
1912																	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 1 W, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Change the date to 1922 and add the present date 1988, to the brass cap.</p> <p>Cor. is 1.30 chs. S of a wash, 5 lks. wide, drains S 30° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0° 09' W, beginning new measurement.</p> <p>Over rolling land.</p>
<p>19.96</p>	<p>Point for a witness point on line bet. secs. 13 and 14 on the southerly right-of-way line of the Central Arizona Project Canal.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 27 ins. in the ground, with cap mkd.</p> <div style="text-align: center; margin: 20px 0;">  <p style="margin: 0;">W P T5N R1W S14 / S13 1988</p> </div> <p>Set a steel fence post near the cor.</p> <p>Cor. is located 43 lks. S of a cyclone fence, bears NE and SW.</p> <p>From this point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., projecting 1 in. above ground, with top mkd. STA. 541+06.63 PC R.O.W. 125.00 FT. RT., bears N 48°51.1' E, 0.493 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal, as shown on their diagram No.344-330-3071.</p> <p>Cor. is located S 15° E, 46 lks. dist. from a cyclone fence cor.; fences bear N 65° E and S 45° W.</p> <p>From this same point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 538+00.00 R.O.W. 125.00 FT. RT., bears S 48°51.1' W, 4.190 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal, as shown on their diagram No.344-330-3071.</p> <p>Cor. is located 2 lks. E of a 4 strand fence, bears S 15° W, and 30 lks. S of a cyclone fence, bears N 50° E and S 50° W.</p>
<p>39.94</p>	<p>The cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 1 W, Gila and Salt River Mer., Arizona

CHAINS											
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T5N</td> <td>R1W</td> </tr> <tr> <td>S11</td> <td>S12</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S14</td> <td>S13</td> </tr> <tr> <td colspan="2" style="text-align: center;">1922</td> </tr> </table>	T5N	R1W	S11	S12			S14	S13	1922	
T5N	R1W										
S11	S12										
S14	S13										
1922											
	A mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, is W of cor.										
	From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°52' W, bet. secs. 12 and 13. Over rolling and mountainous land.										
38.27	The 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>1/4</td> <td>S12</td> </tr> <tr> <td></td> <td>S13</td> </tr> <tr> <td colspan="2" style="text-align: center;">1922</td> </tr> </table> </div>	1/4	S12		S13	1922					
1/4	S12										
	S13										
1922											
	A mound of stone, 3 ft. base, 2 ft. high, is N of cor. There is no evidence of the original bearing trees.										
	N 89°47' W, beginning new measurement.										
39.955	The cor. of secs. 11, 12, 13, and 14.										
	From the cor. of secs. 13, 14, 23, and 24. N 89°56' W, bet. secs. 14 and 23. Over rolling land.										
40.02	The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>1/4</td> <td>S14</td> </tr> <tr> <td></td> <td>S23</td> </tr> <tr> <td colspan="2" style="text-align: center;">1922</td> </tr> </table> </div>	1/4	S14		S23	1922					
1/4	S14										
	S23										
1922											
	from which the original bearing trees <div style="text-align: center;"> <p>A down palo verde, 12 ins. diam., bears N 57° E, 48 lks. dist., mkd. with a decayed blaze. (Record: N 59°57' E)</p> </div>										

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 1 W, Gila and Salt River Mer., Arizona

CHAINS																
	<p>A stump hole, bears N 87 1/4° W, 16 lks. dist., a palo verde, 9 ins. diam., lying alongside, is faintly mkd. 1/4 S on open blaze. (Record: S 89 1/2° W)</p> <hr/> <p>N 89°56' W, beginning new measurement.</p> <p>Over nearly level land.</p> <p>40.06 The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 2 ins. diam., projecting 14 ins. above ground with brass cap mkd.</p> <table border="1" data-bbox="836 703 982 903"> <tr> <td>T5N</td> <td>R1W</td> </tr> <tr> <td>S15</td> <td>S14</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S22</td> <td>S23</td> </tr> <tr> <td colspan="2">1988</td> </tr> <tr> <td colspan="2">1922</td> </tr> </table> <p>from which the original bearing trees</p> <p>An ironwood, 14 ins. diam., bears S 86° E, 1.12 chs. dist., illegible scribe marks are visible on a partly healed blaze. (Record: S 85° E).</p> <p>An ironwood, 15 ins. diam., bears S 53° W, 1.56 chs. dist., mkd. with a decayed blaze. (Record: S 54° W).</p> <p>A dead ironwood, 9 ins. diam., bears N 6° W, 1.13 chs. dist., mkd. with a decayed blaze. (Record: N 7 3/4° W)</p> <p>A mound of stone, 3 ft. base, 2 ft. high, is W of cor.</p> <hr/> <p>North, bet. secs. 14 and 15.</p> <p>Over rolling land through moderate undergrowth.</p> <p>40.01 The 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.</p> <table border="1" data-bbox="844 1669 974 1764"> <tr> <td>1/4</td> </tr> <tr> <td>S15 S14</td> </tr> <tr> <td>1922</td> </tr> </table> <p>from which the original bearing trees</p> <p>An ironwood, 22 ins. diam., bears S 26 1/4° E, 12 lks. dist., mkd. 4 S14 on partly broken off blaze.</p>	T5N	R1W	S15	S14	<hr/>		S22	S23	1988		1922		1/4	S15 S14	1922
T5N	R1W															
S15	S14															
<hr/>																
S22	S23															
1988																
1922																
1/4																
S15 S14																
1922																

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 1 W, Gila and Salt River Mer., Arizona

CHAINS	<p>An ironwood, 15 ins. diam., bears N 38° W, 45 lks. dist., mkd. BT on partly closed blaze. (Record: N 37° W, 44 lks.)</p> <p>Cor is located on the E edge of a wash, 30 lks. wide, drains S 10° E.</p> <p>Cor. is located 35 1/2 lks. W of a 4 strand wire fence, bears S 25° E and N 25° W.</p> <hr/> <p>N 0°02' E, beginning new measurement.</p> <p>0.65 Point for a witness point on line bet. secs. 14 and 15 on the southerly right-of-way line of the Central Arizona Project Canal.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 29 ins. in the ground, with cap mkd.</p> <div data-bbox="857 842 976 1031" style="text-align: center;"> <p>W P T5N R1W S14 S15 1988</p> </div> <p>Cor. is located 3 lks. S of a 4 strand wire fence, bears S 25° E and N 25° W.</p> <p>From this point a rebar, 5/8 in. diam., with an aluminum cap, 1 1/2 ins. diam., projecting 3 ins. above the ground, with top mkd. R.O.W., bears S 25°57.0' E, 2.632 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal, as shown on their diagram No.344-330-3071.</p> <p>Cor. is located S 20° W, 3 lks. dist., from a fence cor.; fences bear N 35° E and N 25° W.</p> <p>From this same point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 479+50.00 R.O.W. 125.00 FT. RT., bears N 25°57.0' W, 5.836 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal, as shown on their diagram No.344-330-3071.</p> <p>Cor. is 2 lks. W of a 4 strand wire fence, bears S 25° E, and 33 lks. S of a cyclone fence, bears N 35° E and S 35° W.</p>
--------	--

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 1 W, Gila and Salt River Mer., Arizona

CHAINS																
5.275	From this point a rebar, 5/8 in. diam., with an aluminum cap, 1 1/2 ins. diam., projecting 2 ins. above ground, with top mkd. with a punch mark, bears East, 1 lk. dist. This point was established on the S right-of-way line of the Central Arizona Project Canal, as shown on their diagram No.344-330-3071.															
9.245	A brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 482+28.20 R.O.W. 125.00 FT. RT., bears East, 0.7 lk. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal, as shown on their diagram No.344-330-3071.															
39.99	<p>The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2 ins. diam., firmly set, projecting 24 ins. above ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T5N</td> <td style="padding: 0 5px;">R1W</td> <td></td> </tr> <tr> <td style="padding: 0 5px;">S10</td> <td style="padding: 0 5px;">S11</td> <td style="border-left: 1px solid black; border-right: 1px solid black; width: 1px;"></td> </tr> <tr> <td colspan="3" style="border-top: 1px solid black; border-bottom: 1px solid black;"></td> </tr> <tr> <td style="padding: 0 5px;">S15</td> <td style="padding: 0 5px;">S14</td> <td style="border-left: 1px solid black; border-right: 1px solid black; width: 1px;"></td> </tr> <tr> <td colspan="3" style="text-align: center; padding: 0 5px;">1922</td> </tr> </table> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">An ironwood, 6 ins. diam., bears N 17 1/2° E, 42 lks. dist., mkd. BT on small blaze. (Record: 44 lks. dist.).</p> <p style="padding-left: 40px;">A palo verde, 6 ins. diam., bears S 78° E, 63 lks. dist., mkd. with a decayed blaze. (Record: S 79° E).</p> <p style="padding-left: 40px;">A palo verde, 6 ins. diam., bears N 60° W, 13 lks. dist., mkd. with a partly healed blaze.</p> <p>From the cor. a pit, 5 x 10 ft., 4 ft. deep, recently dug with a backhoe by persons unknown is located in each section.</p> <hr/> <p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>N 89°58' W, bet. secs. 11 and 14.</p> <p>Ascend over E slope.</p>	T5N	R1W		S10	S11					S15	S14		1922		
T5N	R1W															
S10	S11															
S15	S14															
1922																
30.00	Descend															
40.01	The 1/4 sec. cor. of secs. 11 and 14, monumented with a stone, 3 1/2 x 3 1/2 x 3 1/2 ins., mkd. X, firmly set, in center of a scattered mound of stone, 4 ft. base. There is no evidence of the original iron post.															

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 1 W, Gila and Salt River Mer., Arizona

CHAINS	<p>At the cor point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to bedrock, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5N R1W 1/4 <u>S11</u> <u>S14</u> 1988</p> <p>from which the following cor. accessories</p> <p style="padding-left: 40px;">A magnet without a plastic case, buried 12 ins. below the ground, bears N 25° E, 30.5 lks. dist.</p> <p style="padding-left: 40px;">A magnet in a 1 x 1 x 2 5/8 in. blue colored plastic case, buried 6 ins. below the ground, bears S 56 3/4° E, 31 lks. dist.</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located on a steep W slope.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N 89°56' W, beginning new measurement.</p> <p>Descend over W slope.</p> <p>40.01 The cor. of secs. 10, 11, 14, and 15.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 36 ins. long, 2 ins. diam., bent over, with brass cap mkd. as described in the official record of the 1922 survey of the subdivision of T 5 N, R 1 W, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A stump hole, bears S 28 3/4° W, 1.30 chs. dist., a palo verde, 7 ins. diam., lying alongside, is mkd. with a decayed blaze. (Record: 1.26 chs.)</p> <p style="padding-left: 40px;">A stump hole, bears N 77 1/4° W, 1.31 chs. dist., an iron-wood, 6 ins. diam., lying alongside, is mkd. T5N R1W S on a partly decayed blaze. (Record: N 78 1/4° W, 1.30 chs.)</p>
--------	--

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 1 W, Gila and Salt River Mer., Arizona

CHAINS	<p>At the cor point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">T5N R1W</td> <td style="padding: 2px 5px;">S16</td> <td style="padding: 2px 5px;">S15</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;"></td> <td style="border-top: 1px solid black; padding: 2px 5px;">S21</td> <td style="border-top: 1px solid black; padding: 2px 5px;">S22</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;"></td> <td style="padding: 2px 5px;">1988</td> <td style="padding: 2px 5px;"></td> </tr> </table> </div> <p>Bury the original iron post alongside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>North, bet. secs. 15 and 16.</p> <p>Over rolling land.</p> <p>2.27 Point for a witness point on line bet. secs. 15 and 16 on the southerly right-of-way line of the Central Arizona Project Canal.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 5px;">W P</td> </tr> <tr> <td style="padding: 2px 5px;">T5N R1W</td> </tr> <tr> <td style="padding: 2px 5px;">S16</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;"></td> </tr> <tr> <td style="padding: 2px 5px;">S15</td> </tr> <tr> <td style="padding: 2px 5px;">1988</td> </tr> </table> </div> <p>Set a steel fence post near the cor.</p> <p>Cor. is located 17 lks. S of a cyclone fence, bears N 75° E and S 75° W.</p> <p>From this point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 415+57.31 R.O.W. 125.00 FT. RT., bears N 76°34.5' E, 0.452 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal, as shown on their diagram No.344-330-3071.</p> <p>Cor. is located 17 lks. S of a cyclone fence, bears N 75° E and S 75° W.</p>	T5N R1W	S16	S15		S21	S22		1988		W P	T5N R1W	S16		S15	1988
T5N R1W	S16	S15														
	S21	S22														
	1988															
W P																
T5N R1W																
S16																
S15																
1988																

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 1 W, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>From this same point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., projecting 1 in. above ground, with top mkd. STA. 407+07.79 R.O.W. 125.00 FT. RT., bears S 76°34.5' W, 12.420 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal, as shown on their diagram No.344-330-3071.</p> <p>Cor. is located 16 lks. S of a cyclone fence, bears N 75° E and S 75° W.</p> <p>40.04 The 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S16 S15 1922</p> <p>A mound of stone, 3 ft. base, 2 ft. high, is W of cor.</p> <hr/> <p style="text-align: center;">Subdivision of Section 14, T 5 N, R 1 W, Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 23.</p> <p>North, on the N and S center line of sec. 14.</p> <p>Over rolling land.</p> <p>40.05 Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E and W center line of the sec.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5N R1W C 1/4 S14 1988</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>47.05 Point for a witness point on the N and S center line of sec. 14, on the southerly right-of-way line of the Central Arizona Project Canal.</p>
---------------	--

Subdivision of Section 14,
T 5 N, R 1 W, Gila and Salt River Meridian, Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located 17 lks. S of a cyclone fence, bears S 80° E and N 80° W.</p> <p>From this point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 517+11.90 R.O.W. 125.00 FT. RT., bears S 79°11.9' E, 8.553 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal, as shown on their diagram No. 344-330-3071.</p> <p>Cor. is located 17 lks. S of a cyclone fence, bears S 80° E and N 80° W.</p> <p>From this same point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 510+00.07 R.O.W. 125.00 FT. RT., bears N 79°11.9' W, 2.232 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal, as shown on their diagram No. 344-330-3071.</p> <p>Cor. is located 17 lks. S of a cyclone fence, bears S 80° E and N 80° W.</p>
79.99	<p>The 1/4 sec. cor. of secs. 11 and 14.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 14.</p> <p>N 89°59' W, on the E and W center line of sec. 14.</p> <p>Over rolling land.</p>
40.12	<p>The center 1/4 sec. cor. of sec. 14.</p>

Subdivision of Section 14,
T 5 N, R 1 W, Gila and Salt River Meridian, Arizona

CHAINS	
77.69	<p>Point for a witness point on the E and W center line of sec. 14 on the southerly right-of-way line of the Central Arizona Project Canal.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 36 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>W P T5N R1W</p> <p>C—————C</p> <p>S14 1988</p> </div> <p>Cor. is located 3 lks. S of a 4 strand wire fence, bears N 40° E and S 40° W.</p> <p>From this point a rebar, 5/8 in. diam., with an aluminum cap, 1 1/2 ins. diam., projecting 3 ins. above the ground, with top mkd. R.O.W., bears N 37°32.0' E, 0.111 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal, as shown on their diagram No.344-330-3071.</p> <p>Cor. is located S 65° E, 2 lks. dist., from a fence cor.; fences bear S 35° W and N 25° W.</p> <p>From this same point a rebar, 5/8 in. diam., with an unmarked aluminum cap, 1 1/2 ins. diam., bears S 37°32.0' W, 2.163 chs. dist., hereinbefore described.</p>
79.84	<p>Point for a witness point on the E and W center line of sec. 14 on the southerly right-of-way line of the Central Arizona Project Canal.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>W P T5N R1W</p> <p>C—————C</p> <p>S14 1988</p> </div> <p>Cor. is located 3 lks. S of a 4 strand wire fence, bears S 25° E and N 25° W.</p>

Subdivision of Section 14,
T 5 N, R 1 W, Gila and Salt River Meridian, Arizona

CHAINS	<p>From this point a rebar, 5/8 in. diam., with an unmarked aluminum cap, 1 1/2 ins. diam., bears S 25°57.0' E, 1.908 chs. dist., hereinbefore described.</p> <p>From this same point STA. 479+50.00 R.O.W. 125.00 FT. RT., bears N 25°57.0' W, 6.560 chs. dist., hereinbefore described.</p>
80.16	<p>The 1/4 sec. cor. of secs. 14 and 15.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The land encompassed in this survey is about 7 miles southwest of Lake Pleasant, Arizona. Elevations range from about 1,500 to 2,100 feet above sea level.</p> <p>The Central Arizona Project Canal enters the township on the west boundary of section 19, traverses northeasterly, entering a tunnel in the NE quarter of sec. 13. Access is provided by Jomax Road, a road along the canal, and other secondary roads.</p> <p>The terrain is rolling and hilly. White Peak in section 15 is a prominent hill which is a landmark for miles around. Creosote, scattering palo verde and ironwood and medium cacti is found over most of the area.</p> <hr/>

UNITED STATES
 DEPARTMENT OF THE INTERIOR
 BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Luke B. Granger	Surveying Technician
Robert M. Charboneau	Surveying Technician
Donald B. McClure	Surveying Technician
Wilmer F. Beyl Jr.	Surveying Aid

CERTIFICATE OF SURVEY

I, William P. Carpender, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 9th day of March, 1988, and supplemental special instructions dated March 23, 1988, I have dependently resurveyed a portion of the E bdy. (Gila and Salt River Meridian), and a portion of the subdivisional lines, and surveyed subdivisions in section 14, of Township 5 North, Range 1 West, of the Gila and Salt River Meridian, in the State of Arizona which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

5/9/88

(Date)

William P. Carpender

(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the E bdy. (Gila and Salt River Meridian), and a portion of the subdivisional lines, and the survey of subdivisions in section 14, of Township 5 North, Range 1 West, Gila and Salt River Meridian, Arizona, executed by William P. Carpender, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

MAY 09 1988

(Date)

James P. Kelley

(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I Certify that the foregoing transcript of the field notes of the above-described surveys in T 5 N, R 1 W, Gila and Salt River Meridian, Arizona is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~