

ORIGINAL

1

BOOK 5278

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE

DEPENDENT RESURVEY OF PORTIONS OF THE SOUTH BOUNDARY, SUBDIVISIONAL LINES,

HOMESTEAD ENTRY SURVEY 373, TRACT D EXEMPTION OF HOMESTEAD ENTRY SURVEY 373,

AND THE DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTIONS 28 AND 33;

AND THE

SURVEY OF SUBDIVISION OF SECTIONS 21, 22, 27 AND 33,

AND A SURVEY OF LOT 1, SECTION 33,

TOWNSHIP 22 NORTH, RANGE 8 EAST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

Paul L. Reeves

, Cadastral Surveyor

Under special instructions dated April 30, 1986, approved April 30, 1986

, which provided for the surveys included under Group Number
678 and assignment instructions dated June 22, 1987.

Survey commenced August 3, 1987

Survey completed October 26, 1987

INDEX DIAGRAM

TOWNSHIP 22 NORTH, RANGE 8 EAST,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
		48	23		
19	20	43	21	20	22
			40	17	
30	29	37	28	15	27
			32	13	
31	32	28	33	11	34
			9	4	

Tract D	Pages	51-52
Subdivisions in sec. 21	Pages	52-65
Subdivisions in sec. 22	Pages	65-71
Subdivisions in sec. 27	Pages	71-78
Subdivisions in sec. 28	Pages	78-92
Subdivisions in sec. 33	Pages	92-109

T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS

The following field notes are those of the dependent resurvey of portions of the south boundary, subdivisional lines, Homestead Entry Survey 373, Tract D exemption in Homestead Entry Survey 373, and the dependent resurvey of the subdivision of sections 28 and 33; and the survey of the subdivision of sections 21, 22, 27 and 33, and of lot 1, section 33, Township 22 North, Range 8 East of the Gila and Salt River Meridian, Arizona.

The east 5 miles of the south boundary were surveyed by J.L. Harris in 1879. The south boundary was resurveyed in 1883 by O.D. Wheeler, including the west one mile, of which there is no previous record of survey. Homestead Entry Survey 373 and subdivisional lines of secs. 28 and 33 was surveyed by R.P.A. Johnson in 1915. Homestead Entry Survey 374 was surveyed by C.D. Hodson in 1919, who also resurveyed a portion of the subdivisional lines and subdivided section 15. The subdivisional lines were surveyed by O.D. Wheeler in 1883. Certain cors. were remonumented in 1966 by Wallace R. Ott, and in 1972 by Harry K. Smith. The east two tiers of sections were concurrently resurveyed under this group as shown on the plat accepted December 8, 1987.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated April 30, 1986, for Group No. 678, Arizona.

The directions of all lines were determined by altitude observations on the sun and refer to the true meridian. Distances and angles were measured with a Zeiss Elta 46 instrument.

Preliminary to the resurvey, the lines of prior surveys were retraced and search was made for evidence of the corner positions. In several instances, monuments and/or accessories were found which did not match the description in the original field notes, but which were old and had the characteristics typical for the time of the original survey. This evidence was evaluated along with perpetuations or reestablishments by the private surveyors and engineers. All found corners and those monuments which were determined to be the best available evidence of the original corner positions were remonumented in their positions. Lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>The geographic position of the southeast corner of section 34, as determined from a tie made to U.S. Coast and Geodetic Survey triangulation station "Elden" located in the SE quarter of section 36, T 22 N, R 7 E, is as follows</p> <p>NAD 27: Latitude: 35° 14' 21.58" N Longitude: 111° 31' 26.87" W</p> <p>The mean magnetic declination as shown on Sunset Crater West, Arizona, quadrangle map; published by U.S. Geological survey in 1966, is 13 1/2° E.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the South Boundary T 22 N, R 8 E, Gila and Salt River Mer., Arizona</p> <hr/> <p style="text-align: center;">Restoring the resurvey executed by O.D. Wheeler, Deputy Surveyor, in 1883</p> <hr/> <p>Beginning at the cor. of secs. 2, 3, 34, and 35, monumented with a stainless steel post, mkd. and referenced as described in the field notes of the resurvey executed in 1986 under this same group.</p> <p>N 85°18' W, bet. secs. 3 and 34.</p> <p>Over gently rolling land, through moderate ponderosa pine.</p> <p>5.06 A lot cor., monumented with a rebar, 1/2 in. diam., projecting 4 ins. above the ground, not mkd.</p> <p>15.11 A lot cor., monumented with a rebar, 1/2 in. diam., projecting 1 in. above the ground, with tag attached and mkd. PE 2007.</p> <p>20.14 The E 1/16 sec. cor. of secs. 3 and 34, monumented with the rebar, 14 ins. long, 1/2 in. diam., projecting 2 ins. above the ground, with tag attached and mkd. PE 2007. This cor. was established by J.B. Holmquist, PE 2007, in 1974 and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the cor. point</p>
--------	--

Dependent Resurvey of a Portion of the South Boundary
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E E 1/16 $\frac{S34}{S 3}$ T21N 1987</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 5 ins. diam., bears S 35° E, 71 lks. dist., mkd. X BT at base.</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears S 55 1/2° W, 97 lks. dist., mkd. E 1/16 S 3 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit the local cor. inside the stainless steel post.</p> <p>A steel fence post is alongside the cor.</p> <p>Cor. is located in an E and W fence.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N 85°18' W, beginning new measurement.</p> <p>5.03 A lot cor., monumented with a rebar, 1/2 in. diam., projecting 3 ins. above the ground in an E and W fence, not mkd.</p> <p>10.06 A lot cor., monumented with a rebar, 1/2 in. diam., projecting 1 in. above the ground, with tag attached and mkd. PE 2007.</p> <p>20.11 The 1/4 sec. cor. of secs. 3 and 34, monumented with an iron pipe, 36 ins. long, 1 in. diam., projecting 8 ins. above the ground, with a Coconino County Engineering brass cap attached and erroneously mkd.</p> <p style="text-align: center;">1/4 T22N 34 R9E T21N 3 R9E 1964</p>

Dependent Resurvey of a Portion of the South Boundary
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS

from which the remains of the 1879 bearing trees

A decayed ponderosa pine stump, 33 ins. diam., bears
N 56 3/4° E, 108.5 lks. dist., no marks visible.
(Record: N 55° E, 106 lks. dist.)

A pine stump, 23 ins. diam., bears S 32° W, 64 lks. dist.,
no marks visible. (Record: S 35° W, 66 lks. dist.)

from which bearing trees established by Coconino County in 1964

A ponderosa pine, 21 ins. diam., bears S 68 1/2° W,
55.5 lks. dist., illegible scribe marks visible through
partially healed blaze. (County Record: S 65 1/4° W)

A ponderosa pine, 18 ins. diam., bears N 15 3/4° W, 73 lks.
dist., illegible scribe marks visible through partially
healed blaze. (County Record: N 18 1/2° W.)

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
25 ins. in the ground, with the brass cap mkd.

T22N R8E

1/4 $\frac{S34}{S3}$

T21N
1987

from which a bearing object

A power pole, bears N 80 3/4° E, 39 lks. dist., with marks
582 1, lines extend N and W.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic
case beneath the stainless steel post.

Bury county cor. alongside the stainless steel post.

Cor. is located 1.5 lks. N of an E and W fence; and 50 lks. S of
a graded gravel road, curving northerly and easterly; dirt road
curving westerly.

Dependent Resurvey of a Portion of the South Boundary
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>N 88°35' W, beginning new measurement.</p>
5.015	<p>The E-E-W 1/256 sec. cor. of secs. 3 and 34, monumented with a rebar, 18 ins. long, 5/8 ins. diam., 4 ins. below ground, with an aluminum cap lying alongside, mkd. PE 971 and LS 4321 and a rebar, 36 ins. long, 3/4 in. diam., set alongside. This cor. was established by C.W. Dryden, PE 971 and LS 4321, of unknown date and is accepted as a careful and faithful determination of the position of the corner.</p>
	<p>At the cor. point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S34 E-E-W 1/256 S 3 1987</p>
	<p>from which</p>
	<p style="text-align: center;">A ponderosa pine, 8 ins. diam. bears S 18° E, 12.5 lks. dist., mkd. E-E-W 1/256 S3 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Deposit both local cors. inside the stainless steel post.</p>
	<p>Cor. is located 2.5 lks. N of a fence cor., fences extend E and S and 7.5 lks. S of center of a dirt road, bears E and W.</p>
	<hr style="width: 20%; margin: auto;"/> <p>N 88°35' W, beginning new measurement.</p>
5.015	<p>A lot cor., monumented with a rebar, 1/2 in. diam., projecting 2 ins. above the ground, with a tag attached and mkd. PE 2007.</p>
15.055	<p>Point for the W 1/16 sec. cor. of secs. 3 and 34, found a local cor. lying loose, not mkd.</p>

Dependent Resurvey of a Portion of the South Boundary
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. below ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E W 1/16 $\frac{S34}{S 3}$ T21N 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit local cor. inside the stainless steel post.</p> <p>Cor. is located 69 lks. S of a fence cor. in an open field, fences extend N and N 50° E.</p> <p>35.135 The cor. of secs. 3, 4, 33, and 34, monumented with a rebar, 15 ins. long, 5/8 in. diam., projecting 3 ins. above the ground, not mkd., from which the remains of the original 1879 bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 33 ins. diam., bears N 11 1/2° E, 10 lks. dist., no marks visible through partially healed blaze.</p> <p style="padding-left: 40px;">A pine stump, 30 ins. diam., bears S 27 3/4° E, 58 lks. dist., mkd. TXX1N RV111E III. (Record: S 19° E, 61 lks. dist.)</p> <p style="padding-left: 40px;">A ponderosa pine, 31 ins. diam., bears S 47 1/2° W, 32 lks. dist., opened blaze to read IN RVIII. (Record: S 54° W)</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears N 74° W, 74 lks. dist., no marks visible. (Record: N 70° W, 75 lks. dist.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E S33 S34 ----- S 4 S 3 T21N 1987</p>
--------	---

Dependent Resurvey of a Portion of the South Boundary
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit local cor. inside the stainless steel post.</p> <p>Cor. is located 1.5 lks. W of a fence cor., fences extend E and southerly; and 135 lks. E of a graded dirt road bearing N 25° E and S 20° W.</p> <hr/> <p>S 89°21' W, bet. secs. 4 and 33.</p> <p>Over gently rolling land, through medium ponderosa pine.</p> <p>40.23 The 1/4 sec. cor. of secs. 4 and 33, monumented with a malpais stone, 14 x 14 x 11 ins., lying loose on a mound of stone, 2 ft. base, 1 ft. high, mkd. 1/4 on one face, from which the original 1879 bearing trees.</p> <p style="padding-left: 40px;">A decayed ponderosa pine stump, 24 ins. diam., bears N 66 1/2° E, 18 lks. dist., no marks visible. (Record: N 73° E)</p> <p style="padding-left: 40px;">A ponderosa pine, 34 ins. diam., bears S 33 1/2° E, 32 lks. dist., marks visible 1/4S. (Record: S 25° E)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T22N R8E</p> <p>1/4 $\frac{S33}{S 4}$</p> <p>T21N</p> <p>1987</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears S 69 3/4° E, 88 lks. dist., mkd. 1/4 S4 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S 35° W, 48.5 lks. dist., mkd. X at breast height and BT at base.</p>

Dependent Resurvey of a Portion of the South Boundary
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.</p> <p>Cor. is located 10 lks. S of an abandoned fence bears W only, and 25 lks. N of a fence, bears E and W.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S 88°46' W, beginning new measurement.</p> <p>20.115 A local cor., monumented with a rebar, 1/2 in. diam., projecting 2 ins. above the ground, with a tag attached and mkd. 2007. This cor. was established by James B. Holmquist, PE 2007, in 1974, not monumented. Located 3 lks. SW of a fence cor., fences extend N and E.</p> <p>40.22 The cor. of secs. 4, 5, 32, and 33, monumented with a U.S. Department of Agriculture aluminum post, 2 1/2 ins. diam., projecting 2 ins. above the ground. This cor. was set by the Forest Service Cadastral Surveyor Wallace R. Ott, LS 9431, in 1979, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td></td> <td style="text-align: center;">T22N</td> <td></td> </tr> <tr> <td style="text-align: center;">S32</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td> <td style="text-align: center;">S33</td> </tr> <tr> <td style="border-bottom: 1px solid black; text-align: center;">S 5</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td> <td style="border-bottom: 1px solid black; text-align: center;">S 4</td> </tr> <tr> <td></td> <td style="text-align: center;">T21N</td> <td style="text-align: right;">R8E</td> </tr> <tr> <td></td> <td style="text-align: center;">LS 9431</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1979979</td> <td></td> </tr> </table> </div> <p>from which the 1879 bearing trees</p> <p style="margin-left: 40px;">A ponderosa pine, 39 ins. diam., bears N 54° E, 181 lks. dist., marks visible through partially healed blaze TXXII. (Record: N 53 1/2° E, 178 lks. dist.)</p> <p style="margin-left: 40px;">A ponderosa pine, 29 ins. diam., bears S 20 1/2° E, 137.5 lks. dist., healed blaze. (Record: S 15° E, 135 lks. dist.)</p>		T22N		S32		S33	S 5		S 4		T21N	R8E		LS 9431			1979979	
	T22N																		
S32		S33																	
S 5		S 4																	
	T21N	R8E																	
	LS 9431																		
	1979979																		

Dependent Resurvey of a Portion of the South Boundary
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>A ponderosa pine, 32 ins. diam., bears S 24 1/2° W, 116 lks. dist., healed blaze. (Record: S 30° W, 114 lks. dist.)</p> <p>A decayed stump of undeterminable size, bears N 29° W, 84.5 lks. dist., no marks visible. (Record: N 33 1/2° W, 82 lks. dist.)</p> <p>Cor. is in a mound of stone, 2 1/2 ft. base, 1 ft. high.</p> <p>A steel fence post is alongside the cor.</p> <p>Cor. is located 10 lks. E of a track road, bears N 70° E and S 70° W.</p> <p>From this point U.S. Coast and Geodetic survey triangulation station "ELDEN 1958" bears N 87°52.6' W, (forward bearing) 168.935 chs. dist., monumented with a standard brass disk, cemented into a boulder, 4 x 3 x 1 1/2 ft. high, with top mkd. ELDEN 1958. The reference marks are in place and in good condition as per record.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivisional Lines T 22 N, R 19798 E, Gila and Salt River Mer., Arizona</p> <hr/> <p style="text-align: center;">Restoring the survey executed by O.D. Wheeler, Deputy Surveyor, in 1883.</p> <hr/> <p>From the cor. of secs. 3, 4, 33, and 34, on the S bdy. of the Tp. N 1°35' E, bet. secs. 33 and 34.</p> <p>Over gently rolling land, through medium ponderosa pine.</p> <p>41.63 The 1/4 sec. cor. of secs. 33 and 34, determined from an original bearing tree, and from a bearing tree established by C.W. Dryden, PE 971 and LS 4321, in 1948.</p> <p>from which an 1883 bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears N 49 1/2° W, 50.5 lks. dist., marks visible through partially healed blaze 4S. (Record: N 40° W, 50 lks. dist.)</p> <p>and from which a 1948 bearing tree</p>
--------	--

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>A ponderosa pine, 17 ins. diam., bears N 51° E, 94 lks. dist., healed blaze.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E 1/4 S33 S34 1987</p> <p>from which bearing objects</p> <p>A power pole, bears N 88° E, 113.5 lks. dist., mkd. 3 MST&T CO.</p> <p>A water line head, bears South, 165 lks. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Found a local cor. lying loose near cor. point; a rebar, 1 in. diam., 21 ins. long. Deposit local cor. inside stainless steel post.</p> <p>Cor. is located at the cor. of a chain link fence. Fences extend N and W and 30 lks. W of a graded dirt road, bears N and S.</p> <p style="text-align: center;">_____</p> <p>N 0°03' E, beginning new measurement.</p> <p>40.22 The cor. of secs. 27, 28, 33, and 34, monumented with a bolt, 15 ins. long, 1/2 in. diam., 4 ins. below surface of Burris Road, bears E and W, origin and date unknown and is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below the surface of Burris Road, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E S28 S27 ----- S33 S34 1987</p>
--------	--

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS

from which bearing objects

A powerpole bears N 1° E, 38 lks. dist., mkd. KOPPERS FR-86
WP-G 3-40, lines extend E and W.

A fence cor. bears S 39 3/4° W, 59.5 lks. dist., fences
extend S and W.

The SE cor. of a mobile home bears N 42 1/2° W, 83 lks.
dist.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic
case beneath the stainless steel post.

Deposit the bolt inside the stainless steel post.

From the cor. of secs. 26, 27, 34, and 35, monumented with a
stainless steel post, mkd. and referenced as described in the
field notes of the resurvey executed in 1986 under this same
group.

N 85°43' W, bet. secs. 27 and 34.

Over gently rolling land, through medium ponderosa pine.

19.76 The E 1/16 sec. cor. of secs. 27 and 34, monumented with a rebar,
16 ins. long, 1/2 in. diam., projecting 2 ins. above the ground,
with an aluminum cap attached and mkd. 1/16 2007. This cor. was
established by James B. Holmquist, PE 2007, in 1974 and is
accepted as a careful and faithful determination of the position
of the cor.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
21 ins. in the ground, and in a mound of stone, 3 ft. base, to
top, with brass cap mkd.

T22N R8E
E 1/16 $\frac{S27}{S34}$
1987

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears N 78 1/2° E, 117 lks. dist., mkd. E 1/16 S27 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears N 23° W, 48.5 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit the local cor. inside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 40 lks. N of a track road, bears N 60° E, and S 60° W.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N 85°44' W, beginning new measurement.</p> <p>5.50 Rio De Flag creek, 35 lks. wide, course N 40° E.</p> <p>19.75 The 1/4 sec. cor. of secs. 27 and 34, monumented with a galvanized pipe, 1 1/2 in. diam., projecting 10 ins. above the ground, with a Coconino County Engineering brass cap attached and mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>1/4</p> <p><u>27</u></p> <p>34</p> <p>1964</p> </div> <p>from which a bearing tree of unknown origin</p> <p style="padding-left: 40px;">A ponderosa pine, 40 ins. diam., bears S 80° E, 46 lks. dist., marks, visible through partially healed blaze 1/4 S BT, by Coconino County Engineer alongside an older blaze of unknown origin, no marks possibly an original tree not called out in the 1883 survey notes.</p> <p>and from which a bearing tree established in 1964 by Coconino County Engineering Department</p>
--------	--

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 20 ins. diam., bears S 47 1/2° W, 123.5 lks. dist., healed blaze. (County Record: S 48° W)</p> <p>and from which new bearing trees</p> <p>A ponderosa pine, 15 ins. diam., bears N 40 1/2° E, 172 lks. dist., mkd. 1/4 S27 BT.</p> <p>and from which bearing objects</p> <p>A power pole, bears N 67 1/2° W, 7.5 lks. dist., no marks, line extend N, S 74° E, southerly and W.</p> <p>A fence cor., bears N 31 1/2° W, 58 lks. dist., fences extend N and W.</p> <p>Cor. is located S 10° E, 35 lks. dist., from the intersections of graded dirt roads, extending N, S 74° E, S 22° E, and W.</p> <hr/> <p>N 85°50' W, beginning new measurement.</p>
39.61	<p>The cor. of secs. 27, 28, 33, and 34.</p> <hr/>
	<p>N 1°15' W, bet. secs. 27 and 28.</p> <p>Over nearly level open land.</p>
40.44	<p>The 1/4 sec. cor. of secs. 27 and 28, monumented with a sandstone, 24 x 14 x 12 ins., 48 ins. below ground, mkd. 1/4 on W face, with a rebar, 15 ins. long, 5/8 in. diam., with an aluminum cap attached and mkd. 1/4, origin unknown; and another rebar, 36 ins. long, 1/2 in. diam., set over the 5/8 in. rebar, with an aluminum cap attached and mkd. LS 14671.</p> <p>At the cor. point</p> <p>Drive an aluminum fence post, 6 1/2 ft. long in the ground and set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., over the fence post, 27 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p style="text-align: center;">T22N R8E 1/4 S28 S27 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Deposit the local cors. inside the stainless steel post.</p> <p>Set an aluminum fence post alongside the cor.</p> <hr/> <p>N 1°10' E, beginning new measurement.</p> <p>39.99 The cor. of secs. 21, 22, 27, and 28, monumented with an iron pipe, 27 ins. long, 1 1/2 ins. diam., 2 ins. below the ground. This cor. was set by Jesse D. Roeder, LS 2308, of unknown date, with an aluminum cap set inside and mkd. 2007 21, 22, 27 and 28, by James B. Holmquist, PE, 2007, of unknown date, from which a bearing tree that is not called out in the original survey notes. C.W. Dryden, PE and LS shows this as being an original bearing tree.</p> <p style="padding-left: 40px;">A ponderosa pine, 40 ins. diam., bears N 58 1/2° W, 325 lks. dist., mkd. S 21 BT.</p> <p>from which a bearing tree established by C.W. Dryden, PE 971 and LS 4321, in 1948.</p> <p style="padding-left: 40px;">A ponderosa pine, 22 ins. diam., bears N 33 3/4° E, 295.5 lks. dist., healed blaze. (Dryden's Record: N 32° E)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
--------	--

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS

T22N R8E	
S21	S22
S28	S27
1987	

from which a new bearing tree

A ponderosa pine, 9 ins. diam., bears N 48 1/2° E, 273 lks. dist., mkd. T22N R8E S 22 BT.

and from which

A fence cor. bears N 2 3/4° E, 100 lks. dist., fences extend N, E and W.

The NW cor. of a wood frame house, bears S 32°55' E, 213.5 lks. dist.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Deposit the local cor. inside the stainless steel post.

Cor. is located 55 lks. S of center of Silver Saddle Road, bears E and W.

From this point a local cor., bears N 66° W, 0.008 chs. dist., monumented with a galvanized pipe, 1 1/4 in. diam., projecting 3 ins. above the ground, date and origin unknown.

From this same point, another local cor., bears N 8° W, 2.7 lks. dist., monumented with a rod, 3/8 in. diam., 4 ins. below the ground, date and origin unknown.

From the cor. of secs. 22, 23, 26, and 27, monumented with a stainless steel post, mkd. and referenced as described in the field notes of the resurvey executed in 1986 under this same group.

S 89°56' W, bet. secs. 22 and 27.

Over rolling land, along Silver Saddle Road.

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
9.955	<p>Point for the E-E 1/64 sec. cor. of secs. 22 and 27.</p> <p>Set a cut off stainless steel post, 8 ins. long, 2 1/2 ins. diam., 1 in. below surface of Silver Saddle Road, with brass cap mkd.</p> <p style="text-align: center;">S22 E-E 1/64 S27 1987</p> <p>from which</p> <p>A ponderosa pine, 15 ins. diam., bears N 67 1/4° W, 249.5 lks. dist., mkd. E-E 1/64 S22 BT.</p> <p>A ponderosa pine, 14 ins. diam., bears N 14 1/4° W, 160.5 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 2 lks. S of center line of Silver Saddle Road, bears E and W.</p>
19.91	<p>The E 1/16 sec. cor. of secs. 22 and 27, monumented with a rebar, 18 ins. long, 1/2 in. diam., projecting 5 ins. above the ground, with an aluminum cap attached and mkd. LS 14671. This cor. was established by Kenneth Krenke, LS 14671, of unknown date and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the cor. point</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 34 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T22N R8E E 1/16 $\frac{S22}{S27}$ 1987</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Drive the local cor. alongside the aluminum post, below ground.</p> <p>Set an aluminum fence post alongside the cor.</p> <p>Cor. is located on a cut bank, 38 lks. S of center of Silver Saddle Road, bears E and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S 89°58' W, beginning new measurement.</p> <p>19.90 The 1/4 sec. cor. of secs. 22 and 27, monumented with a Coconino County Engineering brass cap, 24 ins. below surface of Silver Saddle Road, with top mkd.</p> <p style="text-align: center;">1/4 $\frac{S22}{S27}$ 1963</p> <p>from which a bearing tree established by C.W. Dryden, PE and LS of unknown date.</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears N 25 3/4° E, 88 lks. dist., mkd. 1/4 2 BT.</p> <p>At the cor. point</p> <p>Set a cut off stainless steel post, 22 ins. long, 2 1/2 ins. diam., over the county cor., 2 ins. below surface of Silver Saddle Road, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E 1/4 $\frac{S22}{S27}$ 1987</p> <p>from which</p> <p style="padding-left: 40px;">An iron rod, 1/2 in. diam., 1/2 in. below ground, bears North, 104.5 lks. dist.</p> <p style="padding-left: 40px;">A power pole, bears S 35 1/4° E, 40 lks. dist., mkd. NTP 1938.</p>
--------	--

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 14 ins. diam., bears N 48 1/2° W, 148.5 lks. dist., mkd. X at breast height and BT at base.</p> <p>Cor. is located 3.5 lks. S of the center of Silver Saddle Road, bears E and W; and 63 lks. S of a fence and power line, bears E and W.</p> <hr/> <p>S 89°57' W, beginning new measurement.</p>
39.80	<p>The cor. of secs. 21, 22, 27, and 28.</p> <hr/> <p>N 0°41' E, bet. secs. 21 and 22.</p> <p>Over nearly level land through moderate ponderosa pine.</p>
20.01	<p>The S 1/16 sec. cor. of secs. 21 and 22, monumented with a rebar, 16 ins. long, 5/8 in. diam., projecting 1 in. above the ground, with an aluminum cap attached and mkd. 1/16 2007. This cor. was established by James B. Holmquist, PE 2007, of unknown date and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E S 1/16 S21 S22 1987</p> <p>from which</p> <p>A ponderosa pine, 14 ins. diam. bears N 17 3/4° E, 247.5 lks. dist., mkd. S 1/16 S22 BT.</p> <p>A ponderosa pine, 12 ins. diam., bears S 59 1/4° E, 135.5 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Deposit the local cor. inside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°41' E, beginning new measurement.</p>
6.70	Track road, bears S 55° E and N 55° W.
15.01	<p>The N-N-S 1/256 sec. cor. of secs. 21 and 22, monumented with a rebar, 16 ins. long, 5/8 in. diam., projecting 2 ins. above the ground, with an aluminum cap attached and mkd. 1/256 2007. This cor. was established by James B. Holmquist, PE 2007, of unknown date and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>N-N-S 1/256 S21 S22 1987</p> </div> <p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 13 ins. diam., bears N 51 1/4° E, 239.5 lks. dist., mkd. N-N-S 1/256 S22 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 5 ins. diam., bears N 77 1/2° W, 164 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit the local cor. inside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Cor. is located 145 lks. E of a track road, bears N 20° E and S 20° W; 75 lks. E of a power line, bears N 20° E and S 20° W; and 350 lks. E of the easterly ROW fence of U.S. Highway 89, bears N 8° E and S 8° W.</p> <hr/> <p>N 0°41' E, beginning new measurement.</p> <p>5.00 The 1/4 sec. cor. of secs. 21 and 22, monumented with a sandstone, 18 x 10 x 6 ins., 5 ins. below the ground and mkd. 1/4 on the W face and a cross on top. The original survey called for a post. This cor. was perpetuated by C.W. Dryden, PE 971 and LS 4321, in 1948, from which an original bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 39 ins. diam., bears S 50° W, 75.5 lks. dist., mkd. 1/4 S BT. (Record: S 50° E, 83 lks. dist.)</p> <p>from which a bearing tree established by C.W. Dryden in 1948</p> <p style="padding-left: 40px;">A ponderosa pine, 26 ins. diam., bears N 74 1/2° W, 47.5 lks. dist., healed blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T22N R8E 1/4 S21 S22 1987</p> </div> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 5 ins. diam., bears N 26° E, 164.5 lks. dist., mkd. 1/4 S22 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury the mkd. stone alongside the cor.</p> <p>Set a steel fence post alongside the cor.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Cor. is located on the E edge of a track road, bears N 3° E and S 3° W; 47 lks. W of a power line, bears N 4° E and S 4° W; and 300 lks. E of the easterly ROW of U.S. Highway 89, bears N 10° E and S 10° W.</p> <hr/> <p>N 0°09' W, beginning new measurement.</p> <p>40.51 The cor. of secs. 15, 16, 21, and 22 monumented with an Arizona Department of Transportation brass tablet, 3 1/2 ins. diam., 6 ins. below surface of the center of the N bound lanes of U.S. Highway 89. This cor. is a remonumentation of the cor. reestablished by Dwan Utley, LS 11369, in 1983, which was perpetuated by C.W. Dryden, PE 971, and LS 4321, in 1948, with top mkd.</p> <p style="text-align: center;">T22N R 8 E 16 15 21 22</p> <p>There is no remaining evidence of the original bearing trees. from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S 34° E, 292.5 lks. dist., mkd. T22N R8E S22 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S 69 3/4° W, 184.5 lks. dist., mkd. T22N R8E S21 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N 55° W, 264 lks. dist., mkd. T22N R8E S16 BT.</p> <hr/> <p>From the cor. of secs. 14, 15, 22, and 23, monumented with an iron post, set in 1966, mkd. and referenced as described in the field notes of the resurvey executed in 1986 under this same group.</p> <p>N 89°56' W, bet. secs. 15 and 22.</p> <p>Over rolling land, through medium ponderosa pine.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
39.88	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 2 1/2 ins. diam., projecting 7 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E 1/4 $\frac{S15}{S22}$ 1966</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">The stump hole of a decayed tree, bears N 65 3/4° W, 50 lks. dist., with healed blaze. (1966 Record: N 68° W, 48 lks. dist.)</p> <p style="padding-left: 40px;">An alligator juniper, 30 ins. diam., bears S 75° W, 64.5 lks. dist., mkd. 1/4 S BT. (1966 Record: S 71° W, 63 lks. dist.)</p> <p>and from which a 1966 bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears N 67 3/4° E, 92 lks. dist., with healed blaze. (Record: N 67° E)</p> <p>and from which a new bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 5 ins. diam., bears N 28 3/4° W, 120.5 lks. dist., mkd. X at breast height and BT at base.</p> <p>A mound of stone, 2 ft. base, 1 ft. high is N of the cor.</p> <p>A steel fence post is alongside the cor.</p> <p>Add the marks 1987 to the brass cap.</p> <p>Cor. is located on SW side of a dominant knoll.</p> <p style="text-align: center;">_____</p> <p style="text-align: center;">Restoring the resurvey by C.D. Hodson in 1919.</p> <p style="text-align: center;">_____</p> <p>N 89°47' W, beginning new measurement.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona


CHAINS	
20.00	<p>Point for the W 1/16 sec. cor. of secs. 15 and 22, identical with cor. 22, Tract C, HES 374, at proportionate dist., found remains of a charred stake while setting the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E S25 W 1/16 ——— S22 1987</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears N 69 3/4° E, 131.5 lks. dist., mkd. W 1/16 S15 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears S 31° E, 105.5 lks. dist., mkd. W 1/16 S22 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 45 lks. NW of a curve in a land fill road, asphalt surface, road extends N and W from curve; and at the cor. of fences extending N and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 89°47' W, beginning new measurement.</p>
6.05	<p>Cor. 23, Tract C, HES 374, monumented with a malpais stone, 14 x 9 x 8 ins., projecting 4 ins. above the ground, mkd. 23 CC HES 374 on the N face and a cross on top, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">The remains of a pine stump, 25 ins. diam., bears N 68° E, 111.5 lks. dist., no marks visible. (Record: N 68°32' E, 115 lks. dist.)</p> <p style="padding-left: 40px;">The remains of a pine stump, 16 ins. diam., bears S 7° 3/4° W, 270.5 lks. dist., no marks visible. (Record: S 6°47' W, 268 lks. dist.)</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S 43° E, 215 lks. dist., mkd. COR 23 HES 374 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S 7 3/4° W, 99 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury the original stone alongside the cor.</p> <p>Cor. is located 43 lks. N of center of landfill road, asphalt surface, bears E and W; and 1 lk. N of an E and W fence.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S 89°41' W, beginning new measurement.</p> <p>0.840 Cor. 13, Tract A, HES 374, monumented with a malpais stone, 17 x 10 x 9 ins., 6 ins. below ground, mkd. 13 HES 374 on NW face, CC on NE face, and a cross on top and broken glass at base of cor., from which the remains of an original bearing tree.</p> <p style="padding-left: 40px;">A pine stump, 40 ins. diam., bears N 37°02' W, 139 lks. dist., illegible scribe marks visible.</p> <p>At the cor point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>
---------------	---

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS



from which new bearing trees

A ponderosa pine, 4 ins. diam., bears S 26° E, 90 lks. dist, mkd. X at breast height and BT at base.

A ponderosa pine, 12 ins. diam., bears S 7 1/2° W, 89.5 lks. dist, mkd. COR 13 HES 374 BT.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Bury the original stone alongside the stainless steel post.

Cor. is located 43 lks. N of center of landfill road, asphalt surface, bears E and W; and 1 lk. N of an E and W fence.

West, beginning new measurement.

3.145 The W-W 1/64 sec. cor. of secs. 15 and 22, identical with cor. 1, Tract A, HES 374, monumented with a malpais stone, 15 x 13 x 7 ins., projecting 3 ins. above the ground, mkd. 1 CC HES 374 on N face and a cross on top, from which the remains of the original bearing trees

The remains of a pine stump, bears N 86°24' W, 58 lks. dist., no marks visible.

A ponderosa pine, 24 ins. diam., bears S 22°43' E, 177 lks. dist., with healed blaze.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">S 15 W-W 1/64 S22 1987</p> <p>from which a new bearing tree</p> <p style="text-align: center;">A ponderosa pine, 12 ins. diam., bears S 2 1/2° W, 104 lks. dist., mkd. W-W 1/64 S22 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury original stone alongside the stainless steel post.</p> <p>Cor. is located 40 lks. N of center of landfill road, asphalt surface, bears E and W.</p> <hr/> <p>N 89°56' W, beginning new measurement.</p>
10.03	<p>The cor. of secs. 15, 16, 21, and 22.</p>
	<p style="text-align: center;">Restoring the Resurvey by R.P.A. Johnson, in 1915</p> <hr/> <p>From the cor. of secs. 4, 5, 32, and 33, on the S bdy. of the Tp. N 0°43' E, bet. secs. 32 and 33.</p> <p>Over gently rolling land, through medium ponderosa pine.</p>
20.68	<p>Point for the S 1/16 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E S 1/16 S32 S33 1987</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	from which
	A ponderosa pine, 9 ins. diam., bears S 65 1/2° W, 11 lks. dist., mkd. S 1/16 S32 BT.
	A ponderosa pine, 7 ins. diam., bears N 13° W, 19.5 lks. dist., mkd. X at breast height and BT at base.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
	Raise a mound of stone, 3 ft. base, 3 ft. high, W of cor.
	Cor. is located 115 lks. N of a track road, bears S 60° E and N 60° W; and 260 lks. S of a draw, 25 lks. wide, drains N 60° E.
30.05	Winona Road, asphalt surface, bears N 76° E and S 76° W.
30.865	A local cor., monumented with a rebar, 1/2 in. diam., projecting 2 ins. above the ground, with an aluminum cap attached and mkd. LS 9431. Local cor. is 1 lk. N of Winona Road ROW fence, bears N 76° E and S 76° W.
41.36	The 1/4 sec. cor. of secs. 32 and 33, monumented with a U.S. Department of Agriculture aluminum post, 2 1/2 ins. diam., projecting 12 ins. above the ground. This cor. was established by Wallace R. Ott, Forest Service Cadastral Surveyor, LS 9431, in 1975 and is accepted as a careful and faithful determination of the position of the cor., with an aluminum cap attached and mkd.
	<p style="text-align: center;">T22N R8E 1/4 S32 S33 LS 9431 1979</p>
	from which the remains of the 1915 bearing trees
	A ponderosa pine, 22 ins. diam., bears S 37 3/4° E, 19 lks. dist., mkd. 1/4 S33 BT. (Record: S 44°24' E)
	A decayed stump bears N 22°24' W, 39 lks. dist., no marks visible.

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	and from which a bearing object
	A rebar, 1/2 in. diam., firmly set flush with ground,
	bears S 3 1/2° W, 154 lks. dist.
	Cor. is located 56 lks. N of a draw, 20 lks. wide, drains
	S 40° E.
	N 0°39' E, beginning new measurement.
10.10	Southerly ROW fence for U.S. Highway 89, bears N 40° E and
	S 40° W.
13.40	Northerly ROW fence for U.S. Highway 89, bears N 37° E and N 53°W
20.68	Point for the N 1/16 sec. cor. of secs. 32 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	25 ins. in the ground, with brass cap mkd.
	T22N R8E
	N 1/16
	S32 S33
	1987
	from which
	A ponderosa pine, 10 ins. diam., bears N 40 3/4° E,
	195.5 lks. dist., mkd. N 1/16 S33 BT.
	A ponderosa pine, 12 ins. diam., bears N 52 1/4° W,
	117.5 lks. dist., mkd. N 1/16 S32 BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic
	case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
	Cor. is located 4 lks. S of a fence, bears E and W.
30.57	Point for cor. 3, lot 1, sec. 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<div style="text-align: center; margin-bottom: 20px;"> <p>T22N R8E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S32</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">COR 3</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">Lot 1</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 33</td> </tr> </table> <p>1987</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 14 lks. W of a fence cor. fences extend N and S 79° E.</p> <p>31.02 The N-N 1/64 sec. cor. of secs. 32 and 33, identical with cor. 12, Tract A, HES 373, and cor. 2, lot 1, sec. 33, monumented with a granite stone, 22 x 16 x 8 ins., projecting 16 ins. above the ground, marks visible HES 373 on NE face and a cross on top, from which a 1915 bearing tree</p> <p style="margin-left: 40px;">A ponderosa pine, 20 ins. diam., bears S 37°03' W, 122 lks. dist., marks visible through partially healed blaze HES 373.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-bottom: 20px;"> <p>N-N 1/64</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 32</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 33</td> </tr> </table> <p>1987</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury original stone alongside the cor.</p> <p>A steel fence post is alongside the cor.</p> <p>Cor. is located 15 lks. W of an old barn in an automobile wrecking yard.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N 0°41' E, beginning new measurement.</p>	S32		COR 3			Lot 1			S 33	S 32		S 33
S32		COR 3											
		Lot 1											
		S 33											
S 32		S 33											

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS											
10.34	<p>The cor. of secs. 28, 29, 32, and 33, identical with Cor. 1, HES 373, monumented with an iron post, 2 1/2 ins. diam., projecting 4 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td colspan="2">T22N R8E</td> </tr> <tr> <td>S29</td> <td> S28</td> </tr> <tr> <td colspan="2">— —</td> </tr> <tr> <td>S32</td> <td> S33</td> </tr> <tr> <td colspan="2">1966</td> </tr> </table> </div> <p>from which a 1915 bearing tree</p> <p style="padding-left: 40px;">A pine stump, 14 ins. diam., bears N 89 3/4° W, 268 lks. dist., illegible scribe marks. (Record: S 89 1/2° W)</p> <p>and from which a new bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S 30° W, 339.5 lks. dist., mkd. T22N R8E S32 BT.</p> <p>A granite stone 10 x 10 ins. projecting 12 ins. above the ground, marks visible 1-373 on E face, is alongside the cor., bury the stone alongside the cor.</p> <p>Add the marks 1987 to the brass cap.</p> <p>Cor is located 2 lks. N of a fence cor., fences extend E, S and W.</p>	T22N R8E		S29	S28	— —		S32	S33	1966	
T22N R8E											
S29	S28										
— —											
S32	S33										
1966											
40.15	<hr/> <p style="text-align: center;">Restoring the survey by O.D. Wheeler, in 1883.</p> <hr/> <p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>West, bet. secs. 28 and 33.</p> <p>Over nearly level land, along Burris Road.</p> <p>The 1/4 sec. cor. of secs. 28 and 33, monumented with an iron post, 2 1/2 ins. diam., projecting 3 ins. above the ground, with brass cap mkd.</p>										

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T22N R8E 1/4 <u>S28</u> S33 1966</p> <p>from which a 1915 bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 34 ins. diam., bears N 78 1/2° E, 144 lks. dist., illegible scribe marks visible through partially healed blaze.</p> <p>A steel fence post is alongside the cor.</p> <p>Cor. is located 25 lks. N of center of Burris Road, bears E and W and 44 lks. S of an E and W fence.</p> <hr style="width: 20%; margin: 20px auto;"/> <p style="text-align: center;">Restoring the resurvey by R.P.A. Johnson in 1915</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S 89 22' W, beginning new measurement.</p>
10.105	<p>The E-W 1/64 sec. cor. of secs. 28 and 33, identical with cor. 29, Tract C, HES 373, monumented with a rebar, 14 ins. long, 1/2 in. diam., and a rebar, 16 ins. long, 3/8 in. diam., 6 ins. below ground from which an original bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 33 ins. diam., bears S 32°16' W, 66 lks. dist., marks 3 HES BT visible through partially healed blaze .</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below ground, with brass cap mkd.</p> <p style="text-align: center;">S 28 E-W 1/64 S33 1987</p> <p>from which new bearing objects</p> <p style="padding-left: 40px;">A power pole, bears N 1 1/4° E, 52 lks. dist., mkd. NTP 1755.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>A fence cor., bears N 75 3/4° W, 35 lks. dist., fences extend N and W.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit both local cors. inside the stainless steel post.</p> <p>Cor. is located 24 lks. N of Burris Road, bears E and W.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S 89°22' W, beginning new measurement.</p> <p>7.66 Cor. 27, Tract C, HES 373, monumented with a bolt, 16 ins. long, 5/8 in. diam., 6 ins. below ground and a rebar, 14 ins. long, 3/4 in. diam., 34 ins. below ground alongside, origins and dates unknown and are accepted as a careful and faithful determination of the position of the corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 1/2 in. diam., 8 ins. below Burris Road, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p>from which a bearing object</p> <p>The SW cor. of a building of block construction, bears N 24° 55' E, 76 lks. dist., walls extend N 35° E and S 55° E.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit both local cors. inside the stainless steel post.</p> <hr style="width: 20%; margin: 20px auto;"/>
--------	--

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>S 89°22' W, beginning new measurement.</p> <p>0.575 Point for cor. 23, Tract B, HES 373, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set a cut off stainless steel post, 8 ins. long, 2 1/2 ins. diam., 1 in. below surface of Burris Road, with brass cap mkd.</p> <div style="text-align: center;"> </div> <p>from which a bearing object</p> <p style="padding-left: 40px;">The SW cor. of a building of block construction, bears N 52°07' E, 113.5 lks. dist., walls extend N 35° E and S 55° E.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>2.46 Point for the W 1/16 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T22N R8E</p> <p>W 1/16 $\frac{S28}{S33}$</p> <p>1987</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on shoulder of road, 86 lks. W of center of U.S. Highway 89 and 67 lks. E of a ROW fence; road and fence bear N 40° E and S 40° W.</p>
--------	--

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>6.35 Cor. 14, Tract B, HES 373, monumented with a rebar, 18 ins. long, 1/2 in. diam., projecting 3 ins. above the ground, origin and date unknown and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit local cor. inside stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in an open field, 7.5 lks. N of an E and W fence.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S 89°22' W, beginning new measurement.</p> <p>0.550 Cor. 9, Tract A, HES 373, monumented with a rebar, 17 ins. long, 5/8 in. diam., 2 ins. below ground, with a yellow plastic cap attached and mkd. RLS 9078. This cor. was set by Joseph E. Costa, LS 9078, of unknown date, with original granite stone 16 x 12 x 8 ins., 4 ins. below ground in a disturbed position, marks visible is a cross, other marks were destroyed by farm machinery.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
--------	---

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit local cor. inside stainless steel post and bury original stone alongside.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 7.5 lks. N of an E and W fence.</p> <hr/> <p>S 89°22' W, beginning new measurement.</p>
1.42	A local cor., monumented with a rebar, 1/2 in. diam., projecting 3 ins. above the ground, with a yellow plastic cap attached and mkd. RLS 9078.
15.82	The cor. of secs. 28, 29, 32, and 33.
	<hr/> <p>Restoring the retracement by R.P.A. Johnson in 1915.</p> <hr/> <p>N 1°01' W, bet. secs. 28 and 29, identical with line 1-2, Tract A, HES 373.</p> <p>Over gently rolling land, through medium ponderosa pine.</p>
10.21	The S-S 1/64 sec. cor. of secs. 28 and 29, monumented with an U.S. Department of Agriculture iron post, 2 1/2 ins. diam., projecting 3 ins. above the ground. This cor. was reestablished by Charles C. Doak, LS 4476, in 1968, and is accepted as a careful and faithful determination of the position of the cor., with brass cap and mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">TRACT A T22N R8E _____ 2 S29 HES 373 LS 4476 1968</p> <p>A steel fence post is alongside the cor.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N 1°01' W, beginning new measurement.</p>
10.20	<p>Point for the S 1/16 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E S 1/16 S29 S28 1987</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S 68° E, 27 lks. dist., mkd. S 1/16 S28 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S 66 1/4° W, 63.5 lks. dist., mkd. S 1/16 S29 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 4 chs. N of a draw, drains N 40° E.</p>
30.60	<p>The 1/4 sec. cor. of secs. 28 and 29, monumented with an iron post, 2 1/2 ins. diam., projecting 3 ins. above the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p style="text-align: center;">T22N R8E 1/4 S29 S28 1972</p> <p>from which the 1972 bearing trees</p> <p style="margin-left: 40px;">A ponderosa pine, 12 ins. diam., bears N 47 1/2° E, 5.5 lks. dist., mkd. T22N R8E 1/4 S28 BT. (Record: N 44 1/2° E, 5.0 lks. dist.)</p> <p style="margin-left: 40px;">A ponderosa pine, 16 ins. diam., bears N 73° W, 77 lks. dist., mkd. T22N R8E 1/4 S29 BT.</p> <p>A mound of stone, 3 ft. base, 2 ft. high, is W of cor. Cor. is located 164 lks. W of a fence, bears N and S.</p> <hr/> <p style="text-align: center;">Restoring the survey executed by O.D. Wheeler in 1883.</p> <hr/> <p>N 2°10' E, beginning new measurement.</p> <p>40.04 The cor. of secs. 20, 21, 28, and 29, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E S20 S21 ----- S29 S28 1972</p> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A burnt out pine stump, 32 ins. diam., bears N 78° E, 125.5 lks dist., no marks visible. (1972 Record: N 61° E, 110 lks. dist.)</p> <p style="margin-left: 40px;">A burnt out pine stump, 32 ins. diam., bears N 67 1/2° W, 135 lks. dist., no marks visible. (1972 Record: 132 lks. dist.)</p>
--------	---

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	and from which the 1972 bearing trees
	A burnt out ponderosa pine stump, 19 ins. diam., bears N 3 1/2° E, 55 lks. dist., no marks visible. (Record: N 4 1/2° E, 56 lks. dist.)
	A dead and down burnt out ponderosa pine stump, 14 ins. diam., bears S 62° E, 19 lks. dist., no marks visible.
	A dead and down burnt out ponderosa pine, 10 ins. diam., bears S 52° W, 45 lks. dist., marks visible TNR8E S29.
	and from which new bearing trees
	A ponderosa pine, 11 ins. diam., bears N 21 1/2° E, 364.5 lks. dist., mkd. T22N R8E S21 BT.
	A ponderosa pine, 16 ins. diam., bears N 88° W, 233 lks. dist., mkd. T22N R8E S20 BT.
	Add the marks 1987 to the cap
	Cor. is located on a slope, 155 lks. S of a draw draining N 65° E.
	From the cor. of secs. 21, 22, 27, and 28.
	S 89°57' W, bet. secs. 21 and 28.
	Over nearly level land, along S side of Silver Saddle Road, through scattered ponderosa pine.
11.73	A local cor. monumented with a 3/8 in. rebar, projecting 1 in. above the ground, with a yellow plastic cap mkd. RLS 11755.
14.75	Center of U.S. Highway 89, bears N 24° E and S 24° W.
19.925	The E 1/16 sec. cor. of secs. 21 and 28, monumented with an open end pipe, 25 ins. long, 3/4 in. diam., projecting 3 ins. above the ground, origin and date unknown and is accepted as a careful and faithful determination of the position of the corner.

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E E 1/16 $\frac{S21}{S28}$ 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit local cor. inside the stainless steel post.</p> <p>Set steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S 89°57' W, beginning new measurement.</p>
19.965	<p>The 1/4 sec. cor. of secs. 21 and 28, monumented with a sandstone, 20 x 19 x 9 ins., projecting 9 ins. above the ground, mkd. 1/4 on N face and a cross on top. Record calls for a post, 3 ft. long, 3 ins. square, with a marked stone, 12 ins. in the ground. This stone was accepted as the best available evidence in the 1915 subdivision of sec. 28, executed by R.P.A. Johnson.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E 1/4 $\frac{S21}{S28}$ 1987</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 5 ins. diam., bears S 1 1/4° W, 146 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S 46 1/2° W, 246 lks. dist., mkd. 1/4 S28 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury original stone alongside the stainless steel post.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Set an aluminum fence post alongside the cor.</p> <p>Cor. is located at the S edge of a cultivated field; 56 lks. N of a fence cor., fences extend S 72° E, S 4° W and N 82° W; 14 lks. W of a track road, bears S 12° E and N 40° W; and 4.6 lks. N of an angle iron, 3 ins. x 2 1/2 in., projecting 4 ins. above the ground.</p> <hr/> <p>S 89°57' W, beginning new measurement.</p>
19.93	<p>The W 1/16 sec. cor. of secs. 21 and 28, monumented with an open end pipe, 23 ins. long, 3/4 in. diam., 2 ins. below ground. This cor. was established by Jesse D. Roeder, LS 2308, in 1959 and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T22N R8E S21 W 1/16 _____ S28 1987</p> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S 13 1/4° W, 200.5 lks. dist., mkd. W 1/16 S28 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N 26 1/2° W, 362.5 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit local cor. inside stainless steel post.</p> <p>Set a stainless steel fence post alongside cor.</p> <p>Cor. is located 6 lks. E of a fence cor., fences extend N and S 87° E; and 21 lks. E of a track road, bears S 30° E and N 18° W.</p> <hr/> <p>S 89°59' W, beginning new measurement.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
19.93	The cor. of secs. 20, 21, 28, and 29.
	<hr/> <p>N 0°11' W, bet. secs. 20 and 21.</p> <p>Over rolling land, through scattered alligator juniper, oak, ponderosa pine, pinyon, and cliff rose.</p>
19.98	<p>Point for the S 1/16 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E S 1/16 S 20 S 21 1987</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N 87 3/4° E, 266 lks. dist., mkd. S 1/16 S21 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S 41° W, 94 lks. dist., mkd. S 1/16 S20 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
39.96	<p>The 1/4 sec. cor. of secs. 20 and 21, monumented with an iron post, 2 1/2 ins. diam., projecting 24 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E 1/4 S20 S21 1972</p> <p>from which an 1883 bearing tree</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p> <p>10.30</p>	<p>A ponderosa pine, 39 ins. diam., bears N 68 1/4° E, 50 lks. dist., marks 1B visible through partially healed blaze. (1972 Record: N 67° E)</p> <p>and from which a 1972 bearing tree</p> <p>A ponderosa pine, 12 ins. diam., bears S 79 1/4° W, 39 lks. dist., mkd. T22N R8E S20 BT. (Record: S 78° W)</p> <p>Cor. is located on S side of a knoll.</p> <hr/> <p>N 0°04' E, beginning new measurement.</p> <p>The S-N 1/64 sec. cor. of secs. 20 and 21, monumented with a U.S. Department of Agriculture aluminum post, 2 1/2 ins. diam., projecting 5 ins. above the ground. This cor. was established by Wallace R. Ott, Forest Service Cadastral Surveyor, LS 9431, in 1975 and is accepted as a careful and faithful determination of the position of the cor., with an aluminum cap attached and mkd.</p> <p style="text-align: center;">S-N 1/64 LS 9431 1975</p> <p>from which the 1975 bearing trees</p> <p>A ponderosa pine, 24 ins. diam., bears S 18 1/4° E, 180.5 lks. dist., mkd. SN 1/64 BT.</p> <p>A ponderosa pine, 26 ins. diam., bears S 44° W, 132 lks. dist., mkd. SN 1/64 BT.</p> <p>Cor. is located 1.5 lks. S of an E and W fence and 35 lks. N of U.S. Forest Service Road 556, bears E and W.</p> <hr/> <p>N 0°06' E, beginning new measurement.</p>
----------------------------	---

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
10.29	<p>The N 1/16 sec. cor. of secs. 20 and 21, monumented with a rebar, 18 ins. long, 5/8 in. diam., flush with ground, with an aluminum cap attached and mkd. ARENCO PE 8218 LS 13010.. This cor. was established by C.W. Dryden, PE 8218 and LS 13010, of unknown date and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E N 1/16 S20 S21 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit the local cor. inside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 20px auto;"/>
5.16	<p>N 0°06' E, beginning new measurement.</p> <p>The S-N-N 1/256 sec. cor. of secs. 20 and 21, monumented with a U.S. Department of Agriculture aluminum post, 2 1/2 ins. diam., projecting 6 ins. above the ground. This cor. was established by Wallace R. Ott, Forest Service Cadastral Surveyor, LS 9431, in 1975 and is accepted as a careful and faithful determination of the position of the cor., with an aluminum cap attached and mkd.</p> <p style="text-align: center;">S-N-N 1/256 S 20 S 21 LS 9431 1975</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>from which the remains of the 1975 bearing trees</p> <p style="padding-left: 40px;">A pine stump, 24 ins. diam., bears N 78° W, 47.5 lks. dist., with burnt out blaze.</p> <p style="padding-left: 40px;">The root hole and the remains of a fallen tree, bears N 34° W, 78 lks. dist., no marks visible.</p> <p>and from which new bearing objects</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears N 3/4° W, 249.5 lks. dist., mkd. S-N-N 1/256 BT.</p> <p style="padding-left: 40px;">A fence cor., bears N 48 1/2° W, 4.5 lks. dist., fences extend N and W.</p> <p>Add the marks 1987 to the cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°05' E, beginning new measurement.</p> <p>5.15 The N-N 1/64 sec. cor. of secs. 20 and 21, monumented with a U.S. Department of Agriculture aluminum post, 2 1/2 ins. diam., projecting 6 ins. above the ground. This cor. was established by Wallace R. Ott, Forest Service Cadastral Surveyor, LS 9431, in 1975 and is accepted as a careful and faithful determination of the position of the cor., with an aluminum cap attached and mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>N-N 1/64 S20 S 21 LS 9431 1975</p> </div> <p>from which the remains of the 1975 bearing trees</p> <p style="padding-left: 40px;">The root hole of a fallen burnt tree, bears N 44° E, 46 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A ponderosa pine snag, 30 ins. diam., bears N 67 1/2° W, 81 lks. dist., mkd. N-N 1/64 BT.</p>
---------------	---

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 17 ins. diam., bears S 64° W, 158.5 lks. dist., with marks. T22N R8E visible in partially burnt out blaze. (Record: 150 lks. dist.)</p> <p>A root hole bears N 78° W, 113 lks. dist., lying alongside is a fallen ponderosa pine, 8 ins. diam., mkd. T22N R8E S17 BT. (Record: N 76° W)</p> <p>and from which new bearing trees</p> <p>A ponderosa pine, 13 ins. diam., bears N 19 1/2° E, 307 lks. dist., mkd. T22N R8E S16 BT.</p> <p>A ponderosa pine, 8 ins. diam., bears S 29 3/4° E, 205.5 lks. dist., mkd. T22N R8E S21 BT.</p> <p>A ponderosa pine, 9 ins. diam., bears N 6 1/2° W, 192.5 lks. dist., mkd. T22N R8E S17 BT.</p> <p>and from which</p> <p>A local monument, bears North, 3.8 lks. dist., monumented with an open end pipe, 1 1/2 in. diam., projecting 3 ins. above the ground.</p> <p>Add the marks 1987 to the cap.</p> <p>Cor. is located in a N and S fence.</p>
20.05	<p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>N 89°18' W, bet. secs. 16 and 21.</p> <p>Over gently rolling land, through moderate ponderosa pine.</p> <p>Point for the E 1/16 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T22N R8E S16 E 1/16 ——— S21 1987</p> <p>from which</p> <p>A ponderosa pine, 11 ins. diam., bears S 26 1/2° E, 49.5 lks. dist., mkd. E 1/16 S21 BT.</p> <p>A ponderosa pine, 6 ins. diam., bears N 5 1/2° W, 26.5 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
40.10	<p>The 1/4 sec. cor. of secs. 16 and 21, monumented with an iron post, 2 1/2 ins. diam., projecting 5 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E S16 1/4 ——— S21 1987</p> <p>from which the remains of an original bearing tree</p> <p>The remains of a burnt out stump, bears N 19 1/2° W, 28 lks. dist., no marks visible. (Record: N 7 1/2° W)</p> <p>and from which the 1972 bearing trees</p> <p>A ponderosa pine, 13 ins. diam., bears North, 107 lks. dist., with illegible scribe marks visible through partially healed blaze.</p> <p>A ponderosa pine, 18 ins. diam., bears S 49 3/4° E, 128 lks. dist., with marks NR visible through partially healed blaze. (1972 Record S 50 1/2° E)</p> <p>Cor. is located 175 lks. W of a fence, bears S 60° E and N 60° W.</p> <hr style="width: 20%; margin: 10px auto;"/>

Dependent Resurvey of a Portion of the Subdivisional Lines
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>N 89°50' W, beginning new measurement.</p>
20.04	<p>Point for the W 1/16 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E W 1/16 $\frac{S16}{S21}$ 1987</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N 60 3/4° E, 127.5 lks. dist., mkd. W 1/16 S16 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears S 80 3/4° E, 348.5 lks. dist., mkd. W 1/16 S21 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
40.08	<p>The cor. of secs. 16, 17, 20, and 21.</p> <hr/> <p style="text-align: center;">Dependent Resurvey, Tract D, HES 373, T 22 N, R 8 E, Gila and Salt River Mer., Arizona</p> <hr/> <p>From cor. 22, Tract B, HES 373, hereinbefore described.</p> <p>S 36°54' W, on line 22-23, Tract B, HES 373, identical with the boundary of the 1915 Tract D exemption.</p>
13.64	<p>Cor. 23, Tract B, HES 373, on line bet. secs. 28 and 33, hereinbefore described.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>

Dependent Resurvey, Tract D, HES 373,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	S 36°56' W, beginning new measurement on line 23-24, Tract B, HES 373, identical with the boundary of the 1915 Tract D exemption.
3.19	Intersect the N and S center line of the NW 1/4, sec. 33, at a point from which the W 1/16 sec. cor. of secs. 28 and 33, bears N 0°48' E, 2.53 chs. dist., hereinbefore described.
26.04	Cor. 24, Tract B, HES 373, hereinbefore described.
	<hr/> <p>N 89°28' E, on the boundary of the 1915 Tract D exemption, identical with a portion of the E and W center line of the NW 1/4 of sec. 33, bet. cor. 24, Tract B, HES 373 and cor. 26, Tract C, HES 373.</p>
0.580	Cor. 26, Tract C, HES 373, hereinbefore described.
	<hr/> <p>N 36°55.5' E, on line 26-27, Tract C, HES 373, identical with the boundary of the 1915 Tract D exemption.</p>
21.87	Intersect the N and S center line of the NW 1/4, of sec. 33, at a point from which the W 1/16 sec. cor. of secs. 28 and 33, bears N 0°48'E, 3.308 chs. dist., hereinbefore described.
26.04	Cor. 27, Tract C, HES 373, bet. secs. 28 and 33, hereinbefore described.
	<hr/> <p>N 36°52' E, beginning new measurement on line 27-28, Tract C, HES 373, identical with the boundary of the 1915 Tract D, exemption.</p>
12.705	Cor. 28, Tract C, HES 373, on the N and S center line of the SE 1/4 of the SW 1/4, of sec. 28, hereinafter described.
	<hr/> <p>N 0°33' W, on the boundary of the 1915 Tract D, exemption, identical with a portion of the N and S center line of the SE 1/4 of the SW 1/4, of sec. 28, bet. cor. 28, Tract C, HES 373, and cor. 22, Tract B, HES 373.</p>
0.735	Cor. 22, Tract B, HES 373, point of beginning.

Survey of Subdivisions in Section 21
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 21 and 28.</p> <p>N 0°07' E, on the N and S center line of sec. 21.</p>
20.00	<p>Point for the center S 1/16 sec. cor. of sec. 21</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 3 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E C S 1/16 S 21 C 1987</p>
35.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 45 lks. N of Forest Dr. Road, bears E and W.</p> <p>The center N-N-S 1/256 sec. cor. of sec. 21, monumented with an iron pipe, 24 ins. long, 1 1/2 in. diam., 2 ins. below ground. this cor. was established by Jesse D. Roeder, LS 2308, in 1959 and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 21 C-N-N-S 1/256 1987</p>

Survey of Subdivisions in Section 21
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N 72 3/4° E, 150 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears N 20 3/4° W, 146 lks. dist., mkd. C-N-N-S 1/256 S21 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit local cor. inside the stainless steel post.</p> <p>Cor. is located in an E and W fence.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°08' E, beginning new measurement.</p> <p>5.00 The center 1/4 sec. cor. of sec. 21, monumented with an open end pipe, 24 ins. long, 2 ins. diam., projecting 3 ins. above the ground, in a mound of stone, 1 ft. base, 1/2 ft. high. This cor. was established by Jesse D. Roeder, LS 2309, in 1959 and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E C 1/4 S 21 1987</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears N 32° E, 32.5 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears N 75 3/4° W, 31.5 lks. dist., mkd. C 1/4 S21 BT.</p>
--------	--

Survey of Subdivisions in Section 21
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit the local cor. inside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located at the end of an abandoned fence, extending S only, 15 lks. N of a track road, bears E and W; and 55 lks. S of a track road, bears S 60° E and N 60° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°08' E, beginning new measurement.</p>
20.515	<p>Point for the center N 1/16 sec. cor. of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T22N R8E C N 1/16 S 21 C 1987</p> </div> <p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 9 ins. diam., bears S 35 1/2° E, 54 lks. dist., mkd. C-N 1/16 S21 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 7 ins. diam., bears N 55° W, 28 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
41.03	<p>The 1/4 sec. cor. of secs. 16 and 21.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 21 and 22.</p>

Survey of Subdivisions in Section 21
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>S 89°55' W, on the E and W center line of sec. 21.</p> <p>Over nearly level land, through moderate ponderosa pine.</p> <p>20.145 Point for the center E 1/16 sec. cor. of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T22N R8E E 1/16</p> <p>C—————C</p> <p>S 21 1987</p> </div> <p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 10 ins. diam., bears S 21 1/4° E, 96 lks. dist., mkd. X at breast height and BT at base.</p> <p style="margin-left: 40px;">A ponderosa pine, 12 ins. diam., bears N 77 1/2° W, 119.5 lks. dist., mkd. C-E 1/16 S21 BT.</p> <p style="margin-left: 40px;">A local cor., bears S 14° E, 4.3 lks. dist., monumented with a rebar, 5/8 in. diam., with an aluminum cap attached, no marks.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>40.29 The center 1/4 sec. cor. of sec. 21.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S 89°56' W, beginning new measurement.</p> <p>10.025 Point for the center E-W 1/64 sec. cor. of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>
--------	--

Survey of Subdivisions in Section 21
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p style="text-align: center;">S 21 C-E-W 1/64 1987</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S 40 3/4° E, 36.5 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N 30° W, 29 lks. dist., mkd. C-E-W 1/64 S21 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 3 lks. W of a fence cor., fences extend S and W; and 13 lks. S of a track road, bears E and W.</p> <p>20.05 The center W 1/16 sec. cor. of sec. 21, monumented with an open end pipe, 22 ins. long, 1 1/2 ins. diam., projecting 3 ins. above the ground. This cor. was established by Jesse D. Roeder, LS 2308, in 1959 and is accepted as a careful and faithful determination of the position of the original cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E W 1/16 C———C S 21 1987</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears S 62 3/4° W, 241 lks. dist., mkd. C-W 1/16 S21 BT.</p>
--------	--

Survey of Subdivisions in Section 21
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p> <p>20.005</p>	<p>A ponderosa pine, 9 ins. diam., bears N 8 1/4° W, 61 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit the local cor. inside the stainless steel post.</p> <p>Cor. is located 2 lks. SE of a fence cor., fences extend N, E and S; and 70 lks. S of a wash, 15 lks. wide, 4 ft. deep, drains SE.</p> <hr/> <p>S 89°54' W, beginning new measurement.</p> <p>The 1/4 sec. cor. of secs. 20 and 21.</p>
<p>20.005</p>	<p style="text-align: center;">SE 1/4 of Section 21</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 21 and 28.</p> <p>N 0°24' E, on the N and S center line of the SE 1/4 of sec. 21.</p> <p>Over nearly level land through moderate ponderosa pine.</p> <p>The SE 1/16 sec. cor. of sec. 21, monumented with an open end pipe, 26 ins. long, 1 1/2 ins. diam., 1 in. below ground. This cor. was established by Jesse D. Roeder, LS 2308, in 1959 and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E SE 1/16 S 21 1987</p>

Survey of Subdivisions in Section 21
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which a bearing object</p> <p style="padding-left: 40px;">A power pole, bears S 19 1/4° E, 6 lks. dist., mkd. PS 181515.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit local cor. inside the stainless steel post.</p> <p>Cor. is located 2 lks. SW of a fence cor., fences extend N and E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°21' E, beginning new measurement.</p>
<p>15.01</p>	<p>Point for the center N-N-SE 1/256 sec. cor. of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 21 C-N-N-SE 1/256 1987</p>
	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears N 74 1/4° E, 26 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A ponderosa pine, 25 ins. diam., bears N 5 3/4° W, 83.5 lks. dist., mkd. C-N-N-SE 1/256 S21 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located in an E and W fence.</p>
<p>20.01</p>	<p>The center E 1/16 sec. cor. of sec. 21.</p> <hr style="width: 20%; margin: 10px auto;"/>

Survey of Subdivisions in Section 21
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>From the S 1/16 sec. cor. of secs. 21 and 22.</p> <p>S 89°56.5' W, on the E and W center line of the SE 1/4 of sec. 21.</p> <p>Over nearly level land, through moderate ponderosa pine.</p>
20.03	<p>The SE 1/16 sec. cor. of sec. 21.</p> <hr/> <p>S 89°56.5' W, beginning new measurement.</p>
20.06	<p>The center S 1/16 sec. cor. of sec. 21.</p> <hr/> <p style="text-align: center;">NE 1/4 of the SE 1/4 of Section 21</p> <hr/>
20.115	<p>From the N-N-S 1/256 sec. cor. of secs. 21 and 22.</p> <p>S 89°56' W, on the E and W center line of the N 1/2 of the NE 1/4 of SE 1/4 sec. 21.</p> <p>The center N-N-SE 1/256 sec. cor. of sec. 21</p> <hr/> <p style="text-align: center;">NW 1/4 of the SE 1/4 of section 21</p> <hr/>
20.125	<p>From the center N-N-SE 1/256 sec. cor. of sec. 21</p> <p>S 89°55' W on the E and W center line of the N 1/2 of the NW 1/4 of the SE 1/4 of sec. 21.</p> <p>The center N-N-S 1/256 sec. cor. of sec. 21.</p> <hr/> <p style="text-align: center;">SW 1/4 of Section 21</p> <hr/>
19.99	<p>From the W 1/16 sec. cor. of secs. 21 and 28.</p> <p>N 0°03.5' W, on the N and S center line of the SW 1/4 of sec. 21.</p> <p>Over rolling land, through moderate ponderosa pine.</p> <p>The SW 1/16 sec. cor. of sec. 21, monumented with an open end pipe, 6 ins. long, 1 1/2 ins. diam., flush with ground. This cor. was established by Flagstaff Engineering Co. of unknown date and is accepted as a careful and faithful determination of the position of the cor.</p>

Survey of Subdivisions in Section 21
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E SW 1/16 S21 1987</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S 46° W, 42 lks. dist., mkd. SW 1/16 S21 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N 72° W, 15 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p style="text-align: center;">_____</p> <p>N 0°03.5' W, beginning new measurement.</p> <p>19.995 The center W 1/16 sec. cor. of sec. 21.</p> <p style="text-align: center;">_____</p> <p>From the center S 1/16 sec. cor. of sec. 21.</p> <p>S 89°57' W, on the E and W center line of the SW 1/4 of sec. 21.</p> <p>Over gently rolling land, through scattered ponderosa pine.</p> <p>19.99 The SW 1/16 sec. cor. of sec. 21.</p> <p style="text-align: center;">_____</p> <p>S 89°57' W, beginning new measurement.</p> <p>19.97 The S 1/16 sec. cor. of secs. 20 and 21.</p> <p style="text-align: center;">_____</p> <p style="text-align: center;">NE 1/4 of the SW 1/4 of Section 21</p> <p style="text-align: center;">_____</p>
--------	--

Survey of Subdivisions in Section 21
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>From the center N-N-S 1/256 sec. cor. of sec. 21.</p> <p>S 89°56' W, on the E and W center line of the NE 1/4 of the NE 1/4 of SW 1/4 of sec. 21.</p> <p>9.995 The center N-NE-SW 1/256 sec. cor. of sec. 21, monumented with an open end pipe, 24 ins. long, 1 1/2 ins. diam., flush with ground. This cor. was established by Jesse D. Roeder, LS 2308, in 1959 and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 21 C-N-NE-SW 1/256 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit local cor. inside the stainless steel post.</p> <p>Cor. is located 1 lk. SW of a fence cor., fences extend N and E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°13.5' W, beginning new measurement on a portion of the N and S center line of the NE 1/4 of the SW 1/4 of sec. 21.</p> <p>5.00 The center E-W 1/64 sec. cor. of sec. 21.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">NW 1/4 of Section 21</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the center W 1/16 sec. cor. of sec. 21.</p>
--------	--

Survey of Subdivisions in Section 21
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p> <p>20.55</p> <p>41.11</p>	<p>N 0°08' E, on the N and S center line of the NW 1/4 of sec. 21.</p> <p>Over gently rolling land, through moderate ponderosa pine.</p> <p>Point for the NW 1/16 sec. cor. of sec. 21, at intersection with the E and W center line of the NW 1/4 of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E NW 1/16 S21 1987</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N 32° E, 79.5 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S 82 1/4° E, 35.5 lks. dist., mkd. NW 1/16 S21 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>The W 1/16 sec. cor. of secs. 16 and 21.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>From the center N 1/16 sec. cor. of sec. 21.</p> <p>N 89°58' W, on the E and W center line of the NW 1/4 of sec. 21.</p> <p>Over nearly level land, through scattered ponderosa pine.</p>
---	---

Survey of Subdivisions in Section 21
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
20.045	The NW 1/16 sec. cor. of sec. 21.
25.055	Point for the center E-W-NW 1/256 sec. cor. of sec. 21.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	S21 C-E-W-NW 1/256 1987
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located in a N and S fence.
40.075	The N 1/16 sec. cor. of secs. 20 and 21.
	<hr/> SW 1/4 of the NW 1/4 of Section 21 <hr/>
	From the S-N 1/64 sec. cor. of secs. 20 and 21.
	East, on a portion of the E and W center line of the SW 1/4 of the NW 1/4 of sec. 21.
15.03	The center E-SW-NW 1/256 sec. cor. of sec. 21, monumented with a U.S. Department of Agriculture aluminum post, 2 1/2 ins. diam., projecting 2 ins. above the ground. This cor. was established by Wallace R. Ott, Forest Service Cadastral Surveyor, LS 9431, in 1975 and is accepted as a careful and faithful determination of the position of the cor., with an aluminum cap attached and mkd.
	S 21 C-E-SW-NW 1/256 LS 9431 1975

Survey of Subdivisions in Section 21
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>from which the 1975 bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears N 26° E, 78.5 lks. dist., with marks /256 S21 BT visible through partially healed blaze. (Record: 79.4 lks. dist.)</p> <p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears S 52 1/4° E, 163.5 lks. dist., mkd. 1/256 S21 BT. (Record: S 49° E)</p> <p>Cor. is located 2 lks. NW of a fence cor., fences extend N, S 45° E and W; and 30 lks. N of USFS Road 556, bears E and W.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N 0°01' E, beginning new measurement on the N and S center line of the NE 1/4 of the SW 1/4 of the NW 1/4 of sec. 21.</p> <p>10.28 The center E-W-NW 1/256 sec. cor. of sec. 21.</p> <hr style="width: 20%; margin: 20px auto;"/> <p style="text-align: center;">NW 1/4 of the NW 1/4 of Section 21</p> <hr style="width: 20%; margin: 20px auto;"/> <p>From the center E-W-NW 1/256 sec. cor. of sec. 21.</p> <p>N 0°09' E, on the N and S center line of the SE 1/4 of the NW 1/4 of the NW 1/4 of sec. 21.</p> <p>10.29 The center E-NW-NW 1/256 sec. cor. of sec. 21, monumented with a U.S. Department of Agriculture aluminum post, 2 1/2 ins. diam., projecting 5 ins. above the ground, in a mound of stone, 2 ft. base, to top. This cor. was established by Wallace R. Ott, Forest Service Cadastral Surveyor, LS 9431, in 1975 and is accepted as a careful and faithful determination of the position of the cor., with an aluminum cap attached and mkd.</p> <p style="text-align: center;">S 21 C-E-NW-NW 1/256 LS 9431 1975</p>
--------	---

Survey of Subdivisions in Section 21
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>from which the 1975 bearing trees</p> <p>A ponderosa pine, 25 ins. diam., bears S 49° E, 12 lks. dist., mkd. 1/256 S21 BT.</p> <p>An oak stump, 7 ins. diam., bears North, 68 lks. dist., no marks visible. (Record: N 6° W, 67 lks. dist.)</p> <p>and from which a new bearing tree</p> <p>A ponderosa pine, 7 ins. diam., bears N 61 1/4° W, 234.5 lks. dist., mkd. X at breast height and BT at base.</p> <p>Add the marks 1987 to the cap.</p> <p>Cor. is located at the cor. of a fence, fences extend S and W.</p> <hr/> <p>N 89°53' W, beginning new measurement on a portion of the E and W center line of the NW 1/4 of the NW 1/4 of sec. 21.</p> <p>15.03 The N-N 1/64 sec. cor. of secs. 20 and 21.</p>
	<p style="text-align: center;">Survey of Subdivisions in Section 22 T 22 N, R 8 E, Gila and Salt River Mer., Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 22 and 27.</p> <p>N 0°28' E, on the N and S center line of sec. 22.</p> <p>Over gently rolling land, through medium ponderosa pine.</p> <p>20.055 Point for the center S 1/16 sec. cor. of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>

Survey of Subdivisions in Section 22
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 22 and 23, monumented with a stainless steel post, mkd. and referenced as described in the field notes of the resurvey executed in 1986 under this same group.</p> <p>S 89°49' W, on the E and W center line of sec. 22.</p> <p>Over gently rolling land, through medium ponderosa pine.</p> <p>4.91 Point for the center E-E-E 1/256 sec. cor. of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 22 C-E-E-E 1/256 1987</p> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 8 ins diam., bears N 4° E, 69.5 lks. dist., mkd. C-E-E-E 1/256 S22 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S 86 1/4° W, 84.5 lks. dist., mkd. C-E-E-E 1/256 S22 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, N of cor.</p> <p>Set a steel fence post alongside the cor.</p>
19.645	<p>Point for the center E 1/16 sec. cor. of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E E 1/16 C—C S 22 1987</p>

Survey of Subdivisions in Section 22
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A pinyon, 8 ins. diam., bears N 55 3/4° E, 44 lks. dist., mkd. X at breast height and BT at base.</p> <p>A pinyon, 9 ins. diam., bears N 36 1/4° W, 51 lks. dist., mkd. CE 1/16 S22 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>39.29 The center 1/4 sec. cor. of sec. 22.</p> <p>78.94 The 1/4 sec. cor. of secs. 21 and 22.</p>
	<hr/> <p style="text-align: center;">SE 1/4 of Section 22</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 22 and 27.</p> <p>N 0°05.5' E, on the N and S center line of the SE 1/4 of sec. 22.</p> <p>20.08 Point for the SE 1/16 sec. cor. of sec. 22, at intersection with the E and W center line of the SE 1/4 of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E SE 1/16 S 22 1987</p> <p>from which</p> <p>A ponderosa pine, 13 ins. diam., bears S 66 1/4° E, 40 lks. dist., mkd. SE 1/16 S22 BT.</p> <p>A ponderosa pine, 9 ins. diam., bears N 34 3/4° W, 36 lks. dist., mkd. X at breast height and BT at base.</p>

Survey of Subdivisions in Section 22
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
40.16	<p>The center E 1/16 sec. cor. of sec. 22.</p> <hr/>
	<p>From the S 1/16 sec. cor. of secs. 22 and 23, monumented with a stainless steel post, mkd. and referenced as described in the field notes of the resurvey executed in 1986 under this same group.</p> <p>S 89°53' W, on the E and W center line of the SE 1/4 of sec. 22.</p>
4.945	<p>Point for the center E-E-SE 1/256 sec. cor. of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S 22 C-E-E-SE 1/256 1987</p>
	<p>from which</p> <p style="text-align: center;">A ponderosa pine, 8 ins. diam., bears S 35° W, 309.5 lks. dist., mkd. C-E-E-SE 1/256 S22 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
19.775	<p>The SE 1/16 cor. of sec. 22.</p>
39.55	<p>The center S 1/16 sec. cor. of sec. 22.</p>
	<hr/> <p style="text-align: center;">NE 1/4 of the SE 1/4 of Section 22</p> <hr/>

Survey of Subdivisions in Section 22
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>From the center E-E-SE 1/256 sec. cor. of sec. 22.</p> <p>N 0°10' W, on the N and S center line of the E 1/2 of the NE 1/4 of the SE 1/4 of sec. 22.</p>
20.09	<p>The center E-E-E 1/256 sec. cor. of sec. 22.</p>
	<p style="text-align: center;">_____</p> <p style="text-align: center;">SE 1/4 of the SE 1/4 of Section 22</p> <p style="text-align: center;">_____</p>
	<p>From the E-E 1/64 sec. cor. of secs. 22 and 27.</p> <p>N 0°04' W, on a portion of the N and S center line of the SE 1/4 of the SE 1/4 of sec. 22.</p>
10.045	<p>Point for the SE-SE 1/64 sec. cor. of sec. 22.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S 22 SE-SE 1/64 1987</p>
	<p>from which</p>
	<p>A ponderosa pine, 11 ins. diam., bears N 42 3/4° E, 80 lks. dist., mkd. SE-SE 1/64 S22 BT.</p>
	<p>A fence cor. of a wooden fence, bears N 72°34' E, 172 lks. dist., fences extend E and S.</p>
	<p>The NW cor. of a wood frame building, 62.5 ft. x 14.5 ft., bears N 83°26' E, 304.5 lks. dist., sides extend S 78° E and S 12° W.</p>
	<p>A ponderosa pine, 8 ins. diam., bears N 76° W, 205.5 lks. dist., mkd. X at breast height and BT at base.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post alongside the cor.</p> <p style="text-align: center;">_____</p>

Survey of Subdivisions in Section 22
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
4.96	<p>N 89°54.5' E, on a portion of the E and W center line of the SE 1/4 of the SE 1/4 of sec. 22.</p> <p>Point for the center E-SE-SE 1/256 sec. cor. of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S22 C-E-SE-SE 1/256 1987</p> <p>from which</p> <p style="padding-left: 40px;">The NE cor. of a wood frame building, 62.5 ft. x 14.5 ft., bears N 79°54' W, 176 lks. dist., sides extend S 12° W and N 78° W.</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears N 36 1/4° W, 29 lks. dist., mkd. C-E-SE-SE 1/256 S22 BT.</p> <p style="padding-left: 40px;">The SW cor. of a building, 17 ft. x 17 ft., bears N 3°14' W, 216.5 lks. dist., sides extend N 82° E and N 8° W.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°11' W, on the N and S center line of the NE 1/4 of the SE 1/4 of the SE 1/4 of sec. 22.</p>
10.045	<p>The center E-E-SE 1/256 sec. cor. of sec. 22</p> <hr/> <p style="text-align: center;">Survey of Subdivisions in Section 27 T 22 N, R 8 E, Gila and Salt River Mer., Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 27 and 34.</p> <p>N 0°14' E, on the N and S center line of sec. 27.</p>

Survey of Subdivisions in Section 27
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Over nearly level open land.</p> <p>5.215 The center S-S-S 1/64 sec. cor. of sec. 27, monumented with a rebar, 28 ins. long, 5/8 in. diam., 1 in. below ground, origin and date unknown and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S-S-S 1/256 C S27</p> <p> </p> <p> C</p> <p> 1987</p> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 17 ins. diam. bears S 26° E, 103.5 lks. dist., mkd. C-S-S-S 1/256 S27 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit local cor. inside the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high E of cor.</p> <p>A steel fence post is alongside the cor.</p> <p>Cor. is located 18 lks. E of center of a N and S graded gravel road.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N 0°08' E, beginning new measurement.</p>
15.66	<p>The center S 1/16 sec. cor. of sec. 27, monumented with a rebar, 15 ins. long, 5/8 in. diam., flush with ground, with a section of fence post, 26 ins. long, alongside the cor., flush with ground. This cor. was established by Ramsey and Associates in 1972 and is accepted as a careful and faithful determination of the position of the corner.</p>

Survey of Subdivisions in Section 27
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E C S 1/16 S 27 C 1987</p> <p>from which a bearing object</p> <p style="padding-left: 40px;">A power pole, bears S 5 3/4° W, 55 lks. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit local cor. inside stainless steel post and bury the fence post section alongside the cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 22 lks. E of center of a N and S graded gravel road; 2 lks. E of a N and S power line; and 39 lks. E of a fence cor., fences extend S and W.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N 0°11' E, beginning new measurement.</p>
20.875	<p>The center 1/4 sec. cor. of sec. 27, monumented with a rebar, 14 ins. long, 5/8 in. diam., 1 in. below ground, origin and date unknown and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E C 1/4 S 27 1987</p>

Survey of Subdivisions in Section 27
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>from which bearing objects</p> <p style="padding-left: 40px;">A power pole, bears S 4 1/2° W, 44.5 lks. dist., mkd. NTP 1832.</p> <p style="padding-left: 40px;">A cyclone fence cor., bears S 45 1/2° W, 86 lks. dist., fences extend S and W.</p> <p style="padding-left: 40px;">A fence cor., bears N 44 1/4° W, 44 lks. dist., fences extend N and W.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit local cor. inside the stainless steel post.</p> <p>A steel fence post is alongside the cor.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N 0°10' E, beginning new measurement.</p>
41.575	<p>The 1/4 sec. cor. of secs. 22 and 27.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 27, monumented with a stainless steel post, mkd. and referenced as described in the field notes of the resurvey executed in 1986 under this same group.</p> <p>N 87°44' W, on the E and W center line of sec. 27.</p> <p>Over nearly level open land.</p>
19.825	<p>The center E 1/16 sec. cor. of sec. 27, monumented with a rebar, 15 ins. long, 5/8 in. diam., projecting 2 ins. above the ground, origin and date unknown and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of Subdivisions in Section 27
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>T22N R8E E 1/16</p> <p>C-----C</p> <p>S 27 1987</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit the local cor. inside the stainless steel post.</p> <p>A steel fence post is alongside the cor.</p> <p>Cor. is located 45 lks. E of a fence cor., fences extend S and W.</p> <p>From this point a rebar, 5/8 ins. diam., projecting 5 ins. above the ground, bears N 87°48' W, 0.225 chs. dist.</p>
	<p>_____</p>
	<p>N 87°48' W, beginning new measurement.</p>
19.81	<p>The center 1/4 sec. cor. of sec. 27.</p>
	<p>_____</p>
	<p>N 87°47' W, beginning new measurement.</p>
40.54	<p>The 1/4 sec. cor. of secs. 27 and 28.</p>
	<p>_____</p>
	<p>SE 1/4 of Section 27</p>
	<p>From the E 1/16 sec. cor. of secs. 27 and 34.</p> <p>N 0°18' E, on the N and S center line of the SE 1/4 of sec. 27.</p>
5.305	<p>Point for the center S-S-SE 1/256 sec. cor. of sec. 27.</p>

Survey of Subdivisions in Section 27
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 27 C-S-S-SE 1/256 1987</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam. bears N 84 1/4° E, 149 lks. dist., mkd. C-S-S-SE 1/256 S27 BT.</p> <p style="padding-left: 40px;">The SE cor. of an aluminum storage shed, bears S 80°30' W, 237 lks. dist., shed is 12 x 10 ft., walls extend N 26° E and N 64 ° W.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>From this point a local cor., bears S 80°32' E, 0.043 chs. dist., monumented with a rebar, 5/8 in. diam., projecting 6 ins. above the ground. This cor. was established by Charles W. Dryden, PE. 8218, Arizona in 1977 and is not utilized in the course of this survey.</p>
6.25	Rio De Flag Creek, 20 lks. wide, course N 40° E.
10.61	<p>Point for the center S-SE 1/64 sec. cor. of sec. 27, falls in a fence cor. where it is impracticable to set a monument, fences extend S and W.</p> <p>from which</p> <p style="padding-left: 40px;">An aluminum post, 36 ins. long, 3/4 in. diam., set 32 ins. in the ground for a reference monument, bears S 81°46' E, 35.3 ft. dist., with aluminum cap mkd. RM T22N R8E 35.3 FT TO COR S27 1987 and an arrow pointing to the cor.</p>

Survey of Subdivisions in Section 27
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
21.22	<p>An aluminum post, 32 ins. long, 3/4 in. diam., set 32 ins. in the ground for a reference monument, bears S 7°01' E, 28.4 ft. dist., with aluminum cap mkd. RM T22N R8E 28.4 FT TO COR S27 1987 and an arrow pointing to the cor.</p> <p>Set a steel fence post alongside both reference monuments.</p> <p>From this point a rebar, bears North, 0.092 chs. dist. Rebar is 5/8 in. diam., projecting 1 in. above the ground, with an aluminum cap attached and mkd. BIA, origin and date unknown and is not utilized in the course of this survey.</p> <p>Point for the SE 1/16 sec. cor. of sec. 27, at intersection with the E and W center line of the SE 1/4 of sec. 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. below surface of a road, bears E and W with brass cap mkd.</p> <p style="text-align: center;">T22N R8E SE 1/16 S 27 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>from which</p> <p>An aluminum post, 32 ins. long, 3/4 in. diam., set 32 ins. in the ground for a reference monument, bears S 3°16' E, 27.5 ft. dist., with aluminum cap mkd. RM T22N R8E 27.5 FT TO COR S27 1987. Reference monument is located at the cor. of fences extending E, S and W.</p> <p>An aluminum post, 32 ins. long, 3/4 in. diam., set 32 ins. in the ground for a reference monument, bears N 26°55' W, 31.9 ft. dist., with aluminum cap mkd. RM T22N R8E 31.9 FT TO COR S27 1987. Reference monument is located at the cor. of a fence, fences extend N and W.</p>

Survey of Subdivisions in Section 27
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>From this point a rebar, 1/2 in. diam., 6 ins. below ground, bears N 1°18' E, 35 lks. dist.</p>
	<p>From this same point an iron rod, 1 in. diam., projecting 3 ins. above the ground, bears S 0°34' W, 0.408 chs. dist.</p>
42.455	<p>The center E 1/16 sec. cor. of sec. 27.</p> <hr/>
	<p>From the S 1/16 sec. cor. of secs. 26 and 27, monumented with a stainless steel post, mkd. and referenced as described in the field notes of the resurvey executed in 1986 under this same group.</p>
	<p>N 86°44' W, on the E and W center line of the SE 1/4 of sec. 27.</p>
19.79	<p>The SE 1/16 sec. cor. of sec. 27.</p>
39.57	<p>The center S 1/16 sec. cor. of sec. 27.</p> <hr/>
	<p style="text-align: center;">SE 1/4 of the SE 1/4 of Section 27</p> <hr/>
	<p>From the S-S 1/64 sec. cor. of secs. 26 and 27, monumented with a stainless steel post, mkd. and referenced as described in the field notes of the resurvey executed in 1986 under this same group.</p>
	<p>N 86° 15' W, on the E and W center line of the SE 1/4 of the SE 1/4 of sec. 27.</p>
19.77	<p>The center S-SE 1/64 sec. cor. of sec. 27.</p> <hr/>
	<p style="text-align: center;">SW 1/4 of the SE 1/4 of Section 27</p> <hr/>
	<p>From the center S-S-SE 1/256 sec. cor. of sec. 27.</p>
	<p>N 85°59' W, on the E and W center line of the S 1/2 of the SW 1/4 of the SE 1/4 of sec. 27.</p>
19.75	<p>The center S-S-S 1/256 sec. cor. of sec. 27.</p> <hr/>

Dependent Resurvey of Subdivisions in Section 28,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">Restoring the Survey executed by R.P.A. Johnson in 1915</p> <hr style="width: 20%; margin: auto;"/> <p>From the 1/4 sec. cor. of secs. 28 and 33. N 0°06' E, on the N and S center line of sec. 28. Over gently rolling land, through scattered ponderosa pine.</p>
20.19	<p>Point for the center S 1/16 sec. cor. of sec. 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T22N R8E C S 1/16 S 28 C 1987</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
25.24	<p>The center S-N-S 1/256 sec. cor. of sec. 28, identical with cor. 18, Tract B, HES 373, at proportionate dist. there is no remaining evidence of the original cor. Cor. falls in U.S. Highway 89 ROW, not monumented.</p>
40.38	<p>The center 1/4 sec. cor. of sec. 28, identical with cor. 17, Tract B, HES 373, monumented with a granite stone, 26 x 15 x 15 ins., projecting 8 ins. above the ground, over broken glass, mkd. 17 HES 373 on the SW face and a cross on top, from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A pine stump, 36 ins. diam., bears S 32° W, 123.5 lks. dist., no mks. visible. (Record: S 32°51' W, 120 lks. dist.)</p> <p style="margin-left: 40px;">The NW tree is a pine snag, 20 ins. diam., lying loose and unable to determine its true location, mks. visible TB. (Record: N 81°09' W, 95 lks. dist.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p>

Dependent Resurvey of Subdivisions in Section 28,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T22N R8E C 1/4 S 28 1987</p> <p>from which new bearing trees</p> <p>A ponderosa pine, 14 ins. diam. bears N 55 3/4° W, 200.5 lks. dist., mkd C 1/4 S28 BT.</p> <p>A ponderosa pine, 7 ins. diam. bears N 15 3/4° W, 46 lks. dist., mkd X at breast height and BT at base.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury original cor. in the mound of stone.</p> <p>A steel fence post is alongside cor.</p> <p>Cor. is located 7 lks. N of a fence cor., fences extend N for a short dist., S and W.</p> <hr/> <p>N 0°08' E, beginning new measurement.</p>
7.815	<p>A local cor., monumented with a rebar, 1/2 in. diam., projecting 4 ins. above the ground, with an aluminum cap attached and mkd. LS 14671, in a mound of stone, 2 x 1 ft., NW property cor. of Horsemans Lodge.</p>
29.875	<p>A local cor., monumented with a rebar, 1/2 in. diam., inside a steel pipe, 1 in. diam., projecting 5 ins. above the ground, with an aluminum cap attached to the rebar and mkd. 1/64 2007, at the cor. of fences extending S 86° E and N 62° E.</p>
39.995	<p>The 1/4 sec. cor. of secs. 21 and 28.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 27 and 28.</p> <p>S 89°55' W, on the E and W center line of sec. 28.</p>

Dependent Resurvey of Subdivisions in Section 28,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Over gently rolling land, through scattered ponderosa pine.</p> <p>39.185 The center 1/4 sec. cor. of sec. 28.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>West, beginning new measurement.</p> <p>2.265 Cor. 16, Tract B, HES 373, monumented with granite stone, 18 x 15 x 10 ins., projecting 9 ins. above the ground, mkd. 16 HES 373 on E face and a cross on top, from which the original bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 27 ins. diam., bears N 21° E, 40 lks. dist., healed blaze. (Record: N 27°07' E)</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears S 88°35' E, 127 lks. dist., healed blaze.</p> <p>At the cor point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T22N R8E S28</p> <hr style="width: 10%; margin: 0 auto;"/> <div style="display: flex; justify-content: center; align-items: center;"> <div style="text-align: center; margin-right: 10px;"> <p>TR E H E S</p> </div> <div style="text-align: center; margin-right: 10px;"> <p>1987</p> </div> <div style="text-align: center;"> <p>COR 16 TR B 373</p> </div> </div> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>A steel fence post is alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>West, beginning new measurement.</p>
--------	--

Dependent Resurvey of Subdivisions in Section 28,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p> <p>0.480</p>	<p>Cor. 7, Tract A, HES 373, monumented with an iron rod, 24 ins. long, 1 in. diam., projecting 5 ins. above the ground, with a 2 x 2 ins. metal plate attached. This cor. was monumented by C.W. Dryden, PE 971 and LS 4321, in 1959 and is accepted as a careful and faithful perpetuation of the position of the original corner, from which the original bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 36 ins. diam., bears N 53°28' W, 110.5 lks. dist., healed blaze. (Record: 109 lks. dist.)</p> <p style="padding-left: 40px;">A ponderosa pine, 26 ins. diam., bears N 4°19' W, 71 lks. dist., healed blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T22N R8E S 28</p> <hr style="width: 50px; margin: 0 auto;"/> <p>COR 7 / TR A TR E HES 373 1987</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit local cor. inside the stainless steel post.</p> <p>Set an aluminum fence post near the cor.</p> <p>Cor. is located 3 lks. N of an E and W fence.</p> <hr style="width: 200px; margin: 20px auto;"/> <p>West, beginning new measurement.</p>
----------------------------	---

Dependent Resurvey of Subdivisions in Section 28,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS

7.555

The center E-W 1/64 sec. cor. of sec. 28, identical with cor. 6, Tract A, HES 373, monumented with an iron rod, 24 ins. long, 1 in. diam., projecting 1 in. above the ground, with a 2 x 2 in. metal plate attached. This cor. was monumented by C.W. Dryden, PE 971 and LS 4321, in 1959 and is accepted as a careful and faithful perpetuation of the position of the original corner, from which an original bearing tree

A ponderosa pine, 16 ins. diam., bears N 84°59' E, 35 lks. dist., illegible scribe marks visible through partially healed blaze. (Record: 37 lks. dist.)

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

S 28
C-E-W
1/64
1987

from which a new bearing tree

A ponderosa pine, 5 ins. diam., bears N 40 3/4° E, 52.5 lks. dist., mkd. X at breast height and BT at base.

and from which

A fence cor. bears N 39 3/4° W, 12.5 lks. dist., fences extend N and W.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Deposit the iron rod inside the stainless steel post.

A steel fence post is alongside the cor.

Cor. is located 75 lks. E of a gully, 30 lks. wide, 5 ft. deep, drains S 3° W.

Dependent Resurvey of Subdivisions in Section 28,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>S 89°57' W, beginning new measurement.</p>
10.325	<p>Point for the center W 1/16 sec. cor. of sec. 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T22N R8E W 1/16 C-----C S28 1987</p> </div> <p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 14 ins. diam., bears N 13 1/2° E, 71 lks. dist., mkd. C-W 1/16 S28 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 7 ins. diam., bears S 56 1/2° E, 92.5 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set an aluminum fence post near the cor.</p>
30.975	<p>The 1/4 sec. cor. of secs. 28 and 29.</p> <hr style="border: 0.5px solid black; margin: 20px 0;"/> <div style="text-align: center; margin: 10px 0;"> <p>Resurvey of the SW 1/4 of Section 28</p> <hr style="border: 0.5px solid black; width: 20%; margin: 5px auto;"/> </div> <p>From the W 1/16 sec. cor. of secs. 28 and 33.</p> <p>N 0°28' W, on the N and S center line of the SW 1/4 of sec. 28.</p>
20.29	<p>Point for the SW 1/16 sec. cor. of sec. 28, at intersection with the E and W center line of the SW 1/4 of sec. 28.</p>

Dependent Resurvey of Subdivisions in Section 28,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T22N R8E SW 1/16 S 28 1987</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Set an aluminum fence post alongside the cor.</p>
23.30	<p>Draw, drains N 80° E.</p>
30.44	<p>Point for the center N-SW 1/64 sec. cor. of sec. 28.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S28 C-N-SW 1/64 1987</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A pinyon, 10 ins. diam., bears N 10° E, 30.5 lks. dist., mkd. C-N-SW 1/64 S28 BT.</p>
	<p style="padding-left: 40px;">A pinyon, 7 ins. diam., bears N 42 3/4° W, 180.5 lks. dist., mkd. X at breast height and BT at base.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Set an aluminum fence post near the cor.</p>
	<p>Cor. is located 17 lks. N of a track road, bears E and W; and 29 lks. N of a fence, bears E and W.</p>
40.59	<p>The center W 1/16 sec. cor. of sec. 28.</p> <hr style="width: 20%; margin: 10px auto;"/>

Dependent Resurvey of Subdivisions in Section 28,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>From the center S 1/16 sec. cor. of sec. 28.</p> <p>S 89°37' W, on the E and W center line of the SW 1/4 of sec. 28.</p> <p>4.20 Center of U.S. Highway 89, bears N 40° E and S 40° W.</p> <p>5.11 Point for cor. 20, Tract B, HES 373, identical with the center E-E-SW 1/256 sec. cor. of sec. 28; falls in the right of way of U.S. Highway 89; there is no remaining evidence of the position of the original cor., not monumented.</p> <p>10.22 The center E-SW 1/64 sec. cor. of sec. 28, identical with cor. 21, Tract B, HES 373, monumented with an open end pipe, 16 ins. long, 1 1/2 ins. diam., flush with ground, origin and date unknown and is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 28 C-E-SW 1/64 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit the local cor. inside the stainless steel post.</p> <p>A steel fence post is alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S 89°41' W, beginning new measurement.</p> <p>10.21 The SW 1/16 sec. cor. of sec. 28.</p> <p>20.43 Point for the center W-SW 1/64 sec. cor. of sec. 28 .</p>
--------	---

Dependent Resurvey of Subdivisions in Section 28,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S 28 C-W-SW 1/64 1987</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A pinyon, 11 ins. diam., bears S 66° W, 144.5 lks. dist., mkd. X at breast height and BT at base.</p>
	<p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears N 58 3/4° W, 191.5 lks. dist., mkd. C-W-SW 1/64 S28 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Set an aluminum fence post alongside the cor.</p>
	<p>Cor. is located 13 lks. E of a N and S fence; and 350 lks. W of a draw, drains N 50° E.</p>
<p>30.65</p>	<p>The S 1/16 sec. cor. of secs. 28 and 29.</p>
	<p style="text-align: center;">_____</p> <p style="text-align: center;">Resurvey in the NE 1/4 of the SW 1/4 of Section 28</p> <p style="text-align: center;">_____</p>
	<p>From the center N-SW 1/64 sec. cor. of sec. 28.</p>
	<p>N 89°43' E, on a portion of the E and W center line of the NE 1/4 of the SW 1/4, of sec. 28, identical with a portion of line 4-5, Tract A, HES 373.</p>
<p>10.24</p>	<p>The NE-SW 1/64 sec. cor. of sec. 28, identical with cor. 5, Tract A, HES 373, determined at record bearing and dist., from an original bearing tree</p>
	<p style="padding-left: 40px;">A ponderosa pine, 33 ins. diam., bears N 38°28' W, 184 lks. dist., healed blaze.</p>
	<p style="padding-left: 40px;">The NE original bearing tree is a ponderosa pine, 38 ins. diam., lying loose and unable to determine its true location, mkd. 5 HES 373 BT. (Record: N 69°06' E, 98 lks. dist.)</p>

Dependent Resurvey of Subdivisions in Section 28,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S28 NE-SW 1/64 1987</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N 73° W, 165.5 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears N 12 1/2° W, 94.5 lks. dist., mkd. NE-SW 1/64 S28 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set an aluminum fence post near the cor.</p> <p>Cor. is located in a fence line 11 lks. W of a fence cor., fences extend N, S and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>North, on a portion of the N and S center line of the NE 1/4 of the SW 1/4 of sec. 28, identical with line 5-6, Tract A, HES 373.</p> <p>10.11 The center E-W 1/64 sec. cor. of sec. 28, identical with cor. 6, Tract A, HES 373.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Resurvey in the SE 1/4 of the SW 1/4 of Section 28</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the E-W 1/64 sec. cor. of secs. 28 and 33, identical with cor. 29, Tract C, HES 373.</p> <p>N 0°13' W, on the N and S center line of the SE 1/4 of the SW 1/4 of sec. 28, identical in part with line 29-28, Tract C, HES 373.</p> <p>10.08 Cor. 28, Tract C, HES 373, monumented with a rebar, 19 ins. long, 5/8 ins. diam., flush with ground. This cor. was monumented by C.W. Dryden, PE 971 and LS 4321, in 1959 and is accepted as a careful and faithful reestablishment of the position of the original corner.</p>
--------	---

Dependent Resurvey of Subdivisions in Section 28,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border: none; margin: auto;"> <tr> <td style="padding-right: 10px;">H</td> <td style="border-left: 1px solid black; padding-left: 10px;">T22N</td> </tr> <tr> <td style="padding-right: 10px;">E TR D</td> <td style="border-left: 1px solid black; padding-left: 10px;">S 28</td> </tr> <tr> <td style="padding-right: 10px;">S</td> <td style="border-left: 1px solid black;"></td> </tr> <tr> <td style="padding-right: 10px;">3 COR 28</td> <td style="border-left: 1px solid black;"></td> </tr> <tr> <td style="padding-right: 10px;">7 TR C</td> <td style="border-left: 1px solid black; padding-left: 10px;">R8E</td> </tr> <tr> <td style="padding-right: 10px;">3</td> <td style="border-left: 1px solid black; padding-left: 10px;">1987</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit local cor. inside the stainless steel post.</p> <p>Set an aluminum fence post near the cor.</p> <p>Cor. is located 4 lks. W of a N and S fence.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N 0°33' W, beginning new measurement bet. cor. 28, Tract C and cor. 22, Tract B, HES 373 across exemption Tract D.</p> <p>0.735 Cor. 22, Tract B, HES 373, monumented with a spike nail, 12 ins. long, 3 ins. below ground. This cor. was monumented by C. W. Dryden, PE 971 and LS 4321, in 1959 and is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border: none; margin: auto;"> <tr> <td style="padding-right: 10px;">H COR 22</td> <td style="border-left: 1px solid black; padding-left: 10px;">T22N</td> </tr> <tr> <td style="padding-right: 10px;">E TR B</td> <td style="border-left: 1px solid black; padding-left: 10px;">S 28</td> </tr> <tr> <td style="padding-right: 10px;">S</td> <td style="border-left: 1px solid black;"></td> </tr> <tr> <td style="padding-right: 10px;">3</td> <td style="border-left: 1px solid black; padding-left: 10px;">R8E</td> </tr> <tr> <td style="padding-right: 10px;">7 TR D</td> <td style="border-left: 1px solid black;"></td> </tr> <tr> <td style="padding-right: 10px;">3</td> <td style="border-left: 1px solid black; padding-left: 10px;">1987</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>	H	T22N	E TR D	S 28	S		3 COR 28		7 TR C	R8E	3	1987	H COR 22	T22N	E TR B	S 28	S		3	R8E	7 TR D		3	1987
H	T22N																								
E TR D	S 28																								
S																									
3 COR 28																									
7 TR C	R8E																								
3	1987																								
H COR 22	T22N																								
E TR B	S 28																								
S																									
3	R8E																								
7 TR D																									
3	1987																								

Dependent Resurvey of Subdivisions in Section 28,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Deposit the local cor. inside the stainless steel post.</p> <p>Cor. is located within the highway ROW, 88 lks. E of the center of U.S. Highway 89, bears N 40° E, and S 40° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°11' W, beginning new measurement on line 22-21, Tract B, HES 373.</p> <p>9.42 The center E-SW 1/64 sec. cor. of sec. 28, identical with cor. 21, Tract B, HES 373.</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="text-align: center;">Dependent Resurvey in the SW 1/4 of the SW 1/4 of Section 28</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From S-S 1/64 sec. cor. of secs. 28 and 29, identical with cor. 2, Tract A, HES 373.</p> <p>N 89°33' E, on a portion of the E and W center line of the SW 1/4 of the SW 1/4 of sec. 28, identical with line 2-3, Tract A, HES 373.</p> <p>10.16 The SW-SW 1/64 sec. cor. of sec. 28, identical with cor. 3, Tract A, HES 373, monumented with a U.S. Department of Agriculture iron post, 2 1/2 ins. diam., projecting 1 in. above the ground. This cor. was reestablished by Charles C. Doak, LS 4476, in 1968, and is accepted as a careful and faithful determination of the position of the cor., with with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>TRACT A</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding-right: 5px;">T22N</td> <td style="border-left: 1px solid black; padding-left: 5px;"> </td> </tr> <tr> <td style="padding-right: 5px;">R8E</td> <td style="border-left: 1px solid black; padding-left: 5px;"> </td> </tr> <tr> <td style="padding-right: 5px;">S28</td> <td style="border-left: 1px solid black; padding-left: 5px;"> </td> </tr> <tr> <td style="padding-right: 5px;"><hr style="width: 50%; margin: 0;"/></td> <td style="border-left: 1px solid black; padding-left: 5px;"> </td> </tr> <tr> <td style="padding-right: 5px;"></td> <td style="border-left: 1px solid black; padding-left: 5px;"> 3</td> </tr> <tr> <td style="padding-right: 5px;"></td> <td style="border-left: 1px solid black; padding-left: 5px;"> HES 373</td> </tr> <tr> <td style="padding-right: 5px;"></td> <td style="border-left: 1px solid black; padding-left: 5px;"> LS 4476</td> </tr> <tr> <td style="padding-right: 5px;"></td> <td style="border-left: 1px solid black; padding-left: 5px;"> 1968</td> </tr> </table> </div> <p>from which bearing objects</p> <p style="margin-left: 40px;">A local cor., bears S 7 1/4° W, 16.5 lks. dist., monumented with an open end pipe, 2 ins. diam., projecting 3 ins. above the ground.</p>	T22N		R8E		S28		<hr style="width: 50%; margin: 0;"/>			3		HES 373		LS 4476		1968
T22N																	
R8E																	
S28																	
<hr style="width: 50%; margin: 0;"/>																	
	3																
	HES 373																
	LS 4476																
	1968																

Dependent Resurvey of Subdivisions in Section 28,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p style="text-align: center;">A fence post of an abandoned fence, bears S 12 1/2° W, 14.5 lks. dist., fence extends northwesterly only.</p> <p>A steel fence post is alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°41' W, beginning new measurement on a portion of the N and S center line of the SW 1/4 of the SW 1/4 of sec. 28, identical with a portion of line 3-4, Tract A, HES 373.</p> <p>10.175 The center W-SW 1/64 sec. cor. of sec. 28.</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="text-align: center;">Dependent Resurvey in the NW 1/4 of the SW 1/4 of Section 28</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center W-SW 1/64 sec. cor. of sec. 28.</p> <p>N 0°47' W, on a portion of the N and S center line of the NW 1/4 of the SW 1/4 of sec. 28, identical with a portion of line 3-4, Tract A, HES 373.</p> <p>10.175 The NW-SW 1/64 sec. cor. of sec. 28, identical with cor. 4, Tract A, HES 373, monumented with a rebar, 20 ins. long, 1/2 in. diam., projecting 1/2 in. above the ground, with a tag attached and mkd. LS 2473. This cor. was set by Wilfred P. Hanson, LS 2473, of unknown date and is accepted as a careful and faithful perpetuation of the position of the original corner, from which an original bearing tree</p> <p style="text-align: center;">A white oak, 19 ins. diam., bears N 62°20' E, 245.5 lks. dist., healed blaze. (Record: 248 lks. dist.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: right; margin-right: 50px;">S 28 NW-SW 1/64 1987</p>
--------	---

Dependent Resurvey of Subdivisions in Section 28,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which new bearing trees</p> <p>A white oak, 5 ins. diam., bears S 25 1/2° W, 173.5 lks. dist., mkd. X at breast height and BT at base.</p> <p>A ponderosa pine, 10 ins. diam., bears N 81 1/2° W, 66.5 lks. dist., mkd. NW-SW 1/64 S28 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit the local cor. inside the stainless steel post.</p> <p>A steel fence post is alongside the cor.</p> <p>Cor. is located 8 lks. SE of a fence cor. fences extend S and N 45° W; and 25 lks. N of a track road, bears S 88° E and S 81° W.</p>
10.28	<hr/> <p>N 89°49' E, on a portion of the E and W center line of the NW 1/4 of the SW 1/4 of sec. 28, identical with a portion of line 4-5, Tract A, HES 373.</p> <p>The center N-SW 1/64 sec. cor. of sec. 28.</p>
	<hr/> <p>Dependent Resurvey of Subdivisions in Section 33, T 22 N, R 8 E, Gila and Salt River Mer., Arizona</p> <hr/> <p>Restoring the survey executed by R.P.A. Johnson in 1915</p> <hr/> <p>From the 1/4 sec. cor. of secs. 4 and 33, on the S bdy. of the township.</p> <p>N 0°52' E, on the N and S center line of sec. 33.</p> <p>Over nearly level land through scattered to medium ponderosa pine.</p>
41.27	<p>Point for the center 1/4 sec. cor. of sec. 33, at the intersection with the E and W center line of sec. 33.</p>

Dependent Resurvey of Subdivisions in Section 33,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E C 1/4 S 33 1987</p> <p>from which bearing objects</p> <p style="padding-left: 40px;">A fence cor., bears N 32 1/2° E, 36.5 lks. dist., fences extend N and W.</p> <p style="padding-left: 40px;">A power pole, bears N 4 1/4° W, 50.5 lks. dist., mkd. 2-PS 164976.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 8 lks. S of a dirt driveway, bears E and W and 35 lks. W of an asphalt surfaced road, bears N and S.</p>
61.785	<p>The center N 1/16 sec. cor. of sec. 33, monumented with a rebar, 19 ins. long, 1/2 in. diam., flush with ground, with a yellow plastic cap attached and mkd. RLS 11755. This cor. was established by Russell R. Penland Jr., LS 11755, date unknown and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R8E C N 1/16 S 33 C 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit the local cor. inside the stainless steel post.</p>

Dependent Resurvey of Subdivisions in Section 33,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°53' E, beginning new measurement.</p>
20.50	<p>The 1/4 sec. cor. of secs. 28 and 33.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 33 and 34.</p> <p>S 88°54' W, on the E and W center line of sec. 33.</p> <p>Over nearly level land, through medium ponderosa pine.</p>
40.75	<p>The center 1/4 sec. cor. of sec. 33.</p>
60.915	<p>The center W 1/16 sec. cor. of sec. 33, monumented with a rebar, 15 ins. long, 1/2 in. diam., 3 ins. below the ground. This cor. was established by James B. Holmquist, PE 2007, 1974 and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T22N R8E W 1/16 C———C S 33 1987</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fence cor., bears N 23 1/4° E, 115 lks. dist., fences extend N and E.</p> <p style="margin-left: 40px;">A ponderosa pine, 13 ins. diam., bears N 12 3/4° W, 25 lks. dist., mkd. C-W 1/16 S33 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>

Dependent Resurvey of Subdivisions in Section 33,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	Deposit the local cor. inside the stainless steel post.
	Set a steel fence post alongside the cor.
	S 88°55' W, beginning new measurement.
20.165	The 1/4 sec. cor. of secs. 32 and 33.
	NW 1/4 of Section 33
	From the center W 1/16 sec. cor. of sec. 33.
	N 0°43' E, on the N and S center line of the NW 1/4 of sec. 33.
10.31	The center S-NW 1/64 sec. cor. of sec. 33, monumented with a nail in the root crown of a ponderosa pine. This cor. was established by Joseph E. Costa, LS 9078, in 1979 and is accepted as a careful and faithful determination of the position of the corner.
	At the cor. point
	Drive a railroad spike into the root crown, with top mkd.
	S 33
	C-S-NW
	1/64
	1987
	from which
	A ponderosa pine, 12 ins. diam., bears S 11° W, 100.5 lks. dist., mkd. C-S-NW 1/64 S33 BT.
	An aluminum post, 32 ins. long, 3/4 in. diam., set 32 ins. in the ground for a reference monument, bears S 83°51' W, 62 ft. dist., with aluminum cap mkd. RM T22N R8E 62.0 FT TO COR S 33 1987.
	Cor. is located 27 lks. N of a driveway, bears N 35° E and S 71° W.

Dependent Resurvey of Subdivisions in Section 33,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	N 0°48' E, beginning new measurement.
10.28	Point for the NW 1/16 sec. cor. of sec. 33 at the intersection with the E and W center line of the NW 1/4 of sec. 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T22N R8E NW 1/16 S 33 1987</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
	Cor. is located 4.5 lks. dist. E of a fence cor., fences extend N, E and S, old fence extends W.
	From this point a local cor., bears N 65°13'W, 0.057 chs. dist., monumented with a rebar, 1/2 in. diam., projecting 5 ins. above the ground. This cor. was established by Joseph E. Costa, LS 9078, in 1979 and is not utilized in the course of this survey.
15.415	Intersect line 32-33, Tract C, HES 373, not monumented.
	From this point, cor. 32, Tract C, HES 373, bears N 89°05' E, 4.990 chs. dist., monumented with a rebar 1/2 in. diam., projecting 2 ins. above ground, with a yellow plastic cap attached and mkd. RLS 11755, not remonumented, from which an original bearing tree.
	A ponderosa pine, 27 ins. diam., bears S 75°01' W, 154 lks. dist., healed blaze.
	From this same point, cor. 33, Tract C, HES 373, bears S 89°05' W, 5.070 chs. dist., monumented with a scattered mound of stone, not remonumented from which the original bearing trees.
	A ponderosa pine, 32 ins. diam., bears S 3 1/4° E, 174 lks. dist., healed blaze. (Record: S 3°51' E, 74 lks. dist.)

Dependent Resurvey of Subdivisions in Section 33,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A white oak, 29 ins. diam., bears S 57 1/2° W, 255 lks. dist., healed blaze. (Record: S 56°12' W)</p>
27.575	<p>Intersect line 26-27, Tract D, HES 373, not monumented, from which cor. 27, Tract D, bears N 36°55.5' E, 4.170 chs. dist., hereinbefore described.</p>
28.353	<p>Intersect line 23-24, Tract D, HES 373, not monumented, from which cor. 23, Tract D, bears N 36°56' E, 3.190 chs. dist., hereinbefore described.</p>
30.883	<p>The W 1/16 sec. cor. of secs. 28 and 33.</p>
	<hr/> <p>From the center N 1/16 sec. cor. of sec. 33</p>
	<p>S 89°10' W, on the E and W center line of the NW 1/4 of sec. 33.</p>
5.05	<p>The center E-E-NW 1/256 sec. cor. of sec. 33, monumented with a rebar, 18 ins. long, 1/2 in. diam., 1/2 in. below ground, with a yellow plastic cap attached and mkd. RLS 11755. This cor. was established by Russell R. Penland Jr., LS 11755, of unknown date and is accepted as a careful and faithful determination of the position of the corner.</p>
	<p>At the cor. point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S 33 C-E-E-NW 1/256 1987</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Deposit local cor. inside the stainless steel post.</p>
	<p>Set a steel fence post alongside the cor.</p>
	<p>Cor. is located 3 lks. NW of a fence cor., fences extend S and E.</p>

Dependent Resurvey of Subdivisions in Section 33,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	S 89°03' W, beginning new measurement.
5.05	Point for the center E-NW 1/64 sec. cor. of sec. 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	S33
	C-E-NW
	1/64
	1987
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
	Cor. is located 1 lk. E of a N and S fence; and 13 lks. S of a ditch, drains easterly.
15.15	The NW 1/16 sec. cor. of sec. 33.
20.25	The center E-W-NW 1/256 sec. cor. of sec. 33, identical with cor. 34, Tract C, HES 373, monumented with a granite stone, 24 x 8 x 6 ins., projecting 3 ins. above the ground, mkd. 34 HES 373 and a cross on top, from which the original bearing trees
	A ponderosa pine, 35 ins. diam., bears S 37°38' E, 74 lks. dist., healed blaze.
	A ponderosa pine, 12 ins. diam., bears S 22°37' W, 67 lks. dist., mkd. 34 HES 373 + BT.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	S 33
	C-E-W-NW
	1/256
	1987

Dependent Resurvey of Subdivisions in Section 33,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>from which a new bearing object</p> <p>A power pole, bears S 87° E, 25.5 lks. dist., mkd. WP-G-5-40.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury original stone alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 1 lk. S of an E and W fence.</p> <hr/> <p>S 89°15' W, beginning new measurement, now identical with line 34-26, Tract C, HES 373.</p> <p>5.00 The center W-NW 1/64 sec. cor. of sec. 33, monumented with a rebar, 18 ins. long, 1/2 in. diam., projecting 3 ins. above the ground, origin and date unknown and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 33 C-W-NW 1/64 1987</p> <p>from which</p> <p>A ponderosa pine, 27 ins. diam., bears S 28 1/4° W, 21 lks. dist., mkd. C-W-NW 1/64 S33 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit local cor. inside the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 3 ft. high, N of cor.</p>
--------	---

Dependent Resurvey of Subdivisions in Section 33,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in an abandoned E and W fence line.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S 89°12' W, beginning new measurement identical in part with line 34-26, Tract C, HES 373.</p> <p>2.795 Cor. 26, Tract C, HES 373, monumented with a granite stone, 24 x 16 x 10 ins., projecting 9 ins. above the ground, mkd. 26 HES 373 on NE face and a cross on top, from which the original bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 22 ins. diam., bears S 76°14' E, 37.5 lks. dist., healed blaze. (Record: 32 lks. dist.)</p> <p style="padding-left: 40px;">A ponderosa pine, 27 ins. diam., bears S 28 3/4° E, 27 lks. dist., marks visible through partially healed blaze 73. (Record: S 31°47' E)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>HES 373 COR 26 TR D / TR C S 33 T22N R8E 1987</p> </div> <p>from which a bearing object</p> <p style="padding-left: 40px;">A power pole, bears S 72° W, 30.5 lks. dist., mkd. 18.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in U.S. Highway 89 ROW.</p> <hr style="width: 20%; margin: 20px auto;"/>
---------------	--

Dependent Resurvey of Subdivisions in Section 33,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>S 89°28' W, beginning new measurement.</p> <p>0.58 Point for cor. 24, Tract B, HES 373, at proportionate dist., there is no remaining evidence of the original corner.</p> <p>Set a cut off stainless steel post, 8 ins. long, 2 1/2 ins. diam., 1 in. below surface of E edge of U.S. Highway 89 with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>HES 373 COR 24 TR B / TR D S 33 T22N R8E 1987</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 73 lks. E of center of U.S. Highway 89 on paved portion of shoulder, bears N 40° E and S 40° W.</p> <p>Continue measurement, now identical in part with line 24-25, Tract B, HES 373.</p> <p>2.30 Point for the center W-W-NW 1/256 sec. cor. of sec. 33, identical with cor. 25, Tract B, HES 373, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S 33 C-W-W-NW 1/256 1987</p> </div> <p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 11 ins. diam., bears S 74° W, 207 lks. dist., mkd. C-W-W-NW 1/256 S33 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 4 ins. diam., bears N 26 1/4° W, 152 lks. dist., mkd. X at breast height and BT at base.</p>
--------	--

Dependent Resurvey of Subdivisions in Section 33,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 100 lks. W of center of U.S. Highway 89, bears N 40° E and S 40° W; and 10 lks. E of ROW fence, bears N 40° E and S 40° W.</p> <hr/> <p>S 88°57' W, beginning new measurement.</p>
5.005	<p>The N 1/16 sec. cor. of secs. 32 and 33.</p> <hr/> <p style="text-align: center;">Survey of Subdivisions in the NE 1/4 of the NW 1/4, of section 33</p> <hr/> <p>From the center E-E-NW 1/256 sec. cor. of sec. 33</p> <p>N 0°48' E, on the N and S center line of the SE 1/4 of the NE 1/4 of the NW 1/4 of sec. 33.</p>
5.12	<p>The SE-NE-NW 1/256 sec. cor. of sec. 33, monumented with a rebar, 18 ins. long, 1/2 in. diam., projecting 1 in. from the ground. This monument is of unknown origin, and is accepted as a careful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 33 SE-NE-NW 1/256 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Deposit the rebar inside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 2 lks. south of a fence line bearing E and W.</p> <hr/>

Survey of Subdivisions in Section 33, T 22 N, R 8 E,
Gila and Salt River Mer., Arizona

CHAINS	
5.06	<p>S 89°07' W on a portion of the E and W center line of the SE 1/4 of the NW 1/4 of sec. 33.</p> <p>Point for the center S-NE-NW 1/256 sec. cor. of sec. 33, monumented with a rebar, 18 ins. long, 1/2 in. diam., set 2 ins. below the ground, with top of a yellow cap missing. This monument is accepted as a careful and faithful determination of the cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S33 C-S-NE-NW 1/256 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit the rebar inside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in a field, 22 lks. S of a fence bearing E and W; and 29.5 lks. E of a fence bearing N and S.</p>
5.10	<p>S 0°43' W, on a portion of the N and S center line of the NE 1/4 of the NW 1/4 of sec. 33.</p> <p>The center E-NW 1/64 sec. cor. of sec. 33.</p> <p style="text-align: center;">SE 1/4 of the NW 1/4 of section 33</p> <p>From the center E-NW 1/64 sec. 33.</p> <p>S 0°47'W, on the N and S center line of the SE 1/4 of the NW 1/4 of sec. 33.</p>
5.16	<p>Point for the center N-SE-NW 1/256 sec. cor. of sec. 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of Subdivisions in Section 33, T 22 N, R 8 E,
Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">S 33 C-N-SE-NW 1/256 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 2 lks. E of a fence bearing N and S.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N 89°00' E , on the E and W center line of the NE 1/4 of the SE 1/4 of the NW 1/4 of sec. 33.</p> <p>5.055 The NE-SE-NW 1/256 sec. cor. of sec. 33, monumented with a rebar, 18 ins. long, 2 1/2 ins. diam. , set flush with the ground, with yellow plastic cap mkd. 11755. This monument was set by Russell R. Penland Jr. LS 11755, date unknown, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 33 NE-SE-NW 1/256 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit the rebar inside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor is located 2 lks. SW of a fence cor., fences extend N and S</p> <hr style="width: 20%; margin: 20px auto;"/>

Survey of Subdivisions in Section 33, T 22 N, R 8 E,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>N 0°49' E, on a portion of the N and S center line of the NE 1/4 of the SE 1/4 of the NW 1/4 of sec. 33.</p>
5.13	<p>The center E-E-NW 1/256 sec. cor. of sec. 33.</p> <p style="text-align: center;"><u>SW 1/4 of the NW 1/4 of Section 33</u></p> <p>From the center S-NW 1/64 sec. cor. of sec. 33.</p> <p>S 89°00' W, on the E and W center line of the SW 1/4 of the NW 1/4 of sec. 33.</p>
10.09	<p>The SW-NW 1/64 sec. cor. of sec. 33, monumented with a rebar, 17 ins. long, 1/2 in. diam., projecting 3 ins. above the ground. This cor. was established by Joseph E. Costa, LS 9078, in 1979 and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 33 SW-NW 1/64 1987</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S 42° W, 349 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears N 54 3/4° W, 238 lks. dist., mkd. SW-NW 1/64 S33 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit the local cor. inside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located at the cor. of fences extending N and E.</p>

Survey of Subdivisions in Section 33, T 22 N, R 8 E,
Gila and Salt River Mer., Arizona

CHAINS	<p>N 0°44' E, on the N 1/2 of the N and S center line of the SW 1/4 of the NW 1/4 of sec. 33.</p>
10.31	<p>The center W-NW 1/64 sec. cor. of sec. 33.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Subdivisions in the NW 1/4 of the NW 1/4 of Section 33</p> <hr/> <p style="text-align: center;">Restoring the Survey by R.P.A. Johnson, in 1915</p> <hr/> <p>From the center W-W-NW 1/256 sec. cor. of sec. 33, identical with cor. 25, Tract B, HES 373.</p> <p>N 1°05' E, on the N and S center line of the SW 1/4 of the NW 1/4 of the NW 1/4 of sec. 33, identical in part with line 25-13, Tract B, HES 373.</p>
3.52	<p>Cor. 13, Tract B, HES 373, monumented with a granite stone, 22 x 10 x 10 ins., projecting 16 ins. above the ground, mkd. 13 HES 373 on E face and a cross on top.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury original stone alongside the stainless steel post.</p> <p>A steel fence post is alongside the cor.</p> <hr/>
0.83	<p>N 0°50' E, beginning new measurement, identical with line 13-10, Tract E, HES 373.</p> <p>Cor. 10, Tract A, HES 373, monumented with a granite stone, 20 x 14 x 8 ins. projecting 14 ins. above the ground, mkd. 10 HES 373 on NE face.</p>

Dependent Resurvey of Subdivisions in Section 33,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury original stone alongside the stainless steel post.</p> <p>A steel fence post is alongside the cor.</p> <p>Cor. is located 20 lks. W of a N and S fence.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N 0°37' E., beginning new measurement, identical with line 10-11, Tract A, HES 373.</p> <p>4.445 Point for cor. 4, lot 1, sec. 33.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with an aluminum cap attached and mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p>from which</p> <p style="margin-left: 40px;">A power pole, bears S 19 1/2° E, 80.5 lks. dist., mkd. PS 110185.</p> <p style="margin-left: 40px;">A ponderosa pine, 5 ins. diam., bears S 34 1/2° W, 227 lks. dist., mkd. X at breast height and BT at base.</p> <p>Cor. is located in an E and W fence.</p>
--------	--

Dependent Resurvey of Subdivisions in Section 33,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>5.955 The center W-NW-NW 1/256 sec. cor. of sec. 33, identical with cor. 11, Tract A, HES 373, and with cor. 1, lot 1, sec. 33, monumented with a U.S. Department of Agriculture iron post, 2 1/2 ins. diam., flush with the ground. This cor. was set by Charles C. Doak, LS 4476, Arizona in 1968 and is accepted as a careful and faithful reestablishment of the position of the original corner, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>TRACT A</p> <p>11</p> <hr style="width: 50px; margin: 0 auto;"/> <p>T22N HES</p> <p>R8E 373</p> <p>S 33 </p> <p>LS 4476</p> <p>1968</p> </div> <hr style="width: 200px; margin: 20px auto;"/> <p>S 89°20' W, on a portion of the E and W center line of the NW 1/4 of the NW 1/4 of sec. 33, identical with line 11-12, Tract A, HES 373.</p> <p>5.035 The N-N 1/64 sec. cor. of secs. 32 and 33, identical with cor. 12, Tract A, HES 373, hereinbefore described.</p> <hr style="width: 600px; margin: 20px auto;"/> <div style="text-align: center; margin: 10px auto;"> <p>Metes-and-Bounds Survey of Lot 1, Section 33</p> <p>T 22 N, R 8 E, Gila and Salt River Mer., Arizona</p> </div> <hr style="width: 600px; margin: 20px auto;"/> <p>From cor. 1, lot 1, sec. 33, identical with the center W-NW-NW 1/256 sec. cor. of sec. 33 and cor. 11, Tract A, HES 373, hereinbefore described.</p> <p>S 89°20' W, on line 1-2, lot 1, identical with a portion of the E and W center line of the NW 1/4 of the NW 1/4 of sec. 33 and with line 11-12, Tract A, HES 373.</p> <p>5.035 Cor. 2, lot 1, identical with the N-N 1/64 sec. cor. of secs. 32 and 33 and cor. 12, Tract A, HES 373, hereinbefore described.</p> <hr style="width: 200px; margin: 20px auto;"/>
--------	--

Metes-and-Bounds Survey of Lot 1, Section 33,
T 22 N, R 8 E, Gila and Salt River Mer., Arizona

CHAINS	<p>S 0°39' W, on line 2-3, lot 1, identical with a portion of the line bet. secs. 32 and 33.</p>
0.45	<p>Cor. 3, lot 1, sec. 33, hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/>
5.12	<p>S 78°45' E, on line 3-4, lot 1, sec. 33.</p> <p>Cor. 4, lot 1, sec. 33, hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/>
1.51	<p>N 0°37' E, on line 4-1, lot 1, sec. 33, identical with a portion of the N and S center line of the SW 1/4 of the NW 1/4 of the NW 1/4 of sec. 33 and line 10-11, Tract A, HES 373.</p> <p>Cor. 1, lot 1, sec. 33 and point of beginning.</p> <hr style="width: 80%; margin: 10px auto;"/>
<p>General Description</p> <p>The land encompassed in this survey is located at the NE edge of the corporate limits of the City of Flagstaff, Arizona. The elevation ranges from about 6,560 to 7,180 ft. above sea level.</p> <p>The land varies from nearly level to rolling, covered with moderate ponderosa pine, scattered oak, pinyon and juniper, with numerous open areas.</p> <p>Access is by way of U.S. Highway 89, Winona Road, and numerous improved and unimproved roads.</p> <hr style="width: 80%; margin: 10px auto;"/>	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Cheryl A. Baier	Survey Technician
Robert J. Lyle	Survey Technician
Luke Granger	Survey Technician
Robert Charboneau	Survey Technician
Kevin DeRossett	Land Surveyor
Wilmer Beyl	Survey Aid
Thomas Stafford	Survey Aid

CERTIFICATE OF SURVEY

I, Paul L. Reeves, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 30th day of April, 1986, I have dependently resurveyed portions of the south boundary, subdivisional lines, Homestead Entry Survey 373, Tract D exemption of Homestead Entry Survey 373, and dependently resurveyed the subdivision of sections 28 and 33; and surveyed the subdivision of sections 21, 22, 27 and 33, and a survey of lot 1, in section 33, Township 22 North, Range 8 East, of the Gila and Salt River Meridian, in the state of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

NOVEMBER 2, 1988
(Date)

Paul L. Reeves
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of portions the south boundary, subdivisional lines, Homestead Entry Survey 373, Tract D exemption of Homestead Entry Survey 373, and the dependent resurvey of the subdivision of sections 28 and 33; and the survey of subdivision of sections 21, 22, 27 and 33, and a survey of Lot 1, section 33, Township 22 North, Range 8 East, of the Gila and Salt River Meridian, in the state of Arizona, executed by Paul L. Reeves, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

DEC 13 1988
(Date)

James P. Kelley
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I Certify that the foregoing transcript of the field notes of the above-described surveys in T 22 N, R 8 E, Gila and Salt River Meridian, in the state of Arizona is a true copy of the original field notes.~~

~~_____~~
(Date)

~~_____~~
(Chief Cadastral Surveyor of Arizona)