

ORIGINAL

2-5279

1

BOOK 5279

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES  
OF THE

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY, A PORTION OF THE

EAST BOUNDARY, A PORTION OF THE ABANDONED SOUTH BOUNDARY

OF THE NAVAJO INDIAN RESERVATION, AND A PORTION OF THE SUBDIVISIONAL LINES;

THE SURVEY OF A PORTION OF THE EAST BOUNDARY, THE NORTH BOUNDARY, A PORTION

OF THE SUBDIVISIONAL LINES, AND THE SUBDIVISION OF CERTAIN SECTIONS IN

TOWNSHIP 26 NORTH, RANGE 30 EAST

Of the Gila and Salt River Meridian,  
In the State of Arizona

EXECUTED BY

Kevin R. DeRossett, Cadastral Surveyor

Richard S. Kaiser, Cadastral Surveyor

Under special instructions dated April 18, 1984, approved April 18, 1984,  
and supplemental special instructions dated August 29, 1984

, which provided for the surveys included under Group Number  
655 and assignment instructions dated April 18, 1984.

Survey commenced June 6, 1984

Survey completed April 11, 1985

2  
BOOK 5279

INDEX DIAGRAM

TOWNSHIP 26 NORTH, RANGE 30 EAST,

102 121 6	100 120 5	99 114 4	98 111 3	96 108 2	95 105 1 92
118 119 7 28	117 116 8 27	114 112 9 24	110 109 10 22	107 105 11 19	104 102 12 18
18	Abandoned South Bdy. -- Navajo Indian Reservation				41 13
89 19	90 17 88 86 20	75 16 74 73 21	64 15 63 61 22	53 14 51 49 23	38 37 24 16
85 30	84 81 29	71 69 28	60 59 27	48 47 26	35 34 25
80 31 14	79 77 32 13	68 66 33 10	58 56 34 8	45 43 35 6	33 32 36 4

Subdivision of Sec. 13---pp 123

Subdivision of Sec. 14---pp 127

Subdivision of Sec. 22---pp 130

Subdivision of Sec. 23---pp 131

Subdivision of Sec. 24---pp 136

Subdivision of Sec. 30---pp 139

Subdivision of Sec. 32---pp 140

## BOOK 5279

Township 26 North, Range 30 East, Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes are those of the dependent resurvey of the south boundary, a portion of the east boundary, a portion of the abandoned south boundary of the Navajo Indian Reservation, and a portion of the subdivisional lines; the survey of a portion of the east boundary, the north boundary, a portion of the subdivisional lines, and the subdivision of certain sections in Township 26 North, Range 30 East, Gila and Salt River Meridian, Arizona.

John G. Evans surveyed the (abandoned) south boundary of the Navajo Indian Reservation through T 26 N, R 30 E, in 1884-85. James A. Lamport surveyed the south boundary, a portion of the east boundary, and a portion of the subdivisional lines in 1900. Sidney E. Blout resurveyed the south boundary in 1927. Paul L. Reeves resurveyed and surveyed portions of the east boundary in 1978. The west boundary was resurveyed concurrently under this same group.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated April 18, 1984, and the Supplemental Special Instructions dated August 29, 1984, for Group No. 655, Arizona.

Preliminary to the resurvey the lines of previous surveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data was thoroughly verified and only the true line field notes are given herein.

The direction of the lines were determined by hour-angle observations on the sun, and refer to the true meridian. The lines were carried forward by sustained angulation, being supplemented by other hour-angle observations on the sun taken throughout the progress of the survey. Distances and angles were measured using a Zeiss ELTA-46 electronic instrument.

The NAD 27 geographic coordinates and elevation of the southeast township corner were determined by the technique of relative positioning using the Magnavox MX 1502 Satellite Surveyor.

## BOOK 5279

Township 26 North, Range 30 East, Gila and Salt River Meridian, Arizona

CHAINS	
	Corner/Station Elevation                      Latitude                      Longitude
	Southeast Township Corner 6,726 ft.                      35°36'17.314" N    109°04'53.174" W
	The mean magnetic declination was observed to be 12 1/4° E, with no noticeable differences due to local attractions.
	Dependent Resurvey of the S Bdy. of T 26 N, R 30 E, Gila and Salt River Meridian, Arizona
	Restoring the resurvey executed by Sidney E. Blout in 1927
	Beginning at the cor. of Tp. 26 N, Rs. 30 and 31 E, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. as described in the official record of the 1927 dependent resurvey of the S bdy. of T 26 N, R 30 E.
	Set a steel fence post near the cor.
	S 89°55' W, on the S bdy. of sec. 36.
	Over rolling land.
19.00	A trail road, bears N 30° E and S 30° W.
20.95	A barbed wire fence, 5 strand, extending N 30° E and S 30° W.
37.02	The 1/4 sec. cor. of sec. 1 only, T 25 N, R 30 E, bears South, 1.2 lks. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. as described in the official record of the 1927 dependent resurvey of the S bdy. of T 26 N, R 30 E, alongside which an unmarked sandstone, 18 x 12 x 3 ins., is lying loose on the ground.
39.49	The 1/4 sec. cor. of sec. 36 only, T 26 N, R 30 E, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1927 dependent resurvey of the S bdy. of T 26 N, R 30 E, alongside which an unmarked sandstone, 14 x 10 x 4 ins., is lying loose on the ground.
	Remark the brass cap to read

## BOOK 5279

Dependent Resurvey of the S Bdy. of T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T26N R30E 1/4 S36</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1984 1927</p>
	<p>Cor. is located in a barbed wire fence, 3 strand, extending N 10° E and S 10° W.</p> <hr style="width: 20%; margin: auto;"/>
	<p>S 89°56' W, beginning new measurement.</p>
	<p>Over rolling land.</p>
19.00	<p>A barbed wire fence, 5 strand, extending N 5° E and S 5° W.</p>
32.80	<p>Black Creek, 115 lks. wide, 3 ft. deep, drains S 30° W.</p>
37.47	<p>The closing cor. of secs. 1 and 2, T 25 N, R 30 E, monumented with an iron post, 2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines of T 25 N, R 30 E.</p>
	<p>Cor. located 30 lks. S of a barbed wire fence, 5 strand, extending E and W, and 30 lks. N of a barbed wire fence, 5 strand, extending E and W.</p>
39.44	<p>The cor. of secs. 35 and 36, T 26 N, R 30 E, monumented with an iron post, 2 ins. diam., firmly set, 4 ins. below the surface of the ground, with brass cap improperly mkd. T26N R30E S35 S36 S2 T25N R30E 19127.</p>
	<p>Remark the brass cap to read</p>
	<p style="text-align: center;">T26N R30E S35   S36</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S2 T25N R30E 1984 1927</p>
	<p>Cor. is located 30 lks. S of a barbed wire fence, 5 strand, extending E and W, and 30 lks. N of a barbed wire fence, 5 strand, extending E and W.</p>

## BOOK 5279

Dependent Resurvey of the S Bdy. of T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona

CHAINS	
	S 89°56' W, on the S bdy. of sec. 35.
	Over rolling land.
	Enter residential area with 5 residences spreading N and S for approximately 1/4 mi.
31.60	Wood pole power line, 12 strand, bears N 10° E and S 10° W.
32.30	Navajo Route No. 12, 55 ft. wide, asphalt surfaced, bears N 10° E and S 10° W.
33.10	A barbed wire fence, 4 strand, extending N 10° E and S 10° W. Enter cultivated field.
33.50	Wood pole power line, 2 strand, bears S 20° E and N 20° W.
39.45	Point for the 1/4 sec. cor. of sec. 35 only, T 26 N, R 30 E, at proportionate distance; there is no remaining evidence of the original cor.
	Set an aluminum post, 1 in. diam., 28 ins. long, with magnetic base, 18 ins. below the surface of the ground, with cap mkd.
	<p style="text-align: center;">T26N R30E 1/4 S35</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">T25N R30E 1984</p>
	from which
	<p style="margin-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N 0°27' E, 194.8 ft. dist., with brass cap mkd. RM T26N R30E 1/4 S35 194.8 FT. 1984 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>
	<p style="margin-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N 37°32' W, 208.6 ft. dist., with brass cap mkd. RM T26N R30E 1/4 S35 208.6 FT. 1984 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>

Dependent Resurvey of the S Bdy. of T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona

CHAINS	<p>From this point an Arizona State Highway Department right-of-way monument, marking the W right-of-way of Navajo Route No. 12, bears N 32°46' E, 10.05 chs. dist., monumented with a concrete cylinder, 6 ins. diam., firmly set, projecting 10 ins. above ground, with a brass tablet 3 ins. diam., mkd. ARIZONA STATE HWY 1961, witnessed by a 4 x 4 ins. angle iron, firmly set, projecting 2 ft. above ground, painted POT 186+81.95, northerly, 3.0 lks. dist.</p> <p>From this same point a standard brass tablet bench mark of the U.S.G.S., set in concrete form, flush with ground, bears N 32°59' E, 10.01 chs. dist., with top mkd. ELEV. 6681 FT ABOVE SEA 67 DOR 1970 and a triangle in the center.</p> <p>From this same point an Arizona State Highway Department right-of-way monument, marking the E right-of-way of Navajo Route No. 12, bears N 38°53' E, 11.06 chs. dist. monumented with a concrete cylinder, 6 ins. diam., firmly set, projecting 6 ins. above ground, with a brass tablet 3 ins. diam., mkd. ARIZONA STATE HWY 1961, 1962, witnessed by a 4 x 4 ins. angle iron, firmly set, projecting 2 ft. above ground, painted POT 186+81.95, northerly, 2.9 lks. dist.</p> <p>From this same point an Arizona State Highway Department right-of-way monument, marking the E right-of-way of Navajo Route No. 12, bears S 34°15' E, 16.70 chs. dist., monumented with a concrete cylinder, 6 ins. diam., firmly set, projecting 6 ins. above ground, with a brass tablet 3 ins. diam., mkd. ARIZONA STATE HWY 1961, witnessed by a 4 x 4 ins. angle iron, firmly set, projecting 2 ft. above ground, painted P.C. 201+70.55, northerly, 2.4 lks. dist.</p> <p>From this same point an Arizona State Highway Department right-of-way monument, marking the W right-of-way of Navajo Route No. 12, bears S 29°27' E, 16.04 chs. dist. monumented with a concrete cylinder, 6 ins. diam., firmly set, projecting 4 ins. above ground, with a brass tablet 3 ins. diam., mkd. ARIZONA STATE HWY 1961, witnessed by a 4 x 4 ins. angle iron, firmly set, projecting 2 ft. above ground, painted P.C. 201+70.55, northerly, 3.2 lks. dist.</p> <p>Cor. is located in a cultivated field.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S 89°21' W, beginning new measurement.</p> <p>Land, rolling to mountainous.</p>
2.85	<p>A barbed wire fence, 3 strand, extending N 10° E and S 10° W.</p> <p>Leave cultivated field and residential area. Enter mountainous, rugged land.</p>

## BOOK 5279

Dependent Resurvey of the S Bdy. of T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona

CHAINS	
34.30	A trail road bears S 10° E and and N 10° W.
38.60	<p>The closing cor. of secs. 2 and 3, T 25 N, R 30 E, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines of T 25 N, R 30 E, from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A pinyon, 16 ins. diam., bears S 26 1/4° W, 214 lks. dist., mkd. T26N R30E CC BT. (Record: S 25° W.)</p>
39.39	A trail road, bears N 35° E and S 35° W.
40.14	<p>The cor. of secs. 34 and 35, T 26 N, R 30 E, monumented with a sandstone boulder, 7 x 2 x 6 ins., loosely set, 2 ins. in the ground, mkd. with 2 grooves on the E face and 4 grooves on the W face, witnessed by an iron post, 1 lk. W of the cor., 2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. as described in the official record of the 1927 resurvey of the S bdy. of T 26 N, R 30 E, from which the remaining original bearing trees</p> <p style="padding-left: 40px;">A stump hole, bears N 27 3/4° E, 50 lks. dist., with a dead pinyon lying alongside, 13 ins. diam., mkd. T26N R30E 35 BT on open blaze. (Record: N 29° E.)</p> <p style="padding-left: 40px;">A pinyon, 17 ins. diam., bears N 74° W, 52 lks. dist., with a healed blaze. (Record: N 74 1/2° W, 50 lks.)</p>
	<p>At the cor. point</p> <p>Remove the original cor. monument, in place of which reset the iron post, 32 ins. in the ground.</p> <p>Bury the mkd. stone alongside the iron post.</p> <p>Add the marks 1984 to the brass cap.</p> <p>Cor. is located 5 lks. N of the N edge of a meandering trail road, bears generally E and W.</p>
	<hr/> <p>S 89°20' W, on the S bdy. of sec. 34.</p> <p>Over rugged, mountainous land.</p>
36.00	Wash, 1 ch. wide, 50 ft. deep, drains irregularly NE.



## BOOK 5279

Dependent Resurvey of the S Bdy. of T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona

CHAINS	
38.47	<p>The 1/4 cor. of sec. 3 only, T 25 N, R 30 E, bears South, 2.2 lks. dist., monumented with a sandstone boulder, 40 x 30 x 20 ft. above ground, mkd. X 1/4. from which the original bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 34 ins. diam., bears S 49 1/2° E, 92 lks. dist., with a partially healed blaze and illegible scribe marks. (Record: S 48 1/2° E.)</p> <p style="padding-left: 40px;">A dead oak, 9 ins. diam., bears S 29° W, 70 1/2 lks. dist., with a healed blaze. (Record: S 13 1/2° W, 70 lks.)</p> <p>Cor. is located on the N side of a wash, 1 ch. wide, 50 ft. deep, drains NE.</p>
40.11	<p>The 1/4 sec. cor. of sec. 34 only, T 26 N, R 30 E, monumented with a sandstone boulder, 23 x 20 x 2 ft. above ground, mkd. with an X, from which the 1927 accessories</p> <p style="padding-left: 40px;">A sandstone boulder, 23 x 23 x 10 ft. above ground, bears N 51 1/4° E, 37 lks. dist., mkd. X BO (Record: N 57° E.)</p> <p style="padding-left: 40px;">An oak, 12 ins. diam., bears N 60 1/2° W, 20 lks. dist., with a healed blaze. (Record: N 60° W, 21 lks.)</p> <p>At the cor. point</p> <p>Set an aluminum tablet, 3 1/4 ins. diam., 3 1/2 in. magnetic stem, in a drill hole, cemented in place, flush in exposed sandstone, with top mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T26N R30E 1/4 S34</p> <hr style="width: 10%; margin: 0 auto;"/> <p>T25N R30E 1984</p> </div> <p>from which a new accessory</p> <p style="padding-left: 40px;">A vertical sandstone face, 70 ft. high, bears N 26 1/2° W, 27 lks. dist., mkd. X BO.</p> <p>Cor. located 30 lks. N of the center of a wash, 45 lks. wide, 5 ft. deep, drains N 60° E.</p> <div style="text-align: center; margin: 10px 0;"> <hr style="width: 20%; margin: 0 auto;"/> </div> <p>N 88°57' W, beginning new measurement.</p>

## BOOK 5279

Dependent Resurvey of the S Bdy. of T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona

CHAINS	<p>Over rugged, mountainous land.</p> <p>0.50 Wash, 50 lks. wide, 5 ft. deep, drains NE.</p> <p>38.47 The closing cor. of secs. 3 and 4, T 25 N, R 30 E, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, in a collar of stone, 2 1/2 ft. diam., with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines of T 25 N, R 30 E, from which the original bearing trees</p> <p style="padding-left: 40px;">A dead pinyon, 11 ins. diam., bears S 60° E, 30 lks. dist., mkd. T25N R30E S3 CC BT.</p> <p style="padding-left: 40px;">A pinyon, 10 ins. diam., bears S 87 1/4° W, 18 lks. dist., mkd. T25N R30E S4 CC BT. (Record: S 88 1/2° W.)</p> <p>40.12 The cor. of secs. 33 and 34, T 26 N, R 30 E, is determined at record dist. from the original bearing trees. A sandstone boulder, 15 x 11 x 4 ins., mkd. with 3 grooves on one face and 3 grooves on the opposite face, and the 1927 resurvey monument, an iron post, 36 ins. long, 2 ins. diam., with brass cap mkd. as described in the official record of the 1927 dependent resurvey of the S bdy. of T 26 N, R 30 E, are both lying loose near the cor. pt., from which the remaining original bearing trees</p> <p style="padding-left: 40px;">A pinyon, 16 ins. diam., bears N 51 1/4° E, 21 lks. dist., mkd. T26N R30E 34 BT on partially healed blaze. (Record: N 47 3/4° E.)</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears N 13 3/4° W, 26 lks. dist., mkd. T26N R30E S33 on partially healed blaze. (Record: N 46 3/4° W.)</p> <p>At the cor. point</p> <p>Set the 1927 iron post, 26 ins. in the ground, in a mound of stone, 3 ft. base, to top of cap.</p> <p>Bury the mkd. stone alongside the iron post.</p> <p>Add the marks 1984 to the brass cap.</p> <hr/> <p>N 89°44' W, on the S bdy. of sec. 33.</p>
--------	---

## BOOK 5279

Dependent Resurvey of the S Bdy. of T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Over rugged, mountainous land.</p> <p>38.27 The 1/4 sec. cor. of sec. 4 only, T 25 N, R 30 E, bears North, 3.0 lks. dist., monumented with an iron post, projecting 36 ins. above ground, in a mound of stone, 6 ft. base, 32 ins. high, with brass cap mkd. as described in the official record of the 1927 dependent resurvey of the S bdy. of T 26 N, R 30 E, from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam. bears S 76 1/2° E, 25 lks. dist., mkd. 1/4 S4 BT on partially healed blaze. (Record: S 78 1/4° E, 26 lks.)</p> <p style="padding-left: 40px;">A pinyon, 8 ins. diam., bears S 48° W, 26 1/2 lks. dist., mkd. 1/4 S4 BT on partially healed blaze. (Record: S 48 3/4° W., 25 lks.)</p> <p>Cor. is located 30 lks. S of sandstone ledge, bears irregularly NE and SW.</p>
40.34	<p>The 1/4 sec. cor. of sec. 33 only, T 26 N, R 30 E, monumented with a 3 forked juniper, 13 ins. diam., mkd. by a partially healed blaze on N face with scribe marks visible 1/4 S BT 33, and a partially healed blaze on the S face, witnessed by an iron post on the N side of the tree, 1 in. diam., projecting 14 ins. above ground, with brass cap mkd. as described in the official record of the 1927 dependent resurvey of the S bdy. of T 26 N, R 30 E, from which the 1927 bearing tree</p> <p style="padding-left: 40px;">A pinyon, 12 ins. diam., bears N 41 1/4° E, 36 1/2 lks. dist., mkd. 1/4 S33 BT on partially healed blaze. (Record: N 43 3/4° E, 35 lks.)</p> <p>from which a 1900 bearing tree</p> <p style="padding-left: 40px;">A forked juniper, 8 ins. diam., bears N 57 1/2° W, 17 lks. dist., mkd. 1/4 BT on partially healed blaze on S face. (Record: N 81 1/2° W.)</p> <p>Add the marks T26N R30E T25N R30E 1984 to the brass cap.</p> <p>Cor. is located on the S side of a ravine, 20 ft. from top, ravine is 100 ft. deep, drains NE.</p> <hr style="width: 20%; margin: 20px auto;"/>

## BOOK 5279

Dependent Resurvey of the S Bdy. of T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona

CHAINS	
	N 89°15' W, beginning new measurement.
7.50	N side of a large ravine, 100 ft. deep, drains NE.  Enter rolling land.
32.50	Transworld underground pipeline road, 50 ft. wide, bears NE and SW.
37.90	The closing cor. of secs. 4 and 5, T 25 N, R 30 E, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, and bent to the N, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines of T 25 N, R 30 E, from which the original bearing trees  A ponderosa pine stump, 18 ins. diam., bears S 49 3/4° W, 19 1/2 lks. dist. with a partially healed blaze and no visible scribe marks. (Record: S 48 1/2° E, 20 lks.)  A stump hole, bears S 73 1/2° W, 40 lks. dist., with a down pinyon alongside, 12 ins. diam., mkd. T25N R30E S5 CC BT on open blaze. (Record: S 74° W, 38 lks.)
39.93	The cor. of secs. 32 and 33, T 26 N, R 30 E, monumented with a sandstone, 14 x 12 x 4 ins., firmly set, projecting 6 ins. above ground, mkd. with 4 grooves on the E face and 2 grooves on the W face, and witnessed by an iron post on the E side of the monument, 2 ins. diam., firmly set, projecting 14 ins. above ground, bent to the NE, and in a collar of stone, with brass cap mkd. as described in the official record of the 1927 dependent resurvey of the S bdy. of T 26 N, R 30 E, from which the remaining original bearing tree  An oak, 10 ins. diam., bears N 25 1/2° E, 108 1/2 lks. dist., with a healed blaze. (Record: N 25 1/4° E, 108 lks.)  At the cor. point  Set a stainless steel post, 25 ins. long, 2 1/2 ins. diam., bonded to a magnetic poly breakaway base, 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  T26N R30E S32   S33 ----- T25N R30E S5 1984

## BOOK 5279

Dependent Resurvey of the S Bdy. of T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which a new bearing tree</p> <p>A ponderosa pine, 23 ins. diam., bears N 50 3/4° W, 47 1/2 lks. dist., mkd. T26N R30E S32 BT.</p> <p>Bury the original stone monument and 1927 iron post alongside the stainless steel post.</p>
	<p>N 89°45' W, on the S bdy. of sec. 32.</p> <p>Over rolling, mountainous land.</p>
38.03	<p>The 1/4 sec. cor. of sec. 5 only, T 25 N, R 30 E, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. as described in the official record of the 1927 dependent resurvey of the S bdy. of T 26 N, R 30 E, from which the original bearing trees</p> <p>An oak, 12 ins. diam., bears S 9° E, 61 1/2 lks. dist., with a healed blaze. (Record: S 8 3/4° E, 61 lks.)</p> <p>A ponderosa pine stump, 20 ins. diam., bears S 36 3/4° W, 78 lks. dist. mkd. 1/4 S5 BT. (Record: S 36° W.)</p>
40.12	<p>The 1/4 sec. cor. of sec. 32 only, T 26 N, R 30 E, monumented with a sandstone, 16 x 14 x 4 ins., firmly set, projecting 2 ins. above ground, with illegible chisel marks and witnessed by an iron post, 1 in. diam., on the E side of the monument, firmly set, projecting 3 ins. above ground, with brass cap mkd. as described in the official record of the 1927 dependent resurvey of the S bdy. of T 26 N, R 30 E.</p> <p>At the cor. point</p> <p>Remove the original cor. monument, in place of which reset the iron post, 28 ins. in the ground, in a mound of stone, 3 ft. base, to top, and remark the brass cap to read</p> <p style="text-align: center;">T26N R30E 1/4 S32</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">T25N R30E 1984 1927</p>

## BOOK 5279

Dependent Resurvey of the S Bdy. of T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Bury the original stone monument alongside the iron post.</p> <p>Cor. located 15 lks. E of the center of a trail road, bears N 10° E and S 10° W, and 1 ch. S of the center of El Paso Natural Gas (EPNG) underground pipeline, right-of-way, 2 chs. wide, bears E and W.</p> <hr/> <p>S 89°48' W, beginning new measurement.</p> <p>Along the N side of EPNG underground pipeline and graded road.</p>
37.92	<p>The closing cor. of secs. 5 and 6, T 25 N, R 30 E, monumented with a brass tablet, firmly set, flush with exposed sandstone, with top mkd. as described in the official record of the 1927 survey of the subdivisional lines of T 25 N, R 30 E.</p>
39.90	<p>The cor. of secs. 31 and 32, T 26 N, R 30 E, monumented with an iron post, 2 1/2 ins. diam., projecting 36 ins. above ground, and in a mound of stone, 6 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 dependent resurvey of the S bdy. of T 26 N, R 30 E; there is no remaining evidence of the original stone monument. This monument is accepted as the best available evidence of the original cor. position, from which the original bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine stump, 31 ins. diam., bears N 58 1/4° E, 80 1/2 lks. dist., mkd. with an open blaze at base, with a ponderosa pine log lying to the E with illegible scribe marks visible on open blaze. (Record: N 62° E, 81 lks.)</p> <p style="padding-left: 40px;">A ponderosa pine, 30 ins. diam., bears N 32° W, 257 1/2 lks. dist., with a healed blaze. (Record: N 32 1/4° W, 249 lks.)</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears N 21 1/4° E, 348 lks. dist., mkd. T26N R30E S32 BT.</p> <p>Add the marks 1984 to the brass cap.</p> <hr/> <p>N 89°54' W, on the S bdy. of sec. 31.</p> <p>Over rolling, mountainous land.</p>

## BOOK 5279

Dependent Resurvey of the S Bdy. of T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona

CHAINS											
	Along the N side of EPNG underground pipeline and graded road.										
38.03	<p>The 1/4 sec. cor. of sec. 6 only, T 25 N, R 30 E, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, and bent to the E, in a mound of stone, 1 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 dependent resurvey of the S bdy. of T 26 N, R 30 E, from which the original bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 30 ins. diam., bears S 19° E, 54 lks. dist., with a healed blaze. (Record: S 19 1/4° E.)</p> <p style="padding-left: 40px;">A ponderosa pine, 31 ins. diam., bears S 82 1/2° W, 84 lks. dist., with a partially healed blaze and illegible scribe marks.</p>										
40.11	<p>The 1/4 sec. cor. of sec. 31 only, T 26 N, R 30 E, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1927 dependent resurvey of the S bdy. of T 26 N, R 30 E; there is no evidence of the original stone monument. This monument is accepted as the best available evidence of the original cor. position.</p> <p>Add the marks T26N R30E T25N R30E 1984 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 89°40' W, beginning new measurement.</p>										
37.31	<p>The closing cor. of Tps. 25 N, Rs. 29 and 30 E, monumented with an iron post, 3 ins. diam., firmly set, projecting 24 ins. above ground, and in a mound of stone, 3 ft. base, 6 ins. high, with brass cap mismarked.</p> <p>Remark the brass cap to read</p> <div style="text-align: center; margin: 10px 0;"> <p>T26N R30E S31</p> <hr style="width: 50%; margin: 0 auto;"/> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S1</td> <td style="padding: 0 5px;">S6</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">R29E C C R30E</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">T25N</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1984</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1927</td> </tr> </table> </div> <p>from which the remaining original bearing tree</p>	S1	S6	R29E C C R30E		T25N		1984		1927	
S1	S6										
R29E C C R30E											
T25N											
1984											
1927											

BOOK 5279

Dependent Resurvey of the S Bdy. of T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>39.48</p> <p>0.86</p>	<p>A ponderosa pine, 16 ins. diam., bears S 32 1/2° E, 38 lks. dist., with a scribe marks N R30E S6 BT visible on partially healed blaze.</p> <hr/> <p>The cor. of T 26 N, Rs. 29 and 30 E, set, mkd. and witnessed as described in the official record of the dependent resurvey of T 26 N, R 29 E, executed concurrently under this same group.</p> <hr/> <p>Dependent Resurvey of a portion of the E bdy. of T 26 N, R 30 E, Gila and Salt River Meridian, Arizona</p> <hr/> <p>Restoring the resurvey executed by Paul L. Reeves in 1978</p> <hr/> <p>From the 1/4 sec. cor. of sec. 19 only, T 26 N, R 31 E, monumented with an iron post, 2 1/2 in. diam., set, mkd. and witnessed as described in the official record of the 1978 dependent resurvey of a portion of the E bdy. of T 26 N, R 30 E.</p> <p>N 0°40' E, on the E bdy. of sec. 24, T 26 N, R 30 E.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of sec. 24 only, T 26 N, R 30 E, at proportionate dist.; there is no remaining evidence of the 1978 cor.</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 28 ins. long, over a 5 1/2 ft. steel fence post, flush with the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N</p> <p>R30E   R31E</p> <p>1/4 S24  </p> <p>1984</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S 83°04' W, 434.5 ft. dist., with brass cap mkd. 1/4 S24 RM 434.5 FT 1984 and an arrow pointing to the cor. point.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N 42°55' W, 262.8 ft. dist., with brass cap mkd. 1/4 S24 RM 262.8 FT 1984 and an arrow pointing to the cor. point.</p>
--	---



## BOOK 5279

Dependent Resurvey of a portion of the E bdy. of T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath each of the stainless steel post.</p> <p>Cor. located in the flood plain of Black Creek, drains irregularly SE.</p>
20.81	<p>Point for the N 1/16 sec. cor. of sec. 24 only, T 26 N, R 30 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16   S24   1984</p> <p>From this point an iron pipe, 2 ins. diam., firmly set in concrete, 6 ins. below the surface of the ground, bears N 73°30' W, 69.4 lks. dist. This point was established for the N 1/16 sec. cor. of sec. 24 by J.G. Martinez, Arizona L. S. No. 2315, in 1963, using improper procedures and is not utilized in the course of this resurvey.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>
40.00	<p>The cor of secs. 18 and 19 only, T 26 N, R 31 E, monumented with an iron post 2 1/2 ins. diam., with brass cap mkd. as described in the official record of the 1978 dependent resurvey of a portion of the E bdy. of T 26 N, R 30 E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0° 40 E, beginning new measurement</p>
0.76	<p>The cor. of secs. 13 and 24 only, T 26 N, R 30 E, monumented with an iron post, 2 1/2 in. diam., with brass cap mkd. as described in the official record of the 1978 dependent resurvey of a portion of the E bdy. of T 26 N, R 30 E.</p> <hr/>

Dependent. Resurvey of the Abandoned South Boundary. of the Navajo Indian Reservation. through T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p style="text-align: center;">Reestablishment of the survey executed by J.G. Evans, U.S. Deputy Surveyor, in 1884-85</p> <hr style="width: 20%; margin: auto;"/> <p>Note: All mile posts on the abandoned reservation boundary in this township were searched for and those recovered now serve as angle points on the section lines. Those mile posts that were not recovered will hereinafter have no validity and are not called for in the body of this field note record. All corners on this line will now function as corners of equal status.</p> <p>From the closing cor. of secs. 12 and 13, T 26 N, R 30 E, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, witnessed and mkd. as described in the official record of the 1978 dependent resurvey of a portion of the E bdy. of T 26 N, R 30 E.</p> <p>S 89°51' W, bet. secs. 12 and 13, identical with the abandoned S bdy. of the Navajo Indian Reservation.</p> <p>Over broken, rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, 1 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E S12 1/4 — S13 1984</p> <p>from which</p> <p style="text-align: center;">A forked juniper, 14 ins. diam., bears S 44 3/4° E, 78 1/2 lks. dist., mkd. 1/4 S13 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>From this point, a local monument, set for the 1/4 sec. cor. of secs. 12 and 13 by M.A. Perce, Arizona L.S. No. 2615, in 1963 and recorded with the Navajo Tribal Utility Authority, Window Rock, AZ., bears N 13°59' W, 49.3 lks. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 16 ins. above ground, with galvanized iron cap mkd. PERCE ENGR TCG NO. 2 LS 2615, this point was determined by using improper procedures and is not utilized in the course of this survey.</p>
--------	--

Dependent Resurvey of the Abandoned South Boundary of the Navajo Indian Reservation through T 26 N, R 30 E, Gila and Salt River Meridian, Arizona

CHAINS	<p>From this same point, a sandstone boulder, 35 x 6 x 6 ins., lying loose atop the ground, mkd. 1/4 on one face, bears N 9°51' W, 48.9 lks. This stone was set for the 1/4 sec. cor. of secs. 12 and 13 by James A. Lamport, U.S. Deputy Surveyor, in 1900, during the course of an unauthorized survey. It is therefore not utilized during the course of this resurvey. Destroy the stone.</p>								
80.00	<p>The closing cor. of secs. 13 and 14, perpetuated by M. A. Perce, Arizona L.S. 2615, and recorded in the Apache County Court House, St. Johns, Arizona, in 1967, monumented with an iron rebar, 1/2 in. diam., firmly set, 12 ins. below ground, with an aluminum cap, 1 in. diam., mkd. PERCE ENG. LS 2615. This point is accepted as a careful and faithful perpetuation of the original cor. position, and is also the best available evidence of the location of the abandoned S bdy. of the Navajo Indian Reservation, This cor. now functions as the cor. of secs. 11, 12, 13 and 14.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 40 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2" style="padding: 0 10px;">T26N R30E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S11</td> <td style="padding: 0 5px;">S12</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S14</td> <td style="padding: 0 5px;">S13</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">1984</td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A power pole, bears N 23° E, 17 1/2 lks. dist., mkd. at base X BO.</p> <p style="margin-left: 40px;">The SE cor. of the Henry Thomas residence, a brown stucco house, bears S 16 1/2° W, 115 1/2 lks. dist.</p> <p>Deposit the iron rebar with cap inside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>N 89°46' W, bet. secs. 11 and 14.</p> <p>Over rolling to mountainous land.</p>	T26N R30E		S11	S12	S14	S13	1984	
T26N R30E									
S11	S12								
S14	S13								
1984									
1.70	<p>Center of a graded, graveled road, 20 ft. wide, bears N and S.</p>								

Dependent Resurvey of the Abandoned South Boundary of the Navajo Indian Reservation through T 26 N, R 30 E, Gila and Salt River Meridian, Arizona

CHAINS	
7.50	The NW cor. of the Coffee Subdivision, monumented with an iron pipe, 2 ins. diam., projecting 4 ins. above ground, bears North, 11.9 lks. dist.
12.00	Center of a graded, graveled road, 20 ft. wide, bears N 5° E and S 5° W.
19.75	The NW cor. of the lands of Jim McAvoy, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 13 ins. above ground, bears North 25.6 lks. dist.
	Cor. is located 1.5 lks. NE of the cor. of sheep fences extending S and W.
39.74	The 1/4 sec. cor. of sec. 14 only, established by person(s) unknown, with an iron rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground. This is accepted as the best available evidence of the original cor. position and of the location of the abandoned S bdy. of the Navajo Indian Reservation.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T26N R30E</p> <hr style="width: 10%; margin: auto;"/> <p>1/4 S14</p> <p>1984</p>
	from which
	A power pole, bears N 13 3/4° E, 25 1/2 lks. dist., mkd. at base X BO.
	Deposit the local rebar inside the stainless steel post.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.
	Cor. is located under a 4 strand barbed wire fence, extending SE and NW.
	<hr style="width: 20%; margin: auto;"/>
	N 89°45' W, beginning new measurement.
0.26	Point for the 1/4 sec. cor. of sec. 11 only.

Dependent. Resurvey of the Abandoned South Boundary of the Navajo Indian Reservation through T 26 N, R 30 E, Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T26N R30E 1/4 S11 ----- 1984</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>
	<p>Cor. is located 24 lks. N of the left bank of a wash, 10 ft. high, bears S 7° E and NW.</p>
<p>1.10</p>	<p>Wash, 150 lks. wide, 10 ft. deep, drains S 7° E.</p>
	<p>Enter mountainous land, through juniper, pinyon and sagebrush.</p>
<p>19.87</p>	<p>Point for the W 1/16 sec. cor. of sec. 14 only.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">----- W 1/16 S14 1985</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>
<p>27.80</p>	<p>A graded road, bears S 30° E and N 30° W.</p>
<p>39.74</p>	<p>The closing cor. of secs. 14 and 15, reestablished by Tommy R. Conley and recorded in the Apache County Court House, St. Johns, Arizona, in December 1970, monumented with a galvanized iron cap, 1 in. diam., mkd. LID LS 7687, set flush with the surface of exposed concrete, with a 1 in. diam. iron pipe to the NE and a fence post to the SW. This point is accepted as a careful and faithful reestablishment of the position of the original cor., and the best available evidence of the location of the abandoned S bdy. of the Navajo Indian Reservation. This cor. now functions as the cor. of secs. 14 and 15 only.</p>
	<p>At the cor. point</p>
	<p>Atop the LID cor. set a stainless steel post,</p>

Dependent Resurvey of the Abandoned South Boundary of the Navajo Indian Reservation through T 26 N, R 30 E, Gila and Salt River Meridian, Arizona

CHAINS	<div style="text-align: center;"> <p>T26N R30E S11</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S15</td> <td style="padding: 0 5px;">S14</td> </tr> <tr> <td colspan="2" style="text-align: center; padding-top: 5px;">1984</td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A pinyon, 10 ins. diam., bears S 52 1/4° E, 68 lks. dist., mkd. T26N R30E S14 BT.</p> <p style="margin-left: 40px;">A pinyon, 16 ins. diam., bears S 43 3/4° W, 189 1/2 lks. dist., mkd. T26N R30E S15 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <hr/> <p>N 89°51' W, bet. secs. 11 and 15.</p> <p>Over mountainous land.</p> <p>0.52 Point for the cor. of secs. 10 and 11 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, 1 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>T26N R30E S10   S11</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center; padding-top: 5px;">S15</td> </tr> <tr> <td colspan="2" style="text-align: center; padding-top: 5px;">1984</td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A juniper, 9 ins. diam., bears N 70 1/2° E, 58 lks. dist., mkd. T26N R30E S11 BT.</p> <p style="margin-left: 40px;">A juniper, 24 ins. diam., bears N 19 1/2° W, 34 lks. dist., mkd. T26N R30E S10 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Continue measurement between secs. 10 and 15.</p> <p>39.52 Point for the 1/4 sec. cor. of sec. 15 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>	S15	S14	1984		S15		1984	
S15	S14								
1984									
S15									
1984									

Dependent Resurvey of the Abandoned South Boundary of the  
Navajo Indian Reservation through T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">T26N R30E</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1/4 S15 1984</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 23 ins. diam., bears S 17° E, 123 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 21 ins. diam., bears S 40 1/2° W, 64 lks. dist., mkd. 1/4 S15 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>From this point, a cor., not of record (cancelled), established for the 1/4 sec. cor. of secs. 10 and 15 by James A. Lampert, U.S. Deputy Surveyor, in 1900, determined by distance intersection from the original bearing trees, bears N 31°05' W, 63.5 lks. dist. This is not utilized and destroyed all evidence of the cor., and defaced the bearing trees.</p> <p>40.52 Point for the 1/4 sec. cor. of sec. 10 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, 1 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1/4 S10</p> <p style="text-align: center;">1984</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears N 18°09' E, 27.8 ft. dist., with brass cap mkd. T26N R30E RM 1/4 S10 27.8 FT. 1984, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p style="padding-left: 40px;">A point on sandstone outcrop, 35 x 15 x 6 ft. above ground, bears N 75 1/2° E, 72 1/2 lks. dist., mkd. X BO</p> <p style="padding-left: 40px;">A ponderosa pine, 21 ins. diam., bears N 12 1/4° E, 157 1/2 chs. dist., mkd. 1/4 S10 BT</p>
--------	--

Dependent Resurvey of the Abandoned South Boundary. of the  
Navajo Indian Reservation through T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Cor. is located 10 lks. N of a small wash, 10 lks. wide, 1 ft. deep, drains S 25° E.</p>
76.31	<p>The 47 mile cor, monumented with a sandstone, 18 x 12 x 4 ins., firmly set 6 ins. in the ground, in a mound of stone, 2 ft. base, 10 ins. high, with illegible chisel marks on the E face, from which, the remaining original bearing trees</p> <p style="padding-left: 40px;">A pinyon, 15 ins. diam., bears N 78 3/4° E, 48 1/2 lks. dist., mkd. on partially healed blaze NIR 4 VIII M. (Record: N 80° E, 60 lks.)</p> <p style="padding-left: 40px;">A pinyon, 13 ins. diam., bears S 42 1/4° W, 32 lks. dist., mkd. with illegible scribe marks on partially healed blaze.</p> <p>This cor. now functions as an angle point, on the abandoned S bdy. of the Navajo Indian Reservation</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R30E</p> <p>S10</p> <hr style="width: 10%; margin: 0 auto;"/> <p>AP</p> <p>1984</p> </div> <p>Bury the original stone alongside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Cor. is located 75 lks. W of a trail road, bears N and S.</p>
2.73	<p style="text-align: center;">_____</p> <p>N 89°59' W, beginning new measurement.</p> <p>Point for the cor. of secs. 15 and 16 only, hereinafter described.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N 89°59' W, bet. secs. 10 and 16.</p>



Dependent Resurvey of the Abandoned South Boundary of the Navajo Indian Reservation through T 26 N, R 30 E, Gila and Salt River Meridian, Arizona

CHAINS	<p>Over mountainous, rugged land.</p>								
1.48	<p>Point for the cor. of secs. 9 and 10 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, and in a collar of stone, 1 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T26N</td> <td style="padding: 0 5px;">R30E</td> </tr> <tr> <td style="padding: 0 5px;">S9</td> <td style="padding: 0 5px;">S10</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; text-align: center; padding: 5px 0;">S16</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 5px 0;">1984</td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A pinyon, 11 ins. diam., bears N 74 ° E, 30 lks. dist., mkd. T26N R30E S10 BT.</p> <p style="margin-left: 40px;">A pinyon, 12 ins. diam., bears N 4 1/2° W, 21 lks. dist., mkd. T26N R30E S9 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Continue measurement bet. secs. 9 and 16.</p>	T26N	R30E	S9	S10	S16		1984	
T26N	R30E								
S9	S10								
S16									
1984									
1.70	<p>A trail road, bears S 40° E and N 40° W.</p>								
40.93	<p>Point for the 1/4 sec. cor. of sec. 16 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T26N</td> <td style="padding: 0 5px;">R30E</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; text-align: center; padding: 5px 0;">1/4 S16</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 5px 0;">1984</td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A pinyon, 15 ins. diam., bears S 53° E, 21 1/2 lks. dist., mkd. X BT.</p> <p style="margin-left: 40px;">A juniper, 7 ins. diam., bears S 77° W, 100 lks. dist., mkd. 1/4 S16 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>	T26N	R30E	1/4 S16		1984			
T26N	R30E								
1/4 S16									
1984									

Dependent Resurvey of the Abandoned South Boundary of the  
Navajo Indian Reservation through T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona

CHAINS	
41.48	<p>Point for the 1/4 sec. cor. of sec. 9 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R30E 1/4 S9</p> <hr style="width: 10%; margin: auto;"/> <p>1984</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pinyon, 9 ins. diam., bears N 34 3/4° E, 19 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A pinyon, 11 ins. diam., bears N 65 1/4° W, 11 lks. dist., mkd. 1/4 S9 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>
81.48	<p>Point for the cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R30E S8   S9</p> <hr style="width: 10%; margin: auto;"/> <p>S16 1984</p> </div> <p>from which</p> <p style="padding-left: 40px;">A juniper, 16 ins. diam., bears N 17 1/4° E, 160 1/2 lks. dist., mkd. T26N R30E S9 BT.</p> <p style="padding-left: 40px;">A pinyon, 24 ins. diam., bears N 29 1/2° W, 32 1/2 lks. dist., mkd. T26N R30E S8 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Continue measurement bet. secs. 8 and 16.</p>

Dependent Resurvey of the Abandoned South Boundary of the  
Navajo Indian Reservation through T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona.

CHAINS	
81.86	The cor. of secs. 16 and 17 only, hereinafter described.
	<hr/> N 89°59' W, bet. secs. 8 and 17.  Over mountainous land.
28.85	Wood pole power line, 6 strand, bears S 34° E and N 34° W.
29.80	Center of Arizona State Highway No. 264, asphalt surfaced, 40 lks. wide, bears S 34° E, and N 34° W.
30.65	Wood pole power line, 8 strand, bears S 34° E and N 34° W.
35.40	A trail road, bears S 30° E and N 30° W.
39.62	Point for the 1/4 sec. cor. of sec. 8 only.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;">             T26N R30E              1/4 S8  <hr style="width: 10%; margin: auto;"/>             1984           </div>
	from which
	<div style="padding-left: 40px;">             A ponderosa pine, 30 ins. diam., bears N 31 1/2° E, 48 1/2 lks. dist., mkd. 1/4 S8 BT.           </div>
	<div style="padding-left: 40px;">             An oak, 9 ins. diam., bears N 55 1/2° W, 141 1/2 lks. dist., mkd. X BT.           </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.
39.81	Point for the 1/4 sec. cor. of sec. 17 only.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.
	<div style="text-align: center;">             T26N R30E  <hr style="width: 10%; margin: auto;"/>             1/4 S17              1984           </div>

Dependent Resurvey of the Abandoned South Boundary of the  
Navajo Indian Reservation through T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona.

CHAINS									
	<p>from which</p> <p>A ponderosa pine, 32 ins. diam., bears S 25 1/2° E, 148 lks. dist., mkd. X BT.</p> <p>A ponderosa pine, 29 ins. diam., bears S 60 1/2° W, 28 lks. dist., mkd. 1/4 S17 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>								
79.62	<p>Point for the cor. of secs. 7, 8, 17 and 18, determined at the intersection of the projection of a line from the 1/4 sec. cor. through the original closing cor., with the abandoned S bdy Navajo Indian Reservation.</p> <p>Set a stainless steel post, 28 ins long 2 1/2 ins diam, 10 ins in the ground, to bed rock, in a mound of stone 4 ft base to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T26N</td> <td>R30E</td> </tr> <tr> <td>S7</td> <td>S8</td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> <tr> <td colspan="2">1984</td> </tr> </table> </div>	T26N	R30E	S7	S8	S18	S17	1984	
T26N	R30E								
S7	S8								
S18	S17								
1984									
	<p>from which</p> <p>A fir, 18 ins. diam. , bears N 35 1/4° E, 60 lks. dist., mkd T26N R30E S8 BT</p> <p>A fir, 18 ins. diam., bears S 70°1/2 E, 33 lks. dist., mkd. T26N R30E S17 BT</p> <p>A ponderosa pine, 14 ins. diam., bears N 33° W, 32 lks. dist. mkd. T26N R30E 26 BT</p> <p>From this point, the original closing cor. of secs. 17 and 18, bears S 1°31'W, 6.1 lks dist, hereinafter described.</p>								
	<p>N 89°59' W, bet. secs. 7 and 18.</p> <p>Over mountainous land.</p>								
20.00	<p>Bottom of a large wash, 5 chs. wide, 100 ft. deep, drains irregularly E. (scaled)</p>								

Dependent Resurvey of the Abandoned South Boundary of the  
Navajo Indian Reservation through T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona

CHAINS	
35.00	Large wash, 2 chs. wide, 100 ft. deep, drains irregularly SE. (scaled)
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E S7 1/4 — S18 1984</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 27 ins. diam., bears S 42 3/4° W, 165 1/2 lks. dist., mkd. by healed blaze at base.</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears N 4° W, 50 lks. dist., mkd. 1/4 S7 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>From this point, a sandstone, 20 x 20 x 3 ins., not of record (cancelled), established for the 1/4 sec. cor. of secs. 7 and 18 by James A. Lamport, U.S. Deputy Surveyor, in 1900, firmly set, 3 ins. above ground, mkd. - 1 4 L on S face, in a scattered mound of stone, 4 ft. base, 10 ins. high, bears S 81°10' W, 74.3 lks. dist. This is not utilized during the course of this resurvey. Destroy the stone.</p> <p>Enter logged area.</p>
76.59	<p>The original 50 mile cor., monumented with a mound of stone, 3 ft. base, 1 ft. high, with the original sandstone, 24 x 18 x 3 ins., mkd. PL and other illegible marks, lying atop ground near the mound of stone, from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A stump hole, bears N 67 3/4° W, 115 lks. dist., with pine log and attached roots laying atop the ground nearby, with scribing BT visible in open blaze. (Record: N 78° W, 135 lks.)</p> <p>This cor. now functions as an angle point, on the abandoned S bdy. of the Navajo Indian Reservation,</p>

Dependent Resurvey of the Abandoned South Boundary of the Navajo Indian Reservation through T 26 N, R 30 E, Gila and Salt River Meridian, Arizona

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R30E S7</p> <hr style="width: 20%; margin: 0 auto;"/> <p>AP 1984</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A juniper, 16 ins. diam., bears N 41 1/2° W, 37 1/2 lks. dist., mkd. AP51 S7 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears S 13 1/4° E, 88 lks. dist., mkd. AP51 S18 BT.</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 89°59' W, beginning new measurement.</p> <p>3.94 Point for the closing cor. of secs. 7 and 18, at intersection with the W bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding-right: 10px;">T26N</td> <td style="border-left: 1px solid black; padding-left: 10px; padding-right: 10px;">T26N</td> <td></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px; padding-right: 10px;">R30E</td> <td></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px; padding-right: 10px;">S7</td> <td></td> </tr> <tr> <td style="padding-right: 10px;">S13</td> <td style="border-left: 1px solid black; padding-left: 10px; padding-right: 10px;">S18</td> <td style="padding-left: 10px;">CC</td> </tr> <tr> <td style="padding-right: 10px;">R29E</td> <td style="border-left: 1px solid black; padding-left: 10px; padding-right: 10px;"></td> <td></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px; padding-right: 10px;"></td> <td></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px; padding-right: 10px;"></td> <td></td> </tr> </table> <p style="text-align: center; margin-top: 5px;">1984</p> </div>	T26N	T26N			R30E			S7		S13	S18	CC	R29E								
T26N	T26N																					
	R30E																					
	S7																					
S13	S18	CC																				
R29E																						

Dependent Resurvey of the Abandoned South Boundary of the  
Navajo Indian Reservation through T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona

CHAINS	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears N 40° E, 128 1/2 lks. dist., mkd. T26N R30E S7 CC BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 22 ins. diam., bears S 50 1/4° E, 341 lks. dist., mkd. T26N R30E S18 CC BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>From this point, a sandstone, 24 x 15 x 3 ins., not of record, (cancelled) established for the closing cor. of secs. 7 and 18, by James A. Lamport, U.S. Deputy Surveyor, in 1900, loosely set, 4 ins. in the ground, and in a mound of stone, 2 ft. base, 6 ins. high, mkd. with 6 grooves on the E face, 4 grooves and CC on the S face, 6 grooves on the W face, bears S 77°07' E, 3.6 lks. dist. This is not utilized during the course of this resurvey. Destroy all evidence of the cor.</p> <p>From this same point, the cor. of secs. 12 and 13 only, T 26 N, R 29 E, bears N 0°10' W, 3.92 chs. dist. monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap mkd. as described in the official record of the dependent resurvey of the E bdy. of T 26 N, R 29 E, executed concurrently under this same group.</p> <p>From this same point, the 1/4 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp. bears S 0°10' E, 35.98 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap mkd. as described in the official record of the dependent resurvey of the E bdy. of T 26 N, R 29 E, executed concurrently under this same group.</p> <hr/>
--------	---

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>Reestablishment of the survey executed by James A. Lamport, U.S. Deputy Surveyor, in 1900.</p> <hr/>
	<p>From the cor. of secs. 35 and 36, on the S bdy. of the Tp., hereinbefore described.</p>
	<p>N 0°37' W, bet. secs. 35 and 36.</p>
	<p>Over rolling land on a trail road between two barbed wire fences, 5 strand, 60 ft. apart.</p>
40.24	<p>Point for the 1/4 sec. cor. of secs. 35 and 36 at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>T26N R30E 1/4 S35   S36 1984</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>
	<p>Cor. is located 3 lks. W of the W edge of a little used trail road, bears N and S.</p>
57.50	<p>Wood pole power line, 4 strand, bears E and W.</p>
58.70	<p>EPNG underground gas line, bears N 80° E and S 80° W.</p>
60.20	<p>Center of a wash, 10 lks. wide, 2 ft. deep, drains N 65° E and S 45° E. Leave trail road and parallel fence lines.</p>
61.80	<p>A graded road, bears E and W.</p>
69.10	<p>A trail road, bears N 75° E and S 75° W.</p>
72.15	<p>Transwestern underground gas line, bears E and W.</p>
75.60	<p>A trail road, bears S 40° E and N 40° W.</p>
80.48	<p>Point for the cor. of secs. 25, 26, 35 and 36 at proportionate dist.; there is no remaining evidence of the original cor.</p>



Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T26N</td> <td>R30E</td> </tr> <tr> <td>S26</td> <td>S25</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S35</td> <td>S36</td> </tr> <tr> <td colspan="2" style="text-align: center;">1984</td> </tr> </table>	T26N	R30E	S26	S25			S35	S36	1984	
T26N	R30E										
S26	S25										
S35	S36										
1984											
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>										
	<p>From the cor. of secs. 25 and 36 only, on the E bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1978 dependent resurvey of a portion of the E bdy. of T 26 N, R 30 E.</p>										
	<p>N 89°53' W, bet. secs. 25 and 36.</p>										
	<p>Over rolling land.</p>										
<p>39.90</p>	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p>										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T26N</td> <td>R30E</td> </tr> <tr> <td></td> <td>S25</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S36</td> </tr> <tr> <td colspan="2" style="text-align: center;">1984</td> </tr> </table>	T26N	R30E		S25	1/4	—		S36	1984	
T26N	R30E										
	S25										
1/4	—										
	S36										
1984											
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>										
<p>42.50</p>	<p>Left bank of Black Creek, 5 ft. high, bears S 70° E and N 70° W.</p>										
<p>43.00</p>	<p>Right bank of Black Creek, 5 ft. high, bears N 25° E and S 25° W.</p>										
<p>50.05</p>	<p>Underground gas line, with adjacent trail road to the E, bears N 10° E, and S 10° W.</p>										
<p>60.60</p>	<p>Center of a wash, 8 lks. wide, 3 ft. deep, drains S 40° E.</p>										

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
79.80	The cor. of secs. 25, 26, 35 and 36.
	N 0°20' E, bet. secs. 25 and 26.
	Over gently rolling land.
14.48	A fence cor. bears E, 73 lks. dist., fences, 4 strand barbed wire, extending N 70° E, S 5° E and N 5° W, in poor condition.
39.45	A barbed wire fence, 4 strand, extending N 75° E and S 70° W.
40.24	Point for the 1/4 sec. cor. of secs. 25 and 26 at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T26N R30E 1/4 S26   S25 1984</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.
	Cor. located 70 lks. N of the center of a trail road, bears E and W, at the base of the S side of Butterfly Butte.
	Thence over the E side of Butterfly Butte, thence over rolling land.
74.49	Wood pole power line, 3 strand, bears N 75° E and S 75° W.
77.84	Center of wash, 60 lks. wide, 10 ft. deep, drains S 5° E.
80.48	Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T26N R30E S23   S24 ----- S26   S25 1984</p>

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p>From this point an Arizona State Highway Department right-of-way monument, marking the W right-of-way of Navajo Route No. 12, bears N 12°11' E, 24.64 chs. dist., monumented with a concrete cylinder, 6 ins. diam., loosely set and leaning to the NW, projecting 6 ins. above ground, with a brass tablet, 3 ins. diam., mkd. ARIZONA HIGHWAY DEPT 6737.386 65 + 72.00 1961.</p> <p>From this same point an Arizona State Highway Department right-of-way monument, marking the E right-of-way of Navajo Route No. 12, bears N 15°41' E, 24.43 chs. dist., monumented with a concrete cylinder, 6 ins. diam., firmly set, projecting 6 ins. above ground, with a brass tablet 3 ins. diam., mkd. ARIZONA HIGHWAY DEPT 1961, witnessed by a 4 x 4 in. angle iron, firmly set, projecting 22 ins. above ground, painted POT 65 + 72.00, 3.0 lks. northerly.</p> <p>From this same point the NE cor. of an 'L' shaped house, the southernmost house of a group of 5 houses, bears S 55°14' E, 7.85 chs. dist.</p> <p>From this same point an Arizona State Highway Department right-of-way monument, marking the W right-of-way of Navajo Route No. 12, bears S 45°05' E, 10.46 chs. dist., monumented with a concrete cylinder, 6 ins. diam., projecting 14 ins. above ground, with a brass tablet, 3 ins. diam., mkd. ARIZONA HIGHWAY DEPT 1961.</p> <p>From this same point an Arizona State Highway Department right-of-way monument, marking the E right-of-way of Navajo Route No. 12, bears S 37°02' E, 9.95 chs. dist., monumented with a concrete cylinder, 6 ins. diam., firmly set, projecting 4 ins. above ground, with a brass tablet, 3 ins. diam., mkd. ARIZONA HIGHWAY DEPT 1961, witnessed by a 4x4 in. angle iron, firmly set, projecting 30 ins. above ground, painted P.C. 88 + 09.02, 3.0 lks. northerly.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <hr/> <p>From the cor. of secs. 24 and 25 only, on the E bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., with brass cap mkd. as described in the official record of the 1978 dependent resurvey of a portion of the E bdy. of T 26 N, R 30 E.</p> <p>S 89°57' W, bet. secs. 24 and 25.</p> <p>Over rolling land.</p>
--------	---

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
4.60	A trail road, bears S 20° E and N 20° W.
14.93	A barbed wire fence, 5 strand, extending S 40° E and N 40° W.
26.59	A barbed wire fence, 5 strand, extending S 70° E and N 70° W.
33.80	Underground water line, bears N 10° E and S 10° W.
39.67	Point for the 1/4 sec. cor. of secs. 24 and 25 at proportionate dist.; there is no remaining evidence of the original cor. position.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T26N R30E S24 1/4 — S25 1984</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.
	From this point, a sandstone 14 x 10 x 3 ins., bears N 57°33' E, 88 lks. dist. lying loose atop the ground, mkd. 1/4 on one face, alongside which is a car axle, 1 in. diam., firmly set, projecting 3 ins. above ground. Local residents in the area indicated that the land was at one time cultivated and it was concluded that the sandstone had been moved from its original position. This monument was not utilized during the course of this resurvey.
	Bury the stone alongside the stainless steel post.
59.98	A barbed wire fence, 6 strand, extending S 60° E and N 60° W.
70.50	A graded road, bears N 10° E and S 10° W.
72.60	Wood pole power line, 2 strand, bears S 40° E and N 40° W.
77.00	A graded road, bears S 60° E and N 60° W.
79.34	The cor. of secs. 23, 24, 25 and 26.

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	N 0°09' E, bet. secs. 23 and 24.
	Over rolling land.
3.20	A graded road, bears S 30° E and N 30° W.
6.59	Wood pole power line, 2 strand, bears N 20° E and S 20° W.
8.70	Center of Navajo Route No. 12, asphalt surfaced, 55 ft. wide, bears N 15° E and S 15° W.
13.80	A graded road, bears N 80° E and S 80° W.
27.26	Wood pole power line, 20 strand, bears N 25° E and S 25° W.
28.40	A trail road, bears S 60° E and N 60° W.
35.80	Wash, 15 lks. wide, 3 ft. deep, drains E.
40.24	The 1/4 sec. cor. of secs. 23 and 24, monumented with a
	sandstone, 16 x 10 x 4 ins., loosely set, 6 ins. in the ground,
	and in a collar of stone, 1 ft. base, to top, mkd. 1/4 on the W
	face.
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post,
	25 ins. long, 2 1/2 ins. diam., bonded to a magnetic poly
	breakaway base, 26 ins. in the ground, and in a collar of stone,
	1 1/2 ft. base, to top, with brass cap mkd.
	T26N R30E
	1/4
	S23   S24
	1984
	Bury the original stone alongside the stainless steel post.
	_____
	N 0°30' E, beginning new measurement.
10.64	Intersect sheep fence with 2 strands barbed wire, marking the S
	bdy. of a cemetery, bears E and W. Enter cemetery.
19.99	Point for the N 1/16 sec. cor. of secs. 23 and 24.

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S23   S24 1984</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Cor. is located 1 lk. N of a sheep fence with 2 strands barbed wire, marking the N bdy. of a cemetery, bears E and W. Exit cemetery and enter the lands of the St. Michaels Indian School.</p>
39.98	<p>Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E S14   S13 ----- S23   S24 1984</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>
6.10	<p>From the cor. of secs. 13 and 24 only, on the E bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., with brass cap mkd. as described in the official record of the 1978 dependent resurvey of a portion of the E bdy. of T 26 N, R 30 E.</p> <p>N 89°37' W, bet. secs. 13 and 24.</p> <p>Over rolling land.</p> <p>Sheep fence with 2 strands barbed wire, bears S 20° E and N 20° W.</p>
10.10	Center of Black Creek, 4 chs. wide, 3 ft. deep, drains S 20° W.
19.49	Underground water line, bears N 40° E and S 40° W.

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
30.30	Wood pole power line, 3 strand, bears N 15° E and S 15° W.
31.20	A trail road, bears S 35° E and N 35° W.
37.35	Center of Navajo Route No. 12, asphalt surfaced, 55 ft. wide, bears S 5° E and N 5° W.
39.61	<p>The 1/4 sec. cor. of secs. 13 and 24, perpetuated by J.G. Martinez, Arizona L.S. No. 2315, in 1963, not recorded, monumented with a iron pipe, 1 3/4 ins. diam., firmly set in concrete, projecting 6 ins. above ground. This point is accepted as a careful and faithful perpetuation of the cor. position.</p> <p>At the cor. point</p> <p>Saw off the iron pipe and set a brass tablet, 3 1/2 ins. diam., with shank 4 ins. long, cemented into the iron pipe, projecting 2 ins. above ground, with top mkd.</p> <p style="text-align: center;">T26N R30E S13 1/4 — S24 1984</p> <p>From this point an Arizona State Highway Department right-of-way monument, marking the E right-of-way of Navajo Route No. 12, bears N 11°36' E, 11.73 chs. dist., monumented with a concrete cylinder, 6 ins. diam., firmly set, projecting 3 ins. above ground, with a brass tablet, 3 ins. diam., mkd. ARIZONA HIGHWAY DEPT 1961, witnessed by a 4x4 in. angle iron, northerly, 3 lks. dist., firmly set, projecting 26 ins. above ground, painted P.T. 16 + 04.79.</p> <p>From this point an Arizona State Highway Department right-of-way monument, marking the W right-of-way of Navajo Route No. 12, bears S 8°40' E, 6.50 chs. dist., monumented with a concrete cylinder, 6 ins. diam., firmly set, projecting 6 ins. above ground, with a brass tablet, 3 ins. diam., mkd. ARIZONA HIGHWAY DEPT 36 + 42.10 1961, witnessed by a 4 x 4 in. angle iron, northerly, 3 lks. dist., firmly set, projecting 28 ins. above ground, painted P.C. 36 + 42.10.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>Cor. is located in a fence cor., 4 strands barbed wire, in poor condition with the barbed wire lying on the ground, extending S 10° E and N 80° W.</p>
	<p style="text-align: center;">_____</p> <p>N 89°51' W, beginning new measurement.</p>
0.30	Wash, 20 lks. wide, 8 ft. deep, drains irregularly S.
5.45	A barbed wire fence, 4 strand, extending S 80° E and N 80° W, in poor condition, with the barbed wire lying atop ground.
19.44	Wood pole power line, 4 strand, bears S 20° E and N 20° W.
20.09	Point for the W 1/16 sec. cor. of secs. 13 and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">S13 W 1/16 — S24 1984</p>
	From this point, an iron pipe, 1 3/4 ins. diam., firmly set in concrete, projecting 2 ins. above ground, bears S 74°48' W, 16.8 lks. dist. This point was established for the W 1/16 sec. cor. of secs. 13 and 24, by J. G. Martinez, Arizona L. S. No. 2315, in 1963, using improper procedures, and is not utilized during the course of this survey.
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
	Enter the lands of the St. Michaels Indian School.
21.90	Wood pole power line, 19 strand, bears S 20° E and N 20° W.
35.30	Wash, 23 lks. wide, 3 ft. deep, drains S 20° E.
36.00	Underground pipeline, bears N 15° E and S 15° W.
40.18	The cor. of secs. 13, 14, 23 and 24.
	<hr/>



Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	N 0°31' W, bet. secs. 13 and 14.
	Over rolling, broken land, through the lands of St. Michaels Indian School.
11.00	Wash, 30 lks. wide, 2 ft. deep, drains S 30° E.
11.60	Underground pipeline, bears S 40° E and N 40° W.
19.99	Point for the S 1/16 sec. cor. of secs. 13 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	S 1/16
	S14   S13
	1984
	From this point, an iron pipe, 1 3/4 ins. diam., firmly set, projecting 5 ins. above ground, bears S 69°02' W, 17.9 lks. dist. This point was established for the S 1/16 sec. cor. of secs. 13 and 14, by J. G. Martinez, Arizona L. S. No. 2315, in 1963, using improper procedures, and is not utilized during the course of this survey.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.
	Cor. is located 6 lks. N and 8 lks. E of a fence cor., 5 strand barbed wire, extending N and E.
	Leave the lands of St. Michaels Indian School.
35.40	Wood pole power line, 4 strand, bears S 60° E and N 60° W.
35.48	S right-of-way fence of Arizona State Highway No. 264, 4 strand, bears S 60° E and N 60° W.
36.10	Underground water pipeline, bears S 60° E and N 60° W.
37.13	Center of Arizona State Highway No. 264, 60 ft. wide, asphalt surfaced, bears generally S 60° E and N 60° W.

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
38.30	Underground sewer pipeline, bears S 60° E and N 60° W.
38.53	N right-of-way fence of Arizona State Highway No. 264, 5 strand, bears irregularly S 30° E and N 30° W.
39.98	<p>The 1/4 sec. cor. of secs. 13 and 14, reestablished by persons unknown, monumented with an iron pipe, 1/2 in. diam., firmly set, flush with the surface of the ground. This point is accepted as a careful and faithful perpetuation of the original cor. position.</p>
<p>T26N R30E 1/4 S14   S13 1984</p>	
<p>From this point an Arizona Department of Transportation, Highway Division, right-of-way monument, marking the S. right-of-way of Arizona State Highway No. 264, monumented with an aluminum tablet, 3 ins. diam., set flush with the ground in concrete, mkd. ADOT HIGHWAY DIV. 6819.37 1977, bears N.89°51' E., 5.79 chs. dist., witness by a 4x4 in. angle iron, firmly set, projecting 28 ins. above ground, painted P.T. 561+22.03, 2.3 lks. easterly.</p>	
<p>From this same point an Arizona Department of Transportation Highway Division right-of-way monument, marking the N. right-of-way Arizona State Highway No. 264, monumented with an aluminum tablet, 3 ins. diam., firmly set, flush with the ground in concrete, mkd. ADOT HIGHWAY DIV ELEV 6822.84 1977, bears N.89° 53' E., 4.07 chs. dist., witnessed by a 4x4 in. angle iron, firmly set, projecting 24 ins. above ground in painted SEC. LINE 561+22.03, 2.1 lks. northerly.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>From this same point an Arizona Department of Transportation, Highway Division, right-of-way monument, marking the N right-of-way of Arizona State Highway No. 264, bears S 71°58' E, 2.55 chs. dist., monumented with an aluminum tablet, 3 ins. diam., firmly set, flush with the ground in concrete, mkd. ADOT HIGHWAY DIV. ELEV. 6821.34 1977, witnessed by a 4 x 4 in. angle iron, easterly, 3 lks. dist., firmly set, projecting 24 ins. above ground, painted P.T. 554 + 82.97.</p>
	<p>From this same point an Arizona Department of Transportation, Highway Division, right-of-way monument, marking the S right-of-way of Arizona State Highway No. 264, bears S 40° E, 4.87 chs. dist., monumented with an aluminum tablet, 3 ins. diam., set flush with the ground in concrete, mkd. ADOT HIGHWAY DIV. 6616.55 1977, witnessed by a 4 x 4 in. angle iron, firmly set, projecting 28 ins. above ground, painted P.T. 554 + 82.97, 2.0 lks., westerly.</p>
	<p>Bury the iron pipe alongside the stainless steel post.</p>
	<hr/> <p>N 0°10' W, beginning new measurement.</p>
	<p>Enter residential area.</p>
36.06	<p>The cor. of secs. 11, 12, 13 and 14, on the abandoned S bdy. of the Navajo Indian Reservation, hereinbefore described.</p>
	<hr/> <p>From the cor. of secs. 34 and 35, on the S bdy. of the Tp., hereinbefore described.</p>
	<p>N 0°15' W, bet. secs. 34 and 35.</p>
	<p>Over mountainous land.</p>
19.50	<p>Wash, drains NE. (scaled)</p>
39.88	<p>The 1/4 sec. cor. of secs. 34 and 35, monumented with a sandstone, 20 x 6 x 6 ins., firmly set, 4 ins. in the ground, in a scattered mound of stone, mkd. 1/4 35 on the E face and 34 on the W face.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E 1/4 S34   S35 1984</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N 9° E, 41 1/2 lks. dist., mkd. 1/4 S35 BT.</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears S 19° W, 283 1/2 lks. dist., mkd. 1/4 S34 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 1°12' W, beginning new measurement.</p>
6.70	Wood pole power line, 11 strand, bears N 80° E and S 80° W.
6.80	Underground gas line, bears N 60° E and S 60° W.
7.20	Center of a asphalt surfaced road, 21 ft. wide, bears S 80° E and N 80° W.
8.00	Wood pole power line, 4 strands, bears S 80° E and N 80° W.
9.10	Underground gas line, bears S 80° E and N 80° W.
21.70	Wood pole power line, 2 strand, bears S 65° E and N 65° W.
40.69	The cor. of secs. 26, 27, 34 and 35, determined from the remains of the original bearing trees

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS									
	<p>A stump hole, bears N 47 3/4° E, 165 lks. dist., with a pinyon lying nearby, 11 ins. diam., mkd. by a partially healed blaze. (Record: N 47° E)</p> <p>A pinyon, 16 ins. diam., bears S 39 1/4° E, 174 lks. dist., mkd. NE COR 4 at head level and T26N R30E S35 BT at base. (Record: S 41°E)</p> <p>A stump hole, bears N 32 3/4° W, 313 1/2 lks. dist., with a dead pinyon lying nearby, with faint illegible scribe marks. (Record: N 32° W, 212 lks.) Note: Field conditions reveal that the official record of the original survey erroneously stated the distance to be 212 lks. and should have been 312 lks.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, 2 ft. base, 6 ins. high, with brass cap mkd.</p> <table border="1" data-bbox="852 955 998 1113"> <tr> <td>T26N</td> <td>R30E</td> </tr> <tr> <td>S27</td> <td>S26</td> </tr> <tr> <td>S34</td> <td>S35</td> </tr> <tr> <td colspan="2">1984</td> </tr> </table> <p>from which a new bearing tree</p> <p>A pinyon, 12 ins. diam., bears N 32° E, 168 1/2 lks. dist., mkd. T26N R30E S26 BT.</p> <p>From this point a broken sandstone, 12 x 8 x 2 ins., mkd. with 1 groove on one face and 2 grooves on the opposite face, falls near the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S 89°41' W, bet. secs. 26 and 35.</p> <p>Over rolling, broken land.</p>	T26N	R30E	S27	S26	S34	S35	1984	
T26N	R30E								
S27	S26								
S34	S35								
1984									
17.65	Wood pole power line, 21 strand, bears N 5° E and S 5° W.								

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
19.00	Center of Navajo Route No. 12, asphalt surfaced, 55 ft. wide, bears N 5° E and S 5° W.
19.90	Wood pole power line, 2 strand, bears N 5° E and S 5° W, also barbed wire fence, 5 strand, bears N 5° E and S 5° W.
39.87	<p>Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T26N R30E S26 1/4 — S35 1984</p>
	<p>From this point an Arizona State Highway Department right-of-way monument, marking the W right-of-way of Navajo Route No. 12, bears N 52°14' E, 28.51 chs. dist., monumented with a concrete cylinder, 6 ins. diam., firmly set, projecting 3 ins. above ground, with a brass tablet 3 ins. diam., mkd. ARIZONA STATE HIGHWAY 1961, witnessed by a 4 x 4 in. angle iron, northerly, 3 lks. dist., firmly set, projecting 22 ins. above ground, painted POT 125 + 57.30, 3.0 lks. northerly.</p>
	<p>From this same point an Arizona State Highway Department right-of-way monument, marking the E right-of-way of Navajo Route No. 12, bears N 54°20' E, 29.59 chs. dist., monumented with a concrete cylinder, 6 ins. diam., firmly set, projecting 5 ins. above ground, with a brass tablet 3 ins. diam., mkd. ARIZONA STATE HWY 1961, witnessed by a 4 x 4 in. angle iron, northerly, 3 lks. dist., firmly set, projecting 24 ins. above ground, painted POT 125 + 57.30.</p>
	<p>From this same point an Arizona State Highway Department right-of-way monument, marking the E right-of-way of Navajo Route No. 12, bears S 42°43' E, 27.66 chs. dist., monumented with a concrete cylinder, 6 ins. diam., firmly set, projecting 8 ins. above ground, with a brass tablet, 3 ins. diam., mkd. ARIZONA STATE HWY 1961, witnessed by a 4 x 4 in. angle iron, northerly, 3 lks. dist., firmly set, projecting 20 ins. above ground, painted POT 150 + 61.45 PC.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Cor. located in a fenced field, with 2 occupied residences 1/4 mi. N, and 1 occupied residence 1/4 mi S.</p>
79.74	<p>The cor. of secs. 26, 27, 34 and 35.</p> <hr/>
	<p>N 0°13' E, bet. secs. 26 and 27.</p> <p>Over rolling, broken land.</p>
39.82	<p>The 1/4 sec. cor. of secs. 26 and 27, determined from the remains of an original bearing tree</p> <p style="padding-left: 40px;">A pinyon, 25 ins. diam., bears N 80° E, 237 lks. dist., with faint illegible scribe marks.</p> <p>At the cor. point</p> <p>Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2 1/2 ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, and in a mound of stone, 1 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E 1/4 S27   S26 1984</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A juniper, 20 ins. diam., bears N 86 3/4° W, 407 lks. dist., mkd. 1/4 S27 BT.</p> <hr/>
	<p>N 1°05' E, beginning new measurement.</p>
40.07	<p>The cor. of secs. 22, 23, 26 and 27, determined from the original bearing trees</p>

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS											
	<p>A juniper, 16 ins. diam., bears N 27° E, 191 lks. dist., with faint illegible scribe marks visible on partially healed blaze. (Record: N 26° E.)</p> <p>A juniper, 14 ins. diam., bears S 44 1/2° W, 20 lks. dist., with faint illegible scribe marks visible on partially healed blaze. (Record: S 53° W.)</p> <p>At the cor. point</p> <p>Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2 1/2 ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T26N</td> <td>R30E</td> </tr> <tr> <td>S22</td> <td>S23</td> </tr> <tr> <td colspan="2" style="text-align: center;"> </td> </tr> <tr> <td>S27</td> <td>S26</td> </tr> <tr> <td colspan="2" style="text-align: center;">1984</td> </tr> </table> <p>from which a new bearing tree</p> <p>A juniper, 18 ins. diam., bears S 86 1/4° W, 204 lks. dist., mkd. T26N R30E S27 BT</p> <p>From this point a sandstone 32 x 12 x 4 ins., lying on the ground, mkd. with 1 faint chisel mark, falls near the stainless steel post.</p> <p>Bury the original stone alongside the iron post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S 89°15' W, bet. secs. 23 and 26.</p> <p>Over rolling, broken land.</p> <p>2.65 Wood pole power line, 2 strand, bears N 25° E and S 25° W.</p> <p>3.70 Center of Navajo Route No. 12, asphalt surfaced, 56 ft. wide, bears N 25° E and S 25° W.</p> <p>7.60 Wood pole power line, 21 strand, bears N 5° E and S 5° W.</p> <p>39.65 Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p>	T26N	R30E	S22	S23			S27	S26	1984	
T26N	R30E										
S22	S23										
S27	S26										
1984											



Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E S23 1/4 — S26 1984</p> <p>from which</p> <p style="text-align: center;">A juniper, 19 ins. diam., bears N 45 3/4° W, 476 1/2 lks. dist., mkd. 1/4 S23 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>79.30 The cor. of secs. 22, 23, 26 and 27.</p>
	<hr/> <p>N 0°35' W, bet. secs. 22 and 23.</p> <p>Over rolling, broken land.</p> <p>40.58 The 1/4 sec. cor. of secs. 22 and 23, monumented with a sandstone 18 x 18 x 4 ins., firmly set, projecting 8 ins. above ground, mkd. 1/4 22 on the E face and 23 on the W face, with a iron pipe, 2 ins. diam., projecting 16 ins from the ground, firmly set along side, and a rebar, 1/2 in. diam., firmly set flush with the ground, bears West 1.1 lks. dist.</p> <p>At the cor. point</p> <p>Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E 1/4 S22   S23 1984</p> <p>from which</p> <p style="text-align: center;">A pinyon, 16 ins. diam., bears S 86 1/2° E, 264 lks. dist., mkd. 1/4 S23 BT.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>Bury the sandstone monument and local monuments alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N 0°01' W, beginning new measurement.</p>
5.00	<p>A graded road, bears N 80° E and S 80° W.</p>
	<p>Thence descend abrupt edge, thence over level pasture and cultivated lands.</p>
20.32	<p>Point for the N 1/16 sec. cor. of secs. 22 and 23.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">N 1/16 S22   S23 1984</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post alongside the cor.</p>
	<p>Cor. located in the SE cor. of a cornfield 45 lks. W of a 4 strand barbed wire fence extending N and S, and 15 lks. N of a 2 strand barbed wire fence extending E and W.</p>
	<p>Thence ascend S slope.</p>
40.64	<p>The cor. of secs. 14, 15, 22 and 23, monumented with a rebar, 1/2 in. diam., firmly set, projecting 14 ins. above the ground, and in a mound of stone, 3 ft. base, 1 ft. high, alongside which is a sandstone 24 x 15 x 3 ins., mkd. with 3 grooves on one face and 2 grooves on another face, lying loose in the mound of stone. This point is accepted as a careful and faithful perpetuation of the original cor. position, from which the remaining original bearing trees</p>
	<p style="text-align: center;">A juniper, 12 ins. diam., bears N 70 1/4° E, 111 1/2 lks. dist., mkd. N R30E S14 BT. (Record: N 67° E, 106 lks.)</p>

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS									
	<p>A pinyon, 25 ins. diam., bears N 83 1/2° W, 310 lks. dist., mkd. T26N R30E S 15 BT on partially healed blaze. (Record: N 84° W, 317 lks.)</p> <p>At the cor. point</p> <p>Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2 1/2 ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, and in a mound of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T26N</td><td>R30E</td></tr> <tr><td>S15</td><td>S14</td></tr> <tr><td>S22</td><td>S23</td></tr> <tr><td colspan="2">1984</td></tr> </table> </div> <p>from which a new bearing tree</p> <p>A juniper, 14 ins. diam., bears S 48 1/4° W, 138 1/2 lks. dist., mkd. T26N R30E S22 BT.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S 89°54' W, bet. secs. 14 and 23.</p> <p>Over rolling lands of the St. Michaels Indian School.</p> <p>17.70 A graded road, bears S 65° E and N 65° W.</p> <p>18.75 A barbed wire fence, 5 strand, extending S 65° E and N 65° W.</p> <p>Enter pasture land.</p> <p>39.75 A barbed wire fence, 6 strand, extending N and S.</p> <p>39.90 A graded road, bears N and S.</p> <p>40.17 The 1/4 sec. cor. of secs. 14 and 23, perpetuated by J.G. Martinez, Arizona L.S. No. 2315, in 1963, not recorded, monumented with an iron pipe, 2 ins. diam., firmly set in concrete, projecting 4 ins. above ground 1 lk. E of which is a sandstone, 16 x 8 x 5 ins., firmly set in same concrete as the iron pipe, flush with the concrete, with no marks visible. This point is accepted as a careful and faithful perpetuation of the cor. position.</p>	T26N	R30E	S15	S14	S22	S23	1984	
T26N	R30E								
S15	S14								
S22	S23								
1984									

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p>At the cor. point</p> <p>Set a brass tablet, 3 1/2 ins. diam., with shank, 4 ins. long, cemented into the iron pipe, projecting 4 ins. above ground, with top mkd.</p> <p style="text-align: center;">T26N R30E S14 1/4 — S23 1984</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 89°59' W, beginning new measurement.</p> <p>Leave the lands of Saint Michaels Indian School.</p> <p>0.10 Sheep fence, with 3 strands of barbed wire, extending N 20° E and S 20° W.</p> <p>Enter pasture land.</p> <p>0.85 Wood pole power line, 3 strands, bears N 20° E and S 20° W.</p> <p>9.45 Sheep fence, with 3 strands of barbed wire, extending N 10° E and S 10° W.</p> <p>9.99 The E-W 1/64 sec. cor. of secs. 14 and 23, established by J.G. Martinez, Arizona L.S. No. 2315, in 1963, not recorded, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 1 in. above ground, with a rebar, set by the Office of Land Development of the Navajo Tribe, 5/8 in diam., firmly set, projecting 1/2 in. above ground, adjacent to the N. This point is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S14 E-W 1/64 — S23 1984</p> <p>Deposit the rebar inside and the iron pipe alongside of the stainless steel post.</p>
--------	--

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <hr/>
	<p>N 89°59'W, beginning new measurement</p>
8.06	<p>A barbed wire fence, 5 strand, extending N 10° E and S 10° W.</p>
	<p>Leave pasture land.</p>
9.99	<p>The W 1/16 sec. cor. of secs. 14 and 23, established by the Office of Land Development of the Navajo Tribe, not recorded, monumented with a rebar, 5/8 in. diam., firmly set, projecting 1/2 in. above ground. This point is accepted as a careful and faithful establishment of the cor. position.</p>
	<p>At the cor. point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S14 W 1/16 — S23 1984</p>
	<p>Deposit the rebar inside the stainless steel post.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <hr/>
	<p>N 89°59' W, beginning new measurement</p>
19.98	<p>The cor. of secs. 14, 15, 22 and 23.</p> <hr/>
	<p>N 0°07' E, bet. secs. 14 and 15.</p>
	<p>Over rolling, mountainous land.</p>
5.25	<p>Wood pole power line, 2 strand, bears NE and SW.</p>
39.96	<p>The 1/4 sec. cor. of secs. 14 and 15, monumented with a sandstone, 22 x 14 x 4 ins., loosely set, 1 in. in the ground, and in a mound of stone, 3 ft. base, 1 ft. high, faintly mkd. 14 on the E face, from which the remaining original bearing tree</p>

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>A pinyon, 15 ins. diam., bears S 69 1/4° E, 97 lks. dist., with faint illegible scribe marks on partially healed blaze. (Record: S 70° E)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E 1/4 S15   S14 1984</p> <p>from which a new bearing tree</p> <p>A juniper, 15 ins. diam., bears S 41 1/2° W, 91 lks. dist., mkd. 1/4 S15 BT.</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°08' E, beginning new measurement.</p>
9.70	Center of a populated area containing 3 residences, spreading 10 chs. E and W, and 5 chs. N and S.
15.64	A trail road, bears S 20° E and N 20° W.
18.30	Center of Arizona State Highway, No. 264, asphalt surfaced, 60 lks. wide, bearing in curve S 85° E and N 80° W.
19.99	Point for the N 1/16 sec. cor. of secs. 14 and 15.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p style="text-align: center;">N 1/16 S15   S14 1985</p> <p>From this point an Arizona Department of Transportation, Highway Division right-of-way monument, marking the N right-of-way of Arizona State Highway No. 264, bears N 0°34' E, 91 lks. dist., monumented with a galvanized steel tablet, 3 ins. diam., firmly set, flush with the ground in concrete, mkd. ADOT HIGHWAY DIV ELEV. 6907.85 1977, witnessed by a 4 x 4 in. angle iron, northerly, 2.4 lks. dist., firmly set, projecting 31 ins. above ground, painted 497 + 45.67.</p> <p>From this same point an Arizona Department of Transportation, Highway Division right-of-way monument, marking the N right-of-way of Arizona State Highway No. 264, bears N 4°24' E, 14 lks. dist., monumented with a galvanized steel tablet, 3 ins. diam., firmly set, 6 ins. below the surface of the ground in concrete, mkd. ADOT HIGHWAY DIV ELEV. 6909.05 1977, witnessed by a 4 x 4 in. angle iron, easterly, 2.3 lks. dist., firmly set, projecting 17 ins. above ground, painted HW.R.OFW. SEC. LINE 497 + 45.67.</p> <p>From this same point an Arizona Department of Transportation, Highway Division right-of-way monument, marking the N right-of-way of Arizona State Highway No. 264, bears N 76°55' E, 36 lks. dist., monumented with a galvanized steel tablet, 3 ins. diam., firmly set, flush with the surface of a concrete abutment on the E side of a cattle guard, mkd. ADOT HIGHWAY DIV ELEV. 69 STA.</p> <p>From this same point an Arizona Department of Transportation, Highway Division right-of-way monument, marking the S right-of-way of Arizona State Highway No. 264, bears S.0°17'E., 2.17 chs. dist., monumented with a galvanized steel tablet, 3 ins. diam., firmly set, 1 in. below the surface of the ground in concrete, mkd. ADOT HIGHWAY DIV ELEV. 6907.70 1977, witnessed by a 4 x 4 in. angle iron, westerly, 2.0 lks. dist., firmly set, projecting 24 ins. above ground, painted HW.R.of W. SEC LINE 497 + 45.67.</p>
--------	---

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p>From this same point an Arizona Department of Transportation, Highway Division right-of-way monument, marking the S right-of-way of Arizona State Highway No. 264, bears S 5°48' W, 2.14 chs. dist., monumented with a galvanized steel tablet, 3 ins. diam., firmly set, flush with the surface of a concrete abutment on the E side of a cattle guard, mkd. ADOT HIGHWAY DIV ELEV. 6907.93 STA 497X35 1977.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange colored plastic case beneath the stainless steel post.</p> <p>Cor. located in the N right-of-way of Arizona State Highway No. 264.</p>
36.48	<p>The cor. of secs. 14 and 15 only, on the abandoned S bdy. of the Navajo Indian Reservation, hereinbefore described.</p> <hr/> <p>From the cor. of secs. 33 and 34, on the S bdy. of the Tp., hereinbefore described..</p> <p>N 0°51' W, bet. secs. 33 and 34.</p> <p>Over mountainous land.</p> <p>Descend to wash, drains SE, thence ascend steep left bank of wash, 100 ft., thence over rolling, mountainous land.</p>
40.36	<p>Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T26N R30E 1/4 S33   S34 1984</p> </div> <p>from which</p> <p style="margin-left: 40px;">A pinyon, 10 ins. diam., bears N 53 3/4° E, 173 1/2 lks. dist., mkd. 1/4 S34 BT.</p> <p style="margin-left: 40px;">A pinyon, 13 ins. diam., bears S 45 1/2° W, 113 1/2 lks. dist., mkd. 1/4 S33 BT.</p>



Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Cor. located 50 lks. N of the centerline of Transworld underground gas pipeline, bears NE and SW.</p> <p>54.50 El Paso Natural Gas underground gas pipeline, bears E and W.</p> <p>55.25 Wood pole power line, 3 strand, bears E and W.</p> <p>80.72 The cor. of secs. 27, 28, 33 and 34, determined from the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 22 ins. diam., bears N 21 3/4° E, 50 lks. dist., with faint illegible scribe marks. (Record: N 22° E).</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears S 29 1/2° E, 37 lks. dist., mkd. R 30 E S 34 (Record: S 31° E)</p> <p style="padding-left: 40px;">A juniper, 15 ins. diam., bears S 61 1/4° W, 30 lks. dist., mkd. T26N R30E S33 BT. (Record: S 59° W.)</p> <p style="padding-left: 40px;">A juniper, 9 ins. diam., bears N 64 1/2° W, 55 lks. dist., mkd. R30E S BT. (Record: N 64° W, 53 lks.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 10px;">T26N</td> <td style="padding: 0 10px;">R30E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S28</td> <td style="padding: 0 5px;">S27</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S33</td> <td style="padding: 0 5px;">S34</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">1984</td> </tr> </table> </div> <p>From this point, a sandstone, 12 x 8 x 4 ins., lying atop the ground, mkd. with 3 grooves on one face, falls near the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <hr style="border: 0.5px solid black; margin-top: 20px;"/>	T26N	R30E	S28	S27	S33	S34	1984	
T26N	R30E								
S28	S27								
S33	S34								
1984									

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	From the cor. of secs. 26, 27, 34 and 35.
	S 89°49' W, bet. secs. 27 and 34.
	Over rolling land.
19.90	A trail road, bears S 60° E and West.
40.23	The 1/4 sec. cor. of secs. 27 and 34, determined from the remaining original bearing tree.
	A pinyon, 16 ins. diam., bears N 25° W, 245 lks. dist. with faint illegible scribe marks.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T26N R30E S27 1/4 — S34 1984</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.
	Cor. located 30 lks. E of the center of a trail road, bears N and S.
	From this point the NW fence cor. of the Hunters Point Station of the El Paso Natural Gas Company bears S 18 3/4° E, 10.7 lks. dist., an iron post, 4 1/2 ins. diam., firmly set in concrete, projecting 5 1/2 ft. above ground, with fences extending E and S, and existing mkd. X BO, at the base.
	<p style="text-align: center;">_____</p>
	N 89°13' W, beginning new measurement.
	Enter mountainous land.
40.15	The cor. of secs. 27, 28, 33 and 34.
	<p style="text-align: center;">_____</p>

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	N 1°12' E, bet. secs. 27 and 28.
	Over mountainous land.
40.01	The 1/4 sec. cor. of secs. 27 and 28, monumented with a sandstone, 20 x 13 x 5 ins., firmly set, 3 ins. below the surface of the ground, and in a mound of stone, 3 ft. base, 1 ft. high, mkd. with a faint illegible mark on the S face, from which the remains of an original bearing tree
	A root hole, bears N 43 1/2° E, 24 lks. dist., alongside of which is lying a dead juniper, mkd. 1/4 S27 B on open blaze. (Record: N 48° E, 21 lks.)
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, 2 ft. base, to top with brass cap mkd.
	T26N R30E
	1/4
	S28   S27
	1984
	from which
	A pinyon, 15 ins. diam., bears N 88 1/4° E, 163 1/2 lks. dist., mkd. 1/4 S27 BT.
	A pinyon, 9 ins. diam., bears S 84 3/4 ° W, 249 1/2 lks. dist., mkd. 1/4 S28 BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.
	N 0°02' W, beginning new measurement.
39.32	The cor. of secs. 21, 22, 27 and 28, monumented with a sandstone, 24 x 11 x 7 ins., loosely set in a scattered mound of stone, mkd. with 3 grooves on the E face and 2 grooves on the S face, from which the remaining original bearing trees
	A pinyon, 12 ins. diam., bears N 59 1/2° E, 24 lks. dist., mkd. T26 R30E S22 BT on open blaze. (Record: N 57° E.)

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p>A pinyon, 12 ins. diam., bears S 39 1/2° E, 31 lks. dist., mkd. T26N R30E S27 BT on open blaze. (Record: S 43° E, 30 lks.)</p> <p>A pinyon, 16 ins. diam., bears N 41 1/2° W, 20 lks. dist., mkd. T26N R30E S21 BT on open blaze. (Record: N 38° W)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px;">T26N</td> <td style="padding: 2px;">R30E</td> </tr> <tr> <td style="padding: 2px;">S21</td> <td style="padding: 2px;">S22</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 2px;">S28</td> <td style="border-top: 1px solid black; padding: 2px;">S27</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px;">1984</td> </tr> </table> <p>from which a new bearing tree</p> <p>A pinyon, 12 ins. diam., bears S 34° W, 107 lks. dist., mkd. T26N R30E S28 BT.</p> <p>Deposit the original stone alongside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Cor. located 75 lks. E of a power line, 6 strand, bears S 20° E and N 20° W.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S 89°51' W, bet. secs. 22 and 27.</p> <p>Over rolling to mountainous land.</p> <p>40.27 The 1/4 sec. cor. of secs. 22 and 27, determined from the original bearing trees</p> <p>A pinyon, 12 ins. diam., bears N 3° E, 16 lks. dist., mkd. with faint illegible scribe marks on partially healed blaze. (Record: 50 lks.)</p>	T26N	R30E	S21	S22	S28	S27	1984	
T26N	R30E								
S21	S22								
S28	S27								
1984									

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p>A juniper, 9 ins. diam., bears S 8 1/2° W, 36 lks. dist., mkd. with illegible scribe marks on partially healed blaze. (Record: S 4° W.)</p> <p>Note: The record distance to the N bearing tree cannot be reconciled with the positions of both bearing trees and the positions of the blazes. The record distance from the S bearing tree and the record bearing from the N bearing tree are used to determine the original cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T26N R30E S22 1/4 — S27 1984</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>S 89°56' W, beginning new measurement.</p> <hr/> <p>40.19 The cor. of secs. 21, 22, 27 and 28.</p> <hr/> <p>N 0°16' W, bet. secs. 21 and 22.</p> <p>Over mountainous land.</p> <p>Descend 100 ft. to bottom of canyon.</p> <p>18.00 Center of Cienega Creek drains E. (scaled)</p> <p>Ascend over rugged land with large exposed sandstone outcrops.</p> <p>39.64 The 1/4 sec. cor. of secs. 21 and 22, determined from the remains of an original bearing tree</p> <div style="text-align: center; margin: 10px 0;"> <p>A juniper, 7 ins. diam., bears N 80° W, 21 lks. dist., mkd. 1/4 S21 BT.</p> </div> <p>At the cor. point</p>
--------	--

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>Set a brass tablet, 3 1/4 ins. diam., with 4 ins. long shank, flush in exposed sandstone, cemented in place, with top mkd.</p> <p style="text-align: center;">T26N R30E 1/4 S21   S22 1984</p> <p>from which new bearing trees</p> <p>A pinyon, 10 ins. diam., bears N 52° E, 41 lks. dist., mkd. 1/4 S22 BT.</p> <p>A ponderosa pine, 18 ins. diam., bears S 9° W, 105 1/2 lks. dist., mkd. 1/4 S21 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°37' E, beginning new measurement.</p>
5.00	Top of ascent, thence over rolling mountainous land.
31.00	A trail road, bears S 70° E and N 70° W.
40.88	<p>The cor. of secs. 15, 16, 21 and 22, determined from the original bearing trees</p> <p>A juniper stump, 13 ins. diam., bears N 21° E, 25 lks. dist., with no visible mks. (Record: N 25° E)</p> <p>A ponderosa pine stump, 21 ins. diam., bears S 26 1/4° E, 40 lks. dist., with no visible mks. (Record: S 37° E)</p> <p>A ponderosa pine stump, 20 ins. diam., bears S 7 1/2° W, 82 lks. dist., with no visible mks. (Record: S 17° W)</p> <p>A pinyon, 12 ins. diam., bears N 58 1/2° W, 49 lks. dist., mkd. T26N R30E 16 BT in partially healed blaze. (Record: N 55° W, 50 lks. dist.)</p> <p>At the cor. point</p> <p>Set an stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS									
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T26N R30E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">S16</td> <td style="padding: 2px;">S15</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">S21</td> <td style="padding: 2px;">S22</td> </tr> <tr> <td colspan="2" style="text-align: center;">1984</td> </tr> </table>	T26N R30E		S16	S15	S21	S22	1984	
T26N R30E									
S16	S15								
S21	S22								
1984									
	<p>from which new bearing trees</p> <p>A pinyon, 12 ins. diam., bears N 57 1/2° E, 203 1/2 lks. dist., mkd. T26N R30E S15 BT.</p> <p>A pinyon, 10 ins. diam., bears S 63 1/4° E, 128 lks. dist., mkd. T26N R30E S22 BT.</p> <p>A pinyon, 14 ins. diam., bears S 3 1/2° W, 111 lks. dist., mkd. T26N R30E S21 BT.</p> <p>Cor. is located in a scattered mound of stone, 4 ft. diam.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>								
	<hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S 89°24' W, bet. secs. 15 and 22.</p> <p>Over mountainous land.</p>								
20.22	<p>Point for the E 1/16 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">S15</td> </tr> <tr> <td style="padding-right: 10px;">E 1/16</td> <td style="border-top: 1px solid black; width: 20px;"></td> </tr> <tr> <td colspan="2" style="text-align: center;">S22</td> </tr> <tr> <td colspan="2" style="text-align: center;">1984</td> </tr> </table> </p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>	S15		E 1/16		S22		1984	
S15									
E 1/16									
S22									
1984									
40.44	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented with a sandstone, 22 x 6 x 6 ins., loosely set, 2 ins. in the ground, mkd. 1/4 15 on the N face and 22 on the S face, alongside the N side of which is an iron leaf spring, 33 1/2 x 1 1/4 x 1/4 ins., firmly set, 17 ins. in the ground, and in a mound of stone, 3 ft. base, 1 ft. high, from which an original bearing tree.</p>								

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>A juniper, 12 ins. diam., bears N 1 1/4° E, 32 lks. dist., mkd. 1/4 S15 BT. (Record: N 3° E, 30 lks.)</p> <p>At the cor. point</p> <p>Set an stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E S15 1/4 — S22 1984</p> <p>from which a new bearing tree</p> <p>A pinyon, 16 ins. diam., bears S 6 3/4° W, 81 lks. dist., mkd. 1/4 S22 BT</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <hr/> <p>S 89°25' W, beginning new measurement.</p>
14.20	A trail road, bears SE and NW.
39.34	The cor. of secs. 15, 16, 21 and 22.
	<hr/> <p>N 0°58' E, bet. secs. 15 and 16.</p> <p>Over mountainous land.</p>
10.30	Wash, 1 ch. wide, 50 ft. deep, drains E.
14.00	A trail road, bears E and W.
24.70	A trail road, bears E and W.
32.00	Wash, 15 lks. wide, 20 ft. deep, drains E.
34.40	A trail road, bears SE and NW.



Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
40.11	<p>The 1/4 sec. cor. of secs. 15 and 16, monumented with a sandstone, 28 x 19 x 4 ins., loosely set, 4 ins. in the ground, mkd. 1/4 16 on the W face, from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A root hole, bears S 64 1/2° W, 25 1/2 lks. dist., alongside which is lying a rotten pinyon, 7 ins. diam., with scribe marks 1/4 visible in open blaze. (Record: S 70° W, 20 lks.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E 1/4 S16   S15 1984</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears N 81° E, 148 1/2 lks. dist., mkd. 1/4 S15 BT.</p> <p style="padding-left: 40px;">A pinyon, 13 ins. diam., bears N 72 1/4° W, 70 1/2 lks. dist., mkd. 1/4 S16 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Deposit the original stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°19' E, beginning new measurement.</p>
12.00	Power line, 8 strand, bears S 80° E and N 80° W.
13.70	Center of Arizona State Highway No. 264, asphalt surfaced, 40 lks. wide, bears N 75° E and S 75° W.
37.27	The original closing cor. of secs. 15 and 16, monumented with a sandstone, 24 x 12 x 4 ins., loosely set, 2 ins. in the ground, and in a mound of stone, 2 ft. base, 20 ins. high, mkd. with 3 grooves on the E face, and 4 grooves and CC on the S face, from which the original bearing trees

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p>A ponderosa pine, 26 ins. diam., bears S 21 3/4° E, 73 1/2 lks. dist., mkd. 26N R30 S15 B on open blaze. (Record: S 21 1/2° E, 75 lks.)</p> <p>A juniper, 12 ins. diam., bears S 44° W, 36 1/2 lks. dist., mkd. 26N R30E S16 BT CC. (Record: S 37° W, 40 lks.)</p> <p>Add the marks AM to the sandstone monument and bury it in place.</p> <p>37.36 Point for the cor. of secs. 15 and 16, at intersection with the abandoned S bdy. of the Navajo Indian Reservation.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T26N R30E S10</p> <hr style="width: 50%; margin: 0 auto;"/> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S16</td> <td style="padding: 0 5px;">S15</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1984</td> </tr> </table> </div> <p>From this point original bearing trees, established for the closing cor. of secs. 15 and 16. bear S 19 1/2° E, 82 lks. dist. to the ponderosa pine, and S 35 1/2° W, 43 1/2 lks. dist. to the juniper.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Cor. located 20 ft. W of a wash, 10 lks. wide, 4 ft. deep, drains S.</p> <p>From this point the cor. of secs. 9 and 10 only, on the abandoned S bdy. of the Navajo Indian Reservation, bears N 89°59' W, 1.48 chs. dist., hereinbefore described.</p> <p>From this same point M.P. 47 on the abandoned S bdy of the Navajo Indian Reservation bears S.89°59' E., 2.73 chs. dist., hereinbefore described.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 32 and 33, on the S bdy. of the Tp., hereinbefore described.</p> <p>N 0°23' W, bet. secs. 32 and 33.</p>	S16	S15	1984	
S16	S15				
1984					

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	Over mountainous land.
16.30	Wash, 75 lks. wide, 75 ft. deep, drains N 70° E.
35.60	El Paso Natural Gas Co. underground gas pipeline and trail road, bears N 50° E and S 50° W.
40.20	<p>The 1/4 sec. cor. of secs. 32 and 33, monumented with a rotten pine stump, 2 ft. high, 12 ins. diam., alongside of which is lying a rotten pine log, 12 ins. diam., with faint illegible scribe marks visible on two open blazes, from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears N 61 3/4° W, 4 lks. dist., mkd. with a healed blaze on the E face. (Record: N 85° W.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E 1/4 S32   S33 1984</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A pinyon, 10 ins. diam., bears N 61 3/4° E, 118 1/2 lks. dist., mkd. 1/4 S33 BT</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 1°56' E, beginning new measurement.</p>
9.00	<p>Wash, drains NE. (scaled)</p> <p>Thence over rolling land and descend 100 ft. into Cienega Creek.</p>
38.40	Cienega Creek, 20 lks. wide, drains NE, thence ascend 80 ft. over steep SE slope to rolling, broken land.
40.78	The cor. of secs. 28, 29, 32 and 33, determined from the remaining original bearing trees

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS											
	<p>A juniper, 12 ins. diam., bears S 63 1/2° E, 12 lks. dist., mkd. T N R30E and other illegible scribe marks on open blaze. (Record: S 72° E.)</p> <p>A pinyon, 14 ins. diam., bears N 41 1/4° W, 60 lks. dist., mkd. T26N R30E S BT. (Record: N 41° W.)</p> <p>The base of a forked ponderosa pine, lying on the ground, 22 ins. diam., bears S 54 1/2° W, 24 1/2 lks. dist., mkd. T26N R30E S32 BT on open blaze. (Record: S 52° W)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T26N R30E</td> </tr> <tr> <td style="text-align: center;">S29</td> <td style="text-align: center;">S28</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S32</td> <td style="text-align: center;">S33</td> </tr> <tr> <td colspan="2" style="text-align: center;">1984</td> </tr> </table> <p>from which new bearing trees</p> <p>A ponderosa pine, 20 ins. diam., bears N 52 1/4° E, 175 lks. dist., mkd. T26N R30E S28 BT.</p> <p>A juniper, 10 ins. diam., bears S 69 1/4° W, 25 lks. dist., mkd. T26N R30E S32 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N 89°26' W, bet. secs. 28 and 33.</p> <p>Over rugged mountainous land.</p> <p>24.50 A trail road, bears NE and SW.</p> <p>40.02 The 1/4 sec. cor. of secs. 28 and 33, monumented with a sandstone, 15 x 10 x 4 ins., firmly set, 6 ins. in the ground, with faint illegible marks on the N and S faces, from which the remaining original bearing tree</p>	T26N R30E		S29	S28	-----		S32	S33	1984	
T26N R30E											
S29	S28										
-----											
S32	S33										
1984											

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>A pinyon stump, 8 ins. diam., bears S 7 1/4° E, 13 lks. dist., mkd. S3 BT. (Record: S 10° E, 12 lks.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E S28 1/4 — S33 1984</p> <p>from which</p> <p>A pinyon, 10 ins. diam., bears N 28 3/4° E, 41 lks. dist., mkd. 1/4 S28 BT.</p> <p>A pinyon, 12 ins. diam., bears S 12 1/4° W, 103 1/2 lks. dist., mkd. 1/4 S33 BT.</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <hr/> <p>N 89°08' W, beginning new measurement.</p>
14.50	Wash, 10 lks. wide, 1 ft. deep, drains NE.
29.10	Cienega Creek canyon, 4 chs. wide, 200 ft. deep, bears NE and SW.
37.95	The cor. of secs. 28, 29, 32 and 33.
	<hr/> <p>N 2°33' W, bet. secs. 28 and 29.</p> <p>Over rugged, mountainous land.</p>
3.40	Wash, 20 lks. wide, 10 ft. deep, drains N 75° E.
37.00	S bank of wash, 80 ft. high, bears E and W, descend.
41.05	The 1/4 sec. cor. of secs. 28 and 29, falls in a scattered mound of stone, determined at record dist. from the face of the original bearing trees (center side would not intersect)

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>A rotten pine stump, 35 ins. diam., bears S 36 1/4° E, 62 lks. dist., alongside of which is lying a rotted pine log, with faint illegible scribe marks on open blaze. (Record: S 35° E, 60 lks.)</p> <p>A ponderosa pine, 24 ins. diam. bears N 11 1/2° W, 46 1/2 lks. dist., mkd. with illegible scribe marks. (Record: N 14° W, 45 lks.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E 1/4 S29   S28 1984</p> <p>from which a new bearing tree</p> <p>A ponderosa pine, 12 ins. diam., bears N 76° E, 72 1/2 lks. dist., mkd. 1/4 S28 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Cor. is located in the bottom of a wash, 1 1/2 chs. wide, drains E.</p> <p style="text-align: center;">_____</p> <p>N 0°08' W, beginning new measurement.</p>
1.70	Ascend 80 ft. to N bank of a wash, bears irregularly E and W, thence over rugged, rolling land.
33.00	S rim of canyon, bears NE and SW, descend 250 ft.
37.40	Foot of descent, thence nearly level across canyon bottom.
38.00	Ascend 200 ft. over steep SE slope, to cor.
39.70	The cor. of secs. 20, 21, 28 and 29, determined from three of the original bearing trees
	<p>A juniper, 10 ins. diam., bears N 64° E, 34 1/2 lks. dist., mkd. 21 with other illegible scribe marks on open blaze. (Record: 35 lks.)</p>

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS

A dead juniper, 16 ins. diam., bears S 61° W, 44 1/2 lks.  
dist., mkd. T26N R30E S29 BT. (Record: S 62° W, 45 lks.)

A juniper, 8 ins. diam., bears N 23° W, 27 lks. dist., mkd.  
T26N R30E S20 BT. (Record: N 28° W)

from which the remaining original bearing tree

A dead juniper, 14 ins. diam., bears S 68 1/2° E, 90 lks.  
dist., mkd. T26N R30E S28 BT on open blaze. (Record:  
S 66° E, 95 lks.)

The cor. point falls on edge of sandstone conglomerate ledge,  
8 ft. high, and is impracticable to perpetuate. Select a point  
for a witness cor., N 45° W, 15 lks. dist.

At the witness cor. point

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill  
hole, in exposed sandstone conglomerate, cemented in place, with  
top mkd.

WC	
T26N R30E	
S20	S21
-----	
S29	S28
1984	

from which

A vertical sandstone face, 6 ft. high, bears N 15 1/4° E,  
17 lks. dist., mkd. X BO.

A pinyon, 10 ins. diam., bears S 59 1/4° E, 99 lks. dist.,  
mkd. X BT.

Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic  
case beneath the brass tablet.

Cor. located on steep SE slope, 20 ft. below and 1 ch. S of N  
canyon rim, bears irregularly NE and SW.

---

From the cor. of secs. 21, 22, 27 and 28.

N 89°11' W, bet. secs. 21 and 28.

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	Over rugged, mountainous land.
8.50	A trail road, bears N and S.
14.60	E rim of Cienega Creek canyon, bears irregularly N 30° E and S 30° W, thence descend 100 ft. over steep NW slope.
22.35	Center of Cienega Creek, 60 lks. wide, 1 ft. deep, drains N 30° E, thence ascend over SE slope to cor.
40.07	<p>The 1/4 sec. cor. of secs. 21 and 28, monumented with a sandstone, 19 x 12 x 4 ins., loosely set, 2 ins. in the ground, mkd. 1/4 21 on the S face and illegible marks on the N face, with a large sandstone, 18 x 12 x 2 ins., supporting the original monument on the N side, from which the remains of the original bearing trees</p>
	<p>A rotten pine stump, 18 ins. diam., bears N 2 1/2° E, 46 1/2 lks. dist., mkd. with illegible marks visible on open blaze. (Record: N 5° E, 47 lks.)</p>
	<p>A juniper, 10 ins. diam., bears S 37° W, 35 lks. dist., mkd. with illegible marks visible on partially healed blaze. (Record: S 35° W, 27 lks.)</p>
	At the cor. point
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of petrified wood, 1 1/2 ft. diam., to top with brass cap mkd.</p>
	<p style="text-align: center;">T26N R30E S21 1/4 — S28 1984</p>
	from which new bearing trees
	<p>A forked juniper, 10 ins. diam., bears N 2° W, 37 lks. dist., mkd. 1/4 S21 BT.</p>
	<p>A pinyon, 14 ins. diam., bears S 73 3/4° W, 125 lks. dist., mkd. 1/4 S28 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>



## BOOK 5279

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p>N 87°31' W, beginning new measurement.</p> <p>Ascend irregular SE slope, to ridge crest, thence descend 120 ft. over steep NW slope.</p> <p>34.70 Wash, 15 lks. wide, 1 ft. deep, drains irregularly NE, thence across canyon bottom and ascend across steep SE slope.</p> <p>40.64 The cor. of secs. 20, 21, 28 and 29.</p> <hr/> <p>N 0°16' E, bet. secs. 20 and 21.</p> <p>Ascend 20 ft. over steep SE slope.</p> <p>1.00 N canyon rim, bears irregularly NE and SW, thence over rugged mountainous land.</p> <p>33.80 A trail road, bears E and W, enter newly logged area.</p> <p>39.32 Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E 1/4 S20   S21 1984</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 22 ins. diam., bears N 17° E, 90 lks. dist., mkd. 1/4 S21 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears N 36° W, 72 1/2 lks. dist., mkd. 1/4 S20 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>41.60 Wash, 1 ch. wide, 20 ft. deep, drains N 80° E.</p> <p>78.64 The cor. of secs. 16, 17, 20 and 21, monumented with a sandstone, 20 x 10 x 6 ins., loosely set, 4 ins. in the ground, mkd. with 4 grooves on the E face and 3 grooves on the S face, from which the remains of the original bearing trees</p>
--------	--

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p>A pinyon stump, 16 ins. diam., bears N 26 3/4° E, 49 lks. dist., with no visible marks. (Record: N 47° E, 48 lks.)</p> <p>A pinyon stump, 8 ins. diam., bears S 39 1/4° E, 53 1/2 lks. dist., mkd. S and other illegible scribe marks on an open blaze. (Record: S 80° E, 54 lks.)</p> <p>A juniper, 14 ins. diam., bears S 71° W, 33 lks. dist., mkd. T26N R30E S20 BT on open blaze. (Record: S 60° W, 37 lks.)</p> <p>A juniper, 14 ins. diam., bears N 69° W, 11 lks. dist., mkd. T26N R30E S17 BT on open blaze. (Record: N 80° W, 8 lks.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 2px;">T26N</td> <td style="padding: 2px;">R30E</td> </tr> <tr> <td style="padding: 2px;">S17</td> <td style="padding: 2px;">S16</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 2px;">S20</td> <td style="border-top: 1px solid black; padding: 2px;">S21</td> </tr> <tr> <td colspan="2" style="padding: 2px;">1984</td> </tr> </table> </div> <p>from which new bearing trees</p> <p>A pinyon, 12 ins. diam., bears N 52° E, 35 lks. dist., mkd. T26N R30E S16 BT.</p> <p>A pinyon, 14 ins. diam., bears S 41 1/2° E, 133 1/2 lks. dist., mkd. T26N R30E S21 BT.</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S 89°21' W, bet. secs. 16 and 21.</p> <p>Over mountainous land.</p> <p>37.80 Wood pole power line, 6 strand, bears SE and NW.</p>	T26N	R30E	S17	S16	S20	S21	1984	
T26N	R30E								
S17	S16								
S20	S21								
1984									

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
40.33	<p>The 1/4 sec. cor. of secs. 16 and 21, determined at record bearing and distance from the remains of an original bearing tree</p> <p style="padding-left: 40px;">A stump hole, bears N 15° W, 37 lks. dist., with a pinyon log lying to the E, mkd. 1/4 S16 BT on open blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a mound of stone 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; padding-left: 100px;">       T26N R30E        S16        1/4 —        S21        1984     </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A pinyon, 10 ins. diam., bears S 31 1/4° E, 55 lks. dist., mkd. 1/4 S21 BT.</p> <p style="padding-left: 40px;">A forked juniper, 16 ins. diam., bears N 4 3/4° W, 47 1/2 lks. dist., mkd. 1/4 S16 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 88°45' W, beginning new measurement.</p>
19.50	E rim of canyon, 200 ft. high, bears irregularly NE and SW.
29.60	W rim of canyon, 150 ft. high, bears irregularly E and NW.
40.24	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>N 0°21' W, bet. secs. 16 and 17.</p> <p>Over mountainous land.</p>
6.10	S rim of canyon, 200 ft. high, bears irregularly E and W.
10.20	N rim of canyon, 200 ft. high, bears irregularly E and W.

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
39.60	Wood pole power line, 8 strand, bears E and W.
40.28	Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. below the surface of the ground, with brass cap mkd.
	T26N R30E 1/4 S17   S16 1984
	from which
	A pinyon, 18 ins. diam., bears S 18 1/2° E, 88 1/2 lks. dist., mkd. 1/4 S16 BT.
	A ponderosa pine, 14 ins. diam., bears N 87 1/2° W, 105 lks. dist., mkd. 1/4 S17 BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.
	Cor. is located in abandoned trail road, bears irregularly S 80° E and N 80° W.
44.78	Center of Arizona State Highway No. 264, asphalt surfaced, 25 ft. wide, bearing in curve E and N 80° W.
76.73	The original closing cor. of secs. 16 and 17, determined at record dist. from the remains of the original bearing trees
	A stump, 18 ins. diam., bears S 6 1/2° E, 90 lks. dist., no legible marks. (Record: S 5° E.)
	A ponderosa pine, 27 ins. diam., bears S 57° W, 74 lks. dist., mkd. S17 BT and other illegible scribe marks.
	Cor. not remonumented.
77.06	Point for the closing cor. of secs. 16 and 17, at intersection with the abandoned S bdy. of the Navajo Indian Reservation, now functions as the cor. of secs. 16 and 17 only.

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T26N R30E S8</p> <hr style="width: 10%; margin: 0 auto;"/> <p>S17   S16 1984</p> </div> <p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 25 ins. diam., bears S 73 1/2° E, 73 lks. dist., mkd. T26N R30E S16 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>From this point the cor. of secs. 8 and 9 only, on the abandoned S bdy. of the Navajo Indian Reservation, bears S 89°59' E, 38 lks. dist., hereinbefore described.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 31 and 32, on the S bdy. of the Tp., hereinbefore described.</p> <p>N 0°19' W, bet. secs. 31 and 32.</p> <p>Over mountainous land.</p> <p>40.12 The 1/4 sec. cor. of secs. 31 and 32, monumented with a sandstone, 16 x 5 x 4 firmly set, 4 ins. in the ground, and in a mound of stone, 2 ft. base, 6 ins. high, mkd. 1/4 31 on the W face, from which the remains of the original bearing tree</p> <p style="margin-left: 40px;">A ponderosa pine stump, 22 ins. diam., bears N 62 3/4° E, 82 lks. dist., mkd. 32 and other illegible scribe marks. (Record: N 58° W, 130 lks.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>
--------	--

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p style="text-align: center;">T26N R30E 1/4 S31   S32 1984</p> <p>from which new bearing trees</p> <p>A ponderosa pine, 18 ins. diam., bears N 53° E, 53 1/2 lks. dist., mkd. 1/4 S32 BT.</p> <p>A ponderosa pine, 10 ins. diam., bears S 53 3/4° W, 97 1/2 lks. dist., mkd. 1/4 S31 BT.</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°24' W, beginning new measurement.</p>
4.10	A trail road, bears irregularly E and W.
41.04	<p>The cor. of secs. 29, 30, 31 and 32, monumented with a sandstone, 34 x 10 x 4 ins., loosely set, 3 ins. in the ground, and in a mound of stone, 3 ft. base, 1 1/2 ft. high, with no marks visible, from which the remains of the original bearing trees</p> <p>A dead ponderosa pine, 14 ins. diam., bears N 62 1/4° E, 69 lks. dist., mkd. with illegible scribe marks. (Record: N 58° E, 64 lks.)</p> <p>A root hole, bears S 33 1/4° E, 126 lks., alongside which is lying a rotten ponderosa pine, 14 ins. diam., with no visible scribe marks. (Record: S 32° E, 120 lks.)</p> <p>A ponderosa pine, 22 ins. diam., bears S 2 3/4° E, 28 1/2 lks. dist., mkd. with illegible scribe marks on partially healed blaze. (Record: S 9° W, 27 lks.)</p> <p>A ponderosa pine stump, 24 ins. diam., bears N 46° W, 95 lks. dist., mkd. with a partially healed blaze. (Record: N 47° W, 105 lks.)</p> <p>At the cor. point</p> <p>Set an stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<div style="text-align: center; margin-bottom: 10px;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T26N R30E</td> <td></td> <td style="padding: 0 10px;">S29</td> </tr> <tr> <td style="padding: 0 10px;">S30</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td> <td style="padding: 0 10px;">S29</td> </tr> <tr> <td colspan="3" style="border-top: 1px solid black; height: 5px;"></td> </tr> <tr> <td style="padding: 0 10px;">S31</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td> <td style="padding: 0 10px;">S32</td> </tr> <tr> <td colspan="3" style="text-align: center; padding-top: 5px;">1984</td> </tr> </table> </div> <p>from which new bearing trees</p> <p style="margin-left: 40px;">A ponderosa pine, 18 ins. diam., bears N 89 1/4° E, 38 lks. dist., mkd. T26N R30E S29 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 23 ins. diam., bears S 68 1/2° E, 115 1/2 lks. dist., mkd. T26N R30E S32 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 16 ins. diam., bears N 22 3/4° W, 66 lks. dist., mkd. T26N R30E S30 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Cor. located 80 lks. S of a trail road, bears irregularly N 60° E and S 60° W.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N 89°02' W, bet. secs. 29 and 32.</p> <p>Over mountainous land.</p> <p>41.53 The 1/4 sec. cor. of secs. 29 and 32, monumented with a sandstone, 10 x 10 x 4 ft. above ground, marked with an X and other illegible chisel marks, from which an original bearing tree</p> <p style="margin-left: 40px;">A ponderosa pine, 14 ins. diam., bears S 8° E, 36 lks. dist., with faint illegible scribe marks. (Record: Pinyon, S 2° W, 35 lks.)</p> <p>At the cor. point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in stem, in a drill hole, cemented in place, with top mkd.</p> <div style="text-align: center; margin-top: 20px;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T26N R30E</td> <td></td> <td></td> </tr> <tr> <td style="padding: 0 10px;">S29</td> <td></td> <td></td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;">—</td> <td></td> </tr> <tr> <td style="padding: 0 10px;">S32</td> <td></td> <td></td> </tr> <tr> <td colspan="3" style="text-align: center; padding-top: 5px;">1984</td> </tr> </table> </div>	T26N R30E		S29	S30		S29				S31		S32	1984			T26N R30E			S29			1/4	—		S32			1984		
T26N R30E		S29																													
S30		S29																													
S31		S32																													
1984																															
T26N R30E																															
S29																															
1/4	—																														
S32																															
1984																															

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	from which a new bearing tree
	A ponderosa pine, 20 ins. diam., bears N 25° E, 82 1/2 lks. dist., mkd. 1/4 S29 BT.
	S 89°18' W, beginning new measurement.
3.80	Wash, 23 lks., wide, drains N 50° E.
33.00	A trail road, bears irregularly N and S.
40.08	The cor. of secs. 29, 30, 31 and 32.
	S 88°18' W, bet. secs. 30 and 31.
	Over rolling land.
5.50	Center of a wash drains NE.
15.80	A trail road, bears NE and SW.
37.00	A trail road, bears NE and SW.
39.87	The 1/4 sec. cor. of secs. 30 and 31, monumented with exposed sandstone bedrock marked with a faint X, from which the remains of an original bearing tree
	A ponderosa pine stump, 29 ins. diam., bears N 8 1/2° E, 42 1/2 lks. dist., with scribe marks BT visible.
	(Record: N 8° E, 42 lks.)
	At the cor. point
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in a drill hole, flush with exposed sandstone bedrock, cemented in place, with top mkd.
	T26N R30E
	S30
	1/4 —
	S31
	1984



Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>from which new bearing trees</p> <p>A ponderosa pine, 8 ins. diam., bears S 73 1/4° E, 126 lks. dist., mkd. 1/4 S31 BT.</p> <p>A ponderosa pine, 11 ins. diam., bears N 3° W, 147 lks. dist., mkd. 1/4 S30 BT.</p> <p>Cor. located on the S side of a small wash, 50 ft. deep, 10 lks. wide at the bottom, drains NE.</p> <hr/> <p>N 88°29' W, beginning new measurement.</p>
39.62	<p>The cor. of secs. 25, 30, 31 and 36, on the W bdy. of the Tp., set, mkd. and witnessed as described in the official record of the dependent resurvey of the E bdy. of T 26 N, R 29 E, plat accepted June 17, 1988.</p> <hr/>
	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N 0°39' W, bet. secs. 29 and 30.</p> <p>Over mountainous land.</p>
1.20	<p>A trail road, bears N 30° E and S 30° W.</p> <p>Thence over rugged land and descend 80 ft. over sandstone cliff into wash.</p>
9.00	<p>Wash, drains NE. (scaled)</p> <p>Thence ascend 100 ft. over sandstone cliff, thence over rugged land and descend 150 ft. over sandstone cliff into wash.</p>
28.40	<p>Wash, 20 lks. wide, drains irregularly NE.</p> <p>Thence ascend 150 ft. over sandstone cliff, thence over rugged land and enter logged area.</p>
39.63	<p>The 1/4 sec. cor. of secs. 29 and 30, monumented with a sandstone, 20 x 10 x 6 ins., firmly set, 6 ins. in the ground, and in a scattered mound of stone, 4 ft. base, flush with the ground, mkd. 2P on the E face and 1/4 E on the W face, from which the original bearing trees</p>

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>A ponderosa pine, 28 ins. diam., bears N 70 1/4° E, 27 1/2 lks. dist., mkd. by well healed blaze. (Record: N 70° E, 26 lks.)</p> <p>A root hole, bears N 54 3/4° W, 66 1/2 lks. dist., with a ponderosa pine log lying to the E, 14 ins. diam., mkd. S30 BT on open blaze. (Record: N 56° W, 70 lks.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E 1/4 S30   S29 1984</p> <p>from which a new bearing tree</p> <p>A ponderosa pine, 14 ins. diam., bears N 17 1/2° W , 92 1/2 lks. dist., mkd. 1/4 S30 BT.</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°02' W, beginning new measurement.</p>
2.50	Wash, 45 lks. wide, 10 ft. deep, drains SE.
19.25	A graded road, bears N 30° E and S 30° W.
40.34	<p>The cor. of secs. 19, 20, 29 and 30, monumented with a sandstone, 18 x 10 x 6 ins., loosely set, 2 ins. in the ground, and in a mound of stone, 3 ft. base, 1 ft. high, mkd. with 5 grooves on the E face and 2 grooves on the S face, from which the original bearing trees</p> <p>A rotten ponderosa pine stump, 22 ins. diam., bears N 28° E, 80 1/2 lks. dist., with a rotten log lying to the NE. (Record: N 27° E, 80 lks.)</p>

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

## CHAINS

A ponderosa pine, 28 ins. diam., bears S 85 3/4° E, 60 1/2 lks. dist., mkd. T26N R3 E S2 BT on partially healed blaze. (Record: S 84° E, 64 lks.)

A ponderosa pine stump, 16 ins. diam., bears S 25 1/2° W, 41 lks. dist., with a log lying to the SE mkd. T26N R30E S30 BT on open blaze. (Record: S 25° W, 40 lks.)

A dead ponderosa pine, 24 ins. diam., bears N 86° W, 96 lks. dist., mkd. by a well healed blaze. (Record: N 70° W, 101 lks.)

At the cor. point

Set an aluminum post, 15 ins. long, 1 in. diam., 12 ins. in a drill hole, in solid sandstone, cemented in place, and in 3 ins. of soil, aluminum cap flush with the ground and mkd.

T26N R30E	
S19	S20
-----	
S30	S29
1984	

from which new bearing trees

A ponderosa pine, 19 ins. diam., bears N 61 1/2° E, 185 1/2 lks. dist., mkd. T26N R30E S20 BT.

A ponderosa pine, 31 ins. diam., bears S 43 1/2° E, 296 1/2 lks. dist., mkd. T26N R30E S29 BT.

A ponderosa pine, 12 ins. diam., bears S 44 3/4° W, 39 1/2 lks. dist., mkd. T26N R30E S30 BT.

A juniper, 20 ins. diam., bears N 72 1/2° W, 119 lks. dist., mkd. T26N R30E S19 BT.

Deposit the sandstone monument atop the ground alongside the aluminum post, destroy the mound of stone.

Deposit a bare magnet beneath the aluminum post.

Cor. located 1 ch. S of the center of a wash, 50 ft. deep, 45 lks. wide, drains N 50° E.

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S 88°48' W, bet. secs. 20 and 29.</p> <p>Over rugged land.</p>
39.86	<p>The 1/4 sec. cor. of secs. 20 and 29, determined from the remains of the original bearing trees</p> <p>A ponderosa pine stump, 24 ins. diam., bears N 84 1/4° E, 54 lks. dist., with a log lying to the S mkd. 1/4 S29 on open blaze. (Record: N 88° E)</p> <p>A ponderosa pine stump, 18 ins. diam., bears S 34 1/4° W, 31 lks. dist., with a rotten log lying to the S, no scribing visible. (Record: S 30° W.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, 2 ft. diam., to top, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E S20 1/4 — S29 1984</p> <p>from which new bearing trees</p> <p>A juniper, 15 ins. diam., bears S 49° E, 80 lks. dist., mkd. 1/4 S29 BT.</p> <p>A ponderosa pine, 10 ins. diam., bears N 7 1/2° W, 63 lks. dist., mkd. 1/4 S20 BT.</p> <p>Point falls on a sandstone, 24 x 12 x 3 ins., laying on the ground, mkd. on one face 1 and on the other face 1/4, deposit alongside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 89°34' W, beginning new measurement.</p>
3.80	A graded road, bears SE and NW.

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
4.90	Enter logged area.
40.27	The cor. of secs. 19, 20, 29 and 30.
	<hr/> S 89°35' W, bet. secs. 19 and 30.
	Over rolling land.
39.57	The 1/4 sec. cor. of secs. 19 and 30, monumented with a
	sandstone, 13 x 10 x 4 ins., firmly set, 8 ins. in the ground,
	mkd. 1/4 on the N face and 30 on the S face, from which the
	original bearing trees
	<p style="padding-left: 40px;">An oak, 11 ins. diam., bears S 1/2° W, 88 lks. dist., mkd.</p>
	<p style="padding-left: 40px;">by well healed blaze. (Record: S 30° W, 90 lks.)</p>
	<p style="padding-left: 40px;">An oak, 11 ins. diam., bears N 58° W, 29 lks. dist., mkd. by</p>
	<p style="padding-left: 40px;">well healed blaze. (Record: N 45° W, 25 lks.)</p>
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22
	ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T26N R30E</p>
	<p style="text-align: center;">S19</p>
	<p style="text-align: center;">1/4 —</p>
	<p style="text-align: center;">S30</p>
	<p style="text-align: center;">1984</p>
	from which a new accessory
	<p style="padding-left: 40px;">An exposed sandstone outcrop, 1 ch. in diam., bears</p>
	<p style="padding-left: 40px;">N 2 1/4° E, 104 lks. dist., mkd. X BO</p>
	Bury the original stone alongside the stainless steel post.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case
	beneath the stainless steel post.
	<hr style="width: 20%; margin: auto;"/> N 89°44' W, beginning new measurement.
40.09	The cor. of secs. 19, 24, 25 and 30, on the W bdy. of the Tp.,
	set, mkd. and witnessed as described in the official record of
	the dependent resurvey of the E bdy. of T 26 N, R 29 E, plat
	accepted June 17, 1988.
	<hr/>

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>From the cor. of secs. 19, 20, 29 and 30.</p>
	<p>N 1°04' W, bet. secs. 19 and 20.</p>
6.75	<p>An original line tree, a juniper, 11 ins. diam., mkd. with 2 hack marks on the N face and 2 hack marks on the S face, at chest height</p> <p>from which</p> <p style="padding-left: 40px;">A brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in a drill hole, cemented in place, flush in an exposed sandstone outcrop, 10 ft. x 4 ft. x 6 ins. above ground, for a reference monument, bears S 0°24' E, 38.3 ft. dist. mkd. T26N R30E RM AP S19 38.3 ft. 1984 and an arrow pointing to the line tree. Deposit a magnet in the bottom of the drill hole.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°16' E, beginning new measurement.</p>
23.90	<p>A graded road, bears NE and SW</p>
33.32	<p>Point for the 1/4 sec. cor. of secs. 19 and 20, determined from the remains of the original bearing trees</p> <p style="padding-left: 40px;">A rotten ponderosa pine stump, 20 ins. diam., bears N 16 1/2° E, 36 1/2 lks. dist., with a rotten log laying to the W mkd. 1/4 S20. (Record: N 16° E, 35 lks.)</p> <p style="padding-left: 40px;">A rotten ponderosa pine stump, 24 ins. diam., bears S 49° W, 44 1/2 lks. dist., with a rotten log laying to the E mkd. 1/4 S19 BT. (Record: 43 lks.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T26N R30E 1/4 S19   S20 1984</p> </div> <p>from which new bearing trees</p>

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>A ponderosa pine, 14 ins. diam., bears S 3 1/2° W, 182 lks. dist., mkd. 1/4 S19 BT.</p> <p>A ponderosa pine, 15 ins. diam., bears N 78 1/2° W, 178 lks. dist., mkd. X BT.</p> <p>Recover sandstone fragments with illegible marks visible, N 42 1/2° E., 6 lks. dist., in a scattered mound of stone, 3 ft. diam. Bury the fragments alongside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <hr/> <p>N 0°01' W, beginning new measurement.</p> <p>Over rolling land and descend 150 ft. over sandstone bluff into wash.</p>
24.60	<p>Wash, 75 lks. wide, drains irregularly N 70° E.</p> <p>Ascend 150 ft. over sandstone bluff, thence over rolling land.</p>
32.40	<p>A graded road, bears E and W irregularly.</p>
40.13	<p>The cor. of secs. 17, 18, 19 and 20, monumented with a sandstone, 25 x 18 x 4 ins., loosely set, 4 ins. in the ground, and in a mound of stone, 2 ft. diam., mkd. with 4 grooves on the E face and 3 grooves on the S face, from which the remaining original bearing trees</p> <p>A ponderosa pine, 22 ins. diam., bears S 47° E, 38 lks. dist., mkd. with illegible scribe marks. (Record: S 49° E, 36 lks.)</p> <p>A juniper, 23 ins. diam., bears S 25 1/2° W, 111 1/2 lks. dist., mkd. T26N R30E S19 BT. (Record: S 26° W, 110 lks.)</p>

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px;">T26N</td> <td style="padding: 2px;">R30E</td> </tr> <tr> <td style="padding: 2px;">S18</td> <td style="padding: 2px;">S17</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 2px;">S19</td> <td style="border-top: 1px solid black; padding: 2px;">S20</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px;">1984</td> </tr> </table> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears N 8° E, 98 1/2 lks. dist., mkd. T26N R30E S17 BT.</p> <p style="padding-left: 40px;">A pinyon, 15 ins. diam., bears N 36° W, 152 lks. dist., mkd. T26N R30E S18 BT.</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N 89°12' W, bet. secs. 17 and 20.</p> <p>Over rugged land.</p> <p>40.21 The 1/4 sec. cor. of secs. 17 and 20, determined from the original bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears N 3° E, 71 lks. dist., mkd. 1/4 S17 BT. (Record: N 25° E)</p> <p style="padding-left: 40px;">A ponderosa pine, 23 ins. diam., bears S 5° W, 91 lks. dist., mkd. with illegible scribe marks on a partially healed blaze. (Record: S 7° W)</p> <p>At the cor. point</p> <p>Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2 1/2 ins. diam., bonded to a magnetic poly breakaway base, 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>	T26N	R30E	S18	S17	S19	S20	1984	
T26N	R30E								
S18	S17								
S19	S20								
1984									



Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	T26N R30E
	S17 1/4 — S20 1984
	_____
	N 89°22' W, beginning new measurement.
	Over rolling, rugged land, and descend 100 ft. over a sandstone bluff into wash.
6.00	Wash, 30 lks. wide, 2 ft. deep, drains N 60° E.
	Thence ascend 100 ft. over a sandstone bluff, thence over rolling rugged land.
20.60	A trail road, bears NE and SW.
27.00	A trail road, bears NE and SW.
40.25	The cor. of secs. 17, 18, 19 and 20.
	_____
	N 89°34' W, bet. secs. 18 and 19.
	Over rolling land.
39.96	The 1/4 sec. cor. of secs. 18 and 19, monumented with a sandstone, 24 x 16 x 5 ins., firmly set, 12 ins. in the ground, mkd. 1 on the N face and 1/4 on the S face, from which the original bearing trees
	A pinyon, 14 ins. diam., bears S 29° E, 29 lks. dist., mkd. 1/4 S19 BT. (Record: S 30° E, 28 lks.)
	A ponderosa pine stump, 16 ins. diam., bears N 2 1/4° W, 26 lks. dist., with a log lying to the N mkd. with an open blaze and no visible scribe marks. (Record: N 3° E, 25 lks.)
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T26N R30E S18 1/4 — S19 1984

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>from which a new bearing tree</p> <p style="padding-left: 40px;">A pinyon, 10 ins. diam., bears N 36 1/2° W, 43 1/2 lks. dist., mkd. 1/4 S18 BT.</p> <p>Bury the original stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S 89°47' W, beginning new measurement.</p>
39.98	<p>The cor. of secs. 13, 18, 19 and 24, on the W bdy. of the Tp., set, mkd. and witnessed as described in the official record of the dependent resurvey of the E bdy. of T 26 N, R 29 E, plat accepted June 17, 1988.</p> <hr/>
	<p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>N 0°51' W, bet. secs. 17 and 18.</p> <p>Over rolling, rugged land.</p>
11.00	<p>Wash, drains E. (scaled)</p>
20.60	<p>A trail road, bears E and W.</p>
30.00	<p>Wash, drains S 80° E.</p>
40.10	<p>The 1/4 sec. cor. of secs. 17 and 18, monumented with the original cor. tree, a pinyon, 8 ins. diam. with scribe marks /4 S18 on the W face in partially healed blaze, and a well healed blaze on the E face, from which the original bearing trees</p> <p style="padding-left: 40px;">A pinyon, 10 ins. diam., bears N 61 1/2° E, 46 1/2 lks. dist., mkd. 4 S17. (Record: N 56° E, 47 lks.)</p> <p style="padding-left: 40px;">A pinyon, 13 ins. diam., bears S 86° W, 43 1/2 lks. dist., mkd. by well healed blaze. (Record: N 89° W, 44 lks.)</p>

Dependent Resurvey of a Portion of the Subdivisional Lines  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>from which a new accessory</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N 72°30' W, 6.34 ft. dist., with brass cap mkd. T26N R30E RM S18 6.34 FT 1984, and an arrow pointing to the cor. tree. Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <hr/> <p>N 1°31' E, beginning new measurement.</p>
14.90	A trail road, bears S 55° E and N 55° W.
35.95	<p>The cor. of secs. 7, 8, 17 and 18, at intersection with the abandoned S bdy of the Navajo Indian Reservation, hereinbefore described.</p> <p>From this point the original closing cor. of secs. 17 and 18, bears N 1°31' E, 6 lks. dist. monumented with a sandstone, 20 x 10 x 3 ins., mkd. with 4 grooves on the E and 4 grooves and CC on the S face, from which the original bearing trees</p> <p>A stump, 24 ins. diam., bears S 25 3/4° E, 20 1/2 lks. dist., with no scribe, blaze or hack marks. (Record: S 15° E, 20 lks.)</p> <p>A forked juniper, 24 ins. diam., bears S 43 1/2° W, 101 1/2 lks. dist., hereinbefore described in the notes for the cor. of secs. 7, 8, 17, and 18. (Record: S 43° W, 103 chs.)</p> <p>Add the marks. AM to the sandstone, and bury in place .</p> <hr/>

Survey of a Portion of the E Bdy. of  
T 26 N, R 30 E Gila and Salt River Mer., Arizona

CHAINS	
	<p>From the cor. of secs. 6 and 7, T 26 N, R 31 E, on the E bdy of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 4 ins. above ground, with brass cap mkd as described in the official record of the 1978 survey of a portion of the E bdy. of T 26 N R 30 E.</p> <p>From this point, the cor. of secs. 1 and 12, T 26 N, R 30 W, bears South 2.65 chs. dist., hereinafter described.</p> <p>North, bet. secs. 1 and 6</p>
4.30	A barbed wire fence, 5 strand, extending N 90°E and S 90°W.
12.00	Underground water line, bears N 65°E and S 65°W.
19.40	Black Creek Wash, 100 lks. wide, 3 ft. banks, drains S 20°E.
30.20	Sewer line, bears S 20°E and N 20°W.
36.50	Sewer line, bears S 20°E and N 20°W.
37.35	<p>Point for the 1/4 sec. cor. of sec. 1 only, T 26 N, R 30 E.</p> <p>Set a stainless steel post, 238 ins long, 2 1/2 ins. diam., 24 ins in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R30E   R31E 1/4 S1 1984</p> </div> <p>Deposit a magnet in a 1x1x2 5/8 in. orange colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor is located 50 lks. W of a trail road, bears N and S, and 1.50 chs. E of the left bank of black creek wash, 1 ch. wide, drains S.</p> <p>From this point, the cor of secs. 1 and 12 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above, with brass cap mkd. described in the field notes of the 1978 survey of a portion of the E bdy. of T 26N, R 30 E., bears South 40.00 chs. dist.</p>
40.00	Point for the 1/4 sec. cor. of sec. 6 only.

Survey of a Portion of the E Bdy. of  
T 26 N R 30 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Set a stainless steel post, 28 ins long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T26N R30E   R31E 1/4 S6 1984</p> </div> <p>Deposit a magnet in a 1x1x2 5/8 in. orange colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 40 lks. E of the left bank of Black Creek Wash.</p> <p>41.00 Black Creek Wash, 100 lks. wide, 3 ft banks, drains SW.</p> <p>Continue over flood plain of Black Creek Wash.</p> <p>51.60 Black Creek Wash, 400 lks. wide, 2 ft. banks, drains SE.</p> <p>77.35 Point for the 80 1/16 sec. cor. of sec. 1, only, T 26 N, R 30 E</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T26N R30E   R31E 1/16 S1 80 1984</p> </div> <p>from which</p> <p style="margin-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N 80° E, 125 ft. dist., with brass cap mkd. T26N R31E S6 RM 125 FT 1984, and an arrow pointing to the cor. Drove a steel fence post alongside the RM.</p>
--------	--

Survey of a Portion of the E Bdy. of  
T 26 N, R 30 E, Gila and Salt River Mer., Arizona

CHAINS	<p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, for a reference monument, bears N 10° W, 200 ft. dist., with brass cap mkd. T26N R30E S1 RM 200 FT 1984, and an arrow pointing to the cor. Drove a steel fence post alongside the RM.</p> <p>Deposit a magnet in a 1x1x2 5/8 in. orange colored plastic case beneath the stainless steel post.</p> <p>Cor. is located in Black Creek Wash.</p> <p>78.41 Left bank of Black Creek Wash, bears SE, continue over sandy, rolling land.</p> <p>82.65 Point for the cor. of Tps. 26 and 27 N, Rs. 30 and 31 E.</p> <p style="padding-left: 40px;">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td colspan="2">T27N</td></tr> <tr><td style="border-right: 1px solid black; padding: 2px;">R30E</td><td style="padding: 2px;">R31E</td></tr> <tr><td style="border-right: 1px solid black; padding: 2px;">S36</td><td style="padding: 2px;">S31</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td style="border-right: 1px solid black; padding: 2px;">S1</td><td style="padding: 2px;">S6</td></tr> <tr><td colspan="2" style="border-top: 1px solid black; padding: 2px;">T26N</td></tr> <tr><td colspan="2" style="padding: 2px;">1984</td></tr> </table> </div> <p>Deposit a magnet in a 1x1x2 5/8 in. orange colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Land, nearly level Soil, sandy loam, sand Undergrowth, sandbar willow, sagebrush and native grasses, no timber.</p>	T27N		R30E	R31E	S36	S31			S1	S6	T26N		1984	
T27N															
R30E	R31E														
S36	S31														
S1	S6														
T26N															
1984															

Survey of the North Boundary of T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>From the cor. of Tps. 26 and 27 N, Rs. 30 and 31 E, hereinbefore described.</p> <p>N 89°59' W, bet. secs. 1 and 36.</p> <p>Over the flood plain of Black Creek Wash.</p>
5.70	Left bank of Black Creek Wash, 2 ft. high, bears N and S.
10.30	Right bank of Black Creek Wash, 1 ft. high, bears N and S.
29.75	A barbed wire fence, 6 strand, extending N and S.
35.30	Earthen levee, 4 ft. high, bears N and S.
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R30E S36 1/4 — S1 T26N 1984</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located on East edge of a trail road, bears S 30° E and N 30° W.</p>
40.15	Wood pole power line, bears N and S.
58.10	A graded road, bears N and S.
80.00	<p>Point for the cor. of secs. 1, 2, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 40 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R30E S35   S36 —   — S2   S1 T26N 1984</p> </div>

Survey of the North Boundary of T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S 25°01' E, 56.4 ft. dist., with brass cap mkd. T26N R30E RM 1 56.4 FT 1984, and an arrow pointing to the cor. point. Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S 52°40' W, 37.9 ft. dist., with brass cap mkd. T26N R30E RM 2 37.9 FT 1984, and an arrow pointing to the cor. point. Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in a cultivated field.</p> <p>Land, level Soil, sand and sandy loam. Timber, Russian olive, sandbar willow and cottonwood. Undergrowth, native grasses.</p> <hr/> <p>N 89°59' W, bet. secs. 2 and 35.</p> <p>Over level land.</p> <p>6.00 A trail road, bears N and S.</p> <p>7.00 Wood pole power line, bears N and S.</p> <p>18.00 Enter dense pinyon and juniper, begin ascent of moderate E slope of mountains.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E S35 1/4 — S2 T26N 1984</p>



Survey of the North Boundary of T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona.

CHAINS	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 26 ins. diam., bears S 39 3/4° W, 49 1/2 lks. dist., mkd. 1/4 S2 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Cor. is located in Aspen Canyon, 80 ft. deep, 30 lks. N of a wash, 10 lks. wide, drains E.</p> <p>Continue along Aspen Canyon, through dense oak, aspen and ponderosa pine.</p>										
80.00	<p>Point for the cor. of secs. 2, 3, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 2px;">T27N</td> <td style="padding: 2px;">R30E</td> </tr> <tr> <td style="padding: 2px;">S34</td> <td style="padding: 2px;">S35</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 2px;">S3</td> <td style="border-top: 1px solid black; padding: 2px;">S2</td> </tr> <tr> <td style="padding: 2px;">T26N</td> <td style="padding: 2px;"></td> </tr> <tr> <td style="padding: 2px;">1984</td> <td style="padding: 2px;"></td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears N 52 3/4° E, 64 lks. dist., mkd. T27N R30E S35 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S 53 3/4° E, 59 lks. dist., mkd. T26N R30E S2 BT.</p> <p style="padding-left: 40px;">A juniper, 15 ins. diam., bears S 7° W, 84 lks. dist., mkd. T26N R30E S3 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears N 61 1/2° W, 41 lks. dist., mkd. T27N R30E S34 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Cor. located on S side of Aspen Canyon, 80 lks. S of a wash, 5 lks. wide, drains E.</p>	T27N	R30E	S34	S35	S3	S2	T26N		1984	
T27N	R30E										
S34	S35										
S3	S2										
T26N											
1984											

Survey of the North Boundary of T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona.

CHAINS	<p>Land, mountainous and rugged. Soil, sandy loam and rock. Timber, pinyon, juniper, oak, aspen and ponderosa pine. Undergrowth, cacti and native grasses.</p> <hr/> <p>N 89°59' W, bet. secs. 3 and 34.</p> <p>Over steep, mountainous land, through dense ponderosa pine.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T27N R30E S34 1/4 — S3 T26N 1984</p> </div> <p>from which</p> <p style="margin-left: 40px;">A pinyon, 6 ins. diam., bears N 6° E, 80 lks. dist., mkd. 1/4 S34 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 24 ins. diam., bears N 56 3/4° E, 105 lks. dist., mkd. 1/4 S34 BT.</p> <p style="margin-left: 40px;">A juniper, 14 ins. diam., bears S 18 1/2° E, 9 1/2 lks. dist., mkd. 1/4 S3 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>										
80.00	<p>Point for the cor. of secs. 3, 4, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2">T27N R30E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S33</td> <td style="padding: 2px 5px;">S34</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S4</td> <td style="padding: 2px 5px;">S3</td> </tr> <tr> <td colspan="2" style="text-align: center;">T26N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1984</td> </tr> </table> </div>	T27N R30E		S33	S34	S4	S3	T26N		1984	
T27N R30E											
S33	S34										
S4	S3										
T26N											
1984											

Survey of the North Boundary of T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona.

CHAINS	<p>from which</p> <p>A juniper, 14 ins. diam., bears N 23 1/4° E, 95 lks. dist., mkd. T27N R30E S34 BT.</p> <p>A juniper, 12 ins. diam., bears N 88 1/4° E, 78 1/2 lks. dist., mkd. X BT.</p> <p>A juniper, 12 ins. diam., bears S 33° W, 102 lks. dist., mkd. T26N R30E S4 BT.</p> <p>A pinyon, 8 ins. diam., bears N 41 1/2° W, 31 1/2 lks. dist., mkd. T27N R30E S33 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Land, mountainous. Soil, rock and sandy loam. Timber, oak, ponderosa pine, pinyon and juniper.</p> <hr/> <p>N 89°59' W, bet. secs. 4 and 33.</p> <p>Over moderately rolling land, through dense timber.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E S33 1/4 — S4 T26N 1984</p> <p>from which</p> <p>A pinyon, 8 ins. diam., bears S 56° W, 18 1/2 lks. dist., mkd. 1/4 S4 BT.</p> <p>A pinyon, 6 ins. diam., bears N 18° W, 30 lks. dist., mkd. 1/4 S33 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>
--------	---

Survey of the North Boundary of T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona.

CHAINS  80.00	<p>Point for the cor. of secs. 4, 5, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 2px;">T27N</td> <td style="padding: 2px;">R30E</td> </tr> <tr> <td style="padding: 2px;">S32</td> <td style="padding: 2px;">S33</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 2px;">S5</td> <td style="border-top: 1px solid black; padding: 2px;">S4</td> </tr> <tr> <td style="padding: 2px;">T26N</td> <td style="padding: 2px;"></td> </tr> <tr> <td style="padding: 2px;">1984</td> <td style="padding: 2px;"></td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A pinyon, 7 ins. diam., bears N 4 1/2° E, 17 lks. dist., mkd. T27N R30E S33 BT.</p> <p style="margin-left: 40px;">A pinyon, 7 ins. diam., bears S 22° E, 14 lks. dist., mkd. T26N R30E S4 BT.</p> <p style="margin-left: 40px;">A pinyon, 6 ins. diam., bears S 37 3/4° W, 28 lks. dist., mkd. T26N R30E S5 BT.</p> <p style="margin-left: 40px;">A pinyon, 4 ins. diam., bears N 65° W, 15 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Land, moderately rolling. Soil, rock and sandy loam. Timber, oak, pinyon, ponderosa pine and juniper.</p> <hr style="border: 0.5px solid black;"/> <p>N 89°59' W, bet. secs. 5 and 32.</p> <p>Over moderately rolling land, through dense timber.</p>	T27N	R30E	S32	S33	S5	S4	T26N		1984	
T27N	R30E										
S32	S33										
S5	S4										
T26N											
1984											
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a brass tablet, 3 1/4 ins. diam., with a 3 1/2 in. stem, in a drill hole, cemented in place, in exposed bedrock, with top mkd.</p>										

Survey of the North Boundary of T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona.

CHAINS	<p style="text-align: center;">T27N R30E S32 1/4 — S5 T26N 1984</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears N 89° E, 73 lks. dist., mkd. 1/4 S32 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S 18 1/2° E, 31 lks. dist., mkd. 1/4 S5 BT.</p> <p>Deposit a magnet in drill hole below tablet.</p> <p>80.00 Point for the cor. of secs. 5, 6, 31 and 32.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in a drill hole, cemented in place, flush in exposed bedrock, with top mkd.</p> <p style="text-align: center;">T27N R30E S31   S32 —+— S6   S5 T26N 1984</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears N 81 1/4° E, 36 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears S 32 1/2° E, 120 1/2 lks. dist., mkd. T26N R30E S5 BT.</p> <p style="padding-left: 40px;">The marks X BO, chiseled into exposed bedrock, bears N 46 1/4° W, 11 1/2 lks. dist.</p> <p>Deposit a magnet 1 in long, 7/8 in. diam, in the drill hole beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Land, moderately rolling. Soil, rock and sandy loam. Timber, oak, ponderosa pine, pinyon pine and juniper.</p> <hr style="width: 60%; margin-left: 0;"/>
--------	---

Survey of the North Boundary of T 26 N, R 30 E,  
Gila and Salt River Meridian, Arizona.

<p>CHAINS</p> <p>40.00</p> <p>80.78</p>	<p>N 89°59' W, bet. secs. 6 and 31.</p> <p>Over rolling land, through dense timber.</p> <p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E S31 1/4 — S6 T26N 1984</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S 79° E, 67 lks. dist., mkd. 1/4 S6 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears N 14 3/4° W, 130 lks. dist., mkd. 1/4 S31 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>The cor. of Tps. 26 and 27 N, Rs. 29 and 30 E, set, mkd. and witnessed as described in the field notes of the dependent resurvey of the E bdy. of T 26 N, R 29 E, plat accepted June 17, 1988.</p> <p>Land, gently rolling. Soil, sandy loam, exposed bedrock. Timber, oak, ponderosa pine, juniper.</p> <hr/> <p style="text-align: center;">Survey of a portion of the Subdivisional Lines T 26 N, R 30 E, Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. secs. 11, 12, 13, and 14, on the abandoned S. bdy. of the Navajo Indian Reservation, hereinbefore described.</p>
---	---

Survey of a portion of the Subdivisional Lines,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	N 0°01' W, bet. secs. 11 and 12.
	Over rolling land, through sparse pinyon and juniper.
3.15	A trail road, bears NE and SW.
12.50	Wood pole power line, bears S 60° E, and N 60° W.
18.90	Wood pole power line, bears N 20° E, and S 20° W.
21.25	A hog wire fence, bears E and W.
26.40	A trail road, bears N 75° E and S 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T26N R30E 1/4 S11   S12 1984
	Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
47.70	A graded road, bears N 20° E and S 20° W.
67.86	Center of a wood hogan, 15 ft. diam.
68.35	Wood pole power line, bears E and W.
79.10	Wash, 10 lks. wide, 5 ft. deep, drains S 70° E.
80.00	Point for the cor. of secs. 1, 2, 11 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T26N R30E S2   S1 <hr/> S11   S12 1984

Survey of a portion of the Subdivisional Lines,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post alongside the cor.</p>
	<p>Land, moderately rolling.</p>
	<p>Soil, sandy loam.</p>
	<p>Timber, sparse pinyon and juniper.</p>
	<p>Undergrowth, native grasses.</p>
	<p>From the cor. of secs. 1 and 12, on the E bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. as described in the field notes of the 1978 survey of a portion of the E. bdy. of T 26 N, R 30 E.</p>
	<p>S 89°51' W, bet. secs. 1 and 12.</p>
	<p>Over level land.</p>
<p>39.85</p>	<p>A trail road, bears N and S.</p>
<p>40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T26N R30E S1 1/4 — S12 1984</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post alongside the cor.</p>
<p>60.75</p>	<p>A graded road, bears N and S.</p>
<p>80.00</p>	<p>Cor. of secs. 1, 2, 11 and 12.</p>
	<p>Land, level to rolling.</p>
	<p>Soil, sandy loam.</p>
	<p>Timber, sparse pinyon and juniper.</p>
	<p>Undergrowth, greasewood and native grasses.</p>



Survey of a portion of the Subdivisional Lines,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>N 0°01' W, bet. secs. 1 and 2.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T26N R30E 1/4 S2   S1 1984</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post alongside the cor.</p>
48.43	<p>A barbed wire fence, 5 strand, extending NE and SW.</p>
80.00	<p>Point for the 80 1/16 sec. cor. of secs. 1 and 2.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">1/16 S2   S1 80 1984</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post alongside the cor.</p>
85.52	<p>The cor. of secs. 1, 2, 35 and 36, on the N bdy. of the Tp., hereinbefore described.</p>
	<p>Land, rolling to level. Soil, sandy loam. Timber, sparse pinyon and juniper. Undergrowth, native grasses.</p>
	<p>From the cor. of secs. 10 and 11, only, on the abandoned S bdy. of the Navajo Indian Reservation, hereinbefore described.</p>
	<p>N 0°01' W, bet. secs. 10 and 11.</p>
	<p>Over rolling land, through pinyon and juniper.</p>

Survey of a portion of the Subdivisional Lines,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p>3.50 Wash, 1 ch. wide, 20 ft. deep, drains E.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T26N R30E 1/4 S10   S11 1984</p> </div> <p>from which</p> <p style="margin-left: 40px;">A juniper, 14 ins. diam., bears S 26 1/2° E, 28 lks. dist., mkd. 1/4 S11 BT.</p> <p style="margin-left: 40px;">A pinyon, 8 ins. diam., bears N 65 1/2° W, 83 lks. dist., mkd. 1/4 S10 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T26N R30E S3   S2 ----- S10   S11 1984</p> </div> <p>from which</p> <p style="margin-left: 40px;">A forked pinyon, 5 ins. diam., bears N 10° E, 14 lks. dist., mkd. X BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 24 ins. diam., bears S 51° E, 61 lks. dist., mkd. T26N R30E S11 BT.</p> <p style="margin-left: 40px;">A juniper, 16 ins. diam., bears N 80° W, 44 lks. dist., mkd. T26N R30E S3 BT.</p>

Survey of a portion of the Subdivisional Lines,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Land, mountainous. Soil, rock and sandy loam. Timber, pinyon, ponderosa pine and juniper. Undergrowth, native grasses.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N 89°45' W, bet. secs. 2 and 11.</p> <p>Over rolling land, through dense pinyon and juniper.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E S2 1/4 — S11 1984</p> <p>from which</p> <p style="text-align: center;">The NW cor. of a yellow stucco house, 28 x 15 ft., bears S 87°36' E, 3.37 chs. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 8 lks. N of a wash, 15 lks. wide, 4 ft. deep, drains NE.</p>
41.35	<p>A trail road, bears N 20° E and S 20° W.</p>
61.10	<p>Wood pole power line, bears N and S.</p>
80.00	<p>The cor. of secs. 2, 3, 10 and 11.</p>

Survey of a portion of the Subdivisional Lines,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p>Land, rolling. Soil, sandy loam and rock. Timber, pinyon pine and juniper. Undergrowth, sagebrush and native grasses.</p> <hr/> <p>N 0°01' W, bet. secs. 2 and 3.</p> <p>Ascend steep S slope of a ridge.</p> <p>38.25 Wash, 50 lks. wide, 4 ft. deep, drains S 50° E.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E 1/4 S3   S2 1984</p> <p>from which</p> <p style="padding-left: 40px;">A pinyon, 5 ins. diam., bears S 40° E, 72 lks. dist., mkd. 1/4 S2 BT.</p> <p style="padding-left: 40px;">A pinyon, 15 ins. diam., bears N 88° W, 48 1/2 lks. dist., mkd. 1/4 S3 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>40.77 A trail road, bears N 40° E and S 40° W.</p> <p>80.00 Point for the 80 1/16 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">1/16 S3   S2 80 1984</p>
--------	--

Survey of a portion of the Subdivisional Lines,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
85.19	<p>from which</p> <p>A pinyon, 10 ins. diam., bears N 77 1/2° E, 56 lks. dist., mkd. 80 1/16 S2 BT.</p> <p>A pinyon, 6 ins. diam., bears N 52 1/2° W, 13 lks. dist., mkd. 80 1/16 S3 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located on N edge of a trail road, bears SE and NW.</p> <p>The cor. of secs. 2, 3, 34 and 35, on the N bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling, mountainous. Soil, rock and sandy loam. Timber, pinyon, ponderosa pine and juniper. Undergrowth, native grasses and sagebrush.</p>
40.00	<p>From the cor. of secs. 9 and 10, only, on the abandoned S bdy. of the Navajo Indian Reservation, hereinbefore described.</p> <p>N 0°02'W, bet. secs. 9 and 10.</p> <p>Over rolling land, through dense pinyon and juniper.</p> <p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E 1/4 S9   S10 1984</p> <p>from which</p> <p>A pinyon, 5 ins. diam., bears N 53 1/4° E, 42 1/2 lks. dist., mkd. 1/4 S10 BT.</p> <p>A pinyon, 6 ins. diam., bears S 68 1/2° W, 38 1/2 lks. dist., mkd. 1/4 S9 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>

Survey of a portion of the Subdivisional Lines,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p>Set a steel fence post alongside the cor.</p>								
42.00	<p>S edge of canyon, 3 chs. wide, 70 ft. deep, drains SE.</p>								
80.00	<p>Point for the cor. of secs. 3, 4, 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 2px 5px;">T26N</td> <td style="padding: 2px 5px;">R30E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S4</td> <td style="padding: 2px 5px;">S3</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S9</td> <td style="padding: 2px 5px;">S10</td> </tr> <tr> <td colspan="2" style="padding: 2px 5px;">1984</td> </tr> </table> </div> <p>from which</p> <ul style="list-style-type: none"> <li>A juniper, 12 ins. diam., bears N 70 1/4° E, 40 lks. dist., mkd. T26N R30E S3 BT.</li> <li>A pinyon, 8 ins. diam., bears S 43 3/4° E, 39 lks. dist., mkd. T26N R30E S10 BT.</li> <li>A pinyon, 8 ins. diam., bears S 50 1/2° W, 26 lks. dist., mkd. T26N R30E S9 BT.</li> <li>A pinyon, 6 ins. diam., bears N 43 1/2° W, 65 lks. dist., mkd. T26N R30E S4 BT.</li> </ul> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Land, rugged and mountainous. Soil, rock and sandy loam. Timber, dense pinyon, ponderosa pine and juniper. Undergrowth, sparse native grasses.</p> <hr style="border: 0.5px solid black;"/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N 89°53' W, bet. secs. 3 and 10.</p> <p>Over rugged, mountainous land, through dense timber.</p>	T26N	R30E	S4	S3	S9	S10	1984	
T26N	R30E								
S4	S3								
S9	S10								
1984									
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p>								

Survey of a portion of the Subdivisional Lines,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E S3 1/4 — S10 1984</p> <p>from which</p> <p style="padding-left: 40px;">A pinyon, 16 ins. diam., bears N 56 1/4° E, 26 1/2 lks. dist., mkd. 1/4 S3 BT.</p> <p style="padding-left: 40px;">A pinyon, 5 ins. diam., bears S 7° W, 17 lks. dist., mkd. 1/4 S10 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
80.00	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, rugged and mountainous Soil, rock and sandy loam. Timber, dense pinyon, ponderosa pine and juniper. Undergrowth, sparse native grasses.</p>
	<p>N 0°02' W, bet. secs. 3 and 4.</p> <p>Over rugged, mountainous land, through dense timber.</p>
4.00	<p>S edge of Juniper Bark Canyon, 30 chs. wide, 120 ft. deep, drains E.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in a drill hole, cemented in place, flush in exposed bedrock, with top mkd.</p> <p style="text-align: center;">T26N R30E 1/4 S4   S3 1984</p>

Survey of a portion of the Subdivisional Lines,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>from which</p>
	<p>A juniper, 18 ins. diam., bears N 82° E, 39 lks. dist., mkd. 1/4 S3 BT.</p>
	<p>The marks X B0, chiseled in exposed bedrock, bears West, 16 lks. dist.</p>
	<p>Cor. is located 3 lks. W of center of a small drainage.</p>
55.00	<p>S edge of a canyon, 10 chs. wide, 80 ft. deep, drains S 15° E.</p>
77.00	<p>N edge of canyon.</p>
80.00	<p>Point for the 80 1/16 sec. cor. of secs. 3 and 4.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">1/16 S4   S3 80 1984</p>
	<p>from which</p>
	<p>A pinyon, 5 ins. diam., bears N 66° E, 40 1/2 lks. dist., mkd. 80 1/16 S3 BT.</p>
	<p>A pinyon, 9 ins. diam., bears S 64° W, 20 1/2 lks. dist., mkd. 80 1/16 S4 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>
85.03	<p>The cor. of secs. 3, 4, 33 and 34, on the N bdy. of the Tp., hereinbefore described.</p>
	<p>Land, mountainous, rugged.</p>
	<p>Soil, rock and sandy loam.</p>
	<p>Timber, dense pinyon, ponderosa pine and juniper.</p>
	<p>Undergrowth, sparse native grasses.</p>
	<hr/> <p>From the cor. of secs. 8 and 9, only, on the abandoned S bdy. of the Navajo Indian Reservation, hereinbefore described.</p>
	<p>N 0°02' W, bet. secs. 8 and 9.</p>



Survey of a portion of the Subdivisional Lines,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p>Over rugged land, through dense timber.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in a drill hole, cemented in place, flush in a sandstone ledge, with top mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T26N R30E 1/4 S8   S9 1984</p> </div> <p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 14 ins. diam., bears N 50 1/2° E, 23 lks. dist., mkd. 1/4 S9 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 4 ins. diam., bears N 6 1/2° W, 24 lks. dist., mkd. X BT.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T26N R30E S5   S4 ----- S8   S9 1984</p> </div> <p>from which</p> <p style="margin-left: 40px;">A juniper, 6 ins. diam., bears N 52° E, 63 1/2 lks. dist., mkd. T26N R30E S4 BT.</p> <p style="margin-left: 40px;">A pinyon, 6 ins. diam., bears S 42° E, 36 lks. dist., mkd. T26N R30E S9 BT.</p> <p style="margin-left: 40px;">A pinyon, 12 ins. diam., bears S 85° W, 60 1/2 lks. dist., mkd. T26N R30E S8 BT.</p> <p style="margin-left: 40px;">A juniper, 5 ins. diam., bears N 14° W, 13 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>

Survey of a portion of the Subdivisional Lines,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>Set a steel fence post alongside the cor.</p> <p>Land, rugged, mountainous. Soil, rock and sandy loam. Timber, dense pinyon, ponderosa pine and juniper. Undergrowth, sparse native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N 89°59' W, bet. secs. 4 and 9.</p> <p>Over mountainous land, through dense timber.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E S4 1/4 — S9 1984</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 35 ins. diam., bears N 46° E, 74 lks. dist., mkd. 1/4 S4 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 30 ins. diam., bears S 48° E, 32 lks. dist., mkd. 1/4 S9 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
79.96	<p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, mountainous. Soil, rock and sandy loam. Timber, dense pinyon, ponderosa pine and juniper. Undergrowth, sparse native grasses.</p> <hr/> <p>N 0°04' W, bet. secs. 4 and 5.</p>

Survey of a portion of the Subdivisional Lines,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p>Over mountainous land, through dense timber.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E 1/4 S5   S4 1984</p> <p>from which</p> <p style="padding-left: 40px;">A pinyon, 9 ins. diam., bears N 76° E, 53 lks. dist., mkd. 1/4 S4 BT.</p> <p style="padding-left: 40px;">A juniper, 28 ins. diam., bears S 47° W, 34 lks. dist., mkd. 1/4 S5 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
80.00	<p>Point for the 80 1/16 cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">1/16 S5   S4 80 1984</p> <p>from which</p> <p style="padding-left: 40px;">A pinyon, 8 ins. diam., bears N 76° E, 58 1/2 lks. dist., mkd. 80 1/16 S4 BT.</p> <p style="padding-left: 40px;">A pinyon, 4 ins. diam., bears S 80° E, 36 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
85.05	<p>The cor. of secs. 4, 5, 32 and 33, on the N bdy. of the Tp., hereinbefore described.</p>

Survey of a portion of the Subdivisional Lines,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>Land, mountainous. Soil, rock and sandy loam. Timber, dense pinyon, ponderosa pine and juniper. Undergrowth, sparse native grasses.</p>
	<p>From the cor. of secs. 7, 8, 17 and 18, on the abandoned S bdy. of the Navajo Indian Reservation, hereinbefore described.</p> <p>N 0°03' W, bet. secs. 7 and 8.</p> <p>Over mountainous land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E 1/4 S7   S8 1984</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 18 ins. diam., bears N 67° E, 48 1/2 lks. dist., mkd. 1/4 S8 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 26 ins. diam., bears N 27° W, 71 lks. dist., mkd. 1/4 S7 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>
50.89	<p>Intersect the S right-of-way of Arizona State Highway 264, point is coincident with a barbed wire fence, 5 strand, from said point of intersection right-of-way monument PT 406 + 27.34 bears S 76°03' E, 1.33 chs. dist., monumented with an iron pin, projecting 2 ins. above the ground, with nearby steel guard post mkd. ARIZ. ST. HWY PT 406 + 27.34., monument located beneath barbed wire fence.</p>
52.45	<p>Center of Arizona State Highway 264, asphalt surfaced, 40 lks. wide, bears S 76° E and N 76° W.</p>
54.00	<p>Intersect the N right-of-way of Arizona State Highway 264, from said point of intersection right-of-way monument PT 406 + 27.34 bears S 76°03' E, 2.08 chs. dist., monumented with an iron pin, set flush with the ground.</p>

Survey of a portion of the Subdivisional Lines,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS									
54.85	Wood pole power line, bears S 76° E and N 76° W.								
55.65	Wood pole telephone line, bears S 76° E and N 76° W.								
62.90	S edge of canyon, 15 chs. wide, 120 ft. deep, drains E.								
80.00	Point for the cor. of secs. 5, 6, 7 and 8.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table border="1"> <tr> <td>T26N</td> <td>R30E</td> </tr> <tr> <td>S6</td> <td>S5</td> </tr> <tr> <td>S7</td> <td>S8</td> </tr> <tr> <td colspan="2">1984</td> </tr> </table> </div> from which  A ponderosa, 18 ins. diam., bears N 45° E, 49 1/2 lks. dist., mkd. T26N R30E S5 BT.  A juniper, 8 ins. diam., bears S 12° E, 78 lks. dist., mkd. T26N R30E S8 BT.  A pinyon, 4 ins. diam., bears S 49° W, 21 lks. dist., mkd. X BT.  A juniper, 4 ins. diam., bears N 20° W, 30 lks. dist., mkd. X BT.  Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.  Land, mountainous. Soil, rock and sandy loam. Timber, dense pinyon, ponderosa pine and juniper, scattered oak.	T26N	R30E	S6	S5	S7	S8	1984	
T26N	R30E								
S6	S5								
S7	S8								
1984									
39.99	From the cor. of secs. 4, 5, 8 and 9.  N 89°59' W, bet. secs. 5 and 8.  Over mountainous land, through dense timber.  Point for the 1/4 sec. cor. of secs. 5 and 8.								

Survey of a portion of the Subdivisional Lines,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E S5 1/4 — S8 1984</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears N 62 3/4° E, 131 lks. dist., mkd. 1/4 S5 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 22 ins. diam., bears S 47° E, 104 lks. dist., mkd. 1/4 S8 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Cor is located 45 lks. S of a wash, 4 lks. wide, drains SE.</p>
79.98	<p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, mountainous. Soil, rock and sandy loam. Timber, dense pinyon, ponderosa pine and juniper, scattered oak. Undergrowth, sparse native grasses.</p>
40.00	<p>West, bet. secs. 6 and 7.</p> <p>Over mountainous land, through dense timber.</p> <p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E S6 1/4 — S7 1984</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 30 ins. diam., bears N 69 1/4° E, 92 lks. dist., mkd. 1/4 S6 BT.</p>

Survey of a portion of the Subdivisional Lines,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p>A ponderosa pine, 24 ins. diam., bears S 15 1/4° E, 171 lks. dist., mkd. 1/4 S7 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Cor. is located in center of a trail road, bears N 70° E, and S 70° W.</p> <p>Continæ over rolling land, through scattered ponderosa pine.</p>																											
80.36	<p>Point for the closing cor. of secs. 6 and 7, at the intersection with the W bdy. of the Tp.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in a drill hole, cemented in place, flush in exposed bedrock, with top mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">T26N</td> <td style="padding: 2px 5px;">T26N</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S12</td> <td style="padding: 2px 5px;">S6</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">R29E</td> <td style="padding: 2px 5px;">S7</td> <td style="padding: 2px 5px;">CC</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;"></td> <td style="padding: 2px 5px;">R30E</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;"></td> <td colspan="2" style="padding: 2px 5px;">1984</td> </tr> </table> </div> <p>Deposit a magnet beneath the tablet in the drill hole.</p> <p>From this point, the cor. of secs. 1 and 12, T 26 N, R 29 E, bears N 0°04' E, 4.54 chs. dist., set, mkd. and witnessed as described in the field notes of the dependent resurvey of the E bdy. of T 26 N, R 29 E, surveyed concurrently under this group.</p> <p>Land, mountainous to rolling. Soil, rock and sandy loam. Timber, dense pinyon, ponderosa pine and juniper, scattered oak. Undergrowth, sparse native grasses.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>Point for the 1/4 sec. cor. of sec. 7 only, T 26 N, R 30 E, is at midpoint on the W bdy. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td></td> <td style="padding: 2px 5px;">T26N</td> <td></td> </tr> <tr> <td style="padding: 2px 5px;">R29E</td> <td style="border-right: 1px solid black; padding: 2px 5px;"></td> <td style="padding: 2px 5px;">R30E</td> </tr> <tr> <td></td> <td style="border-right: 1px solid black; padding: 2px 5px;"></td> <td style="padding: 2px 5px;">1/4 S7</td> </tr> <tr> <td></td> <td colspan="2" style="padding: 2px 5px;">1984</td> </tr> </table> </div>	T26N	T26N		S12	S6		R29E	S7	CC		R30E			1984			T26N		R29E		R30E			1/4 S7		1984	
T26N	T26N																											
S12	S6																											
R29E	S7	CC																										
	R30E																											
	1984																											
	T26N																											
R29E		R30E																										
		1/4 S7																										
	1984																											

Survey of a portion of the Subdivisional Lines,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>from which</p> <p>A ponderosa pine, 28 ins. diam., bears N 42° E, 35 lks. dist., mkd. 1/4 S7 BT.</p> <p>A ponderosa pine, 6 ins. diam., bears S 1/2° E , 23 lks. dist., mkd. X 1/4 S7 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>From this point, the 1/4 sec. cor. of sec. 12, T 26 N, R 29 E , bears N 0°04' E, 4.23 chs. dist., set, mkd. and witnessed as described in the notes of the dependent resurvey of the E bdy. of T 26 N, R 29 E, executed concurrently under this group.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N 0°06' W, bet. secs. 5 and 6.</p> <p>Over mountainous land, through dense timber.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E 1/4 S6   S5 1984</p>
80.00	<p>from which</p> <p>A ponderosa pine, 27 ins. diam., bears N 5° E, 44 lks. dist., mkd. 1/4 S5 BT.</p> <p>A ponderosa pine, 13 ins. diam., bears S 39° W, 207 lks. dist., mkd. 1/4 S6 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. range colored plastic case beneath the stainless steel post.</p> <p>Point for the 80 1/16 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>



Survey of a portion of the Subdivisional Lines,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p style="text-align: center;">1/16 S6   S5 80 1984</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 30 ins. diam., bears N 41 3/4° E, 129 lks. dist., mkd. 80 1/16 S5 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears N 20° W, 14 lks. dist., mkd. 80 1/16 S6 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Cor. is located 40 lks. N of a wash, 3 lks. wide, drains NE.</p> <p>85.06 The cor. of secs. 5, 6, 31, and 32 on the N bdy. of the Tp., hereinbefore described.</p> <p>Land, mountainous to rolling. Soil, rock and sandy loam. Timber, dense pinyon, ponderosa pine and juniper, scattered oak. Undergrowth, sparse native grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 6 only, on the W bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T26N R29E   R30E 1/4 S6 1984</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 25 ins. diam., bears N 45 1/2° E, 152 chs. dist., mkd. 1/4 S6 BT.</p>
--------	--

Survey of a portion of the Subdivisional Lines,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS

A ponderosa pine, 18 ins. diam., bears S 81° E, 90 1/2 lks.  
dist., mkd. X 1/4 S6 BT.

From this point the 1/4 sec. cor. of sec. 1, T 26 N, R 29 E,  
bears N 0°25' W, 4.83 chs. dist., set, mkd. and witnessed as  
described in the field notes of the dependent resurvey of the E  
bdy. of T 26 N, R 29 E, executed concurrently under this same  
group.

Point for the 80 1/16 sec. cor. of sec. 6 only, on the W bdy. of  
the Tp., is at 80.00 chs. in northing from the closing cor. of  
secs. 6 and 7, and on the line bet. the cor. of secs. 1 and 12,  
T 26 N, R 29 E, and the cor. of Tps. 26 and 27 N, Rs. 29 and  
30 E.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22  
ins. in the ground, and in a mound of stone, with brass cap mkd.

1/16  
S6  
80  
1984

from which

A ponderosa pine, 22 ins. diam., bears S 87° E, 66 lks.  
dist., mkd. 80 1/16 S6 BT.

Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case  
beneath the stainless steel post.

From this point, the cor. of Tps. 26 and 27 N, Rs. 29 and 30 E,  
bears N 0°25' W, 5.12 chs. dist., set, mkd. and witnessed as  
described in the field notes of the dependent resurvey of the E  
bdy. of T26N, R29E, executed concurrently under this same group.

Survey of the Subdivision of Section 13,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 13 and 24, hereinbefore described.</p>
	<p>N 0°28' W, on the N and S center line of sec. 13.</p>
	<p>Through a lightly populated residential area.</p>
11.00	<p>Wood pole power line, 4 strand, bears S 80° E and N 80° W.</p>
14.05	<p>A graded road, bears S 80° E and N 80° W.</p>
19.98	<p>Point for the center S 1/16 sec. cor. of sec. 13.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T26N R30E C S1/16   S13 C 1984</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>
39.96	<p>Point for the center 1/4 sec. cor. of sec. 13, at the intersection with the E and W center line of sec. 13.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T26N R30E C1/4 S13 1984</p>
	<p>From this point an Arizona State Highway Department right-of-way monument, marking the W right-of-way of Navajo Route No. 12, bears N 15°16' E, 8.24 chs. dist., monumented with a concrete cylinder, 6 ins. diam., 1 in. below the surface of the ground, firmly set, with brass tablet, 3 ins. diam., lying atop ground nearby, mkd. ARIZONA HIGHWAY DEPT 2 + 37.65 1962, witnessed by a 4 x 4 in. angle iron, northerly, 3 lks. dist., firmly set, projecting 3 ft. above ground, painted POT 2 + 37.65.</p>

Survey of the Subdivision of Section 13,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>From this same point an Arizona Department of Transportation, Highway Division right-of-way monument, marking the N right-of-way of Arizona State Highway No. 264, bears N 35°26' E, 12.31 chs. dist., monumented with brass tablet, 3 ins. diam., firmly set, flush with the ground in concrete, mkd. ADOT HWY DIV ELEV 6730.16 FT 1977, set under a barbed wire fence, 5 strand, extends N 80° E and S 80° W.</p>
	<p>From this same point an Arizona Department of Transportation, Highway Division right-of-way monument, marking the S right-of-way of Arizona State Highway No. 264, monumented with an aluminum tablet, 3 ins. diam., firmly set, flush with the ground in concrete, mkd. ADOT HWY DIV ELEV 6737.78 FT 1977, bears N 47°55' E, 10.65 chs. dist., witnessed by a 4x4 in. angle iron, easterly, 2.3 lks. dist., firmly set, projecting 2 ft. above ground, painted POT 585 + 30.13.</p>
	<p>From this same point an Arizona State Highway Department right-of-way monument, marking the E right-of-way of Navajo Route No. 12, bears N 58°04' E, 9.34 chs. dist., monumented with a concrete cylinder, 6 ins. diam., firmly set, projecting 7 ins. above ground, with a brass tablet, 3 ins. diam., mkd. ARIZONA HIGHWAY DEPT 1961, witnessed by a 4 x 4 in. angle iron, northerly, 3 lks. dist., firmly set, projecting 28 ins. above ground, painted POT 2 + 37.65.</p>
	<p>From this same point an Arizona State Highway Department right-of-way monument, marking the E right-of-way of Navajo Route No. 12, bears S 56°03' E, 7.90 chs. dist., monumented with a concrete cylinder, 6 ins. diam., firmly set, projecting 7 ins. above ground, with a brass tablet, 3 ins. diam., mkd. ARIZONA STATE HIGHWAY DEPT 1961, witnessed by a 4 x 4 in. angle iron, northerly, 3 lks. dist., firmly set, projecting 29 ins. above ground, painted PC 8 + 6.45.</p>
	<p>From this same point an iron pipe, 1 1/2 in. diam., of unknown origin, bears N 53°10' W, 26.4 lks. dist., firmly set, projecting 1 ft. above ground, and in a collar of stone, 1 1/2 ft. base, 1 ft. high.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>
45.15	<p>Wood pole power line, 4 strand, extending N 80° E and S 80° W, and 5 strand barbed wire fence extending N 80° E, and S 80° W. (S ROW fence)</p>

Survey of the Subdivision of Section 13,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
46.80	Center of Arizona State Highway No. 264, 90 lks. wide, asphalt surfaced, bears N 80° E and S 80° W.
48.25	A barbed wire fence, 5 strand, extending N 80° E and S 80° W. (N ROW fence)
48.85	Wood pole power line, 7 strand, extending N 80° E and S 80° W.
58.18	A 1/2 in. rebar, bears E, 16.5 lks. dist., firmly set, projecting 1 in. above ground, with a 1 in. diam. galvanized iron cap mkd. PERCE ENG TOG #3 LS 2615. This cor. is not intended to be a cor. of the rectangular system, as stated by Mr. Perce.
76.24	The 1/4 sec. cor. of secs. 12 and 13, on the abandoned S bdy of the Navajo Indian Reservation, hereinbefore described.
	<hr/> <p>From the 1/4 sec. cor. of sec. 13 only, on the E bdy. of the Tp., set, mkd. and witnessed as described in the official record of the 1978 dependent resurvey of a portion of the E bdy. of T 26 N, R 30 E.</p> <p>N 89°49' W, on the E and W center line of sec. 13.</p>
33.80	Center of Navajo Route No. 12, 26 ft. wide, asphalt surfaced, bears N 10° E and S 10° W.
40.24	The center 1/4 sec. cor. of sec. 13.
57.45	A barbed wire fence, 5 strand, extending S 20° E and N 20° W.
60.34	Point for the center W 1/16 sec. cor. of sec. 13.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>W1/16</p> <p>C ————— C</p> <p>S13</p> <p>1984</p> </div> <p>From this point a rebar, set by persons unknown, bears N 54°36' W, 14.8 lks. dist., 5/8 in. diam., firmly set, projecting 3 ins. above ground.</p>

Survey of the Subdivision of Section 13,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p>From this same point an iron pipe, set by persons unknown, bears N 85°58' W, 107.2 lks. dist., 1/2 in. diam., firmly set, projecting 2 ins. above ground.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Cor. located in the right-of-way of Arizona State Highway No. 264, on the S side of the road.</p>
65.90	Wood pole power line, 4 strand, extending N 80° E and S 80° W.
68.60	Center of Arizona State Highway No. 264, 90 lks. wide, asphalt surfaced, bears N 80° E and S 80° W.
74.60	Wood pole power line, 3 strand, extending N 80° E and S 80° W, and a barbed wire fence, 5 strand, extending N 80° E and S 80° W.
75.95	A graded road, bears S 60° E and N 60° W.
80.44	The 1/4 sec. cor. of secs. 13 and 14, heretofore described.
<hr/> <p>SW 1/4 Section 13</p> <hr/>	
19.985	<p>From the W 1/16 sec. cor. of secs. 13 and 24, hereinbefore described.</p> <p>N 0°29' W, on the N and S center line of the SW 1/4 of sec. 13.</p> <p>Enter residential area known as Block 2 of Saint Michaels Residential Unit "B", established in 1965.</p> <p>Point for the SW 1/16 sec. cor. of sec. 13, at the intersection with the E and W center line of the SW 1/4 of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S13 1984</p> <p>From this point, an iron pipe, 2 ins. diam., firmly set in concrete, projecting 1 in. above ground, bears N 57°45' W, 15.4 lks. dist. This point was established for the SW 1/16 sec. cor. of sec. 13, by J. G. Martinez, Arizona L. S. No. 2315, in 1963, using improper procedures, and is not utilized during the course of this survey.</p>

Survey of the Subdivision of Section 13,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>
22.90	<p>A graded road, bears S 60° E and N 60° W.</p> <p>Leave residential area.</p>
23.60	<p>Wood pole power line, 4 strand, extending S 80° E and N 80° W.</p>
39.62	<p>Barbed wire fence, 5 strand, marking the S right-of-way of Arizona State Highway No. 264, extending N 85° E and S 85° W.</p>
39.97	<p>The center W 1/16 sec. cor. of sec. 13.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 13.</p> <p>N 89°50' W, on the E and W center line of the SW 1/4 of sec. 13.</p> <p>Through a residential area.</p>
20.10	<p>The SW 1/16 sec. cor. of sec. 13.</p> <p>Leave residential area known as Block 2 of Saint Michaels Residential Unit "B".</p>
40.20	<p>The S 1/16 sec. cor. of secs. 13 and 14, hereinbefore described.</p> <hr/> <p style="text-align: center;">Survey of the Subdivision of Section 14, T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 23, hereinbefore described.</p> <p>N 0°02' W, on the N and S center line of sec. 14.</p> <p>Through a residential area.</p>
40.01	<p>Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E and W centerline of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivision of Section 14,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

<p>CHAINS</p>	<p style="text-align: center;">T26N R30E C1/4 S14 1984</p> <p>From this point an iron pipe, 2 ins. diam., set by persons unknown, bears N 50°24' E, 10 1/2 lks. dist., firmly set, projecting 2 ins. above ground.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>59.91 Point for the center N 1/16 sec. cor. of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N1/16   S14 C 1984</p> <p>From this point an iron pipe, 2 ins. diam., set by persons unknown, bears N 28°50' E, 16 lks. dist., firmly set, projecting 6 ins. above ground.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>76.28 The 1/4 sec. cor. of sec. 14 only, on the abandoned S bdy. of the Navajo Indian Reservation, hereinbefore described.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 14.</p> <p>S 89°56' W, on the E and W center line of sec. 14.</p> <p>39.83 The center 1/4 sec. cor. of sec. 14.</p> <p>59.76 Point for the center W 1/16 sec. cor. of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
---------------	--



Survey of the Subdivision of Section 14,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p style="text-align: center;">W1/16 C-----C S14 1984</p> <p>from which</p> <p style="text-align: center;">The cor. of a 6 ft. chain link fence, extending N and E, bears N 46°10' E, 3 1/2 lks. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>79.69 The 1/4 sec. cor. of secs. 14 and 15, hereinbefore described.</p> <hr/> <p style="text-align: center;">NW 1/4 of Section 14</p> <hr/> <p>From the center W 1/16 sec. cor. of sec. 14.</p> <p>N 0°03' E, on the N and S center line of the NW 1/4 of sec. 14.</p> <p>19.95 Point for the NW 1/16 sec. cor. of sec. 14, at the intersection with the E and W center line of the NW 1/4 of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S14 1984</p> <p>From this point an iron pipe, 2 ins. diam., set by persons unknown, bears S 89°34' W, 12.3 lks. dist., projecting 1 in. above ground.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>36.37 The W 1/16 sec. cor. of sec. 14 only, on the abandoned S bdy. of the Navajo Indian Reservation, hereinbefore described.</p> <hr/> <p>From the center N 1/16 cor. of sec. 14.</p> <p>N 89°56' W, on the E and W center line of the NW 1/4 of sec. 14.</p>
--------	---

Survey of the Subdivision of Section 14,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
19.89	The NW 1/16 sec. cor. of sec. 14.
39.78	The N 1/16 sec. cor. of secs. 14 and 15.
	<hr/> Survey of the Subdivision of Section 22, T 26 N, R 30 E, Gila and Salt River Meridian, Arizona. <hr/>
	From the 1/4 sec. cor. of secs. 22 and 27, hereinbefore described.
	N 0°24' W, on the N and S center line of sec. 22.
40.14	Point for the center 1/4 sec. cor. of sec. 22, at the intersection with the E and W center line of sec. 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T26N R30E C1/4 S22 1984
	from which
	A pinyon, 14 ins. diam., bears S 68 1/2° W, 11 lks. dist., mkd. C 1/4 S22 BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.
	Cor. located on steep N slope, 50 ft. below and 1.5 chs. N of top of sandstone bluff, bears irregularly N 70° E and S 70° W.
80.89	The 1/4 sec. cor. of secs. 15 and 22, hereinbefore described.
	<hr/> From the 1/4 sec. cor. of secs. 22 and 23.
	S 89°13' W, on the E and W center line of sec. 22.
3.90	A graded road, bears N 60° E and S 60° W.
20.08	Point for the center E 1/16 sec. cor. of sec. 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivision of Section 22,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p style="text-align: center;">E1/16 C———C S22 1984</p> <p>From this point an iron pipe, of unknown origin, bears N 83°06' E, 13.4 lks. dist., 1 1/2 ins. diam., loosely set, projecting 16 ins. above ground,</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>40.16 The center 1/4 sec. cor. of sec. 22.</p> <p>80.24 The 1/4 sec. cor. of secs. 21 and 22.</p> <hr/> <p style="text-align: center;">NE 1/4 of Section 22</p> <hr/> <p>From the center E 1/6 sec. cor. of sec. 22.</p> <p>N 0°13' W, on the N and S center line of the NE 1/4 of sec. 22.</p> <p>40.69 The E 1/16 sec. cor. of secs. 15 and 22.</p> <hr/> <p style="text-align: center;">Survey of the Subdivision of Section 23, T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 23 and 26, hereinbefore described.</p> <p>N 0°03.6' W, on the N and S center line of sec. 23.</p> <p>40.409 Point for the center 1/4 sec. cor. of sec. 23, at the intersection with the E and W center line of sec. 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E C1/4 S23 1984</p> <p>From this point a sandstone, of unknown origin, bears N 16°42' E, 3.1 lks. dist., 12 x 16 x 3 ins., lying loose atop the ground, mkd. C 23 on one face.</p> <p>Bury the stone alongside the stainless steel post.</p>
--------	--

Survey of the Subdivision of Section 23,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Enter light residential area.</p>
44.90	<p>A graded road, bears S 80° E and N 80° W.</p>
60.544	<p>Point for the center N 1/16 sec. cor. of sec. 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <math display="block">\begin{array}{c} C \\ N1/16 \quad   \quad S23 \\ C \\ 1984 \end{array}</math> </div> <p>From this point an iron pipe, 2 ins. diam., set by J. G. Martinez, Arizona L. S. No. 2315, in 1963 and not recorded, bears N 2°40' E, 15 lks. dist., firmly set, projecting 5 ins. above ground, cor. located in a fence cor., extending N only, composed of steel posts with no wire.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>
70.612	<p>Point for the center N-N 1/64 sec. cor. of sec. 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, 1 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <math display="block">\begin{array}{c} C \\ N-N 1/64 \quad   \quad S23 \\ C \\ 1984 \end{array}</math> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Cor. located 5 lks. S of a small wash, 10 lks. wide, 4 ft. deep, drains N 70° E.</p>

Survey of the Subdivision of Section 23,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
80.68	<p>The 1/4 sec. cor. of secs. 23 and 24, hereinbefore described.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 23 and 24, hereinbefore described.</p> <p>S 89°29.2' W, on the E and W center line of sec. 23.</p>
24.80	<p>A graded road, bears S 40° E and N 40° W.</p> <p>Enter lightly populated residential area.</p>
39.793	<p>The center 1/4 sec. cor. of sec. 23.</p> <p>Leave lightly populated residential area.</p>
59.799	<p>Point for the center W 1/16 sec. cor. of sec. 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>W1/16</p> <p>C-----C</p> <p>S23</p> <p>1984</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>
79.804	<p>The 1/4 sec. cor. of sec. 22 and 23.</p> <hr/> <p style="text-align: center;">NE 1/4 of Section 23</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 23 and 24, hereinbefore described.</p> <p>S. 89°42' W., on the E and W center line of the NE 1/4 of sec. 23.</p> <p>Over rolling land.</p>
39.98	<p>The center N 1/16 sec. cor. of sec. 23.</p> <hr/> <p style="text-align: center;">NW 1/4 of Section 23</p> <hr/> <p>From the center W 1/16 sec. cor. of sec. 23.</p> <p>N 0°02.6' W, on the N and S center line of the NW 1/4 of sec. 23.</p>

Survey of the Subdivision of Section 23,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	Through a lightly populated residential area.
10.90	A graded road, bears E and W.
20.229	Point for the NW 1/16 sec. cor. of sec. 23, at the intersection with the E and W centerline of the NW 1/4 of sec. 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">NW 1/16 S23 1984</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.
30.342	Point for the center N-NW 1/64 sec. cor. of sec. 23.
	Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. below the surface of the ground, with cap mkd.
	<p style="text-align: center;">S23 C-N-NW 1/64 1984</p>
	Cor. located on the shoulder of the S side of a graded road, bears irregularly E and W, and 50 lks. S of a 4 strand barbed wire fence, bears irregularly E and W.
	Enter pasture.
40.455	The W 1/16 sec. cor. of secs. 14 and 23.
	<hr style="width: 20%; margin: auto;"/>
	From the center N 1/16 sec. cor. of sec. 23.
	S 89°45.0' W, on the E and W center line of the NW 1/4 of sec. 23.
	Through a lightly populated residential area.
9.998	Point for the center E-NW 1/64 sec. cor. of sec. 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">S23 C-E-NW 1/64 1984</p>

Survey of the Subdivision of Section 23,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.



CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>
19.995	<p>The NW 1/16 sec. cor. of sec. 23.</p>
30.20	<p>Top of sandstone bluff, 50 ft. high, bears irregularly E and W, thence descend to cultivated area.</p>
39.991	<p>The N 1/16 sec. cor. of secs. 22 and 23.</p> <hr/> <p style="text-align: center;">NE 1/4 of the NW 1/4 of Section 23</p> <hr/> <p>From the center E-NW 1/64 sec. cor. of sec. 23.</p> <p>N 0°03.2' W, on the N and S center line of the NE 1/4 of the NW 1/4 of sec. 23.</p> <p>Through a lightly populated residential area.</p> <p>Over rolling land, to a sandstone bluff, bears irregularly E and W, thence descend 50 ft., thence over nearly level land.</p>
10.090	<p>Point for the NE-NW 1/64 sec. cor. of sec. 23, at the intersection with the E and W centerline of the NE 1/4 of the NW 1/4 of sec. 23.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. below the surface of the ground, with cap mkd.</p> <p style="text-align: center;">S23 NE-NW 1/64 1984</p> <p>from which</p> <p style="text-align: center;">The N face of a sandstone outcrop, 10 x 8 x 3 ft. above ground, bears S 28 3/4° W, 242 1/2 lks. dist., mkd. X BO.</p> <p>Cor. located in the center of a graded dirt road, bears irregularly E and W, and 40 lks. S of a barbed wire, 4 strand, extends irregularly E and W.</p> <p>Enter pasture.</p>
20.182	<p>The E-W 1/64 sec. cor. of secs. 14 and 23.</p> <hr/>

Survey of the Subdivision of Section 23,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p>From the center N-N 1/64 sec. cor. of sec. 23.</p> <p>S 89°52.9' W, on the E and W center line of the NE 1/4 of the NW 1/4 of sec. 23.</p> <p>Through a lightly populated residential area.</p>
9.995	<p>The NE-NW 1/64 sec. cor. of sec. 23.</p>
19.990	<p>The center N-NW 1/64 sec. cor. of sec. 23.</p>
<hr/> <p>Survey of the Subdivision of Section 24, T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.</p> <hr/>	
40.07	<p>From the 1/4 sec. cor. of secs. 24 and 25, hereinbefore described.</p> <p>N 0°42' E, on the N and S center line of sec. 24.</p> <p>Through a lightly populated residential area.</p> <p>Point for the center 1/4 sec. cor. of sec. 24, at the intersection with the E and W center line of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E C1/4 S24 1984</p> <p>From this point an iron pipe, 2 ins. diam., firmly set, projecting 6 ins. above ground, bears N 24°49' E, 10.2 lks. dist. This point was established for the center 1/4 sec. cor. of sec. 24, by J. G. Martinez, Arizona L. S. No. 2315, in 1963, using improper procedures, and is not utilized during the course of this survey.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>



Survey of the Subdivision of Section 24,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

<p>CHAINS</p> <p>60.08</p>	<p>Point for the center N 1/16 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>From this point an iron pipe, 2 ins. diam., firmly set, projecting 4 ins. above ground, bears N 79°53'E, 21.6 lks. dist. This point was established for the center N 1/16 sec. cor. of sec. 24, by J. G. Martinez, Arizona L. S. No. 2315, in 1963, using improper procedures, and is not utilized during the course of this survey.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>
<p>80.09</p>	<p>The 1/4 sec. cor. of secs. 13 and 24.</p>
<p>39.64</p>	<p>From the 1/4 sec. cor. of sec. 24 only, on the E bdy. of the Tp., hereinbefore described.</p>
<p>59.67</p>	<p>N 89°48' W, on the E and W center line of sec. 24.</p>
<p>39.64</p>	<p>Through a lightly populated residential area.</p>
<p>39.64</p>	<p>The center 1/4 sec. cor. of sec. 24.</p>
<p>59.67</p>	<p>Point for the center W 1/16 sec. cor. of sec. 24.</p>
<p>59.67</p>	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. below the surface of the ground, with cap mkd.</p>
<p>59.67</p>	<div style="text-align: center;">  </div>

Survey of the Subdivision of Section 24,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>From this point an iron pipe, 2 ins. diam., bears N 77°47' E, 22.2 lks. dist., firmly set in concrete in a fence cor. mkd. by steel fence posts only, extending N and E, projecting 6 ins. above ground. This point was established for the center W 1/16 sec. cor. of sec. 24, by J. G. Martinez, Arizona L. S. No. 2315, in 1963, using improper procedures, and is not utilized during the course of this survey.</p> <p>Cor. located on the shoulder of the N side of a graded dirt road, bears irregularly E and W.</p>
79.70	The 1/4 sec. cor. of secs. 23 and 24.
	<hr/> <p style="text-align: center;">NE 1/4 of Section 24</p> <hr/> <p>From the N 1/16 sec. cor. of sec. 24 only, on the E bdy. of the Tp., hereinbefore described.</p> <p>N 89°43' W, on the E and W center line of the NE 1/4 of sec. 24.</p> <p>Along meandering drainage, drains generally E.</p>
39.62	The center-N 1/16 sec. cor of sec. 24.
	<hr/> <p style="text-align: center;">NW 1/4 of Section 24</p> <hr/> <p>From the center W 1/16 sec. cor. of sec. 24.</p> <p>N 0°35' E, on the N and S center line of the NW 1/4 of sec. 24.</p>
20.00	Point for the NW 1/16 sec. cor. of sec. 24, at the intersection with the E and W center line of the NW 1/4 of sec. 24.

Survey of the Subdivision of Section 24,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S24 1984</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <p>Cor. is located S. 83° W., 2 lks. dist. from terminus of sheep fence with 2 strands of barbed wire, extending W.</p> <p>From this point an iron pipe, 2 ins. diam., firmly set, projecting 6 ins. above ground, bears N 81° E, 3.2 lks. dist. This point was established for the NW 1/16 sec. cor. of sec. 24, by J. G. Martinez, Arizona L. S. No. 2315, in 1963, using improper procedures, and is not utilized during the course of this survey.</p>
40.00	<p>The W 1/16 sec. cor. of secs. 13 and 24, hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center N 1/16 sec. cor. of sec. 24.</p> <p>N 89°50' W, on the E and W center line of the NW 1/4 of sec. 24.</p>
20.06	<p>The NW 1/16 sec. cor of sec. 24.</p>
40.12	<p>The N 1/16 sec. cor. of secs. 23 and 24, hereinbefore described.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">Survey of the Subdivision of Section 30, T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 30 and 31.</p> <p>N 0°09' W, on the N and S center line of sec. 30, hereinbefore described.</p>
40.79	<p>Point for the center 1/4 sec. cor. of sec. 30, at the intersection with the E and W center line of sec. 30.</p>

Survey of the Subdivision of Section 30,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E C1/4 S30 1985</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 23 ins. diam., bears N 18° W, 35 1/2 lks. dist., mkd. C1/4 S30 BT.</p> <p>From this point a sandstone of unknown origin, 10 x 12 x 2 ins., bears N 20°30' W, 11.4 lks. dist., loosely set, 4 ins. in the ground, and in a collar of stone, 1 ft. base, 8 ins. high, mkd. CS 30. Bury the mkd. stone in place, over a 60D nail. Destroy the collar of stone.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p>
80.83	<p>The 1/4 sec. cor. of secs. 19 and 30, hereinbefore described.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 29 and 30, hereinbefore described.</p> <p>S 89°59' W, on the E and W center line of sec. 30.</p>
39.50	<p>The center 1/4 sec. cor. of sec. 30.</p>
79.57	<p>The 1/4 sec. cor of secs. 25 and 30, on the W bdy. of the Tp., set, mkd. and witnessed as described in the official record of the dependent resurvey of the E bdy. of T 26 N, R 29 E, executed concurrently under this same group.</p> <hr/> <p style="text-align: center;">Survey of the Subdivision of Section 32, T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.</p> <hr/> <p>From the 1/4 sec. cor. of sec. 32 only, on the S bdy. of the abandoned Navajo Indian Reservation.</p>

Survey of the Subdivision of Section 32,  
T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

<p>CHAINS</p> <p>39.99</p> <p>81.48</p> <p>40.00</p> <p>79.97</p>	<p>N 0°13' W, on the N and S center line of sec. 32.</p> <p>Point for the center 1/4 sec. cor. of sec. 32, at the intersection with the E and W center line of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T26N R30E C1/4 S32 1984</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 23 ins. diam., bears S 58° E, 19 lks. dist., mkd. C 1/4 S32 BT.</p> <p>From this point A sandstone of unknown origin, 22 x 12 x 4 ins., lying loose atop the ground, mkd. CS 32, bears N 69°57' E, 18 lks. dist. Bury the mkd. stone in place, over a 60D nail.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange plastic case beneath the stainless steel post.</p> <hr/> <p>The 1/4 sec. cor. of secs. 29 and 32.</p> <p>From the 1/4 sec. cor. of secs. 32 and 33, hereinbefore described.</p> <p>S 89°57' W, on the E and W center line of sec. 32.</p> <p>The center 1/4 sec. cor. of sec. 32.</p> <p>The 1/4 sec. cor. of secs. 31 and 32.</p>
---	---

T 26 N, R 30 E, Gila and Salt River Meridian, Arizona.

CHAINS	
	<p style="text-align: center;">General Description</p> <p>Township 26 North, Range 30 East is situated about eight miles from the New Mexico-Arizona border. The town of St. Michaels, Arizona, is in the northeast corner of the township.</p> <p>The terrain is generally rolling in the eastern portion of the township. The middle portion of the township is rugged and broken and the western portion of the township is rolling. The elevation ranges from 6500 ft. above sea level in the eastern portion of the township to 7600 ft. above sea level in the western portion of the township.</p> <p>The majority of the township is used by members of the Navajo tribe to graze livestock. The cultivation of crops in the township is scattered with the majority of cultivation occurring in sections 23, 14 and 11. There is marketable ponderosa pine in the higher elevations of the western portion of the township; timber harvesting is ongoing in this area.</p> <p>Arizona State Highway No. 264 enters the township in section 13 and meanders westerly through the township to its exit from section 7. Navajo Route No. 12 begins in section 13 and meanders southerly to its exit from section 35. From both of these major highways there are many graded and trail roads providing access to most areas within the township.</p> <p>The drainage within the township flows in an easterly direction to Black Creek which meanders south near the east boundary of the township.</p> <p>The magnetic declination was determined to be <math>12 \frac{1}{4}^{\circ}</math> E, with no noticeable differences due to local attractions.</p>

UNITED STATES  
 DEPARTMENT OF THE INTERIOR  
 BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Jones C. Curtiss	Engineering Technician
Reuben Mason	Engineering Technician
Andrew Murphy	Engineering Technician
Wilfred D. Chee	Engineering Technician
Albert S. Tsosie Jr.	Engineering Technician
Daniel R. Bryan	Engineering Technician
Barney Woodie	Engineering Technician

CERTIFICATE OF SURVEY

We, Kevin R. DeRossett and Richard S. Kaiser, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 18th day of April 1984, and the supplemental special instructions dated August 29, 1984. We have performed the dependent resurvey of the south boundary, a portion of the east boundary, a portion of the abandoned south boundary of the Navajo Indian Reservation, and a portion of the subdivisional lines; the survey of a portion of the east boundary, the north boundary, a portion of the subdivisional lines and the subdivision of certain sections in Township 26 North, Range 30 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Kevin R. DeRossett and Richard S. Kaiser are no longer assigned to this office and not available for signature.

September 17, 1990  
(Date)

William F. Oliver  
(Chief, Navajo Cadastral Sec.)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Arizona State Office  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the south boundary, a portion of the east boundary, a portion of the abandoned south boundary of the Navajo Indian Reservation, and a portion of the subdivisional lines; the survey of a portion of the east boundary, the north boundary, a portion of the subdivisional lines and the subdivision of certain sections in Township 26 North, Range 30 East, of the Gila and Salt River Meridian, Arizona, executed by Kevin R. DeRossett and Richard S. Kaiser, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

SEP 28 1990  
(Date)

James P. Kelley  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I Certify that the foregoing transcript of the field notes of the above-described surveys in T 26 N, R 30 E, Gila and Salt River Meridian, Arizona is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~