

ORIGINAL

1

BOOK 5295

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE

DEPENDENT RESURVEY OF A PORTION OF THE

SOUTH BOUNDARY AND A PORTION OF THE

SUBDIVISIONAL LINES, AND

THE SURVEY OF THE SUBDIVISIONS IN

SECTIONS 14, 22, 23, 27, 34, AND 35,

TOWNSHIP 23 NORTH, RANGE 6 EAST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

Duane R. Garoutte, Cadastral Surveyor,

Under special instructions dated June 17, 1985, approved June 17 1985

 , which provided for the surveys included under Group Number
668 and assignment instructions dated June 17, 1985.

Survey commenced June 27, 1985
Survey completed November 7, 1985

BOOK 5295

INDEX DIAGRAM

TOWNSHIP 23 NORTH, RANGE 6 EAST,

6	5	4	3	2	1			
7	8	9	10	11	12			
				34				
18	17	16	15	31	14	12	13	
			51		29			
19	20	21	48	22	26	23	10	24
			45			24		
30	29	28	42	27	20	26		25
			39			18		
31	32	33	37	34	15	35	8	36
				6		4		

- Subdivisions of sec. 14 pp. 53-62
- Subdivisions of sec. 22 pp. 62-76
- Subdivisions of sec. 23 pp. 76-87
- Subdivisions of sec. 27 pp. 88-108
- Subdivisions of sec. 34 pp. 108-110
- Subdivisions of sec. 35 pp. 110-127

BOOK 5295

T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the south boundary and a portion of the subdivisional lines, and the survey of the subdivisions in sections 14, 22, 23, 27, 34, and 35, Township 23 North, Range 6 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

The south boundary and subdivisional lines were surveyed by W. R. Fitzgerald in 1883 and resurveyed by Ty White and Bert E. Wakeman in 1943.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated June 17, 1985, for Group No. 668, Arizona.

Preliminary to the resurvey, the lines of the prior surveys were retraced and all corners were recovered. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of lines were determined by altitude observations on the sun and carried forward by sustained angulation and refer to the true meridian. Distances and angles were measured with a Zeiss Elta 46 total station.

The geographic position of the southeast corner of section 35, as published by U.S. Geological Survey, is as follows:

NAD 27: Latitude: 35°19'34.412" N Longitude: 111°43'8.622" W

The mean magnetic declination, as shown on U.S. Geological Survey quadrangle map "HUMPHREYS PEAK, ARIZ.," published in 1966, is 14 1/2° E.

BOOK 5295

Dependent Resurvey, a Portion of the South Boundary,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS

Reestablishment of the resurvey executed by Ty White
and Bert E. Wakeman in 1943

Beginning at the cor. of secs. 1, 2, 35, and 36, monumented with
an iron post, 2 ins. diam., firmly set, projecting 8 ins. above
ground, with brass cap mkd.

T23N R6E	
S35	S36
S 2	S 1
T22N	
1943	

A mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, is W of cor.
N 89°53' W, bet. secs. 2 and 35.

Desc. over gradual SW slope, through scattered ponderosa pine.

0.60 A dim dirt road, bears NE and SW.

19.925 Point for the E 1/16 sec. cor. of secs. 2 and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T23N R6E	
S35	
E 1/16	S 2
T22N	
1985	

from which

A ponderosa pine, 8 ins. diam., bears S 87° E, 95 lks.
dist., mkd. X BT.

A ponderosa pine, 18 ins. diam., bears S 34° E, 102 lks.
dist., mkd. E 1/16 S2 BT.

Deposit a magnet in a 1 x 1 x 2 5/8 in. pink colored plastic case
beneath the stainless steel post.

Set a steel fence post near the cor.

BOOK 5295

Dependent Resurvey, a Portion of the South Boundary,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
39.85	<p>The 1/4 sec. cor. of secs. 2 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p>
	<p style="text-align: center;">S35 1/4 _____ S 2 1943</p>
	<p>A mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, is N of cor.</p> <hr style="width: 20%; margin: auto;"/>
	<p>N 89°55' W, beginning new measurement.</p>
	<p>Desc. over gradual SW slope, through ponderosa pine.</p>
19.915	<p>Point for the W 1/16 sec. cor. of secs. 2 and 35.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T23N R6E S35 W 1/16 _____ S 2 T22N 1985</p>
	<p>from which</p>
	<p>A ponderosa pine, 11 ins. diam., bears S 88 1/2° E, 44 lks. dist., mkd. W 1/16 S2 BT.</p>
	<p>A ponderosa pine, 8 ins. diam., bears S 39 1/4° W, 75.5 lks. dist., mkd. X BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. purple colored plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post near the cor.</p>
39.83	<p>The cor. of secs. 2, 3, 34, and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, and in a collar of stone, with brass cap mkd.</p>

BOOK 5295

Dependent Resurvey, a Portion of the South Boundary,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS

T23N R6E	
S34	S35

S 3	S 2
T22N	
1943	

from which the original bearing tree

A ponderosa pine, 44 ins. diam., bears S 47° E, 99 lks.
dist., no marks visible on axed blaze. (Record: 97 lks.
in agreement with measurement to the face.)

and the bearing trees mkd. in 1943

A ponderosa pine, 26 ins. diam., bears N 45 1/2° E, 332 lks.
dist., with healed blaze. (Record: 333 lks.)

A ponderosa pine, 18 ins. diam., bears S 39 1/4° W, 261 lks.
dist., with healed blaze. (Record: 263 lks.)

S 89°55' W, bet. secs. 3 and 34.

Desc. over gradual SW slope, through aspen and ponderosa pine.

- 0.25 U.S. Forest Service Route 151, graded, bears N and S.
- 0.62 Fence cor., from which fences extend W and S, ends soon; along fence.
- 14.40 Low spur, slopes S.
- 25.00 Bottom of descent; asc. over gradual E slope.
- 40.15 The 1/4 sec. cor. of secs. 3 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

S34
1/4 ———
S 3
1943

from which the bearing trees mkd. in 1943

A ponderosa pine, 18 ins. diam., bears N 30 1/4° E, 78 lks.
dist., with healed blaze.

7
BOOK 5295

Dependent Resurvey, a Portion of the South Boundary,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS									
	<p style="text-align: center;">A ponderosa pine, 23 ins. diam., bears S 63 1/2° E, 158 lks. dist., with healed blaze. (Record: 159 lks.)</p> <p>The cor. is located at fence cor., from which fences extend N, E, and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S 89°55' W, beginning new measurement.</p> <p>Over rolling land, through scattered ponderosa pine; asc. over E. slope.</p> <p>Along fence.</p>								
0.40	A dirt road, bears N and S, curving SE.								
13.00	Top of ascent; desc. over W slope.								
40.02	The cor. of secs. 3, 4, 33, and 34, monumented with an iron post, 2 ins. diam., firmly set in a mound of stone, 2 1/2 ft. base, with brass cap mkd.								
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="border: none;">T23N R6E</td> </tr> <tr> <td style="border: none; border-right: 1px solid black; padding: 2px 5px;">S33</td> <td style="border: none; padding: 2px 5px;">S34</td> </tr> <tr> <td style="border: none; border-right: 1px solid black; padding: 2px 5px;">S 4</td> <td style="border: none; padding: 2px 5px;">S 3</td> </tr> <tr> <td colspan="2" style="border: none; text-align: center;">1943</td> </tr> </table>	T23N R6E		S33	S34	S 4	S 3	1943	
T23N R6E									
S33	S34								
S 4	S 3								
1943									
	<p>from which the original bearing trees</p> <p style="margin-left: 40px;">A down and rotted ponderosa pine, 30 ins. diam., bears N 51 1/2° E, 102 lks. dist.</p> <p style="margin-left: 40px;">A down and rotted ponderosa pine, 40 ins. diam., bears S 79 1/2° W, 25 lks. dist.</p> <p>and the bearing trees mkd. in 1943</p> <p style="margin-left: 40px;">A ponderosa pine, 15 ins. diam., bears N 19 3/4° E, 165 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A ponderosa pine, 18 ins. diam., bears S 34 3/4° E, 37 lks. dist., with healed blaze. (Record: 35 lks.)</p> <p style="margin-left: 40px;">A ponderosa pine, 20 ins. diam., bears S 36 1/2° W, 115 lks. dist., with healed blaze.</p>								

BOOK 5295

Dependent Resurvey, a Portion of the South Boundary,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 17 ins. diam., bears N 28° W, 116 lks. dist., with healed blaze.</p> <p>The cor. is located 4.5 lks. S of fence cor., from which fences extend N, E, and W.</p> <hr/> <p>Dependent Resurvey, a Portion of the Subdivisional Lines, T 23 N, R 6 E, Gila and Salt River Mer., Arizona</p> <hr/> <p>Reestablishment of the survey executed by W. R. Fitzgerald in 1883 and the resurvey executed by Ty White and Bert E. Wakeman in 1943</p> <hr/> <p>From the cor. of secs. 1, 2, 35, and 36, on the S bdy. of the Tp. N 0°26' E, bet. secs. 35 and 36.</p> <p>Asc. over gradual SW slope, changing to W, through ponderosa pine.</p>
15.00	Low spur, slopes W.
19.88	<p>Point for the S 1/16 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23N R6E S 1/16 S35 S36 1985</p> <p>from which</p> <p>A ponderosa pine, 12 ins. diam., bears N 28° E, 156 lks. dist., mkd. S 1/16 S36 BT.</p> <p>A ponderosa pine, 19 ins. diam., bears N 69 1/2° W, 71.5 lks. dist., mkd. S 1/16 S35 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. silver colored plastic case beneath the stainless steel post and raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p>
21.60	Small draw, drains SW, soon W.

9
BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
37.00	Low spur, slopes W.
39.76	The 1/4 sec. cor. of secs. 35 and 36, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, 2 1/2 ft. base, with brass cap mkd. <div style="text-align: center;">1/4 S35 S36 1943</div> <hr/> <p>N 0°37' W, beginning new measurement.</p> <p>Over land sloping generally W, through ponderosa pine.</p>
17.80	Small draw, drains NW.
19.995	Point for the N 1/16 sec. cor. of secs. 35 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T23N R6E N 1/16 S35 S36 1985</div> <p>from which</p> <p style="margin-left: 40px;">A double limber pine, 16 ins. diam., bears N 58 1/4° E, 61.5 lks. dist., mkd. N 1/16 S36 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 18 ins. diam., bears N 53 3/4° W, 157 lks. dist., mkd. N 1/16 S35 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. blue colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
39.99	The cor. of secs. 25, 26, 35, and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS

T23N R6E	
S26	S25
S35	S36
1943	

A small mound of stone is W of the cor.

from which the bearing trees mkd. in 1943

A limber pine, 24 ins. diam., bears N 71 1/2° E, 192 lks.
dist., with no visible scar. (Record: 194 lks.)

A limber pine, 22 ins. diam., bears S 63 3/4° E, 207 lks.
dist., with no visible scar. (Record: 208 lks.)

A pinyon pine, 18 ins. diam., bears S 36° W, 148 lks.
dist., with healed blaze.

Rebuild the mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of
cor.

From the cor. of secs. 23, 24, 25, and 26, monumented with an
iron post, 2 ins. diam., firmly set, projecting 4 ins. above
ground, and in a scattered mound of stone, with brass cap mkd.

T23N R6E	
S23	S24
S26	S25
1943	

from which the bearing trees mkd. in 1943

A double limber pine, 16 ins. diam., bears N 36 1/2° E,
261 lks. dist., with healed blaze on S trunk. (Record:
265 lks.)

A ponderosa pine, 28 ins. diam., bears S 26 3/4° E,
284 lks. dist., with healed blaze. (Record: 286 lks. in
agreement with slope measurement.)

A limber pine, 23 ins. diam., bears S 45 1/4° W, 327 lks.
dist., with healed blaze.

A limber pine, 20 ins. diam., bears N 48 1/2° W, 284 lks.
dist., with healed blaze on most westerly trunk. (Record:
N 47 3/4° W)

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	Rebuild the mound of stone, 3 ft. base, to top, around the iron post.
	N 1°20' E, bet. secs. 23 and 24.
	Over rolling land, through pine and aspen; over a W slope.
5.60	Draw, drains SW.
19.875	Point for the S 1/16 sec. cor. of secs. 23 and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T23N R6E S 1/16 S23 S24 1985</p>
	from which
	A limber pine, 6 ins. diam., bears S 74 1/2° E, 8.5 lks. dist., mkd. S 1/16 S24 BT.
	A limber pine, 6 ins. diam., bears S 34 3/4° W, 32.5 lks. dist., mkd. S 1/16 S23 BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
27.80	Rocky spur, slopes W; desc. over NW slope.
39.75	The 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.
	<p style="text-align: center;">1/4 S23 S24 1943</p>
	from which the bearing trees mkd. in 1943
	A Douglas fir, 12 ins. diam., bears N 47° E, 12 lks. dist., with healed blaze.
	A limber pine, 12 ins. diam., bears N 77° W, 28 lks. dist., with healed blaze.

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS									
	N 1°21' E, beginning new measurement.								
	Over land sloping generally W, through pine and aspen.								
2.70	A dirt road, bears generally E and W.								
12.80	Middle of earth reservoir, approx. 4 chs. diam., bears W, 7.20 chs. dist.								
30.00	Rocky ridge, bears SE and NW; desc. over steep NE slope.								
39.69	The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.								
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T23N R6E</td> </tr> <tr> <td style="text-align: center;">S14</td> <td style="text-align: center;">S13</td> </tr> <tr> <td style="text-align: center;">S23</td> <td style="text-align: center;">S24</td> </tr> <tr> <td colspan="2" style="text-align: center;">1943</td> </tr> </table>	T23N R6E		S14	S13	S23	S24	1943	
T23N R6E									
S14	S13								
S23	S24								
1943									
	from which the bearing trees mkd. in 1943								
	A limber pine, 15 ins. diam., bears N 72 1/2° E, 92 lks. dist., with healed blaze.								
	A limber pine, 13 ins. diam., bears S 34 1/4° E, 207 lks. dist., with healed blaze.								
	An aspen, 17 ins. diam., bears S 27 3/4° W, 64 lks. dist., bark scribed T23N R6E S23 BT. (Record: 65 lks.)								
	An aspen, 13 ins. diam., bears N 47 3/4° W, 88 lks. dist., bark scribed T23N R6E S14 BT.								
	N 1°27' W, bet. secs. 13 and 14.								
	Over rolling land, through pine and aspen; desc. over steep NE slope.								
19.915	Point for the S 1/16 sec. cor. of secs. 13 and 14.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								

.. 13
BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T23N R6E S 1/16 S14 S13 1985</p> <p>from which</p> <p>A white pine, 10 ins. diam., bears S 23° E, 15 lks. dist., mkd. S 1/16 S13 BT.</p> <p>A white pine, 12 ins. diam., bears S 49 3/4° W, 26 lks. dist., mkd. S 1/16 S14 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
39.83	<p>The 1/4 sec. cor. of secs. 13 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S14 S13 1943</p> <p>from which the remains of the bearing trees mkd. in 1943</p> <p>A stump hole, bears S 34 1/2° E, 112 lks. dist.</p> <p>A white pine, 16 ins. diam., bears S 56 1/2° W, 44 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p>A ponderosa pine, 10 ins. diam., bears N 51 3/4° E, 35.5 lks. dist., mkd. 1/4 S13 BT.</p> <p>Add the marks 1985 on the brass cap.</p> <hr/> <p>N 1°26' W, beginning new measurement.</p> <p>Desc. over rolling NW slope, through ponderosa pine and aspen.</p>
19.85	<p>Point for the N 1/16 sec. cor. of secs. 13 and 14.</p>

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23N R6E N 1/16 S14 S13 1985</p> <p>from which</p> <p style="padding-left: 40px;">A white pine, 8 ins. diam., bears S 67 1/2° E, 102 lks. dist., mkd. N 1/16 S13 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N 1° W, 52.5 lks. dist., mkd. N 1/16 S14 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located 55 lks. W of a dirt road, bearing irregularly N and S.</p> <p>27.295 The 1/1024 sec. cor. of secs. 13 and 14, identical with the SE cor. of White Horse Park subdivision, established by Wilfred P. Hanson, L.S. 2473, in 1969 and monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with two steel fence posts alongside, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">1/1024 1985</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S 52 3/4° E, 89 lks. dist., mkd. 1/1024 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears S 36° W, 100.5 lks. dist., mkd. 1/1024 BT.</p>
--------	---

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS

Insert the rebar inside the stainless steel post and deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

N 1°26' W, beginning new measurement.

Desc. over rolling NW slope.

Along easterly bdy. of White Horse Park subdivision.

12.405

The cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 2 ins. diam., firmly set, 2 ins. below the surface of the ground, with brass cap mkd.

T23N R6E	
S11	S12
S14	S13
1943	

from which the original bearing trees

A ponderosa pine, 32 ins. diam., bears N 45° E, 95 lks. dist., with scribe marks T23N R6E visible on blaze made in 1883 and scribe marks T23N R6E S12 BT visible on blaze made in 1943.

A ponderosa pine, 26 ins. diam., bears S 73 1/4° E, 140 lks. dist., with healed blazes.

A decayed ponderosa pine stump, 20 ins. diam., bears S 71 3/4° W, 92 lks. dist., with scribe marks 4 BT visible.

and the bearing tree mkd. in 1943

A ponderosa pine, 22 ins. diam., bears N 34° W, 113 lks. dist., with healed blaze.

The cor. is located at abandoned fence cor., from which fences extend S and W.

From the cor. of secs. 2, 3, 34, and 35, on the S bdy. of the Tp.

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	N 0°07' W, bet. secs. 34 and 35.
	Over gradual SW slope, through scattered ponderosa pine.
	Along U.S. Forest Service Route 151.
20.00	Point for the S 1/16 sec. cor. of secs. 34 and 35, falls in graded road bearing N and S.
	Set an aluminum post, 14 ins. long, 3/4 in. diam., 2 ins. below surface of road, with cap mkd.
	<p style="text-align: center;">T23N R6E S 1/16 S34 S35 1985</p>
	from which
	A ponderosa pine, 12 ins. diam., bears S 46 1/2° E, 165 lks. dist., mkd. S 1/16 S35 BT.
	A ponderosa pine, 15 ins. diam., bears S 22 1/4° W, 211 lks. dist., mkd. S 1/16 S34 BT.
29.50	Top of ascent; desc. over gradual W slope.
40.00	The 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, and in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">1/4 S34 S35 1943</p>
	A mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, is W of cor. and another mound of stone, 4 ft. base, 1 ft. high is NE.
	The cor. is located at SE side of fence cor., from which fences extend W and irregularly N.
	<hr style="width: 20%; margin: auto;"/> <p>N 0°24' E, beginning new measurement.</p>
	Over gradual W slope, through ponderosa pine; line follows near U.S. Forest Service Route 151.
1.10	A dirt road, bears SE and NW, curving N.

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
20.42	<p>The N 1/16 sec. cor. of secs. 34 and 35, established by Wilfred P. Hanson, L.S. 2473, in 1969?, and monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with an iron rod of unknown origin, 1 in. diam., projecting 14 ins. above ground SE, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T23N R6E N 1/16 S34 S35 1985</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S 19° E, 45 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears S 65 1/4° W, 113.5 lks. dist., mkd. N 1/16 S34 BT.</p> <p>Insert the rebar inside the stainless steel post and deposit a magnet in a 1 x 1 x 2 5/8 in. orange colored plastic case beneath the stainless steel post.</p> <p>The cor. is located 1.5 lks. W of fence extending N and S.</p> <p style="text-align: center;">_____</p> <p>N 0°24' E, beginning new measurement.</p> <p>Over gradual W slope, changing to NW, through ponderosa pine.</p> <p>Along fence.</p>
20.42	<p>The cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above ground, and in a mound of stone, 2 ft. base, with brass cap mkd.</p>

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS											
	<table border="1"> <tr> <td colspan="2">T23N R6E</td> </tr> <tr> <td>S27</td> <td>S26</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S34</td> <td>S35</td> </tr> <tr> <td colspan="2">1943</td> </tr> </table>	T23N R6E		S27	S26	<hr/>		S34	S35	1943	
T23N R6E											
S27	S26										
<hr/>											
S34	S35										
1943											
	<p>from which the bearing trees mkd. in 1943</p> <p>A ponderosa pine, 22 ins. diam., bears S 6 3/4° E, 155 lks. dist., with healed blaze. (Record: 156 lks.)</p> <p>A ponderosa pine, 22 ins. diam., bears S 68 3/4° W, 167 lks. dist., with healed blaze.</p> <p>A small mound of stone is W of the cor.</p> <p>Rebuild the mound of stone, 2 1/2 ft. base, 6 ins. high, W of cor.</p> <p>The cor. is located 4 lks. N of fence cor., from which fences extend S and W.</p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>N 89°05' W, bet. secs. 26 and 35.</p> <p>Desc. over gradual W slope, through scattered ponderosa pine.</p>										
19.84	<p>Point for the E 1/16 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T23N R6E</td> </tr> <tr> <td></td> <td>S26</td> </tr> <tr> <td>E 1/16</td> <td>—</td> </tr> <tr> <td></td> <td>S35</td> </tr> <tr> <td colspan="2">1985</td> </tr> </table> </p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>	T23N R6E			S26	E 1/16	—		S35	1985	
T23N R6E											
	S26										
E 1/16	—										
	S35										
1985											

19
BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	From this cor., the NE fence cor. of an 8 ft. high cyclone fence encompassing a spring bears S 31 3/4° E, 1.85 chs. dist.; and the NW fence cor. bears S 15 3/4° E, 1.64 chs. dist.
27.40	Draw, drains NW; slope changing to NW.
29.50	An iron water tank, 10 ft. high, 27 ft. long, bears S, 1 ch. dist.
39.32	A down fence cor. bears S, 75 lks. dist., from which down fences extend E, S, and W.
39.68	The 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, and in a collar of stone, with brass cap mkd.
	S26 1/4 ——— S35 1943
	from which the bearing trees mkd. in 1943
	A willow, 24 ins. diam., bears N 8 3/4° E, 170 lks. dist., with scribe marks 1/4 S26 BT visible on open blaze.
	A willow, 18 ins. diam., bears S 68° E, 142 lks. dist., with scribe marks 1/4 S35 BT visible on partially healed blaze. (Record: 145 lks.)
	From this cor., an open end pipe, of unknown origin, 1 in. diam., projecting 4 ins. above ground, bears N 84° E, 7 lks. dist.
	—————
	N 89°09' W, beginning new measurement.
	Desc. over gradual NW slope.
19.825	Point for the W 1/16 sec. cor. of secs. 26 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	T23E R6E S26 W 1/16 ——— S35 1985
	from which
	A ponderosa pine, 10 ins. diam., bears N 84° E, 194.5 lks. dist., mkd. X BT.
	A ponderosa pine, 13 ins. diam., bears S 83° W, 46.5 lks. dist., mkd. W 1/16 S35 BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
38.10	U.S. Forest Service Route 151, graded, bears S and N, changing to NW.
39.65	The cor. of secs. 26, 27, 34, and 35.
	<hr/> N 0°04' E, bet. secs. 26 and 27.
	Desc. over gradual NW slope, through scattered ponderosa pine.
0.23	Wash, 10 lks. wide, drains NW.
2.80	U.S. Forest Service Route 151, graded, bears SE and NW.
19.57	Point for the S 1/16 sec. cor. of secs. 26 and 27.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, with cap mkd.
	T23N R6E S 1/16 S27 S26 1985
	from which

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A basalt boulder, 1 1/2 x 1 1/2 ft., projecting 6 ins. above ground, bears S 20° W, 19.2 lks. dist., mkd. X BO on NE face.</p> <p>A basalt boulder, 3 x 2 ft., projecting 6 ins. above ground, bears N 69 1/2° W, 31.1 lks. dist., mkd. X BO on the top.</p> <p>From this cor., fence cor. bears N 10 3/4° E, 8 lks. dist., from which fences extend N, E, and S 80° W, 20 lks. dist. to another fence cor., from which fences extend N 80° E, S 25° E, and S 80° W.</p> <p>Along fence.</p>
25.10	A dirt road, bears NE and SW.
29.40	A creek, 10 lks. wide, course SW; asc. over SE slope.
39.14	The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with a steel fence post near by, with brass cap mkd.
	$\begin{array}{c} 1/4 \\ S27 \quad \quad S26 \\ 1943 \end{array}$
	<p>The cor. is located at N end of fence extending S.</p> <p>From this cor., an open end pipe, of unknown origin, 1 in. diam., projecting 10 ins. above ground, bears S 23° E, 60.8 lks. dist. This pipe is located at W end of fence extending E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°08' E, beginning new measurement</p> <p>Over rolling land, asc. over SE slope.</p>
4.00	Top of ascent on Fern Mt., slopes E; desc. over NE slope.
19.59	The N 1/16 sec. cor. of secs. 26 and 27, established by Wilfred P. Hanson, L.S. 2473, in the 1960's, and monumented with a rebar, 24 ins. long, 1/2 in. diam., firmly set, projecting 4 ins. above ground, and is accepted as a careful and faithful determination of the position of the cor.

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T23N R6E
N 1/16
S27 | S26
1985

from which

A limber pine, 8 ins. diam., bears S 37 1/4° W, 71 lks.
dist., mkd. X BT.

A limber pine, 8 ins. diam., bears N 38° W, 19 lks. dist.,
mkd. N 1/16 S27 BT.

Insert the rebar inside the stainless steel post and deposit a
magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath
the stainless steel post.

Set a steel fence post near the cor.

From this cor., the SE cor. of a log cabin, 100 x 30 ft., bears
N 59°12' E, 95 lks. dist., the long side bears N 4° E.

From this same cor., the NW cor. of a log cabin, 13 x 10 ft.,
bears S 16°42' W, 1.71 chs. dist., the long side bears S 10° E.

From this same cor., the SE cor. of a wood shed, 3 1/2 x 3 1/2
ft., bears N 55°41' W, 4.155 chs. dist., one side bears N 85° W.

From this same cor., the SE cor. of a log cabin, 17 x 9 ft.,
bears N 51°37' W, 4.00 chs. dist., the long side bears N 82° W.

From this same cor., the SE cor. of a log cabin, 17 x 14 ft.,
bears N 37°50' W, 2.755 chs. dist., the long side bears N 82° W.

From this same cor., the NE cor. of a log cabin, 17 x 14 ft.,
bears N 36°32' W, 4.11 chs. dist., the long side bears E.

From this same cor., the SE cor. of a log cabin, 40 x 18 ft.,
bears N 25°49' W, 1.60 chs. dist., the long side bears N 7° E.

From this same cor., the NE cor. of a wood shed, 7 x 6 1/2 ft.,
bears N 18°45' W, 1.055 chs. dist., the long side bears N 7° E.

.. 23
BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS											
	From this same cor., the SE cor. of a log cabin, 16 x 12 1/2 ft., bears N 17°03' W, 4.825 chs. dist., the long side bears W.										
	From this same cor., the SW cor. of a privy, 7 x 4 ft., bears N 7°34' W, 3.425 chs. dist., the long side bears N 8° W.										
	—————										
	N 0°08' E, beginning new measurement.										
	Over nearly level land, through aspen, pine, and fir.										
5.19	The easterly side of a garage, 40 1/2 x 17 ft., the SE cor. bears S 12° W, 39 lks. dist., the long side bears N 12° E.										
5.42	The northerly side of same garage, the NE cor. bears S 78° E, 5 lks. dist.										
5.47	The SE cor. of a privy, 5 ft. sq., bears W, 5 lks. dist., one side bears S 88° W.										
19.57	Fence, bears E and W, 6 lks. dist. to fence cor., from which fences extend E and N.										
19.60	The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2 ins. diam., firmly set 6 ins. below the surface, on the W edge of a dirt road bearing S 10° E and N 10° W, with brass cap mkd.										
	<table border="1"><tr><td colspan="2">T23N R6E</td></tr><tr><td>S22</td><td>S23</td></tr><tr><td colspan="2">— —</td></tr><tr><td>S27</td><td>S26</td></tr><tr><td colspan="2">1943</td></tr></table>	T23N R6E		S22	S23	— —		S27	S26	1943	
T23N R6E											
S22	S23										
— —											
S27	S26										
1943											
	from which the remaining original bearing trees										
	A ponderosa pine snag, 47 ins. diam., bears S 2 3/4° E, 48 lks. dist., with scribe marks T23N R6E visible on axed blaze and S26 BT visible on partially healed blaze. (Record: 46 lks. in agreement with measurement to the face.)										
	A ponderosa pine, 38 ins. diam., bears S 49 1/4° W, 161 lks. dist., with scribe marks N R6E S visible on axed blaze. (Record: 160 lks. in agreement with measurement to the face.)										
	and the remaining bearing trees mkd. in 1943										

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A dead and down ponderosa pine, 12 ins. diam., bears N 42 1/2° W, 241 lks. dist., with scribe marks T23N R6E S22 BT visible on open blaze.</p> <p>and new bearing trees</p> <p>A ponderosa pine, 12 ins. diam., bears S 15 1/4° W, 85.5 lks. dist., mkd. T23N R6E S27 BT.</p> <p>A ponderosa pine, 18 ins. diam., bears N 84 3/4° W, 88 lks. dist., mkd. T23N R6E S22 BT.</p>
	<p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>S 89°39' W, bet. secs. 23 and 26.</p> <p>Desc. gradually over land sloping generally W, through ponderosa pine.</p>
19.95	<p>Point for the E 1/16 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23N R6E S23 E 1/16 ——— S26 1985</p> <p>from which</p> <p>A ponderosa pine, 6 ins. diam., bears N 17 1/2° E, 122 lks. dist., mkd. X BT.</p> <p>A ponderosa pine, 18 ins. diam., bears N 52 1/2° W, 208 lks. dist., mkd. E 1/16 S23 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this cor., an open end pipe of unknown origin, 1 in. diam., projecting 14 ins. above ground, bears S 89°46' W, 31.8 lks. dist.</p>
29.925	<p>Point for the W-E 1/64 sec. cor. of secs. 23 and 26.</p>

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S23 W-E 1/64 S26 1985</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N 40° E, 156 lks. dist., mkd. WE 1/64 S23 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N 86 1/4° E, 259 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this cor., an open end pipe of unknown origin, 1 in. diam., projecting 14 ins. above ground, bears N 89°45' W, 27.4 lks. dist. This pipe is located in fence extending N and at N end of gate extending S 13° E, 24 lks. dist. to fence cor., from which fences extend W and N 13° W, soon N.</p> <p>39.845 An open end pipe, of unknown origin, 1 1/2 ins. diam., projecting 6 ins. above ground.</p> <p>39.90 The 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">S23 1/4 _____ S26 1943</p> <p>from which the bearing trees mkd. in 1943</p> <p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears N 58 1/2° E, 38 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears S 9° E, 48 lks. dist., with healed blaze.</p>

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>From this cor., fence cor. bears S 48° E, 4 lks. dist., from which fences extend E, S, and W.</p> <hr/>
	<p>S 89°42' W, beginning new measurement.</p>
	<p>Desc. gradually over land sloping generally W, through aspen and pine.</p>
19.925	<p>Point for the W 1/16 sec. cor. of secs. 23 and 26.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T23N R6E S23 W 1/16 ——— S26 1985</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post near the cor.</p>
	<p>The cor. is located 2.5 lks. N of fence extending E and W.</p>
26.40	<p>Leave timber, edge bears N and S.</p>
35.70	<p>Enter timber, edge bears N and S.</p>
39.80	<p>A dirt road, bears S 10° E and N 10° W.</p>
39.85	<p>The cor. of secs. 22, 23, 26, and 27.</p> <hr/>
	<p>N 1°05' W, bet. secs. 22 and 23.</p>
	<p>Over gently rolling land, through aspen and pine.</p>
	<p>Along fence.</p>
4.994	<p>Point for the S-S-S 1/256 sec. cor. of secs. 22 and 23.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">S-S-S 1/256 S22 S23 1985</p> <p>from which</p> <p>A limber pine, 6 ins. diam., bears N 10 1/2° E, 46 lks. dist., mkd. X BT.</p> <p>A ponderosa pine, 14 ins. diam., bears S 67° W, 61.5 lks. dist., mkd. SSS 1/256 S22 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. gray colored plastic case beneath the stainless steel post.</p> <p>The cor. is located 11 lks. N of fence cor., from which fences extend E and S.</p> <p>5.10 A dirt road, on curve, bears E from S.</p> <p>19.975 Point for the S 1/16 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23N R6E S 1/16 S22 S23 1985</p> <p>from which</p> <p>A ponderosa pine, 8 ins. diam., bears N 82° E, 54 lks. dist., mkd. S 1/16 S23 BT.</p> <p>A ponderosa pine, 12 ins. diam., bears S 15 1/4° W, 49 lks. dist., mkd. S 1/16 S22 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. gray colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
39.95	<p>The 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S22 S23 1943</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A stump hole, bears S 41 1/2° E, 9 lks. dist., with a down aspen alongside, 20 ins. diam., with no marks remaining.</p> <p>and the bearing trees mkd. in 1943</p> <p style="padding-left: 40px;">A limber pine, 20 ins. diam., bears S 51 3/4° E, 152 lks. dist., with healed blaze. (Record: S 50 1/2° E, 151 lks.)</p> <p style="padding-left: 40px;">A limber pine, 14 ins. diam., bears S 64° W, 72 lks. dist., with healed blaze. (Record: 71 lks.)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 3°42' E, beginning new measurement.</p> <p>Over rolling land, through pine, aspen and fir; asc. over gradual W slope.</p>
4.40	A dirt road, bears NE and SW.
11.00	Ridge, bears E and W; desc. over N slope.
19.88	<p>Point for the N 1/16 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23N R6E N 1/16 S22 S23 1985</p> <p>from which</p> <p style="padding-left: 40px;">A Douglas fir, 6 ins. diam., bears S 64 1/2° E, 33.5 lks. dist., mkd. N 1/16 S23 BT.</p> <p style="padding-left: 40px;">A limber pine, 7 ins. diam., bears S 54° W, 84.5 lks. dist., mkd. N 1/16 S22 BT.</p>

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS											
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.										
	Set a steel fence post near the cor.										
24.60	U.S. Forest Service Route 151, graded, bears NE and SW, curving W.										
39.76	The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T23N R6E</td></tr> <tr><td style="text-align: center;">S15</td><td style="text-align: center;">S14</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S22</td><td style="text-align: center;">S23</td></tr> <tr><td colspan="2" style="text-align: center;">1943</td></tr> </table>	T23N R6E		S15	S14	-----		S22	S23	1943	
T23N R6E											
S15	S14										

S22	S23										
1943											
	A mound of stone, 2 ft. base, 1 ft. high, is W of cor.										
	Set a steel fence post near the cor.										
	From the cor. of secs. 13, 14, 23, and 24.										
	S 89°53' W, bet. secs. 14 and 23.										
	Over rolling land, through aspen, pine, and fir; asc. over NE slope.										
10.40	Top of ascent, slopes N; desc. over NW slope.										
19.80	Draw, drains NW; asc. gradually over NE slope.										
19.94	Point for the E 1/16 sec. cor. of secs. 14 and 23.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T23N R6E</td></tr> <tr><td colspan="2" style="text-align: center;">S14</td></tr> <tr><td style="text-align: center;">E 1/16</td><td style="text-align: center;">-----</td></tr> <tr><td colspan="2" style="text-align: center;">S23</td></tr> <tr><td colspan="2" style="text-align: center;">1985</td></tr> </table>	T23N R6E		S14		E 1/16	-----	S23		1985	
T23N R6E											
S14											
E 1/16	-----										
S23											
1985											

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	from which
	A Douglas fir, 8 ins. diam., bears N 40 3/4° E, 78 lks. dist., mkd. E 1/16 S14 BT.
	A Douglas fir, 10 ins. diam., bears S 9 3/4° W, 33 lks. dist., mkd. E 1/16 S23 BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
25.00	Low spur, slopes N; desc. over rolling NW slope.
39.88	The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.
	S14
	1/4 ———
	S23
	1943
	from which the remaining bearing tree mkd. in 1943
	A Douglas fir snag, 8 ins. diam., bears N 24 1/4° W, 39 lks. dist., with scribe marks 1/4 S14 BT visible on open blaze. (Record: N 22° W).
	and new bearing trees
	A Douglas fir, 14 ins. diam., bears S 57 1/2° W, 57 lks. dist., mkd. 1/4 S23 BT.
	A limber pine, 8 ins. diam., bears N 38 1/2° W, 46 lks. dist., mkd. 1/4 S14 BT.
	Add the marks 1985 on the brass cap.

	S 89°43' W, beginning new measurement.
	Desc. over rolling NW slope, through aspen, pine, and fir.

31
BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
19.955	<p>Point for the W 1/16 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23E R6E S14 W 1/16 _____ S23 1985</p> <p>from which</p> <p style="padding-left: 40px;">A limber pine, 5 ins. diam., bears S 75 3/4° E, 41.5 lks. dist., mkd. W 1/16 S23 BT.</p> <p style="padding-left: 40px;">A limber pine, 8 ins. diam., bears N 44 1/4° E, 38 lks. dist., mkd. W 1/16 S14 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
28.20	U.S. Forest Service Route 151, graded, bears NE and SW.
39.91	The cor. of secs. 14, 15, 22, and 23.
<hr/>	
N 2°08' W, bet. secs. 14 and 15.	
Over gently rolling land.	
14.00	Enter timber, edge bears E and W.
19.815	<p>Point for the S 1/16 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23N R6E S 1/16 S15 S14 1985</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N 56 1/4° E, 40.5 lks. dist., mkd. S 1/16 S14 BT.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 14 ins. diam., bears N 63 3/4° W, 46.5 lks. dist., mkd. S 1/16 S15 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
39.63	<p>The 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S15 S14 1943</p> <p>from which the bearing trees mkd. in 1943</p> <p>A white pine, 15 ins. diam., bears S 14° E, 8 lks. dist., with scribe marks 1/4 S14 BT visible on open blaze.</p> <p>A ponderosa pine, 12 ins. diam., bears N 83 1/2° W, 38 lks. dist., with scribe marks 1/4 S15 BT visible on open blaze.</p> <hr/> <p>N 2°09' W, beginning new measurement.</p> <p>Over rolling land, through pine, aspen, and fir.</p>
19.81	<p>Point for the N 1/16 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23N R6E N 1/16 S15 S14 1985</p> <p>from which</p> <p>A Douglas fir, 14 ins. diam., bears S 1 3/4° E, 21.5 lks. dist., mkd. N 1/16 S14 BT.</p>

33
BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A Douglas fir, 12 ins. diam., bears N 63 1/4° W, 37 lks. dist., mkd. N 1/16 S15 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
27.24	<p>The 1/1024 sec. cor. of secs. 14 and 15, established by Wilfred P. Hanson, L.S. 2473, in 1969, and monumented with a rebar, 18 ins. long, 5/8 in. diam., firmly set, projecting 2 ins. above ground, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">1/1024 1985</p> <p>from which</p> <p>A Douglas fir, 9 ins. diam., bears S 60 1/4° E, 20.5 lks. dist., mkd. 1/1024 BT.</p> <p>A Douglas fir, 14 ins. diam., bears N 85 1/4° W, 34 lks. dist., mkd. 1/1024 BT.</p> <p>Insert the rebar inside the stainless steel post and set a steel fence post near the cor.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <hr/> <p>N 2°09' W, beginning new measurement.</p> <p>Desc. over NE slope.</p>
12.38	<p>The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p>

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS

T23N R6E	
S10	S11
S15	S14
1943	

from which the remains of the original bearing trees

A ponderosa pine stump, 24 ins. diam., bears S 79° E,
46 lks. dist., with scribe marks N R6E S14 BT.

The decayed remains of a pine stump, bears S 62 1/4° W,
67 lks. dist., with a down pine alongside, no marks
remaining. (Record: 65 lks.)

and the bearing trees mkd. in 1943

A ponderosa pine snag, 14 ins. diam., bears N 79 1/4° E,
42 lks. dist., with scribe marks T23N R6E S11 BT visible.

A ponderosa pine, 30 ins. diam., bears S 75 1/2° W,
147 lks. dist., with scribe marks T23N R6E S15 BT visible.

A ponderosa pine stump, 24 ins. diam., bears N 32° W,
64 lks. dist., with scribe marks R23E S10 BT visible.

and new bearing trees

A ponderosa pine, 12 ins. diam., bears N 24 3/4° E,
25.5 lks. dist., mkd. T23N R6E S11 BT.

A ponderosa pine, 6 ins. diam., bears N 52° W, 105.5 lks.
dist., mkd. T23N R6E S10 BT.

Add the marks 1985 on the brass cap.

From the cor. of secs. 11, 12, 13, and 14.

S 89°41' W, bet. secs. 11 and 14.

Desc. over rolling NW slope, through pine and aspen.

Along fence and northerly bdy. of White Horse Park subdivision.

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
20.18	<p>Point for the E 1/16 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23N R6E S11 E 1/16 ——— S14 1985</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears N 29° E, 65.5 lks. dist., mkd. E 1/16 S11 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N 29° W, 54.5 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located 12 lks. S of fence extending E and W.</p>
40.36	<p>The 1/4 sec. cor. of secs. 11 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">S11 1/4 ——— S14 1943</p> <p>from which the remaining bearing tree mkd. in 1943</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears N 43° E, 168 lks. dist., with scribe marks 1/4 visible.</p> <p>An open end pipe, of unknown origin, 3/4 in. diam., projecting 27 ins. above ground, is S of cor.</p> <p>The cor. is located 1 ch. W of wooded area.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S 89°30' W, beginning new measurement.</p>

36
BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	Over gently rolling land, across meadow.
8.00	Enter timber, edge bears NE and SW.
10.095	The E-W 1/64 sec. cor. of secs. 11 and 14, established by Wilfred P. Hanson, L.S. 2473, in 1969?, and monumented with a rebar, 12 ins. long, 1/2 in. diam., firmly set, projecting 3 ins. above ground, and is accepted as a careful and faithful determination of the position of the cor.
	At the cor. point
	Set an aluminum post, 12 ins. long, 3/4 in. diam., in drill hole, in bedrock, and in a mound of stone, 2 ft. base, to top, with cap mkd.
	S11 E-W 1/64 ——— S14 1985
	from which
	A ponderosa pine, 16 ins. diam., bears N 70 1/2° E, 31 lks. dist., mkd. EW 1/64 S11 BT.
	Bury the rebar alongside the aluminum post and set a steel fence post near the cor.
	—————
	S 89°30' W, beginning new measurement.
	Over gently rolling land.
10.095	Point for the W 1/16 sec. cor. of secs. 11 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T23N R6E S11 W 1/16 ——— S14 1985
	from which
	A ponderosa pine, 7 ins. diam., bears N 31 1/2° E, 28 lks. dist., mkd. X BT.

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 8 ins. diam., bears N 45 1/4° W, 30.5 lks. dist., mkd. W 1/16 S11 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Over gently rolling land, through pine, aspen, and spruce.</p>
26.596	An aluminum cap, 1 1/2 ins. diam., set flush with ground, mkd. COCONINO COUNTY HWY.
26.928	<p>Point for a witness point on line bet. secs. 11 and 14, on the center of U.S. Forest Service Route 151, graded, bearing N and S.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 8 ins. below surface of road, with cap mkd.</p> <p style="text-align: center;">WP S11 ----- S14 1985</p> <p>from which</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 32 ins. in the ground, for a reference monument, bears N 21° E, 45 ft. dist., with cap mkd. RM 45 FT WP S11 1985, and an arrow pointing to the witness point.</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 32 ins. in the ground, for a reference monument, bears N 39° W, 45.2 ft. dist., with cap mkd. RM 45.2 FT WP S11 1985, and an arrow pointing to the witness point.</p> <p>Set a steel fence post near each reference monument.</p>
28.277	An aluminum cap, 1 1/2 ins. diam., set flush with ground, mkd. COCONINO COUNTY HWY.
30.285	The cor. of secs. 10, 11, 14, and 15.
	<hr/> <p>From the cor. of secs. 3, 4, 33, and 34, on the S bdy. of the Tp. N 0°19' W, bet. secs. 33 and 34.</p>

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	Over broken W slope, changing to SW, through pine and aspen.
	Along fence.
40.87	The 1/4 sec. cor. of secs. 33 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	$\begin{array}{c} 1/4 \\ S33 \mid S34 \\ 1943 \end{array}$
	from which the bearing trees mkd. in 1943
	A ponderosa pine, 41 ins. diam., bears S 43° E, 55 lks. dist., with healed blaze.
	A ponderosa pine, 31 ins. diam., bears S 1° W, 113 lks. dist., with healed blaze.
	The cor. is located 1 lk. N of fence cor., from which fences extend S and E.
	<hr style="width: 20%; margin: 0 auto;"/>
	N 0°06' E, beginning new measurement.
	Asc. over gradual SW slope, through aspen and pine.
0.25	A dirt road, bears NE and SW.
8.00	Low spur, slopes NW; desc. over NW slope.
14.50	Leave timber, edge bears E and W.
28.30	A dirt road, bears E and W.
38.70	A creek, 10 lks. wide, course SW.
39.05	The cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 2 ins. diam., firmly set in a mound of stone, 3 ft. base, with brass cap mkd.
	$\begin{array}{c} T23N \ R6E \\ S28 \mid S27 \\ \hline S33 \mid S34 \\ 1943 \end{array}$
	from which the remaining original bearing tree

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine snag, 41 ins. diam., bears N 28° W, 25 lks. dist., with healed blaze. (Record: 23 lks. in agreement with measurement to the face.)</p> <p>and the bearing trees mkd. in 1943</p> <p>A ponderosa pine, 24 ins. diam., bears N 69 1/2° E, 114 lks. dist., with healed blaze.</p> <p>A rotted ponderosa pine stump, 42 ins. diam., bears S 21 1/2° E, 162 lks. dist., with scribe marks R6E S34 BT visible.</p> <p>A ponderosa pine, 20 ins. diam., bears S 69 3/4° W, 33 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p>A ponderosa pine, 18 ins. diam., bears S 41 3/4° E, 197 lks. dist., mkd. T23N R6E S34 BT.</p> <p>The cor. is located 15 lks. SE of fence cor. from which fences extend N and E.</p> <hr/> <p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>S 89°15' W, bet. secs. 27 and 34.</p> <p>Desc. over gradual NW slope, through ponderosa pine.</p>
6.65	Fence cor., bears N, 46 lks. dist., from which fences extend E and N, 45 lks. dist. to another fence cor., from which fences extend N, S, and a down fence W.
10.07	<p>Point for the E-E 1/64 sec. cor. of secs. 27 and 34.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S27 E-E 1/64 S34 1985</p> <p>from which</p> <p>A ponderosa pine, 24 ins. diam., bears N 78° E, 67.5 lks. dist., mkd. EE 1/64 S27 BT.</p>

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a steel fence post near the cor.</p> <p>The cor. is located 17.5 lks. S of down fence extending E and W, and 87 lks. S of another down fence extending E and W.</p>
20.14	<p>The E 1/16 sec. cor. of secs. 27 and 34, established by Wilfred P. Hanson, L.S. 2473, date unknown, and monumented with a rebar, 24 ins. long, 1/2 in. diam., firmly set, projecting 3 ins. above ground, and is accepted as a careful and faithful determination of the position of the cor.</p>
	<p>At the cor. point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T23N R6E S27 E 1/16 ——— S34 1985</p>
	<p>Insert the rebar inside the stainless steel post and deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post near the cor.</p>
	<p>The cor. is located 17 lks. S of down fence extending E and W, and 79 lks. S of another down fence extending E and W.</p>
	<p style="text-align: center;">—————</p> <p>S 89°17' W, beginning new measurement.</p>
	<p>Desc. over gradual NW slope, through ponderosa pine.</p>
5.03	<p>Point for the E-W-E 1/256 sec. cor. of secs. 27 and 34.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S27 E-W-E 1/256 S34 1985</p>

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A ponderosa pine, 14 ins. diam., bears N 60 1/2° W, 43 lks. dist., mkd. EWE 1/256 S27 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located 13.5 lks. S of down fence extending E and W, and 74 lks. S of another down fence extending E and W.</p> <p>Across meadow.</p>
10.06	<p>A local monument, a rebar, 1/2 in. diam., projecting 1 in. above ground, established by Donald L. Ziemba, L.S. 16218.</p>
20.12	<p>The 1/4 sec. cor. of secs. 27 and 34, monumented with an iron post, 1 in. diam., firmly set flush with the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S27 1/4 ——— S34 1943</p>
	<p>A small mound of stone is N of cor.</p> <p>From this cor., fence cor. bears S 48° W, 14.5 lks. dist., from which fences extend E, S 3 1/2° W and N 3 1/2° E, 69 lks. dist. to another fence cor., from which fences extend E, S 3 1/2° W and W.</p> <p>Rebuild the mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.</p>
	<p style="text-align: center;">—————</p> <p>S 89°16' W, beginning new measurement.</p> <p>Desc. over gradual NW slope, through ponderosa pine.</p>
20.13	<p>Point for the W 1/16 sec. cor. of secs. 27 and 34.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 22 ins. in the ground, and in a mound of stone, 3 1/2 ft. base, to top, with cap mkd.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T23N R6E S27 W 1/16 _____ S34 1985</p> <p>from which</p> <p>A ponderosa pine, 10 ins. diam., bears S 34 1/4° E, 29 lks. dist., mkd. W 1/16 S34 BT.</p> <p>A ponderosa pine, 15 ins. diam., bears N 48 1/2° W, 30 lks. dist., mkd. W 1/16 S27 BT.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located 50 lks. S of fence extending E and W.</p>
39.80	A creek, 10 lks. wide, course SW.
40.26	The cor. of secs. 27, 28, 33, and 34.
	<hr/>
	<p>N 0°10' W, bet. secs. 27 and 28.</p> <p>Asc. over S slope, through ponderosa pine and aspen.</p>
10.10	U.S. Forest Service Route 494, unimproved, bears E and W.
20.02	Point for the S 1/16 sec. cor. of secs. 27 and 28.
	<p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T23N R6E S 1/16 S28 S27 1985</p> <p>from which</p> <p>A ponderosa pine, 13 ins. diam., bears S 34 1/2° E, 20 lks. dist., mkd. S 1/16 S27 BT.</p> <p>A ponderosa pine, 11 ins. diam., bears N 84° W, 35.5 lks. dist., mkd. S 1/16 S28 BT.</p>

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	Set a steel fence post near the cor.
	The cor. is located 65 lks. W of fence extending N and S.
40.04	The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, and in a collar of stone, with brass cap mkd.
	<div style="text-align: center;"> 1/4 S28 S27 1943 </div>
	from which the bearing trees mkd. in 1943
	<div style="padding-left: 40px;">A ponderosa pine, 31 ins. diam., bears N 66° E, 124 lks. dist., with healed blaze. (Record: 126 lks.)</div>
	<div style="padding-left: 40px;">A ponderosa pine, 27 ins. diam., bears S 14 1/4° W, 146 lks. dist., with scribe marks BT visible on pitched over blaze. (Record: 148 lks.)</div>
	Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W of cor.
	<hr style="width: 20%; margin: auto;"/> N 0°21' W, beginning new measurement.
	Asc. over S slope, through ponderosa pine and aspen.
12.00	Rocky spur, slopes SW; desc. over NW slope.
17.00	Foot of descent.
20.035	Point for the N 1/16 sec. cor. of secs. 27 and 28.
	Set an aluminum post, 24 ins. long, 3/4 in. diam., 12 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with cap mkd.
	<div style="text-align: center;"> T23N R6E N 1/16 S28 S27 1985 </div>
	from which
	<div style="padding-left: 40px;">A limber pine, 12 ins. diam., bears N 83° E, 45.5 lks. dist., mkd. N 1/16 S27 BT.</div>

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 10 ins. diam., bears N 33° W, 22 lks. dist., mkd. N 1/16 S28 BT.</p>
	<p>Set a steel fence post near the cor.</p>
	<p>The cor. is located 200 lks. W of fence extending N and S.</p>
25.044	<p>Point for the S-N-N 1/256 sec. cor. of secs. 27 and 28.</p>
	<p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.</p>
	<p style="text-align: center;">S-N-N 1/256 S28 S27 1985</p>
	<p>from which</p>
	<p>A ponderosa pine, 19 ins. diam., bears S 1/2° E, 126 lks. dist., mkd. SNN 1/256 S27 BT.</p>
	<p>A ponderosa pine, 15 ins. diam., bears S 68 1/4° W, 110 lks. dist., mkd. SNN 1/256 S28 BT.</p>
	<p>Set a steel fence post near the cor.</p>
	<p>From this cor., fence cor. bears S 75° E, 2.19 chs. dist., from which fences extend S and W; and another fence cor. bears N 8° W, 27 lks. dist., from which fences extend N and E.</p>
	<p>Across meadow.</p>
34.50	<p>Enter timber, edge bears irregularly E and W; asc. over SE slope.</p>
40.07	<p>The cor. of secs. 21, 22, 27, and 28, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, and in a small collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T23N R6E S21 S22 ----- S28 S27 1943</p>

45
BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS

from which the remaining original bearing tree

An aspen snag, 14 ins. diam., bears N 60 1/2° W, 74 lks.
dist., with no marks remaining.

and the bearing trees mkd. in 1943

A limber pine, 26 ins. diam., bears N 77 1/4° E, 52 lks.
dist., with scribe marks T23N R6E S22 BT visible on open
blaze. (Record: 51 lks. in agreement with measurement to
the face.)

A ponderosa pine, 48 ins. diam., bears S 74 3/4° E, 154 lks.
dist., with scribe marks T23N R6E S27 BT visible on open
blaze.

A ponderosa pine, 32 ins. diam., bears S 47 3/4° W, 233 lks.
dist., with healed blaze. (Record: 234 lks.)

and a new bearing tree

A ponderosa pine, 9 ins. diam., bears N 57 1/2° W, 70.5 lks.
dist., mkd. T23N R6E S21 BT.

Add the marks 1985 on the brass cap.

From the cor. of secs. 22, 23, 26, and 27.

N 89°30' W, bet. secs. 22 and 27.

Over gradual S slope, through aspen, pine, and fir.

20.25 Point for the E 1/16 sec. cor. of secs. 22 and 27.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T23N R6E
S22
E 1/16 ———
S27
1985

from which

A limber pine, 6 ins. diam., bears S 42 1/2° E, 98 lks.
dist., mkd. E 1/16 S27 BT.

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A limber pine, 10 ins. diam., bears N 75 3/4° W, 40.5 lks. dist., mkd. E 1/16 S22 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post near the cor.</p>
23.60	<p>Low spur, slopes S.</p>
25.313	<p>Point for the E-W-E 1/256 sec. cor. of secs. 22 and 27.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">S22 E-W-E 1/256 S27 1985</p>
	<p>from which</p>
	<p>A limber pine, 8 ins. diam., bears N 26° E, 114 lks. dist., mkd. EWE 1/256 S22 BT.</p>
	<p>A limber pine, 14 ins. diam., bears S 79 1/4° W, 35.5 lks. dist., mkd. EWE 1/256 S27 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post near the cor.</p>
38.05	<p>A dirt road, on curve, bears E from S.</p>
40.50	<p>The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, and in a small mound of stone, with brass cap mkd.</p>
	<p style="text-align: center;">S22 1/4 ——— S27 1943</p>

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which the bearing trees mkd. in 1943</p>
	<p>A ponderosa pine snag, 26 ins. diam., bears N 1/2° E, 46 lks. dist., with scribe marks 1/4 S22 BT visible on partially healed blaze.</p>
	<p>A limber pine, 18 ins. diam., bears S 28 1/2° E, 28 lks. dist., with healed blaze.</p>
	<p>and a bearing tree mkd. by Reid Penland, L.S. 11755, in 1982</p>
	<p>A ponderosa pine, 18 ins. diam., bears N 19 1/4° E, 109 lks. dist., mkd. X BT.</p>
	<p>Rebuild the mound of stone, 3 ft. base, to top.</p>
	<p>Add the marks 1985 on the brass cap.</p>
	<hr/> <p>N 89°26' W, beginning new measurement.</p>
	<p>Over rolling S slope, through pine and aspen.</p>
5.067	<p>Point for the E-E-W 1/256 sec. cor. of secs. 22 and 27.</p>
	<p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.</p>
	<p style="text-align: center;">S22 E-E-W 1/256 S27 1985</p>
	<p>from which</p>
	<p>A ponderosa pine, 12 ins. diam., bears N 46 1/4° E, 31 lks. dist., mkd. EEW 1/256 S22 BT.</p>
	<p>A ponderosa pine, 10 ins. diam., bears N 89° E, 65 lks. dist., mkd. X BT.</p>
	<p>Set a steel fence post near the cor.</p>
6.40	<p>U.S. Forest Service Route 151, graded, bears SE and NW.</p>
20.27	<p>Point for the W 1/16 sec. cor. of secs. 22 and 27.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T23N R6E S22 W 1/16 _____ S27 1985</p>
40.54	<p>Set a steel fence post near the cor.</p> <p>The cor of secs. 21, 22, 27, and 28.</p> <hr/> <p>N 1°39' E, bet. secs. 21 and 22.</p> <p>Over rolling land, through pine and aspen; asc. over gradual SE slope, changing to S.</p>
4.90	Fence, bears NE and SW.
9.935	<p>Point for the S-S 1/64 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S-S 1/64 S21 S22 1985</p>
	<p>from which</p> <p style="padding-left: 40px;">A limber pine, 8 ins. diam., bears N 5° E, 45 lks. dist., mkd. SS 1/64 S22 BT.</p> <p style="padding-left: 40px;">A limber pine, 9 ins. diam., bears S 53 1/4° W, 48 lks. dist., mkd. SS 1/64 S21 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located 4.5 lks. W of fence extending N and S.</p>
16.20	A dirt road, bears NW and SE, soon NE.

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
19.87	<p>Point for the S 1/16 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23N R6E S 1/16 S21 S22 1985</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears S 14 1/2° E, 24 lks. dist., mkd. S 1/16 S22 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S 74° W, 64.5 lks. dist., mkd. S 1/16 S21 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Asc. over S slope, changing to SE.</p>
39.74	<p>The 1/4 sec. cor. of secs. 21 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S21 S22 1943</p> <p>from which the bearing trees mkd. in 1943</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears N 71 3/4° E, 49 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears S 24 1/2° W, 83.5 lks. dist., with healed blaze. (Record: 82 lks.)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 1°38' E, beginning new measurement.</p> <p>Over rolling land, through ponderosa pine; asc. over SE slope.</p>
5.00	<p>Top of ascent, slopes E; desc. over N slope through dense aspen.</p>

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS									
19.88	<p>The N 1/16 sec. cor. of secs. 21 and 22, established by Wilfred P. Hanson, L.S. 2473, in 1962, and monumented with a rebar, 5/8 in. diam., buried in a collar of stone, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>Cor. point not remonumented.</p> <p>From this cor., a U.S. Dept. of Agriculture Forest Service monument, an aluminum post, 1 in. diam., firmly set, projecting 10 ins. above ground, and in a collar of stone, with cap mkd. N 1/16 S21 S22 RLS 11755 1983, set by Reid Penland, bears S 22° E, 0.8 lk. dist.</p> <p>The cor. is located near fence cor., from which fences extend E and N.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 1°39' E, beginning new measurement.</p> <p>Along fence.</p>								
3.50	<p>A dirt road, bears generally E and W; and bottom of descent; asc. over SE slope.</p>								
19.855	<p>The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.</p> <table border="1" data-bbox="846 1192 993 1346" style="margin: 10px auto;"> <tr> <td colspan="2" style="text-align: center;">T23N R6E</td> </tr> <tr> <td style="text-align: center;">S16</td> <td style="text-align: center;">S15</td> </tr> <tr> <td style="text-align: center;">S21</td> <td style="text-align: center;">S22</td> </tr> <tr> <td colspan="2" style="text-align: center;">1943</td> </tr> </table> <p>from which the original bearing trees</p> <p>A ponderosa pine snag, 32 ins. diam., bears S 4 1/2° E, 36 lks. dist., with scribe marks T23N R6E S22 BT visible on open blaze.</p> <p>A ponderosa pine snag, 28 ins. diam., bears N 12 3/4° W, 92 lks. dist., with scribe marks T23N R6E S16 BT visible on open blaze. (Record: 91 lks.)</p> <p>and the bearing trees mkd. in 1943</p> <p>A ponderosa pine, 14 ins. diam., bears N 47° E, 22 lks. dist., with healed blaze.</p>	T23N R6E		S16	S15	S21	S22	1943	
T23N R6E									
S16	S15								
S21	S22								
1943									

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A fir, 16 ins. diam., bears S 48 3/4° W, 58 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p>A ponderosa pine, 9 ins. diam., bears N 26° W, 34.5 lks. dist., mkd. T23N R6E S16 BT.</p> <p>Add the marks 1985 on the brass cap.</p> <p>The cor. is located at fence cor., from which fences extend E and S.</p> <hr/> <p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>N 89°33' W, bet. secs. 15 and 22.</p> <p>Asc. over gradual NE slope, across meadow.</p>
9.80	Draw, drains NE; asc. over E slope.
20.13	<p>Point for the E 1/16 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23N R6E S15 E 1/16 ——— S22 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
23.00	Enter timber, edge bears generally N and S.
32.00	Slope changing to SE.
40.26	The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	S15 1/4 ——— S22 1943
	<p>from which the bearing tree recovered in 1943</p> <p style="padding-left: 40px;">A ponderosa pine snag, 28 ins. diam., bears N 52° E, 36 lks. dist., with no marks visible on axed open blaze.</p> <p>and the bearing tree mkd. in 1943</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears S 74 1/2° W, 36 lks. dist., with scribe marks 1/4 S22 BT visible on open blaze. (Record: S 76° W.)</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S 36° E, 26.5 lks. dist., mkd. X BT.</p> <p>Add the marks 1985 on the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 89°40' W, beginning new measurement.</p> <p>Asc. over SE slope.</p>
7.50	Top of ascent, slopes S; desc. over W slope.
10.07	<p>The E-W 1/64 sec. cor. of secs. 15 and 22, established by Wilfred P. Hanson, L.S. 2473, in 1962 and monumented with a rebar, 1/4 in. diam., firmly set, flush with the ground, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>Cor. point not remonumented.</p> <p>From this cor., a rebar, 1/2 in. diam., firmly set, projecting 4 ins. above ground, and in a collar of stone, set by Reid Penland in 1983, bears N 52° E, 3.3 lks. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 89°40' W, beginning new measurement.</p> <p>Desc. over W slope, changing to S.</p>

BOOK 5295

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
10.07	<p>The W 1/16 sec. cor. of secs. 15 and 22, established by Wilfred P. Hanson, L.S. 2473, in 1962 and monumented with a rebar, 1/2 in. diam., firmly set, flush with the ground, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>Cor. point not remonumented.</p> <p>From this cor., a U.S. Dept. of Agriculture Forest Service monument, an aluminum post, 1 in. diam., firmly set, projecting 3 ins. above ground, and in a collar of stone, with cap mkd. W 1/16 S15 S22 RLS 11755 1983, set by Reid Penland, bears S 82° E, 2.3 lks. dist.</p> <p>The cor. is located near fence cor., from which fences extend W and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 89°38' W, beginning new measurement.</p> <p>Asc. over S slope, changing to SE.</p> <p>Along fence.</p>
20.14	<p>The cor. of secs. 15, 16, 21, and 22.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">Subdivision of Section 14, T 23 N, R 6 E, Gila and Salt River Mer., Arizona</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 14 and 23.</p> <p>N 1°48' W, on the N and S center line of sec. 14.</p> <p>Over rolling land, through pine and aspen.</p>
19.84	<p>Point for the center S 1/16 sec. cor. of sec. 14.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>T23N R6E</p> <p>C</p> <p>S 1/16 S 14</p> <p>C</p> <p>1985</p> </div>

BOOK 5295

Subdivision of Section 14,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A spruce, 12 ins. diam., bears S 31 1/4° W, 36 lks. dist., mkd. CS 1/16 S14 BT.</p> <p>A Douglas fir, 14 ins. diam., bears N 69° W, 64.5 lks. dist., mkd. CS 1/16 S14 BT.</p> <p>Set a steel fence post near the cor.</p>
39.68	<p>Point for the center 1/4 sec. cor. of sec. 14, at the intersection with the E and W center line of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23N R6E C 1/4 S14 1985</p>
	<p>from which</p> <p>A ponderosa pine, 8 ins. diam., bears N 34° E, 41.5 lks. dist., mkd. C 1/4 S14 BT.</p> <p>A Douglas fir, 12 ins. diam., bears N 76 1/2° W, 80.5 lks. dist., mkd. C 1/4 S14 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
59.545	<p>Point for the center N 1/16 sec. cor. of sec. 14.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T23N R6E C N 1/16 S 14 C 1985</p>
	<p>from which</p> <p>A white pine, 14 ins. diam., bears N 84 1/2° E, 37 lks. dist., mkd. CN 1/16 S14 BT.</p>

55
BOOK 5295

Subdivision of Section 14,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A white pine, 4 ins. diam., bears S 27° W, 13 lks. dist., mkd. X BT.</p>
	<p>Set a steel fence post near the cor.</p>
66.995	<p>The 1/1024 sec. cor. of sec. 14, on the S bdy. of White Horse Park subdivision, established by Wilfred P. Hanson, L.S. 2473, in 1969 and monumented with a rebar, 18 ins. long, 3/4 in. diam., firmly set, projecting 6 ins. above ground, and is accepted as a careful and faithful determination of the position of the cor.</p>
	<p>At the cor. point</p>
	<p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, and in a collar of stone, with cap mkd.</p>
	<p>1/1024 1985</p>
	<p>from which</p>
	<p>A basalt outcrop, 15 x 5 x 4 ft. above ground, bears S 77 1/4° E, 31 lks. dist., mkd. X BO.</p>
	<p>A white pine, 6 ins. diam., bears S 40 3/4° W, 65.5 lks. dist., mkd. 1024 BT.</p>
	<p>Bury the rebar alongside the aluminum post and set a steel fence post near the cor.</p>
	<p>_____</p> <p>N 1°48' W, beginning new measurement.</p>
12.415	<p>The 1/4 sec. cor. of secs. 11 and 14.</p>
	<p>_____</p> <p>From the 1/4 sec. cor. of secs. 13 and 14.</p>
	<p>S 89°40' W, on the E and W center line of sec. 14.</p>
	<p>Over gently rolling land, through pine, fir, and aspen.</p>
20.055	<p>Point for the center E 1/16 sec. cor. of sec. 14.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 14,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T23N R6E E 1/16 C ————— C S14 1985</p>
	<p>from which</p> <p>A Douglas fir, 8 ins. diam., bears N 68 1/2° E, 18.5 lks. dist., mkd. CE 1/16 S14 BT.</p> <p>A Douglas fir, 11 ins. diam., bears S 17 1/2° W, 22 lks. dist., mkd. CE 1/16 S14 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
40.11	The center 1/4 sec. cor. of sec. 14.
	Over rolling land, through pine and aspen.
60.18	Point for the center W 1/16 sec. cor. of sec. 14.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, with cap mkd.
	<p style="text-align: center;">T23N R6E W 1/16 C ————— C S14 1985</p>
	<p>from which</p> <p>A ponderosa pine, 9 ins. diam., bears N 65° E, 6.5 lks. dist., mkd. CW 1/16 S14 BT.</p> <p>A ponderosa pine, 12 ins. diam., bears N 48° W, 13 lks. dist., mkd. CW 1/16 S14 BT.</p> <p>Set a steel fence post near the cor.</p>
72.00	U.S. Forest Service Route 151, bears N and S. (scaled)
80.25	The 1/4 sec. cor. of secs. 14 and 15.
	<hr/> <p style="text-align: center;">NE 1/4</p> <hr/>

BOOK 5295

Subdivision of Section 14,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
19.86	<p>From the center E 1/16 sec. cor. of sec. 14.</p> <p>N 1°37' W, on the N and S center line of the NE 1/4 of sec. 14.</p> <p>Over rolling land, through pine, fir, and aspen.</p> <p>Point for the NE 1/16 sec. cor. of sec. 14, at the intersection with the E and W center line of the NE 1/4 of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23N R6E NE 1/16 S 14 1987</p> <p>from which</p> <p style="padding-left: 40px;">A Douglas fir, 9 ins. diam., bears S 24° E, 8.5 lks. dist., mkd. NE 1/16 S14 BT.</p> <p style="padding-left: 40px;">A Douglas fir, 13 ins. diam., bears S 49 3/4° W, 31 lks. dist., mkd. NE 1/16 S14 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
27.305	<p>Point for the 1/1024 sec. cor. of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">1/1024 1985</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears S 66 1/4° E, 80.5 lks. dist., mkd. 1/1024 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears S 20 1/4° W, 24 lks. dist., mkd. 1/1024 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>

58
BOOK 5295

Subdivision of Section 14,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
39.715	Set a steel fence post near the cor. The E 1/16 sec. cor. of secs. 11 and 14.
20.115	From the N 1/16 sec. cor. of secs. 13 and 14. S 89°40' W, on the E and W center line of the NE 1/4 of sec. 14. Over rolling land, through pine, fir, and aspen. The NE 1/16 sec. cor. of sec. 14.
40.235	The center N 1/16 sec. cor. of sec. 14.
20.14	From the 1/1024 sec. cor. of secs. 13 and 14, located 7.445 chs., N 1°26' W of the N 1/16 sec. cor. S 89°41' W, on the E and W center line of the N 1/2 of the S 1/2 of the NE 1/4 of the NE 1/4 of sec. 14; along the S bdy. of White Horse Park subdivision. The 1/1024 sec. cor. of sec. 14, located 7.445 chs., N 1°37' W of the NE 1/16.
20.14	S 89°41' W, on the E and W center line of the N 1/2 of the S 1/2 of the NW 1/4 of the NE 1/4 of sec. 14; along the S bdy. of White Horse Park subdivision. The 1/1024 sec. cor. of sec. 14, located 7.45 chs., N 1°48' W of the center N 1/16.
19.885	SE 1/4 From the E 1/16 sec. cor. of secs. 14 and 23. N 1°37.5' W, on the N and S center line of the SE 1/4 of sec. 14. Over rolling land, through pine, fir, and aspen. Point for the SE 1/16 sec. cor. of sec. 14, at the intersection with the E and W center line of the SE 1/4 of sec. 14.

BOOK 5295

Subdivision of Section 14,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.
	<p style="text-align: center;">T23N R6E SE 1/16 S 14 1985</p>
	from which
	A white pine, 13 ins. diam., bears N 89 1/2° E, 22 lks. dist., mkd. SE 1/16 S14 BT.
	A white pine, 6 ins. diam., bears S 17 1/2° W, 28 lks. dist., mkd. SE 1/16 S14 BT.
	Set a steel fence post near the cor.
39.77	The center E 1/16 sec. cor. of sec. 14.
	<hr/> <p>From the S 1/16 sec. cor. of secs. 13 and 14. S 89°47' W, on the E and W center line of the SE 1/4 of sec. 14. Over rolling land, through pine, fir, and aspen.</p>
20.005	The SE 1/16 sec. cor. of sec. 14.
40.01	The center S 1/16 sec. cor. of sec. 14.
	<hr/> <p style="text-align: center;">SW 1/4</p> <hr/>
	<p>From the W 1/16 sec. cor. of secs. 14 and 23. N 1°57.5' W, on the N and S center line of the SW 1/4 of sec. 14. Over rolling land, through pine and aspen.</p>
19.83	Point for the SW 1/16 sec. cor. of sec. 14, at the intersection with the E and W center line of the SW 1/4 of sec. 14
	Set an aluminum post, 12 ins. long, 3/4 in. diam., in a drill hole in basalt outcrop 15 x 15 x 6 ft. high, with cap mkd.

60
BOOK 5295

Subdivision of Section 14,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T23N R6E SW 1/16 S 14 1985</p> <p>from which</p> <p>A white pine, 5 ins. diam., bears N 60° E, 32 lks. dist., mkd. X BT.</p> <p>A white pine, 12 ins. diam., bears S 11° E, 31.5 lks. dist., mkd. SW 1/16 S14 BT.</p>
39.66	The center W 1/16 sec. cor. of sec. 14.
	<hr/> <p>From the center S 1/16 sec. cor. of sec. 14.</p> <p>S 89°41' W, on the E and W center line of the SW 1/4 of sec. 14.</p> <p>Over rolling land, through pine and aspen.</p>
20.01	The SW 1/16 sec. cor. of sec. 14.
24.92	<p>Point for a witness point on the E and W center line of the SW 1/4 of sec. 14, in the center of U.S. Forest Service Route 151, graded, bearing S 25° E and N 25° W.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 7 ins. below surface of road, with cap mkd.</p> <p style="text-align: center;">WP S14 1985</p>
	<p>from which</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 32 ins. flush with the ground, for a reference monument, bears N 22° E, 50 ft. dist., with cap mkd. RM 50 FT WP S14 1985, and an arrow pointing to the witness point.</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 32 ins. flush with the ground, for a reference monument, bears N 68° W, 50 ft. dist., with cap mkd. RM 50 FT WP S14 1985, and an arrow pointing to the witness point.</p> <p>Set a steel fence post near each reference monument.</p>

.. 61
BOOK 5295

Subdivision of Section 14,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
40.02	The S 1/16 sec. cor. of secs. 14 and 15.
	<hr/>
	NW 1/4
	<hr/>
	From the center W 1/16 sec. cor. of sec. 14.
	N 1°58.5' W, on the N and S center line of the NW 1/4 of sec. 14.
	Over gently rolling land, through pine and aspen.
2.00	Leave timber, edge bears N and W.
19.835	Point for the NW 1/16 sec. cor. of sec. 14, at the intersection with the E and W center line of the NW 1/4 of sec. 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T23N R6E NW 1/16 S 14 1985
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
27.273	Point for the 1/1024 sec. cor. of sec. 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	1/1024 1985
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
39.67	The W 1/16 sec. cor. of secs. 11 and 14.
	<hr/>
	From the center N 1/16 sec. cor. of sec. 14.
	S 89°35' W, on the E and W center line of the NW 1/4 of sec. 14.

62
BOOK 5295

Subdivision of Section 14,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	Over gently rolling land, through pine and aspen.
16.00	Leave timber, edge bears NE and SW.
20.13	The NW 1/16 sec. cor. of sec. 14.
32.00	U.S. Forest Service Route 151, bears generally N and S. (scaled)
40.26	The N 1/16 sec. cor. of secs. 14 and 15.
<hr/>	
	From the 1/1024 sec. cor. of sec. 14, located 7.45 chs., N 1°48' W of the center N 1/16.
	S 89°33' W, on the E and W center line of the N 1/2 of the S 1/2 of the NE 1/4 of the NW 1/4 of sec. 14; along the S bdy. of White Horse Park subdivision.
18.75	A local monument, a rebar, 1/4 in. diam., projecting 1 in. above ground, established by Wilfred P. Hanson, L.S. 2473.
20.15	The 1/1024 sec. cor. of sec. 14, located 7.438 chs., N 1°58.5' W of the NW 1/16.
<hr/>	
	S 89°33' W, on the E and W center line of the N 1/2 of the S 1/2 of the NW 1/4 of the NW 1/4 of sec. 14; along the S bdy. of White Horse Park subdivision.
1.70	A local monument, a rebar, 1/4 in. diam., projecting 1 in. above ground, established by Wilfred P. Hanson, L.S. 2473.
10.90	An aluminum cap, 1 1/2 ins. diam., set flush with ground, mkd. COCONINO COUNTY HWY.
12.58	An aluminum cap, 1 1/2 ins. diam., set flush with ground, mkd. COCONINO COUNTY HWY.
16.65	Point for a witness point on the E and W center line of the N 1/2 of the S 1/2 of the NE 1/4 of the NW 1/4 of sec. 14, on the center of U.S. Forest Service Route 151, bearing SE and NW.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 8 ins. below surface of road, with cap mkd.
	WP S14 1985

BOOK 5295

Subdivision of Section 14,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	<p>from which</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 32 ins. in the ground, for a reference monument, bears S 70 1/2°E, 25 ft. dist., with brass cap mkd. RM 25 FT WP S14 1985, and an arrow pointing to the witness point.</p> <p>An aluminum post, 72 ins. long, 3/4 in. diam., set 68 ins. in the ground, for a reference monument, bears S 23 3/4°W, 32 ft. dist., with brass cap mkd. RM 32 FT WP S14 1985, and an arrow pointing to the witness point.</p> <p>Set a steel fence post near each reference monument.</p> <p>20.155 The 1/1024 sec. cor. of secs. 14 and 15, located 7.43 chs., N 2°09' W of the N 1/16.</p> <hr/> <p style="text-align: center;">Subdivisions of Section 22, T 23 N, R 6 E, Gila and Salt River Mer., Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 22 and 27</p> <p>N 1°27' E, on the N and S center line of sec. 22.</p> <p>Over gently rolling land, through pine and aspen.</p> <p>19.925 Point for the center S 1/16 sec. cor of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23N R6E C S 1/16 S22 C 1985</p> <p>from which</p> <p>A ponderosa pine, 12 ins. diam., bears N 59° E, 10 lks. dist., mkd. CS 1/16 S22 BT.</p> <p>A ponderosa pine, 9 ins. diam., bears N 47° W, 38 lks. dist., mkd. X BT.</p>
--------	---

BOOK 5295

Subdivision of Section 22,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. gray colored plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
38.65	U.S. Forest Service Route 151, graded, bears NE and SW.
39.85	The center 1/4 sec. cor. of sec. 22, established by Wilfred P. Hanson, L.S. 2473, in 1962 and monumented with an open end pipe, 28 ins. long, 1 1/2 ins. diam., firmly set flush with the ground, and is accepted as a careful and faithful determination of the position of the cor.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T23N R6E C 1/4 S22 1985
	from which
	A ponderosa pine, 12 ins. diam., bears N 26° E, 144 lks. dist., mkd. X BT.
	A ponderosa pine, 10 ins. diam., bears S 51 1/2° E, 173 lks. dist., mkd. C 1/4 S22 BT.
	Insert the open end pipe inside the stainless steel post and deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	From this cor., a U.S. Dept. of Agriculture Forest Service monument, an aluminum post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above ground, and in a collar of stone, with cap mkd. T23N R6E C 1/4 S22 RLS 11755 1983 set by Reid Penland, bears S 88° E, 1.7 lks. dist.
	N 1°27' E, beginning new measurement.
	Over rolling land, through pines.
4.965	A local monument, a rebar, 1/2 in. diam., projecting 3 ins. above ground, set by Reid Penland in 1983, bears E, 6 lks. dist.

65
BOOK 5295

Subdivision of Section 22
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
9.945	A local monument, a rebar, 1/2 in. diam., projecting 3 ins. above ground, set by Reid Penland in 1983, bears E, 2 lks. dist.
19.74	A local monument, a U.S. Dept. of Agriculture Forest Service monument, an aluminum post, 1 in. diam., loosely set in a mound of stone, 3 ft. base, 2 ft. high, with cap mkd. WC CN 1/16 S22 RLS 11755 1983 10.0 and an arrow, set by Reid Penland, bears E, 2 lks. dist.
19.87	Point for the center N 1/16 sec. cor. of sec. 22, at proportionate dist. Set an aluminum tablet, 3 ins. diam., 3 in. stem, cemented in rock outcropping, with top mkd. <div style="text-align: center;"> <p>T23N R6E</p> <p>C</p> <p>N 1/16 S 22</p> <p>C</p> <p>1985</p> </div> <p>from which</p> <p style="margin-left: 40px;">A limber pine, 10 ins. diam., bears N 19 3/4° E, 40 lks. dist., mkd. CN 1/16 S22 BT.</p> <p style="margin-left: 40px;">A limber pine, 14 ins. diam., bears N 79 3/4° E, 55 lks. dist., mkd. X BT.</p>
20.90	Draw, drains E.
29.805	The center N-N 1/64 sec. cor. of sec. 22, established by Wilfred P. Hanson, L.S. 2473, in 1962, monumented with a rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, in a collar of stone, and is accepted as a careful and faithful determination of the position of the cor. Cor. point not remonumented. <hr style="width: 30%; margin: 10px auto;"/> <p style="margin-left: 40px;">N 1°27' E, beginning new measurement.</p> <p style="margin-left: 40px;">Over rolling land, through pines.</p>
9.94	The 1/4 sec. cor. of secs. 15 and 22. <hr style="width: 80%; margin: 10px auto;"/> <p style="margin-left: 40px;">From the 1/4 sec. cor. of secs. 22 and 23.</p>

BOOK 5295

Subdivision of Section 22
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	N 89°37' W, on the E and W center line of sec. 22.
	Over gently rolling land, through pine, aspen, and fir.
19.355	Point for the center E 1/16 sec. cor. of sec. 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	10 ins. in the ground, and in a mound of stone, 4 ft. base, to
	top, with brass cap mkd.
	<p style="text-align: center;">T23N R6E E 1/16 C ————— C S 22 1985</p>
	from which
	A ponderosa pine, 10 ins. diam., bears N 63 3/4° E,
	49.5 lks. dist., mkd. CE 1/16 S22 BT.
	A limber pine, 8 ins. diam., bears S 58° E, 24 lks. dist.,
	mkd. CE 1/16 S22 BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic
	case beneath the stainless steel post.
	Set a steel fence post near the cor.
37.90	U.S. Forest Service Route 151, graded, bears NE and SW.
38.71	The center 1/4 sec. cor. of sec. 22.
	<hr style="width: 20%; margin: 0 auto;"/> <p>N 89°37' W, beginning new measurement.</p>
	Over gently rolling land, through pines.
9.90	A dirt road, bears NE and SW.
10.09	The center E-W 1/64 sec. cor. of sec. 22, established by Wilfred
	P. Hanson, L.S. 2473, in 1962, and monumented with an open end
	pipe, 1/2 in. diam., firmly set flush with the ground, with a
	rebar, 1/2 in. diam., projecting 2 ins. above ground, set by Reid
	Penland, in 1983, alongside, and is accepted as a careful and
	faithful determination of the position of the cor.

BOOK 5295

Subdivision of Section 22
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Cor. point not remonumented.</p> <hr/> <p>N 89°37' W, beginning new measurement.</p>
3.20	A dirt road, bears SE and NW.
5.05	A local monument, a rebar, 1/2 in. diam., projecting 2 ins. above ground, set by Joseph E. Costa, L.S. 9078.
10.10	<p>The center W 1/16 sec. cor. of sec. 22, established by Wilfred P. Hanson, L.S. 2473, in 1962, and monumented with an open end pipe, 16 ins. long, 1/2 in. diam., firmly set, projecting 1 in. above ground, with a rebar, 1/2 in. diam., projecting 3 ins. above ground, set by Joseph E. Costa, L.S. 9078, alongside, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T23N R6E W 1/16 C ——— C S 22 1987</p> </div> <p>from which</p> <p>A limber pine, 14 ins. diam., bears S 40° E, 68.5 lks. dist., mkd. CW 1/16 S22 BT.</p> <p>A ponderosa pine, 12 ins. diam., bears S 54° W, 10.5 lks. dist., mkd. CW 1/16 S22 BT.</p> <p>Insert the open end pipe inside the stainless steel post and deposit a magnet in a 1 x 1 x 2 5/8 in. grey colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>N 89°37' W, beginning new measurement.</p>

68
BOOK 5295

Subdivision of Section 22
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	Over rolling land, through pines; asc. over SE slope.
10.105	The center W-W 1/64 sec. cor. of sec. 22, established by Wilfred P. Hanson, L.S. 2473, in 1962, and monumented with an open end pipe, 1/2 in. diam., firmly set, projecting 3 ins. above ground, and in a mound of stone, 2 1/2 ft. base, 10 ins. high, and is accepted as a careful and faithful determination of the position of the cor. Cor. point not remonumented.
	<hr/> N 89°37' W, beginning new measurement.
10.105	The 1/4 sec. cor. of secs. 21 and 22. <hr/> NE 1/4 <hr/>
	From the center E 1/16 sec. cor. of sec. 22.
	N 2°35' E, on the N and S center line of the NE 1/4 of sec. 22.
	Over rolling land, through pine, fir, and aspen.
2.60	A dirt road, bears E and W.
19.65	U.S. Forest Service Route 151, graded, bears N 65° E and S 65° W.
19.875	Point for the NE 1/16 sec. cor. of sec. 22, at the intersection with the E and W center line of the NE 1/4 of sec. 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T23N R6E NE 1/16 S22 1985
	from which
	A Douglas fir, 6 ins. diam., bears N 66 3/4° W, 45.5 lks. dist., mkd. X BT.

BOOK 5295

Subdivision of Section 22
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A Douglas fir, 7 ins. diam., bears N 6 1/4° W, 49.5 lks. dist., mkd. NE 1/16 S22 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
20.56	Fence, bears E and W.
39.75	The E 1/16 sec. cor. of secs. 15 and 22.
	<hr/> <p>From the N 1/16 sec. cor. of secs. 22 and 23.</p> <p>N 89°35' W, on the E and W center line of the NE 1/4 of sec. 22.</p> <p>Over rolling land, through pine, fir, and aspen.</p>
19.255	<p>Point for a witness point on the E and W center line of the NE 1/4 of sec. 22, on the center of U.S. Forest Service Route 151, graded, bearing N 65° E and S 65° W.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below surface of road, with brass cap mkd.</p>
	<p style="text-align: center;">WP S22 1985</p>
	<p>from which</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 32 ins. in the ground, for a reference monument, bears S 81 1/2° E, 41.6 ft. dist., with cap mkd. RM 41.6 FT TO COR WP S22 1985, and an arrow pointing to the witness point.</p>
	<p>An aluminum post, 36 ins. long, 3/4 in. diam., set 32 ins. in the ground, for a reference monument, bears S 8 1/4° W, 23.0 ft. dist., with cap mkd. RM 23.0 FT TO COR WP S22 1985, and an arrow pointing to the witness point.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post near each reference monument.</p>

Subdivision of Section 22
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
19.745	The NE 1/16 sec. cor. of sec. 22.
38.40	A dirt road, bears NE and SW.
39.49	The center N 1/16 sec. cor. of sec. 22.
<hr/> <p>SE 1/4</p> <hr/>	
<p>From the E 1/16 sec. cor. of secs. 22 and 27.</p>	
<p>N 0°11' E, on the N and S center line of the SE 1/4 of sec. 22.</p>	
<p>Over gently rolling land, through pine and aspen.</p>	
0.75	A dirt road, bears E and W.
19.945	Point for the SE 1/16 sec. cor. of sec. 22, at the intersection with the E and W center line of the SE 1/4 of sec. 22.
<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>	
<p>T23N R6E SE 1/16 S22 1985</p>	
<p>from which</p>	
<p>A limber pine, 6 ins. diam., bears N 2° E, 22 lks. dist., mkd. SE 1/16 S22 BT.</p>	
<p>A ponderosa pine, 8 ins. diam., bears N 77 1/2° W, 25 lks. dist., mkd. SE 1/16 S22 BT.</p>	
<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. gray colored plastic case beneath the stainless steel post.</p>	
<p>Set a steel fence post near the cor.</p>	
39.89	The center E 1/16 sec. cor. of sec. 22.
<hr/> <p>From the S 1/16 sec. cor. of secs. 22 and 23.</p> <p>N 89°33' W, on the E and W center line of the SE 1/4 of sec. 22.</p>	

BOOK 5295

Subdivision of Section 22
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	Over gently rolling land, through pine and aspen.
19.80	The SE 1/16 sec. cor. of sec. 22.
29.70	Point for the center W-SE 1/64 sec. cor. of sec. 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	16 ins. in the ground, and in a mound of stone, 3 1/2 ft. base,
	to top, with brass cap mkd.
	S22
	C-W-SE
	1/64
	1985
	from which
	A ponderosa pine, 6 ins. diam., bears N 33 1/2° E,
	33.5 lks. dist., mkd. X BT.
	A ponderosa pine, 6 ins. diam., bears N 9° W, 30 lks. dist.,
	mkd. CWSE 1/64 S22 BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. gray colored plastic case
	beneath the stainless steel post.
	Set a steel fence post near the cor.
39.60	The center S 1/16 sec. cor. of sec. 22.
	From the E-W-E 1/256 sec. cor. of secs. 22 and 27.
	N 0°30' E, on the N and S center line of the SE 1/4 of the SW 1/4
	of the SE 1/4 of sec. 22.
	Over gently rolling land, through pine and aspen.
0.65	A dirt road, bears E and W.
9.97	Point for the center E-SW-SE 1/256 sec. cor. of sec. 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	24 ins. in the ground, with brass cap mkd.
	S22
	C-E-SW-SE
	1/256
	1985

BOOK 5295

Subdivision of Section 22
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A ponderosa pine, 8 ins. diam., bears N 12° E, 40 lks. dist., mkd. CESWSE 1/256 S22 BT.</p> <p>A ponderosa pine, 6 ins. diam., bears N 82 3/4° W, 28 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. gray colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>N 89°31.5' W, on the E and W center line of the SW 1/4 of the SE 1/4 of sec. 22.</p>
5.005	<p>Point for the SW-SE 1/64 sec. cor. of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S22 SW-SE 1/64 1985</p>
	<p>from which</p> <p>A ponderosa pine, 8 ins. diam., bears N 3° E, 24 lks. dist., mkd. X BT.</p> <p>A ponderosa pine, 14 ins. diam., bears N 72 3/4° E, 29 lks. dist., mkd. SWSE 1/64 S22 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. gray colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>N 0°49' E, on the N and S center line of the SW 1/4 of the SE 1/4 of sec. 22.</p>
9.967	<p>The center W-SE 1/64 sec. cor. of sec. 22.</p> <hr/> <p style="text-align: center;">SW 1/4</p> <hr/>

BOOK 5295

Subdivision of Section 22
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>From the W 1/16 sec. cor. of secs. 22 and 27.</p> <p>N 1°34' E, on the N and S center line of the SW 1/4 of sec. 22.</p> <p>Over rolling land, through scattered pines.</p>
9.95	<p>Point for the center S-SW 1/64 sec. cor. of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S22 C-S-SW 1/64 1985</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears N 57 3/4° W, 44 lks. dist., mkd. CSSW 1/64 S22 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears N 15° W, 82.5 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. gray colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
14.925	<p>Point for the center N-S-SW 1/256 sec. cor. of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S22 C-N-S-SW 1/256 1985</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N 68° E, 10 lks. dist., mkd. CNSSW 1/256 S22 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N 71 3/4° W, 140.5 lks. dist., mkd. X BT.</p>

74
BOOK 5295

Subdivision of Section 22
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. gray colored plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
18.00	A dirt road, bears N 75° E and S 75° W.
19.90	Point for the SW 1/16 sec. cor. of sec. 22, at the intersection with the E and W center line of the SW 1/4 of sec. 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T23N R6E SW 1/16 S22 1985
	from which
	A ponderosa pine, 12 ins. diam., bears N 30° E, 65 lks. dist., mkd. SW 1/16 S22 BT.
	A ponderosa pine, 12 ins. diam., bears S 71° E, 143 lks. dist., mkd. X BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. gray colored plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
39.80	The center W 1/16 sec. cor. of sec. 22.
	From the center S 1/16 sec. cor. of sec. 22.
	N 89°31.5' W, on the E and W center line of the SW 1/4 of sec. 22.
	Over rolling land, through pine and aspen.
12.60	U.S. Forest Service Route 151, graded, bears N and S.
20.23	The SW 1/16 sec. cor. of sec. 22.
24.70	A dirt road, bears SE and NW.
32.60	A dirt road, bears NE and SW.

BOOK 5295

Subdivision of Section 22
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
40.47	The S 1/16 sec. cor. of secs. 21 and 22.
	<hr/> From the E-E-W 1/256 sec. cor. of secs. 22 and 27. N 1°28.8' E, on the N and S center line of the E 1/2 of the SE 1/4 of the SW 1/4 of sec. 22. Over rolling land, through pine and aspen.
14.943	Point for the NE-SE-SW 1/256 sec. cor. of sec. 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <p>S22 NE-SE-SW 1/256 1985</p> </div>
	from which
	<div style="padding-left: 40px;"> <p>A limber pine, 6 ins. diam., bears N 30 1/2° E, 22.5 lks. dist., mkd. X BT.</p> <p>A ponderosa pine, 8 ins. diam., bears S 39 1/4° E, 18 lks. dist., mkd. NESESW 1/256 S22 BT.</p> </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. gray colored plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
	<hr/> N 89°30' W, on the E and W center line of the N 1/2 of the SE 1/4 of the SW 1/4 of sec. 22. Over rolling land, through pine and aspen.
7.315	Point for a witness point on the E and W center line of the N 1/2 of the SE 1/4 of the SW 1/4 of sec. 22, on the center of U.S. Forest Service Route 151, graded, bearing N and S.
	Set an aluminum post, 24 ins. long, 3/4 in. diam., 18 ins. below surface of road, with cap mkd.
	<div style="text-align: center;"> <p>WP S22 1985</p> </div>

BOOK 5295

Subdivision of Section 22

T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	from which
	<p>An aluminum post, 48 ins. long, 3/4 in. diam., set 44 ins. in the ground, for a reference monument, bears S 45° E, 36.4 ft. dist., with cap mkd. RM 36.4 FT TO COR WP S22 1985, and an arrow pointing to the witness point.</p>
	<p>An aluminum post, 36 ins. long, 3/4 in. diam., set 32 ins. in the ground, for a reference monument, bears S 44 3/4° W, 37.2 ft. dist., with cap mkd. RM 37.2 FT TO COR WP S22 1985, and an arrow pointing to the witness point.</p>
	Set a steel fence post near each reference monument.
15.18	The center N-S-SW 1/256 sec. cor. of sec. 22.
	From the center S-SW 1/64 sec. cor. of sec. 22.
	N 89°29' W, on the E and W center line of the SW 1/4 of the SW 1/4 of sec. 22.
	Over rolling land, through pine and aspen.
20.255	The S-S 1/64 sec. cor. of secs. 21 and 22.
	<p>Subdivision of Section 23, T 23 N, R 6 E, Gila and Salt River Mer., Arizona</p>
	From the 1/4 cor. of secs. 23 and 26.
	N 1°21.5' E, on the N and S center line of sec. 23.
	Over rolling land, through pine, aspen, and fir.
9.97	Point for the center S-S 1/64 sec. cor. of sec. 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>S23 C-S-S 1/64 1985</p>

77
BOOK 5295

Subdivision of Section 23,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	from which
	A limber pine, 12 ins. diam., bears N 19 3/4° E, 155 lks.
	dist., mkd. CSS 1/64 S23 BT.
	A ponderosa pine, 8 ins. diam., bears N 75° W, 116 lks.
	dist., mkd. CSS 1/64 S23 BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic
	case beneath the stainless steel post and raise a mound of stone,
	2 1/2 ft. base, 1 1/2 ft. high, W of cor.
	Set a steel fence post near the cor.
10.14	Fence, bears E and W.
19.94	Point for the center S 1/16 sec. cor. of sec. 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	24 ins. in the ground, with brass cap mkd.
	T23N R6E
	C
	S 1/16 S 23
	C
	1985
	from which
	A limber pine, 7 ins. diam., bears N 64 3/4° E, 40 lks.
	dist., mkd. CS 1/16 S23 BT.
	A Douglas fir, 6 ins. diam., bears N 33° W, 2 lks. dist.,
	mkd. CS 1/16 S23 BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic
	case beneath the stainless steel post.
	Set a steel fence post near the cor.
39.88	Point for the center 1/4 sec. cor. of sec. 23, at the
	intersection with the E and W center line of sec. 23.

78
BOOK 5295

Subdivision of Section 23,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T23N R6E C 1/4 S23 1985</p> <p>from which</p> <p style="padding-left: 40px;">A Douglas fir, 8 ins. diam., bears N 30 1/4° E, 23.5 lks. dist., mkd. C 1/4 S23 BT.</p> <p style="padding-left: 40px;">A limber pine, 6 ins. diam., bears S 66° E, 32.5 lks. dist., mkd. C 1/4 S23 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
47.80	A dirt road, bears E and W.
59.755	Point for the center N 1/16 sec. cor. of sec. 23.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23N R6E C N 1/16 S 23 C 1985</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S 7 3/4° E, 180.5 lks. dist., mkd. CN 1/16 S23 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears S 45 1/4° W, 205 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>

79
BOOK 5295

Subdivision of Section 23,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
79.63	<p>Set a steel fence post near the cor.</p> <p>The 1/4 sec. cor. of secs. 14 and 23.</p> <hr style="border: 0.5px solid black;"/> <p>From the 1/4 sec. cor. of secs. 23 and 24.</p> <p>S 89°49.5' W, on the E and W center line of sec. 23.</p> <p>Over gently rolling land, through pine, aspen, and fir.</p>
19.94	<p>Point for the center E 1/16 sec. cor. of sec. 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T23N R6E E 1/16 C ————— C S 23 1985</p> </div> <p>from which</p> <p style="margin-left: 40px;">A double limber pine, 26 ins. diam., bears S 56° W, 16.5 lks. dist., mkd. CE 1/16 S23 BT on SE trunk.</p> <p style="margin-left: 40px;">A ponderosa pine, 16 ins. diam., bears N 9 1/2° W, 155.5 lks. dist., mkd. CE 1/16 S23 BT.</p>
39.88	<p>The center 1/4 sec. cor. of sec. 23.</p>
60.655	<p>Point for the center W 1/16 sec. cor. of sec. 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T23N R6E W 1/16 C ————— C S23 1985</p> </div>

BOOK 5295

Subdivision of Section 23,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A ponderosa pine, 10 ins. diam., bears S 29 1/2° W, 63 lks. dist., mkd. CW 1/16 S23 BT.</p> <p>A Douglas fir, 10 ins. diam., bears S 67 1/2° W, 60 lks. dist., mkd. CW 1/16 S23 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
81.43	The 1/4 sec. cor. of secs. 22 and 23.
	<hr/> <p style="text-align: center;">SE 1/4</p> <hr/>
	<p>From the E 1/16 sec. cor. of secs. 23 and 26.</p> <p>N 1°21' E, on the N and S center line of the SE 1/4 of sec. 23.</p> <p>Over gently rolling land, through pine, aspen, and fir.</p>
19.905	<p>Point for the SE 1/16 sec. cor. of sec. 23, at the intersection with the E and W center line of the SE 1/4 of sec. 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23N R6E SE 1/16 S23 1985</p>
	<p>from which</p> <p>A ponderosa pine, 16 ins. diam., bears N 5° E, 75 lks. dist., mkd. SE 1/16 S23 BT.</p> <p>A ponderosa pine, 15 ins. diam., bears N 69° W, 59.5 lks. dist., mkd. X BT.</p>

BOOK 5295

Subdivision of Section 23,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
39.815	<p>The center E 1/16 sec. cor. of sec. 23.</p>
	<hr/> <p>From the S 1/16 sec. cor. of secs. 23 and 24.</p> <p>S 89°44' W, on the E and W center line of the SE 1/4 of sec. 23.</p> <p>Over gently rolling land, through pine, fir, and aspen.</p>
19.945	<p>The SE 1/16 sec. cor. of sec. 23.</p>
39.885	<p>The center S 1/16 sec. cor. of sec. 23.</p>
	<hr/> <p>From the W-E 1/64 sec. cor. of secs. 23 and 26.</p> <p>N 1°21.2' E, on the N and S center line of the SW 1/4 of the SE 1/4 of sec. 23.</p> <p>Over gently rolling land, through pines.</p>
9.963	<p>Point for the SW-SE 1/64 sec. cor. of sec. 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S23 SW-SE 1/64 1985</p>
	<p>from which</p>
	<p>A limber pine, 9 ins. diam., bears N 34° E, 68 lks. dist., mkd. X BT.</p>
	<p>A limber pine, 11 ins. diam., bears N 31° W, 37.5 lks. dist., mkd. SWSE 1/64 S23 BT.</p>

BOOK 5295

Subdivision of Section 23,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. blue colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this cor., an open end pipe of unknown origin, 1 in. diam., projecting 12 ins. above ground, bears N 73°19' W, 34.2 lks. dist. This pipe is located at fence cor., from which fences extend S and N 60° W, soon W.</p> <hr/> <p>S 89°41.5' W, on the E and W center line of the SW 1/4 of the SE 1/4 of sec. 23.</p> <p>Over gently rolling land, through pine, fir, and aspen.</p> <p>9.974 The center S-S 1/64 sec. cor. of sec. 23.</p> <hr/> <p style="text-align: center;">SW 1/4</p> <hr style="width: 20%; margin: auto;"/> <p>From the W 1/16 sec. cor. of secs. 23 and 26.</p> <p>N 0°08' E, on the N and S center line of the SW 1/4 of sec. 23.</p> <p>Over gently rolling land, through pine, fir, and aspen.</p> <p>9.98 Point for the center S-SW 1/64 sec. cor. of sec. 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S23 C-S-SW 1/64 1985</p> <p>from which</p> <p style="text-align: center;">A limber pine, 11 ins. diam., bears N 47 3/4° W, 51 lks. dist., mkd. CSSW 1/64 S23 BT.</p>
--------	---

BOOK 5295

Subdivision of Section 23,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 9 ins. diam., bears N 2 1/2° W, 37 lks. dist., mkd. CSSW 1/64 S23 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post near the cor.</p>
10.00	<p>Fence, bears E and W.</p>
19.96	<p>Point for the SW 1/16 sec. cor. of sec. 23, at the intersection with the E and W center line of the SW 1/4 of sec. 23.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T23N R6E SW 1/16 S23 1985</p>
	<p>from which</p>
	<p>A Douglas fir, 6 ins. diam., bears N 51 1/4° E, 13 lks. dist., mkd. X BT.</p>
	<p>A Douglas fir, 8 ins. diam., bears S 8 1/4° E, 59 lks. dist., mkd. SW 1/16 S23 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post near the cor.</p>
39.92	<p>The center W 1/16 sec. cor. of sec. 23.</p>
	<hr/> <p>From the center S 1/16 sec. cor. of sec. 23.</p>
	<p>S 89°46' W, on the E and W center line of the SW 1/4 of sec. 23.</p>
	<p>Over gently rolling land, through pine, fir, and aspen.</p>
20.35	<p>The SW 1/16 sec. cor. of sec. 23.</p>

BOOK 5295

Subdivision of Section 23,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
40.70	The S 1/16 sec. cor. of secs. 22 and 23.
	<hr/> From the center S-S 1/64 sec. cor. of sec. 23. S 89°44' W, on the E and W center line of the SE 1/4 of the SW 1/4 of sec. 23.
20.14	The center S-SW 1/64 sec. cor. of sec. 23.
	<hr/> S 89°44' W, on the E and W center line of the SW 1/4 of the SW 1/4 of sec. 23.
5.034	Point for the center E-SW-SW 1/256 sec. cor. of sec. 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> S23 CE-SW-SW 1/256 1985 </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post and raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N of cor.
	Set a steel fence post near the cor.
	The cor. is located 2 lks. N of fence, extending E and W, 20 lks. dist. to fence cor., from which fences extend E and N.
	<hr/> N 0°10.2' W, on the N and S center line of the NE 1/4 of the SW 1/4 of the SW 1/4 of sec. 23.
4.991	Point for the NE-SW-SW 1/256 sec. cor. of sec. 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.

BOOK 5295

Subdivision of Section 23,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	<p style="text-align: center;">S23 NE-SW-SW 1/256 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. blue colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this cor., fence cor. bears N 85 1/2° W, 26 lks. dist., from which fences extend S and W. An open end pipe, of unknown origin, 30 ins. long, 1 in. diam., was found nearby lying loose on the surface of the ground.</p> <hr/> <p>S 89°45' W, on the E and W center line of the NE 1/4 of the SW 1/4 of the SW 1/4 of sec. 23.</p> <p>5.061 Point for the center N-SW-SW 1/256 sec. cor. of sec. 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S23 C-N-SW-SW 1/256 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this cor., an open end pipe of unknown origin, 1 in. diam., projecting 9 ins. above ground, bears N 82°33' W, 17.4 lks. dist. This pipe is located 1.5 lks. NW of fence cor., from which fences extend E and S.</p> <hr/> <p>S 0°28.5' E, on the N and S center line of the SW 1/4 of the SW 1/4 of sec. 23.</p>
--------	--

BOOK 5295

Subdivision of Section 23,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
9.983	<p>Point for the center S-SW-SW 1/256 sec. cor. of sec. 23, falls in dirt road, on a curve, bearing S from NW, changing to W.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 8 ins. below surface of road, with cap mkd.</p> <p style="text-align: center;">S23 C-S-SW-SW 1/256 1985</p> <p>from which</p> <p style="padding-left: 40px;">An aluminum post, 36 ins. long, 3/4 in. diam., set 32 ins. in the ground, for a reference monument, bears N 88° W, 14.8 ft. dist., with cap mkd. RM C-S-SW-SW 1/256 S23 14.8 FT TO COR 1985, and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An aluminum post, 36 ins. long, 3/4 in. diam., set 32 ins. in the ground, for a reference monument, bears N 3 1/4° W, 33.1 ft. dist., with cap mkd. RM C-S-SW-SW 1/256 S23 33.1 FT TO COR 1985, and an arrow pointing to the cor.</p> <p>Set a steel fence post near each reference monument.</p> <p>From this cor., a capped pipe of unknown origin, 1 1/4 ins. diam., projecting 10 ins. above ground, bears S 56°30' W, 16.2 lks. dist.</p> <p>From this same cor., an open end pipe of unknown origin, bears W, 11 lks. dist. This pipe is bent over at cor. of fences, from which fences extend N, S, and W.</p>
	<hr/>
	<p>S 89°43' W, on the E and W center line of the SW 1/4 of the SW 1/4 of the SW 1/4 of sec. 23.</p>
10.016	<p>The S-S-S 1/256 sec. cor. of secs. 22 and 23.</p>
	<hr/>
	<p style="text-align: center;">NW 1/4</p> <hr/>

BOOK 5295

Subdivision of Section 23,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	From the center W 1/16 sec. cor. of sec. 23.
	N 2°31' E, on the N and S center line of the NW 1/4 of sec. 23.
	Over rolling land, through pine, fir, and aspen.
5.50	A dirt road, bears E and W.
19.87	Point for the NW 1/16 sec. cor. of sec. 23, at the intersection with the E and W center line of the NW 1/4 of sec. 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T23N R6E
	NW 1/16 S23
	1985
	from which
	A Douglas fir, 8 ins. diam., bears N 21 1/2° E, 48 lks. dist., mkd. NW 1/16 S23 BT.
	A Douglas fir, 12 ins. diam., bears N 68 1/2° W, 45 lks. dist., mkd. X BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
39.745	The W 1/16 sec. cor. of secs. 14 and 23.
	From the center N 1/16 sec. cor. of sec. 23.
	S 89°46' W, on the E and W center line of the NW 1/4 of sec. 23.
	Over rolling land, through pine, fir, and aspen.
20.365	The NW 1/16 sec. cor. of sec. 23.
40.735	The N 1/16 sec. cor. of secs. 22 and 23.

BOOK 5295

Subdivision of Section 27,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	From the 1/4 sec. cor. of secs. 27 and 34.
	N 0°05' W, on the N and S center line of sec. 27.
	Over nearly level meadow land.
9.90	Point for the center S-S 1/64 sec. cor. of sec. 27.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.
	S27
	C-S-S
	1/64
	1985
	Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W of cor.
	Set a steel fence post near the cor.
17.00	A creek, 10 lks. wide, course SW.
19.80	Point for the center S 1/16 sec. cor. of sec. 27.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.
	T23N R6E
	C
	S 1/16 S 27
	C
	1985
	Set a steel fence post near the cor.
	Asc. over gradual S slope, through ponderosa pine and aspen.
22.50	U.S. Forest Service Route 794, on curve, bears NE from SW.
23.30	Fence, bears E and W.
24.75	Point for the center S-N-S 1/256 sec. cor. of sec. 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

BOOK 5295

Subdivision of Section 27,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">S27 C-S-N-S 1/256 1985</p> <p>from which</p> <p>A ponderosa pine, 14 ins. diam., bears N 29 1/2° E, 76 lks. dist., mkd. X BT.</p> <p>A ponderosa pine, 16 ins. diam., bears N 61° W, 35 lks. dist., mkd. CSNS 1/256 S27 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
39.60	<p>Point for the center 1/4 sec. cor. of sec. 27, at the intersection with the E and W center line of sec. 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T23N R6E C 1/4 S27 1985</p> <p>from which</p> <p>A ponderosa pine, 16 ins. diam., bears S 48° E, 117 lks. dist., mkd. C 1/4 S27 BT.</p> <p>A ponderosa pine, 10 ins. diam., bears S 31° W, 94 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
56.00	<p>U.S. Forest Service Route 151, graded, bears S 10° E and N 10° W.</p>
59.41	<p>Point for the center N 1/16 sec. cor. of sec. 27.</p>

BOOK 5295

Subdivision of Section 27,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23N R6E C N 1/16 S 27 C 1985</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears N 23° E, 30.5 lks. dist., mkd. CN 1/16 S27 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N 87° E, 14.5 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
66.00	A dirt road, bears NE and SW.
79.22	The 1/4 sec. cor. of secs. 22 and 27.
	<hr/> <p>From the 1/4 sec. cor. of secs. 26 and 27.</p> <p>S 89°55' W, on the E and W center line of sec. 27.</p> <p>Over mountainous land; asc. over E slope.</p>
5.00	Top of ascent on Fern Mountain, slopes SE; desc. over SW slope.
20.18	Point for the center E 1/16 sec. cor. of sec. 27.
	<p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.</p>

BOOK 5295

Subdivision of Section 27,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T23N R6E E 1/16 C ——— C S 27 1985</p>
	<p>Set a steel fence post near the cor.</p>
	<p>Desc. over SW slope, changing to W.</p>
35.315	<p>Point for the center W-W-E 1/256 sec. cor. of sec. 27.</p>
	<p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.</p>
	<p style="text-align: center;">S27 C-W-W-E 1/256 1985</p>
	<p>from which</p>
	<p>A ponderosa pine, 12 ins. diam., bears S 38° E, 52.5 lks. dist., mkd. CWWE 1/256 S27 BT.</p>
	<p>A ponderosa pine, 6 ins. diam., bears S 48° W, 64.5 lks. dist., mkd. X BT.</p>
	<p>Set a steel fence post near the cor.</p>
	<p>Over gently rolling land, through pine and aspen.</p>
36.98	<p>Point for a witness point on the E and W center line of sec. 27, on the center of U.S. Forest Service Route 151, bearing N and S.</p>
	<p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 8 ins. below surface of road, with cap mkd.</p>
	<p style="text-align: center;">WP C ——— C S27 1985</p>

Subdivision of Section 27,
 T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 34 ins. in the ground, for a reference monument, bears S 41° E, 35.4 ft. dist., with cap mkd. RM 35.4 FT TO COR WP S27 1985, and an arrow pointing to the witness point.</p> <p>An aluminum post, 72 ins. long, 3/4 in. diam., set 66 ins. in the ground, for a reference monument, bears S 49 3/4° W, 45.4 ft. dist., with cap mkd. RM 45.4 FT TO COR WP S27 1985, and an arrow pointing to the witness point.</p>
40.36	The center 1/4 sec. cor. of sec. 27.
50.44	<p>Point for the center E-W 1/64 sec. cor. of sec. 27.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S27 C-E-W 1/64 1985</p>
	<p>from which</p> <p>A limber pine, 11 ins. diam., bears N 89 3/4° W, 27 lks. dist., mkd. CEW 1/64 S27 BT.</p> <p>A ponderosa pine, 9 ins. diam., bears N 11 1/2° W, 27 lks. dist., mkd. CEW 1/64 S27 BT.</p> <p>Set a steel fence post near the cor.</p>
60.52	<p>Point for the center W 1/16 sec. cor. of sec. 27.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T23N R6E W 1/16 C ——— C S27 1985</p>

BOOK 5295

Subdivision of Section 27,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p>
	<p>A limber pine, 13 ins. diam., bears S 81 3/4° E, 29 lks. dist., mkd. CW 1/16 S27 BT.</p>
	<p>A ponderosa pine, 10 ins. diam., bears N 12° W, 6 lks. dist., mkd. CW 1/16 S27 BT.</p>
	<p>Set a steel fence post near the cor.</p>
70.60	<p>Point for the center W-W 1/64 sec. cor. of sec. 27.</p>
	<p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.</p>
	<p style="text-align: center;">S27</p>
	<p style="text-align: center;">C-W-W</p>
	<p style="text-align: center;">1/64</p>
	<p style="text-align: center;">1985</p>
	<p>from which</p>
	<p>A ponderosa pine, 8 ins. diam., bears N 87 1/2° W, 68.5 lks. dist., mkd. X BT.</p>
	<p>A ponderosa pine, 12 ins. diam., bears N 15 1/4° W, 61.5 lks. dist., mkd. CWW 1/64 S27 BT.</p>
	<p>Set a steel fence post near the cor.</p>
80.68	<p>The 1/4 sec. cor. of secs. 27 and 28.</p>
	<hr/>
	<p style="text-align: center;">NE 1/4</p>
	<hr/>
	<p>From the center E 1/16 sec. cor. of sec. 27.</p>
	<p>N 0°02' E, on the N and S center line of the NE 1/4 of sec. 27.</p>
	<p>Over rolling land, asc. over SW slope.</p>
14.00	<p>Spur, slopes NW; desc. over N slope through pines.</p>

.. 94
BOOK 5295

Subdivision of Section 27,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
19.70	<p>Point for the NE 1/16 sec. cor. of sec. 27, at the intersection with the E and W center line of the NE 1/4 of sec. 27.</p> <p>Set an aluminum post, 72 ins. long, 3/4 in. diam., 66 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T23N R6E NE 1/16 S27 1985</p> <p>from which</p> <p style="padding-left: 40px;">A limber pine, 14 ins. diam., bears N 2° E, 34.5 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A limber pine, 11 ins. diam., bears N 79° W, 60.5 lks. dist., mkd. NE 1/16 S27 BT.</p> <p>Set a steel fence post near the cor.</p>
23.50	Bottom of descent, over gently rolling land.
39.40	The E 1/16 sec. cor. of secs. 22 and 27.
<hr/>	
From the N 1/16 sec. cor. of secs. 26 and 27.	
N 89°47.5' W, on the E and W center line of the NE 1/4 of sec. 27.	
Over gently rolling land, through pines and aspen.	
20.21	The NE 1/16 sec. cor. of sec. 27.
35.371	Point for the center W-W-NE 1/256 sec. cor. of sec. 27.
Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, with cap mkd.	

BOOK 5295

Subdivision of Section 27,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	S27 C-W-W-NE 1/256 1985
	from which A ponderosa pine, 12 ins. diam., bears S 86° E, 54.5 lks. dist., mkd. CWWNE 1/256 S27 BT. A ponderosa pine, 10 ins. diam., bears N 8 3/4° W, 32 lks. dist., mkd. X BT. Set a steel fence post near the cor.
40.425	The center N 1/16 sec. cor. of sec. 27.
	<hr/> From the center W-W-E 1/256 sec. cor. of sec. 27. N 0°03' W, on the N and S center line of the W 1/2 of the SW 1/4 of the NE 1/4 of sec. 27.
19.78	The center W-W-NE 1/256 sec. cor. of sec. 27.
	<hr/> SE 1/4 <hr/>
	From the E 1/16 sec. cor. of secs. 27 and 34. North, on the N and S center line of the SE 1/4 of sec. 27. Over nearly level land.
19.695	Point for the SE 1/16 sec. cor. of sec. 27, at the intersection with the E and W center line of the SE 1/4 of sec. 27. Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, with cap mkd.

96
BOOK 5295

Subdivision of Section 27,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>T23N R6E SE 1/16 S27 1985</p>
	Set a steel fence post near the cor.
22.50	Fence, bears E and W.
23.10	A creek, 10 lks. wide, course westerly.
24.20	U.S. Forest Service Route 151, graded, bears S 80° E and N 80° W; over rolling land, asc. over S slope, changing to SW.
24.615	Point for the center S-N-SE 1/256 sec. cor. of sec. 27. Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.
	<p>S27 C-S-N-SE 1/256 1985</p>
	Set a steel fence post near the cor.
39.375	The center E 1/16 sec. cor. of sec. 27.
	<hr/> <p>From the S 1/16 sec. cor. of secs. 26 and 27. S 89°36' W, on the E and W center line of the SE 1/4 of sec. 27. Over nearly level land.</p>
6.40	U.S. Forest Service Route 151, graded, bears SE and NW.
8.90	Fence, bears SE and NW.
10.08	Point for the center E-SE 1/64 sec. cor. of sec. 27. Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.

BOOK 5295

Subdivision of Section 27,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	S27 C-E-SE 1/64 1985
	Set a steel fence post near the cor.
20.16	The SE 1/16 sec. cor. of sec. 27.
40.10	A creek, 10 lks. wide, course S from NE.
40.31	The center S 1/16 sec. cor. of sec. 27.
	<hr/> From the center E-SE 1/64 sec. cor. of sec. 27. N 0°02' E, on the N and S center line of the NE 1/4 of the SE 1/4 of sec. 27.
2.55	Fence, bears S 80° E and N 80° W.
2.895	Point for a witness point on the N and S center line of the NE 1/4 of the SE 1/4 of sec. 27, on the center of U.S. Forest Service Route 151, bearing S 80° E and N 80° W.
	Set an aluminum post, 12 ins. long, 3/4 in. diam., 4 ins. below surface of road, with cap mkd.
	WP S27 1985
	from which
	An aluminum post, 36 ins. long, 3/4 in. diam., set 28 ins. in the ground, for a reference monument, bears N 37 1/2° E, 38.2 ft. dist., with cap mkd. RM 38.2 FT TO COR WP S27 1985, and an arrow pointing to the witness point.
	An aluminum post, 24 ins. long, 3/4 in. diam., set 20 ins. in the ground, for a reference monument, bears S 42 3/4° E, 45.7 ft. dist., with cap mkd. RM 45.7 FT TO COR WP S27 1985, and an arrow pointing to the witness point.

BOOK 5295

Subdivision of Section 27,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	Set a steel fence post near each reference monument.
4.00	A creek, 10 lks. wide, course W.
4.906	Point for the center S-NE-SE 1/256 sec. cor. of sec. 27.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.
	S27
	C-S-NE-SE
	1/256
	1985
	Raise a mound of stone, 3 1/2 ft. base, 3 ft. high, W of cor.
	Set a steel fence post near the cor.
	S 89°40.8' W, on the E and W center line of the SW 1/4 of the NE 1/4 of the SE 1/4 of sec. 27.
10.083	The center S-N-SE 1/256 sec. cor. of sec. 27.
	From the E-E 1/64 sec. cor. of secs. 27 and 34.
	N 0°02' E, on the N and S center line of the SE 1/4 of the SE 1/4 of sec. 27.
19.63	The center E-SE 1/64 sec. cor. of sec. 27.
	From the E-W-E 1/256 sec. cor. of sec. 27.
	N 0°01.2' W, on the N and S center line of the SE 1/4 of the SW 1/4 of the SE 1/4 of sec. 27.
9.859	Point for the center E-SW-SE 1/256 sec. cor. of sec. 27.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.

BOOK 5295

Subdivision of Section 27,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">S27 C-E-SW-SE 1/256 1985</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>S 89°26.5' W, on the E and W center line of the SW 1/4 of the SE 1/4 of sec. 27.</p>
15.101	<p>The center S-S 1/64 sec. cor. of sec. 27.</p> <hr/> <p>From the center S-N-SE 1/256 sec. cor. of sec. 27.</p> <p>S 89°41' W, on the E and W center line of the S 1/2 of the NW 1/4 of the SE 1/4 of sec. 27.</p>
2.941	<p>Point for a witness point on the E and W center line of the S 1/2 of the NW 1/4 of the SE 1/4 of sec. 27, on the center of U.S. Forest Service Route 151, bearing S 80° E and N 80° W.</p> <p>Set an aluminum post, 30 ins. long, 3/4 in. diam., 8 ins. below surface of road, with cap mkd.</p> <p style="text-align: center;">WP S27 1985</p> <p>from which</p> <p style="padding-left: 40px;">An aluminum post, 36 ins. long, 3/4 in. diam., set 30 ins. in the ground, for a reference monument, bears N 48° E, 30.9 ft. dist., with cap mkd. RM 30.9 FT TO COR WP S27 1985, and an arrow pointing to the witness point.</p> <p style="padding-left: 40px;">An aluminum post, 36 ins. long, 3/4 in. diam., set 30 ins. in the ground, for a reference monument, bears N 32° W, 32.9 ft. dist., with cap mkd. RM 32.9 FT TO COR WP S27 1985, and an arrow pointing to the witness point.</p>

100
BOOK 5295

Subdivision of Section 27,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	Set a steel fence post near each reference monument.
16.961	Point for a witness point on the E and W center line of the S 1/2 of the NW 1/4 of the SE 1/4 of sec. 27, on the center of U.S. Forest Service Route 794, bearing NE and SW.
	Set an aluminum post, 24 ins. long, 3/4 in. diam., 8 ins. below surface of road, with cap mkd.
	WP S27 1985
	from which
	An aluminum post, 36 ins. long, 3/4 in. diam., set 32 ins. in the ground, for a reference monument, bears N 63° E, 44.5 ft. dist., with cap mkd. RM 44.5 FT TO COR WP S27 1985, and an arrow pointing to the witness point.
	An aluminum post, 36 ins. long, 3/4 in. diam., set 32 ins. in the ground, for a reference monument, bears N 26° W, 44.8 ft. dist., with cap mkd. RM 44.8 FT TO COR WP S27 1985, and an arrow pointing to the witness point.
	Set a steel fence post near each reference monument.
19.70	A dirt road, bears SE and NW, curving northerly.
20.16	The center S-N-S 1/256 sec. cor. of sec. 27.
	SW 1/4
	From the W 1/16 sec. cor. of secs. 27 and 34.
	N 0°08' W, on the N and S center line of the SW 1/4 of sec. 27.
	Over gently rolling land, through ponderosa pine and aspen.
9.955	Point for the center S-SW 1/64 sec. cor. of sec. 27.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, with cap mkd.

101
BOOK 5295

Subdivision of Section 27,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">S27 C-S-SW 1/64 1985</p> <p>from which</p> <p>A ponderosa pine, 8 ins. diam., bears S 56° E, 54 lks. dist., mkd. X BT.</p> <p>A ponderosa pine, 10 ins. diam., bears S 40 1/2° W, 38.5 lks. dist., mkd. CSSW 1/64 S27 BT.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located approximately 125 lks. S 25° W of stock pond, 65 ft. diam., drains NW curving SW.</p>
15.30	U.S. Forest Service Route 794, unimproved, bears E and W.
19.91	<p>Point for the SW 1/16 sec. cor. of sec. 27, at the intersection with the E and W center line of the SW 1/4 of sec. 27.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, with cap mkd.</p>
	<p style="text-align: center;">T23N R6E SW 1/16 S27 1985</p>
23.60	Fence, bears irregularly E and W.
24.888	<p>Point for the center S-N-SW 1/256 sec. cor. of sec. 27.</p> <p>Set an aluminum post, 12 ins. long, 1 in. diam., in a drill hole in boulder, with cap mkd.</p>
	<p style="text-align: center;">S27 C-S-N-SW 1/256 1985</p>

BOOK 5295

Subdivision of Section 27,
T 23 N., R 6 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p>
	<p>A ponderosa pine, 6 ins. diam., bears N 33 1/2° E, 27 lks. dist., mkd. X BT.</p>
	<p>A ponderosa pine, 10 ins. diam., bears N 88° E, 49 lks. dist., mkd. CSNSW 1/256 S27 BT.</p>
	<p>Set a steel fence post near the cor.</p>
39.82	<p>The center W 1/16 sec. cor. of sec. 27.</p> <hr/>
	<p>From the center S 1/16 sec. cor. of sec. 27.</p>
	<p>S 89°35' W, on the E and W center line of the SW 1/4 of sec. 27.</p>
	<p>Over gently rolling land, through ponderosa pine and aspen.</p>
20.14	<p>The SW 1/16 sec. cor. of sec. 27.</p>
30.21	<p>Point for the center W-SW 1/64 sec. cor. of sec. 27.</p>
	<p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.</p>
	<p>S27</p>
	<p>C-W-SW</p>
	<p>1/64</p>
	<p>1985</p>
	<p>from which</p>
	<p>A ponderosa pine, 6 ins. diam., bears N 73° E, 8.5 lks. dist., mkd. CWSW 1/64 S27 BT.</p>
	<p>A ponderosa pine, 11 ins. diam., bears N 15 1/4° W, 55 lks. dist., mkd. X BT.</p>
	<p>Set a steel fence post near the cor.</p>
40.28	<p>The S 1/16 sec. cor. of secs. 27 and 28.</p> <hr/>

BOOK 5295

Subdivision of Section 27,
T 23 N., R 6 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>From the center S-N-S 1/256 sec. cor. of sec. 27.</p> <p>S 89°40' W, on the E and W center line of the S 1/2 of the NE 1/4 of the SW 1/4 of sec. 27.</p>
20.145	<p>The center S-N-SW 1/256 sec. cor. of sec. 27.</p> <hr/>
	<p>From the center S-S 1/64 sec. cor. of sec. 27.</p> <p>S 89°25.5' W, on the E and W center line of the SE 1/4 of the SW 1/4 of sec. 27.</p>
20.14	<p>The center S-SW 1/64 sec. cor. of sec. 27.</p> <hr/>
	<p>S 89°25.5' W, on the E and W center line of the SW 1/4 of the SW 1/4 of sec. 27.</p>
10.068	<p>Point for the SW-SW 1/64 sec. cor. of sec. 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">S27 SW-SW 1/64 1985</p>
	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S 47 1/4° E, 48 lks. dist., mkd. SWSW 1/64 S27 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears S 70 3/4° W, 86 lks. dist., mkd. X BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. purple colored plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post near the cor.</p> <hr/>
	<p>N 0°09' W, on the N and S center line of the SW 1/4 of the SW 1/4 of sec. 27.</p>

BOOK 5295

Subdivision of Section 27,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
2.18	<p>Point for a witness point on the N and S center line of the SW 1/4 of the SW 1/4 of sec. 27, on the center of U.S. Forest Service Route 794, bearing N 70° E and S 70° W.</p> <p>Set an aluminum post, 20 ins. long, 3/4 in. diam., flush with surface of road, with cap mkd.</p> <p style="text-align: center;">WP S27 1985</p> <p>from which</p> <p style="padding-left: 40px;">An aluminum post, 36 ins. long, 3/4 in. diam., set 28 ins. in the ground, for a reference monument, bears S 55° W, 47.2 ft. dist., with cap mkd. RM 47.2 FT TO COR WP S27 1985, and an arrow pointing to the witness point.</p> <p style="padding-left: 40px;">An aluminum post, 36 ins. long, 3/4 in. diam., set 28 ins. in the ground, for a reference monument, bears N 35° W, 38.7 ft. dist., with cap mkd. RM 38.7 FT TO COR WP S27 1985, and an arrow pointing to the witness point.</p> <p>Set a steel fence post near each reference monument.</p>
9.982	<p>The center W-SW 1/64 sec. cor. of sec. 27.</p> <hr/> <p>N 0°09' W, on the N and S center line of the NW 1/4 of the SW 1/4 of sec. 27.</p>
2.60	<p>Fence, bears E and W.</p>
19.965	<p>The center W-W 1/64 sec. cor. of sec. 27.</p> <hr/> <p style="text-align: center;">NW 1/4</p> <hr/> <p>From the center W 1/16 sec. cor. of sec. 27.</p> <p>N 0°13' W, on the N and S center line of the NW 1/4 of sec. 27.</p>

.. 105
BOOK 5295

Subdivision of Section 27,
T 23 N., R 6 E., Gila and Salt River Mer., Arizona

CHAINS	
9.965	<p>Over gently rolling land, through ponderosa pine and aspen.</p> <p>Point for the center S-NW 1/64 sec. cor. of sec. 27.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S27 C-S-NW 1/64 1985</p>
	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S 81° E, 46 lks. dist., mkd. CSNW 1/64 S27 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S 18° E, 35.5 lks. dist., mkd. X BT.</p> <p>Set a steel fence post near the cor.</p>
19.93	<p>Point for the NW 1/16 sec. cor. of sec. 27, at the intersection with the E and W center line of the NW 1/4 of sec. 27.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T23N R6E NW 1/16 S27 1985</p>
39.855	<p>Set a steel fence post near the cor.</p> <p>The W 1/16 sec. cor. of secs. 22 and 27.</p> <hr/> <p>From the center N 1/16 sec. cor. of sec. 27.</p> <p>N 89°46' W, on the E and W center line of the NW 1/4 of sec. 27.</p>

106
BOOK 5295

Subdivision of Section 27,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	Over gently rolling land, through ponderosa pine and aspen.
0.50	U.S. Forest Service Route 151, graded, bears S 10° E and N 10° W.
20.215	The NW 1/16 sec. cor. of sec. 27.
25.267	Point for the center E-W-NW 1/256 sec. cor. of sec. 27.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.
	S27
	C-E-W-NW
	1/256
	1985
	from which
	A ponderosa pine, 26 ins. diam., bears S 80° W, 5 lks. dist., mkd. CEWNW 1/256 S27 BT.
	A ponderosa pine, 12 ins. diam., bears N 25 1/4° W, 116 lks. 116 lks. dist., mkd. X BT.
	Set a steel fence post near the cor.
40.425	The N 1/16 sec. cor. of secs. 27 and 28.
	From the center E-W 1/64 sec. cor. of sec. 27.
	N 0°09' W, on the N and S center line of the SE 1/4 of the NW 1/4 of sec. 27.
9.936	Point for the SE-NW 1/64 sec. cor. of sec. 27.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.
	S27
	SE-NW
	1/64
	1985

107
BOOK 5295

Subdivision of Section 27,
T 23 N., R 6 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A ponderosa pine, 6 ins. diam., bears S 41 1/4° W, 15 lks. dist., mkd. SENW 1/64 S27 BT.</p> <p>Set a steel fence post near the cor.</p> <hr/>
10.093	<p>N 89°55.5' W, on the E and W center line of the SE 1/4 of the NW 1/4 of sec. 27.</p> <p>The center S-NW 1/64 sec. cor. of sec. 27.</p> <hr/>
5.046	<p>N 89°55.5' W, on the E and W center line of the SW 1/4 of the NW 1/4 of sec. 27.</p> <p>Point for the center E-SW-NW 1/256 sec. cor. of sec. 27.</p> <p>Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">S27 C-E-SW-NW 1/256 1985</p>
	<p>from which</p> <p>A ponderosa pine, 12 ins. diam., bears S 55 3/4° E, 167.5 lks. dist., mkd. X BT.</p> <p>A ponderosa pine, 14 ins. diam., bears S 21 1/4° W, 18.5 lks. dist., mkd. CESWNW 1/256 S27 BT.</p> <hr/>
9.978	<p>N 0°15' W, on the N and S center line of the NE 1/4 of the SW 1/4 of the NW 1/4 of sec. 27.</p> <p>The center E-W-NW 1/256 sec. cor. of sec. 27.</p> <hr/>
4.988	<p>N 0°15' W, on the N and S center line of the SE 1/4 of the NW 1/4 of the NW 1/4 of sec. 27.</p> <p>Point for the SE-NW-NW 1/256 sec. cor. of sec. 27.</p>

BOOK 5295

Subdivision of Section 27,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 12 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with cap mkd.</p> <p style="text-align: center;">S27 SE-NW-NW 1/256 1985</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S 16 1/4° W, 210 lks. dist., mkd. SENWNW 1/256 S27 BT.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>N 89°41' W, on the E and W center line of the S 1/2 of the NW 1/4 of the NW 1/4 of sec. 27.</p>
15.168	<p>The S-N-N 1/256 sec. cor. of secs. 27 and 28.</p> <hr/>
	<p style="text-align: center;">Subdivision of Section 34, T 23 N, R 6 E, Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 34, on the S bdy. of the Tp.</p> <p>N 0°04' E, on the N and S center line of sec. 34.</p> <p>Over nearly level, rolling land.</p>
40.43	<p>The center 1/4 sec. cor. of sec. 34, established by Wilfred P. Hanson, L.S. 2473, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, projecting 2 ins. above ground and in a collar of stone, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

109
BOOK 5295

Subdivision of Section 34,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	T23N R6E C 1/4 S34 1985
	Insert the rebar inside the stainless steel post and deposit a magnet in a 1 x 1 x 2 5/8 in. orange colored plastic case beneath the stainless steel post.
	set a steel fence post near the cor.
	Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W of cor.
	The cor. is located on top of ascent, sloping W.
	<hr/> N 0°04' E, beginning new measurement.
	Desc. over N slope.
0.27	Fence, bears E and W.
19.97	A local monument, a rebar, 1/2 in. diam., projecting 2 ins. above ground, established by Wilfred P. Hanson, L.S. 2473. This monument is located in fence extending E and W, 130 lks. dist. to fence cor., from which fences extend N, E, and S.
29.955	A local monument, a rebar, 1/2 in. diam., projecting 1 in. above ground, established by Donald L. Ziembra, L.S. 16218. This monument is located 67 lks. E of fence extending N and S.
39.94	The 1/4 sec. cor. of secs. 27 and 34.
	<hr/> From the 1/4 sec. cor. of secs. 34 and 35.
	N 89°28' W, on the E and W center line of sec. 34.
	Over rolling land, line follows near fence extending W.
10.20	A local monument, a rebar, 1/2 in. diam., projecting 1 in. above ground, established by Wilfred P. Hanson, L.S. 2473 bears N, 1 lk. dist. This monument is located 2 lks. S 45° W of fence cor., from which fences extend N, E, and W.

BOOK 5295

Subdivision of Section 34,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
30.01	A local monument, a rebar, 1/2 in. diam., projecting 2 ins. above ground, established by Wilfred P. Hanson, L.S. 2473. This monument is located 1 lk. W of fence extending N and S, 69 lks. to fence cor., from which fences extend N, E, and W.
40.02	The center 1/4 sec. cor. of sec. 34.
	N 89°28' W, beginning new measurement.
	Desc. over W slope, changing to SW, through scattering pine.
2.60	Fence, bears N and S.
40.29	The 1/4 sec. cor. of secs. 33 and 34.
	Subdivision of Section 35, T 23 N, R 6 E, Gila and Salt River Mer., Arizona
	From the 1/4 sec. cor. of secs. 2 and 35, on the S bdy. of the Tp.
	N 0°02' E, on the N and S center line of sec. 35.
	Over land sloping generally W, through scattering pine.
17.90	Small draw, drains W.
19.94	Point for the center S 1/16 sec. cor. of sec. 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T23N R6E C S 1/16 S 35 C 1985

111
BOOK 5295

Subdivision of Section 35,
T 23 N., R 6 E., Gila and Salt River Mer., Arizona

CHAINS	<p>from which</p> <p>A ponderosa pine, 11 ins. diam., bears S 49 3/4° E, 61 lks. dist., mkd. CS 1/16 S35 BT.</p> <p>A ponderosa pine, 9 ins. diam., bears S 12 1/2° E, 95 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>39.88 The center 1/4 sec. cor. of sec. 35, established by Wilfred P. Hanson, L.S. 2473, in 1969, monumented with a rebar, 16 ins. long, 5/8 in. diam., firmly set 2 ins. below surface of ground, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23N R6E C 1/4 S35 1985</p> <p>from which</p> <p>A ponderosa pine, 22 ins. diam., bears S 59° E, 77 lks. dist., mkd. C 1/4 S35 BT.</p> <p>A ponderosa pine, 6 ins. diam., bears S 63 1/4° W, 70 lks. dist., mkd. X BT.</p> <p>Insert the rebar inside the stainless steel post and deposit a magnet in a 1 x 1 x 2 5/8 in. orange colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>
--------	---

.. 112
BOOK 5295

Subdivision of Section 35,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	N 0°02' E, beginning new measurement.
9.655	A local monument, a rebar, 1/2 in. diam., projecting 3 ins. above ground, established by Wilfred P. Hanson, L.S. 2473.
10.565	A local monument, a rebar, 1/2 in. diam., flush with the ground, established by Wilfred P. Hanson, L.S. 2473.
20.22	The center N 1/16 sec. cor. of sec. 35, established by Wilfred P. Hanson, L.S. 2473, in 1969, monumented with a rebar, 16 ins. long, 1/2 in. diam., firmly set, projecting 2 ins. above ground, and is accepted as a careful and faithful determination of the position of the cor. At the cor. point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T23N R6E C N 1/16 S 35 C 1985 from which A ponderosa pine, 8 ins. diam., bears N 61 1/2° E, 87.5 lks. dist., mkd. CN 1/16 S35 BT. Insert the rebar inside the stainless steel post and deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post. Set a steel fence post near the cor. _____
	N 0°02' E, beginning new measurement.
	Continue on the N and S center line, along a bdy. of Snow Bowl Estates.
10.105	The center N-N 1/64 sec. cor. of sec. 35, established by Wilfred P. Hanson, L.S. 2473, in 1969, monumented with a rebar, 14 ins. long, 1/2 in. diam., firmly set, projecting 1 in. above ground, and is accepted as a careful and faithful determination of the position of the cor.

BOOK 5295

Subdivision of Section 35,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	S35
	C-N-N
	1/64
	1985
	from which
	A ponderosa pine, 14 ins. diam., bears N 34 1/2° E, 141.5 lks. dist., mkd. X BT.
	A ponderosa pine, 18 ins. diam., bears N 34 1/4° W, 98.5 lks. dist., mkd. CNN 1/64 S35 BT.
	Insert the rebar inside the stainless steel post and deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
	From this cor., an open end pipe of unknown origin, 1 in. diam., projecting 10 ins. above ground, bears S 0°30' W, 15.4 lks. dist.
	N 0°02' E, beginning new measurement.
	Continue on the N and S center line of sec. 35.
10.115	The 1/4 sec. cor. of secs. 26 and 35.
	From the 1/4 sec. cor. of secs. 35 and 36.
	N 89°44' W, on the E and W center line of sec. 35.
	Over rolling land, sloping generally W, through ponderosa pine.
15.05	The center W-E-E 1/256 sec. cor. of sec. 35, established by Wilfred P. Hanson, L.S. 2473, in 1969, monumented with a rebar, 16 ins. long, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with an open end pipe of unknown origin, 3/4 in. diam., projecting 1 in. above ground alongside, and is accepted as a careful and faithful determination of the position of the cor.

BOOK 5295

Subdivision of Section 35,
T 23 N. R 6 E. Gila and Salt River Mer., Arizona

CHAINS

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
26 ins. in the ground, with brass cap mkd.

S35
C-W-E-E
1/256
1985

from which

A ponderosa pine, 14 ins. diam., bears S 60 1/2° E,
219 lks. dist., mkd. X BT.

A ponderosa pine, 16 ins. diam., bears S 28° W, 30 lks.
dist., mkd. CWEE 1/256 S35 BT.

Insert the rebar inside the stainless steel post and deposit a
magnet in a 1 x 1 x 2 5/8 in. orange colored plastic case beneath
the stainless steel post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

Set a steel fence post near the cor.

From this cor., an open end pipe of unknown origin, 1 3/4 ins.
diam., projecting 1 in. above ground, bears S 89° W, 30.5 lks.
dist.

N 89°44' W, beginning new measurement.

Continue on the E and W center line, along the S bdy. of Snow
Bowl Estates.

5.015 The center E 1/16 sec. cor. of sec. 35, established by Wilfred P.
Hanson, L.S. 2473, in 1969?, monumented with a rebar, 16 ins.
long, 1/2 in. diam., firmly set, projecting 4 ins. above ground,
and is accepted as a careful and faithful determination of the
position of the cor.

BOOK 5295

Subdivision of Section 35,
T 23 N., R 6 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23N R6E E 1/16 C ————— C S 35 1987</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 17 ins. diam., bears S 1° W, 80.5 lks. dist., mkd. CE 1/16 S35 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 17 ins. diam., bears S 31 3/4° W, 165.5 lks. dist., mkd. X BT.</p> <p>Insert the rebar inside the stainless steel post and deposit a magnet in a 1 x 1 x 2 5/8 in. blue colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N 89°44' W, beginning new measurement.</p> <p>Continue on the E and W center line, along the S bdy. of Snow Bowl Estates.</p> <p>5.015 A local monument, a rebar, 1/2 in. diam., projecting 1 in. above ground, established by Wilfred P. Hanson, L.S. 2473.</p> <p>10.03 A local monument, a rebar, 1/2 in. diam., projecting 2 ins. above ground, established by Wilfred P. Hanson, L.S. 2473.</p> <p>15.05 A local monument, a rebar, 1/2 in. diam., projecting 2 ins. above ground, established by Wilfred P. Hanson, L.S. 2473.</p> <p>20.065 The center 1/4 sec. cor. of sec. 35.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N 89°44' W, beginning new measurement.</p>

BOOK 5295

Subdivision of Section 35,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	Continue on the E and W center line, along the S bdy. of Snow Bowl Estates.
4.995	A local monument, a rebar, 1/2 in. diam., projecting 1 in. above ground, established by Wilfred P. Hanson, L.S. 2473.
9.985	A local monument, a rebar, 1/2 in. diam., projecting 1 in. above ground, established by Wilfred P. Hanson, L.S. 2473.
14.955	A local monument, a rebar, 1/2 in. diam., projecting 2 in. above ground, established by Wilfred P. Hanson, L.S. 2473.
19.94	The center W 1/16 sec. cor. of sec. 35, established by Wilfred P. Hanson, L.S. 2473, monumented with a rebar, 16 ins. long, 1/2 in. diam., firmly set, projecting 1 in. above ground, and is accepted as a careful and faithful determination of the position of the cor.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T23N R6E W 1/16 C ————— C S 35 1987
	from which
	A ponderosa pine, 17 ins. diam., bears S 44° E, 50 lks. dist., mkd. X BT.
	A double ponderosa pine, 13 ins. diam. sly. trunk, bears S 20 1/2° W, 47.5 lks. dist., mkd. CW 1/16 S35 BT.
	Insert the rebar inside the stainless steel post and deposit a magnet in a 1 x 1 x 2 5/8 in. gray colored plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.

BOOK 5295

Subdivision of Section 35,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	<p>N 89°44' W, beginning new measurement.</p> <p>Continue on the E and W center line, along the S bdy. of Snow Bowl Estates.</p> <p>10.00 The center W-W 1/64 sec. cor. of sec. 35, established by Wilfred P. Hanson, L.S. 2473, in 1969, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, projecting 1 in. above ground, with an open end pipe of unknown origin, 3/4 in. diam., projecting 1 in. above ground alongside, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S35 C-W-W 1/64 1985</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears S 65 1/2° E, 95 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears S 23° W, 66 lks. dist., mkd. CWW 1/64 S35 BT.</p> <p>Insert the rebar inside the stainless steel post and deposit a magnet in a 1 x 1 x 2 5/8 in. orange colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this cor., an open end pipe of unknown origin, 1 1/2 ins. diam., loosely set, projecting 10 ins. above ground, bears N 89° W, 15 lks. dist.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N 89°44' W, beginning new measurement.</p>
--------	---

BOOK 5295

Subdivision of Section 35,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	Continue on the E and W center line of sec. 35.
9.15	U.S. Forest Service Route 151, graded, bears N and S.
9.975	The 1/4 sec. cor. of secs. 34 and 35.
	<hr/> <p style="text-align: center;">NE 1/4</p> <hr/>
	From the center E 1/16 sec. cor. of sec. 35.
	N 0°17' W, on the N and S center line of the NE 1/4 of sec. 35.
20.11	The NE 1/16 sec. cor. of sec. 35, established by Wilfred P. Hanson, L.S. 2473, in 1969, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, projecting 6 ins. above ground, and is accepted as a careful and faithful determination of the position of the cor.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T23N R6E NE 1/16 S35 1985</p>
	from which
	A ponderosa pine, 8 ins. diam., bears N 80 3/4° W, 83 lks. dist., mkd. NE 1/16 S35 BT.
	A ponderosa pine, 6 ins. diam., bears N 41 3/4° W, 78 lks. dist., mkd. X BT.
	Insert the rebar inside the stainless steel post and deposit a magnet in a 1 x 1 x 2 5/8 in. orange colored plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
	<hr/>

119
BOOK 5295

Subdivision of Section 35,
T 23 N., R 6 E., Gila and Salt River Mer., Arizona

CHAINS	
	N 0°18' W, beginning new measurement.
20.11	The E 1/16 sec. cor. of secs. 26 and 35.
	<hr/> From the N 1/16 sec. cor. of secs. 35 and 36.
	N 89°24' W, on the E and W center line of the NE 1/4 of sec. 35.
2.30	Small draw, drains NW.
14.96	The center W-E-NE 1/256 sec. cor. of sec. 35, established by Wilfred P. Hanson, L.S. 2473, in 1969, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, projecting 1 in. above ground, with an open end pipe of unknown origin, 3/4 in. diam., projecting 1 in. above ground alongside, and is accepted as a careful and faithful determination of the position of the cor.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	S35 C-W-E-NE 1/256 1985
	from which
	A limber pine, 8 ins. diam., bears S 81° E, 119 lks. dist., mkd. CWENE 1/256 S35 BT.
	A ponderosa pine, 19 ins. diam., bears S 19° E, 58 lks. dist., mkd. X BT.
	Insert the rebar inside the stainless steel post and deposit a magnet in a 1 x 1 x 2 5/8 in. orange colored plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
	<hr/>

BOOK 5295

Subdivision of Section 35,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	N 89°25' W, beginning new measurement.
	Continue on the E and W center line of the NE 1/4, along a bdy. of Snow Bowl Estates.
4.985	The NE 1/16 sec. cor. of sec. 35.
	<hr/>
	N 89°25' W, beginning new measurement.
	Continue on the E and W center line of the NE 1/4, along a bdy. of Snow Bowl Estates.
5.00	A local monument, a rebar, 1/2 in. diam., projecting 2 ins. above ground, established by Wilfred P. Hanson, L.S. 2473.
9.975	A local monument, a rebar, 1/2 in. diam., projecting 2 ins. above ground, established by Wilfred P. Hanson, L.S. 2473.
14.965	A local monument, a rebar, 1/2 in. diam., projecting 2 ins. above ground, established by Wilfred P. Hanson, L.S. 2473.
19.955	The center N 1/16 sec. cor. of sec. 35.
	<hr/>
	From the center W-E-E 1/256 sec. cor. of sec. 35.
	N 0°22' W, on the N and S center line of the W 1/2 of the SE 1/4 of the NE 1/4 of sec. 35, along the E bdy. of Snow Bowl Estates.
9.585	A local monument, a rebar, 1/2 in. diam., projecting 1 ins. above ground, established by Wilfred P. Hanson, L.S. 2473.
10.495	A local monument, a rebar, 1/2 in. diam., projecting 2 ins. above ground, established by Wilfred P. Hanson, L.S. 2473.
20.085	The center W-E-NE 1/256 sec. cor. of sec. 35.
	<hr/>
	SE 1/4
	<hr/>

BOOK 5295

Subdivision of Section 35,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	From the E 1/16 sec. cor. of secs. 2 and 35, on the S bdy. of the Tp.
	N 0°14' E, on the N and S center line of the SE 1/4 of sec. 35.
18.00	Small draw, drains W.
19.91	Point for the SE 1/16 sec. cor. of sec. 35, at the intersection with the E and W center line of the SE 1/4 of sec. 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T23N R6E SE 1/16 S35 1985
	from which
	A ponderosa pine, 18 ins. diam., bears N 51 1/4° E, 147 lks. dist., mkd. SE 1/16 S35 BT.
	A ponderosa pine, 12 ins. diam., bears N 35 1/2° W, 105.5 lks. dist., mkd. X BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
39.82	The center E 1/16 sec. cor. of sec. 35.
	From the S 1/16 sec. cor. of secs. 35 and 36.
	N 89°48' W, on the E and W center line of the SE 1/4 of sec. 35.
10.00	Small draw, drains S 70° W.
19.995	The SE 1/16 sec. cor. of sec. 35.

BOOK 5295

Subdivision of Section 35,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
39.99	The center S 1/16 sec. cor. of sec. 35.
	<hr/> <p style="text-align: center;">SW 1/4</p> <hr/>
	From the W 1/16 sec. cor. of secs. 2 and 35, on the S bdy. of the Tp.
	N 0°01' W, on the N and S center line of the SW 1/4 of sec. 35.
14.50	Small draw, drains W.
19.97	Point for the SW 1/16 sec. cor. of sec. 35, at the intersection with the E and W center line of the SW 1/4 of sec. 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T23N R6E SW 1/16 S35 1985</p>
	from which
	A ponderosa pine, 18 ins. diam., bears N 54° E, 94 lks. dist., mkd. X BT.
	A ponderosa pine, 16 ins. diam., bears N 40 1/4° W, 89.5 lks. dist., mkd. SW 1/16 S35 BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
39.94	The center W 1/16 sec. cor. of sec. 35.
	<hr/> <p>From the center S 1/16 sec. cor. of sec. 35.</p>
	N 89°50' W, on the E and W center line of the SW 1/4 of sec. 35.

BOOK 5295

Subdivision of Section 35,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
9.70	Spring, bears N, 15 lks. dist.
19.93	The SW 1/16 sec. cor. of sec. 35.
39.875	The S 1/16 sec. cor. of secs. 34 and 35.
<hr/> NW 1/4 <hr/>	
	From the center W 1/16 sec. cor. of sec. 35.
	N 0°09' E, on the N and S center line of the NW 1/4 of sec. 35.
20.325	The NW 1/16 sec. cor. of sec. 35, established by Kenneth Krenke, L.S. 14671, monumented with a rebar, 30 ins. long, 1/2 in. diam., firmly set flush with the ground, with aluminum cap mkd. L.S. 14671, with a steel fence post nearby, and is accepted as a careful and faithful determination of the position of the cor.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
T23N R6E NW 1/16 S35 1985	
	Insert the rebar inside the stainless steel post and deposit a magnet in a 1 x 1 x 2 5/8 in. blue colored plastic case beneath the stainless steel post.
<hr/>	
	N 0°13' E, beginning new measurement.
10.15	The center N-NW 1/64 sec. cor. of sec. 35, established by Kenneth Krenke, L.S. 14671, monumented with a rebar, 24 ins. long, 1/2 in. diam., firmly set flush with the ground, with aluminum cap mkd. L.S. 14671, and is accepted as a careful and faithful determination of the position of the cor.

BOOK 5295

Subdivision of Section 35,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S35 C-N-NW 1/64 1985</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears N 2 3/4° E, 95.5 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears N 36 1/2° W, 144.5 lks. dist., mkd. CNNW 1/64 S35 BT.</p> <p>Insert the rebar inside the stainless steel post and deposit a magnet in a 1 x 1 x 2 5/8 in. purple colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N 0°14' E, beginning new measurement.</p>
10.165	<p>The W 1/16 sec. cor. of secs. 26 and 35.</p> <hr/> <p>From the center N 1/16 sec. cor. of sec. 35.</p> <p>N 89°26' W, on the E and W center line of the NW 1/4 of sec. 35.</p>
4.98	<p>A local monument, a rebar, 1/2 in. diam., projecting 2 ins. above ground, established by Wilfred P Hanson, L.S. 2473.</p>
9.955	<p>A local monument, a rebar, 1/2 in. diam., projecting 4 ins. above ground, established by Wilfred P Hanson, L.S. 2473.</p>
19.895	<p>The NW 1/16 sec. cor. of sec. 35.</p> <hr/>

BOOK 5295

Subdivision of Section 35,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	<p>N 89°28' W, beginning new measurement.</p> <p>9.94 The center W-NW 1/64 sec. cor. of sec. 35, established by Kenneth Krenke, L.S. 14671, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with aluminum cap mkd. L.S. 14671, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S35 C-W-NW 1/64 1985</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S 35 1/4° W, 130.5 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N 46 1/2° W, 101 lks. dist., mkd. CWNW 1/64 S35 BT.</p> <p>Insert the rebar inside the stainless steel post and deposit a magnet in a 1 x 1 x 2 5/8 in. blue colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 89°27' W, beginning new measurement.</p> <p>8.90 U.S. Forest Service Route 151, graded, bears N and S.</p> <p>9.945 The N 1/16 sec. cor. of secs. 34 and 35.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the center N-N 1/64 sec. cor. of sec. 35.</p>
--------	---

BOOK 5295

Subdivision of Section 35,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS	
	N 89°18' W, on the E and W center line of the NE 1/4 of the NW 1/4 of sec. 35, along the N bdy. of Snow Bowl Estates.
19.86	The center N-NW 1/64 sec. cor. of sec. 35.
	From the center W-W 1/64 sec. cor. of sec. 35.
	N 0°19' E, on the N and S center line of the SW 1/4 of the NW 1/4 of sec. 35. along the W bdy. of Snow Bowl Estates.
9.74	A local monument, a rebar, 1/2 in. diam., projecting 1 ins. above ground, established by Wilfred P Hanson, L.S. 2473.
10.65	A local monument, a rebar, 1/2 in. diam., projecting 1 ins. above ground, established by Wilfred P Hanson, L.S. 2473.
20.37	The center W-NW 1/64 sec. cor. of sec. 35.
	N 0°19' E, on the N and S center line of the NW 1/4 of the NW 1/4 of sec. 35. along the W bdy. of Snow Bowl Estates.
10.18	The NW-NW 1/64 sec. cor. of sec. 35, established by Wilfred P. Hanson, L.S. 2473, in 1969, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, projecting 2 ins. above ground, and is accepted as a careful and faithful determination of the position of the cor.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">S35 NW-NW 1/64 1985</p>

BOOK 5295

Subdivision of Section 35,
T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS

from which

A ponderosa pine, 18 ins. diam., bears S 82° W, 61 lks.
dist., mkd. NWNW 1/64 S35 BT.

A ponderosa pine, 8 ins. diam., bears N 16 3/4° W,
170.5 lks. dist., mkd. X BT.

Insert the rebar inside the stainless steel post and deposit a
magnet in a 1 x 1 x 2 5/8 in. orange colored plastic case beneath
the stainless steel post.

Set a steel fence post near the cor.

From this cor., an open end pipe of unknown origin, 1 1/2 ins.
diam., loosely set, projecting 8 ins. above ground, bears
S 80° E, 78 lks. dist.

S 89°17' E, on the E and W center line of the NW 1/4 of the
NW 1/4 of sec. 35, along the N bdy. of Snow Bowl Estates.

9.925 The center N-NW 1/64 sec. cor. of sec. 35.

During the execution of the subdivision of sec. 35, monuments of
unknown origin were recovered and their relationship to the
subdivision corners is shown herein. Several monuments may have
been set by Clyde M. Etter, Reg. Hwy. Engr., in 1947 as shown on
his map of survey. There are certain significant differences
between Etter's map and actual ground conditions. As a result of
gross error, Etter's survey was not utilized.

BOOK 5295

T 23 N, R 6 E, Gila and Salt River Mer., Arizona

CHAINS

GENERAL DESCRIPTION

The area encompassed in this survey is located about 11 miles NW of Flagstaff, Arizona and 3 miles W of Humphreys Peak. The elevation ranges from about 8,150 to 9,000 ft. above sea level. The land is gently rolling to rolling covered with ponderosa pine, limber pine, Douglas Fir and aspen and native grasses.

Access is provided by U.S. Forest Service Routes 151 and 794 from U.S. Highway 180.

Improvements have been made mainly in sec. 35.

BOOK 5295

CERTIFICATE OF SURVEY

I, Duane R. Garoutte, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 17th day of June 1985, I have dependently resurveyed a portion of the south boundary and a portion of the subdivisional lines, and surveyed the subdivisions in sections 14, 22, 23, 27, 34, and 35, Township 23 North, Range 6 East, of the Gila and Salt River Meridian, in the State of Arizona which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Feb. 1, 1989

(Date)

Duane R. Garoutte

(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the south boundary and a portion of the subdivisional lines, and the survey of the subdivisions in sections 14, 22, 23, 27, 34, and 35, T 23 N, R 6 E, Gila and Salt River Meridian, Arizona, executed by Duane R. Garoutte, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUL 17 1990

(Date)

James P. Kelley

(Chief Cadastral Surveyor for Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I Certify That the foregoing transcript of the field notes of the above-described surveys in T 23 N, R 6 E, Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor for Arizona)~~