



INDEX DIAGRAM

TOWNSHIP 6 NORTH, RANGE 11 EAST,

			12		10		
6	5	4	24	3	22	2	19
			23			20	17
7	8	9		10		11	15
						20	15
18	17	16		15		14	14
19	20	21		22		23	24
30	29	28		27		26	25
27							
6	31	25	32	33	34	35	36

Subdivision of sec. 2 pp. 29 - 30  
 Subdivision of sec. 3 pp. 30 - 32  
 Subdivision of sec. 12 pp. 32 - 37  
 Subdivision of sec. 31 pp. 37 - 48

## T 6 N, R 11 E, Gila and Salt River Mer., Arizona

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the east, west and north boundaries and a portion of the subdivisional lines, and the survey of the subdivisions in sections 2, 3, 12, and 31, Township 6 North, Range 11 East, Gila and Salt River Meridian, Arizona.

The west boundary, a portion of the south boundary and a portion of the subdivisional lines were surveyed by Theo. F. White in 1881. The west boundary, a portion of the south boundary and a portion of the subdivisional lines were resurveyed, and the north and east boundaries were surveyed and the completion of the south boundary and subdivisional lines by Jesse B. Wright in 1907-08. Certain corners were remonumented by Louis D. Gilbert in 1970. A portion of the west boundary was resurveyed by John P. Bennett in 1980-81. A portion of the south boundary was concurrently resurveyed by Duane R. Garoutte and Alferd D. Pons, under this same group.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated January 13, 1984, and the Supplemental Instructions dated April 18, 1985, for Group No. 647, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of all lines were determined by observations on a U.S. Coast and Geodetic Survey triangulation network, confirmed by altitude observations on the sun and refer to the true meridian. Distances and angles were measured with a Zeiss Elta 46 instrument.

The geographic position of the northwest corner of section 3, as determined from a tie made to U.S. Coast and Geodetic Survey triangulation station "GREEN", located in unsurveyed Township 7 North, Range 11 East, is as follows:

NAD 27: Latitude: 33°53'57.00" N Longitude: 111°13'30.74" W

The mean magnetic declination as taken from quadrangle map "PICTURE MOUNTAIN, ARIZ.", published in 1964 by U.S. Geological Survey is 14° E.

Dependent Resurvey of a Portion of the E Bdy.,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS							
	<p>Restoring the survey executed by Jesse B. Wright in 1907</p> <hr/> <p>Beginning at the cor. of secs. 7, 12, 13, and 18, monumented with a granite boulder in place, 30 x 18 x 8 ins. above ground, mkd. with a cross on top, 2 grooves on the N face and 4 grooves on the S face, with a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>At the cor. point</p> <p>Set an aluminum post, 7 ins. long, 1 in. diam., 4 ins. in a drill hole, in granite rock, cemented in place, with cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T6N</td></tr> <tr><td>R11E R12E</td></tr> <tr><td>S12   S7</td></tr> <tr><td>— —</td></tr> <tr><td>S13   S18</td></tr> <tr><td>1985</td></tr> </table> </div> <p>N 0°03' W, bet. secs. 7 and 12.</p> <p>Over rolling mesa land; asc. over steep rocky SW slope.</p> <p>3.00 Top of ascent, slopes W; desc. over NW slope.</p> <p>33.98 The witness cor. to the 1/4 sec. cor. of secs. 7 and 12, monumented with a granite stone, 18 x 16 x 10 ins., firmly set, projecting 12 ins. above ground, mkd. WC on top, and 1/4 on W face, with a mound of stone, 2 1/2 ft. base, 6 ins. high, W of cor., from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N 71° E, 11 lks. dist., with scribe marks WC 1/4 S7 BT visible on partially healed blaze. (Record: N 65° E.)</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N 89° W, 36 lks. dist., with scribe marks WC 1/4 S12 BT visible on nearly healed blaze. (Record: S 65° W, 35 lks.)</p> <p>This now becomes an angle point.</p> <p>At the cor. point</p>	T6N	R11E R12E	S12   S7	— —	S13   S18	1985
T6N							
R11E R12E							
S12   S7							
— —							
S13   S18							
1985							

Dependent Resurvey of a Portion of the E Bdy.,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">A P T6N R11E R12E S12   S7 1985</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Bury the original stone alongside the stainless steel post.</p>
	<p>Rebuild the mound of stone, 3 1/2 ft. base, 2 ft. high, W of cor.</p>
	<p>N 0°04.5' E, beginning new measurement.</p>
	<p>Desc. from mesa over steep NW slope.</p>
<p>1.50</p>	<p>Draw, drains N 55° E.</p>
<p>5.995</p>	<p>Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T6N R11E R12E 1/4 S12   S7 1985</p>
	<p>from which</p>
	<p style="text-align: center;">A pinyon pine, 10 ins. diam., bears N 62° W, 107 lks. dist., mkd. 1/4 S12 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p>

Dependent Resurvey of a Portion of the E Bdy.,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p>11.00 Draw, drains N 20° W.</p> <p>38.50 Oak Creek, 15 lks. wide, course westerly; asc. over S slope.</p> <p>41.60 Improved dirt road, 30 lks. wide, bears N 65° E and S 65° W.</p> <p>45.95 The cor. of secs. 1, 6, 7, and 12, remonumented by Louis D. Gilbert in 1970, an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, N of cor., with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T6N R11E R12E S1   S6 ----- S12   S7 1970</p> </div> <p>Remove the mound of stone to the N and utilize the stones in raising a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the W Bdy., T 6 N, R 11 E, Gila and Salt River Mer., Arizona</p> <hr/> <p style="text-align: center;">Correcting the resurvey by John P. Bennett in 1980-81</p> <hr/> <p>From the cor. of Tps. 5 and 6 N, Rs. 10 and 11 E, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the W bdy. of T 5 N, R 11 E, executed concurrently under this same group.</p> <p>N 0°09.5' W, bet. secs. 31 and 36.</p> <p>Over bottom of Tonto Creek, subject to seasonal flooding.</p> <p>20.05 Point for the S 1/16 sec. cor. of secs. 31 and 36.</p> <p>From this point, the monument erroneously set in 1980, bears S 89°15' E, 1.142 chs. dist., a rebar, 48 ins. long, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap attached and mkd. as described in the 1980-81 official record.</p>
--------	---

Dependent Resurvey of a Portion of the W Bdy.,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>Remove the rebar from its found position and at the corrected cor. point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a 5 ft. steel fence post, with brass cap mkd.</p> <p style="text-align: center;">T6N R10E R11E S 1/16 S36   S31 1985</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, bears S 89°15' E, 75.4 ft. dist., with brass cap mkd. T6N R11E S31 RM 75.4 FT. TO COR. 1985 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post. Set a steel fence post near the RM.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, bears S 46°32' E, 125.0 ft. dist., with brass cap mkd. T6N R11E S31 RM 125.0 FT. TO COR. 1985 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post. Set a steel fence post near the RM.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p> <p>Destroy the 1980 monument.</p> <p>30.075 Point for the N-S 1/64 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a 5 ft. steel fence post, with brass cap mkd.</p> <p style="text-align: center;">N-S 1/64 S36   S31 1985</p>
---------------	--

Dependent Resurvey of a Portion of the W Bdy.,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
40.10	<p>The 1/4 sec. cor. of secs. 31 and 36, monumented with a rebar, 5/8 in. diam., firmly set, projecting 10 ins. above ground, with aluminum cap attached and mkd.</p> <p style="text-align: center;">T6N R10E R11E 1/4 S36   S31 1980</p> <p>from which the bearing trees mkd. in 1980</p> <p style="padding-left: 40px;">A willow, 14 ins. diam., bears N 38 1/2° E, 49 lks. dist., with scribe marks 1/4 S31 BT visible. (Record: N 41° E, 48 lks. dist.)</p> <p style="padding-left: 40px;">A willow, 12 ins. diam., bears S 82° W, 72 lks. dist., with scribe marks 1/4 S36 BT visible. (Record: S 86° W, 73 lks. dist.)</p> <hr/> <p style="text-align: center;">Restoring the resurvey by John P. Bennett in 1980-81</p> <p>N 0°09.5' W, beginning new measurement.</p> <p>Over Tonto Creek bottom, subject to seasonal flooding.</p>
3.06	<p>Point for the witness cor. to the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the 1908 witness cor., not remonumented.</p>
7.20	<p>Tonto Creek, 100 lks. wide, course SE.</p>
9.00	<p>Over level land.</p>
20.045	<p>The N 1/16 sec. cor. of secs. 31 and 36, monumented with an aluminum post, 1 in. diam., firmly set, projecting 6 ins. above ground, in a mound of stone, 3 ft. base, to top, with cap improperly mkd. with T 5 N; change cap to read</p>

Dependent Resurvey of a Portion of the W Bdy.,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>T6N R10E R11E N 1/16 S36   S31 1985 1980</p>
	<p>A steel fence post is near the cor.</p> <hr style="width: 30%; margin: 10px auto;"/>
	<p>N 0°09.5' W, beginning new measurement</p>
3.50	Improved dirt road, 35 lks. wide, bears SE and N 85° W.
5.015	Point for the S-N-N 1/256 sec. cor. of secs. 31 and 36.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>S-N-N 1/256 S36   S31 1985</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, W of cor.</p>
	<p>Set a steel fence post near the cor.</p>
	<p>The cor. is located N 83 1/4° W, 4.53 chs. dist., from cor. of fences extending E and S.</p>
9.30	Oak Creek, 30 lks. wide, course W.
20.055	The cor. of secs. 25, 30, 31, and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor., with brass cap mkd.
	<p>T6N R10E R11E S25   S30 ----- S36   S31 1980</p>

Dependent Resurvey of a Portion of the W Bdy.,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS

from which the bearing tree mkd. in 1908

A mesquite, 12 ins. diam., bears N 65° E, 72 lks. dist.,  
with healed blaze. (1980 Record: N 69° E, 73 lks.)

A steel fence post is near the cor.

Dependent Resurvey of a Portion of the N Bdy.,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

Restoring the survey executed by Jesse B. Wright in 1907

From the cor. of secs. 1, 2, 35, and 36, monumented with a  
granite boulder in place, 36 x 36 x 18 ins. above ground, mkd.  
with a cross on top, 1 groove to the E and 5 grooves to the W of  
the cross, with a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high,  
N of cor.

At the cor. point

Set an aluminum post, 8 ins. long, 1 in. diam., 5 ins. in a drill  
hole, in granite boulder, cemented in place, with cap mkd.

T7N	R11E						
S35	S36						
<table style="margin: 0 auto;"> <tr> <td style="padding: 2px;">S2</td> <td style="padding: 2px;">S1</td> </tr> <tr> <td colspan="2" style="padding: 2px;">T6N</td> </tr> <tr> <td colspan="2" style="padding: 2px;">1985</td> </tr> </table>		S2	S1	T6N		1985	
S2	S1						
T6N							
1985							

Remove the mound of stone to the N and utilize the stones in  
raising a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of  
cor.

S 89°54' W, bet. secs. 2 and 35.

Desc. over W slope.

- 5.00 Draw, drains S 15° W; asc. over E slope.
- 9.50 Top of rocky point on spur, slopes SE; desc. over S slope.
- 15.70 Slope changes to SW.
- 35.90 Draw, drains S 15° W; asc. over SE slope.

Dependent Resurvey of a Portion of the N Bdy.,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
39.77	<p>The 1/4 sec. cor. of secs. 2 and 35, monumented with a granite stone, 19 x 10 x 6 ins., mkd. 1/4 on N face, firmly set, projecting 8 ins. above the ground, with a scattered mound of stone, N of cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7N R11E S35 1/4 _____ S 2 T6N 1985</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 18 ins. diam., bears N 87 1/4° E, 84 lks. dist., mkd. 1/4 S35 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Rebuild the mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p>
5.00	Top of ascent; desc. over SW slope changing to S.
30.00	Draw, drains S; asc. over SE slope.
39.94	<p>The cor. of secs. 2, 3, 34, and 35, monumented with a granite boulder in place, 25 x 15 x 12 ins. above ground, mkd. with a cross on top, 2 grooves to the E, 4 grooves to the W and 6 grooves to the S of the cross, with a mound of stone, 3 ft. base, 2 ft. high, W of cor., from which the original bearing trees</p>

Dependent Resurvey of a Portion of the N Bdy.,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS																									
	<p>A juniper, 13 ins. diam., bears S 29° W, 219 lks. dist., with scribe marks T N R11E S BT visible on partially healed blaze. (Record: S 31 1/2° W).</p> <p>A juniper, 18 ins. diam., bears N 32 3/4° W, 173 lks. dist., with scribe marks N R1 E BT visible on weathered blaze. (Record: 170 lks.).</p> <p>At the cor. point</p> <p>Set an aluminum post, 7 ins. long, 1 in. diam., 4 ins. in a drill hole, in granite boulder, cemented in place, with cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T7N</td> <td>R11E</td> </tr> <tr> <td>S34</td> <td>S35</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S3</td> <td>S2</td> </tr> <tr> <td colspan="2" style="text-align: center;">T6N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1985</td> </tr> </table> </div> <p>Set a steel fence post near the cor.</p> <p>The cor. is located on a spur, slopes SW.</p> <hr/> <p>S 89°52.5' W, bet. secs. 3 and 34.</p> <p>Desc. over NW slope.</p> <p>33.30 Creek in Juniper Canyon, 15 lks. wide, course SW.</p> <p>39.885 The 1/4 sec. cor. of secs. 3 and 34, monumented with a granite stone, 20 x 14 x 4 ins., mkd. 1/4 on N face, firmly set, projecting 12 ins. above ground.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T7N</td> <td>R11E</td> </tr> <tr> <td colspan="2" style="text-align: center;">S34</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 3</td> </tr> <tr> <td colspan="2" style="text-align: center;">T6N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1985</td> </tr> </table> </div>	T7N	R11E	S34	S35			S3	S2	T6N		1985		T7N	R11E	S34		1/4	—	S 3		T6N		1985	
T7N	R11E																								
S34	S35																								
S3	S2																								
T6N																									
1985																									
T7N	R11E																								
S34																									
1/4	—																								
S 3																									
T6N																									
1985																									

Dependent Resurvey of a Portion of the N Bdy.,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>Bury the original stone alongside the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>N 89°42.5' W, beginning new measurement.</p> <p>Over gently rolling land.</p> <p>29.10 Improved dirt road, 35 lks. wide, bears N 75° E and S 50° W.</p> <p>40.375 The cor. of secs. 3, 4, 33, and 34, remonumented by Louis D. Gilbert in 1970, an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with a mound of stone, 2 ft. base, 1 ft. high, N of cor., with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T7N R11E</td> </tr> <tr> <td>S33</td> <td>S34</td> </tr> <tr> <td>S4</td> <td>S3</td> </tr> <tr> <td colspan="2">T6N</td> </tr> <tr> <td colspan="2">1970</td> </tr> </table> </div> <p>from which the original bearing tree</p> <p style="padding-left: 40px;">A mesquite, 8 ins. diam., bears S 21 1/4° E, 94.5 lks. dist., with scribe marks T6N R11E visible on weathered blaze. (Record: S 10° E, 80 lks.)</p> <p>Remove the mound of stone to the N and utilize the stones in raising a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>From this cor., U.S. Coast and Geodetic Survey triangulation station "GREEN," bears N 88°21.5' W, (forward bearing), 51.085 chs. dist., a standard brass disk, cemented in a drill hole in a boulder projecting 2 ins. above ground, mkd. GREEN 1946.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivisional Lines, T 6 N, R 11 E, Gila and Salt River Mer., Arizona</p> <hr/> <p style="text-align: center;">Restoring the survey executed by Jesse B. Wright in 1907</p> <hr/>	T7N R11E		S33	S34	S4	S3	T6N		1970	
T7N R11E											
S33	S34										
S4	S3										
T6N											
1970											

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p>From the 1/4 sec. cor. of secs. 13 and 14, marked with a cross on top of granite ledge, 50 x 40 x 6 ins. above ground, mkd. 1/4 to the W of the cross, with a mound of stone, 3 ft. base, 2 ft. high, W of cor., from which the original bearing trees.</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears N 45° E, 34 lks. dist., with scribe marks 1/4 S13 BT visible on open blaze. (Record: 30 lks.)</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears N 42 1/4° W, 66.5 lks. dist., with scribe marks 1/4 S14 BT visible on open blaze. (Record: N 31° W, 55 lks. dist.)</p> <p>At the cor. point</p> <p>Set an aluminum tablet, 3 ins. diam., 2 1/2-in. stem., in a drill hole, cemented in place, with cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T6N R11E 1/4 S14   S13 1985</p> </div> <p>N 0°21' W, bet. secs. 13 and 14.</p> <p>Over rolling mesa land; asc. over SE slope.</p> <p>12.00 Slope changes to E.</p> <p>34.50 Top of hill; desc. over N slope.</p> <p>40.12 Point for the cor. of secs. 11, 12, 13, and 14, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T6N R11E S11   S12 ----- S14   S13 1985</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <hr style="width: 80%; margin-left: 0;"/>
--------	--

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>From the cor. of secs. 7, 12, 13, and 18, on the E bdy. of the Tp.</p>
	<p>S 89°53' W, bet. secs. 12 and 13.</p>
	<p>Over rolling mesa land; desc. over broken SW slope, changing to W.</p>
<p>40.01</p>	<p>Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T6N R11E S12 1/4 _____ S13 1985</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A pinyon pine, 7 ins. diam., bears N 84 1/2° E, 57 lks. dist., mkd. 1/4 S12 BT.</p>
	<p style="padding-left: 40px;">A pinyon pine, 8 ins. diam., bears S 10° E, 76.5 lks. dist., mkd. 1/4 S13 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Over gently rolling mesa land.</p>
<p>67.50</p>	<p>Draw, drains N 35° W; asc. over NE slope.</p>
<p>79.20</p>	<p>Top of ascent, slopes N.</p>
<p>80.02</p>	<p>The cor. of secs. 11, 12, 13, and 14.</p> <hr/>
	<p>N 0°14.5' W, bet. secs. 11 and 12.</p>
	<p>Over rolling mesa land; desc. over NW slope.</p>
<p>11.00</p>	<p>Draw, drains S 70° W; asc. over S slope, changing to SE.</p>
<p>26.50</p>	<p>Top of ascent; desc. gradually.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
32.60	<p>The witness cor. to the 1/4 sec. cor. of secs. 11 and 12, monumented with a granite stone, 18 x 10 x 6 ins., firmly set, projecting 6 ins. above ground, mkd. WC 1/4 on top, with a small scattered mound of stone, W of cor. This now becomes an angle point.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">A P T6N R11E S11   S12 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Rebuild the mound of stone, 3 1/2 ft. base, 2 ft. high, W of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°05.5' E, beginning new measurement.</p>
0.75	<p>Desc. from mesa over steep rolling N slope.</p>
7.52	<p>Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T6N R11E 1/4 S11   S12 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS									
24.40	Oak Creek, 25 lks. wide, course N 80° W.								
27.58	Point for the N 1/16 sec. cor. of secs. 11 and 12.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 11 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T6N</td><td>R11E</td></tr> <tr><td>N</td><td>1/16</td></tr> <tr><td>S11</td><td> S12</td></tr> <tr><td colspan="2" style="text-align: center;">1985</td></tr> </table>	T6N	R11E	N	1/16	S11	S12	1985	
T6N	R11E								
N	1/16								
S11	S12								
1985									
	from which								
	<p style="margin-left: 40px;">A juniper, 12 ins. diam., bears N 55° W, 6 lks. dist., mkd. N 1/16 S11 BT.</p>								
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.								
	Asc. over S slope.								
40.30	Spur, slopes SW; desc. over NW slope.								
47.64	The cor. of secs. 1, 2, 11, and 12, remonumented by Louis D. Gilbert in 1970, an iron post, 2 1/2 ins. diam., loosely set, projecting 12 ins. above ground, with a small mound of stone, S of cor., with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T6N</td><td>R11E</td></tr> <tr><td>S2</td><td> S1</td></tr> <tr><td colspan="2" style="border-top: 1px solid black; text-align: center;">1970</td></tr> <tr><td>S11</td><td> S12</td></tr> </table>	T6N	R11E	S2	S1	1970		S11	S12
T6N	R11E								
S2	S1								
1970									
S11	S12								
	Stabilize and surround the monument with a mound of stone, 2 1/2 ft. base, to top.								
	Remove the mound of stone to the S and utilizing the stones in raising a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.								
	<hr/> <p>From the cor. of secs. 1, 6, 7, and 12, on the E bdy. of the Tp. N 89°44' W, bet. secs. 1 and 12.</p>								

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	Over gently rolling S slope.
22.50	Improved dirt road, 30 lks. wide, bears S 60° E and N 45° W.
28.05	Dirt road, 25 lks. wide, bears N 10° E and S 10° W.
29.70	Creek, 10 lks. wide, course S 10° W; asc. over SE slope.
40.18	<p>The 1/4 sec. cor. of secs. 1 and 12, remonumented by Louis D. Gilbert in 1970, an iron post, 2 1/2 ins. diam., loosely set, projecting 18 ins. above ground, in a scattered mound of stone, with a small mound of stone, S of cor., with brass cap mkd.</p> <p style="text-align: center;">T6N R11E S 1 1/4 _____ S12 1970</p> <p>Stabilize and surround the monument with a mound of stone, 3 ft. base, to top.</p> <p>Remove the mound of stone to the S and utilize the stones in raising a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p> <p>Asc. over SE slope, changing to S.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/> <p>S 89°57.5' W, beginning new measurement.</p>
12.00	Spur, slopes S 65° W; desc. gradually over NW slope.
19.965	<p>Point for the W 1/16 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R11E S 1 W 1/16 _____ S12 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. pink colored plastic case beneath the stainless steel post.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
39.93	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor. The cor. of secs. 1, 2, 11, and 12.</p> <hr/>
	<p>N 0°06' E, bet. secs. 1 and 2. Desc. over NW slope.</p>
7.70	<p>Draw, drains N 40° W; over broken W slope.</p>
19.65	<p>Improved dirt road, 35 lks. wide, bears N 80° E and S 65° W.</p>
24.50	<p>Walnut Creek, 20 lks. wide, course S 60° W; asc. over S slope, changing to SW.</p>
40.075	<p>The 1/4 sec. cor. of secs. 1 and 2, monumented with a granite stone, 15 x 8 x 6 ins., mkd. 1/4 on W face, firmly set, projecting 8 ins. above the ground, with a scattered mound of stone, W of cor.</p>
	<p>At the cor. point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T6N R11E 1/4 S2 S1 1985</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Bury the original stone alongside the stainless steel post.</p>
	<p>Rebuild the mound of stone, 3 ft. base, 2 1/2 ft. high, W of cor.</p>
	<p>Set a steel fence post near the cor.</p> <hr/>
	<p>N 0°00.5' E, beginning new measurement.</p>
22.50	<p>Top of ascent; over W slope.</p>
39.96	<p>The cor. of secs. 1, 2, 35, and 36, on the N bdy. of the Tp.</p> <hr/>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	From the cor. of secs. 11, 12, 13, and 14.
	S 88°42' W, bet. secs. 11 and 14.
	Desc. over mountainous land.
40.00	The 1/4 sec. cor. of secs. 11 and 14, monumented with a granite stone, 18 x 6 x 3 ins., mkd. 1/4 on N face, firmly set in a small mound of stone, from which the original bearing tree
	A juniper, 14 ins. diam., bears N 26° W, 55 lks. dist., with illegible scribe marks visible on nearly healed blaze. (Record: 60 lks.).
	At the cor. point
	Set an aluminum post, 7 ins. long, 1 in. diam., 4 ins. in a drill hole, in rock ledge, cemented in place, with cap mkd.
	T6N R11E S11 1/4 ——— S14 1985
	Deposit the original stone alongside the aluminum post.
	Raise a mound of stone, 3 ft. base, 3 ft. high, N of cor.
	The cor. is located on rocky SE slope.
	From the cor. of secs. 1, 2, 11, and 12.
	N 89°57' W, bet. secs. 2 and 11.
	Desc. over NW slope.
3.60	Draw, drains NW; asc. over NE slope.
8.35	Dirt road, 15 lks. wide, bears S 20° E and N 20° W.
16.50	Top of ascent, slopes SE; desc. over W slope.
35.00	Dirt road, 12 lks. wide, bears S 30° E and N 15° W.
39.50	Draw, drains NW.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
39.945	<p>The 1/4 sec. cor. of secs. 2 and 11, remonumented by Louis D. Gilbert in 1970, an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above a mound of stone, 3 1/2 ft. base, 2 ft. high, with brass cap mkd.</p> <p style="text-align: center;">T6N R11E S 2 1/4 ——— S11 1970</p> <p>from which the original bearing tree</p> <p style="padding-left: 40px;">A juniper, 23 ins. diam., bears S 33° E, 236 lks. dist., with scribe marks 1/4 S11 BT visible on ax opened blaze. (Record: 240 lks.)</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A juniper, 11 ins. diam., bears N 4 1/4° E, 51 lks. dist., mkd. 1/4 S2 BT.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/> <p>N 89°50' W, beginning new measurement.</p> <p>Over rolling N slope.</p>
0.24	Fence, bears N and S.
39.80	Draw, drains N.
39.955	<p>The cor. of secs. 2, 3, 10, and 11, remonumented by Louis D. Gilbert in 1970, an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 3 ft. base, to top, with a mound of stone, 2 1/2 ft. base, 1 ft. high, W of cor., with a steel fence post nearby, with brass cap mkd.</p> <p style="text-align: center;">T6N R11E S3   S2 ————— S10   S11 1970</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 45 ins. diam., bears N 10° W, 41 lks. dist., with scribe marks T6N R11E S2 BT visible on open blaze. (Record: N 2° E.)</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A dead juniper, 36 ins. diam., bears N 67° W, 197 lks. dist.</p> <p>and a new bearing tree</p> <p>A juniper, 14 ins. diam., bears S 12 1/2° E, 56.5 lks. dist., mkd. T6N R11E S11 BT.</p> <hr/> <p>N 0°11.5' E, bet. secs. 2 and 3.</p> <p>Desc. over broken NE slope.</p> <p>9.10 Dirt road, 15 lks. wide, bears S 45° E and N 80° W.</p> <p>13.70 Walnut Creek, 15 lks. wide, course N 65° W; asc. over SW slope.</p> <p>16.60 Improved dirt road, 30 lks. wide, bears S 70° E and N 80° W.</p> <p>19.875 Point for the S 1/16 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R11E S 1/16 S3 S2 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p> <p>28.50 Spur, slopes W; desc. over N slope.</p> <p>35.00 Draw, drains W; asc. over S slope.</p> <p>39.75 The 1/4 sec. cor. of secs. 2 and 3, monumented with a granite stone, 12 x 10 x 6 ins., mkd. 1/4 on W face, firmly set, projecting 5 ins. above the ground, with a scattered mound of stone, W of cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	T6N R11E 1/4 S3 S2 1985
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Bury the original stone alongside the stainless steel post.
	Rebuild the mound of stone, 2 1/2 ft. base, 6 ins. high, W of cor.
	Set a steel fence post near the cor.
	<hr/> N 0°10' E, beginning new measurement.
4.00	Spur, slopes S 65° W; desc. over broken W slope.
29.00	Draw, drains SW; asc. over SE slope.
39.96	The cor. of secs. 2, 3, 34, and 35, on the N bdy. of the Tp.
	<hr/> From the cor. of secs. 2, 3, 10, and 11.
	N 89°57.5' W, bet. secs. 3 and 10.
	Asc. over broken NE slope.
15.30	Dirt road, 15 lks. wide, bears NE and SW.
22.80	Spur, slopes N 20° W; desc. over W slope, changing to N.
39.94	The 1/4 sec. cor. of secs. 3 and 10, remonumented by Louis D. Gilbert in 1970, an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T6N R11E S 3 1/4 ——— S10 1970
	A steel fence post is near the cor.
	The cor. is located in a fence, bears N and S.
	<hr/>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS											
	S 89°21.5' W, beginning new measurement.										
	Desc. over N slope, changing to NW.										
19.00	Walnut Creek, 15 lks. wide, course SW; asc. over E slope.										
32.50	Spur, slopes SW; desc. over NW slope.										
40.01	The cor. of secs. 3, 4, 9, and 10, monumented with a granite stone, 16 x 8 x 8 ins., broken into two pieces, mkd. with 3 grooves on the E face, 5 grooves on the S face, firmly set in a mound of stone, 2 1/2 ft. base, 6 ins. high.										
	At the cor. point										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.										
	<table border="0"> <tr> <td colspan="2">T6N R11E</td> </tr> <tr> <td>S4</td> <td>S3</td> </tr> <tr> <td colspan="2">-----</td> </tr> <tr> <td>S9</td> <td>S10</td> </tr> <tr> <td colspan="2">1985</td> </tr> </table>	T6N R11E		S4	S3	-----		S9	S10	1985	
T6N R11E											
S4	S3										
-----											
S9	S10										
1985											
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.										
	Bury the original stone alongside the stainless steel post.										
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.										
	Set a steel fence post near the cor.										
	-----										
	N 0°14' E, bet. secs. 3 and 4.										
	Desc. over NW slope.										
12.50	Draw, drains SW; asc. over SE slope.										
19.50	Top of ascent; desc. over NW slope.										
27.00	Draw, drains W; asc. over SW slope.										
34.00	Spur, slopes W; desc. over NW slope.										

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
40.055	<p>The 1/4 sec. cor. of secs. 3 and 4, monumented with a granite boulder, 50 x 16 x 12 ins. above ground, mkd. with a cross on top, 1/4 on N face, from which the original bearing trees</p> <p>A juniper, 20 ins. diam., bears S 38 1/2° E, 81 lks. dist., with scribe marks 1/4 S3 BT visible on partially healed blaze. (Record: 91 lks.)</p> <p>A juniper, 18 ins. diam., bears S 19° W, 33 lks. dist., with scribe marks 1/4 S4 BT visible on partially healed blaze. (Record: S 24 1/2° W, 35 lks.)</p> <p>At the cor. point</p> <p>Set an aluminum tablet, 3 ins. diam., 2 1/2-in. stem, in a drill hole, cemented in place, with cap mkd.</p> <p style="text-align: center;">T6N R11E 1/4 S4 S3 1985</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p> <hr/>
	<p>N 0°21' W, beginning new measurement.</p>
4.00	<p>Draw, drains SW; asc. over SE slope.</p>
14.00	<p>Top of ridge, bears E and W; desc. over NW slope.</p>
32.80	<p>Creek in Juniper Canyon, 15 lks. wide, course S 80° W; asc. over SE slope.</p>
40.19	<p>The cor. of secs. 3, 4, 33, and 34, on the N bdy. of the Tp.</p> <hr/> <p style="text-align: center;">Restoring the resurvey executed by Jesse B. Wright in 1907-1908</p> <hr/> <p>From the cor. of secs. 5, 6, 31, and 32, on the S bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set 5 ins. below the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the N bdy. of T 5 N, R 11 E, executed concurrently under this same group.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>N 0°17' E, bet. secs. 31 and 32.</p> <p>Over level land.</p>
3.50	<p>Improved dirt road, 40 lks. wide, bears S 30° E and N 30° W.</p>
5.00	<p>Over gently rolling land.</p>
20.34	<p>Point for the S 1/16 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T6N R11E S 1/16 S31 S32 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. blue colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
38.00	<p>Edge of mesa, bears SE and NW.</p>
40.68	<p>True point for the 1/4 sec. cor. of secs. 31 and 32, determined at 1.5 ft. W of small rock mound as described in a survey performed by Travis Lee Gant, LS 5703, in 1979 who recovered the original monument, which no longer exists.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R11E 1/4 S31 S32 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Remove rock mound and utilize stones in raising a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS											
	<p>Set a steel fence post near the cor.</p> <hr/>										
	<p>N 0°13.5' W, beginning new measurement.</p>										
28.60	<p>Wash, 50 lks. wide, drains NW.</p>										
40.275	<p>The cor. of secs. 29, 30, 31, and 32, monumented with a granite stone, 15 x 10 x 8 ins., mkd. with 5 notches on E edge, 1 notch on the S edge, firmly set, projecting 8 ins. above ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W of cor.</p>										
	<p>At the cor. point</p>										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>										
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T6N R11E</td> </tr> <tr> <td style="text-align: center;">S30</td> <td style="text-align: center;">S29</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S31</td> <td style="text-align: center;">S32</td> </tr> <tr> <td colspan="2" style="text-align: center;">1985</td> </tr> </table>	T6N R11E		S30	S29	-----		S31	S32	1985	
T6N R11E											
S30	S29										
-----											
S31	S32										
1985											
	<p>from which</p>										
	<p style="padding-left: 40px;">A paloverde, 4 ins. diam., bears N 42 3/4° W, 34 lks. dist., bark scribed X BT.</p>										
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>										
	<p>Bury the original stone alongside the stainless steel post.</p>										
	<p>Set a steel fence post near the cor.</p> <hr/>										
	<p>S 89°42.5' W, bet. secs. 30 and 31.</p>										
	<p>Over gently rolling land.</p>										
12.00	<p>Top of mesa.</p>										
40.025	<p>The 1/4 sec. cor. of secs. 30 and 31, monumented with a granite stone, 16 x 12 x 8 ins., mkd. 1/4 on N face, firmly set, projecting 6 ins. above ground, with a mound of stone, 3 1/2 ft. base, 1 ft. high, W of cor.</p>										

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T6N R11E S30 1/4 _____ S31 1985</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Bury the original stone alongside the stainless steel post.
	Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, N of cor.
	Set a steel fence post near the cor.
	<p style="text-align: center;">_____</p> N 89°45' W, beginning new measurement.
20.535	Point for the W 1/16 sec. cor. of secs. 30 and 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T6N R11E S30 W 1/16 _____ S31 1985</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, N of cor.
	Set a steel fence post near the cor.
29.40	Improved dirt road, 40 lks. wide, bears NE and SW.
33.50	Oak Creek, 30 lks. wide, course S 15° W.
40.45	Edge of mesa, bears NE and SW.
40.545	The cor. of secs. 25, 30, 31, and 36, on the W bdy. of the Tp.

Survey of Subdivisions in Section 2  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	From the 1/4 sec. cor. of secs. 2 and 11.
	N 0°10.5' E, on the N and S center line of sec. 2.
0.50	Draw, drains NW.
13.20	Improved dirt road, 35 lks. wide, bears N 65° E and S 65° W.
18.20	Walnut Creek, 10 lks. wide, course S 30° W; asc. over broken S slope.
19.98	Point for the center S 1/16 sec. cor. of sec. 2.
	Set an aluminum post, 18 ins. long, 1 in. diam., 10 ins. in the ground, to rock, cemented in place, with cap mkd.
	<p>T6N R11E C S 1/16   S 2 C 1985</p>
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.
	Set a steel fence post near the cor.
39.00	Spur, slopes SW.
39.96	Point for the center 1/4 sec. cor. of sec. 2, at intersection with the E and W center line of sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p>T6N R11E C 1/4 S2 1985</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.
	Set a steel fence post near the cor.
53.00	Spur, slopes W; desc. over N slope.

Survey of Subdivisions in Section 2  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
67.60	Draw, drains N 65° W; asc. over SE slope.
79.93	The 1/4 sec. cor. of secs. 2 and 35, on the N bdy. of the Tp.
	<hr/> From the 1/4 sec. cor. of secs. 1 and 2.
	S 89°52.5' W, on the E and W center line of sec. 2.
	Desc. over broken SW slope.
21.10	Draw, drains S; asc. over SE slope.
39.00	Spur, slopes SW.
39.885	The center 1/4 sec. cor. of sec. 2.
	Desc. over W slope.
50.00	Draw, drains S 30° W; asc. over E slope.
59.00	Spur, slopes SW; desc. over W slope, changing to S.
79.82	The 1/4 sec. cor. of secs. 2 and 3.
	<hr/> <p style="text-align: center;">SW 1/4 of Sec. 2</p> <hr/>
	From the center S 1/16 sec. cor. of sec. 2.
	N 89°59' W, on the E and W center line of the SW 1/4 of sec. 2.
	Over broken S slope.
23.00	Top of ascent; desc. over broken SW slope.
39.94	The S 1/16 sec. cor. of secs. 2 and 3.
	<hr/> <p style="text-align: center;">Survey of Subdivisions in Section 3 T 6 N, R 11 E, Gila and Salt River Mer., Arizona</p> <hr/>
	From the 1/4 sec. cor. of secs. 3 and 10.
	N 0°12.5' E, on the N and S center line of sec. 3.

Survey of Subdivisions in Section 3  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	Desc. over N slope, along fence.
5.20	Draw, drains N 60° W; asc. over SW slope.
14.00	Top of ascent; desc. over N slope.
19.835	Point for the center S 1/16 sec. cor. of sec. 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T6N R11E C S 1/16   S 3 C 1985</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.
	Set a steel fence post near the cor.
	The cor. is located 15 lks. E of a fence, bears N and S.
25.00	Walnut Creek, 20 lks. wide, course N 75° W; asc. over S slope.
39.67	Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E and W center line of sec. 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T6N R11E C 1/4 S3 1985</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, W of cor.
	Set a steel fence post near the cor.
40.50	Spur, slopes W; desc. over broken N slope.

Survey of Subdivisions in Section 3  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
63.30	Improved dirt road, 30 lks. wide, bears S 70° E and N 70° W.
76.60	Creek in Juniper Canyon, 20 lks. wide, course S 60° W.
79.60	The 1/4 sec. cor. of secs. 3 and 34, on the N bdy. of the Tp.
<hr/>	
	From the 1/4 sec. cor. of secs. 2 and 3.
	S 89°55.5' W, on the E and W center line of sec. 3.
	Desc. over S slope, changing to W.
18.50	Draw, drains SW; asc. over SE slope changing to S.
26.50	Improved dirt road, 30 lks. wide, bears N 25° E and S 25° W.
39.92	The center 1/4 sec. cor. of sec. 3.
48.00	Spur, slopes SW; desc. over NW slope.
79.905	The 1/4 sec. cor. of secs. 3 and 4.
<hr/>	
	SE 1/4 of Sec. 3
<hr/>	
	From the S 1/16 sec. cor. of secs. 2 and 3.
	S 89°59' W, on the E and W center line of the SE 1/4 of sec. 3.
	Desc. over SW slope.
14.20	Improved dirt road, 30 lks. wide, bears S 70° E and N 70° W.
24.20	Walnut Creek, 60lks. wide, course N 20° W.
39.93	The center S 1/16 sec. cor. of sec. 3.
<hr/>	
	Survey of Subdivisions in Section 12
	T 6 N, R 11 E, Gila and Salt River Mer., Arizona
<hr/>	
	From the 1/4 sec. cor. of secs. 12 and 13.
	N 0°06.5' W, on the N and S center line of sec. 12.

Survey of Subdivisions in Section 12  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	Over gently rolling mesa land.
40.05	Point for the center 1/4 sec. cor. of sec. 12, at intersection with the E and W center line of sec. 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T6N R11E
	C 1/4 S12
	1985
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
44.50	Desc. from mesa over steep N slope.
50.085	Point for the center S-N 1/64 sec. cor. of sec. 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	S12
	C-S-N
	1/64
	1985
	from which
	A juniper, 8 ins. diam., bears S 48° W, 14 lks. dist., mkd. C-S-N 1/64 S12 BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
	The cor. is located 48 lks. E of a fence, bears N and S.
56.00	Oak Creek, 10 lks. wide, course N 55° W; asc. over S slope.
60.12	Point for the center N 1/16 sec. cor. of sec. 12.

Survey of Subdivisions in Section 12  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a steel fence post, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T6N R11E C N 1/16   S 12 C 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located on W edge of wash, 20 lks. wide, drains irregularly S.</p>
61.50	Dirt road, 15 lks. wide, bears N 60° E and S 60° W.
80.19	The 1/4 sec. cor. of secs. 1 and 12.
	<hr/> <p>From the 1/4 sec. cor. of secs. 7 and 12, on the E bdy. of the Tp.</p> <p>S 89°59.5' W, on the E and W center line of sec. 12.</p> <p>Asc. over steep NE slope.</p>
11.00	Top of ascent; desc. over NW slope.
25.00	Draw, drains N; asc. over NW slope.
40.06	The center 1/4 sec. cor. of sec. 12.
55.085	Point for the center W-E-W 1/256 sec. cor. of sec. 12.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S12 C-W-E-W 1/256 1985</p>

Survey of Subdivisions in Section 12  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
55.35	Desc. from mesa over steep broken N slope.
60.095	Point for the center W 1/16 sec. cor. of sec. 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T6N R11E W 1/16 C-----C S 12 1985</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
80.13	The 1/4 sec. cor. of secs. 11 and 12.
	<p style="text-align: center;">NW 1/4 of Sec. 12</p> <hr style="width: 20%; margin: auto;"/>
	From the center W 1/16 sec. cor. of sec. 12.
	N 0°00.5' W, on the N and S center line of the NW 1/4 of sec. 12.
	Desc. over steep broken N slope.
16.70	Oak Creek, 10 lks. wide, course S 60° W; asc. over broken S slope.
20.065	Point for the NW1/16 sec. cor., at intersection with the E and W center line of the NW 1/4 of sec. 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T6N R11E NW 1/16 S12 1985</p>

Survey of Subdivisions in Section 12  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
37.50	Spur, slopes S 65° W; desc. over NW slope.
40.13	The W 1/16 sec. cor. of secs. 1 and 12.
	From the center N 1/16 sec. cor. of sec. 12.
	S 89°58.5' W, on the E and W center line of the NW 1/4 of sec. 12.
	Over broken S slope.
2.50	Dirt road, 15 lks. wide, bears N 60° E and S 60° W.
20.00	The NW 1/16 sec. cor. of sec. 12.
40.00	The N 1/16 sec. cor. of secs. 11 and 12.
	SE 1/4 of the NW 1/4 of Sec. 12
	From the center S-N 1/64 sec. cor. of sec. 12.
	S 89°59' W, on a portion of the E and W center line of the SE 1/4 of the NW 1/4 of sec. 12.
15.013	Point for the center W-SE-NW 1/256 sec. cor. of sec. 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	S12 C-W-SE-NW 1/256 1985
	from which
	A juniper, 10 ins. diam., bears S 89° W, 117 lks. dist., mkd. C-W-SE-NW 1/256 S12 BT.

Survey of Subdivisions in Section 12  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S 0°02' E, on the N and S center line of the SW 1/4 of the SE 1/4 of the NW 1/4 of sec. 12.</p> <p>Asc. over steep N slope.</p> <p>9.75 Edge of mesa, bears NE and SW.</p> <p>10.033 The center W-E-W 1/256 sec. cor. of sec. 12.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">Survey of Subdivisions in Section 31 T 6 N, R 11 E, Gila and Salt River Mer., Arizona</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the true point for the 1/4 sec. cor. of secs. 6 and 31, on the S bdy. of the Tp., described in the field notes of the dependent resurvey of a portion of the N bdy. of T 5 N, R 11 E, executed concurrently under this same group.</p> <p>North, on the N and S center line of sec. 31.</p> <p>Over bottom land.</p> <p>12.00 Over level land, through residential area.</p> <p>19.00 Improved dirt road, 30 lks. wide, bears SE and NW.</p> <p>20.20 Point for the center S 1/16 sec. cor. of sec. 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T6N R11E</p> <p>C</p> <p>S 1/16   S 31</p> <p>C</p> <p>1985</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. blue colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
--------	---

Survey of Subdivisions in Section 31  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
33.80	Improved dirt road, 35 lks. wide, bears S 60° E and N 60° W.
37.75	Edge of mesa, bears SE and NW.
40.40	<p>The center 1/4 sec. cor. of sec. 31, established by James H. Lange, LS 4245, in 1963, monumented with an iron pipe, 18 ins. long, 1 in. diam., firmly set, projecting 4 ins. above ground and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R11E C 1/4 S31 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert the pipe inside the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located 2 lks. S of cor. of fences extending N, E and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°01.5' E, beginning new measurement.</p> <p>Over mesa land sloping generally S.</p> <p>Along fence.</p>
19.995	<p>Point for the center N 1/16 sec. cor. of sec. 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R11E C N 1/16   S 31 C 1985</p>

Survey of Subdivisions in Section 31  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post near the cor.</p>
	<p>The cor. is located in a fence, bears N and S.</p>
20.025	<p>Cor. of fences extending S and W.</p>
39.99	<p>The 1/4 sec. cor. of secs. 30 and 31.</p>
	<hr/> <p>From the 1/4 sec. cor. of secs. 31 and 32.</p>
	<p>N 89°52.5' W, on the E and W center line of sec. 31.</p>
	<p>Over gently rolling mesa land.</p>
7.70	<p>Desc. from mesa over SW slope.</p>
16.00	<p>Over land sloping S.</p>
20.105	<p>Point for the center E 1/16 sec. cor. of sec. 31.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T6N R11E E 1/16 C———C S 31 1985</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post near the cor.</p>
30.158	<p>The center W-E 1/64 sec. cor. of sec. 31, established by James H.</p>
	<p>Lange, LS 4245, in 1963, monumented with an iron pipe, 18 ins. long, 1 in. diam., firmly set, projecting 4 ins. above ground, with a steel fence post nearby and is accepted as a careful and faithful determination of the position of the cor.</p>
	<p>At the cor. point</p>

Survey of Subdivisions in Section 31  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S31 C-W-E 1/64 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert the pipe inside the stainless steel post.</p> <p>Raise a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N 89°54.5' W, beginning new measurement.</p> <p>10.05 The center 1/4 sec. cor. of sec. 31.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N 89°54.5' W, beginning new measurement.</p> <p>Along fence</p> <p>5.20 Desc. from mesa.</p> <p>8.40 Improved dirt road, 35 lks. wide, bears S 65° E and N 65° W; over level land.</p> <p>20.425 The center W 1/16 sec. cor. of sec. 31, established by James H. Lange, LS 4245, in 1963, monumented with an iron pipe, 18 ins. long, 1 in. diam., firmly set, projecting 3 ins. above ground, at cor. of fences extending E and S and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T6N R11E W 1/16 C———C S31 1985</p>
--------	---

Survey of Subdivisions in Section 31  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert the pipe inside the stainless steel post.</p> <hr/> <p>N 89°54.5' W, beginning new measurement.</p>
8.00	Over bottom land.
16.50	Tonto Creek, 100 lks. wide, course S 20° W.
19.995	The 1/4 sec. cor. of secs. 31 and 36, on the W bdy. of the Tp.
	<hr/> <p style="text-align: center;">SE 1/4 of Sec. 31</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 6 and 31, on the S bdy. of the Tp., monumented with an aluminum post, 1 in. diam., firmly set, projecting 4 ins. above ground, with cap mkd. as described in the field notes of the dependent resurvey of a portion of the N bdy. of T 5 N, R 11 E, executed concurrently under this same group.</p> <p>N 0°08.5' E, on the N and S center line of the SE 1/4 of sec. 31.</p>
18.00	Improved dirt road, 35 lks. wide, bears S 60° E and N 60° W.
20.27	<p>Point for the SE 1/16 sec. cor. of sec. 31, at intersection with the E and W center line of the SE 1/4 of sec. 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R11E SE 1/16 S31 1985</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
21.00	Edge of mesa, bears SE and NW.
40.55	The center E 1/16 sec. cor. of sec. 31.

Survey of Subdivisions in Section 31  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>From the S 1/16 sec. cor. of secs. 31 and 32.</p>
	<p>N 89°43.5' W, on the E and W center line of the SE 1/4 of sec. 31.</p>
10.03	<p>The center E-SE 1/64 sec. cor. of sec. 31, established by James H. Lange, LS 4245, in 1963, monumented with an iron pipe, 18 ins. long, 1 in. diam., firmly set, projecting 2 ins. above ground and is accepted as a careful and faithful determination of the position of the cor.</p>
	<p>At the cor. point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S31 C-E-SE 1/64 1985</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. orange colored plastic case beneath the stainless steel post.</p>
	<p>Insert the pipe inside the stainless steel post.</p>
	<p>Set a steel fence post near the cor.</p>
	<hr style="width: 20%; margin: auto;"/> <p>N 89°40.5' W, beginning new measurement.</p>
10.025	<p>The SE 1/16 sec. cor. of sec. 31.</p>
14.30	<p>Improved dirt road, 35 lks. wide, bears SE and NW.</p>
20.055	<p>The center W-SE 1/64 sec. cor. of sec. 31, established by James H Lange, LS 4245, in 1963, monumented with an iron pipe, 18 ins. long, 1 in. diam., 6 ins. below surface of improved road, with a steel fence post alongside and is accepted as a careful and faithful determination of the position of the cor.</p>
	<p>At the cor. point</p>
	<p>Set an aluminum post, 18 ins. long, 1 in. diam., 10 ins. below the road surface, with cap mkd.</p>

Survey of Subdivisions in Section 31  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p style="text-align: center;">S31 C-W-SE 1/64 1985</p> <p>Reset pipe and fence post alongside the stainless steel post, 10 ins. below the surface.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N 89°41' W, beginning new measurement.</p> <p>6.30 End of improved road.</p> <p>10.025 The center S 1/16 sec. cor. of sec. 31.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">SE 1/4 of the SE 1/4 of Sec. 31</p> <hr style="width: 30%; margin: 10px auto;"/> <p>From the E-E 1/64 sec. cor. of secs. 6 and 31, on the S bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the N bdy. of T 5 N, R 11 E, executed concurrently under this same group.</p> <p>N 0°12.5' E, on the N and S center line of the SE 1/4 of the SE 1/4 of sec. 31.</p> <p>11.90 Improved dirt road, 40 lks. wide, bears S 70° E and N 60° W.</p> <p>20.305 The center E-SE 1/64 sec. cor. of sec. 31.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">NW 1/4 of the SE 1/4 of Sec. 31</p> <hr style="width: 30%; margin: 10px auto;"/> <p>From the center W-SE 1/64 sec. cor. of sec. 31.</p> <p>N 0°04.5' E, on the N and S center line of the NW 1/4 of the SE 1/4 of sec. 31.</p> <p>5.20 Improved dirt road, 35 lks. wide, bears SE and NW.</p> <p>20.245 The center W-E 1/64 sec. cor. of sec. 31.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">SW 1/4 of Sec. 31</p> <hr style="width: 30%; margin: 10px auto;"/>
--------	--

Survey of Subdivisions in Section 31  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>From the W 1/16 sec. cor. of secs. 6 and 31, on the S bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the N bdy. of T 5 N, R 11 E, executed concurrently under this same group.</p>
	<p>N 0°02' W, on the N and S center line of the SW 1/4 of sec. 31.</p>
	<p>Over bottom land.</p>
16.40	<p>Tonto Creek, 200 lks. wide, course S 50° E.</p>
20.12	<p>Point for the SW 1/16 sec. cor. of sec. 31, at intersection with the E and W center line of the SW 1/4 of sec. 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a 5 ft. steel fence post, with brass cap mkd.</p>
	<p style="text-align: center;">T6N R11E SW 1/16 S31 1985</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post near the cor.</p>
28.00	<p>Over level land.</p>
30.18	<p>The center N-SW 1/64 sec. cor. of sec. 31, established by Loyd Emmett Nickelson, Civil Engineer 2199, monumented with a rebar, 18 ins. long, 1/2 in. diam., 5 ins. below the ground, with tag attached and mkd. PE 2199 and is accepted as a careful and faithful determination of the position of the cor.</p>
	<p>At the cor. point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S31 C-N-SW 1/64 1985</p>

Survey of Subdivisions in Section 31  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert the rebar inside the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
30.26	<p>Cor. of fences bears W 1 1/2 lks. dist.; fences extending N and W, 90 lks. to end of fence.</p> <p>Along fence.</p>
40.24	<p>The center W 1/16 sec. cor. of sec. 31.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 31.</p> <p>N 89°41.5' W, on the E and W center line of the SW 1/4 of sec. 31.</p> <p>Over level land.</p>
10.205	<p>Point for the center E-SW 1/64 sec. cor. of sec. 31, falls in path used by small off road terrain vehicles, etc.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. below the ground, with brass cap mkd.</p> <p style="text-align: center;">S31 C-E-SW 1/64 1985</p>
	<p>from which</p> <p style="padding-left: 40px;">A railroad tie, 6 x 6 in., projecting 5 ins. above ground, bears S 80 1/2° E, 12.7 lks. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Over bottom land.</p>
20.41	<p>The SW 1/16 sec. cor. of sec. 31.</p>

Survey of Subdivisions in Section 31  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
33.20	Tonto Creek, 200 lks. wide, course SE.
40.36	The S 1/16 sec. cor. of secs. 31 and 36, on the W bdy. of the Tp.
<hr/> SE 1/4 of the SW 1/4 of Sec. 31 <hr/>	
From the E-W 1/64 sec. cor. of secs. 6 and 31, on the S bdy. of the Tp., monumented with and iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the N bdy. of T 5 N, R 11 E, executed concurrently under this same group.	
N 0°01' W, on the N and S center line of the SE 1/4 of the SW 1/4 of sec. 31.	
Over bottom land.	
6.20	Tonto Creek, 200 lks. wide, course S 75° E.
20.16	The SE 1/16 sec. cor. of sec. 31.
<hr/> NW 1/4 of the SW 1/4 of Sec. 31 <hr/>	
From the center N-SW 1/64 sec. cor. of sec. 31.	
N 89°48' W, on the E and W center line of the NW 1/4 of the SW 1/4 of sec. 31.	
Over level land	
Over bottom land.	
16.80	Tonto Creek, 200 lks. wide, course S 20° E.
19.97	The N-S 1/64 sec. cor. of secs. 31 and 36, on the W bdy. of the Tp.
<hr/> NW 1/4 of Sec. 31 <hr/>	
From the center W 1/16 sec. cor. of sec. 31.	

Survey of Subdivisions in Section 31  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>N 0°08' W, on the N and S center line of the NW 1/4 of sec. 31. Over nearly level land.</p>
5.30	<p>Improved dirt road, 45 lks. wide, bears S 70° E and N 60° W.</p>
18.00	<p>Edge of mesa, bears S 70° E and N 70° W.</p>
20.025	<p>Point for the NW 1/16 sec. cor. of sec. 31, at intersection with the E and W center line of the NW 1/4 of sec. 31.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T6N R11E NW 1/16 S31 1985</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, W of cor.</p>
	<p>Set a steel fence post near the cor.</p>
	<p>The cor. is located N 64 1/2° W, 49 lks. dist., from cor. of fences extending N and E.</p>
25.03	<p>Point for the center S-N-NW 1/256 sec. cor. of sec. 31.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S31 C-S-N-NW 1/256 1985</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, W of cor.</p>
	<p>Set a steel fence post near the cor.</p>
	<p>The cor. is located N 66 1/2° W, 60 lks. dist., from cor. of fences extending S and W.</p>

Survey of Subdivisions in Section 31  
T 6 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
40.045	The W 1/16 sec. cor. of secs. 30 and 31.
	From the center N 1/16 sec. cor. of sec. 31.
	N 89°50.5' W, on the E and W center line of the NW 1/4 of sec. 31.
	Across mesa.
20.48	The NW 1/16 sec. cor. of sec. 31.
25.00	Desc. from mesa.
30.00	Over level land.
36.50	Improved dirt road, 45 lks. wide, bears SE and NW.
40.485	The N 1/16 sec. cor. of secs. 31 and 36, on the W bdy. of the Tp.
	NW 1/4 of the NW 1/4 of Sec. 31
	From the center S-N-NW 1/256 sec. cor. of sec. 31.
	N 89°49' W, on the E and W center line of the S 1/2 of the NW 1/4 of the NW 1/4 of sec. 31.
	Across mesa.
7.50	Desc. from mesa.
10.00	Over level land.
16.50	Improved dirt road, 40 lks. wide, bears NE and SW.
20.005	The S-N-N 1/256 sec. cor. of secs. 31 and 36, on the W bdy. of the Tp.

T 6 N, R 11 E, Gila and Salt River Meridian, Arizona

CHAINS	GENERAL DESCRIPTION
	<p>The area surveyed within the north east portion of the township is located about 6 miles east of Punkin Center, Arizona. The elevation ranges from about 3300 to 4600 feet above sea level and is rolling in sections 2 and 3, and mountainous in section 12 lying on Horse Range Mesa. Walnut Creek flows westerly through sections 2 and 3, and Oak Creek flows westerly through section 12. The land is covered with scrub oak, pine and juniper timber. Access is provided by Greenback Valley Road from Punkin Center.</p> <p>The area surveyed within the south west portion of the township is located in the Tonto Basin about 4 miles southeast of Punkin Center. The elevation ranges from about 2200 to 2350 feet above sea level and is level to gently rolling. Tonto Creek flows southeasterly through section 31. Access is provided by Arizona State Highway 188 and secondary roads. Most of the residents are situated in the SE 1/4 of section 31.</p>

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Timothy J. Moore	Surveying Technician
Delbert L. Bybee	Surveying Technician
Robert M. Charboneau	Surveying Aid
Grant Lopresti	Surveying Aid

CERTIFICATE OF SURVEY

I, Duane R. Garoutte, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 13th day of January, 1984, and supplemental instructions dated April 18, 1985, I have dependently resurveyed a portion of the east, west and north boundaries and a portion of the subdivisional lines, and surveyed the subdivisions in sections 2, 3, 12, and 31, Township 6 North, Range 11 East, of the Gila and Salt River Meridian, in the State of Arizona which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 1, 1989  
(Date)

Duane R. Garoutte  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Arizona State Office  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the east, west and north boundaries and a portion of the subdivisional lines, and the survey of the subdivisions in sections 2, 3, 12, and 31, Township 6 North, Range 11 East, Gila and Salt River Meridian, Arizona, executed by Duane R. Garoutte, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUL 17 1990  
(Date)

James P. Kelly  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I Certify that the foregoing transcript of the field notes of the above-described surveys in T 6 N, R 11 E, Gila and Salt River Meridian, Arizona is a true copy of the original field notes.~~

~~\_\_\_\_\_  
(Date)~~

~~\_\_\_\_\_  
(Chief Cadastral Surveyor of Arizona)~~