

INDEX DIAGRAM

TOWNSHIP 5 NORTH, RANGE 11 EAST,

13	11	10	8	7	6						
4	6	34	5	25	4	22	3	18	2	15	1
33	31	24	20	17							
7	29	8	22	9	10	11	12				
29	27										
18	26	17	16	15	14	13					
19	20	21	22	23	24						
30	29	28	27	26	25						
31	32	33	34	35	36						

- Subdivision of sec. 2 pp. 36 - 42
- Subdivision of sec. 3 pp. 42 - 46
- Subdivision of sec. 5 pp. 46 - 51
- Subdivision of sec. 6 pp. 51 - 54
- Subdivision of sec. 8 pp. 54 - 61

T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS

The following field notes are those of the dependent resurvey of a portion of the west and north boundaries and a portion of the subdivisional lines, and the survey of the subdivisions in sections 2, 3, 5, 6, and 8, Township 5 North, Range 11 East, Gila and Salt River Meridian, Arizona.

Portions of the west and north boundaries and subdivisional lines were surveyed by Theo. F. White in 1881. A portion of the north boundary was resurveyed by Jesse B. Wright in 1907-08. Certain corners were remonumented by Louis D. Gilbert in 1970.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated January 13, 1984, for Group No. 647, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the official records. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of all lines were determined by observations on a U.S. Coast & Geodetic Survey triangulation network, confirmed by altitude observations on the sun and refer to the true meridian. Distances and angles were measured with a Zeiss Elta 4 instrument.

The geographic position of the northwest corner of section 6, as determined from a tie made to U.S. Coast and Geodetic Survey triangulation station "BENCH MARK F 20", located in unsurveyed Township 5 North, Range 10 East, is as follows:

NAD 27: Latitude: 33°48'42.75" N Longitude: 111°16'39.25" W

The mean magnetic declination as taken from quadrangle map "TONTON BASIN, ARIZ.", published in 1964 by U.S. Geological Survey is 14° E.

Dependent Resurvey of a Portion of the W Bdy. of
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

Restoring the 1881 survey by Theo. F. White

Dependent Resurvey of a Portion of the W Bdy.,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>Beginning at the cor. of secs. 1, 6, 7, and 12, on the W bdy. of the Tp., monumented with a mound of stone, 3 ft. base, 6 ins. high. No mkd. stone found. A steel fence post is near the cor. This position is harmoniously related to identified original cors., and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in the mound of stone, with cap mkd.</p> <div style="text-align: center;"> <p>T5N R10E R11E S1 S6 ----- S12 S7 1985</p> </div> <p>N 0°17' W, bet. secs. 1 and 6.</p> <p>Over rolling land.</p> <p>35.30 Draw, drains E.</p> <p>36.90 Arizona State Highway 188, 52 lks. wide, bears E and W.</p> <p>39.48 The 1/4 sec. cor. of secs. 1 and 6, monumented with a mound of stone, 3 ft. base, 1 1/2 ft. high. No mkd. stone found. A steel fence post is near the cor. This position is harmoniously related to identified original cors., and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5N R10E R11E 1/4 S1 S6 1985</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/>
---------------	---

Dependent Resurvey of a Portion of the W Bdy.,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p>N 0°10' W, beginning new measurement.</p> <p>15.00 Top of mesa.</p> <p>36.00 Over bottom land.</p> <p>39.82 The cor. of Tps. 5 and 6 N, Rs. 10 and 11 E, perpetuated by Jesse B. Wright in 1908, remonumented by Louis D. Gilbert in 1970, and recovered by John P. Bennett in 1980, an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T6N</td></tr> <tr><td>R10E</td><td>R11E</td></tr> <tr><td>S36</td><td>S31</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S1</td><td>S6</td></tr> <tr><td colspan="2">T5N</td></tr> <tr><td colspan="2">1970</td></tr> </table> </div> <p>from which the remaining bearing trees mkd. in 1908</p> <p style="margin-left: 40px;">A mesquite, 12 ins. diam., bears S 47° W, 23 lks. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A mesquite, 6 ins. diam., bears N 34 3/4° W, 59 lks. dist., no visible blaze. (1980-81 Record: N 33° W)</p> <p>Two steel fence post are near the cor.</p> <p>From this cor. U.S.C. & G.S. triangulation station "BENCH MARK F 20 1933", bears S 61°34' W, (forward bearing), 29.40 chs. dist., a standard bench mark, set flush in a 12 x 12 in. concrete post, projecting 6 ins. above ground, mkd. F 20 1933.</p> <hr style="width: 50%; margin: 20px auto;"/> <p style="text-align: center;">Dependent Resurvey of a Portion of the N Bdy., T 5 N, R 11 E, Gila and Salt River Mer., Arizona</p> <hr style="width: 50%; margin: 20px auto;"/> <p style="text-align: center;">Restoring the 1907-08 resurvey by Jesse B. Wright</p> <hr style="width: 50%; margin: 20px auto;"/> <p>From the 1/4 sec. cor. of secs. 1 and 36, reestablished by Wright in 1907, monumented with a granite stone, 13 x 8 x 5 ins., mkd. 1/4 on one face, lying on the surface at S side of a mound of stone, 2 1/2 ft. base, 1 ft. high.</p>	T6N		R10E	R11E	S36	S31			S1	S6	T5N		1970	
T6N															
R10E	R11E														
S36	S31														
S1	S6														
T5N															
1970															

Dependent Resurvey of a Portion of the N Bdy.,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R11E S36 1/4 — S1 T5N 1985</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p> <p>S 89°29' W, bet. secs. 1 and 36.</p> <p>Over rolling land.</p>
2.00	Draw, drains SW.
26.50	Draw, drains S.
39.73	<p>Point for the cor. of secs. 1, 2, 35, and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a monument 30 ins. long, composed of an iron post, 25 ins. long, 2 1/2 ins. diam., bonded to a magnetic poly breakaway base, 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T6N R11E S35 S36 — — S2 S1 T5N 1984</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>S 89°20' W, bet. secs. 2 and 35.</p>

Dependent Resurvey of a Portion of the N Bdy.,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	Over rolling land.
0.30	Edge of spur, slopes SW.
39.79	<p>The 1/4 sec. cor. of secs. 2 and 35, monumented with a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high. No mkd. stone or post found. This position is harmoniously related to identified original cors., and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set a monument 30 ins. long, composed of an iron post, 25 ins. long, 2 1/2 ins. diam., bonded to a magnetic poly breakaway base, 15 ins. in the ground, in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T6N R11E S35 1/4 _____ S2 T5N 1984</p> <p>from which</p> <p style="text-align: center;">A juniper, 6 ins. diam., bears S 42° E, 188 lks. dist., mkd. 1/4 S2 BT.</p> <hr style="width: 20%; margin: auto;"/> <p>N 89°14' W, beginning new measurement.</p>
20.235	<p>Point for the W 1/16 sec. cor. of secs. 2 and 35.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T6N R11E S35 W 1/16 _____ S2 T5N 1984</p>
40.47	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.</p> <p>The cor. of secs. 2, 3, 34, and 35, perpetuated by Wright in 1907, monumented with a granite stone, 15 x 8 x 6 ins., lying loose in a small mound of stone, mkd. with 4 notches on one edge and 2 notches on the opposite edge, from which the bearing tree mkd. in 1907</p>

Dependent Resurvey of a Portion of the N Bdy.,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p>A mesquite, 10 ins. diam., bears N 67° W, 173 lks. dist., with illegible scribe marks.</p> <p>At the cor. point</p> <p>Set a monument 30 ins. long, composed of an iron post, 25 ins. long, 2 1/2 ins. diam., bonded to a magnetic poly breakaway base, 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T6N</td><td>R11E</td></tr> <tr><td>S34</td><td>S35</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S3</td><td>S2</td></tr> <tr><td colspan="2" style="text-align: center;">T5N</td></tr> <tr><td colspan="2" style="text-align: center;">1984</td></tr> </table> </div> <p>Bury the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, W of cor.</p> <hr/> <p>S 89°55' W, bet. secs. 3 and 34.</p> <p>Desc. gradually over SW slope.</p> <p>20.08 The E 1/16 sec. cor. of secs. 3 and 34, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, projecting 9 ins. above ground and is accepted as a careful and faithful determination of the position of the cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 14 ins. in the ground, in a mound of stone, 4 ft. base, to top, with cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T6N</td><td>R11E</td></tr> <tr><td colspan="2" style="text-align: center;">S34</td></tr> <tr><td>E 1/16</td><td>_____</td></tr> <tr><td colspan="2" style="text-align: center;">S3</td></tr> <tr><td colspan="2" style="text-align: center;">T5N</td></tr> <tr><td colspan="2" style="text-align: center;">1984</td></tr> </table> </div> <p>Insert the rebar inside the aluminum post.</p> <p>The cor. is located at end of a fence extending W.</p> <hr/>	T6N	R11E	S34	S35			S3	S2	T5N		1984		T6N	R11E	S34		E 1/16	_____	S3		T5N		1984	
T6N	R11E																								
S34	S35																								
S3	S2																								
T5N																									
1984																									
T6N	R11E																								
S34																									
E 1/16	_____																								
S3																									
T5N																									
1984																									

Dependent Resurvey of a Portion of the N Bdy.,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p>S 89°37' W, beginning new measurement.</p> <p>Along fence.</p> <p>20.195 The 1/4 sec. cor. of secs. 3 and 34, perpetuated by Wright in 1907, monumented with a granite stone, 17 x 10 x 8 ins., mkd. 1/4 on top, lying in a mound of stone, 3 1/2 ft. base, 1 ft. high.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 12 ins. in the ground, in a mound of stone, 4 ft. base, to top, with cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T6N R11E S34 1/4 ——— S3 T5N 1984</p> </div> <p>Bury the mkd. stone alongside the aluminum post.</p> <p>The cor. is located S 45° E, 8 lks. dist., from cor. of fences extending E and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S 89°46' W, beginning new measurement.</p> <p>40.20 The cor. of secs. 3, 4, 33, and 34, perpetuated by Wright in 1907, monumented with a granite stone, 17 x 12 x 5 ins., firmly set, projecting 12 ins. above ground, mkd. with 3 notches on the E and W edges, with a mound of stone, 3 1/2 ft. base, 2 ft. high, N of cor.</p> <p>At the cor. point</p> <p>Set a monument 30 ins. long, composed of an iron post, 25 ins. long, 2 1/2 ins. diam., bonded to a magnetic poly breakaway base, 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T6N R11E S33 S34 ——— ——— S4 S3 T5N 1984</p> </div>
--------	---

Dependent Resurvey of a Portion of the N Bdy.,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p>from which</p> <p style="padding-left: 40px;">A mesquite, 5 ins. diam., bears S 35° E, 80 lks. dist., mkd. X BT on a limb 1 ft. above ground.</p> <p style="padding-left: 40px;">A mesquite, 14 ins. diam., bears S 88° W, 130 lks. dist., mkd. T5N R11E S4 BT.</p> <p>Bury the mkd. stone alongside the iron post.</p> <p>Remove mound of stone to the N and utilize the stones in raising a mound of stone, 4 ft. base, 2 1/2 ft. high, W of cor.</p> <hr/> <p>S 89°54' W, bet. secs. 4 and 33.</p> <p>Over gently rolling land.</p> <p>40.05 The 1/4 sec. cor. of secs. 4 and 33, perpetuated by Wright in 1907, determined from the remains of the original bearing trees</p> <p style="padding-left: 40px;">A juniper stump, 14 ins. diam., bears N 12 1/2° E, 208 lks. dist., no marks visible. (1907 Record: N 11° E)</p> <p style="padding-left: 40px;">A juniper stump, 12 ins. diam., bears N 52° E, 223 lks. dist., no marks visible.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 25 ins. in the ground, with cap mkd.</p> <div style="text-align: center; padding-left: 100px;"> <p>T6N R11E S33 1/4 ——— S4 T5N 1984</p> </div> <p>Raise a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, N of cor.</p> <p>The cor. is located on SE slope.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S 89°58' W, beginning new measurement.</p> <p>1.30 Edge of mesa, bears NE and SW.</p> <p>5.50 Desc. from mesa.</p>
--------	---

Dependent Resurvey of a Portion of the N Bdy.,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS													
40.14	<p>The cor. of secs. 4, 5, 32, and 33, perpetuated by Wright in 1907, remonumented by Louis D Gilbert in 1970, an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T6N</td> <td>R11E</td> </tr> <tr> <td>S32</td> <td>S33</td> </tr> <tr> <td>S5</td> <td>S4</td> </tr> <tr> <td colspan="2">T5N</td> </tr> <tr> <td colspan="2">1970</td> </tr> </table> </div> <p>from which the original bearing tree</p> <p style="padding-left: 40px;">A juniper, 18 ins. diam., bears S 69° W, 198 lks. dist., with illegible scribe marks visible on partially healed blaze. (1970 Record: S 79 1/4° W)</p> <p>A mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, is W of cor.</p> <hr/>	T6N	R11E	S32	S33	S5	S4	T5N		1970			
T6N	R11E												
S32	S33												
S5	S4												
T5N													
1970													
	<p>S 89°21' W, bet. secs. 5 and 32.</p>												
	<p>Over gently rolling land.</p>												
31.00	<p>Edge of mesa, bears NE and SW.</p>												
40.03	<p>Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist., based on the 1907 record; there is no remaining evidence of Wright's perpetuation of the original cor.</p> <p>Set a monument 30 ins. long, composed of an iron post, 25 ins. long, 2 1/2 ins. diam., bonded to a magnetic poly breakaway base, 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T6N</td> <td>R11E</td> </tr> <tr> <td>S32</td> <td></td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td>S5</td> <td></td> </tr> <tr> <td colspan="2">T5N</td> </tr> <tr> <td colspan="2">1984</td> </tr> </table> </div> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p>	T6N	R11E	S32		1/4	_____	S5		T5N		1984	
T6N	R11E												
S32													
1/4	_____												
S5													
T5N													
1984													

Dependent Resurvey of a Portion of the N Bdy.,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>From this cor., a local monument, bears S 66°00' E, 6.4 lks. dist., a rebar, 5/8 in. diam., flush with the ground, with aluminum cap attached and mkd. 1/4 32 5 LS 6713 1970. This position was erroneously determined by Gordon H. Long, LS 6713, in 1970 and is not utilized in the course of this survey.</p>
	<p>S 89°19' W, beginning new measurement.</p>
3.00	<p>Desc. from mesa.</p>
19.30	<p>Improved dirt road, 50 lks. wide, on curve, bears SE from NW; over nearly level land.</p>
19.99	<p>Point for the W 1/16 sec. cor. of secs. 5 and 32.</p> <p>Set a monument 30 ins. long, composed of an iron post, 25 ins. long, 2 1/2 ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T6N R11E S32 W 1/16 _____ S5 T5N 1984</p>
	<p>Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, N of cor.</p>
	<p>Set a steel fence post near the cor.</p>
	<p>From this cor., a local monument, bears S 63°00' E, 2.8 lks. dist., a rebar, 5/8 in. diam., flush with the ground, with aluminum cap attached and mkd. W 1/16 32/5 LS 6713. This cor. established by Gordon H. Long, LS 6713, in 1970 is not utilized in the course of this survey because he erroneously determined the position for the 1/4 sec. cor. of secs. 5 and 32, hereinbefore described.</p>
39.98	<p>The cor. of secs. 5, 6, 31, and 32, perpetuated by Wright in 1907-08, remonumented by Louis D. Gilbert in 1970, an iron post, 2 1/2 ins. diam., firmly set 5 ins. below ground, with brass cap mkd.</p>
	<p style="text-align: center;">T6N R11E S31 S32 ----- S6 S5 T5N 1970</p>

Dependent Resurvey of a Portion of the N Bdy.,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which the bearing tree mkd. in 1907-08</p> <p>A mesquite, 10 ins. diam., bears N 8° W, 133 lks. dist., with scribe marks N R11E visible on opened blaze. (Record: N 9 1/2° W)</p> <p>The cor. is located on S edge of driveway, 20 lks. wide, bears NE and SW.</p> <hr/> <p>N 89°32' W, bet. secs. 6 and 31.</p> <p>Over level land.</p>
6.30	Along fence.
10.00	<p>The E-E 1/64 sec. cor. of secs. 6 and 31, established by James H. Lange, LS 4245, in 1963, monumented with an iron pipe, 18 ins. long, 1 in. diam., firmly set, projecting 2 ins. above ground and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S31 E-E 1/64 S6 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert the iron pipe inside the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located 1 lk. E of cor. of fences extending N, E and W.</p> <hr/> <p>N 89°29' W, beginning new measurement.</p> <p>Along fence.</p>
9.87	An iron pipe, 1 in. diam., firmly set, projecting 2 ins. above ground at cor. of fences extending N, E and W.
10.00	Point for the E 1/16 sec. cor. of secs. 6 and 31.

Dependent Resurvey of a Portion of the N Bdy.,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.</p>
	<p style="text-align: center;">T6N R11E S31 E 1/16 ——— S6 T5N 1984</p>
	<p>The cor. is located in a fence, bears E and W.</p>
	<p>Along fence.</p>
19.36	<p>End of fence.</p>
28.90	<p>Point selected for the witness cor. to the 1/4 sec. cor. of secs. 6 and 31, falls on a levee, bears S 30° E and N 30° W.</p> <p>Set a monument 30 ins. long, composed of an iron post, 25 ins. long, 2 1/2 ins. diam., bonded to a magnetic poly breakaway base, 20 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">W C T6N R11E S31 1/4 ←—— S6 T5N 1984</p>
	<p>Over Tonto Creek bottom, subject to seasonal flooding.</p>
30.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist., based on the 1908 record, falls in Tonto Creek, 200 lks. wide, course S 30° E, where it is impracticable to establish a permanent monument; there is no remaining evidence of Wright's perpetuation of the original cor.</p>
	<p style="text-align: center;">—————</p> <p>N 89°28' W, beginning new measurement.</p>
10.20	<p>The E-W 1/64 sec. cor. of secs. 6 and 31, established by James H. Lange, LS 4245, in 1963, monumented with an iron pipe, 18 ins. long, 1 in. diam., firmly set 18 ins. below ground and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p>

Dependent Resurvey of a Portion of the N Bdy.,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>Set a monument 30 ins. long, composed of an iron post, 25 ins. long, 2 1/2 ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S31 E-W 1/64 S6 1984</p> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 12 ins. diam., bears S 14° E, 88.5 lks. dist., mkd. E-W 1/64 S6 BT.</p> <p>Insert the iron pipe inside the iron post.</p> <p>Set a steel fence post near the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 89°28' W, beginning new measurement.</p>
<p>10.20</p>	<p>Point for the W 1/16 sec. cor. of secs. 6 and 31.</p> <p>Set a monument 30 ins. long, composed of an iron post, 25 ins. long, 2 1/2 ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R11E S31 W 1/16 ——— S6 T5N 1984</p> <p>from which</p> <p style="padding-left: 40px;">A cottonwood, 21 ins. diam., bears N 13° E, 67 lks. dist., mkd. W 1/16 S31 BT.</p> <p style="padding-left: 40px;">A cottonwood, 18 ins. diam., bears N 33° W, 48 lks. dist., mkd. W 1/16 S31 BT.</p>
<p>30.11</p>	<p>The cor. of Tps. 5 and 6 N, Rs. 10 and 11 E.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivisional Lines, T 5 N, R 11 E, Gila and Salt River Mer., Arizona</p> <hr/> <p style="text-align: center;">Restoring the 1881 survey by Theo. F. White</p> <hr/>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p>From the cor. of secs. 1, 2, 11, and 12, at the S side of a mound of stone, 3 1/2 ft. base, 2 ft. high. The rock, 14 x 8 x 8 ins., with only 2 marks visible as reported by the Tonto National Forest in 1966 being set in ground south of mound was not found. This position is harmoniously related to identified original cors., and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set a monument 30 ins. long, composed of an iron post, 25 ins. long, 2 1/2 ins. diam., bonded to a magnetic poly breakaway base, 12 ins. in the ground, in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T5N R11E</td> </tr> <tr> <td>S2</td> <td>S1</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S11</td> <td>S12</td> </tr> <tr> <td colspan="2">1984</td> </tr> </table> </div> <p>N 0°04' E, bet. secs. 1 and 2.</p> <p>Over mesa land sloping generally SW.</p> <p>40.16 The 1/4 sec. cor. of secs. 1 and 2, monumented with a granite stone, 12 x 12 x 12 ins., mkd. 1/4 on N face, firmly set 8 ins. in the ground, in a flat mound of stone, 1 1/2 ft. base, from which the original bearing trees</p> <p style="padding-left: 40px;">A dead mesquite, 8 ins. diam., bears S 15° E, 78 lks. dist., no marks visible. (Record: 76 lks.)</p> <p style="padding-left: 40px;">A dead palo verde, 16 ins. diam., bears N 50° W, 28 lks. dist., no marks visible. (Record: N 40° W)</p> <p>At the cor. point</p> <p>Set a monument 30 ins. long, composed of an iron post, 25 ins. long, 2 1/2 ins. diam., bonded to a magnetic poly breakaway base, 12 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T5N R11E</td> </tr> <tr> <td colspan="2">1/4</td> </tr> <tr> <td>S2</td> <td>S1</td> </tr> <tr> <td colspan="2">1984</td> </tr> </table> </div>	T5N R11E		S2	S1	<hr/>		S11	S12	1984		T5N R11E		1/4		S2	S1	1984	
T5N R11E																			
S2	S1																		
<hr/>																			
S11	S12																		
1984																			
T5N R11E																			
1/4																			
S2	S1																		
1984																			

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A granite boulder, 2 x 1 1/2 x 1 ft. above ground, bears S 69° E, 8.2 lks. dist., mkd. X BO on W face.</p> <p>A granite boulder, 4 x 2 1/2 x 1 ft. above ground, bears S 47° W, 52 lks. dist., mkd. X BO on top.</p> <p>Bury the original stone in the mound.</p> <hr/> <p>N 0°01' E, beginning new measurement.</p>
39.80	<p>The cor. of secs. 1, 2, 35, and 36, on the N bdy. of the Tp.</p> <hr/>
	<p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>S 89°26' W, bet. secs. 2 and 11.</p> <p>Over mesa land sloping generally SW.</p>
39.64	<p>Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a monument 30 ins. long, composed of an iron post, 25 ins. long, 2 1/2 ins. diam., bonded to a magnetic poly breakaway base, 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E S2 1/4 _____ S11 1984</p>
79.28	<p>Set a steel fence post near the cor.</p> <p>The cor. of secs. 2, 3, 10, and 11, monumented with a mound of stone, 3 ft. base, 1 1/2 ft. high. No mkd. stone found. This position is harmoniously related to identified original cors., and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set a monument 30 ins. long, composed of an iron post, 25 ins. long, 2 1/2 ins. diam., bonded to a magnetic poly breakaway base, 8 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T5N R11E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S3</td> <td style="padding: 2px 5px;">S2</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; border-bottom: 1px solid black;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S10</td> <td style="padding: 2px 5px;">S11</td> </tr> <tr> <td colspan="2" style="padding: 2px 5px;">1984</td> </tr> </table>	T5N R11E		S3	S2			S10	S11	1984	
T5N R11E											
S3	S2										
S10	S11										
1984											
40.49	<p>N 0°31'E, bet. secs. 2 and 3.</p> <p>Over mesa land sloping W.</p> <p>The 1/4 sec. cor. of secs. 2 and 3, monumented with a mound of stone, 3 1/2 ft. base, 2 ft. high. No mkd. stone found. This position is harmoniously related to identified original cors., and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set a monument 30 ins. long, composed of an iron post, 25 ins. long, 2 1/2 ins. diam., bonded to a magnetic poly breakaway base, 8 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p>										
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T5N R11E</td> </tr> <tr> <td colspan="2" style="padding: 2px 5px;">1/4</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S3</td> <td style="padding: 2px 5px;">S2</td> </tr> <tr> <td colspan="2" style="padding: 2px 5px;">1984</td> </tr> </table>	T5N R11E		1/4		S3	S2	1984			
T5N R11E											
1/4											
S3	S2										
1984											
6.00	<p>N 1°51' W beginning new measurement.</p> <p>Improved dirt road, 30 lks. wide, bears N 80° E and S 80° W.</p>										
14.00	<p>Cor. of fences extending N and E.</p>										
15.09	<p>The N-S-N 1/256 sec. cor. of secs. 2 and 3, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, projecting 1 in. above ground and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">N-S-N</td> </tr> <tr> <td colspan="2" style="padding: 2px 5px;">1/256</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S3</td> <td style="padding: 2px 5px;">S2</td> </tr> <tr> <td colspan="2" style="padding: 2px 5px;">1985</td> </tr> </table>	N-S-N		1/256		S3	S2	1985			
N-S-N											
1/256											
S3	S2										
1985											

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert the rebar inside the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located in a fence, bears N and S.</p> <hr/> <p>N 1°32' W, beginning new measurement.</p>
0.75	<p>Desc. abruptly from mesa.</p>
5.01	<p>The N 1/16 sec. cor. of secs. 2 and 3, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, projecting 1 in. above ground and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E N 1/16 S3 S2 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert the rebar inside the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located in a fence, bears N and S.</p> <hr/>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p>N 1°38' W, beginning new measurement.</p> <p>Along fence.</p> <p>2.50 Greenback Creek, 50 lks. wide, course N 60° W.</p> <p>13.53 Cor. of fences extending E and S.</p> <p>15.04 The N-N-N 1/256 sec. cor. of secs. 2 and 3, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, projecting 8 ins. above ground, in a mound of stone, 1 1/2 ft. base, to top and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N-N-N 1/256 S3 S2 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert the rebar inside the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 2°42'W, beginning new measurement.</p> <p>5.22 The cor. of secs. 2, 3, 34, and 35, on the N bdy. of the Tp.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>N 89°35' W, bet. secs. 3 and 10.</p> <p>Over mesa land sloping W.</p>
--------	--

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
40.18	<p>The 1/4 sec. cor. of secs. 3 and 10, monumented with a mound of stone, 3 1/2 ft. base, 6 ins. high. No mkd. stone found. This position is harmoniously related to identified original cors., and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E S3 1/4 ——— S10 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N 89°10' W, beginning new measurement.</p>
40.38	<p>The cor. of secs. 3, 4, 9, and 10, monumented with a mound of stone, 3 ft. base, 1 ft. high. No mkd. stone found. This position is harmoniously related to identified original cors., and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E S4 S3 ————— S9 S10 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Raise a mound of stone, 4 ft. base, 3 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>N 0°38' W, bet. secs. 3 and 4.</p> <p>Over mesa land sloping W.</p> <p>38.50 Improved dirt road, 30 lks. wide, bears E and N 80° W.</p> <p>39.86 Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T5N R11E 1/4 S4 S3 1985</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p> <p>66.80 Greenback Creek, 30 lks. wide, course W.</p> <p>79.63 The cor. of secs. 3, 4, 33, and 34, on the N bdy. of the Tp.</p> <hr/> <p>From the cor. of secs. 8, 9, 16, and 17, remonumented by Louis D. Gilbert in 1970, an iron post, 2 1/2 ins. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T5N R11E S8 S9 ----- S17 S16 1970</p> </div> <p>A mound of stone, 4 ft. base, 1 1/2 ft. high, is S of cor.</p> <p>A steel fence post is near the cor.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p>
--------	---

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	N 0°07' W, bet. secs. 8 and 9.
	Over mesa land sloping generally W.
20.075	Point for the S 1/16 sec. cor. of secs. 8 and 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T5N R11E
	S 1/16
	S8 S9
	1985
	from which
	A sawed power pole, 8 ins. diam., projecting 4 ins. above ground, with spike in center, bears S 4°26' E, 263 lks. dist.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
37.20	Improved dirt road, 35 lks. wide, bears S 50° E and N 50° W.
40.15	The 1/4 sec. cor. of secs. 8 and 9, remonumented by Louis D. Gilbert in 1970, an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 1 1/2 ft. base, 6 ins. high, with brass cap mkd.
	T5N R11E
	1/4
	S8 S9
	1970
	A mound of stone, 3 ft. base, 1 ft. high, is S of cor.
	A steel fence post is near the cor.
	Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	N 0°05' W, beginning new measurement.
20.07	<p>Point for the N 1/16 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E N 1/16 S8 S9 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. gray colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
40.14	<p>The cor. of secs. 4, 5, 8, and 9, remonumented by Louis D. Gilbert in 1970, an iron post, 2 1/2 ins. diam., firmly set, projecting 6 in. above ground, in a mound of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E S5 S4 ----- S8 S9 1970</p> <p>A mound of stone, 2 1/2 ft. base, 1 ft. high, is N of cor.</p> <p>A steel fence post is near the cor.</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W of cor.</p>
40.18	<p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>N 89°46' W, bet. secs. 4 and 9.</p> <p>Over gently rolling, mesa land.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E S4 1/4 _____ S9 1985</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p>
80.36	The cor. of secs. 4, 5, 8, and 9.
	<hr/> <p>N 0°28' W, bet. secs. 4 and 5.</p> <p>Over gently rolling, mesa land.</p>
0.50	Desc. from mesa.
5.30	Improved dirt road, 30 lks. wide, bears N 55° E and S 55° W.
20.02	Point for the S 1/16 sec. cor. of secs. 4 and 5.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a 5 ft. steel fence post, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T5N R11E S 1/16 S5 S4 1985</p>
	<p>from which</p> <p style="padding-left: 40px;">A mesquite, 8 ins. diam., bears N 42 1/2° W, 125 lks. dist., mkd. S 1/16 S5 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located 10 lks. E of Greenback Creek, 80 lks. wide, course S 10° W.</p>
30.50	Edge of mesa, bears NE and SW.
40.04	<p>The 1/4 sec. cor. of secs. 4 and 5, remonumented by Louis D. Gilbert in 1970, an iron post, 2 1/2 ins. diam., firmly set, projecting 24 ins. above ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p style="text-align: center;">T5N R11E 1/4 S5 S4 1970</p> <hr style="width: 30%; margin: auto;"/> <p>N 0°34' W, beginning new measurement.</p> <p>39.17 The cor. of secs. 4, 5, 32, and 33, on the N bdy. of the Tp.</p> <hr style="width: 30%; margin: auto;"/> <p>From the cor. of secs. 17, 18, 19, and 20, remonumented by Louis D. Gilbert in 1970, an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, in a small mound of stone, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E S18 S17 <hr style="width: 20%; margin: auto;"/>S19 S20 1970</p> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 14 ins. diam., bears S 55° W, 162 lks. dist., no remaining evidence of the mkd. branch called for in 1970. (Record: S 56° W)</p> <p>N 0°23' W, bet. secs. 17 and 18.</p> <p>Over gently rolling land.</p> <p>25.50 Arizona State Highway 188, 54 lks. wide, bears S 20° E and N 20° W.</p> <p>35.00 Over level land.</p> <p>40.24 Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E 1/4 S18 S17 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
--------	--

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS											
80.48	<p>Point for the cor. of secs. 7, 8, 17, and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a 5 ft. steel fence post, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T5N R11E</td> </tr> <tr> <td>S7</td> <td>S8</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> <tr> <td colspan="2">1985</td> </tr> </table> </div> <p>from which</p> <p>A mesquite, 8 ins. diam., bears S 49 1/2° W, 138 lks. dist., mkd. T5N R11E S18 BT.</p> <p>A mesquite, 8 ins. diam., bears N 47° W, 94 lks. dist., mkd. T5N R11E S7 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. blue colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this cor., a local monument, bears S 84°00' E, 50.2 lks. dist., monumented with a rebar, 1/2 in. diam., firmly set 2 ins. below ground, in a small flat mound of stone, with aluminum cap mkd. 7 8 17 18 LS 6713 1970. This position was erroneously determined by Gordon H. Long, LS 6713, in 1970 and is not utilized in the course of this survey.</p> <p>The cor. is located N 41°E, 8.99 chs. dist., from a windmill.</p>	T5N R11E		S7	S8	<hr/>		S18	S17	1985	
T5N R11E											
S7	S8										
<hr/>											
S18	S17										
1985											
	<p>From the cor. of secs. 8, 9, 16, and 17.</p>										
	<p>S 89°51' W bet. secs. 8 and 17.</p>										
	<p>Over gently rolling, mesa land.</p>										
6.48	<p>Along fence.</p>										
8.00	<p>Desc. from mesa.</p>										
20.01	<p>Point for the E 1/16 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a small mound of stone, with brass cap mkd.</p>										

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p style="text-align: center;">T5N R11E S8 E 1/16 _____ S17 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p> <p>From this cor., a local monument, bears N 86°00' W, 7.2 lks. dist., monumented with a rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground, with aluminum cap mkd. 1970 E 1/16 8/17 LS 6713. This cor. established by Gordon H. Long, LS 6713, in 1970 is not utilized in the course of this survey because he erroneously determined the position for the 1/4 sec. cor. of secs. 8 and 17, hereinafter described.</p> <p>The cor. is located S 51° E, 39 lks. dist., from cor. of fences extending N, E, and W.</p> <p>24.00 Over level land.</p> <p>40.02 Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E S8 1/4 _____ S17 1985</p> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 6 ins. diam., bears N 39 1/2° E, 36 lks. dist., mkd. 1/4 S8 BT.</p> <p style="padding-left: 40px;">A mesquite, 6 ins. diam., bears S 30° W, 29 lks. dist., mkd. 1/4 S17 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
--------	--

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p>From this cor., a local monument, bears N 89°00' W, 18.1 lks. dist., monumented with a rebar, 1/2 in. diam., firmly set flush with the ground, with aluminum cap mkd. 1970 1/4 8/17 LS 6713. This position was erroneously determined by Gordon H. Long, LS 6713, in 1970 and is not utilized in the course of this survey.</p> <p>The cor. is located 35 lks. S of a fence, bears E and W.</p>
44.40	<p>Cor. of fences bears N, 16 lks. dist.; fences extend N and E; over bottom land.</p>
60.03	<p>Point for the W 1/16 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a 5 ft. steel fence post, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E S8 W 1/16 ——— S17 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
78.00	<p>Tonto Creek, 150 lks. wide, course S.</p>
78.70	<p>Over level land.</p>
80.04	<p>The cor. of secs. 7, 8, 17, and 18.</p> <hr/> <p>S 89°35' W, bet. secs. 7 and 18.</p> <p>Over level land.</p>
12.50	<p>A dirt road, bears N and S; over gently rolling land.</p>
14.10	<p>Arizona State Highway 188, 57 lks. wide, bears N 4° E and S 4° W.</p>
40.04	<p>The 1/4 sec. cor. of secs. 7 and 18, remonumented by Louis D. Gilbert in 1970, an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E S7 1/4 ——— S18 1970</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A mound of stone, 3 ft. base, 1 ft. high, is N of cor.</p> <p>A steel fence post is near the cor.</p>
	<hr/> <p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N 0°25' W, bet. secs. 7 and 8.</p> <p>Over level land.</p>
20.12	<p>Point for the S 1/16 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a 5 ft. steel fence post, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E S 1/16 S7 S8 1985</p> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 6 ins. diam., bears S 38 1/2° E, 61 lks. dist., mkd. S 1/16 S8 BT.</p> <p style="padding-left: 40px;">A mesquite, 7 ins. diam., bears S 86° W, 116 lks. dist., mkd. S 1/16 S7 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located N 48° E, 10.88 chs. dist., from a windmill.</p>
30.60	<p>Improved dirt road, 50 lks. wide, bears E and W.</p>
40.24	<p>The 1/4 sec. cor. of secs. 7 and 8, remonumented by Louis D. Gilbert in 1970, an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E 1/4 S7 S8 1970</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A dead sycamore, 26 ins. diam., bears S 78° E, 89 lks. dist., no marks.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS											
	<p>A partly burned ash, 27 ins. diam., bears S 15 1/2° E, 110 lks. dist., no marks. (Record: S 16 1/2° E)</p> <p>and the bearing trees mkd. in 1970</p> <p>A dead sycamore, 24 ins. diam., bears N 89 1/2° E, 85 lks. dist., no marks. (Record: N 88° E)</p> <p>A mesquite, 14 ins. diam., bears S 4° W, 61 lks. dist., with scribe marks 1/4 S7 BT visible on partially healed blaze. (Record: S 5° W)</p> <hr/> <p>N 0°17' E, beginning new measurement.</p>										
20.00	Over bottom land.										
39.59	<p>Point for the cor. of secs. 5, 6, 7, and 8, at proportionate dist.; there is no remaining evidence of the original witness cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a 5 ft. steel fence post, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table border="1"> <tr> <td colspan="2">T5N R11E</td> </tr> <tr> <td>S6</td> <td>S5</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S7</td> <td>S8</td> </tr> <tr> <td colspan="2">1985</td> </tr> </table> </div> <p>from which</p> <p>A cottonwood, 12 ins. diam., bears N 17 1/2° E, 333 lks. dist., mkd. T5N R11E S5 BT.</p> <p>A mesquite, 16 ins. diam., bears N 48° W, 421 lks. dist., mkd. T5N R11E S6 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>S 89°36' W, bet. secs. 5 and 8.</p> <p>Over gently rolling, mesa land.</p>	T5N R11E		S6	S5	<hr/>		S7	S8	1985	
T5N R11E											
S6	S5										
<hr/>											
S7	S8										
1985											
0.40	Desc. from mesa.										

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
8.10	Improved dirt road, 30 lks. wide, bears N 55° E and S 55° W; over level land.
19.15	Greenback Creek, 70 lks. wide, course SW.
19.995	<p>Point for the E 1/16 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a 4 ft. steel fence post, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E S5 E 1/16 ——— S8 1985</p> <p>from which</p> <p style="text-align: center;">A mesquite, 8 ins. diam., bears N 9 1/4° W, 171 lks. dist., mkd. E 1/16 S5 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
21.00	Improved dirt road, 35 lks. wide, bears S 15° E and N 15° W.
26.77	Cor. of fences extending N and W; along fence.
39.99	<p>The 1/4 sec. cor. of secs. 5 and 8, monumented with a rebar, 23 ins. long, 1/2 in. diam., firmly set flush with the ground, with aluminum cap mkd. 1/4 5/8 LS 6713 1970 and is accepted as a careful and faithful reestablishment of the position of the original cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E S5 1/4 ——— S8 1985</p> <p>from which</p> <p style="text-align: center;">A power pole, 9 ins. diam., bears N 4 1/4° E, 46.0 lks. dist.</p> <p style="text-align: center;">A power pole, 9 ins. diam., bears N 87° E, 46.3 lks. dist.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert the rebar inside the stainless steel post.</p> <p>The cor. is located S 50° W, 2.5 lks. dist., from cor. of fences extending N, E, and S 35° E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S 89°26' W, beginning new measurement.</p>
18.00	Over bottom land.
20.00	<p>Point for the W 1/16 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a 5 ft. steel fence post, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T5N R11E</p> <p>S5</p> <p>W 1/16 ———</p> <p>S8</p> <p>1985</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. purple colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p>
36.50	Tonto Creek, 100 lks. wide, course SE.
40.00	<p>The cor. of secs. 5, 6, 7, and 8.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N 89°38' W, bet. secs. 6 and 7.</p> <p>Over bottom land.</p>
14.00	Over gently rolling land.
16.50	Edge of mesa, bears SE and NW.
38.15	Arizona State Highway 188, 45 lks. wide, bears S 14° E and N 14° W.
39.91	<p>The 1/4 sec. cor. of secs. 6 and 7, remonumented by Louis D. Gilbert in 1970, an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T5N R11E 1/4 S7 S6 1970</p> <p>Remark the cap to read:</p> <p style="text-align: center;">T5N R11E S6 1/4 _____ S7 1985 1970</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A mesquite, 12 ins. diam., bears N 24° E, 178 lks. dist., no marks. (Record: N 32° E, 181 lks.)</p> <p style="padding-left: 40px;">A dead and down mesquite, 8 ins. diam., bears S 24 3/4° E, 325 lks. dist., no marks. (Record: S 34° E, 323 lks.)</p> <p>A mound of stone, 2 1/2 ft. base, 1 ft. high, is N of cor.</p> <p style="text-align: center;">_____</p> <p>N 89°51' W, beginning new measurement.</p>
40.85	<p>The cor. of secs. 1, 6, 7, and 12, on the W bdy. of the Tp.</p> <hr/> <p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N 0°39' W, bet. secs. 5, and 6.</p> <p>Over bottom land.</p>
3.50	Tonto Creek, 100 lks. wide, course SE.
17.00	Over level land.
19.795	<p>Point for the S 1/16 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E S 1/16 S6 S5 1985</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p>from which</p> <p style="padding-left: 40px;">A mesquite, 8 ins. diam., bears N 13 1/2° E, 125 lks. dist., mkd. S 1/16 S5 BT.</p> <p style="padding-left: 40px;">A mesquite, 8 ins. diam., bears S 74 1/4° W, 21.5 lks. dist., mkd. S 1/16 S6 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. silver colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>39.59 The 1/4 sec. cor. of secs. 5 and 6, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set 3 ins. below the ground, with aluminum cap mkd. 1/4 6/5 LS 6713 1970 and is accepted as a careful and faithful reestablishment of the position of the original cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E 1/4 S6 S5 1985</p> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 8 ins. diam., bears N 31 1/4° E, 13 lks. dist., mkd. 1/4 S5 BT.</p> <p style="padding-left: 40px;">An oak, 14 ins. diam., bears N 3 1/2° W, 33 lks. dist., mkd. 1/4 S6 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. blue colored plastic case beneath the stainless steel post.</p> <p>Insert the rebar inside the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located 30 lks. E of a ditch, 30 lks. wide, drains S 10° E.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/>
--------	---

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p>N 0°27' W, beginning new measurement.</p>
19.82	<p>Point for the N 1/16 sec. cor. of secs. 5 and 6.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. below the ground, with cap mkd.</p> <p style="text-align: center;">T5N R11E N 1/16 S6 S5 1985</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, bears S 51°41' W, 144.1 ft. dist., with brass cap mkd. T5N R11E N 1/16 S6 RM 144.1 FT. 1985, and an arrow pointing to the cor.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 23 ins. in the ground, for a reference monument, bears N 82°01' W, 178.7 ft. dist., with brass cap mkd. T5N R11E N 1/16 S6 RM 178.7 FT. 1985, and an arrow pointing to the cor.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>The cor. is located in a cultivated field.</p>
39.35	<p>The cor. of secs. 5, 6, 31, and 32, on the N bdy. of the Tp.</p> <hr/> <p style="text-align: center;">Survey of Subdivisions in Section 2 T 5 N, R 11 E, Gila and Salt River Mer., Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 2 and 11.</p> <p>N 0°05' W, on the N and S center line of sec. 2.</p> <p>Over mesa land sloping SW, changing to W.</p>

Survey of Subdivisions in Section 2
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
40.325	<p>Point for the center 1/4 sec. cor. of sec. 2, at intersection with the E and W center line of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E C 1/4 S2 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p>
57.50	<p>Greenback Creek, 30 lks. wide, course S 75° W.</p>
60.05	<p>Point for the center N 1/16 sec. cor. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E C N 1/16 S 2 C 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p>
79.89	<p>The 1/4 sec. cor. of secs. 2 and 35, on the N bdy. of the Tp.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 2.</p> <p>S 89°40' W, on the E and W center line of sec. 2.</p> <p>Over mesa land sloping generally W.</p>

Survey of Subdivisions in Section 2
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
39.73	The center 1/4 sec. cor. of sec. 2.
59.345	Point for the center W 1/16 sec. cor. of sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T5N R11E W 1/16 C ————— C S 2 1985</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.
	Set a steel fence post near the cor.
78.96	The 1/4 sec. cor. of secs. 2 and 3.
	<p style="text-align: center;">NW 1/4 of Sec. 2</p> <hr style="width: 20%; margin: auto;"/>
	From the center W 1/16 sec. cor. of sec. 2
	N 0°58' W, on the N and S center line of the NW 1/4 of sec. 2.
12.30	Improved dirt road, 30 lks. wide, bears N 20° E and S 30° W.
14.00	Desc. from mesa.
14.93	Point for the center N-S-NW 1/256 sec. cor. of sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a 5 ft. steel fence post, with brass cap mkd.
	<p style="text-align: center;">S 2 C-N-S-NW 1/256 1985</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
17.10	Greenback Creek, 30 lks. wide, course W.

Survey of Subdivisions in Section 2
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
19.905	<p>Point for the NW 1/16 sec. cor. of sec. 2, at intersection with the E and W center line of the NW 1/4 of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E NW 1/16 S2 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
29.839	<p>Point for the center N-NW 1/64 sec. cor. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a 5 ft. steel fence post, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S 2 C-N-NW 1/64 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located on N side of irrigation ditch, drains W, and 37.5 lks. E of a fence, bears N and S.</p>
34.806	<p>Point for the center N-N-NW 1/256 sec. cor. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 2 C-N-N-NW 1/256 1985</p>

Survey of Subdivisions in Section 2
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.
	Set a steel fence post near the cor.
	The cor. is located 3.5 lks. E of a fence, bears N and S.
39.945	The W 1/16 sec. cor. of secs. 2 and 35, on the N bdy. of the Tp.
	From the center N 1/16 sec. cor. of sec. 2.
	N 89°49' W, on the E and W center line of the NW 1/4 of sec. 2.
9.96	Point for the center E-NW 1/64 sec. cor. of sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.
	S 2
	C-E-N-NW
	1/64
	1985
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
	Set a steel fence post near the cor.
19.92	The NW 1/16 sec. cor. of sec. 2.
35.50	Greenback Creek, 50 lks. wide, course NW.
39.815	The N 1/16 sec. cor. of secs. 2 and 3.
	NE 1/4 of the NW 1/4 of sec. 2
	From the center E-NW 1/64 sec. cor. of sec. 2.
	N 0°31.5' W, on a portion of the N and S center line of the NE 1/4 of the NW 1/4 of sec. 2.
9.898	Point for the NE-NW 1/64 sec. cor. of sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of Subdivisions in Section 2
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">S 2 NE-NW 1/64 1985</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor. Set a steel fence post near the cor.</p> <hr/> <p>N 89°36.8' W, on a portion of the E and W center line of the NE 1/4 of the NW 1/4 of sec. 2.</p>
10.038	<p>The center N-NW 1/64 sec. cor. of sec. 2.</p> <hr/> <p style="text-align: center;">SE 1/4 of the NW 1/4 of sec. 2</p> <hr/> <p>From the center E-NW 1/64 sec. cor. of sec. 2. S 0°31.5' E, on a portion of the N and S center line of the SE 1/4 of the NW 1/4 of sec. 2.</p>
2.50	Greenback Creek, 20 lks. wide, course irregularly W.
4.953	<p>Point for the center N-SE-NW 1/256 sec. cor. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S 2 C-N-SE-NW 1/256 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor. Set a steel fence post near the cor.</p> <hr/> <p>N 89°56.8' W, on the E and W center line of the NW 1/4 of the SE 1/4 of the NW 1/4 of sec. 2.</p>
4.00	Improved dirt road, bears N 80° E and S 80° W.
9.923	The center N-S-NW 1/256 sec. cor. of sec. 2.

Survey of Subdivisions in Section 2
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
19.845	<p style="text-align: center;">SW 1/4 of the NW 1/4 of sec. 2</p> <hr/> <p>N 89°55' W, on the E and W center line of the N 1/2 of the SW 1/4 of the NW 1/4 of sec. 2.</p> <p>The N-S-N 1/256 sec. cor. of secs. 2 and 3.</p>
20.075	<p style="text-align: center;">NW 1/4 of the NW 1/4 of sec. 2</p> <hr/> <p>From the center N-N-NW 1/256 sec. cor. of sec. 2.</p> <p>N 89°27' W, on the E and W center line of the N 1/2 of the NW 1/4 of the NW 1/4 of sec. 2.</p> <p>The N-N-N 1/256 sec. cor. of secs. 2 and 3.</p>
	<p style="text-align: center;">Survey of Subdivisions in Section 3 T 5 N, R 11 E, Gila and Salt River Mer., Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 10.</p> <p>N 0°48' W, on the N and S center line of sec. 3.</p> <p>Over mesa land sloping W.</p> <p>36.00 Improved dirt road, 40 lks. wide, bears N 60° E and S 60° W.</p> <p>40.28 The center 1/4 of sec. 3, monumented with a rebar, 17 ins. long, 1/2 in. diam., firmly set, projecting 3 ins. above ground and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E C 1/4 S3 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>

Survey of Subdivisions in Section 3
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Insert the rebar inside the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°44' W, beginning new measurement.</p>
20.045	<p>The center N 1/16 sec. cor. of sec. 3, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, projecting 8 ins. above ground, and surrounded by mound of stone, 2 1/2 ft. base, 6 ins. high and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T5N R11E</p> <p style="margin: 0;">C</p> <p style="margin: 0;">N 1/16 S 3</p> <p style="margin: 0;">C</p> <p>1985</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert the rebar inside the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°40' W, beginning new measurement.</p>
0.20	<p>End of dirt road, 15 lks. wide, bears E.</p>
6.50	<p>Greenback Creek, 30 lks. wide, course irregularly W.</p>
20.055	<p>The 1/4 sec. cor. of secs. 3 and 34, on the N bdy. of the Tp.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 2 and 3.</p> <p>N 89°54' W, on the E and W center line of sec. 3.</p> <p>Over mesa land sloping W.</p>
20.545	<p>Point for the center E 1/16 sec. cor. of sec. 3.</p>

Survey of Subdivisions in Section 3
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E E 1/16 C ————— C S 3 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p> <p>33.50 Improved dirt road, 40 lks. wide, bears NE and SW.</p> <p>41.09 The center 1/4 sec. cor. of sec. 3.</p> <p style="text-align: center;">—————</p> <p>N 89°46' W, beginning new measurement.</p> <p>40.26 The 1/4 sec. cor. of secs. 3 and 4.</p> <p style="text-align: center;">—————</p> <p style="text-align: center;">NE 1/4 of Sec. 3</p> <p style="text-align: center;">—————</p> <p>From the center E 1/16 sec. cor. of sec. 3.</p> <p>N 1°17' W, on the N and S center line of the NE 1/4 of sec. 3.</p> <p>2.00 Improved dirt road, 30 lks. wide, bears N 80° E and W.</p> <p>15.05 Point for the center N-S-NE 1/256 sec. cor of sec. 3</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 3 C-N-S-NE 1/256 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert a rebar, 16 ins. long, 1/2 in. diam., found lying on the ground, inside the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p>
--------	---

Survey of Subdivisions in Section 3
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	The cor. is located 15 lks. W of cor. of fences extending E and S.
20.21	<p>The E 1/16 sec. cor. of secs. 3 and 34, on the N bdy. of the Tp.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 2 and 3.</p> <p>N 89°59' W, on the E and W center line of the NE 1/4 of sec. 3.</p>
20.37	<p>The NE 1/16 sec. cor. of sec. 3.</p> <hr/> <p>N 89°57' W, beginning new measurement.</p> <p>Along dirt road.</p>
20.35	<p>The center N 1/16 sec. cor. of sec. 3.</p> <hr/> <p style="text-align: center;">NE 1/4 of the NE 1/4 of sec. 3</p> <hr/> <p>From the N-N-N 1/256 sec. cor. of secs. 2 and 3.</p> <p>N 89°57' W, on the E and W center line of the N 1/2 of the NE 1/4 of the NE 1/4 of sec. 3.</p>
20.23	<p>The center N-N-NE 1/256 sec. cor. of sec. 3.</p> <hr/> <p style="text-align: center;">SE 1/4 of the NE 1/4 of sec. 3</p> <hr/> <p>From the N-S-N 1/256 sec. cor. of secs. 2 and 3.</p> <p>West, on the E and W center line of the N 1/2 of the SE 1/4 of the NE 1/4 of sec. 3.</p>
4.50	Dirt road, 15 lks. wide, bears S and N, curving W; along road.
20.395	<p>The center N-S-NE 1/256 sec. cor. of sec. 3.</p> <hr/> <p style="text-align: center;">Survey of Subdivisions in Section 5 T 5 N, R 11 E, Gila and Salt River Mer., Arizona</p> <hr/>
<p>Note: Interior subdivision corners established by Gordon H. Long, LS 6713, in 1970 were not utilized in the course of this survey because he erroneously determined the position for the 1/4 sec. cor. of secs. 5 and 32.</p>	

Survey of Subdivisions in Section 5
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p>From the 1/4 sec. cor. of secs. 5 and 8.</p> <p>N 0°32.5' W, on the N and S center line of sec. 5.</p> <p>Over level land.</p> <p>Along fence.</p>
19.88	<p>Point for the center S 1/16 sec. cor. of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E C S 1/16 S 5 C 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>From this cor., a local monument, bears N 12°00' E, 10.7 lks. dist., monumented with a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground.</p> <p>The cor. is located S 25° W, 8 lks. dist., from cor. of fences extending E and S.</p>
39.76	<p>Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E and W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E C 1/4 S5 1985</p> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 5 ins. diam., bears S 58 1/2° W, 61.5 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this cor., a local monument, bears N 15°45' E, 11.3 lks. dist., monumented with a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with aluminum cap mkd. C 1/4 LS 6713 1970.</p>

Survey of Subdivisions in Section 5
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
45.50	Improved dirt road, 50 lks. wide, bears S 25° E and N 25° W; over level, gently rolling land.
79.03	The 1/4 sec. cor. of secs. 5 and 32, on the N bdy. of the Tp.
	<hr/> <p>From the 1/4 sec. cor. of secs. 4 and 5.</p> <p>S 89°12.5' W on the E and W center line of sec. 5.</p> <p>Over mesa land sloping S.</p>
20.025	Point for the center E 1/16 sec. cor. of sec. 5.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T5N R11E E 1/16 C ————— C S 5 1985</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. orange colored plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
27.00	Desc. from mesa.
37.30	Improved dirt road, 40 lks. wide, bears S 25° E and N 25° W; over level land.
40.05	The center 1/4 sec. cor. of sec. 5.
60.08	Point for the center W 1/16 sec. cor. of sec. 5.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T5N R11E W 1/16 C ————— C S 5 1985</p>
	from which
	<p>A mesquite, 9 ins. diam., bears S 31 1/2° E, 112 lks. dist., mkd. CW 1/16 S5 BT.</p>

Survey of Subdivisions in Section 5
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
80.11	<p>The 1/4 sec. cor. of secs. 5 and 6.</p>
	<hr/> <p style="text-align: center;">SE 1/4 of Sec. 5</p> <hr/>
	<p>From the E 1/16 sec. cor. of secs. 5 and 8.</p> <p>N 0°30' W, on the N and S center line of the SE 1/4 of sec. 5.</p> <p>Over level land.</p>
8.00	<p>Over gently rolling land.</p>
15.00	<p>Edge of mesa, bears E and W.</p>
19.95	<p>Point for the SE 1/16 sec. cor. of sec. 5, at intersection with the E and W center line of the SE 1/4 of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T5N R11E SE 1/16 S 5 1985</p> <p>from which</p> <p style="text-align: center;">A power pole, 9 ins. diam., bears S 83° W, 128 lks. dist.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>From this cor. a local monument bears South, 11.3 lks. dist., monumented with a rebar, 1/2 in. diam., flush with the ground.</p>
39.90	<p>The center E 1/16 sec. cor. of sec. 5.</p>
	<hr/> <p>From the S 1/16 sec. cor. of secs. 4 and 5.</p> <p>S 89°24' W, on the E and W center line of the SE 1/4 of sec. 5.</p> <p>Over gently rolling land.</p>
9.00	<p>Edge of mesa, bears NE and SW.</p>

Survey of Subdivisions in Section 5
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
20.01	The SE 1/16 sec. cor. of sec. 5.
21.50	Desc. from mesa.
28.40	Improved dirt road, bears S 25° E and N 25° W; over level land.
28.75	Along fence.
39.985	Fence, bears S and N, 7.5 lks. to cor. of fences extending E and S.
40.02	The center S 1/16 sec. cor. of sec. 5.
<hr/> SW 1/4 of Sec. 5 <hr/>	
	From the W 1/16 sec. cor. of secs. 5 and 8.
	N 0°35.5' W, on the N and S center line of the SW 1/4 of sec. 5.
	Over bottom land.
3.00	Over level land.
19.84	Point for the SW 1/16 sec. cor. of sec. 5, at intersection with the E and W center line of the SW 1/4 of sec. 5.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T5N R11E SW 1/16 S 5 1985
	from which
	A mesquite, 12 ins. diam., bears S 18 3/4° E, 54 lks. dist., mkd. SW 1/16 S5 BT.
	A mesquite, 5 ins. diam., bears S 39 3/4° W, 25 lks. dist., mkd. X BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. silver colored plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
39.68	The center W 1/16 sec. cor. of sec. 5.

Survey of Subdivisions in Section 5
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p>From the center S 1/16 sec. cor. of sec. 5.</p> <p>S 89°19' W, on the E and W center line of the SW 1/4 of sec. 5.</p> <p>Over level land.</p>
20.015	The SW 1/16 sec. cor. of sec. 5.
40.03	The S 1/16 sec. cor. of secs. 5 and 6.
<hr/> <p>NW 1/4 of Sec. 5</p> <hr/>	
	<p>From the center W 1/16 sec. cor. of sec. 5.</p> <p>N 0°30' W, on the N and S center line of the NW 1/4 of sec. 5.</p> <p>Over level land.</p>
39.31	The W 1/16 sec. cor. of secs. 5 and 32, on the N bdy. of the Tp.
<hr/> <p>Survey of Subdivisions in Section 6 T 5 N, R 11 E, Gila and Salt River Mer., Arizona</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 6 and 7.</p> <p>N 0°37' W, on the N and S center line of sec. 6.</p> <p>Over gently rolling, mesa land.</p>
7.30	Arizona State Highway 188, 45 lks. wide, bears S 14° E and N 14° W.
25.00	Desc. from mesa.
36.50	Tonto Creek, 200 lks. wide, course SE; over bottom land.
39.46	Point for the center 1/4 sec. cor. of sec. 6, at intersection with the E and W center line of sec. 6.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a 5 ft. steel fence post, with brass cap mkd.</p>
	<p>T5N R11E C 1/4 S6 1985</p>
	from which

Survey of Subdivisions in Section 6
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S 55°39' W, 271.9 ft. dist., with brass cap mkd. T5N R11E C 1/4 S6 RM 271.9 FT. TO COR. 1985, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post. Set a steel fence post near the RM.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 18 ins. in the ground, in a mound of stone 2 1/2 ft. base, to top, for a reference monument, bears N 87°42' W, 388.1 ft. dist., with brass cap mkd. T5N R11E C 1/4 S6 RM 388.1 FT. TO COR. 1985, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post. Set a steel fence post near the RM.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
52.00	Tonto Creek, 200 lks. wide, course S 25° W.
59.32	<p>Point for the center N 1/16 sec. cor. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T5N R11E C N 1/16 S 6 C 1985</p> </div> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p>
77.20	Tonto Creek, 200 lks. wide, course S 30° E.
79.03	True point for the 1/4 sec. cor. of secs. 6 and 31, on the N bdy. of the Tp.
19.945	<p>From the 1/4 sec. cor. of secs. 5 and 6.</p> <p>N 89°48' W, on the E and W center line of sec. 6.</p> <p>Over level, bottom land.</p> <p>Point for the center E 1/16 sec. cor. of sec. 6.</p>

Survey of Subdivisions in Section 6
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a 5 ft. steel fence post, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E E 1/16 C ————— C S 6 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p>
39.89	The center 1/4 sec. cor. of sec. 6.
42.80	Tonto Creek, 80 lks. wide, course SE; over gently rolling land.
45.50	Edge of mesa, bears SE and NW.
80.52	The 1/4 sec. cor. of secs. 1 and 6, on the W bdy. of the Tp.
	<hr/> <p>NE 1/4 of Sec. 6</p> <hr/>
19.84	<p>From the center E 1/16 sec. cor. of sec. 6.</p> <p>N 0°32' W, on the N and S center line of the NE 1/4 of sec. 6.</p> <p>Over bottom, level land.</p> <p>Point for the NE 1/16 sec. cor. of sec. 6, at intersection with the E and W center line of the NE 1/4 of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E NE 1/16 S 6 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>Set a steel fence post near the cor.</p>

Survey of Subdivisions in Section 6
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
39.46	The E 1/16 sec. cor. of secs. 6 and 31, on the N bdy. of the Tp.
	<hr/> From the N 1/16 sec. cor. of secs. 5 and 6. N 89°45' W, on the E and W center line of the NE 1/4 of sec. 6. Over level, bottom land.
19.975	The NE 1/16 sec. cor. of sec. 6.
37.20	Tonto Creek, 150 lks. wide, course S.
39.95	The center N 1/16 sec. cor. of sec. 6.
	<hr/> <p style="text-align: center;">Survey of Subdivisions in Section 8 T 5 N, R 11 E, Gila and Salt River Mer., Arizona</p> <hr/>
	Note: Interior subdivision corners established by Gordon H. Long, LS 6713, in 1970 were not utilized in the course of this survey because he erroneously determined the position for the 1/4 sec. cor. of secs. 8 and 17.
	From the 1/4 sec. cor. of secs. 8 and 17. N 0°05' W, on the N and S center line of sec. 8. Over level land.
20.10	Point for the center S 1/16 sec. cor. of sec. 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T5N R11E C S 1/16 S 8 C 1985</p>
	from which <p style="margin-left: 40px;">A mesquite, 6 ins. diam., bears N 63° E, 49 lks. dist., mkd. X BT.</p> <p style="margin-left: 40px;">A mesquite, 8 ins. diam., bears S 8° W, 28 lks. dist., mkd. CS 1/16 S8 BT.</p>

Survey of Subdivisions in Section 8
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this cor., a local monument, bears S 88°15' W, 20.7 lks. dist., monumented with a rebar, 1/2 in. diam., 3 ins. below the ground, with aluminum cap mkd. CS 1/16 LS 6713 1970.</p>
40.20	<p>Point for the center 1/4 sec. cor. of sec. 8, at intersection with the E and W center line of sec. 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E C 1/4 S 8 1985</p> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 7 ins. diam., bears S 2° W, 140 lks. dist., mkd. C 1/4 S8 BT.</p> <p style="padding-left: 40px;">A mesquite, 9 ins. diam., bears S 72 1/4° W, 86.5 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this cor., a local monument, bears N 88°00' W, 11.7 lks. dist., monumented with a rebar, 1/2 in. diam., firmly set, projecting 4 ins. above ground, with aluminum cap mkd. C 1/4 LS 6713 1970.</p>
60.12	<p>Fence, bears E and W.</p>
60.16	<p>Point for the center N 1/16 sec. cor. of sec. 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E C N 1/16 S 8 C 1985</p>

Survey of Subdivisions in Section 8
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	<p>from which</p> <p style="padding-left: 40px;">A mesquite, 6 ins. diam., bears S 20 1/4° E, 74 lks. dist., mkd. CN 1/16 S8 BT.</p> <p style="padding-left: 40px;">A mesquite, 5 ins. diam., bears N 63 1/2° W, 34 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>64.70 Improved dirt road, 25 lks. wide, bears N 70° E and S 70° W.</p> <p>66.50 Greenback Creek, 50 lks. wide, course SW.</p> <p>80.12 The 1/4 sec. cor. of secs. 5 and 8.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 8 and 9.</p> <p>S 89°55 W, on the E and W center line of sec. 8.</p> <p>Over mesa land, sloping W.</p> <p>3.80 Improved dirt road, 35 lks. wide, bears S 50° E and N 50° W.</p> <p>5.80 Desc. from mesa.</p> <p>14.00 Over level land.</p> <p>19.76 Fence, bears N and S.</p> <p>20.00 Point for the center E 1/16 sec. cor. of sec. 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T5N R11E E 1/16 C ————— C S 8 1985</p> </div> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 8 ins. diam., bears N 16 1/2° W, 51.5 lks. dist., mkd. CE 1/16 S8 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. gray colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N of cor.</p>
--------	---

Survey of Subdivisions in Section 8
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a steel fence post near the cor.</p> <p>From this cor., a local monument, bears N 88°30' W, 8.7 lks. dist., monumented with a rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, with aluminum cap mkd. CE 1/16 LS 6713 1970.</p>
40.00	The center 1/4 sec. cor. of sec. 8.
43.20	Fence, bears N and S.
47.00	Over bottom land.
57.755	<p>Point selected for the witness cor. to the center W 1/16 sec. cor. of sec. 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a 5 ft. steel fence post, with brass cap mkd.</p> <div style="text-align: center;"> <p>W C T5N R11E W 1/16 C ← — C S 8 1985</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p>
60.125	Point for the center W 1/16 sec. cor. of sec. 8, falls in Tonto Creek, 150 lks. wide, course irregularly S where it is impracticable to establish a permanent monument.
75.00	Improved dirt road, 35 lks. wide, bears NE and SW.
78.70	Over level land.
80.25	The 1/4 sec. cor. of secs. 7 and 8.
<hr/> <p>NE 1/4 of Sec. 8</p> <hr/>	
	From the center E 1/16 sec. cor. of sec. 8.

Survey of Subdivisions in Section 8
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>N 0°05' W, on the N and S center line of the NE 1/4 of sec. 8. Over level land.</p>
20.015	<p>Point for the NE 1/16 sec. cor. of sec. 8, at intersection with the E and W center line of the NE 1/4 of sec. 8.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T5N R11E NE 1/16 S 8 1985</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. gray colored plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post near the cor.</p>
	<p>The cor. is located N 56 1/2° E, 2.44 chs. dist., from cor. of fences extending S and W.</p>
25.50	<p>Improved dirt road, 35 lks. wide, bears N 10° E and SE.</p>
36.60	<p>Improved dirt road, 35 lks. wide, bears S 15° E and N 15° W.</p>
39.10	<p>Greenback Creek, 70 lks. wide, course S 75° W.</p>
40.03	<p>The E 1/16 sec. cor. of secs. 5 and 8.</p>
	<hr/> <p>From the N 1/16 sec. cor. of secs. 8 and 9.</p>
	<p>S 89°45' W, on the E and W center line of the NE 1/4 of sec. 8.</p>
	<p>Over mesa land sloping generally W.</p>
7.50	<p>Desc. from mesa.</p>
17.60	<p>Improved dirt road, 35 lks. wide, bears S 30° E and N 30° W; over level land.</p>
19.995	<p>The NE 1/16 sec. cor. of sec. 8.</p>
39.99	<p>The center N 1/16 sec. cor. of sec. 8.</p>
	<hr/> <p style="text-align: center;">SE 1/4 of Sec. 8</p>
	<hr/> <p>From the E 1/16 sec. cor. of secs. 8 and 17.</p>

Survey of Subdivisions in Section 8
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	N 0°06' W, on the N and S center line of the SE 1/4 of sec. 8.
	Over gradual W slope.
20.09	Point for the SE 1/16 sec. cor. of sec. 8, at intersection with the E and W center line of the SE 1/4 of sec. 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T5N R11E SE 1/16 S 8 1985</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. orange colored plastic case beneath the stainless steel post.
	Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W of cor.
	Set a steel fence post near the cor.
	From this cor., a local monument, bears S 89°30' W, 9.7 lks. dist., monumented with a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with aluminum cap mkd. 1970 SE 1/16 LS 6713.
	Over level land.
40.18	The center E 1/16 sec. cor. of sec. 8.
	<hr/> From the S 1/16 sec. cor. of secs. 8 and 9.
	S 89°53' W, on the E and W center line of the SE 1/4 of sec. 8.
	Over mesa land sloping generally W.
14.00	Desc. from mesa.
19.63	Fence, bears N and S.
20.005	The SE 1/16 sec. cor. of sec. 8.
	Over level land.
40.01	The center S 1/16 sec. cor. of sec. 8.
	<hr/> <p style="text-align: center;">SW 1/4 of Sec. 8</p> <hr/>

Survey of Subdivisions in Section 8
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>From the W 1/16 sec. cor. of secs. 8 and 17.</p> <p>N 0°15' W, on the N and S center line of the SW 1/4 of sec. 8.</p> <p>Over bottom land.</p>
20.11	<p>Point for the SW 1/16 sec. cor. of sec. 8, at intersection with the E and W center line of the SW 1/4 of sec. 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a 5 ft. steel fence post, with brass cap mkd.</p> <p style="text-align: center;">T5N R11E SW 1/16 S 8 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.</p> <p>Set a steel fence post near the cor.</p>
40.22	<p>True point for the center W 1/16 sec. cor. of sec. 8.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 8.</p> <p>S 89°53' W, on the E and W center line of the SW 1/4 of sec. 8.</p> <p>Over level, bottom land.</p>
20.065	The SW 1/16 sec. cor. of sec. 8.
31.40	Tonto Creek, 100 lks. wide, course SW.
40.13	<p>The S 1/16 sec. cor. of secs. 7 and 8.</p> <hr/> <p style="text-align: center;">NW 1/4 of Sec. 8</p> <hr/> <p>From the true point for the center W 1/16 sec. cor. of sec. 8.</p> <p>N 0°06' E, on the N and S center line of the NW 1/4 of sec. 8.</p> <p>Over bottom land.</p>

Survey of Subdivisions in Section 8
T 5 N, R 11 E, Gila and Salt River Mer., Arizona

CHAINS	
4.70	Improved dirt road, 35 lks. wide, on curve, bears N 60° E from N 60° W.
39.755	The W 1/16 sec. cor. of secs. 5 and 8.
<hr/> GENERAL DESCRIPTION	
<p>The land encompassed in this survey is located in the Tonto Basin about 6 miles SE of Punkin Center, Arizona. The elevation ranges from about 2100 to 3000 feet above sea level. Tonto Creek flows southerly from the north boundary of section 6 through section 8 into Theodore Roosevelt Lake. Greenback Creek flows westerly from the east boundary of section 2 into Tonto Creek in section 8. The area east of Tonto Creek lies mostly on Cline Mesa, sloping gradually W and the area west is rolling. The land is covered with mesquite, palo verde, cat claw, creosote and cacti with scattered cottonwood and willow along Tonto Creek.</p> <p>Access is provided by Arizona State Highway 188 and secondary roads. Most of the residents are situated in the SW 1/4 of the SE 1/4 of section 5. No active claims were noted during the course of this survey.</p>	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Timothy J. Moore	Surveying Technician
Donald L. Brewer	Surveying Technician
Delbert L. Bybee	Surveying Technician
Neil A. Hemminger	Surveying Technician
Kevin L. Miller	Surveying Technician
Robert M. Charboneau	Surveying Aid
Grant Lopresti	Surveying Aid

CERTIFICATE OF SURVEY

We, Duane R. Garoutte and Alferd D. Pons, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 13th day of January, 1984, we have dependently resurveyed a portion of the west and north boundaries and a portion of the subdivisional lines, and surveyed the subdivisions in sections 2, 3, 5, 6, and 8, Township 5 North, Range 11 East, of the Gila and Salt River Meridian, in the State of Arizona which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Alferd D. Pons is no longer assigned to this office and is not available for signature.

7/17/90

(Date)

Dean E Mac Donald

(Chief, Survey Examiner)

February 23, 1989

(Date)

Duane R. Garoutte

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the west and north boundaries and a portion of the subdivisional lines, and the survey of the subdivisions in sections 2, 3, 5, 6, and 8, Township 5 North, Range 11 East, Gila and Salt River Meridian, Arizona, executed by Duane R. Garoutte and Alferd D. Pons, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

JUL 17 1990

(Date)

James P. Kelley

(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I Certify that the foregoing transcript of the field notes of the above-described surveys in T 5 N, R 11 E, Gila and Salt River Meridian, Arizona is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~