

BOOK 5302

INDEX DIAGRAM

TOWNSHIP 25 NORTH, RANGE 29 EAST,

28	6	100	5	82	4	67	3	55	2	41	1	20
	99		99		81		67		54		40	
26	7	97	8	80	9	65	10	51	11	39	12	19
	96		96		79		65		52		38	
25	18	95	17	78	16	63	15	50	14	37	13	17
	94		93		77		62		49		36	
24	19	90	20	74	21	61	22	47	23	35	24	16
	89		88		73		60		46		34	
22	30	87	29	72	28	59	27	45	26	32	25	14
	86		85		70		58		44		32	
21	31	84	32	69	33	56	34	42	35	30	36	12
	11		9		8		7		6		4	

Subdivision of Sec. 2---p 102
 Subdivision of Sec. 10---p 103
 Subdivision of Sec. 14---p 104
 Subdivision of Sec. 18---p 106

Subdivision of Sec. 20---p 107
 Subdivision of Sec. 22---p 111
 Subdivision of Sec. 28---p 114
 Subdivision of Sec. 30---p 116

BOOK 5302

T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS

Following are the notes of the dependent resurvey of the sixth standard parallel north through Range 29 East, the east and west boundaries, a portion of the north boundary, and the subdivisional lines, and the survey of the subdivision of certain sections in Township 25 North, Range 29 East, of the Gila and Salt River Meridian, Arizona.

The Sixth Standard Parallel North was surveyed through Range 29 East and the north and east boundaries of the Tp. were surveyed by Frank Follman in 1883. The west boundary was surveyed by Loyd E. Sechrist in 1920. The north and east boundaries, and the Sixth Standard Parallel North, through Range 29 East were resurveyed by Sidney E. Blout in 1927. The subdivisional lines were surveyed by Sidney E. Blout in 1927. Portions of the north boundary were resurveyed by Jack A. Savlan in 1984 and by Kevin R. DeRossett and Richard S. Kaiser in 1984-85.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated August 19, 1985, for Group No. 670, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of lines were determined by direct solar observations and refer to the true meridian. Distances and angles were measured using a Zeiss SM-4 electronic instrument, and a Nikon NTD-4 electronic instrument.

The geographic coordinates at the following listed points were determined by the technique of relative positioning using the Magnavox MX 1502 Satellite Surveyor. "COY", a first order triangulation station established by the United States Coast and Geodetic Survey was used as the control station. Elevations and coordinates refer to the top of the monument.

BOOK 5302

T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Corner/Station</p> <table> <thead> <tr> <th>Elevation</th> <th>Latitude</th> <th>Longitude</th> </tr> </thead> <tbody> <tr> <td colspan="3">Southeast Township Corner</td> </tr> <tr> <td>7297 ft.</td> <td>35°31'03.32" N</td> <td>109°11'14.13" W</td> </tr> <tr> <td colspan="3">Southwest Township Corner</td> </tr> <tr> <td>7430 ft.</td> <td>35°31'03.21" N</td> <td>109°17'37.06" W</td> </tr> <tr> <td colspan="3">"COY"</td> </tr> <tr> <td>6421 ft.</td> <td>35°47'07.629" N</td> <td>108°34'29.610" W</td> </tr> </tbody> </table> <p>The mean magnetic declination is 12 1/2° E.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of the 6th Stan. Par. N, S Bdy. of T 25 N, R 29 E, Gila and Salt River Mer., Arizona</p> <hr/> <p style="text-align: center;">(Restoring the resurvey executed by L.E. Sechrist in 1920 and the resurvey executed by S.E. Blout in 1927)</p> <hr/> <p>Beginning at the stan. cor. of T 25 N, Rs. 29 and 30 E, monumented with an iron post, 3 ins. diam., firmly set, projecting 20 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 resurvey of the Sixth Stan. Par. N, through R 29 E, from which the 1927 bearing trees:</p> <p style="padding-left: 40px;">A dead piñon, 9 ins. diam. at the base, bears N 38 1/4° E, 213 lks. dist., mkd. T25N R30E S31 SC BT on open blaze. (Record: 212 lks. dist.)</p> <p style="padding-left: 40px;">A dead piñon, 7 ins. diam. at the base, bears N 39 1/2° W, 97 lks. dist., mkd. T25N R29E S36 SC BT on open blaze. (Record: N 39 3/4° W, 96 lks. dist.)</p> <p>and the new bearing trees:</p> <p style="padding-left: 40px;">A piñon, 12 ins. diam. at the base, bears N 31 3/4° E, 361 1/2 lks. dist., mkd. T25N R30E S31 SC BT.</p>	Elevation	Latitude	Longitude	Southeast Township Corner			7297 ft.	35°31'03.32" N	109°11'14.13" W	Southwest Township Corner			7430 ft.	35°31'03.21" N	109°17'37.06" W	"COY"			6421 ft.	35°47'07.629" N	108°34'29.610" W
Elevation	Latitude	Longitude																				
Southeast Township Corner																						
7297 ft.	35°31'03.32" N	109°11'14.13" W																				
Southwest Township Corner																						
7430 ft.	35°31'03.21" N	109°17'37.06" W																				
"COY"																						
6421 ft.	35°47'07.629" N	108°34'29.610" W																				

BOOK 5302

Dependent Resurvey of the 6th Stan. Par. N, S Bdy. of
T 25 N, R 29 E, Gila and Salt River Meridian., Arizona

CHAINS	
	<p>A piñon, 14 ins. diam. at the base, bears N 70 1/2° W, 521 lks. dist., mkd. T25N R29E S36 SC BT.</p> <p>Add the marks 1985 to the brass cap.</p> <p>N 89°59' W, on the S bdy. of sec. 36.</p> <p>Over rolling land.</p>
39.98	<p>The stan. 1/4 sec. cor. of sec. 36 only, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1927 resurvey of the Sixth Stan. Par. N, through R 29 E, from which the 1927 bearing trees:</p> <p>A piñon, 16 ins. diam. at the base, bears N 25 1/2° E, 142 lks. dist., mkd. S36 SC BT on partially healed blaze. (Record: N 26° E, 154 lks. dist.)</p> <p>A piñon, 14 ins. diam. at the base, bears N 78 3/4° W, 159 lks. dist., illegibly mkd. on partially healed blaze. (Record: N 81 1/4° W)</p> <p>Add the marks T25N R29E 1985 to the brass cap.</p> <hr/> <p>S 89°55' W, beginning new measurement.</p>
31.45	<p>Trail road, bears S 60° E and N 60° W.</p>
40.00	<p>The stan. cor. of secs. 35 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 resurvey of the Sixth Stan. Par. N, through R 29 E, from which the 1927 bearing tree:</p> <p>A piñon, 18 ins. diam., bears N 62 1/2° E, 565 1/2 lks. dist., mkd. T25N R29E S36 BT on partially healed blaze. (Record: 566 lks. dist.)</p> <p>and a new bearing tree:</p> <p>A ponderosa pine, 11 ins. diam., bears N 49° W, 289 1/2 lks. dist., mkd. T25N R29E S35 SC BT</p> <p>Add the marks. 1985 to the brass cap.</p> <hr/>

BOOK 5302

Dependent Resurvey of the 6th Stan. Par. N, S Bdy. of
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

CHAINS	
	<p>S 89 59' W, on the S bdy. of sec. 35</p> <p>Over rolling and broken land.</p>
9.05	Trail road, bears N 20° E and S 20° W.
39.99	<p>The stan. 1/4 sec. cor. of sec. 35 only, determined from the 1927 bearing trees, located in a scattered mound of stone, 6 ft. diam., with an iron post, 1 in. diam., laying atop ground, with brass cap mkd. as described in the official record of the 1927 resurvey of the Sixth Stan. Par. N, through R 29 E, from which the 1927 bearing trees:</p> <p style="padding-left: 40px;">A dead ponderosa pine, 17 ins. diam., bears N 31 1/2° E, 69 lks. dist., mkd. 4 S35 SC BT on open blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 28 ins. diam., bears N 66 3/4° W, 60 lks. dist., with healed blaze. (Record: N 67 1/4° W)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">SC T25N R29E <u>1/4 S35</u> 1985</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N 70 1/4° E, 95 1/2 lks. dist., mkd. X BT.</p> <p>Bury the 1927 brass cap alongside the stainless steel post and destroy the iron post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N 89°59' W, beginning new measurement.</p>
2.10	Center of wash, 150 lks. wide, 60 ft. deep, drains S.
36.00	Center of wash, 100 lks. wide, 50 ft. deep, drains S 10° E.

BOOK 5302

Dependent Resurvey of the 6th Stan. Par. N, S Bdy.,
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

CHAINS	
39.97	<p>The stan. cor. of secs. 34 and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 resurvey of the Sixth Stan. Par N, through R 29 E, from which the 1927 bearing trees:</p> <p style="padding-left: 40px;">A ponderosa pine, 33 ins. diam., bears N 74 1/4° E, 145 lks. dist., illegibly mkd. on partially healed blaze. (Record: N 74 1/2° E)</p> <p style="padding-left: 40px;">A root hole, bears N 39 1/4° W, 273 lks. dist., alongside which is laying a ponderosa pine log, 20 ins. diam., mkd. T25N R29E S34 SC BT on open blaze. (Record: N 39 1/2° W., 277 lks. dist.)</p> <p>and a new bearing tree:</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears N 36 3/4° W, 127 1/2 lks. dist., mkd. T25N R29E S34 SC BT.</p> <p>Add the marks 1985 to the brass cap.</p> <hr/> <p>S 89°59' W, on the S bdy. of sec. 34.</p> <p>Over rolling and broken land.</p>
40.00	<p>The stan. 1/4 sec. cor. of sec. 34 only, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, in an embedded mound of stone, 3 ft. base, flush with the surface of the ground, with brass cap mkd. as described in the official record of the 1927 resurvey of the Sixth Stan. Par. N, through R 29 E, from which the 1927 bearing trees:</p> <p style="padding-left: 40px;">A piñon, 12 ins. diam., bears N 14 1/2° E, 78 1/2 lks. dist., illegibly mkd. on partially healed blaze. (Record: 80 lks. dist.)</p> <p style="padding-left: 40px;">A piñon, 16 ins. diam., bears N 7° W, 80 lks. dist., illegibly mkd. on partially healed blaze. (Record: N 6° W, 79 lks. dist.)</p> <p>Add the marks T25N R29E 1985 to the brass cap.</p> <hr/>

BOOK 5302

Dependent Resurvey of the 6th Stan. Par. N, S Bdy. of
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>39.97</p> <p>40.00</p>	<p>S 89°59' W, beginning new measurement.</p> <p>The stan. cor. of secs. 33 and 34, determined from the remains (root holes) of the original bearing trees</p> <p style="padding-left: 40px;">A root hole, bears N 6 1/4° E, 115 1/2 lks. dist., alongside which is laying a piñon log, 10 ins. diam., mkd. T25N R29E S34 SC BT on an open blaze. (Record: N 8 1/4° E, 116 lks. dist.)</p> <p style="padding-left: 40px;">A root hole, bears N 2 1/2° E, 116 lks. dist., alongside which is laying a piñon log, 10 ins. diam., illegibly mkd. on an open blaze. (Record: N 3/4° W)</p> <p>Point falls in the center of a scattered mound of stone, 6 ft. diam. This is accepted as the best available evidence of the position of the original cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to bedrock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC</p> <p>T25N R29E</p> <p><u>S33</u> <u>S34</u></p> <p>1985</p> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N 10 1/2° W, 247 1/2 lks. dist., mkd. T25N R29E S33 SC BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p> <hr/> <p>S 89°59' W, on the S bdy. of sec. 33.</p> <p>Over rolling land.</p> <p>The stan. 1/4 sec. cor. of sec. 33 only, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, in an embedded collar of stone, 2 1/2 ft. base, 3 ins. high, with brass cap mkd. as described in the official record of the 1927 resurvey of the Sixth Stan. Par. N, through R 29 E, from which the 1927 bearing trees:</p>
---	---

BOOK 5302

Dependent Resurvey of the 6th Stan. Par. N, S Bdy. of
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A piñon, 14 ins. diam., bears N 40° E, 29 lks. dist., mkd. 4 S33 SC BT on partially healed blaze. (Record: N 40 1/2° E)</p>
	<p>A piñon, 11 ins. diam., bears N 78 3/4° W, 31 lks. dist., mkd. 33 SC BT in partially healed blaze. (Record: N 78° W)</p>
	<p>Add the marks T25N R29E 1985 to the brass cap.</p>
	<p>S 89°55' W, beginning new measurement.</p>
36.60	<p>Trail road, bears N and S.</p>
40.01	<p>The stan. cor. of secs. 32 and 33, determined from the 1927 bearing trees, located in a scattered mound of stone, 10 ft. diam., from which the 1927 bearing trees:</p>
	<p>A ponderosa pine, 25 ins. diam., bears N 3 1/2° E, 66 lks. dist., mkd. T25N R29E S33 SC BT on partially healed blaze. (Record: N 2° E)</p>
	<p>A piñon, 20 ins. diam., bears N 46 1/4° W, 142 lks. dist., illegibly mkd. on partially healed blaze. (Record: N 47° W)</p>
	<p>At the cor. point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">SC T25N R29E <u>S32 S33</u> 1985</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p>
	<p>S 89°58' W, on the S bdy. of sec. 32.</p>
	<p>Over rolling land.</p>
23.50	<p>Trail road, bears N 50° E and S 50° W.</p>

BOOK 5302

Dependent Resurvey of the 6th Stan. Par. N, S Bdy. of
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

CHAINS	
31.50	Trail road, bears S 10° E and N 10° W.
39.98	<p>The stan. 1/4 sec. cor. of sec. 32 only, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 resurvey of the Sixth Stan. Par. N, through R 29 E, from which the 1927 bearing trees:</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam. at the base, bears N 6 1/2° E, 85 lks. dist., mkd. 1/4 S32 SC BT on partially healed blaze. (Record: N 7° E)</p> <p style="padding-left: 40px;">A piñon, 11 ins. diam. at the base, bears N 56° W, 135 1/2 lks. dist., with healed blaze. (Record: N 55 1/2° W, 136 lks. dist.)</p> <p>Add the marks T25N R29E 1985 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S 89°59' W, beginning new measurement.</p>
34.20	Trail road, bears N 10° E and S 10° W.
39.98	<p>The stan. cor. of secs. 31 and 32, monumented with an iron post, 2 ins. diam., 22 ins. long, firmly set, flush with the surface of the ground, with the top of the post missing, from which the remains of the 1927 bearing trees:</p> <p style="padding-left: 40px;">The base of a decaying piñon log, laying atop the ground, 8 ins. diam., bears N 40 3/4° E, 54 1/2 lks. dist., mkd. T25N R29E S32 BT. (Record: N 42 1/4° E, 54 lks. dist.)</p> <p style="padding-left: 40px;">The base of a decaying piñon log, laying atop the ground, 9 ins. diam., bears N 52° W, 62 1/2 lks. dist., mkd. T25N R29E S31 SC BT. (Record: N 36 3/4° W, 41 lks. dist.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">SC T25N R29E S31 S32 1985</p>

BOOK 5302

Dependent Resurvey of the 6th Stan. Par. N, S Bdy. of
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>A forked oak, 10 ins. diam., bears N 42 3/4° E, 111 1/2 lks. dist., mkd. T25N R29E S32 SC BT.</p> <p>A ponderosa pine, with a lightning blaze on the S face, 40 ins. diam., bears N 10 1/2° W, 295 lks. dist., mkd. T25N R29E S31 SC BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p> <hr/> <p>West, on the S. bdy. of sec. 31.</p> <p>Over rolling land.</p> <p>39.99 The stan. 1/4 sec. cor. of sec. 31 only, determined from the 1927 bearing trees::</p> <p>A piñon, 12 ins. diam., bears N 7 3/4° E, 161 lks. dist., mkd. 1/4 S31 SC BT on partially healed blaze. (Record: N 8° E)</p> <p>A multiple forked piñon, 22 ins. diam. at the base, bears N 68 1/4° W, 123 lks. dist., with healed blaze. (Record: N 69° E)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">SC T25N R29E <u>1/4 S31</u> 1985</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 30 lks. W of a trail road, bears N 35° E and S 35° W.</p> <hr style="width: 20%; margin: 20px auto;"/>

BOOK 5302

Dependent Resurvey of the 6th Stan. Par. N, S Bdy. of
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>39.99</p> <p>39.99</p>	<p>S 89°56' W, beginning new measurement.</p> <p>The stan. cor. of T 25 N, Rs. 28 and 29 E, monumented with an iron post, 3 ins. diam., firmly set, projecting 16 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. as described in the official record of the 1920 resurvey of the Sixth Stan. Par. N, through R 28 E, from which the 1920 bearing trees:</p> <p style="padding-left: 40px;">A ponderosa pine, 28 ins. diam., bears N 27° E, 121 lks. dist., mkd. T25N R29E S SC BT on partially healed blaze.</p> <p style="padding-left: 40px;">A piñon, 12 ins. diam. at the base, bears N 56 3/4° W, 27 lks. dist., mkd. T25N R28E S36 SC BT on decaying open blaze. (Record: N 59° W)</p> <p>and a new bearing tree:</p> <p style="padding-left: 40px;">A piñon, 9 ins. diam., bears N 12 3/4° W, 45 1/2 lks. dist., mkd. X BT at the base.</p> <p>Add the marks 1985 to the brass cap.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of the East Boundary of T 25 N, R 29 E, Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">(Restoring the resurvey executed by S.E. Blout in 1927)</p> <hr/> <p>From the stan. cor. of T 25 N, Rs. 29 and 30 E, hereinbefore described.</p> <p>N 0°06' E, bet. secs. 31 and 36.</p> <p>Over rolling and broken land.</p> <p>39.99 The 1/4 sec. cor. of secs. 31 and 36, monumented with an X chiseled in sandstone bedrock, 3 ins. below the surface of the ground, in a scattered mound of stone, 10 ft. diam., from which the remaining 1927 bearing tree:</p> <p style="padding-left: 40px;">A piñon, 12 ins. diam., bears N 16 1/4° E, 121 lks. dist., illegibly mkd. on partially healed blaze. (Record: N 16 1/2° E, 21 lks. dist.)</p>
---	---

BOOK 5302

Dependent Resurvey of the East Boundary of
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

CHAINS

At the cor. point

Set an aluminum post, 12 ins. long, 1 in. diam., 9 ins. in a drill hole, in sandstone bedrock, cemented in place, with aluminum cap mkd.

T25N	
1/4	
R29E	R30E
S36	S31
1985	

from which

A ponderosa pine, 11 ins. diam., bears S 37 3/4° W,
21 1/2 lks. dist., mkd. 1/4 S36 BT.

Deposit a magnet beneath the aluminum post.

N 0°02' W, beginning new measurement.

39.99

The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap improperly mkd.

T25N	
R29E	R30E
S35	S30
S36	S31
1927	

from which the remains of the 1927 bearing trees:

A ponderosa pine stump, 46 ins. diam., with a ponderosa pine log laying alongside, bears N 17° E, 329 1/2 lks. dist., stump mkd. BT on remnant of open blaze. (Record: 330 lks. dist.)

A dead piñon, 15 ins. diam., bears S 53 1/2° E, 535 lks. dist., illegibly mkd. on a partially healed blaze.

The base of an uprooted ponderosa pine stump, 18 ins diam., 3 ft. long, laying atop the ground, bears S 51 3/4° W, 165 lks. dist., mkd. T25N R29E S36 BT on open blaze. (Record: S 52 1/4° W, 155 lks. dist.)

BOOK 5302

Dependent Resurvey of the East Boundary of
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

CHAINS	<p>Remark the brass cap to read</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T25N</td> </tr> <tr> <td style="text-align: center;">R29E</td> <td style="text-align: center;">R30E</td> </tr> <tr> <td style="text-align: center;">S25</td> <td style="text-align: center;">S30</td> </tr> <tr> <td style="text-align: center;">S36</td> <td style="text-align: center;">S31</td> </tr> <tr> <td colspan="2" style="text-align: center;">1985</td> </tr> <tr> <td colspan="2" style="text-align: center;">1927</td> </tr> </table> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears N 34 1/2° E, 521 1/2 lks. dist., mkd. T25N R30E S30 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S 4 1/2° W, 532 lks. dist., mkd. X BT at the base.</p> <p style="padding-left: 40px;">A point on sandstone bedrock outcrop, even with the general surface, bears N 32° W, 147 lks. dist., mkd. X BO.</p> <p>Cor. is located 5 lks. E of a downed barbed wire fence, 4 strand, extending N 30° E and S 30° W.</p> <hr/> <p>N 0°04' E, bet. secs. 25 and 30.</p> <p>Over rolling and broken land.</p> <p>8.60 Trail road, bears N 20° E and S 20° W.</p> <p>39.99 The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, bent to the NW, with brass cap mkd. as described in the official record of the 1927 resurvey of the E Bdy. of T 25 N, R 29 E, from which the remaining 1927 bearing tree:</p> <p style="padding-left: 40px;">A piñon, 14 ins. diam., bears N 27° E, 26 lks. dist., mkd. 1/4 S30 BT on open blaze. (Record: N 27 1/2° E.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T25N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1/4</td> </tr> <tr> <td style="text-align: center;">R29E</td> <td style="text-align: center;">R30E</td> </tr> <tr> <td style="text-align: center;">S25</td> <td style="text-align: center;">S30</td> </tr> <tr> <td colspan="2" style="text-align: center;">1985</td> </tr> </table>	T25N		R29E	R30E	S25	S30	S36	S31	1985		1927		T25N		1/4		R29E	R30E	S25	S30	1985	
T25N																							
R29E	R30E																						
S25	S30																						
S36	S31																						
1985																							
1927																							
T25N																							
1/4																							
R29E	R30E																						
S25	S30																						
1985																							

BOOK 5302

Dependent Resurvey of the East Boundary of
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>A piñon, 16 ins. diam., bears S 85 1/2° W, 43 1/2 lks. dist., mkd. 1/4 S25 BT.</p> <p>Bury the 1927 brass cap alongside the stainless steel post and destroy the iron post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 50 lks. S of a trail road, bears SE and NW.</p> <hr/> <p>N 0°04' E, beginning new measurement.</p>
40.00	<p>The cor. of secs. 19, 24, 25 and 30, monumented with an iron post, 2 ins. diam., projecting 20 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 resurvey of the E bdy. of T 25 N, R 29 E, from which the 1927 bearing trees:</p> <p>A piñon, 10 ins. diam. at the base, bears N 54 1/2° E, 93 lks. dist., mkd. T25N R30E S19 BT on partially healed blaze.</p> <p>A dead piñon, 13 ins. diam., bears S 40° E, 69 lks. dist., mkd. T25N R30E S30 BT on partially healed blaze.</p> <p>A dead ponderosa pine, 15 ins. diam., bears S 61 3/4° W, 65 1/2 lks. dist., mkd. T25N R29E S25 BT on open blaze. (Record:67 lks. dist.)</p> <p>A piñon, 13 ins. diam., bears N 51° W, 104 lks. dist., illegibly mkd. on partially healed blaze. (Record: N 51° W, 106 lks. dist.)</p> <p>from which the new accessories:</p> <p>A piñon, 10 ins. diam., bears S 83 1/2° E, 36 lks. dist., mkd. T25N R30E S30 BT.</p> <p>A point on exposed sandstone conglomerate bedrock outcrop, 10 ft. diam., even with the general surface, bears S 33 3/4° W, 150 1/2 lks. dist., mkd. X BO.</p> <hr/>

BOOK 5302

Dependent Resurvey of the East Boundary of
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

CHAINS											
	N 0°02' E, bet. secs. 24 and 19.										
	Over rolling and broken land.										
39.96	The 1/4 sec. cor. of secs. 19 and 24, determined from the 1927 bearing trees:										
	A piñon, 8 ins. diam., bears S 44 1/2° E, 22 lks. dist., mkd. 1/4 S 19 BT on partially healed blaze. (Record: S 33 1/4° E)										
	A piñon, 10 ins. diam., bears N 44 1/4° W, 65 lks. dist., mkd. 1/4 S 24 BT on partially healed blaze. (Record: N 47 1/2° W)										
	At the cor. point										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T25N</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">R29E</td><td style="text-align: center;">R30E</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">1985</td></tr> </table>	T25N		1/4		R29E	R30E	S24	S19	1985	
T25N											
1/4											
R29E	R30E										
S24	S19										
1985											
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.										
	N 0°04' E, beginning new measurement.										
40.03	The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the official record of the 1927 resurvey of the E bdy. of T 25 N, R 29 E, from which the 1927 bearing trees:										
	A piñon, 11 ins. diam., bears N 80 1/2° E, 25 lks. dist., illegibly mkd. on partially healed blaze. (Record: 23 lks. dist.)										
	The base of a piñon log, 7 ins. diam., laying atop the ground, bears N 67 1/4° E, 62 lks. dist., mkd. T25N R30E S19 BT on open blaze. (Record: S 60 1/2° E, 61 lks. dist.)										

BOOK 5302

Dependent Resurvey of the East Boundary of
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A piñon, 11 ins. diam., bears S 49 1/2° W, 28 lks. dist., mkd. T25N R29E S24 BT on partially healed blaze.</p>
	<p>A piñon, 8 ins. diam., bears N 81° W, 55 lks. dist., mkd. T25N R2E S13 BT on partially healed blaze. (Record: 35 lks. dist.)</p>
	<p>from which a new bearing tree:</p>
	<p>A piñon, 11 ins. diam., bears S 23 1/4° E, 56 1/2 lks. dist., mkd. T25N R30E S19 BT.</p>
	<p>Encircle the iron post with a collar of stone, 1 ft. base, 6 ins. high.</p>
	<p>Add the marks 1985 to the brass cap.</p>
	<hr/> <p>N 0°01' W, bet. secs. 13 and 18.</p>
	<p>Over rolling land.</p>
<p>40.00</p>	<p>The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1927 resurvey of the E bdy. of T 25 N, R 29 E, from which the 1927 bearing trees:</p>
	<p>A multiple forked piñon, 16 ins. diam. at the base, bears S 88 1/4° E, 99 lks. dist., illegibly mkd. on partially healed blaze.</p>
	<p>A piñon, 14 ins. diam., bears N 58 1/2° W, 99 lks. dist., mkd. 1/4 S13 B on partially healed blaze.</p>
	<p>Add the marks T25N R29E R30E 1985 to the brass cap.</p>
	<hr/> <p>N 0°01' W, beginning new measurement.</p>
<p>39.99</p>	<p>The cor. of secs. 7, 12, 13 and 18, monumented with the bottom portion of an iron post, 2 ins. diam., 12 ins. long, firmly set, 14 ins. below the surface of the ground, the remainder of the iron post, 23 1/2 ins. long, was found nearby, with brass cap mkd. as described in the official record of the 1927 resurvey of the E bdy. of T 25 N, R 29 E, from which the 1927 bearing trees:</p>

BOOK 5302

Dependent Resurvey of the East Boundary of
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

CHAINS

A root hole, bears N 36 1/4° E, 262 lks. dist.,
alongside which is laying a piñon log, 10 ins. diam., mkd.
T25N R30E S7 BT on open blaze. (Record: N 38 1/4° E,
275 lks. dist.)

A root hole, bears S 74 3/4° E, 28 lks. dist.,
alongside which is laying a piñon log, 10 ins. diam.,
illegibly mkd. on partially healed blaze. (Record:
S 72 1/2° E.)

A root hole, bears S 42 1/2° W, 150 1/2 lks. dist.,
alongside which is laying a piñon log, 7 ins. diam., mkd.
T25N R29E S13 BT on open blaze. (Record: 148 lks. dist.)

A root hole, bears N 56 1/4° W, 118 lks. dist.,
alongside which is laying a piñon log, 12 ins. diam., mkd.
T25N R29E S12 BT on open blaze. (Record: N 55 1/2° W)

At the cor. point

Atop the bottom portion of the iron post, set a stainless steel
post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with
brass cap mkd.

T25N	
R29E	R30E
S12	S7
S13	S18
1986	

from which

A forked ponderosa pine, 15 ins. diam., bears
N 64 1/4° E, 215 lks. dist., mkd. T25N R30E S7 BT.

A piñon, 6 ins. diam., bears S 20 1/2° W, 77 lks.
dist., mkd. X at waist height and BT at the base.

A forked ponderosa pine, 8 ins. diam., bears
N 78° W, 269 1/2 lks. dist., mkd. T25N R29E S12 BT.

Deposit the 1927 brass cap alongside the stainless steel post and
destroy the remainder of the iron post.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic
case beneath the stainless steel post.

BOOK 5302

Dependent Resurvey of the East Boundary of
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

CHAINS	
	N 0°04' E, bet. secs. 7 and 12.
	Over rolling land.
13.00	Trail road, bears NE and SW.
39.98	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, bent to the NW, with brass cap mkd. as described in the official record of the 1927 resurvey of the E bdy. of T 25 N, R 29 E, from which the remains of a 1927 bearing tree:</p> <p style="padding-left: 40px;">A root hole, bears N 69° E, 172 lks. dist., alongside which is laying a piñon log, 12 ins. diam., illegibly mkd. on open blaze. (Record: N 71 1/2° E, 206 lks. dist.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T25N 1/4 R29E R30E S12 S7 1985 </div> <p>Bury the 1927 iron post and brass cap alongside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°04' E, beginning new measurement.</p>
39.97	<p>The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 2 ins. diam., firmly set, 6 ins. below the surface of the ground, severely bent, with brass cap mkd. as described in the official record of the 1927 resurvey of the E bdy. of T 25 N, R 29 E, from which the remains of a 1927 bearing tree:</p> <p style="padding-left: 40px;">The base of a piñon log, 15 ins. diam., laying atop the ground, bears S 76 3/4° W, 52 lks. dist., mkd. T25N R29E S12 BT on open blaze. (Record: S 61 3/4° W, 62 lks. dist.)</p>

BOOK 5302

Dependent Resurvey of the East Boundary of
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, encircled with a collar of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T25N</td> </tr> <tr> <td style="text-align: center;">R29E</td> <td style="text-align: center;">R30E</td> </tr> <tr> <td style="text-align: center;">S1</td> <td style="text-align: center;">S6</td> </tr> <tr> <td style="text-align: center;">S12</td> <td style="text-align: center;">S7</td> </tr> <tr> <td colspan="2" style="text-align: center;">1985</td> </tr> </table>	T25N		R29E	R30E	S1	S6	S12	S7	1985	
T25N											
R29E	R30E										
S1	S6										
S12	S7										
1985											
	<p>Bury the 1927 brass cap alongside the stainless steel post and destroy the iron post.</p>										
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p>										
	<hr/>										
	<p>N 0°03' E, bet. secs. 1 and 6.</p>										
	<p>Over rolling land.</p>										
0.80	<p>Trail road, bears N 60° E and S 60° W.</p>										
34.10	<p>Underground gas pipeline and trail road, bears N 65° E and S 65° W.</p>										
40.00	<p>The 1/4 sec. cor. of secs. 1 and 6, monumented with an iron post, 1 in. diam., firmly set, projecting 19 ins. above ground, with brass cap mkd. as described in the official record of the 1927 resurvey of the E bdy. of T 25 N, R 29 E, with a sandstone, 24 x 10 x 2 ins., mkd. 1/4 on one face, laying alongside the iron post, to the S, from which the 1927 bearing trees:</p> <p style="margin-left: 40px;">A ponderosa pine, 32 ins. diam., bears N 16° E, 457 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A piñon, 19 ins. diam. at the base, bears N 78 3/4° W, 119 1/2 lks. dist., with healed blaze. (Record: N 79° W, 120 lks. dist.)</p>										
	<p>Add the marks T25N R29E R30E 1985 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/>										
	<p>N 0°02' E, beginning new measurement.</p>										
41.15	<p>Underground gas pipeline and trail road, bears E and W.</p>										

BOOK 5302

Dependent Resurvey of the West Boundary of
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

CHAINS	
42.04	<p>The closing corner of T. 25 N, Rs. 29 and 30 E, monumented with an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the 1984-85 resurvey of the S bdy. of T 26 N, R 30 E.</p> <p>From this cor., the cor. of T. 26 N, Rs. 29 and 30 E, bears N 89°40' W, 2.17 chs. dist., monumented with an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the 1984 resurvey of the S bdy. of T 26 N, R 29 E.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of the West Boundary of T 25 N, R 29 E, Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">(Restoring the survey executed by L.E. Sechrist in 1920)</p> <hr/> <p>From the stan. cor. of T 25 N, Rs. 28 and 29 E, hereinbefore described.</p> <p>North, bet. secs. 31 and 36.</p> <p>Ascending gradually over rolling land.</p>
40.03	<p>The 1/4 sec. cor. of secs. 31 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 22 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the official record of the 1920 survey of the E bdy. of T 25 N, R 28 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">A forked ponderosa pine, 35 ins. diam., bears S 38 1/2° E, 18 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A ponderosa pine stump, 34 ins. diam., bears S 46 1/2° W, 144 lks. dist., with remnant of open blaze.</p> <p>and a new bearing tree:</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S 72 1/2° W, 202 lks. dist., mkd. 1/4 S36 BT.</p> <p>Add the marks T25N R28E R29E 1985 to the brass cap.</p> <hr/>

BOOK 5302

Dependent Resurvey of the West Boundary of
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

CHAINS	
	N 0°01' E, beginning new measurement.
18.80	Trail road, bears N 55° E and S 55° W.
40.03	<p>The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 2 ins. diam., loosely set, projecting 28 ins. above ground, in a scattered mound of stone, with brass cap mkd. as described in the official record of the 1920 survey of the E bdy. of T 25 N, R 28 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">An oak, 25 ins. diam., bears N 80° E, 63 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A piñon, 23 ins. diam., bears S 54 1/2° E, 38 lks. dist., mkd. T25N R29E S31 BT on open blaze. (Record: S 56° E)</p> <p style="padding-left: 40px;">A piñon, 19 ins. diam., bears S 67 1/4° W, 70 lks. dist., mkd. T25N R28E S36 BT on partially healed blaze. (Record: S 66 1/4° E)</p> <p style="padding-left: 40px;">A piñon, 25 ins. diam. at the base, bears N 71 3/4° W, 208 lks. dist., mkd. T25N R28E on partially healed blaze. (Record: 209 lks. dist.)</p> <p>Support the iron post in a mound of stone, 5 ft. base, 2 ft. high.</p> <hr/> <p>N 0°01' E, bet. secs. 25 and 30.</p> <p>Ascending gradually over rolling land.</p>
10.96	<p>An original line tree, a ponderosa pine, 37 ins. diam., mkd. with two small notches each on N and S sides, and now serves as an angle point.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, 1 1/2 ft. base, to top, for a reference monument, bears S 54°46' E, 48.2 lks. dist., with brass cap mkd. RM T25N R29E AP S30 31.8 FT 1985 and an arrow pointing to the line tree.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p> <hr/>

BOOK 5302

Dependent Resurvey of the West Boundary of
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

CHAINS	
	N 0°04' E, beginning new measurement.
9.95	Trail road, bears S 55° E and N 55° W.
11.80	Wash, 15 lks. wide, 1 ft. deep, drains N 70° E.
29.09	The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the official record of the 1920 survey of the E bdy. of T 25 N, R 28 E, from which the original bearing trees: <p style="margin-left: 40px;">A ponderosa pine, 31 ins. diam., bears N 21 1/2° E, 478 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A ponderosa pine, 41 ins. diam., bears N 80 3/4° W, 124 lks. dist., with healed blaze. (Record: N 80 1/4° W)</p> <p>Add the marks T25N R28E R29E 1985 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/>
	N 0°02' W, beginning new measurement.
17.25	Trail road, bears N 75° E and S 75° W.
25.50	Wash, 38 lks. wide, 1 ft. deep, drains S 60° E.
40.05	The cor. of secs. 19, 24, 25 and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, in a collar of stone, 2 ft. base, 6 ins. high, with brass cap mkd. as described in the official record of the 1920 survey of the E bdy. of T 25 N, R 28 E. <p>from which the new bearing trees:</p> <p style="margin-left: 40px;">A ponderosa pine, 15 ins. diam., bears N 69° E, 240 lks. dist., mkd. T25N R29E S19 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 20 ins. diam., bears S 11 1/2° E, 454 1/2 lks. dist., mkd. T25N R29E S30 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 16 ins. diam., bears S 40 1/2° W, 340 lks. dist., mkd. T25N R28E S25 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 13 ins. diam., bears N 66 3/4° W, 342 lks. dist., mkd. T25N R28E S24 BT.</p> <p>Add the marks 1985 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/>

BOOK 5302

Dependent Resurvey of the West Boundary of
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

CHAINS	
	N 0°01' E, bet. secs. 19 and 24.
	Ascending gradually over rolling land.
27.65	Trail road, bears E and W.
40.06	The 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. as described in the official record of the 1920 survey of the E bdy. of T 25 N, R 28 E, from which the original bearing trees:
	A ponderosa pine stump, 32 ins. diam., bears N 87 3/4° E, 358 lks. dist., mkd. BT on remnant of open blaze. (Record: 197 lks. dist.)
	A ponderosa pine, 32 ins. diam., bears S 42 1/2° W, 193 lks. dist., illegibly mkd. on partially healed blaze. (Record: 359 lks. dist.)
	and a new bearing tree:
	A ponderosa pine, 8 ins. diam., bears N 80 3/4° E, 11 lks. dist., mkd. 1/4 S19 BT.
	Add the marks T25N R28E R29E 1985 to the brass cap.
	N 0°01' E, beginning new measurement.
38.23	Trail road, bears S 65° E and N 65° W.
40.06	The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, in a collar of stone, 2 1/2 ft. base, to top, with brass cap mkd. as described in the official record of the 1920 survey of the E bdy. of T 25 N, R 28 E, from which the original bearing trees:
	A ponderosa pine, 31 ins. diam., bears N 3° E, 60 lks. dist., illegibly mkd. on partially healed blaze.
	A ponderosa pine, 37 ins. diam., bears S 11 3/4° E, 153 lks. dist., illegibly mkd. on partially healed blaze.
	A ponderosa pine, 28 ins. diam., bears S 41 3/4° W, 253 lks. dist., mkd. T25N R28E S24 BT on partially healed blaze.

BOOK 5302

Dependent Resurvey of the West Boundary of
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A ponderosa pine, 26 ins. diam., bears N 61 1/2° W, 399 lks. dist., with healed blaze.</p> <hr/> <p>N 0°11' E, bet. secs. 13 and 18.</p> <p>Ascending gradually over rolling land.</p> <p>8.10 Trail road, bears E and W.</p> <p>19.70 Graded road, bears NE and SW.</p> <p>40.18 The 1/4 sec. cor. of secs. 13 and 18, determined at record dist. from the original bearing trees:</p> <p style="padding-left: 40px;">A triple forked oak, 38 ins. diam. at the base, bears S 51 1/4° E, 304 lks. dist., with healed blaze. (Record: S 54 1/2° E)</p> <p style="padding-left: 40px;">A ponderosa pine, 29 ins. diam., bears N 49° W, 86 lks. dist., mkd. 1/4 S13 BT on open blaze. (Record: N 36 3/4° W)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N 1/4 R28E R29E S13 S18 1985</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p> <hr/> <p>N 0°11' W, beginning new measurement.</p> <p>14.90 Trail road, bears N 80° E and S 80° W.</p> <p>39.93 The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap illegibly mkd., from which the original bearing trees:</p> <p style="padding-left: 40px;">A piñon, 15 ins. diam. at the base, bears N 27 1/4° E, 462 lks. dist., with healed blaze. (Record: N 27°22' E)</p>

BOOK 5302

Dependent Resurvey of the West Boundary of
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

CHAINS													
	<p>A piñon, 16 ins. diam. at the base, bears S 51 1/2° E, 112 lks. dist., mkd. 25 2 S BT on partially healed blaze.</p> <p>A piñon, 17 ins. diam. at the base, bears S 21 3/4° W, 312 lks. dist., mkd. T25N R28E S13 BT on open blaze.</p> <p>A piñon, 23 ins. diam. at the base, bears N 14 3/4° W, 342 1/2 lks. dist., with healed blaze. (Record: N 14°37' W, 342 lks. dist.)</p> <p>Remark the brass cap to read</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T25N</td></tr> <tr><td style="text-align: center;">R28E</td><td style="text-align: center;">R29E</td></tr> <tr><td style="text-align: center;"><u>S12</u></td><td style="text-align: center;"><u>S7</u></td></tr> <tr><td style="text-align: center;">S13</td><td style="text-align: center;">S18</td></tr> <tr><td colspan="2" style="text-align: center;">1985</td></tr> <tr><td colspan="2" style="text-align: center;">1920</td></tr> </table>	T25N		R28E	R29E	<u>S12</u>	<u>S7</u>	S13	S18	1985		1920	
T25N													
R28E	R29E												
<u>S12</u>	<u>S7</u>												
S13	S18												
1985													
1920													
	<hr/> <p>North, bet. secs. 7 and 12.</p> <p>Ascending gradually over rolling land.</p>												
21.00	Underground gas pipeline and trail road, bears N 85° E and S 85° W.												
40.07	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. as described in the official record of the 1920 survey of the E bdy. of T 25 N, R 28 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">A piñon, 15 ins. diam., bears N 73 1/4° E, 136 lks. dist., with healed blaze. (Record: 138 lks. dist.)</p> <p style="padding-left: 40px;">A ponderosa pine, 29 ins. diam., bears S 60 1/2° E, 95 1/2 lks. dist., with healed blaze. (Record: S 61° W, 96 lks. dist.)</p> <p>Add the marks T25N R28E R29E 1985 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°05' E, beginning new measurement.</p>												
11.10	Graded road, bears E and W.												

BOOK 5302

Dependent Resurvey of the West Boundary of
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

CHAINS											
15.55	Trail road, bears S 30° E and N 30° W.										
31.70	Wash, 10 lks. wide, 2 ft. deep, drains NW.										
40.05	<p>The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, bent to the SE, with brass cap mkd. as described in the official record of the 1920 survey of the E bdy. of T 25 N, R 28 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">A ponderosa pine stump, 23 ins. diam., bears N 32 1/4° E, 21 lks. dist., illegibly mkd. on remnant of open blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears S 31° E, 108 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 25 ins. diam., bears S 74° W, 111 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A ponderosa pine stump, 24 ins. diam., bears N 42 1/4° W, 114 lks. dist., with chop marks visible on remnant of open blaze. (Record: 113 lks. dist.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with a collar of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td colspan="2" style="text-align: center;">T25N</td></tr> <tr><td style="text-align: center;">R28E</td><td style="text-align: center;">R29E</td></tr> <tr><td style="text-align: center;">S1</td><td style="text-align: center;">S6</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S7</td></tr> <tr><td colspan="2" style="text-align: center;">1985</td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 23 ins. diam., bears N 24 3/4° E, 461 1/2 lks. dist., mkd. T25N R29E S6 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears N 45 3/4° W, 201 lks. dist., mkd. T25N R28E S1 BT.</p> <p>Bury the 1920 iron post and brass cap alongside the stainless steel post.</p>	T25N		R28E	R29E	S1	S6	S12	S7	1985	
T25N											
R28E	R29E										
S1	S6										
S12	S7										
1985											

BOOK 5302

Dependent Resurvey of the West Boundary of
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p>
	<p>N 0°02' E, bet. secs. 1 and 6.</p>
	<p>Over rolling land.</p>
40.07	<p>The 1/4 sec. cor. of secs. 1 and 6, determined from the original bearing trees:</p>
	<p>A dead piñon, 8 ins. diam., bears S 15 1/4° E, 112 lks. dist., mkd. 1/4 S6 BT on open blaze.</p>
	<p>A ponderosa pine, 26 ins. diam., bears N 48° W, 260 lks. dist., with healed blaze.</p>
	<p>At the cor. point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled with a mound of stone, 3 ft. base, 6 ins. high, with brass cap mkd.</p>
	<p style="text-align: center;">T25N 1/4 R28E R29E S1 S6 1985</p>
	<p>from which</p>
	<p>A ponderosa pine, 13 ins. diam., bears N 26 1/4° E, 188 lks. dist., mkd. 1/4 S6 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p>
	<p>N 0°01' E, beginning new measurement.</p>
3.50	<p>Trail road, bears S 85° E and N 85° W.</p>
38.30	<p>Wash, 15 lks. wide, 1 ft. deep, drains W.</p>
41.35	<p>Underground gas pipeline and trail road, bears E and W.</p>

BOOK 5302

Dependent Resurvey of the West Boundary of
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

CHAINS	
41.90	<p>The closing cor. of T 25 N, Rs. 28 and 29 E, monumented with an iron post, 3 ins. diam., firmly set, projecting 14 ins. above ground, in a collar of stone, 2 ft. base, 1 ft. high, with brass cap mkd. as described in the official record of the 1920 survey of the E bdy. of T 25 N, R 28 E, from which the remains of an original bearing tree:</p> <p style="padding-left: 40px;">A ponderosa pine stump, 20 ins. diam., bears S 42 1/4° W, 289 lks. dist., mkd. S1 CC BT on remnant of open blaze. (Record: S 45 1/2° W)</p> <p>from which the new bearing trees:</p> <p style="padding-left: 40px;">A forked piñon, 15 ins. diam. at the base, bears S 83 1/4° E, 235 1/2 lks. dist., mkd. T25N R29E S6 CC BT.</p> <p style="padding-left: 40px;">A piñon, 16 ins. diam., bears S 84° W, 96 1/2 lks. dist., mkd. T25N R28E S1 CC BT.</p> <p>Add the marks 1985 to the brass cap.</p> <p>From this cor., the cor. of Tps. 26 N, Rs. 28 and 29 E, bears N 89°52' W, 3.81 chs. dist., monumented with an iron post, 2 1/2 ins. diam., set, mkd. and witnessed as described in the official record of the 1984 resurvey of the S Bdy. of T 26 N, R 29 E.</p>
	<hr/> <p>Dependent Resurvey of a Portion of the N. Bdy. of T 25 N, R 29 E, Gila and Salt River Mer., Arizona.</p> <hr/>
	<p>(Restoring the resurveys executed by S.E. Blout in 1927, and J.A. Savlan in 1984)</p> <hr/>
	<p>From the cor. of secs. 31 and 32 only, T. 26 N., R. 29 E., monumented with a stainless steel post, 2 1/2 ins. diam., set, mkd. and witnessed as described in the official record of the 1984 resurvey of the S bdy. of T. 26 N., R. 29 E.</p>
	<p>N 89 49' W, bet. secs. 6 and 31.</p>
	<p>Over rolling land.</p>
37.01	<p>Point for the 1/4 sec. cor. of sec. 6 only, T 25 N, R 29 E, at proportionate dist.; there is no remaining evidence of the original cor. position.</p>

BOOK 5302

Dependent Resurvey of a Portion of the N Bdy. of
T 25 N, R 29 E, Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled with a collar of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;"> <u>T26N R29E</u> 1/4 S 6 T25N R29E 1986 </p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p>
40.30	<p>The 1/4 sec. cor. of sec. 31 only, T 26 N, R 29 E, monumented with an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record of the 1984 resurvey of the S bdy., T 26 N, R 29 E</p> <p>Encircle the iron post with a collar of stone, 2 ft. base, 1 ft. high.</p>
	<p>Dependent Resurvey of the Subdivisional Lines, T 25 N, R 29 E, Gila and Salt River Mer., Arizona</p>
	<p>(Restoring the survey executed by S.E. Blout in 1927)</p>
	<p>From the stan. cor. of secs. 35 and 36, on the S bdy. of the Tp., hereinbefore described.</p> <p>N 0°01 'E, bet. secs. 35 and 36.</p> <p>Over rolling and broken land.</p>
1.90	Trail road, bears S 60° E and N 60° W.
20.95	Trail road, bears N 40° E and S 40° W.
39.99	<p>The 1/4 sec. cor. of secs. 35 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines of T 25 N, R 29 E, from which the original bearing trees:</p> <p style="text-align: center;"> A piñon, 12 ins. diam., bears S 74 3/4° E, 18 lks. dist., mkd. S36 BT on open blaze. (Record: S 75 1/2° E) </p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A dead piñon, 15 ins. diam., bears N 63 3/4° W, 7 lks. dist., mkd. S35 BT on open blaze. (Record: N 68° W, 6 lks. dist.)</p>
	<p>from which a new bearing tree:</p>
	<p>A piñon, 16 ins. diam., bears S 12 3/4° W, 138 lks. dist., mkd. 1/4 S35 BT.</p>
	<p>Add the marks T25N R29E 1985 to the brass cap.</p>
	<p>N 0°05' E, beginning new measurement.</p>
20.30	<p>Wash, 20 lks. wide, 2 ft. deep, drains SW.</p>
40.00	<p>The cor. of secs. 25, 26, 35 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines of T 25 N, R 29 E, from which the original bearing trees:</p>
	<p>A piñon, 18 ins. diam., bears N 33 1/4° E, 20 lks. dist., mkd. T25N R29E S25 BT on partially healed blaze with another blaze 3 1/2 ft. above the ground. (Record: N 31° E)</p>
	<p>A piñon, 15 ins. diam., bears S 73 1/2° E, 36 lks. dist., mkd. T25N R29E S36 BT on partially healed blaze with another blaze 3 1/2 ft. above the ground. (Record: S 74 3/4° E)</p>
	<p>A root hole, bears S 60 3/4° W, 105 1/2 lks. dist., alongside which is laying a piñon log, 10 ins. diam., mkd. T25N R29E S35 BT on open blaze. (Record: S 61 3/4° W, 104 lks. dist.)</p>
	<p>A dead piñon, 14 ins. diam., bears N 71 1/2° W, 95 lks. dist., mkd. T25N R29E S26 BT on open blaze, with another blaze 3 1/2 ft. above the ground.</p>
	<p>from which the new bearing trees:</p>
	<p>A piñon, 11 ins. diam., bears S 63 1/4° W, 116 1/2 lks. dist., mkd. T25N R29E S35 BT.</p>
	<p>A piñon, 11 ins. diam., bears N 30 1/2° W, 92 lks. dist., mkd. T25N R29E S26 BT.</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	Add the marks 1985 to the brass cap.
	From the cor. of secs. 25, 30, 31 and 36, on the E bdy. of the Tp., hereinbefore described.
	N 89°59' W, bet. secs. 25 and 36.
	Over rolling and broken land.
25.00	Trail road, bears NE and SW.
39.98	The 1/4 sec. cor. of secs. 25 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines of T 25 N, R 29 E, from which the original bearing trees:
	A piñon, 7 ins. diam., bears N 63 1/2° E, 19 1/2 lks. dist., mkd. S25 BT on open blaze. (Record:16 lks. dist.)
	A forked piñon, 12 ins. diam. at the base, bears S 12 3/4° E, 17 lks. dist., mkd. 1/4 S36 BT on open blaze on dead fork. (Record: S 14 1/2° E)
	from which a new bearing tree:
	A piñon, 12 ins. diam., bears S 73° W, 71 1/2 lks. dist., mkd. 1/4 S36 BT.
	Add the marks T25N R29E 1985 to the brass cap.
	S 89°58' W, beginning new measurement.
14.00	Trail road, bears S 5° E and N 5° W.
39.94	The cor. of secs. 25, 26, 35 and 36.
	N 0°07' W, bet. secs. 25 and 26.
12.90	Trail road, bears NE and SW.
18.50	Wash, 40 lks. wide, 2 ft. deep, drains S 66° W.
29.20	Trail road, bears S 80° E and N 80° W.
31.20	Trail road, bears S 80° E and N 80° W.

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
40.04	<p>The 1/4 sec. cor. of secs. 25 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines of T 25 N, R 29 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">A piñon, 12 ins. diam., bears S 50 3/4° E, 9 lks. dist., mkd. S25 BT on partially healed blaze. (Record: S 43 1/2° E)</p> <p style="padding-left: 40px;">A piñon, 9 ins. diam., bears S 79 1/4° W, 12 1/2 lks. dist., mkd. S26 BT on partially healed blaze. (Record: S 74 3/4° W, 15 lks. dist.)</p> <p>Add the marks T25N R29E 1985 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°04' W, beginning new measurement.</p>
35.75	Trail road, bears N 70° E and S 70° W.
39.98	<p>The cor. of secs. 23, 24, 25 and 26, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines of T 25 N, R 29 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">A dead decaying piñon, 11 ins. diam., bears N 34 1/4° E, 80 lks. dist., mkd. T25N R29E S24 BT on partially healed blaze. (Record: N 45° E)</p> <p style="padding-left: 40px;">A dead forked piñon, 18 ins. diam., bears S 47 1/2° E, 70 lks. dist., mkd. T25N R29E S25 BT on partially healed blaze. (Record: S 46 3/4° E)</p> <p style="padding-left: 40px;">A ponderosa pine stump, 10 ins. diam., bears S 49 3/4° W, 184 lks. dist., with no blaze visible. (Record: S 49 1/4° W, 180 lks. dist.)</p> <p style="padding-left: 40px;">A ponderosa pine, 39 ins. diam., bears N 11 1/4° W, 146 lks. dist., with healed blaze. (Record: N 16 1/4° W, 145 lks. dist.)</p> <p>from which the new bearing trees:</p> <p style="padding-left: 40px;">A piñon, 12 ins. diam., bears N 65 1/2° E, 140 1/2 lks. dist., mkd. T25N R29E S24 BT.</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A piñon, 12 ins. diam., bears S 81 1/2° E, 108 lks. dist., mkd. T25N R29E S25 BT.</p>
	<p>A ponderosa pine, 23 ins. diam., bears S 7 1/2° W, 176 lks. dist., mkd. T25N R29E S26 BT.</p>
	<p>Add the marks 1985 to the brass cap.</p>
	<hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>S 89°59' W, bet. secs. 24 and 25.</p>
	<p>Over rolling and broken land.</p>
20.20	<p>Trail road, bears N 25° E and S 25° W.</p>
22.20	<p>Wash, 45 lks. wide, 1 ft. deep, drains S 25° W.</p>
27.80	<p>Trail road, bears N 50° E and S 50° W.</p>
40.08	<p>The 1/4 sec. cor. of secs. 24 and 25, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines of T 25 N, R 29 E, from which the original bearing trees:</p>
	<p>A piñon, 10 ins. diam., bears N 75 1/2° E, 65 lks. dist., mkd. S24 BT on partially healed blaze. (Record: 58 lks. dist.)</p>
	<p>A dead piñon, 13 ins. diam., bears S 83 1/2° W, 57 1/2 lks. dist., mkd. S25 BT on open blaze. (Record: S 84 1/4° W, 64 lks. dist.)</p>
	<p>from which a new bearing tree:</p>
	<p>A piñon, 8 ins. diam., bears S 30° E, 47 1/2 lks. dist., mkd. 1/4 S25 BT.</p>
	<p>Add the marks T25N R29E 1985 to the brass cap.</p>
	<p>Cor. is located 10 lks. S of the center of a trail road, bears E and W.</p> <hr/>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	N 89°57' W, beginning new measurement.
35.00	Trail road, bears N 55° E and S 55° W.
40.06	The cor. of secs. 23, 24, 25 and 26.
	N 0°02' W, bet. secs. 23 and 24.
	Over rolling and broken land.
36.65	Trail road, bears N 20° E and S 20° W.
39.99	<p>The 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 1 in. diam., firmly set, 6 ins. below the surface of the ground, bent to the W, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines of T 25 N, R 29 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">A ponderosa pine, 17 ins. diam., bears S 64 1/4° E, 38 lks. dist., with healed blaze. (Record: S 63° E)</p> <p style="padding-left: 40px;">A ponderosa pine, 21 ins. diam., bears S 52 1/2° W, 99 lks. dist., with healed blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T25N R29E 1/4 S23 S24 1986</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p> <p>Remove the found iron post.</p> <p>Cor. is located in an old fence line, wood posts only, extending N 25° E and S 25° W.</p> <hr style="width: 20%; margin: 10px auto;"/>
	N 0°02' W, beginning new measurement.
3.00	Wash, 3 lks. wide, 1/4 ft. deep, drains S 40° W.

BOOK 5302

Dependent Resurvey of the Subdivisional Lines
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
40.00	<p>The cor. of secs. 13, 14, 23 and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 30 ins. above ground, in a mound of stone, 6 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines of T 25 N, R 29 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">A piñon, 8 ins. diam., bears N 15 1/2° E, 140 lks. dist., mkd. T25N R29E S13 BT on open blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears S 62° E, 96 1/2 lks. dist., mkd. T25N R29E S24 BT on partially healed blaze. (Record: 51 lks. dist.)</p> <p style="padding-left: 40px;">A piñon, 9 ins. diam., bears S 37 1/2° W, 52 1/2 lks. dist., mkd. T25N R29E S23 BT on open blaze. (Record: 96 lks. dist.)</p> <p style="padding-left: 40px;">A piñon, 7 ins. diam., bears N 46 1/4° W, 133 1/2 lks. dist., mkd. T25N R29E S14 BT on open blaze. (Record: 135 lks. dist.)</p>
	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>N 89°57' W, bet. secs. 13 and 24.</p>
	<p>Over rolling and broken land.</p>
36.80	<p>Trail road, bears N 10° E and S 10° W.</p>
40.15	<p>The 1/4 sec. cor. of secs. 13 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines of T 25 N, R 29 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears S 37 1/2° W, 85 lks. dist., with healed blaze. (Record: 86 lks. dist.)</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears N 55 1/2° W, 51 lks. dist., with healed blaze.</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	Add the marks T25N R29E 1986 to the brass cap.
	West, beginning new measurement.
2.90	Wash, 20 lks. wide, 1/2 ft. deep, drains S 30° W.
40.09	The cor. of secs. 13, 14, 23 and 24.
	N 0°04' E, bet. secs. 13 and 14.
	Over rolling and broken land.
19.99	Point for the S 1/16 sec. cor. of secs. 13 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to bedrock, supported in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T25N R29E S 1/16 S14 S13 1986</p>
	from which
	<p style="padding-left: 40px;">A forked piñon, 10 ins. diam. at the base, bears N 81 1/2° E, 98 1/2 lks. dist., mkd. S 1/16 S13 BT.</p>
	<p style="padding-left: 40px;">A piñon, 10 ins. diam., bears S 69 1/2° W, 33 1/2 lks. dist., mkd. S 1/16 S14 BT.</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.
39.98	The 1/4 sec. cor. of secs. 13 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines of T 25 N, R 29 E, from which the original bearing trees:
	<p style="padding-left: 40px;">A piñon, 18 ins. diam., bears S 36 1/4° E, 119 1/2 lks. dist., mkd. 4 S1 BT on partially healed blaze. (Record: S 36 3/4° E, 121 lks. dist.)</p>
	<p style="padding-left: 40px;">A piñon, 18 ins. diam., bears S 89 1/2° W, 133 1/2 lks. dist., mkd. 4 S14 on partially healed blaze. (Record: 132 lks. dist.)</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	Add the marks T25N R29E 1986 to the brass cap.
	N 0°02' E, beginning new measurement.
6.10	Trail road, bears N 60° E and S 60° W.
29.90	Trail road, bears N 50° E and S 50° W.
30.40	Wash, 60 lks. wide, 2 ft. deep, drains S 50° W.
37.35	Trail road, bears S 75° E and N 75° W.
39.96	The cor. of secs. 11, 12, 13 and 14, monumented with an iron post, 2 ins. diam., firmly set, projecting 29 ins. above ground, in a mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines of T 25 N, R 29 E, from which the original bearing trees:
	A ponderosa pine, 33 ins. diam., bears N 37 3/4° E, 173 lks. dist., with healed blaze.
	A ponderosa pine, 28 ins. diam., bears S 3 1/4° E, 49 lks. dist., mkd. T25N R29E S13 BT on partially healed blaze.
	A ponderosa pine, 32 ins. diam., bears S 84 1/2° W, 104 lks. dist., mkd. 29E on nearly healed blaze. (Record: S 83 1/4° W, 105 lks. dist.)
	A ponderosa pine, 23 ins. diam., bears N 33 3/4° W, 182 1/2 lks. dist., with healed blaze. (Record: N 34° W, 182 lks. dist.)
	From the cor. of secs. 7, 12, 13 and 18, on the E Bdy. of the Tp., hereinbefore described.
	N 89°58' W, bet. secs. 12 and 13.
	Over rolling land.
20.60	Trail road, bears N and S.
23.45	Trail road, bears N 60° E and S 60° W.
31.30	Wash, 30 lks. wide, 2 ft. deep, drains S 40° W.

BOOK 5302

Dependent Resurvey of the Subdivisional Lines
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
40.04	<p>The 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 1 in. diam., firmly set, projecting 27 ins. above ground, in a mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines of T 25 N, R 29 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears S 51 1/4° E, 115 1/2 lks. dist., with healed blaze. (Record: S 51 1/2° E, 116 lks. dist.)</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears N 29° W, 22 lks. dist., mkd. S12 BT in partially healed blaze.</p> <p>Add the marks T25N R29E 1986 to the brass cap.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>
	<p>S 89°58' W, beginning new measurement.</p>
34.50	<p>Wash, 30 lks. wide, 2 ft. deep, drains S 20° W.</p>
36.60	<p>Trail road, bears N 30° E and S 30° W.</p>
40.06	<p>The cor. of secs. 11, 12, 13 and 14.</p> <hr/>
	<p>N 0°04' E, bet. secs. 11 and 12.</p>
	<p>Over rolling land.</p>
40.01	<p>The 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines of T 25 N, R 29 E, from which the remaining original bearing tree:</p> <p style="padding-left: 40px;">A piñon, 16 ins. diam., bears N 52 1/4° E, 99 lks. dist., mkd. 1/4 S12 BT.</p> <p>from which a new bearing tree:</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears S 57° W, 143 lks. dist., mkd. 1/4 S11 BT.</p> <p>Add the marks T25N R29E 1986 to the brass cap.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	N 0°04' E, beginning new measurement.
19.00	Trail road, bears N 50° E and S 50° W.
39.98	<p>The cor. of secs. 1, 2, 11 and 12, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, in a mound of stone, 3 ft. diam., to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines of T 25 N, R 29 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">A ponderosa pine, 29 ins. diam., bears N 63 1/4° E, 61 lks. dist., with healed blaze. (Record: N 64° E)</p> <p style="padding-left: 40px;">A ponderosa pine, 21 ins. diam., bears S 58° E, 120 lks. dist., mkd. T25N R29E S12 on partially healed blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears S 60 1/4° W, 33 lks. dist., illegibly mkd. on partially healed blaze. (Record: S 60 1/4° W, 33 lks. dist.)</p> <p style="padding-left: 40px;">A ponderosa pine, 34 ins. diam., bears N 38 3/4° W, 97 lks. dist., mkd. T25N R29E S2 BT on partially healed blaze. (Record: N 38° W)</p>
	From the cor. of secs. 7, 12, 13 and 18, on the E Bdy. of the Tp., hereinbefore described.
	N 89°58' W, bet. secs. 1 and 12.
	Over rolling land.
9.65	Trail road, bears N 60° E and S 60° W.
20.90	Trail road, bears S 25° E and N 25° W.
37.95	Trail road, bears N 25° E and S 25° W.
40.03	<p>The 1/4 sec. cor. of secs. 1 and 12, determined from the original bearing trees, situated in a mound of stone, 2 1/2 ft. base, 10 ins. high.</p> <p>from which the original bearing trees:</p> <p style="padding-left: 40px;">A ponderosa pine, 25 ins. diam., bears S 68 1/2° E, 114 lks. dist., with healed blaze</p>

BOOK 5302Dependent Resurvey of the Subdivisional Lines
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 23 ins. diam., bears N 5 3/4° W, 81 lks. dist., with healed blaze. (Record: N 6 1/2° W)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25N R29E S 1 1/4 — S12 1986</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p> <hr/> <p>West, beginning new measurement.</p>
28.20	Trail road, bears N 55° E and S 55° W.
29.10	Trail road, bears N 10° E and S 10° W.
40.02	The cor. of secs. 1, 2, 11 and 12.
	<hr/> <p>N 0°01' W, bet. secs. 1 and 2.</p> <p>Over rolling land.</p>
7.40	Underground gas pipeline and trail road, bears N 70° E and S 70° W.
39.00	Trail road, bears N 70° E and S 70° W.
39.99	The 1/4 sec. cor. of secs. 1 and 2, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines of T 25 N, R 29 E, from which the original bearing trees:
	<p>A ponderosa pine, 30 ins. diam., bears S 31 1/2° E, 130 lks. dist., with healed blaze.</p> <p>A forked ponderosa pine, 24 ins. diam., bears West, 103 lks. dist., with healed blaze.</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	Add the marks T25N R29E 1986 to the brass cap.
	N 0°03' W, beginning new measurement.
26.50	Trail road, bears N 80° E and S 80° W.
40.80	Underground gas line and trail road, bears E and W.
41.82	<p>The closing cor. of secs. 1 and 2, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines of T 25 N, R 29 E.</p> <p>From this cor., the cor. of secs. 35 and 36, T 26 N, R 29 E, bears S 89°48' W, 2.06 chs. dist., monumented with an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1984 resurvey of the S bdy. of T 26 N, R 29 E.</p>
	<p>The 1/4 sec. cor. of sec. 1 only, is monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, witnessed and with brass cap mkd. as described in the official record of the 1984 Resurvey of the S bdy. of T 26 N, R 29 E.</p>
	Add the marks T26N R29E T25N R29E 1986 to the brass cap.
	<p>From this cor., the 1/4 sec. cor. of sec. 36 only, T 26 N, R 29 E, bears S 89°55' W, 2.06 chs. dist., monumented with an stainless steel post, 2 1/2 ins. diam., set, mkd. and witnessed as described in the official record of the 1984 resurvey of the S bdy. of T 26 N, R 29 E.</p>
	<p>From the stan. cor. of secs. 34 and 35, on the S bdy. of the Tp., hereinbefore described.</p>
	N 0°04 'W, bet. secs. 34 and 35.
	Over rolling and broken land.
12.60	The W fork of Black Creek, 200 lks. wide, drains S 60° E.
40.00	The 1/4 sec. cor. of secs. 34 and 35, determined from the original bearing trees:

BQQK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A dead piñon, 15 ins. diam., bears N 9 3/4° E, 28 lks. dist., mkd. S35 BT on open blaze. (Record: N 6 1/2° E)</p>
	<p>A dead piñon, 16 ins. diam., bears S 25 1/2° W, 260 lks. dist., mkd. S34 BT on open blaze. (Record: S 25 3/4° W)</p>
	<p>At the cor. point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with a collar of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T25N R29E 1/4 S34 S35 1985</p>
	<p>from which</p>
	<p>A piñon, 7 ins. diam., bears S 33 1/2° E, 101 1/2 lks. dist., mkd. 1/4 S35 BT.</p>
	<p>A piñon, 8 ins. diam., bears N 34° W, 116 lks. dist., mkd. 1/4 S34 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p>
	<p>From this cor., a sandstone of unknown origin, firmly set, 4 x 3 x 12 ins. above ground, mkd. 1/4 on the W face, bears S 74°38' W, 99 lks. dist.</p>
	<p style="text-align: center;">_____</p> <p>N 0°03' E, beginning new measurement.</p>
40.00	<p>The cor. of secs. 26, 27, 34 and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, alongside which is laying a sandstone, of unknown origin, 14 x 7 x 2 ins., mkd. IA on a face, from which the original bearing trees:</p>
	<p>A piñon, 12 ins. diam., bears N 34° E, 111 1/2 lks. dist., with healed blaze. (Record: 111 lks. dist.)</p>
	<p>A piñon, 13 ins. diam., bears S 50° E, 382 lks. dist., mkd. S35 on partially healed blaze. (Record: 370 lks. dist.)</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A piñon, 18 ins. diam. at the base, bears S 83 1/2° W, 326 lks. dist., mkd. T25N R29E S34 BT on partially healed blaze. (Record: S 78 1/2° W, 323 lks. dist.)</p> <p>A piñon, 18 ins. diam. at the base, bears N 59° W, 313 lks. dist., illegibly mkd. on partially healed blaze. (Record: N 59 1/4° W, 314 lks. dist.)</p> <p>Cor. is located 105 lks. N. of a trail road, bears N 25° E and S 25° W.</p>
	<hr/> <p>From the cor. of secs. 25, 26, 35 and 36. N 89°57' W, bet. secs. 26 and 35. Over rolling and broken land.</p>
39.99	<p>The 1/4 sec. cor. of secs. 26 and 35, determined from the original bearing trees</p> <p>A piñon, 15 ins. diam., bears N 77 3/4° E, 124 lks. dist., mkd. 1/4 S26 BT on partially healed blaze. (Record: N 77 1/2° E)</p> <p>A dead piñon, 17 ins. diam., bears S 50 1/2° E, 53 lks. dist., mkd. 1/4 S35 BT on open blaze. (Record: S 52 1/2° E)</p> <p>This is accepted as the best remaining evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25N R29E S26 1/4 — S35 1986</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p>
	<p>A piñon, 13 ins. diam., bears S 47 1/4° E, 126 lks. dist., mkd. 1/4 S35 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p>
	<p>S 89°58' W, beginning new measurement.</p>
40.04	<p>The cor. of secs. 26, 27, 34 and 35.</p>
	<p>N 0°01' W, bet. secs. 26 and 27.</p>
	<p>Over rolling and broken land.</p>
39.99	<p>The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, bent to the E, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E.</p>
	<p>At the cor. point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p>T25N R29E</p>
	<p>1/4</p>
	<p>S27 S26</p>
	<p>1986</p>
	<p>Deposit the brass cap alongside the stainless steel post and destroy the iron post.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p>
	<p>N 0°03' W, beginning new measurement.</p>
6.05	<p>Trail road, bears S 65° E and N 65° W.</p>
40.00	<p>The cor. of secs. 22, 23, 26 and 27, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 28 ins. diam., bears N 34 1/2° E, 115 1/2 lks. dist., illegibly mkd. on partially healed blaze. (Record: N 33 1/2° E, 116 lks. dist.)</p> <p>A ponderosa pine, 10 ins. diam., bears S 54 3/4° E, 70 lks. dist., mkd. T25N R29E S26 BT on open blaze. (Record: S 5 3/4° E)</p> <p>A ponderosa pine, 31 ins. diam., bears S 52 3/4° W, 39 1/2 lks. dist., with healed blaze. (Record: 39 lks. dist.)</p> <p>A dead ponderosa pine, 10 ft. high, 27 ins. diam., bears N 21 1/4° W, 197 lks. dist., mkd. T25N R29E S22 BT on open blaze. (Record: N 21° W)</p> <p>from which a new bearing tree:</p> <p>A ponderosa pine, 13 ins. diam., bears N 27° W, 97 lks. dist., mkd. T25N R29E S22 BT.</p> <p>Add the marks 1986 to the brass cap.</p> <p>Cor. is located 130 lks. E of the center of a wash, 1 ch. wide, 15 ft. deep, drains SW.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S 89°58' W, bet. secs. 23 and 26.</p> <p>Over rolling land.</p> <p>18.60 Wash, 15 lks. wide, 4 ft. deep, drains S 10° W.</p> <p>31.65 Trail road, bears N 20° E and S 20° W.</p> <p>40.02 The 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A piñon, 16 ins. diam., bears S 48 1/2° W, 196 1/2 lks. dist., with healed blaze. (Record: S 58 1/2° W, 196 lks. dist.)</p> <p>A ponderosa pine, 36 ins. diam., bears N 60 1/4° W, 41 1/2 lks. dist., with healed blaze. (Record: N 60° W, 42 lks. dist.)</p> <p>Add the marks T25N R29E 1986 to the brass cap.</p> <hr/> <p>West, beginning new measurement.</p>
7.10	Trail road, bears S 70° E and N 70° W.
39.91	The cor. of secs. 22, 23, 26 and 27.
	<hr/> <p>N 0°04' W, bet. secs. 22 and 23.</p> <p>Over rolling and broken land.</p>
20.00	<p>Point for the S 1/16 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25N R29E S 1/16 S22 S23 1986</p> <p>from which</p> <p>A piñon, 11 ins. diam., bears N 84° E, 146 1/2 lks. dist., mkd. S 1/16 S23 BT.</p> <p>An oak, 9 ins. diam., bears N 71 1/2° W, 83 1/2 lks. dist., mkd. S 1/16 S22 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
34.13	Barbed wire fence, 3 strand, extending N 65° E and S 65° W.
40.00	<p>The 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, alongside which is laying a sandstone, of unknown origin, 19 x 6 x 5 ins., mkd. IA on a face, from which the original bearing trees:</p> <p style="padding-left: 40px;">A ponderosa pine, 34 ins. diam., bears N 53° E, 134 lks. dist., mkd. 1/4 S23 BT on open blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 31 ins. diam., bears N 39 3/4° W, 118 1/2 lks. dist., mkd. 4 S22 BT on partially healed blaze. (Record: N 40° W, 120 lks. dist.)</p> <p>Add the marks T25N R29E 1986 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°05' W, beginning new measurement.</p>
19.985	<p>Point for the N 1/16 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> T25N R29E N 1/16 S22 S23 1986 </div> <p>from which</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears N 58 1/2° E, 45 lks. dist., mkd. N 1/16 S23 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 5 ins. diam., bears S 64 3/4° W, 18 1/2 lks. dist., mkd. X at 3 ft. above ground and BT at the base.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p>
39.97	<p>The cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2 ins. diam., firmly set in a collar of stone, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine stump, 31 ins. diam., bears N 70 1/2° E, 180 lks. dist., mkd. 4 BT on remnant of open blaze. (Record: N 75 3/4° E, 179 lks. dist.)</p> <p>A ponderosa pine, 32 ins. diam., bears S 48 3/4° E, 264 1/2 lks. dist., illegibly mkd. on partially healed blaze. (Record: S 48 1/2° E, 266 lks. dist.)</p> <p>A ponderosa pine, 23 ins. diam., bears S 43 1/4° W, 215 lks. dist., illegibly mkd. on partially healed blaze. (Record: S 43 1/2° W, 216 lks. dist.)</p> <p>A ponderosa pine, 25 ins. diam., bears N 17° W, 117 lks. dist., illegibly mkd. on partially healed blaze. (Record: N 22 3/4° W)</p> <p>from which a new bearing tree:</p> <p>A ponderosa pine, 9 ins. diam., bears N 29 3/4° E, 59 lks. dist., mkd. T25N R29E S14 BT.</p> <p>Add the marks 1986 to the brass cap.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S 89°55' W, bet. secs. 14 and 23.</p> <p>Over rolling land.</p>
40.00	<p>The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p> <p>A piñon, 10 ins. diam., bears N 15° E, 28 lks. dist., mkd. 1/4 S 14 BT on open blaze. (Record: N 15 1/4° E)</p> <p>A piñon, 11 ins. diam., bears S 32° E, 28 1/2 lks. dist., mkd. 1/4 S 23 BT on open blaze. (Record: S 33° E, 28 lks. dist.)</p> <p>Add the marks T25N R29E 1986 to the brass cap.</p> <hr/> <p>S 89°59' W, beginning new measurement.</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
15.39	Barbed wire fence, 3 strand, extending S 15° E and N 14° W.
39.98	The cor. of secs. 14, 15, 22 and 23.
<hr/>	
N 0°03' E, bet. secs. 14 and 15.	
Over rolling and broken land.	
4.90	Wash, 30 lks. wide, 4 ft. deep, drains S 70° W.
19.98	Point for the S 1/16 sec. cor. of secs. 14 and 15.
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.	
<p style="text-align: center;">T25N R29E S 1/16 S15 S14 1986</p>	
from which	
<p style="margin-left: 40px;">A ponderosa pine, 13 ins. diam., bears N 77 3/4° E, 151 1/2 lks. dist., mkd. S 1/16 S14 BT.</p>	
<p style="margin-left: 40px;">A ponderosa pine, 12 ins. diam., bears N 56 1/2° W, 143 lks. dist., mkd. S 1/16 S15 BT.</p>	
Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.	
23.45	Barbed wire fence, 3 strand, extending S 55° E and N 55° W.
39.96	The 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 20 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:
<p style="margin-left: 40px;">A dead piñon, 11 ins. diam., bears N 61 1/2° E, 73 lks. dist., mkd. 1/4 S14 BT on open blaze. (Record: N 61 3/4° E)</p>	
<p style="margin-left: 40px;">A dead piñon, 26 ins. diam., bears N 70 3/4° W, 146 lks. dist., mkd. 1/4 S15 BT on open blaze. (Record: N 71° W, 155 lks. dist.)</p>	

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS

from which the new bearing trees:

A ponderosa pine, 10 ins. diam., bears N 67° E,
88 1/2 lks. dist., mkd. 1/4 S14 BT.

A ponderosa pine, 10 ins. diam., bears S 71° W,
58 1/2 lks. dist., mkd. 1/4 S15 BT.

Add the marks T25N R29E 1986 to the brass cap.

N 0°01' E, beginning new measurement.

39.98

The cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, alongside which is laying a sandstone, of unknown origin, 24 x 7 x 4 ins., mkd. IA and 2 grooves on one face, and 4 grooves on another face, from which the original bearing trees:

A piñon, 12 ins. diam., bears N 77° E, 63 lks. dist., mkd. T25N R29E S11 BT on partially healed blaze.

A multiple forked piñon, 15 ins. diam. at the base, bears S 63 1/2° E, 65 lks. dist., mkd. T25N R29E S14 BT on partially healed blaze.

A decaying piñon stump, 4 ins. diam., bears S 43 1/2° E, 35 lks. dist., alongside which is laying a piñon log, 4 ins. diam., illegibly mkd. on open blaze.

A piñon, 13 ins. diam., bears N 71 3/4° W, 9 lks. dist., illegibly mkd. on partially healed blaze.
(Record: N 73° W)

from which a new bearing tree:

A forked piñon, 13 ins. diam., bears S 50 3/4° W,
74 lks. dist., mkd. X BT.

Destroy the marked stone.

Add the marks 1986 to the brass cap.

From the cor. of secs. 11, 12, 13 and 14.

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	S 89°56' W, bet. secs. 11 and 14.
	Over rolling and broken land.
40.01	The 1/4 sec. cor. of secs. 11 and 14, monumented with an X chiseled in sandstone bedrock, in a scattered mound of stone, 10 ft. diam., from which the original bearing trees:
	A ponderosa pine, 12 ins. diam., bears N 55 1/2° E, 43 lks. dist., illegibly mkd. on partially healed blaze. (Record: N 56° E, 45 lks. dist.)
	A ponderosa pine, 17 ins. diam., bears S 9 1/4° E, 28 lks. dist., mkd. S 14 BT on partially healed blaze.
	At the cor. point
	Set an aluminum post, 12 ins. long, 1 in. diam., 8 ins. in a drill hole, in sandstone bedrock, cemented in place, encircled with a collar of stone, 2 ft. base, to top, with aluminum cap mkd.
	<p style="text-align: center;">T25N R29E S11 1/4 — S14 1986</p>
	S 89°59' W, beginning new measurement.
5.80	Wash, 30 lks. wide, 6 ft. deep, drains S 60° W.
20.70	Trail road, bears S and N 10° W in curve.
39.98	The cor. of secs. 10, 11, 14 and 15.
	N 0°11' W, bet. secs. 10 and 11.
	Over rolling land.
40.03	The 1/4 sec. cor. of secs. 10 and 11, determined from the original bearing trees:
	A ponderosa pine, 29 ins. diam., bears S 73 3/4° E, 176 lks. dist., with healed blaze. (Record: S 73 1/2° E)

53
BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 23 ins. diam., bears S 23 1/4° W, 93 lks. dist., with healed blaze. (Record: S 25° W)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R29E 1/4 S10 S11 1986</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 100 lks. E of a wash, 30 lks. wide, 2 ft. deep, drains S 10° W, and 180 lks. S of the same wash, 20 lks. wide, 2 ft. deep, drains S 20° W.</p> <hr/> <p>N 0°04' W, beginning new measurement.</p> <p>21.30 Underground gas pipeline and trail road, bears N 68° E and S 68° W.</p> <p>40.00 The cor. of secs. 2, 3, 10 and 11, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, alongside which is laying a sandstone, of unknown origin, 24 x 11 x 4 ins., mkd. with 5 grooves on one face, 2 grooves on another face and IA on another face, from which the original bearing trees:</p> <p style="padding-left: 40px;">A ponderosa pine, 26 ins. diam., bears N 2 1/2° E, 214 lks. dist., with healed blaze. (Record: 224 lks. dist.)</p> <p style="padding-left: 40px;">A ponderosa pine, 30 ins. diam., bears S 67° E, 63 1/2 lks. dist., with healed blaze. (Record: 94 lks. dist.)</p> <p style="padding-left: 40px;">A ponderosa pine, 25 ins. diam., bears S 17 1/4° W, 62 1/2 lks. dist., with healed blaze. (Record: S 12 1/2° W, 63 lks. dist.)</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 38 ins. diam., bears N 48° W, 190 lks. dist., with healed blaze. (Record: N 47 1/2° W, 192 lks. dist.)</p>
	<p>Destroy the marked stone.</p>
	<p>Cor. is located at the cor. of a barbed wire fence, 5 strand, extending N and E, 50 lks. E of a wash, 12 lks. wide, 1 ft. deep, drains S 20° W.</p>
	<p>From the cor. of secs. 1, 2, 11 and 12.</p>
	<p>S 89°59' W, bet. secs. 2 and 11.</p>
	<p>Over rolling and broken land.</p>
40.11	<p>The 1/4 sec. cor. of secs. 2 and 11, determined from the original bearing trees:</p>
	<p>A piñon, 11 ins. diam., bears N 33 1/2° E, 166 lks. dist., illegibly mkd. on partially healed blaze. (Record: N 33° E)</p>
	<p>A ponderosa pine, 24 ins. diam., bears S 63° E, 82 lks. dist., illegibly mkd. on partially healed blaze, which has been chopped on. (Record: S 63 1/2° E)</p>
	<p>At the cor. point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T25N R29E S 2 1/4 — S11 1986</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p>
	<p>Cor. is located N 68° W, 23 1/2 lks. dist. from the cor. of a barbed wire fence, 5 strand, extending N and W.</p>
	<p>S 89°59' W, beginning new measurement.</p>
40.11	<p>The cor. of secs. 2, 3, 10 and 11.</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	N 0°01' W, bet. secs. 2 and 3.
	Over rolling land.
33.80	Wash, 20 lks. wide, 2 ft. deep, drains S 10° W.
39.99	<p>The 1/4 sec. cor. of secs. 2 and 3, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the remaining original bearing tree:</p> <p style="padding-left: 40px;">A ponderosa pine, 38 ins. diam., bears S 58 1/2° E, 267 1/2 lks. dist., mkd. S2 BT on partially healed blaze. (Record: 268 lks. dist.)</p> <p>from which a new bearing tree:</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S 14 1/4° W, 50 lks. dist., mkd. 1/4 S3 BT.</p> <p>Add the marks T25N R29E 1986 to the brass cap.</p> <p>Cor. is located on the W edge of an open field; 90 lks. W of a wash, 5 lks. wide, 1 ft. deep, drains S 10° W; and 220 lks. E of a barbed wire fence, 5 strand, extending N 10° E and S 10° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>North, beginning new measurement.</p>
14.04	Barbed wire fence, 4 strand, extending N 10° E and S 10° W.
15.60	Trail road, bears N 10° E and S 10° W.
40.30	Underground gas pipeline and trail road, bears E and W.
41.57	<p>The closing cor. of secs. 2 and 3, monumented with an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1984 resurvey of the S. bdy., T 26 N, R 29 E.</p> <p>From this cor., the cor. of secs. 34 and 35, T 26 N, R 29 E, bears S 89°48' W, 1.93 chs. dist., monumented with an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1984 resurvey of the S bdy., T 26 N, R 29 E.</p> <hr style="width: 60%; margin: 10px auto;"/>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	<p>The 1/4 sec. cor. of sec. 2 only, is monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the official record of the 1927 resurvey of the S bdy., T 26 N, R 29 E.</p> <p>from which a new bearing tree:</p> <p style="padding-left: 40px;">An oak, 8 ins. diam., bears S 24 1/4° W, 73 lks. dist., mkd. 1/4 S2 BT.</p> <p>Add the marks T26N R29E T25N R29E 1986 to the brass cap.</p> <p>From this cor., the 1/4 sec. cor. of sec. 35 only, T 26 N, R 29 E, bears S 89°50' W, 1.91 chs. dist., monumented with an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record of the 1984 resurvey of the S bdy., T 26 N, R 29 E.</p> <hr/> <p>From the stan. cor. of secs. 33 and 34, on the S bdy. of the Tp., hereinbefore described.</p> <p>N 0°03' W, bet. secs. 33 and 34.</p> <p>Over rolling and broken land.</p> <p>27.55 Trail road, bears N 85° E and S 85° W.</p> <p>39.98 The 1/4 sec. cor. of secs. 33 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, bent to the W, in an embedded collar of stone, 3 ft. base, flush with the surface of the ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines of T 25 N, R 29 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">A ponderosa pine stump, 37 ins. diam., bears N 33 1/4° E, 369 1/2 lks. dist., with decaying blaze. (Record: N 33° E, 370 lks. dist.)</p> <p style="padding-left: 40px;">A piñon, 17 ins. diam. at the base, bears N 11 3/4° W, 416 1/2 lks. dist., mkd. 1/4 S33 BT on open blaze. (Record: N 12° W, 415 lks. dist.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, 2 ft. base, to top, with brass cap mkd.</p>
--------	---

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	T25N R29E 1/4 S33 S34 1986
	from which A ponderosa pine, 14 ins. diam., bears N 42° E, 175 lks. dist., mkd. 1/4 S34 BT. Destroy the iron post and brass cap. Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post. <hr style="width: 20%; margin: auto;"/> N 0°02' W, beginning new measurement.
16.00	Wash, 75 lks. wide, 10 ft. deep, drains S 50° E.
27.30	Wash, 30 lks. wide, 6 ft. deep, drains S 30° E.
40.00	The cor. of secs. 27, 28, 33 and 34, monumented with an X chiseled in sandstone bedrock, in a mound of stone, 6 ft. diam., 2 ft. high, from which the original bearing trees: A ponderosa pine, 28 ins. diam., bears N 63 3/4° E, 118 lks. dist., illegibly mkd. on partially healed blaze. (Record: N 63 1/2° E, 119 lks. dist.) A piñon, 13 ins. diam., bears S 68 3/4° E, 222 lks. dist., mkd. T25N R29E S34 BT on partially healed blaze. (Record: S 69° E) A forked piñon, 10 ins. diam. at the base, bears S 28° W, 177 lks. dist., mkd. T25N R29E S33 BT on partially healed blaze. (Record: 176 lks. dist.) A ponderosa pine, 26 ins. diam., bears N 43 3/4° W, 110 1/2 lks. dist., with healed blaze. (Record: N 38 1/2° W, 110 lks. dist.)
	At the cor. point Set an aluminum post, 14 ins. long, 1 in. diam., 6 ins. in a drill hole, 8 ins. deep, in sandstone bedrock, cemented in place, encircled with a collar of stone, 5 ft. base, to top, with aluminum cap mkd.

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	<table border="1"> <tr> <td>T25N</td> <td>R29E</td> </tr> <tr> <td>S28</td> <td>S27</td> </tr> <tr> <td>S33</td> <td>S34</td> </tr> <tr> <td colspan="2">1986</td> </tr> </table>	T25N	R29E	S28	S27	S33	S34	1986			
T25N	R29E										
S28	S27										
S33	S34										
1986											
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S 89°56' W, bet. secs. 27 and 34.</p> <p>Over rolling and broken land.</p> <p>31.10 Wash, 30 lks. wide, 10 ft. deep, drains S.</p> <p>40.00 The 1/4 sec. cor. of secs. 27 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, bent to the N, in an embedded collar of stone, 2 ft. base, flush with the surface of the ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the remains of the original bearing trees:</p> <p style="padding-left: 40px;">The base of a piñon log, 12 ins. diam., laying atop the ground, bears S 33° W, 24 lks. dist., mkd. 1/4 S34 BT on open blaze. (Record: S 23 1/4° W, 23 lks. dist.)</p> <p style="padding-left: 40px;">The base of a piñon log, 12 ins. diam., laying atop the ground, bears N 35° W, 56 1/2 lks. dist., illegibly mkd. on burnt blaze. (Record: N 30° W, 58 lks. dist.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <table border="1"> <tr> <td>T25N</td> <td>R29E</td> </tr> <tr> <td></td> <td>S27</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S34</td> </tr> <tr> <td colspan="2">1986</td> </tr> </table> </p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 16 ins. diam., bears S 22 1/2° E, 70 lks. dist., mkd. 1/4 S34 BT.</p>	T25N	R29E		S27	1/4	—		S34	1986	
T25N	R29E										
	S27										
1/4	—										
	S34										
1986											

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Bury the brass cap alongside the stainless steel post and destroy the iron post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, 1 ft. N of the cor.</p> <hr/> <p>West, beginning new measurement.</p>
40.01	<p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/> <p>N 0°07' W, bet. secs. 27 and 28.</p> <p>Over rolling and broken land.</p>
39.98	<p>The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., loosely set, projecting 12 ins. above ground, bent to the NE, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the remains of the original bearing trees:</p> <p style="padding-left: 40px;">The base of a piñon log, 13 ins. diam., laying atop the ground, bears N 76 1/2° E, 95 1/2 lks. dist., mkd. 1/4 S27 BT on partially healed blaze. (Record: N 70° E, 84 lks. dist.)</p> <p style="padding-left: 40px;">The base of a piñon log, 20 ins. diam., laying atop the ground, bears S 41 1/4° W, 165 lks. dist., mkd. 1/4 S28 BT on partially healed blaze. (Record: S 54 1/4° W, 179 lks. dist.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with a collar of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25N R29E 1/4 S28 S27 1986</p> <p>Bury the brass cap alongside the stainless steel post and destroy the iron post.</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p> <hr/> <p>N 0°07' W, beginning new measurement.</p>
32.00	Trail road, bears S 60° E and N 60° W.
39.99	<p>The cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the remaining original bearing trees:</p> <p style="padding-left: 40px;">A piñon, 14 ins. diam., bears N 89 1/2° E, 198 1/2 lks. dist., mkd. T25N R29E S22 BT on open blaze. (Record: N 89 3/4° E, 200 lks. dist.)</p> <p style="padding-left: 40px;">The base of a piñon log, 13 ins. diam., laying atop the ground, bears S 67 1/2° W, 209 1/2 lks. dist., mkd. T25N R29E S28 BT on open blaze. (Record: S 64 1/2° W, 183 lks. dist.)</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S 89°59' W, bet. secs. 22 and 27.</p> <p>Over rolling land.</p>
20.80	Trail road, bears S 20° E and N 20° W.
40.07	<p>The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">A piñon, 14 ins. diam. at the base, bears S 82 1/2° W, 115 lks. dist., illegibly mkd. on partially healed blaze. (Record: S 82 3/4° W)</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam. at the base, bears N 61 3/4° W, 108 1/2 lks. dist., mkd. 1/4 S22 BT on partially healed blaze. (Record: N 61 1/2° W, 109 lks. dist.)</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Add the marks T25N R29E 1986 to the brass cap.</p> <hr/> <p>S 89°55' W, beginning new measurement.</p>
40.02	<p>The cor. of secs. 21, 22, 27 and 28.</p> <hr/> <p>North, bet. secs. 21 and 22.</p> <p>Over rolling land.</p>
12.45	<p>Trail road, bears N 40° E and S 40° W.</p>
19.995	<p>Point for the S 1/16 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25N R29E S 1/16 S21 S22 1986</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 11 ins. diam., bears S 68 3/4° E, 85 lks. dist., mkd. S 1/16 S22 BT.</p>
26.85	<p>Trail road, bears E and W.</p>
30.05	<p>Trail road, bears E and W.</p>
39.99	<p>The 1/4 sec. cor. of secs. 21 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, alongside which is laying a sandstone, of unknown origin, 12 x 5 x 2 1/2 ins., mkd. 1/4 on one face, from which the original bearing trees:</p> <p style="padding-left: 40px;">A piñon, 14 ins. diam., bears N 28 1/2° E, 127 1/2 lks. dist., mkd. 1/4 S22 BT on partially healed blaze. (Record: N 28° E, 127 lks. dist.)</p> <p style="padding-left: 40px;">A piñon, 11 ins. diam., bears S 36° W, 81 lks. dist., mkd. 1/4 S21 BT on partially healed blaze.</p> <p>Destroy the marked stone.</p> <hr/>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	N 0°03' W, beginning new measurement.
20.00	Point for the N 1/16 sec. cor. of secs. 21 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	22 ins. in the ground, with brass cap mkd.
	T25N R29E
	N 1/16
	S21 S22
	1986
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic
	case beneath the stainless steel post.
	From this cor., a sandstone, of unknown origin,
	14 x 9 x 1 1/2 ins., laying loose atop the ground, with illegible
	chisel marks visible on one face, bears S 67 1/4° W, 19 lks.
	dist. Destroy the marked stone.
40.00	The cor. of secs. 15, 16, 21 and 22, monumented with an iron
	post, 2 ins. diam., firmly set, projecting 8 ins. above ground,
	with brass cap mkd. as described in the official record of the
	1927 survey of the subdivisional lines, T 25 N, R 29 E.
	from which a new bearing tree:
	A piñon, 9 ins. diam. at the base, bears S 25 1/4° E,
	63 1/2 lks. dist., mkd. X at waist height and BT at the
	base.
	From the cor. of secs. 14, 15, 22 and 23.
	S 89°57' W, bet. secs. 15 and 22.
	Over rolling and broken land.
4.30	Wash, 6 lks. wide, 2 ft. deep, drains S 20° W.
16.80	E rim of small canyon, 15 ft. high, bears S 40° E and N 40° W.
23.70	Wash, 30 lks. wide, 6 ft. deep, drains S 8° E.
27.92	Barbed wire fence, 4 strand, extending S 60° E and N 60° W.

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
29.30	Trail road, bears S 60° E and N 60° W.
36.00	W rim of small canyon, 15 ft. high, bears S 60° E and N 60° W.
39.96	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">A piñon, 12 ins. diam., bears N 53 3/4° E, 8 lks. dist., mkd. 1/4 S15 BT on partially healed blaze. (Record: N 56°E)</p> <p style="padding-left: 40px;">A piñon, 16 ins. diam., bears S 3° W, 20 lks. dist., mkd. 1/4 S22 BT on partially healed blaze.</p> <p>Add the marks T25N R29E 1986 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="padding-left: 40px;">S 89°57' W, beginning new measurement.</p>
31.05	Barbed wire fence, 3 strand, extending S 20° E and N 20° W.
31.75	Trail road, bears S 10° E and N 10° W.
40.04	The cor. of secs. 15, 16, 21 and 22.
	<hr style="width: 100%;"/> <p>N 0°02' W, bet. secs. 15 and 16.</p> <p>Over rolling land.</p>
19.70	Trail road, bears S 50° E and N 50° W.
39.98	<p>The 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, in a collar of stone, 2 ft. base, 1 ft. high, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">A dead piñon, 16 ins. diam., bears S 75 1/2° E., 122 lks. dist., mkd. 1/4 S15 BT on open blaze. (Record: S 76° E)</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A piñon, 14 ins. diam., bears S 42 1/2° W, 141 1/2 lks. dist., mkd. 1/4 S16 BT on partially healed blaze. (Record: 141 lks. dist.)</p> <p>from which a new bearing tree:</p> <p>A piñon, 10 ins. diam., bears S 52 1/2° E, 161 1/2 lks. dist., mkd. 1/4 S15 BT.</p> <p>Add the marks T25N R29E 1986 to the brass cap.</p> <hr/> <p>N 0°02' W, beginning new measurement.</p>
15.00	Wash, 15 lks. wide, 4 ft. deep, drains S 50° E.
39.99	<p>The cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2 ins. diam., firmly set, projecting 3 ins. above ground, in a collar of stone, 2 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p> <p>A ponderosa pine, 40 ins. diam., bears N 54 1/4° E, 210 lks. dist., with healed blaze. (Record: N 54 3/4° E)</p> <p>A ponderosa pine, 25 ins. diam., bears S 44 1/4° E, 102 lks. dist., with healed blaze. (Record: S 44° E, 100 lks. dist.)</p> <p>A ponderosa pine, 29 ins. diam., bears S 69 3/4° W, 106 1/2 lks. dist., mkd. T25N R29E S16 BT on open blaze. (Record: 108 lks. dist.)</p> <p>A decaying ponderosa pine stump, 35 ins. diam., bears N 25 3/4° W, 208 1/2 lks. dist., alongside which is laying a ponderosa pine log, 35 ins. diam., mkd. T25N R29E S9 on open blaze. (Record: N 26° W, 201 lks. dist.)</p> <p>from which a new bearing tree:</p> <p>A ponderosa pine, 13 ins. diam., bears N 2 3/4° W, 141 lks. dist., mkd. T25N R29E S9 BT.</p> <p>Add the marks 1986 to the brass cap.</p> <hr/>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	From the cor. of secs. 10, 11, 14 and 15.
	S 89°54' W, bet. secs. 10 and 15.
	Over rolling and broken land.
40.06	The 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, in a collar of stone, 2 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the remains of the original bearing trees:
	A ponderosa pine stump,, 28 ins. diam., bears N 45° E, 34 lks. dist., with no visible blaze. (Record: N 45 1/4° E)
	A root hole, bears S 6 1/4° W, 46 lks. dist., alongside which is laying a ponderosa pine log, 22 ins. diam., mkd. 1/4 S15 BT on open blaze. (Record: S 5 1/2 E, 48 lks. dist.)
	from which the new bearing trees:
	A ponderosa pine, 8 ins. diam., bears N 5 3/4° E, 101 1/2 lks. dist., mkd. 1/4 S10 BT.
	A ponderosa pine, 25 ins. diam., bears S 50° W, 69 lks. dist., mkd. 1/4 S15 BT.
	Add the marks T25N R29E 1986 to the brass cap.
	Cor. is located 75 lks. E of a wash, 15 lks. wide, 2 ft. deep, drains S 50° W.
	<hr/> N 89°57' W, beginning new measurement.
40.01	The cor. of secs. 9, 10, 15 and 16.
	<hr/> N 0°04' W, bet. secs. 9 and 10.
	Over rolling and broken land.
5.00	Wash, 20 lks. wide, 2 ft. deep, drains S 30° E.

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
22.70	Top of earthen dam with trail road, 20 ft. high, bears S 86° E and N 86° W.
40.00	<p>The 1/4 sec. cor. of secs. 9 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">A ponderosa pine, 22 ins. diam., bears N 27 1/2° E, 22 lks. dist., illegibly mkd. on partially healed blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 28 ins. diam., bears S 27 1/2° W, 128 1/2 lks. dist., with healed blaze. (Record: S 22 1/2° W, 129 lks. dist.)</p> <p>Add the marks T25N R29E 1986 to the brass cap.</p> <p>Cor. is located 150 lks. W of a wash, 30 lks. wide, 1 ft. deep, drains S 10° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°02' W, beginning new measurement.</p>
10.90	Underground gas pipeline and trail road, bears N 80° E and S 80° W.
39.98	<p>The cor. of secs. 3, 4, 9 and 10, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">An oak, 18 ins. diam., bears N 18 1/2° E, 194 1/2 lks. dist., with healed blaze. (Record: N 18 3/4° E, 215 lks. dist.)</p> <p style="padding-left: 40px;">An oak, 9 ins. diam., bears S 46° E, 127 lks. dist., with healed blaze. (Record: S 45 1/2° E)</p> <p style="padding-left: 40px;">A ponderosa pine, 25 ins. diam., bears S 65° W, 196 1/2 lks. dist., illegibly mkd. on partially healed blaze. (Record: 197 lks. dist.)</p> <p style="padding-left: 40px;">A ponderosa pine, 36 ins. diam., bears N 47 3/4° W, 163 1/2 lks. dist., with healed blaze. (Record: 164 lks. dist.)</p> <hr style="width: 60%; margin: 10px auto;"/>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	From the cor. of secs. 2, 3, 10 and 11.
	S 89°56' W, bet. secs. 3 and 10.
	Over rolling land.
39.98	The 1/4 sec. cor. of secs. 3 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:
	A ponderosa pine, 24 ins. diam., bears N 3 1/4° E, 35 lks. dist., with healed blaze. (Record: N 2 1/2° E, 35 lks. dist.)
	A ponderosa pine stump, 23 ins. diam., bears S 16 3/4° W, 82 lks. dist., with no scribing visible on remnant of open blaze.
	from which a new bearing tree:
	A ponderosa pine, 28 ins. diam., bears S 38 1/4° E, 129 lks. dist., mkd. 1/4 S10 BT.
	Add the marks T25N R29E 1986 to the brass cap.
	<hr/> S 89°57' W, beginning new measurement.
3.40	Wash, 15 lks. wide, 1/2 ft. deep, drains S 60° W.
9.00	Trail road, bears N 55° E and S 55° W.
39.98	The cor. of secs. 3, 4, 9 and 10.
	<hr/> N 0°04' W, bet. secs. 3 and 4.
	Over rolling land.
39.98	The 1/4 sec. cor. of secs. 3 and 4, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:
	A ponderosa pine, 23 ins. diam., bears N 38 3/4° E, 64 1/2 lks. dist., with healed blaze. (Record: N 39 1/2° E, 64 lks. dist.)

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 28 ins. diam., bears S 52 1/4° W, 178 lks. dist., with healed blaze. (Record: S 52 1/4° W, 179 lks. dist.)</p> <p>Add the marks T25N R29E 1986 to the brass cap.</p> <hr/> <p>N 0°05' W, beginning new measurement.</p>
21.70	Graded road, 30 lks. wide, bears N 80° E and S 80° W.
41.56	<p>The closing cor. of secs. 3 and 4, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E.</p> <p>from which the new bearing trees:</p> <p>A ponderosa pine, 25 ins. diam., bears S 69 1/4° E, 84 1/2 lks. dist., mkd. T25N R29E S3 CC BT.</p> <p>A ponderosa pine, 20 ins. diam., bears S 31 3/4° W, 301 lks. dist., mkd. T25N R29E S4 CC BT.</p> <p>Add the marks 1986 to the brass cap.</p> <p>Cor. is located on the N edge of an underground gas pipeline and trail road, bears E and W.</p> <p>From this cor., the cor. of secs. 33 and 34, T 26 N, R 29 E, bears N 89°53' W, 2.08 chs. dist., monumented with an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1984 resurvey of the S bdy., T 26 N, R 29 E.</p> <hr/> <p>The 1/4 sec. cor. of sec. 3 only, is monumented with an iron post, 1 in. diam., firmly set, projecting 19 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. as described in the official record of the 1927 resurvey of the S bdy., T 26 N, R 29 E, from which a 1927 bearing tree:</p> <p>A ponderosa pine, 13 ins. diam., bears S 16 1/2° W, 202 lks. dist., with healed blaze. (Record: S 16 1/4° W)</p> <p>from which a new bearing tree:</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	<p>An oak, 10 ins. diam., bears S 63 1/2° E, 98 lks. dist., mkd. X BT.</p> <p>Add the marks T26N R29E T25N R29E 1986 to the brass cap.</p> <p>From this cor., the the 1/4 sec. cor. of sec. 34 only, T 26 N, R 29 E, bears S 89°47' W, 1.94 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., set, mkd. and witnessed as described in the official record of the 1984 resurvey of the S bdy., T 26 N, R 29 E.</p> <hr/> <p>From the stan. cor. of secs. 32 and 33, on the S bdy. of the Tp., hereinbefore described.</p> <p>North, bet. secs. 32 and 33.</p> <p>Over rolling and broken land.</p> <p>10.90 Trail road, bears N 45° E and S 45° W.</p> <p>32.40 Wash, 60 lks. wide, 4 ft. deep, drains N 80° E.</p> <p>38.80 Wash, 60 lks. wide, 5 ft. deep, drains E.</p> <p>39.95 The 1/4 sec. cor. of secs. 32 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">A ponderosa pine, 27 ins. diam., bears S 54 1/2° E, 148 1/2 lks. dist., with healed blaze. (Record: 150 lks. dist.)</p> <p style="padding-left: 40px;">A decaying ponderosa pine stump, 41 ins. diam., bears S 31 1/4° W, 199 1/2 lks. dist., with no blaze visible. (Record: S 30 1/2° W, 200 lks. dist.)</p> <p>from which a new bearing tree:</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S 65 1/4° W, 104 lks. dist., mkd. X BT.</p> <p>Add the marks T25N R29E 1986 to the brass cap.</p> <hr/>
--------	--

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS										
	N 0°01' W, beginning new measurement.									
30.60	Trail road, bears S 35° E and N 35° W.									
39.98	<p>The cor. of secs. 28, 29, 32 and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, in a collar of stone, 1 ft. base, 6 ins. high, with brass cap mkd. T25N R29E S2 S32 S33 1927 and other illegible marks, from which the original bearing trees:</p>									
	<p>A ponderosa pine stump, 26 ins. diam., bears N 48 3/4° E, 405 1/2 lks. dist., with no blaze visible. (Record: 405 lks. dist.)</p>									
	<p>A dead, decaying ponderosa pine,, 40 ins. diam., bears S 25° E, 286 1/2 lks. dist., illegibly mkd. on partially healed blaze. (Record: S 25 1/4° E, 287 lks. dist.)</p>									
	<p>A ponderosa pine, 30 ins. diam., bears S 57 1/4° W, 289 1/2 lks. dist., with healed blaze. (Record: S 57° W, 290 lks. dist.)</p>									
	<p>A dead, decaying ponderosa pine, 30 ins. diam., bears N 83 1/4° W, 337 lks. dist., mkd. T25N R29E S29 BT on existing surface. (Record: N 83 1/2° W, 338 lks. dist.)</p>									
	Remark the brass cap to read									
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tbody> <tr> <td style="padding: 2px;">T25N R29E</td> <td style="padding: 2px;">S29</td> <td style="padding: 2px;">S28</td> </tr> <tr> <td style="padding: 2px;">S32</td> <td style="padding: 2px;">1986</td> <td style="padding: 2px;">S33</td> </tr> <tr> <td></td> <td style="padding: 2px;">1927</td> <td></td> </tr> </tbody> </table>	T25N R29E	S29	S28	S32	1986	S33		1927	
T25N R29E	S29	S28								
S32	1986	S33								
	1927									
	from which a new bearing tree:									
	<p>A ponderosa pine, 14 ins. diam., bears S 79 3/4° E, 262 lks. dist., mkd. T25N R29E S33 BT.</p>									
	From the cor. of secs. 27, 28, 33 and 34.									
	S 89°55' W, bet. secs. 28 and 33.									
	Over rolling and broken land									

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
2.60	Wash, 75 lks. wide, 20 ft. deep, drains S 40° W.
10.30	Trail road, bears N 5° E and S 5° W.
19.99	Point for the E 1/16 sec. cor. of secs. 28 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled with a collar of stone, 3 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T25N R29E S28 E 1/16 — S33 1986</p>
	from which
	<p style="padding-left: 40px;">A piñon, 10 ins. diam., bears N 20 1/2° E, 71 lks. dist., mkd. E 1/16 S28 BT.</p>
	<p style="padding-left: 40px;">A piñon, 11 ins. diam., bears S 48 3/4° E, 77 1/2 lks. dist., mkd. E 1/16 S33 BT.</p>
39.98	The 1/4 sec. cor. of secs. 28 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 20 ins. above ground, in a mound of stone, 6 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:
	<p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears S 53 1/4° E, 116 1/2 lks. dist., with healed blaze. (Record: S 53° E, 116 lks. dist.)</p>
	<p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears N 20 1/4° W, 118 1/2 lks. dist., with healed blaze. (Record: 119 lks. dist.)</p>
	Add the marks T25N R29E 1986 to the brass cap.
	<hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p style="padding-left: 40px;">S 89°56' W, beginning new measurement.</p>
33.90	Trail road, bears S 5° E and N 5° W.
36.60	Wash, 15 lks. wide, 3 ft. deep, drains S 5° W.
39.97	The cor. of secs. 28, 29, 32 and 33.

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	N 0°01' W, bet. secs. 28 and 29.
	Over rolling and broken land.
5.00	Wash, 30 lks. wide, 4 ft. deep, drains S 50° E.
9.50	Trail road, bears S 60° E and N 60° W.
40.01	The 1/4 sec. cor. of secs. 28 and 29, determined from original bearing trees:
	A ponderosa pine, 26 ins. diam., bears
	N 37 1/4° W, 273 1/2 lks. dist., with healed blaze.
	(Record: 275 lks. dist.)
	An oak stump, 18 ins. diam., bears S 62° E,
	249 lks. dist., with no visible blaze.
	(Record: S 62 1/2° E, 248 lks. dist.)
	Point falls in the center of a mound of stone, 3 1/2 ft. diam.,
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	20 ins. in the ground, encircled with a collar of stone, 4 ft.
	base, to top, with brass cap mkd.
	T25N R29E
	1/4
	S29 S28
	1986
	from which
	A forked piñon, 14 ins. diam. at the base, bears
	S 71 3/4° E, 182 lks. dist., mkd. 1/4 S28 BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic
	case beneath the stainless steel post.

	N 0°06' W, beginning new measurement.
10.25	Trail road, bears S 10° E and N 10° W.
39.97	The cor. of secs. 20, 21, 28 and 29, monumented with an iron
	post, 2 ins. diam., firmly set, projecting 28 ins. above ground,
	in a mound of stone, 6 ft. diam., to top, with brass cap mkd. as
	described in the official record of the 1927 survey of the
	subdivisional lines, T 25 N, R 29 E, from which the original
	bearing trees:

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 32 ins. diam., bears N 60 1/4° E, 223 lks. dist., with healed blaze.</p> <p>A root hole, bears S 32 1/4° E, 156 1/2 lks. dist., alongside which is laying a ponderosa pine log, 29 ins. diam., with no visible blaze. (Record: S 31 1/2° E, 141 lks. dist.)</p> <p>A piñon, 8 ins. diam., bears S 21 3/4° W, 104 lks. dist., mkd. T25N R29E S29 BT on partially healed blaze.</p> <p>A ponderosa pine, 27 ins. diam., bears N 22 1/4° W, 114 lks. dist., illegibly mkd. on partially healed blaze. (Record: N 22 3/4° W, 115 lks. dist.)</p> <p>from which a new bearing tree:</p> <p>A piñon, 5 ins. diam., bears S 38 1/2° E, 125 lks. dist., mkd. X BT.</p> <p>Add the marks 1986 to the brass cap.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S 89°51' W, bet. secs. 21 and 28.</p> <p>Over rolling and broken land</p> <p>10.30 Trail road, bears N and S.</p> <p>19.97 Point for the E 1/16 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, supported in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25N R29E S21 E 1/16 — S28 1986</p> <p>from which</p> <p>A piñon, 19 ins. diam., bears N 42 1/2° E, 96 lks. dist., mkd. E 1/16 S21 BT.</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A forked piñon, 18 diam. at the base, bears S 61 1/4° E, 176 1/2 lks. dist., mkd. E 1/16 S28 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p>
	<p>From this cor., a mound of stone, of unknown origin, 2 ft. base, 1 ft. high, bears S 85°20' W, 3.11 chs. dist. Destroy the mound of stone.</p>
39.94	<p>The 1/4 sec. cor. of secs. 21 and 28, monumented with an iron post, 1 in. diam., firmly set, projecting 30 ins. above ground, in a mound of stone, 6 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p>
	<p>A ponderosa pine, 25 ins. diam., bears N 75 1/2° E, 88 1/2 lks. dist., illegibly mkd. on partially healed blaze. (Record: N 65 1/2° E, 88 lks. dist.)</p>
	<p>A ponderosa pine, 26 ins. diam., bears S 58 1/2° W, 237 lks. dist., with healed blaze. (Record: S 58° W, 239 lks. dist.)</p>
	<p>Add the marks T25N R29E 1986 to the brass cap.</p>
	<hr/> <p>N 89°58' W, beginning new measurement.</p>
17.00	<p>Wash, 60 lks. wide, 8 ft. deep, drains S 50° E.</p>
38.00	<p>Trail road, bears S 25° E and N 25° W.</p>
39.93	<p>The cor. of secs. 20, 21, 28 and 29.</p>
	<hr/> <p>N 0°01' W, bet. secs. 20 and 21.</p>
	<p>Over rolling and broken land.</p>
4.20	<p>Trail road, bears S 35° E and N 35° W.</p>
5.30	<p>Trail road, bears S 80° E and N 80° W.</p>
17.70	<p>Barbed wire fence, 5 strand, extending N 70° E and S 70° W.</p>
19.99	<p>Point for the S 1/16 sec. cor. of secs. 20 and 21.</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, to bedrock, encircled with a collar of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25N R29E S 1/16 S20 S21 1986</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 17 ins. diam., bears N 75 3/4° E, 133 lks. dist., mkd. S 1/16 S21 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears S 73° E, 52 1/2 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p>
25.63	Barbed wire fence, 3 strand, extending S 30° E and N 30° W.
26.20	Wash, 45 lks. wide, 4 ft. deep, drains S 20° E.
39.98	<p>The 1/4 sec. cor. of secs. 20 and 21, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the remaining original bearing tree:</p> <p style="padding-left: 40px;">A ponderosa pine, 27 ins. diam., bears S 37 3/4° W, 352 1/2 lks. dist., mkd. 4 S20 BT on partially healed blaze. (Record: S 38° W, 353 lks. dist.)</p> <p>from which a new bearing tree:</p> <p style="padding-left: 40px;">A ponderosa pine, 17 ins. diam., bears N 62° E, 126 lks. dist., mkd. 1/4 S21 BT.</p> <p>Cor. is located 8 lks. S. of a barbed wire fence, 5 strand, extending N 80° E and S 80° W.</p> <p>Add the marks T25N R29E 1986 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°03' W, beginning new measurement.</p>
20.01	Point for the N 1/16 sec. cor. of secs. 20 and 21.

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Set an aluminum post, 12 ins. long, 1 in. diam., 6 ins. in a drill hole, in sandstone bedrock, cemented in place, encircled with a collar of stone, 3 ft. base, to top, cemented in place, with aluminum cap mkd.</p> <p style="text-align: center;">T25N R29E N 1/16 S20 S21 1986</p> <p>from which</p> <p style="padding-left: 40px;">An oak, 7 ins. diam., bears N 60 1/2° E, 87 lks. dist., mkd. N 1/16 S21 BT.</p> <p style="padding-left: 40px;">A point on exposed sandstone face, bears N 56 3/4° W, 16 1/2 lks. dist., mkd. X BO.</p> <p>From this point a sandstone, of unknown origin, 3 x 10 x 18 ins. above ground, mkd. 1/16 on the N face, loosely set, in a mound of stone, 3 ft. base, 1 ft. high, bears N 80°54' W, 1.05 chs. dist. Destroy the mound of stone and bury the marked stone 6 ins. below the ground.</p> <p>40.02 The cor. of secs. 16, 17, 20 and 21, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">A decaying ponderosa pine stump, 25 ins. diam., bears N 3 3/4° E, 106 lks. dist., with no visible blaze. (Record: N 4 1/4° E, 105 lks. dist.)</p> <p style="padding-left: 40px;">A dead ponderosa pine, 29 ins. diam., bears S 23 1/4° E, 76 1/2 lks. dist., mkd. T25N R9E S21 BT on partially healed blaze. (Record: S 22 3/4° E, 78 lks. dist.)</p> <p style="padding-left: 40px;">A piñon, 13 ins. diam., bears S 40 1/2° W, 99 lks. dist., mkd. T25N R29E BT on partially healed blaze.</p> <p style="padding-left: 40px;">A dead piñon, 9 ins. diam. at the base, bears N 73 1/2° W, 133 lks. dist., mkd. N E S1 BT on partially healed blaze.</p> <p>from which the new bearing trees:</p>
--------	--

77
BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	A piñon, 14 ins. diam., bears N 64 1/2° E, 73 lks. dist., mkd. T25N R29E S16 BT.
	A ponderosa pine, 27 ins. diam., bears S 30 1/2° E, 150 1/2 lks. dist., mkd. T25N R29E S21 BT.
	A ponderosa pine, 16 ins. diam., bears N 37 1/4° W, 246 1/2 lks. dist., mkd. T25N R29E S17 BT.
	Add the marks 1986 to the brass cap.
	From the cor. of secs. 15, 16, 21 and 22.
	S 89°56' W, bet. secs. 16 and 21.
	Over rolling land
36.40	Trail road, bears S 75° E and N 75° W.
39.73	Barbed wire fence, 3 strand, extending N 20° E and S 20° W.
39.96	The 1/4 sec. cor. of secs. 16 and 21, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the remaining original bearing tree: The base of a piñon log, 11 ins. diam., laying atop the ground, bears N 64 1/4° E, 78 1/2 lks. dist., mkd. 1/4 S16 BT on open blaze. (Record: N 26° E, 136 lks. dist.) from which the new bearing trees: A ponderosa pine, 8 ins. diam., bears N 87 1/2° E, 129 1/2 lks. dist., mkd. 1/4 S16 BT. A ponderosa pine, 8 ins. diam., bears S 41° W, 107 1/2 lks. dist., mkd. 1/4 S21 BT.
	Add the marks T25N R29E 1986 to the brass cap.
	S 89°55' W, beginning new measurement.
38.40	Trail road, bears S 22° E and N 22° W.

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
39.93	The cor. of secs. 16, 17, 20 and 21.
	<hr/> <p>N 0°01' W, bet. secs. 16 and 17. Over rolling land.</p>
5.25	Trail road, bears S 15° E and N 15° W.
8.30	Barbed wire fence, 3 strand, extending S 80° E and N 80° W.
16.05	Trail road, bears S 70° E and N 70° W.
38.60	Trail road, bears N 30° E and S 30° W.
39.99	<p>The 1/4 sec. cor. of secs. 16 and 17, monumented with an iron post, 1 in. diam., loosely set, projecting 26 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">A forked piñon, 15 ins. diam. at the base, bears S 56 3/4° E, 126 lks. dist., with healed blaze. (Record: S 56 1/2° E)</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears N 21 1/4° W, 242 lks. dist., with healed blaze. (Record: Piñon, N 21 1/2° W)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, encircled with a collar of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T25N R29E 1/4 S17 S16 1986</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p> <p>Bury the brass cap alongside the stainless steel post and destroy the iron post.</p> <p>Cor. is located 75 lks. W of a trail road, bears N 30° E and S 30° W.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	N 0°04' W, beginning new measurement.
30.80	Trail road, bears S 20° E and N 20° W.
39.99	The cor. of secs. 8, 9, 16 and 17, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:
	A ponderosa pine, 32 ins. diam., bears N 59 3/4° E, 226 lks. dist., illegibly mkd. on partially healed blaze. (Record: N 59 1/2° E, 227 lks. dist.)
	An oak, 13 ins. diam., bears S 6 1/2° E, 64 1/2 lks. dist., with healed blaze. (Record: S 6 3/4° E, 227 lks. dist.)
	An oak, 14 ins. diam., bears S 17 1/4° W, 65 1/2 lks. dist., with healed blaze. (Record: S 17° W, 64 lks. dist.)
	An oak, 8 ins. diam., bears N 61 1/2° W, 68 lks. dist., with healed blaze. (Record: N 61° W)
	From the cor. of secs. 9, 10, 15 and 16.
	S 89°55' W, bet. secs. 9 and 16.
	Over rolling land
11.15	Trail road, bears N and S.
34.40	Trail road, bears N 25° E and S 25° E.
34.50	Trail road, bears S 10° E and N 10° W.
39.98	The 1/4 sec. cor. of secs. 9 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 20 ins. diam., bears N 24° E, 39 lks. dist., with healed blaze.</p>
	<p>A decaying ponderosa pine stump, 35 ins. diam., bears S 68° W, 131 lks. dist., alongside which is laying a ponderosa pine log, 35 ins. diam., 2 ft. long, mkd. 1/4 S16 BT on remaining surface.</p>
	<p>from which a new bearing tree:</p>
	<p>A ponderosa pine, 16 ins. diam., bears S 12° E, 81 lks. dist., mkd. 1/4 S16 BT.</p>
	<p>Cor. is located 75 lks. W of a trail road, bears S 20° E and N 20° E.</p>
	<p>Add the marks T25N R29E 1986 to the brass cap.</p> <hr/>
	<p>S 89°57' W, beginning new measurement.</p>
23.70	<p>Trail road, bears S 70° E and N 70° W.</p>
39.91	<p>The cor. of secs. 8, 9, 16 and 17.</p> <hr/>
	<p>N 0°01' W, bet. secs. 8 and 9.</p>
	<p>Over rolling land.</p>
40.00	<p>The 1/4 sec. cor. of secs. 8 and 9, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p>
	<p>A ponderosa pine, 23 ins. diam., bears N 78 1/4° E, 236 lks. dist., with healed blaze. (Record: N 78° E, 276 lks. dist.)</p>
	<p>An oak, 9 ins. diam., bears S 20 3/4° W, 241 1/2 lks. dist., with healed blaze. (Record: 240 lks. dist.)</p>
	<p>Add the marks T25N R29E 1986 to the brass cap.</p> <hr/>
	<p>N 0°02' W, beginning new measurement.</p>
1.70	<p>Underground gas pipeline and trail road, bears N 75° E and S 75° W.</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
39.99	<p>The cor. of secs. 4, 5, 8 and 9, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the remaining original bearing trees:</p> <p style="padding-left: 40px;">A piñon, 14 ins. diam., bears N 31 1/4° E, 193 lks. dist., illegibly mkd. on partially healed blaze. (Record: N 31 1/2° E)</p> <p style="padding-left: 40px;">An oak, 13 ins. diam., bears S 86 1/2° E, 237 1/2 lks. dist., with healed blaze. (Record: S 68 1/2° E, 237 lks. dist.)</p> <p style="padding-left: 40px;">A ponderosa pine, 23 ins. diam., bears N 44° W, 251 1/2 lks. dist., with healed blaze. (Record: 251 lks. dist.)</p> <p>from which a new bearing tree:</p> <p style="padding-left: 40px;">A forked piñon, 7 ins. diam., bears S 40° W, 90 lks. dist., mkd. T25N R29E S8 BT.</p> <p>Add the marks 1986 to the brass cap.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S 89°57' W, bet. secs. 4 and 9.</p> <p>Over rolling land.</p>
23.00	Trail road, bears S 40° E and N 40° W.
36.90	Trail road, bears S 10° E and N 10° W.
38.00	Trail road, bears S 15° E and N 15° W.
39.97	<p>The 1/4 sec. cor. of secs. 4 and 9, determined from the original bearing trees:</p> <p style="padding-left: 40px;">A dead piñon, 18 ins. diam., bears S 88° W, 237 lks. dist., mkd. /4 S9 BT on open blaze. (Record: S 87 3/4° W)</p> <p style="padding-left: 40px;">A ponderosa pine, 31 ins. diam., bears N 13 3/4° W, 248 lks. dist., with healed blaze. (Record: N 15° W)</p> <p>At the cor. point</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R29E S 4 1/4 — S 9 1986</p> <p>from which</p> <p style="text-align: center;">A piñon, 11 ins. diam., bears S 23° W, 182 lks. dist., mkd. 1/4 S9 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p> <hr/> <p>S 89°56' W, beginning new measurement.</p>
7.90	Trail road, bears N 30° E and S 30° W.
17.20	Wash, 15 lks. wide, 5 ft. deep, drains S.
39.89	The cor. of secs. 4, 5, 8 and 9.
	<hr/> <p>N 0°05' W, bet. secs. 4 and 5.</p> <p>Over rolling land.</p>
14.60	Trail road, bears N 40° E and S 40° W.
25.80	Graded road, 30 lks. wide, bears NE and SW.
40.00	<p>The 1/4 sec. cor. of secs. 4 and 5, determined from the original bearing trees:</p> <p style="text-align: center;">A piñon, 11 ins. diam., bears N 23 1/2° E, 226 lks. dist., mkd. BT on partially healed blaze. (Record: N 23 1/4° E)</p> <p style="text-align: center;">A piñon, 13 ins. diam., bears N 23° W, 214 lks. dist., mkd. S5 BT on partially healed blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	<p style="text-align: center;">T25N R29E 1/4 S 5 S 4 1986</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p> <hr/> <p>N 0°05' W, beginning new measurement.</p> <p>7.10 Trail road, bears N 80° E and S 80° W.</p> <p>42.02 The closing cor. of secs. 4 and 5, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, bent to the SE, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the remaining original bearing tree:</p> <p style="padding-left: 40px;">A ponderosa pine, 28 ins. diam., bears S 84 1/2° W, 163 lks. dist., with healed blaze. (Record: S 84 1/4° W)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R29E S33 ----- S 5 S 4 T25N R29E CC 1986</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p> <p>Remove the found iron post.</p> <p>Cor. is located 1 ch. N of an underground gas pipeline and trail road, bears E and W.</p> <p>From this cor., the cor. of secs. 32 and 33, T 26 N, R 29 E, bears N 89°44' W, 2.65 chs. dist., monumented with an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1984 resurvey of the S bdy., T 26 N, R 29 E.</p>
--------	---

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>The 1/4 sec. cor. of sec. 4 only, is monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1984 resurvey of the S bdy., T 26 N, R 29 E, from which a new bearing tree:</p> <p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears S 80 1/2° E, 75 lks. dist., mkd. 1/4 S4 BT.</p> <p>Add the marks T26N R29E T25N R29E 1986 to the brass cap.</p> <p>From this cor., the 1/4 sec. cor. of sec. 33 only, T 26 N, R 29 E, bears N 89°42' W, 2.36 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., set, mkd. and witnessed as described in the official record of the 1984 resurvey of the S bdy., T 26 N, R 29 E.</p> <hr/> <p>From the stan. cor. of secs. 31 and 32, on the S bdy. of the Tp., hereinbefore described.</p> <p>N 0°03' W, bet. secs. 31 and 32.</p> <p>Over rolling land.</p> <p>12.50 Trail road, bears S 65° E and N 65° W.</p> <p>40.00 The 1/4 sec. cor. of secs. 31 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 22 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">A ponderosa pine, 25 ins. diam., bears N 65 1/4° E, 239 lks. dist., with healed blaze. (Record: N 65 1/2° E, 238 lks. dist.)</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears S 57 1/2° W, 154 lks. dist., with healed blaze.</p> <p>from which a new bearing tree:</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears N 71° E, 15 1/2 lks. dist., mkd. 1/4 S32 BT.</p> <p>Add the marks T25N R29E 1986 to the brass cap.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N 0°05' W, beginning new measurement.</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
21.60	Wash, 10 lks. wide, 2 ft. deep, drains S 80° E.
40.00	<p>The cor. of secs. 29, 30, 31 and 32, monumented with an iron post, 2 ins. diam., firmly set, projecting 24 ins. above ground, in a mound of stone, 6 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears N 51° E, 73 lks. dist., mkd. R29E on partially healed blaze. (Record: 74 lks. dist.)</p> <p style="padding-left: 40px;">A piñon, 13 ins. diam., bears S 46 1/2° E, 162 1/2 lks. dist., illegibly mkd. on partially healed blaze. (Record: S 47° E, 162 lks. dist.)</p> <p style="padding-left: 40px;">An oak, 13 ins. diam., bears S 53° W, 100 1/2 lks. dist., mkd. S31 on partially healed blaze. (Record: 100 lks. dist.)</p> <p style="padding-left: 40px;">A piñon, 11 ins. diam., bears N 48 1/2° W, 81 1/2 lks. dist., mkd. 25N R29E S30 BT on partially healed blaze. (Record: N 48° W, 81 lks. dist.)</p> <p>Cor. is located 20 lks. E of barbed wire fence, 4 strand, extending N 20° E and S 20° W, and 60 lks. S of same barbed wire fence, with same bearing.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N 89°59' W, bet. secs. 29 and 32.</p> <p>Over rolling land.</p>
40.00	<p>The 1/4 sec. cor. of secs. 29 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 21 ins. diam., bears N 15 1/2° E, 107 1/2 lks. dist., mkd. 4 BT on partially healed blaze. (Record: N 16 1/2° E, 108 lks. dist.)</p>
	<p>A piñon, 13 ins. diam., bears S 25° E, 74 lks. dist., mkd. 4 S32 BT on partially healed blaze. (Record: S 26° E)</p>
	<p>Add the marks T25N R29E 1986 to the brass cap.</p> <hr/>
	<p>N 89°56' W, beginning new measurement.</p>
40.02	<p>The cor. of sec. 29, 30, 31 and 32.</p> <hr/>
	<p>N 89°58' W, bet. secs. 30 and 31.</p>
	<p>Over rolling land.</p>
5.37	<p>Barbed wire fence, 4 strand, extending N 20° E and S 20° W.</p>
39.97	<p>The 1/4 sec. cor. of secs. 30 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, in a mound of stone, 6 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p>
	<p>A ponderosa pine, 19 ins. diam., bears N 26° E, 93 1/2 lks. dist., with healed blaze. (Record: N 27° E, 93 lks. dist.)</p>
	<p>A ponderosa pine, 24 ins. diam., bears S 25 3/4° W, 132 1/2 lks. dist., with healed blaze. (Record: S 25 1/4° W, 133 lks. dist.)</p>
	<p>Add the marks T25N R29E 1986 to the brass cap.</p>
	<p>Cor. is located 30 lks. E of a barbed wire fence, 4 strand, extending S 10° E and N 10° W.</p> <hr/>
	<p>N 89°58' W, beginning new measurement.</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
2.15	Trail road, bears S 20° E and N 20° W.
18.15	Trail road, bears S 30° E and N 30° W.
39.90	The cor. of secs. 25, 30, 31 and 36, on the W bdy. of the Tp., hereinbefore described.
<hr/>	
From the cor. of secs. 29, 30, 31 and 32.	
N 0°03' W, bet. secs. 29 and 30.	
Over rolling and broken land.	
30.00	Barbed wire fence, 4 strand, extending N 5° E and S 5° W.
39.00	Wash, 20 lks. wide, 3 ft. deep, drains S 70° E.
40.00	The 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 26 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the remaining original bearing tree:
<p style="margin-left: 40px;">A dead, decaying ponderosa pine, 38 ins. diam.,</p>	
<p style="margin-left: 40px;">bears N 44 1/4 ° E, 219 lks. dist., mkd. 1/4 S29 BT on</p>	
<p style="margin-left: 40px;">remaining surface. (Record: N 43 1/2° E, 221 lks. dist.)</p>	
from which the new bearing trees:	
<p style="margin-left: 40px;">A ponderosa pine, 11 ins. diam., bears N 33° E,</p>	
<p style="margin-left: 40px;">32 1/2 lks. dist., mkd. 1/4 S29 BT.</p>	
<p style="margin-left: 40px;">A ponderosa pine, 17 ins. diam., bears</p>	
<p style="margin-left: 40px;">S 66 1/2° W, 90 1/2 lks. dist., mkd. 1/4 S30 BT.</p>	
Add the marks T25N R29E 1986 to the brass cap.	
From this cor., a metal post, 5 ins. diam., serving as the cor.	
of barbed wire fences, extending S 5° W and S 80° W, bears	
N 46 3/4° W, 29 lks. dist.	
<hr/>	

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	N 0°01' W, beginning new measurement.
10.60	Wash, 45 lks. wide, 13 ft. deep, drains S 60° E.
36.70	Trail road, bears N 35° E and S 35° W.
40.01	<p>The cor. of secs. 19, 20, 29 and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">A ponderosa pine, 32 ins. diam., bears N 45° E, 572 1/2 lks. dist., mkd. T25N R29E S20 on partially healed blaze. (Record: 573 lks. dist.)</p> <p style="padding-left: 40px;">A root hole, bears S 5° E, 433 lks. dist., alongside which is laying a decaying ponderosa pine log, 22 ins. diam., mkd. T25N R29E S29 BT on remaining surface.</p> <p style="padding-left: 40px;">A ponderosa pine, 33 ins. diam., bears S 57 1/2° W, 240 lks. dist., mkd. R29E 30 BT on partially healed blaze. (Record: S 57 3/4° W)</p> <p style="padding-left: 40px;">A piñon, 13 ins. diam., bears N 69 1/2° W, 98 lks. dist., mkd. 25N R29E S19 BT on partially healed blaze. (Record: N 70 1/4° W)</p> <p>from which a new bearing tree:</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears S 25° E, 110 lks. dist., mkd. T25N R29E S29 BT.</p> <p>Add the marks 1986 to the brass cap.</p>
	From the cor. of secs. 20, 21, 28 and 29.
	N 89°58' W, bet. secs. 20 and 29.
	Over rolling land.
39.98	<p>The 1/4 sec. cor. of secs. 20 and 29, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A piñon, 8 ins. diam., bears N 31 1/4° E, 123 1/2 lks. dist., with healed blaze. (Record: N 31 3/4° E, 123 lks. dist.)</p>
	<p>A ponderosa pine, 22 ins. diam., bears S 24 1/4° E, 247 lks. dist., with healed blaze. (Record: S 21 1/4° E, 248 lks. dist.)</p>
	<p>Add the marks T25N R29E 1986 to the brass cap.</p> <hr/>
	<p>N 89°56' W, beginning new measurement.</p>
35.40	<p>Trail road, bears S 15° E and N 15° W.</p>
39.99	<p>The cor. of secs. 19, 20, 29 and 30.</p> <hr/>
	<p>N 89°54' W, bet. secs. 19 and 30.</p>
	<p>Over rolling land.</p>
39.97	<p>The 1/4 sec. cor. of secs. 19 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. 1927, with other marks defaced, from which the original bearing trees:</p>
	<p>A ponderosa pine, 25 ins. diam., bears N 12 1/4° E, 59 lks. dist., with healed blaze.</p>
	<p>A piñon, 12 ins. diam., bears S 72 3/4° W, 81 lks. dist., mkd. 4 S30 BT on partially healed blaze. (Record: S 72 1/4 ° W, 80 lks. dist.)</p>
	<p>At the cor. point</p>
	<p>Remark the brass cap to read</p>
	<p style="text-align: center;">T25N R29E S19 1/4 — S30 1986 1927</p> <hr/>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	N 89°54' W, beginning new measurement.
1.30	Trail road, bears S 55° E and N 55° W.
3.40	Wash, 30 lks. wide, 1 ft. deep, drains S 15° E.
39.81	The cor. of secs. 19, 24, 25 and 30, on the W bdy. of the Tp., hereinbefore described.
	From the cor. of secs. 19, 20, 29 and 30.
	N 0°02' E, bet. secs. 19 and 20.
	Over rolling land.
19.99	Point for the S 1/16 sec. cor. of secs. 19 and 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T25N R29E S 1/16 S19 S20 1986</p>
	from which
	<p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S 47 3/4° E, 17 lks. dist., mkd. S 1/16 S20 BT.</p>
	<p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears S 79 1/2° W, 122 lks. dist., mkd. S 1/16 S19 BT.</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.
30.60	Trail road, bears S 10° E and N 10° W.
33.70	Trail road, bears E and W.
39.98	The 1/4 sec. cor. of secs. 19 and 20, monumented with a wood post, of unknown origin, 3 x 1 ins., firmly set, projecting 5 ins. above ground. This is accepted as the best available evidence of the original cor. position, from which the original bearing trees:

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>An oak, 20 ins. diam., bears N 9 1/4° E, 40 1/2 lks. dist., mkd. 20 on decaying blaze. (Record: N 9 3/4° E, 40 lks. dist.)</p> <p>A root hole, bears S 72 3/4° W, 99 1/2 lks. dist., alongside which is laying an oak log, 8 ins. diam., mkd. S19 BT on partially healed blaze. (Record: S 72 1/2° W, 99 lks. dist.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R29E 1/4 S19 S20 1986</p> <p>from which</p> <p>A piñon, 8 ins. diam., bears S 70 1/4° E, 18 lks. dist., mkd. 1/4 S20 BT.</p> <p>A piñon, 8 ins. diam., bears N 10° W, 34 1/2 lks. dist., mkd. 1/4 S19 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p> <p>Bury the wood post alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°02' W, beginning new measurement.</p> <p>18.20 Trail road, bears S 70° E and N 70° W.</p> <p>19.05 Trail road, bears N 50° E and S 50° W.</p> <p>19.995 Point for the N 1/16 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R29E N 1/16 S19 S20 1986</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A piñon, 7 ins. diam., bears N 63 1/2° E, 32 1/2 lks. dist., mkd. N 1/16 S20 BT.</p> <p>A piñon, 6 ins. diam., bears S 57° W, 104 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p> <p>From this cor., a sandstone, of unknown origin, firmly set, 10 x 2 x 7 ins. above ground, mkd. 1/16 on the E face, bears N 81°17' W, 135 lks. dist. Bury the marked stone.</p>
23.60	Trail road, bears E and W.
33.50	Trail road, bears E and W.
39.99	<p>The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p> <p>A ponderosa pine, 31 ins. diam., bears N 42 1/4° E, 168 lks. dist., illegibly mkd. on partially healed blaze. (Record: N 42 1/2° E, 169 lks. dist.)</p> <p>A ponderosa pine stump, 17 ins. diam., bears S 40 1/4° E, 107 lks. dist., mkd. T25N R29E S20 BT on open blaze. (Record: 108 lks. dist.)</p> <p>A ponderosa pine, 16 ins. diam., bears S 68° W, 59 lks. dist., with healed blaze. (Record: S 66 3/4° W, 60 lks. dist.)</p> <p>A ponderosa pine, 24 ins. diam., bears N 41 3/4° W, 202 1/2 lks. dist., with healed blaze. (Record: N 42 1/4° W, 203 lks. dist.)</p> <p>from which a new bearing tree:</p> <p>A ponderosa pine, 16 ins. diam., bears S 46 1/2° E, 31 1/2 lks. dist., mkd. T25N R29E S20 BT.</p> <p>Add the marks 1986 to the brass cap.</p> <hr/>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	From the cor. of secs. 16, 17, 20 and 21.
	N 89°57' W, bet. secs. 17 and 20.
	Over rolling land.
29.30	Wash, 75 lks. wide, 5 ft. deep, drains S 55° E.
39.92	<p>The 1/4 sec. cor. of secs. 17 and 20, monumented with an X chiseled on exposed sandstone face, in the near vicinity of which is laying the original monument, an iron post, 1 ins. diam., 36 ins. long, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears S 23 1/2° E, 33 lks. dist., mkd. 1/4 S20 BT on partially healed blaze. (Record: S 43° W)</p> <p style="padding-left: 40px;">A decaying ponderosa pine stump, 39 ins. diam., bears N 43 1/2° W, 67 lks. dist., mkd. BT on a separated wood fragment. (Record: N 26 1/2° W)</p> <p>At the cor. point</p> <p>Set an aluminum post, 21 ins. long, 1 in. diam., 8 ins. in a drill hole, in sandstone bedrock, cemented in place, encircled with a collar of stone, 3 ft. base, to top, with aluminum cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T25N R29E</p> <p>S17</p> <p>1/4 —</p> <p>S20</p> <p>1986</p> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N 18° W, 171 1/2 lks. dist., mkd. 1/4 S17 BT.</p> <p>Deposit the brass cap in the collar of stone, alongside the aluminum post, and destroy the iron post.</p> <p>From this cor., a cor. of barbed wire fences, 3 strand, extending N and E, bears N 75° W, 7 lks. dist.</p> <hr style="width: 20%; margin: 20px auto;"/>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	N 89°58' W, beginning new measurement.
3.20	Trail road, bears N 20° E and S 20° W.
8.10	Trail road, bears N 25° E and S 25° W.
39.96	The cor. of secs. 17, 18, 19 and 20.
	N 89°47' W, bet. secs. 18 and 19.
	Over rolling land.
20.60	Trail road, bears S 30° E and N 30° W.
39.98	<p>The 1/4 sec. cor. of secs. 18 and 19, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A decaying ponderosa pine stump, 27 ins. diam., bears N 48 1/4° E, 97 lks. dist., with no visible blaze. (Record: N 49° E)</p> <p style="padding-left: 40px;">A decaying ponderosa pine stump, 30 ins. diam., bears S 64 1/4 ° E, 192 1/2 lks. dist., with no visible blaze. (Record: 194 lks. dist.)</p> <p>from which the new bearing trees:</p> <p style="padding-left: 40px;">A piñon, 9 ins. diam., bears N 44° E, 21 lks. dist., mkd. 1/4 S18 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears S 6 3/4° W, 34 lks. dist., mkd. 1/4 S19 BT.</p> <p>Add the marks T25N R29E 1986 to the brass cap.</p>
	N 89°49' W, beginning new measurement.
14.70	Trail road, bears S 85° E and N 85° W.
39.79	The cor. of secs. 13, 18, 19 and 24, on the W bdy. of the Tp., hereinbefore described.

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	From the cor. of secs. 17, 18, 19 and 20.
	N 0°02' W, bet. secs. 17 and 18.
	Over rolling land.
20.00	Trail road, bears S 55° E and N 55° W.
39.99	The 1/4 sec. cor. of secs. 17 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:
	A decaying ponderosa pine stump, 35 ins. diam., bears N 36 1/2° E, 98 lks. dist., with no visible blaze.
	A piñon, 21 ins. diam., bears N 21° W, 142 lks. dist., mkd. 1/4 S18 BT on open blaze. (Record: 145 lks. dist.)
	from which a new bearing tree:
	A piñon, 19 ins. diam. at the base, bears N 84 1/2° E, 26 1/2 lks. dist., mkd. 1/4 S17 BT.
	Add the marks T25N R29E 1986 to the brass cap.
	N 0°07' W, beginning new measurement.
11.90	Trail road, bears N 70° E and S 70° W.
39.99	The cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the remaining original bearing trees:
	A piñon, 20 ins. diam., bears N 51 1/2° E, 111 1/2 lks. dist., illegibly mkd. on partially healed blaze. (Record: 110 lks. dist.)
	A ponderosa pine, 25 ins. diam., bears S 76° E, 277 lks. dist., with healed blaze. (Record: S 75 3/4° E)

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A piñon, 21 ins. diam. at the base, bears N 19 1/4° W, 124 lks. dist., mkd. S7 BT on partially healed blaze.</p> <p>from which a new bearing tree:</p> <p>A piñon, 8 ins. diam., bears S 44° W, 118 1/2 lks. dist., mkd. T25N R29E S18 BT.</p> <p>Add the marks 1986 to the brass cap.</p> <hr/>
	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N 89°57' W, bet. secs. 8 and 17.</p> <p>Over rolling land.</p>
39.97	<p>The 1/4 sec. cor. of secs. 8 and 17, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p> <p>A decaying ponderosa pine stump, 39 ins. diam., bears S 43° E, 134 1/2 lks. dist., with no visible blaze. (Record: 135 lks. dist.)</p> <p>A ponderosa pine, 21 ins. diam., bears N 19 1/4 ° W, 93 lks. dist., with healed blaze. (Record: N 19 1/2° W, 94 lks. dist.)</p> <p>from which a new bearing tree:</p> <p>A ponderosa pine, 20 ins. diam., bears S 80° E, 68 lks. dist., mkd. 1/4 S17 BT.</p> <p>Add the marks T25N R29E 1986 to the brass cap.</p> <hr/>
27.55	<p>N 89°59' W, beginning new measurement.</p>
39.97	<p>Trail road, bears S 20° E and N 20° W.</p> <p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/>
	<p>N 89°41' W, bet. secs. 7 and 18.</p> <p>Over rolling land.</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
19.60	Intersect barbed wire fence, 6 strand, extending N 42° E and S 42° W, at a point S 42° W, 6 lks. dist. from cor. of barbed wire fences, extending E and S 42° W.
21.20	Graded road, 27 lks. wide, bears NE and SW.
40.01	<p>The 1/4 sec. cor. of secs. 7 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears S 79° E, 408 1/2 lks. dist., mkd. BT on partially healed blaze. (Record: 409 lks. dist.)</p> <p style="padding-left: 40px;">A piñon, 21 ins. diam., bears N 33 3/4° W, 257 lks. dist., mkd. 4 S7 BT on partially healed blaze. (Record: N 34° W, 258 lks. dist.)</p> <p>Add the marks T25N R29E 1986 to the brass cap.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N 89°42' W, beginning new measurement.</p>
39.63	<p>The cor. of secs. 7, 12, 13 and 18, on the W bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N 0°03' W, bet. secs. 7 and 8.</p> <p>Over rolling land.</p>
14.40	Trail road, bears N 70° E and S 70° W.
16.00	Graded road, 30 lks. wide, bears N 40° E and S 40° W.
31.60	Underground gas pipeline and trail road, bears N 75° E and S 75° W.
40.00	<p>The 1/4 sec. cor. of secs. 7 and 8, monumented with an iron post, 1 in. diam., firmly set, projecting 27 ins. above ground, bent to the W, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 22 ins. diam., bears N 57 3/4° E, 95 lks. dist., with healed blaze. (Record: N 57 1/2° E, 94 lks. dist.)</p> <p>A ponderosa pine, 22 ins. diam., bears N 42° W, 40 lks. dist., with healed blaze. (Record: N 43° W)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R29E 1/4 S 7 S 8 1986</p> <p>Bury the brass cap alongside the stainless steel post and destroy the iron post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°03' W, beginning new measurement.</p>
17.00	Trail road, bears S 70° E and N 70° W.
40.11	<p>The cor. of secs. 5, 6, 7 and 8, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p> <p>A ponderosa pine, 17 ins. diam., bears N 73 1/2° E, 111 1/2 lks. dist., with healed blaze. (Record: 112 lks. dist.)</p> <p>A ponderosa pine, 24 ins. diam., bears S 48° E, 117 lks. dist., with healed blaze. (Record: 116 lks. dist.)</p> <p>A ponderosa pine, 20 ins. diam., bears S 2 3/4° W, 63 1/2 lks. dist., with healed blaze. (Record: 63 lks. dist.)</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>A dead ponderosa pine, 23 ins. diam., bears N 61° W, 399 lks. dist., mkd. T25N R29E S6 BT on open blaze.</p> <p>from which a new bearing tree:</p> <p>A piñon, 7 ins. diam., bears N 69 1/2° W, 66 1/2 lks. dist., mkd. T25N R29E S6 BT.</p> <p>Add the marks 1986 to the brass cap.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N 89°55' W, bet. secs. 5 and 8.</p> <p>Over rolling land.</p>
26.50	Graded road, 30 lks. wide, bears NE and SW.
40.00	<p>The 1/4 sec. cor. of secs. 5 and 8, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p> <p>A ponderosa pine, 27 ins. diam., bears N 47 1/4° E, 259 1/2 lks. dist., with healed blaze. (Record: N 47 1/2° E, 258 lks. dist.)</p> <p>A piñon, 13 ins. diam., bears S 69 1/2° E, 302 1/2 lks. dist., mkd. S8 BT on partially healed blaze. (Record: 302 lks. dist.)</p> <p>Add the marks T25N R29E 1986 to the brass cap.</p> <hr/> <p>N 89°48' W, beginning new measurement.</p>
2.75	Trail road, bears S 25° E and N 25° W.
39.98	The cor. of secs. 5, 6, 7 and 8.
	<hr/> <p>N 89°41' W, bet. secs. 6 and 7.</p> <p>Over rolling land.</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
40.00	<p>The 1/4 sec. cor. of secs. 6 and 7, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivisional lines, T 25 N, R 29 E, from which the original bearing trees:</p> <p style="padding-left: 40px;">A piñon, 15 ins. diam., bears S 31° W, 253 1/2 lks. dist., with healed blaze. (Record: 253 lks. dist.)</p> <p style="padding-left: 40px;">A ponderosa pine, 27 ins. diam., bears N 70 1/2° W, 492 1/2 lks. dist., with healed blaze. (Record: 492 lks. dist.)</p> <p>Add the marks T25N R29E 1986 to the brass cap.</p> <p>Cor. is located 60 lks. W of a trail road, bears S 50° E and N 50° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 89°40' W, beginning new measurement.</p>
39.47	<p>The cor. of secs. 1, 6, 7 and 12, on the W bdy. of the Tp., hereinbefore described.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N 0°08' W, bet. secs. 5 and 6.</p> <p>Over rolling land.</p>
40.01	<p>The 1/4 sec. cor. of secs. 5 and 6, determined from the original bearing trees:</p> <p style="padding-left: 40px;">A ponderosa pine, 21 ins. diam., bears S 82 1/4° E, 640 lks. dist., with healed blaze. (Record: S 82 1/2° E)</p> <p style="padding-left: 40px;">A decaying ponderosa pine stump, 26 ins. diam., bears N 25 3/4° W, 394 lks. dist., mkd. T on remnant of open blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

BOOK 5302

Dependent Resurvey of the Subdivisional Lines,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T25N R29E 1/4 S 6 S 5 1986</p>
	<p>from which</p>
	<p style="text-align: center;">A piñon, 9 ins. diam., bears S 17 1/2° W, 85 lks. dist., mkd. 1/4 S6 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p>
	<hr/> <p>N 0°08' W, beginning new measurement.</p>
5.30	Trail road, bears N 80° E and S 80° W.
41.30	Underground gas pipeline and trail road, bears E and W.
42.14	<p>The closing cor. of secs. 5 and 6, monumented with an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1984 resurvey of the S bdy., T 26 N, R 29 E.</p>
	<p>From this cor., the cor. of secs. 31 and 32, T 26 N, R 29 E, bears N 89°49' W, 3.02 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., set, mkd. and witnessed as described in the official record of the 1984 resurvey of the S bdy., T 26 N, R 29 E.</p>
	<hr/> <p>The 1/4 sec. cor. of sec. 5 only, is monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the official record of the 1984 resurvey of the S bdy., T 26 N, R 29 E.</p>
	<p>Add the marks T26N R29E T25N R29E 1986 to the brass cap.</p>
	<p>From this cor., the 1/4 sec. cor. of sec. 32 only, T 26 N, R 29 E, bears N 89°46' W, 2.68 chs. dist., monumented with a piñon, 18 ins. diam., mkd. and witnessed as described in in the official record of the 1984 resurvey of the S bdy., T 26 N, R 29 E.</p>

BOOK 5302

Survey of the Subdivision of Certain Sections,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	Survey of the Subdivision of Section 2
<p>39.99</p>	<p>From the 1/4 sec. cor. of secs. 2 and 11. N 0°02' W, on the N and S centerline of sec. 2. Over rolling land.</p> <p>Point for the center 1/4 sec. cor. of sec. 2, at intersection with the E-W center line of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R29E C1/4 S 2 1986</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 6 ins. diam., bears S 33 3/4° E, 28 1/2 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A forked piñon, 15 ins. diam. at the base, bears S 26° W, 80 lks. dist., mkd. C 1/4 S2 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p> <p>From this cor., a sandstone, of unknown origin, firmly set, 15 x 4 x 10 ins. above ground, mkd. 2 on the W face, bears N 50°35' W, 2.63 chs. dist. Destroy the marked stone.</p> <p>From this same cor. the cor. of barbed wire fences, 5 strand, extending S and W, bears N 67 1/2° E, 36 1/2 lks. dist.</p>
<p>80.75</p>	<p>Underground gas pipeline and trail road, bears E and W.</p>
<p>81.70</p>	<p>The 1/4 sec. cor. of sec. 2 only, on the N bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 2. S 89°59' W, on the E and W centerline of sec. 2. Over rolling land.</p>

BOOK 5302

Survey of the Subdivision of Certain Sections,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
24.70	Trail road, bears N and S.
40.12	The center 1/4 sec. cor. of sec. 2.
70.20	Trail road, bears N 15° E and S 15° W.
70.40	Barbed wire fence, 3 strand, extending N 15° E and S 15° W.
77.90	Wash, 10 lks. wide, 1 ft. deep, drains S 55° W.
80.22	The 1/4 sec. cor. of secs. 2 and 3, hereinbefore described.
<hr/> Survey of the Subdivision of Section 10 <hr/>	
	From the 1/4 sec. cor. of secs. 10 and 15.
	N 0°04' W, on the N and S centerline of sec. 10.
	Over rolling land.
40.06	Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E-W center of sec. 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled with a collar of stone, 2 ft. base, to top, with brass cap mkd.
	T25N R29E C1/4 S10 1986
	from which
	A ponderosa pine, 11 ins. diam., bears S 34 1/4° E, 104 lks. dist., mkd. C 1/4 S10 BT.
	A ponderosa pine, 12 ins. diam., bears N 76 3/4° W, 123 lks. dist., mkd. X BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.
56.50	Underground gas pipeline and trail road, bears N 80° E and S 80° W.

BOOK 5302

Survey of the Subdivision of Certain Sections,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
65.00	Trail road, bears S 80° E and N 80° W.
80.05	The 1/4 sec. cor. of secs. 3 and 10.
<hr/>	
From the 1/4 sec. cor. of secs. 10 and 11.	
S 89°56' W, on the E and W centerline of sec. 10.	
Over rolling land.	
37.50	Trail road, bears N 40° E and S 40° W.
39.99	The center 1/4 sec. cor. of sec. 10.
70.30	Trail road, bears N 20° E and S 20° W.
73.30	Trail road, bears N 10° E and S 10° W.
80.00	The 1/4 sec. cor. of secs. 9 and 10.
<hr/>	
Survey of the Subdivision of Section 14	
<hr/>	
From the 1/4 sec. cor. of secs. 14 and 23.	
N 0°01' E, on the N and S centerline of sec. 14	
Over rolling and broken land.	
9.00	Trail road, bears N 60° E and S 60° W.
20.00	Point for the C-S 1/16 sec. cor. of sec. 14.
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.	
T25N R29E C S1/16 S14 C 1986	
from which	
A ponderosa pine, 12 ins. diam., bears S 41 3/4° W, 43 lks. dist., mkd. C S 1/16 S14 BT.	

BOOK 5302

Survey of the Subdivision of Certain Sections,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.
30.65	Trail road, bears E and W.
40.00	Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E-W center line of sec. 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T25N R29E C1/4 S14 1986</p>
	from which
	<p style="padding-left: 40px;">A ponderosa pine, 32 ins. diam., bears S 63 1/2° E, 104 lks. dist., mkd. C 1/4 S14 BT.</p>
	<p style="padding-left: 40px;">A ponderosa pine, 37 ins. diam., bears N 65 1/4° W, 42 lks. dist., mkd. X BT.</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.
41.40	Wash, 40 lks. wide, 8 ft. deep, drains N 80° E.
75.20	Trail road, bears N 60° E and S 60° W.
79.96	The 1/4 sec. cor. of secs. 11 and 14.
	From the 1/4 sec. cor. of secs. 13 and 14.
	S 89°56' W, on the E and W centerline of sec. 14.
	Over rolling and broken land.
40.02	The center 1/4 sec. cor. of sec. 14.
67.70	Wash, 20 lks. wide, 6 ft. deep, drains S 25° W.

BOOK 5302

Survey of the Subdivision of Certain Sections,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
71.60	Trail road, bears N and S.
80.00	The 1/4 sec. cor. of secs. 14 and 15.
<hr/> SE 1/4 Section 14 <hr/>	
From the S 1/16 sec. cor. of secs. 13 and 14, hereinbefore described.	
S 89°56' W, on the E and W centerline of the SE 1/4 of sec. 14.	
Over rolling land, broken land.	
40.00	The C-S 1/16 sec. cor. of sec. 14.
<hr/> SW 1/4 Section 14 <hr/>	
From the C-S 1/16 sec. cor. of sec. 14.	
S 89°58' W, on the E and W centerline of the SW 1/4 of sec. 14.	
Over rolling and broken land.	
39.97	The S 1/16 sec. cor. of secs. 14 and 15.
<hr/> Survey of the Subdivision of Section 18 <hr/>	
From the 1/4 sec. cor. of secs. 18 and 19.	
N 0°06' W, on the N and S centerline of sec. 18.	
Over rolling land.	
40.09	Point for the center 1/4 sec. cor. of sec. 18, at intersection with the E-W center line of sec. 18.
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, encircled with a collar of stone, 3 ft. base, to top, with brass cap mkd.	
T25N R29E C1/4 S18 1986	

BOOK 5302

Survey of the Subdivision of Certain Sections,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A ponderosa pine, 14 ins. diam., bears S 57 3/4° E, 88 lks. dist., mkd. C 1/4 S18 BT.</p> <p>An oak, 23 ins. diam., bears S 67 1/2° W, 5 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p>
60.60	Graded road, 30 lks. wide, bears N 40° E and S 40° W.
80.05	The 1/4 sec. cor. of secs. 7 and 18.
	<hr/> <p>From the 1/4 sec. cor. of secs. 17 and 18.</p> <p>N 89°40' W, on the E and W centerline of sec. 18.</p> <p>Over rolling land.</p>
11.60	Trail road, bears S 55° E and N 55° W.
25.60	Trail road, bears S 30° E and N 30° W.
40.03	The center 1/4 sec. cor. of sec. 18.
53.40	Graded road, 30 lks. wide, bears N 40° E and S 40° W.
79.61	The 1/4 sec. cor of secs. 13 and 18, on the W bdy. of the Tp., hereinbefore described.
	<hr/> <p style="text-align: center;">Survey of the Subdivision of Section 20</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 20 and 29.</p> <p>N 0°01' W, on the N and S centerline of sec. 20.</p> <p>Over rolling land.</p>
19.99	<p>Point for the C-S 1/16 sec. cor. of sec. 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

BOOK 5302

Survey of the Subdivision of Certain Sections,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T25N R29E C S1/16 S20 C 1986</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 6 ins. diam., bears N 22° E, 6 1/2 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears N 82 3/4° E, 16 lks. dist., mkd. C-S 1/16 S20 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p> <p>21.90 Trail road, bears S 50° E and N 50° W.</p> <p>39.98 Point for the center 1/4 sec. cor. of sec. 20, at intersection with the E-W center line of sec. 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R29E C1/4 S20 1986</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears N 46 1/4° E, 31 1/2 lks. dist., mkd. C 1/4 S20 BT.</p> <p style="padding-left: 40px;">A piñon, 6 ins. diam., bears N 60° W, 30 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p> <p>59.995 Point for the C-N 1/16 sec. cor. of sec. 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled with a collar of stone, 2 ft. base, to top, with brass cap mkd.</p>

BOOK 5302

Survey of the Subdivision of Certain Sections,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	T25N R29E C N1/16 S20 C 1986
	from which A ponderosa pine, 10 ins. diam., bears N 13 1/2° E, 34 1/2 lks. dist., mkd. C N 1/16 S20 BT. A oak, 7 ins. diam., bears S 16° E, 197 lks. dist., mkd. C-N 1/16 S20 BT. Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.
80.01	The 1/4 sec. cor. of secs. 17 and 20. <hr/> From the 1/4 sec. cor. of secs. 20 and 21. N 89°57' W, on the E and W centerline of sec. 20. Over rolling land.
39.97	The center 1/4 sec. cor. of sec. 20.
79.93	The 1/4 sec. cor. of secs. 19 and 20. <hr/> <div style="text-align: center;">NE 1/4 of Section 20</div> <hr/> From the N 1/16 sec. cor. of secs. 20 and 21. N 89°58' W, on the E and W centerline of the NE 1/4 of sec. 20. Over rolling and broken land.
31.90	Barbed wire fence, 4 strand, extending S 30° E and N 30° W.
36.30	Wash, 10 lks. wide, 4 ft. deep, drains S 80° E.
39.95	The C-N 1/16 sec. cor. of sec. 20. <hr/>

BOOK 5302

Survey of the Subdivision of Certain Sections,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<hr/> SE 1/4 of Section 20 <hr/>
	From the S 1/16 sec. cor. of secs. 20 and 21.
	N 89°58' W, on the E and W centerline of the SE 1/4 of sec. 20.
	Over rolling land.
36.10	Trail road, bears S 80° E and N 80° W.
39.97	The C-S 1/16 sec. cor. of sec. 20.
	<hr/> SW 1/4 of Section 20 <hr/>
	From the C-S 1/16 sec. cor. of sec. 20.
	N 89°56' W, on the E and W centerline of the SW 1/4 of sec. 20.
	Over rolling land.
34.70	Trail road, bears S 20° E and N 20° W.
39.98	The S 1/16 sec. cor. of secs. 19 and 20.
	<hr/> NW 1/4 of Section 20 <hr/>
	From the C-N 1/16 sec. cor. of secs. 20.
	N 89°57' W, on the E and W centerline of the NW 1/4 of sec. 20.
	Over rolling land.
17.60	Trail road, bears S 10° E and N 10° W.
31.20	Trail road, bears N and S.
39.20	Trail road, bears N 55° E and S 55° W.
39.96	The N 1/16 sec. cor. of secs. 19 and 20.

BOOK 5302

Survey of the Subdivision of Certain Sections,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	Survey of the Subdivision of Section 22
<p>19.985</p>	<p>From the 1/4 sec. cor. of secs. 22 and 27. North, on the N and S centerline of sec. 20. Over rolling land.</p> <p>Point for the C-S 1/16 sec. cor. of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R29E C S1/16 S22 C 1986</p> </div> <p>from which</p> <p style="padding-left: 40px;">A piñon, 6 ins. diam., bears S 70° E, 48 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A piñon, 7 ins. diam., bears N 17° W, 18 1/2 lks. dist., mkd. C S 1/16 S22 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p> <p>22.70 Trail road, bears S 80° E and N 80° W.</p> <p>23.16 Barbed wire fence, 3 strand, extending E and W.</p> <p>39.97 Point for the center 1/4 sec. cor. of sec. 22, at intersection with the E-W center line of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R29E C1/4 S22 1986</p> </div>

112
BOOK 5302

Survey of the Subdivision of Certain Sections,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A piñon, 8 ins. diam., bears N 83° E, 103 lks. dist., mkd. X BT.</p> <p>A piñon, 8 ins. diam., bears N 43 1/4° W, 39 1/2 lks. dist., mkd. C 1/4 S22 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p>
59.965	<p>Point for the C-N 1/16 sec. cor. of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, with brass cap mkd.</p> <p style="text-align: center;">T25N R29E C N1/16 S22 C 1986</p>
	<p>from which</p> <p>A piñon, 11 ins. diam., bears East, 10 lks. dist., mkd. C N 1/16 S22 BT.</p> <p>A piñon, 12 ins. diam., bears N 52 1/2° W, 45 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p>
79.96	<p>The 1/4 sec. cor. of secs. 15 and 22.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 22 and 23.</p> <p>S 89°56' W, on the E and W centerline of sec. 22.</p> <p>Over rolling land.</p>
40.02	<p>The center 1/4 sec. cor. of sec. 22.</p>
80.04	<p>The 1/4 sec. cor. of secs. 21 and 22.</p> <hr/>
15.60	<p>Wash, 30 lks. wide, 10 ft. deep, drains S 10° E.</p>

BOOK 5302

Survey of the Subdivision of Certain Sections,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>NE 1/4 of Section 22</p> <hr/>
	<p>From the N 1/16 sec. cor. of secs. 22 and 23, hereinbefore described.</p> <p>S 89°57' W, on the E and W centerline of the NE 1/4 of sec. 22.</p> <p>Over rolling land.</p>
39.99	The C-N 1/16 sec. cor. of sec. 22.
	<p>SE 1/4 of Section 22</p> <hr/>
	<p>From the S 1/16 sec. cor. of secs. 22 and 23.</p> <p>S 89°58' W, on the E and W centerline of the SE 1/4 of sec. 22.</p> <p>Over rolling land.</p>
5.50	Wash, 30 lks. wide, 30 ft. deep, drains S 5° W.
31.20	Trail road, bears S 20° E and N 20° W.
40.05	The C-S 1/16 sec. cor. of sec. 22.
	<p>SW 1/4 of Section 22</p> <hr/>
	<p>From the C-S 1/16 sec. cor. of sec. 22.</p> <p>S 89°57' W, on the E and W centerline of the SW 1/4 of sec. 22.</p> <p>Over rolling land.</p>
29.50	Trail road, bears N 70° E and S 70° W.
31.40	Trail road, bears N 20° E and S 20° W.
40.02	The S 1/16 sec. cor. of secs. 21 and 22.

BOOK 5302

Survey of the Subdivision of Certain Sections,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>NW 1/4 of Section 22</p> <hr/>
	<p>From the C-N 1/16 sec. cor. of sec. 22.</p> <p>S 89°58' W, on the E and W centerline of the NW 1/4 of sec. 22.</p> <p>Over rolling land.</p>
27.62	Barbed wire fence, 4 strand, extending S 10° E and N 10° W.
31.10	Trail road, bears N 20° E and S 20° W.
40.04	The N 1/16 sec. cor. of secs. 21 and 22.
	<hr/> <p>Survey of the Subdivision of Section 28</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 28 and 33.</p> <p>N 0°04' W, on the N and S centerline of sec. 28.</p> <p>Over rolling land.</p>
40.01	<p>Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E-W center line of sec. 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25N R29E C1/4 S28 1986</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.</p>
52.10	Trail road, bears S 35° E and N 35° W.
54.90	Trail road, bears NE and SW.
79.93	The 1/4 sec. cor. of secs. 21 and 28.
	<hr/> <p>From the 1/4 sec. cor. of secs. 27 and 28.</p>

BOOK 5302

Survey of the Subdivision of Certain Sections,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	S 89°56' W, on the E and W centerline of sec. 28.
	Over rolling land.
19.98	Point for the C-E 1/16 sec. cor. of sec. 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	19 ins. in the ground, to bedrock, encircled with a collar of
	stone, 4 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T25N R29E E1/16 C———C S28 1986</p>
	from which
	A piñon, 7 ins. diam., bears S 45 3/4° W, 31 1/2 lks.
	dist., mkd. X BT.
	A piñon, 18 ins. diam., bears N 2° W, 29 lks.
	dist., mkd. C E 1/16 S28 BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic
	case beneath the stainless steel post.
25.30	Wash, 20 lks. wide, 5 ft. deep, drains S 25° E.
39.96	The center 1/4 sec. cor. of sec. 28.
79.89	The 1/4 sec. cor. of secs. 28 and 29.
	<hr/> <p style="text-align: center;">NE 1/4 of Section 28</p> <hr/>
	From the C-E 1/16 sec. cor. of sec. 28.
	N 0°06' W, on the N and S centerline of the NE 1/4 of sec. 28.
	Over rolling land.
39.96	The E 1/16 sec. cor. of secs. 21 and 28.
	<hr/>

BOOK 5302

Survey of the Subdivision of Certain Sections,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	
	SE 1/4 of Section 29
	From the E 1/16 sec. cor. of secs. 28 and 33.
	N 0°06' W, on the N and S centerline of the SE 1/4 of sec. 28.
	Over rolling land.
29.20	Wash, 30 lks. wide, 4 ft. deep, drains S 40° E.
38.70	Trail road, bears S 40° E and N 40° W.
40.00	The C-E 1/16 sec. cor. of sec. 28.
	Subdivision of Section 30
	From the 1/4 sec. cor. of secs. 30 and 31.
	N 0°03' W, on the N and S centerline of sec. 30.
	Over rolling land.
40.03	Point for the center 1/4 sec. cor. of sec. 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with a collar of stone, 2 ft. base, to top, with brass cap mkd.
	T25N R29E C1/4 S30 1986
	from which
	A ponderosa pine, 10 ins. diam., bears N 47 1/4° E, 14 lks. dist., mkd. C 1/4 S30 BT.
	A ponderosa pine, 10 ins. diam., bears N 74 3/4° W, 45 lks. dist., mkd. X BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. orange colored plastic case beneath the stainless steel post.
80.06	The 1/4 sec. cor. of secs. 19 and 30.

BOOK 5302

Survey of the Subdivision of Certain Sections,
T 25 N, R 29 E, Gila and Salt River Mer., Arizona

CHAINS	<p>From the 1/4 sec. cor. of secs. 29 and 30.</p> <p>N 89°56' W, on the E and W centerline of sec. 30.</p> <p>Over rolling land.</p> <p>39.96 The center 1/4 sec. cor. of sec. 30.</p> <p>79.79 The 1/4 sec. cor. of secs. 25 and 30, on the W bdy. of the Tp., hereinbefore described.</p>
GENERAL DESCRIPTION	
<p>The area surveyed is within the Navajo Indian Reservation, approximately 8 miles southwest of St. Michaels, Arizona, The terrain varies from rolling to rugged land broken up by abrupt sandstone washes ranging in depth from 10 to approximately 150 ft. The elevation ranges from 7100 to 7600 feet above sea level.</p> <p>The drainage in the area is in a southerly direction. The soil varies from sandy clay loam to clay with sandstone outcroppings and large exposed sandstone areas. The vegetation consists of ponderosa pine, piñon, juniper, scrub oak, sagebrush, rabbitbrush, native grasses and scattered yucca and cacti.</p> <p>Access is provided by Bureau of Indian Affairs Forestry Road No. 9000, a graded dirt road meandering southerly about 7 miles from Arizona State Highway 264 to its entrance into the township on the north boundary of sec. 3. Access to the township itself is provided by forestry road 9000 and a number of trail roads which meander throughout most of the township.</p> <p>The area is used by members of the Navajo tribe to raise sheep, goats, cattle and horses. The Navajo tribe also utilizes the timber resources available throughout the township.</p> <p>The average magnetic declination is 12 1/2° E, with no noticeable variation due to local attraction.</p>	

BOOK 5302

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Daniel N. Patterson	Cadastral Surveyor
Wilfred D. Chee	Engineering Technician II
Jones C. Curtiss	Engineering Technician II
Jeff Barney	Survey Aide
Albert Benally	Survey Aide
Calvin Cardy	Survey Aide
Dean Clyde	Survey Aide
Ralph Jones	Survey Aide
Seymour Jones	Survey Aide
Ron Milford	Survey Aide

CERTIFICATE OF SURVEY

I, Kevin R. DeRossett, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 19th day of August, 1985, I have dependently resurveyed the sixth standard parallel north through Range 29 East, the east and west boundaries, a portion of the north boundary, and the subdivisional lines, and the survey of the subdivision of certain sections, in Township 25 North, Range 29 East, of the Gila and Salt River Meridian, in the state of Arizona which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

Kevin R. DeRossett is no longer assigned to this office and not available for signature.

1/14/91

(Date)

William F. Oliver

(Chief, Navajo Project Office)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the sixth standard parallel north through Range 29 East, the east and west boundaries, a portion of the north boundary, and the subdivisional lines, and the survey of the subdivision of certain sections of Township 25 North, Range 29 East, Gila and Salt River Meridian, executed by Kevin R. DeRossett, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

2/05/91

(Date)

Jerry K. Talbot

(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I Certify that the foregoing transcript of the field notes of the above-described surveys in T. 25 N., R. 29 E., Gila and Salt River Meridian, Arizona is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~