

ORIGINAL

¹ BOOK 5306

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,

THE SUBDIVISIONAL LINES,

SUBDIVISION OF SELECTED SECTIONS

AND

METES-AND-BOUNDS SURVEYS

IN

TOWNSHIP 7 NORTH, RANGE 27 EAST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

William P. Carpenter, Cadastral Surveyor

Under Special Instructions dated June 6, 1990, approved July 6, 1990,
which provided for the surveys included under Group Number 721 and assignment
instructions dated July 6, 1990.

Survey commenced July 11, 1990

Survey completed September 14, 1990

INDEX DIAGRAM

TOWNSHIP 7 NORTH, RANGE 27 EAST,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

- Subdivision Sec. 1 pg 15
- " Sec. 2 pg 17
- " Sec. 12 pg 21
- Lot 8, Sec. 1 pg 26
- Lot 6, Sec. 12 pg 28
- Lot 12, Sec. 12 pg 32
- Lot 2, Sec. 13 pg 34
- Lot 3, Sec. 13 pg 37
- Tract 39 pg 45
- Tract 40 pg 49

T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of the dependent resurvey of a portion of the north boundary, subdivisional lines, subdivisions of selected sections and metes-and-bounds surveys in Township 7 North, Range 27 East, Gila and Salt River Meridian, Arizona.

The north boundary and the subdivisional lines were surveyed by W. R. Fitzgerald, in 1883, and resurveyed by Ty White, Claude F. Warner, and Frank Motosh, in 1940. Jerrold E. Knight resurveyed a portion of the subdivisional lines, surveyed subdivision lines in sections 1, 2, and 12, and surveyed the metes-and-bounds lines of Tract 38, in 1968.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated June 6, 1990, for Group No. 721, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of all lines were determined by hour angle observations on the sun, confirmed by an Arizona Department of Transportation Triangulation Network, and refer to the true meridian. Distances and angles were measured with a Zeiss Elta 46 total station instrument.

The geographic position of the southeast corner of section 14, as determined from a tie made to Arizona Department of Transportation, Highway Division triangulation station "PORT, 1978", located in section 32, Township 9 North, Range 29 East, is as follows:

NAD: Latitude: 33°59'40.6" N. Longitude: 109°27'17.1" W.

The mean magnetic declination, as taken from "GREER, ARIZ." quadrangle map, published in 1981 by the U.S. Geological Survey and modified for U.S.D.A. Forest Service use, is 12 1/2° E.

Dependent Resurvey, a Portion of the N. Bdy.,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">Restoring the resurvey executed by Ty White, Claude F. Warner, and Frank Motosh, in 1940</p> <hr style="width: 20%; margin: auto;"/> <p>Beginning at the cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 12 ins. from the ground, with brass cap, mkd. as described in the official record of the 1940 resurvey of the N. bdy., from which original bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears S. 45° W., 34 lks. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears N. 14 1/2° W., 39 lks. dist., with illegible scribe marks, (Record: N. 13 3/4° W., 40 lks.).</p> <p>and a 1940 bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears S. 51 3/4° E., 154 lks. dist., mkd. T7N R27E S1 BT (Record: 155 lks.).</p> <p>Iron post is set in a scattered mound of stone,</p> <p>Add the marks 1990 to the brass cap.</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 40 3/4° E., 300 lks. dist., mkd. T8N R27E S36 BT.</p> <p>Rebuild the mound of stone, 4 ft. base, to top.</p> <p>A steel fence post, with U.S. Forest Service signs attached, is set alongside the cor.</p> <p>N. 89°43' W., bet. secs. 2 and 35, on the N. bdy. of the Tp.</p> <p>Over nearly level land, through moderate ponderosa pine timber, in a U.S. Forest Service campground.</p> <p>13.50 Rock ledge, on top of Benny Creek drainage, bears NE and SW.</p> <p>Descend</p>
--------	--

Dependent Resurvey of a Portion of the N. Bdy.,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
17.00	Benny Creek, 10 lks. wide, course NE.
	Ascend
19.95	Point for the E 1/16 sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T8N R27E S35 E 1/16 ——— S2 T7N 1990</p>
	from which
	A ponderosa pine, 11 ins. diam., bears S. 6 1/2° W., 28 lks. dist., mkd. E 1/16 S2 BT.
	A ponderosa pine, 8 ins. diam., bears N. 49 1/4 ° W., 26 lks. dist., mkd. E 1/16 S35 BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
	The cor. is located on a steep, rocky E. slope.
21.75	Rock ledge, on top of Benny Creek drainage, bears N. and S.
	Thence over nearly level land.
30.35	Fence, bears SE and NW.
33.10	Track road, 15 lks. wide, bears NE and SW.
39.90	The 1/4 sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp., monumented with an iron post, 1 in. diam., projecting 5 ins. from the ground, with brass cap mkd. as described in the official record of the 1940 resurvey of the N. bdy., from which the original bearing tree

Dependent Resurvey of a Portion of the N. Bdy.,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

A ponderosa pine, 20 ins. diam., bears N. 30° E., 39 lks. dist., mkd. with S35 visible in a partially healed blaze.

and the 1940 bearing tree

A ponderosa pine, 19 ins. diam., bears S. 40 1/4° E., 97 lks. dist., mkd. with 1/4 S2 visible in a partially healed blaze.

Iron post is set in a scattered mound of stone (Record: No mound of stone),

Remark brass cap to read

T8N R27E
S35
1/4 ———
S2
T7N
1990
1940

Rebuild the mound of stone, 4 ft. base, to top.

Dependent Resurvey, Subdivisional Lines,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

Restoring the resurvey executed by
Jerrold E. Knight, in 1968

From the cor. of secs.13, 14, 23, and 24, monumented with an iron post, 2 ins. diam., firmly set, leaning to the N., projecting 11 ins. from the ground, with brass cap mkd. as described in the official record of the 1968 resurvey, from which bearing trees of record

A ponderosa pine 18 ins. diam., bears N. 52 1/2° E., 34 lks. dist., with a healed blaze.

A spruce, 16 ins. diam., bears S. 7 1/2° E., 74 lks. dist., with a healed blaze.

A stump hole, bears S. 88 3/4° W., 196 lks. dist., a down ponderosa pine, 30 ins. diam., is alongside, mkd. T7N R27E S23 BT.

Dependent Resurvey, Subdivisional Lines,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A ponderosa pine , 11 ins. diam., bears N. 77° W., 25 lks. dist., with a healed blaze.</p> <p>Iron post is set in a well embedded mound of stone, 3 1/2 ft. base, to top</p> <p>Not remonumented.</p> <p>From this cor. point, Arizona Department of Transportation, Highway Division triangulation station "PORT, 1978", bears N. 42°17'19" E. (forward bearing), 1,021.28 chs. dist., monumented with an aluminum disk, 3 1/2 ins. diam., firmly set in a concrete cylinder, 10 ins. diam., projecting 5 ins. above the ground, mkd. ARIZONA D.O.T. HWY DIV P.& M. GEODETIC SURVEY PORT 1978 and a triangle, (the station is located near the Springerville Airport).</p> <p>N. 0°09' W., bet. secs. 13 and 14.</p> <p>Over land sloping gently northeasterly into the E. fork of the Little Colorado River, through moderate pine and spruce timber.</p>
5.00	Enter riparian growth in the marshy river plain.
15.00	Leave marshy river plain.
20.00	<p>The S 1/16 sec. cor. of secs. 13 and 14, monumented with an iron post, 2 1/2 ins. diam., projecting 2 ins. from the ground, with brass cap mkd. as described in the official record of the 1968 resurvey, from which bearing objects.</p> <p>A ponderosa pine, 19 ins. diam., bears S. 67° E., 44 lks. dist., mkd. S1/16 S13 BT.</p> <p>The cor. of fences reported in 1968, (N. 22° E., 59 lks), has been removed.</p> <p>Iron post is set in a mound of stone, 2 ft. base, to top,</p> <p>A steel fence post, with U.S. Forest Service signs attached, is set alongside the iron post.</p> <p>Not remonumented.</p> <p>from which new bearing objects</p> <p>A cor. of fences, bears N. 88 1/4° E., 22 lks. dist., extends NE and W.</p>

Dependent Resurvey, Subdivisional Lines,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	The cor. is located in a fence, bears E. and W.
	N. 0°09' W., beginning new measurement.
	Ascend, enter moderate ponderosa pine timber.
14.53	Cor. 8, Lot 3, sec. 13, hereinafter described.
15.50	Descend, entering a populated area, along the W. edge of Apache County Road No. 1121.
19.42	The witness 1/4 sec. cor. of secs. 13 and 14, monumented with an iron post, 1 in. diam., set 9 ins. below the surface of the ground, with brass cap mkd. as described in the official record of the 1940 resurvey, from which bearing trees of record
	A ponderosa pine, 20 ins. diam., bears N. 67 1/2° E., 65 lks. dist., mkd. WC 1/4 S13 BT, (remark to read WP S13 BT).
	A ponderosa pine, 22 ins. diam., bears S. 34° W., 12 lks. dist., with a healed blaze.
	A steel fence post, with U.S. Forest Service signs attached, is set alongside cor.
	This cor. now functions as a witness point.
	Remark brass cap to read.
	WP T7N R27E S14 S13 1990 1940
	The cor. is located on the W. edge of Apache County Road No. 1121.
20.02	True point for the 1/4 sec. cor of secs. 13 and 14, perpetuated by George Sohn, P.E. 2510, as shown on a map in the possession of Thomas H. Glantz, P.O. Box 147, Greer, Arizona. Point is monumented with a rebar, 19 ins. long, 5/8 ins. diam., set 5 ins. below the surface of the ground, with an aluminum cap, 1 1/2 ins. diam., mkd. PE 2510 1/4. This is accepted as a careful and faithful perpetuation of the original cor. position.

Dependent Resurvey, Subdivisional Lines,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
18 ins. below the surface of the graded road, with brass cap mkd.

T7N R27E
1/4
S14 | S13
1990

from which

An aluminum post, 36 ins. long, 3/4 ins. diam., set 29 ins.
in the ground, for a reference monument, bears
N. 71 3/4° E., 59.93 ft. dist., with cap mkd. RM T7N R27E
1/4 59.93 FT TO COR S13 1990, and an arrow pointing to the
cor.

An aluminum post, 36 ins. long, 3/4 ins. diam., set 30 ins.
in the ground, for a reference monument, bears
S. 32 1/2° E., 102.39 ft. dist., with cap mkd. RM T7N R27E
1/4 S13 102.39 FT TO COR 1990, and an arrow pointing to
the cor.

A ponderosa pine, 8 ins. diam., bears S. 56° W., 88 lks.
dist., mkd. 1/4 S14 BT.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case
beneath the stainless steel post.The found cor. is set above a rebar, 1/2 in. diam., 28 ins. long,
13 ins. below the surface of the ground.

Deposit both the local rebars inside the stainless steel post.

A telephone cable, bears N. and S., is set 21 ins. below the
surface alongside the stainless steel post.The cor. is located on the W. edge of Apache County Road No.
1121, 50 lks. wide, bears N. and S.

N. 0°09' W., beginning new measurement.

3.40

Rail fence, bears NE and SW, leave W. edge of road, enter yard of
a residence.

Dependent Resurvey, Subdivisional Lines,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
4.95	Propane tank, 3 ft. diam., 10 ft. long, bears E., 5 lks. dist.
6.31	An aluminum cap, 1 1/2 ins. diam., set flush with the surface, in a concrete collar 8 ins. diam., mkd. PE 2510 B4 L1 L2, established by George Sohn, PE 2510, recorded in book 5 of townsite maps, page 54, at the Apache County Recorder's office, St. Johns, Arizona. The cor. is located in a rail fence, bears E. and W.
9.30	A point 7 lks. W. of the SE cor. of a stable, 20 x 30 ft.
9.60	A point 7 lks. W. of the NE cor. of a stable.
11.60	An aluminum cap, 1 1/2 ins. diam., set flush with the surface, in a concrete collar 8 ins diam., mkd. PE 2510 B1 L3, established by George Sohn, PE 2510, recorded in book 5 of townsite maps, page 54, at the Apache County Recorder's office, St. Johns, Arizona.
11.97	Cor. 3, Lot 2, sec. 13, identical with cor. 7, Lot 3, sec. 13, hereinafter described.
12.80	A point 8.5 lks. W. of the SE cor. of the S. wall of a house, 34 x 46 ft.
13.50	A point 18 lks. W. of the NW cor. of a house.
15.49	Cor. 2, Lot 2, sec. 13, hereinafter described.
15.95	Little Colorado River, 40 lks. wide, course NE. Thence over nearly level, swampy river plain, through dense riparian growth.
16.70	Cor. of fences extending NE and W. Leave populated area.
40.06	The cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 2 ins. diam., projecting 18 ins. from the ground, with brass cap mkd. as described in the official record of the 1968 resurvey of the subdivisional lines T. 7 N., R. 27 E.. Cor. is set in a scattered mound of stone, Not remonumented. Rebuild the mound of stone, 5 ft. base, to top.

Dependent Resurvey, Subdivisional Lines,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A steel fence post, with U.S. Forest Service signs attached, is set alongside the iron post.</p>
	<p>The cor. is located at the S. side of fence cor. extending N., S. and W.</p>
	<p>N. 0°51' E., bet. secs. 11 and 12.</p>
	<p>Over nearly level, marshy river plain, through dense riparian growth.</p>
19.89	<p>The S 1/16 sec. cor. of sec. 11 and 12, monumented with an iron post, 2 1/2 ins. diam., loosely set, projecting 12 ins. from the ground, with brass cap mkd. as described in the official record of the 1968 resurvey of the subdivisional lines, T. 7 N., R. 27 E.</p>
	<p>A steel fence post, with U.S. Forest Service signs attached, is set alongside the iron post.</p>
	<p>Not remonumented.</p>
	<p>No suitable reference monuments available.</p>
	<p>N. 0°51' E., beginning new measurement.</p>
14.00	<p>Ascend, leave river plain, enter populated area.</p>
15.35	<p>Cor. 3, Lot 12, sec. 12, hereinafter described.</p>
19.545	<p>The witness 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 1 in. diam., projecting 6 ins. from the ground, with brass cap mkd. as described in the official record of the 1940 resurvey of the subdivisional lines, from which bearing trees of record</p>
	<p>A ponderosa pine, 49 ins. diam., bears N. 85° E., 2.60 chs. dist., mkd. WC 1/4 S12 BT, (remark to read WP S12 BT).</p>
	<p>A ponderosa pine, 26 ins. diam., bears S. 4° W., 2.42 chs. dist., mkd. WC 1/4 S11 BT, (remark to read WP S11 BT).</p>
	<p>A steel fence post, with U.S. Forest Service signs attached, is set alongside the iron post.</p>
	<p>Cor. now functions as a witness point</p>

Dependent Resurvey, Subdivisional Lines,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Remark brass cap to read.</p> <p style="text-align: center;">WP T7N R27E S11 S12 1990 1940</p> <p>The cor. is located near the S. edge of Apache County Road No. 1120.</p> <p>19.895 True point for the 1/4 sec. cor of secs. 11 and 12, identical with cor. 3, Lot 6, sec. 12, and cor. 2, Lot 12, sec. 12, determined on line and at record dist. from the witness 1/4 sec. cor. for secs. 11 and 12. This is accepted as the best remaining evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set a railroad spike, 6 ins. long, 5/8 in. sq., flush with the paved surface.</p> <p>from which</p> <p style="padding-left: 40px;">An aluminum post, 36 ins. long, 3/4 ins. diam., set 32 ins. in the ground, for a reference monument, bears N. 1 3/4° E., 46.78 ft. dist., with cap mkd. RM T7N R27E 1/4 46.78 FT TO COR S12 1990, and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An aluminum post, 36 ins. long, 3/4 ins. diam., set 29 ins. in the ground, for a reference monument, bears S. 62 3/4° W., 56.11 ft. dist., with cap mkd. RM T7N R27E 1/4 S11 56.11 FT TO COR 1990, and an arrow pointing to the cor.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case, below the railroad spike.</p> <p>The cor. is located in the southerly lane of Apache County Road No. 1120, 50 lks. wide, bears NE and SW.</p> <p style="text-align: center;">—————</p> <p>N. 1°30' E., bet. secs. 11 and 12, beginning new measurement</p> <p>0.05 Center line of the right-of-way of Apache County Road No. 1120, 50 lks. wide, bears NE and SW.</p>
--------	--

Dependent Resurvey, Subdivisional Lines,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
6.65	Top of hill; descend.
17.00	Enter nearly level, swampy river plain, with dense riparian growth.
18.79	AP 4, Tract 38, identical with cor. 2, Lot 6, sec. 12, hereinafter described.
19.52	<p>The N 1/16 sec. cor. of secs. 11 and 12, identical with AP 5, Tract 38, monumented with an iron post, 2 1/2 ins. diam., projecting 8 ins. from the ground, with a brass cap mkd. as described in the official record of the 1968 resurvey of the subdivisional lines T. 7 N., R. 27 E.</p> <p>Not remonumented</p> <p>The cor. is located at cor. of fences extending N., E., S., and W.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 2, monumented with an iron post, 1 in. diam., projecting 8 ins. from the ground, with a brass cap mkd. as described in the official record of the 1968 resurvey of the subdivisional lines, T. 7 N., R. 27 E.</p> <p>from which a 1940 bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam. bears N. 15 3/4° W., 49 lks. dist., mkd. 1/4 S2 BT.</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam. bears N. 18 1/2° E., 1.33 chs. dist., mkd. 1/4 S1 BT.</p> <p style="padding-left: 40px;">A steel fence post, with U.S. Forest Service signs attached, is set alongside the cor.</p> <p>Remark brass cap to read</p> <div style="text-align: center; padding: 10px 0;"> <p>T7N R27E</p> <p>1/4</p> <p>S2 S1</p> <p>1990</p> <p>1940</p> </div> <p>The cor. is located 1 lk. NE of a cor. of fences extending S. and W.</p>

Dependent Resurvey, Subdivisional Lines,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 1°49' W., bet. secs. 1 and 2.</p>
	<p>Over nearly level land, through moderate ponderosa pine timber.</p>
6.675	<p>A point for a witness point at intersection of line 2-3, Tract 39, identical with the center line of Apache County Road No. 1122, 50 lks. wide, bears SE and NW, hereinafter described.</p>
	<p>Thence enter a U.S. Forest Service campground.</p>
20.24	<p>Point for the N 1/16 sec. cor. of secs. 1 and 2.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T7N R27E N 1/16 S2 S1 1990</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam. bears N. 11 1/4° E., 25 lks. dist., mkd. N1/16 S1 BT.</p>
	<p style="padding-left: 40px;">A ponderosa pine, 5 ins. diam. bears N. 59 3/4° W., 21 lks. dist., mkd. X BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post alongside the cor.</p>
	<p>Cor. is located near camp site No. 37 of the Hoyer Memorial Campground.</p>
40.29	<p>The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.</p>
	<hr/>

Dependent Resurvey, Subdivision of Selected Sections,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Restoring the surveys executed by Jerrold E. Knight, in 1968</p> <hr/> <p>Section 1</p> <hr/> <p>From the center W 1/16 sec. cor. of sec. 1, identical with AP 9, Tract 39, monumented with an iron post, 2 1/2 ins. diam., projecting 11 ins. from the ground, with brass cap mkd. as described in the official record of the 1968 survey of the subdivision of sections, from which bearing objects of record</p> <p style="padding-left: 40px;">A rebar, 1/2 in. diam., projecting 4 ins. from the ground, bears N. 32 1/2° E., 22 lks. dist. (Record: N. 41° E.).</p> <p style="padding-left: 40px;">A rebar, 5/8 in. diam., projecting 6 ins. from the ground, bears N. 89 3/4° W., 30 lks. dist., with a tag attached, mkd. PE 6123.</p> <p>A mound of stone, 2 ft. base, 1 ft. high, is set N. of the cor. (Record: Iron post in a mound of stone),</p> <p>A steel fence post, with U.S. Forest Service signs attached, is set alongside the iron post.</p> <p>Remark brass cap to read.</p> <div style="text-align: center; padding: 10px;"> <p>T7N R27E W 1/16 C ————— C S1 1990 1968</p> </div> <p>Rebuild the mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of the cor.</p> <p>S. 89°54' W., on the E. and W. center line of sec. 1.</p> <p>1.10 Arizona Highway No. 373, paved surface, 90 lks. wide, bears SE and NW.</p> <p>19.80 The 1/4 sec. cor. of secs. 1 and 2, identical with AP 8, Tract 39, hereinbefore described.</p> <hr/>
--------	--

Dependent Resurvey, Subdivision of Selected Sections,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>SW 1/4 Section 1</p> <hr/>
	<p>From the SW 1/16 sec. cor. of sec. 1, identical with Cor. 2, Lot 8, sec. 1, monumented with an iron post, 2 1/2 ins. diam., projecting 5 ins. from the ground, with brass cap mkd. as described in the official record of the 1968 survey of the subdivision of sections, from which an original bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 17 ins. diam. bears N. 56 1/2° E., 17 lks. dist., with illegible scribe marks visible in a partially healed blaze (Record: N. 50° E.).</p> <p>A steel fence post, with U.S. Forest Service signs attached, is set alongside the iron post.</p> <p>Remark brass cap to read</p> <p style="text-align: center;">T7N R27E SW 1/16 + S1 1990 1968</p> <p>N. 1°26' W., on the N. and S. center line of the SW 1/4 of sec. 1.</p>
14.935	Cor. 1, Lot 8, sec. 1, identical with the center line of the right-of-way of Arizona Highway No. 373, 90 lks. wide, bears SE and NW, hereinafter described.
20.105	The center W 1/16 sec. cor. of sec. 1, identical with AP 9, Tract 39, hereinbefore described.
	<hr/>
	<p>From the center S 1/16 sec. cor. of sec. 1, monumented with an iron post, 2 1/2 ins. diam., projecting 12 ins. from the ground, with brass cap mkd. as described in the official record of the 1968 survey of the subdivision of sections, from which an original bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam. bears N. 73 1/4° W., 22 lks. dist., mkd. with a healed blaze (Record: N. 28 1/2° W.).</p> <p>Cor. is set in a scattered mound of stone,</p> <p>A steel fence post, with U.S. Forest Service signs attached, is set alongside the iron post.</p>

Dependent Resurvey, Subdivision of Selected Sections,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Remark brass cap to read</p> <p style="text-align: center;">T7N R27E C S1/16 S1 C 1990 1968</p> <p>The cor. is located 3 lks. N. of a cor. of fences extending S. and W.</p> <p>S. 89°31' W., on the E. and W. center line of the SW 1/4 of sec. 1.</p> <p>16.91 Cor. 3, Lot 8, sec. 1, identical with the center line of the right-of-way of Arizona Highway No. 373, 90 lks. wide, in a curve with tangents bearing NW and SW ,hereinafter described.</p> <p>19.67 The SW 1/16 sec. cor. of sec. 1.</p> <hr/> <p style="text-align: center;">Section 2</p> <hr/> <p>From the center 1/4 sec. cor. of sec. 2, monumented with an iron post, 2 1/2 ins. diam., projecting 13 ins. from the ground, with brass cap mkd. as described in the official record of the 1968 survey of the subdivision of sections, from which original bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam. bears N. 57° E., 40 lks. dist., mkd. C 1/4 S2 BT (Record: N. 56 1/2° E., 41 lks.).</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam. bears S. 14 1/4° W., 61 lks. dist., mkd. with a healed blaze (Record: S. 17 1/2° W., 63 lks.).</p> <p>A scattered mound of stone is set S. of the cor. (Record: In a collar of stone),</p> <p>Remark brass cap to read</p> <p style="text-align: center;">T7N R27E C 1/4 + S2 1990 1968</p>
--------	---

Dependent Resurvey, Subdivision of Selected Sections,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Rebuilt mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of the cor.</p> <p>N. 1°38' W., on the N. and S. center line of sec. 2.</p> <p>Descend through moderate ponderosa pine timber.</p>
9.70	Begin steeper descent.
20.135	<p>Point for the center N 1/16 sec. cor. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T7N R27E</p> <p>C</p> <p>N1/16 S2</p> <p>C</p> <p>1990</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 8 ins. diam. bears S. 3 3/4° E., 46 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam. bears N. 38 1/4° W., 1.73 chs. dist., mkd. CN 1/16 S2 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Thence over nearly level land.</p>
20.75	Track road, 20 lks. wide, bears NE and W.
23.90	<p>Rock ledge, on top of Benny Creek drainage, bears NE and SW.</p> <p>Descend</p>
25.70	<p>Benny Creek, 20 lks. wide, course NE.</p> <p>Ascend</p>
27.40	Rock ledge, on top of Benny Creek drainage, bears NE and SW.

Dependent Resurvey, Subdivision of Selected Sections,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Thence over nearly level land
34.50	Track road, 15 lks. wide, bears NE and SW.
39.94	The 1/4 sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp., hereinbefore described.
	From the 1/4 sec. cor. of secs. 1 and 2, identical with AP 8, Tract 39.
	N. 89°15' W., on the E. and W. center line of sec. 2.
12.50	Graded dirt road, 30 lks. wide, bears SE and NW.
20.015	The center E 1/16 sec. cor. of sec. 2, identical with AP 7, Tract 39, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. from the ground, with a brass cap mkd. as described in the official record of the 1968 survey of the subdivision of sections, from which original bearing trees
	A ponderosa pine, 16 ins. diam. bears S. 33 3/4° W., 90 lks. dist., with illegible scribe marks visible in a partially healed blaze (Record: S. 43 1/2° W., 91 lks.).
	A ponderosa pine, 16 ins. diam. bears N. 36 3/4° W., 36 lks. dist., with illegible scribe marks visible in a partially healed blaze (Record: N. 35° W., 37 lks.).
	A rebar, 1/2 in. diam., is set alongside the iron post.
	Cor. is set in a scattered mound of stone (Record: mound of stone, N. of cor.).
	A steel fence post, with U.S. Forest Service signs attached, is set alongside the iron post.
	Remark brass cap to read
	<p style="text-align: center;">T7N R27E E1/16 C—C S2 1990 1968</p>
	Rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of the cor.

Dependent Resurvey, Subdivision of Selected Sections,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.025	<p>N. 89°12' W., beginning new measurement</p> <p>The center 1/4 sec. cor. of sec. 2.</p>
	<p style="text-align: center;">NE 1/4 Section 2</p> <hr style="width: 20%; margin: auto;"/>
15.14	<p>From the center E 1/16 sec. cor. of sec. 2</p> <p>N. 1°44' W., on the N. and S. center line of the NE 1/4 of sec. 2.</p> <p>Point for the center N-S-NE 1/256 sec. cor. of sec. 2, identical with AP 6, Tract 39.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T7N R27E S2 C-N-S-NE 1/256 1990</p>
	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears N. 2 1/2° E., 1.38 chs. dist., mkd. C-N-S-NE 1/256 S2 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam. bears N. 26 1/4° W., 61 lks. dist., mkd. X BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post alongside the cor.</p>
20.19	<p>Point for the NE 1/16 sec. cor. of sec. 2, at intersection with the E. and W. center line of the NE 1/4 of sec. 2.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T7N R27E NE 1/16 S2 1990</p>

Dependent Resurvey, Subdivision of Selected Sections,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>A ponderosa pine, 8 ins. diam. bears N. 47 1/2° E., 18 lks. dist., mkd. NE 1/16 S2 BT.</p> <p>A ponderosa pine, 8 ins. diam. bears N. 19 3/4° W., 27 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
40.12	The E 1/16 sec. cor. of sec. 2, on the N. bdy. of the Tp., hereinbefore described.
	<hr/> <p>From the N 1/16 sec. cor. of secs. 1 and 2</p> <p>N. 89°22' W., on the E. and W. center line of the NE 1/4 of sec. 2.</p>
19.98	The NE 1/16 sec. cor of sec. 2
39.97	The center N 1/16 sec. cor. of sec. 2
	<hr/> <p>Section 12</p> <hr/>
	<p>From the point for the center 1/4 sec. cor. of sec. 12, determined from bearing objects</p> <p>A ponderosa pine, 10 ins. diam. bears S. 53° W., 41 lks. dist., mkd. C 1/4 S12 BT.</p> <p>The NW cor. of a cabin, 20 x 12 ft., bears S. 26° E., 79 lks. dist.</p> <p>The SW cor. of a cabin, 32 x 16 ft., bears N. 56° E., 1.48 chs. dist.</p> <p>An iron post, 30 ins. long, 2 1/2 in. diam., with a brass cap mkd. as described in the official record of the 1968 survey of the subdivision of sections, was found leaning against a tree nearby.</p>

Dependent Resurvey, Subdivision of Selected Sections,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>At the cor. point</p> <p>Reset the iron post, 25 ins. in the ground and remark brass cap to read</p> <p style="text-align: center;">T7N R27E C 1/4 + S12 1990 1968</p> <p>from which a new bearing tree</p> <p style="text-align: center;">The southerly fork of a fir, 8 ins. diam., bears N. 22 1/2° W., 1.14 chs. dist., mkd. C 1/4 S12 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the iron post.</p> <p>Set a steel fence post alongside the cor.</p> <p>N. 0°24' E., on the N. and S. center line of sec. 12.</p> <p>Descend, through a populated area, with moderate ponderosa pine timber.</p>
9.955	Intersect line 13-14, Tract 40, at a point from which AP 14, Tract 40, bears S.75°32' E., 0.925 chs. dist., hereinafter described.
19.715	<p>Center N 1/16 sec. cor. of sec. 12, identical with AP 16, Tract 40, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. from the ground, loosely set in a scattered mound of stone, with brass cap mkd. as described in the official record of the 1968 survey of the subdivision of sections, from which bearing trees of record</p> <p style="text-align: center;">A ponderosa pine, 12 ins. diam. bears N. 50° E., 18 lks. dist., mkd. CN 1/16 S12 BT (Record: N. 48° E.).</p> <p style="text-align: center;">A ponderosa pine, 15 ins. diam. bears N. 40° W., 67 lks. dist., mkd. CN 1/16 S12 BT (Record: 60 lks.).</p> <p>At the cor. point</p>

Dependent Resurvey, Subdivision of Selected Sections,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Reset the iron post, 16 ins. in the ground, in a mound of stone, 4 ft. base, to top, remark brass cap to read</p> <p style="text-align: center;">T7N R27E C N 1/16 S12 C 1990 1968</p> <p>from which an new bearing object</p> <p style="padding-left: 40px;">A magnet in a 1 x 1 x 2 5/8 ins. grey colored plastic case, 12 ins. below ground, bears S. 52 1/2° W., 76 lks. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the cor.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°20' E., beginning new measurement</p> <p>6.29 Intersect line 2-3, Tract 40, at a point from which AP 2, Tract 40, bears N. 45°04' E., 2.50 chs. dist., hereinafter described.</p> <p>19.71 The 1/4 sec. cor. of secs. 1 and 12, monumented with an iron post, 1 ins. diam., firmly set, projecting 7 ins. from the ground, with brass cap mkd.</p> <p style="text-align: center;">S1 1/4 — S12 1940</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears N. 30 1/2° E., 135 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears S. 79° E., 55 lks. dist., with illegible scribe mks. on a partially open blaze.</p> <p>A steel fence post, with U.S. Forest Service signs attached, is set alongside the iron post.</p> <p>Cor. is located 5 lks. W. of cor. of fences extending, N., ESE and W.</p> <hr style="width: 80%; margin: 10px auto;"/>
--------	---

Dependent Resurvey, Subdivision of Selected Sections,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the center 1/4 sec. cor. of sec. 12.</p>
	<p>S. 89°45' W., on the E. and W. center line of sec. 12.</p>
	<p>Descend through dense ponderosa pine timber.</p>
3.66	<p>Intersect line 11 and 12, Tract 40, at a point from which AP 11, Tract 40, bears S. 59°08.5' W., 2.99 chs. dist., hereinafter described.</p>
19.905	<p>The center W 1/16 sec. cor. of sec. 12, monumented with an iron post, 2 1/2 ins. diam., projecting 8 ins. from the ground, with brass cap mkd. as described in the official record of the 1968 survey of the subdivision of sections, from which remains of bearing trees of record</p>
	<p>A pine stump, bears S. 6° W., 50 lks. dist. (Record: S. 7° W.).</p>
	<p>A pine stump, bears N. 65 3/4° W., 32 lks. dist. (Record: N. 68° W., 33 lks.).</p>
	<p>A scattered mound of stone is set N. of the cor.</p>
	<p>Remark brass cap to read</p>
	<p style="text-align: center;">T7N R27E W 1/16 C———C S12 1990 1968</p>
	<p>from which new bearing trees</p>
	<p>A ponderosa pine, 7 ins. diam. bears N. 70 1/4° E., 64 lks. dist., mkd. X BT.</p>
	<p>A ponderosa pine, 10 ins. diam. bears N. 35 3/4° W., 27 lks. dist., mkd. CW 1/16 S12 BT.</p>
	<p>Rebuild the mound of stone, 3 ft. base, 1 1/2 ft. high, N. of the cor.</p>
	<p style="text-align: center;">—————</p> <p>S. 89°42' W., beginning new measurement</p>

Dependent Resurvey, Subdivision of Selected Sections,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
4.84	Intersect line 8 and 9, Tract 40, at a point from which AP 8, Tract 40, bears N. 47°53' W., 5.43 chs. dist., hereinafter described.
19.92	The 1/4 sec. cor. of secs. 11 and 12, hereinbefore described.
<hr/>	
From the center W 1/16 sec. cor. of sec. 12	
N. 0°55' E., on the N. and S. center line of the NW 1/4 of sec. 12.	
14.665	Intersect line 5-6, Tract 40, identical with line 6-7, Lot 6, at a point from which AP 5, Tract 40, identical with Cor. 7, Lot 6, bears N. 22°16' E., 1.82 chs. dist., hereinafter described.
14.70	Center line of the right-of-way of Arizona Highway No. 373, 90 lks. wide, in a curve with tangents bearing NE and SW.
17.465	Intersect line 3-4, Tract 38, identical with line 1-2, Lot 6, at a point from which AP 3, Tract 38, identical with Cor. 1, Lot 6, bears S. 86°28' E., 0.185 chs. dist., hereinafter described.
19.61	The NW 1/16 sec. cor. of sec. 12, identical with AP 6, Tract 38, monumented with an iron post, 2 1/2 ins. diam., projecting 12 ins. from the ground, with brass cap mkd. as described in the official record of the 1968 survey of the subdivision of sections
Cor. is set in a mound of stone, 3 ft. base to top.	
Not remonumented	
<hr/>	
From the center N 1/16 sec. cor. of sec. 12, identical with AP 16, Tract 40.	
S. 89°26' W., on the E. and W. center line of the NW 1/4 of sec. 12.	
7.89	Intersect line 3-4, Tract 40, at a point from which AP 3, Tract 40, bears N. 57°54' E., 4.88 chs. dist., hereinafter described.
18.40	Center line of the right-of-way of Arizona Highway No. 373, 90 lks. wide, in a curve with tangents bearing NE and SW.

Dependent Resurvey, Subdivision of Selected Sections,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>19.255 Intersect line 2-3, Tract 38, at a point from which AP 2, Tract 38, bears N. 8°35' E., 0.80 chs. dist., hereinafter described.</p> <p>19.73 The NW 1/16 sec. cor. of sec. 12, identical with AP 6, Tract 38.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°26.5' W., on line 5-6, Tract 38, beginning new measurement.</p> <p>19.74 The N 1/16 sec. cor. of secs. 11 and 12, identical with AP 5, Tract 38.</p> <hr/> <p style="text-align: center;">Metes-and-Bounds Surveys, T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Lot 8, Section 1</p> <hr/> <p>From the point for Cor. 1, Lot 8, sec. 1, at the intersection of the N. and S. center line of the SW 1/4 of sec. 1, with the center line of the right-of-way of Arizona Highway No. 373.</p> <p>Set a railroad spike, 7 ins. long, 5/8 in. sq., flush with the paved surface.</p> <p>from which</p> <p style="padding-left: 40px;">An aluminum post, 23 ins. long, 3/4 ins. diam., set 20 ins. in the ground, for a reference monument, bears N. 45° E., 58.71 ft. dist., with cap mkd. RM T7N R27E 58.71 FT TO COR COR S1 1990, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.</p> <p style="padding-left: 40px;">An aluminum post, 18 ins. long, 3/4 ins. diam., set 6 ins. in the ground, in a drill hole in bedrock, encircled in a mound of stone, 3 ft. base, to top, for a reference monument, bears N. 45° W., 94.94 ft. dist., with cap mkd. RM T7N R27E 94.94 FT TO COR COR S1 1990, and an arrow pointing to the cor.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case, below the railroad spike.</p> <p>From this cor. point, the easterly right-of-way station 138+68.95, monumented with a brass disk, 3 ins. diam., firmly set in concrete, flush with the surface of the ground, mkd. AZ HWY DEPT PT 138+68.95 50' 1959, bears S. 17°48' E., 9.56 chs. dist.</p>
--------	---

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this same cor. point, the westerly right-of-way station 138+68.95, monumented with a brass disk, 3 ins. diam., firmly set in concrete, flush with the surface of the ground, mkd. AZ HWY DEPT PT 138+68.95 50' 1959, bears S. 8°44' E., 9.56 chs. dist.</p>
	<p>From this same cor. point, the westerly right-of-way station 161+01.74, monumented with a brass disk, 3 ins. diam., firmly set in concrete, 1 in. below the surface of the ground, mkd. AZ HWY DEPT 161+01.74 50' 1959, bears N. 15°03' W., 24.30 chs. dist.</p>
	<p>From this same cor. point, the easterly right-of-way station 161+01.74, monumented with a brass disk, 3 ins. diam., firmly set in concrete, projecting 3 ins. above the ground, mkd. AZ HWY DEPT PC 161+01.74 50' 1959, bears N. 11°29' W., 24.30 chs. dist.</p>
	<p>S. 1°26' E., on line 1-2, identical with a portion of the N. and S. center line of the SW 1/4 of sec. 1.</p>
14.935	<p>Cor. 2, identical with the SW 1/16 sec. cor. of sec. 1, hereinbefore described.</p>
	<p>Thence N. 89°31' E., on line 2-3, identical with a portion of the E. and W. center line of the SW 1/4 of sec. 1.</p>
2.76	<p>Point for cor. 3, at intersection with the center line of the right-of-way of Arizona Highway 373.</p>
	<p>Set a railroad spike, 7 ins. long, 5/8 in. square, flush with the paved surface.</p>
	<p>from which</p>
	<p>An aluminum post, 36 ins. long, 3/4 ins. diam., set 32 ins. in the ground, for a reference monument, bears N. 89°31' E., 50.25 ft. dist., with cap mkd. RM T7N R27E 50.25 FT TO COR COR S1 1990, and an arrow pointing to the cor.</p>
	<p>An aluminum post, 36 ins. long, 3/4 ins. diam., set 32 ins. in the ground, for a reference monument, bears S. 89°31' W., 50.12 ft. dist., with cap mkd. RM T7N R27E 50.12 FT TO COR COR S1 1990, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case, beneath the railroad spike.</p>

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, the easterly right-of-way station 130+85.20, monumented with a brass disk, 3 ins. diam., firmly set in concrete, flush with the surface of the ground, mkd. AZ HWY DEPT PC 130+85.20 50' 1959, bears S. 8°39' E., 6.25 chs. dist.</p>
	<p>From this same cor. point, westerly right-of-way station 138+68.95, bears N. 17°08' W., 5.71 chs. dist., hereinbefore described,</p>
	<p>From this same cor. point, the easterly right-of-way station 138+68.95, bears N. 2°04' W., 5.81 chs. dist., hereinbefore described.</p>
	<hr/> <p>Thence on line 3-4, identical with the arc of an 2° circular curve to the left having a radius of 2862.40 ft., along the center line of Arizona Highway No. 373, the chord of said arc bears N. 9°31.5' W., 5.71 chs. dist.,</p>
5.713	<p>Point for Cor. 4, identical with a point of curvature on the center line of the right-of-way of Arizona Highway 373.</p> <p>Set a railroad spike, 7 ins. long, 5/8 in. square, flush with the paved surface.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case, beneath the railroad spike.</p>
	<p>From this cor. point, the easterly right-of-way station 138+68.95, hereinbefore described, bears N. 76°41' E., 76 lks. dist.</p>
	<p>From this same cor. point, the westerly right-of-way station 138+68.95, bears S. 76°41' W., 76 lks. dist. hereinbefore described.</p>
	<hr/> <p>Thence N. 13°16' W., on line 4-1, identical with the center line of the right-of-way of Arizona Highway No. 373.</p>
9.53	<p>Cor. 1, point of beginning.</p>
	<hr/> <p style="text-align: center;">Lot 6, Section 12</p> <hr/>
	<p>From cor. 1, Lot 6, sec. 12, identical with AP 3, Tract 38, monumented with an iron post, 2 1/2 ins. diam., projecting 7 ins. from the ground, with brass cap mkd. as described in the official record of the 1968 survey of Tract 38, T. 7 N., R. 27 E.</p>


Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

Cor. is set in a mound of stone, 3 ft. base, to top.

A steel fence post, with U.S. Forest Service signs attached, is set alongside the iron post.

Remark brass cap to read



From this cor. point, the NW 1/16 sec. cor. of sec. 12, identical with AP 6, Tract 38, bears N. 3°51' W, 2.16 chs. dist., hereinbefore described.

From this same cor. point, AP 2, Tract 38, identical with the westerly right-of-way station 109+15.81, monumented with a brass disk, 3 ins. diam., firmly set in concrete, 3 ins. below the surface of the ground, mkd. AZ HWY DEPT 110+27.70 POT AHD 109+15.81 50' 1959, bears N. 8°35' E., 2.98 chs. dist.

From this same cor. point, the easterly right-of-way station 109+15.81, monumented with a brass disk, 3 ins. diam., firmly set in concrete, flush with the surface of the ground, mkd. AZ HWY DEPT 19, bears N. 34°12' E., 3.49 chs. dist.

N. 86°28' W. on line 1-2, Lot 6, sec. 12, identical with line 3-4, Tract 38.

0.185 Intersect the N-S center line of the NW 1/4, Sec. 12, at a point from which the NW 1/16 Sec. cor. of sec. 12, bears N. 0°55' E., 2.145 chs. dist., hereinbefore described.

19.93 Point for Cor. 2, identical with AP 4, Tract 38, on the line bet. secs. 11 and 12, monumented with an iron post, 2 1/2 ins. diam., projecting 7 ins. from the ground, with brass cap mkd. as described in the official record of the 1968 survey of Tract 38, T. 7 N., R. 27 E.

A steel fence post, with U.S. Forest Service signs attached, is set alongside the cor.

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Remark brass cap to read</p> <div style="text-align: center;"> <p>T7N R27E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S11</td> <td style="padding-left: 5px;">TR 38</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;"></td> <td style="padding-left: 5px;">AP 4</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;"></td> <td style="padding-left: 5px;">S12</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;"></td> <td style="padding-left: 5px;">COR 2 Lot 6</td> </tr> </table> <p>1990 1968</p> </div> <p>Cor. is located in a fence, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence S. 1°30' W., on line 2-3, identical with a portion of the line bet. secs. 11 and 12.</p> <p>18.79 Point for cor. 3, identical with cor. 2, Lot 12, sec. 12, and the 1/4 sec. cor. of secs. 11 and 12, hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence N. 79°41.5' E., on line 3-4, identical with line 1-2, Lot 12, sec. 12.</p> <p>3.88 Point for Cor. 4, identical with cor. 1, Lot 12, sec. 12, on the center line of the right-of-way of Arizona Highway No. 373.</p> <p>Set a railroad spike, 4 ins. long, 1/2 in. square, flush with the paved surface.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case, beneath the railroad spike.</p> <p>From this cor. point, the southerly right-of-way station 91+62.56, monumented with a brass disk, 3 ins. diam., firmly set in concrete, flush with the surface of the ground, mkd. AZ HWY DEPT PC 91+62.56 50' 1959, bears S. 6°31' E., 76 lks. dist.</p> <p>From this same cor. point, the northerly right-of-way station 91+62.56, monumented with a brass disk, 3 ins. diam., firmly set in concrete, projecting 3 ins. from the ground, mkd. AZ HWY DEPT PC 91+62.56 50' 1959, bears N. 6°31' W., 76 lks. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence on line 4-5, identical with the arc of a 5°40' circular curve to the left having a radius of 1010.98 ft., on the center line of the right-of-way of Arizona Highway No. 373, the chord of said arc bears N. 61°31' E., 10.79 chs. dist.,</p>	S11	TR 38		AP 4		S12		COR 2 Lot 6
S11	TR 38								
	AP 4								
	S12								
	COR 2 Lot 6								

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
7.933	AP 8, Tract 40, hereinafter described.
11.029	<p>Point for cor. 5, identical with AP 7, Tract 40.</p> <p>Set a a railroad spike, 4 ins. long, 1/2 in. square, flush with the paved surface.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case, beneath the railroad spike.</p> <p>From this cor. point, the southerly right-of-way station 98+92.24, monumented with a brass disk, 3 ins. diam., firmly set in concrete, flush with the surface of the ground, mkd. AZ HWY DEPT 98+92.24 50' 1959, bears S. 50°21' E., 76 lks. dist.</p> <p>From this same cor. point, the northerly right-of-way station 98+92.24, monumented with a brass disk, 3 ins. diam., firmly set in concrete, flush with the surface of the ground, mkd. AZ HWY DEPT PT 98+92.24 50' 1959, bears N. 50°21' W., 76 lks. dist.</p> <hr/> <p>Thence N. 39°38' E., on line 5-6, identical with line 6-7, Tract 40 on the center line of the right-of-way of Arizona Highway No. 373.</p>
7.81	<p>Point for cor. 6, identical with AP 6, Tract 40.</p> <p>Set a railroad spike, 4 ins. long, 1/2 in. square, flush with the paved surface..</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case, beneath the railroad spike.</p> <p>From this cor. point, the easterly right-of-way station 104+07.24, monumented with a brass disk, 3 ins. diam., firmly set in concrete, flush with the surface of the ground, mkd. AZ HWY DEPT PC 104+07.24 50' 1959, bears S. 50°25' E., 76 lks. dist.</p> <p>From this same cor. point, the northerly right-of-way station 104+07.24, monumented with a brass disk, 3 ins. diam., firmly set in concrete, flush with the surface of the ground, mkd. AZ HWY DEPT PC 104+07.24 50' 1959, bears N. 50°25' W., 76 lks. dist.</p> <hr/> <p>Thence on line 6-7, identical with line 5-6, Tract 40 and the arc of a 6° circular curve to the left having a radius of 954.93 ft., along the center line of Arizona Highway No. 373, the chord of said arc bears N. 29°08' E., 5.26 chs. dist.</p>

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
3.469	Intersect the N-S center line of the NW 1/4 of Sec. 12, at a point from which the NW 1/4 Sec. cor. of sec. 12, bears N. 0°55' E., 4.945 chs. dist., hereinbefore described.
5.289	Point for Cor. 7, identical with AP 5, Tract 40, at the intersection of the center lines of the right-of-way of Arizona Highway No. 373 and Apache County Road No. 1126.
	Set a railroad spike, 4 ins. long, 1/2 in. square, flush with the paved surface.
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case, beneath the railroad spike.
	From this cor. point, the easterly right-of-way station 110+27.70, monumented with a brass disk, 3 ins. diam., firmly set in concrete, flush with the surface of the ground, mkd. AZ HWY DEPT 19, bears N. 20°39' E., 4.27 lks. dist.
	From this same cor. point, the easterly right-of-way station 104+07.24, hereinbefore described, bears S. 21°16' W., 5.45 chs. dist.
	From this same cor. point, the westerly right-of-way station 104+07.24, bears S. 37°24' W., 5.18 chs. dist., hereinbefore described.
	From this same cor. point, the westerly right-of-way station 110+27.70, identical with AP 2, Tract 38, bears N. 0°08' W., 4.06 chs. dist., hereinbefore described.

	Thence N. 22°16' W., on line 7-1.
1.20	Cor. 1, identical with AP 3, Tract 38, point of beginning.

	Lot 12, Section 12,

	From Cor. 1, Lot 12, sec. 12, identical with Cor. 4, Lot 6, sec. 12, hereinbefore described.
	S. 79°41.5' W., on line 1-2, identical with line 3-4, Lot 6, sec. 12.
3.88	Cor. 2, identical with cor. 3, Lot 6, sec. 12, and the 1/4 sec. cor. of secs. 11 and 12, hereinbefore described.

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Thence S. 0°51' W., on line 2-3, identical with a portion of the line bet. secs. 11 and 12.</p> <p>0.35 Witness point, hereinbefore described.</p> <p>4.545 Point for Cor. 3</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T7N R27W LOT 12 COR 3 S11 S12 1990</p> </div> <p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 12 ins. diam. bears S. 86 3/4° E., 1.77 chs. dist., mkd. COR S12 BT.</p> <p style="margin-left: 40px;">An aluminum post, 36 ins. long, 3/4 ins. diam., set 31 ins. in the ground, for a reference monument, bears S. 22 1/2° E., 56.49 ft. dist., with cap mkd. RM T7N R27E COR S12 56.49 FT TO COR 1990, and an arrow pointing to the cor.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>The cor. is located on a stone wall, 18 ins. wide, 32 ins. high, bears N. and S.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>Thence N. 77°13' E., on line 3-4.</p> <p>3.335 Point for Cor. 4</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T7N R27E / LOT 12 COR 4 / S12 1990</p> </div>
--------	---

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p>from which</p> <p>A ponderosa pine, 4 ins. diam. bears N. 73 1/4° E., 2.21 chs. dist., mkd. X BT.</p> <p>A ponderosa pine, 12 ins. diam. bears S. 35 1/4° E., 1.29 chs. dist., mkd. COR S12 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>Thence N. 8°01' E., on line 4-1.</p> <p>4.545 Cor. 1, identical with Cor. 4, Lot 6, sec. 12, point of beginning.</p> <hr/> <p style="text-align: center;">Lot 2, Section 13</p> <hr/> <p>From the point for Cor. 1, Lot 2, sec. 13, identical with Cor. 5, Lot 3, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below the surface of a graded road, with brass cap mkd.</p> <div style="text-align: center;"> <p>T7N R27E S13 COR 1 COR 5 LOT 2 LOT 3 1990</p> </div> <p>from which</p> <p>A ponderosa pine, 12 ins. diam. bears N. 82 1/4° W., 69 lks. dist., mkd. COR 1 LOT 2 S13 BT.</p> <p>An aluminum post, 36 ins. long, 3/4 ins. diam., set 32 ins. in the ground, for a reference monument, bears N. 34° W., 58.87 ft. dist., with cap mkd. RM T7N R27E 58.87 FT TO COR S13 COR 1990, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.</p> <p>The cor. is located on the center line of the graded surface of Apache County Road No. 1121.</p>
---------------	---



Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>N. 40°19' W., on line 1-2.</p> <p>1.51 Point for Cor. 2, at intersection with the line bet. secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T7N R27E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S14</td> <td style="padding: 2px 5px;">S13</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;"></td> <td style="padding: 2px 5px;">COR 2</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;"></td> <td style="padding: 2px 5px;">LOT 2</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;"></td> <td style="padding: 2px 5px;">1990</td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 7 ins. diam. bears N. 58 1/4° E., 92 lks. dist., mkd. COR S13 BT.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>Thence S. 0°09' E., on line 2-3, identical with a portion of the line bet. secs. 13 and 14.</p> <p>3.52 Point for Cor. 3, identical with cor. 7, Lot 3, sec. 13, established by George Sohn, PE 2510, to determined a parcel described in a warranty deed recorded in docket 276, page 4, at the Apache County Recorder's office St. Johns, Arizona. This point is monumented with a rebar, 17 ins. long, 5/8 in. diam., firmly set 2 ins. below the surface of the ground, with an aluminum cap, 1 1/2 ins. diam., mkd. PE 2510. This is accepted as a careful and faithful determination of the cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T7N R27E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;"></td> <td style="padding: 2px 5px;">S13</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;"></td> <td style="padding: 2px 5px;">LOT 2</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;"></td> <td style="padding: 2px 5px;">COR 3</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S14</td> <td style="padding: 2px 5px;">COR 7</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;"></td> <td style="padding: 2px 5px;">LOT 3</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;"></td> <td style="padding: 2px 5px;">S13</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;"></td> <td style="padding: 2px 5px;">1990</td> </tr> </table> </div>	S14	S13		COR 2		LOT 2		1990		S13		LOT 2		COR 3	S14	COR 7		LOT 3		S13		1990
S14	S13																						
	COR 2																						
	LOT 2																						
	1990																						
	S13																						
	LOT 2																						
	COR 3																						
S14	COR 7																						
	LOT 3																						
	S13																						
	1990																						

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Deposit the rebar inside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence East, on line 3-4, identical with line 6-7, Lot 3, sec. 13.</p> <p>0.886 Point for Cor. 4, identical with cor. 6, Lot 3, sec. 13.</p> <p>Set a stainless steel post, 15 ins. long, 2 1/2 ins. diam., 12 ins. below the surface of a graded road, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T7N R27E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S13</td> <td style="padding: 2px 5px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">LOT 2</td> <td style="padding: 2px 5px;">LOT 3</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">COR 4</td> <td style="padding: 2px 5px;">COR 6</td> </tr> </table> <p style="margin-top: 5px;">S13 1990</p> </div> <p>from which</p> <p style="margin-left: 40px;">An aluminum post, 36 ins. long, 3/4 ins. diam., set 33 ins. in the ground, for a reference monument, bears N. 53 1/4° E., 75.88 ft. dist., with cap mkd. RM T7N R27E COR 6 LOT 3 75.88 FT TO COR S13 1990, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.</p> <p style="margin-left: 40px;">An aluminum post, 36 ins. long, 3/4 ins. diam., set 33 ins. in the ground, for a reference monument, bears S. 52 1/4° E., 58.86 ft. dist., with cap mkd. RM T7N R27E COR 6 LOT 3 58.86 FT TO COR S13 1990, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. is located on the center line of the graded surface of Apache County Road. No. 1121.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence N. 1°57' E., on line 4-1, identical with line 5-6, Lot 3, sec. 13, on the center line of the graded surface of Apache County Road No. 1121.</p>	T7N R27E		S13		LOT 2	LOT 3	COR 4	COR 6
T7N R27E									
S13									
LOT 2	LOT 3								
COR 4	COR 6								

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
2.37	<p>Cor. 1, identical with cor. 5, Lot 3, sec. 13, point of beginning.</p> <hr/> <p style="text-align: center;">Lot 3, Section 13,</p> <hr/> <p>From the point for cor. 1, Lot 3, sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>T7N R27E COR 1 LOT 3 S13 1990</p> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam. bears N 49 3/4° E., 64 lks. dist., mkd. COR S13 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 5 ins. diam. bears S. 51 1/2° E., 1.07 chs. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>S. 73°05' W., on line 1-2.</p>
3.165	<p>Point for cor. 2, at intersection with the center line of the graded surface of Apache County Road No. 1121.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below the surface of the graded road, with brass cap mkd.</p> <div style="text-align: center;">  <p>T7N R27E S13 COR 2 LOT 3 1990</p> </div>

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

from which


An aluminum post, 36 ins. long, 3/4 ins. diam., set 29 ins. in the ground, for a reference monument, bears N. 67 1/2° E., 77.66 ft. dist., with cap mkd. RM T7N R27E COR 77.66 FT TO COR S13 1990, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.

A ponderosa pine, 21 ins. diam. bears N. 26 3/4° W., 1.16 chs. dist., mkd. COR S13 BT.

Thence S. 7°37' W., on line 2-3, within the right-of-way of Apache County Road No. 1121.

3.015 Point for Cor. 3.

Set a stainless steel post, 15 ins. long, 2 1/2 ins. diam., 18 ins. below the surface of the graded road, with brass cap mkd.



from which

An aluminum post, 36 ins. long, 3/4 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 57 3/4° W., 92.77 ft. dist., with cap mkd. RM T7N R27E 92.77 FT TO COR COR S13 1990, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.

A ponderosa pine, 10 ins. diam. bears N. 37 1/2° W., 1.23 chs. dist., mkd. COR S13 BT.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.

Set a steel fence post alongside the cor.

The cor. is located on the W. edge of the graded surface of Apache County Road No. 1121.


Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Thence S. 15°30' E., on line 3-4, within the right-of-way of Apache County Road No. 1121.</p> <p>4.225 Point for Cor. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a steel fence post driven into the ground, and in a mound of stone, 3 ft. base, to top, with a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p style="margin: 0;">T7N R27E</p> <p style="margin: 0;">S13 } COR 4</p> <p style="margin: 0;"> } LOT 3</p> <p style="margin: 0;"> } 1990</p> </div> <p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 12 ins. diam. bears S. 85 1/2° W., 1.28 chs. dist., mkd. COR S13 BT.</p> <p style="margin-left: 40px;">An aluminum post, 36 ins. long, 3/4 ins. diam., set 34 ins. in the ground, for a reference monument, bears N. 56 1/2° W., 94.03 ft. dist., with cap mkd. RM T7N R27E 94.03 FT TO COR COR S13 1990, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>The cor. is located above the cut bank on the E. side of Apache County Road No. 1121.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence S. 37°13' W., on line 4-5, within the right-of-way of Apache County Road No. 1121.</p> <p>8.025 Point for cor. 5, identical with cor. 1, Lot 2, sec. 13, hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/>
--------	--

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Thence S. 1°57' W., on line 5-6, identical with line 4-1, Lot 2, sec. 13, on the center line of the graded surface of Apache County Road No. 1121.</p> <p>2.37 Point for cor. 6, identical with cor. 4, Lot 2, sec. 13, hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence West, on line 6-7, identical with line 3-4, Lot 2, sec. 13.</p> <p>0.886 Point for Cor. 7, identical with Cor. 3, Lot 2, sec. 13, on the line bet. secs. 13 and 14, hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence S. 0°09' E., on line 7-8, identical with a portion of the line bet. secs. 13 and 14.</p> <p>11.97 The 1/4 sec. cor. of secs. 13 and 14, hereinbefore described.</p> <p>12.62 The witness point on the line bet. secs. 13 and 14, hereinbefore described.</p> <p>17.46 Point for cor. 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p>from which</p> <p>A ponderosa pine, 10 ins. diam. bears S. 60 1/2° W., 79 lks. dist., mkd. COR S13 BT.</p> <p>An aluminum post, 36 ins. long, 3/4 ins. diam., set 29 ins. in the ground, for a reference monument, bears S. 3° E., 71.58 ft. dist., with cap mkd. RM T7N R27E COR 71.58 FT TO COR S13 1990, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.</p>
--------	---


Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>A steel fence post, with U.S. Forest Service signs attached, is set alongside the iron post.</p> <p>The cor. is located in a fence, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence S. 76°47' E., on line 8-9.</p>
7.20	<p>Point for cor. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T7N R27E LOT 3 COR 9</p>  <p>S13 1990</p> </div> <p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 7 ins. diam. bears N. 73 3/4° E., 45 lks. dist., mkd. COR S13 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 5 ins. diam. bears S. 18 1/2° E., 14 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence N. 49°55' E., on line 9-10.</p>
3.255	<p>Point for cor. 10.</p>

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
22 ins. in the ground, with brass cap mkd.



from which

A ponderosa pine, 8 ins. diam. bears N. 73° E., 17 lks.
dist., mkd. X BT.

A ponderosa pine, 11 ins. diam. bears S. 2° W., 24 lks.
dist., mkd. COR S13 BT.


Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic
case beneath the stainless steel post.

Set a steel fence post alongside the cor.

Thence N. 26°26' W., on line 10-11.

4.33 Point for cor. 11.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
22 ins. in the ground, with brass cap mkd.



from which

A ponderosa pine, 5 ins. diam. bears N. 43 1/4° E., 25 lks.
dist., mkd. X BT.

A ponderosa pine, 9 ins. diam. bears S. 65 1/4° E., 46 lks.
dist., mkd. COR S13 BT

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.

Set a steel fence post alongside the cor.

Thence N. 88°19' W., on line 11-12.

2.41 Point for cor. 12.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

T7N R27E
COR 12 | S13
LOT 3 |
1990

from which

A ponderosa pine, 5 ins. diam. bears N. 27° E., 64 lks. dist., mkd. X BT.

A ponderosa pine, 9 ins. diam. bears N. 85 1/2° E., 15 lks. dist., mkd. COR S13 BT.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.

Set a steel fence post alongside the cor.

Thence N. 0°04' W., on line 12-13.

15.19 Point for cor. 13.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

T7N R27E
COR 13 | S13
LOT 3 |
1990

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

from which

A ponderosa pine, 6 ins. diam. bears S. 81 1/2° E., 37 lks. dist., mkd. COR S13 BT.

A spruce, 7 ins. diam. bears S. 23 1/2° E., 51 lks. dist., mkd. COR S13 BT.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.

Set a steel fence post alongside the cor.

Thence N. 21°46' E., on line 13-14.

8.48 Point for cor. 14.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T7N R27E
COR 14 | S13
LOT 3 |
1990

from which

A ponderosa pine, 12 ins. diam. bears N. 64 3/4° E., 46 lks. dist., mkd. COR S13 BT.

A spruce, 5 ins. diam. bears S. 52 1/2° E., 93 lks. dist., mkd. X BT.


Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.

Set a steel fence post alongside the cor.

Thence N. 1°55' W., on line 14-1.

6.74 Point for Cor. 1, point of beginning.

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	Tract 39,
	<p>From the point for AP 1, Tract 39, sec. 1, at the intersection with the center lines of the right-of-way of Arizona Highway No. 373 and graded surface of Apache County Road No. 1122.</p> <p>Set a railroad spike, 7 ins. long, 5/8 in. square, flush with the paved surface.</p> <p>from which</p> <p style="padding-left: 40px;">An aluminum post, 36 ins. long, 3/4 ins. diam., set 33 ins. in the ground, for a reference monument, bears N. 15° E., 105.36 ft. dist., with cap mkd. RM T7N R27E 105.36 FT TO COR AP S1 1990, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.</p> <p style="padding-left: 40px;">An aluminum post, 36 ins. long, 3/4 ins. diam., set 33 ins. in the ground, for a reference monument, bears N. 30° W., 173.34 ft. dist., with cap mkd. RM T7N R27E 173.34 FT TO COR AP S1 1990, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case, 12 ins. beneath the railroad spike.</p> <p>N. 84°33' W., on line 1-2, within the right-of-way of Apache County Road No. 1122.</p>
10.14	<p>Point for AP 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T7N R27E S1</p>  <p>AP 2 TR 39 1990</p> </div>

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>from which</p> <p>An aluminum post, 24 ins. long, 3/4 ins. diam., set 16 ins. in the ground, for a reference monument, bears N. 57 3/4° E., 50 ft. dist., with cap mkd. RM T7N R27E S1 50 FT TO COR AP 1990, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.</p> <p>A ponderosa pine, 6 ins. diam. bears N. 8 1/2° W., 85 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. is located on the S. edge of the graded surface of Apache County Road No. 1122.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence N. 60°43' W., on line 2-3, within the right-of-way of Apache County Road No. 1122.</p> <p>9.90 Point for a witness point, at intersection with the line bet. secs. 1 and 2.</p> <p>Set an aluminum post, 36 ins. long, 3/4 ins. diam., set 10 ins. below the surface the graded road, with cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> WP T7N R27E S2 S1 1990 </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the aluminum post.</p> <p>From this cor. point, the 1/4 sec. cor. of secs. 1 and 2, bears S. 1°49' E., 6.675 chs. dist., hereinbefore described.</p> <p>18.59 Point for AP 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T7N R27E S2 / \ AP 3 TR 39 1990 </div>
--------	--

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

from which

A ponderosa pine, 10 ins. diam. bears N. 81 1/2° E.,
1.52 chs. dist., mkd. AP S2 BT.

An aluminum post, 36 ins. long, 3/4 ins. diam., set 28 ins.
in the ground, for a reference monument, bears
N. 12 3/4° W., 50 ft. dist., with cap mkd. RM T7N R27E 50
FT TO COR AP S2 1990, and an arrow pointing to the cor.
Set a steel fence post alongside the reference monument.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic
case beneath the stainless steel post.

Set a steel fence post alongside the cor.

The cor. is located near the N. edge of Apache County Road
No. 1122.

Thence S. 58°57' W., on line 3-4, within the right-of-way of
Apache County Road No. 1122.

4.86 Point for AP 4.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
12 ins. below the surface of the graded road, with brass cap mkd.

T7N R27E

S2



AP 4

TR 39

1990

from which

An aluminum post, 36 ins. long, 3/4 ins. diam., set 32 ins.
in the ground, for a reference monument, bears
N. 30 1/4° E., 100 ft. dist., with cap mkd. RM T7N R27E
100 FT TO COR AP S2 1990, and an arrow pointing to the
cor. Set a steel fence post alongside the reference
monument.

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

An aluminum post, 36 ins. long, 3/4 ins. diam., set 33 ins. in the ground, for a reference monument, bears N. 21 1/2° W., 100 ft. dist., with cap mkd. RM T7N R27E 100 FT TO COR AP S2 1990, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.


Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.

The cor. is located on the center line of the graded surface of Apache County Road No. 1122.

Thence N. 49°08' W, on line 4-5, leaving Apache County Road No. 1122.

8.805 Point for AP 5.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.



from which


An aluminum post, 36 ins. long, 3/4 ins. diam., set 32 ins. in the ground, for a reference monument, bears N. 5° E., 50 ft. dist., with cap mkd. RM T7N R27E 50 FT TO COR AP S2 1990, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.

A ponderosa pine, 7 ins. diam. bears S. 75 3/4° E., 1.48 chs. dist., mkd. AP S2 BT.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.

Set a steel fence post alongside the cor.

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Thence N. 56°43' W., on line 5-6.</p>
2.22	<p>AP 6, identical with the center N-S-NE 1/256 sec. cor. of sec. 2, hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence S. 1°44' E., on line 6-7, identical with a portion of the N. and S. center line of the NE 1/4 of sec. 2.</p>
15.14	<p>AP 7, identical with the center E 1/16 sec. cor. of sec. 2, hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence S. 89°15' E., on line 7-8, identical with a portion of the E and W center line of sec. 2.</p>
20.015	<p>AP 8, identical with the 1/4 sec. cor. of secs. 1 and 2, hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence N. 89°54' E., on line 8-9, identical with a portion of the E. and W. center line of sec. 1.</p>
19.80	<p>AP 9, identical with the center W 1/16 sec. cor. of sec. 1, hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence N. 57°08' W., on line 9-1.</p>
1.53	<p>AP 1, point of beginning.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">Tract 40,</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the point for AP 1, Tract 40, sec. 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>T7NR27E S12</p>  <p>AP 1 TR 40 1990</p> </div>

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

from which

An aluminum post, 36 ins. long, 3/4 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 27 1/4° E., 110.95 ft. dist., with cap mkd. RM T7N R27E 110.95 FT TO COR S12 AP 1990, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.

A ponderosa pine, 9 ins. diam. bears N. 54 1/4° W., 1.57 chs. dist., mkd. AP S12 BT.


Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.

Set a steel fence post alongside the cor.

S. 74°40' W., on line 1-2, within the right-of-way of Apache County Road No. 1126.

4.01 Point for AP 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.




from which

An aluminum post, 36 ins. long, 3/4 ins. diam., set 29 ins. in the ground, for a reference monument, bears N. 15 1/4° E., 106.81 ft. dist., with cap mkd. RM T7N R27E 106.81 FT TO COR S12 AP 1990, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.


A ponderosa pine, 8 ins. diam. bears N. 79 3/4° W., 1.75 chs. dist., mkd. AP S12 BT.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Set a steel fence post alongside the cor.</p> <p>The cor. is located on the S. edge of Apache County Road No. 1126.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence S. 45°04' W., on line 2-3, within the right-of-way of Apache County Road No. 1126.</p> <p>2.50 Intersect the N. and S. center line of sec. 12, at a point from which the center N 1/16 sec. cor. of sec. 12, bears S. 0°20' W., 6.29 chs. dist., hereinbefore described.</p> <p>7.855 Point for AP 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T7N R27E S12</p>  <p>AP 3 TR 40 1990</p> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam. bears S. 80 3/4° W., 2.13 chs. dist., mkd. AP S12 BT.</p> <p style="padding-left: 40px;">An aluminum post, 36 ins. long, 3/4 ins. diam., set 28 ins. in the ground, for a reference monument, bears N. 7 1/4° W., 106.62 ft. dist., with cap mkd. RM T7N R27E 106.62 FT TO COR S12 AP 1990, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>The cor. is located on the S. edge of Apache County Road No. 1126.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence S. 57°54' W., on line 3-4, within the right-of-way of Apache County Road No. 1126.</p>
--------	---

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
4.88	Intersect the E. and W. center line of the NW 1/4 of sec. 12, at a point from which the center N 1/16 sec. cor. of sec. 12, bears N. 89°26' E., 7.89 chs. dist., hereinbefore described.
13.835	Point for AP 4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T7N R27E S12  AP 4 TR 40 1990</p>
	from which
	<p style="text-align: center;">An aluminum post, 36 ins. long, 3/4 ins. diam., set 31 ins. in the ground, for a reference monument, bears N. 32° E., 180.61 ft. dist., with cap mkd. RM T7N R27E 180.61 FT TO COR S12 AP 1990, and an arrow pointing to the cor. Set a steel fence post alongside the reference monument.</p>
	<p style="text-align: center;">A ponderosa pine, 11 ins. diam. bears N. 40 1/4° W., 2.84 chs. dist., mkd. AP S12 BT.</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
	The cor. is located near the S. edge of Apache County Road No. 1126.
	<p style="text-align: center;">_____</p> <p>Thence N. 69°18' W., on line 4-5, on the center line of the graded surface of Apache County Road No. 1126.</p>
3.90	Point for AP 5, identical with cor. 7, Lot 6, sec. 12, at intersection with the center line of the right-of-way of Arizona Highway No. 373, hereinbefore described.
	<p style="text-align: center;">_____</p> <p>Thence on line 5-6, identical with line 7-6, Lot 6, sec. 12, on the center line of Arizona Highway No. 373, along the arc of a 6° circular curve to the right having a radius of 954.93 ft., the chord of said arc bears S. 29°08' W., 5.26 chs. dist.</p>


Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
3.469	Intersect the N. and S. center line of the NW 1/4 of sec. 12, at a point from which the NW 1/16 sec. cor. of sec. 12 bears N. 0°55' W. 4.945 chs. dist., hereinbefore described.
5.289	AP 6, identical with Cor. 6, Lot 6, sec. 12, hereinbefore described.
7.81	<p>Thence S. 39°38' W., on line 6-7, identical with line 5-6, Lot 6, sec. 12, on the center line of the right-of-way of Arizona Highway No. 373.</p> <p>AP 7, identical with Cor. 5, Lot 6, sec. 12, hereinbefore described.</p> <p>Thence on line 7-8, identical with a portion of line 4-5, Lot 6, sec. 12, on the center line of Arizona Highway No. 373, along the arc of a 5°40' circular curve to the right having a radius of 1010.98 ft., the chord of said arc bears S. 46°41' W., 3.09 chs. dist.</p>
3.095	<p>Point for AP 8.</p> <p>Set a railroad spike, 4 ins. long, 1/2 in. square, flush with paved surface.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the railroad spike.</p> <p>From this cor. point, the northerly right-of-way station 91+62.50, bears S. 72°44' W., 7.67 chs. dist. hereinbefore described.</p>
5.43	<p>Thence S. 47°53' E., on line 8-9, leaving the right-of-way of Arizona Highway No. 373.</p> <p>Intersect the E. and W. center line of sec. 12, at a point from which the Center-W 1/16 sec. cor., bears N. 89°42' W. 4.84 chs. dist., hereinbefore described.</p>
12.43	Point for AP 9.

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
23 ins. in the ground, with brass cap mkd.



from which

A fir, 7 ins. diam. bears N. 76 3/4° E., 1.10 chs. dist.,
mkd. AP S12 BT.

A ponderosa pine, 11 ins. diam. bears S. 21 1/4° E., 20 lks.
dist., mkd. AP S12 BT.


Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic
case beneath the stainless steel post.

Set a steel fence post alongside the cor.

Thence N. 53°29' E., on line 9-10.

4.27 Point for AP 10.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
23 ins. in the ground, with brass cap mkd.



from which

A fir, 6 ins. diam. bears S. 85 1/4° E., 53 lks. dist., mkd.
X BT.

A ponderosa pine, 10 ins. diam. bears S. 33 1/4° E., 68 lks.
dist., mkd. AP S12 BT.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic
case beneath the stainless steel post.

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence N. 87°16' E., on line 10-11.</p>
15.04	<p>Point for AP 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 6 ins. diam. bears S. 86 1/4° E., 46 lks. dist., mkd. X BT.</p> <p style="margin-left: 40px;">A fir, 7 ins. diam. bears S. 9 1/2° W., 11 lks. dist., mkd. AP S12 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence N. 59°08.5' W., on line 11-12.</p>
2.99	<p>Intersect the E. and W. center line of sec. 12, at a point from which the center 1/4 sec. cor. of sec. 12, bears N. 89°45' E., 3.66 chs. dist., hereinbefore described.</p>
9.69	<p>Point for AP 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div>

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

from which

A ponderosa pine, 7 ins. diam. bears N. $35\frac{3}{4}^{\circ}$ E., 62 lks. dist., mkd. AP S12 BT.

An aspen, 4 ins. diam. bears S. $74\frac{1}{2}^{\circ}$ E., 56 lks. dist., bark scribed X BT.


Deposit a magnet in a $1 \times 1 \times 2\frac{5}{8}$ ins. white colored plastic case beneath the stainless steel post.

Set a steel fence post alongside the cor.

Thence N. $29^{\circ}12'$ E., on line 12-13.

8.99 Point for AP 13.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.



from which

A fir, 11 ins. diam. bears S. $59\frac{1}{4}^{\circ}$ E., 75 lks. dist., mkd. AP S12 BT.

A ponderosa pine, 5 ins. diam. bears S. 9° E., 37 lks. dist., mkd. X BT.

Deposit a magnet in a $1 \times 1 \times 2\frac{5}{8}$ ins. white colored plastic case beneath the stainless steel post.

Set a steel fence post alongside the cor.

Thence S. $75^{\circ}32'$ E., on line 13-14.

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>5.265 Intersect the N. and S. center line of sec. 12, at a point from which the center N 1/16 sec. cor. of sec. 12, bears N. 0°24' E., 9.76 chs. dist.</p> <p>6.19 Point for AP 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 7 ins. diam. bears S. 24 3/4° E., 1.20 chs. dist., mkd. AP S12 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 11 ins. diam., Bears S. 69° W., 1.35 chs. dist., mkd. AP S12 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>Thence N. 22°21' E., on line 14-15.</p> <p>5.93 Point for AP 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 10 ins. diam. bears N. 68 1/2° E., 1.15 chs. dist., mkd. AP S12 BT.</p> <p style="margin-left: 40px;">A fir, 9 ins. diam. bears S. 20° E., 89 lks. dist., mkd. AP S12 BT.</p>
--------	--

Metes-and-Bounds Surveys,
T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>Thence N. 34°16' W., on line 15-16.</p> <p>5.46 AP 16, identical with the center N 1/16 sec. cor. of sec. 12, hereinbefore described.</p> <hr/> <p>Thence N. 61°40' E., on line 16-17.</p> <p>7.08 Point for AP 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T7N R27E TR 40 / S13 AP 17 1990</p> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam. bears N. 11 1/4° E., 35 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam. bears S. 28 3/4° E., 18 lks. dist., mkd. AP S12 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>Thence N. 5°32' W., on line 17-1.</p> <p>5.78 AP 1, Tract 40, point of beginning.</p> <hr/>
--------	--

T. 7 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The areas surveyed in T. 7 N., R. 27 E., are located near the town of Greer, Arizona, and approximately 13 air miles SW of Springerville, Arizona. The terrain varies from nearly level, swampy river plane, to mountainous. The elevation ranges from about 8,200 to 8,600 ft. above sea level. The land drains into the Little Colorado River, which courses northerly through the project area. The soil is rocky in the higher elevations, and marshy along the river plane. The vegetation varies from dense ponderosa pine forest to dense riparian growth along the river, with open, grassy meadows interspersed.

Access is obtained by way of Arizona Highways No. 260 and No. 373, with several graded U.S. Forest Service roads, maintained by Apache County, branching from Highway No. 373.

A National Recreation Area is adjacent to the project area to the east. The community of Greer contains several hundred year around residents, increasing to several thousand seasonal visitors. Many summer residences, located on both public and private land, are scattered throughout the area. Several shops, resorts, and skiing areas are well established.

The mean magnetic declination, as taken from "GREER, ARIZ." quadrangle map, published in 1981 by the U.S. Geological Survey and modified for U.S.D.A. Forest Service use, is 12 1/2° E.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Cheryl A. Baier	Surveying Technician
Gordon R. Bubel	Surveying Technician

