

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE

DEPENDENT RESURVEY OF PORTIONS OF THE SOUTH AND WEST BOUNDARIES,

A PORTION OF THE SUBDIVISIONAL LINES,

AND CERTAIN TRACTS,

AND THE SUBDIVISION OF CERTAIN SECTIONS

AND

A METES-AND BOUNDS SURVEY IN

TOWNSHIP 32 NORTH, RANGE 11 EAST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

William F. Olver and Daniel N. Patterson, Cadastral Surveyors

Under special instructions dated March 16, 1988 approved March 16, 1988

 , which provided for the surveys included under Group Number
700 and assignment instructions dated March 17, 1988 and August 29, 1990

Survey commenced May 16, 1988

Survey completed August 30, 1990

INDEX DIAGRAM

TOWNSHIP 32 NORTH, RANGE 11 EAST,

| | | | | | |
|----------------|----------------|-------------|-------------|----------|----|
| 6 | 5 | 4 | 3 | 2 | 1 |
| 7 | 8 39 53 | 9 38 | 10 | 11 | 12 |
| 18 51 50 | 17 37 50 | 16 27 36 | 15 27 | 14 | 13 |
| 15 19 49 48 | 20 35 | 21 25 34 | 22 19 25 | 23 19 | 24 |
| 14 30 44 43 | 29 33 42 | 28 23 31 | 27 18 22 | 26 17 | 25 |
| 13 31 39 10 | 32 28 8 | 33 20 6 | 34 16 4 | 35 | 36 |

- | | | |
|--------------------|-----------------------------|-----------------------------|
| Tract 37-pp. 54-58 | Sub. of Sec. 17-pp. 76-78 | M&B Surv. S. 28-pp. 108-110 |
| Tract 38-pp. 58-62 | Sub. of Sec. 19-pp. 78-80 | M&B Surv. S. 29-pp. 110 |
| Tract 39-pp. 62-65 | Sub. of Sec. 20-pp. 80-82 | M&B Surv. S. 32-pp. 110-115 |
| Tract 40-pp. 66-69 | Sub. of Sec. 21-pp. 82-83 | M&B Surv. S. 31-pp. 115-116 |
| Tract 41-pp. 69-72 | Sub. of Sec. 28-pp. 83-92 | |
| Tract 42-pp. 72-73 | Sub. of Sec. 30-pp. 92-93 | |
| Tract 43-pp. 74-75 | Sub. of Sec. 31-pp. 94-101 | |
| Tract 53-pp. 75-76 | Sub. of Sec. 32-pp. 101-107 | |

BOOK 5308

T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of the dependent resurvey of portions of the south and west boundaries, a portion of the subdivisional lines, and certain tracts, the subdivision of certain sections and a metes-and-bounds survey in Township 32 North, Range 11 East, Gila and Salt River Meridian, Arizona.

The history of the related previous surveys is as follows:

| <u>Surveys of Tp.</u> | <u>By Whom</u> | <u>Date</u> |
|--|----------------------|-------------|
| Unapproved survey of all tracts. | Charles Von Erxleben | 1899 |
| Resurvey of all tracts. | Sidney E. Blout | 1907-1908 |
| Survey of the S. and W. bdys. and subdivisional lines. | Philip Contzen | 1905 |
| Retracement and resurvey of portions of S. bdy. and subdivisional lines. | Sidney E. Blout | 1907-1908 |
| Res. portion of W. bdy., and portion of subdivisional lines, and survey of subdivision of sec. 29. | Leonard W. Murphy | 1962 |

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated March 16, 1988, for Group No. 700, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of lines were determined by hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured using a Nikon NTD-4 electronic instrument.

BOOK 5308

T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS

The geographic position of the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., as determined from a tie made to U.S. Coast and Geodetic Survey triangulation station "TUBA CITY 1951", is as follows:

NAD 27: Latitude: 36°06'14.30" N. Longitude: 111°11'37.04" W.

The mean magnetic declination as shown on TUBA CITY, ARIZ. quadrangle map, published by U.S. Geological Survey in 1969 is 14 1/2° E.

Dependent Resurvey of a Portion of the S. Bdy.,
T. 32 N., R. 11 E., Gila and Salt River Meridian,

Restoring the resurvey executed by
Sidney E. Blout, in 1907

Beginning at the cor. of secs. 2, 3, 34 and 35, Tps. 31 and 32 N., R. 11 E., monumented with a blue limestone, 17 x 6 x 5 ins., loosely set, projecting 15 ins. above the ground, mkd. 32 N on N. face, 2 notches on NE edge, 11 E on E. face, 31 N on S face, 4 notches on SW edge, 11 E on W. face and X on top.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

| | |
|------|------|
| T32N | R11E |
| S34 | S35 |
| | |
| S 3 | S 2 |
| T31N | |
| 1988 | |

Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Bury the stone alongside the cor. and raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.

Dependent Resurvey of a Portion of the S. Bdy.,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>From this cor. point, second order United States Coast and Geodetic Survey triangulation station, "Tuba City 1951", bears N. 39°08' W., (mean bearing), 208.86 chs. dist., monumented with a brass disk, 3 1/2 ins. diam., firmly set, cemented in bedrock, with brass disk mkd. TUBA CITY 1951 and a triangle.</p> <p>N. 89°30' W., bet. secs. 3 and 34.</p> <p>Over rolling and broken land.</p> |
| 33.19 | Barbed wire fence, 4 strand, bears SE and NW. |
| 35.50 | Center line of State Highway 264, asphalt surfaced, 39 lks. wide, bears SE and NW. |
| 38.16 | Barbed wire fence, 4 strand, bears SE and NW. |
| 39.76 | <p>Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R11E S34 1/4 — S 3 T31N 1988</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in a cultivated field.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°53' W., beginning new measurement.</p> <p>Over rolling land.</p> |
| 5.70 | Graded road, 23 lks. wide, bears NE and SW. |
| 27.80 | Trail road, bears NE and SW. |
| 27.99 | Barbed wire fence, 4 strand, bears NE and SW. |

Dependent Resurvey of a Portion of the S. Bdy.,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | | | |
|--------|--|------|------|-----|-----|-----|-----|------|--|------|--|
| 29.07 | <p>Point for a closing cor., with line 1-2, Tract 52, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Not remonumented.</p> <hr/> <p>S. 89°53' W., on a blank line, beginning new measurement</p> | | | | | | | | | | |
| 10.91 | <p>Point for the cor. of secs. 3, 4, 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a steel fence post, with brass cap mkd.</p> | | | | | | | | | | |
| | <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>T32N</td> <td>R11E</td> </tr> <tr> <td>S33</td> <td>S34</td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> <tr> <td colspan="2" style="text-align: center;">T31N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1988</td> </tr> </table> | T32N | R11E | S33 | S34 | S 4 | S 3 | T31N | | 1988 | |
| T32N | R11E | | | | | | | | | | |
| S33 | S34 | | | | | | | | | | |
| S 4 | S 3 | | | | | | | | | | |
| T31N | | | | | | | | | | | |
| 1988 | | | | | | | | | | | |
| | <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 5°04' E., 112.53 ft. dist., with brass cap mkd. T31N R11E S3 RM 112.53 FT TO COR 1988, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> | | | | | | | | | | |
| | <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 85°17' E., 143.43 ft. dist., with brass cap mkd. T32N R11E S34 RM 143.43 FT TO COR 1988, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> | | | | | | | | | | |
| | <p>Cor. is located in Moenkopi Wash, 151 lks. wide, 15 ft. deep, drains NW.</p> <hr/> | | | | | | | | | | |
| | <p>N 89°55' W., on a blank line, bet. secs. 4 and 33.</p> | | | | | | | | | | |

Dependent Resurvey of a Portion of the S. Bdy.,
T. 32 N., R. 11 E., Gila and Salt River Meridian,

| CHAINS | | | | | | | | | | | | | |
|----------------------------|---|-----------|--|-----|-----|----------------------------|--|-----|-----|------|--|------|--|
| 40.24 | <p>Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 34 ins. below the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R11E S33 1/4 — S 4 T31N 1988</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°50' W., on a blank line, beginning new measurement.</p> | | | | | | | | | | | | |
| 40.22 | <p>True point for the cor. of secs. 4, 5, 32 and 33, at proportionate dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a steel fence post, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1" style="margin: auto;"> <tr> <td colspan="2">T32N R11E</td> </tr> <tr> <td>S32</td> <td>S33</td> </tr> <tr> <td colspan="2"><hr style="width: 100%;"/></td> </tr> <tr> <td>S 5</td> <td>S 4</td> </tr> <tr> <td colspan="2">T31N</td> </tr> <tr> <td colspan="2">1988</td> </tr> </table> </div> | T32N R11E | | S32 | S33 | <hr style="width: 100%;"/> | | S 5 | S 4 | T31N | | 1988 | |
| T32N R11E | | | | | | | | | | | | | |
| S32 | S33 | | | | | | | | | | | | |
| <hr style="width: 100%;"/> | | | | | | | | | | | | | |
| S 5 | S 4 | | | | | | | | | | | | |
| T31N | | | | | | | | | | | | | |
| 1988 | | | | | | | | | | | | | |

Dependent Resurvey of a Portion of the S. Bdy.,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| | |
|---------------|--|
| <p>CHAINS</p> | <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, for a reference monument, bears S. 72°32' W., 100.39 ft. dist., with brass cap mkd. T31N R11E S5 RM 100.39 FT TO COR 1988, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post and set a steel fence post to the N.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, for a reference monument, bears N. 17°38' W., 65.70 ft. dist., with brass cap mkd. T32N R11E S32 RM 65.70 FT TO COR 1988, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post and set a steel fence post to the N.</p> <p>Cor. is located in Moenkopi Wash, 76 lks. wide, 15 ft. deep, drains West.</p> <hr/> <p>N. 89°50' W., on a blank line, bet. secs. 5 and 32.</p> <p>1.00 Point for the witness cor. for secs. 4, 5, 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor. This cor. now functions as an angle point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> AP T32N R11E S32 <hr style="width: 20%; margin: auto;"/> S 5 T31N 1989 </p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 5 lks. SW of left bank of Moenkopi Wash, drains NW.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89°47' W., on a blank line, beginning new measurement.</p> |
|---------------|--|

Dependent Resurvey of a Portion of the S. Bdy.,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 18.99 | <p>Point for the E 1/16 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R11E S32 E 1/16 — S 5 T31N 1988</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| 38.98 | <p>Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 14 ins. long, 1 in. diam., 12 ins. in a drill hole, cemented in place, in sandstone bedrock, with magnetized aluminum cap mkd.</p> <p style="text-align: center;">T32N R11E S32 1/4 — S 5 T31N 1988</p> <p>Deposit a magnet, 1 in. long, 7/8 in. diam., beneath the aluminum post.</p> |
| | <p>From this cor. point, the cor. of barbed wire fences, 5 strand, located N. of the base of a mesa, 35 ft. high, bears South, 4 lks. dist., extending N., NE and SW.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°55' W., on a blank line, beginning new measurement.</p> |
| 18.47 | <p>Point for a closing cor. at the intersection with line 3-4, Tract 41; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R11E S32 CC — TR 41 S 5 T31N 1989</p> |

Dependent Resurvey of a Portion of the S. Bdy.,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | | | |
|--------|--|------|------|-----|-----|-----|-----|------|--|------|--|
| | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in a cultivated field.</p> <hr/> <p>N. 89°55' W., between secs. 5 and 32, beginning new measurement</p> | | | | | | | | | | |
| 10.00 | Barbed wire fence, 4 strand, bears SE and NW. | | | | | | | | | | |
| 12.93 | Trail road, bears NE and SW. | | | | | | | | | | |
| 13.93 | Barbed wire fence, 4 strand, bears SE and NW. | | | | | | | | | | |
| 21.43 | <p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T32N</td> <td>R11E</td> </tr> <tr> <td>S31</td> <td>S32</td> </tr> <tr> <td>S 6</td> <td>S 5</td> </tr> <tr> <td colspan="2">T31N</td> </tr> <tr> <td colspan="2">1988</td> </tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post N. of the cor.</p> <hr/> <p>N. 89°50' W., bet. secs. 6 and 31.</p> <p>Over level land through cultivated fields.</p> | T32N | R11E | S31 | S32 | S 6 | S 5 | T31N | | 1988 | |
| T32N | R11E | | | | | | | | | | |
| S31 | S32 | | | | | | | | | | |
| S 6 | S 5 | | | | | | | | | | |
| T31N | | | | | | | | | | | |
| 1988 | | | | | | | | | | | |
| 6.70 | S. bank of Moenkopi Wash, bears NE and SW. | | | | | | | | | | |
| 8.60 | Center of Moenkopi Wash, 106 lks. wide, 30 ft. deep, drains SW. | | | | | | | | | | |
| 10.40 | N. bank of Moenkopi Wash, bears NE and SW. | | | | | | | | | | |
| 14.15 | Concrete irrigation canal, 8 lks. wide, 3 ft. deep., drains SW. | | | | | | | | | | |
| 14.45 | Trail road, bears NE and SW. | | | | | | | | | | |
| 19.99 | <p>Point for the E 1/16 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> | | | | | | | | | | |

Dependent Resurvey of a Portion of the S. Bdy.,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p style="text-align: center;">T32N R11E S31 E 1/16 — S 6 T31N 1988</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post N. of the cor.</p> |
| 30.26 | Barbed wire fence, 6 strand, bears SE and NW. |
| 39.98 | <p>Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R11E S31 1/4 — S 6 T31N 1988</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post N. of the cor.</p> <p>Cor. is located in a cultivated field.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°51' W., beginning new measurement.</p> <p>Over level land.</p> |
| 5.13 | Barbed wire fence, 6 strand, bears SE and NW. |
| 5.22 | Trail road, bears SE and NW. |
| 6.21 | Barbed wire fence, 5 strand, bears SE and NW. |
| 20.01 | <p>Point for the W 1/16 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 3 ins. below the surface of the ground, with brass cap mkd.</p> |

Dependent Resurvey of a Portion of the S. Bdy.,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| | |
|--------|--|
| CHAINS | <p style="text-align: center;">T32N R11E S31 W 1/16 — S 6 T31N 1988</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post 10 1/2 lks. N. of the cor.</p> <p>Corner is located in a trail road, bears E. and W., and 23 lks. S. of a concrete irrigation canal, 8 lks. wide, 3 ft. deep, drains SW.</p> <p>38.46 Point for the cor. of Tps. 31 and 32 N., Rs. 10 and 11 E., at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R10E R11E S36 S31 — — S 1 S 6 T31N 1988</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post 3 lks. N. of the cor.</p> <p>Cor. is located in a cultivated field.</p> <p>From this cor. point, the cor. of secs. 1, 6, 7 and 12, T. 31 N., Rs. 10 and 11 E., bears S. 0°24' W., 79.94 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap mkd. as described in the field note record of the dependent resurvey of a portion of the east boundary, T. 31 N., R. 10 E., executed concurrently under this same group.</p> <p>From this same cor. point, the 1/4 sec. cor. of secs. 3 and 34, Tps. 31 and 32 N., R. 10 E., bears N. 89°58' W., 199.90 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap mkd. as described in the field note record of the dependent resurvey of a portion of the north boundary, T. 31 N., R. 10 E., executed concurrently under this same group.</p> |
|--------|--|

Dependent Resurvey of a Portion of the W. Bdy.,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>Restoring the survey executed by Philip Contzen, in 1905</p> <hr/> <p>From the cor. of Tps. 31 and 32 N., Rs. 10 and 11 E., hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 31 and 36, on the W. bdy. of the Tp.</p> <p>Over level to broken land.</p> |
| 6.70 | Power line, bears E. and W. |
| 6.83 | S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway. |
| 7.54 | Center line of U.S. Highway 160, asphalt surfaced, 54 lks. wide, bears ENE and WSW. |
| 8.35 | N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway. |
| 19.985 | Point for the S 1/16 sec. cor. of secs. 31 and 36. |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R10E R11E S 1/16 S36 S31 1988</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| 22.00 | Top of earthen dike, 15 ft. high, bears E. and W. |
| 39.97 | Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor. |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N 1/4 R10E R11E S36 S31 1988</p> |

Dependent Resurvey of a Portion of the W. Bdy.,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | | | |
|--------|---|------|--|------|------|-----|-----|-----|-----|------|--|
| | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor.</p> | | | | | | | | | | |
| 45.40 | S. rim of mesa, 50 ft. high, bears SE and NW. | | | | | | | | | | |
| 76.50 | Graded road, 45 lks. wide, bears E. and W. | | | | | | | | | | |
| 77.40 | Power line, bears NE and SW. | | | | | | | | | | |
| 79.94 | <p>The cor. of secs. 25, 30, 31 and 36, monumented with a blue limestone, 14 x 8 x 6 ins., laying loose on the surface of the ground, mkd. N on N. face, 11E on E. face, 1 notch on SE edge, R10E on W. face and 2 notches on NW edge. This is accepted as the best available evidence of the original cor. position. (Record: 18 x 6 x 5 ins.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T32N</td> </tr> <tr> <td>R10E</td> <td>R11E</td> </tr> <tr> <td>S25</td> <td>S30</td> </tr> <tr> <td>S36</td> <td>S31</td> </tr> <tr> <td colspan="2">1988</td> </tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Bury the stone alongside the cor.</p> <hr/> <p>N. 0°06' E., bet. secs. 25 and 30.</p> <p>Over rolling land.</p> | T32N | | R10E | R11E | S25 | S30 | S36 | S31 | 1988 | |
| T32N | | | | | | | | | | | |
| R10E | R11E | | | | | | | | | | |
| S25 | S30 | | | | | | | | | | |
| S36 | S31 | | | | | | | | | | |
| 1988 | | | | | | | | | | | |
| 1.30 | Trail road, bears NE, in curve to the left. | | | | | | | | | | |
| 9.10 | S. rim of mesa, 40 ft. high, bears E. and W. | | | | | | | | | | |
| 14.10 | N. rim of mesa, 40 ft. high, bears E. and W. | | | | | | | | | | |

Dependent Resurvey of a Portion of the W. Bdy.,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|---|---|
| 39.84 | <p>The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, flush with the surface of the ground, with brass cap mkd. as described in the official record of the 1962 resurvey of a portion of the W. bdy. of T. 32 N., R. 11 E.</p> |
| <hr/> <p>Restoring the resurvey executed by Leonard W. Murphy, in 1962</p> <hr/> | |
| <p>From the 1/4 sec. cor. of secs. 25 and 30.</p> | |
| <p>N. 0°04' E., bet. secs. 25 and 30.</p> | |
| <p>Over rolling sand dunes.</p> | |
| 5.80 | <p>Graded road, 45 lks. wide, bears NE and SW.</p> |
| 30.90 | <p>Trail road, bears SE and NW.</p> |
| 40.05 | <p>The cor. of secs. 19, 24, 25 and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the official record of the 1962 resurvey of a portion of the W. bdy. of T. 32 N., R. 11 E.</p> |
| <hr/> <p>N. 0°04' E., bet. secs. 19 and 24.</p> | |
| <p>Over rolling sand dunes.</p> | |
| 40.06 | <p>Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> |
| <p>T32N 1/4 R10E R11E S24 S19 1988</p> | |
| <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> | |
| 62.20 | <p>Enter inhabited area.</p> |

Dependent Resurvey of a Portion of the W. Bdy.,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| | |
|--------|--|
| CHAINS | |
| 66.10 | Leave inhabited area. |
| 70.70 | Trail road, bears E. and W. |
| 80.12 | <p>The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the official record of the 1962 resurvey of a portion of the W. bdy. of T. 32 N., R. 11 E.</p> <p>Add the marks 1988 to the brass cap.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, W. of the cor.</p> |
| | <hr/> <p>Dependent Resurvey, a Portion of the Subdivisional Lines, T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona</p> <hr/> |
| | <p>Restoring the survey executed by Philip Contzen, in 1905</p> <hr/> |
| | <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°05' E., bet. secs. 34 and 35.</p> <p>Over rolling land.</p> |
| 15.15 | <p>Trail road, bears NE and SW.</p> <p>Thence descend 60 ft. to level land.</p> |
| 39.97 | <p>Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px;"> <p>T32N R11E 1/4 S34 S35 1988</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| 42.50 | Trail road, bears NE and SW. |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | | | | | | | | | | | |
|--------|--|------|------|-----|-----|-----|-----|------|--|------|------|--|-----|-----|---|--|-----|------|--|
| 79.94 | <p>Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T32N</td> <td>R11E</td> </tr> <tr> <td>S27</td> <td>S26</td> </tr> <tr> <td>S34</td> <td>S35</td> </tr> <tr> <td colspan="2">1988</td> </tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in the center of a trail road, bears E. and W.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 35, monumented with a limestone, 15 x 6 x 5 ins., mkd. 1/4 26 on one face, S35 on opposite face, and X on top, laying loose on sandstone bedrock. This is accepted as the best available evidence of the original cor. position. (Record: 18 x 7 x 5 ins.)</p> <p>At the cor. point</p> <p>Set an aluminum post, 12 ins. long, 1 in. diam., 10 ins. in a drill hole, cemented in place, in sandstone bedrock, with magnetized aluminum cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T32N</td> <td>R11E</td> </tr> <tr> <td></td> <td>S26</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S35</td> </tr> <tr> <td colspan="2">1988</td> </tr> </table> </div> <p>Deposit a magnet, 1 in. long, 7/8 in. diam., beneath the aluminum post.</p> <p>Deposit the stone in a mound of stone, 3 ft. base, 1 ft. high, N. of the cor.</p> <p>S. 89°50' W., bet. secs. 26 and 35.</p> <p>Over sandstone outcrops.</p> | T32N | R11E | S27 | S26 | S34 | S35 | 1988 | | T32N | R11E | | S26 | 1/4 | — | | S35 | 1988 | |
| T32N | R11E | | | | | | | | | | | | | | | | | | |
| S27 | S26 | | | | | | | | | | | | | | | | | | |
| S34 | S35 | | | | | | | | | | | | | | | | | | |
| 1988 | | | | | | | | | | | | | | | | | | | |
| T32N | R11E | | | | | | | | | | | | | | | | | | |
| | S26 | | | | | | | | | | | | | | | | | | |
| 1/4 | — | | | | | | | | | | | | | | | | | | |
| | S35 | | | | | | | | | | | | | | | | | | |
| 1988 | | | | | | | | | | | | | | | | | | | |
| 15.80 | Trail road, bears NE and SW. | | | | | | | | | | | | | | | | | | |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 27.75 | Trail road, bears NE and SW. |
| 39.985 | The cor. of secs. 26, 27, 34 and 35. |
| | North, bet. secs. 26 and 27. |
| | Over gently rolling land. |
| 39.97 | Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate dist.; there is no remaining evidence of the original cor. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T32N R11E 1/4 S27 S26 1988</p> |
| | Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. |
| 53.70 | Power line, bears NE and SW. |
| 54.18 | S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway. |
| 54.65 | Center line of U.S. Highway 160, asphalt surfaced, 55 lks. wide, bears ENE and WSW. |
| 58.00 | N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway. |
| 79.94 | Point for the cor. of secs. 22, 23, 26 and 27, at proportionate dist.; there is no remaining evidence of the original cor. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T32N R11E S22 S23 S27 S26 1988</p> |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| | <p>From the 1/4 sec. cor. of secs. 23 and 26, monumented with a limestone, 17 x 9 x 4 ins., mkd. 1/4 23 on one face, 26 on opposite face, and X on another face, laying loose on the surface of the ground. This is accepted as the best available evidence of the original cor. position. (Record: 18 x 6 x 5 ins.)</p> |
| | <p>At the cor. point</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T32N R11E S23 1/4 — S26 1988</p> |
| | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| | <p>Bury the stone alongside the cor.</p> |
| | <p>S. 89°40' W., bet. secs. 23 and 26.</p> |
| | <p>Over gently rolling land.</p> |
| 21.00 | <p>Enter inhabited area.</p> |
| 25.60 | <p>Leave inhabited area.</p> |
| 40.01 | <p>The cor. of secs. 22, 23, 26 and 27.</p> |
| | <p>N. 0°01' W., bet. secs. 22 and 23.</p> |
| | <p>Over rolling sand dunes.</p> |
| 39.97 | <p>Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| | |
|--------|--|
| CHAINS | <p style="text-align: center;">T32N R11E 1/4 S22 S23 1988</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>79.94 The cor. of secs. 14, 15, 22, and 23, monumented with a sandstone, 18 x 6 x 6 ins., firmly set, projecting 14 ins. above the ground, mkd. 32N on N. face, 2 notches on NE edge, 11E on E. face, 3 notches on SE edge, and X on top. (Record: Limestone.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R11E S15 S14 ----- S22 S23 1988</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Bury the stone alongside the cor.</p> <hr/> <p style="text-align: center;">Restoring the resurvey executed by Sidney E. Blout, in 1908</p> <hr/> <p>From the 1/4 sec. cor. of secs. 33 and 34, monumented with a sandstone, 18 x 7 x 7 ins., firmly set, projecting 8 ins. above the ground, mkd. 1/4 33 on E. face, S34 on W. face, and X on top. (Record: Limestone, 18 x 6 x 5 ins.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R11E 1/4 S33 S34 1988</p> |
|--------|--|

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | |
|--------|--|------|------|-----|-----|-----|-----|------|--|
| | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Bury the stone alongside the cor.</p> <p>Cor. is located at base of ridge, 60 ft. high, bears E. and W. S. 0°15' E., bet. secs. 33 and 34.</p> <p>Over rolling land.</p> | | | | | | | | |
| 1.77 | Center of ridge, 50 ft. high, 20 ft. wide, bears NE and SW. | | | | | | | | |
| 23.67 | Center line of Highway 264, asphalt surfaced, 38 lks. wide, bears SE and NW. | | | | | | | | |
| 23.92 | <p>Point for the closing cor. of secs. 33 and 34, with line 2-3, Tract 51, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Not remonumented.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 0°15' E., thence on a blank line</p> | | | | | | | | |
| 16.15 | <p>Cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 33 and 34.</p> <p>N. 0°07' E., bet. secs. 33 and 34.</p> | | | | | | | | |
| 40.04 | <p>Point for the cor. of secs. 27, 28, 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 2px;">T32N</td> <td style="padding: 2px;">R11E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">S28</td> <td style="padding: 2px;">S27</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">S33</td> <td style="padding: 2px;">S34</td> </tr> <tr> <td colspan="2" style="padding: 2px;">1988</td> </tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> | T32N | R11E | S28 | S27 | S33 | S34 | 1988 | |
| T32N | R11E | | | | | | | | |
| S28 | S27 | | | | | | | | |
| S33 | S34 | | | | | | | | |
| 1988 | | | | | | | | | |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>From this cor. point, an iron rod, of unknown origin, 1 in. diam., 60 ins. long, firmly set, projecting 6 ins. above the ground, bears S. 26°45' W., 10 lks. dist. Bury alongside the cor.</p> <hr/> <p style="text-align: center;">Restoring the survey executed by Philip Contzen, in 1905</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°42' W., bet. secs. 27 and 34.</p> <p>Over gently rolling land.</p> <p>4.85 Trail road, bears NE and SW.</p> <p>39.995 The 1/4 sec. cor. of secs. 27 and 34, monumented with a blue limestone, 17 x 6 x 6 ins., firmly set, projecting 8 ins. above ground, mkd. 1/4 27 on N. face, S34 on S. face, and X on top. (Record: 19 x 7 x 5 ins.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R11E S27 1/4 — S34 1988</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Bury the stone alongside the cor.</p> <hr/> <p>N. 89°42' W., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>39.915 The cor. of secs. 27, 28, 33 and 34.</p> <hr/> |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | N. 0°04' W., bet. secs. 27 and 28. |
| | Over rolling land. |
| 0.80 | Barbed wire fence, 4 strand, bears NE and SW. |
| 20.02 | Point for the S 1/16 sec. cor. of secs. 27 and 28. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T32N R11E S 1/16 S28 S27 1988 |
| | Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. |
| 22.50 | Power line, bears NE and SW. |
| 22.58 | S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway. |
| 22.61 | S. right-of-way line of U.S. Highway 160, parallels highway. |
| 23.75 | Point for a witness point at intersection with the center line of U.S. Highway 160, bears ENE and WSW. Impracticable to monument. |
| | from which |
| | A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 8°43' E., 75.50 ft. dist., with brass cap mkd. T32N R11E WP S27 RM 75.50 FT TO COR 1988, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. |
| | A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 8°47' W., 199.50 ft. dist., with brass cap mkd. T32N R11E WP S28 RM 199.50 FT TO COR 1988, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | Point for the cor. is located 29 lks. S. of the N. edge of pavement, 56 lks. wide. |
| 26.78 | N. right-of-way line of U.S. Highway 160, parallels highway. |
| 26.79 | N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway. |
| 40.04 | Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. below the surface of the ground, with brass cap mkd. |
| | <p style="text-align: center;">T32N R11E 1/4 S28 S27 1988</p> |
| | Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. |
| | Cor. is located on the E. edge of a trail road, bears SE and NW. |
| 66.30 | Graded road, 23 lks. wide, bears SE, in curve to the right. |
| 80.08 | Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T32N R11E S21 S22 ----- S28 S27 1988</p> |
| | Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------------|---|
| | <p>From this cor. point an iron rod, 5/8 ins. diam., firmly set, flush with the surface of the ground, bears S. 19°03' W., 13 lks. dist., with aluminum cap, 2 ins. diam., mkd. NAVAJO LAND DEVELOPMENT 13969 1985. This monument was established by Melvin F. Bautista, Arizona L.S. No. 13969, using improper procedures, and is not utilized during the course of this survey. Bury alongside the cor.</p> |
| <p>39.99</p> | <p>From the cor. of secs. 22, 23, 26 and 27. N. 89°36' W., bet. secs. 22 and 27. Over gently rolling land. Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R11E S22 1/4 — S27 1988</p> |
| | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| <p>43.30</p> | <p>Trail road, bears NE and SW.</p> |
| <p>65.40</p> | <p>Trail road, bears SE and NW.</p> |
| <p>79.98</p> | <p>The cor. of secs. 21, 22, 27 and 28.</p> |
| | <p>North, bet. secs. 21 and 22. Over nearly level land.</p> |
| <p>3.90</p> | <p>S. rim of mesa, 35 ft. high, bears SE and W.</p> |
| <p>6.80</p> | <p>Trail road, bears NE and SW.</p> |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 13.60 | Trail road, bears NE and SW. |
| 17.60 | Trail road, bears NE and SW. |
| 24.70 | Trail road, bears NE and SW. |
| 35.00 | Trail road, bears SE, in curve to the right. |
| 40.04 | <p>The 1/4 sec. cor. of secs. 21 and 22, monumented with a blue limestone, 18 x 7 x 3 ins., laying loose on the surface of the ground, mkd. 1/4 S22 on one face and 21 on the opposite face, with a piece of blue limestone, 7 x 6 x 4 ins., buried below the original stone, and mkd. S on one face. This point is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R11E 1/4 S21 S22 1988</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Bury the stone fragments alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°05' W., beginning new measurement.</p> |
| 7.30 | SE edge of Pasture Reservoir, bears NE and SW. |
| 13.95 | NW edge of Pasture Reservoir, bears NE and SW. |
| 40.64 | <p>Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R11E S16 S15 S21 S22 1988</p> </div> |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in rolling sand dunes.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°05' W., bet. secs. 15 and 22.</p> <p>Over rolling sand dunes.</p> |
| 40.005 | <p>Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 14 ins. long, 1 in. diam., 12 ins. in a drill hole, cemented in place, in sandstone bedrock, with magnetized aluminum cap mkd.</p> <p style="text-align: center;">T32N R11E S15 1/4 — S22 1988</p> <p>Deposit a magnet, 1 in. long, 7/8 in. diam., beneath the aluminum post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <p>From this cor. point, a blue limestone, 4 x 4 x 3 ins., laying loose on the surface of the ground, mkd. 1/4 on one face, bears S. 42°40' E., 30 lks. dist.; This is not accepted as the position of the original cor., deposit in mound of stone.</p> |
| 80.01 | <p>The cor. of secs. 15, 16, 21 and 22.</p> <hr/> <p>N. 0°07' W., bet. secs. 15 and 16.</p> <p>Over gently rolling land.</p> |
| 13.20 | <p>Trail road, bears NE and SW.</p> |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 40.64 | <p>The 1/4 sec. cor. of secs. 15 and 16, monumented with a sandstone, 16 x 6 x 4 ins., laying loose on a rock shelf, mkd. 1/4 16 on one face, 15 on opposite face, and X on top. (Record: Limestone, 18 x 7 x 6 ins.) This is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set an aluminum post, 14 ins. long, 1 in. diam., 12 ins. in a drill hole, cemented in place, in sandstone bedrock, with magnetized aluminum cap mkd.</p> <p style="text-align: center;">T32N R11E 1/4 S16 S15 1988</p> <p>Deposit a magnet, 1 in. long, 7/8 in. diam., beneath the aluminum post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <p>Deposit the found stone in the mound of stone.</p> <hr/> <p style="text-align: center;">Restoring the resurvey executed by Sidney E. Blout, in 1908</p> <hr/> <p>From the point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T32N R11E 1/4 S32 S33 1988</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>S. 0°03' W., bet. secs. 32 and 33.</p> |
| 4.77 | Barbed wire fence, 4 strand, bears E. and W. |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| | |
|--------|--|
| CHAINS | |
| 3.53 | S. rim of mesa, 100 ft. high, bears E. and W. |
| 8.83 | Trail road, bears SE and NW. |
| 9.08 | Barbed wire fence, 3 strand, bears SE and NW. |
| 9.775 | Point for the closing cor., at intersection with line 2-3, Tract 53; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>T32N R11E CC S32 S33</p> <hr style="width: 10%; margin: auto;"/> <p>TR 53 1989</p> </div> Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. <hr style="width: 20%; margin: auto;"/> S. 0°03' W., on a blank line, beginning new measurement. 30.255 The cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described. <hr style="width: 80%; margin: auto;"/> <div style="text-align: center;"> <p>Restoring the survey executed by Leonard W. Murphy, in 1962</p> <hr style="width: 20%; margin: auto;"/> </div> From the 1/4 cor. of secs. 32 and 33. N. 0°03' E., bet. secs. 32 and 33. Over broken land. 19.995 Point for the N 1/16 sec. cor. of secs. 32 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | T32N R11E N 1/16 S32 S33 1988 |
| | Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. |
| | Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor. |
| 24.10 | Wash, 60 lks. wide, 30 ft. deep, drains SW. |
| 28.75 | Barbed wire fence, 3 strand, bears SE and NW. |
| 31.80 | Barbed wire fence, 3 strand, bears NE and SW. |
| 36.20 | Power line, bears SE and NW. |
| 37.00 | Telephone line, bears SE and NW. |
| 39.99 | The cor. of secs. 28, 29, 32 and 33, determined at record bearing and dist. from the remaining 1962 reference monument |
| | An iron post, 2 1/2 ins. diam., firmly set, 54 ins. below the surface of the ground, bears S. 70° E., 66 ft. dist., with brass cap mkd. T32N R11E S33 RM 66 FT 1962, and an arrow pointing to the cor. |
| | At the cor. point |
| | Set a railroad spike, flush with the surface of the pavement of U.S. Highway 160, with top mkd. |
| | BLM 29 28 --- 32 33 1988 |
| | Cor. is located 13 lks. N. of the S. edge of pavement of U.S. Highway 160, 70 lks. wide, bears NE, in curve to the right. |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Restoring of the resurvey executed by Sidney E. Blout, in 1908</p> <hr/> |
| | <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 89°59' W., bet. secs. 28 and 33.</p> <p>Over level to rolling land.</p> |
| 0.92 | Barbed wire fence, 4 strand, bears NE and SW. |
| 4.10 | Trail road, bears SE and NW. |
| 7.80 | Trail road, bears NE and SW. |
| 16.90 | Enter housing development. |
| 20.07 | Point for the E 1/16 sec. cor. of secs. 28 and 33. |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T32N R11E S28 E 1/16 ——— S33 1988 </p> |
| | <p>from which</p> <p style="padding-left: 40px;">The SE cor. of a concrete block house, 51 x 34 ft., bears N. 65 1/2° E., 43 1/2 lks. dist., long side bears NW.</p> <p style="padding-left: 40px;">The SW cor. of same house, bears N. 34 1/2° W., 57 lks. dist., long side bears SE.</p> |
| | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| 21.90 | Paved road, 42 lks. wide, bears NE and SW. |
| 26.10 | Intersect the E. side of a concrete block house, main portion measuring 51 x 26 ft., the southernmost cor. bears SW, 28 1/2 lks. dist., the long side bears NE. |
| 27.65 | Paved road, 42 lks. wide, bears NE and SW. |
| 29.20 | Leave housing development. |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 40.14 | <p>The 1/4 sec. cor. of secs. 28 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 17 ins. above ground, with brass cap mkd. as described in the official record of the 1962 resurvey of a portion of the subdivisional lines of T. 32 N., R. 11 E.</p> |
| | <p>Add the marks 1988 to the brass cap.</p> |
| | <p>Raise a supporting mound of stone, 4 ft. base, to top.</p> |
| | <hr/> <p>Restoring the resurvey executed by Leonard W. Murphy, in 1962</p> <hr/> |
| | <p>From the 1/4 sec. cor. of secs. 28 and 33.</p> |
| | <p>N. 89°50' W., bet. secs. 28 and 33.</p> |
| | <p>Over nearly level land.</p> |
| 9.85 | <p>Intersect the E. side of a concrete block house, with overall dimensions of 51 x 29 ft., the southernmost cor. bears SW, 13 lks. dist., the long side bears NE.</p> |
| 12.10 | <p>Intersect the E. side of a concrete block house, 37 x 28 ft., the southernmost cor. bears SW, 23 lks. dist., the long side bears NE.</p> |
| 20.06 | <p>Point for the W 1/16 sec. cor. of secs. 28 and 33.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> |
| | <p>T32N R11E S28 W 1/16 — S33 1988</p> |
| | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| 21.50 | <p>Wash, 45 lks. wide, 2 ft. deep, drains SW.</p> |
| 25.25 | <p>Trail road, bears SE and NW.</p> |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--|--|
| 32.10 | Center line of State Highway 264, asphalt surfaced, 45 lks. wide, bears SE. and NW. |
| 40.12 | The cor. of secs. 28, 29, 32 and 33. |
| <hr/> | |
| N. 0°05' E., bet. secs. 28 and 29. | |
| Over nearly level to gently rolling land. | |
| 0.49 | Point for a witness point at intersection with the center line of U.S. Highway 160, bears NE on curve to the right. Impracticable to monument. |
| 3.90 | Intersect S. side of main structure of Navajo Trail Mall, a concrete block building, with overall dimensions of 140 x 116 ft., the southernmost cor. bears SW, 141 lks. dist., the long side bears NE. |
| 9.70 | Center line of State Highway 264, asphalt surfaced, 104 lks. wide, bears SE and NW. |
| 11.45 | Power line, bears NE and SW. |
| 20.01 | Point for the S 1/16 sec. cor. of secs. 28 and 29. |
| Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. | |
| T32N R11E S 1/16 S29 S28 1988 | |
| Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. | |
| 22.00 | Enter inhabited area. |
| 40.02 | The 1/4 sec. cor. of secs. 28 and 29, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the official record of the 1962 resurvey of a portion of the subdivisional lines of T. 32 N., R. 11 E. |
| Not remonumented. | |
| <hr/> | |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p style="text-align: center;">Restoring the survey executed by Philip Contzen, in 1905</p> <hr style="width: 20%; margin: auto;"/> |
| | <p>From the cor. of secs. 21, 22, 27 and 28.</p> |
| | <p>N. 89°56' W., bet. secs. 21 and 28.</p> |
| | <p>Over gently rolling land.</p> |
| 40.02 | <p>Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T32N R11E S21 1/4 — S28 1988</p> |
| | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| | <p>From this cor. point, an iron rod, 5/8 in. diam., 20 ins. long, firmly set, flush with the surface of the ground, bears S. 43°39' W., 18 lks. dist., with aluminum cap, 2 ins. diam., mkd. NAVAJO LAND DEVELOPMENT 13969 1/4 1985. This monument was established by Melvin F. Bautista, Arizona L.S. No. 13969, using improper procedures, and is not utilized during the course of this survey. Bury alongside the cor.</p> |
| | <p>From this same point, an iron pipe, of unknown origin, 3 ins. diam., 48 ins. long, firmly set in concrete, projecting 19 ins. above the ground, bears S. 55° W., 7 lks. dist., with lead cap mkd. QTR COR. and arrows pointing E. and W. Bury alongside the cor.</p> |
| 53.20 | <p>E. rim of Dynamite Butte, bears NE and SW.</p> |
| 53.50 | <p>W. rim of Dynamite Butte, bears SE and NW.</p> |
| 67.20 | <p>Paved road on E. edge of housing development, 36 lks. wide, bears NE and SW.</p> |
| 71.60 | <p>Paved road, 35 lks. wide, bears N. and S.</p> |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 75.51 | Intersect the E. side of a wood framed house, with overall dimensions of 50 x 38.5 ft., the SE cor. bears South, 4 lks. dist., the long side bears North. |
| 78.70 | Graded road, 45 lks. wide, bears SE and NW. |
| 80.04 | <p>The cor. of secs. 20, 21, 28 and 29, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the official record of the 1962 resurvey of a portion of the subdivisional lines of T. 32 N., R. 11 E.</p> <p>Not remonumented.</p> <p>Cor. is located 1 lk. E. of cor. of wire mesh fences, extending N. and W.</p> <hr/> <p>N. 0°01' W., bet. secs. 20 and 21.</p> <p>Over gently rolling land.</p> |
| 13.50 | Top of earthen dike, 6 ft. high, bears E. and W. |
| 40.04 | <p>Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R11E 1/4 S20 S21 1988</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 1 lk. E. of a wire mesh fence, bears N. and S.</p> |
| 46.75 | Barbed wire fence, 4 strand, bears NE and SW. |
| 54.10 | Center of landing strip, asphalt surfaced, 68 lks. wide, bears NE and SW. |
| 80.08 | The cor. of secs. 16, 17, 20 and 21, monumented with a sandstone, 17 x 8 x 6 ins., firmly set, projecting 2 ins. above the ground, mkd. 3 on N. face, 3 notches on NE edge, 11E on E. face, and 1 notch on SE edge. (Record: Limestone, 20 x 9 x 5 ins.) |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | |
|--------|---|------|------|-----|-----|-----|-----|------|--|
| | <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px;">T32N</td> <td style="padding: 2px;">R11E</td> </tr> <tr> <td style="padding: 2px; border-right: 1px solid black;">S17</td> <td style="padding: 2px;">S16</td> </tr> <tr> <td style="padding: 2px; border-right: 1px solid black;">S20</td> <td style="padding: 2px;">S21</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px;">1988</td> </tr> </table> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Deposit the stone in a mound of stone, 1 ft. base, 1 ft. high, W. of the cor.</p> <p>Cor. is located 1 1/2 lks. E. of cor. of wire mesh fences, extending S. and W.</p> <p>From this cor. point an iron rod, of unknown origin, 1/2 in. diam., 60 ins. long, firmly set, projecting 2 ins. above the ground, bears West, 1 lk. dist. Bury alongside the cor.</p> | T32N | R11E | S17 | S16 | S20 | S21 | 1988 | |
| T32N | R11E | | | | | | | | |
| S17 | S16 | | | | | | | | |
| S20 | S21 | | | | | | | | |
| 1988 | | | | | | | | | |
| | <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 89°16' W., bet. secs. 16 and 21.</p> <p>Over rolling sand dunes.</p> | | | | | | | | |
| 4.70 | Trail road, bears NE and SW. | | | | | | | | |
| 12.20 | E. rim of mesa, 50 ft. high, bears N. and S. | | | | | | | | |
| 39.98 | <p>The 1/4 sec. cor. of secs. 16 and 21, monumented with an iron rod, of unknown origin, 1 in. diam., 60 ins. long, firmly set, projecting 24 ins. above the ground, with a buried sandstone, 19 x 6 x 3 ins., alongside, mkd. 1/4 16 on one face and X on another face. This is accepted as a careful and faithful perpetuation of the original cor. position. (Record: Limestone, 18 x 7 x 5 ins.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> | | | | | | | | |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p style="text-align: center;">T32N R11E S16 1/4 — S21 1988</p> <p>Bury the iron rod and the stone, alongside the cor.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <hr/> <p>West, beginning new measurement.</p> |
| 35.95 | Graded road, 45 lks. wide, bears SE, in curve to the left. |
| 39.99 | The cor. of secs. 16, 17, 20 and 21. |
| | <hr/> <p>N. 0°13' E., bet. secs. 16 and 17.</p> <p>Over rolling sand dunes.</p> |
| 2.10 | Graded road, 45 lks. wide, bears NE and SW. |
| 13.50 | Trail road, bears SE and NW. |
| 39.98 | Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor. |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R11E 1/4 S17 S16 1988</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this point, an iron rod, of unknown origin, 1 in. diam., 60 ins. long, firmly set, projecting 18 ins. above the ground, bears N. 83°52' W., 18 lks. dist. Bury alongside the cor.</p> |
| 55.25 | Graded road, 30 lks. wide, bears NE and SW. |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS

79.96

Point for the cor. of secs. 8, 9, 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, on top of a steel fence post, with brass cap mkd.

| | |
|------|------|
| T32N | R11E |
| S 8 | S 9 |
| S17 | S16 |
| 1988 | |

Raise a mound of stone, 3 ft. base, 1 ft. high, W. of the cor.

Cor. is located in rolling sand dunes.

From the 1/4 sec. cor. of secs. 9 and 16, monumented with the mks. X 9 16 chiseled on a sandstone ledge, and witnessed by a mound of stone, 2 1/2 ft. base, 1 ft. high, to the N. This is accepted as the best remaining evidence of the original cor. position.

At the cor. point.

Set an aluminum post, 14 ins. long, 1 in. diam., 12 ins. in a drill hole, cemented in place, in sandstone bedrock, with magnetized aluminum cap mkd.

| | |
|------|------|
| T32N | R11E |
| S 9 | |
| 1/4 | — |
| S16 | |
| 1988 | |

Deposit a magnet, 1 in. long, 7/8 in. diam., beneath the aluminum post.

Rebuild the mound of stone, 3 ft. base, 1 ft. high, N. of the cor.

Cor. is located on sandstone outcrop.

N. 89°50' W., bet. secs. 9 and 16.

Over sandstone outcrops.

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 15.40 | Graded road, 30 lks. wide, bears NE and SW. |
| 39.88 | The cor. of secs. 8, 9, 16 and 17. |
| | N. 0°15' W., bet. secs. 8 and 9. |
| | Over rolling sand dunes. |
| 39.98 | <p>The 1/4 sec. cor. of secs. 8 and 9, monumented with a sandstone, 14 x 8 x 2 ins., laying loose on a sandstone ledge, mkd. 9 on one face and 8 on the opposite face, and witnessed by a mound of stone, 3 ft. base, 1 ft. high., W. of the cor. This is accepted as the best available evidence of the original cor. position. (Record: Limestone, 18 x 7 x 5 ins.)</p> <p>At the cor. point</p> <p>Set an aluminum post, 12 ins. long, 1 in. diam., 11 ins. in a drill hole, cemented in place, in sandstone bedrock, with magnetized aluminum cap mkd.</p> <p style="text-align: center;">T32N R11E 1/4 S 8 S 9 1988</p> <p>Deposit a magnet, 1 in. long, 7/8 in. diam., beneath the aluminum post.</p> <p>Deposit the stone in a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> |
| | <p>Restoring the resurvey executed by Sidney E. Blout, in 1908</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 31 and 32.</p> <p>Over level and broken land.</p> |
| 3.30 | Moenkopi Wash, 230 lks. wide, 10 ft. deep, drains NW. |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 5.90 | Trail road, bears SE and NW. |
| 8.25 | Trail road, bears SE and NW. |
| 8.41 | Barbed wire fence, 4 strand, bears SE and NW. |
| 18.47 | S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway. |
| 18.50 | S. right-of-way line of U.S. Highway 160, parallels highway. |
| 19.19 | Point for a witness point at intersection with the center line of U.S. Highway 160, bears ENE and WSW. |
| | Set a railroad spike, flush with the surface of the pavement of U.S. Highway 160, with top mkd. |
| | <p>BLM WP S31 S32 1988</p> |
| | from which |
| | <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 8°18' E., 45 ft. dist., with brass cap mkd. T32N R11E WP S32 RM 45.00 FT TO COR 1988, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| | <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 8°18' W., 55 ft. dist., with brass cap mkd. T32N R11E WP S31 RM 55.00 FT TO COR 1988 and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| | <p>Cor. is located 28 lks. S. of the N. edge of pavement, 54 lks. wide.</p> |
| 20.00 | Point for the S 1/16 sec. cor. of secs. 31 and 32. |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p style="text-align: center;">T32N R11E S 1/16 S31 S32 1988</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| 20.02 | N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway. |
| 20.03 | N. right-of-way line of U.S. Highway 160, parallels highway. |
| 28.10 | Graded road, 45 lks. wide, bears SE and NW. |
| 40.00 | True point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate dist. Impracticable to monument. |
| 50.00 | Point for the witness 1/4 sec. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor. |
| | <p>Set an aluminum tablet, 3 1/4 ins. diam., 3 1/2 ins. stem., 3 ins. below the surface of sandstone bedrock, cemented in place, with top mkd.</p> <p style="text-align: center;">WC T32N R11E 1/4 S31 S32 1988</p> <p>Deposit a magnet, 1 ins. long, 7/8 ins. diam., beneath the aluminum tablet.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W. of the cor.</p> <p>Cor. is located on the S. rim of a mesa, 100 ft. high, bears E. and W.</p> <hr/> <p style="text-align: center;">Restoring the resurvey executed by Leonard W. Murphy, in 1962</p> <hr/> <p>N. 0°02' W., beginning new measurement, bet. secs. 31 and 32.</p> <p>Over gently rolling land.</p> |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 19.70 | Wash, 23 lks. wide, 5 ft. deep, drains SE. |
| 24.80 | Trail road, bears NE and SW. |
| 29.985 | <p>The cor. of secs. 29, 30, 31 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 ins. above the ground, with brass cap mkd. as described in the official record of the 1962 resurvey of a portion of the subdivisional lines of T. 32 N., R. 11 E.</p> <p>Not remonumented.</p> |
| <hr/> | |
| | From the cor. of secs. 28, 29, 32 and 33. |
| | N. 89°56' W., bet. secs. 29 and 32. |
| | Over gently rolling land. |
| 0.408 | <p>Point for a witness point at intersection with the center line of U.S. Highway 160, bears NE on a curve to the right.</p> <p>Impracticable to monument.</p> |
| 4.75 | Graded road, 38 lks. wide, bears SE and NW. |
| 13.30 | Trail road, bears NE and SW. |
| | Enter residential area. |
| 19.965 | Point for the E 1/16 sec. cor. of secs. 29 and 32. |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. below the surface of the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T32N R11E S29 E 1/16 — S32 1988</p> |
| | from which |
| | <p style="text-align: center;">A wooden power pole, bears S. 40 3/4° W., 107 lks. dist.</p> |
| | <p style="text-align: center;">The SW cor. of a concrete block house, 66 x 29.5 ft., bears N. 60 1/2° W., 77 1/2 lks. dist., long side bears NE.</p> |
| | <p style="text-align: center;">The SE cor. of the same concrete house, bears N. 34 1/4° W., 41 lks. dist., long side bears SW.</p> |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| | <p>Cor. is located in a gravel surfaced parking area.</p> |
| 22.17 | <p>Chain link fence, bears N. and S.</p> |
| 39.93 | <p>The 1/4 sec. cor. of secs. 29 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the official record of the 1962 resurvey of a portion of the subdivisional lines of T. 32 N., R. 11 E.</p> |
| | <p>Not remonumented.</p> |
| | <p>From the cor. of secs. 29, 30, 31 and 32.</p> |
| | <p>N. 89°53 W., bet. secs. 30 and 31.</p> |
| | <p>Over gently rolling land.</p> |
| 19.40 | <p>Top of earthen dike, 10 ft. high, bears SE and NW.</p> |
| 20.02 | <p>Point for the E 1/16 sec. cor. of secs. 30 and 31.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T32N R11E S30 E 1/16 — S31 1988</p> |
| | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| | <p>From this cor. point, an iron rod of unknown origin, 1 in. diam., 60 ins. long, firmly set, projecting 12 ins. above the ground, bears East, 2 lks. dist. Bury alongside the cor.</p> |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--|--|
| 40.04 | <p>The 1/4 sec. cor. of secs. 30 and 31, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the official record of the 1962 resurvey of a portion of the subdivisional lines of T. 32 N., R. 11 E.</p> <p>Not remonumented.</p> |
| <hr/> <p>Restore the survey executed by Philip Contzen, in 1905</p> <hr/> | |
| <p>N. 89°52' W., beginning new measurement, bet. secs. 30 and 31.</p> <p>Over gently rolling land.</p> | |
| 7.30 | Top of earthen dike, 10 ft. high, bears NE and SW. |
| 31.70 | Graded road, 38 lks. wide, bears NE and SW. |
| 38.43 | The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described. |
| <hr/> <p>Restoring the resurvey executed by Leonard W. Murphy, in 1962</p> <hr/> | |
| <p>From the cor. of secs. 29, 30, 31 and 32.</p> | |
| <p>N. 0°02' E., bet. secs. 29 and 30.</p> | |
| <p>Over gently rolling land.</p> | |
| 4.70 | Trail road, bears SE and NW. |
| 24.60 | Paved road, 61 lks. wide, bears E. and W. |
| 30.50 | Paved road, 53 lks. wide, bears SE and NW. |
| 40.04 | Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor. |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. below the surface of the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T32N R11E 1/4 S30 S29 1988</p> |
| | <p>from which</p> |
| | <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 71°25' E., 66 ft. dist., with brass cap mkd. T32N R11E 1/4 S29 RM 66.00 FT TO COR 1988, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| | <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set flush with the surface of the ground, for a reference monument, bears N. 18°35' W., 66 ft. dist., with brass cap mkd. T32N R11E 1/4 S30 RM 66.00 FT TO COR 1988 and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| | <p>Cor. is located in a paved road, 53 lks. wide, bears N. and S., 27 lks. W. of the E. edge of pavement.</p> |
| 44.90 | <p>Intersection of two paved roads, each 53 lks. wide, bears N., S., and E., W.</p> |
| 50.055 | <p>The S-N 1/64 sec. cor. of secs. 29 and 30, monumented with an iron post, 2 1/2 ins. diam., set 16 ins. below the surface of the ground, with brass cap missing.</p> |
| | <p>At the cor. point</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. below the surface of the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">S-N 1/64 S30 S29 1988</p> |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| | |
|--------|--|
| CHAINS | <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set flush with the surface of the ground, for a reference monument, bears N. 67°07' E., 25 ft. dist., with brass cap mkd. T32N R11E 1/64 S29 RM 25.00 FT TO COR 1988, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set flush with the surface of the ground, for a reference monument, bears N. 22°53' W., 66 ft. dist., with brass cap mkd. T32N R11E 1/64 S30 RM 66.00 FT TO COR 1988 and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in a paved road, 53 lks. wide, bears N. and S., 25 lks. E. of the W. edge of pavement.</p> <hr/> <p>N. 0°02' E., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>10.005 Point for the N 1/16 sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R11E N 1/16 S30 S29 1988</p> |
|--------|--|

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set flush with the surface of the ground, for a reference monument, bears S. 64°34' E., 55 ft. dist., with brass cap mkd. T32N R11E N 1/16 S29 RM 55.00 FT TO COR 1988, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 25°26' W., 100 ft. dist., with brass cap mkd. T32N R11E N 1/16 S30 RM 100.00 FT TO COR 1988, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in the center of a graded road, 52 lks. wide, bears N. and S., 75 lks. S. of intersection with graded road, 52 lks. wide, bears NE and SW.</p> |
| 20.02 | <p>The N-N 1/64 sec. cor. of secs. 29 and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the official record of the 1962 resurvey of a portion of the subdivisional lines of T. 32 N., R. 11 E.</p> <p>Not remonumented.</p> <p>Cor. is located alongside the cor. of wire mesh fences, extending N. and E.</p> <hr/> <p>N. 0°02' E., beginning new measurement.</p> <p>Over gently rolling land.</p> |
| 10.005 | <p>The cor. of secs. 19, 20, 29 and 30, monumented with an iron post, 2 1/2 ins. diam., set 6 ins. below the surface of the ground, with brass cap mkd. as described in the official record of the 1962 resurvey of a portion of the subdivisional lines of T. 32 N., R. 11 E.</p> <p>Not remonumented.</p> <p>Cor. is located in a wire mesh fence, bears N. and S.</p> <hr/> |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | West, bet. secs. 19 and 30. |
| | Over gently rolling land. |
| 5.65 | Graded road, 53 lks. wide, bears SE and NW. |
| 20.01 | Point for the E 1/16 sec. cor. of secs. 19 and 30. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T32N R11E |
| | S19 |
| | E 1/16 — |
| | S30 |
| | 1988 |
| | Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. |
| | From this cor. point, an iron rod, of unknown origin, 1 in. diam., 60 ins. long, firmly set, projecting 8 ins. above the ground, bears N. 65° E., 3 1/2 lks. dist. Bury alongside the cor. |
| 22.01 | Barbed wire fence, 4 strand, on SE edge of cemetery, bears NE and SW. |
| 31.93 | Barbed wire fence, 5 strand, on SW edge of cemetery, bears NE and SW. |
| 40.02 | The 1/4 sec. cor. of secs. 19 and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the official record of the 1962 resurvey of a portion of the subdivisional lines of T. 32 N., R. 11 E. |
| | Add the marks 1988 to the brass cap. |
| | Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor. |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| | | | | | | | | | | | |
|--------|---|------|------|-----|-----|-------|-----|------|-----|------|--|
| CHAINS | <p>Restoring the survey executed by Philip Contzen, in 1905</p> <hr style="width: 20%; margin: auto;"/> | | | | | | | | | | |
| 40.01 | <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°01' W., bet. secs. 19 and 20.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T32N</td><td>R11E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td>S19</td><td>S20</td></tr> <tr><td colspan="2" style="text-align: center;">1988</td></tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 3 lks. W. of a wire mesh fence, bears N. and S.</p> | T32N | R11E | 1/4 | | S19 | S20 | 1988 | | | |
| T32N | R11E | | | | | | | | | | |
| 1/4 | | | | | | | | | | | |
| S19 | S20 | | | | | | | | | | |
| 1988 | | | | | | | | | | | |
| 80.02 | <p>Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T32N</td><td>R11E</td></tr> <tr><td>S18</td><td>S17</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td>S19</td><td>S20</td></tr> <tr><td colspan="2" style="text-align: center;">1988</td></tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, an iron rod, of unknown origin, 1 in. diam., 60 ins. long, firmly set, projecting 2 ins. above the ground, bears S. 74° E., 16 lks. dist. Bury alongside the cor.</p> <p>From this same cor. point, the cor. of wire mesh fences, extending E. and S., bears S. 74 3/4° E., 17 lks. dist.</p> <hr style="width: 80%; margin: 10px auto;"/> | T32N | R11E | S18 | S17 | ----- | | S19 | S20 | 1988 | |
| T32N | R11E | | | | | | | | | | |
| S18 | S17 | | | | | | | | | | |
| ----- | | | | | | | | | | | |
| S19 | S20 | | | | | | | | | | |
| 1988 | | | | | | | | | | | |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | From the cor. of secs. 16, 17, 20 and 21. |
| | N. 89°55 W., bet. secs. 17 and 20. |
| | Over rolling sand dunes. |
| 15.00 | Graded road, 30 lks. wide, bears N. and S. |
| 40.025 | Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the original cor. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, on top of a steel fence post, with brass cap mkd. |
| | <p style="text-align: center;">T32N R11E S17 1/4 — S20 1988</p> |
| | Cor. is located 7 lks. N. of a wire mesh fence, bears E. and W. |
| 80.05 | The cor. of secs. 17, 18, 19 and 20. |
| | N. 89°56' W., bet. secs. 18 and 19. |
| | Over gently rolling land. |
| 1.30 | Graded road, 53 lks. wide, bears NE, in curve to the right. |
| 20.00 | Point for the E 1/16 sec. cor. of secs. 18 and 19. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T32N R11E S18 E 1/16 — S19 1988</p> |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| | <p>From this cor. point, an iron rod, of unknown origin, 1 in. diam., 60 ins. long, firmly set, projecting 6 ins. above the ground, bears S. 12°35' E., 20 lks. dist. Bury alongside the cor.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T32N R11E S18 1/4 — S19 1988</p> |
| 78.20 | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.</p> |
| | <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°01' W., bet. secs. 17 and 18.</p> <p>Over rolling sand dunes.</p> |
| 1.60 | <p>Graded road, 53 lks. wide, bears NE and SW.</p> |
| 20.005 | <p>Point for the S 1/16 sec. cor. of secs. 17 and 18.</p> <p>Set an aluminum post, 14 ins. long, 1 in. diam., 10 ins. in a drill hole, cemented in place, in sandstone bedrock, with magnetized aluminum cap mkd.</p> |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p style="text-align: center;">T32N R11E S 1/16 S18 S17 1988</p> <p>Deposit a magnet, 1 in. long, 7/8 in. diam., beneath the aluminum post.</p> <p>From this cor. point, an iron rod of unknown origin, 1/2 in. diam., 18 ins. long, firmly set, projecting 4 ins. above the ground, bears S. 15° E., 17 lks. dist. Bury alongside the cor.</p> <p>40.01 The 1/4 sec. cor. of secs. 17 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the official record of the 1962 resurvey of a portion of the subdivisional lines of T. 32 N., R. 11 E.</p> <p>Add the marks 1988 to the brass cap.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°18' E., beginning new measurement.</p> <p>Over rolling sand dunes.</p> <p>40.06 The cor. of secs. 7, 8, 17 and 18, monumented with a blue limestone, 15 x 14 x 5 ins., firmly set, projecting 8 ins. above the ground, mkd. T32N on N. face, 5 notches on NE edge, 11E on E. face, R11E and 4 grooves on S. face, and 5 grooves on W. face. (Record: 18 x 6 x 5 ins.)</p> <p>At the cor. point</p> <p>Set an aluminum post, 20 ins. long, 1 in. diam., 10 ins. in a drill hole, cemented in place, in sandstone bedrock, encircled with a collar of stone, 1 ft. base, to top, with magnetized aluminum cap mkd.</p> |

Dependent Resurvey, a Portion of the Subdivisional Lines,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | | | |
|-----------|--|-----------|--|-----|-----|-----|-----|------|--|------|--|
| | <table border="1"> <tr> <td colspan="2">T32N R11E</td> </tr> <tr> <td>S 7</td> <td>S 8</td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> <tr> <td colspan="2">1988</td> </tr> </table> | T32N R11E | | S 7 | S 8 | S18 | S17 | 1988 | | | |
| T32N R11E | | | | | | | | | | | |
| S 7 | S 8 | | | | | | | | | | |
| S18 | S17 | | | | | | | | | | |
| 1988 | | | | | | | | | | | |
| | <p>Deposit a magnet, 1 in. long, 7/8 in. diam., beneath the aluminum post.</p> <p>Bury the stone alongside the cor.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 89°59' W., bet. secs. 8 and 17.</p> <p>Over rolling sand dunes.</p> | | | | | | | | | | |
| 39.84 | <p>The 1/4 sec. cor. of secs. 8 and 17, monumented with a blue limestone, 16 x 9 x 6 ins., laying loose on the surface of the ground, mkd. 1/4 8 on one face, S17 on opposite face, and X on another face. This is accepted as the best available evidence of the original cor. position. (Record: 18 x 7 x 5 ins.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, on top of a steel fence post, with brass cap mkd.</p> | | | | | | | | | | |
| | <table border="1"> <tr> <td colspan="2">T32N R11E</td> </tr> <tr> <td colspan="2">S 8</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td colspan="2">S17</td> </tr> <tr> <td colspan="2">1988</td> </tr> </table> | T32N R11E | | S 8 | | 1/4 | — | S17 | | 1988 | |
| T32N R11E | | | | | | | | | | | |
| S 8 | | | | | | | | | | | |
| 1/4 | — | | | | | | | | | | |
| S17 | | | | | | | | | | | |
| 1988 | | | | | | | | | | | |
| | <p>Bury the stone alongside the cor.</p> <hr/> <p>N. 89°40' W., beginning new measurement.</p> | | | | | | | | | | |
| 9.40 | Graded road, 30 lks. wide, bears N. and S. | | | | | | | | | | |
| 9.60 | Power line, bears N. and S. | | | | | | | | | | |
| 40.32 | The cor. of secs. 7, 8, 17 and 18. | | | | | | | | | | |

Dependent Resurvey of Certain Tracts,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS

Restoring the surveys executed by
Sidney E. Blout, in 1907-1908

Tract 37

From the point for Cor. No. 1, Tract 37, identical with Cor. No. 2, Tract 54, Cor. No. 3, Tract 56, and Cor. No. 4, Tract 53, at proportionate position; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

| | |
|-------|-------|
| T32N | R11E |
| TR 37 | TR 53 |
| 1 | 4 |
| ----- | |
| 2 | 3 |
| TR 54 | TR 56 |
| 1989 | |

Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

From this cor. point, Cor. No. 3, Tract 60, identical with Cor. No. 4, Tract 59, bears S. 0°12' E., 19.98 chs. dist., hereinafter described.

No evidence of the intermediate cors. were found.

Thence N. 0°01' E., on line 1-2, identical with line 4-3, Tract 53.

Over rolling and broken land.

0.35 Barbed wire fence, 3 strand, bears E. and W.

5.01 Point for Cor. No. 3, Tract 53, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of Certain Tracts,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <div style="text-align: center;"> <p>T32N R11E</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>5.90 Graded road, 30 lks. wide, bears NE, in curve to the right.</p> <p>7.70 Base of mesa, 200 ft. high, bears E. and W.</p> <p>14.91 Point for a witness point at intersection with the E. and W. center line of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R11E</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <p>15.60 S. rim of mesa, 150 ft. high, bears E. and W.</p> <p>20.04 Point for Cor. No. 2, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, flush with the surface of limestone bedrock, with top mkd.</p> <div style="text-align: center;"> <p>T32N R11E</p> </div> |

Dependent Resurvey of Certain Tracts,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| | | | | | | | | | | | | | |
|---|--|------|------|-------|-------|---|--|---|---|-------|-------|------|--|
| CHAINS | <p>Deposit a magnet, 1 in. long, 7/8 in. diam., beneath the aluminum tablet.</p> <p>Raise a mound of stone, 3 ft. diam., 1 1/2 ft. high, N. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence S. 89°16' W., on line 2-3, Tract 37.</p> <p>Over broken land.</p> <p>5.10 Ravine, 45 lks. wide, 20 ft. deep, drains SW, at base of mesa, 150 ft. high, bears NE and SW.</p> <p>6.66 E. right-of-way line of U.S. Highway 160, parallels highway.</p> <p>8.315 Point for a witness point at intersection with the center line of U.S. Highway 160, asphalt surfaced, 53 lks. wide, bears NE, in spiral curve to the left. Impracticable to monument.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 65°05' E., 49.20 ft. dist., with brass cap mkd. T32N R11E WP TR 37 RM 49.20 FT TO COR 1989, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 65°12' W., 200.80 ft. dist., with brass cap mkd. T32N R11E WP S32 RM 200.80 FT TO COR 1989, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>10.02 Point for Cor. No. 3, identical with Cor. No. 2, Tract 38, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T32N</td> <td style="padding: 0 10px;">R11E</td> </tr> <tr> <td style="padding: 0 10px;">S 32</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center; border-top: 1px solid black; padding-top: 5px;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">2</td> <td style="padding: 0 5px;">3</td> </tr> <tr> <td style="padding: 0 5px;">TR 38</td> <td style="padding: 0 5px;">TR 37</td> </tr> </table> </td> </tr> <tr> <td colspan="2" style="text-align: center; padding-top: 5px;">1989</td> </tr> </table> </div> | T32N | R11E | S 32 | | <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">2</td> <td style="padding: 0 5px;">3</td> </tr> <tr> <td style="padding: 0 5px;">TR 38</td> <td style="padding: 0 5px;">TR 37</td> </tr> </table> | | 2 | 3 | TR 38 | TR 37 | 1989 | |
| T32N | R11E | | | | | | | | | | | | |
| S 32 | | | | | | | | | | | | | |
| <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">2</td> <td style="padding: 0 5px;">3</td> </tr> <tr> <td style="padding: 0 5px;">TR 38</td> <td style="padding: 0 5px;">TR 37</td> </tr> </table> | | 2 | 3 | TR 38 | TR 37 | | | | | | | | |
| 2 | 3 | | | | | | | | | | | | |
| TR 38 | TR 37 | | | | | | | | | | | | |
| 1989 | | | | | | | | | | | | | |

Dependent Resurvey of Certain Tracts,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <hr/> <p>Thence S. 0°12' E., on line 3-4, identical with line 2-1, Tract 38.</p> <p>Over rolling and broken land.</p> |
| 2.20 | Base of mesa, 60 ft. high, bears NE and SW. |
| 3.30 | Intersect the center line of U.S. Highway 160, asphalt surfaced, 57 lks. wide, bears NE, in curve to the left. |
| 4.985 | Intersect the E. and W. center line of sec. 32. Not monumented. |
| 6.01 | E. right-of-way line of U.S. Highway 160, parallels highway. |
| 9.28 | E. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway. |
| 10.085 | Cor. No. 1, Tract 38 identical with Cor. No. 2, Tract 39, hereinafter described. |
| | <hr/> <p>Thence S. 0°03' W., beginning new measurement, identical with a portion of line 1-2, Tract 39.</p> <p>Over rolling land.</p> |
| 9.84 | Barbed wire fence, 3 strand, bears NE and SW. |
| 10.00 | Point for Cor. No. 4, identical with Cor. No. 3, Tract 54, at proportionate dist.; there is no remaining evidence of the original cor. |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-left: 100px;"> <p>T32N R11E</p> <p style="margin-left: 20px;"> TR 37</p> <p style="margin-left: 20px;"> 4</p> <p style="margin-left: 20px;"> ----- </p> <p style="margin-left: 20px;"> 3</p> <p style="margin-left: 20px;"> TR 54</p> <p style="margin-left: 20px;">1989</p> </div> |

Dependent Resurvey of Certain Tracts,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| | |
|--------|---|
| CHAINS | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, an iron rod of unknown origin, 1/8 in. diam., 24 ins. long, firmly set, projecting 6 ins. above the ground, bears S. 55 1/2° E., 8 lks. dist. Bury alongside the cor.</p> <p>Cor. is located 9 lks. N. of a sanitary sewer manhole.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence N. 89°03' E., on line 4-1, identical with Line 3-2, Tract 54.</p> <p>Over level land.</p> |
| 9.99 | <p>Cor. No. 1, identical with Cor. No. 2, Tract 54, Cor. No. 3, Tract 56, and Cor. No. 4, Tract 53, point of beginning.</p> <hr/> <p style="text-align: center;">Tract 38</p> <hr/> <p>From the point for Cor. No. 1, Tract 38, identical with Cor. No. 2, Tract 39, and an angle point on line 3-4, Tract 37, determined from the original witness cor.</p> <p style="padding-left: 40px;">A blue limestone, 14 x 7 x 3 ins., firmly set, projecting 3 ins. above the ground, with no visible mks., bears N. 89°06' E, 15 lks. dist. (Record: 14 x 12 x 4 ins.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> |

Dependent Resurvey of Certain Tracts,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | | | | | | | | | |
|--------|--|------|------|-------|--|--|---|-------|--|--|---|-------|--|--|------|--|-------|
| | <table border="0"> <tr> <td>T32N</td> <td>R11E</td> </tr> <tr> <td>TR 38</td> <td> </td> </tr> <tr> <td></td> <td>1</td> </tr> <tr> <td>-----</td> <td> </td> </tr> <tr> <td></td> <td>2</td> </tr> <tr> <td>TR 39</td> <td> </td> </tr> <tr> <td></td> <td>1989</td> </tr> <tr> <td></td> <td>TR 37</td> </tr> </table> | T32N | R11E | TR 38 | | | 1 | ----- | | | 2 | TR 39 | | | 1989 | | TR 37 |
| T32N | R11E | | | | | | | | | | | | | | | | |
| TR 38 | | | | | | | | | | | | | | | | | |
| | 1 | | | | | | | | | | | | | | | | |
| ----- | | | | | | | | | | | | | | | | | |
| | 2 | | | | | | | | | | | | | | | | |
| TR 39 | | | | | | | | | | | | | | | | | |
| | 1989 | | | | | | | | | | | | | | | | |
| | TR 37 | | | | | | | | | | | | | | | | |
| | from which | | | | | | | | | | | | | | | | |
| | <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, at the witness cor. point, for a reference monument, bears N. 89°06' E., 9.99 ft. dist., with brass cap mkd. T32N R11E 1-38 2-39 RM 9.99 FT TO COR 1989, and an arrow pointing to the cor. Bury the original witness cor. stone alongside the stainless steel post. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> | | | | | | | | | | | | | | | | |
| | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> | | | | | | | | | | | | | | | | |
| | <p>Cor. is located on E. edge of wash, 114 lks. wide, 10 ft. deep, drains SW.</p> | | | | | | | | | | | | | | | | |
| | <p>Thence N. 0°12' W., on line 1-2, identical with a portion of line 3-4, Tract 37.</p> | | | | | | | | | | | | | | | | |
| | <p>Over rolling and broken land.</p> | | | | | | | | | | | | | | | | |
| 5.10 | Intersect the E. and W. center line of sec. 32. | | | | | | | | | | | | | | | | |
| 6.785 | Intersection the center line of U.S. Highway 160. | | | | | | | | | | | | | | | | |
| 10.085 | Cor. No. 2, identical with Cor. No. 3, Tract 37, hereinbefore described. | | | | | | | | | | | | | | | | |
| | ----- | | | | | | | | | | | | | | | | |
| | <p>Thence S. 88°53' W., on line 2-3.</p> | | | | | | | | | | | | | | | | |
| | <p>Over gently rolling land.</p> | | | | | | | | | | | | | | | | |
| 0.965 | <p>Point for a witness point at intersection with the N. and S. center line of the NE 1/4 of sec. 32.</p> | | | | | | | | | | | | | | | | |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> | | | | | | | | | | | | | | | | |

Dependent Resurvey of Certain Tracts,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <div style="text-align: center;"> <p>T32N R11E WP E S 32 ----- E TR 38 1989</p> </div> |
| | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| 1.04 | <p>W. right-of-way line of U.S. Highway 160, bears NE and SW.</p> |
| 1.71 | <p>W. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, bears NE and SW.</p> |
| 19.865 | <p>Cor. No. 3, monumented with a blue limestone, 15 x 6 x 6 ins., firmly set, projecting 3 ins. above the ground, mkd. 3 over 38 on E. face.</p> |
| | <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <div style="text-align: center;"> <p>T32N R11E S 32 ┌───┐ │ 3 └───┘ TR 38 1989</p> </div> |
| | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| | <p>Bury the stone alongside the cor.</p> |
| | <p style="text-align: center;">-----</p> |
| | <p>Thence S. 0°16' E., on line 3-4.</p> |
| | <p>Over rolling and broken land.</p> |
| 4.56 | <p>Point for a witness point at intersection with the E. and W. center line of sec. 32.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |

Dependent Resurvey of Certain Tracts,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| | |
|--------|---|
| CHAINS | <div style="text-align: center; margin-bottom: 20px;"> <p>T32N R11E WP S 32 C ——— C TR 38 1989</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, N. of the cor.</p> <p>7.90 S. rim of mesa, 100 ft. high, bears E. and W.</p> <p>10.01 Point for Cor. No. 4, identical with Cor. No. 2, Tract 40, and Cor. No. 3, Tract 39, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-bottom: 20px;"> <p>T32N R11E S 32 TR 38 4 ——— 2 3 TR 40 TR 39 1989</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, an iron rod of unknown origin, 1/8 in. diam., 24 ins. long, firmly set, projecting 12 ins. above the ground, bears N. 56°39' E., 56 lks. dist. Bury alongside the cor.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, N. of the cor.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>Thence N. 89°06' E., on line 4-1, identical with line 3-2, Tract 39.</p> <p>Over rolling land.</p> |
|--------|---|

Dependent Resurvey of Certain Tracts,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| | | | | | | | | | | | | | | | |
|--------|---|------|------|-------|-------|---|---|-------|--|---|---|-------|-------|------|--|
| CHAINS | <p>5.75 N. right-of-way line of U.S. Highway 160, parallels highway.</p> <p>6.12 N. right-of-way fence of U.S. Highway 160, parallels highway.</p> <p>13.34 Intersect the center line of U.S. Highway 160, asphalt surfaced, 54 lks. wide, bears NE, in curve to the left.</p> <p>15.40 Power line, bears NE and SW.</p> <p>15.90 S. right-of-way line of U.S. Highway 160, parallels highway.</p> <p>15.93 S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.</p> <p>18.845 Intersect the N. and S. center line of the SE 1/4 of sec. 32. Not monumented.</p> <p>19.855 Cor. No. 1, identical with Cor. No. 2, Tract 39, point of beginning.</p> <hr/> <p style="text-align: center;">Tract 39</p> <hr/> <p>From the point for Cor. No. 1, Tract 39, identical with Cor. No. 2, Tract 42, Cor. No. 3, Tract 43, and Cor. No. 4, Tract 55, at proportionate position; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 10px;">T32N</td> <td style="padding: 2px 10px;">R11E</td> </tr> <tr> <td style="padding: 2px 10px;">TR 39</td> <td style="padding: 2px 10px;">TR 55</td> </tr> <tr> <td style="padding: 2px 10px; text-align: center;">1</td> <td style="padding: 2px 10px; text-align: center;">4</td> </tr> <tr> <td colspan="2" style="padding: 2px 10px; text-align: center;">-----</td> </tr> <tr> <td style="padding: 2px 10px; text-align: center;">2</td> <td style="padding: 2px 10px; text-align: center;">3</td> </tr> <tr> <td style="padding: 2px 10px;">TR 42</td> <td style="padding: 2px 10px;">TR 43</td> </tr> <tr> <td colspan="2" style="padding: 2px 10px; text-align: center;">1989</td> </tr> </table> <p>Set a steel fence post N. of the cor.</p> | T32N | R11E | TR 39 | TR 55 | 1 | 4 | ----- | | 2 | 3 | TR 42 | TR 43 | 1989 | |
| T32N | R11E | | | | | | | | | | | | | | |
| TR 39 | TR 55 | | | | | | | | | | | | | | |
| 1 | 4 | | | | | | | | | | | | | | |
| ----- | | | | | | | | | | | | | | | |
| 2 | 3 | | | | | | | | | | | | | | |
| TR 42 | TR 43 | | | | | | | | | | | | | | |
| 1989 | | | | | | | | | | | | | | | |

Dependent Resurvey of Certain Tracts,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | | | |
|--------|--|-------|-------|--|---|--|---|--|-------|--|------|
| | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Thence N. 0°03' E., on line 1-2, identical with line 3-4, Tract 55.</p> <p>Over nearly level to rolling land.</p> | | | | | | | | | | |
| 0.12 | Barbed wire fence, 3 strand, bears E. and W. | | | | | | | | | | |
| 5.00 | <p>Point for Cor. No. 3, Tract 55, identical with Cor. No. 4, Tract 54, at proportionate dist.; there is no remaining evidence of original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T32N R11E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">TR 39</td> <td style="padding: 0 5px;">TR 54</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">4</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">3</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">TR 55</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">1989</td> </tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post N. of the cor.</p> | TR 39 | TR 54 | | 4 | | 3 | | TR 55 | | 1989 |
| TR 39 | TR 54 | | | | | | | | | | |
| | 4 | | | | | | | | | | |
| | 3 | | | | | | | | | | |
| | TR 55 | | | | | | | | | | |
| | 1989 | | | | | | | | | | |
| 5.17 | <p>Barbed wire fence, 3 strand, bears NE and SW.</p> <p>Continue on line 1-2, identical with line 3-4, Tract 54.</p> | | | | | | | | | | |
| 10.00 | <p>Cor. No. 3, Tract 54, identical with Cor. No. 4, Tract 37, hereinbefore described.</p> <p>Continue on line 1-2, identical with a portion of line 3-4, Tract 37.</p> | | | | | | | | | | |
| 20.00 | <p>Cor. No. 2, identical with Cor. No. 1, Tract 38, hereinbefore described.</p> <hr style="width: 20%; margin: 20px auto;"/> | | | | | | | | | | |

Dependent Resurvey of Certain Tracts,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | Thence S. 89°06' W., on line 2-3, identical with Line 1-4, Tract 38. |
| | Over rolling land. |
| 1.01 | Intersect the N. and S. center line of the SE 1/4 of sec. 32. |
| 6.515 | Intersect the center line of U.S. Highway 160. |
| 19.855 | Cor. No. 3, identical with Cor. No. 2, Tract 40, and Cor. No. 4, Tract 38, hereinbefore described. |
| | <hr/> Thence S. 0°16' E., on line 3-4, identical with line 2-1, Tract 40. |
| | Over nearly level land. |
| 0.64 | Barbed wire fence, 3 strand, bears E. and W. |
| 1.76 | N. right-of-way line of U.S. Highway 160, parallels highway. |
| 1.81 | N. right-of-way fence of U.S. Highway 160, barbed wire, 4 strand, parallels highway. |
| 4.895 | Intersect the center line of U.S. Highway 160, asphalt surfaced, 55 lks. wide, bears ENE and WSW. |
| 5.93 | Power line, bears NE and SW. |
| 6.46 | S. right-of-way fence of U.S. Highway 160, barbed wire, 4 strand, parallels highway. |
| 6.48 | S. right-of-way line of U.S. Highway 160, parallels highway. |
| 20.02 | Point for Cor. No. 4, identical with Cor. No. 1, Tract 40, Cor. No. 2, Tract 41, and Cor. No. 3, Tract 42, at proportionate dist.; there is no remaining evidence of the original cor. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |

Dependent Resurvey of Certain Tracts,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | | | | | | | |
|--------|---|------|------|-------|-------|---|---|-------|--|---|---|-------|-------|------|--|
| | <table border="1"> <thead> <tr> <th>T32N</th> <th>R11E</th> </tr> </thead> <tbody> <tr> <td>TR 40</td> <td>TR 39</td> </tr> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">4</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">2</td> <td style="text-align: center;">3</td> </tr> <tr> <td>TR 41</td> <td>TR 42</td> </tr> <tr> <td colspan="2" style="text-align: center;">1989</td> </tr> </tbody> </table> | T32N | R11E | TR 40 | TR 39 | 1 | 4 | ----- | | 2 | 3 | TR 41 | TR 42 | 1989 | |
| T32N | R11E | | | | | | | | | | | | | | |
| TR 40 | TR 39 | | | | | | | | | | | | | | |
| 1 | 4 | | | | | | | | | | | | | | |
| ----- | | | | | | | | | | | | | | | |
| 2 | 3 | | | | | | | | | | | | | | |
| TR 41 | TR 42 | | | | | | | | | | | | | | |
| 1989 | | | | | | | | | | | | | | | |
| | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, an iron rod of unknown origin, 1/8 in. diam., 24 ins. long, firmly set, projecting 2 ins. above the ground, bears N. 39°04' E., 42 1/2 lks. dist. Bury alongside the cor.</p> <p>From this same cor. point, the corner of barbed wire fences, 5 strand, extending N. and S., and 4 strand, extending SE, bears N. 85° E., 5 lks. dist.</p> | | | | | | | | | | | | | | |
| | ----- | | | | | | | | | | | | | | |
| | <p>Thence N. 89°02' E., on line 4-1, identical with line 3-2, Tract 42.</p> <p>Over nearly level land.</p> | | | | | | | | | | | | | | |
| 18.73 | Intersect the N. and S. center line of the SE 1/4 of sec. 32. | | | | | | | | | | | | | | |
| 19.45 | Trail road, bears N. and S. | | | | | | | | | | | | | | |
| 19.59 | Barbed wire fence, 4 strand, bears N. and S. | | | | | | | | | | | | | | |
| 19.745 | Cor. No. 1, identical with Cor. No. 2, Tract 42, Cor. No. 3, Tract 43, and Cor. No. 4, Tract 55, point of beginning. | | | | | | | | | | | | | | |
| | ----- | | | | | | | | | | | | | | |

Dependent Resurvey of Certain Tracts,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| | | | | |
|--------|---|----|--|----|
| CHAINS | Tract 40 | | | |
| 15.125 | <p>From Cor. No. 1, Tract 40, identical with Cor. No. 2, Tract 41, Cor. No. 3, Tract 42, and Cor. No. 4, Tract 39, hereinbefore described.</p> <p>Thence N. 0°16' W., on line 1-2, identical with line 4-3, Tract 39.</p> <p>Over nearly level land.</p> <p>Intersect the center line of U.S. Highway 160.</p> | | | |
| 20.02 | <p>Cor. No. 2, identical with Cor. No. 3, Tract 39, and Cor. No. 4, Tract 38, hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence S. 88°54' W., on line 2-3.</p> <p>Over rolling and broken land.</p> | | | |
| 1.15 | <p>Point for a witness point at intersection with the N. and S. center line of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T32N R11E</p> <p>WP</p> <p>C</p> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">32</td> </tr> </table> <hr style="width: 20%; margin: 5px auto;"/> <p>C</p> <p>TR 40</p> <p>1989</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 4 ft. base, 2 ft. high, N. of the cor.</p> | S | | 32 |
| S | | 32 | | |

Dependent Resurvey of Certain Tracts,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| | |
|--------|--|
| CHAINS | <p>Cor. is located 29 lks. N. of N. edge of wash, 23 lks. wide, 8 ft. deep, drains SE.</p> <p>18.70 Graded road, 38 lks. wide, bears NE and SW.</p> <p>19.795 Point for Cor. No. 3, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T32N R11E</p> <p>S 32</p> <div style="display: inline-block; border-left: 1px solid black; border-bottom: 1px solid black; padding: 0 10px;"> <p style="margin: 0;">3</p> <p style="margin: 0;">TR 40</p> </div> <p style="margin: 0;">1989</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence S. 0°13' E., on line 3-4.</p> <p>Over rolling and broken land.</p> <p>0.60 Graded road, 30 lks. wide, bears NE and SW.</p> <p>7.12 N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.</p> <p>7.30 N. right-of-way line of U.S. Highway 160, parallels highway.</p> <p>10.46 Point for a witness point at intersection with the center line of U.S. Highway 160, bears ENE and WSW. Impracticable to monument.</p> <p>from which</p> <p style="margin-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 16°43' E., 100 ft. dist., with brass cap mkd. T32N R11E WP TR 40 RM 100.00 FT TO COR 1989, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
|--------|--|

Dependent Resurvey of Certain Tracts,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| | | | | | | | | | | | | | | | | | | | |
|--------|--|------|------|--|--|-------|--|--|---|--|------|---|--|--|-------|--|--|--|------|
| CHAINS | <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 16°43' W., 200 ft. dist., with brass cap mkd. T32N R11E WP S32 RM 200.00 FT TO COR 1989, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. point is located 28 lks. S. of the N. edge of pavement, 55 lks. wide.</p> <p>11.40 Power line, bears NE and SW.</p> <p>11.92 S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.</p> <p>12.04 S. right-of-way line of U.S. Highway 160, parallels highway.</p> <p>19.35 Concrete irrigation canal, 8 lks. wide, 3 ft. deep, drains NW.</p> <p>20.03 Point for Cor. No. 4, identical with Cor. No. 3, Tract 41, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 10px;">T32N</td> <td style="padding: 0 10px;">R11E</td> <td></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 5px;">TR 40</td> <td></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 5px;">4</td> <td></td> </tr> <tr> <td style="padding: 0 10px;">S 32</td> <td style="border-left: 1px solid black; padding-left: 5px;">3</td> <td style="border-top: 1px solid black; padding-top: 2px;"></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 5px;">TR 41</td> <td></td> </tr> <tr> <td></td> <td></td> <td style="text-align: center;">1989</td> </tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, an iron rod of unknown origin, 1/8 ins. diam., 24 ins. long, firmly set, projecting 3 ins. above the ground, bears N. 27°43' E., 62 1/2 lks. dist. Bury alongside the cor.</p> <p>From this same cor. point, a cor. of barbed wire fences, 5 strand, extending N. and SE, bears S. 40° E., 7 1/2 lks. dist.</p> | T32N | R11E | | | TR 40 | | | 4 | | S 32 | 3 | | | TR 41 | | | | 1989 |
| T32N | R11E | | | | | | | | | | | | | | | | | | |
| | TR 40 | | | | | | | | | | | | | | | | | | |
| | 4 | | | | | | | | | | | | | | | | | | |
| S 32 | 3 | | | | | | | | | | | | | | | | | | |
| | TR 41 | | | | | | | | | | | | | | | | | | |
| | | 1989 | | | | | | | | | | | | | | | | | |

Dependent Resurvey of Certain Tracts,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | Cor. is located 23 lks. N. of trail road, bears SE and NW. |
| | <hr/> Thence N. 88°54' E., on line 4-1, identical with line 3-2, Tract 41. |
| | Over level land. |
| 2.30 | Irrigation canal, 12 lks. wide, 6 ft. deep, drains NW. |
| 9.17 | Barbed wire fence, 5 strand, extends N. and S. |
| 18.54 | Intersect the N. and S. center line of sec. 32. Not monumented. |
| 18.70 | Irrigation canal, 12 lks. wide, 6 ft. deep, drains NW. |
| 19.81 | Cor. No. 1, identical with Cor. No. 2, Tract 41, Cor. No. 3, Tract 42, and Cor. No. 4, Tract 39, point of beginning. |
| | <hr/> <p style="text-align: center;">Tract 41</p> <hr/> |
| | From Cor. No. 1, Tract 41, identical with Cor. No. 4, Tract 42, monumented with a blue limestone, 29 x 12 x 4 ins., laying loose on the surface of the ground, mkd. 4 over 42 on one face and 1 over 41 on another face. This is accepted as the best available evidence of the original cor. position. (Record: 15 x 6 x 5 ins.) |
| | At the cor. point |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. |

Dependent Resurvey of Certain Tracts,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | <table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">T32N</td> <td style="text-align: center;">R11E</td> </tr> <tr> <td style="text-align: center;">TR 41</td> <td style="text-align: center;">TR 42</td> </tr> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">4</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 5</td> </tr> <tr> <td style="text-align: center;">T31N</td> <td style="text-align: center;">R11E</td> </tr> <tr> <td colspan="2" style="text-align: center;">1989</td> </tr> </table> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Deposit the stone in a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <p>From this cor. point, an iron rod of unknown origin, 1/8 in. diam., 24 ins. long, firmly set, projecting 6 ins. above the ground, bears S. 60°44' W., 69 lks. dist. Bury alongside the cor.</p> <p>Cor. is located on N. slope of mesa, bears NE and SW, 20 ft. below rim.</p> <p>Thence N. 0°16' W., on line 1-2, Tract 41, identical with Line 4-3, Tract 42.</p> <p>Over descent to nearly level land.</p> <p>5.90 Base of mesa, 100 ft. high, bears NE and SW.</p> <p>8.80 Wash, 152 lks. wide, 20 ft. deep, drains SW.</p> <p>19.37 Barbed wire fence, 5 strand, bears SE and NW.</p> <p>19.55 Irrigation canal, 12 lks. wide, 4 ft. deep, drains NW.</p> <p>20.02 Cor. No. 2, identical with Cor. No. 1, Tract 40, Cor. No. 3, Tract 42, and Cor. No. 4, Tract 39, hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence S. 88°54' W., on line 2-3, identical with line 1-4, Tract 40.</p> | T32N | R11E | TR 41 | TR 42 | 1 | 4 | ----- | | S 5 | | T31N | R11E | 1989 | |
|--------|---|------|------|-------|-------|---|---|-------|--|-----|--|------|------|------|--|
| T32N | R11E | | | | | | | | | | | | | | |
| TR 41 | TR 42 | | | | | | | | | | | | | | |
| 1 | 4 | | | | | | | | | | | | | | |
| ----- | | | | | | | | | | | | | | | |
| S 5 | | | | | | | | | | | | | | | |
| T31N | R11E | | | | | | | | | | | | | | |
| 1989 | | | | | | | | | | | | | | | |

Dependent Resurvey of Certain Tracts,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | |
|--------|---|------|-----------|------|-------|-----|---|------|--|
| | Over level land. | | | | | | | | |
| 1.27 | Intersect the N. and S. center line of sec. 32. | | | | | | | | |
| 19.81 | Cor. No. 3, identical with Cor. No. 4, Tract 40, hereinbefore described. | | | | | | | | |
| | <hr/> Thence S. 0°13' E., on line 3-4. | | | | | | | | |
| | Over nearly level cultivated land. | | | | | | | | |
| 14.10 | The closing cor. of secs. 5 and 32, on the S. bdy. of the Tp., hereinbefore described. | | | | | | | | |
| | Thence in sec. 5, T. 31 N., R. 11 E. | | | | | | | | |
| 20.03 | Point for Cor. No. 4, at proportionate dist.; there is no remaining evidence of the original cor. | | | | | | | | |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. | | | | | | | | |
| | <table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 10px;">T31N</td> <td style="border-left: 1px solid black; padding-left: 10px;">T32N R11E</td> </tr> <tr> <td style="padding-right: 10px;">R11E</td> <td style="border-left: 1px solid black; padding-left: 10px;">TR 41</td> </tr> <tr> <td style="padding-right: 10px;">S 5</td> <td style="border-left: 1px solid black; padding-left: 10px;">4</td> </tr> <tr> <td colspan="2" style="text-align: center;">1989</td> </tr> </table> | T31N | T32N R11E | R11E | TR 41 | S 5 | 4 | 1989 | |
| T31N | T32N R11E | | | | | | | | |
| R11E | TR 41 | | | | | | | | |
| S 5 | 4 | | | | | | | | |
| 1989 | | | | | | | | | |
| | Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. | | | | | | | | |
| | Raise a mound of stone, 2 ft. base, 1 ft. high, N. of the cor. | | | | | | | | |
| | From this cor. point, an iron pipe of unknown origin, 2 ins. diam., 30 ins. long, firmly set, projecting 18 ins. above the ground, bears S. 88°48' W., 55 lks. dist. Bury alongside the cor. | | | | | | | | |
| | Cor. is located 6 lks. N. of a barbed wire fence, 4 strand, bears E. and W. | | | | | | | | |
| | <hr/> Thence N. 88°52' E., on line 4-1, Tract 41. | | | | | | | | |
| | Over rolling land. | | | | | | | | |

Dependent Resurvey of Certain Tracts,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| | | | | | | | | | | | | | | | |
|--------|--|------|------|-------|-------|---|---|-------|--|-----|--|------|------|------|--|
| CHAINS | | | | | | | | | | | | | | | |
| 12.45 | Barbed wire fence, 4 strand, bears NE and SW, at base of mesa, 100 ft. high, bears N. and S. | | | | | | | | | | | | | | |
| 13.40 | Top of ridge, bears SE and NW. | | | | | | | | | | | | | | |
| 19.83 | Cor. No. 1, identical with Cor. No. 4, Tract 42, point of beginning. | | | | | | | | | | | | | | |
| | Tract 42 | | | | | | | | | | | | | | |
| | <p>From the point for Cor. No. 1, Tract 42, identical with Cor. No. 4, Tract 43, at proportionate position; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">T32N</td> <td style="text-align: center;">R11E</td> </tr> <tr> <td style="text-align: center;">TR 42</td> <td style="text-align: center;">TR 43</td> </tr> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">4</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 5</td> </tr> <tr> <td style="text-align: center;">T31N</td> <td style="text-align: center;">R11E</td> </tr> <tr> <td colspan="2" style="text-align: center;">1989</td> </tr> </table> <p>from which</p> <p style="padding-left: 40px;">An X BO, chiseled on the NW face of a sandstone cliff, 5 ft. above the ground, bears S. 28 1/4° E., 31 lks. dist.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Thence N. 0°03' E., on line 1-2, identical with line 3-4, Tract 43.</p> <p>Over rolling land.</p> | T32N | R11E | TR 42 | TR 43 | 1 | 4 | ----- | | S 5 | | T31N | R11E | 1989 | |
| T32N | R11E | | | | | | | | | | | | | | |
| TR 42 | TR 43 | | | | | | | | | | | | | | |
| 1 | 4 | | | | | | | | | | | | | | |
| ----- | | | | | | | | | | | | | | | |
| S 5 | | | | | | | | | | | | | | | |
| T31N | R11E | | | | | | | | | | | | | | |
| 1989 | | | | | | | | | | | | | | | |
| 2.20 | Base of mesa, 150 ft. high, bears NE and SW. | | | | | | | | | | | | | | |

Dependent Resurvey of Certain Tracts,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 6.45 | Moenkopi Wash, 230 lks. wide, 15 ft. deep, drains NW. |
| 15.88 | Barbed wire fence, 5 strand, bears NE and SW. |
| 20.00 | Cor. No. 2, identical with Cor. No. 1, Tract 39, Cor. No. 3, Tract 43, and Cor. No. 4, Tract 55, heretofore described. |
| | <hr/> Thence S. 89°02' W., on line 2-3, identical with line 4-1, Tract 39. |
| | Over nearly level land. |
| 1.015 | Intersect the N. and S. center line of the SE 1/4 of sec. 32. |
| 19.745 | Cor. No. 3, identical with Cor. No. 1, Tract 40, Cor. No. 2, Tract 41, and Cor. No. 4, Tract 39, hereinbefore described. |
| | <hr/> Thence S. 0°16' E., on line 3-4, identical with line 1-2, Tract 41. |
| | Over nearly level land. |
| 20.02 | Cor. No. 4, identical with Cor. No. 1, Tract 41, hereinbefore described. |
| | <hr/> Thence N. 88°58' E., on line 4-1. |
| | Over rolling and broken land. |
| 19.635 | Cor. No. 1, identical with Cor. No. 4, Tract 43, point of beginning. |
| | <hr/> |

Dependent Resurvey of a Portion of Certain Tracts,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| | | | | | | | | | | | | | |
|--------|---|------|------|-------|-------|---|---|-----|--|------|------|------|--|
| CHAINS | Tract 43 | | | | | | | | | | | | |
| 9.975 | <p>From cor. No. 4, identical with Cor. No. 1, Tract 42, hereinbefore described.</p> <p>Thence N. 89°09' E., on line 4-1, in sec. 5, T. 31 N., R. 11 E.</p> <p>Over rolling land.</p> <p>Cor. No. 1, identical with Cor. No. 4, Tract 60, monumented with a blue limestone, 21 x 6 x 4 ins., firmly set, projecting 5 ins. above the ground, mkd. 1 over 4 on N. face, 4 over 60 on E. face, and 1 43 on W. face. (Record: 16 x 6 x 6 ins.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T32N</td> <td style="padding: 0 10px;">R11E</td> </tr> <tr> <td style="padding: 0 10px;">TR 43</td> <td style="padding: 0 10px;">TR 60</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">1</td> <td style="padding: 0 10px;">4</td> </tr> <tr> <td colspan="2" style="text-align: center; border-top: 1px solid black;">S 5</td> </tr> <tr> <td style="padding: 0 10px;">T31N</td> <td style="padding: 0 10px;">R11E</td> </tr> <tr> <td colspan="2" style="text-align: center;">1989</td> </tr> </table> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Bury the stone alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence N. 0°38' E., on line 1-2, identical with line 3-4, Tract 60.</p> <p>Over rolling land.</p> | T32N | R11E | TR 43 | TR 60 | 1 | 4 | S 5 | | T31N | R11E | 1989 | |
| T32N | R11E | | | | | | | | | | | | |
| TR 43 | TR 60 | | | | | | | | | | | | |
| 1 | 4 | | | | | | | | | | | | |
| S 5 | | | | | | | | | | | | | |
| T31N | R11E | | | | | | | | | | | | |
| 1989 | | | | | | | | | | | | | |

Dependent Resurvey of a Portion of Certain Tracts,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| | | | | | | | | | | | | | |
|----------------------------|---|------|------|--|-------|--|---|-------|---|--|-------|--|------|
| <p>CHAINS</p> <p>10.03</p> | <p>Cor. No. 3, Tract 60, identical with Cor. No. 4, Tract 59, monumented with a blue limestone, 17 x 15 x 5 ins., laying loose on the surface of the ground, mkd. 4 over 59 on one face, 3 over 60 on another face, and 443 on another face. This is accepted as the best available evidence of the original cor. position. (Record: 16 x 6 x 6 ins.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding-right: 10px;">T32N</td> <td style="border-left: 1px solid black; padding-left: 10px;">R11E</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px;">TR 59</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px;">4</td> </tr> <tr> <td style="padding-right: 10px;">TR 43</td> <td style="border-left: 1px solid black; padding-left: 10px;">3</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px;">TR 60</td> </tr> <tr> <td></td> <td style="padding-left: 10px;">1989</td> </tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Bury the stone alongside the cor.</p> <hr/> <p style="text-align: center;">Tract 53</p> <hr/> <p>From the point for Cor. No. 2, Tract 53, determined at record bearing and dist. from Cor. No. 3, Tract 53, there is no remaining evidence of the original cor.</p> | T32N | R11E | | TR 59 | | 4 | TR 43 | 3 | | TR 60 | | 1989 |
| T32N | R11E | | | | | | | | | | | | |
| | TR 59 | | | | | | | | | | | | |
| | 4 | | | | | | | | | | | | |
| TR 43 | 3 | | | | | | | | | | | | |
| | TR 60 | | | | | | | | | | | | |
| | 1989 | | | | | | | | | | | | |

Dependent Resurvey of Certain Tracts,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| | |
|--------|---|
| CHAINS | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T32N R11E S 33 2 TR 53 1989</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in a graded road, 30 lks. wide, bears SE and NW. Thence S. 89°16' W., along line 2-3.</p> <p>1.20 The closing cor. of secs. 32 and 33, hereinbefore described.</p> <p>10.11 Barbed wire fence, 3 strand, bears N. and S.</p> <p>10.18 Cor. No. 3, on line 1-2, Tract 37, hereinbefore described.</p> <hr/> <p style="text-align: center;">Subdivision of Certain Sections, T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Section 17</p> <hr/> <p>From the 1/4 sec. cor. of secs. 17 and 20. N. 0°22' E., on the N. and S. center line of sec. 17. Over rolling sand dunes.</p> <p>12.90 Graded road, 53 lks. wide, bears E. and W.</p> |
|--------|---|

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 19.99 | <p>Point for the center S 1/16 cor. of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R11E C S1/16 S17 C 1988</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, an iron rod of unknown origin, 1 in. diam., 60 ins. long, firmly set, projecting 8 ins. above the ground, bears S. 56° W., 14 lks. dist. Bury alongside the cor.</p> |
| 39.98 | <p>Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E. and W. center line of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, on top of a steel fence post, with brass cap mkd.</p> <p style="text-align: center;">T32N R11E C1/4 S17 1988</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> |
| 47.10 | Power line, bears SE and NW. |
| 47.75 | Trail road, bears SE and NW. |
| 79.89 | The 1/4 sec. cor. of secs. 8 and 17. |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------------------|--|
| | From the 1/4 sec. cor. of secs. 16 and 17. |
| | N. 89°55' W., on the E. and W. center line of sec. 17. |
| | Over rolling sand dunes. |
| 11.40 | Graded road, 38 lks. wide, bears NE and SW. |
| 33.50 | Trail road, bears SE and NW. |
| 34.00 | Power line, bears SE and NW. |
| 39.93 | The center 1/4 sec. cor. of sec. 17. |
| 80.22 | The 1/4 sec. cor. of secs. 17 and 18. |
| SW 1/4, Section 17 | |
| | From the center S 1/16 sec. cor. of sec. 17. |
| | N. 89°54' W., on the E. and W. center line of the SW 1/4 of sec. 17. |
| | Over rolling sand dunes. |
| 40.16 | The S 1/16 sec. cor of secs. 17 and 18. |
| Section 19 | |
| | From the 1/4 sec. cor. of secs. 19 and 30. |
| | N. 0°01' W., on the N. and S. center line of sec. 19. |
| | Over rolling land. |
| 40.035 | Point for the center 1/4 sec. cor., at intersection with the E. and W. center line of sec. 19. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T32N R11E C1/4 S19 1988 |
| | Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|---|---|
| 62.50 | Graded road, 38 lks. wide, bears SE and NW. |
| 67.00 | Graded road, 38 lks. wide, bears SE, in curve to the left. |
| 80.07 | The 1/4 sec. cor. of secs. 18 and 19. |
| <hr/> | |
| From the 1/4 sec. cor. of secs. 19 and 20. | |
| N. 89°59' W., on the E. and W. center line of sec. 19. | |
| Over rolling land. | |
| 3.10 | Graded road, 38 lks. wide, bears N. and S. |
| 16.30 | Graded road, 38 lks. wide, bears SE and NW. |
| 20.005 | Point for the center E 1/16 sec. cor. of sec. 19. |
| Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. | |
| T32N R11E E1/16 C———C S19 1988 | |
| Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. | |
| 40.01 | The center 1/4 sec. cor. of sec. 19. |
| 78.28 | The 1/4 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp. |
| <hr/> NE 1/4, Section 19 <hr/> | |
| From the center E 1/16 sec. cor. of sec. 19. | |
| N. 0°01' W., on the N. and S. center line of the NE 1/4 of sec. 19. | |
| Over gently rolling land. | |
| 2.40 | Graded road, 38 lks. wide, bears SE and NW. |
| 40.02 | The E 1/16 sec. cor. of secs. 18 and 19. |
| <hr/> | |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | SE 1/4, Section 19 |
|--------|---|
| 40.02 | <p>From the E 1/16 sec. cor. of secs. 19 and 30.</p> <p>N. 0°01' W., on the N. and S. center line of the SE 1/4 of sec. 19.</p> <p>Over rolling land.</p> <p>The center E 1/16 sec. cor. of sec. 19.</p> |
| | <p style="text-align: center;">Section 20</p> <hr/> <p>From the 1/4 sec. cor. of secs. 20 and 29, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. as described in the official record of the 1962 resurvey of a portion of the subdivisional lines, T. 32 N., R. 11 E..</p> <p>Not remonumented.</p> <p>Cor. is located at the SE cor. of wood framed garage building, 48 x 28.5 ft., long side bears W.</p> <p>N. 0°02' W., on the N. and S. center line of sec. 20.</p> <p>Over nearly level land.</p> <p>0.43 Intersect S. side of Tuba City Auto Parts Store, a concrete block building, 84 x 30 ft., the SE cor. bears East, 9 lks. dist., long side bears N.</p> <p>2.75 N. edge of graded parking lot, bears E. and W.</p> <p>2.95 Birch Lane, a paved road, 39 lks. wide, bears E. and W.</p> <p>3.20 Power line, bears E. and W.</p> <p>3.32 Intersect S. side of a concrete block building, 37.4 x 14.5 ft., the SE cor. bears East, 20 lks. dist., the long side bears East.</p> <p>12.10 Power line, bears E. and W.</p> <p>12.40 Cedar Avenue, a paved road, 48 lks. wide, bears E. and W.</p> <p>14.46 Intersect S. side of loading dock, of old hospital facility, a concrete block building, the SE cor. of the loading dock, bears East 9 lks. dist.</p> |

Subdivision of Certain Sections,
T. 32 N., R. 11 E.,

| CHAINS | |
|--------|--|
| 20.35 | Elm Street, a paved road, 45 lks. wide, bears E. and W. |
| 28.50 | Power line, bears E. and W. |
| 28.80 | E. Fir Avenue, a paved road, 38 lks. wide, bears E. and W. |
| 30.93 | Intersect the S. side of E. wing of Tuba City Elementary School, a concrete block building, the E. wing measuring 66 x 66 ft., the SE cor. bears East, 68 lks. dist. |
| 34.46 | Intersect S. side of N. wing of a school building, a concrete block building, the N. wing measuring 237 x 62 ft., the SW cor. of the N. wing bears NW, 20 lks. dist., long side bears SE |
| 40.04 | Point for the center 1/4 sec. cor. of sec. 20., at intersection with the E. and W. center line of sec. 20. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T32N R11E C1/4 S20 1988 |
| | Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. |
| 40.70 | Grand View Street, a paved road, 30 lks. wide, bears E. and W. |
| | Thence enter residential area. |
| 54.00 | Thence ascend into sand dunes. |
| 80.06 | The 1/4 sec. cor. of secs. 17 and 20. |
| | From the 1/4 sec. cor. of secs. 20 and 21. |
| | N. 89°55' W., on the E. and W. center line of sec. 20. |
| | Over gently rolling land. |
| 2.93 | Barbed wire fence, 4 strand, bears NE and SW. |
| 6.30 | Landing strip, asphalt surfaced, 76 lks. wide, bears NE and SW. |
| 9.51 | Barbed wire fence, 4 strand, bears NE and SW. |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--|---|
| 11.00 | Chain link fence, bears NE and SW. |
| 16.89 | Chain link fence, bears N. and S. |
| 40.02 | The center 1/4 sec. cor. of sec. 20. |
| 43.15 | Main Street, a paved road, 53 lks. wide, bears N. and S. |
| 43.68 | Chain link fence, on E. edge of school playground, bears N. and S. |
| 53.75 | Chain link fence, on W. edge of school playground, bears NE and SW. |
| 80.05 | The 1/4 sec. cor. of secs. 19 and 20. |
| Section 21 | |
| From the 1/4 sec. cor. of secs. 21 and 28. | |
| N. 0°01' W., on the N. and S. center line of sec. 21. | |
| Over gently rolling land. | |
| 16.15 | Trail road, bears NE and SW. |
| 40.04 | Point for the center 1/4 sec. cor. of sec. 21, at intersection with the E. and W. center line of sec. 21. |
| Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. | |
| T32N R11E C1/4 S21 1988 | |
| Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. | |
| Raise a mound of stone, 2 ft. base, 1 ft. high, W. of the cor. | |
| 46.65 | Trail road, bears NE and SW. |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|------------|---|
| 80.12 | The 1/4 sec. cor. of secs. 16 and 21. |
| | <hr/> From the 1/4 sec. cor. of secs. 21 and 22. N. 89°56' W., on the E. and W. center line of sec. 21. Over gently rolling land. |
| 4.50 | E. edge of Pasture Canyon Reservoir, bears NE and SW. |
| 14.00 | Trail road on W. edge of Pasture Canyon Reservoir, bears NE and SW. |
| 40.03 | The center 1/4 sec. cor. of sec. 21. |
| 48.00 | Trail road, bears NE and SW. |
| 75.00 | Graded road, 45 lks. wide, bears N. and S. |
| 80.03 | The 1/4 sec. cor. of secs. 20 and 21. |
| Section 28 | |
| | <hr/> From the 1/4 sec. cor. of secs. 28 and 33. N. 0°01' E., on the N. and S. center line of sec. 28. Over gently rolling land. |
| 16.30 | Power line, bears NE and SW. |
| 16.42 | S. right-of-way line of U.S. Highway 160, parallels highway. |
| 16.43 | S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway. |
| 17.565 | Point for a witness point at intersection with the center line of U.S. Highway 160, bears ENE and WSW. Set a railroad spike, flush with the surface of the pavement of U.S. Highway 160, with top mkd. |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| | |
|--------|---|
| CHAINS | <div style="text-align: center; margin-bottom: 20px;"> BLM WP C S 28 C 1988 </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 8°47' E., 75 ft. dist., with brass cap mkd. T32N R11E WP S28 RM 75.00 FT TO COR 1988, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 8°47' W., 200 ft. dist., with brass cap mkd. T32N R11E WP S28 RM 200.00 FT TO COR 1988, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 46 lks. S. of the N. edge of pavement, 72 lks. wide.</p> <p>20.045 Point for the center S 1/16 cor. of sec. 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-bottom: 20px;"> T32N R11E C S1/16 S28 C 1988 </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>20.63 N. right-of-way line of U.S. Highway 160, parallels highway.</p> <p>20.66 Chain link fence, extends NE and SW.</p> <p>20.81 S. edge of paved parking lot of U.S. Post Office, bears NE and SW.</p> |
|--------|---|

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 23.16 | Chain link fence, at N. edge of U.S. Post Office parking lot and S. edge of paved Bureau of Indian Affairs parking lot, bears NE and SW. |
| 28.24 | Chain link fence, at N. edge of Bureau of Indian Affairs parking lot and S. edge of gravel surfaced fire station parking lot, bears NE and SW. |
| 32.70 | N. edge of fire station parking lot, bears SE, in curve to the right. |
| 34.25 | Paved road, 38 lks. wide, bears SE, in curve to the right. |
| 34.61 | Chain link fence, on S. edge of Grey Hills High School complex, bears SE, in curve to the right. |
| 37.70 | <p>Point for a witness point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R11E</p> <p>WP</p> <p>C</p> <p>S 28</p> <p>C</p> <p>1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 3 1/2 lks. S. of a brick wall, bears SSE and NNW.</p> |
| 38.35 | <p>Intersect S. edge of concrete porch of middle dormitory building on the W. side of Grey Hills High School, porch is 18 ft. wide, the SW cor. bears WSW, 4 lks. dist.</p> <p>Thence through Grey Hills High School, a brick structure with overall dimensions of 900 x 400 ft., long axis bears SSE and NNW.</p> |
| 40.09 | Point for the center 1/4 sec. cor., at intersection with the E. and W. center line of sec. 28, impracticable to monument. |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 48.66 | Intersect N. side of auditorium of Grey Hills High School, 66 ft. long, the NE cor. bears ENE, 25 lks. dist. |
| | Thence leave Grey Hills High School. |
| 51.00 | Point for a witness point. |
| | Set a stainless steel post. 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd. |
| | <p style="text-align: center;">T32N R11E WP C S 28 C 1990</p> |
| | Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. |
| 54.21 | Chain link fence, bears SE and NW. |
| 64.55 | East Drive, a paved road, 45 lks. wide, bears NE, in curve to the right. |
| 69.25 | Paved road, 45 lks. wide, bears NE, in curve to the right. |
| 70.10 | Intersect the S. side of a two story wood framed apartment building, approximately 170 x 50 ft., the SW cor. bears SW, 18 lks. dist., the long side bears NE. |
| 80.13 | The 1/4 sec. cor. of secs. 21 and 28. |
| | From the 1/4 sec. cor. of secs. 27 and 28. |
| | N. 89°56' W., on the E. and W. center line of sec. 28. |
| | Over gently rolling land. |
| 20.04 | Point for the center E 1/16 sec. cor. of sec. 28. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| | |
|---------------|--|
| <p>CHAINS</p> | <p style="text-align: center;">T32N R11E E1/16 C ——— C S28 1988</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>21.07 Intersect the E. side of an apartment building, a concrete block building, 93.6 x 43 ft., the SE cor. bears SW, 15 lks. dist., the long side bears NE.</p> <p>33.60 Point for a witness point.</p> <p>Set a stainless steel, post, 28 ins. long. 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R11E WP S C ——— C 28 1990</p> <p>Deposit a magnet enclosed in 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 1 1/2 lks. S. of a chain link fence, bears ENE and WSW.</p> <p>34.06 Intersect E. side of southernmost dormitory building on E. side of Grey Hills High School, 51 ft. long, the SE cor. of dormitory bears SSE, 2 lks. dist.</p> <p>Thence through Grey Hills High School, a brick structure with overall dimensions of 900 x 400 ft., long axis bears SSE and NNW.</p> <p>40.08 Point for the center 1/4 sec. cor. of sec. 28.</p> <p>41.11 Intersect W. side of northermost dormitory building on the W. side of Grey Hills High School, 51 ft. long, the NW cor. of dormitory bears NNW, 20 lks. dist.</p> <p>Thence leave Grey Hills High School.</p> <p>41.30 Point for a witness point.</p> |
|---------------|--|

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------------------|---|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 1 in. below the surface of the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T32N R11E WP S C——C 28 1990</p> |
| | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| 42.37 | <p>Intersect E. side of child care center, a brick structure, 57 x 57 ft., the NE cor. bears NNW, 31 lks. dist.</p> |
| 53.46 | <p>Chain link fence, extends SE, in curve to the left.</p> |
| 53.80 | <p>Paved road, 30 lks. wide, bears SE, in curve to the left.</p> |
| 60.12 | <p>Point for the center W 1/16 sec. cor. of sec. 28.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T32N R11E W1/16 C——C S28 1988</p> |
| | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| 80.16 | <p>The 1/4 sec. cor. of secs. 28 and 29.</p> |
| SE 1/4, Section 28 | |
| | <p>From the E 1/16 sec. cor. of secs. 28 and 33.</p> |
| | <p>N. 0°02' W., on the N. and S. center line of the SE 1/4 of sec. 28.</p> |
| | <p>Over rolling land.</p> |
| 0.34 | <p>Intersect S. side of a concrete block house, approximately 51 x 26 ft., the SW cor. bears NW, 35 lks. dist., the long side bears SE.</p> |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 19.40 | Power line, bears NE and SW. |
| 19.51 | S. right-of-way line of U.S. Highway 160, parallels highway. |
| 19.53 | S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway. |
| 20.035 | Point for the SE 1/16 sec. cor. of sec. 28, at intersection with the E. and W. center line of the SE 1/4 of sec. 28. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, to bedrock, encircled with a collar of stone, 3 ft. base, to top, with brass cap mkd. |
| | <p>T32N R11E SE1/16 S28 1988</p> |
| | Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. |
| 20.665 | Point for a witness point at intersection with the center line of U.S. Highway 160, bears ENE and WSW. |
| | Set a railroad spike, flush with the surface of the pavement of U.S. Highway 160, with top mkd. |
| | <p>BLM WP C SE1/4 S28 C 1988</p> |
| | from which |
| | <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 8°48' E., 75 ft. dist., with brass cap mkd. T32N R11E WP S28 RM 75.00 FT TO COR 1988, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 8°48' W., 200 ft. dist., with brass cap mkd. T32N R11E WP S28 RM 200.00 FT TO COR 1988, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 28 lks. S. of the N. edge of pavement, 57 lks. wide.</p> |
| 23.70 | N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway. |
| 23.73 | N. right-of-way line of U.S. Highway 160, parallels highway. |
| 40.07 | The center E 1/16 sec. cor. of secs. 21 and 28. |
| | <hr/> <p>From the S 1/16 sec. cor. of secs. 27 and 28.</p> <p>N. 89°58' W., on the E. and W. center line of the SE 1/4 of sec. 28.</p> <p>Over rolling land.</p> |
| 16.10 | Power line, bears NE and SW. |
| 16.67 | S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway. |
| 16.70 | S. right of way line of U.S. Highway 160, parallels highway. |
| 20.055 | The SE 1/16 sec. cor. of sec. 28. |
| 24.14 | <p>Point for a witness point at intersection with the center line of U.S. Highway 160, bears ENE and WSW.</p> <p>Set a railroad spike, flush with the surface of the pavement of U.S. Highway 160, with top mkd.</p> |
| | <p style="text-align: center;">BLM WP SE1/4 C——C S28 1988</p> |

Subdivision of Certain Sections,,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 8°49' E., 75 ft. dist., with brass cap mkd. T32N R11E WP S28 RM 75.00 FT TO COR 1988, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 8°49' W., 200 ft. dist., with brass cap mkd. T32N R11E WP S28 RM 200.00 FT TO COR 1988, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 28 lks. S. of the N. edge of pavement, 56 lks. wide.</p> |
| 40.115 | The center S 1/16 sec. cor. of sec. 28. |
| | <hr/> SW 1/4, Section 28 <hr/> |
| | <p>From the W 1/16 sec. cor. of secs. 28 and 33.</p> <p>N. 0°03' E., on the N. and S. center line of the SW 1/4 of sec. 28.</p> |
| | Over gently rolling land. |
| 7.10 | Power line, bears NE and SW. |
| 12.32 | S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway. |
| 13.90 | Point for a witness point at intersection with the center line of U.S. Highway 160, hereinafter described. |
| 15.78 | Intersect the S. side of W. wing of Davis Chevrolet Service Dept., a steel frame building, W. wing measures 120 x 40 ft., the SW cor. bears SW, 41 lks. dist., the long side bears NE. |
| 20.025 | <p>Point for the SW 1/16 sec. cor. of sec. 28, at the intersection with the E. and W. center line of the SW 1/4 of sec. 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|-------------------|--|
| | <p>T32N R11E SW1/16 S28 1988</p> |
| | <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| 20.71 | Chain link fence, extends SE and NW. |
| 40.05 | The center W 1/16 sec. cor. of sec. 28. |
| <hr/> | |
| | <p>From the center S 1/16 sec. cor. of sec. 28.</p> <p>N. 89°53' W., on the E. and W. center line of the SW 1/4 of sec. 28.</p> <p>Over gently rolling land.</p> |
| 3.72 | N. right-of-way line of U.S. Highway 160, bears ENE and WSW. |
| 5.80 | Paved entrance road to Toh Nanees Dizi Shopping Center, 41 lks. wide, bears N. and S. |
| 9.80 | S. edge of parking lot, asphalt surfaced, bears NE and SW. |
| 15.00 | W. edge of same parking lot, bears SE and NW. |
| 19.88 | Chain link fence, bears SE and NW. |
| 20.05 | The SW 1/16 sec. cor. of sec. 28. |
| 24.68 | Chain link fence, bears NE and SW. |
| 30.50 | Graded road, 45 lks. wide, bears SE and NW. |
| 40.10 | The S 1/16 sec. cor. of secs. 28 and 29. |
| <hr/> | |
| <p>Section 30</p> | |
| <hr/> | |
| | <p>From the 1/4 sec. cor. of secs. 30 and 31.</p> <p>N. 0°02' E., on the N. and S. center line of sec. 30.</p> <p>Over gently rolling land.</p> |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 0.38 | Barbed wire fence, 5 strand, bears NE and SW. |
| 23.50 | Top of earthen dike, 15 ft. high, bears E. and W. |
| 33.10 | Graded road, 45 lks. wide, bears NE and SW. |
| 39.95 | Point for the center 1/4 sec. cor. of sec. 30, at the intersection with the E. and W. center line of sec. 30. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T32N R11E C1/4 S30 1988 |
| | Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. |
| 41.60 | Power line, bears E. and W. |
| 49.30 | Graded road, 45 lks. wide, bears NE and SW. |
| 80.00 | The 1/4 sec. cor. of secs. 19 and 30. |
| | From the 1/4 sec. cor. of secs. 29 and 30. |
| | S. 89°59' W., on the E. and W. center line of sec. 30. |
| | Over gently rolling land. |
| 1.91 | Intersect E. side of concrete block house, 38 x 20 ft., SE cor. bears S., 9 lks. dist., long side bears N. |
| 8.60 | Power line, bears N. and S. |
| 11.10 | Paved road, 53 lks. wide, bears NE and SW. |
| 36.20 | Graded road, 45 lks. wide, bears NE and SW. |
| 40.03 | The center 1/4 sec. cor. of sec. 30. |
| 78.41 | The 1/4 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp. |

Subdivision of Certain Sections,,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | Section 31 |
|--------|--|
| | <p>From the 1/4 sec. cor. of secs. 6 and 31, on the S. bdy. of the Tp.</p> <p>N. 0°04' W., on the N. and S. center line of sec. 31.</p> <p>Over nearly level land.</p> |
| 3.15 | Barbed wire fence, 5 strand, bears E. and W. |
| 3.25 | Concrete irrigation canal, 7 lks. wide, 2 ft. deep, drains W. |
| 12.50 | Power line, bears NE and SW. |
| 12.56 | S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway. |
| 13.24 | Center line of U.S. Highway 160, asphalt surfaced, 54 lks. wide, bears ENE and WSW. |
| 14.08 | N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway. |
| 19.99 | <p>Point for the center S 1/16 cor. of sec. 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R11E</p> <p>C</p> <p>S1/16 S31</p> <p>C</p> <p>1988</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| 21.55 | Barbed wire fence, 5 strand, bears NE and SW. |
| 22.75 | Trail road, bears NE, in curve to the right. |
| 23.80 | Power line, bears NE and SW. |
| 31.20 | Base of mesa, 100 ft. high, bears NE and SW. |
| 38.30 | Top of spur ridge, bears SE and NW. |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 39.98 | <p>Point for the center 1/4 sec. cor. of sec. 31, at intersection with the E. and W. centerline of sec. 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R11E C1/4 S31 1988</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on steep S. slope of mesa, 25 lks. N. of N. rim of ravine, drains SE.</p> |
| 42.00 | Top of spur ridge, bears SE and NW. |
| 57.40 | S. rim of mesa, 100 ft. high, bears SE and NW. |
| 65.20 | Wash, 225 lks. wide, 30 ft. deep, drains SE. |
| 79.95 | The 1/4 sec. cor. of secs. 30 and 31. |
| 13.50 | <p>From the true point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>N. 89°51' W., on the E. and W. center line of sec. 31.</p> <p>Over rolling and broken land.</p> <p>Base of mesa, 80 ft. high, bears NE and SW.</p> |
| 20.00 | <p>Point for the center E 1/16 sec. cor. of sec. 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R11E E1/16 C——C S31 1988</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| 20.62 | Barbed wire fence, 4 strand, bears SE and NW. |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 24.10 | Base of mesa, 100 ft. high, bears NE and SW. |
| 33.50 | E. rim of spur ridge, 100 ft. high, bears NE and SW. |
| 34.60 | W. rim of same ridge, 100 ft. high, bears NE and SW. |
| 35.90 | Ravine, 76 lks. wide, 30 ft. deep, drains SW. |
| 37.10 | Ravine, 91 lks. wide, 40 ft. deep, drains SW. |
| 40.00 | The center 1/4 sec. cor. of sec. 31. |
| 43.10 | Ravine, 151 lks. wide, 80 ft. deep, drains SE. |
| 51.40 | Top of spur ridge, 80 ft. high, bears NE and SW. |
| 56.40 | Top of spur ridge, 50 ft. high, bears NE and SW. |
| 58.45 | Base of spur ridge. |
| 60.02 | Point for the center W 1/16 sec. cor. of sec. 31. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T32N R11E W1/16 C——C S31 1988</p> |
| | Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. |
| | Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor. |
| | Cor. is located in a canyon, 230 lks. wide, bears NE and SW, 23 lks. W. of a spring, flows SW. |
| 62.40 | Top of spur ridge, 50 ft. high, bears SE and NW. |
| 65.80 | Top of spur ridge, 50 ft. high, bears NE and SE. |
| 75.50 | Top of spur ridge, 50 ft. high, bears NE and SE. |
| 78.44 | The 1/4 sec. cor. of secs. 31 and 36, on the W. bdy. of the Tp. |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | NE 1/4, Section 31 |
|--------|--|
| | From the center E 1/16 sec. cor. of sec. 31. |
| | N. 0°02' W., on the N. and S. center line of the NE 1/4 of sec. 31. |
| | Over rolling land. |
| 14.20 | Base of mesa, 100 ft. high, bears NW and SE. |
| 21.40 | S. rim of mesa, 100 ft. high, bears NE and SW. |
| 39.975 | The E 1/16 sec. cor. of secs. 30 and 31. |
| | SE 1/4, Section 31 |
| | From the E 1/16 sec. cor. of secs. 6 and 31, on the S. bdy. of the Tp. |
| | N. 0°03' W., on the N. and S. center line of the SE 1/4 of sec. 31. |
| | Over nearly level land. |
| 6.05 | Trail road, bears NE and SW. |
| 6.20 | Concrete irrigation canal, 8 lks. wide, 3 ft. deep, drains SW. |
| 6.49 | Barbed wire fence, 4 strand, bears NE and SW. |
| 15.50 | Power line, bears NE and SW. |
| 15.53 | S. right-of-way line of U.S. Highway 160, parallels highway. |
| 15.54 | S. right-of-way fence of U.S. Highway 160, parallels highway. |
| 16.215 | Point for a witness point at intersection with the center line of U.S. Highway 160, bears ENE and WSW. |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Set a railroad spike, flush with the surface of the pavement of U.S. Highway 160, with top mkd.</p> <p style="text-align: center;">BLM WP C SE 1/4 S31 C 1988</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 8°18' E., 45 ft. dist., with brass cap mkd. T32N R11E WP S31 RM 45.00 FT TO COR 1988, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 8°18' W., 55 ft. dist., with brass cap mkd. T32N R11E WP S31 RM 45.00 FT TO COR 1988, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| 17.06 | N. right-of-way line of U.S. Highway 160, parallels highway. |
| 17.07 | N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway. |
| 19.995 | Point for the SE 1/16 sec. cor. of sec. 31, at intersection with the E. and W. center line of the SE 1/4 of sec. 31. |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R11E SE1/16 S31 1988</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| 26.95 | Trail road, bears E. and W. |
| 28.10 | Power line, bears E. and W. |
| 39.99 | The center E 1/16 sec. cor. of sec. 31. |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------------------|--|
| | From the S 1/16 sec. cor. of secs. 31 and 32. |
| | N. 89°51' W., on the E. and W. center line of the SE 1/4 of sec. 31. |
| | Over nearly level land. |
| 0.26 | N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, bears NE and SW. |
| 0.29 | N. right-of-way line of U.S. Highway 160, bears NE and SW. |
| 3.10 | E. edge of parking lot, asphalt surfaced, bears SE and NW. |
| 8.77 | Intersect E. side of Van's Trading Co. Garage, a concrete block building, 128 x 26 ft., the NE cor. bears NW, 75 lks. dist., the long side bears NW. |
| 9.38 | Barbed wire fence, 4 strand, bears SE and NW. |
| 19.995 | The SE 1/16 sec. cor. of sec. 31. |
| 24.70 | Barbed wire fence, 5 strand, bears SE and NW. |
| 39.99 | The center S 1/16 sec. cor. of sec. 31. |
| SW 1/4, Section 31 | |
| | From the W 1/16 sec. cor. of secs. 6 and 31, on the S. bdy. of the Tp., hereinbefore described. |
| | N. 0°05' W., on the N. and S. center line of the SW 1/4 of sec. 31. |
| | Over nearly level land. |
| 9.55 | Power line, bears NE and SW. |
| 9.60 | S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway. |
| 10.28 | Intersect the center line of U.S. Highway 160, asphalt surfaced, 55 lks. wide, bears ENE and WSW. |
| 11.12 | N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway. |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 19.99 | <p>True point for the SW 1/16 sec. cor. of sec. 31., at intersection with the E. and W. center line of the SW 1/4 of sec. 31. Cor. point falls in a hogan, 20 ft. diam., not suitable for a permanent monument.</p> <p>From this cor. point, a point selected for a witness cor. bears S. 89°51 E., 0.795 chs. dist., hereinafter described.</p> |
| 39.98 | <p>The center W 1/16 sec. cor. of sec. 31.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 31.</p> <p>N. 89°51' W., on the E. and W. center line of the SW 1/4 of sec. 31.</p> <p>Over gently rolling land.</p> |
| 3.69 | <p>Barbed wire fence, 5 strand, extends NE and SW.</p> |
| 3.95 | <p>Trail road, bears NE and SW.</p> |
| 7.10 | <p>Power line, bears NE and SW.</p> |
| 7.70 | <p>Top of ridge, 15 ft. high, bears NE and SW.</p> |
| 10.50 | <p>Power line, bears SE and NW.</p> |
| 18.51 | <p>Wire mesh fence, on E. edge of corral, extends N. and S.</p> |
| 19.22 | <p>Point selected for the witness SW 1/16 sec. cor. of sec. 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">WC T32N R11E SW1/16 S31</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">1988</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|------------|---|
| | <p>from which</p> <p>The NE cor. of a wood framed house, 31 x 24.5 ft., bears S. 34 1/2° W., 87 lks. dist., the long side bears SW.</p> <p>The NW cor. of same house, bears S. 47 1/4° W., 128 lks. dist.</p> <p>Cor. is located in a corral.</p> |
| 19.62 | Wood rail fence, on W. edge of corral, extends SE and NW. |
| 20.015 | True point for the SW 1/16 sec. cor. of sec. 31, unsuitable for monumentation. |
| 37.44 | Barbed wire fence, 6 strand, extends NE and SW. |
| 38.45 | The S 1/16 sec. cor. of secs. 31 and 36, on the W. bdy. of the Tp. |
| Section 32 | |
| | <p>From the 1/4 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.</p> <p>N. 0°06' E., on the N. and S. center line of sec. 32.</p> <p>Over rolling land.</p> |
| 2.80 | Moenkopi Wash, 151 lks. wide, 25 ft. deep, drains SW. |
| 13.90 | Barbed wire fence, 5 strand, bears SE and NW. |
| 14.485 | Intersect line 4-1, Tract 40, identical with line 3-2, Tract 41. |
| 27.67 | S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway. |
| 27.69 | S. right-of-way line of U.S. Highway 160, parallels highway. |
| 29.275 | Intersect the center line of U.S. Highway 160, asphalt surfaced, 53 lks. wide, bears ENE and WSW. |
| 30.10 | Base of mesa, 200 ft. high, bears E. and W. |
| 32.28 | N. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway. |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 32.44 | N. right-of-way line of U.S. Highway 160, parallels highway. |
| 34.505 | Witness point at intersection with line 2-3, Tract 40. |
| 36.60 | S. rim of mesa, 200 ft. high, bears E. and W. |
| 39.98 | True point for the center 1/4 sec. cor. of sec. 32, at intersection with the E. and W. center line of sec. 32. Point falls on the W. face of a sandstone ledge, unsuitable for monumentation. From this cor. point, the point selected for a witness cor., bears S. 89°53' E., 0.175 chs. dist., hereinafter described. |
| 46.20 | Top of ridge, 30 ft. high, bears E. and W. |
| 59.96 | Point for the center N 1/16 cor. of sec. 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>T32N R11E</p> <p> C</p> <p>N1/16 S32</p> <p> C</p> <p> 1988</p> </div> |
| | Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. |
| | Set a steel fence post N. of the cor. |
| 67.90 | Wash, 151 lks. wide, 25 ft. deep, drains SE. |
| 79.94 | The 1/4 sec. cor. of secs. 29 and 32. |
| | From the 1/4 sec. cor. of secs. 32 and 33. |
| | N. 89°53' W., on the E. and W. center line of sec. 32. |
| | Over rolling and broken land. |
| 8.985 | Witness point at intersection with line 1-2, Tract 37. |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 18.26 | E. right-of-way line of U.S. Highway 160, parallels highway. |
| 18.99 | Intersect line 3-4, Tract 37, identical with line 2-1, Tract 38. |
| 19.39 | E. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway. |
| 19.98 | Point for the center E 1/16 sec. cor. of sec. 32. |
| | Set a railroad spike, flush with the surface of the pavement of U.S. Highway 160, with top mkd. |
| | T32N R11E E1/16 C——C S32 1988 |
| | Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath each reference monument. |
| | Corner is located in U.S. Highway 160, asphalt surfaced, 57 lks. wide, 19 lks. NW of the SE edge of pavement. |
| 20.10 | Intersect the center line of U.S. Highway 160, bears NE, in curve to the left. |
| 21.80 | Base of mesa, 60 ft. high, bears SE and NW. |
| 22.80 | E. rim of mesa, 60 ft. high, bears SE and NW. |
| 24.02 | W. right-of-way line of U.S. Highway 160, parallels highway. |
| 38.845 | Witness point at intersection with line 3-4, Tract 38. |
| 39.785 | Point selected for the witness cor to the center 1/4 sec. cor. of sec. 32. |
| | Set an aluminum tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, 3 ins. below the surface of bedrock, cemented in place, with top mkd. |
| | WC T32N R11E C1/4 S32 <hr style="width: 10%; margin: 0 auto;"/> 1988 |
| | Deposit a magnet, 1 in. long, 7/8 in. diam., beneath the aluminum tablet. |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------------------|---|
| 39.96 | True point for the center 1/4 sec. cor. of sec. 32. |
| 63.20 | Graded road, 45 lks. wide, bears SE and NW. |
| 65.25 | Power line, bears NE and SW. |
| 68.20 | W. rim of mesa, 150 ft. high, bears N. and S. |
| 79.92 | True point for the 1/4 sec. cor. of secs. 31 and 32. |
| NE 1/4, Section 32 | |
| | From the center E 1/16 sec. cor. of sec. 32. |
| | N. 0°05' E., on the N. and S. center line of the NE 1/4 of sec. 32. |
| | Over rolling land. |
| 0.166 | Point for a witness point at intersection with the center line of U.S. Highway 160, bears NE, in curve to the left. |
| | Set a railroad spike, flush with the surface of the pavement of U.S. Highway 160, with top mkd. |
| | BLM WP C NE1/4 S32 C 1988 |
| | from which |
| | A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 54°32' E., 100 ft. dist., with brass cap mkd. T32N R11E WP S32 RM 100.00 FT TO COR 1989, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 54°32' W., 200 ft. dist., with brass cap mkd. T32N R11E WP S32 RM 200.00 FT TO COR 1988, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 28 lks. SE of the NW edge of pavement, 56 lks. wide.</p> |
| 0.90 | Base of mesa, 40 ft. high, bears NE and SW. |
| 4.965 | Witness point at intersection with line 2-3, Tract 38. |
| 6.40 | W. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway. |
| 6.46 | W. right-of-way line of U.S. Highway 160, parallels highway. |
| 11.70 | Barbed wire fence, 4 strand, bears NE and SW. |
| 19.99 | <p>Point for the NE 1/16 sec. cor. of sec. 32, at intersection with the E. and W. center line of the NE 1/4 of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R11E NE1/16 S32 1988</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>from which</p> <p style="padding-left: 40px;">The SE cor. of a two story wood framed house, with overall dimensions of 54 x 36 ft., bears N. 24 1/4° W., 175 lks. dist., the long side bears SW.</p> <p style="padding-left: 40px;">The SW cor. of same house, bears N. 48° W., 206 1/2 lks. dist.</p> |
| 39.98 | The E 1/16 sec. cor. of secs. 29 and 32. |
| | From the N 1/16 sec. cor. of secs. 32 and 33. |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>N. 89°55' W., on the E. and W. center line of the NE 1/4 of sec. 32.</p> |
| | <p>Over rolling and broken land.</p> |
| 4.40 | <p>Wash, 300 lks. wide, 20 ft. deep, drains SW.</p> |
| 9.20 | <p>E. right-of-way line of U.S. Highway 160, parallels highway.</p> |
| 10.85 | <p>Point for a witness point at intersection with the center line of U.S. Highway 160, bears NNE and SSW.</p> |
| | <p>Set a railroad spike, flush with the surface of the pavement of U.S. Highway 160, with top mkd.</p> |
| | <p style="text-align: center;">BLM WP NE1/4 C——C S32 1988</p> |
| | <p>from which</p> |
| | <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 66°40' E., 100 ft. dist., with brass cap mkd. T32N R11E WP S32 RM 100.00 FT TO COR 1988, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| | <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 66°40' W., 200 ft. dist., with brass cap mkd. T32N R11E WP S32 RM 200.00 FT TO COR 1989, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath each reference monument.</p> |
| | <p>Cor. is located 28 lks. E. of the W. edge of pavement, 55 lks. wide.</p> |
| 12.00 | <p>Paved road, 23 lks. wide, bears NE and SW.</p> |
| 14.13 | <p>W. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, parallels highway.</p> |

Subdivision of Certain Sections,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--|---|
| 14.14 | W. right-of-way line of U.S. Highway 160, parallels highway. |
| 16.80 | Trail road, bears NE and SW. |
| 19.975 | The NE 1/16 sec. cor. of sec. 32. |
| 27.03 | Intersect the E. side of a wood framed house, 66 x 30 ft., the NE cor. bears NW., 60 lks. dist., long side bears NW. |
| 30.30 | Top of earthen dike, 15 ft. high, bears NE and SW. |
| 39.95 | The center N 1/16 sec. cor. of sec. 32. |
| SE 1/4, Section 32 | |
| From the E 1/16 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp. | |
| N. 0°04' E., on the N. and S. center line of the SE 1/4 of sec. 32. | |
| Over nearly level land. | |
| 2.70 | Moenkopi Wash, 300 lks. wide, 30 ft. deep, drains NW. |
| 11.03 | Intersect the S. side of a concrete block house, 57 x 24 ft., the SE cor. bears ESE, 49 lks. dist. the long side bears ESE. |
| 14.895 | Intersect line 4-1, Tract 39, identical with line 3-2, Tract 42. |
| 34.90 | Intersect line 4-1, Tract 38, identical with line 3-2, Tract 39. |
| 37.73 | S. right-of-way line of U.S. Highway 160, bears NE, in curve to the left. |
| 37.89 | S. right-of-way fence of U.S. Highway 160, barbed wire, 5 strand, bears NE, in curve to the left. |
| 40.02 | The center E 1/16 sec. cor. of sec. 32. |

Metes-and-Bounds Survey,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| | |
|--------|--|
| CHAINS | Section 28 |
| | <p>From the witness point on the line between secs. 27 and 28, at intersection with the center line of U.S. Highway 160.</p> <p>From this cor. point, the point for Arizona Dept. of Transportation station no. 22+15.20, bears N. 81°15' E., 3.565 chs. dist., determined from the original right-of-way monuments</p> <p style="padding-left: 40px;">A brass disk, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, flush with the surface of the ground, bears S. 8°46' E., 1.125 chs. dist., with brass disk mkd. ELEV. + STA.</p> <p style="padding-left: 40px;">A brass disk, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, 8 ins. below the surface of the ground, bears N. 8°46' W., 2.995 chs. dist., with brass disk mkd. ELEV. + STA.</p> <p>Thence S. 81°15' W., along the center line of U.S. Highway 160.</p> |
| 11.815 | <p>Point for Arizona Dept. of Transportation station no. 12+00.00, not monumented, determined from the original right-of-way monuments</p> <p style="padding-left: 40px;">A concrete cylinder, 6 ins. diam., firmly set, flush with the surface of the ground, bears S. 8°43' E., 1.135 chs. dist.</p> <p style="padding-left: 40px;">A brass disk, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, projecting 3 ins. above the ground, bears N. 8°43' W., 3.03 chs. dist., with brass disk mkd. ELEV. + STA.</p> <p>Not monumented.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence S. 81°14' W., along the center line of U.S. Highway 160.</p> |
| 8.47 | <p>The witness point at intersection with the N. and S. center line of the SE 1/4 of sec. 28.</p> |
| 12.605 | <p>The witness point at intersection with the E. and W. center line of the SE 1/4 of sec. 28.</p> |

Metes-and-Bounds Survey,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 18.185 | <p>Point for Arizona Dept. of Transportation station no. 0+00.00, determined from the original right-of-way monuments</p> <p>A brass disk, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, flush with the surface of the ground, bears S. 8°49' W., 1.135 chs. dist., with brass disk mkd. ELEV. + STA.</p> <p>A brass disk, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, flush with the surface of the ground, bears N. 8°49' W., 3.03 chs. dist., with brass disk mkd. ELEV. + STA.</p> <p>Not monumented.</p> <hr/> <p>Thence S. 81°10' W., along the center line of U.S. Highway 160.</p> |
| 10.585 | <p>The witness point, at intersection with the N. and S. center line of sec. 28.</p> |
| 24.43 | <p>Arizona Dept. of Transportation sta. no. 16+10.00, identical with the point of curvature of a circular curve to the left, monumented with a nail and tin tag, set flush with the surface of pavement, established by the Arizona Dept. of Transportation in October, 1988.</p> <p>from which the remaining original right-of-way monument</p> <p>A brass disk, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, projecting 2 ins. above the ground, bears S. 9°09' E., 1.515 chs. dist., with brass disk mkd. ELEV. + STA.</p> <hr/> <p>NOTE: The curve data established by the Arizona Dept. of Transportation bet. P.C. sta. 16+10.00 and P.T. sta. 44+99.21 cannot be reconciled with the field measurements of the tangent bearings.</p> <p>A "tailored curve" was calculated which utilizes existing field conditions. A significant difference occurs between the P.T. sta. of the "tailored curve" and the P.T. sta. monumented by Arizona Dept. of Transportation.</p> <p>Thence along a 2°00'19" circular curve to the left, having a radius of 2857.12 ft., on the center line of U.S. Highway 160, the long chord of said arc bears S. 52°17' W., 41.90 chs. dist., a chord of said arc bears S. 76°54' W., 6.545 chs. dist.</p> |

Metes-and-Bounds Survey,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 6.55 | <p>Point for a witness point at intersection with the N. and S. center line of the SW 1/4 of sec. 28.</p> |
| | <p>Thence continuing along the same 2°00'19" circular curve to the left, having a radius of 2857.12 ft., on the center line of U.S. Highway 160, a chord of said arc bears S. 56°23' W., 24.108 chs. dist.</p> |
| 30.98 | <p>Point for a witness point at intersection with the line between secs. 28 and 29.</p> |
| | <hr/> <p>Section 29</p> <hr/> |
| | <p>From the point for a witness point at intersection with the line between secs. 28 and 29, on the center line of U.S. Highway 160.</p> |
| | <p>Thence along a 2°00'19" circular curve to the left, having a radius of 2857.12 ft., on the center line of U.S. Highway 160, a chord of said arc bears S. 39°51' W., 0.638 chs. dist.</p> |
| 0.64 | <p>Point for a witness point at intersection with the line between secs. 29 and 32.</p> |
| | <hr/> <p>Section 32</p> <hr/> |
| | <p>From the point for a witness point at intersection with the line between secs. 29 and 32, on the center line of U.S. Highway 160.</p> |
| | <p>Thence along a 2°00'19" circular curve to the left, having a radius of 2857.12 ft., on the center line of U.S. Highway 160, a chord of said arc bears S. 31°21' W., 12.08 chs. dist.</p> |
| 12.12 | <p>Point of tangency of curve. Not monumented.</p> |
| | <hr/> |
| 0.04 | <p>Thence S. 23°20' W., along the center line of U.S. Highway 160.</p> <p>Arizona Dept. of Transportation sta. no. 44+99.21, identical with the former point of tangency, monumented with a nail and tin tag, established by the Arizona Dept. of Transportation, in October 1988; and is utilized in the course of this survey only for alignment of the center line tangent.</p> |
| | <p>from which the original right-of-way monuments</p> |

Metes-and-Bounds Survey,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>A brass disk, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, flush with the surface of the ground, bears S. 66°43' E., 1.515 chs. dist., with brass disk mkd. ELEV. + STA.</p> |
| | <p>A brass disk, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, projecting 2 ins. above the ground, bears N. 66°43' W., 1.515 chs. dist., with brass disk mkd. ELEV. + STA.</p> |
| 10.52 | <p>Witness point at intersection with the E. and W. center line of the NE 1/4 of sec. 32.</p> |
| 24.75 | <p>Point for Arizona Dept. of Transportation sta. no. 61+31.98, identical with the tangent to spiral, established perpendicular to the tangent bearing of the N. right-of-way line and at record dist. from the remaining original right-of-way monument:</p> |
| | <p>A brass disk, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., loosely set, projecting 9 ins. above the ground, bears N. 66°40' W., 3.03 chs. dist., with brass disk mkd. ELEV. + STA.</p> |
| | <p>At the cor. point</p> |
| | <p>Set a railroad spike, flush with the surface of the pavement of U.S. Highway 160.</p> |
| | <p style="text-align: center;">BLM WP TS 1988</p> |
| | <p>from which</p> |
| | <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 66°40' E., 39 ft. dist., with brass cap mkd. T32N R11E TS S32 RM 39.00 FT TO COR 1988, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> |
| | <p>Cor. is located 29 lks. E. of the W. edge of pavement, 54 lks. wide.</p> |

Metes-and-Bounds Survey,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| | |
|--------|--|
| CHAINS | <p>Thence along a transitional spiral curve to the right, having a full central angle of 49°56.3', a spiral angle of 8°00', and a full tangent of 868.32 ft., on the center line of U.S. Highway 160, the long chord of said spiral bears S. 26°00' W., 6.06 chs. dist., a chord of said spiral bears S. 23°39' W., 2.085 chs. dist.</p> |
| 2.085 | <p>Point for the witness point at intersection with line 2-3, Tract 37.</p> <p>Thence continuing on the same 8°00' spiral curve to the right, on the center line of U.S. Highway 160, a chord of which bears S. 27°00' W., 3.725 chs. dist.</p> |
| 5.81 | <p>Intersect the line 3-4, Tract 37, identical with line 2-1, Tract 38.</p> <p>Thence continuing on the same 8°00' spiral curve to the right, on the center line of U.S. Highway 160, a chord of which bears S. 30°49' W., 0.25 chs. dist.</p> |
| 6.06 | <p>Point for the Arizona Dept. of Transportation sta. no. 65+31.98, identical with spiral to curve, established at record angular deflection and dist. from sta. no. 61+31.98 on the center line of U.S. Highway 160.</p> <p>Set a railroad spike, flush with the surface of the pavement of U.S. Highway 160, with top mkd.</p> <p style="text-align: center;">BLM WP SC 1988</p> <p>Cor. is located 28 lks. E. of the W. edge of pavement, 56 lks. wide.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence along a 4°00'36" circular curve to the right, having a delta angle of 33°56.3', a radius of 1428.78 ft., on the center line of U.S. Highway 160, the long chord of said arc bears S. 48°19' W., 12.635 chs. dist., a chord on said arc bears S. 33°22' W., 1.56 chs. dist.</p> |
| 1.56 | <p>Witness point at intersection with the N. and S. center line of the NE 1/4 of sec. 32.</p> |

Metes-and-Bounds Survey,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Thence continuing along the same 4°00'36" circular curve to the right, on the center line of U.S. Highway 160, a chord of said arc bears S. 35°57' W., 0.205 chs. dist.</p> |
| 1.765 | <p>Intersect the E. and W. center line of sec. 32.</p> |
| | <p>Thence continuing along the same 4°00'36" circular curve to the right, on the center line of U.S. Highway 160, a chord of said arc bears S. 45°59' W., 7.49 chs. dist.</p> |
| 9.29 | <p>Intersect line 4-1, Tract 38, identical with Line 3-2, Tract 39.</p> |
| | <p>Thence continuing along the same 4°00'36" circular curve to the right, on the center line of U.S. Highway 160, a chord of said arc bears S. 60°37' W., 3.525 chs. dist.</p> |
| 12.82 | <p>Point for Arizona Dept. of Transportation sta. no. 73+78.65, identical with curve to spiral, established at record angular deflection and dist. from sta. no. 77+78.65, on the center line of U.S. Highway 160, hereinafter described</p> |
| | <p>At the cor. point</p> <p>Set a railroad spike, flush with the surface of the pavement of U.S. Highway 160, with top mkd.</p> |
| | <p style="text-align: center;">BLM WP CS 1988</p> |
| | <p>Cor. is located 28 lks. S. of the N. edge of pavement, 55 lks. wide.</p> |
| | <p style="text-align: center;">_____</p> <p>Thence along a transitional spiral curve to the right, having a full central angle of 49°56.3', a spiral angle of 8°00', and a full tangent of 868.32 ft., on the center line of U.S. Highway 160, the chord of said spiral bears S. 70°37' W., 6.06 chs. dist.</p> |
| 6.06 | <p>Point for Arizona Dept. of Transportation sta. no. 77+78.65 back and 77+82.63 ahead, identical with the spiral to tangent, established from the original right-of-way monuments</p> <p style="padding-left: 40px;">A brass disk, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, projecting 4 ins. above the ground, bears S. 16°43' E., 1.51 chs. dist., with brass disk mkd. ELEV. + STA.</p> |

Metes-and-Bounds Survey,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>A brass disk, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, 20 ins. below the surface of the ground, bears N. 16°43' W., 3.03 chs. dist., with brass disk mkd. ELEV. + STA.</p> <p>Set a railroad spike, flush with the surface of the pavement of U.S. Highway 160, with top mkd.</p> <p style="text-align: center;">BLM WP ST 1988</p> <p>Cor. is located 28 lks. S. of the N. edge of pavement, 55 lks. wide.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence S. 73°17' W., along the center line of U.S. Highway 160.</p> |
| 4.725 | Intersect line 3-4, Tract 39, identical with line 1-2, Tract 40. |
| 5.955 | Intersect the N. and S. center line of sec. 32. |
| 25.365 | Point for a witness point at intersection with line 3-4, Tract 40. |
| 31.17 | <p>Point for Arizona Dept. of Transportation, sta. no. 98+41.50, identical with the point of curvature, determined from the original right-of-way monuments</p> <p>A brass disk, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, projecting 3 ins. above the ground, bears S. 16°43' E., 1.515 chs. dist., with brass disk mkd. ELEV. + STA.</p> <p>A brass disk, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, projecting 3 ins. above the ground, bears N. 16°43' W., 3.03 chs. dist., with brass disk mkd. ELEV. + STA.</p> <p>Set a railroad spike, flush with the surface of the pavement of U.S. Highway 160, with top mkd.</p> <p style="text-align: center;">BLM WP PC 1988</p> |

Metes-and-Bounds Survey,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Cor. is located 28 lks. S. of the N. edge of pavement, 61 lks. wide.</p> <hr/> <p>Thence along a $1^{\circ}59'59''$ circular curve to the right, having a radius of 2864.99 ft., on the center line of U.S. Highway 160, the chord of said arc bears S. $77^{\circ}29'$ W., 6.38 chs. dist.</p> <p>6.39 Point for Arizona Dept. of Transportation sta. no. 102+63.90 back and 102+97.90 ahead, identical with the point of tangency, established from the original right-of-way monuments</p> <p style="padding-left: 40px;">A brass disk, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, projecting 3 ins. above the ground, bears S. $8^{\circ}17'$ E., 0.68 chs. dist., with brass disk mkd. ELEV. + STA.</p> <p style="padding-left: 40px;">A brass disk, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, projecting 3 ins. above the ground, bears N. $8^{\circ}17'$ W., 0.835 chs. dist., with brass disk mkd. ELEV. + STA.</p> <p>Set a railroad spike, flush with the surface of the pavement of U.S. Highway 160, with top mkd.</p> <p style="text-align: center;">BLM WP PT 1988</p> <p>Cor. is located 28 lks. S. of the N. edge of pavement, 58 lks. wide.</p> <hr/> |
| 9.65 | <p>Witness point at intersection with the line between secs. 31 and 32.</p> <hr/> <p style="text-align: center;">Section 31</p> <hr/> <p>From the witness point at intersection with the line between secs. 31 and 32.</p> <p>Thence S. $81^{\circ}43'$ W., along the center line of U.S. Highway 160.</p> |

Metes-and-Bounds Survey,
T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 3.02 | <p>An Arizona Dept. of Transportation sta., number unknown, not monumented, determined at record angular deflection and dist. from an original right-of-way monument</p> <p style="padding-left: 40px;">A brass disk, 3 ins. diam., set in a concrete cylinder, 6 ins. diam., firmly set, flush with the surface of the ground, bears N. 8°17' W., 0.835 chs. dist., with brass disk mkd. ELEV. + STA.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence S. 81°42' W., along the center line of U.S. Highway 160.</p> |
| 17.19 | <p>The witness point at intersection with the N. and S. center line of the SE 1/4 of sec. 31 and 32.</p> <p>From this cor., an Arizona Dept. of Transportation sta., number unknown, not monumented, bears S. 81°42' W., 13.12 chs. dist., established at record angular deflection and dist. from an original right-of-way monument</p> <p style="padding-left: 40px;">A concrete cylinder, 6 ins. diam., firmly set, flush with the surface of the ground, bears N. 8°18' W., 0.835 chs. dist.</p> <hr style="width: 60%; margin: 10px auto;"/> |

T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The area surveyed is in the vicinity of Tuba City, Arizona. The terrain varies from gently rolling to broken land, with scattered mesas, washes, sand dunes, and sandstone outcrops.

Elevation ranges from 4,500 ft. to 5,000 ft. above sea level. The soil is generally sandy loam, with some exposed bedrock. The vegetation consists of native grasses, greasewood, rabbit brush, sage brush and yucca. Drainage is generally westerly.

Access to the area is provided by U.S. Highway 160 and State Highway 264 with numerous paved and graded roads in the vicinity of Tuba City, and trail roads throughout the remainder of the township.

Permanent residences are located in secs. 16 through 22, and secs. 27 through 34.

Secs. 31, 32, 33 and 34 are used for farming and livestock. The remainder of the sections surveyed are used for residential and business purposes.

There is no evidence of active mining at the present time.

The mean declination throughout the township is 14 1/2° E., with no noticeable differences due to local magnetic attractions.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Navajo Tribal Personnel

| NAMES | CAPACITY |
|-----------------|------------------------|
| Art Brown | Engineering Technician |
| Daniel Bryan | Engineering Technician |
| Aldon Francisco | Engineering Technician |
| Rick McCabe | Engineering Technician |
| Steve Tsosie | Engineering Technician |

BLM PERSONNEL

| | |
|------------------|--------------------|
| Robin T. Mathews | Cadastral Surveyor |
|------------------|--------------------|

CERTIFICATE OF SURVEY

We, William F. Olver and Daniel N. Patterson, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 16th day of March, 1988, we have dependently resurveyed portions of the south and west boundaries, a portion of the subdivisional lines, and certain tracts, and subdivided certain sections, and executed a metes-and-bounds surveys, of Township 32 North, Range 11 East, of the Gila and Salt River Meridian, in the state of Arizona which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Daniel N. Patterson is no longer assigned to this office and is not available for signature.

February 25, 1991
(Date)

William F. Olver
(Chief, Navajo Project Office)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of portions of the south and west boundaries, a portion of the subdivisional lines, and certain tracts, subdivision of certain sections, and metes-and-bounds surveys, of Township 32 North, Range 11 East, Gila and Salt River Meridian, Arizona, executed by William F. Olver and Daniel N. Patterson, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

MAR 6 1991
(Date)

James P. Kelly
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I certify that the foregoing transcript of the field notes of the above-described surveys in T. 32 N., R. 11 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~