

ORIGINAL

1

BOOK 5324

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE

CORRECTIVE DEPENDENT RESURVEY AND DEPENDENT RESURVEY OF PORTIONS OF THE

SOUTH AND WEST BOUNDARIES OF THE SAN CARLOS INDIAN RESERVATION,

AND THE FIRST STANDARD PARALLEL SOUTH

ON THE SOUTH BOUNDARY OF TOWNSHIP 5 SOUTH, RANGE 16 EAST,

AND THE EAST BOUNDARY AND SUBDIVISIONAL LINES OF

TOWNSHIP 6 SOUTH, RANGE 16 EAST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

Duane R. Garoutte , Cadastral Surveyor

William P. Carpender , Cadastral Surveyor

Under special instructions dated March 5 , 1986, approved March 5 , 1986
and supplemental special instructions dated and approved October 9, 1986
_____ , which provided for the surveys included under Group Number
677 and assignment instructions dated March 5 , 1986, and
October 9, 1986.

Survey commenced March 10 , 1986

Survey completed January 20 , 1987

INDEX DIAGRAM

TOWNSHIP 6 SOUTH, RANGE 16 EAST,

26	24	21	20	18	16
6	5	4 63	3 51	2 41	1 32
			62	51	41
7	8	9 61	10 49	11 40	12 31
			59	49	39
18	17	16 58	15 47	14 39	13 28
			57	46	38
19	20	21 55	22 45	23 36	24
			53	43	35
30	29	28	27	26 34	25
31	32	33	34	35	36

BOOK 5324

T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS

The following field notes describe the corrective dependent resurvey and dependent resurvey of portions of the south and west boundaries of the San Carlos Indian Reservation, and the First Standard Parallel South on the south boundary of Township 5 South, Range 16 East, and the east boundary and subdivisional lines of Township 6 South, Range 16 East, Gila and Salt River Meridian, Arizona.

The history of surveys is as follows:

The north (First Standard Parallel South), east, and west boundaries and subdivisional lines were surveyed by John L. Harris in 1877. The south and west boundaries of the San Carlos Indian Reservation were surveyed by Paul Riecker in 1883. The First Standard Parallel South on the south boundary of T 5 S, R 16 E, was resurveyed by Philip Contzen in 1904. The west boundary was resurveyed by William H. Thorn in 1919. The east boundary and a portion of the First Standard Parallel South through Range 16 East was resurveyed by William E. Hiester in 1928. The south boundary of the San Carlos Indian Reservation, a portion of the First Standard Parallel South, through Range 16 East, and portions of the east boundary and subdivisional lines were retraced by Ty White and Raymond F. Moss in 1939. The west boundary of the San Carlos Indian Reservation, a portion of the First Standard Parallel South, through Range 16 East, and a portion of the subdivisional lines were retraced by Dupree R. Averill and G. Marvin Litz in 1946. The south and west boundaries of the San Carlos Indian Reservation were resurveyed by Ray Harpin and Douglas A. Cody in 1973-74.

A field investigation revealed two lines exist over the east 5 miles of the First Standard Parallel South, through Range 16 East. The first survey was executed by John L. Harris in 1877, and the second survey executed by Phillip Contzen in 1904. The Harris line is reestablished as the controlling south boundary of T 5 S, R 16 E, and all evidence of the Contzen cors. along this line is destroyed.

BOOK 5324

T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS

A corrective dependent resurvey was deemed necessary to correct a discrepancy between two prior surveys over the north 3 miles between Townships 6 South, Ranges 16 and 17 East. The first survey was executed by John L. Harris in 1877 and the second survey executed by William E. Hiester in 1928. The Harris line is reestablished as the controlling east boundary of T 6 S, R 16 E, except for a portion of the W bdy. of sec. 18 and a small portion of the W bdy. of sec. 19, T 6 S, R 17 E, within what was originally sec. 13, T 6 S, R 16 E. These portions of secs. 18 and 19 are the only patents to lands outside the San Carlos Indian Reservation. The field notes of the reestablishment of the Hiester line are included with the field notes of T 6 S, R 17 E, executed concurrently under this same group. The 1/4 sec. cor. on the E bdy. of sec. 13 is established on the Hiester line at 40.00 chains in northing from the cor. of secs. 13 and 24.

During the resurvey of the west boundary of the San Carlos Indian Reservation, station 2 Miles plus 2.12 chs. established by Ray Harpin and Douglas A. Cody in 1974, was found to be 1.12 chs. west of its record position. The monument is removed and reset on the San Carlos Indian Reservation line at a suitable location.

The position for the cor. of secs. 15, 16, 21, and 22, T 6 S, R 16 E, accepted by Ty White and Raymond F. Moss in 1939 was considered, but found not in agreement with existing original cors. and local ground conditions, and is not utilized in this survey.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, the Special Instructions dated March 5, 1986, for Group No. 677, Arizona and the Supplemental Instructions dated October 9, 1986.

Preliminary to the resurvey, the lines of the original surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original records. The retracement data were thoroughly verified and only the true line field notes are given herein.

BOOK 5324

T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS

The directions of all lines were determined by observations on a U.S. Coast and Geodetic triangulation network, confirmed by direct solar observations and carried forward by sustained angulation and refer to the true meridian. Distances and angles were measured with a Zeiss Elta 46 electronic instrument.

The geographic position of the southeast corner of section 26, as determined from a tie made to U.S. Coast and Geodetic Survey triangulation station "MALPAIS", located in the NW quarter of section 17, is as follows:

NAD 27: Latitude: 32°52'29.8" N Longitude: 110°40'21.9" W


The mean magnetic declination, as taken from quadrangle map SADDLE Mtn., ARIZ., published in 1949, and photoinspected in 1972, by U.S. Geological Survey is 13° E.

Dependent Resurvey, Portion of the South Boundary,
San Carlos Indian Reservation,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona


Reestablishment of the dependent resurvey executed by
Ray Harpin and Douglas A. Cody in 1973-74

Beginning at AP 45, identical with 41 Miles plus 12.08 chs., on the S bdy. of the San Carlos Indian Reservation in sec. 18, T 6 S, R 17 E, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above a mound of stone, 4 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the S bdy. of the San Carlos Indian Reservation, T 6 S, R 17 E, executed concurrently under this same group.




Dependent Resurvey, Portion of the South Boundary,
San Carlos Indian Reservation,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>The cor. is located in fence, bears N 51 1/2° E and S 51 1/4° W.</p> <p>S 51°16' W, on the S bdy. of the San Carlos Indian Reservation, bet. AP 45 and AP 46.</p> <p>Over rolling mountainous land.</p>
10.25	<p>Intersect the 1877 Harris line on the E bdy. of sec. 13, T 6 S, R 16 E.</p> <p>Point for the closing cor. of secs. 13 and 18, T 6 S, Rs. 16 and 17 E, hereinafter described.</p> <p>From this point the Harris cor. of secs. 12 and 13, T 6 S, R 16 E, bears N 0°29' W, 24.965 chs. dist., hereinafter described.</p> <p>Continue measurement</p>
11.48	<p>Intersect the 1928 Hiester line on the W bdy. of sec. 18, T 6 S, R 17 E.</p> <p>Point for the closing cor. of secs. 13 and 18, T 6 S, Rs. 16 and 17 E, hereinafter described.</p> <p>From this point the Hiester 1/4 sec. cor. of sec. 18, T 6 S, R 17 E, bears S 1°34' E, 13.195 chs. dist., hereinafter described.</p> <p>Continue measurement through sec. 13, T 6 S, R 16 E.</p>
42.04	<p>Station 41 Miles plus 54.12 chs., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>SCIR 41 M + 54.12</p>  <p>T6S R16E 1973</p> </div> <p>The cor. is located in fence, bears NE and SW.</p> <hr style="width: 20%; margin: 0 auto;"/>



Dependent Resurvey, Portion of the South Boundary,
 San Carlos Indian Reservation,
 T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	
	S 51°14' W, beginning new measurement.
42.15	AP 46, identical with 42 Miles plus 16.27 chs., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.
	<div style="text-align: center;"> <p>SCIR AP 46 42 M + 16.27</p>  <p>T6S R16E 1973</p> </div>
	A mound of stone, 4 ft. base, 1 1/2 ft. high, is W of cor.
	The cor. is located in fence, bears NE and SW.
	S 51°51' W, on the S bdy. of the San Carlos Indian Reservation, bet. AP 46 and AP 47.
	Over rolling land.
14.05	Fence cor., from which fences bear NE and E-W.
14.16	Point for the witness point at intersection with the line bet. secs. 13 and 24, hereinafter described.
	From this point the cor. of secs. 13, 14, 23, and 24, bears West, 10.285 chs. dist., hereinafter described.
	Continue measurement through sec. 24.
27.30	Point for the witness point at intersection with the line bet. secs. 23 and 24, hereinafter described.
	From this point the cor. of secs. 13, 14, 23, and 24, bears N 0°19' E, 8.115 chs. dist., hereinafter described.
	Continue measurement through sec. 23.
35.745	Station 42 Miles plus 51.98 chs., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, with brass cap mkd.



Dependent Resurvey, Portion of the South Boundary,
 San Carlos Indian Reservation,
 T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">SCIR 42 M + 51.98</p>  <p style="text-align: center;">T6S R16E 1973</p> <p>A steel fence post is set alongside the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>S 51°48' W, beginning new measurement.</p>
47.06	<p>AP 47, identical with 43 Miles plus 19.03 chs., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">SCIR AP 47 43 M + 19.03</p>  <p style="text-align: center;">T6S R16E 1973</p> <p>A mound of stone, 3 ft. base, 2 ft. high, is W of cor. with a steel fence post set along side.</p> <hr style="width: 80%; margin: auto;"/> <p>S 48°19' W, on the S bdy. of the San Carlos Indian Reservation, bet. AP 47 and AP 48.</p> <p>Over rolling land.</p>
31.095	<p>Station 43 Miles plus 50.12 chs., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">SCIR 43 M + 50.12</p>  <p style="text-align: center;">T6S R16E 1973</p> <p>A steel fence post is set alongside the cor.</p> <hr style="width: 20%; margin: auto;"/>

Dependent Resurvey, Portion of the South Boundary,
 San Carlos Indian Reservation,
 T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	
	S 48°19' W, beginning new measurement.
17.92	Point for the witness point at intersection with the line bet. secs. 22 and 23, hereinafter described.
	From this point the cor. of secs. 22, 23, 26, and 27, bears S 0°17' W, 4.39 chs. dist., hereinafter described.
	Continue measurement through sec. 22.
24.69	Point for the witness point at intersection with the line bet. secs. 22 and 27, hereinafter described.
	From this point the cor. of secs. 22, 23, 26, and 27, bears N 88°43' E, 5.035 chs. dist., hereinafter described.
	Continue measurement through sec. 27.
25.92	Station 43 Miles plus 76.04 chs., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.
	<div style="text-align: center;"> <p>SCIR 43 M + 76.04</p>  <p>T6S R16E 1973</p> </div>
	A steel fence post is set alongside the cor.
	<hr style="width: 20%; margin: auto;"/>
	S 48°18' W, beginning new measurement.
24.17	AP 48, identical with 44 Miles plus 20.21 chs., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd.
	<div style="text-align: center;"> <p>SCIR AP 48 44 M + 20.21</p>  <p>T6S R16E 1973</p> </div>
	A steel fence post is set alongside the cor.
	<hr style="width: 20%; margin: auto;"/>

Dependent Resurvey, Portion of the South Boundary,
San Carlos Indian Reservation,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	
28.305	<p>S 42°54' W, on the S bdy. of the San Carlos Indian Reservation, bet. AP 48 and the Southwest Cor.</p> <p>Station 44 Miles plus 48.51 chs., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>SCIR 44 M + 48.51</p>  <p>T6S R16E 1973</p> </div> <p>A steel fence post is set alongside the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>S 42°53' W, beginning new measurement.</p>
46.71	<p>The Southwest Cor., identical with 45 Miles plus 15.23 chs., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>SCIR 45 M + 15.23</p>  <p>T6S R16E 1973</p> </div> <p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A paloverde, 10 ins. diam., bears N 76° W, 164 1/2 lks. dist., no marks. (Record: 163 lks.)</p> <p>A mound of stone, 4 ft. base, 2 ft. high, is NW of cor. and a steel fence post is set alongside.</p> <p>From this cor., Corner 1, U.S. Mineral Survey 4638, established by Edwin H. Jenkins in 1966, bears N 41°58' E, 2.483 chs. dist., monumented with an iron pipe, 1 3/4 ins. diam., projecting 10 ins. above ground and in a mound of stone, 3 ft. base, 1 ft. high, with lead cap mkd. USMS 4638 1 SFAP 22. An iron pipe, 1 1/4 in. diam., projecting 16 ins. above ground, is alongside.</p> <hr style="width: 60%; margin: auto;"/>

Dependent Resurvey of a Portion of the West Boundary,
 San Carlos Indian Reservation,
 T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS									
	<p style="text-align: center;">Reestablishment of the dependent resurvey executed by Ray Harpin and Douglas A. Cody in 1973-74</p> <hr style="width: 20%; margin: auto;"/> <p>From the Southwest Cor., identical with 45 Miles plus 15.23 chs., hereinbefore described.</p> <p>N 1°07' W, on the W bdy. of the San Carlos Indian Reservation, bet. the Southwest Cor. and the AP, identical with 0 Mile plus 77.31 chs.</p> <p>Over rolling land.</p>								
44.72	<p>Station 0 Mile plus 44.72 chs., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T6S</td> <td style="padding: 0 5px;">SCIR</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">0 M +</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R16E</td> <td style="padding: 0 5px;">44.72</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">1974</td> </tr> </table> </div> <p>A mound of stone, 2 ft. base, 1 ft. high, is E of cor.</p> <hr style="width: 20%; margin: auto;"/>	T6S	SCIR		0 M +	R16E	44.72		1974
T6S	SCIR								
	0 M +								
R16E	44.72								
	1974								
	<p>N 1°08' W, beginning new measurement.</p>								
25.56	<p>Point for the witness point at intersection with the line bet. secs. 22 and 27, hereinafter described.</p> <p>From this point the cor. of secs. 21, 22, 27, and 28, bears S 88°43' W, 0.525 chs. dist., hereinafter described.</p> <p>Continue measurement through sec. 22.</p>								
32.60	<p>AP, identical with 0 Mile plus 77.31 chs., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap erroneously mkd. for R 16 W; the cap is now mkd.</p>								

Dependent Resurvey of a Portion of the West Boundary,
San Carlos Indian Reservation,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS											
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 10px;">T6S</td> <td style="border-left: 1px solid black; padding-left: 10px;">SCIR</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px;">AP</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px;">0 M +</td> </tr> <tr> <td style="padding-right: 10px;">R16E</td> <td style="border-left: 1px solid black; padding-left: 10px;">77.31</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px;">1974</td> </tr> </table> <p>A mound of stone, 3 ft. base, 2 ft. high, is E of cor.</p>	T6S	SCIR		AP		0 M +	R16E	77.31		1974
T6S	SCIR										
	AP										
	0 M +										
R16E	77.31										
	1974										
51.26	<p>N 0°16' W, on the W bdy. of the San Carlos Indian Reservation, bet. the AP, identical with 0 Mile plus 77.31 chs. and Station 1 Mile plus 48.57 chs.</p> <p>Over rolling land.</p> <p>Station 1 Mile plus 48.57 chs., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 10px;">T6S</td> <td style="border-left: 1px solid black; padding-left: 10px;">SCIR</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px;">1 M +</td> </tr> <tr> <td style="padding-right: 10px;">R16E</td> <td style="border-left: 1px solid black; padding-left: 10px;">48.57</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px;">1974</td> </tr> </table> <p>A mound of stone, 3 ft. base, 2 ft. high, is E of cor. with a steel fence post set alongside</p>	T6S	SCIR		1 M +	R16E	48.57		1974		
T6S	SCIR										
	1 M +										
R16E	48.57										
	1974										
21.785	<p style="text-align: center;">Corrective Dependent Resurvey, a Portion of the West Boundary, San Carlos Indian Reservation, T 6 S, R 16 E, Gila and Salt River Mer., Arizona</p> <hr/> <p style="text-align: center;">Correction of a portion of the dependent resurvey executed by Ray Harpin and Douglas A. Cody in 1973-74</p> <hr/> <p>N 0°15' W, on the W bdy. of the San Carlos Indian Reservation, bet. Station 1 Mile plus 48.57 chs. and Station 2 Miles plus 45.55 chs.</p> <p>Over rolling land.</p> <p>Point for the witness point at intersection with the line bet. secs. 15 and 22, hereinafter described.</p> <p>From this point the cor. of secs. 15, 16, 21, and 22, bears S 89°05' W, 0.615 chs. dist., hereinafter described.</p>										

Corrective Dependent Resurvey, Portion of the West Boundary,
 San Carlos Indian Reservation,
 T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS													
	<p>Continue measurement through sec. 15.</p>												
<p>36.24</p>	<p>Point for Station 2 Miles plus 4.81 chs.</p> <p>From this point Station 2 Miles plus 2.12 chs. erroneously monumented in 1974, bears S 25°48' W, 2.55 chs. dist., an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above a mound of stone, 3 ft. base, 1 ft. high.</p> <p>Destroy the mound of stone and remove the iron post, 28 ins. long, from the found position and reset it at the point on the W bdy. of the San Carlos Indian Reservation, 25 ins. in the ground; the cap is now mkd.</p> <div style="text-align: center;"> <p>1986</p> <table border="0"> <tr> <td>T6S</td> <td> </td> <td>SCIR</td> </tr> <tr> <td></td> <td> </td> <td>2 M +</td> </tr> <tr> <td>R16E</td> <td> </td> <td>04.81</td> </tr> <tr> <td></td> <td> </td> <td>1974</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, E of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>The cor. is located 90 lks. E. of fence, bears N and S and 2.65 chs. S of trail road, bears NE and SW.</p>	T6S		SCIR			2 M +	R16E		04.81			1974
T6S		SCIR											
		2 M +											
R16E		04.81											
		1974											
<p>76.96</p>	<p>Station 2 Miles plus 45.55 chs., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T6S</td> <td> </td> <td>SCIR</td> </tr> <tr> <td></td> <td> </td> <td>2 M +</td> </tr> <tr> <td>R16E</td> <td> </td> <td>45.55</td> </tr> <tr> <td></td> <td> </td> <td>1974</td> </tr> </table> </div> <p>A mound of stone, 3 ft. base, 1 ft. high, is E of cor.</p> <p>The cor. is located in fence, bears N and S.</p> <hr/>	T6S		SCIR			2 M +	R16E		45.55			1974
T6S		SCIR											
		2 M +											
R16E		45.55											
		1974											

Dependent Resurvey. Portion of the West Boundary,
 San Carlos Indian Reservation,
 T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS																
	<p style="text-align: center;">Reestablishment of the dependent resurvey executed by Ray Harpin and Douglas A. Cody in 1973-74</p> <hr style="width: 20%; margin: auto;"/> <p>N 0°17' W, on the W bdy. of the San Carlos Indian Reservation, bet. Station 2 Miles plus 45.55 chs. and the AP, identical with 2 Miles plus 76.73 chs.</p> <p>Over rolling land.</p>															
<p>23.49</p>	<p>Point for the witness point at intersection with the line bet. secs. 10 and 15, hereinafter described.</p> <p>From this point the cor. of secs. 9, 10, 15, and 16, bears S 88°43' W, 0.895 chs. dist., hereinafter described.</p> <p>Continue measurement through sec. 10.</p>															
<p>31.18</p>	<p>AP, identical with 2 Miles plus 76.73 chs., monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. base, 1 ft. high, with brass cap erroneously mkd. for R 16 W; the cap is now mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T6S</td> <td> </td> <td>SCIR</td> </tr> <tr> <td></td> <td> </td> <td>AP</td> </tr> <tr> <td></td> <td> </td> <td>2 M +</td> </tr> <tr> <td>R16E</td> <td> </td> <td>76.73</td> </tr> <tr> <td></td> <td></td> <td>1974</td> </tr> </table> </div> <p>The cor. is located in fence, bears N and S.</p> <hr/>	T6S		SCIR			AP			2 M +	R16E		76.73			1974
T6S		SCIR														
		AP														
		2 M +														
R16E		76.73														
		1974														
<p>42.15</p>	<p>N 1°56' E, on the W bdy. of the San Carlos Indian Reservation, bet. the AP, identical with 2 Miles plus 76.73 chs. and the AP, identical with 3 Miles plus 71.20 chs.</p> <p>Over rolling land.</p> <p>Station 3 Miles plus 38.78 chs., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T6S</td> <td> </td> <td>SCIR</td> </tr> <tr> <td></td> <td> </td> <td>3 M +</td> </tr> <tr> <td>R16E</td> <td> </td> <td>38.78</td> </tr> <tr> <td></td> <td></td> <td>1974</td> </tr> </table> </div>	T6S		SCIR			3 M +	R16E		38.78			1974			
T6S		SCIR														
		3 M +														
R16E		38.78														
		1974														

Dependent Resurvey, Portion of the West Boundary,
San Carlos Indian Reservation,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS											
	<p>A mound of stone, 3 ft. base, 1 ft. high, is E of cor.</p> <p>The cor. is located in fence, bears N and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 2°03' E, beginning new measurement.</p>										
29.885	<p>Point for the witness point at intersection with the line bet. secs. 3 and 10, hereinafter described.</p> <p>From this point the cor. of secs. 3, 4, 9, and 10, bears S 88°35' W, 3.775 chs. dist., hereinafter described.</p> <p>Continue measurement through sec. 3.</p>										
32.35	<p>AP, identical with 3 Miles plus 71.20 chs., monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T6S</td> <td style="padding: 0 5px;">SCIR</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">AP</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">3 M +</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R16E</td> <td style="padding: 0 5px;">71.20</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">1974</td> </tr> </table> </div> <p>The cor. is located in fence, bears N and S.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N 0°23' W, on the W bdy. of the San Carlos Indian Reservation, bet. the AP, identical with 3 Miles plus 71.20 chs. and the 5 Mile Cor.</p> <p>Over rolling land.</p>	T6S	SCIR		AP		3 M +	R16E	71.20		1974
T6S	SCIR										
	AP										
	3 M +										
R16E	71.20										
	1974										
45.035	<p>Station 4 Miles plus 36.29 chs., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T6S</td> <td style="padding: 0 5px;">SCIR</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">4 M +</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R16E</td> <td style="padding: 0 5px;">36.29</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">1974</td> </tr> </table> </div> <p>The cor. is located in fence, bears N and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°21' W, beginning new measurement.</p>	T6S	SCIR		4 M +	R16E	36.29		1974		
T6S	SCIR										
	4 M +										
R16E	36.29										
	1974										

Dependent Resurvey of a Portion of the West Boundary,
 San Carlos Indian Reservation,
 T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	<p>33.81 Point for the witness point at intersection with the First Standard Parallel South, on the S bdy. of sec. 33, T 5 S, R 16 E, hereinafter described.</p> <p>From this point, the stan. cor. of secs. 33 and 34, bears N 89°56' E, 3.495 chs. dist., hereinafter described.</p> <p>Continue measurement in sec. 33, T 5 S, R 16 E.</p> <p>43.69 The 5 Mile Cor., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T5S</td> <td style="border-left: 1px solid black; padding: 0 5px;">SCIR</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding: 0 5px;">5 M</td> </tr> <tr> <td style="padding: 0 5px;">R16E</td> <td style="border-left: 1px solid black; padding: 0 5px;">1974</td> </tr> </table> </div> <p>A mound of stone, 3 ft. base, 2 ft. high, is E of cor.</p> <p>The cor. is located in fence, bears N and S.</p> <hr style="width: 100%;"/> <div style="text-align: center; margin: 10px 0;"> <p>Corrective Dependent Resurvey A Portion, First Standard Parallel South T 5 S, R 16 E, Gila and Salt River Mer., Arizona</p> </div> <hr style="width: 100%;"/> <div style="text-align: center; margin: 10px 0;"> <p>Reestablishment of the survey executed by John L. Harris in 1877, correcting the dependent resurvey executed by Phillip Contzen in 1904</p> </div> <hr style="width: 100%;"/> <p>From the point for the Harris stan. cor. of Tps. 5 S, Rs. 16 and 17 E, determined by extending the line easterly from the Harris stan. cor. of secs. 34 and 35, to and through the Harris closing cor. of Tps. 6 S, Rs. 16 and 17 E, at record dist. This cor. now refers to the stan. cor. of sec. 36 only, T 5 S, R 16 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">SC</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;">T5S</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;">R16E</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;">S 36</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> </tr> </table> <p>1986</p> </div>	T5S	SCIR		5 M	R16E	1974	SC		T5S		R16E		S 36	
T5S	SCIR														
	5 M														
R16E	1974														
SC															
T5S															
R16E															
S 36															

Corrective Dependent Resurvey
 A Portion, First Standard Parallel South
 T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>The cor. is located 73 lks. N of fence, bears E and W.</p> <p>S 89°30' W, on the S bdy. of sec. 36.</p> <p>Over mountainous land; asc. over NE slope.</p> <p>4.32 The closing cor. of secs. 6 and 31, Tps. 5 and 6 S, R 17 E, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the First Standard Parallel South, on the S bdy. of T 5 S, R 17 E, executed concurrently under this same group.</p> <p>9.20 The Harris closing cor. of Tps. 6 S, Rs. 16 and 17 E, determined at record dist. from the Harris stan. cor. of secs. 34 and 35, and at record dist. from the Harris and Hiester cor. of secs. 13 and 24 only, Tps. 6 S, Rs. 16 and 17 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock mkd. X, and in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5S R16E S 36 S 1 S 6 R16E R17E T6S CC 1986</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>15.00 Top of mountain, bears SE and NW; desc. over steep SW slope, changing to W.</p> <p>40.00 Point for the stan. 1/4 sec. cor. of sec. 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC T5S R16E 1/4 S 36 1986</p> </div>
--------	---

Corrective Dependent Resurvey
 A Portion, First Standard Parallel South
 T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 4 ft. base, 3 ft. high, N of cor.</p> <p>The cor. is located 59 lks. S of fence, bears E and W.</p> <p>From this cor., Contzen's stan. 1/4 sec. cor. of sec. 36, bears S 82°08' W, 4.105 chs. dist., monumented with a sandstone, 18 x 11 x 10 ins., firmly set, projecting 12 ins. above ground, mkd. 1/4 on N face, with a scattered mound of stone, 3 ft. base, 1 ft. high, N. Destroy all evidence of this cor.</p> <p>Desc. over W slope, changing to S.</p> <p>48.825 The 1/4 sec. cor. of sec. 1 only, T 6 S, R 16 E, hereinafter described.</p> <p>80.00 Point for the stan. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>SC T5S R16E S 35 S 36 ----- 1986</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N of cor.</p> <p>The cor. is located on a spur, sloping N 60° W from N 70° E.</p> <p>From this cor., Contzen's stan. cor. of secs. 35 and 36, bears S 87°20' W, 3.96 chs. dist., monumented with a limestone, 14 x 8 x 6 ins., firmly set, projecting 8 ins. above ground, mkd. SC on N face, 5 grooves on W face and 1 groove on E face, with a mound of stone, 2 ft. base, 1 ft. high, N. Destroy all evidence of this cor.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>S 89°30' W, on the S bdy. of sec. 35.</p> <p>Over mountainous land; desc. over SW slope.</p>
--------	---

Corrective Dependent Resurvey
A Portion, First Standard Parallel South
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	
8.45	<p>The closing cor. of secs. 1 and 2, T 6 S, R 16 E, hereinafter described.</p>
	<p>Continue desc. along a spur, sloping generally W.</p>
40.00	<p>Point for the stan. 1/4 sec. cor. of secs. 35, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p>SC T5S R16E <u>1/4 S 35</u> 1986</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p>
	<p>Set a steel fence post alongside the cor.</p>
	<p>The cor. is located on a N slope and 110 lks. N of a spur, sloping westerly.</p>
	<p>From this cor., Contzen's stan. 1/4 sec. cor. of sec. 35, bears N 88°11' W, 3.39 chs. dist., monumented with a limestone, 16 x 12 x 8 ins., firmly set, projecting 10 ins. above ground, mkd. SC on N face and 1/4 on top, with a mound of stone, 2 1/2 ft. base, 1 ft. high, N. Destroy all evidence of this cor.</p>
	<p>Over rolling land.</p>
48.49	<p>The 1/4 sec. cor. of sec. 2 only, T 6 S, R 16 E, hereinafter described.</p>
80.00	<p>The original stan. cor. of secs. 34 and 35, monumented with a limestone, 23 x 14 x 11 ins., firmly set, projecting 7 ins. above ground, mkd. with 2 notches on E edge, with a mound of stone, 2 ft. base, 1 ft. high, N., from which the remains of an original bearing tree</p>
	<p>A dead and down paloverde, 7 ins. diam., bears N 18° E, 38 lks. dist., no marks remain on upper and lower partly healed blazes. (Record: North)</p>
	<p>At the cor. point</p>

Corrective Dependent Resurvey
 A Portion, First Standard Parallel South
 T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T5S R16E S 34 S 35 <hr style="width: 50px; margin: 0 auto;"/> 1986</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post and bury the original stone alongside.</p> <p>Rebuild the mound of stone, 4 ft. base, 3 ft. high, N of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>From this cor. Contzen's stan. cor. of secs. 34 and 35, bears N 80°33' W, 3.31 chs. dist., monumented with a sandstone, 16 x 8 x 6 ins., firmly set, projecting 10 ins. above ground, mkd. SC on N face, 4 grooves on W face and 2 grooves on E face, with a mound of stone, 3 ft. base, 1 1/2 ft. high, N. Destroy all evidence of this cor.</p> <hr style="border: 0.5px solid black;"/> <p>S 89°56' W, on the S bdy. of sec. 34.</p> <p>Over rolling land.</p> <p>8.53 The closing cor. of secs. 2 and 3, T 6 S, R 16 E, hereinafter described.</p> <p>39.275 Point for the stan. 1/4 sec. cor. of sec. 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">SC T5S R16E 1/4 S 34 <hr style="width: 50px; margin: 0 auto;"/> 1986</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
--------	--

Corrective Dependent Resurvey
A Portion, First Standard Parallel South
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>The cor. is located on a S slope and approx. 50 lks. N of draw, drains SW.</p>
	<p>From this cor., Contzen's stan. 1/4 sec. cor. of sec. 34, bears N 81°53' W, 3.785 chs. dist., monumented with a granite stone, 17 x 10 x 8 ins., firmly set, projecting 10 ins. above ground, mkd. SC 1/4 on N face, with a scattered mound of stone, N of the cor. Destroy all evidence of this cor.</p>
47.36	<p>The 1/4 sec. cor. of sec. 3 only, T 6 S, R 16 E, hereinafter described.</p>
78.55	<p>Point for the stan. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T5S R16E S 33 S 34 ----- 1986</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Raise a mound of stone, 4 ft. base, 2 1/2 ft. high, N of cor.</p>
	<p>Set a steel fence post alongside the cor.</p>
	<p>The cor. is located on W side of spur, slopes S.</p>
	<p>From this cor., Contzen's stan. cor. of secs. 33 and 34, bears N 58°58'E, 1.055 chs. dist., monumented with a sandstone, 15 x 8 x 6 ins., firmly set, projecting 6 ins. above ground, mkd. SC on N face, 3 grooves on E face and 3 notches on SW edge, with a mound of stone, 3 ft. base, 1 ft. high, N. Destroy all evidence of this cor.</p>
	<p>S 89°56' W, on the S bdy. of sec. 33.</p> <p>Over rolling land.</p>
3.495	<p>Point for a witness point on the S bdy. of sec. 33, on the W bdy. of the San Carlos Indian Reservation.</p>

Corrective Dependent Resurvey
A Portion, First Standard Parallel South
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> WP S 33 S 33 S S 3 S 3 I C R 1986 </p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>The point is located 3 lks. E of fence, bears N and S.</p> <p>From this point, the 5 Mile Cor., bears N 0°21'W, 9.88 chs. dist., hereinbefore described.</p> <p>7.64 The closing cor. of secs. 3 and 4, T 6 S, R 16 E, hereinafter described.</p> <p>39.275 The stan. 1/4 sec. cor. of sec. 33, determined at record bearing and distance from the remains of the original bearing tree</p> <p style="padding-left: 40px;">A root hole, bears South, 53 lks. dist., with an uprooted paloverde alongside, 9 ins. diam., with illegible scribe marks visible on open blaze.</p> <p>A granite stone, 16 x 14 x 4 ins., mkd. 1/4 S, was found lying in the mound of stone built by Contzen in 1904.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> SC T5S R16E 1/4 S 33 1986 </p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post and remove the original stone from the 1904 mound and bury alongside the cor.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N of cor.</p> <p>Set a steel fence post alongside the cor.</p>
--------	--

Corrective Dependent Resurvey
A Portion, First Standard Parallel South
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	<p>The cor. is located on a W slope.</p> <p>From this cor., Contzen's stan. 1/4 sec. cor. of sec. 33, bears N 20°21' E, 0.545 chs. dist., monumented with a granite stone, 18 x 10 x 4 ins., firmly set, projecting 10 ins. above ground, mkd. SC 1/4 on N face, with a mound of stone, 3 ft. base, 1 ft. high, N. Destroy all evidence of this cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S 89°51' W, beginning new measurement.</p> <p>7.90 The 1/4 sec. cor. of sec. 4 only, T 6 S, R 16 E, hereinafter described.</p> <p>39.625 The original stan. cor. of secs. 32 and 33, monumented with a basalt stone, 24 x 12 x 6 ins., firmly set, projecting 9 ins. above ground, mkd. with 1 notch on N edge and 1 notch on S edge.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>SC T5S R16E S 32 S 33</p> <hr style="width: 50%; margin: 0 auto;"/> <p>1986</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post and bury the original stone alongside.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>The cor. is located on a NW slope.</p> <p>From this cor., Contzen's stan. cor. of secs. 32 and 33, bears N 5°42' W, 0.52 chs. dist., monumented with a granite stone, 21 x 9 x 4 ins., firmly set, projecting 11 ins. above ground, mkd. with 2 grooves on W face and 4 grooves on E face, with a mound of stone, 3 ft. base, 1 ft. high, N. Destroy all evidence of this cor.</p> <hr style="width: 80%; margin: 10px auto;"/>
--------	--

Corrective Dependent Resurvey
A Portion, First Standard Parallel South
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	<p>N 89°46' W, on the S bdy. of sec. 32.</p> <p>Over rolling land.</p> <p>7.81 The closing cor. of secs. 4 and 5, T 6 S, R 16 E, bears South, 0.02 chs. dist., monumented with an embedded mound of stone, 3 ft. diam., 3 ins. high. No remains of wooden post found. This position is harmoniously related to existing original corners and is accepted as the best available evidence of the original corner position.</p> <p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A paloverde, 10 ins. diam., bears S 53 3/4° W, 70 lks. dist., no marks remain on rotted blaze. (Record: S 48° W, 75 lks.)</p> <p>At the cor. point</p> <p>Set an open end pipe, 18 ins. long, 3/4 in. diam., 16 ins in the ground and in the existing mound of stone.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the open end pipe.</p> <p>40.025 Point for the stan. 1/4 sec. cor. of sec. 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T5S R16E <u>1/4 S 32</u> 1986</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, N of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>The cor. is located approx. 175 lks. W of power line, bears S 25° E and N 25° W; and 125 lks. N of wash, 30 lks. wide, drains N 60° W.</p>
--------	--

Corrective Dependent Resurvey
A Portion, First Standard Parallel South
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>From this cor., Contzen's stan. 1/4 sec. cor. of sec. 32, bears N 20°08' W, 0.225 chs. dist., monumented with a basalt stone, 11 x 11 x 8 ins., firmly set, projecting 6 ins. above ground, mkd. SC on top and 1/4 on N face, with a mound of stone, 2 ft. base, 6 ins. high, N, from which the bearing trees mkd. in 1904</p> <p>A paloverde, 12 ins. diam., bears N 7 1/2° E, 48 lks. dist., no marks. (Record: 50 lks.)</p> <p>A paloverde stump, 8 ins. diam., bears N 52 1/2° W, 51 lks. dist., no marks. (Record: N 48 1/2° W)</p> <p>Destroy all evidence at the 1904 corner position.</p>
47.71	<p>A local monument, an oval shape iron rod, 1 x 1/2 in. diam., firmly set, projecting 2 ins. above ground, and in a mound of stone, 2 ft. base, 6 ins. high, bears North, 0.18 chs. dist.</p>
80.05	<p>The stan. cor. of secs. 31 and 32, determined from a tie to post 2130+65.43 on the center line of Arizona State Highway No. 77 (Oracle Jct - Globe Highway) calculated from the Arizona State Highway location map, Oracle Jct-Globe Highway (Aravaipa - Winkelman Section March 1961). This is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC T5S R16E S 31 S 32 ----- 1986</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>The cor. is located on a fill and 4 1/2 lks. S of fence cor. from which fences bear N and E.</p> <p>From this point, post 2130 + 65.43 on the center line of Arizona State Highway No. 77 (Oracle Jct - Globe Highway) bears S 89°51.5'W, 10.05 chs. dist.</p> <hr/>

Dependent Resurvey
 A Portion, First Standard Parallel South
 T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Reestablishment of the dependent resurvey executed by Philip Contzen in 1904</p> <hr/>
	<p>S 89°51.5' W, on the S bdy. of sec. 31.</p>
	<p>Over rolling land.</p>
7.40	<p>A local monument, an open end pipe, 1 in. diam., firmly set, projecting 1 in. above ground and in a mound of stone, 1 1/2 ft. base, 6 ins. high, bears North, 0.03 chs. dist.</p>
10.05	<p>Sta. PC 2129+04.77, on the center line of State Highway 77, monumented with a railroad spike, flush with pavement, bears S 13°52' E, 2.435 chs. dist.</p>
	<p>From this point, sta. 2123+37.00 ST on the center line of State Highway 77, monumented with a railroad spike, flush with pavement, bears S 13°52' E, 11.035 chs. dist.</p>
10.065	<p>State Highway 77, on curve, bears SE from NW.</p>
40.43	<p>The stan. 1/4 sec. cor. of sec. 31, monumented with an open end pipe, of unknown origin, 18 ins. long, 3/4 in. diam., firmly set, 1 in below surface of the ground. This position is harmoniously related to existing original corners and is accepted as the best available evidence of the original corner position.</p>
	<p>At the cor. point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T5S R16E <u>1/4 S 31</u> 1986</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Insert open end pipe inside stainless steel post.</p>
	<p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N of cor.</p>
	<p>Set a steel fence post alongside the cor.</p>

Dependent Resurvey
 A Portion, First Standard Parallel South
 T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	<p>The cor. is located on E edge of dirt road, 18 lks. wide, bears SE and NW.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S 89°48.5' W, beginning new measurement.</p> <p>39.26 The stan. cor. of Tps. 5 S, Rs. 15 and 16 E, monumented with the lower portion of an iron post, 18 ins. long, 3 ins. diam., cement filled and corroded by rust, firmly set, 2 ins. below surface of the ground. This is accepted as the best available evidence of the original cor. position.</p> <p>from which the remaining original bearing tree:</p> <p style="padding-left: 40px;">A mesquite, 12 ins. diam., bears N 8 1/4° E, 68 lks. dist., no marks remain. (Record: N 6° E)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> SC T5S R15E R16E S 36 S 31 <hr style="width: 50%; margin: 0 auto;"/> 1986 </div> <p>from which</p> <p style="padding-left: 40px;">A magnet in a 1 x 1 x 2 5/8 in. orange colored plastic case, set 24 ins. in the ground, bears S 72° W, 52 1/2 lks. dist.</p> <p style="padding-left: 40px;">A magnet in a 1 x 1 x 2 5/8 in. blue colored plastic case, set 24 ins. in the ground, bears N 6° W, 44 1/2 lks. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post and bury the remains of the iron post alongside the cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>From this cor., an open end pipe, 1 in. diam., bent over, bears S 58° W, 9 lks. dist.</p>
--------	--

Dependent Resurvey
 A Portion, First Standard Parallel South
 T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS

From this same cor., the original closing cor. of Tps. 6 S, Rs. 15 and 16 E, bears S 89°22' W, 7.055 chs. dist., monumented with the upper portion of a corroded iron post, 10 ins. long, 3 ins. diam., firmly set, 2 ins. below surface of the ground, with fragments found in the hole beneath the iron post. The brass cap was erroneously mkd. as the stan. cor. of Tps. 5 S, Rs. 15 and 16 E. This is accepted as the best available evidence of the original cor. position.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T5S R15E
 S 36

S 1	S 6
R15E	R16E
T6S	
CC	
1986	

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post and bury the remains of the iron post alongside the cor.

Set a steel fence post alongside the cor.

The cor. is located 2 lks. N of fence cor., from which fences bear E, W, and NW, and 2 lks. E of power line, bears SE and NW.

Corrective Dependent Resurvey, Portion, East Boundary,
 T 6 S, R 16 E, Gila and Salt River Mer., Arizona

Reestablishment of the surveys executed by
 John L. Harris and William E. Hiester in 1877 and 1928

From the cor. of secs. 13 and 24 only, monumented with an iron post, 2 ins. diam., leaning, projecting 12 ins. above a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd.

Corrective Dependent Resurvey, a Portion, East Boundary,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS													
	<table border="0"> <tr><td>T6S</td><td></td></tr> <tr><td>R16E</td><td> T6S</td></tr> <tr><td>S13</td><td> R17E</td></tr> <tr><td>—</td><td> S19</td></tr> <tr><td>S24</td><td> </td></tr> <tr><td>1928</td><td> </td></tr> </table>	T6S		R16E	T6S	S13	R17E	—	S19	S24		1928	
T6S													
R16E	T6S												
S13	R17E												
—	S19												
S24													
1928													
	<p>The original monument, a sandstone, 18 x 14 x 5 ins., mkd. with 3 notches on one edge only, is alongside.</p> <p>Straighten and reset the iron post, 12 ins. in the ground and rebuild the mound of stone, 4 ft. base, to top.</p> <p>The cor. is located 5 lks. S of fence, bears E and W and on a NW slope.</p> <p>N 1°29' W, bet. secs. 13 and 19 on the E. bdy. of the tp.</p> <p>Over rolling mountainous land.</p>												
1.11	The closing cor. of secs. 18 and 19, T 6 S, R 17 E, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. from ground, in a mound of stone 4 ft. base to top, with brass cap mkd. as described in the field note record of the dependent resurvey of the W. bdy. of T 6 S, R 17 W, executed concurrently under this same group.												
39.825	The 1/4 sec. cor. of sec. 13 only, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above a mound of stone, 5 ft. base, 2 1/2 ft. high, with brass cap mkd. as described in the field note record of the dependent resurvey of a portion of the W bdy. of T 6 S, R 17 E, executed concurrently under this same group. This cor. now functions as an angle point.												
	<hr style="width: 20%; margin: 0 auto;"/>												
	N 1°34'W, beginning new measurement.												
0.19	The 1/4 cor. of sec. 13 only, determined at 40.00 chs. in latitude from the cor. of secs. 13 and 24 only.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.												
	<table border="0"> <tr><td>T6S</td><td></td></tr> <tr><td>R16E</td><td> R17E</td></tr> <tr><td>1/4 S 13</td><td> </td></tr> <tr><td>1986</td><td> </td></tr> </table>	T6S		R16E	R17E	1/4 S 13		1986					
T6S													
R16E	R17E												
1/4 S 13													
1986													

Corrective Dependent Resurvey, a Portion, East Boundary,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
1.265	The 1/4 sec. cor. of sec. 18, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above a mound of stone, 4 ft. base, 2 1/2 ft. high, with brass cap mkd. as described in the field note record of the dependent resurvey of a portion of the W bdy. of T 6 S, R 17 E, executed concurrently under this same group.
14.46	The closing cor. of secs. 13 and 18, at the intersection with the S bdy. of the San Carlos Indian Reservation, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 ft. base, 1 ft. high, with brass cap mkd. as described in the field note record of the dependent resurvey of a portion of the W bdy. of T 6 S, R 17 E, executed concurrently under this same group.
1.23	<p style="text-align: center;">_____</p> <p>N 51°16'E, on the S bdy of the San Carlos Indian Reservation.</p> <p>Point for a closing cor. at intersection with the line between secs. 13 and 18.</p>
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">SCIR CC T6S T6S R16E R17E S 13 S 18</p> <p style="text-align: center;">S 18 T6S R17E 1986</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	The cor. is located in fence, bears NE and SW.

BOOK 5324

Corrective Dependent Resurvey, a Portion, East Boundary,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>From this point, AP 45 identical with 41 Miles plus 12.08 chs., bears N 51°16' E, 10.25 chs. dist., hereinbefore described.</p> <hr/> <p>N 0°29'W, bet. secs. 13 and 18 on the E bdy of the tp.</p> <p>24.965 Point for the cor. of secs. 12 and 13 only, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R16E R17E S 12 ——— S 18 S 13 1986</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>The cor is located on a N slope.</p> <hr/> <p>N 0°29' W, on the E bdy. of sec. 12.</p> <p>Over rolling mountainous land.</p> <p>1.115 The 1986 closing cor. of secs. 7 and 18, T 6 S, R 17 E, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T 6 S, R 17 E, executed concurrently under this same group.</p> <p>40.00 Point for the 1/4 sec. cor. of sec. 12 only, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R16E R17E 1/4 S 12 1986</p> </div>

BOOK 5324

Corrective Dependent Resurvey, a Portion, East Boundary,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS																			
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>The cor. is located on low spur, slopes SW.</p>																		
41.12	<p>Point for the 1/4 sec. cor. of sec. 7, T 6 S, R 17 E, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T 6 S, R 17 E, executed concurrently under this same group.</p>																		
80.00	<p>Point for the cor. of secs. 1 and 12 only, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p>																		
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T6S</td><td> </td><td></td></tr> <tr><td>S 1</td><td> </td><td>T6S</td></tr> <tr><td>—</td><td> </td><td>R17E</td></tr> <tr><td>S 12</td><td> </td><td>S 7</td></tr> <tr><td>R16E</td><td> </td><td></td></tr> <tr><td></td><td> </td><td>1986</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>The cor. is located 45 lks. S of wash, 25 lks. wide, drains SW.</p> <hr/> <p>N 0°29' W, on the E. bdy. of sec. 1.</p> <p>Over rolling mountainous land.</p>	T6S			S 1		T6S	—		R17E	S 12		S 7	R16E					1986
T6S																			
S 1		T6S																	
—		R17E																	
S 12		S 7																	
R16E																			
		1986																	
1.125	<p>The closing cor. of secs. 6 and 7, T 6 S, R 17 E, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 5 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T 6 S, R 17 E, executed concurrently under this same group.</p>																		

BOOK 5324

Corrective Dependent Resurvey, a Portion, East Boundary,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of sec. 1 only, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R16E R17E 1/4 S 1 1986</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 4 ft. base, 3 ft. high, W of cor.</p>
41.125	<p>Point for the 1/4 sec. cor. of sec. 6, T 6 S, R 17 E, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 ft. base, 6 ins. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T 6 S, R 17 E, executed concurrently under this same group. .</p> <p>Asc. over steep S slope, changing to SW.</p>
75.00	<p>Top of mountain, bears SE and NW; desc. over NE slope.</p>
80.00	<p>The closing cor. of Tps. 6 S, Rs. 16 and 17 E, on the First Standard Parallel South, hereinbefore described.</p> <p>From this cor. the stan. cor. of Tps. 5 S, Rs. 16 and 17 E., bears N 89°30' E, 9.20 chs. dist., hereinbefore described.</p>
<hr/> <p>Dependent Resurvey, a Portion of the Subdivisional Lines, T 6 S, R 16 E, Gila and Salt River Mer., Arizona</p> <hr/>	
<p>Reestablishment of the Survey Executed by John L. Harris in 1877</p> <hr/>	

BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS						
	<p>From the cor. of secs. 25, 26, 35, and 36, monumented with an iron pipe, 2 ins. diam., projecting 18 ins. above ground, perpetuated by Stitzer & Associates Inc., with a rebar, 24 ins. long, 3/4 in. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd. 25 26 35 36 LS 4399, with a mound of stone, 2 ft. base, 6 ins. high, N of cor., with a steel fence post alongside. The original granite stone, 12 x 8 x 6 ins., mkd. with 1 notch only is lying loose alongside.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T6S R16E</td></tr> <tr><td>S26 S25</td></tr> <tr><td>— —</td></tr> <tr><td>S35 S36</td></tr> <tr><td>1986</td></tr> </table> </div> <p>Insert rebar inside stainless steel post and bury the original stone and iron pipe alongside.</p> <p>Remove the mound of stone N and raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>N 0°23' W, bet. secs. 25 and 26.</p> <p>Over rolling land.</p>	T6S R16E	S26 S25	— —	S35 S36	1986
T6S R16E						
S26 S25						
— —						
S35 S36						
1986						
39.70	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T6S R16E</td></tr> <tr><td>1/4</td></tr> <tr><td>S26 S25</td></tr> <tr><td>1986</td></tr> </table> </div>	T6S R16E	1/4	S26 S25	1986	
T6S R16E						
1/4						
S26 S25						
1986						
79.40	<p>Point for the cor. of secs. 23, 24, 25, and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>					

BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T6S R16E</td> </tr> <tr> <td>S23</td> <td>S24</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S26</td> <td>S25</td> </tr> <tr> <td colspan="2" style="text-align: center;">1986</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 4 ft. base, 2 1/2 ft. high, W of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>From this cor., a rebar, 3/4 in. diam., projecting 6 ins. above the ground, with aluminum cap mkd. 23 24 25 26 LS 4399, bears S 62°24' E, 1.52 chs. dist., with a scattered mound of stone alongside. This cor. is not utilized in this survey.</p> <hr/> <p>From the cor. of secs. 19, 24, 25, and 30, on the E bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above a mound of stone, 3 ft. base, 6 ins. high, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T6S</td> </tr> <tr> <td>R16E</td> <td>R17E</td> </tr> <tr> <td>S24</td> <td>S19</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S25</td> <td>S30</td> </tr> <tr> <td colspan="2" style="text-align: center;">1928</td> </tr> </table> <p>The original monument, a granite stone, 16 x 12 x 10 ins., mkd. with 4 notches on one edge only, is alongside.</p> <p>from which the remains of an original bearing tree:</p> <p style="padding-left: 40px;">A paloverde stump, 12 ins. diam., bears North, 22 lks. dist., no marks.</p> <p>Rebuild the mound of stone, 3 ft. base, 1 ft. high.</p> <p>S 89°43' W, bet. secs. 24 and 25.</p> <p>Over rolling land.</p> <p>40.09 Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the original cor.</p>	T6S R16E		S23	S24			S26	S25	1986		T6S		R16E	R17E	S24	S19			S25	S30	1928	
T6S R16E																							
S23	S24																						
S26	S25																						
1986																							
T6S																							
R16E	R17E																						
S24	S19																						
S25	S30																						
1928																							

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	
80.17	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R16E S24 1/4 ——— S25 1986</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>The cor. of secs. 23, 24, 25, and 26.</p> <hr/> <p>N 0°19' E, bet. secs. 23 and 24.</p> <p>Over rolling land.</p>
39.70	<p>Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R16E 1/4 S23 S24 1986</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>From this cor., a rebar 3/4 in. diam., projecting 10 ins. above ground, with aluminum cap mkd. 1/4 23 24 LS 4399, in a scattered mound of stone, bears S 45°31' E, 0.825 chs. dist. This cor. is not utilized in this survey.</p>

BOOK 5324

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	
71.285	<p>Point for a witness point on the S bdy. of the San Carlos Indian Reservation.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, 6 ins. high, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP SCIR S23 S24 S23 S24 1986</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, NW of the point.</p> <p>From this point, station 42 Miles plus 51.98 chs., bears S 51°51' W, 8.445 chs. dist., hereinbefore described.</p>
79.40	<p>The cor. of secs. 13, 14, 23, and 24, monumented with a basalt stone, 18 x 16 x 12 ins., firmly set, projecting 12 ins. above ground, mkd. with 3 grooves on the S face only, with a rebar, 24 ins. long, 3/4 in. diam., firmly set alongside, projecting 8 ins. above ground, with aluminum cap erroneous mkd. 11 12 13 14 LS 4399, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W, with a steel fence post alongside.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R16E S14 S13 ----- S23 S24 1986</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert rebar inside stainless steel post and bury the original stone alongside.</p>

BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>The cor. is located 10 1/2 lks. S of fence, bears E and W.</p> <hr/> <p>From the cor. of secs. 13 and 24 only, on the E bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 13 and 24.</p> <p>Over rolling land, along fence.</p> <p>39.745 Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T6S R16E S13 1/4 ——— S24 1986 </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p> <p>The cor. is located in fence, bears E and W and 40 lks. N of wash, 50 lks. wide, drains westerly.</p> <p>69.205 Point for a witness point on the S bdy. of the San Carlos Indian Reservation.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> WP SCIR S S13 S13 C ——— I / R S24 S24 1986 </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, NW of point.</p>
--------	--

BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>From this point, a fence cor., bears NE, 11 lks. dist.</p> <p>From this same point, AP 46, identical with 42 Miles plus 16.27 chs., bears N 51°51' E, 14.16 chs. dist., hereinbefore described.</p>
79.49	<p>The cor. of secs. 13, 14, 23, and 24.</p> <hr/>
	<p>N 0°33' W, bet. secs. 13 and 14.</p> <p>Over rolling land.</p>
39.86	<p>Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R16E 1/4 S14 S13 1986</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
79.72	<p>Point for the cor. of secs. 11, 12, 13, and 14, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R16E S11 S12 ----- S14 S13 1986</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <hr/> <p>From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp., hereinbefore described.</p> <p>S 89°48' W, bet. secs. 12 and 13.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	
39.78	<p>Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T6S R16E S12 1/4 ——— S13 1986 </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N of cor.</p> <p>Set a steel fence post alongside the cor.</p>
79.56	<p>The cor. of secs. 11, 12, 13, and 14.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>N 0°33' W, bet. secs. 11 and 12.</p> <p>Over rolling land.</p>
39.86	<p>Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T6S R16E 1/4 S11 S12 1986 </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>The cor. is located 30 lks. S of wash, drains NW.</p>
79.72	<p>Point for the cor. of secs. 1, 2, 11, and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p>

BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T6S</td><td>R16E</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td>S11</td><td>S12</td></tr> <tr><td colspan="2">1986</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>The cor. is located 75 lks. S of spur, slopes S.</p> <hr/> <p>From the cor. of secs. 1 and 12 only, on the E bdy. of the Tp., hereinbefore described.</p> <p>S 89°36' W, bet. secs. 1 and 12.</p> <p>Over rolling land.</p>	T6S	R16E	S 2	S 1	S11	S12	1986			
T6S	R16E										
S 2	S 1										
S11	S12										
1986											
39.815	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T6S</td><td>R16E</td></tr> <tr><td colspan="2">S 1</td></tr> <tr><td>1/4</td><td>_____</td></tr> <tr><td colspan="2">S12</td></tr> <tr><td colspan="2">1986</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 5 ft. base, 4 ft. high, N of cor.</p> <p>Set a steel fence post alongside the cor.</p>	T6S	R16E	S 1		1/4	_____	S12		1986	
T6S	R16E										
S 1											
1/4	_____										
S12											
1986											
79.63	<p>The cor. of secs. 1, 2, 11, and 12.</p> <hr/> <p>N 0°14' W, bet. secs. 1 and 2.</p> <p>Over rolling land.</p>										

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	
39.86	<p>Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R16E 1/4 S 2 S 1 1986</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 4 ft. base, 3 1/2 ft. high, W of cor.</p> <p>The cor. is located on steep SE slope.</p>
79.87	<p>Point for the closing cor. of secs. 1 and 2, on the First Standard Parallel South, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5S R16E S 35 ----- S 2 S 1 T6S R16E CC 1986</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>The cor. is located on steep SW slope.</p> <p>From this point the stan. cor. of secs. 35 and 36, T 5 S, R 16 E, bears N 89°30' E, 8.45 chs. dist., hereinbefore described.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>The point for the 1/4 sec. cor. of sec. 1 only, T 6 S, R 16 E, on the First Standard Parallel South, is at midpoint on the N bdy. of sec. 1.</p>

BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R16E ----- 1/4 S 1 T6S R16E 1986</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, S of cor.</p> <p>The cor. is located on steep S slope.</p> <p>From this point the stan. 1/4 sec. cor. of sec. 36, T 5 S, R 16 E, bears N 89°30' E, 8.825 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>S 89°59' W, bet. secs. 23 and 26.</p> <p>Over rolling land.</p> <p>39.93 Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R16E S23 1/4 ----- S26 1986</p> <p>Deposit 2 magnets each in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N of cor.</p> <p>Set a steel fence post alongside the cor.</p>
--------	--



BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	<p>From this cor. a rebar, 3/4 in. diam., projecting 4 ins. above the ground, in a small mound of stone, with aluminum cap mkd. 1/4 23 26 IS 4399, bears S 70°27' E, 0.71 chs. dist. This cor. is not utilized in this survey.</p> <p>79.85 The cor. of secs. 22, 23, 26, and 27 monumented with a rebar, 1/2 in. diam., driven into bedrock, firmly set flush with the ground. This is accepted as the best available evidence of the original cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, directly over rebar and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2">T6S R16E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S22</td> <td style="padding: 2px 5px;">S23</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; height: 1px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S27</td> <td style="padding: 2px 5px;">S26</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">1986</td> </tr> </table> </div> <p>from which Stitzer's reference monuments</p> <p style="margin-left: 40px;">A steel pin, 1 in. diam., projecting 30 ins. above ground, with top mkd. 22 23 26 27 300' EA. OF COR., bears N 87°45' E, 300.2 ft.</p> <p style="margin-left: 40px;">A steel pin, 1 in. diam., projecting 30 ins. above ground, with top mkd. 22 23 26 27 475' EA. OF COR., bears N 87°51' E, 475.5 ft.</p> <p style="margin-left: 40px;">An iron pipe, 1 in. diam., projecting 33 ins. above ground, with top mkd. 22 23 26 27 188.2' SO. OF COR., bears S 0°19' E, 188.2 ft.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>The cor. is located 80 lks. W of dirt road, 35 lks. wide, bears SE and NW.</p> <hr style="border: 0.5px solid black; margin-top: 20px;"/>	T6S R16E		S22	S23			S27	S26	1986	
T6S R16E											
S22	S23										
S27	S26										
1986											

BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	<p>N 0°17' E, bet. secs. 22 and 23.</p> <p>Over rolling land.</p> <p>4.39 Point for a witness point on the S bdy. of the San Carlos Indian Reservation.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>From this point, station 43 Miles plus 50.12 chs., bears N 48°19' E, 17.92 chs. dist., hereinbefore described.</p> <p>39.77 Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W of cor.</p> <p>The cor. is located 220 lks. N of trail road, on curve bearing E from N, and 95 lks. E of same road.</p> <p>From this cor., a rebar, 3/4 in. diam., projecting 6 ins. above the ground, with aluminum cap mkd. 1/4 22 23 IS 4399, with a steel fence post alongside, bears North, 0.115 chs. dist.</p>
--------	---

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS									
79.54	<p>The cor. of secs. 14, 15, 22, and 23, monumented with a basalt stone, 18 x 16 x 10 ins., firmly set, projecting 10 ins. above ground, mkd. with 3 notches on the S edge and 2 notches on the E edge, with a rebar, 24 ins. long, 3/4 in. diam., firmly set alongside, projecting 8 ins. above ground, with aluminum cap mkd. 14 15 22 23 LS 4399, with a mound of stone, 3 ft. base, 1 ft. high, W of the cor., with a steel fence post alongside.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T6S</td> <td>R16E</td> </tr> <tr> <td>S15</td> <td>S14</td> </tr> <tr> <td>S22</td> <td>S23</td> </tr> <tr> <td colspan="2">1986</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert rebar inside stainless steel post and bury the original stone alongside.</p> <p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>The cor. is located 3 lks. S of fence, bears E and W, and 170 lks. S of trail road, bears NE and SW.</p>	T6S	R16E	S15	S14	S22	S23	1986	
T6S	R16E								
S15	S14								
S22	S23								
1986									
39.94	<p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>N 89°56' W, bet. secs. 14 and 23.</p> <p>Over rolling land, along fence.</p> <p>The 1/4 sec. cor. of secs. 14 and 23, perpetuated by Stitzer & Associates, Inc., LS 4339, monumented with a rebar, 24 ins. long, 3/4 in. diam., firmly set, projecting 12 ins. above ground. This is accepted as a careful and faithful perpetuation of the original corner position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>								

BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T6S R16E S14 1/4 _____ S23 1986</p> <p>from which</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 30 ins. in the ground, and in a mound of stone, 2 ft. base., to top, for a reference monument, bears S 10 1/2° E, 59.8 ft. dist., with cap mkd. RM 1/4 S23 1986 59.8 FT TO COR and an arrow pointing to the cor.</p> <p>An aluminum post, 36 ins. long, 3/4 in. diam., set 24 ins. in the ground, and in a mound of stone, 2 1/2 ft. base., to top, for a reference monument, bears S 86 3/4° W, 212.9 ft. dist., with cap mkd. RM 1/4 S23 1986 212.9 FT TO COR and an arrow pointing to the cor.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert rebar inside stainless steel post.</p> <p>Raise a mound of stone, 4 ft. base, 2 1/2 ft. high, N of cor.</p> <p>The cor. is located in fence, bears E and W, and in wash, 60 lks. wide, drains SW.</p> <hr/> <p>N 89°54' W, beginning new measurement.</p>
39.95	<p>The cor. of secs. 14, 15, 22, and 23.</p> <hr/> <p>N 0°16' W, bet. secs. 14 and 15.</p> <p>Over rolling land.</p>
39.435	<p>The 1/4 sec. cor. of secs. 14 and 15, monumented with a basalt stone, 15 x 10 x 10 ins., firmly set, projecting 10 ins. above ground, no marks, with a rebar, 24 ins. long, 3/4 in. diam., firmly set alongside, projecting 8 ins. above ground, with aluminum cap mkd. 1/4 14 15 LS 4399, with a mound of stone, 2 ft. base, 1 ft. high, N, with a steel fence post alongside.</p>

BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
22 ins. in the ground, with brass cap mkd.

T6S R16E
1/4
S15|S14
1986

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic
case beneath the stainless steel post.

Insert rebar inside stainless steel post and bury the original
stone alongside.

Remove the mound of stone N, and raise a mound of stone,
2 1/2 ft. base, 1 1/2 ft. high, W of cor.

The cor. is located 270 lks. N of wash, 150 lks. wide, drains
W from SE.

N 0°34' W, beginning new measurement.

39.77

The cor. of secs. 10, 11, 14, and 15, monumented with a basalt
stone, 22 x 12 x 6 ins., firmly set, projecting 10 ins. above
ground, mkd. with 4 notches on the S edge and 2 notches on the
E edge, with a rebar, 24 ins. long, 3/4 in. diam., firmly set
alongside, projecting 6 ins. above ground, with aluminum cap mkd.
10 11 14 15 LS 4399, with a mound of stone, 3 ft. base,
1 ft. high, W, with a steel fence post alongside.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
20 ins. in the ground, and in a mound of stone, 2 ft. base, to
top, with brass cap mkd.

T6S R16E
S10|S11

S15|S14
1986

BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>Insert rebar inside stainless steel post and bury the original stone alongside.</p> <p>Rebuild the mound of stone, 3 ft. base, 1 1/2 ft. high, W of cor.</p> <p>The cor. is located 145 lks. N of trail road, bears N 55° E from S 70° W.</p>
39.85	<p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>S 89°42' W, bet. secs. 11 and 14.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R16E</p> <p>S11</p> <p>1/4 ———</p> <p>S14</p> <p>1986</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N of cor.</p> <p>Set a steel fence post alongside the cor.</p>
79.70	<p>The cor. of secs. 10, 11, 14, and 15.</p> <hr/> <p>N 0°43' W, bet. secs. 10 and 11.</p> <p>Over rolling land.</p>
39.935	<p>The 1/4 sec. cor. of secs. 10 and 11, monumented with a granite stone, 12 x 10 x 8 ins., firmly set, projecting 8 ins. above ground, mkd. 1/4 on top, with a mound of stone, 3 ft. base, 1 ft. high, N of the cor.</p>

BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R16E 1/4 S10 S11 1986</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post and bury the original stone alongside.</p> <p>Remove the mound of stone to the N, and raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N 0°42' W, beginning new measurement.</p>
39.865	<p>The cor. of secs. 2, 3, 10, and 11, monumented with a basalt stone, 16 x 10 x 10 ins., firmly set, projecting 8 ins. above ground, mkd. with 5 notches on the S edge and 2 notches on the E edge, with a mound of stone, 3 ft. base, 1 ft. high, N of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R16E S 3 S 2 ----- S10 S11 1986</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post and bury the original stone alongside.</p> <p>Remove the mound of stone to the N, and raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Set a steel fence post alongside the cor.</p>

BOOK 5324

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	
	<p>The cor. is located 30 lks. N of low spur, slopes W.</p> <hr/>
	<p>From the cor. of secs. 1, 2, 11, and 12.</p>
	<p>S 89°46' W, bet. secs. 2 and 11.</p>
	<p>Over rolling land.</p>
39.955	<p>Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T6S R16E</p>
	<p style="text-align: center;">S 2</p>
	<p style="text-align: center;">1/4 ———</p>
	<p style="text-align: center;">S11</p>
	<p style="text-align: center;">1986</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post alongside the cor.</p>
79.90	<p>The cor. of secs. 2, 3, 10, and 11.</p> <hr/>
	<p>N 0°25.5' W, bet. secs. 2 and 3.</p>
	<p>Over rolling land.</p>
39.83	<p>The 1/4 sec. cor. of secs. 2 and 3, monumented with a granite stone, 18 x 12 x 8 ins., firmly set, projecting 10 ins. above ground, mkd. 1/4 on top, with a mound of stone, 2 1/2 ft. base, 1 ft. high, N of the cor., from which the remains of an original bearing tree</p>
	<p style="text-align: center;">A dead and down paloverde, 10 diam., bears S 35° E, 43 lks. dist., no marks remain on rotted blaze.</p>
	<p>At the cor. point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p>

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	<p style="text-align: center;">T6S R16E 1/4 S 3 S 2 1986</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Remove the mound of stone to the N, and raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor. and deposit the original stone in the mound.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°18' W, beginning new measurement.</p> <p>39.74 Intersect the First Standard Parallel South.</p> <p>Point for the closing cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5S R16E S 34</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="text-align: center;">S 3 S 2 T6S R16E CC 1986</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>The cor. is located on SW slope.</p> <p>From this point, the original closing cor. of secs. 2 and 3, bears N 0°18' W, 0.07 chs. dist., monumented with a basalt stone, 24 x 16 x 14 ins., firmly set, projecting 15 ins. above ground, mkd. with 2 notches on the SE edge and 4 notches on the NW edge, with a mound of stone, 1 1/2 ft. base, 1 ft. high, SW. Add the marks AM and bury the stone in place. Remove the mound of stone and utilize the stones in supporting the 1986 monument.</p>
--------	---

BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS

From this same point, the stan. cor. of secs. 34 and 35, T 5 S, R 16 E, bears N 89°56' E, 8.53 chs. dist., hereinbefore described.

The point for the 1/4 sec. cor. of sec. 2 only, T 6 S, R 16 E, on the First Standard Parallel South, is at midpoint on the N bdy. of sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a mound of stone of stone, 4 ft. base, to top, with brass cap mkd.

T5S R16E

1/4 S 2
T6S R16E
1986

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

The cor. is located 35 lks. N of draw, drains N 75° W, and on steep S slope.

From this point the stan. 1/4 sec. cor. of sec. 35, T 5 S, R 16 E, bears N 89°30' E, 8.49 chs. dist., hereinbefore described.

From the cor. of secs. 22, 23, 26, and 27.

S 88°43' W, bet. secs. 22 and 27.

Over rolling land.

5.035

Point for a witness point on the S bdy. of the San Carlos Indian Reservation.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.

WP
SCIR
S S22 S22
C /
I /
R S27 S27
1986

BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS																
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the point.</p> <p>From this point station 43 Miles plus 76.04 chs., bears S 48°19' W, 1.23 chs. dist., hereinbefore described.</p> <p>38.51 The 1/4 sec. cor. of secs. 22 and 27, perpetuated by John H. Stitzer, LS 4399, monumented with a lead capped pipe, 12 ins. long, 1 in. diam., firmly set, projecting 2 ins. above ground, mkd. 1/4 22 27, with a steel fence post alongside. This is accepted as a careful and faithful perpetuation of the original cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R16E S22 1/4 ——— S27 1986</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert lead capped pipe inside stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N of cor.</p> <hr style="width: 20%; margin: auto;"/> <p>S 88°43' W, beginning new measurement.</p>															
37.935	<p>Point for a witness point on line bet. secs. 22 and 27, on the W bdy. of the San Carlos Indian Reservation.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td></td> <td>WP</td> <td>S</td> </tr> <tr> <td>S22</td> <td> S22</td> <td>C</td> </tr> <tr> <td colspan="3"><hr style="width: 50%; margin: auto;"/></td> </tr> <tr> <td>S27</td> <td> S27</td> <td>I</td> </tr> <tr> <td>1986</td> <td></td> <td>R</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p>		WP	S	S22	S22	C	<hr style="width: 50%; margin: auto;"/>			S27	S27	I	1986		R
	WP	S														
S22	S22	C														
<hr style="width: 50%; margin: auto;"/>																
S27	S27	I														
1986		R														

BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Set a steel fence post alongside the cor.</p> <p>From this point an AP, identical with station zero (0) Miles plus 44.72 chs., bears N 1°08' W, 7.04 chs. dist., hereinbefore described.</p> <p>38.46 The cor. of secs. 21, 22, 27, and 28, perpetuated by person(s) unknown, monumented with a granite stone, 15 x 11 x 3 ins., firmly set, projecting 7 ins. above ground, mkd. with 3 vertical grooves on the E face and 2 vertical grooves on the S face and X on top, with a rebar, 24 ins. long, 3/4 in. diam., firmly set alongside, projecting 8 ins. above ground, with aluminum cap mkd. 21 22 27 28 LS 4399, with a mound of stone, 3 ft. base, 1 ft. high, N of the cor., supporting a post in fence. This is accepted as a careful and faithful perpetuation of the cor. position.</p> <p>from which the remains of an original bearing tree:</p> <p style="padding-left: 40px;">A paloverde stump, 12 ins. diam., bears N 11° E, 92 lks. dist., no marks.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T6S</td> <td style="padding: 0 5px;">R16E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S21</td> <td style="padding: 0 5px;">S22</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S28</td> <td style="padding: 0 5px;">S27</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1986</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert rebar inside stainless steel post and bury the marked stone alongside.</p> <p>Rebuild the mound of stone, 3 ft. base, 1 1/2 ft. high, N of cor.</p> <p>The cor. is located 3 lks. N of fence cor., from which fences bear N and W.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>N 0°38' W, bet. secs. 21 and 22.</p> <p>Over rolling land.</p>	T6S	R16E	S21	S22	S28	S27	1986	
T6S	R16E								
S21	S22								
S28	S27								
1986									

BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	
39.96	<p>The 1/4 sec. cor. of secs. 21 and 22, monumented with a basalt stone, 16 x 8 x 6 ins., firmly set, projecting 10 ins. above ground, mkd. 1/4 on top, with a rebar, 3/4 in. diam., firmly set alongside, projecting 8 ins. above ground, with aluminum cap mkd. 1/4 21 22 LS 4399, with a mound of stone, 1 1/2 ft. base, 1 ft. high, N of the cor., with a steel fence post alongside; from which the remains of an original bearing tree</p> <p style="text-align: center;">A mesquite stump, 10 ins. diam., bears S 69 1/4° W, 21 lks. dist., no marks. (Record: S 65 1/2° W, 22 lks.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R16E 1/4 S21 S22 1986</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert rebar inside stainless steel post and bury the original stone alongside.</p> <p>Remove the mound of stone N, and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°11' W, beginning new measurement.</p>
40.13	<p>The cor. of secs. 15, 16, 21, and 22, perpetuated by Sidney C. Kain, LS 1052, monumented with an iron pipe, 28 ins. long, 1 in. diam., firmly set, projecting 14 ins. above ground and in a mound of stone, 3 ft. base, to top, with cap mkd. 15 16 21 22 1052. Sidney C. Kain, LS 1052. This is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS																					
	<div style="text-align: center;"> <table border="1"> <tr> <td>T6S R16E</td> <td></td> </tr> <tr> <td>S16</td> <td>S15</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S21</td> <td>S22</td> </tr> <tr> <td colspan="2" style="text-align: center;">1986</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert iron pipe inside stainless steel post and raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of cor.</p> <p>The cor. is located 17 lks. W of fence, bears N and S.</p> <p>From this cor., the monument accepted in 1939 and 1946, bears N 7°24' W, 1.09 chs. dist., an iron pipe, 3 1/2 ins. diam., projecting 3 ft. above a mound of stone, 3 ft. base, 2 ft. high.</p> <hr/> <p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>S 89°11' W, bet. secs. 15 and 22.</p> <p>Over rolling land, along fence.</p> <p>38.97 The 1/4 sec. cor. of secs. 15 and 22, perpetuated by Stitzer & Associates, Inc., monumented with a rebar, 3/4 in. diam., firmly set, projecting 8 ins. above ground, mkd. 1/4 15 22 LS 4399, with a steel fence post alongside. This is accepted as a careful and faithful perpetuation of the original corner position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T6S R16E</td> <td></td> </tr> <tr> <td>S15</td> <td></td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td>S22</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">1986</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert rebar inside stainless steel post.</p> <p>The cor. is located 38 lks. S of fence, bears E and W.</p> <hr/> <p>S 89°05' W, beginning new measurement.</p>	T6S R16E		S16	S15			S21	S22	1986		T6S R16E		S15		1/4	_____	S22		1986	
T6S R16E																					
S16	S15																				
S21	S22																				
1986																					
T6S R16E																					
S15																					
1/4	_____																				
S22																					
1986																					

BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS																									
38.315	<p>Point for a witness point on the W bdy. of the San Carlos Indian Reservation.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table data-bbox="841 493 1055 646" style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td style="text-align: center;">WP</td> <td></td> <td style="text-align: center;">S</td> </tr> <tr> <td style="text-align: center;">S15</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td> <td style="text-align: center;">S15</td> <td style="text-align: center;">C</td> </tr> <tr> <td colspan="4" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S22</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td> <td style="text-align: center;">S22</td> <td style="text-align: center;">I</td> </tr> <tr> <td colspan="4" style="text-align: center;">1986</td> </tr> <tr> <td colspan="4" style="text-align: center;">R</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>From this point station 2 Miles plus 04.81 chs., bears N 0°15' W, 14.455 chs. dist., hereinbefore described.</p>		WP		S	S15		S15	C	-----				S22		S22	I	1986				R			
	WP		S																						
S15		S15	C																						

S22		S22	I																						
1986																									
R																									
38.93	<p>The cor. of secs. 15, 16, 21, and 22.</p> <hr/> <p>N 0°28' W, bet. secs. 15 and 16.</p> <p>Over rolling land.</p>																								
39.33	<p>The 1/4 sec. cor. of secs. 15 and 16, perpetuated by Stitzer & Associates Inc., monumented with a rebar, 24 ins. long, 3/4 in. diam., firmly set, projecting 4 ins. above ground, with aluminum cap mkd. 1/4 15 16 LS 4399, with a steel fence post alongside. This is accepted as a careful and faithful perpetuation of the original corner position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over another steel fence post, with brass cap mkd.</p> <table data-bbox="852 1570 990 1690" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T6S R16E</td> </tr> <tr> <td colspan="2" style="text-align: center;">1/4</td> </tr> <tr> <td style="text-align: center;">S16</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td> <td style="text-align: center;">S15</td> </tr> <tr> <td colspan="3" style="text-align: center;">1986</td> </tr> </table>	T6S R16E		1/4		S16		S15	1986																
T6S R16E																									
1/4																									
S16		S15																							
1986																									

BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Insert rebar inside stainless steel post.</p> <p>The cor. is located on steep NW slope.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0°28' W, beginning new measurement.</p> <p>39.33 The cor. of secs. 9, 10, 15, and 16, perpetuated by Stitzer & Associates Inc., monumented with a rebar, 3/4 in. diam., firmly set, projecting 10 ins. above ground, with aluminum cap mkd. 9 10 15 16 LS 4399 in a scattered mound of stone, 3 ft. base, 1 ft. high, with a steel fence post alongside. The original conglomerate stone, 16 x 6 x 6 ins., mkd. with 3 and 4 notches on the edges is lying loose alongside.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 0 5px;">T6S</td> <td style="padding: 0 5px;">R16E</td> </tr> <tr> <td style="padding: 0 5px;">S 9</td> <td style="padding: 0 5px;">S10</td> </tr> <tr> <td colspan="2" style="text-align: center; border-top: 1px solid black; border-bottom: 1px solid black; width: 100px;"></td> </tr> <tr> <td style="padding: 0 5px;">S16</td> <td style="padding: 0 5px;">S15</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1986</td> </tr> </table> </div> <p>Deposit a magnet beneath the stainless steel post.</p> <p>Insert rebar inside stainless steel post and bury the original stone alongside.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>The cor. is located 10 1/2 lks. S of fence, bears E and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>S 88°43' W, bet. secs. 10 and 15.</p> <p>Over rolling land.</p>	T6S	R16E	S 9	S10			S16	S15	1986	
T6S	R16E										
S 9	S10										
S16	S15										
1986											

BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS																
38.98	<p>The 1/4 sec. cor. of secs. 10 and 15, perpetuated by Stitzer & Associates Inc. monumented with a rebar, 3/4 in. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd. 1/4 10 15 LS 4399, with a steel fence post alongside. This is accepted as a careful and faithful perpetuation of the original corner position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R16E S10 1/4 ——— S15 1986</p> </div> <p>Deposit a magnet beneath the stainless steel post.</p> <p>Insert rebar inside stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N of cor.</p> <hr style="width: 20%; margin: auto;"/> <p>S 88°43' W, beginning new measurement.</p>															
38.085	<p>Point for a witness point on the W bdy. of the San Carlos Indian Reservation.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td></td> <td>WP</td> <td>S</td> </tr> <tr> <td>S10</td> <td> S10</td> <td>C</td> </tr> <tr> <td colspan="3" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S15</td> <td> S15</td> <td>I</td> </tr> <tr> <td colspan="2" style="text-align: center;">1986</td> <td>R</td> </tr> </table> </div> <p>Deposit a magnet beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, N of point.</p> <p>Set a steel fence post alongside the point.</p> <p>The point is located in fence, bears N and S.</p> <p>From this point an AP, identical with station 2 Miles plus 76.73 chs., bears N 0°15' W, 7.69 chs. dist., hereinbefore described.</p>		WP	S	S10	S10	C				S15	S15	I	1986		R
	WP	S														
S10	S10	C														
S15	S15	I														
1986		R														

BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS	
38.98	The cor. of secs. 9, 10, 15, and 16.
	<hr/> <p>N 0°19' W, bet. secs. 9 and 10.</p> <p>Over rolling land.</p>
40.07	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor. position.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, 6 ins. high, with brass cap mkd.</p> <p style="text-align: center;">T6S R16E 1/4 S 9 S10 1986</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, NE of the cor. to prevent erosion of cor.</p> <hr/> <p>N 0°17' W, beginning new measurement.</p>
39.55	<p>The cor. of secs. 3, 4, 9, and 10, monumented with a basalt stone, 16 x 10 x 8 ins., firmly set, projecting 10 ins. above ground, mkd. with 5 notches on the S edge and 3 notches on the E edge, with a mound of stone, 3 ft. base, 1 ft. high, N, from which the remains of an original bearing tree</p> <p style="text-align: center;">A dead and down paloverde, 4 ins. diam. (original position indeterminate), bears S 18° W, 82 lks. dist., no marks remain on rotted blaze. (Record: S 29° W, 80 lks.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS						
	<div style="text-align: center;"> <table border="1"> <tr><td>T6S R16E</td></tr> <tr><td>S 4 S 3</td></tr> <tr><td>— —</td></tr> <tr><td>S 9 S10</td></tr> <tr><td>1986</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post and bury the original stone alongside.</p> <p>Remove the mound of stone N and utilize the stones in supporting the monument.</p>	T6S R16E	S 4 S 3	— —	S 9 S10	1986
T6S R16E						
S 4 S 3						
— —						
S 9 S10						
1986						
38.705	<p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>S 88°35' W, bet. secs. 3 and 10.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T6S R16E</td></tr> <tr><td>S 3</td></tr> <tr><td>1/4 ———</td></tr> <tr><td>S10</td></tr> <tr><td>1986</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>The cor. is located on SE slope, and 150 lks. E of spur, slopes SW.</p>	T6S R16E	S 3	1/4 ———	S10	1986
T6S R16E						
S 3						
1/4 ———						
S10						
1986						
73.635	<p>Point for a witness point on the W bdy. of the San Carlos Indian Reservation.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p>					

BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS																
	<div style="text-align: center;"> <table border="0"> <tr> <td></td> <td>WP</td> <td>S</td> </tr> <tr> <td>S 3</td> <td> S 3</td> <td>C</td> </tr> <tr> <td colspan="3" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S10</td> <td> S10</td> <td>I</td> </tr> <tr> <td></td> <td>1986</td> <td>R</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, E of point.</p> <p>The point is located in fence, bears N and S.</p> <p>From this point an AP, identical with station 3 Miles plus 71.20 chs., bears N 2°03' E, 2.465 chs. dist., hereinbefore described.</p> <p>77.41 The cor. of secs. 3, 4, 9, and 10.</p>		WP	S	S 3	S 3	C				S10	S10	I		1986	R
	WP	S														
S 3	S 3	C														
S10	S10	I														
	1986	R														
	<p>N 0°34' W, bet. secs. 3 and 4.</p> <p>Over rolling land.</p>															
	<p>40.62 Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R16E</p> <p>1/4</p> <p>S 4 S 3</p> <p>1986</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>The cor. is located on gentle S slope.</p>															
81.40	<p>Intersect the First Standard Parallel South.</p> <p>Point for the closing cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>															

BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS

T5S R16E
S 33

S 4	S 3
T6S R16E	
CC	
1986	

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, S of cor.

The cor. is located on NE slope.

From this point the original closing cor. of secs. 3 and 4, recovered by Averill and Litz in 1946, bears N 0°34' W, 0.08 chs. dist., monumented with a granite stone, 20 x 16 x 10 ins., firmly set, projecting 14 ins. above ground, mkd. with 3 notches on the E edge only, with a mound of stone, 4 ft. base, 2 ft. high, S. Add the marks AM and bury the stone in place. Remove the mound of stone and utilize the stones in supporting the 1986 monument.

From this same point the stan. cor. of secs. 33 and 34, T 5 S, R 16 E, bears N 89°56' E, 7.64 chs. dist., hereinbefore described.

The point for the 1/4 sec. cor. of sec. 3 only, T 6 S, R 16 E, on the First Standard Parallel South, is at midpoint on the N bdy. of sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T5S R16E

1/4 S 3
T6S R16E
1986

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, S of cor.

Set a steel fence post alongside the cor.

BOOK 5324

Dependent Resurvey, a Portion of the Subdivisional Lines,
T 6 S, R 16 E, Gila and Salt River Mer., Arizona

CHAINS

From this point the stan. 1/4 sec. cor. of sec. 34, T 5 S, R 16 E, bears N 89°56' E, 8.085 chs. dist., hereinbefore described.

The point for the 1/4 sec. cor. of sec. 4 only, T 6 S, R 16 E, on the First Standard Parallel South, is at midpoint on the N bdy. of sec. 4.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T5S R16E

1/4 S 4
T6S R16E
1986

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Set a steel fence post alongside the cor.

From this point the stan. 1/4 sec. cor. of sec. 33, T 5 S, R 16 E, bears N 89°51' E, 7.90 chs. dist., hereinbefore described.

GENERAL DESCRIPTION

The land encompassed in this survey is located on the easterly side of State Highway 77 and about 6 miles southeast from Winkelman, Arizona. The elevation ranges from about 2,000 to 4,000 feet above sea level. The land is gently rolling to mountainous, covered with paloverde, catclaw, creosote, and cactus.

Access is provided by a few unimproved dirt roads from State Highway 77.

Gypsum mines are located in sec. 27.

BOOK 5324

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Paul L. Reeves	Cadastral Surveyor
Robert D. Begley	Land Surveyor (In Training)
Luke B. Granger	Surveying Technician
Robert M. Charboneau	Surveying Technician
Robert J. Lyle	Surveying Technician
David L. Belcher	Surveying Technician
Cheryl A. Baier	Surveying Technician
Rebecca Ramirez	Surveying Aid

CERTIFICATE OF SURVEY

We, Duane R. Garoutte and William P. Carpender, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 5th day of March 1986, and supplemental special instructions dated October 9, 1986, We have correctively dependently resurveyed and dependently resurveyed portions of the south and west boundaries of the San Carlos Indian Reservation, and the First Standard Parallel South, on the south boundary of Township 5 South, Range 16 East, and the east boundary and subdivisional lines of Township 6 South, Range 16 East, of the Gila and Salt River Meridian, in the State of Arizona which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 15, 1989
(Date)

Duane R. Garoutte
(Cadastral Surveyor)

MAY 22, 1989
(Date)

William P. Carpender
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

Bureau of Land Management

The foregoing field notes of the corrective dependent resurvey and dependent resurvey of portions of the south and west boundaries of the San Carlos Indian Reservation, and the First Standard Parallel South, on the south boundary of T 5 S, R 16 E, and the east boundary and subdivisional lines of T 6 S, R 16 E, Gila and Salt River Meridian, Arizona, executed by Duane R. Garoutte and William P. Carpender, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

JUL 15 1991

(Date)

James P. Kelley
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I Certify That the foregoing transcript of the field notes of the above-described surveys in T 6 S, R 16 E, Gila and Salt River Mer., Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~