BOOK 5327 ORIGINAL

# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

## FIELD NOTES

OF THE

DEPENDENT RESURVEY
OF PORTIONS OF THE NORTH BOUNDARY AND THE SUBDIVISIONAL LINES,
PORTIONS OF CERTAIN MINERAL SURVEYS,
THE SUBDIVISION OF SECTION 3
AND
A METES-AND-BOUNDS SURVEY IN
TOWNSHIP 23 NORTH, RANGE 18 WEST
Of the Gila and Salt River Meridian, In the State of Arizona
EXECUTED BY
Paul L. Reeves , Cadastral Surveyor
Under special instructions dated <u>February 1</u> , 1988, approved <u>February 1</u> 1988
, which provided for the surveys included under Group Number
703 and assignment instructions dated <u>January 11</u> , 1989.
Survey commenced <u>January 12</u> , 1989
Survey completed April 3 , 1989

## INDEX DIAGRAM

		TOWNSHIP _	23 NORTH	, RANGE <u>18 WI</u>	EST,	
	6	5	4 13	3 3 9	2	1
	7	8	9	10	11	12
	18	17	16	15	14	13
	19	20	21	22	23	24
	30	29	28	27	26	25
	31	32	33	34	35	36
M M M M M M M	IS 3520 Peggy IS 3520 Bullio	nal Lead ssee ykill ykill Mill Site on South Gypson na	14-16 17-17 17-19 19-21 21-24 24-26 26-27 , 47-48 27-28 28-31 31 33 33-34 34-34 , 42-44	MS 3073 MS 3073 MS 3368 MS 1427 MS 12732 MS 12732 Subdivis Metes—ar	Little Giant Johnny Bull	36-37, 40-42 37-38 38-40 44-45 45-47 48-49 49-50 50-55 ey 56-62

T.23 N., R.18 W., Gila and Salt River Meridian, Arizona

### **CHAINS**

The following field notes described the dependent resurvey of portions of the north boundary and the subdivisional lines, portions of certain mineral surveys, the subdivision of section 3 and a metes-and-bounds survey in Township 23 North, Range 18 West, Gila and Salt River Meridian, Arizona.

The north boundary was surveyed by Omar H. Case in 1872, and the subdivisional lines in 1873. Guy H. Richardson and Hugo Price resurveyed the north boundary in 1916. Donald E. Harding resurveyed the subdivisional lines in 1955. The history of the mineral surveys is contained in the survey record.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973 and the Special Instructions dated February 1, 1988, for Group No. 703, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of lines were determined by direct solar observations and refer to the true meridian. Distances and angles were measured using a Zeiss Elta 46 total station instrument.

The geographic position of the southeast corner of section 3, as determined from a tie made to U.S. Coast and Geodetic Survey triangulation station "CHLORIDE 1938", located in the NE quarter of section 31, T. 24 N., R. 18 W., is as follows:

NAD 27: Latitude: 35°24'15.69" N Longitude: 114°10'57.36" W

The magnetic declination as taken from quadrangle map CHLORIDE, ARIZ., published in 1968 by U.S. Geological Survey, is 15° E.


Dependent Resurvey, Portion of the N. Bdy., T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS	
4	Restoring the resurvey executed by
	Guy H. Richardson and Hugo Price in 1916.
	Beginning at the cor. of secs. 2, 3, 34, and 35, on the N. bdy.
	of the Tp., monumented with an iron post, 3 ins. diam.,
	projecting 9 ins. from the ground, with brass cap erroneously mkd., S2 S3 T23N R18W 1916.
	A mound of stone, 2 1/2 x 2 ft. is set W. of cor.
	Remark brass cap to read
	T24N R18W S34   S35
	S 3 S 2
	T23N
	1989 1916
	A power pole, bears NE, 50 lks. dist., lines extend NE and S.
	N. 89°09' W., on the N. bdy. of sec. 3.
	Over mountainous land, through moderate catclaw, oak brush, yucca, and cacti.
0.17	Point for witness point at intersection with line 4-1 of M. S. 3520, Bullion South.

Dependent Resurvey, Portion of the N. Bdy., T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

## **CHAINS**

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.

Set a steel fence post alongside the cor.

From this point, cor. 1 of M. S. 3520, Bullion South, bears N.59°30' E., 0.145 chs. dist., hereinafter described.

7.71 Point for witness point, at intersection with line 1-2 of M.S.1221, Schuylkill Millsite.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{WP} \\ \text{S.M.} & \begin{array}{c} \text{T24N R18W} \\ \text{S34} \end{array} \\ \text{MS 1221} & \begin{array}{c} \text{S 3} \\ \text{T23N} \end{array} \\ 1989 \end{array}$$

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.

Set a steel fence post alongside the cor.

Cor. is located in a wash, 40 lks. wide, 5 ft. deep, drains SW.

From this cor. point, cor. 1 of M.S. 1221, Schuylkill Millsite, bears S.3°39' E., 2.905 chs. dist., hereinafter described.

BOOK 5327

Dependent Resurvey, Portion of the N. Bdy.,
T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

	T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona
CHAINS	
18.04	Point for witness point at intersection with line 2-3 of M.S. 1221, Schuylkill.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, in a mound of stone, 4 1/2 ft. base to top, with brass cap mkd.
	T24N R18W S34 \ S.  S 3 \ MS 1221 T23N 1989
	from which a bearing object
	A cross on a granite boulder, 4 x 4 x 5 ft., bears S. 14°40' E., 6.6 ft. dist., mkd. X BO on the N. face.
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
	From this cor. point, cor. 3 of M.S. 1221, Schuylkill, bears S. 4°25' E., 4.08 chs. dist., hereinafter described.
32.41	Point for witness point at intersection with line 1-2 of the cancelled survey, M.S. 1013, Distaff.

# Dependent Resurvey, Portion of the N. Bdy., T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

	T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, in a mound of stone, 4 1/2 ft. base to top, with brass cap mkd.
	WP T24N R18W S34
	S'3 T23N R18W 1989
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
	From this cor. point, cor. 1 of the cancelled M.S. 1013, Distaff, bears S. 0°45 E., 4.30 chs. dist., hereinafter described.
	From this same cor. point, a local cor. bears N. 83°27' W., 0.06 chs. dist., monumented with a yellow plastic cap cemented flush in a boulder, 3 x 2 ft., projecting 1/2 ft. from the ground, mkd. RLS 8904. This point was established by Jack M. Kesler, LS 8904, in 1980, using improper control cors. and is not utilized in the course of this resurvey.
	From this same cor. point, another local cor. bears N. 66°10' W., 0.047 chs. dist., monumented with an open end pipe, 1 in. diam., projecting 6 ins. from the ground. Origin and date unknown, and is not utilized in the course of this resurvey.
39.00	A cor. of fences, extends S. and W.
39.90	Point for the 1/4 sec. cor. of sec. 34 only, at midpoint on the S. bdy. of sec. 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

BOOK 5327

Dependent Resurvey, Portion of the N. Bdy.,
T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS	
	T24N R18W
	1/4 S34
	T23N R18W
	1989
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
40.69	The 1/4 sec. cor. of sec. 3 only, monumented with an iron post, 1 in. diam., projecting 12 ins. from the ground, in a mound of stone, 2 1/2 ft. base, 6 ins. high, with brass cap mkd. as described in the official field note record of the 1916 resurvey.
	Remark brass cap to read
	T24N R18W
	1/4 S 3
	T23N R18W
	1989
	1916
	Cor. is located in a fence, bears E. and W.
	N. 89°14' W., beginning new measurement.
39.11	The closing cor. of secs. 33 and 34, monumented with an iron post, 2 ins. diam., projecting 28 ins. from the ground, in a mound of stone, 2 1/2 x 1 1/2 ft., with brass cap mkd. as described in the official field note record of the 1916 resurvey.
	Remark brass cap to read
	T24N R18W
	СС
	S33   S34
	s 3
	T23N
	1989
	1916
	Cor. is located in a fence, bears E. and W.
	I

Dependent Resurvey, Portion of the N. Bdy., T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

	T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona
CHAINS	
40.74	The cor. of secs. 3 and 4, only, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. from the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd. as described in the official field note record of the 1916 resurvey.
	Remark brass cap to read
	T24N R18W S33
	S 4 S 3 T23N 1989 1916
	Cor. is located in a fence, bears E. and W.
	Dependent Resurvey, Portion of the Subdivisional lines, T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona
	Restoring the resurvey executed by  Donald E. Harding in 1955
	From the cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 2 1/2 ins. diam., projecting 3 ins. from the ground, with brass cap mkd. as described in the official field note record of the 1955 resurvey.
	A mound of stone, 3 x 2 ft. is set W. of cor.

N. 2°40' E., bet. secs. 2 and 3.

Over mountainous land, through moderate catclaw, oak brush, yucca, and cacti.

3.885 Point for witness point at intersection with line 3-4 of M.S. 3073, Little Giant.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 2 1/2 ft. base to top, with brass cap mkd.

# B00K 5327

Dependent Resurvey, Portion of the Subdivisional lines, T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

	R. 18 W., Gila and Salt River Meridian, Arizona
CHAINS	
	WP T23N R18W S 3   S 2 L. G. MS 3073 1989
	cor. point, cor. 4 of M.S. 3073, Little Giant, bears E., 9.915 chs. dist., hereinafter described.
2 1/2 in. of stone,	ec. cor. of secs. 2 and 3, monumented with an iron post, diam., projecting 18 ins. from the ground, in a mound 3 ft. base to top, with brass cap mkd. as described in ial field note record of the 1955 resurvey.
N. 0°35'	E., beginning new measurement.
15.36 Point for M.S. 3520	witness point at intersection with line 2-3 of , Peggy.
I I	inless steel post, 28 ins. long, 2 1/2 ins. diam., n the ground, with brass cap mkd.
	WP P MS 3520
	S 3   S 2 T23N R18W 1989
	magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case he stainless steel post.
Raise a m	ound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of
Set a ste	el fence post alongside the cor.
Cor. is le	ocated 40 lks. S. of a track road, bears NE and SW.
cor. 3 of	cor. point, cor. 2 of M.S. 3520, Peggy, identical with M.S. Bullion South, bears N. 83°27 E., 3.095 chs. reinafter described.
	of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., ore described

# B00K 5327

Dependent Resurvey, Portion of the Subdivisional lines, T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

r	
CHAINS	
	From the cor. of secs. 2, 3, 10, and 11.
l.	N. 89°53' W., bet. secs. 3 and 10.
12.68	Point for witness point at intersection with line 3-4 of M.S. 3073, Altata.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base to top, with brass cap mkd.
	T23N S 3 A. S10 MS 3073
	S10 / MS 3073 R18W / 1989
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
	Cor. is located 10 lks. N. of a powerline, bears SE and NW.
	From this cor. point, cor. 4 of M.S. 2203, Silver Age, identical with cor. 4 of M.S. 3073, Altata, bears N. 29°41 E., 0.115 chs. dist., hereinafter described.
40.56	The 1/4 sec. cor. of secs. 3 and 10, monumented with an iron post, 2 1/2 ins. diam., projecting 16 ins. from the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd. as described in the official field note record of the 1955 resurvey.
	Not remonumented
:	Cor. is located in a powerline bears SE and NW.
	From this cor. point, U.S. Coast and Geodetic Survey Triangulation Station "CHLORIDE 1938" bears N. 61°20'36" W. (forward bearing) 261.649 chs. dist., monumented with a brass tablet, 3 1/2 ins. diam., set flush in a boulder with top mkd. CHLORIDE 1938 and a triangle in center. Both reference monuments are in and in good order.

Dependent Resurvey, Portion of the Subdivisional lines, T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

	1. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona
CHAINS	
	S. 89°58' W., beginning new measurement.
20.12	Point for the W. 1/16 sec. cor. of secs. 3 and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 11 ins. in the ground, in a mound of stone, 3 1/2 ft. base to top, with brass cap mkd.
	T23N R18W S 3 W 1/16 ——— S10 1989
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
30.30	A graded road, bears NE and SW.
34.80	Wash, 50 lks. wide, 3 ft. deep, drains S W.
37.16	Point for witness point at intersection with line 4-1 of M.S. 1273A, Silver Bell.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	WP T23N S.B. S 3
	MS 1273A \S10 R18W 1989
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.
	Set a steel fence post alongside the cor.
	From this cor. point, cor. 1 of M.S. 1273A, Silver Bell, identical with cor. 4 of M.S. 1273A, Sonoma, bears N. 18°43' W., 3.19 chs. dist., hereinafter described.

# B00K 5327

Dependent Resurvey, Portion of the Subdivisional lines,

	T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona
CHAINS	
40.24	The cor. of secs. 3, 4, 9, and 10, monumented with an iron post, 2 1/2 ins. diam., projecting 24 ins. from the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd. as described in the official field note record of the 1955 resurvey.
	Cor. is located 1 ch. E. of a wash, 75 lks. wide, 3 ft. deep, drains SE.
	N. 1°13' E., bet. secs. 3 and 4.
8.628	Point for witness point at intersection with line 1-4 of M.S. 1273A, Sonoma.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T23N R18W S 4 S 3 MS 1273A 1989
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	Raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.
	Set a steel fence post alongside the cor.
	From this cor. point, cor. 4 of M.S. 1273A, Sonoma, identical with cor. 1 of M.S. 1273A, Silver Bell, bears S. 18°31 E., 5.91 chs. dist., hereinafter described.
	From this same cor. point, an open end pipe, of unknown origin, 2 ins. diam., bears N. 15°30' W., 0.224 lks. dist., projecting 2 ins. from the ground.
20.055	The S 1/16 sec. cor. of secs. 3 and 4, established by Nathaniel Devlin of unknown date, monumented with an open end pipe 18 ins. long, 1 in. diam., projecting 1 in. from the ground, with a tag riveted to the side mkd. RCE 1855. This is accepted as a careful and faithful determination of the cor. position.

BOOK 5327

Dependent Resurvey, Portion of the Subdivisional lines,
T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona


	T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona
CHAINS	
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T23N R18W S 1/16 S 4   S 3 1989
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Deposit the local monument inside the stainless steel post.
	Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.
	Set a steel fence post alongside the cor.
40.11	The 1/4 sec. cor. of secs. 3 and 4, monumented with an iron post, 2 1/2 ins. diam., projecting 2 ins. from the ground, with brass cap mkd. as described in the official field note record of the 1955 resurvey.
40.20	N. 1°03' E., beginning new measurement.  The cor. of secs. 3 and 4 only, on the N. bdy. of the Tp., hereinbefore described.
	Dependent Resurvey, Portions of Certain Mineral Surveys, T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona
	M.S. 1428 Bullion Beck
	From cor. 2, perpetuated by Jack E. Kesler, RLS 8904, in 1980, monumented with a rebar, 24 ins. long, 5/8 in. diam., projecting 1 in. from the ground, in a mound of stone, 2 x 2 ft., with aluminum cap mkd. MS 1428 2 B.B. RLS 8904, from which an original bearing object
	A cross on a granite reef, bears S. 64°16' E., 55 ft. dist., mkd. X BR 2-1428 on the W. face. (Record: S. 63°45' E)
1	

## **CHAINS**

This is accepted as a careful and faithful perpetuation of the original cor. position.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Deposit the local monument inside the stainless steel post.

Set a steel fence post alongside the cor.

Cor. is located 3 lks. N. of a fence cor. fences extending N., E. and S.

From this cor. point, the 1/4 sec. cor. of sec. 3 only, on the N. bdy. of the Tp., bears N. 29°40' W., 17.57 chs. dist., hereinafter described.

S. 86°57' E., on line 1-2.

4.545 The North End Center, determined by a mound of stone, 3 x 2 ft.; this is accepted as the best available evidence of the original cor. position.

Not remonumented

9.09 Cor. 1, marked 1-1428 and a cross at true cor. point, on a granite reef, 10 x 10 x 10 ft., with cross located 6 ins. from the general surface, from which an original bearing object

A cross on same granite reef, bears N. 50°26' W., 2.2 ft. dist., mkd. X BR 1 1428 on SE face. (Record: N. 48°20' W.)

Dependent Resurvey, Portions of Certain Mineral Surveys, T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

### **CHAINS**

At the cor. point

Set an aluminum post, 8 ins. long, 3/4 in. diam., 3 ins. in a drill hole, in granite reef, cemented in place, with magnetized aluminum cap mkd.

S. 10°38' W., on line 4-1.

18.245

Cor. 2 of M.S. 3595B, Terminal, monumented with a granite boulder, 2 1/2 x 2 x 1 ft., loosely set, mkd. X 2 TMS 3595B.

A mound of stone, 3 1/2 x 1 1/2 ft. is set SE of cor.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Set a steel fence post alongside the cor.

From this cor. point, cor. 4, identical with cor. 1 of M.S. 1428, Little Wonder, bears S. 10°41 W., 0.49 chs. dist.

From this same point, cor. 3 of M.S. 3363, Montana, bears N. 66°28 W., 6.8 lks. dist.

# B00K 5327

CHAINS	
CHAINS	M.S. 3595B Terminal
	From cor. 2, hereinbefore described.
	N. 83°35' E., on line 2-3.
5.26	Cor. 3, identical with cor. 3, M.S. 1427 Great Lead, monumented with a schist stone, 24 x 24 x 18 ins., projecting 12 ins. from the ground, mkd. X on top, 3 TMS 3595B on S. face and 3 GL 1427 on N. face.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T23N G.L. S 3 MS 1427 R18W 3
	T. 3 MS 3595B 1989
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
ī	Bury the stone in mound of stone.
	Raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.
	Set a steel fence post alongside the cor.
	Cor. is located 120 lks. W. of a graded road, bears SE and NW.
	M.S. 1427 Great Lead
	From cor. 3, identical with cor. 3 of M.S. 3595B, Terminal, hereinbefore described.
	N. 2°14' W., on line 2-3.

# B00K 5327

	1. 25 N., N. 10 W., Gila and Bare Rivel Periodall, Alizona
CHAINS	
22.60	Cor. 2, monumented with a wooden post, 1 x 2 ins., projecting 42 ins. from the ground, in a mound of stone, $2\ 1/2\ x\ 1$ ft., from which an bearing object
	A cross on a granite boulder, 6 x 5 x 4 ft., bears N. 87°20' W., 1.42 chs. dist., mkd. X on top and 2 1427 GL BR on SE. face (Record: N. 88°05' W.).
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T23N S 3 2 R18W G.L. MS 1427 1989
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Bury the wooden post in the mound of stone.
	Set a steel fence post alongside the cor.
	N. 87°44' E., on line 1-2.
4.535	The North End Center, on line 2-3 of M.S. 1427 Tennessee, monumented with a wooden post, 48 ins. long, 4 ins. sq., projecting 48 ins. from the ground, in a mound of stone 3 x 2 ft.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, in a mound of stone, 3 1/2 ft. base to top, with brass cap mkd.

Dependent Resurvey, Portions of Certain Mineral Surveys, T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

T23N	${f T}$
S 3	MS 1427
R18W	_
MS 1427	
198	19
	S 3 R18W NEC GL MS 1427

Deposit a magnet in a  $1 \times 1 \times 2$  5/8 ins. white plastic case beneath the stainless steel post.

Bury the wooden post in the mound of stone.

Set a steel fence post alongside the cor.

## M.S. 1427 Tennessee

From the North End Center of M.S. 1427, Great Lead, hereinbefore described.

N.  $5^{\circ}55'$  W., on line 2-3.

5.795 Cor. 2, monumented with a wooden post 48 ins. long, 4 ins. sq., projecting 18 ins. from the ground, in a mound of stone 2 1/2 x 2 ft., from which an bearing object

A cross on a granite boulder 1 1/2 x 1 x 1 1/2 ft., bears N. 38°26' W., 87.4 lks. dist., mkd. X 2 1427 on top. (Record: N. 39°30' W., 92.7 lks. dist.)

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, in a mound of stone, 3 1/2 ft. base to top, with brass cap mkd.

Dependent Resurvey, Portions of Certain Mineral Surveys, T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

**CHAINS** 

Deposit a magnet in a  $1 \times 1 \times 2$  5/8 ins. white plastic case beneath the stainless steel post.


Bury the original wooden post in the mound of stone.

Set a steel fence post alongside the cor.

N. 81°31' E., on line 1-2.

3.02 Point for witness point at intersection with line 3-4 of M.S. 1221, Schuylkill.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W. of cor.

Set a steel fence post alongside the cor.

From this cor. point, cor. 1 bears N. 81°31' E., 5.540 chs. dist., determined at record bearing and dist., from an original bearing object

A cross on a granite boulder, 2 1/2 x 2 1/2 x 3 1/2 ft., bears S. 8°30' E., 41.5 ft. dist., mkd. X BR 1427 on N.

### **CHAINS**

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Set a steel fence post alongside the cor.

Cor. is located 2 chs. E. of a wash, 30 lks. wide, 3 ft. deep, drains SW.

## M.S. 1221 Schuylkill

From the witness point at the intersection of line 3-4, with line 1-2 M.S. 1427 Tennessee, hereinbefore described.

From this cor. point, cor. 4 bears N. 84°24'E., 2.38 chs. dist., hereinbefore described.

S. 84°24' W., on a portion of line 3-4.

2.73 Cor. 3, monumented with a wooden post, 28 ins. long, 4 ins. sq., projecting 20 ins. from the ground, in a mound of stone 2 x 1 1/2 ft. high.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.

CHAINS	

Deposit a magnet in a  $1 \times 1 \times 2$  5/8 ins. white plastic case beneath the stainless steel post.

Bury the wooden post in the mound of stone.

Set a steel fence post alongside the cor.

N. 4°25' W., on line 3-2.

4.080 Witness point bet. secs. 3 and 34, hereinbefore described.

From this cor. point, the sec. cor. of secs. 2, 3, 34, and 35, bears S. 89°09' E., 18.04 chs. dist., hereinbefore described.

15.164 Cor. 2, monumented with a wooden post, 28 ins. long, 4 ins. sq., projecting 26 ins. from the ground, in a mound of stone 2 1/2 x 1 ft., with a metal tag mkd., SLC 2.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.

Deposit a magnet in a  $1 \times 1 \times 2$  5/8 ins. white plastic case beneath the stainless steel post.

Bury the wooden post in the mound of stone.

Set a steel fence post alongside the cor.

N. 85°33' E., on line 2-1

4.535

Cor. 1, monumented with a wooden post, 42 ins. long, 4 ins. sq., projecting 36 ins. from the ground, in a mound of stone  $2\ 1/2\ x\ 2$  ft.

At the cor. point

**CHAINS** 

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 3 1/2 ft. base to top, with brass cap mkd.

T24N R18W
S. 1 S34
MS 1221
1989

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Bury the wooden post in the mound of stone.

Set a steel fence post alongside the cor.

S. 6°36' E., on line 1-4.

6.72 Cor. 3, M.S. 1221, Schuylkill Millsite, determined at proportionate dist. on line 1-4; there is no remaining evidence of the original cor. position.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

T24N R18W
S
MS 1221
3 S.M.
MS 1221
1989

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Set a steel fence post alongside the cor.

From this cor. point, cor. 4, identical with cor. 4, M.S. 1221, Schuylkill Millsite, bears S. 6°36' E., 8.35 chs. dist., determined at record bearing and dist. from an original bearing object

Dependent Resurvey, Portions of Certain Mineral Surveys, T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

### **CHAINS**

A cross on a granite boulder, 9 x 8 x 4 ft., bears S. 6°55' E., 126 ft. dist., marks visible X BR on N. face.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Set a steel fence post alongside the cor.

Cor. is located 50 lks. W. of a wash, 30 lks. wide, 3 ft. deep, drains SW.

## Mineral Survey 1221 Schuylkill Millsite

From cor. 3, hereinbefore described

N. 84°01' E., on line 3-2

5.57 Point for cor 2, determined at record bearing and dist. from an original bearing object

A cross on a granite boulder, 2 x 1 1/2 x 2 ft., bears N. 19°07' E., 121.5 ft. dist., mkd. X BR 2 1221 on W.

At the cor. point

Dependent Resurvey, Portions of Certain Mineral Surveys, T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

T24N R18W

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Set a steel fence post alongside the cor.

S. 3°39' E., on line 2-1

5.470 Witness point at intersection with the line between secs. 3 and 34, hereinbefore described.

From this cor. point, the cor. of secs. 2, 3, 34 and 35 bears S. 89°09' E., 7.71 chs. dist., hereinbefore described.

8.375 Cor. 1, on line 1-4 of M.S. 3520 Peggy, monumented with a mound of stone 2 1/2 ft. base, 1 ft. high, from which an original bearing object

A cross on a pyramid-shaped granite boulder, 3 x 2 x 2 ft., bears S. 50°26' W., 48.25 ft. dist., mkd. X BR 3 1221 on N. (Record: S. 51°04' W.,)

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

# B00K 5327

CHAINS	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Set a steel fence post alongside the cor.
	M.S. 3520 Peggy
	From cor.1 of M.S. 1221 Schuylkill Millsite, hereinbefore described.
	N. 82°07' E., on line 4-1 of M.S. 3520, Peggy.
0.735	The North End Center, monumented with a wooden post, 48 ins. long, 4 ins. sq., projecting 42 ins. from the ground, in a mound of stone 4 x 3 ft.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T23N R18W S 3
	NEC
	P. MS 3520
	1989
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	Bury the wooden post in the mound of stone.
	Set a steel fence post alongside the cor.

CHAINS	T
	N. 83°28' E., beginning new measurement.
2.58	Cor. 1, identical with cor. 4 of M.S. 3520, Bullion South, monumented with a wooden post, 48 ins. long, 4 ins. sq., projecting 36 ins. from the ground, in a mound of stone 3 x 1 1/2 ft., mkd. BS 4 NW COR. BULLION SOUTH on SE face, and P 1 3520 NE COR. PEGGY on SW face.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T23N R18W S 3
	P. 1 4 B.S. MS 3520 MS 3520 1989
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	Bury the original wooden post in the mound of stone.
	Set a steel fence post alongside the cor.
	M.S. 3520 Bullion South
	From cor. 4, identical with cor. 1 of M.S. 3520, Peggy, hereinbefore described.
	N. 59°30' E., on line 4-1.
1.365	The North End Center, monumented with a wooden post, 4 ins. sq., projecting 42 ins. from the ground, in a mound of stone 3 x 2 ft., mkd. N. END CEN. BULLION SOUTH.
	Not remonumented

	T. 23 N., R. 18 W., Gila and Sait River Meridian, Arizona
CHAINS	
4.715	Witness point, on the line bet. secs. 3 and 34, hereinbefore described.
	From this cor. point, the cor of secs. 2, 3, 34, and 35, bears S. 89°09' E., 0.17 chs. dist., hereinbefore described.
4.86	Cor. 1, identical with cor. 1 of M.S. 3520, Burlock, monumented with a wooden post, 48 ins. long, 4 ins. sq., projecting 36 ins. from the ground.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, in a mound of stone, 3 1/2 ft. base to top, with brass cap mkd.
	T24N R18W S34
	1/1
	B.S. B.
	MS 3520 MS 3520 1989
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Bury the wooden post in the mound of stone.
	Set a steel fence post alongside the cor.
	From this cor. point, the cor of secs. 2, 3, 34, and 35, bears S. 31°46' E., 0.09 chs. dist.
	M.S. 1428 Molly Gipson
	From cor. 2, identical with cor. 3 of M.S. 1428, Little Wonder, monumented with a wooden post, 42 ins. long, 6 ins. sq., projecting 36 ins. from the ground, in a mound of stone 3 x 1 ft., from which an original bearing object
I	1

	T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona
CHAINS	
	A cross on a granite boulder, 3 x 2 1/2 x 1 ft., bears S. 26°30' W., 40.7 ft. dist., mkd. X BR 3 4 1428. (Record: S. 26°10' W., mkd. X BR 3 2 1428)
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 3 1/2 ft. base to top, with brass cap mkd.
	T23N MS 1428 T23N S 3 R18W 2 M.G. MS 1428 1989
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	Bury the wooden post in the mound of stone.
	Set a steel fence post alongside the cor.
	From this cor. point, the 1/4 sec. cor. of sec. 3, only, bears N. 8°26' W., 35.23 chs. dist., hereinbefore described,
	S. 3°09' W., on line 2-3.
5.265	Witness point, on the E. and W. center line of sec. 3, hereinbefore described.
	From this cor. point, the center 1/4 of sec. 3, bears N. 89°26' W., 5.94 chs. dist., hereinbefore described.
22.725	Cor. 3, monumented with a wooden post, 42 ins. long, 6 ins. sq., projecting 36 ins. from the ground, in a mound of stone 3 1/2 x 2 ft., from which an original bearing object

Dependent Resurvey, Portions of Certain Mineral Surveys, T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

**CHAINS** 

A cross on a granite boulder, 3 1/2 x 3 x 1 1/2 ft., bears N. 86°57' W., 32.5 ft. dist., mkd. X BR 3 1428. (Record: N. 87°40' W.)

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.

Deposit a magnet in a  $1 \times 1 \times 2$  5/8 ins. white plastic case beneath the stainless steel post.

Bury the wooden post in the mound of stone.

Set a steel fence post alongside the cor.

S. 86°52' E., on line 3-4.

The South End Center, monumented with a mound of stone 2 x 1 1/2 ft., with the remains of a wooden post, 36 ins. long, 6 ins. sq., lying loose alongside.

Not remonumented

9.085 Cor. 4, on line 2-3 of M.S. 3363 Arizona, determined at record bearing and dist., from an original bearing object

A cross on a granite boulder, 3 1/2 x 3 x 1 1/2 ft., bears N. 27°50' W., 49.5 ft. dist., mkd. X BR 4 1428 on top.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.

## CHAINS

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W. of cor.

Set a steel fence post alongside the cor.

## M.S. 3363 Arizona

From cor. 4 of M.S. 1428, Molly Gipson, on line 2-3, hereinbefore described.

S. 3°22' W., on line 2-3.

3.385

Cor. 3, monumented with a granite stone,  $28 \times 9 \times 9$  ins., projecting 13 ins. from the ground, in a mound of stone  $3 \times 1$  ft., mkd. X on top and 3 3363 on E. face, from which an original bearing object

A cross on a granite boulder, 3 1/2 x 2 1/2 x 2 1/2 ft., bears S. 29°30' E., 40.8 ft. dist., mkd. X BR 3 3363A on top. (Record: 40.4 ft. dist.)

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.

## CHAINS

Deposit a magnet in a  $1 \times 1 \times 2$  5/8 ins. white plastic case beneath the stainless steel post.

Bury stone in mound of stone.


Set a steel fence post alongside the cor.

S. 66°29' E., on line 3-4.

9.16 Cor. 4, monumented with a granite stone 22 x 8 x 5 ins., projecting 12 ins. from the ground, mkd. X on top and 4 3363A on N. face.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Bury stone in the mound of stone.

Set a steel fence post alongside the cor.

N. 2°34' E., on line 4-1.


18.45 Cor. 1. o

Cor. 1, on line 1-2 of M.S. 3363 Montana, monumented with a granite stone  $30 \times 8 \times 8$  ins., projecting 12 ins. from the ground, in a mound of stone  $2 \times 1$  ft., mkd. X on top and 1 3363A on S. face.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.

## CHAINS



Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Bury the stone in the mound of stone.

Raise a mound of stone, 4 ft. base, 2 1/2 ft. high, W. of cor.

Set a steel fence post alongside the cor.

## M.S. 3363 Montana

From cor. 1 of M.S. 3363, Arizona, hereinbefore described.

S. 66°30' E., on line 1-2

4.705

Cor. 1, on line 2-3 of M.S. 3368 Silver Knight, determined at record bearing and dist. from an original bearing object

A cross on a granite boulder, 3 x 2 x 2 ft., bears N. 73°42' W., 13.5 ft. dist., mkd. X on top and BR 1 3363 M on W. face.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Deposit a magnet in a  $1 \times 1 \times 2 = 5/8$  ins. white plastic case beneath the stainless steel post.

## **CHAINS**

Raise a mound of stone, 4 ft. base, 2 ft. high, W. of cor.

Set a steel fence post alongside the cor.

Cor. is located 50 lks. N. of a wash, 20 lks. wide, 4 ft. deep, drains SW.

From this cor. point, cor. 2 of M.S. 3368, Silver Knight, identical with cor. 2 of M.S. 3368, Johnny Bull, bears N. 1°53' W., 12.61 chs. dist., monumented with remains of rotted wooden post in a mound of stone 2 1/2 x 1 ft., from which an original bearing object

A cross on a granite boulder, 4 1/2 x 1 1/2 x 3 ft., bears S. 70°17' W., 91.2 ft. dist., mkd. X BR 2 JB, and other illegible chisel marks.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 1/2 ft. base to top, with brass cap mkd.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Bury remains of original wooden post alongside the cor.

Set a steel fence post alongside the cor.

## M.S. 3368 Silver Knight

From cor. 1 of M.S. 3363, Montana, hereinbefore described.

S. 1°51' E., on line 2-3.

8.60 Point for a witness point at intersection with line 2-3 of M.S. 2203, Silver Age.

Dependent Resurvey, Portions of Certain Mineral Surveys, T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

## CHAINS


Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 1/2 ft. base to top, with brass cap mkd.

Deposit a magnet in a  $1 \times 1 \times 2$  5/8 ins. white plastic case beneath the stainless steel post.

Set a steel fence post alongside the cor.

From this cor. point, cor. 3 of M.S. 3368, Silver Knight, bears S. 1°51' E., 1.54 chs. dist., determined at proportionate dist., there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Set a steel fence post alongside the cor.

From this cor. point, the South End Center, bears N. 81°32' E.,4.555 chs. dist., monumented with a wooden post, 4 ins. sq., loosely set, in a mound of stone 3 x 1 ft., not remonumented.


# B00K 5327

CHAING	T
CHAINS	M.S. 2203 Silver Age
	From the witness point on line 2-3, M.S. 3368 Silver Knight, hereinbefore described.
	N. 88°43' W., on a portion of line 2-3.
0.135	Cor. 3, at proportionate dist., there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 3 1/2 ft. base to top, with brass cap mkd.
	T23N R18W
	S 3 3 S.A. MS 2203 1989
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
	Cor. is located 90 lks. E. of a track road, bears NE and SW.
	S. 1°38' W., on line 3-4.
22.58	Cor.4, identical with cor. 4 of M.S. 3073, Altata, monumented with a the remains of a wooden post, in an embedded mound of stone, from which an original bearing object
	A cross on a granite boulder, 2 x 2 1/2 x 1 1/2 ft., bears N. 33°31' E., 24 ft. dist., mkd. X BR 2203 SW on top. (Record: N. 32°50' E.,)
	At the cor. point

Dependent Resurvey, Portions of Certain Mineral Surveys, T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

#### **CHAINS**

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base to top, with brass cap mkd.



Deposit a magnet in a  $1 \times 1 \times 2$  5/8 ins. white plastic case beneath the stainless steel post.

Bury original wooden post alongside the cor.

Set a steel fence post alongside the cor.

Cor. is located 50 lks. S. of a wash, 20 lks. wide, 10 ft. deep, drains SW.

### M.S. 3073 Altata

From cor. 4, identical with cor. 4 of M.S. 2203, Silver Age, hereinbefore described.

S. 29°41' W., on line 4-3.

0.115 Witness point on the line bet. secs. 3 and 10, hereinbefore described.

From this cor. point, the cor. of secs. 2, 3, 10, and 11 bears S. 89°53′ E., 12.68 chs. dist., hereinbefore described.

4.46 Cor. 3, monumented with a granite stone, 24 x 15 x 8 ins., projecting 18 ins. from the ground, mkd. with an X on top and A 3 3073 on E. face. A mound of stone 3 x 1 ft. is W. of cor.

Dependent Resurvey, Portions of Certain Mineral Surveys, T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

#### **CHAINS**

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\begin{array}{c}
\text{T23N} & \text{A.} \\
\text{S10} & \text{3} \\
\text{R18W} & \text{MS} & 3073
\end{array}$$

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Bury original stone alongside the cor.

Set a steel fence post alongside the cor.

From this cor. point, the cor. of secs. 2, 3, 10 and 11, bears N. 75°46' E., 15.29 chs. dist., hereinbefore described.

## Mineral Survey 3073 Little Giant

From cor. 4, monumented with a schist stone 24 x 18 x 8 ins., projecting 24 ins. from the ground, in a mound of stone 3 ft. base, 1 ft. high, mkd. X on top, and LG 4 3073 on W., from which original bearing objects

- A cross on a schist boulder, 2 1/2 x 2 1/2 ft., projecting 2 1/2 ft. from the ground, bears S. 89°50' E., 22.4 ft. dist., mkd. X BR 4 3073 on W. (Record: N. 89°23' E., 22.7 ft. dist.)
- A cross on a granite boulder, 12 x 10 ft., projecting 8 ft. from the ground, bears S. 22°20' E., 75.9 ft. dist., mkd. X BR 4 3073 on N. (Record: S. 0°40' E., 73.2 ft. dist.)

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, in a mound of stone, 3 1/2 ft. base to top, with brass cap mkd.

Dependent Resurvey, Portions of Certain Mineral Surveys, T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

#### CHAINS

Deposit a magnet in a  $1 \times 1 \times 2$  5/8 ins. white plastic case beneath the stainless steel post.

Bury original stone in the mound of stone.

Set a steel fence post alongside the cor.

From this cor. point, the cor. of secs. 2, 3, 10 and 11, bears N. 72°20' E., 8.17 chs. dist., hereinbefore described.


N. 50°06' W., on line 3-4.

9.915 Witness point, on the line bet. secs. 2 and 3, hereinbefore described.

From this cor. point, the cor. of secs. 2, 3, 10, and 11 bears S. 2°40' W., 3.885 chs. dist., hereinbefore described.

14.455 Point for a witness point at intersection with line 1-2 of M.S. 2203, Silver Age, .

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 2 1/2 ft. base to top, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Set a steel fence post alongside the cor.

From this cor. point, Cor. 3, bears N.  $50^{\circ}06^{\circ}$  W., 2.55 chs. dist., monumented with a schist stone,  $20 \times 10 \times 10$  ins., projecting 12 ins. from the ground, in a mound of stone  $3 \times 1$  ft., mkd. X LG on top, and 3 3073 on SW face, from which original bearing objects


A cross on a schist boulder, 3 x 2 1/2 x 4 ft., bears N. 38°39' E., 10.5 ft. dist., mkd. X BR 3 3073 on W. face.

#### **CHAINS**

A cross on a schist boulder, 3 1/2 x 3 x 1 ft., bears N. 12°47' W., 33.5 ft. dist., mkd. X BR 3 3073 on top. (Record: 32.5 ft. dist.)

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.

Bury original stone in the mound of stone.

Set a steel fence post alongside the cor.

From this same cor. point, cor. 1 of M.S. 2203, Silver Age, bears S. 1°56' W., 6.975 chs. dist., hereinafter described.

### Mineral Survey 2203 Silver Age

From the witness point on line 1-2 at intersection with line 3-4 M.S. 3073, Little Giant, hereinbefore described.

From this cor. point, cor. 1, bears S.1°56 W., 6.975 chs. dist., monumented with remains of a wooden post, 4 ins. sq., loosely set, in a mound of stone 3 ft. base, 2 ft. high, from which an original bearing object

A cross on a granite boulder, 2 1/2 x 1 x 2 ft., bears N. 10°36' W., 10.4 ft. dist., mkd. X BR 2203 NSE on top. (Record: N. 9°55' W., 10.8 ft. dist.)

Dependent Resurvey, Portions of Certain Mineral Surveys, T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

#### **CHAINS**

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Bury the original wooden post alongside cor.

Set a steel fence post alongside the cor.

N. 1°56' E., on a portion of line 1-2.

15.70

Cor. 2, monumented with a wooden post, 26 ins. long, 4 ins. sq., projecting 18 ins. from the ground, in a mound of stone 2 ft. base, 1 ft. high, with illegible scribe marks.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 4 1/2 ft. base to top, with brass cap mkd.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Bury the original wooden post in the mound of stone.

Set a steel fence post alongside the cor.

N. 88°43' W., on line 2-3.


Dependent Resurvey, Portions of Certain Mineral Surveys, T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

#### CHAINS

### 0.040

Point for witness point at intersection with line 3-4 of M.S. 3368, Silver Knight.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.

Set a steel fence post alongside the cor.

From this cor. point cor. 3 bears N. 88°43' W., 9.165 chs. dist., hereinbefore described,

From this same cor. point, the South End Center of M.S. 3368 Silver Knight, bears S. 81°32' E., 4.513 chs. dist., hereinbefore described.

## M.S. 3368 Silver Knight

From the witness point at the intersection of line 3-4 with line 2-3 M.S. 2203 Silver Age, hereinbefore described.


N. 81°32' E., on a portion of line 3-4.

#### 0.042

Cor. 4, monumented with a wooden post, 48 ins. long, 4 ins. sq., projecting 30 ins. from the ground, in a mound of stone 2 ft. base, 1 ft. high, with illegible scribe marks.

#### CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 3 1/2 ft. base to top, with brass cap mkd.



Deposit a magnet in a  $1 \times 1 \times 2$  5/8 ins. white plastic case beneath the stainless steel post.

Bury the original wooden post in the mound of stone.

Set a steel fence post alongside the cor.

N. 3°33' W., on line 4-1.

16.935 Witness point on the E. and W. center line of sec. 3, hereinbefore described.


From this cor. point, the 1/4 sec. cor. of secs. 2 and 3, bears S. 89°26' E., 5.65 chs. dist., hereinbefore described.

Cor. 1, identical with cor. 1 of M.S. 3368, Johnny Bull, monumented with a wooden post, 48 ins. long, 4 ins. sq., projecting 30 ins. from the ground, in a mound of stone 4 x 2 ft., mkd. NE COR 1 SILVER KNIGHT 3368 on SW face and SE COR 1 JOHNNY BULL 3368 on NW face, from which an original bearing object

A cross on a granite boulder, 7 x 5 x 4 1/2 ft., bears S. 64°05' E., 23.2 ft. dist., mkd. X BR 1 JB 1 SK 3368 on NW. (Record: S. 63°47' E., 21.7 ft. dist.)

#### **CHAINS**

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, in a mound of stone, 4 1/2 ft. base to top, with brass cap mkd.



Deposit a magnet in a  $1 \times 1 \times 2$  5/8 ins. white plastic case beneath the stainless steel post.

Bury the wooden post in the mound of stone.

Set a steel fence post alongside the cor.

## M.S. 3368 Johnny Bull

From cor. 1, identical with cor. 1 of M.S. 3368, Silver Knight, hereinbefore described.

N. 3°40' W., on line 4-1.


7.58 Cor. 4, on line 2-3 of M.S. 1427 Tennessee South, monumented with a wooden post, 48 ins. long, 4 ins. sq., projecting 36 ins. from the ground, in a mound of stone 3 1/2 x 2 1/2 ft., mkd., NE COR 4 JOHNNY BULL 3368 on SW face, from which an original bearing object

A cross on a granite boulder, 4 1/2 x 3 1/2 x 3 ft., bears N. 50°33' W., 54 ft. dist., mkd. X BR 4 JB 3368 on S. face (Record: N. 30°56' W.).

Dependent Resurvey, Portions of Certain Mineral Surveys, T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

#### **CHAINS**

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a  $1 \times 1 \times 2$  5/8 ins. white plastic case beneath the stainless steel post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.

Bury the original wooden post in the mound of stone.

Set a steel fence post alongside the cor.

### M.S. 1427 Tennessee South

From cor. 4, hereinbefore described.

N. 81°15' E., on line 2-3.

0.88

Cor. 2, monumented with the remains of a wooden post, 4 ins. sq., projecting 30 ins. from the ground, in a mound of stone 2 x 1 ft., from which an original bearing object

A cross on a granite boulder, 5 1/2 x 3 1/2 x 2 1/2 ft., bears N. 1°16' E., 47.5 ft. dist., mkd. X BR 2 1427 TS NEC 3353 on S. face (Record: N. 0°10' E.).

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a mound of stone, 2 1/2 ft. base to top, with brass cap mkd.

Dependent Resurvey, Portions of Certain Mineral Surveys, T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

	T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Bury the original wooden post in the mound of stone.
	Set a steel fence post alongside the cor.
	N. 8°25' W., on line 1-2.
0.60	The East Side Center, monumented with a wooden post, 4 ins. sq., projecting 36 ins. from the ground, in a mound of stone 3 x 1 1/2 ft., mkd. with illegible scribe marks on W. face.
	Not remonumented
1.20	Cor. 1, identical with cor. 4 of M.S. 1427, Tennessee, and cor. 3 of M.S. 3520, Peggy, monumented with a wooden post, 48 ins. long, 4 ins. sq., projecting 48 ins. from the ground, in a mound of stone 5 x 1 1/2 ft., mkd. with illegible scribe marks on N. face and S. face, from which original bearing objects
	A cross on a granite boulder, 6 x 5 x 2 ft., bears N. 7°54' E., 29 ft. dist., mkd. X BR 4 1427 and 1 1427 TS on S. face (Record: N. 7°15' E.).
	A cross on a granite boulder, 3 1/2 x 2 1/2 x 2 ft., bears N. 13°53' E., 6.22 ft. dist., mkd. X P 3 3520 on S. face (Record: N. 24°20' E.).
	A cross on a granite boulder, 3 1/2 x 3 x 2 ft., bears N. 65°44' E., 20.45 ft. dist., mkd. X P 3 3520 on W. face (Record: N. 65°32' E.).
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, in a mound of stone, 5 ft. base to top, with brass cap mkd.
	T. P. MS 1427 MS 3520 4 3
	1 T23N T.S. S 3 MS 1427 R18W

1989

CHAINS	ı		
	1		

Deposit a magnet in a  $1 \times 1 \times 2$  5/8 ins. white plastic case beneath the stainless steel post.

Bury the wooden post in the mound of stone.

Set a steel fence post alongside the cor.

## M.S. 3520 Peggy

From cor. 3, identical with cor. 1 of M.S. 1427, Tennessee South, and cor. 4 of M.S. 1427, Tennessee, hereinbefore described.

N. 83°27' E., on line 3-2.

4.545 The South End Center, monumented with a wooden post, 4 ins. sq., projecting 36 ins. from the ground, in a mound of stone 2 1/2 ft. base, 6 ins., high, mkd. 2520 on N. face.

Not remonumented

CHAINC


5.99 Witness point on the line bet. secs. 2 and 3, hereinbefore described.

From this cor. point, the 1/4 cor. of secs. 2 and 3, bears S. 0°35' W., 15.36 chs. dist., hereinbefore described.

9.085 Cor. 2, identical with cor. 3 of M.S. 3520, Bullion South, monumented with a wooden post, 48 ins. long, 4 ins. sq., projecting 36 ins. from the ground, in a mound of stone 3 1/2 x 1 1/2 ft., mkd. BULLION SOUTH on N. face, and illegible marks on W. face.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 1/2 ft. base to top, with brass cap mkd.



#### CHAINS

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Bury the wooden post in the mound of stone.

Set a steel fence post alongside the cor.

From this cor. point, the 1/4 sec. cor. of secs. 2 and 3, bears S. 11°37' W., 16.04 chs. dist., hereinbefore described.

#### M.S. 1273A Silver Bell

From cor. 4, monumented with a mound of stone,  $3 \times 2$  ft., from which an original bearing object

A cross on a granite boulder, 2 x 2 ft., flush with ground surface, bears S. 66°35' E., 4 ft. dist., marks visible X A on top.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Set a steel fence post alongside the cor.

Cor. is located 170 lks. E. of a graded road, bears NE and SW.

From this cor. point, the cor. of secs. 3, 4, 9 and 10, bears N. 26°48' W., 20.74 chs. dist., hereinbefore described.

N. 18°43' W., on line 4-1.

19.55 Witness point on the line bet. secs. 3 and 10, hereinbefore described.

	T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona
CHAINS	
	From this cor. point, the sec. cor. of secs. 3, 4, 9, and 10, bears S. 89°58' W., 3.08 chs. dist., hereinbefore described.
22.74	Cor. 1, identical with cor. 4 of M.S. 1273A, Sonoma, monumented with a open end pipe, 21 ins. long, 1 in. diam., projecting 4 ins. from the ground, in a scattered mound of stone, from which an original bearing object
	A cross on a granite boulder, 4 x 3 x 1 1/2 ft., bears S. 31°50' W., 34.4 ft. dist., mkd. X BR 4 1273A on NE face.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	S. MS 1273A 4 T23N N 3 T18W S.B. MS1273A 1989
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Deposit the open end pipe alongside the stainless steel post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Set a steel fence post alongside the cor.
	M.S. 1273A Sonoma
	From cor. 4, identical with cor. 1 of M.S. 1273A, Silver Bell, hereinbefore described.
	N. 18°31' W., on line 4-1.
5.91	Witness point on the line bet. secs. 3 and 4, hereinbefore described.
	From this cor. point, the cor. of secs. 3, 4, 9 and 10, bears S. 1°13' W., 8.628 chs. dist., hereinbefore described.

## CHAINS

22.65

Cor. 1, identical with cor. 1 of M.S. 1273A, Valley View, monumented with a mound of stone 3  $1/2 \times 2$  ft., from which an original bearing object

A cross on a granite boulder, 2 1/2 x 2 1/2 x 1 ft., bears N. 64°57' W., 87.1 ft. dist., mkd. X BR 1 1273A on E. face (Record: N. 65°10' W., 89 ft. dist.).

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

Set a steel fence post alongside the cor.

Subdivision of Section 3, T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

From the 1/4 sec. cor. of secs. 3 and 10.

N. 1°31' E., on the N. and S. center line of sec. 3.

Over gently rolling land, through moderate catclaw, sagebrush, cacti and scattered juniper.

19.845 Point for the center S 1/16 sec. cor. of sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.

## Subdivision of Section 3,

T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

	1. 23 N., R. 10 W., GIIA and Sait River Meridian, Arizona
CHAINS	
	T23N R18W
	S 1/16   S 3
	1989
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
39.69	The center 1/4 sec. cor. of sec. 3, monumented with an open end pipe 18 ins. long, 1 in. diam., set flush, with a tag riveted to the side mkd. RCE 1855, established by Nathaniel Devlin of unknown date. This is accepted as a careful and faithful determination of the position of the cor.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T23N R18W C 1/4 S 3 1989
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Raise a mound of stone, 3 ft. base 2 ft. high, W. of cor.
	Deposit the local monument inside the stainless steel post.
	Set a steel fence post alongside the cor.
	N. 1°31' E., beginning new measurement.
40.06	The 1/4 sec. cor. of sec. 3 only, on the N. bdy. of the Tp., hereinbefore described.
	From the 1/4 sec. cor. of secs. 2 and 3.
	N. 89°26' W., on the E. and W. center line of sec. 3.
5.65	Point for a witness point at intersection with line 1-4 of M.S. 3368, Silver Knight.

## Subdivision of Section 3,

T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

#### CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

S.K. 
$$\begin{array}{c} \text{WP} \\ \text{C} \\ \text{C} \\ \text{C} \end{array}$$
 S.K.  $\begin{array}{c} \text{T23N} \\ \text{C} \\ \text{S 3368} \end{array}$  R18W

Deposit a magnet in a  $1 \times 1 \times 2 = 5/8$  ins. white plastic case beneath the stainless steel post.

Raise a mound of stone, 3 1/2 ft. base 2 1/2 ft. high, N. of cor.

Set a steel fence post alongside the cor.

From this cor. point, cor. 1 of M.S. 3368, Silver Knight, identical with cor. 1 of M.S. 3368, Johnny Bull, bears N. 3°33' W., 5.745 chs. dist., hereinafter described.

Point for a witness point at intersection with line 2-3 of M.S. 1428, Molly Gipson.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Raise a mound of stone, 2 1/2 ft. base 1 1/2 ft. high, N. of cor.

Set a steel fence post alongside the cor.

From this cor. point, cor. 2 of M.S. 1428, Molly Gipson, identical with cor. 3 of M.S. 1428, Little Wonder, bears N. 3°09' E., 5.265 chs. dist., hereinafter described.

41.34 The center 1/4 sec. cor. of sec. 3.

N. 89°26' W., beginning new measurement.

17.245 | Point for cor. 1 lot 34, sec. 3.


Form 9600-10a (November 1987) USDI-BLM

## Subdivision of Section 3,

T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

OI		INIC
	[A]	

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.



Deposit a magnet in a  $1 \times 1 \times 2$  5/8 ins. white plastic case beneath the stainless steel post.

Set a steel fence post alongside the cor.

18.21 Graded gravel road, bears SE and NW.

18.405 Point for cor. 2 lot 34, identical with cor. 1 lot 35, sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Sct a steel fence post alongside the cor.

19.805 | Point for cor. 2 lot 35, identical with cor. 1 lot 36, sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

## Subdivision of Section 3,

T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a steel fence post alongside the cor.
	Cor. is located in a fence, bears SE and NW.
20.215	Point for the center W 1/16 sec. cor. of sec. 3, identical with cor. 2 lot 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 1 ins. below ground, with brass cap mkd.
	T23N R18W W 1/16 C————————————————————————————————————
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	Cor. is located in a residential yard.
40.43	The 1/4 sec. cor. of secs. 3 and 4.
	SW 1/4 of Section 3
	From the W 1/16 sec. cor. of secs. 3 and 10.
	N. 1°22' E., on the N. and S. center line of the SW 1/4 of sec. 3.
19.95	Point for the SW 1/16 sec. cor. of sec. 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T23N R18W SW 1/16 S 3 1989
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
	Cor. is located in a wash, 3 chs. wide, 5 ft. deep, drains SE.
35.451	Point for cor. 3 lot 37, sec. 3.

## B00K 5327

## Subdivision of Section 3,

T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

	T 25 No., No. 10 We, Gifa and Batt River Reflectan, Artzona		
CHAINS			
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.		
	COR. 3 LOT 37 S 3 T23N R18W 1989		
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.		
	Set a steel fence post alongside the cor.		
	Cor. is located 59 lks. S. of a yard fence, bears E. and W.		
38.621	Point for cor. 2 lot 37, identical with cor. 3 lot 36, sec. 3.		
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.		
	T23N COR. 3 LOT 36 S 3 R19W COR. 2 LOT 37 1989		
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.		
	Cor. is located in a fence, extends NE and SW.		
39.90	The center W 1/16 sec. cor. of sec. 3, identical with cor. 2 of lot 36.		
	From the center S 1/16 sec. cor. of sec. 3.		
	N. 89°42' W., on the E. and W. center line of the SW 1/4 of sec. 3.		
20.165	The SW 1/16 sec. cor. of sec. 3.		
40.33	The S 1/16 sec. cor. of sec. 3 and 4.		

Metes-and-Bounds Surveys,

T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

#### CHAINS

#### **MEMORANDUM**

This Metes-and-Bounds survey is identical with a portion of the cancelled M.S. 1013, Distaff. Lines 5-1 and 1-2 are the controlling lines of Patent 613073, dated 1/04/1989, in sec. 3, T.23 N., R.18 W..

From cor. 2 of M.S. 1428, Bullion Beck, identical with cor. 5 of cancelled M.S. 1013, Distaff, hereinbefore described.

From this cor. point, the 1/4 sec. cor. of sec. 3, only, on the N. bdy. of the tp., bears N. 23°40' W., 17.37 chs. dist., hereinbefore described.

N. 1°55' W.

7.745 A local monument, bears East, 0.012 chs. dist., monumented with a rebar, 5/8 in. diam., projecting 3 ins. from the ground, in a mound of stone, 3 x 2 ft., with yellow plastic cap attached and mkd. RLS 8904. This point was established by Jack E. Kesler, RLS 8904, in 1980, using improper control cors. and is not utilized in the course of this resurvey.

10.855 Cor. 1 of cancelled M.S. 1013, Distaff, monumented with a wooden post, 48 ins. long, 4 ins. sq., projecting 36 ins. from the ground, in a mound of stone 3 ft. base 2 ft. high, from which an original bearing object

A granite boulder, 5 x 3 x 3 ft., bears S. 86°14' W., 50.5 ft. dist., mkd. D 1 R on E. face (Record: S. 86°50' W., 51 ft. dist.).

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T23N R18W

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

## Metes-and-Bounds Surveys, T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

	25 No, No 16 We, Gild and bate Nivel heritatan, Arizona
CHAINS	
	Bury the original wooden post in the mound of stone.
	Set a steel fence post alongside the cor.
	N. 0°45' W., beginning new measurement.
4.30	Witness point on the line bet. secs. 3 and 34, hereinbefore described.
	From this cor. point, the 1/4 sec. cor. of sec. 34, only, T.24N., R.18 W., bears N. 89°09' W., 7.49 chs. dist.
	From this same cor. point, cor. 2 of the cancelled M.S. 1013 Distaff, bears N. 0°45' W., 7.00 chs. dist., monumented with a mound of stone, 3 1/2 x 3 ft., from which an original bearing object
	A granite boulder, 3 x 3 x 3 ft., bears S. 84°03' W., 68.2 ft. dist., marks visible, BR on E. face (Record: S. 82°20' W., 66 ft. dist.)
	Not remonumented
	Lot 34
	From cor. 1 of lot 34, sec.3, hereinbefore described.
	N. 89°26' W., on line 1-2, identical with a portion of the E. and W. center line of sec. 3.
1.16	Cor. 2, identical with cor. 1 of lot 35, sec. 3, hereinbefore described.
	S. 2°55' E., on line 2-3, identical with line 4-1 of lot 35, sec. 3.
2.728	Point for cor. 3, identical with cor. 4 of lot 35 sec. 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	1

Metes-and-Bounds Survey, T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS	
	COR. 4   COR. 3 LOT 35   LOT 34 S 3 T23N R18W
	1989
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
	Cor. is located in a fence, bears NE and SW.
	N. 88°12' E., on line 3-4.
1.16	Point for cor. 4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	COR. 4 LOT 34
	T23N R18W 1989
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
	Cor. is located at the cor. of fences extending SW and NW.
	N. 2°57' W., on line 4-1.
2.68	Cor. 1, point of beginning.

BOOK 5327

Metes-and-Bounds Surveys
T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS	
	Lot 35
	From cor. 1, identical with cor. 2 of lot 34, sec. 3, hereinbefore described.
	N. 89°26' W., on line 1-2, identical with a portion of the E. and W. center line of sec. 3.
1.40	Cor. 2, identical with cor. 1 of lot 36, sec. 3, hereinbefore described
	S. 4°53' E., on line 2-3, identical with line 1-4 of lot 36, sec. 3.
1.231	Point for cor. 4, identical with cor. 1 of lot 37, sec. 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	COR. 4 LOT 36 COR. 1 LOT 37 1989
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located at the cor. of fences extending N., S. and W.
	Continue measurement on line 2-3, identical with a portion of line 1-4 of lot 37, sec. 3.
2.79	Point for cor. 3, on line 1-4 lot 37, sec. 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	LOT 37 COR. 3 LOT 35 T23N S 3 R18W 1989

## Metes-and-Bounds Surveys,

T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
	Cor. is located at the intersection of fences extending N., E. and S.
	N. 88°12' E., on line 3-4, sec. 3.
1.30	Cor. 4, identical with cor. 3 of lot 34, sec. 3, hereinbefore described.
	N. 2°55' W., on line 4-1, identical with line 2-3 of lot 34, sec. 3.
2.728	Cor. 1, identical with cor. 2 of lot 34, sec. 3, and point of beginning.
	Lot 36
	From cor. 1, identical with cor. 2 of lot 35, sec. 3, hereinbefore described.
	N. 89°26' W., on line 1-2, identical with a portion of the E. and W. center line of sec. 3.
0.41	Cor. 2, identical with the center W 1/16 sec. cor. of sec. 3.
·	S. 1°22' W., on line 2-3, identical with a portion of the N. and S. center line of the SW 1/4 of sec. 3.
1.279	Cor. 3, identical with cor. 2 of lot 37, sec. 3, hereinbefore described.
	N. 84°59' E., on line 3-4, identical with line 1-2 of lot 37, sec. 3.
0.548	Cor. 4, identical with cor. 1 of lot 37, sec. 3, hereinbefore described.

Metes-and-Bounds Surveys,

T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

	1. 23 N., N. 10 W., GIR and Safe River reflecting / Hillord
CHAINS	
	N. 4°53' W., on line 4-1, identical with a portion of line 2-3 of lot 35, sec. 3.
1.231	Cor. 1, identical with cor. 2 of lot 35, sec. 3, and point of beginning.
	Lot 37
	From cor. 1, identical with cor. 4 of lot 36, on line 2-3 lot 35, sec. 3, hereinbefore described.
	S. 84°59' W., on line 1-2, identical with line 3-4 of lot 36, sec. 3.
0.548	Cor. 2, identical with cor. 3 of lot 36, sec. 3, hereinbefore described.
	S. 1°22' W., on line 2-3, identical with a portion of the N. and S. center line of the SW 1/4, of sec. 3.
3.17	Cor. 3, sec. 3, hereinbefore described.
	N. 88°36' E., on line 3-4.
0.895	Point for cor. 4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	COR. 4 LOT 37
	S 3 T23N R18W
	1989
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
	<del></del>

Metes-and-Bounds Surveys, T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona

	T. 23 N., R. 18 W., Gila and Salt River Meridian, Arizona
CHAINS	
	N. 4°53' W., on line 4-1.
1.649	Cor. 3, of lot 35, hereinbefore described.
	Continue measurement on line 4-1, identical with a portion of line 2-3 of lot 35, sec. 3.
3.208	Cor. 1, identical with cor. 4 of lot 36, sec. 3, and point of beginning.
	GENERAL DESCRIPTION
	The community of Chloride, Arizona, is located in section 3 of this survey. The elevation varies from 3,910 ft. to 4,484 ft. above sea level.
	The land varies from gently rolling to mountainous, covered with scattered to medium cat claw, oak brush, creosote, juniper and cacti.
	Access is by way of U.S. highway 62 and numerous graded and track roads.
	There doesn't appear to be any mining activity at this time, within the bounds of this survey.

## BOOK 5327 UNITED STATES

## DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

## FIELD ASSISTANTS

NAMES	CAPACITY
Cheryl A. Baier	Surveying Technician
Bruce J. Olson	Survey Aid
Craig L. McFarland	Survey Aid

### CERTIFICATE OF SURVEY

I, Paul L. Reeves, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 1st day of February, 1988, I have dependently resurveyed portions of the north boundary and subdivisional lines, portions of certain mineral surveys, the subdivision of section 3 and a metes—and—bounds survey, in Township 23 North, Range 18 West, of the Gila and Salt River Meridian, in the State of Arizona which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Paul L. Reeves is no longer assigned to this office and is unavailable for signature.

7/22/91	James L. Derdel
(Daté)	(Field Supervisor)

#### CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Arizona State Office Phoenix, Arizona

The foregoing field notes of the dependent resurvey of portions of the north boundary and subdivisional lines, certain mineral surveys, the subdivision of section 3 a metes-and-bounds survey in Township 23 North, Range 18 West, Gila and Salt River Meridian, Arizona, executed by Paul L. Reeves, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUL 2 2 1991	James P. Hellay
(Date)	(Chief Cadastral Surveyor of Arizona)
	CEDITIFICATE OF TRANSCRIPT
	CERTIFICATE OF TRANSCRIFT
	transcript of the field notes of the above-described, Gila and Salt River Meridian, Arizona is a true copy
(Date)	(Chief Cadastral Surveyor of Arizona)