

INDEX DIAGRAM

TOWNSHIP 27 NORTH, RANGE 30 EAST

29	28	26	25	24	22
21 6 91	5 75	4 64	3 53	2 41	1 12
90	90	74	63	52	40
19 7 88	8 73	9 62	10 50	11 39	12 10
87	86	72	61	49	38
18 18 85	17 71	16 60	15 48	14 36	13 8
84	83	70	59	48	36
16 19 82	20 69	21 58	22 46	23 34	24 6
81	80	68	57	46	33
15 30 79	29 67	28 56	27 45	26 32	25 5
78	77	66	55	44	31
13 31 76	32 65	33 53	34 43	35 30	36 4

Subdiv. of Sec. 13--pp.92-95

BOOK 5328

T. 27 N., R. 30 E., Gila and Salt River Mer., Arizona

CHAINS

The following field notes are those of the survey of the east, west and north boundaries, the subdivisional lines and the subdivision of section 13 of Township 27 North, Range 30 East, Gila and Salt River Mer., Arizona.

The history of the related surveys is as follows:

<u>Survey</u>	<u>By Whom</u>	<u>Date</u>
SW cor. of Tp. reestab. in res. of E. bdy. of T. 26 N., R. 29 E.	Jack A. Savlan	1984
SE cor. of Tp. estab. in surv. of N. 1 M. of line bet. Rs. 30 & 31 E., T. 26 N.	Kaiser & Werdel	1984
Surv. of S. bdy. of Tp. (N. bdy. T. 26 N., R. 30 E.)	DeRossett & Kaiser	1984
S. bdy. of T. 1 N., Rs. 5 and 6 W., Nav. Special Base and Mer.	Ehud N. Darling	1870
Res. of above line	John G. Evans	1885
E., W., N. bdys. and subdiv. lines of T. 1 N., R. 6 W., Nav. Special Base and Mer.	Ehud N. Darling	1870

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, the Special Instructions dated November 27, 1987, and the Supplemental Special Instructions dated March 26, 1990, for Group No. 699, Arizona.

The survey data were thoroughly verified and only the true line field notes are given herein.

The directions of all lines were determined by hour angle observations of the sun and refer to the true meridian. Distances and angles were measured using a Zeiss ELTA-3 total station.

BOOK 5328

T. 27 N., R. 30 E., Gila and Salt River Mer., Arizona

CHAINS	<p>The geographic position of the SE cor. of the Tp., determined by using the Motorola Eagle GPS units, utilizing U.S.G.& G.S. 1st. order triangulation stations, "CRAFTON and GARANADO", is as follows:</p> <p>NAD 27: Latitude: 35°41'32.33" N. Longitude: 109°04'52.89" W.</p> <p>The mean magnetic declination as shown on ZITH-TUSAYAN BUTTE 4 NW, ARIZ. quadrangle map, published by U.S. Geological Survey in 1957, is 14° E.</p> <hr/> <p style="text-align: center;">Survey of the East Boundary, T. 27 N., R. 30 E., Gila and Salt River Mer., Arizona</p> <hr/> <p>Beginning at the cor. of Tps. 26 and 27 N., Rs. 30 and 31 E., set, mkd. and witnessed as described in the official record of the 1984 survey of the north one mile of the line between Rs. 30 and 31 E., T. 26 N.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over level land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
--------	--

Survey of the East Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T27N 1/4 R30E R31E S36 S31 1989</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
51.65	Barbed wire fence, 3 strand, extends S. 80° E. and N. 80° W.
56.75	Barbed wire fence, 4 strand, extends S. 70° E. and N. 70° W.
71.30	Barbed wire fence, 3 strand, extends S. 74° E. and N. 74° W.
80.00	Point for the cor. of secs. 25, 30, 31 and 36.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E R31E S25 S30 ----- S36 S31 1989</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, level with rolling sand dunes. Soil, sand. No timber, sparse sagebrush and native grasses.</p> <hr/> <p>North, bet. secs. 25 and 30.</p> <p>Over level to gently rolling land.</p>
5.25	Barbed wire fence, 4 strand, with wire mesh, extends S. 70° E. and N. 70° W.
27.80	Barbed wire fence, 6 strand, extends S. 74° E. and N. 74° W.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>

Survey of the East Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	T27N 1/4 R30E R31E S25 S30 1989
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
44.54	Southernmost cor. of chain link fenced sewage pump station enclosure, 66 X 52 ft., long side bears N. 38° E., bears West, 28 lks. dist.
74.61	Center of iron manhole cover, 24 ins. diam., bears East, 125 lks. dist., mkd. SEWER.
80.00	Point for the cor. of secs. 19, 24, 25 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T27N R30E R31E S24 S19 <hr style="width: 10%; margin: 0 auto;"/> S25 S30 1989
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
	Cor. is located 158 lks. E. of left bank of Black Creek, a sandy wash, drains SW, and 21 lks. W. of trail road, bears N. and S.
	Land, level to gently rolling. Soil, sand. No timber; dense willow brush and salt cedar.
	North, bet. secs. 19 and 24.
	Over level to gently rolling land.
6.70	Left bank of Black Creek, a sandy wash, drains SSW.
15.10	Right bank of Black Creek, a sandy wash, drains SSW.
29.10	Power line, 4 strand, bears N. 40° E. and S. 40° W.

Survey of the East Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
30.40	Trail road, bears N. 80° E. and S. 80° W.
35.29	Southernmost cor. of house trailer on permanent foundation, 57 x 10 ft., long side bears N. 22° E., bears West, 292 lks. dist.
35.90	Barbed wire fence, 4 strand, with wire mesh, extends S. 73° E. and N. 73° W.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>T27N 1/4 R30E R31E S24 S19 1989</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in a fenced sheep pasture.</p>
46.05	Barbed wire fence, 4 strand, with wire mesh, extends S. 66° E. and N. 66° W.
51.60	Graded road, 38 lks. wide, bears N. 32° E. and S. 32° W.
54.70	Power line, 2 strand, bears N 33° E. and S 33° W.
80.00	Point for the cor. of secs. 13, 18, 19 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> <p>T27N R30E R31E S13 S18 ----- S24 S19 1989</p> </div>

Survey of the East Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on the W. slope of a ridge, bears N. and S.</p> <p>Land, level to gently rolling. Soil, sand and shale. Timber, scattered pinon and juniper.</p> <hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over level to gently rolling land.</p> <p>11.70 Trail road, bears S. 59° E. and N. 59° W.</p> <p>28.10 Power line, 2 strand, bears N. 73° E. and S. 73° W.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 3 ins. below the surface of the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T27N 1/4 R30E R31E S13 S18 1989</p> </div> <p>from which</p> <p style="margin-left: 40px;">The SW cor. of a stucco covered frame house, 35 x 25 ft., bears N. 87° E., 43 1/2 lks. dist., long side bears North.</p> <p style="margin-left: 40px;">The NE cor. of a mobile home on a permanent foundation, 72 x 14 ft., bears S. 58 3/4° E., 134 1/2 lks. dist., long side bears West.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the center of an octagonal shaped hogan, bears N. 28 1/4° E., 174 lks. dist.</p> <p>60.00 Point for the N 1/16 sec. cor. of secs. 13 and 18.</p>
--------	--

Survey of the East Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N N 1/16 R30E R31E S13 S18 1989</p> <p>from which</p> <p style="padding-left: 40px;">A power pole, bears N. 87 3/4° E., 328 lks. dist., mkd. WOC HPT H588 SPPAS 440.</p> <p style="padding-left: 40px;">A power pole, bears N. 73 1/4° W., 183 lks. dist., mkd. WOC HP H588 SPPAS 440.</p> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, West of the cor.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
61.20	South bank of Bonito Creek Wash, approximately 60 ft. deep, drains SE.
62.78	Easternmost cor. of frame house, 40 1/2 x 24 ft., long side bears N. 29° W., bears West, 376 lks. dist.
64.73	NE cor. of frame house, 25 x 24 ft., long side bears N. 84° W., bears West, 425 lks. dist.
70.30	North bank of Bonito Creek Wash, approximately 60 ft. deep, drains SE.
73.29	Easternmost cor. of St. Dominic Hall, 80 1/3 x 125 1/3 ft., long side bears S. 62° W., bears West, 195 lks. dist.
75.30	NE cor. of Our Lady of the Blessed Sacrament Church, a stone structure, 87 x 41 ft., long side bears S. 7° W., bears West, 55 lks. dist.
75.80	Center line of road to Blue Creek Canyon, asphalt surfaced, 30 lks. wide, bears S. 84° E. and N. 84° W.
76.33	Terminus of chain link fence, extending N. 6° E., bears West, 24 lks. dist.
76.81	South side of cinder block building, 16 1/2 ft. square, the SW cor. bears N. 83° W., 6 lks. dist.

Survey of the East Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS													
78.47	Chain link fence, extends N. 6° E. and S. 6° W.												
78.97	Cor. of chain link fences, extending S. 84° E. and S. 6° W., bears East, 5 1/2 lks. dist.												
80.00	Point for the cor. of secs. 7, 12, 13 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd. <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T27N</td> </tr> <tr> <td style="text-align: center;">R30E</td> <td style="text-align: center;">R31E</td> </tr> <tr> <td style="text-align: center;">S12</td> <td style="text-align: center;">S 7</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S13</td> <td style="text-align: center;">S18</td> </tr> <tr> <td colspan="2" style="text-align: center;">1989</td> </tr> </table> <p>from which</p> <p style="margin-left: 40px;">A 60-penny common nail, set in a joint at the SW cor. of a concrete curb, bears S. 9 3/4° E., 63 1/2 lks. dist.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 6 lks. SE of a cottonwood tree, 23 ins. diam., and on the east shoulder of the road to Blue Water Creek Canyon, bears N. 8° E. and S. 8° W.</p> <p>Land, level to gently rolling. Soil, sandy loam and clay. No timber, sparse native grasses.</p> <hr/> <p>North, bet. secs. 7 and 12.</p> <p>Over level to rolling land.</p>	T27N		R30E	R31E	S12	S 7	-----		S13	S18	1989	
T27N													
R30E	R31E												
S12	S 7												

S13	S18												
1989													
5.28	SW cor. of native stone building, 138 x 58 ft., long side bears S. 84° E., bears East, 1 lk. dist.												
8.03	SE cor. of log cabin, 58 x 33 ft., long side bears S. 84° E., bears West, 48 lks. dist. Enter residential area.												
40.00	Point for the 1/4 sec. cor. of secs. 7 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.												

Survey of the East Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p style="text-align: center;">T27N 1/4 R30E R31E S12 S 7 1989</p> <p>from which</p> <p style="padding-left: 40px;">An elm, 14 ins. diam., bears N. 66 1/4° E., 112 lks. dist., unmkd.</p> <p style="padding-left: 40px;">The center of an iron manhole cover, 2 ft. diam., bears S. 17 1/4° E., 35 1/2 lks. dist., mkd. SEWER.</p> <p style="padding-left: 40px;">The easternmost cor. of a stucco covered frame house, 25 x 15 ft., long side bears S. 45° W., bears N. 43 1/4° W., 190 1/2 lks. dist.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on the west side of a gentle slope, in a yard common to two dwellings.</p> <p>Leave residential area, ascend through dense juniper and piñon.</p> <p>80.00 Point for the cor. of secs. 1, 6, 7 and 12.</p> <p style="padding-left: 40px;">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to bedrock, and supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E R31E S 1 S 6 ----- S12 S 7 1989</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 8 ins. diam., bears N. 72 3/4° E., 51 1/2 lks. dist., mkd. BT S6 T27N R31E, reading from bottom to top.</p> <p style="padding-left: 40px;">A forked piñon, 10 ins. diam. at base, bears S. 34° E., 24 1/2 lks. dist., mkd. BT S7 T27N R31E, reading from bottom to top.</p>
--------	--

Survey of the East Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>A forked piñon, 15 ins. diam. at base, bears S. 47° W., 57 1/2 lks. dist., mkd. BT S12 T27N R30E, reading from bottom to top.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on the east side of a gently sloping ridge, bears NE and SW.</p> <p>Land, level to rolling. Soil, sand and sandy loam. Timber, dense juniper and piñon.</p>
	<p>North, bet. secs. 1 and 6.</p> <p>Over rolling land, ascending east slope of ridge.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, and supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N 1/4 R30E R31E S 1 S 6 1989</p> </div>
	<p>from which</p> <p>A piñon, 13 ins. diam., bears S. 41° E., 141 1/2 lks. dist., mkd. BT 1/4 S6, reading from bottom to top.</p> <p>A piñon, 10 ins. diam., bears S. 48 1/2° W., 15 1/2 lks. dist., mkd. BT 1/4 S1, reading from bottom to top.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on the east side of a gently sloping ridge, bears SE and NW.</p>
80.00	<p>Point for the cor. of Tps. 27 and 28 N., Rs. 30 and 31 E.</p>

Survey of the East Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
22 ins. in the ground, with brass cap mkd.

T28N	
R30E	R31E
S36	S31

S 1	S 6
T27N	
1989	

from which

A piñon, 15 ins. diam., bears N. 74 1/2° E., 25 1/2 lks.
dist., mkd. BT T28N R31E S31, reading from bottom to top.

A piñon, 13 ins. diam., bears S. 46° E., 49 1/2 lks.
dist., mkd. BT T27N R31E S6, reading from bottom to top.

A piñon, 8 ins. diam., bears S. 68 1/4° W., 123 1/2 lks.
dist., mkd. BT T27N R30E S1, reading from bottom to top.

A piñon, 18 ins. diam., bears N. 41 1/2° W., 95 1/2 lks.
dist., mkd. BT T28N R30E S36, reading from bottom to top.

Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic
case beneath the stainless steel post.

Land, rolling.

Soil, sand and sandy loam.

Timber, dense juniper and piñon.

Survey of the West Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

From the cor. of Tps. 26 and 27 N., Rs. 29 and 30 E., set, mkd.
and witnessed as described in the official record of the 1984
dependent resurvey of the E. bdy. of T. 26 N., R 29 E.

North, bet. sec. 31 and 36.

Over rolling land.

Survey of the West Boundary
 T. 27 N., R. 30 E.
 Gila and Salt River Mer., Arizona

CHAINS	
4.30	Trail road, bears E. and W.
8.30	Trail road, bears N. 42° E. and S. 42° W.
12.25	Trail road, bears S. 50° E. and N. 50° W.
18.40	Trail road, bears N. 86° E. and S. 86° W.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T27N 1/4 R29E R30E S36 S31 1989 </div> from which A ponderosa pine, 14 ins. diam., bears S. 66 3/4° E., 160 lks. dist., mkd. 1/4 S31 BT. A ponderosa pine, 17 ins. diam., bears S. 48 3/4° W., 145 1/2 lks. dist., mkd. 1/4 S36 BT. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
46.35	Trail road, bears N. 85° E. and S. 85° W.
54.10	Trail road, bears N. 65° E. and S. 65° W.
80.00	Point for the cor. of secs. 25, 30, 31 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T27N R29E R30E S25 S30 <hr style="width: 100%;"/> S36 S31 1989 </div>

Survey of the West Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A ponderosa pine, 15 ins. diam., bears N. 74 1/4° E., 157 lks. dist., mkd. T27N R30E S30 BT.</p> <p>A ponderosa pine, 12 ins. diam., bears S. 86 1/4° E., 66 lks. dist., mkd. T27N R30E S31 BT.</p> <p>A ponderosa pine, 13 ins. diam., bears S. 56 3/4° W., 177 1/2 lks. dist., mkd. T27N R29E S36 BT.</p> <p>A ponderosa pine, 13 ins. diam., bears N. 14 3/4° W., 69 lks. dist., mkd. T27N R29E S25 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, clay with sandstone outcroppings. Timber, ponderosa pine and scrub oak.</p> <hr/> <p>North, bet. sec. 25 and 30.</p> <p>Over rolling land.</p> <p>1.05 Trail road, bears E. and W.</p> <p>16.75 Trail road, bears N. 80° E. and S. 80° W.</p> <p>37.05 Trail road, bears E. and W.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N 1/4 R29E R30E S25 S30 1989</p> <p>from which</p> <p>A ponderosa pine, 21 ins. diam., bears N. 41 1/4° E., 61 1/2 lks. dist., mkd. 1/4 S30 BT.</p>

Survey of the West Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>A ponderosa pine, 16 ins. diam., bears N. 69 1/4° W., 92 lks. dist., mkd. 1/4 S25 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>												
63.55	Trail road, bears E. and W.												
80.00	<p>Point for the cor. of secs. 19, 24, 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2" style="padding: 0 10px;">T27N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R29E</td> <td style="padding: 0 5px;">R30E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S24</td> <td style="padding: 0 5px;">S19</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; padding: 0 10px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S25</td> <td style="padding: 0 5px;">S30</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">1989</td> </tr> </table> </div> <p>from which</p> <p>A ponderosa pine, 14 ins. diam., bears N. 54 3/4° E., 157 1/2 lks. dist., mkd. T27N R30E S19 BT.</p> <p>A ponderosa pine, 15 ins. diam., bears S. 87° E., 139 1/2 lks. dist., mkd. T27N R30E S30 BT.</p> <p>A ponderosa pine, 17 ins. diam., bears S. 16 3/4° W., 90 1/2 lks. dist., mkd. T27N R29E S25 BT.</p> <p>A ponderosa pine, 19 ins. diam., bears N. 8 3/4° W., 83 lks. dist., mkd. T27N R29E S24 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, clay with sandstone outcroppings. Timber, ponderosa pine and scrub oak.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>North, bet. sec. 19 and 24.</p> <p>Over rolling land.</p>	T27N		R29E	R30E	S24	S19			S25	S30	1989	
T27N													
R29E	R30E												
S24	S19												
S25	S30												
1989													
2.75	Trail road, bears N. 60° E. and S. 60° W.												

Survey of the West Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>40.00 Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T27N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R29E</td><td style="padding: 0 5px;">R30E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S24</td><td style="padding: 0 5px;">S19</td></tr> <tr><td colspan="2">1989</td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 18 ins. diam., bears N. 72 1/2° E., 109 1/2 lks. dist., mkd. 1/4 S19 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 17 ins. diam., bears N. 78 1/4° W., 27 1/2 lks. dist., mkd. 1/4 S24 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>53.30 Graded road, 38 lks. wide, bears N. 20° E. and S. 20° W.</p> <p>56.40 Barbed wire fence, 5 strand, extends N. 20° E. and S. 20° W.</p> <p>80.00 Point for the cor. of secs. 13, 18, 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T27N</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R29E</td><td style="padding: 0 5px;">R30E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S13</td><td style="padding: 0 5px;">S18</td></tr> <tr style="border-top: 1px solid black;"><td style="border-right: 1px solid black; padding: 0 5px;">S24</td><td style="padding: 0 5px;">S19</td></tr> <tr><td colspan="2">1989</td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 16 ins. diam., bears N. 36 3/4° E., 104 lks. dist., mkd. T27N R30E S18 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 13 ins. diam., bears S. 47 1/2° E., 140 1/2 lks. dist., mkd. T27N R30E S19 BT.</p>	T27N		1/4		R29E	R30E	S24	S19	1989		T27N		R29E	R30E	S13	S18	S24	S19	1989	
T27N																					
1/4																					
R29E	R30E																				
S24	S19																				
1989																					
T27N																					
R29E	R30E																				
S13	S18																				
S24	S19																				
1989																					

Survey of the West Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 9 ins. diam., bears S. 54 1/4° W., 49 1/2 lks. dist., mkd. T27N R29E S24 BT.</p>
	<p>A ponderosa pine, 26 ins. diam., bears N. 6° W., 107 lks. dist., mkd. T27N R29E S13 BT.</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
	<p>Land, rolling. Soil, clay with sandstone outcroppings. Timber, ponderosa pine and scrub oak.</p>
	<p>North, bet. sec. 13 and 18.</p>
	<p>Over rolling land.</p>
9.10	<p>Trail road, bears S. 80° E. and N. 80° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p>
	<p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, 7 ins. below the surface of the ground, in bedrock, in a drill hole, cemented in place, with top mkd.</p>
	<p style="text-align: center;">T27N 1/4 R29E R30E S13 S18 1989</p>
	<p>from which</p>
	<p>A ponderosa pine, 19 ins. diam., bears N. 31 3/4° E., 33 lks. dist., mkd. 1/4 S18 BT.</p>
	<p>A ponderosa pine, 10 ins. diam., bears N. 14 3/4° W., 99 lks. dist., mkd. 1/4 S13 BT.</p>
	<p>Deposit a magnet, 1 in. long, 7/8 in. diam., inside drill hole beneath the brass tablet.</p>
80.00	<p>Point for the cor. of secs. 7, 12, 13 and 18.</p>

Survey of the West Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2" style="padding: 2px 10px;">T27N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">R29E</td> <td style="padding: 2px 5px;">R30E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S12</td> <td style="padding: 2px 5px;">S 7</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; padding: 2px 0 2px 10px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S13</td> <td style="padding: 2px 5px;">S18</td> </tr> <tr> <td colspan="2" style="padding: 2px 10px;">1989</td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 22 ins. diam., bears N. 34 1/4° E., 258 lks. dist., mkd. T27N R30E S7 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 12 ins. diam., bears S. 39 1/4° E., 67 lks. dist., mkd. T27N R30E S18 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 9 ins. diam., bears S. 55 1/2° W., 150 lks. dist., mkd. T27N R29E S13 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 11 ins. diam., bears N. 78 1/4° W., 96 lks. dist., mkd. T27N R29E S12 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, clay with sandstone outcroppings. Timber, ponderosa pine and scrub oak.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>North, bet. sec. 7 and 12.</p> <p>Over rolling land.</p> <p>13.10 Barbed wire fence, 5 strand, extends S. 22° E. and N. 22° W.</p> <p>14.80 Graded road, 38 lks. wide, bears S. 22° E. and N. 22° W.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	T27N		R29E	R30E	S12	S 7			S13	S18	1989	
T27N													
R29E	R30E												
S12	S 7												
S13	S18												
1989													

Survey of the West Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<div style="text-align: center; margin-bottom: 10px;"> <p>T27N 1/4 R29E R30E S12 S 7 1989</p> </div> <p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 10 ins. diam., bears S. 51 1/2° E., 158 1/2 lks. dist., mkd. 1/4 S7 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 16 ins. diam., bears S. 24 3/4° W., 62 lks. dist., mkd. 1/4 S12 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>46.95 Trail road, bears N. 70° E. and S. 70° W.</p> <p>80.00 Point for the cor. of secs. 1, 6, 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-bottom: 10px;"> <p>T27N R29E R30E S 1 S 6 ----- S12 S 7 1989</p> </div> <p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 10 ins. diam., bears N. 48° E., 112 lks. dist., mkd. T27N R30E S6 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 16 ins. diam., bears S. 65° E., 143 1/2 lks. dist., mkd. T27N R30E S7 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 17 ins. diam., bears S. 38 3/4° W., 113 lks. dist., mkd. T27N R29E S12 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 24 ins. diam., bears N. 21° W., 66 lks. dist., mkd. T27N R29E S1 BT.</p>
--------	--

Survey of the West Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
	<p>Land, rolling. Soil, clay with sandstone outcroppings. Timber, ponderosa pine and scrub oak.</p> <hr/>
	<p>North, bet. sec. 1 and 6.</p>
	<p>Over rolling land.</p>
34.45	<p>Trail road, bears S. 85° E. and N. 85° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N 1/4 R29E R30E S 1 S 6 1989</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 77 1/2° E., 95 lks. dist., mkd. 1/4 S6 BT.</p>
	<p style="padding-left: 40px;">A ponderosa pine, 26 ins. diam., bears S. 88 1/2° W., 107 lks. dist., mkd. 1/4 S1 BT.</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of Tps. 27 and 28 N., Rs. 29 and 30 E.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the West Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS

T28N	
R29E	R30E
S36	S31
— —	
S 1	S 6
T27N	
1989	

from which

A ponderosa pine, 12 ins. diam., bears N. 51 3/4° E.,
94 lks. dist., mkd. T28N R30E S31 BT.

A ponderosa pine, 10 ins. diam., bears S. 79 1/2° E.,
19 lks. dist., mkd. T27N R30E S6 BT.

A ponderosa pine, 22 ins. diam., bears S. 45 1/2° W.,
33 lks. dist., mkd. T27N R29E S1 BT.

A ponderosa pine, 11 ins. diam., bears N. 13 3/4° W.,
73 lks. dist., mkd. T28N R29E S36 BT.

Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic
case beneath the stainless steel post.

Land, rolling.

Soil, clay with sandstone outcroppings.

Timber, ponderosa pine and scrub oak.

Survey of the North Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

From the cor. of Tps. 27 and 28 N., Rs. 30 and 31 E.,
hereinbefore described.

N. 89°59' W., bet. secs. 1 and 36.

Over rolling and broken land.

2.95

Trail road, bears N. 20° E. and S. 20° W.

Survey of the North Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS 40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, and supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T28N R30E S36 1/4 — S 1 T27N 1989 </div> <p>from which</p> <p style="margin-left: 40px;">A piñon, 9 ins. diam., bears S. 20 1/4° W., 112 lks. dist., mkd. 1/4 S1 BT.</p> <p style="margin-left: 40px;">A piñon, 8 ins. diam., bears N. 74° W., 34 1/2 lks. dist., mkd. 1/4 S36 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>												
49.50	<p>West rim of mesa, bears N. 20° E. and S. 20° W.</p>												
80.00	<p>Point for the cor. of secs. 1, 2, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T28N R30E</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S36</td> </tr> <tr> <td style="padding: 0 5px;">S35</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 5px;">S 2</td> <td style="border-left: 1px solid black; border-top: 1px solid black; padding: 0 5px;"></td> <td style="border-top: 1px solid black; padding: 0 5px;">S 1</td> </tr> <tr> <td style="padding: 0 5px;">T27N</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">1989</td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A cliff face, 60 ft. high, bears N. 58 3/4° E., 167 lks. dist., with X BO chiseled 5 ft. above ground.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>	T28N R30E		S36	S35			S 2		S 1	T27N		1989
T28N R30E		S36											
S35													
S 2		S 1											
T27N		1989											

Survey of the North Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>Land, rolling and broken. Soil, rocky clay. Timber, piñon and juniper.</p> <hr/> <p>N. 89°59' W., bet. secs. 2 and 35.</p> <p>Over broken land.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case, 24 ins. below the surface of the ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 12 ins. in the ground, to bedrock, and supported in a mound of stone, 4 ft. base, to top, for a reference monument, bears S. 0°01' W., 71 ft. dist., with brass cap mkd. T27N R30E 1/4 S2 RM 71 FT TO COR 1989, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 33°45' W., 66 ft. dist., with brass cap mkd. T28N R30E 1/4 S35 RM 66 FT TO COR 1989, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in Cold Spring Wash, 30 lks. wide, 8 ft. deep, drains SSE.</p>										
80.00	<p>Point for the cor. of secs. 2, 3, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2">T28N R30E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S34</td> <td style="padding: 2px 5px;">S35</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 3</td> <td style="padding: 2px 5px;">S 2</td> </tr> <tr> <td colspan="2" style="padding: 2px 5px;">T27N</td> </tr> <tr> <td colspan="2" style="padding: 2px 5px;">1989</td> </tr> </table> </div>	T28N R30E		S34	S35	S 3	S 2	T27N		1989	
T28N R30E											
S34	S35										
S 3	S 2										
T27N											
1989											

Survey of the North Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

<p>CHAINS</p> <p>from which</p>	<p>A piñon, 14 ins. diam., bears N. 39 1/2° E., 41 lks. dist., mkd. T28N R30E S35 BT.</p> <p>A piñon, 9 ins. diam., bears S. 36 1/2° E., 72 lks. dist., mkd. T27N R30E S2 BT.</p> <p>A piñon, 20 ins. diam., bears S. 23 1/2° W., 65 lks. dist., mkd. T27N R30E S3 BT.</p> <p>A piñon, 8 ins. diam., bears N. 75 1/4° W., 64 1/2 lks. dist., mkd. T28N R30E S34 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, broken. Soil, rocky clay. Timber, piñon and juniper.</p> <hr/> <p>N. 89°59' W., bet. secs. 3 and 34.</p> <p>Over rolling hills.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R30E S34 1/4 — S 3 T27N 1989</p> <p>from which</p> <p>A piñon, 8 ins. diam., bears N. 34 3/4° E., 49 1/2 lks. dist., mkd. 1/4 S34 BT.</p> <p>A piñon, 14 ins. diam., bears S. 19 1/4° E., 40 1/2 lks. dist., mkd. 1/4 S3 BT.</p>
---------------------------------	--

Survey of the North Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>										
80.00	<p>Point for the cor. of secs. 3, 4, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 2px 5px;">T28N</td> <td style="padding: 2px 5px;">R30E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S33</td> <td style="padding: 2px 5px;">S34</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 4</td> <td style="padding: 2px 5px;">S 3</td> </tr> <tr> <td colspan="2" style="padding: 2px 5px;">T27N</td> </tr> <tr> <td colspan="2" style="padding: 2px 5px;">1989</td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A piñon, 7 ins. diam., bears N. 34 1/4° E., 14 lks. dist., mkd. T28N R30E S34 BT.</p> <p style="margin-left: 40px;">A piñon, 12 ins. diam., bears S. 35 3/4° E., 23 lks. dist., mkd. T27N R30E S3 BT.</p> <p style="margin-left: 40px;">A piñon, 7 ins. diam., bears S. 51 1/2° W., 43 lks. dist., mkd. T27N R30E S4 BT.</p> <p style="margin-left: 40px;">A piñon, 10 ins. diam., bears N. 21° W., 63 lks. dist., mkd. T28N R30E S33 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, rolling hills. Soil, sandy loam and clay. Timber, piñon and juniper.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>N. 89°59' W., bet. secs. 4 and 33.</p> <p>Over rolling hills.</p>	T28N	R30E	S33	S34	S 4	S 3	T27N		1989	
T28N	R30E										
S33	S34										
S 4	S 3										
T27N											
1989											
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										

Survey of the North Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p style="text-align: center;">T28N R30E S33 1/4 — S 4 T27N 1989</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears N. 1 1/4° E., 50 lks. dist., mkd. 1/4 S33 BT.</p> <p style="padding-left: 40px;">A piñon, 9 ins. diam., bears S. 2 1/4° E., 12 1/2 lks. dist., mkd. 1/4 S 4 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R30E S32 S33 — — S 5 S 4 T27N 1989</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 7 ins. diam., bears N. 16 1/2° E., 164 1/2 lks. dist., mkd. T28N R30E S33 BT.</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N. 89 1/4° E., 71 lks. dist., mkd. T28N R30E S33 BT.</p> <p style="padding-left: 40px;">A piñon, 8 ins. diam., bears S. 62 1/2° W., 19 lks. dist., mkd. T27N R30E S5 BT.</p> <p style="padding-left: 40px;">A forked piñon, 14 ins. diam. at base, bears N. 62 1/4° W., 163 lks. dist., mkd. T28N R30E S32 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>

Survey of the North Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>Land, rolling hills. Soil, sandy loam and clay. Timber, piñon and juniper.</p>
	<p>N. 89°59' W., bet. secs. 5 and 32.</p>
	<p>Over rolling hills.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R30E S32 1/4 — S 5 T27N 1989</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A juniper, 7 ins. diam., bears N. 24 1/2° E., 16 1/2 lks. dist., mkd. 1/4 S 32 BT.</p>
	<p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S. 4 1/4° E., 45 1/2 lks. dist., mkd. 1/4 S5 BT.</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 31 and 32.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. below the surface of the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R30E S31 S32 — — S 6 S 5 T27N 1989</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears N. 12 3/4° E., 224 1/2 lks. dist., mkd. T28N R30E S32 BT.</p>
	<p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears S. 21 1/4° E., 41 1/2 lks. dist., mkd. T27N R30E S5 BT.</p>

Survey of the North Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 24 ins. diam., bears S. 47 1/4° W., 90 lks. dist., mkd. T27N R30E S6 BT.</p>
	<p>A ponderosa pine, 5 ins. diam., bears N. 48 3/4° W., 46 1/2 lks. dist., mkd. X BT.</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located on SE edge of graded road, 24 lks. wide, bears N. 45° E. and S. 45° W.</p>
	<p>Land, rolling hills. Soil, clay with sandstone outcroppings. Timber, juniper, ponderosa pine, scrub oak, and piñon.</p>
	<hr/> <p>N. 89°59' W., bet. secs. 6 and 31.</p>
	<p>Over rolling land.</p>
9.85	<p>Southernmost cor. of log cabin on stone foundation, 40 x 31 ft., long side bears N. 64° W., bears North, 444 lks. dist.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R30E S31 1/4 — S 6 T27N 1989</p>
	<p>from which</p>
	<p>A ponderosa pine, 12 ins. diam., bears S. 35 1/4° E., 97 lks. dist., mkd. 1/4 S6 BT.</p>
	<p>A ponderosa pine, 16 ins. diam., bears N. 10 3/4° W., 19 lks. dist., mkd. 1/4 S31 BT.</p>

Survey of the North Boundary,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

<p>CHAINS</p> <p>80.37</p> <p>37.10</p> <p>40.00</p>	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>The cor. of Tps. 27 and 28 N., Rs. 29 and 30 E., hereinbefore described.</p> <p>Land, rolling. Soil, clay with sandstone outcroppings. Timber, ponderosa pine and scrub oak.</p> <hr/> <p style="text-align: center;">Survey of the Subdivisional Lines, T. 27 N., R. 30 E., Gila and Salt River Mer., Arizona</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., set, mkd. and witnessed as described in the official record of the 1984 survey of the N. bdy. of T. 26 N., R. 30 E.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over rolling land.</p> <p>Wash, 30 lks. wide, 7 ft. deep, drains S. 80° E.</p> <p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E 1/4 S35 S36 1989</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 16 ins. diam., bears N. 89 3/4° E., 16 lks. dist., mkd. 1/4 S36 BT.</p> <p style="padding-left: 40px;">A juniper, 19 ins. diam., bears N. 64 3/4° W., 32 lks. dist., mkd. 1/4 S35 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
--	--

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS									
49.40	Wash, 45 lks. wide, 15 ft. deep, drains N. 70° E.								
80.00	Point for the cor. of secs. 25, 26, 35 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T27N</td> <td style="padding: 0 5px;">R30E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S26</td> <td style="padding: 0 5px;">S25</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S35</td> <td style="padding: 0 5px;">S36</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1989</td> </tr> </table> from which A ponderosa pine, 4 ins. diam., bears N. 67 1/2° E., 80 1/2 lks. dist., mkd. X BT. A ponderosa pine, 4 ins. diam., bears S. 27 1/2° E., 123 1/2 lks. dist., mkd. X BT. A juniper, 9 ins. diam., bears N. 82 1/2° W., 38 lks. dist., mkd. T27N R30E S26 BT. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post. Land, rolling. Soil, sandy loam. Timber, juniper and scattered ponderosa pine. <hr/> From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described. N. 89°58' W., bet. secs. 25 and 36. Over rolling land.	T27N	R30E	S26	S25	S35	S36	1989	
T27N	R30E								
S26	S25								
S35	S36								
1989									
11.99	Barbed wire fence, 6 strand, extends N. 10° E. and S. 10° W.								
40.005	Point for the 1/4 sec. cor. of secs. 25 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	T27N R30E S25 1/4 — S36 1989
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
55.20	Graded road, 38 lks. wide, bears N. 4° E. and S. 4° W.
72.64	Barbed wire fence, 5 strand, extends S. 66° E. and N. 66° W.
80.01	The cor. of secs. 25, 26, 35 and 36.
	Land, rolling. Soil, sand. No timber; willow brush and salt cedar.
	N. 0°01' W. bet. secs. 25 and 26.
	Over rolling land, on gradual ascent.
36.60	Trail road, bears S. 45° E. and N. 45° W.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T27N R30E 1/4 S26 S25 1989
	from which
	A juniper, 6 ins. diam., bears N. 71° E., 27 1/2 lks. dist., mkd. 1/4 S25 BT.
	A juniper, 10 ins. diam., bears N. 83 3/4° W., 94 1/2 lks. dist., mkd. 1/4 S26 BT.

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>								
80.00	<p>Point for the cor. of secs. 23, 24, 25 and 26.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, flush with sandstone surface, cemented in place, with top mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 2px 5px;">T27N</td> <td style="padding: 2px 5px;">R30E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S23</td> <td style="padding: 2px 5px;">S24</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S26</td> <td style="padding: 2px 5px;">S25</td> </tr> <tr> <td colspan="2" style="padding: 2px 5px;">1989</td> </tr> </table> </div> <p>from which</p> <ul style="list-style-type: none"> A piñon, 6 ins. diam., bears N. 62 1/2° E., 41 lks. dist., mkd. T27N R30E S24 BT. A piñon, 7 ins. diam., bears S. 17 1/4° E., 102 lks. dist., mkd. T27N R30E S25 BT. A piñon, 11 ins. diam., bears S. 18° W., 81 1/2 lks. dist., mkd. T27N R30E S26 BT. A piñon, 7 ins. diam., bears N. 12 3/4° W., 137 lks. dist., mkd. T27N R30E S23 BT. <p>Deposit a magnet, 1 in. long, 7/8 in. diam., inside drill hole beneath brass tablet.</p> <p>Land, rolling. Soil, sandy clay. Timber, juniper and piñon.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°58' W., bet. secs. 24 and 25.</p> <p>Over level and rolling land.</p>	T27N	R30E	S23	S24	S26	S25	1989	
T27N	R30E								
S23	S24								
S26	S25								
1989									
18.70	<p>Power line, 4 strand, bears N. 20° E. and S. 20° W.</p>								

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
19.10	Graded road, 30 lks. wide, bears N. 20° E. and S. 20° W.
40.01	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E S24 1/4 — S25 1989</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
40.60	Wash, 8 lks. wide, 8 ft. deep, drains N. 60° E.
80.02	<p>The cor. of secs. 23, 24, 25 and 26.</p> <p>Land, level to rolling. Soil, sand. Timber, piñon; willow brush and salt cedar.</p> <hr/> <p>N. 0°01' W. bet. secs. 23 and 24.</p> <p>Over rolling land, on gradual ascent.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E 1/4 S23 S24 1989</p>

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>from which</p> <p style="padding-left: 40px;">A piñon, 7 ins. diam., bears N. 46 1/4° E., 58 lks. dist., mkd. 1/4 S24 BT.</p> <p style="padding-left: 40px;">A piñon, 11 ins. diam., bears N. 38 3/4° W., 23 lks. dist., mkd. 1/4 S23 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>74.80 Trail road, bears N. 40° E. and S. 40° W.</p> <p>80.00 Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T27N R30E</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black;">S14</td> <td style="text-align: center;">S13</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black;">S23</td> <td style="text-align: center;">S24</td> </tr> <tr> <td colspan="2" style="text-align: center;">1989</td> </tr> </table> <p>from which</p> <p style="padding-left: 40px;">A piñon, 13 ins. diam., bears N. 45 3/4° E., 92 lks. dist., mkd. T27N R30E S13 BT.</p> <p style="padding-left: 40px;">A piñon, 8 ins. diam., bears S. 40° E., 42 lks. dist., mkd. T27N R30E S24 BT.</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears S. 20 1/2° W., 49 lks. dist., mkd. T27N R30E S23 BT.</p> <p style="padding-left: 40px;">A piñon, 9 ins. diam., bears N. 47° W., 36 1/2 lks. dist., mkd. T27N R30E S14 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper.</p> <hr style="width: 100%; margin-top: 20px;"/>	T27N R30E		S14	S13	S23	S24	1989	
T27N R30E									
S14	S13								
S23	S24								
1989									

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°58' W., bet. secs. 13 and 24.</p> <p>Over rolling land, on ascent.</p>
40.005	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T27N R30E S13 1/4 — S24 1989</p> </div> <p>from which</p> <p style="margin-left: 40px;">A piñon, 9 ins. diam., bears S. 18 3/4° W., 64 lks. dist., mkd. 1/4 S24 BT.</p> <p style="margin-left: 40px;">A piñon, 8 ins. diam., bears N. 56° W., 122 lks. dist., mkd. 1/4 S13 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
75.35	<p>Trail road, bears N. 15° E. and S. 15° W.</p>
80.01	<p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over rolling and nearly level land.</p>
12.75	<p>Trail road, bears S. 85° E. and N. 85° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p>

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E 1/4 S14 S13 1989</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 8 ins. diam., bears S. 76 1/2° E., 103 1/2 lks. dist., mkd. 1/4 S13 BT.</p> <p style="padding-left: 40px;">A piñon, 18 ins. diam., bears S. 62 3/4° W., 81 1/2 lks. dist., mkd. 1/4 S14 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
49.60	Trail road, bears S. 53° E. and N. 53° W.
65.00	Trail road, bears N. 50° E. and S. 50° W.
80.00	Point for the cor. of secs. 11, 12, 13 and 14.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E S11 S12 ----- S14 S13 1989</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 7 ins. diam., bears N. 35° E., 63 1/2 lks. dist., mkd. T27N R30E S12 BT.</p> <p style="padding-left: 40px;">A piñon, 9 ins. diam., bears S. 66 3/4° E., 64 lks. dist., mkd. T27N R30E S13 BT.</p> <p style="padding-left: 40px;">A piñon, 8 ins. diam., bears S. 20 1/4° W., 59 lks. dist., mkd. T27N R30E S14 BT.</p> <p style="padding-left: 40px;">A piñon, 6 ins. diam., bears N. 29 1/4° W., 64 1/2 lks. dist., mkd. T27N R30E S11 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>Land, rolling to nearly level. Soil, sandy clay and sandstone outcroppings. Timber, piñon and juniper.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°57' W., bet. secs. 12 and 13.</p> <p>Over rolling and nearly level land.</p> <p>0.60 Center line of road to Blue Creek Canyon, asphalt surfaced, 30 lks. wide, bears N. 10° E. and S. 10° W.</p> <p>1.00 Bonito Creek Wash, 45 lks. wide, 40 ft. deep, drains South.</p> <p>4.45 Center of shrine with statue of the Virgin Mary, bears South, 5.30 chs. dist.</p> <p>20.005 Point for the E 1/16 sec. cor. of secs. 12 and 13.</p> <p>Set a brass tablet, 3 1/4 ins diam., 3 1/2 ins. stem, in a drill hole, cemented in place, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T27N R30E S12 E 1/16 — S13 1990</p> <p>from which</p> <p style="padding-left: 40px;">A forked piñon, 10 ins. diam. at base, bears N. 62 1/4° E., 55 lks. dist., mkd. E 1/16 S12 BT.</p> <p style="padding-left: 40px;">A rock outcrop, 6 ft. wide, 2 1/2 ft. high, bears S. 36 1/4° W., 32 lks. dist., with X BO chiseled on the NE face.</p> <p>Raise a mound of stone, 1 3/4 ft. base, 1 1/2 ft. high, North of the cor.</p> <p>Deposit a magnet, 1 in. long, 7/8 in. diam., in the drill hole beneath the brass tablet.</p> <p>Cor. is located 26 lks. South of south rim of Blue Creek Canyon, bears N. 47° E. and S. 47° W.</p> <p>40.01 Point for the 1/4 sec. cor. of secs. 12 and 13.</p>
--------	---

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E S12 1/4 — S13 1989</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears N. 53 1/2° E., 44 lks. dist., mkd. 1/4 S12 BT.</p> <p style="padding-left: 40px;">A piñon, 7 ins. diam., bears S. 32 1/4° E., 111 1/2 lks. dist., mkd. 1/4 S13 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>59.65 Trail road, bears N. 40° E. and S. 40° W.</p> <p>80.02 The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, rolling to nearly level. Soil, sandy loam and clay. Timber, piñon and juniper.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over level and broken land.</p> <p>24.50 South rim of Blue Creek Canyon, 140 ft. high, bears N. 48° E. and S. 48° W.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E 1/4 S11 S12 1989</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 11 ins. diam., bears S. 33 3/4° E., 32 1/2 lks. dist., mkd. 1/4 S12 BT.</p>
--------	---

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>A piñon, 8 ins. diam., bears N. 23 1/4° W., 44 lks. dist., mkd. 1/4 S11 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Enter inhabited area.</p> <p>63.30 Wash, 91 lks. wide, 30 ft. deep, drains N. 10° E.</p> <p>80.00 Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T27N R30E</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td colspan="2">— —</td></tr> <tr><td>S11</td><td>S12</td></tr> <tr><td colspan="2">1989</td></tr> </table> <p>from which</p> <p>The SW cor. of a wooden house, 28 x 16 ft., long side bears N. 10° E., bears N. 66 1/4° E., 61 lks. dist.</p> <p>A power pole, bears S. 65 3/4° E., 324 1/2 lks. dist., mkd. C1 03A 2.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>From this cor., third order U. S. Geological Survey triangulation station "DEFIANCE", with latitude of 35°45'06.463" N., longitude of 109°05'35.790" W., (NAD27), and elevation of 7406 ft., bears S. 20°03' E., 76.32 chs. dist., monumented with a standard brass disk, 4 ins. diam., cemented flush with the surface of a sandstone outcrop, 26 x 16 x 2 1/2 ins. above the ground, with top of disk mkd. 1955 DEFIANCE and a triangle.</p> <p>Land, level to broken. Soil, sandy loam and clay. Timber, piñon and juniper.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°58' W., bet. secs. 1 and 12.</p> <p>Over rolling and broken land.</p>	T27N R30E		S 2	S 1	— —		S11	S12	1989	
T27N R30E											
S 2	S 1										
— —											
S11	S12										
1989											

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
37.90	Trail road, bears N. 10° E. and S. 10° W.
40.015	Point for the 1/4 sec. cor. of secs. 1 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T27N R30E S 1 1/4 — S12 1989
	from which
	A piñon, 8 ins. diam., bears N. 46 1/4° E., 44 1/2 lks. dist., mkd. 1/4 S1 BT.
	A piñon, 10 ins. diam., bears S. 16 3/4° W., 39 lks. dist., mkd. 1/4 S12 BT.
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
52.50	Trail road, bears N. 10° E. and S. 10° W.
63.00	East rim of Blue Creek Canyon, 140 ft. high, bears N. 30° E. and S. 30° W.
71.80	Base of canyon wall, bears N and S.
71.90	Graded road, 23 lks. wide, bears N. 45° E. and S. 45° W.
73.40	Wash, 15 lks. wide, 30 ft. deep, drains S. 45° W.
	Enter inhabited area.
77.15	Power line, 3 strand, bears N and S.
80.03	The cor. of secs. 1, 2, 11 and 12.
	Land, rolling to broken. Soil, sandy loam and clay. Timber, piñon and juniper.
	N. 0°01' E., bet. secs. 1 and 2.
	Over rolling hills.

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
7.90	Wash, 76 lks. wide, 25 ft. deep, drains S. 20° E. Leave inhabited area.
14.20	Same wash, 61 lks. wide, 4 ft. deep, drains S. 60° W.
38.80	Wash, 30 lks. wide, 10 ft. deep, drains N. 60° E.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T27N R30E 1/4 S 2 S 1 1989
	from which A piñon, 6 ins. diam., bears N. 66 3/4° E., 60 lks. dist., mkd. 1/4 S1 BT. A piñon, 6 ins. diam., bears N. 63° W., 60 1/2 lks. dist., mkd. 1/4 S2 BT. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
51.65	Power line, 3 strand, bears S. 20° E. and N. 20° W.
53.14	Barbed wire fence, 5 strand, extends S. 30° E. and N. 30° W.
54.40	Graded road, 38 lks. wide, bears S. 30° E. and N. 30° W.
55.16	Barbed wire fence, 4 strand, extends S. 30° E. and N. 30° W.
77.20	Wash, 91 lks. wide, 12 ft. deep, drains S. 28° E.
79.98	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described. Land, rolling hills. Soil, sandy loam and clay. Timber, piñon and juniper.

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS											
	<p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., set, mkd. and witnessed as described in the official record of the 1984 survey of the N. bdy. of T. 26 N., R. 30 E.</p>										
	<p>N. 0°01' W., bet. secs. 34 and 35.</p>										
	<p>Over rolling land.</p>										
18.40	<p>Top of ridgeline, bears N. 65° E. and S. 65° W.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p>										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T27N R30E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S34</td><td style="text-align: center;">S35</td></tr> <tr><td colspan="2" style="text-align: center;">1989</td></tr> </table>	T27N R30E		1/4		S34	S35	1989			
T27N R30E											
1/4											
S34	S35										
1989											
	<p>from which</p>										
	<p style="padding-left: 40px;">A piñon, 6 ins. diam., bears S. 29° E., 87 lks. dist., mkd. 1/4 S35 BT.</p>										
	<p style="padding-left: 40px;">A piñon, 10 ins. diam., bears N. 67° W., 62 lks. dist., mkd. 1/4 S34 BT.</p>										
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>										
78.40	<p>Trail road, bears N. 20° E. and S. 20° W.</p>										
80.00	<p>Point for the cor. of secs. 26, 27, 34 and 35.</p>										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T27N R30E</td></tr> <tr><td style="text-align: center;">S27</td><td style="text-align: center;">S26</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S34</td><td style="text-align: center;">S35</td></tr> <tr><td colspan="2" style="text-align: center;">1989</td></tr> </table>	T27N R30E		S27	S26	-----		S34	S35	1989	
T27N R30E											
S27	S26										

S34	S35										
1989											
	<p>from which</p>										
	<p style="padding-left: 40px;">A piñon, 8 ins. diam., bears N. 41 3/4° E., 80 lks. dist., mkd. T27N R30E S26 BT.</p>										
	<p style="padding-left: 40px;">A piñon, 8 ins. diam., bears S. 31° E., 48 lks. dist., mkd. T27N R30E S35 BT.</p>										

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>A piñon, 8 ins. diam., bears S. 52 1/4° W., 66 1/2 lks. dist., mkd. T27N R30E S34 BT.</p> <p>A ponderosa pine, 22 ins. diam., bears N. 47 1/4° W., 139 lks. dist., mkd. T27N R30E S27 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 2 lks. West of west edge of graded road, 38 lks. wide, bears N. and S.</p> <p>Land, rolling. Soil, sandy loam and clay. Timber, piñon, juniper and ponderosa pine.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89°59' W., bet. secs. 26 and 35.</p> <p>Over rolling land, on ascent.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E S26 1/4 — S35 1989</p> <p>from which</p> <p>A piñon, 9 ins. diam., bears S. 41 1/2° W., 29 lks. dist., mkd. 1/4 S35 BT.</p> <p>A piñon, 7 ins. diam., bears N. 4° W., 70 lks. dist., mkd. 1/4 S26 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
60.35	Trail road, bears S. 60° E. and N. 60° W.
70.40	Top of ridgeline, bears S. 20° E. and N. 20° W.
80.00	The cor. of secs. 26, 27, 34 and 35.

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>Land, rolling. Soil, sandy loam and clay. Timber, piñon and ponderosa pine.</p> <hr/> <p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over rugged and level land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T27N R30E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S27</td><td style="padding: 0 5px;">S26</td></tr> <tr><td colspan="2" style="text-align: center;">1989</td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A piñon, 8 ins. diam., bears N. 63 1/2° E., 59 lks. dist., mkd. 1/4 S26 BT.</p> <p style="margin-left: 40px;">A piñon, 7 ins. diam., bears S. 80° W., 48 lks. dist., mkd. 1/4 S27 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on the northeast side of Natural Bridge Canyon, drains SSE.</p> <p>80.00 Point for the cor. of secs. 22, 23, 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T27N R30E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S22</td><td style="padding: 0 5px;">S23</td></tr> <tr><td colspan="2" style="border-top: 1px solid black; text-align: center;"> </td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S27</td><td style="padding: 0 5px;">S26</td></tr> <tr><td colspan="2" style="text-align: center;">1989</td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A piñon, 12 ins. diam., bears S. 19 1/2° E., 121 1/2 lks. dist., mkd. T27N R30E S26 BT.</p> <p style="margin-left: 40px;">A piñon, 16 ins. diam., bears S. 26 3/4° W., 133 lks. dist., mkd. T27N R30E S27 BT.</p>	T27N R30E		1/4		S27	S26	1989		T27N R30E		S22	S23			S27	S26	1989	
T27N R30E																			
1/4																			
S27	S26																		
1989																			
T27N R30E																			
S22	S23																		
S27	S26																		
1989																			

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, rugged to level. Soil, sandy loam and clay. Timber, piñon and juniper.</p>
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°59' W., bet. secs. 23 and 26.</p> <p>Over rolling land, on ascent.</p>
40.005	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R30E S23 1/4 — S26 1989</p>
	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears S. 38 1/4° E., 69 1/2 lks. dist., mkd. 1/4 S26 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears N. 89 3/4° W., 82 1/2 lks. dist., mkd. 1/4 S23 BT.</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
73.65	<p>Trail road, bears N. 10° E. and S. 10° W.</p>
80.01	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, rolling. Soil, sandy loam and clay. Timber, piñon and ponderosa pine.</p>
	<p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over nearly level land.</p>

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
20.58	Barbed wire fence, 3 strand, extends N. 80° E. and S. 80° W.
23.83	Barbed wire fence, 3 strand, extends N. 80° E. and S. 80° W.
39.60	Trail road, bears N. 50° E. and S. 50° W.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>T27N R30E 1/4 S22 S23 1989</p> </div> <p>from which</p> <p style="margin-left: 40px;">A piñon, 8 ins. diam., bears N. 44 1/2° E., 39 lks. dist., mkd. 1/4 S23 BT.</p> <p style="margin-left: 40px;">A piñon, 8 ins. diam., bears S. 68 1/4° W., 56 1/2 lks. dist., mkd. 1/4 S22 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
80.00	Point for the cor. of secs. 14, 15, 22 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>T27N R30E S15 S14 ----- S22 S23 1989</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy loam. Timber, piñon and scattered juniper.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p>

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>West, bet. secs. 14 and 23.</p> <p>Over rolling and nearly level land.</p> <p>40.01 Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E S14 1/4 — S23 1989</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 12 ins. diam., bears S. 43 1/4° E., 59 lks. dist., mkd. 1/4 S23 BT.</p> <p style="padding-left: 40px;">A piñon, 15 ins. diam., bears N. 14 1/2° W., 60 lks. dist., mkd. 1/4 S14 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>80.02 The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, rolling to nearly level. Soil, sandy loam and clay. Timber, piñon and juniper.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over level to rugged land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E 1/4 S15 S14 1989</p>
--------	--

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>from which</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears N. 73° E., 82 lks. dist., mkd. 1/4 S14 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears N. 83 1/2° W., 154 lks. dist., mkd. 1/4 S15 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 5px;">T27N</td> <td style="padding: 2px 5px;">R30E</td> </tr> <tr> <td style="padding: 2px 5px;">S10</td> <td style="padding: 2px 5px;">S11</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 2px 5px;">S15</td> <td style="border-top: 1px solid black; padding: 2px 5px;">S14</td> </tr> <tr> <td style="padding: 2px 5px;">1989</td> <td></td> </tr> </table> <p>from which</p> <p style="padding-left: 40px;">A piñon, 7 ins. diam., bears N. 32 1/4° E., 126 lks. dist., mkd. T27N R30E S11 BT.</p> <p style="padding-left: 40px;">A piñon, 12 ins. diam., bears S. 52° E., 143 1/2 lks. dist., mkd. T27N R30E S14 BT.</p> <p style="padding-left: 40px;">A piñon, 7 ins. diam., bears S. 44° W., 54 lks. dist., mkd. T27N R30E S15 BT.</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears N. 18 3/4° W., 106 lks. dist., mkd. T27N R30E S10 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, level to rugged. Soil, sandy loam. Timber, piñon, ponderosa pine and scattered juniper.</p> <hr style="width: 60%; margin-left: 0;"/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>West, bet. secs. 11 and 14.</p>	T27N	R30E	S10	S11	S15	S14	1989	
T27N	R30E								
S10	S11								
S15	S14								
1989									

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>Over nearly level land.</p>
27.00	<p>West edge of mesa, bears N. 50° E. and S. 50° W., thence descend abruptly to nearly level land.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E S11 1/4 — S14 1989</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 12 ins. diam., bears N. 61 1/4° E., 150 lks. dist., mkd. 1/4 S11 BT.</p> <p style="padding-left: 40px;">A piñon, 11 ins. diam., bears S. 17° E., 92 lks. dist., mkd. 1/4 S14 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
80.02	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, nearly level with one steep descent. Soil, sandy loam and clay. Timber, piñon and juniper.</p> <hr/> <p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over rugged land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case, 16 ins. below the surface of the ground.</p> <p>from which</p>

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS											
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 28°38' E., 100 ft. dist., with brass cap mkd. T27N R30E 1/4 S11 RM 100 FT TO COR 1989, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>A piñon, 9 ins. diam., bears N. 52° E., 92 lks. dist., mkd. 1/4 S11 BT.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 61°18' W., 66 ft. dist., with brass cap mkd. T27N R30E 1/4 S10 RM 66 FT TO COR 1989, and an arrow pointing to the cor. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>A piñon, 10 ins. diam., bears N. 33 3/4° W., 60 lks. dist., mkd. 1/4 S10 BT.</p> <p>Cor. is located in a wash, 5 lks. wide, 3 ft. deep, drains S. 35° E.</p>										
62.80	Graded road, 30 lks. wide, bears N. 50° E. and S. 50° W.										
80.00	Point for the cor. of secs. 2, 3, 10 and 11.										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T27N R30E</td> </tr> <tr> <td style="text-align: center;">S 3</td> <td style="text-align: center;">S 2</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S10</td> <td style="text-align: center;">S11</td> </tr> <tr> <td colspan="2" style="text-align: center;">1989</td> </tr> </table> <p>from which</p> <p>A piñon, 7 ins. diam., bears N. 50 1/4° E., 36 1/2 lks. dist., mkd. X BT.</p> <p>A piñon, 11 ins. diam., bears S. 9 1/2° E., 79 lks. dist., mkd. T27N R30E S11 BT.</p> <p>A piñon, 9 ins. diam., bears S. 22 1/2° W., 94 1/2 lks. dist., mkd. T27N R30E S10 BT.</p>	T27N R30E		S 3	S 2	-----		S10	S11	1989	
T27N R30E											
S 3	S 2										

S10	S11										
1989											

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>A piñon, 11 ins. diam., bears N. 58 1/2° W., 106 lks. dist., mkd. T27N R30E S3 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, rugged. Soil, sandy loam. Timber, piñon and juniper.</p>
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>West, bet. secs. 2 and 11.</p> <p>Over rugged land.</p>
39.995	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R30E S 2 1/4 — S11 1989</p>
	<p>from which</p> <p>A piñon, 13 ins. diam., bears S. 25 1/4° E., 64 lks. dist., mkd. 1/4 S11 BT.</p> <p>A piñon, 12 ins. diam., bears N. 76 1/4° W., 78 lks. dist., mkd. 1/4 S2 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
79.99	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, rugged. Soil, sandy loam and clay. Timber, piñon and juniper.</p>

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over rugged land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R30E 1/4 S 3 S 2 1989</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A piñon, 11 ins. diam., bears N. 25 1/4° E., 16 1/2 lks. dist., mkd. 1/4 S2 BT.</p>
	<p style="padding-left: 40px;">A piñon, 10 ins. diam., bears S. 78 3/4° W., 91 1/2 lks. dist., mkd. 1/4 S3 BT.</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., hereinbefore described.</p>
	<p>Land, rugged. Soil, sandy loam. Timber, piñon and juniper.</p>
	<hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., set, mkd. and witnessed as described in the official record of the 1984 survey of the N. bdy. of T. 26 N., R. 30 E.</p>
	<p>N. 0°02' W., bet. secs. 33 and 34.</p>
	<p>Over rolling land.</p>
14.50	<p>Trail road, bears S. 60° E. and N. 60° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p>

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E 1/4 S33 S34 1989</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 18 ins. diam., bears N. 59° E., 44 1/2 lks. dist., mkd. 1/4 S34 BT.</p> <p style="padding-left: 40px;">A piñon, 11 ins. diam., bears N. 74 3/4° W., 39 lks. dist., mkd. 1/4 S33 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
75.40	Graded road, 30 lks. wide, bears S. 85° E. and N. 85° W.
76.68	Barbed wire fence, 4 strand, extends S. 85° E. and N. 85° W.
80.00	Point for the cor. of secs. 27, 28, 33 and 34.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E S28 S27 ----- S33 S34 1989</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 11 ins. diam., bears N. 47° E., 33 lks. dist., mkd. T27N R30E S27 BT.</p> <p style="padding-left: 40px;">A piñon, 11 ins. diam., bears S. 54° E., 45 1/2 lks. dist., mkd. T27N R30E S34 BT.</p> <p style="padding-left: 40px;">A piñon, 5 ins. diam., bears S. 37° W., 98 lks. dist., mkd. T27N R30E S33 BT.</p> <p style="padding-left: 40px;">A piñon, 8 ins. diam., bears N. 18 3/4° W., 72 1/2 lks. dist., mkd. T27N R30E S28 BT.</p>

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Timber, piñon and juniper.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°59' W., bet. secs. 27 and 34.</p> <p>Over rolling land.</p> <p>32.24 Barbed wire fence, 4 strand, extends N. 55° E. and S. 55° W.</p> <p>40.005 Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E S27 1/4 — S34 1989</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears S. 11 3/4° W., 29 lks. dist., mkd. 1/4 S34 BT.</p> <p style="padding-left: 40px;">A piñon, 8 ins. diam., bears N. 81° W., 82 lks. dist., mkd. 1/4 S27 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>80.01 The cor. of secs. 27, 28, 33 and 34.</p> <p>Land, rolling. Soil, sandy loam. Timber, piñon and juniper.</p> <hr/>
--------	--

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over rolling land.</p> <p>36.40 Trail road, bears N. 70° E. and S. 70° W.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T27N R30E 1/4 S28 S27 1989</p> </div> <p>from which</p> <p style="margin-left: 40px;">A piñon, 9 ins. diam., bears N. 83 1/4° E., 105 1/2 lks. dist., mkd. 1/4 S27 BT.</p> <p style="margin-left: 40px;">A piñon, 7 ins. diam., bears N. 51° W., 142 lks. dist., mkd. 1/4 S28 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>40.20 Trail road, bears N. 25° E. and S. 25° W.</p> <p>80.00 Point for the cor. of secs. 21, 22, 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T27N R30E S21 S22 ----- S28 S27 1989</p> </div> <p>from which</p> <p style="margin-left: 40px;">A piñon, 10 ins. diam., bears N. 66 1/2° E., 42 1/2 lks. dist., mkd. T27N R30E S22 BT.</p>
--------	--

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>A piñon, 7 ins. diam., bears S. 36° E., 104 lks. dist., mkd. T27N R30E S27 BT.</p>
	<p>A piñon, 8 ins. diam., bears S. 21 1/4° W., 101 lks. dist., mkd. T27N R30E S28 BT.</p>
	<p>A piñon, 8 ins. diam., bears N. 32 1/2° W., 56 1/2 lks. dist., mkd. T27N R30E S21 BT.</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
	<p>Land, rolling. Soil, sandy loam. Timber, piñon and juniper.</p>
	<p>From the cor. of secs. 22, 23, 26 and 27.</p>
	<p>N. 89°59' W., bet. secs. 22 and 27.</p>
	<p>Over rolling land.</p>
33.50	<p>Trail road, bears N. 50° E. and S. 50° W.</p>
40.005	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R30E S22 1/4 — S27 1989</p>
	<p>from which</p>
	<p>A piñon, 8 ins. diam., bears N. 32 1/2° E., 58 lks. dist., mkd. 1/4 S22 BT.</p>
	<p>A piñon, 6 ins. diam., bears S. 7 1/4° E., 55 lks. dist., mkd. 1/4 S27 BT.</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
61.35	<p>Trail road, bears S. 50° E. and N. 50° W.</p>

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
69.80	Trail road, bears N. 50° E. and S. 50° W.
80.01	The cor. of secs. 21, 22, 27 and 28. Land, rolling. Soil, sandy loam. Timber, piñon and juniper.
	<hr/>
	N. 0°02' W., bet. secs. 21 and 22. Over rolling and rugged land.
18.20	Trail road, bears S. 67° E. and N. 67° W.
32.60	Trail road, bears S. 60° E. and N. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T27N R30E 1/4 S21 S22 1989
	from which A piñon, 9 ins. diam., bears N. 50° E., 35 1/2 lks. dist., mkd. 1/4 S22 BT. A piñon, 7 ins. diam., bears N. 87° W., 52 1/2 lks. dist., mkd. 1/4 S21 BT.
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 15, 16, 21 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T27N R30E S16 S15 ----- S21 S22 1989

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>from which</p> <p>A ponderosa pine, 16 ins. diam., bears N. 81 1/4° E., 63 lks. dist., mkd. T27N R30E S15 BT.</p> <p>A piñon, 8 ins. diam., bears S. 60° E., 123 lks. dist., mkd. T27N R30E S22 BT.</p> <p>A ponderosa pine, 22 ins. diam., bears S. 46 1/2° W., 134 1/2 lks. dist., mkd. T27N R30E S21 BT.</p> <p>A ponderosa pine, 16 ins. diam., bears N. 43 1/2° W., 68 lks. dist., mkd. T27N R30E S16 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, rolling to rugged. Soil, sandy loam. Timber, piñon, ponderosa pine and scattered scrub oak.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>West, bet. secs. 15 and 22.</p> <p>Over rolling and rugged land.</p> <p>40.005 Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E S15 1/4 — S22 1989</p> <p>from which</p> <p>A piñon, 9 ins. diam., bears N. 35 1/2° E., 66 lks. dist., mkd. 1/4 S15 BT.</p> <p>A piñon, 16 ins. diam., bears S. 10° E., 106 1/2 lks. dist., mkd. 1/4 S22 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
--------	---

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
80.01	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, rolling to rugged. Soil, sandy loam. Timber, piñon, juniper and scattered ponderosa pine.</p> <hr/>
	<p>N. 0°02' W., bet. secs. 15 and 16.</p>
	<p>Over broken land.</p>
25.25	<p>Trail road, bears N. 70° E. and S. 70° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E 1/4 S16 S15 1989</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A piñon, 9 ins. diam., bears S. 65 1/2° E., 24 1/2 lks. dist., mkd. 1/4 S15 BT.</p>
	<p style="padding-left: 40px;">A piñon, 8 ins. diam., bears S. 86° W., 109 1/2 lks. dist., mkd. 1/4 S16 BT.</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 9, 10, 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E S 9 S10 ----- S16 S15 1989</p>

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>from which</p> <p style="padding-left: 40px;">A piñon, 17 ins. diam., bears N. 54 1/4° E., 63 lks. dist., mkd. T27N R30E S10 BT.</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears S. 72 1/2° E., 46 lks. dist., mkd. T27N R30E S15 BT.</p> <p style="padding-left: 40px;">A piñon, 7 ins. diam., bears S. 65 1/2° W., 23 lks. dist., mkd. T27N R30E S16 BT.</p> <p style="padding-left: 40px;">A piñon, 9 ins. diam., bears N. 34 1/4° W., 42 1/2 lks. dist., mkd. T27N R30E S9 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on the north edge of a trail road, bears S. 70° E. and N. 70° W.</p> <p>Land, broken. Soil, sandy loam and clay. Timber, piñon and juniper.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°59' W., bet. secs. 10 and 15.</p> <p>Over broken land.</p> <p>24.25 Trail road, bears N. 10° E. and S. 10° W.</p> <p>40.005 Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E S10 1/4 — S15 1989</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 13 ins. diam., bears S. 43 3/4° W., 175 lks. dist., mkd. 1/4 S15 BT.</p>
--------	---

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>A piñon, 13 ins. diam., bears N. 11° W., 56 1/2 lks. dist., mkd. 1/4 S10 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>80.01 The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, broken. Soil, sandy loam and clay. Timber, piñon, juniper and scattered ponderosa pine.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over broken land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E 1/4 S 9 S10 1989</p> <p>from which</p> <p>A piñon, 12 ins. diam., bears N. 85 1/2° E., 34 lks. dist., mkd. 1/4 S10 BT.</p> <p>A ponderosa pine, 13 ins. diam., bears S. 33 3/4° W., 83 lks. dist., mkd. 1/4 S9 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 3, 4, 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E S 4 S 3 ----- S 9 S10 1989</p>
---------------	--

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A piñon, 5 ins. diam., bears N. 39 1/4° E., 45 1/2 lks. dist., mkd. X BT.</p> <p>A piñon, 8 ins. diam., bears S. 72 1/4° E., 17 lks. dist., mkd. T27N R30E S10 BT.</p> <p>A piñon, 7 ins. diam., bears S. 30° W., 80 lks. dist., mkd. T27N R30E S9 BT.</p> <p>A piñon, 10 ins. diam., bears N. 23 1/4° W., 59 lks. dist., mkd. T27N R30E S4 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, broken. Soil, sandy loam and clay. Timber, piñon and juniper.</p>
	<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 89°59' W., bet. secs. 3 and 10.</p> <p>Over broken land.</p>
40.005	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E S 3 1/4 — S10 1989</p> <p>from which</p> <p>A piñon, 15 ins. diam., bears N. 49 3/4° E., 49 1/2 lks. dist., mkd. 1/4 S3 BT.</p> <p>A piñon, 16 ins. diam., bears S. 6° E., 12 lks. dist., mkd. 1/4 S10 BT.</p>

Survey of the Subdivisional Lines
of T. 27 N., R. 30 E.
Gila and Salt River Mer., Arizona

<p>CHAINS</p> <p>80.01</p> <p>40.00</p> <p>80.01</p>	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, broken. Soil, sandy loam and clay. Timber, piñon and juniper.</p> <hr/> <p>N. 0°01' W., bet. secs. 3 and 4.</p> <p>Over rolling hills.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E 1/4 S 4 S 3 1989</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 12 ins. diam., bears S. 87 1/2° E., 52 lks. dist., mkd. 1/4 S3 BT.</p> <p style="padding-left: 40px;">A piñon, 12 ins. diam., bears S. 51 3/4° W., 20 lks. dist., mkd. 1/4 S4 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling hills. Soil, sandy loam and clay. Timber, piñon and juniper.</p> <hr/>
--	--

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., set, mkd. and witnessed as described in the official record of the 1984 survey of the N. bdy. of T. 26 N., R. 30 E.</p>
	<p>N. 0°03' W., bet. secs. 32 and 33.</p>
	<p>Over rolling land.</p>
17.95	<p>Trail road, bears N. 80° E. and S. 80° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R30E 1/4 S32 S33 1989</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A piñon, 10 ins. diam., bears N. 42 1/2° E., 137 lks. dist., mkd. 1/4 S33 BT.</p>
	<p style="padding-left: 40px;">A piñon, 17 ins. diam., bears S. 62° W., 14 1/2 lks. dist., mkd. 1/4 S32 BT.</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
75.20	<p>Trail road, bears N. 75° E. and S. 75° W.</p>
80.00	<p>Point for the cor. of secs. 28, 29, 32 and 33.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R30E S29 S28 ----- S32 S33 1989</p>

Survey of the Subdivisional Lines,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A piñon, 10 ins. diam., bears N. 32 1/4° E., 142 lks. dist., mkd. T27N R30E S28 BT.</p> <p>A ponderosa pine, 10 ins. diam., bears S. 44 3/4° E., 17 lks. dist., mkd. T27N R30E S33 BT.</p> <p>A ponderosa pine, 7 ins. diam., bears S. 63 1/4° W., 57 lks. dist., mkd. T27N R30E S32 BT.</p> <p>A piñon, 12 ins. diam., bears N. 55 1/2° W., 91 lks. dist., mkd. T27N R30E S29 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Timber, piñon, ponderosa pine and scattered scrub oak.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34. N. 89°58' W., bet. secs. 28 and 33. Over rolling land.</p>
40.005	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E S28 1/4 — S33 1989</p> <p>from which</p> <p>A piñon, 9 ins. diam., bears N. 19° E., 147 lks. dist., mkd. 1/4 S28 BT.</p> <p>A piñon, 10 ins. diam., bears S. 49 3/4° W., 173 lks. dist., mkd. 1/4 S33 BT.</p>

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
75.25	Trail road, bears N. 45° E. and S. 45° W.
80.01	<p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, rolling. Soil, sandy loam. Timber, piñon and ponderosa pine.</p> <hr/> <p>N. 0°03' W., bet. secs. 28 and 29.</p> <p>Over rolling hills.</p>
22.05	Trail road, bears N. 60° E. and S. 60° W.
36.55	Trail road, bears N. 51° E. and S. 51° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T27N R30E 1/4 S29 S28 1989</p> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 22 ins. diam., bears S. 61 1/4° E., 38 lks. dist., mkd. 1/4 S28 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S. 63° W., 87 1/2 lks. dist., mkd. 1/4 S29 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
80.00	Point for the cor. of secs. 20, 21, 28 and 29.

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, and supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td style="padding: 0 10px;">T27N</td> <td style="padding: 0 10px;">R30E</td> </tr> <tr> <td style="padding: 0 10px;">S20</td> <td style="padding: 0 10px;">S21</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 10px;">S29</td> <td style="border-top: 1px solid black; padding: 0 10px;">S28</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">1989</td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 47 1/4° E., 125 1/2 lks. dist., mkd. T27N R30E S21 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S. 49° E., 72 lks. dist., mkd. T27N R30E S28 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S. 69° W., 124 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 23 ins. diam., bears N. 55 1/4° W., 81 lks. dist., mkd. T27N R30E S20 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, rolling hills. Soil, clay loam with sandstone outcroppings. Timber, ponderosa pine, piñon and scattered scrub oak.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 89°58' W., bet. secs. 21 and 28.</p> <p>Over rolling hills.</p> <p>40.005 Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <table style="margin: auto;"> <tr> <td style="padding: 0 10px;">T27N</td> <td style="padding: 0 10px;">R30E</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">S21</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="padding: 0 10px;">—</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">S28</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">1989</td> </tr> </table> </div>	T27N	R30E	S20	S21	S29	S28	1989		T27N	R30E		S21	1/4	—		S28	1989	
T27N	R30E																		
S20	S21																		
S29	S28																		
1989																			
T27N	R30E																		
	S21																		
1/4	—																		
	S28																		
1989																			

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A ponderosa pine, 16 ins. diam., bears S. 32 1/2° E., 105 1/2 lks. dist., mkd. 1/4 S28 BT.</p> <p>A ponderosa pine, 17 ins. diam., bears N. 37 1/4° W., 85 1/2 lks. dist., mkd. 1/4 S21 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
80.01	<p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, rolling hills. Soil, clay loam with sandstone outcroppings. Timber, ponderosa pine, scrub oak and piñon.</p> <hr/>
	<p>N. 0°03' W., bet. secs. 20 and 21.</p> <p>Over rolling hills and broken land.</p>
31.80	<p>Trail road, bears E and W.</p>
38.90	<p>Trail road, bears S. 80° E. and N. 80° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E 1/4 S20 S21 1989</p>
	<p>from which</p> <p>A piñon, 10 ins. diam., bears N. 15 1/2° E., 57 1/2 lks. dist., mkd. 1/4 S21 BT.</p> <p>A piñon, 4 ins. diam., bears S. 75 1/4° W., 28 lks. dist., mkd. X BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS									
59.70	Trail road, bears N. 85° E. and S. 85° W.								
80.00	Point for the cor. of secs. 16, 17, 20 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T27N</td> <td style="padding: 0 5px;">R30E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S17</td> <td style="padding: 0 5px;">S16</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S20</td> <td style="padding: 0 5px;">S21</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1989</td> </tr> </table> from which A blue spruce, 8 ins. diam., bears S. 65 1/2° E., 90 1/2 lks. dist., mkd. T27N R30E S21 BT. A blue spruce, 6 ins. diam., bears S. 41° W., 56 1/2 lks. dist., mkd. X BT. A blue spruce, 6 ins. diam., bears N. 49 1/4° W., 57 1/2 lks. dist., mkd. T27N R30E S17 BT. Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post. Land, rolling hills to broken. Soil, clay loam with sandstone outcroppings. Timber, ponderosa pine, piñon, scrub oak and blue spruce. <hr style="width: 80%; margin-left: 0;"/> From the cor. of secs. 15, 16, 21 and 22. N. 89°58' W., bet. secs. 16 and 21. Over broken land.	T27N	R30E	S17	S16	S20	S21	1989	
T27N	R30E								
S17	S16								
S20	S21								
1989									
33.30	Trail road, bears N. 40° E. and S. 40° W.								
40.005	Point for the 1/4 sec. cor. of secs. 16 and 21.								

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, flush with sandstone surface, cemented in place, with top mkd.</p>
	<p style="text-align: center;">T27N R30E S16 1/4 — S21 1989</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears N. 34° E., 56 1/2 lks. dist., mkd. 1/4 S16 BT.</p>
	<p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears S. 26 3/4° E., 81 1/2 lks. dist., mkd. 1/4 S21 BT.</p>
	<p>Deposit a magnet, 1 in. long, 7/8 in. diam., inside drill hole beneath the brass tablet.</p>
80.01	<p>The cor. of secs. 16, 17, 20 and 21.</p>
	<p>Land, broken. Soil, clay loam with sandstone outcroppings. Timber, ponderosa pine, scrub oak, piñon and blue spruce.</p>
	<hr/> <p>N. 0°03' W., bet. secs. 16 and 17.</p>
	<p>Over broken and rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R30E 1/4 S17 S16 1989</p>

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>from which</p> <p>A ponderosa pine, 17 ins. diam., bears N. 84° E., 44 lks. dist., mkd. 1/4 S16 BT.</p> <p>A ponderosa pine, 10 ins. diam., bears S. 58 1/4° W., 13 lks. dist., mkd. 1/4 S17 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 8, 9, 16 and 17.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, flush with sandstone surface, cemented in place, with top mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2">T27N R30E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 8</td> <td style="padding: 2px 5px;">S 9</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S17</td> <td style="padding: 2px 5px;">S16</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">1989</td> </tr> </table> </div> <p>from which</p> <p>A blue spruce, 10 ins. diam., bears N. 56 1/4° E., 115 1/2 lks. dist., mkd. T27N R30E S9 BT.</p> <p>A blue spruce, 13 ins. diam., bears S. 39 1/2° E., 104 lks. dist., mkd. T27N R30E S16 BT.</p> <p>A blue spruce, 11 ins. diam., bears S. 59 1/4° W., 76 lks. dist., mkd. T27N R30E S17 BT.</p> <p>Deposit a magnet, 1 in. long, 7/8 in. diam., inside drill hole beneath the brass tablet.</p> <p>Land, broken and rolling. Soil, clay loam with sandstone outcroppings. Timber, ponderosa pine, piñon, scrub oak and blue spruce.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°58' W., bet. secs. 9 and 16.</p> <p>Over rugged land.</p>	T27N R30E		S 8	S 9	S17	S16	1989	
T27N R30E									
S 8	S 9								
S17	S16								
1989									

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>40.00 Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E S 9 1/4 — S16 1989</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 13 ins. diam., bears S. 72 1/4° E., 73 lks. dist., mkd. 1/4 S16 BT.</p> <p style="padding-left: 40px;">A piñon, 8 ins. diam., bears N. 54 1/2° W., 93 lks. dist., mkd. 1/4 S9 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, rugged. Soil, sandy loam with sandstone outcroppings. Timber, piñon, ponderosa pine and blue spruce.</p> <hr/> <p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over rugged land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E 1/4 S 8 S 9 1989</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears S. 80° E., 53 lks. dist., mkd. 1/4 S9 BT.</p>

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS									
	<p>A piñon, 14 ins. diam., bears S. 73° W., 101 lks. dist., mkd. 1/4 S8 BT.</p>								
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>								
78.57	<p>Barbed wire fence, 5 strand, extends N. 20° E. and S. 20° W.</p>								
80.00	<p>Point for the cor. of secs. 4, 5, 8 and 9.</p>								
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T27N R30E</td> </tr> <tr> <td style="text-align: center;">S 5</td> <td style="text-align: center;">S 4</td> </tr> <tr> <td style="text-align: center;">S 8</td> <td style="text-align: center;">S 9</td> </tr> <tr> <td colspan="2" style="text-align: center;">1989</td> </tr> </table>	T27N R30E		S 5	S 4	S 8	S 9	1989	
T27N R30E									
S 5	S 4								
S 8	S 9								
1989									
	<p>from which</p>								
	<p>A piñon, 15 ins. diam., bears N. 81 1/4° E., 136 lks. dist., mkd. T27N R30E S4 BT.</p>								
	<p>A blue spruce, 15 ins. diam., bears S. 12 1/2° E., 140 1/2 lks. dist., mkd. T27N R30E S9 BT.</p>								
	<p>A blue spruce, 23 ins. diam., bears S. 26 1/4° W., 80 lks. dist., mkd. T27N R30E S8 BT.</p>								
	<p>A ponderosa pine, 20 ins. diam., bears N. 69° W., 136 lks. dist., mkd. T27N R30E S5 BT.</p>								
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>								
	<p>Land, rugged. Soil, sandy loam with sandstone outcroppings. Timber, piñon, ponderosa pine, scrub oak and blue spruce.</p>								
	<hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p>								
	<p>N. 89°59' W., bet. secs. 4 and 9.</p>								
	<p>Over rolling land.</p>								
40.005	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p>								

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E S 4 1/4 — S 9 1989</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 8 ins. diam., bears N. 7° E., 28 lks. dist., mkd. 1/4 S4 BT.</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears S. 66° E., 7 lks. dist., mkd. 1/4 S9 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>80.01 The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, rolling. Soil, sandy loam with sandstone outcroppings. Timber, piñon, juniper and scattered ponderosa pine.</p> <hr/> <p>N. 0°01' W., bet. secs. 4 and 5.</p> <p>Over rugged land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E 1/4 S 5 S 4 1989</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 7 ins. diam., bears S. 22° E., 72 lks. dist., mkd. 1/4 S4 BT.</p>
---------------	---

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>A blue spruce, 4 ins. diam., bears S. 47 1/4° W., 84 lks. dist., mkd. X BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>79.98 The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rugged. Soil, sandy loam with sandstone outcroppings. Timber, piñon, juniper and scattered blue spruce.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., set, mkd. and witnessed as described in the official record of the 1984 survey of the N. bdy. of T. 26 N., R. 30 E.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over rolling land.</p> <p>4.25 Trail road, bears N. 78° E. and S. 78° W.</p> <p>19.50 Trail road, bears N. 47° E. and S. 47° W.</p> <p>23.55 Trail road, bears N. 37° E. and S. 37° W.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E 1/4 S31 S32 1989</p> <p>from which</p> <p>A ponderosa pine, 28 ins. diam., bears S. 51 1/4° E., 39 lks. dist., mkd. 1/4 S32 BT.</p> <p>A ponderosa pine, 21 ins. diam., bears N. 44 1/2° W., 10 1/2 lks. dist., mkd. 1/4 S31 BT.</p>
--------	--

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS									
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.								
60.30	Trail road, bears N. 70° E. and S. 70° W.								
78.35	Trail road, bears S. 73° E. and N. 73° W.								
80.00	Point for the cor. of secs. 29, 30, 31 and 32.								
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, 10 ins. below the surface of the ground, in sandstone bedrock, cemented in place, with top mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 10px;">T27N</td> <td style="padding: 0 10px;">R30E</td> </tr> <tr> <td style="padding: 0 10px;">S30</td> <td style="padding: 0 10px;">S29</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 10px;">S31</td> <td style="border-top: 1px solid black; padding: 0 10px;">S32</td> </tr> <tr> <td style="padding: 0 10px;">1989</td> <td></td> </tr> </table>	T27N	R30E	S30	S29	S31	S32	1989	
T27N	R30E								
S30	S29								
S31	S32								
1989									
	from which								
	A ponderosa pine, 19 ins. diam., bears N. 50 1/4° E., 80 1/2 lks. dist., mkd. T27N R30E S29 BT.								
	A ponderosa pine, 18 ins. diam., bears S. 45° E., 69 lks. dist., mkd. T27N R30E S32 BT.								
	A ponderosa pine, 16 ins. diam., bears N. 75 1/4° W., 82 1/2 lks. dist., mkd. T27N R30E S30 BT.								
	Deposit a magnet, 1 in. long, 7/8 in. diam., inside drill hole beneath the brass tablet.								
	Land, rolling.								
	Soil, clay loam with sandstone outcroppings.								
	Timber, ponderosa pine, piñon and scattered scrub oak.								
	From the cor. of secs. 28, 29, 32 and 33.								
	N. 89°59' W., bet. secs. 29 and 32.								
	Over rolling land.								
39.99	Point for the 1/4 sec. cor. of secs. 29 and 32.								

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, flush with sandstone surface, cemented in place, with top mkd.</p>
	<p style="text-align: center;">T27N R30E S29 1/4 — S32 1989</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears N. 50 1/4° E., 34 lks. dist., mkd. 1/4 S29 BT.</p>
	<p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears S. 37 1/4° W., 151 1/2 lks. dist., mkd. 1/4 S32 BT.</p>
	<p>Deposit a magnet, 1 in. long, 7/8 in. diam., inside drill hole beneath the brass tablet.</p>
79.98	<p>The cor. of secs. 29, 30, 31 and 32.</p>
	<p>Land, rolling. Soil, clay and loam with sandstone outcroppings. Timber, ponderosa pine, piñon and scrub oak.</p>
	<hr/> <p>N. 89°59' W., bet. secs. 30 and 31.</p>
	<p>Over rolling land.</p>
0.90	<p>Trail road, bears S. 10° E. and N. 10° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R30E S30 1/4 — S31 1989</p>

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S. 14 1/2° W., 71 lks. dist., mkd. 1/4 S31 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears N. 57 1/4° W., 20 lks. dist., mkd. 1/4 S30 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>80.73 The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, clay and loam with sandstone outcroppings. Timber, ponderosa pine, piñon and scrub oak.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over rolling land.</p> <p>4.70 Trail road, bears N. 75° E. and S. 75° W.</p> <p>28.20 Trail road, bears S. 80° E. and N. 80° W.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, and supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E 1/4 S30 S29 1989</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears N. 39 3/4° E., 99 1/2 lks. dist., mkd. 1/4 S29 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears S. 89 3/4° W., 42 lks. dist., mkd. 1/4 S30 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
--------	---

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS											
77.60	Trail road, bears S. 60° E. and N. 60° W.										
80.00	<p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, and supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T27N R30E</td> </tr> <tr> <td>S19</td> <td>S20</td> </tr> <tr> <td colspan="2">-----</td> </tr> <tr> <td>S30</td> <td>S29</td> </tr> <tr> <td colspan="2">1989</td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 17 ins. diam., bears N. 41 1/2° E., 129 1/2 lks. dist., mkd. T27N R30E S20 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears S. 68 3/4° E., 64 1/2 lks. dist., mkd. T27N R30E S29 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears S. 84 3/4° W., 219 lks. dist., mkd. T27N R30E S30 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears N. 2 1/2° W., 51 lks. dist., mkd. T27N R30E S19 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, clay and loam with sandstone outcroppings. Timber, ponderosa pine, piñon and scrub oak.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>N. 89°59' W., bet. secs. 20 and 29.</p> <p>Over rolling land.</p>	T27N R30E		S19	S20	-----		S30	S29	1989	
T27N R30E											
S19	S20										

S30	S29										
1989											
39.99	Point for the 1/4 sec. cor. of secs. 20 and 29.										

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T27N R30E S20 1/4 — S29 1989</p>
	from which
	A ponderosa pine, 22 ins. diam., bears S. 6 3/4° W., 77 lks. dist., mkd. 1/4 S29 BT.
	A ponderosa pine, 28 ins. diam., bears N. 34 1/4° W., 162 1/2 lks. dist., mkd. 1/4 S20 BT.
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
79.98	The cor. of secs. 19, 20, 29 and 30.
	<p>Land, rolling. Soil, clay and loam with sandstone outcroppings. Timber, ponderosa pine, piñon and scrub oak.</p>
	N. 89°59' W., bet. secs. 19 and 30.
	Over rolling land.
6.10	Trail road, bears S. 60° E. and N. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T27N R30E S19 1/4 — S30 1989</p>

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears N. 22 1/2° E., 95 lks. dist., mkd. 1/4 S19 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 17 ins. diam., bears S. 64° W., 59 1/2 lks. dist., mkd. 1/4 S30 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>80.67 The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, clay and loam with sandstone outcroppings. Timber, ponderosa pine, piñon and scrub oak.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over rolling land.</p> <p>13.45 Trail road, bears S. 70° E. and N. 70° W.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E 1/4 S19 S20 1989</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears N. 72 3/4° E., 143 lks. dist., mkd. 1/4 S20 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 23 ins. diam., bears N. 82 1/2° W., 150 1/2 lks. dist., mkd. 1/4 S19 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
--------	---

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS											
50.55	Trail road, bears E and W.										
80.00	Point for the cor. of secs. 17, 18, 19 and 20.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, and supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T27N</td> <td>R30E</td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> <tr> <td colspan="2" style="text-align: center;"> </td> </tr> <tr> <td>S19</td> <td>S20</td> </tr> <tr> <td colspan="2" style="text-align: center;">1989</td> </tr> </table>	T27N	R30E	S18	S17			S19	S20	1989	
T27N	R30E										
S18	S17										
S19	S20										
1989											
	from which										
	A ponderosa pine, 24 ins. diam., bears N. 15 1/2° E., 47 lks. dist., mkd. T27N R30E S17 BT.										
	A ponderosa pine, 6 ins. diam., bears S. 51 1/4° E., 59 lks. dist., mkd. T27N R30E S20 BT.										
	A juniper, 6 ins. diam., bears S. 47 1/2° W., 28 lks. dist., mkd. T27N R30E S19 BT.										
	A ponderosa pine, 28 ins. diam., bears N. 57 3/4° W., 103 1/2 lks. dist., mkd. T27N R30E S18 BT.										
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.										
	Land, rolling. Soil, clay and loam with sandstone outcroppings. Timber, ponderosa pine, scrub oak, juniper and piñon.										
	From the cor. of secs. 16, 17, 20 and 21.										
	N. 89°59' W., bet. secs. 17 and 20.										
	Over broken and rolling land.										
39.99	Point for the 1/4 sec. cor. of secs. 17 and 20.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p style="text-align: center;">T27N R30E S17 1/4 — S20 1989</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 29° E., 47 lks. dist., mkd. 1/4 S17 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 27 ins. diam., bears S. 43 1/2° W., 159 1/2 lks. dist., mkd. 1/4 S20 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>78.12 Barbed wire fence, 2 strand, extends S. 45° E. and N. 45° W.</p> <p>79.98 The cor. of secs. 17, 18, 19 and 20.</p> <p>Land, broken to rolling. Soil, clay and loam with sandstone outcroppings. Timber, ponderosa pine, scrub oak and piñon.</p> <hr/> <p>N. 89°59' W., bet. secs. 18 and 19.</p> <p>Over nearly level land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E S18 1/4 — S19 1989</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears N. 65 1/2° E., 124 1/2 lks. dist., mkd. 1/4 S18 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears S. 8 3/4° W., 92 lks. dist., mkd. 1/4 S19 BT.</p>
--------	--

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
73.30	Graded road, 38 lks. wide, bears N. 16° E. and S. 16° W.
73.96	Barbed wire fence, 5 strand, extends N. 16° E. and S. 16° W.
80.59	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, nearly level. Soil, clay and loam with sandstone outcroppings. Timber, ponderosa pine, piñon and scrub oak.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20. N. 0°03' W., bet. secs. 17 and 18. Over nearly level to rolling land.</p>
1.94	Barbed wire fence, 2 strand, extends S. 45° E. and N. 45° W.
4.10	Trail road, bears N. 75° E. and S. 75° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to bedrock, and in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E 1/4 S18 S17 1989</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N. 40 1/2° E., 64 lks. dist., mkd. 1/4 S17 BT.</p> <p style="padding-left: 40px;">A forked ponderosa pine, 12 ins. diam. at base, bears N. 37 1/4° W., 108 lks. dist., mkd. 1/4 S18 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
53.40	Trail road, bears S. 71° E. and N. 71° W.

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS									
75.80	Trail road, bears E and W.								
80.00	<p>Point for the cor. of secs. 7, 8, 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T27N</td> <td>R30E</td> </tr> <tr> <td>S 7</td> <td>S 8</td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> <tr> <td colspan="2">1989</td> </tr> </table> </div> <p>from which</p> <p>A ponderosa pine, 30 ins. diam., bears N. 55 3/4° E., 81 lks. dist., mkd. T27N R30E S8 BT.</p> <p>A ponderosa pine, 27 ins. diam., bears S. 11 1/4° E., 90 1/2 lks. dist., mkd. T27N R30E S17 BT.</p> <p>A ponderosa pine, 13 ins. diam., bears S. 44 1/4° W., 108 1/2 lks. dist., mkd. T27N R30E S18 BT.</p> <p>A ponderosa pine, 13 ins. diam., bears N. 27 3/4° W., 104 1/2 lks. dist., mkd. T27N R30E S7 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level to rolling. Soil, clay and loam with sandstone outcroppings. Timber, ponderosa pine, scrub oak and piñon.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89°58' W., bet. secs. 8 and 17.</p> <p>Over rugged and rolling land.</p>	T27N	R30E	S 7	S 8	S18	S17	1989	
T27N	R30E								
S 7	S 8								
S18	S17								
1989									
40.00	Point for the 1/4 sec. cor. of secs. 8 and 17.								

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to bedrock, and supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E S 8 1/4 — S17 1989</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears S. 5° E., 65 lks. dist., mkd. 1/4 S17 BT.</p> <p style="padding-left: 40px;">A douglas fir, 10 ins. diam., bears N. 23 1/2° W., 24 lks. dist., mkd. 1/4 S8 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>80.00 The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, rugged to rolling. Soil, clay and loam with sandstone outcroppings. Timber, ponderosa pine, piñon, scrub oak and douglas fir.</p> <hr/> <p>N. 89°58' W., bet. secs. 7 and 18.</p> <p>Over rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, and supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E S 7 1/4 — S18 1989</p>
---------------	---

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 27° E., 52 lks. dist., mkd. 1/4 S7 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S. 47 1/2° W., 125 lks. dist., mkd. 1/4 S18 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>74.30 Graded road, 38 lks. wide, bears S. 20° E. and N. 20° W.</p> <p>75.02 Barbed wire fence, 5 strand, extends S. 20° E. and N. 20° W.</p> <p>80.49 The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, clay and loam with sandstone outcroppings. Timber, ponderosa pine, piñon and scrub oak.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°03' W., bet. secs. 7 and 8.</p> <p>Over rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E 1/4 S 7 S 8 1989</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears N. 14 1/4° E., 74 lks. dist., mkd. 1/4 S8 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears N. 63° W., 43 lks. dist., mkd. 1/4 S7 BT.</p>
--------	--

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS											
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.										
	From this cor., third order U. S. Geological Survey triangulation station "PINEY HILL L.O.", with latitude of 35°45'40.752" N., longitude of 109°10'03.808" W., (NAD27), and elevation of 8102 ft., bears N. 28°41' E., 23.65 chs. dist., monumented with a standard brass disk, 4 ins. diam., cemented flush with the surface of sandstone bedrock, with top of disk mkd. 1955 PINEY HILL L.O. and a triangle.										
46.25	Trail road, bears E and W.										
73.85	Graded road, 23 lks. wide, bears S. 40° E. and N. 40° W.										
80.00	Point for the cor. of secs. 5, 6, 7 and 8.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.										
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T27N R30E</td> </tr> <tr> <td style="text-align: center;">S 6</td> <td style="text-align: center;">S 5</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 7</td> <td style="text-align: center;">S 8</td> </tr> <tr> <td colspan="2" style="text-align: center;">1989</td> </tr> </table>	T27N R30E		S 6	S 5	-----		S 7	S 8	1989	
T27N R30E											
S 6	S 5										

S 7	S 8										
1989											
	from which										
	A ponderosa pine, 14 ins. diam., bears N. 25 1/2° E., 187 lks. dist., mkd. T27N R30E S5 BT.										
	A ponderosa pine, 24 ins. diam., bears S. 48 3/4° E., 119 1/2 lks. dist., mkd. T27N R30E S8 BT.										
	A ponderosa pine, 6 ins. diam., bears S. 70 1/4° W., 56 lks. dist., mkd. T27N R30E S7 BT.										
	A ponderosa pine, 15 ins. diam., bears N. 21° W., 113 1/2 lks. dist., mkd. T27N R30E S6 BT.										
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.										

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>Land, rolling. Soil, clay and loam with sandstone outcroppings. Timber, ponderosa pine, scrub oak and piñon.</p>
	<p>From the cor. of secs. 4, 5, 8 and 9.</p>
	<p>N. 89°59' W., bet. secs. 5 and 8.</p>
	<p>Over rugged and rolling land.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R30E S 5 1/4 — S 8 1989</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears S. 15 1/4° E., 108 lks. dist., mkd. 1/4 S8 BT.</p>
	<p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N. 55 1/4° W., 47 lks. dist., mkd. 1/4 S5 BT.</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
69.85	<p>Power line, 2 strand, bears S. 2° E. and N. 2° W.</p>
71.30	<p>Graded road, 23 lks. wide, bears N. 28° E. and S. 28° W.</p>
80.02	<p>The cor. of secs. 5, 6, 7 and 8.</p>
	<p>Land, rugged to rolling. Soil, sandy loam. Timber, ponderosa pine, scrub oak and piñon.</p>
	<p>N. 89°59' W., bet. secs. 6 and 7.</p>

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	Over rolling land.
5.15	Graded road, 23 lks. wide, bears S. 30° E. and N. 30° W.
17.00	Trail road, bears N. 44° E. and S. 44° W.
29.60	Trail road, bears S. 40° E. and N. 40° W.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T27N R30E S 6 1/4 — S 7 1989</p>
	from which
	<p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears N. 25 1/2° E., 63 1/2 lks. dist., mkd. 1/4 S6 BT.</p>
	<p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S. 21° E., 33 1/2 lks. dist., mkd. 1/4 S7 BT.</p>
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
80.39	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.
	<p>Land, rolling. Soil, clay and loam with sandstone outcroppings. Timber, ponderosa pine, scrub oak and piñon.</p>
	From the cor. of secs. 5, 6, 7 and 8.
	North, bet. secs. 5 and 6.
	Over rolling land.
35.80	Trail road, bears N. 72° E. and S. 72° W.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 6.

Survey of the Subdivisional Lines,
T. 27 N. R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E 1/4 S 6 S 5 1989</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S. 82 1/4° E., 74 lks. dist., mkd. 1/4 S5 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S. 64 3/4° W., 68 1/2 lks. dist., mkd. 1/4 S6 BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>50.00 Graded road, 24 lks. wide, bears S. 79° E. and N. 79° W.</p> <p>80.00 The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, clay and loam with sandstone outcroppings. Timber, ponderosa pine, scrub oak and piñon.</p> <hr/> <p style="text-align: center;">Survey of the Subdivision of Section 13, T. 27 N. R. 30 E., Gila and Salt River Mer., Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 24, hereinbefore described.</p> <p>North, on the N. and S. center line of sec. 13.</p> <p>Over rolling land, on ascent.</p> <p>39.99 Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E. and W. center line of the sec.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E C1/4 S13 1990</p>
--------	---

Subdivision of Section 13,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p>A piñon, 20 ins. diam., bears S. 48 3/4° E., 192 lks. dist., mkd. C 1/4 S13 BT.</p> <p>A piñon, 9 ins. diam., bears N. 68 1/2° W., 103 1/2 lks. dist., mkd. X BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
59.985	<p>Point for the C-N 1/16 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T27N R30E</p> <p>C</p> <p>N1/16 S13</p> <p>C</p> <p>1990</p> </div> <p>from which</p> <p>A piñon, 8 ins. diam., bears S. 21 1/2° E., 73 1/2 lks. dist., mkd. C-N 1/16 S13 BT.</p> <p>A piñon, 10 ins. diam., bears N. 71 3/4° W., 33 lks. dist., mkd. X BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
79.98	<p>The 1/4 sec. cor. of secs. 12 and 13, hereinbefore described.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°58' W., on the E. and W. center line of sec. 13.</p> <p>Over rolling land, on ascent.</p>
20.005	<p>Point for the C-E 1/16 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 13,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

CHAINS	<p style="text-align: center;">T27N R30E E1/16 C———C S13 1990</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 5 ins. diam., bears S. 9 3/4° E., 150 lks. dist., mkd. C-E 1/16 S13 BT.</p> <p style="padding-left: 40px;">A piñon, 11 ins. diam., bears N. 76° W., 78 lks. dist., mkd. X BT.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>40.01 The center 1/4 sec. cor. of sec. 13.</p> <p>80.01 The 1/4 sec. cor. of secs. 13 and 14, hereinbefore described.</p> <hr/> <p style="text-align: center;">NE 1/4 of Section 13</p> <hr/> <p>From the C-E 1/16 sec. cor. of sec. 13.</p> <p>North, on the N. and S. center line of the NE 1/4 of sec. 13.</p> <p>Over rolling land.</p> <p>20.00 Point for the NE 1/16 sec. cor. of sec. 13, at intersection with the E. and W. center line of the NE 1/4 of the sec.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R30E NE 1/16 S13 1990</p> <p>from which</p> <p style="padding-left: 40px;">A forked piñon, 10 ins. diam. at base, bears S. 29° E., 114 lks. dist., mkd. NE 1/16 S13 BT.</p>
--------	---

Subdivision of Section 13,
T. 27 N., R. 30 E.,
Gila and Salt River Mer., Arizona

<p>CHAINS</p> <p>40.00</p> <p>20.005</p> <p>40.01</p>	<p>A piñon, 8 ins. diam., bears S. 64° W., 69 1/2 lks. dist., mkd. X BT.</p> <p>Raise a mound of stone, 2 1/4 ft. base, 1 ft. high, West of the cor.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>The E 1/16 sec. cor. of secs. 12 and 13, hereinbefore described.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°58' W., on the E. and W. center line of the NE 1/4 of sec. 13.</p> <p>Over rolling land, on ascent.</p> <p>The NE 1/16 sec. cor. of sec. 13.</p> <p>The C-N 1/16 sec. cor. of sec. 13.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>Township 27 North, Range 30 East is situated about two miles west of the New Mexico-Arizona border. The western part of the town of Ft. Defiance, Arizona, is in the northeast corner of the township.</p> <p>The terrain is generally rolling in the eastern and western portions of the township. The remainder of the township is generally rugged and broken. The elevation ranges from 6600 to 8100 ft. above sea level.</p> <p>Some clearings in the township are used by members of the Navajo tribe to graze livestock. There is marketable ponderosa pine in the western portion of the township; juniper and piñon predominates elsewhere.</p> <p>Access is provided by graded roads in the western, eastern and northern portions of the township, and by trail roads in the remainder.</p> <p>The drainages within the township flow in easterly and northeasterly directions.</p> <p>The magnetic declination was determined to be 14° E.</p>
---	--

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Daniel H. Leslie	Co-op Student
Daniel Bryan	Navajo Tribal Surveying Technician
Jones Curtiss	Navajo Tribal Surveying Technician
Andrew Murphy	Navajo Tribal Surveying Technician
Barney Woodie	Navajo Tribal Surveying Technician

CERTIFICATE OF SURVEY

We, Robin T. Mathews and Olian T. Shockley, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 27th day of November, 1987, and supplemental special instructions bearing date of the 26th day of March, 1990, we have surveyed the east, west and north boundaries, the subdivisional lines, and the subdivision of section 13, of Township 27 North, Range 30 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

06/10/91
(Date)

Robin T. Mathews
(Cadastral Surveyor)

06/26/1991
(Date)

Olian T. Shockley
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the survey of the east, west and north boundaries, the subdivisional lines, and the subdivision of section 13 of Township 27 North, Range 30 East, Gila and Salt River Meridian, Arizona, executed by Robin T. Mathews and Olian T. Shockley, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

JUL 30 1991
(Date)

Acting Jenny K. Talbot
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I Certify that the foregoing transcript of the field notes of the above-described surveys in T. 27 N., R. 30 E., Gila and Salt River Meridian, Arizona is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~