

ORIGINAL

BOOK 5332

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES  
OF THE

---

DEPENDENT RESURVEY,

---

PORTIONS OF,

---

THE SAN IGNACIO DEL BABOCOMARI LAND GRANT,

---

THE NORTH BOUNDARY, (FOURTH STANDARD PARALLEL SOUTH),

---

THE WEST BOUNDARY, THE SUBDIVISIONAL LINES

---

CERTAIN HOMESTEAD ENTRY SURVEYS,

---

AND THE SUBDIVISION OF CERTAIN SECTIONS,

---

AND A METES AND BOUNDS SURVEY,

---

TOWNSHIP 21 SOUTH, RANGE 17 EAST

---

Of the Gila and Salt River Meridian,

In the State of Arizona

---

EXECUTED BY

Paul L. Moss, Cadastral Surveyor

Daniel A. Wiesner, Cadastral Surveyor

---

Under Special Instructions dated January 14, 1991, approved January 14, 1991, and Supplemental Special Instructions dated January 25, 1991, approved January 25, 1991, which provided for the surveys included under Group Number 727 and assignment instructions dated January 15, 1991.

Survey commenced January 22, 1991

Survey completed March 11, 1991

# BOOK 5332

## INDEX DIAGRAM

TOWNSHIP 21 SOUTH, RANGE 17 EAST,

|    |    |    |    |    |    |    |   |
|----|----|----|----|----|----|----|---|
| 6  |    | 13 |    |    |    |    |   |
| 18 | 6  | 28 | 5  | 4  | 3  | 2  | 1 |
| 27 |    | 24 |    |    |    |    |   |
| 15 | 7  | 8  | 9  | 10 | 11 | 12 |   |
| 18 | 17 | 16 | 15 | 14 | 13 |    |   |
| 19 | 20 | 21 | 22 | 23 | 24 |    |   |
| 30 | 29 | 28 | 27 | 26 | 25 |    |   |
| 31 | 32 | 33 | 34 | 35 | 36 |    |   |

San Ignacio Del Babocomari Land Grant pp 4-9  
 H.E.S. No. 526 pp 34-43  
 H.E.S. No. 527 pp 43-47  
 Subdivision Sec. 5 pp 47-50  
 Subdivision Sec. 6 pp 50-57  
 Metes-and-bounds survey pp 57-58

## BOOK 5332

T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes described the dependent resurvey of portions of, the San Ignacio Del Babocomari Land Grant, the north boundary, (Fourth Standard Parallel South), the West boundary, the subdivisional lines, Certain Homestead Entry Surveys and the subdivision of certain sections, and a metes and bounds survey, Township 21 South, Range 17 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this retracement and dependent resurvey is as follows: the exterior boundary of the San Ignacio Del Babocomari Private Land Grant was surveyed by Phillip Contzen, U.S. Deputy Surveyor in 1902, the survey of the Fourth Standard Parallel South thorough Ranges 16 and 17 East was surveyed by Theodore F. White, U.S. Deputy Surveyor in 1874 and 1876, the resurvey of the Fourth Standard Parallel South through Ranges 17, 18, and 19 East was surveyed by Phillip Contzen, U.S. Deputy Surveyor in 1902, the subdivision and the retracement of a portion of the north boundary of Township 21 South, Range 17 East was executed by John F. Hesse, U.S. Surveyor in 1912, the survey and resurvey of the west boundary of Township 21 South, Range 17 East was executed by John F. Hesse, U.S. Surveyor in 1912, the resurvey of the Fourth Standard Parallel thru part of Range 16 East and the survey of part of the east boundary of Township 21 South, Range 16 East was executed by Dupree R. Averill, U.S. Surveyor in 1925, and Homestead Entry Surveys Numbers 526 and 527 were executed by C. A. Long, Surveyor, Forest Service in 1917.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated January 14, 1991, and the Supplemental Special Instructions dated January 25, 1991, for Group Number 727, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and a search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data was thoroughly verified and only the true line field notes are given herein.

The directions of all lines were determined by direct hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with a Topcon GTS-3B total station.

## BOOK 5332

T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

## CHAINS

The geographic position of corner 9, H.E.S. 526, as determined from a tie made to U.S. Army Corps of Engineers Survey triangulation station "4-F-904", located in the SW quarter of section 6, is as follows:

Latitude: 31°37'56.50" N. Longitude: 110°39'06.01" W. NAD27

The mean magnetic declination, as taken from quadrangle map SONOITA, ARIZ., published in 1958 by U.S. Geological Survey, is 12° E.

---

Dependent Resurvey,  
Portion of the San Ignacio Del Babocomari Land Grant,  
T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

---

Restoring the survey executed by  
Phillip Contzen, in 1902

---

Beginning at the 22 1/2 mile cor., monumented with a limestone 15 x 9 x 7 ins., firmly set, projecting 6 ins. above the ground, marked 22 1/2M on N. face, SIDB on E. face and PL on the W. face, from which an original bearing tree

An oak, 28 ins. diam., bears S. 45° W., 161 lks. dist., mkd. with a healed blaze. (Record: 163 lks.).

A mound of stone, 3 ft. base, 1 ft. high, is W. of cor.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T21S  
R17E  
S8  
1991

/ 22 1/2 M  
SIDB

from which

An oak, 15 ins. diam., bears S. 6 1/2° W., 204 lks. dist., mkd. 22 1/2M SIDB BT.

Dependent Resurvey,  
 Portion of the San Ignacio Del Babocomari Land Grant,  
 T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
|        | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken brown glass beneath the stainless steel post.</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <p>Rebuild mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Cor. is located beneath a barbed wire fence, 5 strands, bears ESE and WNW.</p> <p>N. 19°02' W., on the 23rd mile.</p> <p>Over rolling ground, along a 5 strand barbed wire fence, through scattered cacti, oak, and juniper timber.</p>  |
| 21.36  | Point for the closing cor. of secs. 5 and 8, hereinafter described.  |
| 33.00  | Ridge, bears E. and W.   |
| 40.22  | <p>The 23 mile cor., monumented with a limestone 17 x 12 x 7 ins., firmly set, projecting 8 ins. above the ground, marked 23M on N. face, SIDB on E. face and PL on the W. face., from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A double oak, 15 ins. diam., bears S. 21° W., 170 lks., dist., mkd. with a healed blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p>from which</p> <p style="padding-left: 40px;">An oak, 11 ins. diam., bears S. 69° E., 32 lks. dist., mkd. 23M SIDB BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken brown glass beneath the stainless steel post.</p> <p>Cor. is located beneath a barbed wire fence, 5 strands, bears SSE and NNW.</p> |

Dependent Resurvey,  
 Portion of the San Ignacio Del Babocomari Land Grant,  
 T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
|        | N. 18°59' W., on the 24th mile.  |
|        | Over rolling ground, along a 5 strand barbed wire fence, through scattered cacti, oak, and juniper timber.   |
| 17.65  | Ridge, bears E. and W.   |
| 23.49  | Point for the closing cor. of the E. and W. center line of sec. 5, hereinafter described.  |
| 25.25  | Dry wash, 30 lks. wide, drains NE.   |
| 29.40  | Dry wash, 30 lks. wide, drains WNW.  |
| 32.20  | Ridge, bears E. and W.   |
| 39.00  | Dry wash, 25 lks. wide, drains NE.   |
| 39.97  | <p>The 23 1/2 mile cor., determined from original bearing trees</p> <p style="padding-left: 40px;">An oak, 18 ins. diam., bears N. 85° W., 46 lks. dist., mkd. with a healed blaze.</p> <p style="padding-left: 40px;">A twin oak, 11 ins. diam., bears N. 11 3/4° W., 43 lks. dist., mkd. with a healed blaze.</p> <p>A limestone, 4 x 3 x 1 1/2 ft., is laying loose below a rock outcrop, mkd. with an X on top face; and 23 1/2M, PL, and SIDB on the other faces</p> <p>A mound of stone, 2 ft. base, 1 ft. high, is set N. of cor.</p> <p>At the cor. point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, in a rock outcrop, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>T21S<br/>R17E<br/>S5</p> <p>23 1/2 M<br/>SIDB</p> <p>1991</p> </div> |

Dependent Resurvey,  
 Portion of the San Ignacio Del Babocomari Land Grant,  
 T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
|        | <p>from which</p> <p>An oak, 19 ins. diam., bears N. 71° E., 92 lks. dist., mkd.<br/>           23 1/2M SIDB BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case<br/>           beneath the brass tablet.</p> <p>Cor. is located beneath a barbed wire fence, 5 strands, bears SSE<br/>           and NNW.</p> <hr/> <p>N. 19°00' W., beginning new measurement.</p> <p>Over rolling ground, along a 5 strand barbed wire fence, through<br/>           scattered cacti, oak, and juniper timber.</p> |
| 2.65   | Dry wash, 16 lks. wide, drains NE.   |
| 3.00   | Left bank of dry wash, 65 lks. wide, bears SE and NW.  |
| 5.20   | Left bank of same wash bears N. and S.   |
| 9.65   | Ridge, bears NE and SW.  |
| 12.35  | Ridge, bears NE and SW.  |
| 13.75  | Dry wash, 25 lks. wide, drains NE.   |
| 26.80  | Natural gas pipeline gate and trail road, 22 lks. wide, bears<br>E. and W.   |
| 27.32  | Point for the closing cor. of sec. 5 and 32, Tps. 20 and 21 S.,<br>R. 17 E., hereinafter described.  |
| 38.68  | The closing cor. of secs. 31 and 32, T. 20 S., R. 17 E.,<br>monumented with a limestone, 14 x 12 x 12 ins., loosely set, mkd.<br>SIDB on N. face, 32 on E. face, CC on S. face, and 31 on the<br>W. face.  |

Dependent Resurvey,  
Portion of the San Ignacio Del Babocomari Land Grant,  
T. 20 S., R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS       |   |
|--------------|---|
|              | <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20S R17E<br/>S31      SIDB<br/>           <br/>          CC S32<br/>          1991</p> </div> <p>Deposit four 40d spike nails and broken green glass beneath the stainless steel post.</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <p>Raise mound of stone, 2 1/2 ft. base, 2 ft. high, S. of cor.</p> <p>From this cor. point, the Standard cor. of secs. 31 and 32, on the N. bdy. of T. 21 S., R. 17 E., bears S. 0°13' E., 10.80 chs. dist., hereinafter described.</p> <p>Cor. is located beneath a barbed wire fence, 5 strands, bears SSE and NNW.</p> |
| <p>40.21</p> | <p>The 24 mile cor., monumented with a limestone, 20 x 9 x 8 ins., firmly set, projecting 9 ins. above the ground, marked 24M on N. face, SIDB on E. face and PL on the W. face.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20S R17E<br/>S31      SIDB<br/>                 24M<br/>          1991</p> </div> <p>from which</p> <p style="padding-left: 40px;">An oak, 14 ins. diam., bears S. 77 1/4° E., 80 1/2 lks. dist., mkd. X BT.</p>  |



Dependent Resurvey,  
 Portion of the San Ignacio Del Babocomari Land Grant,  
 T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS

A double oak, 8 ins. diam., bears S. 37 1/4° E.,  
 162 1/2 lks. dist., mkd. 24M SIDB BT.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and  
 broken brown glass beneath the stainless steel post.

Bury the mkd. stone alongside the stainless steel post.

The cor. is located beneath a barbed wire fence, 5 strands, bears  
 SSE and NNW.

Dependent Resurvey,  
 Portion of the N. bdy., (Fourth Standard Parallel South),  
 T. 21 S., R. 17 E., Gila and Salt River Mer. Arizona

Restoring the survey executed by  
 Phillip Contzen, in 1902

From the stan. cor. of secs. 31 and 36, T. 20 S., R. 16 and  
 17 E., identical with cor. 1, H.E.S. 527, monumented with an iron  
 post, 3 ins. diam., firmly set, projecting 18 ins. above the  
 ground, encircled with a collar of stone, with brass cap mkd. SC  
 T20S R16 E R17E S36 S31 1925.

Remark brass cap to read

|       |      |
|-------|------|
| SC    |      |
| T20S  |      |
| R16E  | R17E |
| S36   | S31  |
| ----- |      |
| 1991  |      |
| 1925  |      |

Cor. falls N. 34 1/4° E., 48 1/2 lks. dist., from a power pole,  
 mkd. J03061911, power lines, 2 strands, extend ESE and WNW.

Cor. falls N. 74 3/4° W., 157 1/2 lks. dist., from a power pole,  
 mkd. J03062011, power lines, 2 strands, extend ESE and WNW.

Dependent Resurvey,  
Portion of the N. Bdy., (Fourth Standard Parallel South),  
T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS

From this cor. point, the stan. 1/4 sec. cor. of sec. 36,  
T. 20 S., R. 16 E., bears S. 89°52' W., 39.89 chs. dist.,  
monumented with an iron post, 1 ins. diam., firmly set,  
projecting 6 ins. above the ground, with brass cap mkd.  
SC 1/4 S36 1925, from which an original bearing tree,

An oak, 17 ins. diam., bears N. 66° E., 106 1/2 lks. dist.,  
mkd. with healed blaze. (Record: 102 lks.)

Remark the brass cap to read

SC  
T20S R16E  
1/4 S36

1991  
1925

from which

A conglomerate boulder, 4 x 3 x 3 ft. high, bears  
N. 73 1/4° E., 133 lks. dist., with X BO chiseled in  
3 in. high letters, on the top face.

Rebuild a mound of stone, 3 1/2 ft. base, 3 ft. high, N. of  
cor.

Cor. is located beneath a barbed wire fence, 4 strands,  
bears E. and W.

From this same cor. point, the closing cor. of secs. 1 and 6,  
T. 21 S., Rs. 16 and 17 E., bears S. 89°52" W., 8.69 chs. dist.,  
hereinafter described.

Dependent Resurvey,  
Portion of the N. Bdy., (Fourth Standard Parallel South),  
T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

|        |   |
|--------|---|
| CHAINS | <p>S. 89°02' E., on the N. bdy. of the tp., identical with a portion of line 1-2, H.E.S. 527.</p> <p>Over rolling ground, through scattered cacti, oak, and juniper timber</p> <p>1.05 Papago Springs Road, dirt road, 30 lks. wide, bears E. and W.</p> <p>1.55 Power line, 2 strands, bears N. and S.</p> <p>2.87 Point for the 1/4 sec. cor. of sec. 6 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. beneath the surface of Papago Springs Road, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T20S R17E</p> <hr style="width: 50px; margin: 0 auto;"/> <p>1/4 S6</p> <p>T21S R17E</p> <p>1991</p> </div> <p>from which</p> <p style="margin-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument bears S. 39° E., 38.1 ft. dist., with brass cap mkd. T21S R17E S6 RM 38.1 FT TO COR 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Cor. is located beneath a smooth wire fence, 5 strands, bears E. and W.</p> <p style="margin-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 51° W., 45.8 ft. dist., with brass cap mkd. T21S R17E S6 RM 45.8 FT TO COR 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Cor. is located beneath a smooth wire fence, 5 strands, bears E. and W.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken brown glass beneath the stainless steel post.</p> <p>Cor. falls N. 56 3/4° W., 42 1/2 lks. dist., from a power pole, mkd. J0306221, power lines, 2 strands, extend E. and W.</p> |
|--------|---|

Dependent Resurvey,  
Portion of the N. Bdy., (Fourth Standard Parallel South),  
T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
| 32.80  | Private dirt road, 30 lks. wide, bears ESE intersects Papago Springs Road, 36 lks. wide, bears E. and W.   |
| 33.39  | <p>Cor. 2, H.E.S. 527, identical with the closing cor. at intersection with line 3-2, H.E.S. 527; hereinafter described.</p> <p>Thence, along a barbed wire fence, 4 strands, bearing E. and SSE and a power line, 2 strands, bears E. and W.</p>  |
| 39.50  | <p>The stan. 1/4 sec. cor. of sec. 31, T. 20 S., R. 17 E., monumented with a red sandstone, 25 x 11 x 4 ins., firmly set, projecting 8 ins. above ground, mkd. SC 1/4 on the N. face.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC<br/>T20S R17E<br/>1/4 S31<br/>-----<br/>1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken brown glass beneath the stainless steel post.</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <p>Cor. falls South, 1 1/2 lks. dist., from a metal fence cor. post, with barbed wire fences, 4 strands, extending E. and W., and N.</p> <p>Raise a mound of stone, 4 ft. base, 2 ft. high, N. of cor.</p> <p style="text-align: center;">-----</p> <p>N. 89°00' E., beginning new measurement.</p> <p>Over rolling ground, along a 4 strand barbed wire fence and 2 strand power line, through scattered cacti, oak, and juniper timber.</p> |

Dependent Resurvey,  
Portion of the N. Bdy., (Fourth Standard Parallel South),  
T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS    |  |    |  |      |  |      |      |     |     |    |  |           |  |      |  |
|-----------|--|----|--|------|--|------|------|-----|-----|----|--|-----------|--|------|--|
| 3.37      | Point for the closing cor. of secs. 5 and 6, hereinafter described.  |    |  |      |  |      |      |     |     |    |  |           |  |      |  |
| 5.80      | Dry wash, 20 lks. wide, drains N.  |    |  |      |  |      |      |     |     |    |  |           |  |      |  |
| 10.15     | Dry wash, 15 lks. wide, drains N.  |    |  |      |  |      |      |     |     |    |  |           |  |      |  |
| 17.95     | Center of gate, 6 ft. wide, in 4-strand barbed wire fence, bears E. and W.   |    |  |      |  |      |      |     |     |    |  |           |  |      |  |
| 22.65     | Terminus of power line, 2 strands, bears W.  |    |  |      |  |      |      |     |     |    |  |           |  |      |  |
| 36.05     | Dry wash, 15 lks. wide, drains NNE.  |    |  |      |  |      |      |     |     |    |  |           |  |      |  |
| 39.97     | <p>The stan. cor. of secs. 31 and 32, T. 20 S, R. 17 E., monumented with a conglomerate stone, 17 x 8 x 8 ins., loosely set, projecting 12 ins. above ground, mkd. SC on top, 5 notches on E. face, and 1 notch on the W. face, from which an original bearing tree</p> <p style="padding-left: 40px;">An oak, 8 ins. diam., bears N. 66° W., 72 lks. dist., mkd. with healed blaze. (Record: N. 69 1/4° W., 68 lks.)</p> <p>A mound of stone, 3 ft. base, 2 ft. high, is set N. of cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">SC</td></tr> <tr><td colspan="2">T20S</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R17E</td><td style="padding: 0 5px;">R17E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S31</td><td style="padding: 0 5px;">S32</td></tr> <tr><td colspan="2" style="border-top: 1px solid black; margin-top: 5px;">S5</td></tr> <tr><td colspan="2">T21S R17E</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken brown glass beneath the stainless steel post.</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <p>Rebuild a mound of stone, 4 ft. base, 2 ft. high, N. of cor.</p> <p>Cor. is located beneath a barbed wire fence, 4 strands, bears E. and W.</p> | SC |  | T20S |  | R17E | R17E | S31 | S32 | S5 |  | T21S R17E |  | 1991 |  |
| SC        |  |    |  |      |  |      |      |     |     |    |  |           |  |      |  |
| T20S      |  |    |  |      |  |      |      |     |     |    |  |           |  |      |  |
| R17E      | R17E   |    |  |      |  |      |      |     |     |    |  |           |  |      |  |
| S31       | S32  |    |  |      |  |      |      |     |     |    |  |           |  |      |  |
| S5        |  |    |  |      |  |      |      |     |     |    |  |           |  |      |  |
| T21S R17E |  |    |  |      |  |      |      |     |     |    |  |           |  |      |  |
| 1991      |  |    |  |      |  |      |      |     |     |    |  |           |  |      |  |

Dependent Resurvey,  
 Portion of the N. Bdy., (Fourth Standard Parallel South),  
 T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS      |  |
|-------------|--|
|             | <p>From this cor. point, the closing cor. of the line between secs. 31 and 32, T. 20 S., R. 17 E., with the San Ignacio Del Babocomari Land Grant, bears N. 0°13' W., 10.80 chs. dist., hereinafter described.</p>   |
|             | <p>N. 89°05' E., on the S. bdy. of sec. 32.</p> <p>Over rolling ground, along 4 strand barbed wire fence, through scattered cacti, oak, and juniper timber.</p>  |
| <p>3.44</p> | <p>Point for the 1/4 sec. cor. of sec. 5 only, at proportionate dist.; No cor. was established during the original survey.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T20S R17E<br/> <hr style="width: 50px; margin: 0 auto;"/>                     1/4 S5<br/>                     T21S R17E<br/>                     1991</p>  |
| <p>3.66</p> | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken brown glass beneath the stainless steel post.</p> <p>Point for the closing cor. of secs. 5 and 32, determined at proportionate dist. on the San Ignacio Del Babocomari Land Grant. There is no remaining evidence of the original cor. position.</p> <p style="text-align: center;">A granite stone, 18 x 10 x 10 ins., was laying loose on the ground mkd. SIDB on N. face and SC CC on the W. face.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20S R17E<br/>                     S32<br/> <hr style="width: 50px; margin: 0 auto;"/>                     SIDB<br/>                     CC<br/>                     S5<br/>                     T21S<br/>                     1991</p> |

Dependent Resurvey,  
Portion of the N. Bdy., (Fourth Standard Parallel South),  
T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

## CHAINS

from which

An oak, 4 ins. diam., bears N. 85° W., 89 1/2 lks.  
dist., mkd. X BT.

A double alligator juniper, 6 ins. diam., bears N. 38° W.,  
133 1/2 lks. dist., mkd. T20S R17E S32 CC BT.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and  
broken brown glass beneath the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Deposit the mkd. stone in the mound of stone.

Cor. is located beneath a barbed wire fence, 5 strands, bears  
SSE and NNW.

From this cor. point, the 23 1/2 Mile cor., San Ignacio Del  
Babocomari Land Grant, bears S. 19°00' E., 27.32 chs. dist.;  
hereinbefore described.

---

Dependent Resurvey, Portion of the West boundary,  
T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

---

Restoring the survey executed by  
Dupree R. Averill, in 1912

---

From the 1/4 sec. cor. of sec. 7 only, on the W. bdy. of the tp.,  
monumented with an iron post, 1 in. diam., firmly set, projecting  
17 ins. above the ground, bent over flush with the ground, with  
brass cap missing, from which the original bearing trees

An oak root hole, 40 ins. diam., bears N. 68 1/2° E.,  
121 lks. dist.

An oak, 16 ins. diam., bears S. 11 3/4° E., 118 lks. dist.,  
mkd. with a healed blaze.

Dependent Resurvey, Portion of the West Boundary,  
T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

|               |   |      |      |  |        |  |      |
|---------------|---|------|------|--|--------|--|------|
| <p>CHAINS</p> | <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T21S</p> <table style="margin: auto;"> <tr> <td style="padding-right: 10px;">R16E</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">R17E</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">1/4 S7</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">1991</td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 11 ins. diam., bears N. 53 1/4° E., 52 lks. dist., mkd. 1/4 S7 BT.</p> <p style="padding-left: 40px;">An oak, 8 ins. diam., bears S. 27 1/4° E., 155 lks. dist., mkd. 1/4 S7 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken brown glass beneath the stainless steel post.</p> <p>Bury the original iron post, 36 ins. long, alongside the stainless steel post.</p> <p>Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, E. of cor. N. 0°14' W., on the W. bdy. of sec. 7.</p> <p>Over rolling mountainous ground, through scattered cacti, oak, and juniper timber.</p> <p>4.44 The 1/4 sec. cor. of sec. 12 only, T. 21 S., R. 16 E., monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd. 1/4 S12 1925, from which an remaining bearing tree</p> <p style="padding-left: 40px;">An oak, 19 ins. diam., bears S. 77 1/2° W., 102 lks. dist., mkd. with a healed blaze.</p> | R16E | R17E |  | 1/4 S7 |  | 1991 |
| R16E          | R17E  |      |      |  |        |  |      |
|               | 1/4 S7  |      |      |  |        |  |      |
|               | 1991  |      |      |  |        |  |      |







BOOK 5332

Dependent Resurvey, Portion of the West Boundary,  
T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

|        |  |      |      |    |  |     |      |      |    |  |  |  |      |  |      |
|--------|--|------|------|----|--|-----|------|------|----|--|--|--|------|--|------|
| CHAINS | <p>Remark the brass cap to read.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 2px;">T21S</td> <td style="padding: 2px;">T21S</td> </tr> <tr> <td style="padding: 2px;">S1</td> <td style="padding: 2px;"> </td> </tr> <tr> <td style="border-top: 1px solid black; padding: 2px;">S12</td> <td style="border-top: 1px solid black; padding: 2px;">R17E</td> </tr> <tr> <td style="padding: 2px;">R16E</td> <td style="padding: 2px;">S6</td> </tr> <tr> <td style="padding: 2px;"></td> <td style="padding: 2px;"> </td> </tr> <tr> <td style="padding: 2px;"></td> <td style="padding: 2px;">1991</td> </tr> <tr> <td style="padding: 2px;"></td> <td style="padding: 2px;">1925</td> </tr> </table> <hr style="width: 30%; margin: 10px auto;"/> </div> <p>N. 0°02' E., beginning new measurement.</p> <p>Over rolling mountainous land, through scattered cacti, oak, and juniper timber.</p> <p>5.25 Dry wash, 10 lks. wide, drains NW.</p> <p>9.00 Ridge, bears SSE and NNW.</p> <p>15.48 Point for S. 1/16 sec. cor. of sec. 6 only. Point falls in a stream, 15 lks. wide, course NNE; impractical to establish a permanent monument.</p> <p>From this cor. point, the point selected for the witness cor. to the S. 1/16 sec. cor. of sec. 6 only, bears N. 20°00' W., 70 lks., dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> | T21S | T21S | S1 |  | S12 | R17E | R16E | S6 |  |  |  | 1991 |  | 1925 |
| T21S   | T21S   |      |      |    |  |     |      |      |    |  |  |  |      |  |      |
| S1     |  |      |      |    |  |     |      |      |    |  |  |  |      |  |      |
| S12    | R17E   |      |      |    |  |     |      |      |    |  |  |  |      |  |      |
| R16E   | S6   |      |      |    |  |     |      |      |    |  |  |  |      |  |      |
|        |  |      |      |    |  |     |      |      |    |  |  |  |      |  |      |
|        | 1991   |      |      |    |  |     |      |      |    |  |  |  |      |  |      |
|        | 1925   |      |      |    |  |     |      |      |    |  |  |  |      |  |      |

## BOOK 5332

Dependent Resurvey, Portion of the West Boundary,  
T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | WC<br>T21S<br>R16E   R17E<br>  S 1/16<br>  S6<br> <br>1991  |
|        | <p>from which</p> <p>A double alligator juniper, 5 ins. diam., bears<br/>S. 69 1/4° E., 91 lks. dist., mkd. WC S1/16 S6 BT.</p> <p>An alligator juniper, 9 ins. diam., bears S. 31 1/4° E.,<br/>88 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case<br/>and broken green glass beneath the stainless steel post.</p> |
| 18.20  | Stream, 55 lks. wide, course NNW.   |
| 23.00  | Dry wash, 5 lks. wide drains WSW.   |
| 23.17  | Point for AP 2, hereinafter described.  |
| 23.60  | Ridge, bears NE and SW.   |
| 24.25  | Dry wash, 10 lks. wide, drains W.   |
| 25.80  | Old downed barbed wire fence, 4 strands, bears ENE and WSW.   |
| 26.00  | Ridge, bears ENE and WSW.   |

## BOOK 5332

Dependent Resurvey, Portion of the West Boundary,  
T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |      |      |  |      |  |      |     |  |    |  |      |  |  |      |  |
|--------|---|------|------|--|------|--|------|-----|--|----|--|------|--|--|------|--|
| 26.40  | Old downed barbed wire fence, 4 strands, bears ENE and WSW.   |      |      |  |      |  |      |     |  |    |  |      |  |  |      |  |
| 26.95  | Dry wash, 10 lks. wide, drains SW.  |      |      |  |      |  |      |     |  |    |  |      |  |  |      |  |
| 27.45  | Dry wash, 10 lks. wide, drains SSW.   |      |      |  |      |  |      |     |  |    |  |      |  |  |      |  |
| 32.80  | Ridge, bears ESE and WNW.   |      |      |  |      |  |      |     |  |    |  |      |  |  |      |  |
| 35.10  | Dry wash, 10 lks. wide, drains W.   |      |      |  |      |  |      |     |  |    |  |      |  |  |      |  |
| 35.38  | <p>The 1/4 sec. cor. of sec. 6 only, monumented with an iron post, 1 in. diam., firmly set, projecting 32 ins. above the ground, in a supporting mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, with brass cap, mkd. 1/4 S6 1912, from which a bearing tree of record</p> <p style="text-align: center;">An alligator juniper, 20 ins. diam., bears S. 30° E.,<br/>77 lks. dist., mkd. 1/4 S6 BT.</p> <p>Remark the brass cap to read</p> <div style="text-align: center;"> <table border="0"> <tr><td></td><td>T21S</td><td></td></tr> <tr><td>R16E</td><td> </td><td>R17E</td></tr> <tr><td>1/4</td><td> </td><td>S6</td></tr> <tr><td></td><td>1991</td><td></td></tr> <tr><td></td><td>1912</td><td></td></tr> </table> </div> <p>from which</p> <p style="text-align: center;">An oak, 10 ins. diam., bears N. 54 1/4° E., 53 lks. dist.,<br/>mkd. 1/4 S6 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 3°52' E., beginning new measurement.</p> <p>Over rolling mountainous land, through cacti, oak, and juniper timber.</p> |      | T21S |  | R16E |  | R17E | 1/4 |  | S6 |  | 1991 |  |  | 1912 |  |
|        | T21S  |      |      |  |      |  |      |     |  |    |  |      |  |  |      |  |
| R16E   |   | R17E |      |  |      |  |      |     |  |    |  |      |  |  |      |  |
| 1/4    |   | S6   |      |  |      |  |      |     |  |    |  |      |  |  |      |  |
|        | 1991  |      |      |  |      |  |      |     |  |    |  |      |  |  |      |  |
|        | 1912  |      |      |  |      |  |      |     |  |    |  |      |  |  |      |  |

## BOOK 5332

Dependent Resurvey, Portion of the West Boundary,  
T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
| 4.46   | <p>The 1/4 sec. cor. of sec. 1 only, T. 21 S., R. 16 E., monumented with an iron post, 1 in. diam., firmly set, projecting 26 ins. above the ground, and in a supporting mound of stone, 4 ft. base, 2 ft. high, with brass cap, mkd. 1/4 S1 1925.</p> <p>Remark the brass cap to read</p> <div style="text-align: center;"> <p>T21S<br/>R16E   R17E<br/>1/4 S1  <br/>1991<br/>1925</p> </div> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 6 ins. diam., bears S. 24 1/4° W., 41 lks. dist., mkd. 1/4 S1 BT.</p> <p style="padding-left: 40px;">A double oak, 10 ins. diam., bears N. 79 1/2° W., 97 lks. dist., mkd. X BT.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0°25' W., beginning new measurement.</p> <p>Over rolling mountainous land, through scattered cacti, oak, and juniper timber.</p> |
| 3.35   | Ridge, bears E. and W.   |
| 10.75  | Draw, 10 lks. wide, drains NW.   |
| 11.85  | Draw, 5 lks. wide, drains WSW.   |
| 15.59  | <p>Point for the N. 1/16 sec. cor. of sec. 6 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T21S<br/>R16E   R17E<br/>N 1/16<br/>S6<br/>1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken brown glass beneath the stainless steel post.</p>   |

## BOOK 5332

Dependent Resurvey, Portion of the West Boundary,  
T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |   |   |    |    |      |      |      |      |
|--------|--|---|---|----|----|------|------|------|------|
|        | Raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.   |   |   |    |    |      |      |      |      |
| 17.15  | Trail road, 12 lks. wide, bears ESE and WNW.   |   |   |    |    |      |      |      |      |
| 33.25  | Natural gas pipeline road, dirt road, 12 lks. wide, bears E. and W.  |   |   |    |    |      |      |      |      |
| 37.05  | The closing cor. for the line between secs. 1 and 6, established in 1912, monumented with an iron post, 30 ins. long, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. T20S R16E R17E S36 S31 CC S1 S6 R16E R17E T21S 1912. Add the marks AM 1991 to the brass cap and bury the iron post in place, 4 ins. below the surface of the ground. Cor. is located beneath a barbed wire fence, 4 strands, bears E. and W.  |   |   |    |    |      |      |      |      |
| 37.06  | Point for the closing cor. for the line between secs. 1 and 6, at intersection with the N. Bdy., (Fourth Standard Parallel South), of the tp.<br><br>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  |   |   |    |    |      |      |      |      |
|        | <p style="text-align: center;">T20S R16E<br/>S36</p> <hr style="width: 10%; margin: auto;"/> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">C</td> <td style="padding: 2px 5px;">C</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S1</td> <td style="padding: 2px 5px;">S6</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">R16E</td> <td style="padding: 2px 5px;">R17E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">T21S</td> <td style="padding: 2px 5px;">1991</td> </tr> </table> | C | C | S1 | S6 | R16E | R17E | T21S | 1991 |
| C      | C  |   |   |    |    |      |      |      |      |
| S1     | S6   |   |   |    |    |      |      |      |      |
| R16E   | R17E   |   |   |    |    |      |      |      |      |
| T21S   | 1991   |   |   |    |    |      |      |      |      |
|        | from which   |   |   |    |    |      |      |      |      |
|        | An oak, 13 ins. diam., bears S. 46 1/4° E., 71 lks. dist., mkd. CC T21S R17E S6 BT.  |   |   |    |    |      |      |      |      |
|        | An alligator juniper, 9 ins. diam., bears S. 21 3/4° W., 78 lks. dist., mkd. CC T21S R16E S1 BT.   |   |   |    |    |      |      |      |      |

## BOOK 5332

Dependent Resurvey, Portion of the West Boundary,  
T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken brown glass beneath the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this cor. point, the stan. 1/4 sec. cor. of sec. 36,  
T. 20 S., R. 16 E. bears S. 89°52' W., 31.29 chs. dist.;  
hereinbefore described.

---

Dependent Resurvey, Portion of the Subdivisional lines,  
T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

---

Restoring the survey executed by  
John F. Hesse, in 1912

---

From the cor. of secs. 5, 6, 7, and 8, monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above the ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap, mkd., T21S R17E S5 S6 S7 S8 1912.

Remark brass cap to read.

|           |    |
|-----------|----|
| T21S R17E |    |
| S6        | S5 |
| -----     |    |
| S7        | S8 |
| 1991      |    |
| 1912      |    |

from which new bearing trees

An alligator juniper, 9 ins. diam., bears N. 33 3/4° E.,  
43 lks. dist., mkd. T21S R17E S5 BT.

An alligator juniper, 8 ins. diam., bears S. 27 1/4° E.,  
11 1/2 lks. dist., mkd. T21S R17E S8 BT.

An oak, 20 ins. diam., bears S. 32° W., 284 lks. dist.,  
mkd. T21S R17E S7 BT.

An oak, 12 ins. diam., bears N. 22 1/4° W., 134 lks. dist.,  
mkd. T21S R17E S6 BT.




## BOOK 5332

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS    |  |           |    |     |       |    |      |      |
|-----------|--|-----------|----|-----|-------|----|------|------|
|           | S. 89°57' E., bet. secs. 5 and 8.  |           |    |     |       |    |      |      |
|           | Over rolling mountainous land, through scattered cacti, oak, and juniper timber.   |           |    |     |       |    |      |      |
| 22.75     | Dry wash, 40 lks. wide, drains NE.   |           |    |     |       |    |      |      |
| 23.25     | Ridge, bears NNE and SSW.  |           |    |     |       |    |      |      |
| 24.95     | Dry wash, 12 lks. wide, drains N.  |           |    |     |       |    |      |      |
| 31.40     | Ridge, bears SSE and NNW.  |           |    |     |       |    |      |      |
| 35.60     | Swail, 70 lks wide, drains SSE.  |           |    |     |       |    |      |      |
| 39.97     | The 1/4 sec. cor. of secs. 5 and 8, monumented with an iron post, 1 in. diam., firmly set, projecting 27 ins. above the ground, and in a supporting mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, with brass cap, mkd. 1/4 S5 S8 1912. |           |    |     |       |    |      |      |
|           | Remark the brass cap to read   |           |    |     |       |    |      |      |
|           | <table style="margin-left: auto; margin-right: auto;"> <tr><td>T21S R17E</td></tr> <tr><td>S5</td></tr> <tr><td>1/4</td></tr> <tr><td>_____</td></tr> <tr><td>S8</td></tr> <tr><td>1991</td></tr> <tr><td>1912</td></tr> </table>        | T21S R17E | S5 | 1/4 | _____ | S8 | 1991 | 1912 |
| T21S R17E |  |           |    |     |       |    |      |      |
| S5        |  |           |    |     |       |    |      |      |
| 1/4       |  |           |    |     |       |    |      |      |
| _____     |  |           |    |     |       |    |      |      |
| S8        |  |           |    |     |       |    |      |      |
| 1991      |  |           |    |     |       |    |      |      |
| 1912      |  |           |    |     |       |    |      |      |
|           | from which new bearing trees   |           |    |     |       |    |      |      |
|           | An alligator juniper, 11 ins. diam., bears N. 77 3/4° E., 71 lks. dist., mkd. X BT.  |           |    |     |       |    |      |      |
|           | An oak, 9 ins. diam., bears N. 28 3/4° W., 73 lks. dist., mkd. 1/4 S5 BT.  |           |    |     |       |    |      |      |
|           | _____  |           |    |     |       |    |      |      |

BOOK 5332

Dependent Resurvey, Portion of the Subdivisional Lines  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | S. 89°59' E., beginning new measurement.  |
|        | Over rolling mountainous land, through scattered cacti, oak, and juniper timber.  |
| 4.30   | Dry wash, 15 lks. wide, drains N.   |
| 6.05   | Ridge, bears N. and S.  |
| 12.95  | Dry wash, 30 lks. wide, drains NE.  |
| 14.90  | Fence cor., barbed wire, 4 strands, bears E. and S.   |
| 16.10  | Dry wash, 45 lks. wide, drains NNW.   |
| 19.92  | An iron pipe, 1 in. diam., firmly set, projecting 2 ins. above the ground, with no cap. The iron pipe falls on top of a ridge, bearing N. and S., beneath a barbed wire fence, 4 strands, bearing E. and W.   |
| 28.22  | The closing cor. for line between secs. 5 and 8, established in 1912, monumented with an iron post, 36 ins. long, 2 ins. diam., firmly set, projecting 10 ins. above ground with brass cap mkd. SIDB S5 CC S8 T21S R17E 1912. Add the marks AM 1991 to the brass cap and bury iron post in place, 6 ins. below the surface of the ground. |
| 28.23  | Point for the closing cor. for the line between secs. 5 and 8, at intersection with the San Ignacio Del Babocomari Land Grant.<br><br>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.  |
|        |   |

## BOOK 5332

Dependent Resurvey, Portion of the Subdivisional Lines  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
|        | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken brown glass beneath the stainless steel post.</p> <p>Cor. is located S. 20° W., 2 lks. dist., from a wooden fence corner post, 9 ins. square, with barbed wire fences, 5 strands, extending SSE and NNW, and 4 strands, extending W.</p> <p>From this cor. point, the 22 1/2 Mile cor. of the San Ignacio Del Babocomari Land Grant bears S. 19°02' E., 21.36 chs. dist.; hereinbefore described.</p> <hr/> <p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>S. 89°57' W., bet. secs. 6 and 7.</p> <p>Over rolling mountainous land, through scattered cacti, oak, and juniper timber.</p> |
| 9.75   | Fence, barbed wire, 6 strands, bears SSE and NNW.  |
| 11.35  | Power line, 2 strands, bears SE and NW.  |
| 14.10  | Gravel road, 30 lks. wide, bears SSE and NNW.  |
| 30.15  | Dry wash, 15 lks. wide, drains NE.   |
| 35.15  | Ridge, bears SSE and NNW.  |
| 39.60  | Dry wash, 25 lks. wide, drains NNW.  |
| 39.96  | <p>The 1/4 sec. cor. of secs. 6 and 7, monumented with an iron post, 1 in. diam., firmly set, projecting 19 ins. above the ground, in a supporting mound of stone, 4 ft. base, 3 ft. high, with brass cap, mkd. S6 1/4 S7 1912., from which the original bearing trees</p> <p style="padding-left: 40px;">An oak, 12 ins. diam., bears N. 10 1/4° E., 26 lks. dist., mkd. with a healed blaze. (Record: N. 12 1/2° E., 28 lks.)</p>  |

## BOOK 5332

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | <p>An alligator juniper, 13 ins. diam., bears S. 55° W.,<br/>27 lks. dist., mkd. 1/4 S7 BT, visible through a partially<br/>healed blaze. (Record: S. 53 1/4° W., 28 lks.)</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T21S R17E<br/>S6<br/>1/4</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S7<br/>1991<br/>1912</p> <hr style="width: 30%; margin: auto;"/> <p>N. 89°49' W., beginning new measurement.</p> <p>Over rolling mountainous land, through scattered cacti, oak, and<br/>juniper timber</p> <p>6.60 Ridge, bears SSE and NNW.</p> <p>11.74 The cor. of secs. 6 and 7 only, on the W. bdy of tp.,<br/>hereinbefore described.</p> <hr style="width: 80%; margin: auto;"/> <p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over rolling ground, through scattered cacti, oak, and juniper<br/>timber.</p> <p>4.95 Point for cor. 6, (closing cor.), H.E.S. 526.</p> <p style="padding-left: 40px;">A sandstone 24 x 11 x 10 ins., broken in half and laying<br/>loose nearby, mkd. X on top, 6 HES 526 on one side, and CC<br/>on an adjoining side.</p> |

## BOOK 5332

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
26 ins. in the ground, with brass cap mkd.

|           |    |
|-----------|----|
| HES 526   |    |
| COR 6     | CC |
| S6        | S5 |
| T21S R17E |    |
| 1991      |    |

from which new bearing trees

An oak, 17 ins. diam., bears S. 26 1/4° W., 181 1/2 lks.  
dist., mkd. X BT.

A double alligator juniper, 5 ins. diam., bears  
N. 31 3/4° W., 59 1/2 lks. dist., mkd. X BT.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and  
broken brown glass beneath the stainless steel post.

Bury the mkd. stone alongside the stainless steel post.

Thence, across private property.

40.04

The 1/4 sec. cor. of secs. 5 and 6, monumented with a rebar,  
1/2 in. diam., firmly set, projecting 6 ins. above the ground, of  
unknown origin. This position was accepted by Mr. Timothy C.  
Shelest, Arizona Registered Land Surveyor, R.L.S. No. 13569,  
according to the Record of Survey plat of a portion of H.E.S.  
526, filed in book of surveys No. 1, page 117, on August 2, 1989,  
at the Santa Cruz County Courthouse, Nogales, Arizona. This is  
accepted as the best available evidence of the original position  
cor.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush  
with the surface of the ground, with brass cap mkd.

## BOOK 5332

Dependent Resurvey, Portion of the Subdivisional Lines  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS

T21S R17E

1/4

S6 | S5

1991

from which

An oak, 4 ins. diam., bears S.  $8\ 3/4^\circ$  W., 148 1/2 lks.  
dist., mkd. X BT.

An oak, 5 ins. diam., bears N.  $84^\circ$  W., 97 lks. dist., mkd.  
1/4 S6 BT.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and  
broken green glass beneath the stainless steel post.

Bury the rebar alongside the stainless steel post.

---

N.  $0^\circ 05'$  W., beginning new measurement.

Over rolling ground, across private property, through scattered  
cacti, oak, and juniper timber.

4.40 Point for cor. 1, (closing cor.), H.E.S. 526, identical with  
cor. 5, H.E.S. 527, monumented with a red sandstone 24 x 8 x 6  
ins. diam., firmly set, projecting 9 ins. above the ground, mkd.  
5 HES 527 on N. face, CC on E. face, and 1 HES 526 on the S.  
face.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
25 ins. in the ground, with brass cap mkd.

## BOOK 5332

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | T21S R17E<br>S6<br>AP 5   HES 527<br>_____<br>AP 1   HES 526<br>1991  |
| 19.86  | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken brown glass beneath the stainless steel post.</p> <p>Bury the original stone alongside the stainless steel post.</p> <p>Cor. is located in a barbed wire fence, 5 strands, bears E. and W.</p> <p>Point for cor. 3, (closing cor.), H.E.S. 527, monumented with a sandstone 19 x 12 x 9 ins., firmly set projecting 7 ins. above ground, mkd. with an X on top, CC on N. face, and 3 HES 527 on the W. face, from which the original bearing trees</p> <p style="padding-left: 40px;">An oak, 11 ins. diam., bears S. 84 1/4° E., 55 lks. dist., mkd. with a healed blaze.</p> <p style="padding-left: 40px;">An oak stump, 6 ins. diam., cut off to 8 ins. above ground, bears N. 85° W., 86 lks. dist.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> |

## BOOK 5332

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | <p style="text-align: center;"> <del>HES 527</del>   <del>T21S R17E</del><br/> <del>AP 3 C</del>   <del>S6</del><br/> <del>1991</del> </p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">An oak, 9 ins. diam., bears N. 1 1/2° W., 239 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken green glass beneath the stainless steel post.</p> <p>Bury the found stone alongside the stainless steel post.</p> <p>The cor. is located 1 1/2 lks. W. of a barbed wire fence, 5 strands, bears SSE and NNW.</p> <p>Thence, leave private property.</p> |
| 19.90  | <p>Point for the N. 1/16 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">           T21S R17E<br/>           N 1/16<br/>           S6   S5<br/>           1991         </p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken green glass beneath the stainless steel post.</p> <p>Cor. is located in a barbed wire fence, 5 strands, bears SSE and NNW.</p>   |
| 40.15  | <p>Natural gas pipeline dirt road, 20 lks. wide, bears E. and W.</p>  |



## BOOK 5332

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |    |    |      |    |      |  |
|--------|---|----|----|------|----|------|--|
| 40.65  | <p>The closing cor. for the line between secs 5 and 6, established in 1912, monumented with an iron post, 36 ins. long, 2 ins. diam., firmly set, projecting 12 ins. above ground with brass cap mkd. T20S R17E S31 S32 CC S6 S5 1912. Add the marks AM 1991 to the brass cap and bury the iron post in place, 5 ins. below the surface of the ground. Cor. is located beneath a barbed wire fence, 4 strands, bearing E. and W., and under a power line, 2 strands, bearing E. and W.</p>  |    |    |      |    |      |  |
| 40.68  | <p>Point for the closing cor. for the line between secs. 5 and 6 with the N. Bdy., (Fourth Standard Parallel South), of the tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, to bedrock, in a mound of stone 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20S R17E<br/>S31</p> <hr style="width: 50px; margin: 0 auto;"/> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S6</td> <td style="padding: 0 5px;">CC</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T21S</td> <td style="padding: 0 5px;">S5</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">1991</td> <td></td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">An oak, 10 ins. diam., bears S. 68 1/2° E., 166 1/2 lks. dist., mkd. T21S R17E CC S5 BT.</p> <p style="padding-left: 40px;">An oak, 9 ins. diam., bears S. 33 1/2° W., 87 1/2 lks. dist., mkd. T21S R17E CC S6 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken brown glass beneath the stainless steel post.</p> <p>Cor. is located 3 lks. N. of a barbed wire fence, 4 strands, bears E. and W.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 20 S., R. 17 E. bears S. 89°00' W., 3.37 chs. dist.; hereinbefore described.</p> | S6 | CC | T21S | S5 | 1991 |  |
| S6     | CC  |    |    |      |    |      |  |
| T21S   | S5  |    |    |      |    |      |  |
| 1991   |   |    |    |      |    |      |  |

## BOOK 5332

Dependent Resurvey of Certain Homestead Entry Surveys,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS

## Homestead Entry Survey No. 526

Restoring the survey executed by  
C. A. Long, Forest Service Surveyor, in 1917

From cor. 1, identical with cor. 5, H.E.S. 527, on the line  
between secs. 5 and 6, hereinbefore described.

N. 89°52' E., on line 1-2, identical with line 5-4, H.E.S. 527.

Over rolling ground, along a 5 strand barbed wire fence, through  
scattered cacti, oak, and juniper timber.

7.03

Cor. 2, identical with cor. 4, H.E.S. 527, monumented with an  
iron post, 2 ins. diam., firmly set, projecting 12 ins. above  
ground, with brass cap mkd., T21S R17E S5 HES 527 4 HES 526 2  
1917, from which original bearing trees

An oak, 15 ins. diam., bears N. 5 3/4° E., 287 1/2 lks.  
dist., mkd. X BT.

A double oak, 6 ins. diam., bears S. 83 1/2° E., 164 lks.  
dist., mkd. X BT.

Remark brass cap to read

|       |      |
|-------|------|
| HES   | T21S |
| 527 4 | R17E |
| HES 2 | S5   |
| 526   |      |
|       | 1991 |
|       | 1917 |

Cor. is located S. 40° E., 1 1/2 lks. dist. from a metal fence  
cor., of barbed wire fences, 5 strands, fences extend SSE, W.,  
and NNW.

## BOOK 5332

Dependent Resurvey of Certain Homestead Entry Surveys,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

|        |  |
|--------|--|
| CHAINS | <p>S. 25°31' E., on line 2-3.</p> <p>Over rolling ground, along a 5 strand barbed wire fence, through scattered cacti, oak, and juniper timber.</p> <p>0.10 Private dirt road, 20 lks. wide, bears E. and W.</p> <p>4.90 The point for a witness point on the E. and W. center line of sec. 5, hereinafter described.</p> <p>7.79 Cor. 3, monumented with a red sandstone 23 x 11 x 10 ins., firmly set, projecting 7 ins. above the ground, marked X on top and 3 HES 526 on the W. face. The original memorial limestone, 4 x 3 x 2 ins., mkd. X, at base of original stone.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p style="margin: 0;">COR 3      T21S<br/>HES      R17E<br/>526      S5<br/>1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case, broken brown glass, and the original memorial limestone beneath the stainless steel post.</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Cor. is located beneath a barbed wire fence, 5 strands, bears SSE and NNW.</p> <p>Cor. is located N. 20° W., 3 lks. dist., from a wood fence cor. post of barbed wire fences bears fences, 5 strands, extend SSE, SSW, and NNW.</p> <hr style="width: 20%; margin: 20px auto;"/> |
|--------|--|

Dependent Resurvey, Certain Homestead Entry Surveys,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

|        |  |
|--------|--|
| CHAINS | <p>S. 19°44' W., on line 3-4.</p> <p>Over rolling ground, along a 5 strand barbed wire fence, through scattered cacti, oak, and juniper timber.</p> <p>15.15 End of barbed wire fence, 4 strands, bears NNE, and beginning of mesh wire fence, bears SSW.</p> <p>16.05 Cor. 4, monumented with a red sandstone 19 x 10 x 6 ins., firmly set, projecting 6 ins. above the ground, marked X on top and 4 HES 526 on the W. face.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>COR 4 / T21S<br/>HES / R17E<br/>526 / S5<br/>1991</p> </div> <p>from which</p> <p>An oak, 4 ins. diam., bears S. 85° E., 40 1/2 lks. dist., mkd. X BT.</p> <p>A double oak, 8 ins. diam., bears S. 31 3/4° E., 82 lks. dist., mkd. X BT.</p> <p>A metal fence cor. post, of mesh wire fences bears S. 12° E., 3 lks. dist., fences extend NNE and S.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken brown glass beneath the stainless steel post.</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <p>Cor. is located 1 lk. W. of mesh wire fence, extending NNE and SSW.</p> <hr style="width: 20%; margin: 20px auto;"/> |
|--------|--|


## BOOK 5332

Dependent Resurvey, Certain Homestead Entry Surveys,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

|         |  |         |      |       |      |  |    |      |  |
|---------|--|---------|------|-------|------|--|----|------|--|
| CHAINS  | <p>S. 0°01' W., on line 4-5.</p> <p>Over rolling ground, along a mesh wire fence, through scattered cacti, oak, and juniper timber.</p> <p>17.37 Cor. 5, H.E.S. 526 ,monumented with a red sandstone 32 x 12 x 9 ins., firmly set, projecting 10 ins. above the ground, marked X on top and 5 HES 526 on the W. face.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">HES 526</td> <td style="padding: 2px 5px;">T21S</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">COR 5</td> <td style="padding: 2px 5px;">R17E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;"></td> <td style="padding: 2px 5px;">S5</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">1991</td> </tr> </table> <p>from which</p> <p style="padding-left: 40px;">An oak, 8 ins. diam., bears S. 59° E., 43 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken brown glass beneath the stainless steel post.</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <p>Cor. is located S. 65° E., 1 1/2 lks. dist., from a metal fence cor. post, 6 ins. diam., of mesh wire fences and a barbed wire fence mesh wire fences extend N. and W. and barbed wire fence, 6 strands, extends S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>West, on line 5-6.</p> <p>Over rolling ground, along a mesh wire fence, through scattered cacti, oak, and juniper timber.</p> | HES 526 | T21S | COR 5 | R17E |  | S5 | 1991 |  |
| HES 526 | T21S   |         |      |       |      |  |    |      |  |
| COR 5   | R17E   |         |      |       |      |  |    |      |  |
|         | S5   |         |      |       |      |  |    |      |  |
| 1991    |  |         |      |       |      |  |    |      |  |


## BOOK 5332

Dependent Resurvey, Certain Homestead Entry Surveys,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
| 4.91   | <p>Cor. 6, (closing cor.), at intersection with the line bet. secs. 5 and 6, hereinbefore described.</p> <p>From this cor. point, the cor. of secs. 5, 6, 7 and 8 bears S. 0°03' E., 4.95 chs. dist., hereinbefore described.</p> <hr/> <p>West, on line 6-7.</p> <p>Over rolling ground, along a wire mesh fence, through scattered cacti, oak, and juniper timber.</p>   |
| 11.33  | <p>Cor. 7, monumented with a red sandstone, 24 x 6 x 7 ins., firmly set, projecting 8 ins. above the ground, marked X on top and 7 HES 526 on the E. face.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>HES 526<br/>COR 7</p> <p>S6<br/>T21S R17E<br/>1991</p> </div> <p>from which</p> <p style="padding-left: 40px;">An oak, 5 ins. diam., bears S. 3 3/4° E., 128 1/2 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">An alligator juniper, 6 ins. diam., bears N. 67 3/4° W., 135 1/2 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken brown glass beneath the stainless steel post.</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <p>Cor. is located along side a metal cor. post, mesh wire fences extends E. and NNW.</p> <hr/> |


## BOOK 5332

Dependent Resurvey, Certain Homestead Entry Surveys,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | N. 12°24' W., on line 7-8.  |
|        | Over rolling ground, along a mesh wire fence, through scattered cacti, oak, and juniper timber.   |
| 2.10   | Power line, 2 strands, bears SW and NNW.  |
| 6.06   | Cor. 8, monumented with a red sandstone, 26 x 6 x 6 ins., firmly set, projecting 3 ins. above the ground, marked X on the top and 8 HES 526 on the E. face. |
|        | At the cor. point   |
|        | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.  |
|        |   |
|        | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken brown glass beneath the stainless steel post.  |
|        | Bury the mkd. stone alongside the stainless steel post.   |
|        | Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, E. of cor.  |
|        | Cor. is located 22 lks. S. of a private drive, 20 lks. wide, bears ESE and WNW.   |
|        | Cor. is located 1 1/2 lks. N., of a metal fence cor., 6 ins. diam., mesh wire fences extends E. and SSE and barbed wire fence, 7 strands, extends WNW.      |

## BOOK 5332

Dependent Resurvey, Certain Homestead Entry Surveys,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
|        | <p>N. 75°48' W., on line 8-9.</p> <p>Over rolling ground, along a 7 strand barbed wire fence, through scattered cacti, oak, and juniper timber.</p> <p>15.67 Point for cor. 9, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>T21S R17E    HES 526<br/>S6            COR 9<br/>1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken brown glass beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Cor. is located 13 lks., SSE from a steel cattle guard cor. post, 6 ins. diam.</p> <p>From this cor. point, Army Corps of Engineers VABM, "4F904", with published latitude of 31°37'54.921" N. and longitude of 110°39'06.386" W., NAD27 bears S. 11°35' W., 2.47 chs. dist. monumented with a standard brass disk, 4 ins. diam., set in 6 x 6 ins. square concrete block, firmly set, projecting 6 ins. above the ground, with top of disk mkd., 1947 4F904 ASA 67 FT.,</p> <hr style="width: 20%; margin: 10px auto;"/> |
| 0.30   | <p>N. 32°50' W., on line 9-10.</p> <p>Over rolling ground, along a mesh wire fence, through scattered cacti, oak, and juniper timber.</p> <p>Private dirt road, 15 lks. wide, bears ESE and WNW.</p>   |



## BOOK 5332

Dependent Resurvey, Certain Homestead Entry Surveys,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS    |   |           |         |    |        |  |      |
|-----------|---|-----------|---------|----|--------|--|------|
| 7.55      | Power line, bears N. and S., and barbed wire fence, 7 strands, bears E., and wire mesh fence, bears SSE and NNW.  |           |         |    |        |  |      |
| 10.10     | Rebar, 5/8 in. diam., firmly set, projecting 10 ins. above the ground, with an alum. cap, 1 1/2 ins. diam., no mks., at intersection of mesh wire fences, bearing E., SSE and NNW.  |           |         |    |        |  |      |
| 15.33     | AP 1, hereinafter described.  |           |         |    |        |  |      |
| 22.30     | Private dirt road with cattle guard, 15 lks. wide, bears E. and W.  |           |         |    |        |  |      |
| 22.50     | The witness point on the N. and S. center line of sec. 6, at intersection with line 9-10, H.E.S. 526, hereinafter described.  |           |         |    |        |  |      |
| 26.22     | Cor. 10, monumented with a red sandstone, 29 x 10 x 8 ins., firmly set, projecting 13 ins. above the ground, marked X on top and the E. face is covered by concrete.  |           |         |    |        |  |      |
|           | At the cor. point   |           |         |    |        |  |      |
|           | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.  |           |         |    |        |  |      |
|           | <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">T21S R17E</td> <td style="border-left: 1px solid black; padding-left: 5px;">HES 526</td> </tr> <tr> <td style="text-align: center;">S6</td> <td style="border-left: 1px solid black; padding-left: 5px;">COR 10</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 5px;">1991</td> </tr> </table> | T21S R17E | HES 526 | S6 | COR 10 |  | 1991 |
| T21S R17E | HES 526   |           |         |    |        |  |      |
| S6        | COR 10  |           |         |    |        |  |      |
|           | 1991  |           |         |    |        |  |      |
|           | from which  |           |         |    |        |  |      |
|           | <p>A double alligator juniper, 8 ins. diam., bears<br/>S. 4 1/4° E., 17 1/2 lks. dist., mkd. X BT.</p>  |           |         |    |        |  |      |
|           | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken brown glass beneath the stainless steel post.  |           |         |    |        |  |      |
|           | Bury the mkd. stone alongside the stainless steel post.   |           |         |    |        |  |      |
|           | Cor. is located 2 lks. SSW from a metal fence cor. post, 6 ins. diam., set in concrete bears, barbed wire fence, 7 strands, extends SSE.  |           |         |    |        |  |      |

## BOOK 5332

Dependent Resurvey, Certain Homestead Entry Surveys,  
T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |  |     |  |     |      |   |      |       |    |    |  |         |  |      |  |      |
|--------|---|--|-----|--|-----|------|---|------|-------|----|----|--|---------|--|------|--|------|
|        | <p>Cor. is located 1 1/2 lks. W. of terminus of a barbed wire fence, 7 strands, bears SSE.</p> <hr/> <p>N. 6°26' W., on line 10-11.</p> <p>Over rolling ground, through scattered cacti, oak, and juniper timber.</p>   |  |     |  |     |      |   |      |       |    |    |  |         |  |      |  |      |
| 0.15   | Dirt road, 15 lks. wide, bears E. and W.  |  |     |  |     |      |   |      |       |    |    |  |         |  |      |  |      |
| 0.25   | Fence cor., barbed wire, 4 strands, bears N. and E., thence, along a 5 strand barbed wire fence.  |  |     |  |     |      |   |      |       |    |    |  |         |  |      |  |      |
| 3.12   | The point for the witness point on the E. and W. center line of sec. 6, at intersection with line 10-11, H.E.S. 526.hereinafter described.  |  |     |  |     |      |   |      |       |    |    |  |         |  |      |  |      |
| 7.45   | Private dirt road, 18 lks. wide, bears E. and W.  |  |     |  |     |      |   |      |       |    |    |  |         |  |      |  |      |
| 7.71   | <p>Cor. 11, identical with cor. 6, H.E.S. 527, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd., T21S R17E S6 HES 527 6 11 HES 526 1917.</p> <p>Remark brass cap to read</p> <div style="text-align: center;"> <table> <tr><td></td><td>HES</td></tr> <tr><td></td><td>527</td></tr> <tr><td>T21S</td><td>6</td></tr> <tr><td>R17E</td><td>_____</td></tr> <tr><td>S6</td><td>11</td></tr> <tr><td></td><td>HES 526</td></tr> <tr><td></td><td>1991</td></tr> <tr><td></td><td>1917</td></tr> </table> </div> <p>Cor. is located 3 lks. NNW from a metal fence cor. post, 6 ins. diam., barbed wire fence, 5 strands extends E.</p> <p>From this cor. point, the SW cor. of a red brick pillar, 16 x 16 x 56 ins., bears N. 20 1/4° E., 28 1/2 lks. dist.</p> <p>From this same cor. point, the NW cor. of a red brick pillar, 16 x 16 x 56 ins., bears N. 79° E., 11 1/2 lks. dist.</p> <hr/> |  | HES |  | 527 | T21S | 6 | R17E | _____ | S6 | 11 |  | HES 526 |  | 1991 |  | 1917 |
|        | HES   |  |     |  |     |      |   |      |       |    |    |  |         |  |      |  |      |
|        | 527   |  |     |  |     |      |   |      |       |    |    |  |         |  |      |  |      |
| T21S   | 6   |  |     |  |     |      |   |      |       |    |    |  |         |  |      |  |      |
| R17E   | _____   |  |     |  |     |      |   |      |       |    |    |  |         |  |      |  |      |
| S6     | 11  |  |     |  |     |      |   |      |       |    |    |  |         |  |      |  |      |
|        | HES 526   |  |     |  |     |      |   |      |       |    |    |  |         |  |      |  |      |
|        | 1991  |  |     |  |     |      |   |      |       |    |    |  |         |  |      |  |      |
|        | 1917  |  |     |  |     |      |   |      |       |    |    |  |         |  |      |  |      |

## BOOK 5332

Dependent Resurvey, Certain Homestead Entry Surveys,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

|  |  |
|--|--|
| CHAINS   | <p>N. 89°57' E., on line 11-1, identical with line 6-5, H.E.S. 527.</p> <p>Over rolling ground, along a barbed wire fence, through scattered cacti, oak, and juniper timber.</p>   |
| 2.86   | Intersect the N. and S. center line of section 6, hereinafter described.   |
| 42.85  | Cor. 1, identical with cor. 5, H.E.S. 527, and point of beginning.   |
| <hr/> <p>Homestead Entry Survey 527</p> <hr/>  |  |
| <p>Restoring the survey executed by<br/>C. A. Long, Forest Service Surveyor, in 1917</p> <hr/> |  |
|  | <p>From cor. 1, identical with the stan. cor. of secs. 31 and 36, T. S., Rs. 16 and 17 E., hereinbefore described.</p> <p>S. 89°02' E., on line 1-2, identical with a portion of the N. bdy., (Fourth Standard Parallel South), of the tp.</p> |
| 2.87   | The 1/4 sec. cor. of sec. 6 only, on the N. bdy. of the tp., hereinbefore described.   |
| 33.39  | The closing cor. of line 2-3, also functions as cor. 2, monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd., T20S R17E S1 T21S R17E HES 527 2 S6 CC 1925.                          |

## BOOK 5332

Dependent Resurvey, Certain Homestead Entry Surveys,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | Remark brass cap to read  |
|        | T20S R17E<br>S1<br><hr/> 2   T21S<br>HES   R17E<br>527   S6<br>CC<br>1991<br>1925   |
|        | from which  |
|        | A sedimentary boulder, 7 x 4 x 1 ft. high, bears<br>S. 67° E., 243 lks. dist., with X BO chiseled in 3 in.<br>high letters, on the top.                   |
|        | Cor. is located alongside a wooden fence cor. post, 8 ins.<br>square, with barbed wire fences, 4 strands, extends E. and SSE.                             |
|        | Cor. falls 60 1/2 lks., NE from a power pole, mkd. J03065111,<br>with power lines extends SE and WSW.   |
|        | _____   |
|        | S. 24°30' E., on line 2-3.  |
|        | Over rolling ground, along a barbed wire fence, through scattered<br>cacti, oak, and juniper timber.  |
| 0.18   | Power line, 2 strands, bears SE and NW.   |
| 0.35   | Dirt road, 15 lks. wide, bears ESE and WNW.   |
| 0.69   | Natural Gas Pipeline gate.  |
| 22.88  | Point for the witness point on the E. and W. center line of the<br>NE 1/4 of sec. 6, at intersection with line 2-3, H.E.S. 527,<br>hereinafter described. |

## BOOK 5332

Dependent Resurvey of Certain Homestead Entry Surveys,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

|        |  |
|--------|--|
| CHAINS |  |
| 22.93  | Cor. 3, hereinbefore described.<br><hr/>   |
|        | S. 24°32' E., on line 3-4.<br><br>Over rolling ground, along a barbed wire fence, through scattered cacti, oak, and juniper timber.              |
| 16.98  | Cor. 4, identical with cor. 2, H.E.S. 526, hereinbefore described.<br><hr/>  |
|        | S. 89°52' W., on line 4-5, identical with line 2-1, H.E.S. 526.  |
| 7.03   | Cor. 5, identical with cor. 1, H.E.S. 526, hereinbefore described.<br><hr/>  |
|        | S. 89°57' W., on line 5-6, identical with line 1-11, H.E.S. 526.   |
| 39.99  | Intersect the N. and S. center line of sec. 6, hereinafter described.  |
| 42.85  | Cor. 6, identical with cor. 11, H.E.S. 526, hereinbefore described.<br><hr/>   |
|        | N. 4°31' W., on line 6-7.<br><br>Over rolling ground, along a barbed wire fence, through scattered cacti, oak, and juniper timber.               |
| 0.15   | Private gravel road, 18 lks. wide, bears E. and W.   |
| 15.54  | Point for the witness point on the E. and W. center line of the NW 1/4 sec. 6, at intersection with line 6-7, H.E.S. 527, hereinafter described. |

Dependent Resurvey of Certain Homestead Entry Surveys,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
| 30.88  | An iron pipe, 1 in. diam., firmly set, projecting 20 ins. above the ground, tagged RLS 13569.   |
| 35.26  | Fence cor., barbed wire, 7 strands, bears N. and SSE.   |
| 36.55  | Oiled gravel road, 30 lks. wide, bears NNE and SSW.   |
| 37.03  | The closing cor., established in 1913, for line 6-7, monumented with an iron post, 2 ins. diam., firmly set, 12 ins. below the ground, with brass cap mkd., T20S R16E S36 T21S R17E S6 CC 7 HES 527 1917. Add the marks AM 1991 to the brass cap. Cor. is located on W. edge of oiled gravel road, 30 lks. wide, bears NNE and S. |
| 37.04  | Point for the closing cor. for line 6-7, with the N. bdy., (Fourth Standard Parallel South), of the tp.; also functions as cor. 7.  |
|        | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.  |
|        | <pre> T20S R16E   S36 -----   C C T21S   R17E   COR 7   S6   HES 527     1991 </pre>  |
|        | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken brown glass beneath the stainless steel post.  |
|        | Cor is located 46 lks. WSW from an iron fence cor. post, 5 ins. diam. with smooth wire fences, 5 strands, extends ESE and S.  |
|        | Cor. is located 16 1/2 lks. ENE from an iron fence cor. post, 5 ins. diam., with 5 barbed wire fence, extends N. and a barbed wire fence, 4 strands, extends W.   |

## BOOK 5332

Dependent Resurvey, Certain Homestead Entry Surveys,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS  |   |
|---|---|
|   | N. 89°52' E., on line 7-1, identical with a portion of the N. Bdy., (Fourth Standard Parallel South).         |
| 2.85  | Cor. 1, identical with the stan. cor. of secs. 31 and 36, T. 20 S., Rs. 16 and 17 E., and point of beginning. |
| Subdivision of Certain Sections,<br>T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona |   |
| Section 5   |   |
|   | From the 1/4 sec. cor. of secs. 5 and 8.  |
|   | N. 0°01' W., on the N. and S. center line of sec. 5.  |
| 1.85  | Ridge, bears E. and W.  |
| 3.90  | Dry wash, 10 lks. wide, drains E.   |
| 6.90  | Ridge, bears E. and W.  |
| 10.00   | Dry wash, 5 lks. wide, drains NE.   |
| 10.60   | Dry wash, 5 lks. wide, drains E.  |
| 11.40   | Ridge, bears E. and W.  |
| 12.20   | Dry wash, 10 lks. wide, drains ESE.   |
| 20.00   | Ridge, bears E. and W.  |
| 23.70   | Dry wash, 5 lks. wide, drains E.  |
| 26.40   | Ridge, bears E. and W.  |

## BOOK 5332

Subdivision of Certain Sections,  
T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

|                         |   |
|-------------------------|---|
| <p>CHAINS<br/>40.05</p> | <p>Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E. and W. center line of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to bedrock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T21S R17E<br/>C 1/4 S5<br/>1991</p> <p>from which</p> <p style="padding-left: 40px;">An oak, 8 ins. diam., bears N. 10° E., 55 1/2 lks. dist., mkd. T21S R17E C1/4 S5 BT.</p> <p style="padding-left: 40px;">An oak, 7 ins. diam., bears N. 40 3/4° W., 74 1/2 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken brown glass beneath the stainless steel post.</p> <p>40.30 Ridge, bears E. and W.</p> <p>50.30 Dry wash, 25 lks. wide, drains NNE.</p> <p>58.70 Ridge, bears ENE and WSW.</p> <p>65.70 Ridge, bears E. and W.</p> <p>81.45 The 1/4 sec. cor. of sec. 5 only, on the N. bdy. of the tp., (Fourth Standard Parallel South), hereinbefore described.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 6.</p> <p>S. 89°58' E., on the E. and W. center line of sec. 5.</p> <p>Over rolling ground, across private property, through scattered cacti, oak and juniper timber.</p> <p>9.13 Point for a witness point on the E. and W. center line, at intersection with line 2-3, H.E.S. 526.</p> |
|-------------------------|---|





BOOK 5332

Subdivision of Certain Sections,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

|        |  |
|--------|--|
| CHAINS | <p>52.53 Dry wash, 30 lks. wide, drains NE.</p> <p>54.44 The closing cor. for the E. and W. center line of sec. 5, at intersection with the San Ignacio Del Babocomari Land Grant.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p>from which</p> <p style="margin-left: 40px;">An alligator juniper, 18 ins. diam., bears S. 25 3/4° W., 102 lks. dist., mkd. S5 CC BT.</p> <p style="margin-left: 40px;">An alligator juniper, 11 ins. diam., bears N. 48° W., 129 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken green glass beneath the stainless steel post.</p> <p>From this cor. point, the 23 1/2 Mile cor., San Ignacio Del Babocomari Land Grant bears N. 18°59' W., 16.48 chs. dist.; hereinbefore described.</p> <hr style="border: 0.5px solid black; margin: 20px 0;"/> <p style="text-align: center;">Subdivision of Section 6</p> <hr style="border: 0.5px solid black; margin: 20px 0;"/> <p>From the 1/4 sec. cor. of secs. 6 and 7.</p> <p>N. 0°06' W., on the N. and S. center line of sec. 6.</p> |
|--------|--|


## BOOK 5332

Subdivision of Certain Sections,  
T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
| 0.70   | Dry wash, 15 lks. wide, drains NNE.   |
| 3.20   | Dry wash, 20 lks. wide, drains NNE.   |
| 4.50   | Ridge, bears NE and SW.   |
| 6.65   | Dry wash, 5 lks. wide, drains NW.   |
| 6.90   | Dry wash, 10 lks. wide, drains E.   |
| 7.35   | Ridge, bears E. and W.  |
| 8.15   | Dry wash, 40 lks. wide, drains NW.  |
| 16.85  | Ridge, bears E. and W.  |
| 19.30  | Dry wash, 10 lks. wide, drains NNW.   |
| 19.94  | Point for the center S. 1/16 sec. cor. of sec. 6.   |
|        | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. |
|        | <p style="text-align: center;">T21S R17E<br/>C<br/>S 1/16   S6<br/>C<br/>1991</p>   |
|        | from which  |
|        | <p style="text-align: center;">An alligator juniper, 8 ins. diam., bears S. 41 3/4° E.,<br/>39 lks. dist., mkd. CS 1/16 S6 BT.</p>              |
|        | <p style="text-align: center;">An alligator juniper, 6 ins. diam., bears S. 33° W., 82 lks.<br/>dist., mkd. X BT.</p>                           |
|        | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken green glass beneath the stainless steel post.                            |

## BOOK 5332

Subdivision of Certain Sections,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
| 20.30  | Dry wash, 5 lks. wide, drains SW.   |
| 24.40  | Dry wash, 5 lks. wide, drains SW.   |
| 27.30  | Ridge, bears ESE and WNW.   |
| 27.63  | Intersect line between AP 1 and AP 2, not monumented.   |
| 28.90  | Dry wash, 10 lks. wide, drains W.   |
| 32.90  | Trail road, 40 lks. wide, bears SSE and NNW.  |
| 33.41  | Trail road, 20 lks. wide, bears ENE and WSW.  |
| 33.65  | Point for the witness point at intersection with line 9-10,<br>H.E.S. 526.  |
|        | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,<br>27 ins. in the ground, with brass cap mkd.               |
|        |                                      |
|        | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and<br>broken brown glass beneath the stainless steel post. |
|        | Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.  |
|        | Thence, across private property.  |
| 33.70  | Barbed wire fence, 4 strands, bears SE and NW.  |
| 33.75  | Barbed wire fence, 4 strands, bears E. and W.   |
| 36.85  | Private dirt road, 15 lks. wide, bears E. and W.  |
| 37.30  | Barbed wire fence, 4 strands, bears E. and W.   |

## BOOK 5332

Subdivision of Certain Sections,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

|        |  |
|--------|--|
| CHAINS |  |
| 39.89  | Point for the center 1/4 sec. cor. of sec. 6, at intersection with E. and W. center line of sec. 6.                  |
|        | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.               |
|        | <p style="text-align: center;">T21S R17E<br/>C 1/4 S6<br/>1991</p>   |
|        | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken brown glass beneath the stainless steel post. |
|        | Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.   |
| 44.05  | Barbed wire fence, 7 strands, bears E. and W.  |
| 44.20  | Private dirt road, 30 lks. wide, bears E. and W.   |
| 44.40  | Barbed wire fence, 9 strands, bears E. and W.  |
| 44.44  | Intersect line 11-1 H.E.S. 526, identical with line 5-6 H.E.S. 527, point not monumented.                            |
| 44.65  | Private dirt road, 15 lks. wide, bears E. and W.   |
| 59.35  | Barbed wire fence, 4 strands, bears E. and W.  |
| 59.96  | Point for the center N. 1/16 sec. cor. of sec. 6.  |
|        | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, with brass cap mkd.               |
|        | <p style="text-align: center;">T21S R17E<br/>C<br/>N 1/16   S6<br/>C<br/>1991</p>                                    |
|        | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken brown glass beneath the stainless steel post. |
| 75.10  | Barbed wire fence, 5 strands, bears E. and W.  |

## BOOK 5332

Subdivision of Certain Sections,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona


| CHAINS   |  |
|--|--|
| 80.85  | Barbed wire fence, 5 strands, bears E. and W.  |
| 80.90  | Power line, 2 strands, bears E. and W.   |
| 81.32  | The 1/4 sec. cor. of sec. 6 only, on the N. bdy. of Tp, (Fourth Standard Parallel South), hereinbefore described.. |
| <hr/>  |  |
| From the 1/4 sec. cor. of secs. 5 and 6.   |  |
| S. 89°44' W., on the E. and W. center line of sec. 6.  |  |
| Over rolling ground, across private property, through scattered cacti, oak, and juniper timber.                      |  |
| 39.99  | The center 1/4 sec. cor. of sec. 6.  |
| 42.35  | Point for a witness point at intersection with line 10-11, H.E.S. 526.   |
| Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.               |  |
|  |  |
| Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken brown glass beneath the stainless steel post. |  |
| Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.   |  |
| Cor. is located beneath a barbed wire fence, 10 strands, bears N. and S.   |  |
| Thence, leave private property.  |  |
| 43.05  | Graded dirt road, 30 lks. wide, bears N. and S.  |

Subdivision of Certain Sections,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS  |  |
|---|--|
| 51.60   | Dry wash, 5 lks. wide, drains SSW.   |
| 51.66   | The 1/4 sec. cor. of sec. 6 only, on the W. tp. bdy., hereinbefore described.  |
| <hr/> NE 1/4 of Section 6 <hr/>   |  |
| From the N. 1/16 sec. cor. of secs. 5 and 6.<br><br>S. 89°58' W., on the E. and W. center line of the NE 1/4 of sec. 6.<br><br>Over rolling ground, through scattered cacti, oak, and juniper timber. |  |
| 0.02  | Point for a witness point at intersection with line 2-3, H.E.S. 527.<br><br>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. |
|   |  |
| Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken green glass beneath the stainless steel post.<br><br>Thence, across private property.  |  |
| 40.00   | The center N. 1/16 sec. cor. of sec. 6.  |

## BOOK 5332

Subdivision of Certain Sections,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
| 11.71  | <p style="text-align: center;">SW 1/4 of Section 6</p> <hr/> <p>From the center S. 1/16 sec. cor. of sec. 6.</p> <p>S. 89°57' W., on the E. and W. center line of the SW 1/4 of sec. 6.</p> <p>Over rolling mountainous ground, through scattered cacti, oak, and juniper timber.</p> <p>The S. 1/16 sec. cor. of sec. 6 only, on the W. bdy. of tp., hereinbefore described.</p>   |
| 4.06   | <p style="text-align: center;">NW 1/4 of Section 6</p> <hr/> <p>From the center N. 1/16 sec. cor. of sec. 6.</p> <p>Over rolling ground, across private property, through scattered cacti, oak, and juniper timber.</p> <p>S. 89°36' W., on the E. and W. center line of the NW 1/4 of sec. 6.</p> <p>Point for a witness point at intersection with line 6-7, H.E.S. 527.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken green glass beneath the stainless steel post.</p> <p>Cor. is located beneath a barbed wire fence, 5 strands, bears N. and S.</p> <p>Thence, leave private property.</p> <p>4.35 Graded dirt road, 40 lks. wide, bears NNE and SSW.</p> |



## BOOK 5332


Subdivision of Certain Sections,  
T. 21 S, R. 17 E., Gila and Salt River Meridian, Arizona

| CHAINS  |  |
|---|--|
| <p>11.44</p> <p>1.10</p> <p>3.88</p> <p>13.70</p> <p>14.40</p> <p>15.57</p> | <p>The N. 1/16 sec. cor. of sec. 6 only, on the W. bdy. of tp., hereinbefore described.</p> <hr/> <p style="text-align: center;">A Metes and Bounds Survey,<br/>T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>"Note" This Metes and Bounds Survey, in section 6, facilitates a possible land exchange.</p> <hr/> <p>From AP 1, T. 21 S., R. 17 E., on line 9-10, H.E.S. 526 in sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T21S R17E</p> <p>AP1</p> <p>S6 ——— HES 526</p> <p>1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and broken green glass beneath the stainless steel post.</p> <p>Cor. is located 1 lk. W. of a barbed wire fence, 7 strands, bears SE and NW.</p> <p>From this cor. point, cor. 9, H.E.S. 526, bears S. 32°50' E., 15.33 chs. dist., hereinbefore described.</p> <p>West, on the line bet. AP 1 and AP 2.</p> <p>Over rolling ground, through scattered cacti, oak, and juniper timber.</p> <p>Dirt road, 30 lks. wide, bears SSE and NNW.</p> <p>Intersect the N and S. centerline sec. 6, hereinbefore described.</p> <p>Dry wash, 5 lks. wide, course NW.</p> <p>Dry wash, 5 lks. wide, course W.</p> <p>Point for AP 2, on W. bdy. of tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> |

## BOOK 5332

A Metes and Bounds Survey,  
T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona

CHAINS



from which

An oak, 4 ins. diam., bears S.  $11^{\circ}$  E., 50 lks. dist., mkd. X BT.

A double alligator juniper, 7 ins. diam., bears S.  $47\ 1/4^{\circ}$  W., 45  $1/2$  lks. dist., mkd. X BT.

Deposit a magnet in a 1 x 1 x 2  $5/8$  ins. white plastic case and broken green glass beneath the stainless steel post.

From this cor. point, the  $1/4$  sec. cor. of sec. 6, only, on the W. bdy. of the tp., bears N.  $0^{\circ}02'$  E., 12.21 chs. dist., hereinbefore described.

---

 GENERAL DESCRIPTION
 

---

The land encompassed in this survey is located approximately 2 miles southerly of Sonoita, Arizona. Elevation ranges from 4900 to 5100 feet above sea level.

Access is by way of Papago Springs Road. Numerous improved and unimproved roads are located within the survey.

The terrain varies throughout the area, from gently rolling ground within the homestead entry surveys, to abrupt rolling mountainous ground on the east and west boundaries of the township.

Vegetation consists of dense oak and juniper on the E. and W. bdys., with pasture and grassy fields within the homestead entry surveys. Cacti abound throughout the area.

There are several horse ranches and a few cattle ranches on the survey.

No mining activity was noted.



## CERTIFICATE OF SURVEY

We, Paul L. Moss, Cadastral Surveyor, and Dainel A. Wiesner, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 14th day of January, 1991, and Supplemental Special Instructions bearing the date of the 25th day of January, 1991, We have dependently resurveyed portions, of the San Ignacio Del Babocomari Land Grant, the N. Bdy. (Fourth Standard Parallel South), the west boundary, the subdivisional lines and certain Homestead Entry Surveys, the subdivision of certain sections and a Metes and Bounds Survey, Township 21 South, Range 17 East, Gila and Salt River Meridian, in the state of Arizona, which are represented in the foregoing field notes as having been executed by Paul L. Moss and Daniel A. Wiesner, under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Paul L. Moss and Dainel A. Wiesner are no longer assigned to this office and are not available for signatures.

9/11/91

(Date)

James L. Wendel  
(Field Supervisor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Arizona State Office  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of portions, of the San Ignacio Del Babocomari Land Grant, the N. Bdy. (Fourth Standard Parallel South), the west boundary, the subdivisional lines and certain Homestead Entry Surveys, the subdivision of certain sections and a Metes and Bounds Survey in Township 21 South, Range 17 East, Gila and Salt River Meridian, Arizona, executed by Paul L. Moss, Cadastral Surveyor, and Daniel A. Wiesner, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

OCT 9 1991

(Date)

Joe A. Stotares  
(Chief Cadastral Surveyor of Arizona)~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 21 S., R. 17 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~(Date)~~~~(Chief Cadastral Surveyor of Arizona)~~