

ORIGINAL

1 BOOK 5347

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE

SURVEY

THE SOUTH BOUNDARY, IDENTICAL WITH THE SEVENTH STANDARD PARALLEL NORTH,

THE WEST BOUNDARY, IDENTICAL WITH THE SIXTH GUIDE MERIDIAN EAST,

THE EAST AND NORTH BOUNDARIES

AND

THE SUBDIVISIONAL LINES

OF

TOWNSHIP 29 NORTH, RANGE 25 EAST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

Daniel N. Patterson and Leonard R. Sandoval, Cadastral Surveyors

Under Special Instructions dated November 22, 1989, approved November 22, 1989,
which provided for the surveys included under Group Number 715 and assignment
instructions dated November 22, 1989.

Survey commenced November 27, 1989

Survey completed January 23, 1991

BOOK 5347

INDEX DIAGRAM

TOWNSHIP 29 NORTH, RANGE 25 EAST,

25 13 6	24 73 5	23 61 4	22 52 3	21 44 2	20 35 1 19
72 13 7	71 71 8	60 59 9	51 51 10	43 42 11	34 33 12 18
70 12 18	69 68 17	58 58 16	50 49 15	42 41 14	32 31 13 17
68 11 19	67 66 20	57 56 21	49 48 22	40 39 23	30 29 24 16
66 10 30	65 64 29	55 54 28	47 46 27	38 37 26	28 27 25 16
63 9 31 4	62 61 32 5	54 53 33 5	45 45 34 6	36 35 35 7	27 26 36 15 8

T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of the survey of the south boundary, identical with the Seventh Standard Parallel North, the west boundary, identical with the Sixth Guide Meridian East, the east and north boundaries and the subdivisional lines of Township 29 North, Range 25 East, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated November 22, 1989, for Group No. 715, Arizona.

The west boundary of the Navajo Indian Reservation, and the boundaries and subdivisional lines of Townships 2 and 3 North, Range 11 West, Navajo Special Meridian, were surveyed by Ehud N. Darling in 1869. The west boundary of the Navajo Indian Reservation was dependently resurveyed by L.E. Sechrist in 1919-20.

The directions of all lines were determined by direct hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured using Zeiss Elta-3, Lietz Set4, and Topcon GTS3B electronic total station instruments.

The geographic position of the standard corner of T. 29 N., Rs. 25 and 26 E., as determined from a tie made to Electronic Control Point 7, hereinafter described, is as follows:

Latitude: 35°52'02.95" N. Longitude: 109°36'01.72" W. NAD27

The geographic coordinates of Electronic Control Point 7, hereinafter described, was determined by the technique of relative positioning utilizing the Motorola Golden Eagle Global Positioning System Satellite Surveyor. "BEAUTIFUL" and "GANADO", first order triangulation stations established by the U.S. Coast and Geodetic Survey, were used as the main control stations. The geographic position is as follows:

Latitude: 35°52'04.03" N., Longitude: 109°35'47.43" W. NAD27

The mean magnetic declination, as taken from 1985 magnetic declination map published by the U.S. Geological Survey, is 12 1/2° E.

Survey of the South Boundary
 Identical With the Seventh Standard Parallel North,
 T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Beginning at the stan. cor. of T. 29 N., Rs. 24 and 25 E., a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the S. bdy. of T. 29 N., R. 24 E., identical with the Seventh Standard Parallel North, through R. 24 E., executed concurrently under this same group.</p>
	<p>East, on the S. bdy. of sec. 31.</p>
	<p>Over gently rolling land.</p>
<p>40.00</p>	<p>Point for the stan. 1/4 sec. cor. of sec. 31.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T29N R25E 1/4 S31 <hr style="width: 10%; margin: auto;"/> 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
<p>53.40</p>	<p>Trail road, bears NNE and SSW.</p>
<p>80.00</p>	<p>Point for the stan. cor. of secs. 31 and 32.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T29N R25E S31 S32 <hr style="width: 10%; margin: auto;"/> 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Land, gently rolling. Soil, sandy clay. No timber; sparse native grasses.</p> <hr/>

Survey of the South Boundary,
 Identical With the Seventh Standard Parallel North,
 T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>East, on the S. bdy. of sec. 32.</p> <p>Over gently rolling land.</p> <p>40.00 Point for the stan. 1/4 sec. cor. of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> SC T29N R25E 1/4 S32 <hr style="width: 50px; margin: 0 auto;"/> 1990 </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 15 lks. E. of a trail road, bears NE and SW.</p> <p>73.35 Trail road, bears SE and NW.</p> <p>80.00 Point for the stan. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> SC T29N R25E S32 S33 <hr style="width: 50px; margin: 0 auto;"/> 1990 </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; sparse native grasses.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>East, on the S. bdy. of sec. 33.</p> <p>Over gently rolling land.</p> <p>40.00 Point for the stan. 1/4 sec. cor. of sec. 33.</p>
--------	---

Survey of the South Boundary,
 Identical With the Seventh Standard Parallel North,
 T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">SC T29N R25E 1/4 S33 <hr style="width: 10%; margin: auto;"/> 1990</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
50.20	Graded road, 30 lks. wide, bears NE and SW.
80.00	Point for the stan. cor. of secs. 33 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">SC T29N R25E S33 S34 <hr style="width: 10%; margin: auto;"/> 1990</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 90 lks. S. of a trail road, bears SE and NW.
	Land, gently rolling. Soil, sandy clay. No timber; sparse native grasses.
	<hr/> East, on the S. bdy. of sec. 34.
	Over gently rolling land.
40.00	Point for the stan. 1/4 sec. cor. of sec. 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">SC T29N R25E 1/4 S34 <hr style="width: 10%; margin: auto;"/> 1990</p>

Survey of the South Boundary,
 Identical With the Seventh Standard Parallel North,
 T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>										
80.00	<p>Point for the stan. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">SC</td></tr> <tr><td>T29N</td><td>R25E</td></tr> <tr><td>S34</td><td> S35</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td colspan="2">1990</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; sparse native grasses.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>East, on the S. bdy. of sec. 35.</p> <p>Over gently rolling land.</p>	SC		T29N	R25E	S34	S35			1990	
SC											
T29N	R25E										
S34	S35										
1990											
40.00	<p>Point for the stan. 1/4 sec. cor. of sec. 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">SC</td></tr> <tr><td>T29N</td><td>R25E</td></tr> <tr><td>1/4</td><td>S35</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td colspan="2">1990</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	SC		T29N	R25E	1/4	S35			1990	
SC											
T29N	R25E										
1/4	S35										
1990											
77.60	<p>Trail road, bears N and S.</p>										
80.00	<p>Point for the stan. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>										

Survey of the South Boundary,
 Identical With the Seventh Standard Parallel North,
 T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	SC T29N R25E S35 S36 <hr style="width: 50%; margin: auto;"/> 1990
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Land, gently rolling. Soil, sandy clay. No timber; sparse native grasses.
	<hr/> East, on the S. bdy. of sec. 36. Over gently rolling land.
14.00	Graded road, 30 lks. wide, bears ESE and WNW.
40.00	Point for stan. 1/4 sec. cor. of sec. 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.
	SC T29N R25E 1/4 S36 <hr style="width: 50%; margin: auto;"/> 1990
51.00	Power line, bears NNE and SSW.
80.00	Point for the stan. cor. of T. 29 N., Rs. 25 and 26 E. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	SC T29N R25E R26E S36 S31 <hr style="width: 50%; margin: auto;"/> 1990

Survey of the South Boundary,
 Identical With the Seventh Standard Parallel North,
 T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, Electronic Control Point 7, monumented with a railroad spike, set flush with the surface of the ground, with top mkd. EC-7, bears N. 84°41' E., 17.91 chs. dist.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; sparse native grasses.</p> <hr/> <p style="text-align: center;">Survey of the West Boundary, Identical With the Sixth Guide Meridian East, T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the stan. cor. of T. 29 N., Rs. 24 and 25 E., hereinbefore described.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rolling land.</p>
5.80	Trail road, bears NNE and SSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29N R24E R25E 1/4 S36 S31 1990</p> </div>
61.95	Trail road, bears NE and SW.
80.00	Point for the cor. of secs. 25, 30, 31, and 36.

Survey of the West Boundary,
 Identical With the Sixth Guide Meridian East,
 T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="836 388 1023 577"> <tr><td colspan="2" style="text-align:center">T29N</td></tr> <tr><td style="text-align:center">R24E</td><td style="text-align:center">R25E</td></tr> <tr><td style="text-align:center">S25</td><td style="text-align:center">S30</td></tr> <tr><td colspan="2" style="text-align:center">-----</td></tr> <tr><td style="text-align:center">S36</td><td style="text-align:center">S31</td></tr> <tr><td colspan="2" style="text-align:center">1990</td></tr> </table> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p>	T29N		R24E	R25E	S25	S30	-----		S36	S31	1990	
T29N													
R24E	R25E												
S25	S30												

S36	S31												
1990													
	<p>North, bet. sccs. 25 and 30.</p>												
	<p>Over rolling land.</p>												
<p>40.00</p>	<p>Point for the 1/4 sec. cor. of sccs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="836 1144 1023 1312"> <tr><td colspan="2" style="text-align:center">T29N</td></tr> <tr><td style="text-align:center">R24E</td><td style="text-align:center">R25E</td></tr> <tr><td colspan="2" style="text-align:center">1/4</td></tr> <tr><td style="text-align:center">S25</td><td style="text-align:center">S30</td></tr> <tr><td colspan="2" style="text-align:center">1990</td></tr> </table> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T29N		R24E	R25E	1/4		S25	S30	1990			
T29N													
R24E	R25E												
1/4													
S25	S30												
1990													
<p>69.70</p>	<p>Pine Springs Wash, 38 lks. wide, 15 ft. deep, drains ENE.</p>												
<p>79.21</p>	<p>Barbed wire fence, 5 strand, bears E and W.</p>												
<p>80.00</p>	<p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>												

Survey of the West Boundary,
 Identical With the Sixth Guide Meridian East,
 T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T29N</td></tr> <tr><td>R24E</td><td>R25E</td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td colspan="2">1990</td></tr> </table>	T29N		R24E	R25E	S24	S19	<hr/>		S25	S30	1990	
T29N													
R24E	R25E												
S24	S19												
<hr/>													
S25	S30												
1990													
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/> <p>North, bet. secs. 19 and 24.</p> <p>Over rolling land.</p>												
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T29N</td></tr> <tr><td>R24E</td><td>R25E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td colspan="2">1990</td></tr> </table>	T29N		R24E	R25E	1/4		S24	S19	1990			
T29N													
R24E	R25E												
1/4													
S24	S19												
1990													
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>												
66.50	<p>Graded road, 45 lks. wide, bears E and W.</p>												
80.00	<p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T29N</td></tr> <tr><td>R24E</td><td>R25E</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td colspan="2">1990</td></tr> </table>	T29N		R24E	R25E	S13	S18	<hr/>		S24	S19	1990	
T29N													
R24E	R25E												
S13	S18												
<hr/>													
S24	S19												
1990													

Survey of the West Boundary,
Identical With the Sixth Guide Meridian East,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/>
	<p>North, bet. secs. 13 and 18.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29N R24E R25E 1/4 S13 S18 1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 7, 12, 13, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29N R24E R25E S12 S 7 ----- S13 S18 1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/>

Survey of the West Boundary,
 Identical With the Sixth Guide Meridian East,
 T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>North, bet. secs. 7 and 12.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T29N R24E R25E 1/4 S12 S 7 1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
68.75	<p>Trail road, bears SE and NW.</p>
80.00	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T29N R24E R25E S 1 S 6 ----- S12 S 7 1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/>
9.20	<p>North, bet. secs. 1 and 6.</p> <p>Over gently rolling land.</p> <p>Trail road, bears ENE and WSW.</p>

Survey of the West Boundary,
Identical With the Sixth Guide Meridian East,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
11.75	Trail road, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 6. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>T29N R24E R25E 1/4 S 1 S 6 1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
44.85	Trail road, bears SE and NW.
80.00	Point for the cor. of Tps. 29 and 30 N., Rs. 24 and 25 E. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>T30N R24E R25E S36 S31 ----- S 1 S 6 T29N 1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, Electronic Control Point 9, monumented with an aluminum post, 36 ins. long, 5/8 in. diam., set flush with the surface of the ground, with magnetized aluminum cap mkd. EC-9 1990, bears N. 81°01' E., 261.64 chs. dist. This control point has latitude of 35°57'42.84" N. and longitude of 109°38'59.08" W. (NAD27), as determined by the technique of relative positioning utilizing the Motorola Golden Eagle Global Positioning System Satellite Surveyor. "BEAUTIFUL" and "GANADO", first order triangulation stations established by the U.S. Coast and Geodetic Survey, were used as the control stations.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/>

Survey of the East Boundary,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the stan. cor. of T. 29 N., Rs. 25 and 26 E., on the Seventh Standard Parallel North, hereinbefore described.</p>
	<p>North, bet. secs. 31 and 36.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T29N R25E R26E 1/4 S36 S31 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
46.62	<p>W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.</p>
50.59	<p>Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears SSE and NNW.</p>
54.53	<p>E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.</p>
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T29N R25E R26E S25 S30 ----- S36 S31 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Land, rolling.</p>
	<p>Soil, sandy clay.</p>
	<p>No timber; sparse brush and native grasses.</p>

Survey of the East Boundary,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>North, bet. secs. 25 and 30.</p> <p>Over rolling land.</p>
10.40	<p>W. rim of Beautiful Valley, bears SSE and NNW, thence descend into the rolling and broken badlands.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29N R25E R26E 1/4 S25 S30 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located at bottom of descent.</p>
80.00	<p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29N R25E R26E S24 S19 ----- S25 S30 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy clay and clay. No timber; sparse brush and native grasses.</p> <hr/> <p>North, bet. secs. 19 and 24.</p> <p>Over rolling and broken land.</p>

Survey of the East Boundary,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29N R25E R26E 1/4 S24 S19 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on W. edge of a wash, 33 lks. wide, 1 ft. deep, drains NE.</p>
80.00	<p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29N R25E R26E S13 S18 ----- S24 S19 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy clay and clay. No timber; sparse brush and native grasses.</p>
37.60	<p>North, bet. secs. 13 and 18.</p> <p>Over rolling and broken land.</p> <p>Graded road, 45 lks. wide, bears ESE and WNW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the East Boundary,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T29N R25E R26E 1/4 S13 S18 1990
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Thence ascend from Beautiful Valley.
63.00	W. rim of Beautiful Valley, bears ENE and WSW. Enter rolling land.
72.00	Trail road, bears NE and SW.
80.00	Point for the cor. of secs. 7, 12, 13, and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T29N R25E R26E S12 S 7 <hr style="width: 50%; margin: 0 auto;"/> S13 S18 1990
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Land, rolling and broken. Soil, sandy clay and clay. No timber; sparse brush and native grasses.
	<hr/> North, bet. secs. 7 and 12.
	Over rolling land.
29.72	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
33.00	Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears NNE and SSW.
36.30	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.

Survey of the East Boundary,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
37.90	Power line, bears NNE and SSW.												
40.00	Point for the 1/4 sec. cor. of secs. 7 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T29N</td></tr> <tr><td style="text-align: center;">R25E</td><td style="text-align: center;">R26E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.	T29N		R25E	R26E	1/4		S12	S 7	1990			
T29N													
R25E	R26E												
1/4													
S12	S 7												
1990													
80.00	Point for the cor. of secs. 1, 6, 7, and 12. Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, in sandstone bedrock, with top mkd. <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T29N</td></tr> <tr><td style="text-align: center;">R25E</td><td style="text-align: center;">R26E</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the brass tablet. Land, rolling. Soil, sandy clay with some exposed bedrock. No timber; sparse brush and native grasses.	T29N		R25E	R26E	S 1	S 6	-----		S12	S 7	1990	
T29N													
R25E	R26E												
S 1	S 6												

S12	S 7												
1990													
	<hr/> <p>North, bet. secs. 1 and 6. Over rolling land.</p>												
40.00	Point for the 1/4 sec. cor. of secs. 1 and 6. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.												

Survey of the East Boundary,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p style="text-align: center;">T29N R25E R26E 1/4 S 1 S 6 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of Tps. 29 and 30 N., Rs. 25 and 26 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E R26E S36 S31 ----- S 1 S 6 T29N 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p> <hr/> <p style="text-align: center;">Survey of the North Boundary, T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 29 and 30 N., Rs. 25 and 26 E., hereinbefore described.</p> <p>N. 89°59' W., bet. secs. 1 and 36.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>

Survey of the North Boundary,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T30N R25E S36 1/4 — S 1 T29N 1990</p>
74.50	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Trail road, bears NNE and SSW.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 35, and 36.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R25E S35 S36 — — S 2 S 1 T29N 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/>
	<p>N. 89°59' W., bet. secs. 2 and 35.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R25E S35 1/4 — S 2 T29N 1990</p>

Survey of the North Boundary,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>												
62.05	Trail road, bears SSE and NNW.												
66.85	Trail road, bears SE and NW.												
80.00	<p>Point for the cor. of secs. 2, 3, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 2px 5px;">T30N</td> <td style="padding: 2px 5px;">R25E</td> </tr> <tr> <td style="padding: 2px 5px;">S34</td> <td style="padding: 2px 5px;">S35</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 2px 5px;">S 3</td> <td style="border-top: 1px solid black; padding: 2px 5px;">S 2</td> </tr> <tr> <td style="padding: 2px 5px;">T29N</td> <td style="padding: 2px 5px;">1990</td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">An X chiseled on top of the SW cor. of a concrete culvert outlet, bears S. 66 1/4° E., 34 lks. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in a stock pond enclosure, 48 ft. N. of the S. embankment, bears E. and W.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr style="border: 0.5px solid black;"/> <p>N. 89°59' W., bet. secs. 3 and 34.</p> <p>Over rolling land.</p>	T30N	R25E	S34	S35	S 3	S 2	T29N	1990				
T30N	R25E												
S34	S35												
S 3	S 2												
T29N	1990												
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 2px 5px;">T30N</td> <td style="padding: 2px 5px;">R25E</td> </tr> <tr> <td style="padding: 2px 5px;">S34</td> <td style="padding: 2px 5px;">—</td> </tr> <tr> <td style="padding: 2px 5px;">1/4</td> <td style="padding: 2px 5px;">—</td> </tr> <tr> <td style="padding: 2px 5px;">S 3</td> <td style="padding: 2px 5px;">—</td> </tr> <tr> <td style="padding: 2px 5px;">T29N</td> <td style="padding: 2px 5px;">—</td> </tr> <tr> <td style="padding: 2px 5px;">1990</td> <td style="padding: 2px 5px;">—</td> </tr> </table> </div>	T30N	R25E	S34	—	1/4	—	S 3	—	T29N	—	1990	—
T30N	R25E												
S34	—												
1/4	—												
S 3	—												
T29N	—												
1990	—												

Survey of the North Boundary,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
78.60	Trail road, bears NE and SW.
80.00	Point for the cor. of secs. 3, 4, 33, and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <p>T30N R25E S33 S34 ----- S 4 S 3 T29N 1990</p> </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	<p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p>
	N. 89°59' W., bet. secs. 4 and 33.
	Over rolling land.
22.20	Trail road, bears SSE and NNW.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <p>T30N R25E S33 1/4 — S 4 T29N 1990</p> </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 4, 5, 32, and 33.

Survey of the North Boundary,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS															
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T30N</td><td>R25E</td></tr> <tr><td>S32</td><td>S33</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td colspan="2" style="text-align: center;">T29N</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/>	T30N	R25E	S32	S33			S 5	S 4			T29N		1990	
T30N	R25E														
S32	S33														
S 5	S 4														
T29N															
1990															
	<p>N. 89°59' W., bet. secs. 5 and 32.</p>														
	<p>Over rolling land.</p>														
<p>40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p>														
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T30N</td><td>R25E</td></tr> <tr><td colspan="2" style="text-align: center;">S32</td></tr> <tr><td colspan="2" style="text-align: center;">1/4 —</td></tr> <tr><td colspan="2" style="text-align: center;">S 5</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td colspan="2" style="text-align: center;">T29N</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T30N	R25E	S32		1/4 —		S 5				T29N		1990	
T30N	R25E														
S32															
1/4 —															
S 5															
T29N															
1990															
<p>40.30</p>	<p>Trail road, bears SSE and NNW.</p>														
<p>55.35</p>	<p>Trail road, bears NE and SW.</p>														
<p>73.45</p>	<p>Trail road, bears ESE and WNW.</p>														
<p>80.00</p>	<p>Point for the cor. of secs. 5, 6, 31, and 32.</p>														
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>														

Survey of the North Boundary,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<div style="text-align: center;"> <p>T30N R25E S31 S32 ----- S 6 S 5 T29N 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/>
	<p>N. 89°59' W., bet. secs. 6 and 31.</p> <p>Over rolling land.</p>
21.90	A circular log hogan, 15 ft. diam., bears South, 3.00 chs. dist.
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T30N R25E S31 1/4 — S 6 T29N 1990</p> </div>
79.47	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of Tps. 29 and 30 N., Rs. 24 and 25 E., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/>

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the stan. cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°01' W., bet. secs. 35 and 36.
	Over rolling land.
4.80	Trail road, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 35 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.
	<p style="text-align: center;">T29N R25E 1/4 S35 S36 1990</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
74.65	Trail road, bears ESE and WNW.
74.78	Barbed wire fence, 5 strand, bears ESE and WNW.
80.00	Point for the cor. of secs. 25, 26, 35, and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T29N R25E S26 S25 ----- S35 S36 1990</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	<p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p>

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp. hereinbefore described.
	West, bet. secs. 25 and 36.
	Over rolling land.
10.34	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
12.00	Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears SSE and NNW.
13.69	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
15.70	Power line, bears SSE and NNW.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T29N R25E S25 1/4 — S36 1990</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.00	The cor. of secs. 25, 26, 35, and 36.
	Land, rolling.
	Soil, sandy clay.
	No timber; sparse brush and native grasses.
	<hr/> N. 0°01' W., bet. secs. 25 and 26.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T29N R25E 1/4 S26 S25 1990
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
63.80	Trail road, bears ESE and WNW.
80.00	Point for the cor. of secs. 23, 24, 25, and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T29N R25E S23 S24 <hr style="width: 100%;"/> S26 S25 1990
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.
	From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.
	N. 89°59' W., bet. secs. 24 and 25.
	Over rolling and broken land, on ascent from valley.
28.10	W. rim of Beautiful Valley, bears NE and SW, thence over rolling land.
34.15	Trail road, bears SSE and NNW.
34.99	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
36.57	Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears SSE and NNW.
38.17	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
40.005	Point for the 1/4 sec. cor. of secs. 24 and 25. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T29N R25E S24 1/4 — S25 1990 </div> from which <div style="text-align: center;"> A wood power pole, bears S. 10 3/4° E., 185 1/2 lks. dist., mkd. CC355, lines extending SSE and NNW </div> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.01	The cor. of secs. 23, 24, 25, and 26. Land, rolling and broken. Soil, sandy clay and clay. No timber; sparse brush and native grasses. <hr/> N. 0°01' W., bet. secs. 23 and 24. Over rolling land.
20.75	Trail road, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T29N R25E 1/4 S23 S24 1990 </div>

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>										
55.00	Trail road, bears SE and NW.										
55.70	Trail road, bears NE and SW.										
80.00	<p>Point for the cor. of secs. 13, 14, 23, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 10px;">T29N</td> <td style="padding: 2px 10px;">R25E</td> </tr> <tr> <td style="padding: 2px 10px;">S14</td> <td style="padding: 2px 10px;">S13</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 2px 10px;">S23</td> <td style="border-top: 1px solid black; padding: 2px 10px;">S24</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 10px;">1990</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°59' W., bet. secs. 13 and 24.</p> <p>Over rolling and broken land on ascent from valley.</p>	T29N	R25E	S14	S13	S23	S24	1990			
T29N	R25E										
S14	S13										
S23	S24										
1990											
32.00	W. rim of Beautiful Valley, bears ESE and WNW, thence over rolling land.										
40.01	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 10px;">T29N</td> <td style="padding: 2px 10px;">R25E</td> </tr> <tr> <td colspan="2" style="padding: 2px 10px;">S13</td> </tr> <tr> <td style="padding: 2px 10px;">1/4</td> <td style="padding: 2px 10px;">—</td> </tr> <tr> <td colspan="2" style="padding: 2px 10px;">S24</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 10px;">1990</td> </tr> </table> </div>	T29N	R25E	S13		1/4	—	S24		1990	
T29N	R25E										
S13											
1/4	—										
S24											
1990											

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
44.85	Trail road, bears N. and S.
45.85	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
47.36	Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears N. and S.
48.90	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
49.50	Power line, bears N. and S.
80.02	<p>The cor. of secs. 13, 14, 23, and 24.</p> <p>Land, rolling and broken. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over rolling land.</p>
15.65	Trail road, bears NE and SW.
33.00	Graded road, 30 lks. wide, bears ENE and WSW.
38.45	Trail road, bears ESE and WNW.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T29N R25E 1/4 S14 S13 1990</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
44.70	The SE cor. of a log house, 20 x 20 ft., bears West, 21.15 chs. dist., sides bear N and W.										
46.30	The SE cor. of a stucco house, 35 x 15 ft., bears West, 21.00 chs. dist., long side bears N.										
47.70	Center of a wood frame hogan, 15 ft. diam., bears West, 20.50 chs. dist.										
48.90	Trail road, bears ENE and WSW, and the SW cor. of a stucco house, 15 x 15 ft., bears East, 6.90 chs. dist., sides bear N. and E.										
75.70	Trail road, bears SSE and NNW.										
80.00	Point for the cor. of secs. 11, 12, 13, and 14.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table border="1"> <tr> <td colspan="2">T29N R25E</td> </tr> <tr> <td>S11</td> <td>S12</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S14</td> <td>S13</td> </tr> <tr> <td colspan="2">1990</td> </tr> </table>	T29N R25E		S11	S12	<hr/>		S14	S13	1990	
T29N R25E											
S11	S12										
<hr/>											
S14	S13										
1990											
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.										
	Cor. is located 260 lks. E. of a trail road, bears SSE and NNW.										
	Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.										
	From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.										
	N. 89°59' W., bet. secs. 12 and 13.										
	Over rolling land.										
15.67	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.										

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
17.37	Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears NNE and SSW.
19.10	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strand, parallels highway.
19.90	Power line, bears NNE and SSW.
40.01	Point for the 1/4 sec. cor. of secs. 12 and 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T29N R25E S12 1/4 — S13 1990
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
56.20	Trail road, bears SSE and NNW.
80.02	The cor. of secs. 11, 12, 13, and 14.
	Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.
	N. 0°01' W., bet. secs. 11 and 12.
	Over rolling land.
12.65	Trail road, bears NNE and SSW.
31.40	Trail road, bears ESE and WNW.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T29N R25E 1/4 S11 S12 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
72.90	<p>Trail road, bears SSE and NNW.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11, and 12.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T29N R25E S 2 S 1 ----- S11 S12 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located 50 lks. E. of trail road, bears NE and SW, and 130 lks. E. of a trail road, bears N. and S.</p>
	<p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p>
	<p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>N. 89°58' W., bet. secs. 1 and 12.</p>
	<p>Over rolling land.</p>
40.005	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T29N R25E S 1 1/4 — S12 1990</p>

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
54.05	Trail road, bears NNE and SSW.
80.01	The cor. of secs. 1, 2, 11, and 12.
	Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.
	North, bet. secs. 1 and 2.
	Over nearly level land.
24.40	Trail road, bears ENE and WSW.
27.50	Trail road, bears ESE and WNW.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T29N R25E 1/4 S 2 S 1 1990</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
50.10	Trail road, bears NNE and SSW.
79.96	The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.
	Land, nearly level. Soil, sandy clay. No timber; sparse brush and native grasses.
	From the stan. cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described.

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over rolling land.</p>
10.10	Trail road, bears ENE and WSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29N R25E 1/4 S34 S35 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 26, 27, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29N R25E S27 S26 ----- S34 S35 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>West, bet. secs. 26 and 35.</p> <p>Over rolling land.</p>
19.71	Barbed wire fence, 5 strand, bears ESE and WNW.
20.25	Trail road, bears ESE and WNW.

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.005	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R25E S26 1/4 — S35 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the 9 Mile Cor. on the 1868 west boundary of the Navajo Indian Reservation, bears N. 80°26' E., 9.30 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. NIR 9M 1920. As it is impracticable to bury the iron post, remove brass cap and mark AM on north side of iron post.</p>
80.01	<p>The cor. of secs. 26, 27, 34, and 35.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over rolling land.</p>
15.85	Trail road, bears ESE and WNW.
16.03	Barbed wire fence, 5 strand, bears ESE and WNW.
16.25	Trail road, bears ESE and WNW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R25E 1/4 S27 S26 1990</p>

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>										
80.00	<p>Point for the cor. of secs. 22, 23, 26, and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 2px 5px;">T29N</td> <td style="padding: 2px 5px;">R25E</td> </tr> <tr> <td style="padding: 2px 5px;">S22</td> <td style="padding: 2px 5px;">S23</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 2px 5px;">S27</td> <td style="border-top: 1px solid black; padding: 2px 5px;">S26</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">1990</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>West, bet. secs. 23 and 26.</p> <p>Over rolling land.</p>	T29N	R25E	S22	S23	S27	S26	1990			
T29N	R25E										
S22	S23										
S27	S26										
1990											
17.65	<p>Trail road, bears SSE and NNW.</p>										
21.42	<p>The SW cor. of a wood frame house, 31 x 26 ft., bears North, 1.77 chs. dist., long side bears NNE.</p>										
40.01	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 2px 5px;">T29N</td> <td style="padding: 2px 5px;">R25E</td> </tr> <tr> <td></td> <td style="padding: 2px 5px;">S23</td> </tr> <tr> <td style="padding: 2px 5px;">1/4</td> <td style="padding: 2px 5px;">—</td> </tr> <tr> <td></td> <td style="padding: 2px 5px;">S26</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">1990</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T29N	R25E		S23	1/4	—		S26	1990	
T29N	R25E										
	S23										
1/4	—										
	S26										
1990											

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, the 10 Mile Cor. on the 1868 west boundary of the Navajo Indian Reservation, bears N. 73°52' E., 9.44 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. NIR 10M 1920. As it is impracticable to bury the iron post, remove brass cap and mark AM on north side of iron post.</p>
40.70	<p>Trail road, bears ESE and WNW.</p>
40.75	<p>The SE cor. of a wood frame house, 24 x 12 ft., bears North, 23.40 chs. dist., long side bears N.</p>
44.35	<p>The center of a hexagonal wood frame hogan, bears North, 25.90 chs. dist.</p>
45.34	<p>The SW cor. of a wood frame house, 36 x 18 ft., bears North, 23.98 chs. dist., long side bears N.</p>
60.25	<p>Trail road, bears NNE and SSW.</p>
80.02	<p>The cor. of secs. 22, 23, 26, and 27.</p>
	<p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p>
	<hr/> <p>N. 0°01' W., bet. secs. 22 and 23.</p>
	<p>Over rolling land.</p>
6.00	<p>Trail road, bears E. and W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T29N R25E 1/4 S22 S23 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22, and 23.</p>

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T29N</td><td>R25E</td></tr> <tr><td>S15</td><td>S14</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S22</td><td>S23</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 14, 23, and 24. S. 89°59' W., bet. secs. 14 and 23. Over rolling land.</p>	T29N	R25E	S15	S14			S22	S23	1990	
T29N	R25E										
S15	S14										
S22	S23										
1990											
27.70	Trail road, bears NNE and SSW.										
39.45	Trail road, bears ESE and WNW.										
40.005	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T29N</td><td>R25E</td></tr> <tr><td></td><td>S14</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S23</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the 11 Mile Cor. on the 1868 west boundary of the Navajo Indian Reservation, bears N. 67°27' E., 9.70 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. NIR 11M 1920. As it is impracticable to bury the iron post, remove brass cap and mark AM on north side of iron post.</p>	T29N	R25E		S14	1/4	—		S23	1990	
T29N	R25E										
	S14										
1/4	—										
	S23										
1990											

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
44.20	Trail road, bears NNE and SSW.
80.01	<p>The cor. of secs. 14, 15, 22, and 23.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over rolling land.</p>
14.90	Graded road, 36 lks. wide, bears ENE and WSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T29N R25E 1/4 S15 S14 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14, and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T29N R25E S10 S11 ----- S15 S14 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/>

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the cor. of secs. 11, 12, 13, and 14.
	S. 89°59' W., bet. secs. 11 and 14.
	Over rolling land.
5.50	Trail road, bears NNE and SSW.
29.65	Trail road, bears NNE and SSW.
40.005	Point for the 1/4 sec. cor. of secs. 11 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T29N R25E
	S11
	1/4 —
	S14
	1990
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
59.50	Trail road, bears ESE and WNW.
80.01	The cor. of secs. 10, 11, 14, and 15.
	Land, rolling.
	Soil, sandy clay.
	No timber; sparse brush and native grasses.
	N. 0°01' W., bet. secs. 10 and 11.
	Over rolling land.
12.55	Trail road, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T29N R25E
	1/4
	S10 S11
	1990

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>										
80.00	<p>Point for the cor. of secs. 2, 3, 10, and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T29N</td> <td style="padding: 0 5px;">R25E</td> </tr> <tr> <td style="padding: 0 5px;">S 3</td> <td style="padding: 0 5px;">S 2</td> </tr> <tr> <td style="border-right: 1px solid black; border-bottom: 1px solid black; padding: 0 5px;">S10</td> <td style="border-bottom: 1px solid black; padding: 0 5px;">S11</td> </tr> <tr> <td style="padding: 0 5px;">1990</td> <td></td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>S. 89°58' W., bet. secs. 2 and 11.</p> <p>Over rolling land.</p>	T29N	R25E	S 3	S 2	S10	S11	1990			
T29N	R25E										
S 3	S 2										
S10	S11										
1990											
9.00	<p>Trail road, bears NNE and SSW.</p>										
40.01	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T29N</td> <td style="padding: 0 5px;">R25E</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 2</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="padding: 0 5px;">—</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S11</td> </tr> <tr> <td style="padding: 0 5px;">1990</td> <td></td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T29N	R25E		S 2	1/4	—		S11	1990	
T29N	R25E										
	S 2										
1/4	—										
	S11										
1990											

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, the 13 Mile Cor. on the 1868 west boundary of the Navajo Indian Reservation, bears N. 56°17' E., 10.47 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. NIR 13M 1920. As it is impracticable to bury the iron post, remove brass cap and mark AM on north side of iron post.</p>
47.65	Trail road, bears SE and NW.
75.05	Trail road, bears SE and NW.
80.02	The cor. of secs. 2, 3, 10, and 11.
	<p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/>
	North, bet. secs. 2 and 3.
	Over nearly level land.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T29N R25E 1/4 S 3 S 2 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.02	The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., hereinbefore described.
	<p>Land, nearly level. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/>

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the stan. cor. of secs. 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p>
	<p>N. 0°02' W., bet. secs. 33 and 34.</p>
	<p>Over rolling land.</p>
19.10	<p>Trail road, bears ENE and WSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T29N R25E 1/4 S33 S34 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 27, 28, 33, and 34.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T29N R25E S28 S27 ----- S33 S34 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p>
	<hr/> <p>From the cor. of secs. 26, 27, 34, and 35.</p>
	<p>N. 89°59' W., bet. secs. 27 and 34.</p>
	<p>Over rolling land.</p>

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.995	<p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R25E S27 1/4 — S34 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
41.95	Trail road, bears NE and SW.
51.15	Trail road, bears SSE and NNW.
51.90	The center shaft of a windmill, bears South, 9.70 chs. dist.
79.99	<p>The cor. of secs. 27, 28, 33, and 34.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over rolling land.</p>
28.70	Trail road, bears ENE and WSW.
35.05	Trail road, bears SE and NW.
37.23	Barbed wire fence, 5 strand, bears ESE and WNW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R25E 1/4 S28 S27 1990</p>

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>										
63.05	<p>Trail road, bears NE and SW.</p>										
80.00	<p>Point for the cor. of secs. 21, 22, 27, and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 2px 5px;">T29N</td> <td style="padding: 2px 5px;">R25E</td> </tr> <tr> <td style="padding: 2px 5px;">S21</td> <td style="padding: 2px 5px;">S22</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 2px 5px;">S28</td> <td style="border-top: 1px solid black; padding: 2px 5px;">S27</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">1990</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 22, 23, 26, and 27. N. 89°59' W., bet. secs. 22 and 27. Over rolling land.</p>	T29N	R25E	S21	S22	S28	S27	1990			
T29N	R25E										
S21	S22										
S28	S27										
1990											
39.99	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 2px 5px;">T29N</td> <td style="padding: 2px 5px;">R25E</td> </tr> <tr> <td style="padding: 2px 5px;"></td> <td style="padding: 2px 5px;">S22</td> </tr> <tr> <td style="padding: 2px 5px;">1/4</td> <td style="padding: 2px 5px;">—</td> </tr> <tr> <td style="padding: 2px 5px;"></td> <td style="padding: 2px 5px;">S27</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">1990</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T29N	R25E		S22	1/4	—		S27	1990	
T29N	R25E										
	S22										
1/4	—										
	S27										
1990											
72.25	<p>The center shaft of a windmill, bears North, 9.80 chs. dist.</p>										

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>79.98 The cor. of secs. 21, 22, 27, and 28.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. below the surface of the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T29N R25E 1/4 S21 S22 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in a trail road, bears SSE and NNW.</p>
58.00	<p>Trail road, bears NNE and SSW.</p>
76.90	<p>Graded road, 38 lks. wide, bears ENE and WSW.</p>
80.00	<p>Point for the cor. of secs. 15, 16, 21, and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T29N R25E S16 S15 ----- S21 S22 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/>

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>N. 89°58' W., bet. secs. 15 and 22.</p> <p>Over rolling land.</p>
<p>39.99</p>	<p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R25E S15 1/4 — S22 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
<p>66.00</p>	<p>Graded road, 38 lks. wide, bears ENE and WSW.</p>
<p>79.98</p>	<p>The cor. of secs. 15, 16, 21, and 22.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/>
<p>40.00</p>	<p>N. 0°02' W., bet secs. 15 and 16.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R25E 1/4 S16 S15 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
70.85	Trail road, bears ENE and WSW.										
80.00	Point for the cor. of secs. 9, 10, 15, and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <table style="margin-left: auto; margin-right: auto;"> <tr><td>T29N</td><td>R25E</td></tr> <tr><td>S 9</td><td>S10</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S16</td><td>S15</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses. <hr/>	T29N	R25E	S 9	S10			S16	S15	1990	
T29N	R25E										
S 9	S10										
S16	S15										
1990											
	From the cor. of secs. 10, 11, 14, and 15. N. 89°58' W., bet. secs. 10 and 15. Over rolling land.										
39.99	Point for the 1/4 sec. cor. of secs. 10 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <table style="margin-left: auto; margin-right: auto;"> <tr><td>T29N</td><td>R25E</td></tr> <tr><td></td><td>S10</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S15</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.	T29N	R25E		S10	1/4	—		S15	1990	
T29N	R25E										
	S10										
1/4	—										
	S15										
1990											
70.05	Trail road, bears ENE and WSW.										
73.50	Trail road, bears NNE and SSW.										
79.98	The cor. of secs. 9, 10, 15, and 16.										

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/>
	<p>N. 0°02' W., bet. secs. 9 and 10.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R25E 1/4 S 9 S10 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
66.75	<p>Trail road, bears E. and W.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 9, and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R25E S 4 S 3 ----- S 9 S10 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 2, 3, 10, and 11.</p>
	<p>N. 89°57' W., bet. secs. 3 and 10.</p>

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
21.30	Trail road, bears NNE and SSW.
39.995	Point for the 1/4 sec. cor. of secs. 3 and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T29N R25E S 3 1/4 — S10 1990</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
40.50	Bi-Keesh Wash, 75 lks. wide, 10 ft. deep, drains NNE.
79.99	The cor. of secs. 3, 4, 9, and 10.
	Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.
	<hr/> N. 0°01' W., bet. secs. 3 and 4.
	Over rolling land.
29.70	Trail road, bears ENE and WSW.
32.55	Trail road, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T29N R25E 1/4 S 4 S 3 1990</p>

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
56.95	Trail road, bears ENE and WSW.
77.90	Trail road, bears NE and SW.
79.98	The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described.
	Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.
	From the stan. cor. of secs. 32 and 33, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°03' W., bet. secs. 32 and 33.
	Over rolling land.
14.50	Trail road, bears NNE and SSW.
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T29N R25E 1/4 S32 S33 1990
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
47.25	Trail road, bears NE and SW.
80.00	Point for the cor. of secs. 28, 29, 32, and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T29N R25E S29 S28 S32 S33 1990

Survey of the Subdivisional Lines,
T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.
	<hr/> From the cor. of secs. 27, 28, 33, and 34.
	S. 89°59' W., bet. secs. 28 and 33.
	Over rolling land.
27.05	Trail road, bears NE and SW.
39.99	Point for the 1/4 sec. cor. of secs. 28 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T29N R25E S28 1/4 — S33 1990</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
50.30	Trail road, bears NNE and SSW.
51.95	Trail road, bears NNE and SSW.
58.95	Trail road, bears N. and S.
79.98	The cor. of secs. 28, 29, 32, and 33.
	Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.
	<hr/> N. 0°03' W., bet. secs. 28 and 29.
	Over rolling land.

CHAINS	Survey of the Subdivisional Lines, T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona
34.00	The SE cor. of a wood frame house, 37 x 25 ft., bears West, 19.20 chs. dist., long side bears W.
37.15	Trail road, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T29N R25E 1/4 S29 S28 1990
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
53.55	Trail road, bears ENE and WSW.
59.28	Barbed wire fence, 5 strands, bears ESE and WNW.
59.50	Trail road, bears ESE and WNW.
80.00	Point for the cor. of secs. 20, 21, 28, and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T29N R25E S20 S21 ----- S29 S28 1990
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.
	<hr/> From the cor. of secs. 21, 22, 27, and 28.
	S. 89°59' W., bet. secs. 21 and 28.
	Over rolling land.

CHAINS	Survey of the Subdivisional Lines, T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona
39.99	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R25E S21 1/4 — S28 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
60.75	<p>Trail road, bears NNE and SSW.</p>
79.98	<p>The cor. of secs. 20, 21, 28, and 29.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p>
	<hr/> <p>N. 0°03' W., bet. secs. 20 and 21.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R25E 1/4 S20 S21 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
62.50	<p>Graded road, 30 lks. wide, bears E. and W.</p>
80.00	<p>Point for the cor. of secs. 16, 17, 20, and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

CHAINS																			
	<p style="text-align: center;">Survey of the Subdivisional Lines, T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T29N</td> <td>R25E</td> </tr> <tr> <td>S17</td> <td>S16</td> </tr> <tr> <td>S20</td> <td>S21</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/> <p>From the cor. of secs. 15, 16, 21, and 22. S. 89°59' W., bet. secs. 16 and 21. Over rolling land.</p> <p>22.00 The NW cor. of a wood frame house, 40 x 30 ft., bears South, 14.30 chs. dist., long side bears S.</p> <p>23.00 Trail road, bears SSE and NNW.</p> <p>39.99 Point for the 1/4 sec. cor. of secs. 16 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T29N</td> <td>R25E</td> </tr> <tr> <td></td> <td>S16</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S21</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>79.98 The cor. of secs. 16, 17, 20, and 21. Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/>	T29N	R25E	S17	S16	S20	S21	1991		T29N	R25E		S16	1/4	—		S21	1991	
T29N	R25E																		
S17	S16																		
S20	S21																		
1991																			
T29N	R25E																		
	S16																		
1/4	—																		
	S21																		
1991																			

CHAINS	
	<p style="text-align: center;">Survey of the Subdivisional Lines, T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R25E 1/4 S17 S16 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 8, 9, 16, and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R25E S 8 S 9 ----- S17 S16 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/> <p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>S. 89°59' W., bet. secs. 9 and 16.</p> <p>Over rolling land.</p>
23.70	<p>Trail road, bears NNE and SSW.</p>
25.30	<p>The NW cor. of a wood framed house, 36 x 24 ft., bears South, 24.30 chs. dist., long side bears SSW.</p>

CHAINS	
	Survey of the Subdivisional Lines, T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona
28.55	Trail road, bears SSE and NNW.
39.995	Point for the 1/4 sec. cor. of secs. 9 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T29N R25E S 9 1/4 — S16 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
79.99	The cor. of secs. 8, 9, 16, and 17.
	Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.
	N. 0°03' W., bet. secs. 8 and 9.
	Over rolling land.
22.45	Trail road, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T29N R25E 1/4 S 8 S 9 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
46.60	Trail road, bears ESE and WNW.
52.07	The SW cor. of a wood frame house, 32 x 24 ft., bears East, 11 lks. dist., long side bears NNE.

CHAINS											
	<p style="text-align: center;">Survey of the Subdivisional Lines, T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona</p>										
<p>80.00</p>	<p>Point for the cor. of secs. 4, 5, 8, and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T29N</td> <td>R25E</td> </tr> <tr> <td>S 5</td> <td>S 4</td> </tr> <tr> <td>S 8</td> <td>S 9</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 9, and 10. S. 89°59' W., bet. secs. 4 and 9. Over rolling land.</p>	T29N	R25E	S 5	S 4	S 8	S 9	1991			
T29N	R25E										
S 5	S 4										
S 8	S 9										
1991											
<p>28.45</p>	<p>Trail road, bears ESE and WNW.</p>										
<p>38.05</p>	<p>Trail road, bears NE and SW.</p>										
<p>39.995</p>	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T29N</td> <td>R25E</td> </tr> <tr> <td>S 4</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 9</td> <td></td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T29N	R25E	S 4		1/4	—	S 9		1991	
T29N	R25E										
S 4											
1/4	—										
S 9											
1991											
<p>48.60</p>	<p>Trail road, bears NNE and SSW.</p>										

CHAINS	Survey of the Subdivisional Lines, T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona
53.70	The SW cor. of a wood frame house, 16 x 12 ft., bears North, 8.75 chs. dist., long side bears NNE.
57.85	Trail road, bears SE and NW.
79.99	The cor. of secs. 4, 5, 8, and 9. Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.
<hr/>	
	N. 0°02' W., bet. secs. 4 and 5. Over rolling land.
16.20	Trail road, bears SSE and NNW.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T29N R25E 1/4 S 5 S 4 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
46.55	Trail road, bears E. and W.
80.03	The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described. Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.
<hr/>	
	From the stan. cor. of secs. 31 and 32, on the S. bdy. of the Tp., hereinbefore described.

<p>CHAINS</p>	<p style="text-align: center;">Survey of the Subdivisional Lines, T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R25E 1/4 S31 S32 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>51.50 Trail road, bears NE and SW.</p> <p>80.00 Point for the cor. of secs. 29, 30, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R25E S30 S29 ----- S31 S32 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/> <p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>West, bet. secs. 29 and 32.</p> <p>Over rolling land.</p> <p>40.005 Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
---------------	--

CHAINS	
	<p style="text-align: center;">Survey of the Subdivisional Lines, T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona</p>
	<p style="text-align: center;">T29N R25E S29 1/4 — S32 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
65.15	Trail road, bears NE and SW.
75.90	Trail road, bears SE and NW.
80.01	The cor. of secs. 29, 30, 31, and 32.
	<p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/>
	<p>West, bet. secs. 30 and 31.</p>
	<p>Over rolling land.</p>
34.00	Trail road, bears NNE and SSW.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T29N R25E S30 1/4 — S31 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
41.75	The NE cor. of a wood frame house, 24 x 12 ft., bears South, 6.25 chs. dist., long side bears SSW.
42.10	Trail road, bears NNE and SSW.
48.95	The center of a hexagonal wood hogan, 16 ft. diam., bears South, 7.10 chs. dist.

CHAINS	
	Survey of the Subdivisional Lines, T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona
50.85	The NE cor. of a wood frame house, 37 x 15 ft., bears South, 11.40 chs. dist., long side bears SSW.
55.39	The center of a hexagonal wood hogan, 20 ft. diam., bears South, 27 lks. dist.
79.91	The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., hereinbefore described.
	Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.
	<hr/> From the cor. of secs. 29, 30, 31, and 32.
	N. 0°03' W., bet. secs. 29 and 30.
	Over rolling land.
4.70	Trail road, bears SE and NW.
33.10	Trail road, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T29N R25E 1/4 S30 S29 1990
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 65 lks. S. of a trail road, bears NNE and SSW.
80.00	Point for the cor. of secs. 19, 20, 29, and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS	Survey of the Subdivisional Lines, T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T29N</td><td>R25E</td></tr> <tr><td>S19</td><td>S20</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S30</td><td>S29</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table>	T29N	R25E	S19	S20			S30	S29	1990	
T29N	R25E										
S19	S20										
S30	S29										
1990											
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.										
	Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.										
	<hr/> From the cor. of secs. 20, 21, 28, and 29.										
	West, bet. secs. 20 and 29.										
	Over rolling land.										
40.00	Point for the 1/4 sec. cor. of secs. 20 and 29.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T29N</td><td>R25E</td></tr> <tr><td></td><td>S20</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S29</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table>	T29N	R25E		S20	1/4	—		S29	1990	
T29N	R25E										
	S20										
1/4	—										
	S29										
1990											
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.										
73.82	Barbed wire fence, 5 strand, bears ESE and WNW.										
75.45	Trail road, bears NNE and SSW.										
80.00	The cor. of secs. 19, 20, 29, and 30.										
	Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.										

CHAINS	
	<p style="text-align: center;">Survey of the Subdivisional Lines, T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona</p>
	<p>West, bet. secs. 19 and 30.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>T29N R25E S19 1/4 — S30 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
64.02	<p>Barbed wire fence, 5 strand, bears ENE and WSW.</p>
64.90	<p>Pine Springs Wash, 30 lks. wide, 20 ft. deep, drains NE.</p>
79.83	<p>The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., hereinbefore described.</p>
	<p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p>
	<hr/> <p>From the cor. of secs. 19, 20, 29, and 30.</p>
	<p>N. 0°03' W., bet. secs. 19 and 20.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>T29N R25E 1/4 S19 S20 1991</p>

CHAINS	<p style="text-align: center;">Survey of the Subdivisional Lines, T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>47.85 Trail road, bears NE and SW.</p> <p>64.60 Graded road, 33 lks. wide, bears E. and W.</p> <p>70.15 Trail road, bears NE and SW.</p> <p>80.00 Point for the cor. of secs. 17, 18, 19, and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T29N</td> <td style="padding: 0 5px;">R25E</td> </tr> <tr> <td style="padding: 0 5px;">S18</td> <td style="padding: 0 5px;">S17</td> </tr> <tr> <td style="border-right: 1px solid black; border-bottom: 1px solid black; padding: 0 5px;">S19</td> <td style="border-bottom: 1px solid black; padding: 0 5px;">S20</td> </tr> <tr> <td style="padding: 0 5px;">1991</td> <td></td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>West, bet. secs. 17 and 20.</p> <p>Over rolling land.</p> <p>38.90 Trail road, bears NNE and SSW.</p> <p>39.985 Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T29N</td> <td style="padding: 0 5px;">R25E</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S17</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="padding: 0 5px;">—</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S20</td> </tr> <tr> <td style="padding: 0 5px;">1991</td> <td></td> </tr> </table> </div>	T29N	R25E	S18	S17	S19	S20	1991		T29N	R25E		S17	1/4	—		S20	1991	
T29N	R25E																		
S18	S17																		
S19	S20																		
1991																			
T29N	R25E																		
	S17																		
1/4	—																		
	S20																		
1991																			

<p>CHAINS</p>	<p style="text-align: center;">Survey of the Subdivisional Lines, T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>43.60 The SW cor. of a wood frame house, 16 x 16 ft., bears North, 18.65 chs. dist., sides bear NNE and ESE.</p> <p>43.90 The SW cor. of a stucco house, 30 x 20 ft., bears North, 19.45 chs. dist., long side bears ESE.</p> <p>65.90 The SE cor. of a stucco house, 20 x 20 ft., bears North, 92 lks. dist., sides bear N. and W.</p> <p>79.97 The cor. of secs. 17, 18, 19, and 20.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/> <p>West, bet. secs. 18 and 19.</p> <p>Over rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R25E S18 1/4 — S19 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>79.76 The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/> <p>From the cor. of secs. 17, 18, 19, and 20.</p>
---------------	---

<p>CHAINS</p>	<p style="text-align: center;">Survey of the Subdivisional Lines, T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over rolling land.</p> <p>26.95 Trail road, bears SE and NW.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p style="padding-left: 40px;">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <table style="margin: auto;"> <tr><td colspan="2">T29N R25E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S18</td><td> </td><td>S17</td></tr> <tr><td colspan="3">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 7, 8, 17, and 18.</p> <p style="padding-left: 40px;">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <table style="margin: auto;"> <tr><td colspan="2">T29N R25E</td></tr> <tr><td>S 7</td><td> </td><td>S 8</td></tr> <tr><td colspan="3">-----</td></tr> <tr><td>S18</td><td> </td><td>S17</td></tr> <tr><td colspan="3">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/> <p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>West, bet. secs. 8 and 17.</p> <p>Over rolling land.</p> <p>15.25 Trail road, bears NNE and SSW.</p>	T29N R25E		1/4		S18		S17	1991			T29N R25E		S 7		S 8	-----			S18		S17	1991		
T29N R25E																									
1/4																									
S18		S17																							
1991																									
T29N R25E																									
S 7		S 8																							

S18		S17																							
1991																									

CHAINS	
	<p style="text-align: center;">Survey of the Subdivisional Lines, T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona</p>
39.97	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R25E S 8 1/4 — S17 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
79.94	<p>The cor. of secs. 7, 8, 17, and 18.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/> <p>N. 89°59' W., bet. secs. 7 and 18.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R25E S 7 1/4 — S18 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
43.75	<p>Trail road, bears SSE and NNW.</p>
79.70	<p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/>

CHAINS	
	<p style="text-align: center;">Survey of the Subdivisional Lines, T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0°03' W., bet. secs. 7 and 8.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29N R25E 1/4 S 7 S 8 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
77.75	<p>Trail road, bears ESE and WNW.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 7, and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29N R25E S 6 S 5 ----- S 7 S 8 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/> <p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>N. 89°59' W., bet. secs. 5 and 8.</p> <p>Over rolling land.</p>

CHAINS	
	<p style="text-align: center;">Survey of the Subdivisional Lines, T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona</p>
39.975	<p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R25E S 5 1/4 — S 8 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
47.20	Trail road, bears ENE and WSW.
79.95	<p>The cor. of secs. 5, 6, 7, and 8.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/> <p>N. 89°58' W., bet. secs. 6 and 7.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R25E S 6 1/4 — S 7 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
79.61	The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., hereinbefore described.

<p>CHAINS</p>	<p style="text-align: center;">Survey of the Subdivisional Lines, T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/> <p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0°05' W., bet. secs. 5 and 6.</p> <p>Over rolling land.</p> <p>27.40 Trail road, bears ENE and WSW.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R25E 1/4 S 6 S 5 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>70.70 Trail road, bears E. and W.</p> <p>80.04 The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/>
---------------	--

CHAINS

T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona

GENERAL DESCRIPTION

The area surveyed is within the Navajo Indian Reservation. The township is located about 10 miles north-northwest of Ganado, Arizona. The terrain is mostly low rolling hills with the elevation ranging from 5800 to 6300 feet above sea level. The soil is mostly sandy clay with some badlands in the eastern portion. There is no timber in the township; mostly sparse brush and native grasses. The drainage is to the north.

U.S. Highway 191 enters the township in section 36 and exits in section 12. A main graded road extends westward through the center of the township. There are numerous trail roads branching off of these main roads. Residents located throughout the township utilize the township for grazing livestock.

The geographic position of the northwest cor. of the Tp., as determined from a tie made to Electronic Control Point 9, hereinbefore described, is as follows:

Latitude: 35°57'16.20" N., Longitude: 109°42'26.50" W. NAD27

There is no evidence of any kind of mining activity. The mean magnetic declination is 12 1/2° E. throughout the township.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Daniel Bryan	Engineering Technician II
Wilfred Chee	Engineering Technician II
Nelson Kinsel	Engineering Technician II
Reuben Mason	Engineering Technician II
Andrew Murphy	Engineering Technician II
Barney Woodie	Engineering Technician II

CERTIFICATE OF SURVEY

We, Daniel N. Patterson and Leonard R. Sandoval, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 22nd day of November, 1989, we have surveyed the south boundary, identical with the Seventh Standard Parallel North, the west boundary, identical with the Sixth Guide Meridian East, the east and north boundaries and the subdivisional lines of Township 29 North, Range 25 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Daniel N. Patterson is no longer assigned to this office and is not available for signature.

February 24, 1992
(Date)

William F. Oliver
(Project Manager)

February 24, 1992
(Date)

Leonard R. Sandoval
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the survey of the south boundary, identical with the Seventh Standard Parallel North, the survey of the west boundary, identical with the Sixth Guide Meridian East, the survey of the east and north boundaries and the subdivisional lines of Township 29 North, Range 25 East, Gila and Salt River Meridian, Arizona, executed by Daniel N. Patterson and Leonard R. Sandoval, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

MAR 4 1992
(Date)

Jerry H. Talbot
(Chief Cadastral Surveyor of Arizona)

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 29 N., R. 25 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.

(Date)

(Chief Cadastral Surveyor of Arizona)