

ORIGINAL

1

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

R-5359

FIELD NOTES
OF THE

SURVEY OF

THE WEST BOUNDARY,

IDENTICAL WITH THE SIXTH GUIDE MERIDIAN EAST,

THE EAST AND NORTH BOUNDARIES,

AND

THE SUBDIVISIONAL LINES

OF

TOWNSHIP 30 NORTH, RANGE 25 EAST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

William F. Olver and Patrick S. Twohy, Cadastral Surveyors

Under special instructions dated November 22, 1989, approved November 22, 1989,
which provided for the surveys included under Group Number 715 and assignment
instructions dated December 18, 1989 and January 28, 1991.

Survey commenced January 16, 1990

Survey completed March 26, 1991

INDEX DIAGRAM

TOWNSHIP 30 NORTH, RANGE 25 EAST,

	22	21	20	19	18	17
9	6	71 5	58 4	50 3	41 2	32 1 15
	70	69	57	49	40	31
8	7	57 8	56 9	48 10	40 11	30 12 14
	68	67	56	47	39	29
7	18	66 17	55 16	47 15	38 14	28 13 13
	65	65	54	46	37	27
6	19	64 20	53 21	45 22	36 23	26 24 12
	63	62	53	44	36	25
5	30	61 29	52 28	43 27	35 26	24 25 11
	60	60	51	43	34	24
4	31	59 32	50 33	42 34	33 35	23 36 10
	15	14	13			

T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of the west boundary, identical with the Sixth Guide Meridian East, the east and north boundaries, and the subdivisional lines of Township 30 North, Range 25 East, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated November 22, 1989, for Group No. 715, Arizona.

This survey supersedes portions of Townships 3 and 4 North, Range 11 West of the Navajo Special Meridian. The West boundary of the 1868 Navajo Reservation is identified, where possible, for historical purposes, only, and has no legal significance in this survey. The survey history of that portion of the superseded Navajo Special Meridian is included in these notes for informational purposes only.

The west boundary of the Navajo Indian Reservation and the boundaries and subdivision of Townships 3 and 4 North, Range 11 West, Navajo Special Meridian, were surveyed by E.N. Darling in 1869. The west boundary of the Navajo Indian Reservation was dependently resurveyed by L.E. Sechrist in 1919-20.

The south boundary of the township was surveyed by Daniel N. Patterson and Leonard R. Sandoval in 1989-91, with plat and notes approved March 4, 1992.

The directions of all lines were determined by direct hour angle observations on the sun and refer to the true meridian. Distances and angles were measured using a Topcon GTS3B electronic total station instrument.

The geographic position of the southeast corner of the township, as determined from a tie made to U.S. Geological Survey triangulation station "SNAKE 1955", hereinafter described, is as follows:

Latitude: 35°57'16.15" N. Longitude: 109°36'01.73" W. NAD27

The mean magnetic declination, as taken from the 1985 magnetic declination map published by U.S. Geological Survey, is 12 1/2° E.

Survey of The West Boundary,
Identical With the Sixth Guide Meridian East,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Beginning at the cor. for T. 29 and 30 N., Rs. 24 and 25 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T30N R24E R25E S36 S31 S1 S6 T29N 1990.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T30N R24E R25E 1/4 S36 S31 1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
71.65	Trail road, bears NE and SW.
75.45	Trail road, bears ESE and WNW.
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T30N R24E R25E S25 S30 ----- S36 S31 1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Survey of The West Boundary,
Identical With the Sixth Guide Meridian East,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Land, gently rolling. Soil, sandy clay. No timber; yucca, greasewood, rabbitbrush and native grasses.</p> <hr/> <p>North, bet. secs. 25 and 30.</p> <p>Over gently rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T30N R24E R25E 1/4 S25 S30 1990 </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T30N R24E R25E S24 S19 <hr style="width: 50%; margin: 0 auto;"/> S25 S30 1990 </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; cacti, yucca, greasewood, rabbitbrush and native grasses.</p> <hr/>
--------	---

Survey of The West Boundary,
Identical With the Sixth Guide Meridian East,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>North, bet. secs. 19 and 24.</p> <p>Over gently rolling land.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T30N</td></tr> <tr><td>R24E</td><td>R25E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T30N		R24E	R25E	1/4		S24	S19	1990	
T30N											
R24E	R25E										
1/4											
S24	S19										
1990											
80.00	<p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T30N</td></tr> <tr><td>R24E</td><td>R25E</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2" style="border-top: 1px solid black; text-align: center;">1990</td></tr> <tr><td>S24</td><td>S19</td></tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; cacti, yucca, greasewood, rabbitbrush and native grasses.</p> <hr style="border: 0.5px solid black; margin-top: 20px;"/>	T30N		R24E	R25E	S13	S18	1990		S24	S19
T30N											
R24E	R25E										
S13	S18										
1990											
S24	S19										

Survey of The West Boundary,
 Identical With the Sixth Guide Meridian East,
 T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>North, bet. secs. 13 and 18.</p> <p>Over gently rolling land.</p>
34.85	<p>Trail road, bears ENE and WSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T30N R24E R25E 1/4 S13 S18 1990 </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
56.00	<p>Trail road, bears E. and W.</p>
80.00	<p>Point for the cor. of secs. 7, 12, 13, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T30N R24E R25E S12 S 7 <hr style="width: 50%; margin: 0 auto;"/> S13 S18 1990 </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; cacti, yucca, greasewood, rabbitbrush and native grasses.</p> <hr style="border: 0.5px solid black; margin-top: 20px;"/>

Survey of The West Boundary,
 Identical With the Sixth Guide Meridian East,
 T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>North, bet. secs. 7 and 12.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T30N R24E R25E 1/4 S12 S 7 1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
62.90	<p>Tse Ba Ni Zi Ni Wash, 76 lks. wide, 15 ft. deep, drains NE.</p>
80.00	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T30N R24E R25E S 1 S 6 ----- S12 S 7 1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; cacti, yucca, greasewood, rabbitbrush and native grasses.</p> <hr style="border: 0.5px solid black; margin-top: 20px;"/>

Survey of The West Boundary,
 Identical With the Sixth Guide Meridian East,
 T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>North, bet. secs. 1 and 6.</p> <p>Over gently rolling land.</p>
4.40	<p>Graded road, 38 lks. wide, bears NE and SW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T30N R24E R25E 1/4 S 1 S 6 1990 </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of Tps. 30 and 31 N., Rs. 24 and 25 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T31N R24E R25E S36 S31 <hr style="width: 50%; margin: 0 auto;"/> S 1 S 6 T30N 1990 </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; cacti, yucca, greasewood, rabbitbrush and native grasses.</p>

BOOK 5359

Survey of the East Boundary,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of Tps. 29 and 30 N., Rs. 25 and 26 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T30N R25E R26E S36 S31 S1 S6 T29N 1990.</p>
	<p>From this cor. point, U.S. Geological Survey triangulation station "SNAKE 1955", with published latitude of 35°58'21.623" N. and longitude of 109°35'45.482" W., NAD27, bears N. 11°25' E., 102.37 chs. dist., monumented with a standard brass disk, 3 1/2 ins. diam., cemented flush with the surface of bedrock, with top of disk mkd. SNAKE 1955 and a triangle.</p>
	<p>North, bet. secs. 31 and 36.</p>
	<p>Over rolling land.</p>
8.30	<p>Trail road, bears E. and W.</p>
8.70	<p>The NE cor. of a stucco house, 13 x 13 ft., bears West, 27.80 chs. dist., sides bear S. and W.</p>
10.30	<p>Trail road, bears ESE and WNW.</p>
12.15	<p>The NE cor. of a wood frame house, 24 x 16 ft., bears West, 37.25 chs. dist., long side bears SSW.</p>
12.60	<p>The NE cor. of a stucco house, 17 x 14 ft., bears West, 29.85 chs. dist., long side bears SSE.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T30N R25E R26E 1/4 S36 S31 1991</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
42.80	<p>The NE cor. of a stucco house, 40 x 20 ft., bears West, 28.25 chs. dist., long side bears W.</p>
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p>

BOOK 5359

Survey of the East Boundary,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T30N</td></tr> <tr><td style="text-align: center;">R25E</td><td style="text-align: center;">R26E</td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S30</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S36</td><td style="text-align: center;">S31</td></tr> <tr><td colspan="2" style="text-align: center;">1991</td></tr> </table> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 45 lks. S. of a trail road, bears E. and W.</p> <p>Land, rolling. Soil, sandy clay. No timber; native grasses, yucca and scattered brush.</p> <hr/> <p>North, bet. secs. 25 and 30.</p> <p>Over rolling land.</p>	T30N		R25E	R26E	S25	S30	-----		S36	S31	1991	
T30N													
R25E	R26E												
S25	S30												

S36	S31												
1991													
22.50	Trail road, bears ENE and WSW.												
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T30N</td></tr> <tr><td style="text-align: center;">R25E</td><td style="text-align: center;">R26E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S30</td></tr> <tr><td colspan="2" style="text-align: center;">1991</td></tr> </table>	T30N		R25E	R26E	1/4		S25	S30	1991			
T30N													
R25E	R26E												
1/4													
S25	S30												
1991													
54.20	Wash, 15 lks. wide, 4 ft. deep, drains WNW.												
64.90	Power line, 4 strands, bears SSE and NNW.												
73.50	Wash, 12 lks. wide, 4 ft. deep, drains W.												
80.00	Point for the cor. of secs. 19, 24, 25, and 30.												

BOOK 5359

Survey of the East Boundary,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, to bedrock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T30N</td></tr> <tr><td>R25E</td><td>R26E</td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td colspan="2">— —</td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in a rocky wash, 5 lks. wide, 1 ft. deep, drains W., 150 lks. E. of where it changes course and drains SW, and 200 lks. E. of a power line, 4 strands, bears SSE and NNW.</p> <p>Land, rolling. Soil, sandy clay. No timber; native grasses and scattered brush.</p> <hr/> <p>North, bet. secs. 19 and 24.</p> <p>Over rolling land.</p>	T30N		R25E	R26E	S24	S19	— —		S25	S30	1991	
T30N													
R25E	R26E												
S24	S19												
— —													
S25	S30												
1991													
13.47	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.												
19.60	The SE cor. of a wood frame house, 30 x 16 ft., bears West, 20.80 chs. dist., long side bears NNE.												
21.15	Center of a hexagonal log hogan, 15 ft. diam., bears West, 19.50 chs. dist.												
26.20	Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears SSE and NNW.												
38.86	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.												
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												

.. 13
BOOK 5359

Survey of the East Boundary,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T30N R25E R26E 1/4 S24 S19 1991</p> <p>from which</p> <p>A U.S. Coast and Geodetic Survey bench mark, monumented with a standard brass tablet, 3 1/2 ins. diam., set in a concrete collar, 10 ins. square, projecting 5 ins. above ground, with top mkd. 5917.491 FT M33 1933, bears S. 38 3/4° E., 158 lks. dist.</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E R26E S13 S18 ----- S24 S19 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; native grasses and scattered brush.</p> <hr/>
36.35	<p>North, bet. secs. 13 and 18.</p> <p>Over rolling land.</p>
40.00	<p>Trail road, bears NNE and SSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p>

BOOK 5359

Survey of the East Boundary,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E R26E 1/4 S13 S18 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>56.80 W. rim of Beautiful Valley, bears NE and SW, thence descend into broken land.</p> <p>80.00 Point for the cor. of secs. 7, 12, 13, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E R26E S12 S 7 ----- S13 S18 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. falls on the steep N. wall of a canyon, 15 lks. S. of the top of a ridge, bears NE and SW.</p> <p>Land, rolling to broken. Soil, sandy and rocky clay. No timber; scattered native grasses.</p> <hr/> <p>North, bet. secs. 7 and 12.</p> <p>Over broken land along W. edge of Beautiful Valley.</p> <p>34.40 W. rim of Beautiful Valley, bears NE and SW, thence over rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 7 and 12.</p>
---------------	---

BOOK 5359

Survey of the East Boundary,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E R26E 1/4 S12 S 7 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E R26E S 1 S 6 ----- S12 S 7 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, broken to rolling. Soil, sandy and rocky clay. No timber; native grasses and scattered brush.</p>
	<p>North, bet. secs. 1 and 6.</p> <p>Over rolling land.</p>
1.75	<p>Wash, 9 lks. wide, 3 ft. deep, drains ENE.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

BOOK 5359

Survey of the East Boundary,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T30N R25E R26E 1/4 S 1 S 6 1991</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
47.35	Trail road, bears NE and SW.
48.40	Graded road, 17 lks. wide, bears NE and SW.
61.01	The SE cor. of a log house, 34 x 16 ft., bears West, 65 lks. dist., long side bears N.
62.49	Inside an octagonal wood frame hogan, the westernmost cor. of which bears West, 1 lk. dist.
64.00	Descend into Beautiful Valley over broken land.
80.00	<p>Point for the cor. of Tps. 30 and 31 N., Rs. 25 and 26 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T31N R25E R26E S 36 S 31 ----- S 1 S 6 T30N 1991</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located 146 lks. S. of the S. rim of a canyon, bears E. and W., and 280 lks. E. of a wash, 100 lks. wide, 25 ft. deep, drains N.</p>
	<p>Land, rolling to broken. Soil, sandy and rocky clay. No timber; native grasses and scattered brush.</p>

Survey of the North Boundary,
 T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the cor. of Tps. 30 and 31 N., Rs. 25 and 26 E., hereinbefore described.
	West, bet. secs. 1 and 36.
	Over broken land.
20.60	W. rim of Beautiful Valley, bears N. and S., thence over rolling land.
21.40	Trail road, bears N. and S.
26.58	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.
28.09	Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears N. and S.
29.62	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.
35.10	Power line, 4 strands, bears N. and S.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T31N R25E S36 1/4 — S 1 T30N 1991</p>
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
76.95	Trail road, bears NE and SW.
80.00	Point for the cor. of secs. 1, 2, 35, and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

BOOK 5359

Survey of the North Boundary,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">T31N</td> <td style="text-align: center;">R25E</td> </tr> <tr> <td style="text-align: center;">S35</td> <td style="text-align: center;">S36</td> </tr> <tr> <td style="text-align: center;">S 2</td> <td style="text-align: center;">S 1</td> </tr> <tr> <td colspan="2" style="text-align: center;">T30N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T31N	R25E	S35	S36	S 2	S 1	T30N		1991			
T31N	R25E												
S35	S36												
S 2	S 1												
T30N													
1991													
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, broken to rolling. Soil, sandy clay. No timber; native grasses and scattered yucca.</p>												
	<hr/> <p>West, bet. secs. 2 and 35.</p> <p>Over rolling land.</p>												
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>												
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">T31N</td> <td style="text-align: center;">R25E</td> </tr> <tr> <td></td> <td style="text-align: center;">S35</td> </tr> <tr> <td style="text-align: center;">1/4</td> <td style="text-align: center;">—</td> </tr> <tr> <td></td> <td style="text-align: center;">S 2</td> </tr> <tr> <td colspan="2" style="text-align: center;">T30N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T31N	R25E		S35	1/4	—		S 2	T30N		1991	
T31N	R25E												
	S35												
1/4	—												
	S 2												
T30N													
1991													
52.70	<p>Trail road, bears NE and SW.</p>												
80.00	<p>Point for the cor. of secs. 2, 3, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>												

Survey of the North Boundary,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS							
	<div style="text-align: center;"> <table border="1"> <tr><td>T31N R25E</td></tr> <tr><td>S34 S35</td></tr> <tr><td>S 3 S 2</td></tr> <tr><td>T30N</td></tr> <tr><td>1991</td></tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 100 lks. E. of a trail road, bears NNE and SSW.</p> <p>Land, rolling. Soil, sandy clay. No timber; native grasses and scattered brush.</p>	T31N R25E	S34 S35	S 3 S 2	T30N	1991	
T31N R25E							
S34 S35							
S 3 S 2							
T30N							
1991							
	<hr/> <p>West, bet. secs. 3 and 34.</p>						
	<p>Over rolling land.</p>						
9.90	<p>Trail road, bears NE and SW.</p>						
20.70	<p>Trail road, bears N. and S., thence over nearly level land.</p>						
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p>						
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>						
	<div style="text-align: center;"> <table border="1"> <tr><td>T31N R25E</td></tr> <tr><td>S34</td></tr> <tr><td>1/4 —</td></tr> <tr><td>S 3</td></tr> <tr><td>T30N</td></tr> <tr><td>1991</td></tr> </table> </div>	T31N R25E	S34	1/4 —	S 3	T30N	1991
T31N R25E							
S34							
1/4 —							
S 3							
T30N							
1991							
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>						
80.00	<p>Point for the cor. of secs. 3, 4, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>						

Survey of the North Boundary,
 T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T31N</td> <td>R25E</td> </tr> <tr> <td>S33</td> <td>S34</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; text-align: center;">T30N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T31N	R25E	S33	S34			S 4	S 3	T30N		1991	
T31N	R25E												
S33	S34												
S 4	S 3												
T30N													
1991													
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling to nearly level. Soil, sandy clay. No timber; native grasses and scattered brush.</p> <hr/> <p>West, bet. secs. 4 and 33.</p> <p>Over nearly level land.</p>												
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T31N</td> <td>R25E</td> </tr> <tr> <td></td> <td>S33</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 4</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; text-align: center;">T30N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T31N	R25E		S33	1/4	—		S 4	T30N		1991	
T31N	R25E												
	S33												
1/4	—												
	S 4												
T30N													
1991													
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>												
76.30	<p>Trail road, bears SSE and NNW.</p>												
80.00	<p>Point for the cor. of secs. 4, 5, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												

Survey of the North Boundary,
 T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T31N</td><td>R25E</td></tr> <tr><td>S32</td><td>S33</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td colspan="2" style="text-align: center;">T30N</td></tr> <tr><td colspan="2" style="text-align: center;">1991</td></tr> </table>	T31N	R25E	S32	S33			S 5	S 4	T30N		1991	
T31N	R25E												
S32	S33												
S 5	S 4												
T30N													
1991													
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay. No timber; native grasses and scattered brush.</p> <hr/> <p>West, bet. secs. 5 and 32.</p> <p>Over nearly level land.</p>												
21.10	Trail road, bears N. and S.												
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T31N</td><td>R25E</td></tr> <tr><td></td><td>S32</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S 5</td></tr> <tr><td colspan="2" style="text-align: center;">T30N</td></tr> <tr><td colspan="2" style="text-align: center;">1991</td></tr> </table>	T31N	R25E		S32	1/4	—		S 5	T30N		1991	
T31N	R25E												
	S32												
1/4	—												
	S 5												
T30N													
1991													
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>												
53.15	Trail road, bears NNE and SSW.												
69.40	Dike, 20 lks. wide, 15 ft. high, bears N. and S.												
80.00	<p>Point for the cor. of secs. 5, 6, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>												

Survey of the North Boundary,
 T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<table border="1"> <tr> <td>T31N</td> <td>R25E</td> </tr> <tr> <td>S31</td> <td>S32</td> </tr> <tr> <td>S 6</td> <td>S 5</td> </tr> <tr> <td colspan="2">T30N</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table>	T31N	R25E	S31	S32	S 6	S 5	T30N		1991			
T31N	R25E												
S31	S32												
S 6	S 5												
T30N													
1991													
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay. No timber; native grasses and scattered brush.</p> <hr/> <p>West, bet. secs. 6 and 31.</p> <p>Over nearly level land.</p>												
14.50	Graded road, 33 lks. wide, bears NE and SW, thence ascend gradual E. slope over gently rolling land.												
40.00	Point for the 1/4 sec. cor. of secs. 6 and 31.												
	<table border="1"> <tr> <td>T31N</td> <td>R25E</td> </tr> <tr> <td>S31</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 6</td> <td></td> </tr> <tr> <td colspan="2">T30N</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table>	T31N	R25E	S31		1/4	—	S 6		T30N		1991	
T31N	R25E												
S31													
1/4	—												
S 6													
T30N													
1991													
79.03	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of Tps. 30 and 31 N., Rs. 24 and 25 E., hereinbefore described.</p> <p>Land, nearly level to gently rolling. Soil, sand clay. No timber; native grasses and scattered brush.</p> <hr/>												

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p>From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T30N R25E S35 S36 S2 S1 T29N 1990.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over gently rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E 1/4 S35 S36 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>49.40 Trail road, bears NNE and SSW.</p> <p>80.00 Point for the cor. of secs. 25, 26, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E S26 S25 ----- S35 S36 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; native grasses and scattered brush.</p> <hr/>
---------------	--

BOOK 5359

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°59' W., bet. secs. 25 and 36.</p> <p>Over gently rolling land.</p> <p>20.30 Trail road, bears ENE and WSW.</p> <p>21.50 Trail road, bears N. and S.</p> <p>26.50 The SE cor. of a stucco house, 22 x 16 ft., bears North, 6.55 chs. dist., long side bears N.</p> <p>40.01 Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E S25 1/4 — S36 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>60.55 Trail road, bears NNE and SSW.</p> <p>80.02 The cor. of secs. 25, 26, 35, and 36.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; native grasses and scattered brush.</p> <hr/> <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over gently rolling land.</p> <p>22.45 Center shaft of a windmill, mkd. 10K-251, bears East, 23.25 chs. dist.</p> <p>25.45 Trail road, bears E. and W.</p>
--------	---

BOOK 5359

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

<p>CHAINS 40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T30N R25E 1/4 S26 S25 1991</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
<p>80.00</p>	<p>Point for the cor. of secs. 23, 24, 25, and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T30N R25E S23 S24 ----- S26 S25 1991</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; native grasses and scattered brush.</p>
<p>11.60 12.50 29.30</p>	<hr/> <p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°59' W., bet. secs. 24 and 25.</p> <p>Over gently rolling land.</p> <p>Wash, 15 lks. wide, 2 ft. deep, drains WNW.</p> <p>Wash, 25 lks. wide, 10 ft. deep, drains WSW.</p> <p>Trail road, bears NNE and SSW.</p>

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS 40.015	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E S24 1/4 — S25 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
51.90	<p>Trail road, bears NNE and SSW.</p>
80.03	<p>The cor. of secs. 23, 24, 25, and 26.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; native grasses and scattered brush.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over rolling land.</p>
11.70	<p>Trail road, bears SE and NW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E 1/4 S23 S24 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 13, 14, 23, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

27
BOOK 5359

Survey of the Subdivisional Lines,
 T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T30N R25E</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black;">S14</td> <td style="text-align: center;">S13</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black;">S23</td> <td style="text-align: center;">S24</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T30N R25E		S14	S13	S23	S24	1991	
T30N R25E									
S14	S13								
S23	S24								
1991									
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Corner is located on top of a small mesa, 160 lks. N. of S. rim, and 260 lks. S. of N. rim.</p> <p>Land, rolling. Soil, sandy clay. No timber; native grasses and scattered brush.</p> <hr/> <p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°59' W., bet. secs. 13 and 24.</p> <p>Over rolling land.</p>								
4.95	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.								
6.49	Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears SSE and NNW.								
8.01	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.								
12.60	Power line, 4 strands, bears SSE and NNW.								
14.85	The NW cor. of a wood frame house, 56 x 34 ft., bears South, 9.05 chs. dist., long side bears S.								
16.00	Graded road, 30 lks. wide, bears SSE and NNW.								
17.55	Trail road, bears NNE and SSW.								
18.41	The NW cor. of a stucco house, 28 x 20 ft., bears South, 1.40 chs. dist., long side bears E.								
40.015	Point for the 1/4 sec. cor. of secs. 13 and 24.								

Survey of the Subdivisional Lines,
 T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E S13 1/4 — S24 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.03	<p>Point for the cor. of secs. 13, 14, 23, and 24.</p> <p>Land, rolling. Soil, sandy clay. No timber; native grasses and scattered brush.</p>
40.00	<p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E 1/4 S14 S13 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
44.00	Wash, 30 lks. wide, 5 ft. deep, drains SW.
57.95	Trail road, bears ENE and WSW.
64.30	Wash, 15 lks. wide, 2 ft. deep, drains SW.

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS 80.00	<p>Point for the cor. of secs. 11, 12, 13, and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T30N</td> <td style="padding: 0 10px;">R25E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S11</td> <td style="padding: 0 5px;">S12</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S14</td> <td style="padding: 0 5px;">S13</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">1991</td> </tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; native grasses and scattered brush.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°59' W., bet. secs. 12 and 13.</p> <p>Over broken land, on ascent.</p> <p>8.70 W. rim of Beautiful Valley, bears N. and S., thence over rolling land.</p> <p>9.40 Trail road, bears N. and S.</p> <p>14.69 E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.</p> <p>16.22 Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears SSE and NNW.</p> <p>17.75 W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.</p> <p>23.10 Trail road, bears SSE and NNW.</p> <p>23.20 Power line, 4 strands, bears SSE and NNW.</p> <p>40.015 Point for the 1/4 sec. cor. of secs. 12 and 13.</p>	T30N	R25E	S11	S12	S14	S13	1991	
T30N	R25E								
S11	S12								
S14	S13								
1991									

Survey of the Subdivisional Lines,
 T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E S12 1/4 — S13 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.03	<p>The cor. of secs. 11, 12, 13, and 14.</p> <p>Land, broken to rolling. Soil, sandy clay. No timber; native grasses and scattered brush.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over rolling land.</p>
13.00	<p>Wash, 60 lks. wide, 12 ft. deep, drains W.</p>
34.30	<p>Trail road, bears E. and W.</p>
34.75	<p>Wash, 8 lks. wide, 4 ft. deep, drains W.</p>
38.40	<p>Wash, 15 lks. wide, 5 ft. deep, drains WSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E 1/4 S11 S12 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11, and 12.</p>

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="857 365 1008 520"><tr><td>T30N</td><td>R25E</td></tr><tr><td>S 2</td><td>S 1</td></tr><tr><td>S11</td><td>S12</td></tr><tr><td colspan="2">1991</td></tr></table> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; native grasses and scattered brush.</p> <hr/> <p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 1 and 12.</p> <p>Over rolling land.</p> <p>20.96 E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.</p> <p>22.48 Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears N. and S.</p> <p>24.02 W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.</p> <p>29.30 Trail road, bears N. and S.</p> <p>29.40 Power line, 4 strands, bears N. and S.</p> <p>40.005 Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>	T30N	R25E	S 2	S 1	S11	S12	1991	
T30N	R25E								
S 2	S 1								
S11	S12								
1991									

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T30N R25E S 1 1/4 — S12 1991</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
46.65	<p>The NE cor. of a stucco house, 32 x 20 ft., bears South, 8.95 chs. dist., long side bears SSW.</p>
80.01	<p>The cor. of secs. 1, 2, 11, and 12.</p> <p>Land, rolling. Soil, sandy clay. No timber; native grasses and scattered brush.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 1 and 2.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R25E 1/4 S 2 S 1 1991</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
79.97	<p>The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. No timber; native grasses and scattered brush.</p> <hr/>

BOOK 5359

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p>From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T30N R25E S34 S35 S3 S2 T29N 1990.</p> <p>from which</p> <p style="padding-left: 40px;">An X chiseled on top of the SW cor. of a concrete culvert outlet, bears S. 66 1/4° E., 34 lks. dist.</p> <p>From this cor. point, the 14 Mile Cor. on the 1868 W. bdy. of the Navajo Indian Reservation, bears N. 82°04' E., 49.05 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. NIR 14M 1920. As it is impracticable to bury the iron post, remove brass cap and mark AM on the N. side of the iron post.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Across a stock pond.</p> <p>4.75 Top of dike, 15 lks. wide, 10 ft. high, bears NE and SW, thence over nearly level land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p style="padding-left: 40px;">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E 1/4 S34 S35 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 26, 27, 34, and 35.</p> <p style="padding-left: 40px;">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
---------------	---

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T30N</td> <td style="padding: 0 10px;">R25E</td> </tr> <tr> <td style="padding: 0 10px;">S27</td> <td style="padding: 0 10px;">S26</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 10px;">S34</td> <td style="border-top: 1px solid black; padding: 0 10px;">S35</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">1991</td> </tr> </table>	T30N	R25E	S27	S26	S34	S35	1991			
T30N	R25E										
S27	S26										
S34	S35										
1991											
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay. No timber; native grasses.</p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>N. 89°59' W., bet. secs. 26 and 35.</p> <p>Over nearly level land.</p>										
26.85	Dike, 15 lks. wide, 5 ft. high, bears NE and SW.										
39.60	Pine Springs Wash, 45 lks. wide, 4 ft. deep, drains NNE.										
39.995	Point for the 1/4 sec. cor. of secs. 26 and 35.										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>										
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T30N</td> <td style="padding: 0 10px;">R25E</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">S26</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">1/4 —</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">S35</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">1991</td> </tr> </table>	T30N	R25E		S26		1/4 —		S35	1991	
T30N	R25E										
	S26										
	1/4 —										
	S35										
1991											
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the 15 Mile Cor. on the 1868 W. bdy. of the Navajo Indian Reservation, bears N. 47°22' E., 11.58 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. NIR 15M 1920. As it is impracticable to bury the iron post, remove brass cap and mark AM on the N. side of the iron post.</p>										
79.99	The cor. of secs. 26, 27, 34, and 35.										

BOOK 5359

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, nearly level. Soil, sandy clay. No timber; native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over nearly level land.</p>
14.10	Dike, 8 lks. wide, 4 ft. high, bears ENE and WSW.
39.15	Dike, 8 lks. wide, 4 ft. high, bears ENE and WSW.
39.65	Trail road, bears ENE and WSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T30N R25E 1/4 S27 S26 1991</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
68.65	Trail road, bears NNE and SSW.
58.65	The center of a hexagonal hogan, bears West, 23.25 chs. dist.
80.00	<p>Point for the cor. of secs. 22, 23, 26, and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T30N R25E S22 S23 ----- S27 S26 1991</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

BOOK 5359

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, nearly level. Soil, sandy clay. No timber; native grasses.</p> <hr/>
	<p>From the cor. of secs. 23, 24, 25, and 26.</p>
	<p>N. 89°59' W., bet. secs. 23 and 26.</p>
	<p>Over nearly level land.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R25E S23 1/4 — S26 1991</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>From this cor. point, the 16 Mile Cor. on the 1868 W. bdy. of the Navajo Indian Reservation, bears N. 42°55' E., 12.40 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. NIR 16M 1920. As it is impracticable to bury the iron post, remove brass cap and mark AM on the N. side of the iron post.</p>
59.20	<p>Wash, 30 lks. wide, 2 ft. deep, drains N.</p>
77.25	<p>Trail road, bears N. and S.</p>
79.98	<p>The cor. of secs. 22, 23, 26, and 27.</p>
	<p>Land, nearly level. Soil, sandy clay. No timber; native grasses and scattered brush.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 22 and 23.</p>
	<p>Over gently rolling land.</p>

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS 19.90	Trail road, bears SE and NW.								
27.85	Dike, 6 lks. wide, 3 ft. high, bears NE and SW.								
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T30N</td><td>R25E</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S22</td><td> S23</td></tr> <tr><td>1991</td><td></td></tr> </table> </div> Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.	T30N	R25E	1/4		S22	S23	1991	
T30N	R25E								
1/4									
S22	S23								
1991									
80.00	Point for the cor. of secs. 14, 15, 22, and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T30N</td><td>R25E</td></tr> <tr><td>S15</td><td> S14</td></tr> <tr><td>S22</td><td> S23</td></tr> <tr><td>1991</td><td></td></tr> </table> </div> Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Land, gently rolling. Soil, sandy clay. No timber; native grasses.	T30N	R25E	S15	S14	S22	S23	1991	
T30N	R25E								
S15	S14								
S22	S23								
1991									
39.995	From the cor. of secs. 13, 14, 23, and 24. N. 89°59' W., bet. secs. 14 and 23. Over gently rolling land. Point for the 1/4 sec. cor. of secs. 14 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.								

BOOK 5359

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T30N R25E S14 1/4 — S23 1991</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the 17 Mile Cor. on the 1868 W. bdy. of the Navajo Indian Reservation, bears N. 39°34' E., 13.08 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, 6 ins. below the surface of the ground, with brass cap mkd. NIR 17M 1920. As it is impracticable to bury the iron post, remove brass cap and mark AM on the N. side of the iron post.</p> <p>Thence over nearly level land.</p>
79.99	<p>The cor. of secs. 14, 15, 22, and 23.</p> <p>Land, gently rolling to nearly level. Soil, sandy clay. No timber; native grasses and scattered brush.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R25E 1/4 S15 S14 1991</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
78.75	<p>Trail road, bears ENE and WSW.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14, and 15.</p>

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="857 363 1008 520"><tr><td>T30N</td><td>R25E</td></tr><tr><td>S10</td><td>S11</td></tr><tr><td>S15</td><td>S14</td></tr><tr><td colspan="2">1991</td></tr></table> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 245 lks. W. of a trail road, bears ENE and WSW.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; native grasses.</p> <hr/>	T30N	R25E	S10	S11	S15	S14	1991			
T30N	R25E										
S10	S11										
S15	S14										
1991											
	<p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>West, bet. secs. 11 and 14.</p> <p>Over gently rolling land.</p>										
22.60	Wash, 40 lks. wide, 3 ft. deep, drains SSW.										
40.005	Point for the 1/4 sec. cor. of secs. 11 and 14.										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="857 1283 1008 1440"><tr><td>T30N</td><td>R25E</td></tr><tr><td colspan="2">S11</td></tr><tr><td colspan="2">1/4 —</td></tr><tr><td colspan="2">S14</td></tr><tr><td colspan="2">1991</td></tr></table> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T30N	R25E	S11		1/4 —		S14		1991	
T30N	R25E										
S11											
1/4 —											
S14											
1991											
80.01	<p>The cor. of secs. 10, 11, 14, and 15.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; native grasses and scattered brush.</p> <hr/>										

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over gently rolling land.</p>
39.00	<p>Trail road, bears ENE and WSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T30N R25E 1/4 S10 S11 1991</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 10, and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T30N R25E S 3 S 2 ----- S10 S11 1991</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 165 lks. S. and 225 lks. W. of a trail road, bears SE and NW.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; native grasses and scattered brush.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>West, bet. secs. 2 and 11.</p> <p>Over gently rolling land.</p>

Survey of the Subdivisional Lines,
 T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS 40.015	Point for the 1/4 sec. cor. of secs. 2 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T30N R25E S 2 1/4 — S11 1991 </div> Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
45.60	The center of a hexagonal hogan, bears South, 35.60 chs. dist.
46.60	The center of a hexagonal hogan, bears South, 36.55 chs. dist.
80.03	The cor. of secs. 2, 3, 10, and 11. Land, gently rolling. Soil, sandy clay. No timber; native grasses and scattered brush.
North, bet. secs. 2 and 3. Over gently rolling land.	
7.80	Trail road, bears ENE and WSW.
38.40	Trail road, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T30N R25E 1/4 S 3 S 2 1991 </div> Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

<p>CHAINS 79.97</p> <p>24.35</p> <p>40.00</p> <p>80.00</p>	<p>The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; native grasses and scattered brush.</p> <hr/> <p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T30N R25E S33 S34 S4 S3 T29N 1990.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over gently rolling land.</p> <p>Trail road, bears E. and W.</p> <p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E 1/4 S33 S34 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 27, 28, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E S28 S27 ----- S33 S34 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
--	---

BOOK 5359

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, gently rolling. Soil, sandy clay. No timber; native grasses and scattered brush.</p> <hr/>
	<p>From the cor. of secs. 26, 27, 34, and 35.</p>
	<p>N. 89°59' W., bet. secs. 27 and 34.</p>
	<p>Over gently rolling land.</p>
16.40	<p>Wash, 25 lks. wide, 2 ft. deep, drains NNE.</p>
20.25	<p>Trail road, bears N. and S.</p>
21.55	<p>Trail road, bears ENE and WSW.</p>
40.005	<p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R25E S27 1/4 — S34 1991</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.01	<p>The cor. of secs. 27, 28, 33, and 34.</p>
	<p>Land, gently rolling. Soil, sandy clay. No timber; native grasses and scattered brush.</p> <hr/>
	<p>N. 0°02' W., bet. secs. 27 and 28.</p>
	<p>Over gently rolling land.</p>
24.70	<p>Trail road, bears E. and W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p>

BOOK 5359

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E 1/4 S28 S27 1991</p>
59.85	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Trail road, bears E. and W.</p>
80.00	<p>Point for the cor. of secs. 21, 22, 27, and 28.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E S21 S22 ----- S28 S27 1991</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; native grasses and scattered brush.</p>
	<hr/> <p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>N. 89°59' W., bet. secs. 22 and 27.</p> <p>Over gently rolling land.</p>
40.005	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T30N R25E S22 1/4 — S27 1991</p>
80.01	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 21, 22, 27, and 28.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; native grasses and scattered brush.</p> <hr/>
	<p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R25E 1/4 S21 S22 1991</p>
44.85	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Trail road, bears NNE and SSW.</p>
59.50	<p>Balakai Wash, 25 lks. wide, 2 ft. deep, drains ENE.</p>
73.30	<p>Trail road, bears NE and SW.</p>
80.00	<p>Point for the cor. of secs. 15, 16, 21, and 22.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

BOOK 5359

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<table border="1"> <tr><td>T30N</td><td>R25E</td></tr> <tr><td>S16</td><td>S15</td></tr> <tr><td>S21</td><td>S22</td></tr> <tr><td colspan="2">1991</td></tr> </table>	T30N	R25E	S16	S15	S21	S22	1991			
T30N	R25E										
S16	S15										
S21	S22										
1991											
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; native grasses and scattered brush.</p> <hr/> <p>From the cor. of secs. 14, 15, 22, and 23. N. 89°59' W., bet. secs. 15 and 22. Over nearly level land.</p>										
38.05	Trail road, bears N. and S.										
40.01	Point for the 1/4 sec. cor. of secs. 15 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table border="1"> <tr><td>T30N</td><td>R25E</td></tr> <tr><td colspan="2">S15</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td colspan="2">S22</td></tr> <tr><td colspan="2">1991</td></tr> </table>	T30N	R25E	S15		1/4	—	S22		1991	
T30N	R25E										
S15											
1/4	—										
S22											
1991											
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>										
55.05	Trail road, bears NNE and SSW.										
66.95	Trail road, bears SE and NW.										
80.02	The cor. of secs. 15, 16, 21, and 22. Land, nearly level. Soil, sandy clay. No timber; native grasses and scattered brush.										

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	N. 0°02' W., bet. secs. 15 and 16. Over gently rolling land.										
36.90	Trail road, bears E. and W.										
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <table border="0"><tr><td>T30N</td><td>R25E</td></tr><tr><td></td><td>1/4</td></tr><tr><td>S16</td><td> S15</td></tr><tr><td></td><td>1991</td></tr></table> Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.	T30N	R25E		1/4	S16	S15		1991		
T30N	R25E										
	1/4										
S16	S15										
	1991										
70.85	Trail road, bears E. and W.										
80.00	Point for the cor. of secs. 9, 10, 15, and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <table border="0"><tr><td>T30N</td><td>R25E</td></tr><tr><td>S 9</td><td> S10</td></tr><tr><td colspan="2"><hr/></td></tr><tr><td>S16</td><td> S15</td></tr><tr><td></td><td>1991</td></tr></table> Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Land, gently rolling. Soil, sandy clay. No timber; native grasses.	T30N	R25E	S 9	S10	<hr/>		S16	S15		1991
T30N	R25E										
S 9	S10										
<hr/>											
S16	S15										
	1991										
	<hr/> From the cor. of secs. 10, 11, 14, and 15. N. 89°58' W., bet. secs. 10 and 15. Over gently rolling land.										

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS 23.30	Trail road, bears N. and S.
40.015	Point for the 1/4 sec. cor. of secs. 10 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T30N R25E S10 1/4 — S15 1991</div> Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.03	The cor. of secs. 9, 10, 15, and 16. Land, gently rolling. Soil, sandy clay. No timber; native grasses and scattered brush.
<p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over gently rolling land.</p>	
7.40	Trail road, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T30N R25E 1/4 S 9 S10 1991</div> Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
68.10	Trail road, bears SSE and NNW.
80.00	Point for the cor. of secs. 3, 4, 9, and 10.

Survey of the Subdivisional Lines,
 T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="857 365 1008 520"> <tr><td>T30N</td><td>R25E</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td>S 9</td><td>S10</td></tr> <tr><td colspan="2">1991</td></tr> </table> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 185 lks. S. of a trail road, bears E. and W.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; native grasses.</p>	T30N	R25E	S 4	S 3	S 9	S10	1991			
T30N	R25E										
S 4	S 3										
S 9	S10										
1991											
	<p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>N. 89°59' W., bet. secs. 3 and 10.</p> <p>Over gently rolling land.</p>										
6.55	Center shaft of a windmill, mkd. 10R-58, bears North, 5.25 chs. dist.										
8.65	Trail road, bears NNE and SSW.										
40.02	Point for the 1/4 sec. cor. of secs. 3 and 10.										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="857 1381 1008 1537"> <tr><td>T30N</td><td>R25E</td></tr> <tr><td>S 3</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S10</td><td></td></tr> <tr><td colspan="2">1991</td></tr> </table> <p>Deposit broken glass from a clear bottle and a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T30N	R25E	S 3		1/4	—	S10		1991	
T30N	R25E										
S 3											
1/4	—										
S10											
1991											
60.75	Trail road, bears NE and SW.										

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS 80.04	<p>The cor. of secs. 3, 4, 9, and 10.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; native grasses.</p> <hr/>
	<p>N. 0°02' E., bet. secs. 3 and 4.</p> <p>Over nearly level land.</p>
28.95	<p>Trail road, bears NE and SW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E 1/4 S 4 S 3 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
79.97	<p>The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, nearly level. Soil, sandy clay. No timber; native grasses.</p> <hr/>
	<p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T30N R25E S32 S33 S5 S4 T29N 1990.</p> <p>N. 0°03' W., bet. secs. 32 and 33.</p> <p>Over rolling land.</p>
23.75	<p>Trail road, bears E. and W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p>

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E 1/4 S32 S33 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 28, 29, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E S29 S28 ----- S32 S33 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; native grasses and cacti.</p> <hr/> <p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>West, bet. secs. 28 and 33.</p> <p>Over gently rolling land.</p> <p>32.95 Trail road, bears N. and S.</p> <p>39.99 Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
--------	---

Survey of the Subdivisional Lines,
 T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T30N R25E S28 1/4 — S33 1991</p>
79.98	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 28, 29, 32, and 33.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; native grasses and cacti.</p> <hr/>
25.70	<p>N. 0°03' W., bet. secs. 28 and 29.</p> <p>Over gently rolling land.</p> <p>Trail road, bears E. and W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
44.90	<p style="text-align: center;">T30N R25E 1/4 S29 S28 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Trail road, bears NNE and SSW.</p>
80.00	<p>Point for the cor. of secs. 20, 21, 28, and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
 T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<div style="text-align: center;"> <table border="1"> <tr> <td>T30N R25E</td> <td></td> </tr> <tr> <td>S20</td> <td>S21</td> </tr> <tr> <td>S29</td> <td>S28</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; native grasses and cacti.</p> <hr/>	T30N R25E		S20	S21	S29	S28	1991			
T30N R25E											
S20	S21										
S29	S28										
1991											
	<p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>N. 89°59' W., bet. secs. 21 and 28.</p> <p>Over gently rolling land.</p>										
26.15	Trail road, bears NE and SW.										
39.99	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T30N R25E</td> <td></td> </tr> <tr> <td>S21</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S28</td> <td></td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T30N R25E		S21		1/4	—	S28		1991	
T30N R25E											
S21											
1/4	—										
S28											
1991											
73.90	Trail road, bears SSE and NNW.										
79.98	<p>The cor. of secs. 20, 21, 28, and 29.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; native grasses.</p> <hr/>										
	<p>N. 0°03' W., bet. secs. 20 and 21.</p>										

BOOK 5359

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	Over gently rolling land.										
11.70	Trail road, bears SSE and NNW.										
39.65	Dike, 15 lks. wide, 4 ft. high, bears E. and W.										
40.00	Point for the 1/4 sec. cor. of secs. 20 and 21.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T30N</td><td>R25E</td></tr> <tr><td></td><td>1/4</td></tr> <tr><td>S20</td><td> S21</td></tr> <tr><td></td><td>1991</td></tr> </table>	T30N	R25E		1/4	S20	S21		1991		
T30N	R25E										
	1/4										
S20	S21										
	1991										
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.										
	Cor. is located on the S. edge of a dry stock pond.										
44.30	Dike, 15 lks. wide, 4 ft. high, bears SSE and W.										
58.60	Wash, 20 lks. wide, 4 ft. deep, drains ENE.										
80.00	Point for the cor. of secs. 16, 17, 20, and 21.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T30N</td><td>R25E</td></tr> <tr><td>S17</td><td> S16</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S20</td><td> S21</td></tr> <tr><td></td><td>1991</td></tr> </table>	T30N	R25E	S17	S16	<hr/>		S20	S21		1991
T30N	R25E										
S17	S16										
<hr/>											
S20	S21										
	1991										
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.										
	<p>Land, gently rolling. Soil, sandy clay. No timber; native grasses and scattered brush.</p>										
	<hr/> <p>From the cor. of secs. 15, 16, 21, and 22.</p>										

BOOK 5359

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	N. 89°59' W., bet. secs. 16 and 21. Over gently rolling land.
39.98	Point for the 1/4 sec. cor. of secs. 16 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. T30N R25E S16 1/4 — S21 1991 Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
79.96	The cor. of secs. 16, 17, 20, and 21. Land, gently rolling. Soil, sandy clay. No timber; native grasses and scattered brush.
	N. 0°03' W., bet. secs. 16 and 17. Over nearly level land.
14.35	Trail road, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. T30N R25E 1/4 S17 S16 1991 Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
65.80	Trail road, bears ENE and WSW.

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

<p>CHAINS 80.00</p>	<p>Point for the cor. of secs. 8, 9, 16, and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="852 420 1006 577"><tr><td>T30N</td><td>R25E</td></tr><tr><td>S 8</td><td>S 9</td></tr><tr><td>S17</td><td>S16</td></tr><tr><td colspan="2">1991</td></tr></table> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay. No timber; native grasses.</p> <hr/> <p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>N. 89°59' W., bet. secs. 9 and 16.</p> <p>Over gently rolling land.</p> <p>39.97 Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="852 1218 1006 1375"><tr><td>T30N</td><td>R25E</td></tr><tr><td>S 9</td><td></td></tr><tr><td>1/4</td><td>—</td></tr><tr><td>S16</td><td></td></tr><tr><td colspan="2">1991</td></tr></table> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>79.94 The cor. of secs. 8, 9, 16, and 17.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; native grasses.</p> <hr/>	T30N	R25E	S 8	S 9	S17	S16	1991		T30N	R25E	S 9		1/4	—	S16		1991	
T30N	R25E																		
S 8	S 9																		
S17	S16																		
1991																			
T30N	R25E																		
S 9																			
1/4	—																		
S16																			
1991																			

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over gently rolling land.</p>										
5.10	Trail road, bears E. and W.										
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T30N R25E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S 8</td><td style="text-align: center;"> S 9</td></tr> <tr><td colspan="2" style="text-align: center;">1991</td></tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T30N R25E		1/4		S 8	S 9	1991			
T30N R25E											
1/4											
S 8	S 9										
1991											
41.90	Trail road, bears ENE and WSW.										
56.00	Trail road, bears NE and SW.										
80.00	<p>Point for the cor. of secs. 4, 5, 8, and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T30N R25E</td></tr> <tr><td style="text-align: center;">S 5</td><td style="text-align: center;"> S 4</td></tr> <tr><td colspan="2" style="border-top: 1px solid black; text-align: center;"> </td></tr> <tr><td style="text-align: center;">S 8</td><td style="text-align: center;"> S 9</td></tr> <tr><td colspan="2" style="text-align: center;">1991</td></tr> </table> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; native grasses.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over nearly level land.</p>	T30N R25E		S 5	S 4			S 8	S 9	1991	
T30N R25E											
S 5	S 4										
S 8	S 9										
1991											

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS 39.96	Point for the 1/4 sec. cor. of secs. 4 and 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T30N R25E S 4 1/4 — S 9 1991
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
79.92	The cor. of secs. 4, 5, 8, and 9. Land, nearly level. Soil, sandy clay. No timber; native grasses.
	N. 0°03' W., bet. secs. 4 and 5.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T30N R25E 1/4 S 5 S 4 1991
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
79.98	The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described. Land, gently rolling. Soil, sandy clay. No timber; native grasses.

BOOK 5359

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T30N R25E S31 S32 S6 S5 T29N 1990.</p>
	<p>N. 0°03' W., bet. secs. 31 and 32.</p>
	<p>Over rolling land.</p>
5.50	<p>Trail road, bears SE and NW.</p>
22.50	<p>Trail road, bears E. and W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R25E 1/4 S31 S32 1991</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
78.00	<p>Trail road, bears ENE and WSW.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31, and 32.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R25E S30 S29 ----- S31 S32 1991</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located 330 lks. W. of a trail road, bears SE and NW.</p>

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. No timber; native grasses.</p> <hr/> <p>From the cor. of secs. 28, 29, 32, and 33. N. 89°59' W., bet. secs. 29 and 32. Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E S29 1/4 — S32 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
59.50	Trail road, bears SSE and NNW.
70.40	Trail road, bears N. and S.
80.00	<p>The cor. of secs. 29, 30, 31, and 32. Land, gently rolling. Soil, sandy clay. No timber; native grasses.</p> <hr/> <p>West, bet. secs. 30 and 31. Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 30 and 31. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T30N R25E S30 1/4 — S31 1991</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
68.10	Trail road, bears ENE and WSW.
79.39	The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., hereinbefore described.
	<p>Land, gently rolling. Soil, sandy clay. No timber; native grasses.</p>
	<hr/> <p>From the cor. of secs. 29, 30, 31, and 32.</p>
	N. 0°03' W., bet. secs. 29 and 30.
	Over gently rolling land.
4.60	Trail road, bears SE and NW.
26.85	Trail road, bears E. and W.
27.20	Trail road, bears NE and SW.
27.35	The SE cor. of a log house, 20 x 20 ft., bears West, 37.05 chs. dist., sides bear N. and W.
29.80	The center of a hexagonal log hogan, bears West, 36.50 chs. dist.
30.90	The center of a hexagonal log hogan, bears West, 35.75 chs. dist.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

BOOK 5359

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T30N R25E 1/4 S30 S29 1991</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
68.30	Trail road, bears NNE and SSW.
71.50	Wash, 30 lks. wide, 3 ft. deep, drains ENE.
80.00	Point for the cor. of secs. 19, 20, 29, and 30.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R25E S19 S20 ----- S30 S29 1991</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; native grasses.</p> <hr/>
	From the cor. of secs. 20, 21, 28, and 29.
	N. 89°59' W., bet. secs. 20 and 29.
	Over gently rolling land.
25.25	Trail road, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 29.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

BOOK 5359

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T30N R25E S20 1/4 — S29 1991
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
66.30	Trail road, bears NNE and SSW.
69.30	Wash, 30 lks. wide, 3 ft. deep, drains NNE.
80.00	The cor. of secs. 19, 20, 29, and 30.
	Land, gently rolling. Soil, sandy clay. No timber; native grasses.
	West, bet. secs. 19 and 30.
	Over gently rolling land.
21.50	Trail road, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T30N R25E S19 1/4 — S30 1991
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
54.75	Trail road, bears NNE and SSW.
58.25	Wash, 10 lks. wide, 4 ft. deep, drains N.
79.30	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., hereinbefore described.

BOOK 5359

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, gently rolling. Soil, sandy clay. No timber; native grasses.</p> <hr/> <p>From the cor. of secs. 19, 20, 29, and 30. N. 0°03' W., bet. secs. 19 and 20. Over gently rolling land.</p>
27.40	Wash, 30 lks. wide, 1 ft. deep, drains E.
31.10	Wash, 15 lks. wide, 2 ft. deep, drains NE.
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with cap mkd.</p> <div style="text-align: center;"> <p>T30N R25E 1/4 S19 S20 1991</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
44.90	Trail road, bears E. and W.
71.55	Trail road, bears E. and W.
75.35	Trail road, bears ENE and WSW.
80.00	<p>Point for the cor. of secs. 17, 18, 19, and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T30N R25E S18 S17 ----- S19 S20 1991</p> </div>

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; native grasses.</p> <hr/> <p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>N. 89°59' W., bet. secs. 17 and 20.</p> <p>Over gently rolling land.</p>
6.05	Trail road, bears N. and S.
10.10	Trail road, bears SSE and NNW.
10.85	Trail road, bears SE and NW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E S17 1/4 — S20 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
60.30	Trail road, bears ENE and WSW.
80.00	<p>The cor. of secs. 17, 18, 19, and 20.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; native grasses.</p> <hr/> <p>West, bet. secs. 18 and 19.</p> <p>Over gently rolling land.</p>

BOOK 5359

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS 14.75	Trail road, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. T30N R25E S18 1/4 — S19 1991 Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
44.50	The center of an octagonal hogan, bears North, 36.60 chs. dist.
45.90	The SE cor. of a log house, 15 x 12 ft., bears North, 34.95 chs. dist., long side bears N.
65.35	Trail road, bears SSE and NNW.
79.21	The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., hereinbefore described. Land, gently rolling. Soil, sandy clay. No timber; native grasses.
	From the cor. of secs. 17, 18, 19, and 20. N. 0°03' W., bet. secs. 17 and 18. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with cap mkd. T30N R25E 1/4 S18 S17 1991

BOOK 5359

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.										
60.90	Trail road, bears E. and W.										
80.00	Point for the cor. of secs. 7, 8, 17, and 18.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T30N</td> <td>R25E</td> </tr> <tr> <td>S 7</td> <td>S 8</td> </tr> <tr> <td colspan="2" style="text-align: center;"> </td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T30N	R25E	S 7	S 8			S18	S17	1991	
T30N	R25E										
S 7	S 8										
S18	S17										
1991											
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.										
	Cor. is located 355 lks. E. of a trail road, bears ENE and WSW.										
	<p>Land, gently rolling. Soil, sandy clay. No timber; native grasses.</p>										
	From the cor. of secs. 8, 9, 16, and 17.										
	N. 89°59' W., bet. secs. 8 and 17.										
	Over nearly level land.										
8.20	Trail road, bears N. and S.										
40.00	Point for the 1/4 sec. cor. of secs. 8 and 17.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T30N</td> <td>R25E</td> </tr> <tr> <td></td> <td>S 8</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S17</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T30N	R25E		S 8	1/4	—		S17	1991	
T30N	R25E										
	S 8										
1/4	—										
	S17										
1991											

BOOK 5359

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.00	<p>The cor. of secs. 7, 8, 17, and 18.</p> <p>Land, level. Soil, sandy clay. No timber; native grasses.</p> <hr/>
	<p>West, bet. secs. 7 and 18.</p> <p>Over nearly level land.</p>
8.50	Trail road, bears ENE and WSW.
15.15	Trail road, bears NNE and SSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E S 7 1/4 — S18 1991</p>
79.13	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, nearly level. Soil, sandy clay. No timber; native grasses.</p> <hr/>
	<p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0°03' W., bet. secs. 7 and 8.</p> <p>Over nearly level land.</p>

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS 5.40	Trail road, bears ENE and WSW.
31.40	Trail road, bears NNE and SSW.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T30N R25E 1/4 S 7 S 8 1991</div>
80.00	Point for the cor. of secs. 5, 6, 7, and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T30N R25E S 6 S 5 ----- S 7 S 8 1991</div>
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Land, nearly level. Soil, sandy clay. No timber; native grasses.
	From the cor. of secs. 4, 5, 8, and 9. N. 89°59' W., bet. secs. 5 and 8. Over nearly level land.
14.05	Trail road, bears N. and S.
33.10	Trail road, bears SSE and NNW.

Survey of the Subdivisional Lines,
 T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS 40.015	<p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E S 5 1/4 — S 8 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
56.95	Trail road, bears NNE and SSW.
80.03	<p>The cor. of secs. 5, 6, 7, and 8.</p> <p>Land, nearly level. Soil, sandy clay. No timber; native grasses.</p> <hr/> <p>West, bet. secs. 6 and 7.</p> <p>Over nearly level land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R25E S 6 1/4 — S 7 1991</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
60.40	Tse Ba Ni Zi Ni Wash, 60 lks. wide, 10 ft. deep, drains NE.
79.05	The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., hereinbefore described.

BOOK 5359

Survey of the Subdivisional Lines,
T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, nearly level. Soil, sandy clay. No timber; native grasses.</p> <hr/>
	<p>From the cor. of secs. 5, 6, 7, and 8.</p>
	<p>N. 0°01' W., bet. secs. 5 and 6.</p>
	<p>Over nearly level land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R25E 1/4 S 6 S 5 1991</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
47.30	<p>Wash, 20 lks. wide, 3 ft. deep, drains NE</p>
47.80	<p>Wash, 15 lks. wide, 3 ft. deep, drains E.</p>
79.99	<p>The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., hereinbefore described.</p>
	<p>Land, nearly level. Soil, sandy clay. No timber; native grasses and scattered brush.</p> <hr/>

T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	GENERAL DESCRIPTION
	<p>The area surveyed is within the Navajo Indian Reservation, approximately 12 miles south of Chinle, Arizona. The terrain is gently rolling land, which gradually levels out to the north of the township. There are numerous washes, and the drainage is northerly.</p> <p>Elevation varies from 5,700 to 6,000 feet above sea level. The soil is mostly sandy clay, with a small area of exposed sandstone bedrock in the northeast portion of the township. The vegetation consists of native grasses, cacti, yucca, greasewood and rabbitbrush.</p> <p>Access to the township is provided by U.S. Highway 191, which enters the township in section 24 and exits in section 1. There are graded roads and trail roads throughout the township. Permanent residences are scattered throughout the township. Much of the township is used for the grazing of sheep, cattle and horses.</p> <p>There is no evidence of any kind of mining activity. The mean magnetic declination is 12 1/2° E.</p>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Jones Curtiss	Surveying Technician
Daniel Bryan	Navajo Engineering Technician
Edward Clarke	Navajo Engineering Technician
Nelson Kinsel	Navajo Engineering Technician
Reuben Mason	Navajo Engineering Technician
Barney Woodie	Navajo Engineering Technician

CERTIFICATE OF SURVEY

We, William F. Olver and Patrick S. Twohy, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 22nd day of November, 1989, we have surveyed the west boundary, identical with the Sixth Guide Meridian East, the east and north boundaries, and the subdivisional lines of Township 30 North, Range 25 East, of the Gila and Salt River Meridian, in the state of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

February 24, 1992
(Date)

William F. Olver
(Project Manager)

MARCH 4, 1992
(Date)

Patrick S. Twohy
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the survey of the west boundary, identical with the Sixth Guide Meridian East, the east and north boundaries, and the subdivisional lines of Township 30 North, Range 25 East, Gila and Salt River Meridian, executed by William F. Olver and Patrick S. Twohy, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

JUN 11 1992
(Date)

James P. Kelley
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I Certify that the foregoing transcript of the field notes of the above-described surveys in T. 30 N., R. 25 E., Gila and Salt River Meridian, Arizona is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~