

ORIGINAL

1

BOOK 5371

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE

DEPENDENT RESURVEY

OF PORTIONS OF, THE EAST BOUNDARY,

THE SUBDIVISIONAL LINES,

AND

SUBDIVISION OF SECTION 24,

AND A METES-AND-BOUNDS SURVEY OF LOT 1,

IN SECTION 24,

TOWNSHIP 11 NORTH, RANGE 19 EAST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

William P. Carpender, Cadastral Surveyor

Under special instructions dated October 5, 1989, approved October 6, 1989

_____, which provided for the surveys included under Group Number
714 and assignment instructions dated October 5, 1989.

Survey commenced October 31, 1989

Survey completed May 15, 1990

INDEX DIAGRAM

TOWNSHIP 11 NORTH , RANGE 19 EAST ,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision Section 24
Survey Lot 1

pp 9-14
pp 14-16

T. 11 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of portions of the east boundary, the subdivisional lines, and the subdivision of section 24, and a metes-and-bounds survey of lot 1, in section 24, Township 11 North, Range 19 East, Gila and Salt River Meridian, Arizona.

The township lines and the township subdivisional lines were originally surveyed by H. A. Coe in 1882-83. The exterior and subdivisional lines of the township were dependently resurveyed by Roger F. Wilson, Robert H. Fischer and Benjamin J. Mollette, in 1935-36.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973 and the Special Instructions dated October 5, 1989.

Preliminary to the survey, the lines of the original survey were retraced and search was made for all corners and other calls of the record; identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Lot 1, section 24, Township 11 North, Range 19 East, is also known as Small Tracts Act AZ-2. The location of lot 1 was indicated by Jim Muth, Apache-Sitgreaves National Forest representative.

The directions of all lines were determined by hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with Topcon GTS-3B and Zeiss Elta 46 total station instruments.

The geographic position of the cor. of secs. 13, 14, 23 and 24 was determined by the technique of relative positioning using the Mini Ranger G.P.S. Geodetic System. U.S.G.S. triangulation Station, "Dead", was used as the control station. Coordinates refer to the top of the monument.

Latitude: 34°20'36.77" N. Longitude: 110°17'09.88" W. NAD 27

The mean magnetic declination, as taken from "SHUMWAY 2 SE, ARIZ." quadrangle map, an unedited, advance sheet including field additions made in 1961 by the U.S. Geological Survey, is 14° E.

Dependent Resurvey, Portion of the East Boundary,
T. 11 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">Restoring the resurvey executed by Roger F. Wilson, Robert H. Fischer, and Benjamin J. Mollette, in 1936</p> <hr style="width: 20%; margin: auto;"/> <p>Beginning at the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., monumented with an iron pipe, 2 ins. diam., firmly set 4 ins. below the ground, with a brass cap, mkd., T11N R19E R20E S19 S24 S25 S30 1936, from which a bearing tree of record</p> <p style="padding-left: 40px;">A live oak stump, bears S. 26 1/4° W., 4.03 chs. dist., with a reversed scribed blaze alongside, mkd. BT.</p> <p>Not remonumented.</p> <p>from which new bearing objects</p> <p style="padding-left: 40px;">The center of a well, 3 ft. diam., bears N. 84 3/4° W, 3.45 chs. dist.</p> <p style="padding-left: 40px;">A rebar, 1/2 in. diam., set flush with the ground, bears S. 89 1/4° E., 14.5 lks. dist., with an aluminum cap, 2 ins. diam., with illegible marks.</p> <p style="padding-left: 40px;">A rebar, 1/2 in. diam., projecting 4 ins. above the ground, bears S. 89 1/4° E., 52 lks. dist., with an aluminum cap, 2 ins. diam., mkd. Troy Baldwin Show Low R.P. 24.75 RLS 7335.</p> <p>The cor. is located in a driveway, on the E. edge of a dirt road, bears NW and SE.</p> <p>N. 0°58' W., bet. secs. 19 and 24</p> <p>Ascend through cultivated land.</p>
24.40	Center of State Highway 260, asphalt surfaced, 30 lks. wide, bears SE and NW.
40.32	<p>The 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., projecting 13 ins. above the ground, firmly set in concrete, in a stone collar, 2 ft. diam., with a brass cap, mkd., 1/4 S24 S19 1936, from which</p> <p style="padding-left: 40px;">A dead juniper, 7 ins. diam., bears S. 51 3/4° E., 35 lks. dist., mkd. with a blaze with no marks visible (Record: S. 50° E., 36 lks.).</p> <p>Not remonumented.</p> <hr style="width: 80%; margin-left: 0;"/>

Dependent Resurvey, Portion of the Subdivisional lines,
T. 11 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">Restoring the resurvey executed by Roger F. Wilson, Robert H. Fischer and Benjamin J. Mollette in 1936.</p> <hr style="width: 20%; margin: auto;"/> <p>From the 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 1 in. diam., projecting 13 ins. above the ground, firmly set, and in a mound of stone, 3 ft. base, to top, with a brass cap mkd., 1/4 S23 S24 1936, from which</p> <p style="padding-left: 40px;">A juniper stump, 26 ins. diam., bears S. 66 3/4° E., 45 lks. dist., mkd. BT (Record: S. 67 1/2° E., 46 lks.).</p> <p style="padding-left: 40px;">A juniper, 13 ins. diam., bears S. 57 1/2° W., 1.00 ch. dist., mkd. 1/4 S23 BT.</p> <p>A steel fence post is set alongside the cor.</p> <p>Not remonumented.</p> <p>N. 0°29' W., bet. secs. 23 and 24.</p> <p>Descend steeply, through pine, juniper, and underbrush.</p>
6.40	Fence, bears NE and SW; end steep descent and leave timber, thence descend gently over rolling pasture land.
6.75	Graded road, 20 lks. wide, bears NNE, and SW.
7.10	Power pole line, bears SSE and NNW.
20.20	<p>The N 1/16 sec. cor. of secs. 23 and 24, determined by Donald M. Wiley, Registered Land Surveyor No. 4083, Arizona, monumented with an aluminum post, 2 1/2 ins. diam., projecting 9 ins. above the ground, with an aluminum cap mkd. N. 1/16 S23 S24 LS 4083 1978. This is accepted as a careful and faithful determination of the cor. position.</p> <p>Not remonumented.</p>
27.65	Track road, 15 lks. wide, bears E. and W.
28.80	Fence, bears E. and W.
29.54	A rebar of unknown origin, 5/8 in. diam., projecting 3 ins. above the ground.

Dependent Resurvey, Portion of the Subdivisional lines,
T. 11 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
29.55	A galvanized iron pipe of unknown origin, 1 3/4 ins. diam., projecting 4 ins. above the ground, bears West, 0.7 lk. dist.
29.56	Cor. of fences, bearing N., E., and W.
35.75	A steel disk, 3 ins. diam., set in concrete, flush with the surface of the ground, mkd. Arizona Highway Dept. 982X46.56 Elev 6431.46 1974, located under a fence, bears ESE and WNW.
37.35	Center of State Highway 260, asphalt surfaced, 60 lks. wide, bears ESE and WNW.
38.96	A steel disk, 3 ins. diam., set in concrete, 2 ins. below the surface of the ground, mkd. Arizona Highway Dept. 981X74.80 Elev 6432.10 1974, located under a fence, bears ESE and WNW.
39.96	The witness cor. to secs. 13, 14, 23, and 24, monumented with an iron post, 2 ins. diam., projecting 8 ins. above the ground, with a brass cap, mkd., WC T11N R19E S13 S14 S23 S24 1936.
	Not remonumented.
40.41	True point for the cor. of secs. 13, 14, 23, and 24, perpetuated by Ronald E. Stoll, Registered Land Surveyor No. 11758, Arizona, monumented with an aluminum post, 2 1/2 ins. diam., projecting 2 ins. above the ground, with an aluminum cap mkd. T11N. R19E S13 S14 S23 S24 RLS 11758 1984 and a cross, from which 1936 bearing trees of record
	A juniper, 19 ins. diam., bears S. 67 1/2° E., 1.31 chs. dist., mkd. with a healed blaze (Record: 132 lks.).
	A juniper, 17 ins. diam., bears S. 80° W., 2.31 chs. dist., mkd. with a healed blaze (Record: S. 79 3/4° W., 230 lks.).
	A juniper, 40 ins. diam., bears N. 9° W., 1.05 chs. dist., mkd. T11N R19E S14 BT (Record: 106 lks.).
	A steel fence post is set alongside the cor.
	This is accepted as a careful and faithful perpetuation of the cor. position.
	Not remonumented.
	The cor. is located in an abandoned road bed.

Dependent Resurvey, Portion of the Subdivisional lines,
T. 11 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 13 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, and in a collar of stone, 2 ft. diam., with a brass cap mkd., 1/4 S13 S24 1936, from which</p> <p style="padding-left: 40px;">A dead juniper branch, 5 ins. diam., bears S. 83 1/4° E, 36 lks. dist., mkd. 1/4 24 BT (Record S. 84° E).</p> <p style="padding-left: 40px;">A juniper stump, 6 ins. diam., bears N. 20 3/4° W, 42 lks. dist., cut below the blaze (Record N. 21° W., 43 lks.).</p> <p>Remark brass cap to read</p> <div style="text-align: center; margin-left: 100px;"> <p>T11N R19E</p> <p>S13</p> <p>1/4 ———</p> <p>S24</p> <p>1989</p> <p>1936</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pinon pine, 9 ins. diam. bears N. 64 1/2° E., 42 lks. dist., mkd. 1/4 S13 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam. bears S. 56 1/2° W., 47 lks. dist., mkd. 1/4 S24 BT.</p> <p>Rebuild the mound of stone, 3 ft. base, to top.</p> <p>S. 89°52' W., bet. secs. 13 and 24.</p> <p>Descend gradually through dense pine, juniper, and underbrush.</p>
0.04	Fence, bears N. and S.
8.00	Dirt road, 15 lks. wide, bears NE and SW.
19.025	Point for the W 1/16 sec. cor. of secs. 13 and 24.

Dependent Resurvey, Portion of the Subdivisional lines,
T. 11 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T11N R19E S13 W 1/16 _____ S24 1990</p>
	from which
	A juniper, 4 ins. diam., bears N. 53 3/4° E., 51 lks. dist., mkd. X BT.
	A pinon, 11 ins. diam. bears S. 15° E., 21 lks. dist., mkd. W 1/16 S24 BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
	Ascend gradually.
23.80	Low ridge, bears N. and S; descend.
33.295	Point for the W-W-W 1/256 sec. cor. of secs. 13 and 24, determined by Ronald E. Stoll, Registered Land Surveyor No. 11758, Arizona, monumented with an aluminum post, 2 1/2 ins. diam., projecting 5 ins. above the ground, with an aluminum cap, mkd. T11N R19E W-W-W 1/256 S13 S24 RLS 11758 1984. This is accepted as a careful and faithful determination of of the cor. position.
	Not remonumented.
	From this cor. point, an iron pipe of unknown origin, 1 1/4 ins. diam., projecting 4 ins. above the ground, bears S. 15 3/4° E., 4 lks. dist.
34.60	Road, asphalt surfaced, 30 lks. wide, in a curve bearing southeasterly and northwesterly.
38.05	The cor. of secs. 13, 14, 23, and 24.

Subdivision of Section 24,
T. 11 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 24 and 25, monumented with an iron post, 1 in. diam., projecting 10 ins. above the ground, firmly set, and in a collar of stone, 1 1/2 ft. diam., with a brass cap, mkd., 1/4 S24 S25 1936. from which</p>
	<p>A juniper, 16 in. diam., bears S. 50° W., 90 lks. dist., with partiality covered blaze mkd. 1/4 S. (Record: S. 49 1/2° W.)</p>
	<p>A juniper, 23 ins. diam., bears S. 9 3/4° W., 106 lks. dist., mkd. 1/4 S25 BT. (Record: S. 9 1/2° W., 107 lks.)</p>
	<p>A juniper, 8 ins. diam., bears N. 80° W., 36 lks. dist., mkd. 1/4 S24 BT. (Record: N. 80 1/2° W., 35 lks. dist.)</p>
	<p>Not remonumented.</p>
	<p>N. 2°04' W., on the N. and S. center line of sec. 24.</p>
	<p>Ascend through dense pine, juniper, and underbrush.</p>
10.50	<p>Ridge, bears NE and SW; descend.</p>
39.79	<p>Point for the center 1/4 sec. cor. of sec. 24, determined by Ronald E. Stoll, Registered Land Surveyor No. 11758, Arizona, at intersection with the E. and W. center line of sec. 24, monumented with an aluminum post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with an aluminum cap, mkd. T11N R19E C 1/4 S24 RLS 11758 1984, from which</p>
	<p>A ponderosa pine, 6 ins. diam. bears S. 24 1/4° E., 20 lks. dist., mkd. with a partly healed blaze.</p>
	<p>A ponderosa pine, 8 ins. diam. bears S. 62° W., 28 lks. dist., mkd. with a partly healed blaze.</p>
	<p>This is accepted as a careful and faithful determination of the cor. position.</p>
	<p>Not remonumented.</p>
	<p>Continue descent along a marked and posted line.</p>
56.57	<p>A rebar, 1/2 diam., projecting 5 ins. above the ground, located under a fence, bears ESE and WNW, marking the southerly right-of-way line of State Highway 260.</p>

Subdivision of Section 24,
T. 11 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
58.45	Center of State Highway 260, asphalt surfaced, 60 lks. wide, in a curve, bearing southeasterly and northwesterly.
59.72	<p>Point for the center N 1/16 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R19E</p> <p>C</p> <p>N 1/16 S24</p> <p>C</p> <p>1990</p> </div> <p>from which</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N. 70 1/2° W., 1.53 chs. dist., mkd. CN1/16 S24 BT.</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears N. 47 1/2° W., 1.16 chs. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
60.23	Fence on the northerly right-of-way line of State Highway 260, bears ESE and WNW.
79.65	The 1/4 sec. cor. of secs. 13 and 24.
17.70	<hr/> <p>From the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of Tp., hereinbefore described.</p> <p>S. 89°02' W., on the E. and W. center line of sec. 24.</p> <p>Over cleared, rolling land.</p>
20.62	<p>Center of State Highway 260, asphalt surfaced, 30 lks. wide, bears SE and NW.</p> <p>Point for the center E 1/16 sec. cor. of sec. 24, determined by persons unknown, monumented with a pinion gear, 7/8 in. diam., set flush with the paved surface of a road, 30 lks. wide, bears SE and NW. This is accepted as a careful and faithful determination of the cor. position.</p> <p>Not remonumented.</p>

Subdivision of Section 24,
T. 11 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Continue along a marked and posted line, through dense pine, juniper, and underbrush.
24.37	A rebar, 1/2 in. diam., projecting 5 ins. above the ground, located under a fence, bears E. and W.
41.24	The center 1/4 sec. cor. of sec. 24.
56.00	Ridge, bears NNE and SSW.
60.81	Point for the center W 1/16 sec. cor. of sec. 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a stone collar 1 1/2 ft. diam., with brass cap mkd.
	<p style="text-align: center;">T11N R19E W 1/16 C———C S24 1990</p>
	from which
	<p style="padding-left: 40px;">A pinon, 6 ins. diam. bears N. 85 1/2° E., 19 lks. dist., mkd. X BT.</p>
	<p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N. 37 3/4° W., 26 lks. dist., mkd. CW 1/16 S24 BT.</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
80.38	The 1/4 sec. cor. of secs. 23 and 24.
	<p style="text-align: center;">NW 1/4 of Section 24.</p> <hr style="width: 20%; margin: auto;"/>
	From the center W 1/16 sec. cor. of sec. 24.
	N. 1°16' W., on the N. and S. center line of the NW 1/4 of sec. 24.

Subdivision of Section 24,
T. 11 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.06	<p>The point for the NW 1/16 sec. cor. of sec. 24, at intersection with the E. and W. center line of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a stone collar, 2 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T11N R19E NW 1/16 S24 1990</p> <p>from which</p> <p style="padding-left: 40px;">A pinon, 6 ins. diam. bears N. 52° E., 49 lks. dist., mkd. NW1/16 S24 BT.</p> <p style="padding-left: 40px;">A pinon, 8 ins. diam. bears S. 55 1/4° E., 38 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
29.50	Center of State Highway 260, asphalt surfaced, 60 lks. wide, in a curve, bearing southeasterly and northwesterly.
40.12	The W 1/16 sec. cor. of secs. 13 and 24.
	<hr/> <p>From the center N 1/16 sec. cor. of sec. 24.</p> <p>S. 89°26' W., on the E. and W. center line of the NW 1/4 of sec. 24.</p>
1.70	Center of State Highway 260, asphalt surfaced, 60 lks. wide, in a curve, bears SE and NW.
19.29	The NW 1/16 sec. cor. of sec. 24.
32.51	AP 4, lot 1, hereinafter described.

Subdivision of Section 24,
T. 11 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
33.765	<p>Point for the C-W-W-NW 1/256 sec. cor. of sec. 24, identical with AP 3, lot 1, determined by Ronald E. Stoll, Registered Land Surveyor No. 11758, Arizona, monumented with an aluminum post, 2 1/2 ins. diam., set 2 ins. below the surface of the ground, with an aluminum cap mkd. T11N R19E C-W-W-NW 1/256 AP 1 STA 2 AZ S24 RLS 11758 1984, from which</p> <p style="padding-left: 40px;">A gambel oak, 19 ins. diam. bears S. 51° E., 83 lks. dist., mkd. with a healed blaze.</p> <p style="padding-left: 40px;">A gambel oak, 15 ins. diam. bears S. 1 1/4° E., 58 lks. dist., mkd. X BT.</p> <p>This is accepted as a careful and faithful determination of the cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R19E C-W-W-NW 1/256 S24 1989</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury the Aluminum post alongside the stainless steel post.</p> <p>A steel fence post is set alongside the cor.</p> <p>The cor. is located in a stock pond.</p>
38.585	<p>The N 1/16 sec. cor. of secs. 23 and 24.</p> <hr/> <p>From the C-W-W-NW 1/256 sec. cor. of sec. 24.</p> <p>N. 0°39.8' W., on the N. and S. center line of the W 1/2 of the NW 1/4 of the NW 1/4 of sec. 24.</p>

Subdivision of Section 24,
T. 11 N., R. 19 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>13.818</p> <p>15.45</p> <p>20.17</p>	<p>AP 2, lot 1, hereinafter described.</p> <p>Center of State Highway 260, asphalt surfaced, 60 lks. wide, in a curve, bears SE and NW.</p> <p>The W-W-W 1/256 sec. cor. of secs. 13 and 24.</p> <hr/> <p style="text-align: center;">Metes-and-Bounds Survey of Lot 1, Section 24, T. 11 N., R. 19 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the point for AP 1, as indicated by Jim Muth, U.S. Forest Service representative, marked by an aluminum post, 2 1/2 ins. diam., 30 ins. long, projecting 9 ins. above the ground, with aluminum cap mkd. T11N R19E AP 3 STA 2 AZ S24 LS 11758 1984.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury the aluminum post alongside the stainless steel post.</p> <p>A steel fence post is set alongside the cor.</p> <p>The cor. is located under a fence on the southerly right-of-way line of State Highway 260, in a curve bearing southeasterly and northwesterly.</p> <p>From this cor. point, a steel disk, set in concrete, projecting 2 ins. above the ground, mkd. Arizona Highway Dept. Elev 6509.33 STA 1028X23.62 PT 1974, is located along the arc of a 0°30' circular curve to the right having a radius of 11,359.16 ft., along the southerly right-of-way line of State Highway No. 260, the chord of said arc bears S. 64°51.3' E., 29.80 chs. dist.</p>
---	---

Metes-and-Bounds Survey of Lot 1, Section 24,
T. 11 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Thence along the arc of a 0°30' circular curve to the left having a radius of 11,359.16 ft., on line 1-2, identical with the southerly right-of-way line of State Highway No. 260, the chord of said arc bears N 70°08.8' W., 1.337 chs. dist.</p> <p>1.337 The point for AP 2, as indicated by Jim Muth, U.S. Forest Service representative, marked by an aluminum post, 2 1/2 ins. diam., 30 ins. long, projecting 5 ins. above the ground, with aluminum cap mkd. T11N R19E AP 4 STA 2 AZ S24 RLS 11758 1984.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div data-bbox="857 709 1036 865" style="text-align: center;"> <p>T11N R19E</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.</p> <p>Bury the aluminum post alongside the stainless steel post.</p> <p>A steel fence post is set alongside the cor.</p> <p>From this cor., a steel disk, set in concrete, 3 ins. below the surface of the ground, mkd. Arizona Highway Dept. 984X92.51 Elev 6435.39 1974, is located along the arc of a 0°30' circular curve to the left having a radius of 11,359.16 ft., along the southerly right-of-way line of State Highway No. 260, the chord of said arc bears N. 70°31.6' W., 1.349 chs. dist.</p>
13.818	<p>Thence S. 0°39.8' E., on line 2-3, identical with a portion of the N. and S. center line of the W 1/2 of the NW 1/4 of the NW 1/4 of sec. 24.</p> <p>AP 3, identical with the C-W-W-NW 1/256 sec. cor. of sec. 24, hereinbefore described.</p> <p>Thence N. 89°26' E., on line 3-4, identical with a portion of the E. and W. center line of the NW 1/4 of sec. 24.</p>

Metes-and-Bounds Survey of Lot 1, Section 24,
T. 11 N., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS

1.255

The point for AP 4, as indicated by Jim Muth, U.S. Forest Service representative, marked by an aluminum post, 2 1/2 ins. diam., 30 ins. long, projecting 5 ins. above the ground, with aluminum cap mkd. T11N R19E AP 2 STA 2 AZ S24 LS 11758 1984, from which

A dead ponderosa pine, 36 ins. diam. bears N. 22 1/2° E.,
49 lks. dist., mkd. X BT.

A ponderosa pine, 18 ins. diam. bears S. 18 3/4° E.,
1.50 chs. dist., mkd. X BT.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
25 ins. in the ground, with brass cap mkd.

T11N R19E	
LOT 1	S24
AP 4	
1989	

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic
case beneath the stainless steel post.

Bury the aluminum post alongside the stainless steel post.

A steel fence post is set alongside the cor.

Thence N. 0°41.0' W., on line 4-1.

13.351

AP 1, point of beginning.

GENERAL DESCRIPTION

The land encompassed in this survey is located adjacent to the
southeasterly side of the community of Clay Springs, AZ. The
elevation is approximately 6,500 ft. above sea level.

The terrain consists of nearly level land with moderate pine and
juniper timber in the northeasterly portion of the section,
rising to steep slopes with heavy pine, juniper, and undergrowth
in the southwesterly portion.

Access is by way of State Highway 260.

The mean magnetic declination is 14° E.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Gerald A. Van Wagenen	Surveying Technician
Keith P. Primm	Land Surveyor (Trainee)
Mark D. Wahlfield	Land Surveyor (Trainee)
Stephen K. Hansen	Surveying Technician
Cheryl A. Baier	Surveying Technician
Gordon R. Bubel	Surveying Technician
Wallace R. Ott Jr.	Surveying Aide
Craig L. McFarland	Surveying Aide

CERTIFICATE OF SURVEY

I, William P. Carpende, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 5th day of October, 1989, I have dependently resurveyed portions of, the east boundary, the subdivisional lines, and the subdivision of section 24, and a metes-and-bounds survey of Lot 1, in section 24, Township 11 North, Range 19 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

DECEMBER 3, 1992
(Date)

William P. Carpende
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of portions of, the east boundary, the subdivisional lines, and the subdivision of section 24, and a metes-and-bounds survey of Lot 1, in section 24, Township 11 North, Range 19 East, Gila and Salt River Meridian, Arizona, executed by William P. Carpende, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

DEC 21 1992
(Date)

James P. Kelley
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I Certify that the foregoing transcript of the field notes of the above-described survey in T. 11 N., R. 19 E., Gila and Salt River Meridian, Arizona is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~