

ORIGINAL

1

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

BOOK 5376

FIELD NOTES

OF THE

EAST

AND

NORTH BOUNDARIES

AND

THE SUBDIVISIONAL LINES

OF

TOWNSHIP 30 NORTH, RANGE 26 EAST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

Steve D. Cully, Cadastral Surveyor

Under Special Instructions dated and approved November 22, 1989, which provided for the surveys included under Group Number 715 and assignment instructions dated January 28, 1991.

Survey commenced May 23, 1991

Survey completed September 12, 1991

2
BOOK 5376

INDEX DIAGRAM

TOWNSHIP 30 NORTH, RANGE 26 EAST,

17 6	16 75 5	15 62 4	13 51 3	12 39 2	11 28 1 9
75 7	74 73 8	61 60 9	51 49 10	38 37 11	27 26 12 8
73 18	72 71 17	60 58 16	48 47 15	36 35 14	25 24 13 7
70 19	69 68 20	57 56 21	45 44 22	34 33 23	23 22 24 6
67 30	67 66 29	55 54 28	43 42 27	32 31 26	21 19 25 5
65 31	64 63 32	53 52 33	41 40 34	31 29 35	19 18 36 4

BOOK 5376

T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of the east and north boundaries, and the subdivisional lines of Township 30 North, Range 26 East, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated November 22, 1989, for Group No. 715, Arizona.

This survey supersedes portions of Townships 3 and 4 North, Range 10 West, of the Navajo Special Meridian. The survey history of that portion of the superseded Navajo Special Meridian is included in these notes for informational purposes only.

The boundaries and subdivision of Townships 3 and 4 North, Range 10 West, Navajo Special Meridian, were surveyed by E.N. Darling in 1869.

The south boundary of the township was surveyed by Steve D. Cully and William F. Olver in 1990-91. The west boundary of the township was surveyed by William F. Olver and Patrick S. Twohy in 1990-91.

The directions of all lines were determined by direct hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with a Lietz SET4A electronic total station instrument.

The geographic position of the true point for the southeast corner of the township, as determined from a tie made to U.S. Geological Survey triangulation station "SNAKE 1955", hereinafter described, is as follows:

Latitude: 35°57'16.18" N. Longitude: 109°29'36.93" W. NAD27

The mean magnetic declination, as taken from the 1985 magnetic declination map published by U.S. Geological Survey, is 12 1/2° E.

BOOK 5376

Survey of the East Boundary,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Beginning at the true point for the cor. of Tps. 29 and 30 N., Rs. 26 and 27 E.</p> <p>From this cor. point, the witness cor. to the cor. of Tps. 29 and 30 N., Rs. 26 and 27 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. WC T30N R26E R27E S36 S31 S1 S6 T29N 1991, bears South, 3.00 chs. dist.</p> <p>From this same cor. point, U.S. Geological Survey triangulation station "SNAKE 1955", with published latitude of 35°58'21.623" N. and longitude of 109°35'45.482" W., NAD 27, bears on a mean bearing N. 77°41' W., 470.03 chs. dist., monumented with a standard brass disk, 3 1/2 ins. diam., cemented flush with the surface of bedrock, with top of disk mkd. SNAKE 1955 and a triangle.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rugged land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T30N R26E R27E 1/4 S36 S31 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
61.45	Trail road, bears ESE and WNW.
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T30N R26E R27E S25 S30 ----- S36 S31 1991</p> </div>

Survey of the East Boundary,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>A piñon, 10 ins. diam., bears S. 53 3/4° W., 242 lks. dist., mkd. T30N R26E S36 BT.</p> <p>A piñon, 14 ins. diam., bears N. 19 1/2° W., 241 1/2 lks. dist., mkd. T30N R26E S25 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rugged. Soil, rocky clay. Timber, scattered piñon and juniper; undergrowth, native grasses and cacti.</p> <hr/>
	<p>North, bet. secs. 25 and 30.</p> <p>Over rugged land.</p>
10.90	Wash, 265 lks. wide, 8 ft. deep, drains NW.
18.60	Wash, 75 lks. wide, 10 ft. deep, drains W.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R26E R27E 1/4 S25 S30 1991</p>
	<p>from which</p> <p>A piñon, 8 ins. diam., bears S. 8 3/4° W., 189 lks. dist., mkd. 1/4 S25 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

BOOK 5376

Survey of the East Boundary,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
72.95	Trail road, bears SE and NW.												
75.10	Wash, 76 lks. wide, 15 ft. deep, drains SW.												
80.00	Point for the cor. of secs. 19, 24, 25, and 30.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T30N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S30</td></tr> <tr><td colspan="2" style="text-align: center;">1991</td></tr> </table>	T30N		R26E	R27E	S24	S19	-----		S25	S30	1991	
T30N													
R26E	R27E												
S24	S19												

S25	S30												
1991													
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.												
	Land, rugged. Soil, rocky clay. Timber, scattered piñon and juniper; undergrowth, native grasses and cacti.												
	North, bet. secs. 19 and 24.												
	Over rugged land.												
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T30N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">1991</td></tr> </table>	T30N		R26E	R27E	1/4		S24	S19	1991			
T30N													
R26E	R27E												
1/4													
S24	S19												
1991													
	from which												
	A juniper, 8 ins. diam., bears S. 63 1/4° W., 95 lks. dist., mkd. 1/4 S24 BT.												

7
BOOK 5376

Survey of the East Boundary,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.												
63.10	Trail road, bears ENE and WSW.												
80.00	Point for the cor. of secs. 13, 18, 19, and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.												
	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T30N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td style="text-align: center;">S13</td><td style="text-align: center;">S18</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">1991</td></tr> </table>	T30N		R26E	R27E	S13	S18	-----		S24	S19	1991	
T30N													
R26E	R27E												
S13	S18												

S24	S19												
1991													
	from which A juniper, 16 ins. diam., bears N. 14 3/4° W., 149 1/2 lks. dist., mkd. T30N R26E S13 BT.												
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.												
	Land, rugged. Soil, rocky clay. Timber, piñon and juniper; undergrowth, native grasses and cacti.												
	North, bet. secs. 13 and 18. Over rugged land.												
14.80	S. rim of canyon, bears E. and W.												
17.20	N. rim of canyon, bears SE and NW.												
40.00	Point for the 1/4 sec. cor. of secs. 13 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.												

BOOK 5376

Survey of the East Boundary,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T30N R26E R27E 1/4 S13 S18 1991</p> <p>from which</p> <p style="text-align: center;">A juniper, 10 ins. diam., bears S. 88 1/4° W., 36 lks. dist., mkd. 1/4 S13 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
52.00	S. rim of Cottonwood Canyon, bears ESE and WNW.
60.30	N. rim of Cottonwood Canyon, bears ESE and WNW.
80.00	Point for the cor. of secs. 7, 12, 13, and 18.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R26E R27E S12 S 7 ----- S13 S18 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rugged. Soil, rocky clay. Timber, piñon and juniper; undergrowth, native grasses and cacti.</p> <hr/> <p>North, bet. secs. 7 and 12.</p> <p>Over rugged land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 7 and 12.

BOOK 5376

Survey of the East Boundary,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R26E R27E 1/4 S12 S 7 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located 10 lks. S. of a trail road, bears ENE and WSW.</p>
48.00	<p>Trail road, bears NE and SW.</p>
75.65	<p>Trail road, bears E. and W.</p>
80.00	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R26E R27E S 1 S 6 ----- S12 S 7 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Land, rugged. Soil, rocky clay. Timber, piñon and juniper; undergrowth, native grasses and cacti.</p>
	<p>North, bet. secs. 1 and 6.</p>
	<p>Over rugged land.</p>
30.30	<p>Trail road, bears NNE and SSW.</p>

BOOK 5376

Survey of the East Boundary,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T30N R26E R27E 1/4 S 1 S 6 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 145 lks. S. of a trail road, bears ESE and WNW.</p>
50.15	Trail road, bears SSE and NNW.
80.00	<p>Point for the cor. of Tps. 30 and 31 N., Rs. 26 and 27 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T31N R26E R27E S36 S31 ----- S 1 S 6 T30N 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rugged. Soil, rocky clay. Timber, piñon and juniper; undergrowth, native grasses and cacti.</p> <hr/> <p style="text-align: center;">Survey of the North Boundary, T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 30 and 31 N., Rs. 26 and 27 E., hereinbefore described.</p>

Survey of the North Boundary,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	S. 89°59' W., bet. secs. 1 and 36.
	Over rugged land.
9.90	Trail road, bears N. and S.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	26 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T31N R26E S36 1/4 — S 1 T30N 1991 </div>
	from which
	<div style="text-align: center;"> A rock outcrop, 20 x 16 x 12 ft. high, bears N. 15 3/4° W., 117 1/2 lks. dist., with X BO chiseled on the S. face. </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case
	beneath the stainless steel post.
60.10	Trail road, bears SSE and NNW.
68.25	Trail road, bears ENE and WSW.
70.35	Trail road, bears SSE and NNW.
80.00	Point for the cor. of secs. 1, 2, 35, and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	22 ins. in the ground, to bedrock, encircled with a collar of
	stone, with brass cap mkd.
	<div style="text-align: center;"> T31N R26E S35 S36 ———— S 2 S 1 T30N 1991 </div>

BOOK 5376

Survey of the North Boundary,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

from which

A rock outcrop, bears S. $39\frac{3}{4}^{\circ}$ W., 216 $\frac{1}{2}$ lks. dist.,
with X BO chiseled on the NE face.

A juniper, 14 ins. diam., bears N. $43\frac{3}{4}^{\circ}$ W., 222 lks.
dist., mkd. T31N R26E S35 BT.

Deposit a magnet in a 1 x 1 x 2 $\frac{5}{8}$ ins. white plastic case
beneath the stainless steel post.

Cor. is located 340 lks. N. of a trail road, bears ENE and WSW.

Land, rugged.

Soil, rocky clay.

Timber, pinon and juniper; undergrowth, native grasses and cacti.

S. $89^{\circ}59'$ W., bet. secs. 2 and 35.

Over rolling land.

11.15 Trail road, bears SE and NW.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 35.

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam.,
26 ins. in the ground, with brass cap mkd.

T31N R26E
S35
1/4 —
S 2
T30N
1991

from which

A forked juniper, 9 ins. diam. at base, bears S. $24\frac{3}{4}^{\circ}$ W.,
226 lks. dist., mkd. 1/4 S2 BT.

A forked juniper, 8 ins. diam. at base, bears N. $74\frac{1}{4}^{\circ}$ W.,
303 lks. dist., mkd. 1/4 S35 BT.

Deposit a magnet in a 1 x 1 x 2 $\frac{5}{8}$ ins. white plastic case
beneath the stainless steel post.

BOOK 5376

Survey of the North Boundary,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
72.30	Wash, 30 lks. wide, 5 ft. deep, drains SSW.												
80.00	Point for the cor. of secs. 2, 3, 34, and 35.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.												
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T31N</td> <td>R26E</td> </tr> <tr> <td>S34</td> <td>S35</td> </tr> <tr> <td colspan="2" style="text-align: center;">— —</td> </tr> <tr> <td>S 3</td> <td>S 2</td> </tr> <tr> <td colspan="2" style="text-align: center;">T30N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T31N	R26E	S34	S35	— —		S 3	S 2	T30N		1991	
T31N	R26E												
S34	S35												
— —													
S 3	S 2												
T30N													
1991													
	from which												
	A forked juniper, 5 ins. diam. at base, bears N. 45 1/4° E., 107 lks. dist., mkd. T31N R26E S35 BT.												
	A forked juniper, 9 ins. diam. at base, bears S. 42 3/4° E., 268 lks. dist., mkd. T30N R26E S2 BT.												
	A rock outcrop, 2 ft. high, bears N. 74 1/2° W., 55 1/2 lks. dist., with X BO chiseled on the SE face.												
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.												
	Cor. is located 140 lks. E. of a cliff, 40 ft. high, bears N. and S.												
	Land, rolling. Soil, rocky clay and sand. Timber, piñon and juniper; undergrowth native grasses and cacti.												
	<hr/> S. 89°59' W., bet. secs. 3 and 34.												
	Over rugged land.												
13.50	Wash, 30 lks. wide, 4 ft. deep, drains WNW.												
40.00	Point for the 1/4 sec. cor. of secs. 3 and 34.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.												

BOOK 5376

Survey of the North Boundary,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T31N R26E S34 1/4 — S 3 T30N 1991</p> <p>from which</p> <p style="text-align: center;">A forked juniper, 8 ins. diam. at base, bears S. 31 1/4° W., 144 lks. dist., mkd. 1/4 S3 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
74.15	Center of a hexagonal hogan, 20 ft. diam., bears South, 3.90 chs. dist.
77.30	NW cor. of a stucco house, 40 X 30 ft., bears South, 3.70 chs. dist., long side bears SSW.
78.10	Trail road, bears SE and NW.
78.96	Center of a hexagonal hogan, 20 ft. diam., bears South, 3.50 chs. dist.
80.00	<p>Point for the cor. of secs. 3, 4, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R26E S33 S34 — — S 4 S 3 T30N 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rugged. Soil, rocky clay. Timber, scattered juniper; undergrowth, native grasses and cacti.</p> <hr/>

BOOK 5376

Survey of the North Boundary,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
	S. 89°59' W., bet. secs. 4 and 33.												
	Over nearly level land.												
14.40	Trail road, bears SE and NW.												
31.80	Graded road, 27 lks. wide, bears N. and S.												
40.00	Point for the 1/4 sec. cor. of secs. 4 and 33.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T31N</td><td>R26E</td></tr> <tr><td></td><td>S33</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S 4</td></tr> <tr><td>T30N</td><td></td></tr> <tr><td>1991</td><td></td></tr> </table>	T31N	R26E		S33	1/4	—		S 4	T30N		1991	
T31N	R26E												
	S33												
1/4	—												
	S 4												
T30N													
1991													
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.												
48.25	Center shaft of windmill, mkd. 10R2, bears South, 11.35 chs. dist.												
72.90	Nazlini Wash, 760 lks. wide, 4 ft. deep, drains N.												
80.00	Point for the cor. of secs. 4, 5, 32, and 33.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T31N</td><td>R26E</td></tr> <tr><td>S32</td><td>S33</td></tr> <tr><td colspan="2">—</td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td>T30N</td><td></td></tr> <tr><td>1991</td><td></td></tr> </table>	T31N	R26E	S32	S33	—		S 5	S 4	T30N		1991	
T31N	R26E												
S32	S33												
—													
S 5	S 4												
T30N													
1991													
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.												
	Land, nearly level. Soil, clay and sand. No timber; native grasses and cacti.												

BOOK 5376

Survey of the North Boundary,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS															
	S. 89°59' W., bet. secs. 5 and 32.														
	Over nearly level land.														
40.00	Point for the 1/4 sec. cor. of secs. 5 and 32.														
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.														
	<table data-bbox="868 577 1015 766" style="margin-left: auto; margin-right: auto;"> <tr><td>T31N</td><td>R26E</td></tr> <tr><td>S32</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S</td><td>5</td></tr> <tr><td>T30N</td><td></td></tr> <tr><td>1991</td><td></td></tr> </table>	T31N	R26E	S32		1/4	—	S	5	T30N		1991			
T31N	R26E														
S32															
1/4	—														
S	5														
T30N															
1991															
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.														
	Thence ascend over rugged land.														
66.60	W. rim of Beautiful Valley, bears NE and SW.														
	Thence over nearly level land.														
80.00	Point for the cor. of secs. 5, 6, 31, and 32.														
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.														
	<table data-bbox="868 1249 1015 1438" style="margin-left: auto; margin-right: auto;"> <tr><td>T31N</td><td>R26E</td></tr> <tr><td>S31</td><td>S32</td></tr> <tr><td colspan="2">—</td></tr> <tr><td>S</td><td>6</td></tr> <tr><td>S</td><td>5</td></tr> <tr><td>T30N</td><td></td></tr> <tr><td>1991</td><td></td></tr> </table>	T31N	R26E	S31	S32	—		S	6	S	5	T30N		1991	
T31N	R26E														
S31	S32														
—															
S	6														
S	5														
T30N															
1991															
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.														
	Land, nearly level and rugged.														
	Soil, clay and sand.														
	No timber; native grasses and cacti.														

BOOK 5376

Survey of the North Boundary,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	S. 89°59' W., bet. secs. 6 and 31.
	Over nearly level land.
3.00	Trail road, bears NNE and SSW.
4.25	Center of a hexagonal hogan, 20 ft. diam., bears South, 1.80 chs. dist.
33.50	W. rim of mesa, bears NE and SW.
	Thence descend into rugged land.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T31N R26E S31 1/4 — S 6 T30N 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located on the E. edge of a wash, 22 lks. wide, 5 ft. deep, drains NNE.
69.40	W. rim of valley, bears NNE and SSW.
	Thence over nearly level land.
78.93	The cor. of Tps. 30 and 31 N., Rs. 25 and 26 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 16 ins. above ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd. T31N R25E R26E S36 S31 S1 S6 T30N 1991.
	Land, nearly level and rugged. Soil, clay and sand. No timber; native grasses and cacti.

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T30N R26E S35 S36 S2 S1 T29N 1991.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over rugged land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R26E 1/4 S35 S36 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
63.50	<p>Wash, 20 lks. wide, 8 ft. deep, drains NE.</p>
80.00	<p>Point for the cor. of secs. 25, 26, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T30N R26E S26 S25 ----- S35 S36 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rugged. Soil, clay and sand. Timber, scattered piñon and juniper; undergrowth, native grasses and cacti.</p> <hr/>

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.
	S. 89°59' W., bet. secs. 25 and 36.
	Over rugged land.
31.40	Wash, 76 lks. wide, 50 ft. deep, drains NW.
39.985	Point for the 1/4 sec. cor. of secs. 25 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T30N R26E S25 1/4 — S36 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
57.80	Nazlini Wash, 240 lks. wide, 4 ft. deep, drains N.
79.97	The cor. of secs. 25, 26, 35, and 36.
	<p>Land, rugged. Soil, clay and sand. Timber, scattered piñon and juniper; undergrowth, native grasses and cacti.</p>
	N. 0°01' W., bet. secs. 25 and 26.
	Over rugged land.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26.
	Set a magnet in a 1 x 1 x 2 5/8 ins. white plastic case, 12 ins. below the surface of the ground.

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, for a reference monument, bears S. 45° W., 50 ft. dist., with brass cap mkd. T30N R26E 1/4 S26 RM 50 FT TO COR 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground, for a reference monument, bears N. 45° W., 75 ft. dist., with brass cap mkd. T30N R26E 1/4 S26 RM 75 FT TO COR 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on W. edge of Nazlini Wash, 420 lks. wide, 5 ft. deep, drains NW.</p>										
80.00	<p>Point for the cor. of secs. 23, 24, 25, and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T30N R26E</td> </tr> <tr> <td style="text-align: center;">S23</td> <td style="text-align: center;">S24</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S26</td> <td style="text-align: center;">S25</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table> <p>from which</p> <p>A juniper, 10 ins. diam., bears N. 57 3/4° E., 149 1/2 lks. dist., mkd. T30N R26E S24 BT.</p> <p>A juniper, 10 ins. diam., bears N. 28 1/2° W., 180 lks. dist., mkd. T30N R26E S23 BT.</p>	T30N R26E		S23	S24	-----		S26	S25	1991	
T30N R26E											
S23	S24										

S26	S25										
1991											

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 5 chs. S. of a wash, 150 lks. wide, 30 ft. deep, drains NW.</p> <p>Land, rugged. Soil, clay and sand. Timber, scattered piñon and juniper; undergrowth, native grasses and cacti.</p> <hr/> <p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°59' W., bet. secs. 24 and 25.</p> <p>Over rugged land.</p>
37.50	Trail road, bears ENE and WSW.
39.97	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T30N R26E S24 1/4 — S25 1991</p>
79.94	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 23, 24, 25, and 26.</p> <p>Land, rugged. Soil, clay and sand. Timber, scattered piñon and juniper; undergrowth, native grasses and cacti.</p> <hr/>

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°01' W., bet. secs. 23 and 24.
	Over rugged land.
12.20	SE cor. of a stucco house, 35 x 18 ft., bears West, 30.80 chs. dist., long side bears N.
12.70	SE cor. of a stucco house, 30 x 24 ft., bears West, 28.40 chs. dist., long side bears NNE.
19.90	SE cor. of a stucco house, 30 x 18 ft., bears West, 17.20 chs. dist., long side bears NNE.
21.10	Center of a hexagonal hogan, 18 ft. diam., bears West, 14.50 chs. dist.
39.60	Trail road, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T30N R26E 1/4 S23 S24 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
46.75	Trail road, bears NNE and SSW.
55.35	Trail road, bears SSE and NNW.
66.30	Graded road, 38 lks. wide, bears ESE and WNW.
71.00	Wash, 15 lks. wide, 5 ft. deep, drains WNW.
80.00	Point for the cor. of secs. 13, 14, 23, and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

BOOK 5376

Survey of the Subdivisional Lines, T. 30 N., R. 26 E.,
Gila and Salt River Meridian, Arizona

CHAINS											
	<table border="1"> <tr> <td colspan="2">T30N R26E</td> </tr> <tr> <td>S14</td> <td>S13</td> </tr> <tr> <td colspan="2" style="text-align: center;">—</td> </tr> <tr> <td>S23</td> <td>S24</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T30N R26E		S14	S13	—		S23	S24	1991	
T30N R26E											
S14	S13										
—											
S23	S24										
1991											
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rugged. Soil, clay and sand. Timber, scattered piñon and juniper; undergrowth, native grasses and cacti.</p> <hr/> <p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 13 and 24.</p> <p>Over rugged land.</p>										
13.00	NE cor. of a stucco house, 30 ft. square, bears South, 10.70 chs. dist., sides bear SSW and WNW.										
18.95	NE cor. of a stucco house, 30 x 24 ft., bears South, 19.20 chs. dist., long side bears SSW.										
21.70	E. rim of canyon, bears ENE and WSW.										
30.70	W. rim of canyon, bears ENE and WSW.										
39.96	Point for the 1/4 sec. cor. of secs. 13 and 24.										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>										
	<table border="1"> <tr> <td colspan="2">T30N R26E</td> </tr> <tr> <td colspan="2">S13</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td colspan="2">S24</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table>	T30N R26E		S13		1/4	—	S24		1991	
T30N R26E											
S13											
1/4	—										
S24											
1991											

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>A piñon, 8 ins. diam., bears N. 64 3/4° W., 125 lks. dist., mkd. 1/4 S13 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
43.70	E. rim of canyon, bears NE and SW.
43.30	SW cor. of a house, 35 x 25 ft., bears North, 13.90 chs. dist., long side bears N.
49.80	W. rim of canyon, bears NE and SW.
79.92	The cor. of secs. 13, 14, 23, and 24.
	<p>Land, rugged. Soil, clay and sand. Timber, scattered piñon and juniper; undergrowth, native grasses and cacti.</p> <hr/> <p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over rugged land.</p>
8.70	Trail road, bears E. on curve to the left.
21.50	S. rim of Cottonwood Canyon, bears ESE and WNW.
31.60	N. rim of Cottonwood Canyon, bears ESE and WNW.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R26E 1/4 S14 S13 1991</p>
	<p>from which</p> <p>A piñon, 22 ins. diam., bears N. 75 1/2° W., 199 lks. dist., mkd. 1/4 S14 BT.</p>

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case
beneath the stainless steel post.

80.00

Point for the cor. of secs. 11, 12, 13, and 14.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
10 ins. in the ground, to bedrock, in a mound of stone, 3 ft.
base, to top, with brass cap mkd.

T30N R26E	
S11	S12

S14	S13
1991	

from which

A piñon, 13 ins. diam., bears N. 13 3/4° E., 228 1/2 lks.
dist., mkd. T30N R26E S12 BT.

A piñon, 9 ins. diam., bears S. 67 1/4° E., 102 lks. dist.,
mkd. T30N R26E S13 BT.

A piñon, 7 ins. diam., bears S. 16 1/4° W., 187 1/2 lks.
dist., mkd. T30N R26E S14 BT.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case
beneath the stainless steel post.

Cor. is located on SE edge of a wash, 38 lks. wide, 3 ft. deep,
drains SW.

Land, rugged.

Soil, clay and sand.

Timber, scattered piñon and juniper; undergrowth, native grasses
and cacti.

From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the
Tp., hereinbefore described.

S. 89°59' W., bet. secs. 12 and 13.

Over rugged land.

26
BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
21.20	Trail road, bears NNE and SSW.
29.90	Wash, 30 lks. wide, 15 ft. deep, drains S.
39.955	Point for the 1/4 sec. cor. of secs. 12 and 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T30N R26E S12 1/4 — S13 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
52.20	Trail road, bears N. and S.
79.91	The cor. of secs. 11, 12, 13, and 14.
	Land, rugged. Soil, clay and sand. Timber, scattered piñon and juniper; undergrowth, native grasses and cacti.
	N. 0°01' W., bet. secs. 11 and 12.
	Over rugged land.
15.35	Trail road, bears ENE and WSW.
16.10	Trail road, bears ENE and WSW.
33.00	Wash, 23 lks. wide, 4 ft. deep, drains WSW.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

T30N R26E
1/4
S11 | S12
1991

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case
beneath the stainless steel post.

41.55 Trail road, bears NE and SW.

80.00 Point for the cor. of secs. 1, 2, 11, and 12.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
6 ins. in the ground, to bedrock, supported in a mound of stone,
3 ft. base, to top, with brass cap mkd.

T30N R26E
S 2 | S 1

S11 | S12
1991

from which

A piñon, 11 ins. diam., bears N. 50 3/4° E., 16 1/2 lks.
dist., mkd. T30N R26E S1 BT.

A piñon, 18 ins. diam., bears S. 64° E., 124 lks. dist.,
mkd. T30N R26E S12 BT.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case
beneath the stainless steel post.

Land, rugged.

Soil, clay and sand.

Timber, scattered piñon and juniper; undergrowth, native grasses
and cacti.

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the
Tp., hereinbefore described.

West, bet. secs. 1 and 12.

Over rugged land.

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.95	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R26E S 1 1/4 — S12 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
43.90	Wash, 12 lks. wide, 3 ft. deep, drains WSW.
79.90	<p>The cor. of secs. 1, 2, 11, and 12.</p> <p>Land, rugged. Soil, clay and sand. Timber, scattered piñon and juniper; undergrowth, native grasses and cacti.</p> <hr/> <p>N. 0°05' W., bet. secs. 1 and 2.</p> <p>Over rugged land.</p>
12.70	Wash, 30 lks. wide, 4 ft. deep, drains SSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T30N R26E 1/4 S 2 S 1 1991</p> <p>from which</p> <p style="text-align: center;">A piñon, 13 ins. diam., bears N. 75 3/4° E., 126 1/2 lks. dist., mkd. 1/4 S1 BT.</p>

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A piñon, 16 ins. diam., bears N. 77 3/4° W., 180 lks. dist., mkd. 1/4 S2 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
54.30	<p>Trail road, bears ENE and WSW.</p>
56.45	<p>Trail road, bears NE and SW.</p>
79.98	<p>The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.</p>
	<p>Land, rugged. Soil, clay and sand. Timber, scattered piñon and juniper; undergrowth, native grasses and cacti.</p>
	<p>From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T30N R26E S34 S35 S3 S2 T29N 1991.</p>
	<p>N. 0°01' W., bet. secs. 34 and 35.</p>
	<p>Over rugged land.</p>
13.40	<p>Trail road, bears E. and W.</p>
13.90	<p>SE cor. of a wood frame house, 32 x 22 ft., bears West, 32.00 chs. dist., long side bears N.</p>
22.48	<p>SW cor. of a stucco house, 30 x 18 ft., bears East, 384 lks. dist., long side bears NNE.</p>
22.47	<p>Center of a hexagonal hogan, 22 ft. diam., bears East, 159 lks. dist.</p>
21.64	<p>SW cor. of a stucco house, 30 x 18 ft., bears East, 74 lks. dist., long side bears N.</p>
28.00	<p>SE cor. of a stucco house, 20 x 16 ft., bears West, 9.10 chs. dist., long side bears NNE.</p>
28.60	<p>Trail road, bears ESE and WNW.</p>

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
31.30	S. rim of canyon, bears ESE and WNW.
34.50	N. rim of canyon, bears E. and W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T30N R26E 1/4 S34 S35 1991 </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on a steep ridge, bears NE and SW, 170 lks. S. of N. edge.</p>
44.90	Wash, 23 lks. wide, 5 ft. deep, drains NW.
47.90	Graded road, 45 lks. wide, bears SE and NW.
49.80	Wash, 38 lks. wide, 6 ft. deep, drains WNW.
56.20	Underground gas pipeline, bears SE and NW.
74.20	Wash, 15 lks. wide, 4 ft. deep, drains WNW.
80.00	<p>Point for the cor. of secs. 26, 27, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T30N R26E S27 S26 <hr style="width: 100%;"/> S34 S35 1991 </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rugged. Soil, clay and sand. No timber; native grasses and cacti.</p> <hr/>
	<p>From the cor. of secs. 25, 26, 35, and 36.</p>
	<p>West, bet. secs. 26 and 35.</p>
	<p>Over rugged land.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R26E</p>
	<p style="text-align: center;">S26</p>
	<p style="text-align: center;">1/4 —</p>
	<p style="text-align: center;">S35</p>
	<p style="text-align: center;">1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.02	<p>The cor. of secs. 26, 27, 34, and 35.</p>
	<p>Land, rugged.</p>
	<p>Soil, clay and sand.</p>
	<p>No timber; native grasses and cacti.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 26 and 27.</p>
	<p>Over rugged land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R26E</p>
	<p style="text-align: center;">1/4</p>
	<p style="text-align: center;">S27 S26</p>
	<p style="text-align: center;">1991</p>

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.										
80.00	Point for the cor. of secs. 22, 23, 26, and 27.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to bedrock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T30N</td> <td>R26E</td> </tr> <tr> <td>S22</td> <td>S23</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S27</td> <td>S26</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T30N	R26E	S22	S23			S27	S26	1991	
T30N	R26E										
S22	S23										
S27	S26										
1991											
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.										
	<p>Land, rugged. Soil, clay and sand. No timber; native grasses and cacti.</p>										
	From the cor. of secs. 23, 24, 25, and 26.										
	West, bet. secs. 23 and 26.										
	Over rugged land.										
19.20	N. rim of Nazlini Canyon, bears ESE and WNW.										
34.80	N. rim of Nazlini Canyon, bears ENE and WSW.										
40.025	Point for the 1/4 sec. cor. of secs. 23 and 26.										
	Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, in bedrock, with top mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T30N</td> <td>R26E</td> </tr> <tr> <td></td> <td>S23</td> </tr> <tr> <td></td> <td>1/4 —</td> </tr> <tr> <td></td> <td>S26</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T30N	R26E		S23		1/4 —		S26	1991	
T30N	R26E										
	S23										
	1/4 —										
	S26										
1991											

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet, 1 in. long, 7/8 in. diam., beneath the brass tablet.
42.50	NE rim of Nazlini Canyon, bears SE and NW.
51.10	Nazlini Wash, 227 lks. wide, 5 ft. deep, drains NNW.
55.40	Center of water well head, 6 ins. diam., bears North, 278 lks. dist.
60.50	SW rim of Nazlini Canyon, bears SE and NW.
69.60	Top of earthen dike, bears NE and SW.
80.05	The cor. of secs. 22, 23, 26, and 27.
	Land, rugged. Soil, clay and sand. No timber; native grasses and cacti.
	N. 0°01' W., bet. secs. 22 and 23.
	Over rugged land.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T30N R26E 1/4 S22 S23 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
42.00	SW rim of Nazlini Canyon, bears SE and NW.
50.52	Center of water well head, bears West, 40 lks. dist.

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
54.50	Nazlini Wash, 544 lks. wide, 12 ft. deep, drains WNW.										
62.00	NE rim of Nazlini Canyon, bears SE and NW.										
64.30	Graded road, 45 lks. wide, bears NNE and SSW.										
80.00	Point for the cor. of secs. 14, 15, 22, and 23.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T30N</td> <td>R26E</td> </tr> <tr> <td>S15</td> <td>S14</td> </tr> <tr> <td>S22</td> <td>S23</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T30N	R26E	S15	S14	S22	S23	1991			
T30N	R26E										
S15	S14										
S22	S23										
1991											
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.										
	Cor is located 250 lks. S. of S. rim of Cottonwood Canyon, bears ENE and WSW, and 330 lks. E. of same rim, bears NE and SW.										
	Land, rugged. Soil, clay and sand. No timber; native grasses and cacti.										
	From the cor. of secs. 13, 14, 23, and 24.										
	West, bet. secs. 14 and 23.										
	Over rugged land.										
27.40	Trail road, bears ENE and WSW.										
40.035	Point for the 1/4 sec. cor. of secs. 14 and 23.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T30N</td> <td>R26E</td> </tr> <tr> <td></td> <td>S14</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S23</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T30N	R26E		S14	1/4	—		S23	1991	
T30N	R26E										
	S14										
1/4	—										
	S23										
1991											

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.07	<p>The cor. of secs. 14, 15, 22, and 23.</p> <p>Land, rugged. Soil, clay and sand. No timber; native grasses and cacti.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over rugged land.</p>
5.60	Cottonwood Wash, 380 lks. wide, 8 ft. deep, drains SSW.
9.40	N. rim of Cottonwood Canyon, bears ENE and WSW.
35.15	Trail road, bears NNE and SSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R26E 1/4 S15 S14 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
53.30	Trail road, bears ENE and WSW.
55.05	Trail road, bears SE and NW.
80.00	<p>Point for the cor. of secs. 10, 11, 14, and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">T30N</td> <td style="text-align: center;">R26E</td> </tr> <tr> <td style="text-align: center;">S10</td> <td style="text-align: center;">S11</td> </tr> <tr> <td style="text-align: center;">S15</td> <td style="text-align: center;">S14</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 260 lks. S. of a wash, 8 lks. wide, 20 ft. deep, drains WSW.</p> <p>Land, rugged. Soil, clay and sand. No timber; native grasses and cacti.</p> <hr/> <p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>West, bet. secs. 11 and 14.</p> <p>Over rugged land.</p> <p>25.60 Trail road, bears SSE and NNW.</p> <p>33.80 Trail road, bears NNE and SSW.</p> <p>39.65 SE rim of canyon, bears NE and SW.</p> <p>40.045 Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to bedrock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">T30N</td> <td style="text-align: center;">R26E</td> </tr> <tr> <td></td> <td style="text-align: center;">S11</td> </tr> <tr> <td style="text-align: center;">1/4</td> <td style="text-align: center;">—</td> </tr> <tr> <td></td> <td style="text-align: center;">S14</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T30N	R26E	S10	S11	S15	S14	1991		T30N	R26E		S11	1/4	—		S14	1991	
T30N	R26E																		
S10	S11																		
S15	S14																		
1991																			
T30N	R26E																		
	S11																		
1/4	—																		
	S14																		
1991																			

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
52.00	NW rim of canyon, bears ENE and WSW.
57.45	SE rim of canyon, bears ENE and WSW.
61.10	NW rim of canyon, bears ENE and WSW.
80.09	<p>The cor. of secs. 10, 11, 14, and 15.</p> <p>Land, rugged. Soil, rocky clay and sand. No timber; native grasses and cacti.</p> <hr/>
	N. 0°01' W., bet. secs. 10 and 11.
	Over rugged land.
11.15	Trail road, bears ESE and WNW.
15.50	Wash, 23 lks. wide, 2 ft. deep, drains W.
23.40	Wash, 60 lks. wide, 15 ft. deep, drains WSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R26E 1/4 S10 S11 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
70.10	Wash, 8 lks. wide, 8 ft. deep, drains SW.
70.80	Wash, 8 lks. wide, 3 ft. deep, drains WNW.
76.20	Wash, 12 lks. wide, 2 ft. deep, drains WSW.

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Point for the cor. of secs. 2, 3, 10, and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <table data-bbox="868 451 1015 609" style="margin-left: auto; margin-right: auto;"> <tr><td>T30N</td><td>R26E</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S10</td><td>S11</td></tr> <tr><td colspan="2" style="text-align: center;">1991</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 430 lks. S. of a wash, 30 lks. wide, 4 ft. deep, drains WNW.</p> <p>Land, rugged. Soil, rocky clay and sand. No timber; native grasses and cacti.</p>	T30N	R26E	S 3	S 2			S10	S11	1991	
T30N	R26E										
S 3	S 2										
S10	S11										
1991											
	<p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>West, bet. secs. 2 and 11.</p> <p>Over rugged land.</p>										
40.055	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, in bedrock, with top mkd.</p> <table data-bbox="868 1333 1015 1491" style="margin-left: auto; margin-right: auto;"> <tr><td>T30N</td><td>R26E</td></tr> <tr><td>S 2</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S11</td><td></td></tr> <tr><td colspan="2" style="text-align: center;">1991</td></tr> </table> <p>Deposit a magnet, 1 in. long, 7/8 in. diam., beneath the brass tablet.</p>	T30N	R26E	S 2		1/4	—	S11		1991	
T30N	R26E										
S 2											
1/4	—										
S11											
1991											
44.40	<p>E. rim of canyon, bears NNE and SSW.</p>										

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
49.60	W. rim of canyon, bears NNE and SSW.
80.11	<p>The cor. of secs. 2, 3, 10, and 11.</p> <p>Land, rugged. Soil, rocky clay and sand. No timber; native grasses and cacti.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over rugged land.</p>
13.80	Wash, 38 lks. wide, 2 ft. deep, drains WSW.
28.30	Wash, 46 lks. wide, 3 ft. deep, drains SSW.
29.20	Wash, 30 lks. wide, 3 ft. deep, drains SSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R26E 1/4 S 3 S 2 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
43.80	Trail road, bears ESE and WNW.
45.80	Wash, 105 lks. wide, 20 ft. deep, drains W.
49.60	Wash, 15 lks. wide, 6 ft. deep, drains NW.
75.40	Canyon, 75 lks. wide, 30 ft. deep, drains WSW.
79.98	The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., hereinbefore described.

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rugged. Soil, rocky clay and sand. No timber; native grasses and cacti.</p> <hr/>
	<p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T30N R26E S33 S34 S4 S3 T29N 1991.</p>
	<p>N. 0°02' W., bet. secs. 33 and 34.</p>
	<p>Over nearly level land.</p>
17.30	<p>Trail road, bears ESE and WNW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R26E 1/4 S33 S34 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 27, 28, 33, and 34.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R26E S28 S27 ----- S33 S34 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located 10 lks. S. of a power line, bears E. and W., and 460 lks. S. of a graded road, 38 lks. wide, bears E. and W.</p>

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, nearly level. Soil, clay and sand. No timber; native grasses and cacti.</p> <hr/> <p>From the cor. of secs. 26, 27, 34, and 35. West, bet. secs. 27 and 34. Over rolling land.</p>
20.80	Underground gas pipeline, bears SE and NW.
22.00	Wash, 12 lks. wide, 3 ft. deep, drains NW.
25.50	Graded road, 38 lks. wide, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p>T30N R26E S27 1/4 — S34 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
40.60	NE cor. of a stucco house, 60 x 28 ft., bears South, 19.30 chs. dist., long side bears S.
42.40	Trail road, bears N. and S.
45.35	NE cor. of a stucco house, 30 x 18 ft., bears South, 12.20 chs. dist., long side bears SSW.
45.65	Center of a hexagonal hogan, 20 ft. diam., bears South, 6.40 chs. dist.
45.90	NE cor. of a stucco house, 20 ft. square, bears South, 5.60 chs. dist., sides bear S. and W.

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
49.35	NE cor. of a stucco house, 20 x 15 ft., bears South, 5.80 chs. dist., long side bears SSW.
50.05	Trail road, bears SE and NW.
54.70	Power line, bears N. and S.
80.00	The cor. of secs. 27, 28, 33, and 34.
	Land, rolling. Soil, rocky clay and sand. No timber; native grasses and cacti.
	N. 0°02' W., bet. secs. 27 and 28.
	Over nearly level land.
7.50	Wash, 300 lks. wide, 4 ft. deep, drains WSW.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T30N R26E 1/4 S28 S27 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
59.90	NE cor. of a log house, 20 x 16 ft., bears West, 147 lks. dist., long side bears S.
60.30	Center of a hexagonal hogan, 15 ft. diam., bears West, 30 lks. dist.
62.27	NE cor. of a stucco house, 26 x 16 ft., bears West, 48 lks. dist., long side bears SSW.
80.00	Point for the cor. of secs. 21, 22, 27, and 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<table border="1" style="margin: auto;"> <tr> <td colspan="2">T30N R26E</td> </tr> <tr> <td>S21</td> <td>S22</td> </tr> <tr> <td colspan="2" style="text-align: center;">—</td> </tr> <tr> <td>S28</td> <td>S27</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T30N R26E		S21	S22	—		S28	S27	1991	
T30N R26E											
S21	S22										
—											
S28	S27										
1991											
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, clay and sand. No timber; native grasses and cacti.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>West, bet. secs. 22 and 27.</p> <p>Over rolling land.</p>										
25.46	SW cor. of a stucco house, 24 x 20 ft., bears North, 146 lks. dist., long side bears N.										
34.20	Graded road, 30 lks. wide, bears N. and S.										
40.00	Point for the 1/4 sec. cor. of secs. 22 and 27.										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <table border="1" style="margin: auto;"> <tr> <td colspan="2">T30N R26E</td> </tr> <tr> <td></td> <td>S22</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S27</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table> </p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Thence enter nearly level land.</p>	T30N R26E			S22	1/4	—		S27	1991	
T30N R26E											
	S22										
1/4	—										
	S27										
1991											
59.10	Underground gas pipeline, bears SSE and NNW.										
63.40	Graded road, 38 lks. wide, bears SSE and NNW.										
80.00	The cor. of secs. 21, 22, 27, and 28.										

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling to nearly level. Soil, rocky clay and sand. No timber; native grasses and cacti.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over nearly level land.</p>
23.15	SE cor. of a wood frame house, 32 x 16 ft., bears West, 7 lks. dist., long side bears NNE.
23.80	SW cor. of a log house, 25 x 10 ft., bears East, 8.45 chs. dist., long side bears N.
24.55	SW cor. of a stucco house, 22 x 20 ft., bears East, 26 lks. dist., long side bears N.
27.44	Center of an octagonal hogan, 25 ft. diam., bears East, 6 lks. dist.
28.03	Center of an octagonal hogan, 25 ft. diam., bears East, 12 lks. dist.
29.45	SE cor. of a log house, 15 x 14 ft., bears East, 9.40 chs. dist., long side bears NNE.
34.30	Graded road, 30 lks. wide, bears SE and NW.
37.20	Trail road, bears E. and W.
37.25	SW cor. of a stucco house, 32 x 26 ft., bears East, 5.45 chs. dist., long side bears N.
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R26E 1/4 S21 S22 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
70.50	Trail road, bears ESE and WNW.
80.00	Point for the cor. of secs. 15, 16, 21, and 22.
	Set a magnet in a 1 x 1 x 2 5/8 ins. white plastic case, 12 ins. below the surface of the ground.
	from which
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 10° E., 100.0 ft. dist., with brass cap mkd. T30N R26E S15 RM 100.0 FT TO COR 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 10° W., 396.0 ft. dist., with brass cap mkd. T30N R26E S21 RM 396.0 FT TO COR 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	Cor. is located in Nazlini Wash, 630 lks. wide, drains WNW, 45 lks. S. of N. bank.
	<p>Land, nearly level. Soil, clay and sand. No timber; native grasses and cacti.</p>
	From the cor. of secs. 14, 15, 22, and 23.
	West, bet. secs. 15 and 22.
	Over rolling land.
8.50	NW rim of Cottonwood Canyon, bears NE and SW.
28.75	SW cor. of a log house, 30 x 26 ft., bears North, 5.95 chs. dist., long side bears NNE.
29.50	Trail road, bears NNE and SSW.

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
33.61	Center of a hexagonal hogan, 18 ft. diam., bears South, 322 lks. dist.
35.08	NW cor. of a wood frame house, 32 x 16 ft., bears South, 266 lks. dist., long side bears S.
35.99	NW cor. of a log house, 24 x 16 ft., bears South, 36 lks. dist., long side bears S.
37.70	Power line, bears NE and SW.
38.80	Power line, bears SSE and NNW.
40.005	Point for the 1/4 sec. cor. of secs. 15 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T30N R26E S15 1/4 — S22 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Thence over nearly level land.
40.25	Trail road, bears NNE and SSW.
41.63	NE cor. of a stucco house, 38 x 24 ft., bears South, 478 lks. dist., long side bears SSW.
41.67	Center of an octagonal hogan, 20 ft. diam., bears South, 433 lks. dist.
46.40	Graded road, 38 lks. wide, bears SSE and NNW.
72.60	Underground gas pipeline, bears SSE and NNW.
80.01	The cor. of secs. 15, 16, 21, and 22.

47
BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Land, rolling to nearly level. Soil, rocky clay and sand. No timber; native grasses and cacti.
	<hr/> N. 0°02' W., bet. secs. 15 and 16.
	Over nearly level land.
5.80	Trail road, bears ESE and WNW.
6.55	Wash, 15 lks. wide, 4 ft. deep, drains WNW.
20.80	Trail road, bears E. and W.
25.60	SE cor. of a stucco house, 25 x 15 ft., bears West, 9.75 lks. dist., long side bears NNE.
25.60	Center of a hexagonal hogan, 18 ft. diam., bears West, 7.05 chs. dist.
26.20	NE cor. of a stucco house, 38 x 32 ft., bears West, 21.60 chs. dist., long side bears SSW.
27.49	Center of a hexagonal hogan, 18 ft. diam., bears West 21.15 chs. dist.
28.31	SW cor. of a log house, 35 x 20 ft., bears West, 79 lks. dist., long side bears N.
33.00	Power line, bears E. and W.
36.85	SW cor. of a stucco house, 32 x 15 ft., bears East, 6.90 chs. dist., long side bears NNE.
38.35	Center of a hexagonal hogan, 16 ft. diam., bears East, 7.50 chs. dist.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

48
BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T30N R26E 1/4 S16 S15 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
44.80	Graded road, 30 lks. wide, bears E. and W.
80.00	Point for the cor. of secs. 9, 10, 15, and 16. Set a magnet in a 1 x 1 x 2 5/8 ins. white plastic case, 12 ins. below the surface of the ground. from which A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 70° E., 100.0 ft. dist., with brass cap mkd. T30N R26E S10 RM 100.0 FT TO COR 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 70° W., 50.0 ft. dist., with brass cap mkd. T30N R26E S16 RM 50.0 FT TO COR 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Cor is located on W. edge of a graded road, 30 lks. wide, bears N. and S. Land, nearly level. Soil, clay and sand. No timber; native grasses and cacti.
	From the cor. of secs. 10, 11, 14, and 15. N. 89°59' W., bet. secs. 10 and 15. Over nearly level land.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 15.

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R26E S10 1/4 — S15 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
49.60	Top of dike, 27 lks. wide, 30 ft. high, bears N. and S.
65.70	Power line, bears SSE and NNW.
72.60	Underground gas pipeline, bears N. and S.
80.00	The cor. of secs. 9, 10, 15, and 16.
	<p>Land, nearly level. Soil, rocky clay and sand. No timber; native grasses and cacti.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over nearly level land.</p>
16.90	SW cor. of a log house, 30 x 25 ft., bears East, 11.00 chs. dist., long side bears NNE.
18.10	Center of a hexagonal hogan, 18 ft. diam., bears East, 13.15 chs. dist.
18.80	Center of a hexagonal hogan, 18 ft. diam., bears East, 14.50 chs. dist.
19.85	Center of a hexagonal hogan, 16 ft. diam., bears East, 13.15 chs. dist.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T30N R26E 1/4 S 9 S10 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
50.80	Wash, 38 lks. wide, 4 ft. deep, drains SW.
60.15	Trail road, bears ENE and WNW.
76.20	Power line, bears SSE and NNW.
80.00	Point for the cor. of secs. 3, 4, 9, and 10.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R26E S 4 S 3 ----- S 9 S10 1991</p>
	<p>from which</p>
	<p style="text-align: center;">SW cor. of a concrete block house, 30 x 15 ft., bears N. 39 1/4° E, 440 lks. dist., long side bears NNW.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located 210 lks. W. of a trail road, bears N. and S., 145 lks. S. and 410 lks. E. of a power line, bears ENE and WSW, 300 lks. S. of a trail road, bears E. and W., and 40 lks. E. of a power line, bears N. and S.</p>

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, nearly level. Soil, sand and clay. No timber; native grasses.</p> <hr/>
	<p>From the cor. of secs. 2, 3, 10, and 11. N. 89°59' W., bet. secs. 3 and 10. Over rolling hills.</p>
39.995	<p>Point for the 1/4 sec. cor. of secs. 3 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R26E S 3 1/4 — S10 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
42.20	<p>Wash, 23 lks. wide, 3 ft. deep, drains WSW.</p>
43.35	<p>Trail road, bears N. and S.</p>
79.99	<p>The cor. of secs. 3, 4, 9, and 10. Land, rolling. Soil, sand and clay. No timber; native grasses.</p> <hr/>
40.00	<p>N. 0°02' W., bet. secs. 3 and 4. Over nearly level land. Point for the 1/4 sec. cor. of secs. 3 and 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T30N R26E 1/4 S 4 S 3 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
55.30	Wash, 40 lks. wide, 3 ft. deep, drains WSW.
74.20	Graded road, 30 lks. wide, bears NNE and SSW.
76.30	Power line, bears E. and W.
79.93	The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described.
	Land, nearly level. Soil, sand and clay. No timber; native grasses.
	<hr/> From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T30N R26E S32 S33 S5 S4 T29N 1991.
	N. 0°03' W., bet. secs. 32 and 33.
	Over nearly level land.
28.15	Trail road, bears ESE and WNW.
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T30N R26E 1/4 S32 S33 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Point for the cor. of secs. 28, 29, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <table data-bbox="868 451 1015 609" style="margin-left: auto; margin-right: auto;"> <tr> <td>T30N</td> <td>R26E</td> </tr> <tr> <td>S29</td> <td>S28</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S32</td> <td>S33</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sand and clay. No timber; native grasses.</p>	T30N	R26E	S29	S28			S32	S33	1991	
T30N	R26E										
S29	S28										
S32	S33										
1991											
<p>From the cor. of secs. 27, 28, 33, and 34.</p>											
<p>S. 89°59' W., bet. secs. 28 and 33.</p>											
<p>Over nearly level land.</p>											
8.80	Bis-ii-ah Wash, 300 lks. wide, 3 ft. deep, drains NNE.										
13.20	Trail road, bears ENE and WSW.										
15.25	Trail road, bears ESE and WNW.										
21.50	Trail road, bears NNE and SSW.										
23.32	Intersect E. side of a stucco house, 34 x 24 ft., the SE. cor. bears South, 1 lk. dist., long side bears W.										
24.85	NW cor. of a log house, 18 x 16 ft., bears South, 403 lks. dist., long side bears S.										
26.30	NW cor. of a log house, 16 ft. square, bears South, 12.20 chs. dist., sides bear ESE and SSW.										
29.45	Center of a hexagonal hogan, 18 ft. diam., bears South, 12.80 chs. dist.										
30.65	Northernmost cor. of a stucco house, 30 x 22 ft., bears South, 14.05 chs. dist., long side bears SE.										

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
33.90	NW cor. of a wood frame house, 30 x 20 ft., bears South, 12.70 chs. dist., long side bears S.
38.80	Power line, bears NNE and SSW.
39.985	Point for the 1/4 sec. cor. of secs. 28 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T30N R26E S28 1/4 — S33 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
55.55	Center of a hexagonal hogan, 18 ft., diam., bears North, 415 lks. dist.
57.40	SW cor. of a wood frame house, 30 x 25 ft., bears North, 312 lks. dist., long side bears NNE.
57.95	SW cor. of a log house, 48 x 40 ft., bears North, 419 lks. dist., long side bears N., and SW cor. of a wood frame house, 56 x 16 ft., bears North, 6.90 chs. dist., long side bears N.
59.30	Trail road, bears N. and S.
73.75	Trail road, bears N. and S.
79.97	The cor. of secs. 28, 29, 32, and 33. Land, nearly level. Soil, sand and clay. No timber; native grasses.
	N. 0°03' W., bet. secs. 28 and 29.
	Over nearly level land.
8.10	Graded road, 38 lks. wide, bears E. and W.

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R26E 1/4 S29 S28 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 20, 21, 28, and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R26E S20 S21 ----- S29 S28 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 85 lks. W. and 435 lks. S. of a trail road, bears SSE and NNW.</p> <p>Land, nearly level. Soil, sand and clay. No timber; native grasses.</p> <hr/> <p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>S. 89°59' W., bet. secs. 21 and 28.</p> <p>Over nearly level land.</p>
39.975	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T30N R26E S21 1/4 — S28 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
45.70	Bis-ii-ah Wash, 300 lks. wide, 4 ft. deep, drains N.
79.10	Trail road, bears NNE and SSW.
79.95	The cor. of secs. 20, 21, 28, and 29.
	<p>Land, nearly level. Soil, sand and clay. No timber; native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 20 and 21.</p> <p>Over nearly level land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R26E 1/4 S20 S21 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
74.10	Power line, bears E. and W.
78.85	Trail road, bears NE and SW.
80.00	<p>Point for the cor. of secs. 16, 17, 20, and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

BOOK 5376

Survey of the Subdivisional Lines, T. 30 N., R. 26 E.,
Gila and Salt River Meridian, Arizona

CHAINS									
	<table border="1" style="margin: auto;"> <tr> <td>T30N</td> <td>R26E</td> </tr> <tr> <td>S17</td> <td>S16</td> </tr> <tr> <td>S20</td> <td>S21</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T30N	R26E	S17	S16	S20	S21	1991	
T30N	R26E								
S17	S16								
S20	S21								
1991									
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sand and clay. No timber; native grasses.</p> <hr/> <p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>S. 89°59' W., bet. secs. 16 and 21.</p> <p>Over nearly level land across bed of Nazlini Wash.</p>								
17.50	W. bank of Nazlini Wash, 15 ft. high, bears SSE and NNW.								
	Thence enter nearly level land.								
18.94	Trail road, bears SSE and NNW.								
23.90	Trail road, bears NNE and SSW.								
24.17	Barbed wire fence, bears NNE and SSW.								
29.95	Center shaft of windmill, mkd. 10R-3, bears North, 26.05 chs. dist.								
33.68	Barbed wire fence, bears SSE and NNW.								
33.90	Trail road, bears SSE and NNW.								
37.38	NW cor. of a concrete block house, 30 x 16 ft., bears South, 3 lks. dist., long side bears SSW.								
37.65	Barbed wire fence, bears NNE and SSW.								
39.965	Point for the 1/4 sec. cor. of secs. 16 and 21.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.								

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T30N R26E S16 1/4 — S21 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
41.90	Center of a hexagonal hogan, 18 ft. diam., bears North, 17.60 chs. dist.
42.60	SW cor. of a stucco house, 50 x 26 ft., bears North, 16.45 chs. dist., long side bears N.
43.12	Barbed wire fence, bears ESE and WNW.
44.67	Barbed wire fence, bears NNE and SSW.
53.57	Barbed wire fence, bears N. and S.
56.70	Power line, bears N. and S.
57.25	Trail road, bears N. and S.
67.00	Bis-ii-ah Wash, 600 lks. wide, 5 ft. deep, drains NNW.
79.93	The cor. of secs. 16, 17, 20, and 21. Land, nearly level. Soil, sand and clay. No timber; native grasses.
	N. 0°03' W., bet. secs. 16 and 17. Over nearly level land.
14.30	Bis-ii-ah Wash, 10 lks. wide, 3 ft. deep, drains W.
16.14	Barbed wire fence, bears E. and W.
19.64	Barbed wire fence, bears NNE and SSW.
25.72	Barbed wire fence, bears ENE and WSW.
26.30	Graded road, 38 lks. wide, bears NE and SW.

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
30.10	Nazlini Wash, 10 chs. wide, 4 ft. deep, drains SW.										
36.27	Barbed wire fence, bears E. and W.										
40.00	Point for the 1/4 sec. cor. of secs. 16 and 17.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T30N R26E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S17</td><td style="text-align: center;">S16</td></tr> <tr><td colspan="2" style="text-align: center;">1991</td></tr> </table>	T30N R26E		1/4		S17	S16	1991			
T30N R26E											
1/4											
S17	S16										
1991											
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.										
50.65	Trail road, bears NNE and SSW.										
51.32	Barbed wire fence, bears ENE and WSW.										
65.47	Barbed wire fence, bears NNE and SSW.										
80.00	Point for the cor. of secs. 8, 9, 16, and 17.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T30N R26E</td></tr> <tr><td style="text-align: center;">S 8</td><td style="text-align: center;">S 9</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S17</td><td style="text-align: center;">S16</td></tr> <tr><td colspan="2" style="text-align: center;">1991</td></tr> </table>	T30N R26E		S 8	S 9	-----		S17	S16	1991	
T30N R26E											
S 8	S 9										

S17	S16										
1991											
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.										
	Cor. is located in a trail road, bears SSE and NNW.										
	Land, nearly level. Soil, sand and clay. No timber; native grasses.										
	From the cor. of secs. 9, 10, 15, and 16.										

60
BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	West, bet. secs. 9 and 16.
	Over nearly level land.
39.97	Point for the 1/4 sec. cor. of secs. 9 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T30N R26E
	S 9
	1/4 —
	S16
	1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
79.94	The cor. of secs. 8, 9, 16, and 17.
	Land, nearly level.
	Soil, sand and clay.
	No timber; native grasses.
	N. 0°03' W., bet. secs. 8 and 9.
	Over nearly level land.
22.93	Barbed wire fence, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 9.
	Set a magnet in a 1 x 1 x 2 5/8 ins. white plastic case, 24 ins. below the surface of the ground.
	from which
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, for a reference monument, bears S. 35° E., 275.0 ft. dist., with brass cap mkd. T30N R26E 1/4 S9 RM 275.0 FT TO COR 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, for a reference monument, bears N. 35° W., 350.0 ft. dist., with brass cap mkd. T30N R26E 1/4 S8 RM 350.0 FT TO COR 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in Nazlini Wash, 850 lks. wide, 5 ft. deep, drains NNE, 455 lks. E. of W. bank.</p>								
80.00	<p>Point for the cor. of secs. 4, 5, 8, and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T30N R26E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 5</td> <td style="padding: 2px 5px;">S 4</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 8</td> <td style="padding: 2px 5px;">S 9</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sand and clay. No timber; native grasses.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over nearly level land.</p>	T30N R26E		S 5	S 4	S 8	S 9	1991	
T30N R26E									
S 5	S 4								
S 8	S 9								
1991									
11.60	Underground gas pipeline, bears SSE and NNW.								
16.10	Graded road, 30 lks. wide, bears SSE and NNW.								
22.75	Center of a hexagonal hogan, 20 ft. diam., bears South, 20.75 chs. dist.								
26.20	Center of a hexagonal hogan, 16 ft. diam., bears South, 17.95 chs. dist.								

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
26.50	NW cor. of a log house, 40 x 15 ft., bears South, 18.80 chs. dist., long side bears S.
26.75	NW cor. of a wood frame house, 30 x 15 ft., bears South, 11.50 chs. dist., long side bears S.
29.00	NW cor. of a stucco house, 35 x 15 ft., bears South, 16.10 chs. dist., long side bears S.
29.35	NW cor. of a wood frame house, 15 x 12 ft., bears South, 10.35 chs. dist., long side bears S.
34.65	NW cor. of a wood frame house, 32 x 25 ft., bears South, 16.45 chs. dist., long side bears S.
39.97	Point for the 1/4 sec. cor. of secs. 4 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T30N R26E S 4 1/4 — S 9 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
40.30	NE cor. of a stucco house, 40 x 15 ft., bears South, 7.25 chs. dist., long side bears S.
65.00	Nazlini Wash, 12 chs. wide, 4 ft. deep, drains N.
79.94	The cor. of secs. 4, 5, 8, and 9. Land, nearly level. Soil, sand and clay. No timber; native grasses.
	N. 0°06' W., bet. secs. 4 and 5.
	Over nearly level land.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5.

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T30N R26E 1/4 S 5 S 4 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
69.00	Wash, 225 lks. wide, 3 ft. deep, drains E.
79.93	The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described.
	<p>Land, nearly level. Soil, sand and clay. No timber; native grasses.</p>
	<p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T30N R26E S31 S32 S6 S5 T29N 1991.</p>
	N. 0°03' W., bet. secs. 31 and 32.
	Over nearly level land.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T30N R26E 1/4 S31 S32 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 29, 30, 31, and 32.

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>										
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>T30N</td> <td>R26E</td> </tr> <tr> <td>S30</td> <td>S29</td> </tr> <tr> <td>S31</td> <td>S32</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T30N	R26E	S30	S29	S31	S32	1991			
T30N	R26E										
S30	S29										
S31	S32										
1991											
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>										
	<p>Land, nearly level. Soil, sand and clay. No timber; native grasses.</p>										
	<p>From the cor. of secs. 28, 29, 32, and 33.</p>										
	<p>S. 89°59' W., bet. secs. 29 and 32.</p>										
	<p>Over nearly level land.</p>										
14.15	<p>Trail road, bears N. and S.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p>										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>										
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>T30N</td> <td>R26E</td> </tr> <tr> <td></td> <td>S29</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S32</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T30N	R26E		S29	1/4	—		S32	1991	
T30N	R26E										
	S29										
1/4	—										
	S32										
1991											
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>										
80.00	<p>The cor. of secs. 29, 30, 31, and 32.</p>										
	<p>Land, nearly level. Soil, sand and clay. No timber; native grasses.</p>										

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	S. 89°58' W., bet. secs. 30 and 31.
	Over nearly level land.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T30N R26E S30 1/4 — S31 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Thence over rugged land, on ascent from Beautiful Valley.
62.40	W. rim of Beautiful Valley, bears N. and S.
	Thence over nearly level land.
65.05	E. right-of-way fence of U.S. Highway 191, barbed wire, 6 strands, parallels highway.
66.62	Center of U.S. Highway 191, asphalt pavement, 45 lks. wide, bears SSE and NNW.
68.15	W. right-of-way fence of U.S. Highway 191, barbed wire, 6 strands, parallels highway..
70.90	Power line, bears SSE and NNW.
79.43	The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T30N R26E S25 S30 S36 S31 1991.
	Land, nearly level and rugged.
	Soil, sand and clay.
	No timber; native grasses.

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over nearly level land.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T30N R26E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S30</td><td style="padding: 0 5px;">S29</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T30N R26E		1/4		S30	S29	1991			
T30N R26E											
1/4											
S30	S29										
1991											
71.60	<p>Graded road, 27 lks. wide, bears SE and NW.</p>										
80.00	<p>Point for the cor. of secs. 19, 20, 29, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T30N R26E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S19</td><td style="padding: 0 5px;">S20</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S30</td><td style="padding: 0 5px;">S29</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sand and clay. No timber; native grasses.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>S. 89°59' W., bet. secs. 20 and 29.</p> <p>Over nearly level land.</p>	T30N R26E		S19	S20			S30	S29	1991	
T30N R26E											
S19	S20										
S30	S29										
1991											

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
12.50	Wash, 45 lks. wide, 4 ft. deep, drains N.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T30N R26E S20 1/4 — S29 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.00	The cor. of secs. 19, 20, 29, and 30.
	Land, nearly level. Soil, sand and clay. No timber; native grasses.
	S. 89°57' W., bet. secs. 19 and 30.
	Over nearly level land.
10.40	Graded road, 30 lks. wide, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled with a collar of stone, with brass cap mkd.
	T30N R26E S19 1/4 — S30 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located near foot of ascent from Beautiful Valley.

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Thence enter rugged land on ascent from Beautiful Valley.
58.00	W. rim of Beautiful Valley, bears N. and S.
	Thence enter nearly level land.
74.70	E. right-of-way fence of U.S. Highway 191, barbed wire, 6 strands, parallels highway.
76.21	Center of U. S. Highway 191, asphalt pavement, 45 lks. wide, bears SSE and NNW.
77.73	W. right-of-way fence of U.S. Highway 191, barbed wire, 6 strands, parallels highway.
79.36	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above ground, and a mound of stone, 3 ft. base, to top, with brass cap mkd. T30N R25E R26E S24 S19 S25 S30 1991.
	Land, nearly level and rugged. Soil, sand and clay. No timber; native grasses.
	From the cor. of secs. 19, 20, 29, and 30.
	N. 0°03' W., bet. secs. 19 and 20.
	Over nearly level land.
30.40	Graded road, 38 lks. wide, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T30N R26E 1/4 S19 S20 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	Point for the cor. of secs. 17, 18, 19, and 20.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T30N</td> <td>R26E</td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> <tr> <td colspan="2" style="text-align: center;"> </td> </tr> <tr> <td>S19</td> <td>S20</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T30N	R26E	S18	S17			S19	S20	1991	
T30N	R26E										
S18	S17										
S19	S20										
1991											
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.										
	Land, nearly level. Soil, sand and clay. No timber; native grasses.										
	From the cor. of secs. 16, 17, 20, and 21.										
	S. 89°58' W., bet. secs. 17 and 20.										
	Over nearly level land.										
6.30	Wash, 53 lks. wide, 3 ft. deep, drains NNE.										
9.80	Same wash, 30 lks. wide, 4 ft. deep, drains SE.										
12.05	Same wash, 53 lks. wide, 4 ft. deep, drains NE.										
16.00	Trail road, bears NNW on curve to left.										
20.67	SW cor. of a stucco house, 35 x 18 ft., bears North, 126 lks. dist., long side bears NNE.										
27.50	SE cor. of a stucco house, 18 x 18 ft., bears North, 11.85 chs. dist., long side bears NNE.										
33.40	Graded road, 27 lks. wide, bears NNE and SSW.										
40.00	Point for the 1/4 sec. cor. of secs. 17 and 20.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.										

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T30N R26E S17 1/4 — S20 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
46.85	Trail road, bears ENE and WSW.
52.95	Trail road, bears ESE and WNW.
67.20	Center of a hexagonal hogan, 18 ft. diam., bears North, 5.25 chs. dist.
68.60	SE cor. of a wood frame house, 35 x 25 ft., bears North, 6.80 chs. dist., long side bears NNE.
69.00	Center of a hexagonal hogan, 18 ft. diam., bears North, 6.95 chs. dist.
80.00	The cor. of secs. 17, 18, 19, and 20. Land, nearly level. Soil, sand and clay. No timber; native grasses.
	S. 89°57' W., bet. secs. 18 and 19. Over nearly level land.
40.00	True point for the 1/4 sec. cor. of secs. 18 and 19, falls on steep N. slope of a clay outcrop, impracticable to monument.
41.25	Point selected for the witness cor. to the 1/4 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	WC T30N R26E S18 1/4 → S19 1991

Survey of the Subdivisional Lines,
 T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Thence enter rugged land, on ascent from Beautiful Valley.</p>
49.40	<p>W. rim of Beautiful Valley, bears N. and S.</p>
61.70	<p>Trail road, bears N. and S.</p>
79.29	<p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. T30N R25E R26E S13 S18 S24 S19 1991.</p>
	<p>Land, nearly level and rugged. Soil, sand and clay. No timber; native grasses.</p>
	<hr/> <p>From the cor. of secs. 17, 18, 19, and 20. N. 0°03' W., bet. secs. 17 and 18. Over rolling hills.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R26E 1/4 S18 S17 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 7, 8, 17, and 18.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>T30N</td> <td>R26E</td> </tr> <tr> <td>S 7</td> <td>S 8</td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling hills. Soil, sand and clay. No timber; native grasses.</p> <hr/> <p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>S. 89°58' W., bet. secs. 8 and 17.</p> <p>Over nearly level land.</p>	T30N	R26E	S 7	S 8	S18	S17	1991			
T30N	R26E										
S 7	S 8										
S18	S17										
1991											
11.00	Nazlini Wash, 455 lks. wide, 5 ft. deep, drains N.										
39.99	Point for the 1/4 sec. cor. of secs. 8 and 17.										
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>T30N</td> <td>R26E</td> </tr> <tr> <td>S 8</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S17</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>	T30N	R26E	S 8		1/4	—	S17		1991	
T30N	R26E										
S 8											
1/4	—										
S17											
1991											
79.98	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 7, 8, 17, and 18.</p> <p>Land, nearly level. Soil, sand and clay. No timber; native grasses.</p> <hr/> <p>S. 89°57' W., bet. secs. 7 and 18.</p> <p>Over rugged land on ascent from Beautiful Valley.</p>										

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
23.50	Wash, 45 lks. wide, 1 ft. deep, drains NE.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T30N R26E S 7 1/4 — S18 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
79.21	The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with the surface of the ground, with brass cap mkd. T30N R25E R26E S12 S7 S13 S18 1991.
	Land, rugged. Soil, sand and clay. No timber; native grasses.
	<hr/>
	From the cor. of secs. 7, 8, 17, and 18.
	N. 0°03' W., bet. secs. 7 and 8.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T30N R26E 1/4 S 7 S 8 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 5, 6, 7, and 8.

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="868 388 1015 535"> <tr><td>T30N</td><td>R26E</td></tr> <tr><td>S 6</td><td>S 5</td></tr> <tr><td>S 7</td><td>S 8</td></tr> <tr><td colspan="2">1991</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sand and clay. No timber; native grasses.</p>	T30N	R26E	S 6	S 5	S 7	S 8	1991			
T30N	R26E										
S 6	S 5										
S 7	S 8										
1991											
	<hr/> <p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>S. 89°58' W., bet. secs. 5 and 8.</p> <p>Over nearly level land.</p>										
39.97	<p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="868 1186 1015 1333"> <tr><td>T30N</td><td>R26E</td></tr> <tr><td>S 5</td><td>—</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 8</td><td>—</td></tr> <tr><td colspan="2">1991</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T30N	R26E	S 5	—	1/4	—	S 8	—	1991	
T30N	R26E										
S 5	—										
1/4	—										
S 8	—										
1991											
52.90	<p>Wash, 70 lks. wide, 2 ft. deep, drains NNE.</p>										
79.94	<p>The cor. of secs. 5, 6, 7, and 8.</p> <p>Land, rolling. Soil, sand and clay. No timber; native grasses.</p> <hr/>										

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>S. 89°57' W., bet. secs. 6 and 7.</p> <p>Over rugged land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R26E S 6 1/4 — S 7 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
79.14	<p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. T30N R25E R26E S1 S6 S12 S7 1991.</p>
	<p>Land, rolling. Soil, sand and clay. No timber; native grasses.</p>
	<p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0°10' W., bet. secs. 5 and 6.</p> <p>Over rugged land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T30N R26E 1/4 S 6 S 5 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

BOOK 5376

Survey of the Subdivisional Lines,
T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.95	<p>The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., hereinbefore described.</p>
	<p>Land, rugged. Soil, sand and clay. No timber; native grasses.</p>
	<hr/> <p>GENERAL DESCRIPTION</p> <hr/>
	<p>The area surveyed is within the Navajo Indian Reservation, is approximately 12 miles south of Chinle, Arizona. The elevation varies from 5,600 to 6,200 feet above sea level.</p>
	<p>U.S. Highway 191 enters the township in section 31 and exits in section 19. Navajo Route 27, a graded road, passes N. and S. through the center of the township. Numerous other graded and trail roads provide access to most of the township.</p>
	<p>The soil varies from sand and clay to rocky clay and rock, with the eastern and western portions being rugged. The drainage is northerly, with Nazlini and Bis-ii-ah Washes being the principal drainages.</p>
	<p>The timber is mainly in the eastern portion, and consists of light piñon and juniper. The vegetation is of poor quality and mainly consists of native grasses and cacti.</p>
	<p>There is no mining, and very little agricultural activity, mainly consisting of small sheep herds. There are a large number of dwellings in the center of the township. There is no ground water to be found, except for a few wells.</p>
	<p>The mean magnetic declination is 12 1/2° E., with no local attractions.</p> <hr/>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Kenneth D. Roy	Cadastral Surveyor-in-Training
Edward Clarke	Engineering Technician
Barney Woodie	Engineering Technician

CERTIFICATE OF SURVEY

I, Steve D. Cully, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 22nd day of November, 1989, I have surveyed the east and north boundaries, and the subdivisional lines of Township 30 North, Range 26 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

1/20/93
(Date)

Steve D Cully
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the east and north boundaries, and the subdivisional lines of Township 30 North, Range 26 East, Gila and Salt River Meridian, Arizona, executed by Steve D. Cully, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

FEB 22 1993
(Date)

James P. Kelly
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 30 N., R. 26 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____~~
~~(Date)~~

~~_____~~
~~(Chief Cadastral Surveyor of Arizona)~~