

ORIGINAL

1

BOOK 5403

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE
SURVEY OF

THE SIXTH GUIDE MERIDIAN EAST,

(WEST BOUNDARY),

THE EAST BOUNDARY

AND

THE SUBDIVISIONAL LINES

OF

TOWNSHIP 32 NORTH, RANGE 25 EAST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

Leonard R. Sandoval, Cadastral Surveyor

Under special instructions dated November 22, 1989, approved November 22, 1989, which provided for the surveys included under Group Number 715 and assignment instructions dated November 22, 1989.

Survey commenced February 7, 1990

Survey completed December 27, 1991

INDEX DIAGRAM

TOWNSHIP 32 NORTH, RANGE 25 EAST,

70 9 6	70 69 5	57 56 4	48 47 3	39 38 2	29 28 1 16
68 8 7	67 66 8	55 54 9	46 45 10	37 36 11	27 26 12 15
66 7 18	65 64 17	53 53 16	45 44 15	36 35 14	25 24 13 14
64 6 19	63 62 20	52 51 21	43 43 22	34 33 23	24 22 24 12
61 5 30	60 60 29	51 50 28	42 41 27	32 31 26	21 20 25 11
59 4 31	58 57 32	49 48 33	40 39 34	30 29 35	19 18 36 10

T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>The following field notes describe the survey of the Sixth Guide Meridian East, (west boundary), the east boundary and the subdivisional lines of Township 32 North, Ranges 25 East, Gila and Salt River Meridian, Arizona.</p> <p>The survey was executed in accordance with the specifications as set forth in the <u>Manual of Surveying Instructions, 1973</u>, and the <u>Special Instructions</u> dated November 22, 1989, for Group No. 715, Arizona.</p> <p>This survey supersedes portions of Townships 5 and 6 North, Range 11 West of the Navajo Special Meridian. The west boundary of the 1868 Navajo Reservation is identified, where possible, for historical purposes only, and has no legal significance in this survey. The survey history of that portion of the superseded Navajo Special Meridian is included in these notes for informational purposes only.</p> <p>The west boundary of the Navajo Indian Reservation and the boundaries and subdivision of Townships 5 and 6 North, Range 11 West, Navajo Special Meridian, were surveyed by E.N. Darling in 1869. The west boundary of the Navajo Indian Reservation was dependently resurveyed by L.E. Sechrist in 1919-20.</p> <p>The south boundary of the township was surveyed by Leonard R. Sandoval in 1990-91. The Eighth Standard Parallel North, (north boundary), thru Ranges 24 and 25 East was surveyed by Leonard R. Sandoval in 1989-90.</p> <p>The closing cors. and 1/4 sec. cors. of minimum control on the Eighth Standard Parallel North (north boundary) were established by tying each direction to the controlling standard cors. For simplicity, only ties to the nearest cor. are given in the field notes and shown on the plat.</p> <p>The directions of lines were determined by direct hour angle observations on the sun and refer to the true meridian. Distances and angles were measured using Lietz SET-4 and Zeiss ELTA-3 electronic total station instruments.</p> <p>The geographic position of the southeast corner of the township, as determined from a tie made to U.S. Coast and Geodetic Survey triangulation station "BEAUTIFUL 1951", hereinafter described, is as follows:</p> <p>Latitude: 36°07'42.51" N. Longitude: 109°36'01.71" W. NAD27</p> <p>The mean magnetic declination as taken from the 1985 magnetic declination map published by U.S. Geological Survey, is 12 1/2° E.</p>
--------	---

Survey of the Sixth Guide Meridian East,
 (West Boundary),
 T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Beginning at the cor. of Tps. 31 and 32 N., Rs. 24 and 25 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T32N R24E R25E S1 S6 S31 S36 T31N 1990.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R24E R25E 1/4 S36 S31 1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R24E R25E S25 S30 --- S36 S31 1990</p> </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay with sandstone outcrops. No timber; brush and native grasses.</p> <hr/>

Survey of the Sixth Guide Meridian East,
 (West Boundary),
 T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>North, bet. secs. 25 and 30.</p>												
	<p>Over rolling land.</p>												
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p>												
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T32N</td></tr> <tr><td style="text-align: center;">R24E</td><td style="text-align: center;">R25E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S30</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table>	T32N		R24E	R25E	1/4		S25	S30	1990			
T32N													
R24E	R25E												
1/4													
S25	S30												
1990													
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>												
76.00	<p>Enter sandstone outcrops of Red Rock Rim.</p>												
80.00	<p>Point for the cor. of secs. 19, 24, 25, and 30.</p>												
	<p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, flush with surface of sandstone bedrock, with top mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T32N</td></tr> <tr><td style="text-align: center;">R24E</td><td style="text-align: center;">R25E</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S30</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table>	T32N		R24E	R25E	S24	S19	-----		S25	S30	1990	
T32N													
R24E	R25E												
S24	S19												

S25	S30												
1990													
	<p>Deposit a magnet, 1 in. long, 7/8 in. diam., in the drill hole beneath the brass tablet.</p>												
	<p>Land, rolling. Soil, sandy clay and sandstone outcrops. No timber; brush and native grasses.</p>												
	<hr/>												

Survey of the Sixth Guide Meridian East,
 (West Boundary),
 T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	North, bet. secs. 19 and 24.												
	Over rolling and broken land.												
38.70	Wash at bottom of canyon, drains NE.												
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24.												
	Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, flush with surface of sandstone bedrock, with top mkd.												
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T32N</td></tr> <tr><td style="text-align: center;">R24E</td><td style="text-align: center;">R25E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table>	T32N		R24E	R25E	1/4		S24	S19	1990			
T32N													
R24E	R25E												
1/4													
S24	S19												
1990													
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case in the drill hole beneath the brass tablet.												
	Cor. is located on a ledge on N. side of sandstone canyon, drains NE.												
80.00	Point for the cor. of secs. 13, 18, 19, and 24.												
	Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, flush with surface of sandstone bedrock, with top mkd.												
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T31N</td></tr> <tr><td style="text-align: center;">R24E</td><td style="text-align: center;">R25E</td></tr> <tr><td style="text-align: center;">S13</td><td style="text-align: center;">S18</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table>	T31N		R24E	R25E	S13	S18	-----		S24	S19	1990	
T31N													
R24E	R25E												
S13	S18												

S24	S19												
1990													
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case in the drill hole beneath the brass tablet.												

Survey of the Sixth Guide Meridian East,
 (West Boundary),
 T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Land, rolling and broken. Soil, sandstone bedrock and sand. No timber; sparse brush and native grasses.</p> <hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over broken and rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T32N R24E R25E 1/4 S13 S18 1990 </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>59.80 High voltage transmission line, bears NE and SW.</p> <p>62.65 Trail road, bears NE and SW.</p> <p>80.00 Point for the cor. of secs. 7, 12, 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T32N R24E R25E S12 S 7 <hr style="width: 50%; margin: 0 auto;"/> S13 S18 1990 </div> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, broken and rolling. Soil, sandy clay with sandstone bedrock in southern portion. No timber; brush and native grasses.</p> <hr/>
--------	--

Survey of the Sixth Guide Meridian East,
(West Boundary),
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	North, bet. secs. 7 and 12.												
	Over rolling and broken land.												
24.20	Graded road, 45 lks. wide, bears ENE and WSW.												
40.00	Point for the 1/4 sec. cor. of secs. 7 and 12.												
	Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, flush with surface of sandstone bedrock, with top mkd.												
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T32N</td></tr> <tr><td style="text-align: center;">R24E</td><td style="text-align: center;">R25E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table>	T32N		R24E	R25E	1/4		S12	S 7	1990			
T32N													
R24E	R25E												
1/4													
S12	S 7												
1990													
	Deposit a magnet, 1 in. long, 7/8 in. diam., in the drill hole beneath the brass tablet.												
80.00	Point for the cor. of secs. 1, 6, 7, and 12.												
	Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, flush with surface of sandstone bedrock, with top mkd.												
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T32N</td></tr> <tr><td style="text-align: center;">R24E</td><td style="text-align: center;">R25E</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">1990</td></tr> </table>	T32N		R24E	R25E	S 1	S 6	-----		S12	S 7	1990	
T32N													
R24E	R25E												
S 1	S 6												

S12	S 7												
1990													
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case in the drill hole beneath the brass tablet.												
	Land, rolling and broken.												
	Soil, sandy clay and sandstone bedrock.												
	No timber; sparse brush and native grasses.												

Survey of the Sixth Guide Meridian East,
 (West Boundary),
 T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	North, bet. secs. 1 and 6.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 6.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T32N R24E R25E 1/4 S 1 S 6 1990</p>
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
74.60	Trail road, bears NNE and SSW.
80.61	Point for the closing cor. of T. 32 N., Rs. 24 and 25 E., at intersection with the Eighth Standard Parallel North, the N. bdy. of the Tp.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T33N R24E S36</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S 1 S 6 R24E R25E T32N CC 1990</p>
	Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	From this cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 33 N., R. 24 E., bears West, 15.04 chs. dist., monumented with a brass tablet, 3 1/4 ins. diam., cemented in place, flush with surface of sandstone bedrock, with top mkd. SC T33N R24E 1/4 S36 1990.

Survey of the Sixth Guide Meridian East,
 (West Boundary),
 T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Land, rolling. Soil, sandy clay and sandstone bedrock. No timber; brush and native grasses.</p> <hr/> <p style="text-align: center;">Survey of the East Boundary, T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 31 and 32 N., Rs. 25 and 26 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T32N R25E R26E S1 S6 S31 S36 T31N 1991.</p> <p>From this cor. point, U.S. Coast and Geodetic Survey triangulation station "BEAUTIFUL 1951", with published latitude of 36°04'12.342" N. and longitude of 109°36'31.975" W., NAD27, bears S. 6°40.0' W., 324.285 chs. dist., monumented with a standard brass disk, 3 1/2 ins. diam., cemented in place, flush with surface of sandstone bedrock, with top mkd. BEAUTIFUL 1951 and a triangle.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over nearly level land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T32N R25E R26E 1/4 S36 S31 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
68.40	<p>Power line, bears NE and SW.</p>
79.33	<p>SE right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.</p>
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the East Boundary,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<div style="text-align: center;"> <table border="1" style="margin: auto;"> <tr><td colspan="2">T32N</td></tr> <tr><td>R25E</td><td>R26E</td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S36</td><td>S31</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45°00' E., 25.0 ft. dist., with brass cap mkd. T32N R26E S31 RM 25.0 FT TO COR 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45°00' W., 180.0 ft. dist., with brass cap mkd. T32N R26E S25 RM 180.0 FT TO COR 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay. No timber; brush and native grasses.</p> <hr/> <p>North, bet. secs. 25 and 30.</p> <p>Over nearly level land.</p> <p>1.57 Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears NE and SW.</p> <p>3.63 NW right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.</p> <p>9.70 Power line, bears NE and SW.</p> <p>31.05 Trail road, bears NNE and SSW.</p>	T32N		R25E	R26E	S25	S30			S36	S31	1991	
T32N													
R25E	R26E												
S25	S30												
S36	S31												
1991													

Survey of the East Boundary,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R25E R26E 1/4 S25 S30 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
47.60	<p>Graded road, 23 lks. wide, bears ESE and WNW.</p>
56.88	<p>Center of hospital road, asphalt pavement, 60 lks. wide, bears SSE and NNW.</p>
69.20	<p>Graded road, 38 lks. wide, bears ENE and WSW.</p>
80.00	<p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R25E R26E S24 S19 ----- S25 S30 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay. No timber; brush and native grasses.</p>
	<p>North, bet. secs. 19 and 24.</p>
	<p>Over gently rolling land.</p>

Survey of the East Boundary,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
5.75	Graded road, 45 lks. wide, bears NNE and SSW.
5.95	Underground pipeline, bears ESE and WNW.
6.30	Power line, bears ESE and WNW.
11.40	SE cor. of wood frame house, 40 x 26 ft., bears West, 5.65 chs. dist., long side bears NNE.
14.00	Power line, bears NNE and SSW.
14.80	Power line, bears ESE and WNW.
15.40	Trail road, bears E. and W.
25.50	Wash, 38 lks. wide, 5 ft. deep, drains E.
32.40	Trail road, bears ESE and WNW.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T32N R25E R26E 1/4 S24 S19 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
45.85	Trail road, bears E. and W.
63.50	Graded road, 38 lks. wide, bears ENE and WSW.
76.45	Trail road, bears NE and SW.
80.00	Point for the cor. of secs. 13, 18, 19, and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the East Boundary,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<table border="1"> <tr><td colspan="2">T32N</td></tr> <tr><td>R25E</td><td>R26E</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td colspan="2">1991</td></tr> </table>	T32N		R25E	R26E	S13	S18	-----		S24	S19	1991	
T32N													
R25E	R26E												
S13	S18												

S24	S19												
1991													
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, an iron post, 1 in. diam., firmly set, flush with the surface of the ground, bears S. 86°34' E., 4.17 chs. dist., with stainless steel cap mkd. NAVAJO LAND DEVELOPMENT LA 36.10 LO 109.36.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.</p>												
	<hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over nearly level land.</p>												
30.20	Trail road, bears ESE in curve to left.												
40.00	Point for the 1/4 sec. cor. of secs. 13 and 18.												
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												
	<table border="1"> <tr><td colspan="2">T32N</td></tr> <tr><td>R25E</td><td>R26E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2">1991</td></tr> </table>	T32N		R25E	R26E	1/4		S13	S18	1991			
T32N													
R25E	R26E												
1/4													
S13	S18												
1991													
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>												
45.60	Trail road, bears NE and SW.												
74.20	Trail road, bears ESE and WNW.												
80.00	Point for the cor. of secs. 7, 12, 13, and 18.												

Survey of the East Boundary,
 T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="812 378 1006 577"> <tr><td colspan="2" style="text-align:center">T32N</td></tr> <tr><td style="text-align:center">R25E</td><td style="text-align:center">R26E</td></tr> <tr><td style="text-align:center">S12</td><td style="text-align:center">S 7</td></tr> <tr><td colspan="2" style="text-align:center">-----</td></tr> <tr><td style="text-align:center">S13</td><td style="text-align:center">S18</td></tr> <tr><td colspan="2" style="text-align:center">1991</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay. No timber; brush and native grasses.</p>	T32N		R25E	R26E	S12	S 7	-----		S13	S18	1991	
T32N													
R25E	R26E												
S12	S 7												

S13	S18												
1991													
	<hr/>												
	<p>North, bet. secs. 7 and 12.</p>												
	<p>Over nearly level land.</p>												
18.80	<p>NE cor. of a log house, 44 x 13 ft., bears West, 13.25 chs. dist., long side bears S.</p>												
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p>												
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												
	<table border="1" data-bbox="812 1218 1006 1407"> <tr><td colspan="2" style="text-align:center">T32N</td></tr> <tr><td style="text-align:center">R25E</td><td style="text-align:center">R26E</td></tr> <tr><td colspan="2" style="text-align:center">1/4</td></tr> <tr><td style="text-align:center">S12</td><td style="text-align:center">S 7</td></tr> <tr><td colspan="2" style="text-align:center">1991</td></tr> </table>	T32N		R25E	R26E	1/4		S12	S 7	1991			
T32N													
R25E	R26E												
1/4													
S12	S 7												
1991													
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>												
45.00	<p>Graded road, 30 lks. wide, bears ESE and WNW.</p>												
80.00	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p>												

Survey of the East Boundary,
 T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T32N</td></tr> <tr><td>R25E</td><td>R26E</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S12</td><td>S 7</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay. No timber; brush and native grasses.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over nearly level land.</p>	T32N		R25E	R26E	S 1	S 6	<hr/>		S12	S 7	1991	
T32N													
R25E	R26E												
S 1	S 6												
<hr/>													
S12	S 7												
1991													
14.20	SE cor. of a wood frame house, 34 x 24 ft., bears West, 17.15 chs. dist., long side bears N.												
17.90	SE cor. of a wood frame house, 32 x 24 ft., bears West, 10.70 chs. dist., long side bears N.												
18.05	SE cor. of a wood frame house, 36 x 24 ft., bears West, 14.75 chs. dist., long side bears WSW.												
19.30	SE cor. of a L-shaped stucco house, with overall dimensions of 48 x 40 ft., bears West, 14.80 chs. dist., long side bears N.												
19.40	NE cor. of a stucco house, 14 x 14 ft., bears West, 17.10 chs. dist., sides bear S. and W.												
21.70	NE cor. of a wood frame house, 30 x 16 ft., bears West, 20.20 chs. dist., long side bears S.												
26.15	SE cor. of a wood frame church, 84 x 40 ft., bears West, 9.55 chs. dist., long side bears N.												
27.10	NW cor. of a brick house, 42 x 20 ft., bears West, 4.15 chs. dist., long side bears SSW.												
29.65	NE cor. of a wood frame church, 54 x 30 ft., bears West, 9.70 chs. dist., long side bears W.												
32.70	Power line, bears ENE and WSW.												

Survey of the East Boundary,
 T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
35.75	Graded road, 38 lks. wide, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 6. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T32N R25E R26E 1/4 S 1 S 6 1991 </div>
	from which <div style="text-align: center;"> A power pole, mkd. 41, bears N. 77 1/4° E., 242 lks. dist., lines extending SSE and NNW. </div> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
48.25	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.
48.80	Power line, bears SSE and NNW.
52.51	Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears SSE and NNW.
56.30	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.
61.49	Telephone line, bears SSE and NNW.
73.01	Barbed wire fence, 6 strands, bears ENE and WSW.
80.75	Point for the closing cor. of T. 32 N., Rs. 25 and 26 E., at intersection with the Eighth Standard Parallel North, the N. bdy. of the Tp.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the East Boundary,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS					
	<p>T33N R25E S36</p> <hr style="width: 10%; margin: auto;"/> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">S 1</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 6</td> </tr> <tr> <td style="padding: 0 5px;">R25E</td> <td style="border-left: 1px solid black; padding: 0 5px;">R26E</td> </tr> </table> <p>T32N CC 1991</p>	S 1	S 6	R25E	R26E
S 1	S 6				
R25E	R26E				
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 33 N., R. 25 E., bears West, 13.02 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T33N R25E 1/4 S36 1990.</p> <p>Land, nearly level. Soil, sandy clay. No timber; brush and native grasses.</p>				
	<p>Survey of the Subdivisional Lines, T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona</p>				
	<p>From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T32N R25E S1 S2 S35 S36 T31N 1991.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over nearly level land.</p>				
5.83	SE right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.				
7.89	Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears NE and SW.				
9.95	NW right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.				
16.00	Power line, bears NE and SW.				
40.00	Point for the 1/4 sec. cor. of secs. 35 and 36.				

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R25E 1/4 S35 S36 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
75.20	<p>Trail road, bears NE and SW.</p>
78.80	<p>Trail road, bears ESE and WNW.</p>
80.00	<p>Point for the cor. of secs. 25, 26, 35, and 36.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R25E S26 S25 ----- S35 S36 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Land, nearly level. Soil, sandy clay. No timber; brush and native grasses.</p>
	<p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>N. 89°59' W., bet. secs. 25 and 36.</p>
	<p>Over nearly level land.</p>
1.70	<p>Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears NE and SW.</p>
3.95	<p>NW right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.</p>
10.60	<p>Power line, bears NE and SW.</p>

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
25.70	Trail road, bears ESE and WNW.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T32N R25E S25 1/4 — S36 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
74.90	Trail road, bears NE and SW.
80.00	The cor. of secs. 25, 26, 35, and 36.
	Land, nearly level. Soil, sandy clay. No timber; brush and native grasses.
	N. 0°01' W., bet. secs. 25 and 26.
	Over gently rolling land.
13.40	Trail road, bears E. and W.
19.20	Trail road, bears NNE and SSW.
36.50	Trail road, bears SSE and NNW.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T32N R25E 1/4 S26 S25 1991

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS									
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.								
52.30	SW cor. of a wood frame house, 20 x 10 ft., bears East, 10.65 chs. dist., long side bears N.								
53.49	Southernmost cor. of an octagonal wood frame hogan, 10 ft. sides, bears East, 13 lks. dist.								
55.58	SW cor. of a wood frame house, 20 x 16 ft., bears East, 1.86 chs. dist., long side bears N.								
63.00	SW cor. of a wood frame house, 40 x 24 ft., bears East, 12.10 chs. dist., long side bears N.								
80.00	Point for the cor. of secs. 23, 24, 25, and 26.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T32N R25E</td> </tr> <tr> <td style="text-align: center;">S23</td> <td style="text-align: center;">S24</td> </tr> <tr> <td style="text-align: center;">S26</td> <td style="text-align: center;">S25</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T32N R25E		S23	S24	S26	S25	1991	
T32N R25E									
S23	S24								
S26	S25								
1991									
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.</p>								
	<p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 24 and 25.</p> <p>Over rolling land.</p>								
4.00	Graded road, 45 lks. wide, bears NNE and SSW.								
14.75	Center of hospital road, asphalt pavement, 60 lks. wide, bears SE in curve to right.								

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
27.01	Intersect the E. side of an irregularly shaped hospital building, the southeastermost cor. bears SSE, 35 lks. dist.
40.00	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R25E S24 1/4 — S25 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
52.23	Chainlink fence, bears NNE and SSW.
52.45	SW cor. of Chinle Hospital Steering Committee Tract, as shown on Navajo Land Administration plat dated April 1, 1980, bears South, 74 lks. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 1 in. above ground, at the cor. of chainlink fences, bear NNE and ESE.
54.80	Trail road, bears NNE in curve to right.
67.60	Southwesternmost cor. of hexagonal wood frame hogan, 10 ft. sides, bears North, 3.70 chs. dist.
67.75	Southwesternmost cor. of octagonal wood frame hogan, 10 ft. sides, bears North, 3.20 chs. dist.
73.60	Trail road, bears N. and S.
80.00	<p>The cor. of secs. 23, 24, 25, and 26.</p> <p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
	N. 0°01' W., bet. secs. 23 and 24.
	Over rolling land.


Survey of the Subdivisional Lines,
 T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
18.95	SW cor. of a wood frame house, 25 x 16 ft., bears East, 6.45 chs. dist., long side bears E.
37.20	Graded road, 38 lks. wide, bears ESE and WNW.
38.90	Intersect circular water tank, the center of which bears ENE, 76 lks. dist.
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R25E 1/4 S23 S24 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	Cor. is located 13 1/2 lks. S. of barbed wire fence, bears E. and W.
47.25	SW cor. of a wood frame house, 30 x 25 ft., bears East, 4.15 chs. dist., long side bears N.
47.55	SE cor. of a wood frame house, 40 x 20 ft., bears West, 6.15 chs. dist., long side bears N.
80.00	<p>Point for the cor. of secs. 13, 14, 23, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R25E S14 S13 ----- S23 S24 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
 T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
	<p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>West, bet. secs. 13 and 24.</p>
	<p>Over rolling land.</p>
39.995	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R25E S13 1/4 — S24 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
79.99	<p>The cor. of secs. 13, 14, 23, and 24.</p>
	<p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 13 and 14.</p>
	<p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 14; falls on sheer cliff, where it is impractical to construct a permanent monument.</p>
	<p>From this cor. point, the selected point for the witness cor. to the 1/4 sec. cor. of secs. 13 and 14, bears S. 45°00' E., 2.50 chs. dist.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
 T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS									
80.00	<div style="text-align: center;">  <p>WC T32N R25E 1/4 S14 S13 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 11, 12, 13, and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T32N R25E</td><td></td></tr> <tr><td>S11 S12</td><td></td></tr> <tr><td>S14 S13</td><td></td></tr> <tr><td>1991</td><td></td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy clay and clay. No timber; brush and native grasses.</p>	T32N R25E		S11 S12		S14 S13		1991	
T32N R25E									
S11 S12									
S14 S13									
1991									
22.30 38.20 39.995	<hr/> <p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°59' W., bet. secs. 12 and 13.</p> <p>Over rolling land.</p> <p>Trail road, bears ESE and WNW.</p> <p>Trail road, bears NNE and SSW.</p> <p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								

Survey of the Subdivisional Lines,
 T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T32N R25E S12 1/4 — S13 1991</p>
79.99	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 11, 12, 13, and 14.</p> <p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
40.00	<p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
48.55	<p style="text-align: center;">T32N R25E 1/4 S11 S12 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Thence enter nearly level land of Chinle Valley.</p> <p>Southwesternmost cor. of a octagonal wood frame hogan, 8 ft. sides, bears East, 2.98 chs. dist.</p>
78.80	<p>Graded road, 30 lks. wide, bears ESE and WNW.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<div style="text-align: center;"> <table border="1"> <tr><td>T32N</td><td>R25E</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S11</td><td>S12</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 1.95 chs. E. of a graded road, 30 lks. wide, bears ESE and WNW.</p> <p>Land, rolling to nearly level. Soil, sandy clay. No timber; brush and native grasses.</p>	T32N	R25E	S 2	S 1			S11	S12	1991	
T32N	R25E										
S 2	S 1										
S11	S12										
1991											
	<p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 1 and 12.</p> <p>Over nearly level land.</p>										
16.25	Trail road, bears NNE and SSW.										
35.35	Trail road, bears NE and SW.										
39.995	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<div style="text-align: center;"> <table border="1"> <tr><td>T32N</td><td>R25E</td></tr> <tr><td>S 1</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S12</td><td></td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T32N	R25E	S 1		1/4	—	S12		1991	
T32N	R25E										
S 1											
1/4	—										
S12											
1991											
79.99	<p>The cor. of secs. 1, 2, 11, and 12.</p> <p>Land, nearly level Soil, sandy clay. No timber; brush and native grasses.</p>										

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°01' W., bet. secs. 1 and 2.
	Over nearly level land.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T32N R25E 1/4 S 2 S 1 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
51.85	Trail road, bears NE and SW.
80.75	Point for the closing cor. of secs. 1 and 2, at intersection with the Eighth Standard Parallel North, the N. bdy. of the Tp.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T33N R25E S35 ----- S 2 S 1 T32N R25E CC 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	From this cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 33 N., R. 25 E., bears West, 13.02 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T33N R25E 1/4 S35 1990.
	Land, nearly level.
	Soil, sandy clay.
	No timber; brush and native grasses.

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>The point for the 1/4 sec. cor. of sec. 1 only, T. 32 N., R. 25 E., at midpoint on the N. bdy. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E ----- 1/4 S 1 T32N R25E 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 35 and 36, T. 33 N., R. 25 E., bears West, 13.02 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T33N R25E S35 S36 1990.</p>
	<p>From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T32N R25E S2 S3 S34 S35 T31N 1991.</p> <p>From this cor. point, the 26 Mile Cor. of the 1869 survey of the W. bdy. of the Navajo Indian Reservation, bears N. 67°28' E., 50.64 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. NIR 26M 1920. As it is impracticable to bury the iron post, remove brass cap and mark AM on the N. side of the iron post.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over rolling land.</p>
37.65	Trail road, bears NNE and SSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
 T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T32N R25E 1/4 S34 S35 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
58.35	<p>Trail road, bears ENE and WSW.</p>
80.00	<p>Point for the cor. of secs. 26, 27, 34, and 35.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R25E S27 S26 ----- S34 S35 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
	<hr/> <p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>N. 89°59' W., bet. secs. 26 and 35.</p> <p>Over nearly level land.</p>
35.50	<p>SE cor. of a stucco house, 35 x 20 ft., bears North, 6.65 chs. dist., long side bears NNE; thence ascend over rolling and broken E. slope of Ventana Mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R25E S26 1/4 — S35 1991</p>

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the 27 Mile Cor. of the 1869 survey of the W. bdy. of the Navajo Indian Reservation, bears N. 17°53' E., 21.545 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. NIR 27M 1920. As it is impracticable to bury the iron post, remove brass cap and mark AM on the N. side of the iron post.</p>
60.10	E. rim of Ventana Mesa, bears NNE and SSW; thence across gently rolling land.
61.20	Trail road, bears NNE and SSW.
80.00	<p>The cor. of secs. 26, 27, 34, and 35.</p> <p>Land, nearly level to rolling and broken to gently rolling. Soil, sandy clay and clay. No timber; brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over rolling land.</p>
14.95	Trail road, bears ENE and WSW.
36.15	Trail road, bears NE and SW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R25E 1/4 S27 S26 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
54.05	Trail road, bears NNE and SSW.
67.60	Trail road, bears ENE and WSW.
68.30	Trail road, bears SSE and NNW.
80.00	Point for the cor. of secs. 22, 23, 26, and 27.

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R25E S22 S23 ----- S27 S26 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
	<hr/> <p>From the cor. of secs. 23, 24, 25, and 26.</p>
	<p>N. 89°59' W., bet. secs. 23 and 26.</p>
	<p>Over broken land.</p>
<p>24.40</p>	<p>E. rim of Ventana Mesa, bears N. and S.; thence over rolling land.</p>
<p>40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R25E S23 1/4 — S26 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located 1.75 chs. W. of trail road, bears ESE and WNW.</p>
<p>44.05</p>	<p>Trail road, bears NNE and SSW.</p>
<p>74.85</p>	<p>Trail road, bears SE and NW.</p>

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 22, 23, 26, and 27.</p> <p>Land, broken to rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over rolling land.</p>
5.10	Trail road, bears ESE and WNW.
27.95	Trail road, bears E. and W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R25E 1/4 S22 S23 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
51.30	Trail road, bears SE and NW.
80.00	<p>Point for the cor. of secs. 14, 15, 22, and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R25E S15 S14 ----- S22 S23 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 14, 23, and 24. N. 89°59' W., bet. secs. 14 and 23. Over rolling land.</p>
18.30	E. rim of Ventana Mesa, bears N. and S.
23.20	Graded road, 33 lks. wide, bears NNE and SSW.
27.90	Trail road, bears SE and NW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R25E S14 1/4 — S23 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the 29 Mile Cor. of the 1869 survey of the W. bdy. of the Navajo Indian Reservation, bears N. 15°26' E., 23.555 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. NIR 29M 1920. As it is impracticable to bury the iron post, remove brass cap and mark AM on the N. side of the iron post.</p>
47.75	Trail road, bears ENE and WSW.
68.10	Trail road, bears ESE and WNW.
80.00	The cor. of secs. 14, 15, 22, and 23.

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 14 and 15.</p>
	<p>Over rolling land.</p>
21.40	<p>Wash, 38 lks. wide, 4 ft. deep, drains NNW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R25E 1/4 S15 S14 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
71.60	<p>Trail road, bears NE and SW.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14, and 15.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R25E S10 S11 ----- S15 S14 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>N. 89°59' W., bet. secs. 11 and 14.</p> <p>Over broken land.</p>
11.10	E. rim of Ventana Mesa; thence over rolling land.
21.45	Trail road, bears SE and NW.
40.005	Point for the 1/4 sec. cor. of secs. 11 and 14.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R25E S11 1/4 — S14 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
60.70	Graded road, 38 lks. wide, bears SE and NW.
80.01	<p>The cor. of secs. 10, 11, 14, and 15.</p> <p>Land, broken to rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over rolling land.</p>
29.50	Graded road, 38 lks. wide, bears SSE and NNW.
30.95	Trail road, bears NNE and SSW.
34.75	Center shaft of windmill bears East, 2.75 chs. dist.
36.00	Trail road, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11.

Survey of the Subdivisional Lines,
 T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R25E 1/4 S10 S11 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 2, 3, 10, and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R25E S 3 S 2 ----- S10 S11 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
37.00	<p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>N. 89°59' W., bet. secs. 2 and 11.</p> <p>Over nearly level land.</p> <p>Ascend over Ventana Mesa badlands.</p>
40.005	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T32N R25E S 2 1/4 — S11 1991</p>
80.01	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 2, 3, 10, and 11.</p> <p>Land, nearly level to rugged. Soil, sandy clay and clay. No timber; brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over broken land.</p>
4.85	S. rim of a canyon, bears ENE and WSW.
9.50	Trail road, bears ENE and WSW.
10.90	Wash, 150 lks. wide, 4 ft. deep, drains ENE.
23.10	N. rim of a canyon, bears NNE and SSW; thence over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R25E 1/4 S 3 S 2 1991</p>
80.73	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the closing cor. of secs. 2 and 3, at intersection with the Eighth Standard Parallel North, the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">T33N R25E S34</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">S 3 S 2 T32N R25E CC 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 33 N., R. 25 E., bears West, 13.02 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T33N R25E 1/4 S34 1990.</p> <p>Land, broken to rolling. Soil, sandy clay. No timber; brush and native grasses.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 2 only, T. 32 N., R. 25 E., at midpoint on the N. bdy. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">1/4 S 2 T32N R25E 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 34 and 35, T. 33 N., R. 25 E., bears West, 13.02 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T33N R25E S34 S35 1990.</p> <hr/> <p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T32N R25E S3 S4 S33 S34 T31N 1991.</p>
--------	---

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°02' W., bet. secs. 33 and 34.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 33 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T32N R25E 1/4 S33 S34 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
42.90	Trail road, bears NE and SW.
58.60	Trail road, bears SE and NW.
71.10	Trail road, bears E. and W.
80.00	Point for the cor. of secs. 27, 28, 33, and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T32N R25E S28 S27 ----- S33 S34 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.
<hr/>	
	From the cor. of secs. 26, 27, 34, and 35.
	N. 89°59' W., bet. secs. 27 and 34.
	Over gently rolling land.

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
37.90	Trail road, bears NE and SW.
40.005	Point for the 1/4 sec. cor. of secs. 27 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T32N R25E S27 1/4 — S34 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
73.95	Trail road, bears NE and SW.
80.01	The cor. of secs. 27, 28, 33, and 34.
	Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.
	N. 0°02' W., bet. secs. 27 and 28.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T32N R25E 1/4 S28 S27 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 21, 22, 27, and 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<table border="1"> <tr> <td>T32N R25E</td> <td></td> </tr> <tr> <td>S21</td> <td>S22</td> </tr> <tr> <td>S28</td> <td>S27</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T32N R25E		S21	S22	S28	S27	1991			
T32N R25E											
S21	S22										
S28	S27										
1991											
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.</p>										
	<p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>N. 89°59' W., bet. secs. 22 and 27.</p> <p>Over gently rolling land.</p>										
6.55	Trail road, bears SE and NW.										
13.00	Center shaft of a windmill, No. 10T-531, bears North, 12.45 chs. dist.										
18.70	Trail road, bears NNE and SSW.										
22.10	Trail road, bears NE and SW.										
40.005	Point for the 1/4 sec. cor. of secs. 22 and 27.										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<table border="1"> <tr> <td>T32N R25E</td> <td></td> </tr> <tr> <td>S22</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S27</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T32N R25E		S22		1/4	—	S27		1991	
T32N R25E											
S22											
1/4	—										
S27											
1991											
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>										
80.01	<p>The cor. of secs. 21, 22, 27, and 28.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.</p>										

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°02' W., bet. secs. 21 and 22.
	Over gently rolling land.
30.85	Trail road, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T32N R25E 1/4 S21 S22 1991 </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 15, 16, 21, and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T32N R25E S16 S15 S21 S22 1991 </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 17 lks. S. of trail road, bears NE and SW.
	Land, gently rolling.
	Soil, sandy clay.
	No timber; brush and native grasses.
	<hr/>
	From the cor. of secs. 14, 15, 22, and 23.
	N. 89°59' W., bet. secs. 15 and 22.
	Over gently rolling land.
12.55	Trail road, bears NNE and SSW.

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
27.40	Trail road, bears NNE and SSW.
40.005	Point for the 1/4 sec. cor. of secs. 15 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T32N R25E S15 1/4 — S22 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.01	The cor. of secs. 15, 16, 21, and 22.
	<p>Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
	N. 0°02' W., bet. secs. 15 and 16.
	Over gently rolling land.
19.00	Trail road, bears ESE and WNW.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T32N R25E 1/4 S16 S15 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 9, 10, 15, and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<div style="text-align: center;"> <table border="1"> <tr><td>T32N</td><td>R25E</td></tr> <tr><td>S 9</td><td>S10</td></tr> <tr><td>S16</td><td>S15</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.</p>	T32N	R25E	S 9	S10	S16	S15	1991			
T32N	R25E										
S 9	S10										
S16	S15										
1991											
29.75	<p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>N. 89°59' W., bet. secs. 10 and 15.</p> <p>Over gently rolling land.</p> <p>Trail road, bears SSE and NNW.</p>										
40.01	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
80.02	<div style="text-align: center;"> <table border="1"> <tr><td>T32N</td><td>R25E</td></tr> <tr><td colspan="2">S10</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td colspan="2">S15</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 9, 10, 15, and 16.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.</p>	T32N	R25E	S10		1/4	—	S15		1991	
T32N	R25E										
S10											
1/4	—										
S15											
1991											
40.00	<p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over gently rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p>										

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R25E 1/4 S 9 S10 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
52.00	<p>NE cor. of a wood frame house, 15 x 15 ft., bears West, 7.40 chs. dist., sides bear SSW and WNW.</p>
61.30	<p>Graded road, 38 lks. wide, bears E. and W.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 9, and 10.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R25E S 4 S 3 ----- S 9 S10 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 10, and 11. N. 89°59' W., bet. secs. 3 and 10. Over broken and rolling land.</p>
40.015	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.03	<p style="text-align: center;">T32N R25E S 3 1/4 — S10 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 3, 4, 9, and 10.</p> <p>Land, broken to rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
40.00	<p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
67.30	<p style="text-align: center;">T32N R25E 1/4 S 4 S 3 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>High voltage transmission line, bears NE and SW.</p>
80.71	<p>Point for the closing cor. of secs. 3 and 4, at intersection with the Eighth Standard Parallel North, the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T33N R25E S33 ----- S 4 S 3 T32N R25E CC 1991</p>

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 33 N., R. 25 E., bears West, 12.98 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd. SC T33N R25E 1/4 S33 1990.</p> <p>Land, rolling and broken. Soil, sandy clay and sandstone bedrock. No timber; brush and native grasses.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 3 only, T. 32 N., R. 25 E., at midpoint on the N. bdy. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E ----- 1/4 S 3 T32N R25E 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 33 and 34, T. 33 N., R. 25 E., bears West, 13.00 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with a mound of stone, 3 ft. base, 16 ins. high, with brass cap mkd. SC T33N R25E S33 S34 1990.</p> <hr/> <p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T32N R25E S4 S5 S32 S33 T31N 1991.</p> <p>N. 0°03' W., bet. secs. 32 and 33.</p> <p>Over gently rolling land.</p>
--------	---

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R25E 1/4 S32 S33 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 28, 29, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R25E S29 S28 ----- S32 S33 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
39.99	<p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>West, bet. secs. 28 and 33.</p> <p>Over gently rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R25E S28 1/4 — S33 1991</p>

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.98	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 28, 29, 32, and 33.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
40.00	<p>N. 0°03' W., bet. secs. 28 and 29.</p> <p>Over gently rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R25E 1/4 S29 S28 1991</p> </div>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 20, 21, 28, and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R25E S20 S21 ----- S29 S28 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.</p>

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>N. 89°59' W., bet. secs. 21 and 28.</p> <p>Over gently rolling land.</p>
39.985	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R25E S21 1/4 — S28 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
79.97	<p>The cor. of secs. 20, 21, 28, and 29.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
29.95	<p>N. 0°03' W., bet. secs. 20 and 21.</p> <p>Over gently rolling land.</p> <p>Trail road, bears E. and W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R25E 1/4 S20 S21 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Point for the cor. of secs. 16, 17, 20, and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T32N R25E</td> </tr> <tr> <td>S17</td> <td>S16</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S20</td> <td>S21</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.</p>	T32N R25E		S17	S16	<hr/>		S20	S21	1991	
T32N R25E											
S17	S16										
<hr/>											
S20	S21										
1991											
	<hr/>										
	<p>From the cor. of secs. 15, 16, 21, and 22.</p>										
	<p>N. 89°59' W., bet. secs. 16 and 21.</p>										
	<p>Over gently rolling land.</p>										
39.985	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T32N R25E</td> </tr> <tr> <td colspan="2">S16</td> </tr> <tr> <td colspan="2">1/4 —</td> </tr> <tr> <td colspan="2">S21</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T32N R25E		S16		1/4 —		S21		1991	
T32N R25E											
S16											
1/4 —											
S21											
1991											
79.97	<p>The cor. of secs. 16, 17, 20, and 21.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.</p>										
	<hr/>										

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°03' W., bet. secs. 16 and 17.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T32N R25E 1/4 S17 S16 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
41.20	Trail road, bears ESE and WNW.
43.45	Trail road, bears NE and SW.
80.00	Point for the cor. of secs. 8, 9, 16, and 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T32N R25E S 8 S 9 ----- S17 S16 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Land, gently rolling.
	Soil, sandy clay.
	No timber; brush and native grasses.
	From the cor. of secs. 9, 10, 15, and 16.
	N. 89°59' W., bet. secs. 9 and 16.
	Over gently rolling land.

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.98	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R25E S 9 1/4 — S16 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
67.70	Trail road, bears N. and S.
79.96	<p>The cor. of secs. 8, 9, 16, and 17.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
	<p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R25E 1/4 S 8 S 9 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
42.60	Trail road, bears NE and SW.
49.00	Graded road, 38 lks. wide, bears ENE and WSW.
72.26	NE cor. of a log cabin, 14 x 14 ft., bears West, 2.97 chs. dist., sides bear S. and W.
80.00	Point for the cor. of secs. 4, 5, 8, and 9.

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R25E S 5 S 4 ----- S 8 S 9 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 9, and 10. N. 89°58' W., bet. secs. 4 and 9. Over gently rolling land.</p>
15.40	NW cor. of a stucco house, 44 x 14 ft., bears South, 3.05 chs. dist., long side bears S.
31.65	NW cor. of a log house, 43 x 12 ft., bears South, 10.15 chs. dist., long side bears SSW.
39.98	Point for the 1/4 sec. cor. of secs. 4 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T32N R25E S 4 1/4 — S 9 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
65.10	Trail road, bears ESE and WNW.
69.90	Trail road, bears ENE and WSW.

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
76.00	SW cor. of a stucco house, 20 x 16 ft., bears North, 3.30 chs. dist., long side bears N.
79.96	<p>The cor. of secs. 4, 5, 8, and 9.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
	<p>N. 0°03' W., bet. secs. 4 and 5.</p> <p>Over rolling land.</p>
10.20	Trail road, bears ESE and WNW.
11.10	High voltage transmission line, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R25E 1/4 S 5 S 4 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Thence descend into broken land.</p>
80.65	<p>Point for the closing cor. of secs. 4 and 5, at intersection with the Eighth Standard Parallel North, the N. bdy. of the Tp.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, flush with surface of sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T33N R25E S32 ----- S 5 S 4 T32N R25E CC 1991</p>

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case in the drill hole beneath the brass tablet.</p> <p>From this cor. point, the witness cor. to the stan. 1/4 sec. cor. of sec. 32, T. 33 N., R. 25 E., bears West, 13.87 chs. dist., monumented with a brass tablet, 3 1/4 ins. diam., cemented in place, flush with surface of sandstone bedrock, with top mkd. WC SC T33N R25E 1/4 S32 1990 and an arrow pointing east.</p> <p>Land, rolling and broken. Soil, sandy clay and sandstone bedrock. No timber; brush and native grasses.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 4 only, T. 32 N., R. 25 E., at midpoint on the N. bdy. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E ----- 1/4 S 4 T32N R25E 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the true point for the stan. cor. of secs. 32 and 33, T. 33 N., R. 25 E., bears West, 13.00 chs. dist., which falls on steep slope of a large clay ridge; from which the witness cor. to the stan. cor. of secs. 32 and 33, T. 33 N., R. 25 E., bears N. 34°16' W., 0.22 ch. dist. monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with a mound of stone, 3 ft. base, 13 ins. high, with brass cap mkd. WC SC T33N R25E S32 S33 1990 and an arrow pointing southeast.</p> <hr/> <p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T32N R25E S5 S6 S31 S32 T31N 1991.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over rolling land.</p>
--------	---

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS															
26.20	Trail road, bears ENE and WSW.														
40.00	Point for the 1/4 sec. cor. of secs. 31 and 32.														
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.														
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T32N R25E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S31</td><td> </td><td>S32</td></tr> <tr><td colspan="3">1991</td></tr> </table>	T32N R25E		1/4		S31		S32	1991						
T32N R25E															
1/4															
S31		S32													
1991															
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.														
80.00	Point for the cor. of secs. 29, 30, 31, and 32.														
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.														
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T32N R25E</td></tr> <tr><td>S30</td><td> </td><td>S29</td></tr> <tr><td colspan="3">-----</td></tr> <tr><td>S31</td><td> </td><td>S32</td></tr> <tr><td colspan="3">1991</td></tr> </table>	T32N R25E		S30		S29	-----			S31		S32	1991		
T32N R25E															
S30		S29													

S31		S32													
1991															
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.														
	Cor. is located 20 lks. S. of trail road, bears E. and W.														
	Land, rolling. Soil, sandy clay. No timber; brush and native grasses.														
	From the cor. of secs. 28, 29, 32, and 33.														
	N. 89°59' W., bet. secs. 29 and 32.														
	Over rolling land.														
40.01	Point for the 1/4 sec. cor. of secs. 29 and 32.														
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.														

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T32N R25E S29 1/4 — S32 1991</p>
80.02	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 29, 30, 31, and 32.</p> <p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
40.00	<p>N. 89°59' W., bet. secs. 30 and 31.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
44.30	<p style="text-align: center;">T32N R25E S30 1/4 — S31 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Foot of cliff at E. edge of Red Rock Rim, bears NNE and SSW; thence enter broken land.</p>
78.40	<p>The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling to broken. Soil, sandy clay and sandstone bedrock. No timber; brush and native grasses.</p>

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R25E 1/4 S30 S29 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
58.40	<p>Trail road, bears ESE and WNW.</p>
80.00	<p>Point for the cor. of secs. 19, 20, 29, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R25E S19 S20 ----- S30 S29 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
	<hr/> <p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>N. 89°59' W., bet. secs. 20 and 29.</p> <p>Over rolling land.</p>

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
12.15	Trail road, bears NE and SW.
40.01	Point for the 1/4 sec. cor. of secs. 20 and 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T32N R25E S20 1/4 — S29 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.02	The cor. of secs. 19, 20, 29, and 30.
	<p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
	<hr/> <p>N. 89°59' W., bet. secs. 19 and 30.</p>
	Over rolling land.
9.80	Wash, 30 lks. wide, 6 ft. deep, drains NE.
11.30	Trail road, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T32N R25E S19 1/4 — S30 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
43.40	Foot of cliff at E. edge of Red Rock Rim, bears NNE and SSW; thence enter broken land.
47.90	Top of Red Rock Rim, bears NNE and SSW.
78.31	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., hereinbefore described.
	Land, rolling and broken. Soil, sandy clay and sandstone bedrock. No timber; brush and native grasses.
	From the cor. of secs. 19, 20, 29, and 30.
	N. 0°03' W., bet. secs. 19 and 20.
	Over rolling land.
11.00	Wash, 38 lks. wide, 8 ft. deep, drains NNE.
20.75	SE cor. of a log house, 30 x 15 ft., bears West, 17.40 chs. dist., long side bears NNE.
24.20	Wash, 2.10 chs. wide, 8 ft. deep, drains E.
30.85	Trail road, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T32N R25E 1/4 S19 S20 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
42.65	Trail road, bears NE and SW.
56.40	Wash, 38 lks. wide, 8 ft. deep, drains ENE.
80.00	Point for the cor. of secs. 17, 18, 19, and 20.

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="836 388 990 546"> <tr> <td>T32N</td> <td>R25E</td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> <tr> <td>S19</td> <td>S20</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>	T32N	R25E	S18	S17	S19	S20	1991			
T32N	R25E										
S18	S17										
S19	S20										
1991											
	<p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>N. 89°59' W., bet. secs. 17 and 20.</p> <p>Over gently rolling land.</p>										
<p>40.015</p>	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="836 1176 990 1333"> <tr> <td>T32N</td> <td>R25E</td> </tr> <tr> <td></td> <td>S17</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S20</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T32N	R25E		S17	1/4	—		S20	1991	
T32N	R25E										
	S17										
1/4	—										
	S20										
1991											
<p>80.03</p>	<p>The cor. of secs. 17, 18, 19, and 20.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.</p>										

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 89°59' W., bet. secs. 18 and 19.
	Over rolling and broken land.
29.60	Foot of cliff at E. edge of Red Rock Rim, bears SSE and NNW.
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19.
	Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, flush with surface of sandstone bedrock, with top mkd.
	<p style="text-align: center;">T32N R25E S18 1/4 — S19 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case in the drill hole beneath the brass tablet.
	Cor. is located atop Red Rock Rim.
78.22	The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., hereinbefore described.
	Land, rolling and broken. Soil, sandy clay and sandstone bedrock. No timber; brush and native grasses.
	From the cor. of secs. 17, 18, 19, and 20.
	N. 0°03' W., bet secs. 17 and 18.
	Over rolling land.
12.90	Foot of sheer cliff at S. edge of a rock butte, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T32N R25E 1/4 S18 S17 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
72.90	Trail road, bears ESE and WNW.
80.00	<p>Point for the cor. of secs. 7, 8, 17, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R25E S 7 S 8 ----- S18 S17 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy clay and sandstone bedrock. No timber; brush and native grasses.</p> <hr/> <p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>West, bet. secs. 8 and 17.</p> <p>Over rolling land.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R25E S 8 1/4 — S17 1991</p>

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.04	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 7, 8, 17, and 18.</p> <p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
16.75	<p>N. 89°58' W., bet. secs. 7 and 18.</p> <p>Over rolling land.</p> <p>Trail road, bears ESE and WNW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R25E S 7 1/4 — S18 1991</p>
49.60	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>High voltage transmission line, bears NE and SW.</p>
78.13	<p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
	<p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0°03' W., bet. secs. 7 and 8.</p> <p>Over rolling land.</p>

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
34.00	Graded road, 38 lks. wide, bears ENE and WSW.
34.90	High voltage transmission line, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T32N R25E 1/4 S 7 S 8 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 5, 6, 7, and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T32N R25E S 6 S 5 ----- S 7 S 8 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 1.10 chs. E. of foot of cliff at E. edge of Red Rock Rim, bears N. and S.
	<p>Land, rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
	From the cor. of secs. 4, 5, 8, and 9.
	West, bet. secs. 5 and 8.
	Over rolling land.
15.80	High voltage transmission line, bears NE and SW.
23.98	SW cor. of barbed wire fence enclosure, 94 x 65 ft., bears North, 0.17 ch. dist., long side bears NNE.
40.025	Point for the 1/4 sec. cor. of secs. 5 and 8.

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.05	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R25E S 5 1/4 — S 8 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 5, 6, 7, and 8.</p> <p>Land, rolling. Soil, sandy clay with sandstone outcrop. No timber; brush and native grasses.</p>
40.00	<p>N. 89°58' W., bet. secs. 6 and 7.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 6 and 7; falls on a sheer cliff, where it is impractical to construct a permanent monument.</p>
41.00	<p>Point selected for the witness cor. to the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 ins. stem, in a drill hole, cemented in place, flush with surface of sandstone bedrock, with top mkd.</p> <p style="text-align: center;">WC T32N R25E S 6 1/4 —> S 7 1991</p>
78.03	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case in the drill hole beneath the brass tablet.</p> <p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., hereinbefore described.</p>

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Land, rolling and broken. Soil, sandstone bedrock and sandy clay. No timber; brush and native grasses.</p> <hr/> <p>From the cor. of secs. 5, 6, 7, and 8. N. 0°03' W., bet. secs. 5 and 6. Over rolling and broken land.</p> <p>4.90 Foot of cliff at E. edge of Red Rock Rim, bears E. and W.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 5 and 6. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R25E 1/4 S 6 S 5 1991</p> <p>80.65 Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the closing cor. of secs. 5 and 6, at intersection with the Eighth Standard Parallel North, the N. bdy. of the Tp. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E S31 ----- S 6 S 5 T32N R25E CC 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
--------	--

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>From this cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 33 N., R. 25 E., bears West, 12.98 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T33N R25E 1/4 S31 1990.</p> <p>Land, rolling and broken. Soil, sandy clay and sandstone bedrock. No timber; brush and native grasses.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 5 only, T. 32 N., R. 25 E., at midpoint on the N. bdy. of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E ----- 1/4 S 5 T32N R25E 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 31 and 32, T. 33 N., R. 25 E., bears West, 13.00 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T33N R25E S31 S32 1990.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 6 only, T. 32 N., R. 25 E., at 40.00 chs. westing from the closing cor. of secs. 5 and 6, on the N. bdy. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R25E ----- 1/4 S 6 T32N R25E 1991</p>
--------	---

Survey of the Subdivisional Lines,
T. 32 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. cor. of T. 33 N., Rs. 24 and 25 E., bears West, 12.98 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T33N R24E R25E S36 S31 1990.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>The area surveyed is within the Navajo Indian Reservation, approximately 3 miles west of Chinle, Arizona. The terrain is mostly rolling land on Ventana Mesa with sandstone bedrock of Red Rock Rim in the western part of the township. There are numerous washes, and the drainage is generally easterly.</p> <p>Elevation varies from 5,500 to 6,100 feet above sea level. The soil is mostly sandy clay with some sandstone bedrock in the western portion of the township. The vegetation consists of native grasses, greasewood, rabbitbrush and scattered cacti.</p> <p>Principal access to the township is provided by U.S. Highway 191, which passes through the township in sections 35 and 36, and again in section 1. There is a graded road which passes through the northern part of the township. There are trail roads scattered throughout the township. Permanent residences are mostly in the eastern portion of the township. Much of the township is used for the grazing of sheep, cattle and horses. There is no evidence of any kind of mining activity.</p> <p>The mean magnetic declination is 12 1/2° E.</p> <hr/>
--------	---

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Jones Curtiss	Surveying Technician
Daniel Bryan	Engineering Technician
Wilfred Chee	Engineering Technician
Nelson Kinsel	Engineering Technician
Reuben Mason	Engineering Technician
Andrew Murphy	Engineering Technician
Barney Woodie	Engineering Technician

