

ORIGINAL

BOOK 5418

1

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY OF

---

THE SOUTH BOUNDARY, PORTIONS OF THE EAST BOUNDARY,

---

SUBDIVISIONAL LINES AND SUBDIVISION OF SECTIONS 26 AND 27,

---

AND CERTAIN RECORD MEANDERS IN SECTIONS 26 AND 27,

---

AND THE SURVEY OF A PORTION OF THE EAST BOUNDARY,

---

THE NORTH BOUNDARY, PORTIONS OF THE SUBDIVISIONAL LINES AND

---

SUBDIVISION OF SECTION 27 AND A METES-AND-BOUNDS SURVEY IN SECTION 26,

---

OF

---

TOWNSHIP 27 NORTH, RANGE 26 EAST

---

Of the Gila and Salt River Meridian,  
In the State of Arizona

EXECUTED BY

Leonard R. Sandoval, Cadastral Surveyor

---

Under Special Instructions dated November 22, 1989, approved November 22, 1989, which provided for the surveys included under Group Number 715 and assignment instructions dated November 22, 1989.

Survey Commenced January 23, 1990

Survey Completed August 16, 1990

# BOOK 5418

2

## INDEX DIAGRAM

TOWNSHIP 27 NORTH, RANGE 26 EAST,

96 6	95 116 5	94 110 4	93 107 3	92 103 2	91 100 1 90
116 7	115 114 8	110 109 9	106 105 10	103 102 11	99 99 12 90
113 18	112 111 17	108 107 16	105 104 15	101 101 14	98 97 13 89
65 19	65 64 20	53 51 21	44 43 22	35 34 23	24 21 24 15
63 30	62 62 29	51 49 28	42 40 27	32 27 26	20 18 25 14
59 31 4	56 54 32 7	49 45 33 10	38 36 34 11	26 24 35 12	18 17 36 13 13

Resurvey of Subdivision of sec. 26, p. 67  
 Resurvey of Subdivision of sec. 27, pp. 67-81  
 Adjusted Record Meanders in sec. 26, pp. 81-83  
 Adjusted Record Meanders in sec. 27, pp. 83-88  
 Survey of Subdivision of sec. 27, pp. 117-119  
 Survey of Metes-and-Bounds Survey in sec. 26, p. 119

## BOOK 5418

T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the dependent resurvey of the south boundary, portions of the east boundary, subdivisional lines and subdivision of sections 26 and 27, and certain record meanders in sections 26 and 27, and the survey of a portion of the east boundary, the north boundary, and portions of the subdivisional lines and subdivision of section 27, and a metes-and-bounds survey in section 26, of Township 27 North, Range 26 East, Gila and Salt River Meridian, Arizona.

This survey supersedes portions of Township 1 North, Ranges 10 and 11 West of the Navajo Special Meridian. The survey history of that portion of the superseded Navajo Special Meridian is included in these notes for informational purposes only.

The Base Line, (south boundary) and the remaining boundaries and subdivision of Township 1 North, Ranges 10 and 11 West, Navajo Special Meridian, were surveyed by E.N. Darling in 1869.

The south boundary and portions of the east and west boundaries and a portion of the subdivisional lines were surveyed by S.E. Day in 1905. The south boundary, portions of the east and west boundaries and a portion of the subdivisional lines were resurveyed, and Tract 37, the subdivision of certain sections and various meander lines were surveyed by F.C. Miller in 1915. A portion of the west boundary was dependently resurveyed and a portion of the west boundary was surveyed by William F. Olver, Leonard R. Sandoval and Olian T. Shockley in 1989-90.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated November 22, 1989, for Group No. 715, Arizona.

Preliminary to the resurvey, the lines of the latest survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the latest record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of all lines were determined by direct hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with Nikon NTD-4, Topcon GTS-3B and Leitz SET-4A total station instruments.

BOOK 5418

T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

The geographic position of the southeast corner of the township was determined by the technique of static differential positioning using the Motorola Eagle Global Positioning System Satellite Surveyor. U.S. Coast and Geodetic Survey triangulation stations "GANADO 1951" and "LOHALI 1951", first order triangulation stations, were used as the control stations. The geographic position is as follows:

Latitude: 35°41'29.48" N. Longitude: 109°30'23.22" W. NAD27

The mean magnetic declination, as taken from the 1985 magnetic declination map published by U.S. Geological Survey, is 12 1/2° E.

---

Dependent Resurvey of the South Boundary,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

---

Restoring the Resurvey executed by  
F. C. Miller, in 1915

---

Beginning at the cor. of Tps. 26 and 27 N., Rs. 25 and 26 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T27N R25E R26E S1 S6 S31 S36 T26N 1990 1915, witnessed by a mound of stone, 3 ft. base, 2 ft. high, to the S.

S. 89°54' E., bet. secs. 6 and 31.

Over nearly level land.

8.915 Point for the W-W 1/64 sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T27N R26E  
S31  
W-W 1/64  
S 6  
T26N  
1990

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

## BOOK 54 18

Dependent Resurvey of the South Boundary,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
18.92	<p>The W 1/16 sec. cor. of secs. 6 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. W 1/16 S31 S6 1915.</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T27N R26E S31 W1/16 — S 6 T26N 1990 1915</p> <hr/> <p>S. 89°55' E., beginning new measurement.</p> <p>Over nearly level land.</p>
9.985	<p>The E-W 1/64 sec. cor. of secs. 6 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. 1/64 S31 S6 1915.</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T27N R26E S31 E-W 1/64 S 6 T26N 1990 1915</p> <hr/> <p>East, beginning new measurement.</p> <p>Over nearly level land.</p>
10.01	<p>The 1/4 sec. cor. of secs. 6 and 31, monumented with a flanged, concrete filled iron post, 18 ins. long, 1 in. diam., firmly set, flush with the surface of the ground, and is accepted as the best available evidence of the 1915 cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

## BOOK 5418

Dependent Resurvey of the South Boundary,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T27N R26E S31 1/4 — S 6 T26N 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Destroy the remains of the 1915 iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°55' E., beginning new measurement.</p> <p>Over rolling land.</p>
10.00	<p>Point for the W-E 1/64 sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R26E S31 W-E 1/64 S 6 T26N 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
14.68	<p>Point for the original meander cor. of secs. 6 and 31, right bank of Pueblo Colorado River, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R26E S31 — / MC S 6 / T26N 1990</p> <p>Cor. is located on poorly defined present right bank of Pueblo Colorado Wash, bears NNE and SSW.</p>

7  
BOOK 5418

Dependent Resurvey of the South Boundary,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
30.00	<p>Thence across the Pueblo Colorado Wash.</p> <p>Point for the E-E 1/64 sec. cor., identical with the original meander cor. of secs. 6 and 31, left bank of Pueblo Colorado River, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a steel fence post, 5 ft. long, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;">           T27N R26E            S31            MC E-E 1/64            S 6            T26N            1990         </div>										
40.00	<p>Cor. is located on poorly defined left bank of Pueblo Colorado Wash, bears NNE and SSW.</p> <p>The cor. of secs. 5, 6, 31, and 32, determined at record bearing and distance from the 1915 bearing tree:</p> <p style="margin-left: 40px;">A piñon, 20 ins. diam., bears N. 84° W., 24 lks. dist., with scribe mks. T27N R26E BT visible on partially healed blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T27N R26E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S31</td> <td style="padding: 0 5px;">S32</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 6</td> <td style="padding: 0 5px;">S 5</td> </tr> <tr> <td colspan="2" style="text-align: center;">T26N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1990</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>S. 89°57' E., bet. secs. 5 and 32.</p> <p>Over rolling land.</p>	T27N R26E		S31	S32	S 6	S 5	T26N		1990	
T27N R26E											
S31	S32										
S 6	S 5										
T26N											
1990											
10.02	<p>The W-W 1/64 sec. cor. of secs. 5 and 32, determined at record bearing and distance from the original bearing tree:</p>										

## BOOK 5418

Dependent Resurvey of the South Boundary,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A juniper, 18 ins. diam., bears N. 24 1/2° E., 54 lks. dist., with scribe mks. 1/64 S32 BT visible on open blaze.</p>
	<p>At the cor. point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R26E S32 W-W 1/64 S 5 T26N 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<hr/> <p>East, beginning new measurement.</p>
	<p>Over rolling land.</p>
6.09	<p>The meander cor. of secs. 5 and 32, N. bdy. of right-of-way of South Side Canal, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. T27N R26E S32 S5 MC T26N 1915.</p>
	<p>from which the remaining original bearing tree</p>
	<p style="text-align: center;">A piñon, 12 ins. diam., bears N. 50° E., 68 lks., dist., with scribe mks. MC T2 R2 S32 BT visible on partially defaced blaze. (Record: 14 ins. diam., N. 49° W.)</p>
	<p>Add the marks 1990 to the brass cap.</p>
	<hr/> <p>N. 89°59' E., beginning new measurement.</p>
	<p>Over rolling land.</p>
3.79	<p>Point for the W 1/16 sec. cor. of secs. 5 and 32, at proportionate dist.; there is no remaining evidence of the original temporary point. Not remonumented.</p>
5.73	<p>The meander cor. of secs. 5 and 32, N. bdy. of right-of-way of South Side Canal, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T27N R26E S32 S5 MC T26N 1915.</p>



## BOOK 5418

Dependent Resurvey of the South Boundary,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Add the marks 1990 to the brass cap.</p> <hr/> <p>S. 89°53' E., beginning new measurement.</p> <p>Over rolling land.</p>
7.995	<p>Point for the E-W 1/64 sec. cor. of secs. 5 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S32 E-W 1/64 S 5 T26N 1990</p>
10.295	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The meander cor. of secs. 5 and 32, N. bdy. of right-of-way of South Side Canal, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T27N R26E S32 S5 MC T26N 1915.</p>
	<p>Add the marks 1990 to the brass cap.</p> <hr/> <p>S. 89°52' E., beginning new measurement.</p> <p>Over rolling land.</p>
7.96	<p>The 1/4 sec. cor. of secs. 5 and 32, determined at record bearing and distance from the 1915 bearing tree:</p> <p style="padding-left: 40px;">A piñon, 15 ins. diam., bears N. 5° W., 104 lks. dist., with scribe mks. 1/4 S32 BT visible on partially healed blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

## BOOK 5418

Dependent Resurvey of the South Boundary,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T27N R26E S32 1/4 — S 5 T26N 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <hr/> <p>S. 89°56' E., beginning new measurement.</p> <p>Over rolling land.</p>
39.83	<p>The cor. of secs. 4, 5, 32, and 33, monumented with an iron post, 3 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. T27N R26E S32 S33 S5 S4 T26N 1915.</p> <p>from which the 1915 bearing trees</p> <p style="padding-left: 40px;">A dead piñon, 12 ins. diam., bears N. 12 1/2° E., 105 lks. dist., with scribe mks. T27N R26E S33 BT visible on open blaze. (Record: N. 14° E.)</p> <p style="padding-left: 40px;">A piñon stump, 12 ins. diam., bears East, 122 lks. dist., with no scribe mks. visible. (Record: 14 ins. diam., S. 88° E.)</p> <p style="padding-left: 40px;">A dead piñon, 15 ins. diam., bears S. 8° W., 61 1/2 lks. dist., with scribe mks. T26N R26E S5 BT visible on open blaze. (Record: S. 10° W., 60 lks. dist.)</p> <p style="padding-left: 40px;">A piñon, 12 ins. diam., bears N. 33 1/2° W., 114 lks. dist., with scribe mks. T27N R26E S32 BT visible on open blaze.</p> <p>Add the marks 1990 to the brass cap.</p> <hr/> <p>S. 89°53' E., bet. secs. 4 and 33.</p> <p>Over rolling land.</p>
39.89	<p>The 1/4 sec. cor. of secs. 4 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. 1/4 S33 S4 1915.</p> <p>Remark the brass cap to read</p>

## BOOK 5418

Dependent Resurvey of the South Boundary,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T27N R26E S33 1/4 — S 4 T26N 1990 1915</p> <p>from which the remains of the 1915 bearing trees</p> <p>A stump hole, bears S. 10° W., 19 lks. dist., with an uprooted piñon, 12 ins. diam., lying alongside, with scribe mks. 1/4 S4 BT visible on open blaze.</p> <p>A stump hole, bears N. 29° W., 56 1/2 lks. dist., with an uprooted piñon, 8 ins. diam., lying alongside, with scribe mks. 1/4 S33 BT visible on open blaze. (Record: 59 lks. dist.)</p> <hr/> <p>S. 89°47' E., beginning new measurement.</p> <p>Over rolling land.</p>
40.00	<p>The cor. of secs. 3, 4, 33, and 34, monumented with an iron post, 3 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T27N R26E S3 S4 S33 S34 T26N 1915.</p> <p>from which the remaining 1915 bearing tree</p> <p>A multiple trunked juniper, 24 ins. at base, bears S. 65 1/2° W., 8 1/2 lks. dist., with scribe mks. T26N R26E S4 BT visible on open blaze. (Record: Piñon, 8 ins. diam., S. 56° W., 7 lks. dist.)</p> <p>Add the marks 1990 to the brass cap.</p> <hr/> <p>S. 89°59' E., bet. secs. 3 and 34.</p> <p>Over rolling land.</p>
39.985	<p>Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate dist.; there is no remaining evidence of the 1915 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>

## BOOK 5418

Dependent Resurvey of the South Boundary,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T27N R26E S34 1/4 — S 3 T26N 1990</p>
	<p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
62.02	<p>W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.</p>
63.57	<p>Center of U.S. Highway 191, asphalt pavement, 40 lks. wide, bears NNE and SSW.</p>
65.12	<p>E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.</p>
79.97	<p>The cor. of secs. 2, 3, 34, and 35, monumented with an iron post, 3 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T27N R26E S2 S3 S34 S35 T26N 1915.</p>
	<p>Add the marks 1990 to the brass cap.</p>
	<hr/> <p>S. 89°57' E., bet. secs. 2 and 35.</p>
	<p>Over gently rolling land.</p>
39.97	<p>The 1/4 sec. cor. of secs. 2 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. 1/4 S35 S2 1915.</p>
	<p>Remark the brass cap to read</p>
	<p style="text-align: center;">T27N R26E S35 1/4 — S 2 T26N 1990 1915</p>
	<hr/> <p>S. 89°58' E., beginning new measurement.</p>
	<p>Over gently rolling land.</p>

## BOOK 54 18

Dependent Resurvey of the South Boundary,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.99	<p>The cor. of secs. 1, 2, 35, and 36, monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T27N R26E S1 S2 S35 S36 T26N 1915.</p> <p>Add the marks 1990 to the brass cap.</p> <p>Cor. is located 25 lks. W. of a trail road, bears N. and S.</p> <hr/> <p>S. 89°54' E., bet. secs. 1 and 36.</p> <p>Over gently rolling land.</p>
39.995	<p>Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist.; there is no remaining evidence of the 1915 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S36 1/4 — S 1 T26N 1990</p> <p>Deposit a magnet enclosed in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
79.99	<p>The cor. of Tps. 26 and 27 N., Rs. 26 and 27 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. T27N R26E R27E S1 S6 S31 S36 T26N 1915.</p> <p>Add the marks 1990 to the brass cap.</p> <p>From this cor. point, a brass tablet, 3 1/2 ins. diam., set in a concrete collar, 8 ins. diam., firmly set, flush with the surface of the ground, bears N. 88°50' W., 10.86 chs. dist., with top mkd. NAVAJO CONTROL SYSTEM TRAV WR BRUSH PT 60 LAS 1969.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the East Boundary, T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Restoring the Resurvey executed by F. C. Miller, in 1915</p> <hr/>

## BOOK 5418

Dependent Resurvey of a Portion of the East Boundary,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of Tps. 26 and 27 N., Rs. 26 and 27 E., hereinbefore described.</p> <p>N. 0°05' E., bet. secs. 31 and 36.</p> <p>Over rolling land.</p>
39.995	<p>Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the 1915 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R26E R27E 1/4 S36   S31 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
79.99	<p>Point for the cor. of secs. 25, 30, 31, and 36, at proportionate dist.; there is no remaining evidence of the 1915 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R26E   R27E S25   S30 ----- S36   S31 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<hr/> <p>N. 0°05' E., bet. secs. 25 and 30.</p> <p>Over rolling land.</p>
26.59	<p>S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.</p>
28.10	<p>Center of Arizona State Highway 264, asphalt pavement, 60 lks. wide, bears E. and W.</p>
29.65	<p>N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.</p>

## BOOK 54 18

Dependent Resurvey of a Portion of the East Boundary,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.995	<p>The 1/4 sec. cor. of secs. 25 and 30, determined at record bearing and distance from the remaining 1915 bearing tree:</p> <p style="padding-left: 40px;">A piñon, 20 ins. diam., bears N. 74 1/2° E., 130 lks. dist., with scribe mks. 1/4 S30 BT visible on open blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R26E R27E 1/4 S25   S30 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>North, beginning new measurement.</p> <p>Over rolling land.</p>
39.99	<p>The cor. of secs. 19, 24, 25, and 30, monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T27N R26E R27E S19 S24 S25 S30 1915.</p> <p>from which the 1915 bearing trees</p> <p style="padding-left: 40px;">A piñon, 24 ins. diam., bears N. 73° E., 94 lks. dist., with scribe mks. T27N R27E S19 BT visible on open blaze.</p> <p style="padding-left: 40px;">A piñon, 20 ins. diam., bears S. 37 1/2° W., 129 lks. dist., with erroneous scribe mks. T27N R26E R27E S24 BT visible on open blaze: remark to read T27N R26E S25 BT.</p> <p style="padding-left: 40px;">A piñon stump, 30 ins. diam., bears N. 46° W., 84 lks. dist., with scribe mks. 27N 26E S24 BT visible on open blaze.</p> <p>Add the marks 1990 to the brass cap.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°02' W., bet. secs. 19 and 24.</p> <p>Over rolling land.</p>

## BOOK 54 18

Dependent Resurvey of a Portion of the East Boundary,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
38.60	S. rim of floodplain of Pueblo Colorado Wash, 15 ft. high, bears E. and W.
39.94	Point for the true point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the 1915 witness cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T27N R26E R27E 1/4 S24   S19 1990
	from which
	<p>A brass tablet, 3 1/4 ins. long, 2 1/2 ins. stem, set in a drill hole in sandstone bedrock, cemented in place, for a reference monument, bears S. 30° E., 120.0 ft. dist., with top mkd. T27N R27E 1/4 S19 RM 120.0 FT. TO COR. 1990 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case in the drill hole beneath the brass tablet.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/12 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 60° W., 220.0 ft. dist., with brass cap mkd. T27N R26E 1/4 S24 RM 220.0 FT. TO COR. 1990 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located in floodplain of Pueblo Colorado Wash, 155 lks. S. of left bank of Pueblo Colorado Wash, 76 lks. wide, 5 ft. deep, bears ENE on curve to left, and 185 lks. W. of Naakai N Daachaahi Wash, 45 lks. wide, 3 ft. deep, drains N.</p>
54.20	Center of Pueblo Colorado Wash, 200 lks. wide, 10 ft. deep, drains SW.
79.88	The cor. of secs. 13, 18, 19, and 24, monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. T27N R26E R27E S13 S18 S19 S24 1915.
	from which the remaining 1915 bearing tree



Dependent Resurvey of a Portion of the East Boundary,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A piñon, 20 ins. diam., bears N. 20 1/2° E., 65 lks. dist., with faint scribe mks. T27N S18 BT visible on partially healed blaze.</p> <p>Add the marks 1990 to the brass cap.</p>
	<hr/> <p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona</p> <hr/>
	<p>Restoring the Resurvey executed by F. C. Miller, in 1915</p> <hr/>
	<p>From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°04' E., bet. secs. 35 and 36.</p> <p>Over rolling land.</p>
39.995	<p>Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the 1915 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E 1/4 S35   S36 1990</p> <p>from which</p> <p style="text-align: center;">A wood power pole, bears N. 43 3/4° W., 319 1/2 lks. dist., with mks. VOC HPT H987 SPPAS 445.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
79.99	<p>Point for the cor. of secs. 25, 26, 35, and 36, at proportionate dist.; there is no remaining evidence of the 1915 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

18  
BOOK 54 18

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS																
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T27N R26E</td> <td></td> <td style="padding: 0 10px;">S25</td> </tr> <tr> <td style="padding: 0 10px;">S26</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td> <td style="padding: 0 10px;">S25</td> </tr> <tr> <td colspan="3" style="border-top: 1px solid black; border-bottom: 1px solid black;"></td> </tr> <tr> <td style="padding: 0 10px;">S35</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td> <td style="padding: 0 10px;">S36</td> </tr> <tr> <td colspan="3" style="text-align: center; padding-top: 5px;">1990</td> </tr> </table>	T27N R26E		S25	S26		S25				S35		S36	1990		
T27N R26E		S25														
S26		S25														
S35		S36														
1990																
	<p>from which</p> <p style="margin-left: 40px;">A piñon, 5 ins. diam., bears N. 47 3/4° E., 77 lks. dist., mkd. X BT.</p> <p style="margin-left: 40px;">A piñon, 6 ins. diam., bears S. 3 3/4° E., 84 lks. dist., mkd. T27N R26E S36 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <hr/> <p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°53' W., bet. secs. 25 and 36.</p> <p>Over rolling land.</p>															
37.20	Airplane landing strip, dirt surface, 210 lks. wide, bears NNE and SSW.															
40.00	Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the 1915 cor.															
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.															
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T27N R26E</td> <td></td> <td style="padding: 0 10px;">S25</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td> <td style="padding: 0 10px;">S36</td> </tr> <tr> <td colspan="3" style="border-top: 1px solid black; border-bottom: 1px solid black;"></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td> <td style="padding: 0 10px;">S36</td> </tr> <tr> <td colspan="3" style="text-align: center; padding-top: 5px;">1990</td> </tr> </table>	T27N R26E		S25			S36						S36	1990		
T27N R26E		S25														
		S36														
		S36														
1990																
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.															
80.00	The cor. of secs. 25, 26, 35, and 36.															
	N. 0°01' E., bet. secs. 25 and 26.															
20.32	S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.															

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
21.84	Center of Arizona State Highway 264, asphalt pavement, 60 lks. wide, bears E. and W.
23.36	N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
39.995	<p>The 1/4 sec. cor. of secs. 25 and 26, determined at record bearing and distance from the remaining 1915 bearing tree:</p> <p style="padding-left: 40px;">A piñon, 12 ins. diam., bears S. 39° W., 72 lks. dist., with illegible scribe mks. visible on partially healed blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding-left: 100px;">       T27N R26E        1/4        S26   S25        1990     </div> <p>from which</p> <p style="padding-left: 40px;">A forked piñon, 14 ins. diam. at base, bears S. 59 1/2° E., 72 1/2 lks. dist., mkd. 1/4 S25 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0°07' W., beginning new measurement.</p> <p>Over rolling and broken land.</p>
40.11	<p>The cor. of secs. 23, 24, 25, and 26, determined at record distances from the remaining 1915 bearing trees:</p> <p style="padding-left: 40px;">A forked piñon, 12 ins. diam. at base, bears N. 54 3/4° E., 66 lks. dist., with scribe mks. T27N R26E S24 BT visible on open blaze. (Record: N. 44 1/2° E.)</p> <p style="padding-left: 40px;">A piñon, 13 ins. diam., bears N. 64° W., 87 lks. dist., with scribe mks. T27N R26E S23 BT visible on open blaze. (Record: N. 61 1/2° W.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<table border="1" style="margin: auto;"> <tr> <td colspan="2">T27N R26E</td> </tr> <tr> <td>S23</td> <td>S24</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S26</td> <td>S25</td> </tr> <tr> <td colspan="2" style="text-align: center;">1990</td> </tr> </table>	T27N R26E		S23	S24			S26	S25	1990	
T27N R26E											
S23	S24										
S26	S25										
1990											
	<p>from which</p> <p style="padding-left: 40px;">A piñon, 14 ins. diam., bears S. 57 3/4° E., 250 lks. dist., mkd. T27N R26E S25 BT.</p> <p style="padding-left: 40px;">A forked piñon, 8 ins. diam. at base, bears S. 67° W., 21 lks. dist., mkd. T27N R26E S26 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <hr/> <p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°54' W., bet. secs. 24 and 25.</p> <p>Over rolling land.</p>										
38.27	E. right-of-way fence of Navajo Route 27, barbed wire, 5 strands, parallels highway.										
39.83	Center of Navajo Route 27, asphalt pavement, 50 lks. wide, bears SSE and NNW.										
40.02	<p>The 1/4 sec. cor. of secs. 24 and 25, determined at record bearing and distance from the remaining 1915 bearing tree:</p> <p style="padding-left: 40px;">A piñon, 25 ins. diam., bears N. 45 1/2° W., 86 lks. dist., with scribe mks. 1/4 S24 BT visible on open blaze. (Record: 30 ins. dia.)</p> <p>At the cor. point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 ins. stem, in a drill hole, in asphalt pavement, cemented in place, with top mkd.</p>										
	<table border="1" style="margin: auto;"> <tr> <td colspan="2">T27N R26E</td> </tr> <tr> <td colspan="2" style="text-align: center;">S24</td> </tr> <tr> <td colspan="2" style="text-align: center;">1/4 —</td> </tr> <tr> <td colspan="2" style="text-align: center;">S25</td> </tr> <tr> <td colspan="2" style="text-align: center;">1990</td> </tr> </table>	T27N R26E		S24		1/4 —		S25		1990	
T27N R26E											
S24											
1/4 —											
S25											
1990											

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p>
	<p>A piñon, 10 ins. diam., bears N. 61° E., 197 lks. dist., mkd. X BT.</p>
	<p>Deposit a magnet, 1 in. long, 7/8 in. diam., in the drill hole beneath the brass tablet.</p>
	<p>Cor. is located 6 lks. E. of W. edge of pavement of Navajo Route 27, bears SSE and NNW.</p>
	<p>N. 89°43' W., beginning new measurement.</p>
	<p>Over rolling land.</p>
1.39	<p>W. right-of-way fence of Navajo Route 27, barbed wire, 5 strands, parallels highway.</p>
40.09	<p>The cor. of secs. 23, 24, 25, and 26.</p>
	<p>N. 0°01' E., bet. secs. 23 and 24.</p>
	<p>Over broken to nearly level land.</p>
9.975	<p>Point for the S-S 1/64 sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the original temporary cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>T27N R26E</p>
	<p>S-S</p>
	<p>1/64</p>
	<p>S23   S24</p>
	<p>1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
19.95	<p>Point for the S 1/16 sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the original temporary point.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T27N R26E S1/16 S23   S24 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located 220 lks. S. of left bank of Pueblo Colorado Wash, 5 ft. high, bears ENE and WSW.</p>
23.74	<p>Point for the original meander cor. of secs. 23 and 24, on the right bank of the Pueblo Colorado River, at proportionate dist.; there is no remaining evidence of the original cor. Point falls in the Pueblo Colorado Wash, where it is impracticable to establish a permanent monument. Not remonumented.</p>
27.20	<p>Right bank of Pueblo Colorado Wash, 15 ft. high, bears ENE and WSW.</p>
29.925	<p>Point for the N-S 1/64 sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. below the surface of the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R26E N-S 1/64 S23   S24 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located in a cultivated field.</p>
34.81	<p>Point for the meander cor. of secs. 23 and 24, S. bdy. of right-of-way of N. Side Canal (record erroneously states S. Side Canal), at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">MC S23   S24 T27N R26E 1990</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
 T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.90	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 3 lks. E. of barbed wire fence, 4 strands, bears N. and S.</p> <p>Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the 1915 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R26E        1/4        S23   S24        1990</p>
79.80	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on rocky S. slope of a mesa.</p> <p>The cor. of secs. 13, 14, 23, and 24, determined at record bearing and distance from the remaining 1915 bearing tree:</p> <p style="padding-left: 40px;">A juniper, 30 ins. diam., bears S. 13° E., 117 lks. dist., with scribe mks. T27N R26E visible on partially healed blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R26E        S14   S13        -----        S23   S24        1990</p>
	<p>from which a bearing tree not of record</p> <p style="padding-left: 40px;">A piñon, 12 ins. diam., bears S. 50 3/4° W., 124 lks. dist., with scribe mks. T27N R26E S23 BT visible on open blaze.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.
	N. 89°53' W., bet. secs. 13 and 24.
	Over rolling land.
4.07	E. right-of-way fence of Navajo Route 27, barbed wire, 4 strands, parallels highway.
5.58	Center of Navajo Route 27, asphalt pavement, 47 lks. wide, bears N. and S.
7.11	W. right-of-way fence of Navajo Route 27, barbed wire, 4 strands, parallels highway.
34.01	Point for the witness cor. for the 1/4 sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the 1915 witness cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">WC T27N R26E S13 1/4 ← S24 1990</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located on the E. shore of Ganado Lake, a reservoir.
40.01	True point for the 1/4 sec. cor. of secs. 13 and 24, falls in Ganado Lake, where it is impracticable to establish a permanent monument.
80.02	The cor. of secs. 13, 14, 23, and 24.
	From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°05' E., bet. secs. 34 and 35.
	Over rolling land.
40.02	Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the 1915 cor.



## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E 1/4 S34   S35 1990</p> <p>from which</p> <p>A stainless post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 82°35' W., 176.8 ft. dist., with brass cap mkd. T27N R26E 1/4 S34 RM 176.8 FT TO COR 1990, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless post.</p> <p>A stainless post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 48°44' W., 188.9 ft. dist., with brass cap mkd. T27N R26E 1/4 S34 RM 188.9 FT TO COR 1990, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in Ganado Community Cemetery.</p>
70.36	SE right-of-way fence of U.S. Highway 191, barbed wire, 4 strands, parallels highway.
74.05	Center of U.S. Highway 191, asphalt pavement, 40 lks. wide, bears NNE and SSW.
80.04	<p>The cor. of secs. 26, 27, 34, and 35, monumented with a bent iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. T27N R26E S26 S27 S34 S35 1915.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S27   S26 ----- S34   S35 1990</p>

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>A stainless post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45°00' E., 230.0 ft. dist., with brass cap mkd. T27N R26E S35 RM 230.0 FT TO COR 1990, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless post.</p> <p>A stainless post, 28 ins. long, 2 1/2 ins. diam., set flush with the surface of the ground, for a reference monument, bears S. 45°00' W., 85.0 ft. dist., with brass cap mkd. T27N R26E S34 RM 85.0 FT TO COR 1990, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Destroy the 1915 iron post.</p> <p>Cor. is located 16 lks. E. of W. right-of-way fence of U.S. Highway 191, barbed wire, 4 strands, 134 lks. W. of center of U.S. Highway 191, asphalt pavement, 40 lks. wide, and 286 lks. W. of E. right-of-way fence of U.S. Highway 191, barbed wire, 4 strands, all bear N. and S.</p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>N. 89°54' W., bet. secs. 26 and 35.</p> <p>Over rolling land.</p> <p>39.96 Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the 1915 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S26 1/4 — S35 1990</p> <p>from which</p> <p>A piñon, 12 ins. diam., bears S. 86° W., 288 1/2 lks. dist., mkd. 1/4 S35 BT.</p>

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.92	<p>A juniper, 6 ins. diam., bears N. 12 1/2° W., 107 lks. dist., mkd. 1/4 S26 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 26, 27, 34, and 35.</p>
15.60	<p>N. 0°04' W., bet. secs. 26 and 27.</p> <p>Over rolling land.</p> <p>Center of Arizona State Highway 264, asphalt pavement, 40 lks. wide, bears E. and W.</p>
17.08	<p>N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.</p>
20.02	<p>The S 1/16 sec. cor. of secs. 26 and 27, monumented with a rebar, 5/8 in. diam., set flush with surface of the ground, with a yellow plastic cap mkd. LS 17428, established by George Perce, Arizona R.L.S. No. 17428, in 1990; and is accepted as a careful and faithful determination of the cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S1/16 S27   S26 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and the rebar, 20 ins. long, beneath the stainless steel post.</p> <p>From this cor. point, a brass disk, 3 ins. diam., set in a concrete collar, 12 ins. diam., firmly set, flush with the surface of the ground, with top mkd. LIMBAUGH ENGINEERS INC. M.T.-1 LS 6355 1968, established by Limbaugh Engineers Inc., in 1968, bears S. 41° E., 1 lk. dist. The position of this cor. is irreconcilable with the plat position, and it is not utilized in the course of this resurvey.</p> <p>Cor. is located 2 1/2 lks. E. of barbed wire fence, 5 strands, bears N. and S.</p> <p style="text-align: center;">_____</p> <p>N. 0°04' W., beginning new measurement.</p>

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS										
	Over nearly level land.									
9.685	<p>Point for AP 1 of a metes-and-bounds survey in sec. 26, determined at record dist. of 16.64 chs. from the original meander cor. of secs. 26 and 27, N. bdy. of right-of-way of S. Side Canal and left bank of Pueblo Colorado River, hereinafter described. The record dist. was obtained from exchange deed between the United States of America and Board of National Missions of the Presbyterian Church dated March 22, 1946.</p>									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p>									
	<div style="text-align: center;"> <p>T27N R26E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S27</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">AP1</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;"></td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S26</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;"></td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">1990</td> </tr> </table> </div>	S27		AP1			S26			1990
S27		AP1								
		S26								
		1990								
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>									
	<p>From this cor. point, a rebar, 5/8 in. diam., set flush with the surface of the ground, bears South, 1 lk. dist., with yellow plastic cap mkd. LS 17428; established by George Perce, Arizona R.L.S. No. 17428, in 1990. The position of this cor. is irreconcilable with the plat position, and it is not utilized in the course of this resurvey.</p>									
	<p>From this same cor. point, a brass disk, 3 ins. diam., set in a concrete sidewalk slab, 8 x 6 ft., bears S. 21 1/2° E., 3 1/2 lks. dist., with top mkd. LIMBAUGH ENGINEERS INC. M.T.-22 LS 6355 1968; established by Limbaugh Engineers Inc., in 1968. The position of this cor. is irreconcilable with the plat position, and it is not utilized in the course of this resurvey.</p>									
10.01	<p>The N-S 1/64 sec. cor. of secs. 26 and 27, monumented with a rebar, 5/8 in. diam., set flush with surface of the ground, with yellow plastic cap mkd. LS 17428, reestablished by George Perce, Arizona R.L.S. No. 17428, in 1990; and is accepted as a careful and faithful reestablishment of the original temporary point position.</p>									
	<p>At the cor. point</p>									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>									

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
10.01	<p style="text-align: center;">T27N R26E N-S 1/64 S27   S26 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and the rebar, 20 ins. long, beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°04' W., beginning new measurement.</p> <p>Over nearly level land.</p> <p>The 1/4 sec. cor. of secs. 26 and 27, monumented with a rebar, 5/8 in. diam., set flush with surface of the ground, with yellow plastic cap mkd. LS 17428, reestablished by George Perce, Arizona R.L.S. No. 17428, in 1990; and is accepted as a careful and faithful reestablishment of the 1915 cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E 1/4 S27   S26 1990</p> <p>from which</p> <p style="padding-left: 40px;">The SE cor. of a stucco house, bears S. 82° W., 111 1/2 lks. dist.</p> <p style="padding-left: 40px;">The NE cor. of same house, bears N. 71 1/2° W., 115 1/2 lks. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case and the rebar, 20 ins. long, beneath the stainless steel post.</p> <p>Cor. is located in the back yard of a residence.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°04' W., beginning new measurement.</p> <p>Over nearly level land.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
45.425	<p>Point for the meander cor. of secs. 23 and 26, on S. bdy. of right-of-way of N. Side Canal, at proportionate dist.; there is no remaining evidence of the original cor. This cor. formally served as a meander cor. on the right bank of the Pueblo Colorado River.</p> <p>Set a magnet in a 1 x 1 x 2 5/8 ins. white plastic case, 30 ins. below the surface of the ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 80°43' W., 162.8 ft. dist., with brass cap mkd. T27N R26E MC S26 RM 162.8 FT TO COR 1990, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless post.</p> <p style="padding-left: 40px;">A stainless post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 7°32' W., 213.8 ft. dist., with brass cap mkd. T27N R26E MC S23 RM 213.8 FT TO COR 1990, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless post.</p> <p>Cor. is located on unstable embankment on E. edge of graded road, 30 lks. wide, bears NNE and SSW.</p>
79.96	<p>The cor. of secs. 22, 23, 26, and 27.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>N. 0°04' W., bet. secs. 22 and 23.</p> <p>Over rolling land.</p>
39.83	<p>Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the 1915 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T27N R26E 1/4 S22   S23 1990</p> </div> <p>from which</p> <p style="padding-left: 40px;">A piñon, 6 ins. diam., bears N. 51 1/2° E., 37 lks. dist., mkd. 1/4 S23 BT.</p>

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
6.305	<p>The original meander cor. of secs. 26 and 27, N. bdy. of right-of-way of S. Side Canal and left bank of Pueblo Colorado River, monumented with an iron post, 1 in. diam., firmly set, flush with the surface of ground, with brass cap mkd. T27N R26E MC S26 S27 MC 1915.</p> <p>From this cor. point, a brass disk, 3 ins. diam., set in a concrete collar, 12 ins. diam., firmly set, projecting 6 ins. above ground, bears N. 1°19' E., 41 1/2 lks. dist., with top mkd. LIMBAUGH ENGINEERS INC.</p> <p>From this same cor. point, a brass disk, 3 ins. diam., set in a concrete collar, 12 ins. diam., firmly set, projecting 2 ins. above ground, bears N. 20° E., 3 lks. dist., with top mkd. LIMBAUGH ENGINEERS INC. M.T.-19 LS 6355 1968.</p> <p>Add the marks 1990 to the brass cap.</p> <p>Cor. is located 100 lks. S. of left bank of Pueblo Colorado Wash, bears NE and SW.</p> <hr/> <p>N. 0°02' W., beginning new measurement.</p> <p>Over nearly level land.</p>
9.515	<p>Point for the original meander cor. of secs. 26 and 27, on the right bank of the Pueblo Colorado River (record erroneously states left bank), at proportionate dist.; there is no remaining evidence of the original cor. Point falls in the Pueblo Colorado Wash, drains SW, where it is impracticable to establish a permanent monument. Not remonumented.</p>
10.60	<p>Right bank of Pueblo Colorado Wash, bears NE and SW.</p>
13.72	<p>Point for the true point for the N 1/16 sec. cor. of secs. 26 and 27, at proportionate dist.; there is no remaining evidence of the original witness cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E N1/16 S27   S26 1990</p>

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>A stainless post, 28 ins. long, 2 1/2 ins. diam., set flush with the surface of the ground, for a reference monument, bears S. 42°22' E., 59.3 ft. dist., with brass cap mkd. T27N R26E N1/16 S26 RM 59.3 FT TO COR 1990, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless post.</p> <p>A stainless post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°25' W., 102.7 ft. dist., with brass cap mkd. T27N R26E N1/16 S27 RM 102.7 FT TO COR 1990, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 7 lks. N. of unstable N. bank of wash, 23 lks. wide, 10 ft. deep, drains SSE, and 12 lks. W. of center of wash, 15 lks. wide, 4 ft. deep, drains SW.</p>
23.735	<p>The N-N 1/64 sec. cor. of secs. 26 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. 1/64 S27 S26 1915.</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T27N R26E N-N 1/64 S27   S26 1990 1915</p> <p>Cor. is located in a barbed wire fence, 4 strands, bears SE and NW.</p> <p style="text-align: center;">_____</p> <p>N. 0°15' W., beginning new measurement.</p> <p>Over nearly level land.</p>
8.685	<p>Point for the meander cor. of secs. 26 and 27, on the S. bdy. of proposed N. Side Canal right-of-way, at proportionate dist.; there is no remaining evidence of the original cor.</p>



BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E MC</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S27</td> <td style="padding: 0 5px;">S26</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1990</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in a cultivated field, 25 lks. S. of a barbed wire fence, 5 strands, bears E. and W.</p>	S27	S26	1990					
S27	S26								
1990									
9.70	Canal, 12 lks. wide, 4 ft. deep, drains WSW.								
9.96	<p>Point for the cor. of secs. 22, 23, 26, and 27, at proportionate dist.; there is no remaining evidence of the 1915 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T27N R26E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S22</td> <td style="padding: 0 5px;">S23</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S27</td> <td style="padding: 0 5px;">S26</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1990</td> </tr> </table>	T27N R26E		S22	S23	S27	S26	1990	
T27N R26E									
S22	S23								
S27	S26								
1990									
	<p>from which</p> <p style="padding-left: 40px;">The SW cor. of a house, 44 x 16 ft., bears N. 41 1/4° E., 168 1/2 lks. dist., long side bears E.</p> <p style="padding-left: 40px;">The southernmost cor. of a log cabin, 32 x 14 ft., bears N. 9 1/2° W., 141 lks. dist., long side bears NE.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>								
	<p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>N. 89°56' W., bet. secs. 23 and 26.</p> <p>Over broken to nearly level land.</p>								
19.90	Left bank of Pueblo Colorado Wash, bears NE and SW.								

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
25.385	<p>Point for the original meander cor. of secs. 23 and 26, on the right bank of the Pueblo Colorado River, at proportionate dist.; there is no remaining evidence of the original cor. Point is located on the face of the right bank of the Pueblo Colorado Wash, 20 ft. high, bears NE and SW, where it is impracticable to establish a permanent monument. Not remonumented.</p>
29.985	<p>Point for the W-E 1/64 sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the original cor. This cor. formally served as a meander cor. on the right bank of the Pueblo Colorado River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S23 W-E 1/64 S26 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the 1915 cor. Point falls on the face of the right bank of the Pueblo Colorado Wash, 30 ft. high, where it is impracticable to establish a permanent monument.</p> <p>From this cor. point, the selected point for the witness cor. to the 1/4 sec. cor. of secs. 23 and 26, bears N. 20° E., 1.085 chs. dist.</p> <p>At the witness cor. point, set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WC T27N R26E S23 1/4 — ✓ S26 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
79.66	<p>A piñon, 12 ins. diam., bears S. 18 1/4° W., 151 lks. dist., mkd. 1/4 S22 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 14, 15, 22, and 23, determined at record bearing and distance from the remaining 1915 bearing tree:</p> <p>A piñon, 20 ins. diam., bears S. 28 1/2° E., 258 lks. dist., with scribe mks. T27N R26E S23 BT visible on open blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T27N</td><td>R26E</td></tr> <tr><td>S15</td><td>S14</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S22</td><td>S23</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">1990</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T27N	R26E	S15	S14			S22	S23	1990	
T27N	R26E										
S15	S14										
S22	S23										
1990											
40.035	<p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>S. 89°57' W., bet. secs. 14 and 23.</p> <p>Over rolling land.</p> <p>Point for 1/4 sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the 1915 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T27N</td><td>R26E</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">S14</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">1/4 —</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">S23</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">1990</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 22 lks. W. of a trail road, bears NNE and SSW.</p>	T27N	R26E	S14		1/4 —		S23		1990	
T27N	R26E										
S14											
1/4 —											
S23											
1990											

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.07	The cor. of secs. 14, 15, 22, and 23.
40.31	<p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' E., bet. secs. 33 and 34.</p> <p>Over rolling land.</p>
40.31	<p>The 1/4 sec. cor. of secs. 33 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. 1/4 S33 S34 1915.</p>
	<p>Remark the brass cap to read</p>
	<p style="text-align: center;">T27N R26E</p>
	<p style="text-align: center;">1/4</p>
	<p style="text-align: center;">S33   S34</p>
	<p style="text-align: center;">1990</p>
	<p style="text-align: center;">1915</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A juniper, 7 ins. diam., bears S. 54° E., 161 lks. dist., mkd. 1/4 S34 BT.</p>
	<p style="padding-left: 40px;">A piñon, 6 ins. diam., bears N. 39° W., 42 lks. dist., mkd. 1/4 S33 BT.</p>
	<p style="text-align: center;">N. 0°01' W., beginning new measurement.</p>
	<p>Over rolling land.</p>
9.88	<p>Point for the S-N 1/64 sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the original temporary point.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R26E</p>
	<p style="text-align: center;">S-N</p>
	<p style="text-align: center;">1/64</p>
	<p style="text-align: center;">S33   S34</p>
	<p style="text-align: center;">1990</p>

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p>
	<p>A piñon, 10 ins. diam., bears S. 12 1/2° E., 98 lks. dist., mkd. S-N 1/64 S34 BT.</p>
	<p>A piñon, 14 ins. diam., bears S. 65 1/4° W., 108 lks. dist., mkd. S-N 1/64 S33 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
19.76	<p>Point for the N 1/16 sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the original temporary point.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R26E N1/16 S33   S34 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
20.20	<p>Graded road, 38 lks. wide, bears NE and SW.</p>
21.35	<p>Canal, 6 lks. wide, 4 ft. deep, drains SW.</p>
22.21	<p>The meander cor. of secs. 33 and 34, on N. bdy. of right-of-way of S. Side Canal, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R26E S33 S34 MC 1915.</p>
	<p>Add the marks 1990 to the brass cap.</p>
	<p>Cor. is located in a barbed wire fence, 3 strands, bears NE and SW.</p>
	<p style="text-align: center;">_____</p> <p>N. 0°03' E., beginning new measurement.</p>
	<p>Over nearly level land.</p>
3.995	<p>An original closing cor. monument of secs. 33 and 34, an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. CC S33 S34 T27N R26E 1915.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located in a barbed wire fence, 8 strands, bears E. and W.</p> <hr/> <p>N. 0°11' E., beginning new measurement on a blank line through Tract 37.</p> <p>Over nearly level land.</p>
13.515	<p>Point for the cor. of secs. 27, 28, 33, and 34, at proportionate dist., falls in an abandoned cultivated field; there is no remaining evidence of the 1915 temporary point. Not remonumented.</p> <hr/>
	<p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>N. 89°55' W., bet. secs. 27 and 34.</p> <p>Over rolling land.</p>
20.01	<p>Point for the E 1/16 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S27 E1/16 — S34 1990</p> <p>from which</p> <p style="padding-left: 40px;">The southernmost cor. of a wood frame house, 36 x 26 ft., bears N. 6 1/2° E., 200 lks. dist., long side bears NW.</p> <p style="padding-left: 40px;">The SE cor. of a wood frame house, 36 x 26 ft., bears N. 44° E., 172 1/2 lks. dist., long side bears WNW.</p> <p style="padding-left: 40px;">A wood power pole, bears S. 22° E., 139 lks. dist., with mks. WCC HPT H289 SPPAS 530.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
40.02	<p>Cor. is located on N. edge of a trail road, bears E. and W.</p> <p>The 1/4 sec. cor. of secs. 27 and 34, determined at record bearing and distance from the remaining 1915 bearing tree:</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">A piñon, 17 ins. diam., bears N. 66 1/4° W., 275 lks. dist., with faint scribe mks. 1/4 visible on open blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S27 1/4 — S34 1990</p> <p>from which</p> <p style="text-align: center;">The SW cor. of a wood frame house, 40 x 25 ft., bears N. 57 3/4° E., 256 1/2 lks. dist., long side bears N.</p> <p style="text-align: center;">The NE cor. of a wood frame house, 50 x 45 ft., bears N. 79 1/2° W., 264 lks. dist., long side bears S.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 8 lks. E. of W. edge of a graded road, 27 lks. wide, bears N. and S.</p> <p>From this cor. point, a rebar, 5/8 in. diam., set 6 ins. below the surface of the ground, bears S. 34° W., 2 1/2 lks. dist., with yellow plastic cap mkd. LS 17428; established by George Perce, Arizona R.L.S. No. 17428, in 1990.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°57' W., beginning new measurement.</p> <p>Over nearly level land.</p>
20.00	<p>Point for the W 1/16 sec. cor. of secs. 27 and 34, identical with the meander cor. on the N. bdy. of right-of-way of S. Side Canal, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S27 W1/16 ———— MC S34 1990</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in an abandoned reservoir.</p>
27.96	<p>Point for an original closing cor. monument of secs. 27 and 34, at proportionate dist.; there is no remaining evidence of the original cor. Not remonumented.</p> <p>Thence continue on a blank line through Tract 37.</p>
40.00	<p>The point for the cor. of secs. 27, 28, 33, and 34.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>N. 0°09' W., on a blank line through Tract 37.</p> <p>Over nearly level land.</p>
26.47	<p>An original closing cor. monument of secs. 27 and 28, an iron post, 2 ins. diam., firmly set, projecting 8 ins. above a mound of stone, 3 ft. base, 1 1/2 ft. high, with brass cap mkd. T27N R26E S27 S28 CC 1915.</p> <p>Cor. is located in a barbed wire fence, 4 strands, bears E. and W.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>N. 0°02' W., beginning new measurement, bet. secs. 27 and 28.</p> <p>Over rolling land.</p>
3.525	<p>Point for the N-S 1/64 sec. cor. of secs. 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center; margin: 10px 0;">             T27N R26E              N-S              1/64              S28   S27              1990           </p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
13.54	<p>The 1/4 sec. cor. of secs. 27 and 28, monumented with a bent iron post, 1 in. diam., loosely set, projecting 16 ins. above ground, in a mound of stone, 2 ft. base, 1 ft. high, with brass cap mkd. 1/4 S28 S27 1915.</p>




## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T27N R26E
	1/4
	S28   S27
	1990
	from which the remaining 1915 bearing tree
	A forked juniper, 18 ins. diam. at base, bears
	N. 76 1/2° E., 76 1/2 lks. dist., with scribe mks.
	1/4 S27 BT visible on open blaze. (Record: N. 78° E.,
	75 lks. dist.)
	and a new accessory
	An angle iron, bears N. 59 3/4° E., 95 1/2 lks. dist.,
	firmly set, projecting 24 ins. above ground, with mks. PT
	1596+7667, serving as a monument for the S. bdy. of the
	right-of-way of Arizona State Highway 264.
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case
	beneath the stainless steel post.
	Destroy the 1915 iron post.
	N. 0°04' W., beginning new measurement.
	Over rolling land.
1.06	S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
2.86	Center of Arizona State Highway 264, asphalt pavement, 39 lks. wide, bears ESE and WNW.
4.77	N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
9.105	Point for the meander cor. of secs. 27 and 28, on the S. bdy. of right-of-way of proposed N. Side Canal, at proportionate dist.;
	there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	 <p style="margin: 0;">T27N R26E MC S28   S27 1990</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
36.65	Graded road, 36 lks. wide, bears ENE and WSW.
40.03	<p>The cor. of secs. 21, 22, 27, and 28, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. T27N R26E S21 S22 S28 S27 1915.</p> <p>from which the remaining 1915 tree</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears S. 71° E., 224 lks. dist., with scribe mks. 27N R26E S27 visible on partially healed blaze. (Record: S. 71 1/2° E., 225 lks. dist.)</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears N. 81° E., 260 1/2 lks. dist., mkd. T27N R26E S22 BT.</p> <p>Add the marks 1990 to the brass cap.</p> <hr style="border: 0.5px solid black;"/> <p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>N. 89°53' W., bet. secs. 22 and 27.</p> <p>Over rolling land.</p>
40.00	<p>The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. 1/4 S22 S27 1915.</p> <p>Remark the brass cap to read</p> <p style="text-align: center; padding-left: 40px;">             T27N R26E              S22              1/4 —              S27              1990              1915           </p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which the remaining 1915 bearing tree</p> <p style="padding-left: 40px;">A forked piñon, 8 ins. diam. at base, bears N. 10 1/2° E., 57 1/2 lks. dist., with scribe mks. 1/4 S22 BT visible on open blaze. (Record: 18 ins. diam., N. 10° E., 55 lks. dist.)</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A piñon, 8 ins. diam., bears S. 45 1/2° E., 82 lks. dist., mkd. 1/4 S27 BT.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 89°57' W., beginning new measurement.</p> <p>Over rolling land.</p>
31.00	Graded road, 36 lks. wide, bears ENE and WSW.
40.02	The cor. of secs. 21, 22, 27, and 28.
	<hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°01' W., bet. secs. 21 and 22.</p> <p>Over rolling land.</p>
39.99	<p>The 1/4 sec. cor. of secs. 21 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. 1/4 S21 S22 1915.</p> <p>Remark the brass cap to read</p> <div style="text-align: center; padding-left: 100px;"> <p>T27N R26E</p> <p>1/4</p> <p>S21   S22</p> <p>1990</p> <p>1915</p> </div> <p>from which the 1915 bearing trees</p> <p style="padding-left: 40px;">A juniper stump, 14 ins. diam., bears N. 77° E., 52 lks. dist., with visible axe mks.</p> <p style="padding-left: 40px;">A forked juniper, 17 ins. diam. at base, bears S. 51° W., 43 lks. dist., with scribe mks. 1/4 S21 BT visible on open blaze. (Record: S. 52 1/2° W.)</p>

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
39.97	<p>and a new bearing tree</p> <p>A forked juniper, 12 ins. at base, bears N. 62 1/2° E., 62 lks. dist., mkd. 1/4 S22 BT.</p> <hr/> <p>N. 0°02' W., beginning new measurement.</p> <p>Over rolling and broken land.</p> <p>The cor. of secs. 15, 16, 21, and 22, determined at record bearings and distances from the remaining 1915 bearing trees:</p> <p>A piñon, 8 ins. diam., bears S. 56° E., 58 lks. dist., with scribe mks. T27N R26E S22 BT visible on open blaze.</p> <p>A piñon, 12 ins. diam., bears N. 47° W., 20 lks. dist., with scribe mks. T27N R26E S16 BT visible on open blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table data-bbox="841 1115 993 1272" style="margin-left: auto; margin-right: auto;"> <tr><td>T27N</td><td>R26E</td></tr> <tr><td>S16</td><td>S15</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S21</td><td>S22</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">1990</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T27N	R26E	S16	S15			S21	S22	1990	
T27N	R26E										
S16	S15										
S21	S22										
1990											
39.90	<p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>N. 89°53' W., bet. secs. 15 and 22.</p> <p>Over rolling and broken land.</p> <p>The 1/4 sec. cor. of secs. 15 and 22, determined at record bearings and distances from the 1915 bearing trees:</p> <p>A piñon, 15 ins. diam., bears N. 32 1/2° E., 71 lks. dist., with scribe mks. 1/4 S14 BT visible on open blaze.</p> <p>A piñon, 24 ins. diam., bears S. 35° W., 92 lks. dist., with scribe mks. 1/4 S22 BT visible on open blaze.</p>										

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona


CHAINS	
40.04	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S15 1/4 — S22 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <hr/> <p>N. 89°39' W., beginning new measurement.</p> <p>Over rolling and broken land.</p> <p>The cor. of secs. 15, 16, 21, and 22.</p>
20.02	<p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°13' W., bet. secs. 32 and 33.</p> <p>Over rolling land.</p> <p>The S 1/16 cor. of secs. 32 and 33, identical with the meander cor. on the N. bdy. of right-of-way of South Side Canal (record erroneously states proposed North Side Canal), monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. S1/16 S32 S33 1915.</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T27N R26E S1/16 S32   S33 — — MC 1990 1915</p> <p>from which the original bearing trees</p> <p style="text-align: center;">A juniper, 10 ins. diam., bears S. 6 1/4° E., 94 lks. dist., with scribe mks. S33 visible on partially healed blaze. (Record: S. 4 1/2° E., 93 lks. dist.)</p>

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A piñon, 10 ins. diam., bears S. 89 1/2° W., 177 1/2 lks. dist., with scribe mks. S1/16 S32 BT visible on open blaze. (Record: 12 ins. dia., W., 180 lks. dist.)</p> <hr/> <p>N. 0°04' W., beginning new measurement.</p> <p>Over rolling land.</p> <p>9.98 Point for the N-S 1/64 sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E N-S 1/64 S32   S33 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 30 lks. N. of a graded road, 30 lks. wide, bears E. and W.</p>
19.96	<p>The 1/4 sec. cor. of secs. 32 and 33, monumented with a bent iron post, 1 in. diam., loosely set, projecting 16 ins. above ground, with brass cap mkd. 1/4 S32 S33 1915.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E 1/4 S32   S33 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Destroy the 1915 iron post.</p> <hr/> <p>N. 0°01' W., beginning new measurement.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
10.015	<p>Over rolling land.</p> <p>Point for the S-N 1/64 sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S-N 1/64 S32   S33 1990</p>
15.625	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the original meander cor. of secs. 32 and 33, on the left bank of the Pueblo Colorado River, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E MC </p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on poorly defined left bank of Pueblo Colorado Wash, bears NE and SW.</p>
20.03	<p>Point for the N 1/16 sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the original temporary point. Point falls in Pueblo Colorado Wash. Not remonumented.</p>
29.05	<p>Right bank of Pueblo Colorado Wash, bears NE and SW.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
30.045	<p>The N-N 1/64 sec. cor., identical with the original meander cor. of secs. 32 and 33, on the right bank of the Pueblo Colorado River, monumented with a bent iron post, 1 in. diam., loosely set, projecting 10 ins. above ground, with brass cap mkd. T27N R26E 1/64 S32 S33 MC 1915.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R26E N-N 1/64 S32   S33 — — MC 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Destroy the original iron post.</p> <p>Cor. is located at foot of slope, bears NE and SW.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°18' E., beginning new measurement.</p> <p>Over rolling land.</p>
10.035	<p>Point for the cor. of secs. 28, 29, 32, and 33, at proportionate dist.; there is no remaining evidence of the 1915 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R26E S29   S28 — — S32   S33 1990</p> </div>



Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>From the point for the cor. of secs. 27, 28, 33, and 34, inside Tract 37.</p>
	<p>N. 89°50' W., on a blank line through Tract 37.</p> <p>Over nearly level land.</p>
27.97	<p>Point for a closing cor. of secs. 28 and 33, at proportionate dist. Point falls in Pueblo Colorado Wash. Not remonumented.</p>
	<p>Thence bet. secs. 28 and 33.</p>
74.11	<p>Point for the original meander cor. of secs. 28 and 33, on the right bank of the Pueblo Colorado River, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R26E S28 ———/ MC S33 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located on right bank of Pueblo Colorado Wash, 4 ft. high, bears NE and SW.</p>
80.01	<p>The cor. of secs. 28, 29, 32, and 33.</p>
	<p>N. 0°17' W., bet. secs. 28 and 29.</p> <p>Over rolling land.</p>
10.035	<p>The S-S 1/64 sec. cor. of secs. 28 and 29, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. 1/64 S29 S28 1915.</p>
	<p>Remark the brass cap to read</p>

BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T27N R26E S-S 1/64 S29   S28 1990 1915</p> <p>from which</p> <p style="text-align: center;">A piñon, 8 ins. diam., bears S. 26° W., 171 1/2 lks. dist., mkd. S-S 1/64 S29 BT.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°01' W., beginning new measurement.</p> <p>Over rolling land.</p>
9.955	<p>The S 1/16 sec. cor. of secs. 28 and 29, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. S1/16 S29 S28 1915.</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T27N R26E S1/16 S29   S28 1990 1915</p> <p>Cor. is located on E. edge of a wood fence post.</p> <hr style="width: 20%; margin: auto;"/> <p>North, beginning new measurement.</p>
10.01	<p>The N-S 1/64 sec. cor. of secs. 28 and 29, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. 1/64 S29 S28 1915.</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T27N R26E N-S 1/64 S29   S28 1990 1915</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°01' W., beginning new measurement.</p> <p>Over rolling land.</p>

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
10.005	<p>Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the 1915 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E 1/4 S29   S28 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
50.025	<p>The cor. of secs. 20, 21, 28, and 29, monumented with a bent iron post, 2 ins. diam., loosely set, projecting 16 ins. above ground, with brass cap mkd. T27N R26E S20 S21 S29 S28 1915.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S20   S21 ----- S29   S28 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Destroy the 1915 iron post.</p>
40.00	<p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>N. 89°50' W., bet. secs. 21 and 28.</p> <p>Over rolling land.</p> <p>The 1/4 sec. cor. of secs. 21 and 28, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. 1/4 S21 S28 1915.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona


CHAINS	
	<p>Remark the brass to read</p> <p style="text-align: center;">T27N R26E S21 1/4 — S28 1990 1915</p> <hr style="width: 30%; margin: 10px auto;"/>
	<p>N. 89°51' W., beginning new measurement.</p> <p>Over rolling land.</p>
22.18	NE right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
25.00	Center of Arizona State Highway 264, asphalt pavement, 36 lks. wide, bears ESE and WNW.
28.10	SW right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
39.94	The cor. of secs. 20, 21, 28, and 29.
	<hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°05' W., bet. secs. 20 and 21.</p> <p>Over rolling land.</p>
6.73	SW right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
8.37	Center of Arizona State Highway 264, asphalt pavement, 36 lks. wide, bears ESE and WNW.
10.12	NE right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
39.98	<p>Point for the true point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p style="text-align: center;">T27N R26E 1/4 S20   S21 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the 1915 witness cor. to the 1/4 sec. cor. of secs. 20 and 21, bears N. 0°05' W., 0.40 chs. dist., monumented with an iron post, 1 in. diam., firmly set, flush with the surface of the ground, with brass cap mkd. 1/4 S20 S21 WC 1915, and is no longer utilized in the course of this resurvey. Destroy the 1915 iron post.</p> <hr/> <p>N. 0°02' E., beginning new measurement.</p> <p>Over rolling land.</p> <p>The cor. of secs. 16, 17, 20, and 21, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. T27N R26E S17 S16 S20 S21 1915.</p> <p>Add the mks. 1990 to the brass cap.</p>
39.97	<p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>N. 89°49' W., bet. secs. 16 and 21.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate dist.; there is no remaining evidence of the 1915 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S16 1/4 — S21 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
 T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.94	The cor. of secs. 16, 17, 20, and 21.
8.80	From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., hereinbefore described.
9.00	N. 0°02' E., bet. secs. 31 and 32.
15.00	Over nearly level land.
8.80	S. bank of Pueblo Colorado Wash, bears ENE and WSW.
9.00	Point for the original meander cor. of secs. 31 and 32, on the left bank of the Pueblo Colorado River, at proportionate dist.; there is no remaining evidence of the original cor. Point falls in Pueblo Colorado Wash. Not remonumented.
15.00	Point for the original meander cor. of secs. 31 and 32, on the right bank of the Pueblo Colorado River, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <p>T27N R26E            S31   S32              MC            1990</p> </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located on right bank of Pueblo Colorado Wash, bears ENE and WSW.
20.00	Point for the S 1/16 sec. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <p>T27N R26E            S1/16            S31   S32            1990</p> </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
 T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
30.00	<p>Point for the N-S 1/64 sec. cor., at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E          N-S          1/64          S31   S32          1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
39.20	<p>Graded road, 30 lks. wide, bears ENE and WSW.</p>
40.00	<p>The 1/4 sec. cor. of secs. 31 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. 1/4 S31 S32 1915.</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T27N R26E          1/4          S31   S32          1990          1915</p> <hr/> <p>N. 0°02' E., beginning new measurement.</p> <p>Over nearly level land.</p>
10.005	<p>The S-N 1/64 sec. cor. of secs. 31 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. 1/64 S31 S32 1915.</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T27N R26E          S-N          1/64          S31   S32          1990          1915</p> <hr/> <p>N. 0°02' E., beginning new measurement.</p> <p>Over nearly level land.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
10.005	<p>Point for the N 1/16 sec. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E N1/16 S31   S32 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 30 lks. W. of W. bank of a wash, 60 lks. wide, 3 ft. deep, drains S.</p>
20.01	<p>The N-N 1/64 sec. cor. of secs. 31 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. 1/64 S31 S32 1915.</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T27N R26E N-N 1/64 S31   S32 1990 1915</p> <p>Cor. is located 12 lks. N. of a woven wire fence, bears E. and W., and 23 lks. W. of a woven wire fence, bears N. and S.</p>
10.01	<p>N. 0°02' E., beginning new measurement.</p> <p>Over nearly level land.</p> <p>The cor. of secs. 29, 30, 31, and 32, monumented with an iron post, 2 ins. diam., firmly set, flush with the surface of the ground, with brass cap mkd. T27N R26E S29 S30 S31 S32 1915.</p> <p>Add the mks. 1990 to the brass cap.</p> <hr/> <p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>N. 89°59' W., bet. secs. 29 and 32.</p> <p>Over gently rolling land.</p>



## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
9.99	<p>Point for the E-E 1/64 sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S29 E-E 1/64 S32 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
19.98	<p>Point for the E 1/16 sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S29 E1/16 — S32 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
29.97	<p>Point for the W-E 1/64 sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S29 W-E 1/64 S32 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
36.40	Graded road, 38 lks. wide, bears NE and SW.
39.00	Trail road, bears ENE and WSW.

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.96	<p>Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the 1915 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S29 1/4 — S32 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
49.95	<p>Point for the E-W 1/64 sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S29 E-W 1/64 S32 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
59.94	<p>The W 1/16 sec. cor. of secs. 29 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. W1/16 S29 S32 1915.</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T27N R26E S29 W1/16 — S32 1990 1915</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89°53' W., beginning new measurement.</p> <p>Over gently rolling land.</p>

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
9.93	<p>Point for the W-W 1/64 sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S29 W-W 1/64 S32 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
19.86	<p>The cor. of secs. 29, 30, 31, and 32.</p>
8.685	<p>From the cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. T27N R25E R26E S25 S30 S31 S36 1990 1915.</p> <p>S. 89°50' E., bet. secs. 30 and 31.</p> <p>Over nearly level land.</p>
10.005	<p>The W-W 1/64 sec. cor. of secs. 30 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. 1/64 S30 S31 1915.</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T27N R26E S30 W-W 1/64 S31 1990 1915</p> <hr/> <p>S. 89°47' E., beginning new measurement.</p> <p>Over nearly level land.</p>
10.005	<p>The W 1/16 sec. cor. of secs. 30 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. W1/16 S30 S31 1915.</p>

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Remark the brass cap to read</p> <p style="text-align: center;">T27N R26E S30 W1/16 — S31 1990 1915</p> <hr/> <p>S. 89°51' E., beginning new measurement.</p> <p>Over nearly level land.</p>
10.015	<p>The E-W 1/64 sec. cor. of secs. 30 and 31, monumented with a bent iron post, 1 in. diam., loosely set, projecting 24 ins. above ground, with brass cap mkd. 1/64 S30 S31 1915.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S30 E-W 1/64 S31 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Destroy the original iron post.</p> <hr/> <p>S. 89°49' E., beginning new measurement.</p> <p>Over nearly level land.</p>
10.01	<p>The 1/4 sec. cor. of secs. 30 and 31, monumented with a bent iron post, 1 in. diam., loosely set, projecting 21 ins. above ground, with brass cap mkd. 1/4 S30 S31 1915.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T27N R26E S30 1/4 — S31 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Destroy the 1915 iron post.</p> <hr/> <p>S. 89°59' E., beginning new measurement.</p> <p>Over nearly level land.</p>
10.00	<p>The W-E 1/64 sec. cor. of secs. 30 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. 1/64 S30 S31 1915.</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T27N R26E S30 W-E 1/64 S31 1990 1915</p> <hr/> <p>S. 89°59' E., beginning new measurement.</p> <p>Over nearly level land.</p>
10.015	<p>The E 1/16 sec. cor. of secs. 30 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. E1/16 S30 S31 1915.</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T27N R26E S30 E1/16 — S31 1990 1915</p> <hr/> <p>East, beginning new measurement.</p> <p>Over nearly level land.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
10.01	<p>The E-E 1/64 sec. cor. of secs. 30 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. 1/64 S30 S31 1915.</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T27N R26E S30 E-E 1/64 S31 1990 1915</p> <hr/> <p>S. 89°56' E., beginning new measurement.</p> <p>Over nearly level land.</p>
10.00	<p>The cor. of secs. 29, 30, 31, and 32.</p> <hr/> <p>N. 0°02' E., bet. secs. 29 and 30.</p> <p>Over rolling land.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the 1915 cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E 1/4 S30   S29 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.04	<p>The cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. T27N R26E S19 S20 S29 S30 1915.</p> <p>Add the mks. 1990 to the brass cap.</p> <hr/> <p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>N. 89°57' W., bet. secs. 20 and 29.</p> <p>Over rolling land.</p>

## BOOK 5418

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
36.60	Wash, 182 lks. wide, 10 ft. deep, drains SW.
39.79	The 1/4 sec. cor. of secs. 20 and 29, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. 1/4 S20 S29 1915.
	Remark the brass cap to read
	<p style="text-align: center;">T27N R26E S20 1/4 — S29 1990 1915</p> <hr style="width: 30%; margin: auto;"/>
	N. 89°57' W., beginning new measurement.
	Over rolling land.
39.90	The cor. of secs. 19, 20, 29, and 30.
	<hr/> <p>From the cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd. T27N R25E R26E S19 S24 S25 S30 1990 1915.</p>
	from which the original bearing trees
	<p style="padding-left: 40px;">A juniper, 30 ins. diam., bears N. 62 1/2° E., 118 lks. dist., with scribe mks. T27N R26E S19 visible on partially healed blaze.</p>
	<p style="padding-left: 40px;">A juniper, 30 ins. diam., bears S. 59 3/4° W., 33 lks. dist., with scribe mks. T27N R25E S25 BT visible on open blaze.</p>
	S. 89°55' E., bet. secs. 19 and 30.
	Over rolling land.
38.54	The 1/4 sec. cor. of secs. 19 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap erroneously mkd. 1/4 S29 S30 1915.
	Remark the brass cap to read

.. 64  
**BOOK 54 18**

Dependent Resurvey of a Portion of the Subdivisional Lines,  
 T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T27N R26E S19 1/4 — S30 1990 1915 <hr style="width: 30%; margin: 10px auto;"/>
	S. 89°49' E., beginning new measurement.  Over rolling land.
39.97	The cor. of secs. 19, 20, 29, and 30.  <hr/> N. 0°01' W., bet. secs. 19 and 20.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the 1915 cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T27N R26E 1/4 S19   S20 1990
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
52.22	S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
53.94	Center of Arizona State Highway 264, asphalt pavement, 40 lks. wide, bears ESE and WNW.
55.68	N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
80.00	Point for the cor. of secs. 17, 18, 19, and 20, at proportionate dist.; there is no remaining evidence of the 1915 cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
39.85	<div style="text-align: center; margin-bottom: 10px;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>T27N R26E</td></tr> <tr><td>S18   S17</td></tr> <tr><td style="border-top: 1px solid black;">S19   S20</td></tr> <tr><td style="border-top: 1px solid black;">1990</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <hr style="border: 0.5px solid black;"/> <p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>N. 89°55' W., bet. secs. 17 and 20.</p> <p>Over rolling land.</p> <p>The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. 1/4 S17 S20 1915.</p> <p>Remark the brass cap to read</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>T27N R26E</td></tr> <tr><td>S17</td></tr> <tr><td>1/4 —</td></tr> <tr><td>S20</td></tr> <tr><td>1990</td></tr> <tr><td>1915</td></tr> </table> </div> <hr style="border: 0.5px solid black;"/> <p>N. 89°58' W., beginning new measurement.</p> <p>Over rolling land.</p>	T27N R26E	S18   S17	S19   S20	1990	T27N R26E	S17	1/4 —	S20	1990	1915
T27N R26E											
S18   S17											
S19   S20											
1990											
T27N R26E											
S17											
1/4 —											
S20											
1990											
1915											
39.83	<p>The cor. of secs. 17, 18, 19, and 20.</p> <hr style="border: 0.5px solid black;"/> <p>From the cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T27N R25E R26E S13 S18 S19 S24 1990.</p> <p>from which the 1990 bearing tree</p> <p style="margin-left: 40px;">A piñon, 15 ins. diam., bears S. 88 1/4° W., 107 1/2 lks. dist., with scribe mks. T27N R25E S24 BT visible on partially healed blaze.</p> <p>S. 89°54' E., bet. secs. 18 and 19.</p> <p>Over rolling land.</p>										

## BOOK 5418


Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
38.55	<p>Point for the 1/4 sec. cor. of secs. 18 and 19, determined at record distances from the 1915 bearing trees:</p> <p style="padding-left: 40px;">A juniper, 30 ins. diam., bears S. 10° E., 121 lks. dist., with scribe mks. 1/4 S19 BT visible on open blaze. (Record: S. 4 3/4° E.)</p> <p style="padding-left: 40px;">A juniper, 20 ins. diam., bears N. 59 1/4° W., 153 lks. dist., with scribe mks. 1/4 S18 BT visible on open blaze. (Record: N. 59° W.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;">       T27N R26E        S18        1/4 —        S19        1990     </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 89°51' E., beginning new measurement.</p> <p>Over rolling land.</p>
1.77	SW right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
3.87	Center of Arizona State Highway 264, asphalt pavement, 39 lks. wide, bears SE and NW.
5.96	NE right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
39.93	The cor. of secs. 17, 18, 19, and 20.


Dependent Resurvey of a Portion of the  
 Subdivision of Section 26,  
 T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">Restoring the Survey executed by                      F. C. Miller, in 1915</p> <hr/> <p style="text-align: center;">NW1/4 of Section 26</p> <hr/>
	<p>From the N 1/16 sec. cor. of secs. 26 and 27, hereinbefore described.</p>
	<p>S. 89°48' E., on the E. and W. center line of the NW1/4 of sec. 26.</p>
	<p>Over nearly level land.</p>
<p>20.00</p>	<p>Point for the NW 1/16 sec. cor. of sec. 26, identical with the original meander cor. on the left bank of the Pueblo Colorado River, now also functioning as a special meander cor., at proportionate dist.; there is no remaining evidence of the original cor. Point falls in Pueblo Colorado Wash. Not remonumented.</p>
<p>25.00</p>	<p>The meander cor. on the N. bdy. of right-of-way of the S. Side Canal, now functioning as a special meander cor., monumented with an iron post, 1 in. diam., firmly set, flush with the surface of the ground, with brass cap mkd. N 1/1 S26 1915.</p>
	<p>Remark the brass cap to read</p> <div style="text-align: center;"> <p>T27N R26E</p> <p>S</p> <p>N —   N SMC</p> <p>26</p> <p>1990</p> <p>1915</p> </div> <p>Cor. is located 165 lks. W. of an irrigation ditch, 20 lks. wide, 4 ft. deep, drains SSW.</p>
	<p style="text-align: center;">Dependent Resurvey of a Portion of the                      Subdivision of Section 27,                      T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona</p>
	<p style="text-align: center;">Restoring the Survey executed by                      F. C. Miller, in 1915</p> <hr/> <p>From the 1/4 sec. cor. of secs. 27 and 34, hereinbefore described.</p>

Dependent Resurvey of a Portion of the  
 Subdivision of Section 27,  
 T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°12' W., on the N. and S. center line of sec. 27.
	Over gently rolling land.
6.80	Graded road, 45 lks. wide, bears ENE and WSW.
7.55	Irrigation ditch, 23 lks. wide, 4 ft. deep, drains WSW.
8.02	Woven wire and barbed wire fence, bears ENE and WSW.
9.98	Point for the C-S-S 1/64 sec. cor. of sec. 27, identical with the meander cor. on the N. bdy. of right-of-way of South Side Canal, now functioning as a special meander cor., at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <p>T27N R26E                      C-S-S 1/64                      C                      S   27                        C                      SMC                      1990</p> </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located in an abandoned cultivated field.
18.14	S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
19.00	Center of Arizona State Highway 264, asphalt pavement, 46 lks. wide, bears ENE and WSW.
19.96	The C-S 1/16 cor. of sec. 27, monumented with an iron post, set 15 ins. below the surface of the ground, with brass cap mkd. S1/16 1/4 S27 1/4 1915.
	Remark the brass cap to read
	<div style="text-align: center;"> <p>T27N R26E                      C                      S1/16   S27                      C                      1990                      1915</p> </div>

Dependent Resurvey of a Portion of the  
 Subdivision of Section 27,  
 T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 69°15' E., 63.7 ft. dist., with brass cap mkd. T27N R26E C-S1/16 S27 RM 63.7 FT. TO COR. 1990 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 17°13' W., 73.0 ft. dist., with brass cap mkd. T27N R26E C-S1/16 S27 RM 73.0 FT. TO COR. 1990 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in graded area within right-of-way of Arizona State Highway 264.</p> <hr/> <p>N. 0°03' E., beginning new measurement.</p> <p>Over nearly level land.</p> <p>0.83 N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.</p> <p>8.51 The original meander cor. on the left bank of the Pueblo Colorado River, now serving as a special meander cor., monumented with a badly corroded, concrete filled, flanged iron post, 20 ins. long, 1 in. diam., set flush with surface of the ground, and is accepted as the best available evidence of the original cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R26E</p> <p>SMC</p> <p>C</p>  <p>S 27</p> <p>C</p> <p>1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Dependent Resurvey of a Portion of the  
Subdivision of Section 27,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit the remains of the original iron post inside the stainless steel post.</p> <p>Cor. is located on the left bank of Pueblo Colorado Wash, bears E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°06' E., beginning new measurement.</p> <p>Over nearly level land.</p> <p>9.50 Right bank of Pueblo Colorado Wash, bears NE and SW.</p> <p>11.50 The center 1/4 sec. cor. of sec. 27, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. C1/4 S27 1915.</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T27N R26E C1/4 S27 1990 1915</p> <p>Cor. is located 1/2 lk. W. of barbed wire fence, 5 strands, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03' E., beginning new measurement.</p> <p>Over nearly level land.</p> <p>9.995 The C-S-N 1/64 sec. cor. of sec. 27, monumented with a badly bent and corroded iron post, 36 ins. long, 1 in. diam., set 8 ins. below the surface of the ground, with brass cap mkd. 1/64 S27 1915.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S27 C-S-N 1/64 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
--------	---

Dependent Resurvey of a Portion of the  
 Subdivision of Section 27,  
 T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Destroy the original iron post.</p> <p>Cor. is located 1 1/2 lks. W. of a barbed wire fence, 5 strands, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03' E., beginning new measurement, on continuation of previous bearing.</p> <p>Over nearly level land.</p> <p>1.70 Point for the meander cor. on the S. bdy. of right-of-way of proposed North Side Canal, now functioning as a special meander cor. of sec. 27, at record dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T27N R26E              SMC              C</p> <hr style="width: 50%; margin: 0 auto;"/> <p>S   27              C              1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 1 1/2 lks. W. of a barbed wire fence, 5 strands, bears N. and S.</p> <hr style="width: 100%; margin: 10px 0;"/> <p>From the point for the C-E 1/16 sec. cor. of sec. 27, determined at record bearing and distance from the original bearing tree:</p> <p style="margin-left: 40px;">A piñon, 18 ins. diam., bears S. 67° E., 280 lks. dist., with illegible marks and hack marks visible on open blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T27N R26E              E1/16              C—C              S27              1990</p> </div>
--------	---

Dependent Resurvey of a Portion of the  
 Subdivision of Section 27,  
 T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona


CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>From this cor. point, a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, bears S. 61 1/4° W., 4.3 lks. dist., with yellow plastic cap mkd. LS 17428; established by George Perce, Arizona R.L.S. No. 17428, in 1990.</p>
	<p>From this same cor. point, the 1/4 sec. cor. of secs. 26 and 27, bears S. 89°56' E., 19.975 chs. dist., hereinbefore described. This tie is included only to verify the position of the C-E 1/16 sec. cor. of sec. 27. The intervening cor. was searched for and no evidence was found.</p>
	<p>S. 89°56' W., on the E. and W. center line of sec. 27.</p>
	<p>Over nearly level land.</p>
<p>6.65</p>	<p>Left bank of Pueblo Colorado Wash, bears ENE and WSW.</p>
<p>7.47</p>	<p>Point for the original meander cor. on the left bank of the Pueblo Colorado River, at proportionate dist.; there is no remaining evidence of the original cor. Point falls in Pueblo Colorado Wash. Not remonumented.</p>
<p>10.025</p>	<p>Point for the C-W-E 1/64 sec. cor. of sec. 27, at proportionate dist.; there is no remaining evidence of the original temporary stake. Point falls in Pueblo Colorado Wash. Not remonumented.</p>
<p>17.445</p>	<p>Point for the original meander cor. on the right bank of the Pueblo Colorado River, now functioning as a special meander cor., at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R26E              S              C ——— / C SMC              27/              1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located on present right bank of Pueblo Colorado Wash, bears ENE and WSW.</p>



Dependent Resurvey of a Portion of the  
 Subdivision of Section 27,  
 T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.05	The center 1/4 sec. cor. of sec. 27.
	<p>West, beginning new measurement.</p> <p>Over nearly level land.</p>
10.008	<p>Point for the C-E-W 1/64 sec. cor. of sec. 27, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S27 C-E-W 1/64 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on the E. edge of a trail road, bears N. and S., and 26 lks. E. of a barbed wire fence, 5 strands, bears N. and S.</p>
20.015	<p>Point for the C-W 1/16 sec. cor. of sec. 27, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E W1/16 C—C S27 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in an abandoned cultivated field.</p>
30.023	<p>Point for the C-W-W 1/64 sec. cor. of sec. 27, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>


Dependent Resurvey of a Portion of the  
 Subdivision of Section 27,  
 T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T27N R26E                      S27                      C-W-W                      1/64                      1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
33.19	NE right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
35.99	Center of Arizona State Highway 264, asphalt pavement, 40 lks. wide, bears SE and NW.
38.50	SW right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
40.03	The 1/4 sec. cor. of secs. 27 and 28, hereinbefore described.
	<hr/> <p>NE1/4 of Section 27</p> <hr/>
	<p>From the N 1/16 sec. cor. of secs. 26 and 27, hereinbefore described.</p> <p>S. 89°47' W., on the E. and W. center line of the NE1/4 of sec. 27.</p> <p>Over nearly level land.</p>
2.195	<p>The meander cor. on the S. bdy. of right-of-way of proposed N. Side Canal, now functioning as a special meander cor., monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. MC N1/16 S27 1915.</p> <p>Remark the brass cap to read</p> <div style="text-align: center;"> <p>T27N R26E</p>  </div>


Dependent Resurvey of a Portion of the  
Subdivision of Section 27,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>From the NE 1/16 sec. cor. of sec. 27, monumented with a badly corroded iron post, 5 1/2 ins. long, approximately 1 in. diam., with concrete core, 8 ins. long, firmly set, flush with the surface of the ground, and is accepted as the best available evidence of the original cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E NE1/16 S27 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Bury the remains of the original iron post alongside the stainless steel post.</p> <p>From this cor. point, the C-E 1/16 sec. cor. of sec. 27, bears South, 19.965 chs. dist. This tie is included only to verify the position of the NE 1/16 sec. cor. of sec. 27. The intervening cors. were searched for and no evidence was found.</p> <p>From this same cor. point, a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, bears S. 45° W., 4 lks. dist., with aluminum cap mkd. M.T. 30 LS6355.</p> <p>From this same cor. point, a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, bears N. 70 1/2° W., 7 lks. dist., with yellow plastic cap mkd. LS 17428.</p> <p>N. 0°06' W., on the N. and S. center line of the NE1/4 of sec. 27.</p> <p>Over nearly level land.</p>
2.80	<p>The meander cor. on the S. bdy. of right-of-way of proposed North Side Canal, now functioning as a special meander cor., monumented with a badly corroded iron post, 14 ins. long, 1 in. diam., and fragments of iron flanges, set 16 ins. below the surface of the ground, and is accepted as the best available evidence of the original cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the  
 Subdivision of Section 27,  
 T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T27N R26E                      SMC                      E                        1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Bury the remains of the original iron post alongside the stainless steel post.</p> <p>From this cor. point, a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, bears S. 46 1/2° W., 3.6 lks. dist., with aluminum cap mkd. M.T.-29 LS 6355.</p> <p>From this same cor. point, a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, bears N. 67 1/2° W., 6.9 lks. dist., with yellow plastic cap mkd. LS 17428.</p> <hr/> <p>From the point for the C-W-E 1/64 sec. cor. of sec. 27.</p> <p>N. 0°01' W., on the N. and S. center line of the W1/2 of the NE1/4 of sec. 27, on record bearing.</p> <p>Over nearly level land.</p> <p>0.70 Right bank of Pueblo Colorado Wash, bears ENE and WSW.</p> <p>4.50 Point for the original meander cor. on the right bank of the Pueblo Colorado River, at record dist.; there is no remaining evidence of the original cor. Not remonumented.</p> <p>From this cor. point, a rebar, 5/8 in. diam., firmly set flush with the surface of the ground, bears S. 71° W., 2 1/2 lks. dist., with yellow plastic cap mkd. LS 17428; established by George Perce, Arizona R.L.S. No. 17428, in 1990. Original evidence was not utilized in reestablishing this cor., and it is not utilized in the course of this resurvey.</p> <p>8.00 Right bank of Pueblo Colorado Wash, bears SE and NW.</p> <p>10.00 Point for the SW-NE 1/64 sec. cor. of sec. 27, at record dist.; there is no remaining evidence of the original cor. Not remonumented.</p> <p>18.40 Right bank of Pueblo Colorado Wash, bears E. and W.</p>

Dependent Resurvey of a Portion of the  
 Subdivision of Section 27,  
 T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.00	<p>Point for the C-W-NE 1/64 sec. cor. of sec. 27, at record dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E                      S27                      C-W-NE                      1/64                      1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, bears S. 83 1/4° W., 4 lks. dist., with yellow plastic cap mkd. LS 17428; established by George Perce, Arizona R.L.S. No. 17428, in 1990. Original evidence was not utilized in reestablishing this cor., and it is not utilized in the course of this resurvey.</p> <p>From this same cor. point, a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above ground, bears S. 29 1/4° W., 4.3 lks. dist.; of unknown origin, and is not utilized in the course of this resurvey.</p>
24.00	<p>Point for the meander cor. on the S. bdy. of right-of-way of proposed North Side Canal, now functioning as a special meander cor., at record dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E                      SMC                        1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, an unflanged iron pipe, 1 in. diam., firmly set flush with the surface of the ground, bears S. 13 3/4° W., 4 lks. dist.; of unknown origin, and is not utilized in the course of this resurvey.</p>

Dependent Resurvey of a Portion of the  
Subdivision of Section 27,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

From this same cor. point, a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, bears S. 35 3/4° W., 4.5 lks. dist., with aluminum cap mkd. M.T. 32 LS 6355; established by Limbaugh Engineers Inc., in 1968. Original evidence was not utilized in reestablishing this cor., and it is not utilized in the course of this resurvey.

From this same cor. point, a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, bears S. 86° W., 4.4 lks. dist., with yellow plastic cap mkd. LS 17428; established by George Perce, Arizona R.L.S. No. 17428, in 1990. Original evidence was not utilized in reestablishing this cor., and it is not utilized in the course of this resurvey.

SE1/4 of Section 27

From the N-S 1/64 sec. cor. of secs. 26 and 27, hereinbefore described.


N. 89°59' W., on the E. and W. center line of the N 1/2 of the SE1/4 of sec. 27.

Over nearly level land.

20.015

Point for the C-N-SE 1/64 sec. cor. of sec. 27, identical with the meander cor. on N. bdy. of right-of-way of S. Side Canal, and also now functioning as a special meander cor., at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

From this cor. point, a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, bears S. 51 1/4° W., 79 lks. dist., with yellow plastic cap mkd. LS 17428; established by George Perce, Arizona R.L.S. No. 17428, in 1990. The position of this cor. is irreconcilable with the plat position and is not utilized in the course of this resurvey.

Dependent Resurvey of a Portion of the  
Subdivision of Section 27,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona



CHAINS	
30.03	<p>Cor. is located bet. two mobile homes, 2 lks. N. of an entry gate.</p> <p>The NW-SE 1/64 sec. cor. of sec. 27, monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. 1/64 S27 1915.</p>
	<p>Remark the brass cap to read</p> <p style="text-align: center;">T27N R26E S27 NW-SE 1/64 1990 1915</p> <hr style="width: 20%; margin: auto;"/>
	<p>N. 89°53' W., beginning new measurement.</p> <p>Over nearly level land.</p>
7.295	<p>The original meander cor. on the left bank of the Pueblo Colorado River, now functioning as a special meander cor., monumented with a rust encrusted concrete cylinder, 19 ins. long, approximately 1 in. diam., firmly set, flush with the surface of the ground, and is accepted as the best available evidence of the original cor.</p>
	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R26E SMC / S 27 W NW SE 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Deposit the remains of the original iron post inside the stainless steel post.</p>
	<p>Cor. is located 30 lks. W. of a barbed wire fence, 4 strands, bears NNE and SSW.</p> <hr/>

Dependent Resurvey of a Portion of the  
Subdivision of Section 27,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona



CHAINS	<p>From the C-S 1/16 sec. cor. of sec. 27.</p> <p>S. 89°57' E., on the E. and W. center line of the SE1/4 of sec. 27.</p> <p>Over nearly level land.</p>
8.70	<p>The meander cor. on N. bdy. of right-of-way of South Side Canal, now functioning as a special meander cor., monumented with a badly corroded, flanged, concrete filled iron post, 27 ins. long, 1 in. diam., firmly set, flush with the surface of the ground, and is accepted as the best available evidence of the original cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T27N R26E</p> <p>S</p> <p>S ——— / S SMC</p> <p>27/</p> <p>1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 2 lks. N. of a barbed wire fence, 5 strands, bears E. and W.</p>
7.63	<p>From the NW-SE 1/64 sec. cor. of sec. 27.</p> <p>N. 0°23' E., on the N. and S. center line of the NW1/4 of the SE1/4 of sec. 27.</p> <p>Over nearly level land.</p> <p>The original meander cor. on the left bank of the Pueblo Colorado River, now functioning as a special meander cor., monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mks. obliterated except for 1915.</p> <p>Remark the brass cap to read</p>




Dependent Resurvey of a Portion of the  
Subdivision of Section 27,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<div style="text-align: center;"> <p>T27N R26E N NW SE SMC</p>  </div> <hr/> <p>From the NW-SE 1/64 sec. cor. of sec. 27.</p> <p>S. 0°01' E., on the N. and S. center line of the NW1/4 of the SE1/4 of sec. 27, on record bearing.</p> <p>Over nearly level land.</p> <p>8.80 Point for the meander cor. on N. bdy. of right-of-way of S. Side Canal, now functioning as a special meander cor., at record dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>T27N R26E S NW SE S   27</p>  </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, a brass tablet, 2 ins. diam., set in a concrete collar, 14 ins. diam., firmly set, projecting 6 ins. above ground, bears N. 87° W., 6 lks. dist., with top mkd. M.T.-7 LS 6355 1968; established by Limbaugh Engineers Inc., in 1968, using improper reestablishment procedures and is not utilized in the course of this resurvey.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the Record Meanders of the Left Bank of the Pueblo Colorado River in Section 26, T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Restoring the Survey executed by F. C. Miller, in 1915</p>
--------	---



Dependent Resurvey of a Portion of the Record Meanders  
of the Left Bank of the Pueblo Colorado River in Section 26,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
1.24	<p>From the original meander cor. of secs. 26 and 27, on N. bdy. of right-of-way of S. Side Canal and left bank of the Pueblo Colorado River, hereinbefore described.</p> <p>N. 77°46' E., along the adjusted record meanders of the left bank of the Pueblo Colorado River, identical with the N. bdy. of right-of-way of S. Side Canal.</p> <p>Over nearly level land.</p> <p>Point for AP 3 of a metes-and-bounds survey, at distance specified in the exchange deed between the United States of America and Board of National Missions of the Presbyterian Church, dated March 22, 1946.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R26E</p>  </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
9.09	<p>Point for AP 1 on the N. bdy. of right-of-way of S. Side Canal and left bank of the Pueblo Colorado River, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R26E</p>  </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence N. 33°29' E., 4.595 chs., continuing along the adjusted record meanders of the left bank of the Pueblo Colorado River.</p> <p style="margin-left: 40px;">N. 17°02' W., 1.80 chs.</p> <p style="margin-left: 40px;">N. 49°30' E., 7.295 chs.</p>



Dependent Resurvey of a Portion of the Record Meanders  
of the Left Bank of the Pueblo Colorado River in Section 26,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 68°01' E., 3.835 chs. Point for the NW 1/16 sec. cor. of sec. 26, identical with a special meander cor. on the left bank of the Pueblo Colorado River, hereinbefore described.</p>
	<p>Dependent Resurvey of a Portion of the Record Meanders of the S. Bdy. of right-of-way of proposed N. Side Canal in Sec. 27, T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona</p>
	<p>Restoring the Survey executed by F. C. Miller, in 1915</p> <hr/> <p>From the special meander cor. on the E. and W. center line of the NE1/4 of sec. 27, on the S. bdy. of right-of-way of proposed canal, hereinbefore described.</p> <p>S. 11°14' W., along the adjusted record meanders of the S. bdy. of right-of-way of proposed North Side Canal.</p> <p>Over nearly level land.</p>
<p>3.495</p>	<p>Point for AP 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R26E S27 AP 4 1990</p>  </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
<p>3.695</p>	<p>S. 76°32' W., beginning new measurement.</p> <p>Over nearly level land.</p> <p>Point for AP 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Record Meanders of the  
S. Bdy. of right-of-way of proposed N. Side Canal in Sec. 27,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T27N R26E S27</p>  <p style="text-align: center;">AP 5 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, a rebar, 5/8 in. diam., firmly set, projecting 6 ins. above ground, bears S. 57 3/4° W., 11 lks. dist., with aluminum cap mkd. M.T.-25-A LS 6355; established by Limbaugh Engineers Inc. Original evidence was not utilized in establishing this cor., and it is not utilized in the course of this resurvey.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S. 83°32' W., beginning new measurement.</p> <p>Over nearly level land.</p>
4.695	<p>Point for AP 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S27</p>  <p style="text-align: center;">AP 6 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, a rebar, 5/8 in. diam., firmly set, flush with the surface of ground, bears N. 79° W., 1.5 lks. dist., with yellow plastic cap mkd. LS 17428; established by George Perce, Arizona R.L.S. No. 17428, in 1990. Original evidence was not utilized in establishing this cor., and it is not utilized in the course of this resurvey.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 34°27' W., beginning new measurement.</p> <p>Over nearly level land.</p>
3.40	<p>Point for AP 7.</p>



Dependent Resurvey of a Portion of the Record Meanders of the  
S. Bdy. of right-of-way of proposed N. Side Canal in Sec. 27,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R26E S27</p>  <p>AP 7 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, a rebar, 5/8 in. diam., firmly set, flush with the surface of ground, bears S. 41° W., 2 lks. dist., with yellow plastic cap mkd. LS 17428; established by George Perce, Arizona R.L.S. No. 17428, in 1990. Original evidence was not utilized in establishing this cor., and it is not utilized in the course of this resurvey.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 74°57' W., beginning new measurement.</p> <p>Over nearly level land.</p>
4.60	<p>Point for AP 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R26E S27</p>  <p>AP 8 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, a rebar, 5/8 in. diam., firmly set, flush with the surface of ground, bears S. 44° W., 3 lks. dist., with yellow plastic cap mkd. LS 17428; established by George Perce, Arizona R.L.S. No. 17428, in 1990. Original evidence was not utilized in establishing this cor., and it is not utilized in the course of this resurvey.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 34°27' W., beginning new measurement.</p> <p>Over nearly level land.</p>


Dependent Resurvey of a Portion of the Record Meanders of the  
S. Bdy. of right-of-way of proposed N. Side Canal in Sec. 27,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
4.35	<p>The special meander cor. on the N. and S. center line of the NE1/4 of sec. 27, on the S. bdy. of right-of-way of proposed North Side Canal, hereinbefore described.</p> <hr/> <p>From the special meander cor. on the N. and S. center line of the NW1/4 of the NE1/4 of sec. 27, on the S. bdy. of right-of-way of proposed North Side Canal, hereinbefore described.</p> <p>S. 30°21' W., along the adjusted record meanders of the S. bdy. of proposed N. Side Canal.</p> <p>Over nearly level land.</p>
6.505	<p>Point for AP 12.</p> <p>Set a magnet in a 1 x 1 x 2 5/8 ins. white plastic case, 3 ft. below the surface of the ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 62°52' W., 108.3 ft. dist., with brass cap mkd. T27N R26E AP12 S27 RM 108.3 FT. TO COR. 1990, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, for a reference monument, bears N. 8°26' W., 174.9 ft. dist., with brass cap mkd. T27N R26E AP12 S27 RM 174.9 FT. TO COR. 1990, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
9.49	<p>Cor. is located in a wash, 50 lks. wide, 3 ft. deep, drains S.</p> <hr/> <p>S. 45°05' W., beginning new measurement.</p> <p>Over nearly level land.</p> <p>The special meander cor. on the N. and S. center line of sec. 27, on the S. bdy. of right-of-way of proposed North Side Canal, hereinbefore described.</p> <hr/>

Dependent Resurvey of a Portion of the Record Meanders of the  
N. Bdy. of right-of-way of S. Side Canal in Sec. 27,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">Restoring the Survey executed by F. C. Miller, in 1915</p> <hr/> <p>From the C-N-SE 1/64 sec. cor. of sec. 27, identical with a special meander cor. on the N. bdy. of right-of-way of South Side Canal, hereinbefore described.</p> <p>S. 19°31' W., along the adjusted record meanders of the N. bdy. of right-of-way of South Side Canal.</p> <p>Over nearly level land.</p>
8.05	<p>Point for AP 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R26E AP3</p>  <p>S27 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, a brass tablet, 2 ins. diam., set in a concrete collar, 14 ins. diam., firmly set, flush with the surface of the ground, bears S. 38° W., 8 lks. dist., with top mkd. M.T.-4 LS 6355 1968; established by Limbaugh Engineers Inc., in 1968, using improper establishment procedures and is not utilized in the course of this resurvey.</p> <hr/> <p>S. 68°47' W., beginning new measurement.</p> <p>Over nearly level land.</p>
1.40	<p>Point for AP 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R26E AP4</p>  <p>S27 1990</p> </div>

Dependent Resurvey of a Portion of the Record Meanders of the  
N. Bdy. of right-of-way of S. Side Canal in Sec. 27,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
3.80	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <hr/> <p>N. 77°13' W., beginning new measurement.</p> <p>Over nearly level land.</p> <p>Point for AP 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R26E AP5</p>  <p>S27 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <hr/> <p>S. 56°17' W., beginning new measurement.</p> <p>Over nearly level land.</p>
2.78	<p>The special meander cor. on the N. and S. center line of the NW1/4 of the SE1/4 of sec. 27, on the N. bdy. of right-of-way of South Side Canal, hereinbefore described.</p> <hr/> <p>S. 47°31' W., beginning new measurement.</p> <p>Over nearly level land.</p>
1.81	<p>The special meander cor. on the E. and W. center line of the SE1/4 of sec. 27, on the N. bdy. of right-of-way of South Side Canal, hereinbefore described.</p> <hr/>



Survey of a Portion of the East Boundary,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.
	North, bet. secs. 13 and 18.
	Over rolling land.
6.10	Power line, bears NNE and SSW.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <p>T27N R26E R27E 1/4 S13   S18 1990</p> </div>
	from which
	<div style="text-align: center;"> <p>A brass cap, 3 ins. diam., set in a concrete collar, 8 ins. diam., firmly set, projecting 12 ins. above ground, bears N. 71 1/4° W., 116 lks. dist., with top mkd. BIA ROADS and witnessed by an angle iron to the S., mkd. STA#158+43.23.</p> </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
42.55	SE right-of-way fence of Navajo Route 27, barbed wire, 4 strands, parallels highway.
45.59	Center of Navajo Route 27, asphalt pavement, 47 lks. wide, bears NNE and SSW.
48.59	NW right-of-way fence of Navajo Route 27, barbed wire, 4 strands, parallels highway.
80.00	Point for the cor. of secs. 7, 12, 13, and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <p>T27N R26E   R27E S12   S 7 ----- S13   S18 1990</p> </div>

Survey of a Portion of the East Boundary,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>
40.00	<p>North, bet. secs. 7 and 12.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R26E R27E 1/4 S12   S 7 1990</p> </div>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R26E   R27E S 1   S 6 ----- S12   S 7 1990</p> </div>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>
	<p>North, bet. secs. 1 and 6.</p> <p>Over rolling land.</p>

Survey of a Portion of the East Boundary,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R26E R27E 1/4 S 1   S 6 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of Tps. 27 and 28 N., Rs. 26 and 27 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T28N R26E   R27E S36   S31 ----- S 1   S 6 T27N 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p> <hr/> <p style="text-align: center;">Survey of the North Boundary, T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 27 and 28 N., Rs. 26 and 27 E, hereinbefore described.</p> <p>N. 89°53' W., bet. secs. 1 and 36.</p> <p>Over rolling land.</p>
32.50	Graded road, 53 lks. wide, bears N. and S.
38.10	Graded road, 53 lks. wide, bears NNE and SSW.

Survey of the North Boundary,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E S36 1/4 — S 1 T27N 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E S35   S36 —   — S 2   S 1 T27N 1990</p> <p>from which</p> <p style="padding-left: 40px;">A forked juniper, 19 ins. diam. at base, bears N. 52 1/2° E., 173 lks. dist., mkd. T28N R26E S36 BT.</p> <p style="padding-left: 40px;">A forked piñon, 19 ins. diam. at base, bears S. 42 3/4° E., 133 lks. dist., mkd. T27N R26E S1 BT.</p> <p style="padding-left: 40px;">A piñon, 6 ins. diam., bears S. 57 1/2° W., 7 lks. dist., mkd. T27N R26E S2 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, juniper and piñon; undergrowth, sparse native grasses.</p> <hr/> <p>N. 89°53' W., bet. secs. 2 and 35.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p>

Survey of the North Boundary,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E S35 1/4 — S 2 T27N 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S34   S35 —   — S 3   S 2 T27N 1990</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 8 ins. diam., bears N. 24 3/4° E., 10 1/2 lks. dist., mkd. T28N R26E S35 BT.</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears S. 35 1/4° W., 276 1/2 lks. dist., mkd. T27N R26E S3 BT.</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears N. 67 1/2° W., 199 lks. dist., mkd. T28N R26E S34 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy clay Timber, juniper and piñon; undergrowth, sparse native grasses.</p> <hr/> <p>N. 89°53' W., bet. secs. 3 and 34.</p> <p>Over rolling and broken land.</p>
38.00	<p>Point selected for the witness cor. to the 1/4 sec. cor. of secs. 3 and 34.</p>

Survey of the North Boundary,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WC T28N R26E S34 1/4 ← S 3 T27N 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
40.00	<p>True point for the 1/4 sec. cor. of secs. 3 and 34; falls on the steep bank of a narrow ravine where it is impracticable to establish a permanent monument.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E S33   S34 ----- S 4   S 3 T27N 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, juniper and piñon; undergrowth, sparse native grasses.</p> <hr/> <p>N. 89°53' W., bet. secs. 4 and 33.</p> <p>Over rolling land.</p>
27.60	<p>Graded road, 30 lks. wide, bears ENE and WSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the North Boundary,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T28N R26E S33 1/4 — S 4 T27N 1990</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 4, 5, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R26E S32   S33 —   — S 5   S 4 T27N 1990</p>
	<p>from which</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears N. 24 3/4° E., 162 lks. dist., mkd. T28N R26E S33 BT.</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears S. 25 1/2° E., 147 lks. dist., mkd. T27N R26E S4 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, a microwave repeater station, bears S. 47° W., 3.15 chs. dist.</p> <p>Land, rolling. Soil, sandy clay. Timber, juniper and piñon; undergrowth, sparse native grasses.</p>
	<hr/> <p>N. 89°53' W., bet. secs. 5 and 32.</p> <p>Over nearly level land.</p>
3.70	Power line, bears N. and S.
4.80	W. rim of Ganado Mesa, bears N. and S.

Survey of the North Boundary,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Thence descend from mesa over broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E S32 1/4 — S 5 T27N 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Thence over nearly level land.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E S31   S32 —   — S 6   S 5 T27N 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, nearly level and broken. Soil, sandy clay and clay. Timber, juniper and piñon; undergrowth, sparse native grasses.</p>
40.00	<p>N. 89°53' W., bet. secs. 6 and 31.</p> <p>Over nearly level land.</p> <p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>



Survey of the North Boundary,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T28N R26E S31 1/4 — S 6 T27N 1990
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
77.83	The cor. of Tps. 27 and 28 N., Rs. 25 and 26 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T28N R25E R26E S36 S31 S1 S6 T27N 1990.  Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.
<hr/> Survey of a Portion of the Subdivisional Lines, T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona <hr/>	
	From the cor. of secs. 13, 14, 23, and 24, hereinbefore described.
	N. 0°01' W., bet. secs. 13 and 14.
	Over rolling land.
1.00	Trail road, bears ESE and WNW.
11.70	Trail road, bears NE and SW.
23.75	Trail road, bears ESE and WNW.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T27N R26E 1/4 S14   S13 1990
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
64.75	Graded road, 38 lks. wide, bears NNE and SSW.

Survey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Point for the cor. of secs. 11, 12, 13, and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T27N R26E</td> </tr> <tr> <td>S11</td> <td>S12</td> </tr> <tr> <td colspan="2">—</td> </tr> <tr> <td>S14</td> <td>S13</td> </tr> <tr> <td colspan="2">1990</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>	T27N R26E		S11	S12	—		S14	S13	1990	
T27N R26E											
S11	S12										
—											
S14	S13										
1990											
	<p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.</p>										
	<p>N. 89°53' W., bet. secs. 12 and 13.</p>										
	<p>Over rolling land.</p>										
30.45	<p>Trail road, bears NNE and SSW.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T27N R26E</td> </tr> <tr> <td colspan="2">S12</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td colspan="2">S13</td> </tr> <tr> <td colspan="2">1990</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T27N R26E		S12		1/4	—	S13		1990	
T27N R26E											
S12											
1/4	—										
S13											
1990											
52.80	<p>Trail road, bears SSE and NNW.</p>										
72.60	<p>Graded road, 30 lks. wide, bears NNE and SSW.</p>										
80.00	<p>The cor. of secs. 11, 12, 13, and 14.</p>										

Survey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>
40.00	<p>N. 0°01' W., bet. secs. 11 and 12. Over rolling land. Point for the 1/4 sec. cor. of secs. 11 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E 1/4 S11   S12 1990</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Point for the cor. of secs. 1, 2, 11, and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S 2   S 1 ----- S11   S12 1990</p>
40.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Land, rolling. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p> <hr/> <p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described. N. 89°53' W., bet. secs. 1 and 12. Over rolling land. Point for the 1/4 sec. cor. of secs. 1 and 12.</p>

Survey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R26E S 1 1/4 — S12 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
42.00	<p>Graded road, 38 lks. wide, bears NNE and SSW.</p>
80.00	<p>The cor. of secs. 1, 2, 11, and 12.</p>
	<p>Land, rolling. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>
	<p>N. 0°02' W., bet. secs. 1 and 2.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R26E 1/4 S 2   S 1 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
43.25	<p>Trail road, bears ESE and WNW.</p>
79.99	<p>The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.</p>
	<p>Land, rolling. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>

Survey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 14, 15, 22, and 23, hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R26E 1/4 S15   S14 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Thence over broken land.</p>
51.30	<p>S. rim of Ganado Mesa, bears E. and W.</p> <p>Thence over rolling land.</p>
70.00	<p>Trail road, bears ENE and WSW.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14, and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R26E S10   S11 ----- S15   S14 1990</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>
	<hr/> <p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>S. 89°58' W., bet. secs. 11 and 14.</p>

Survey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling and broken land.
40.035	Point for the 1/4 sec. cor. of secs. 11 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set flush with the surface of the ground, with brass cap mkd.
	<p style="text-align: center;">T27N R26E S11 1/4 — S14 1990</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located in a small draw, drains SSE.
52.55	Trail road, bears N. and S.
80.07	The cor. of secs. 10, 11, 14, and 15.
	Land, rolling and broken.
	Soil, sandy clay.
	Timber, scattered juniper and piñon; undergrowth, sparse native grasses.
	N. 0°01' W., bet. secs. 10 and 11.
	Over rolling land.
28.80	Trail road, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T27N R26E 1/4 S10   S11 1990</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 2, 3, 10, and 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T27N R26E S 3   S 2 ----- S10   S11 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>
	<p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>S. 89°58' W., bet. secs. 2 and 11.</p> <p>Over rolling land.</p>
40.045	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R26E S 2 1/4 — S11 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.09	<p>The cor. of secs. 2, 3, 10, and 11.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>
	<p>N. 0°02' E., bet. secs. 2 and 3.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.21	<p style="text-align: center;">T27N R26E 1/4 S 3   S 2 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 60 lks. S. of a trail road, bears NE and SW.</p> <p>The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>
40.00	<p>From the cor. of secs. 15, 16, 21, and 22, hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
56.80	<p style="text-align: center;">T27N R26E 1/4 S16   S15 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>N. rim of Ganado Mesa, bears NE and SW.</p>
80.00	<p>Point for the cor. of secs. 9, 10, 15, and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>



Survey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T27N R26E S 9   S10 ----- S16   S15 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>
39.955	<p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>N. 89°46' W., bet. secs. 10 and 15.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
71.45	<p style="text-align: center;">T27N R26E S10 1/4 — S15 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>NW rim of Ganado Mesa, bears N. and S.</p>
79.91	<p>The cor. of secs. 9, 10, 15, and 16.</p> <p>Land, rolling and broken. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>
40.00	<p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p>

Survey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E 1/4 S 9   S10 1990</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 8 ins. diam., bears N. 21 1/4° E., 88 1/2 lks. dist., mkd. 1/4 S10 BT.</p> <p style="padding-left: 40px;">A piñon, 12 ins. diam., bears N. 56 1/2° W., 68 lks. dist., mkd. 1/4 S9 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
<p>80.00</p>	<p>Point for the cor. of secs. 3, 4, 9, and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S 4   S 3 ----- S 9   S10 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>
<p>39.95</p>	<p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>N. 89°46' W., bet. secs. 3 and 10.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.90	<p style="text-align: center;">T27N R26E S 3 1/4 — S10 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 3, 4, 9, and 10.</p> <p>Land, rolling and broken. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>
40.00	<p>N. 0°04' W., bet. secs. 3 and 4.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
80.04	<p style="text-align: center;">T27N R26E 1/4 S 4   S 3 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>
31.10	<p>From the cor. of secs. 16, 17, 20, and 21, hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over rolling land.</p> <p>Trail road, bears NE and SW.</p>

Survey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E 1/4 S17   S16 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 8, 9, 16, and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S 8   S 9 ----- S17   S16 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>
	<p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>N. 89°48' W., bet. secs. 9 and 16.</p> <p>Over rolling land.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S 9 1/4 — S16 1990</p>

Survey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.96	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 8, 9, 16, and 17.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>
33.20	<p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over rolling broken land.</p> <p>S. rim of Ganado Mesa, bears NE and SW.</p> <p>Thence over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E 1/4 S 8   S 9 1990</p> <p>from which</p> <p style="padding-left: 40px;">A piñon, 14 ins. diam., bears N. 62 1/2° E., 87 1/2 lks. dist., mkd. 1/4 S9 BT.</p> <p style="padding-left: 40px;">A piñon, 10 ins. diam., bears S. 29 1/4° W., 83 lks. dist., mkd. 1/4 S8 BT.</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 4, 5, 8, and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S 5   S 4 ----- S 8   S 9 1990</p>

Survey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, broken and rolling. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>
40.00	<p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>N. 89°49' W., bet. secs. 4 and 9.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S 4 1/4 — S 9 1990</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 4, 5, 8, and 9.</p> <p>Land, rolling and broken. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>
24.50	<p>N. 0°04' W., bet. secs. 4 and 5.</p> <p>Over rolling land.</p> <p>Graded road, 45 lks. wide, bears NE and SW.</p>
38.40	<p>NW rim of Ganado Mesa, bears ENE and WSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.94	<p style="text-align: center;">T27N R26E 1/4 S 5   S 4 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Thence enter broken land.</p> <p>The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling and broken. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>
40.00	<p>From the cor. of secs. 17, 18, 19, and 20, hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
80.00	<p style="text-align: center;">T27N R26E 1/4 S18   S17 1990</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears N. 84° W., 277 lks. dist., mkd. 1/4 S18 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Thence ascend over broken land.</p> <p>Point for the cor. of secs. 7, 8, 17, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<div style="text-align: center;"> <table border="1"> <tr><td>T27N</td><td>R26E</td></tr> <tr><td>S 7</td><td>S 8</td></tr> <tr><td>S18</td><td>S17</td></tr> <tr><td colspan="2">1990</td></tr> </table> </div> <p>from which</p> <p>A juniper, 4 ins. diam., bears S. 18 1/2° E., 20 lks. dist., mkd. X BT.</p> <p>A piñon, 8 ins. diam., bears S. 38 3/4° W., 38 1/2 lks. dist., mkd. T27N R26E S18 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located below the SW rim of Ganado Mesa, bears N. and S.</p> <p>Land, rolling and broken. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>	T27N	R26E	S 7	S 8	S18	S17	1990			
T27N	R26E										
S 7	S 8										
S18	S17										
1990											
	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89°56' W., bet. secs. 8 and 17.</p> <p>Over rolling and broken land.</p>										
39.845	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T27N</td><td>R26E</td></tr> <tr><td>S 8</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S17</td><td></td></tr> <tr><td colspan="2">1990</td></tr> </table> </div> <p>from which</p> <p>A piñon, 8 ins. diam., bears N. 46 3/4° E., 189 lks. dist., mkd. 1/4 S8 BT</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T27N	R26E	S 8		1/4	—	S17		1990	
T27N	R26E										
S 8											
1/4	—										
S17											
1990											
79.69	<p>The cor. of secs. 7, 8, 17, and 18.</p>										



Survey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>
	<p>N. 89°52' W., bet. secs. 7 and 18.</p>
	<p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R26E</p>
	<p style="text-align: center;">S 7</p>
	<p style="text-align: center;">1/4 —</p>
	<p style="text-align: center;">S18</p>
	<p style="text-align: center;">1990</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A juniper, 10 ins. diam., bears S. 29 3/4° E., 123 1/2 lks. dist., mkd. 1/4 S18 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located on W. slope of Ganado Mesa, bears NNE and SSW.</p>
78.39	<p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N</p>
	<p>R25E R26E S7 S12 S13 S18 1990.</p>
	<p>from which the original bearing trees</p>
	<p style="padding-left: 40px;">A piñon, 9 ins. diam., bears N. 75° E., 21 lks. dist., with scribe mks. T27N R26E S7 BT visible on open blaze.</p>
	<p style="padding-left: 40px;">A piñon, 10 ins. diam., bears S. 23 1/2° E., 135 1/2 lks. dist., with scribe mks. T27N R26E S18 BT visible on open blaze.</p>
	<p style="padding-left: 40px;">A piñon, 8 ins. diam., bears S. 67° W., 145 1/2 lks. dist., with scribe mks. T27N R25E S13 BT visible on open blaze.</p>

Survey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p> <hr/> <p>From the cor. of secs. 7, 8, 17, and 18. N. 0°03' W., bet. secs. 7 and 8. Over rolling and broken land.</p>
37.60	Graded road, 30 lks. wide, bears ESE and WNW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R26E 1/4 S 7   S 8 1990</p> </div> <p>from which</p> <p style="padding-left: 40px;">A piñon, 9 ins. diam., bears S. 64° E., 65 1/2 lks. dist., mkd. 1/4 S8 BT.</p> <p style="padding-left: 40px;">A piñon, 8 ins. diam., bears S. 59 1/2° W., 90 lks. dist., mkd. 1/4 S7 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
50.20	<p>N. rim of Ganado Mesa, bears E. and W. Thence descend over broken land.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 7, and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R26E S 6   S 5 ----- S 7   S 8 1990</p> </div>

Survey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>A juniper, 9 ins. diam., bears S. 78 3/4° W., 109 lks. dist., mkd. T27N R26E S7 BT.</p> <p>A juniper, 7 ins. diam., bears N. 33 1/2° W., 17 lks. dist., mkd. T27N R26E S6 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>
24.65	<p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>N. 89°56' W., bet. secs. 5 and 8.</p> <p>Over rolling land.</p>
39.845	<p>Graded road, 30 lks. wide, bears ENE and WSW.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E S 5 1/4 — S 8 1990</p>
51.20	<p>from which</p> <p>A juniper, 8 ins. diam., bears N. 60 1/4° W., 326 1/2 lks. dist., mkd. 1/4 S5 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
79.69	<p>W. rim of Ganado Mesa, bears NNE and SSW.</p> <p>Thence descend over broken land.</p> <p>The cor. of secs. 5, 6, 7, and 8.</p>

Survey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>
	<p>N. 89°52' W., bet. secs. 6 and 7.</p>
	<p>Over broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R26E S 6 1/4 — S 7 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Thence over gently rolling land.</p>
70.70	<p>Power line, bears NE and SW.</p>
78.28	<p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R25E R26E S1 S6 S7 S12 1990.</p>
	<p>Land, broken and gently rolling. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p>
	<p>From the cor. of secs. 5, 6, 7, and 8.</p>
	<p>N. 0°18' W., bet. secs. 5 and 6.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of a Portion of the Subdivisional Lines,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>T27N R26E 1/4 S 6   S 5 1990</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
59.40	Underground pipeline, bears NE and SW.
60.50	Power line, bears NE and SW.
63.25	Trail road, bears NE and SW.
80.02	<p>The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered juniper and piñon; undergrowth, sparse native grasses.</p> <hr/> <p style="text-align: center;">Survey of a Portion of the Subdivision of Section 27, T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">NE1/4 of Section 27</p> <hr/> <p>From the NE 1/16 sec. cor. of sec. 27, hereinbefore described.</p> <p>N. 89°50' W., on the E. and W. center line of the NE1/4 of sec. 27.</p> <p>Over nearly level land.</p>
10.03	<p>The C-W-NE 1/64 sec. cor. of sec. 27, hereinbefore described.</p> <hr/> <p style="text-align: center;">SE1/4 of Section 27</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 27 and 34, hereinbefore described.</p> <p>N. 0°04' W., on the N. and S. center line of the SE1/4 of sec. 27.</p> <p>Over gently rolling land.</p>

Survey of a Portion of the Subdivision of Section 27,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
12.53	S. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
13.97	Center of Arizona State Highway 264, asphalt pavement, 40 lks. wide, bears E. and W.
15.56	N. right-of-way fence of Arizona State Highway 264, barbed wire, 5 strands, parallels highway.
20.005	<p>Point for the SE 1/16 sec. cor. of sec. 27, at intersection with the E. and W. center line of the SE1/4 of sec. 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R26E SE1/16 S27 1990</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, bears S. 9° W., 1 lk. dist., with yellow cap mkd. LS 17428; established by George Perce, Arizona R.L.S No. 17428, in 1990. Original evidence was not utilized in establishing this cor., and it is not utilized in the course of this survey.</p>
30.005	<p>The C-N-SE 1/64 sec. cor. of sec. 27, identical with a special meander cor. on N. bdy. of right-of-way of S. Side Canal, hereinbefore described.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 26 and 27, hereinbefore described.</p> <p>N. 89°57' W., on the E. and W. center line of the SE1/4 of sec. 27, on mean bearing.</p> <p>Over gently rolling land.</p>
7.01	Intersect E. fence of Ganado Mission Cemetery, 8 x 5.4 chs., the NE cor. bears North, 96 lks. dist., long side bears E. and W.
15.01	Intersect W. fence of Ganado Mission Cemetery, the NW cor. bears North, 84 lks. dist.
18.07	Intersect E. side of mobile home, 65 x 14 ft., the NE cor. bears North, 29 lks. dist., long side bears N. and S.

Survey of a Portion of the Subdivision of Section 27,  
T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.015	The SE 1/16 sec. cor. of sec. 27.
	<p>Survey of a Metes-and-Bounds Survey in Section 26, T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona</p>
	<p>From AP 1 of a metes-and-bounds survey in sec. 26, on the line bet. secs. 26 and 27, hereinbefore described.</p>
	<p>N. 85°00' E., on line 1-2.</p>
4.20	<p>Point for AP 2, at record distances from AP 1 and AP 3, as specified in the exchange deed between the United States of America and Board of National Missions of the Presbyterian Church, dated March 22, 1946.</p>
	<p>Set a stainless steel spike, 1 in. diam., 3 ins. stem, flush with surface of asphalt pavement, with top mkd. BLM.</p>
	<p>from which</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set flush with the surface of the ground, for a reference monument, bears S. 30°43' W., 114.9 ft. dist., with brass cap mkd. T27N R26E AP2 S26 RM 114.9 FT. TO COR. 1990, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 56°32' W., 109.1 ft. dist., with brass cap mkd. T27N R26E AP2 S26 RM 109.1 FT. TO COR. 1990, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located in a street, asphalt pavement, 65 lks. wide, bears E. and W., 32 lks. N. of center.</p>
	<p>N. 10°15' W., on line 2-3.</p>
	<p>Over nearly level land.</p>
16.80	<p>AP 3 of the metes-and-bounds survey, on the adjusted record meanders of the left bank of Pueblo Colorado River, identical with the N. bdy. of right-of-way of S. Side Canal, hereinbefore described.</p>

T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	GENERAL DESCRIPTION
	<p>The area surveyed is within the Navajo Indian Reservation, with the community of Ganado located in sections 26, 27, 28, 33, and 34. Arizona State Highway 264 enters the township in sec. 25 and exits in sec. 18. U.S. Highway 191 enters the township in sec. 34 and intersects Arizona State Highway 264 in sec. 26. From these main highways there are numerous graded roads and trail roads throughout the township.</p> <p>The terrain is mostly rolling and broken, with the northern part of the township mostly consisting of Ganado Mesa. The main drainage is Pueblo Colorado Wash, which drains southwesterly, with a reservoir located in sections 13 and 24. The elevation varies from 6,200 to 6,800 feet above sea level. The soil is predominantly sandy clay. The timber consists of scattered juniper, piñon and sparse cottonwood. The other vegetation is brush and sparse native grasses.</p> <p>Most of the township is utilized for grazing livestock. There is no mining activity in the township.</p> <p>The mean magnetic declination is 12 1/2° E.</p>



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Jones Curtiss	Surveying Technician
Wilfred Chee	Engineering Technician
Reuben Mason	Engineering Technician

## CERTIFICATE OF SURVEY

I, Leonard R. Sandoval, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 22nd day of November, 1989, I have dependently resurveyed the south boundary, portions of the east boundary, subdivisional lines and subdivision of sections 26 and 27, and certain record meanders in sections 26 and 27, and surveyed a portion of the east boundary, the north boundary, portions of the subdivisional lines and subdivision of section 27 and metes-and-bounds survey in section 26, of Township 27 North, Range 26 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

AUG 23 1994

(Date)

*Leonard R. Sandoval*  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Arizona State Office  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the south boundary, portions of the east boundary, subdivisional lines and subdivision of sections 26 and 27, and certain record meanders in sections 26 and 27, and the survey of a portion of the east boundary, the north boundary, portions of the subdivisional lines and subdivision of section 27 and metes-and-bounds survey in section 26, of Township 27 North, Range 26 East, Gila and Salt River Meridian, Arizona, executed by Leonard R. Sandoval, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

OCT 4 1994

(Date)

*James P. Kelley*

(Chief Cadastral Surveyor of Arizona)

---

 CERTIFICATE OF TRANSCRIPT
 

---

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 27 N., R. 26 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.

(Date)

(Chief Cadastral Surveyor of Arizona)