

ORIGINAL

1

BOOK 5419

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES  
OF THE  
SURVEY

---

OF

---

THE

---

EAST BOUNDARY

---

AND THE

---

SUBDIVISIONAL LINES,

---

OF

---

TOWNSHIP 28 NORTH, RANGE 26 EAST

---

---

Of the Gila and Salt River Meridian,  
In the State of Arizona

EXECUTED BY

Robin T. Mathews and Leonard R. Sandoval, Cadastral Surveyors

---

Under Special Instructions dated November 22, 1989, approved November 22, 1989, which provided for the surveys included under Group Number 715, and assignment instructions dated November 22, 1989 and April 4, 1990.

Survey Commenced November 27, 1989

Survey Completed June 13, 1991

# BOOK 5419

2

## INDEX DIAGRAM

TOWNSHIP 28 NORTH, RANGE 26 EAST

67 6 64 68	66 5 50 62	51 4 40 49	41 3 30 39	32 2 20 29	21 1 9 19
7 61 61	8 48 60	9 39 48	10 29 38	11 18 28	12 8 18
18 59 58	17 47 58	16 37 46	15 27 36	14 17 26	13 8 16
19 57 56	20 45 55	21 36 45	22 25 35	23 15 25	24 6 15
30 54 53	29 44 53	28 34 43	27 24 33	26 13 23	25 5 13
31 52	32 42	33 32	34 22	35 11	36 4

## BOOK 5419

T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the survey of the east boundary and subdivisional lines, of Township 28 North, Range 26 East, Gila and Salt River Meridian, Arizona.

This survey supersedes portions of Townships 1 and 2 North, Ranges 10 and 11 West of the Navajo Special Meridian. The survey history of that portion of the superseded Navajo Special Meridian is included in these notes for informational purposes only.

The boundaries and subdivision of Townships 1 and 2 North, Ranges 10 and 11 West, Navajo Special Meridian, were surveyed by E.N. Darling in 1869.

The Seventh Standard Parallel North, through Range 25 East, (north boundary), was surveyed by Daniel N. Patterson and Leonard R. Sandoval in 1989-91. The Seventh Standard Parallel North, through Range 26 East, (north boundary), was surveyed by Steve D. Cully and William F. Olver in 1990-91. The west boundary was surveyed by William F. Olver and John A. Pex in 1990. The south boundary of the township was surveyed by Leonard R. Sandoval concurrently under this same group.

The closing cors. and 1/4 sec. cors. of minimum control on the Seventh Standard Parallel North (north boundary) were established by tying each direction to the controlling standard cors. For simplicity, only ties to the nearest cor. are given in the field notes and shown on the plat.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated November 22, 1989, for Group No. 715, Arizona.

The directions of all lines were determined by direct hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with a Zeiss ELTA-3 total station instrument.

The geographic position of the southeast corner of the township was determined by the technique of static differential positioning using the Motorola Eagle Global Positioning System Satellite Surveyor. U.S. Coast and Geodetic Survey first order triangulation stations "GANADO 1951" and "LOHALI 1951" were used as control stations. The geographic position is as follows:

Latitude: 35°46'42.595" N., Longitude: 109°30'23.152" W. NAD27

The mean magnetic declination, as taken from the 1985 magnetic declination map published by U.S. Geological Survey, is 12 1/2° E.

## BOOK 5419

Survey of the East Boundary,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Beginning at the cor. of Tps. 27 and 28 N., Rs. 26 and 27 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T28N R26E R27E S1 S6 S31 S36 T27N 1990.</p>
	<p>North, bet. secs. 31 and 36.</p>
	<p>Over rolling land.</p>
21.85	<p>Trail road, bears SSE and NNW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R26E R27E 1/4 S36   S31 1991</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A forked juniper, 24 ins. diam. at base, bears S. 34° E., 57 1/2 lks. dist., mkd. 1/4 S31 BT.</p>
	<p style="padding-left: 40px;">A forked piñon, 14 ins. diam. at base, bears S. 65° W., 49 lks. dist., mkd. 1/4 S36 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located on top of a hill, bears NE and SW.</p>
52.85	<p>SE cor. of a stucco house, 20 x 15 ft., bears West, 11.30 chs. dist., long side bears NNE.</p>
60.00	<p>Graded road, 30 lks. wide, bears E. and W.</p>
64.10	<p>Power line, bears ENE and WSW.</p>
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p>

## BOOK 5419

Survey of the East Boundary,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T28N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S30</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S36</td><td style="text-align: center;">S31</td></tr> <tr><td colspan="2" style="text-align: center;">1991</td></tr> </table>	T28N		R26E	R27E	S25	S30	-----		S36	S31	1991	
T28N													
R26E	R27E												
S25	S30												
-----													
S36	S31												
1991													
	<p>from which</p>												
	<p>A piñon, 18 ins. diam., bears N. 55 3/4° E., 70 lks. dist., mkd. T28N R27E S30 BT.</p>												
	<p>A piñon, 15 ins. diam., bears S. 18 1/2° E., 142 1/2 lks. dist., mkd. T28N R27E S31 BT.</p>												
	<p>A juniper, 12 ins. diam., bears S. 82 3/4° W., 23 1/2 lks. dist., mkd. T28N R26E S36 BT.</p>												
	<p>A forked juniper, 18 ins. diam. at base, bears N. 28 1/4° W., 148 lks. dist., mkd. T28N R26E S25 BT.</p>												
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>												
	<p>Land, rolling. Soil, sandy and rocky clay.</p>												
	<p>Timber, piñon and juniper; brush and native grasses.</p>												
	<hr/>												
	<p>North, bet. secs. 25 and 30.</p>												
	<p>Over rolling land on gradual ascent.</p>												
10.00	<p>Enter rugged land.</p>												
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p>												
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T28N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S30</td></tr> <tr><td colspan="2" style="text-align: center;">1991</td></tr> </table>	T28N		R26E	R27E	1/4		S25	S30	1991			
T28N													
R26E	R27E												
1/4													
S25	S30												
1991													

## BOOK 5419

Survey of the East Boundary,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>from which</p> <p>A forked piñon, 8 ins. diam. at base, bears S. 39 1/2° E., 201 lks. dist., mkd. 1/4 S30 BT.</p> <p>A juniper, 11 ins. diam., bears N. 84 1/2° W., 60 1/2 lks. dist., mkd. 1/4 S25 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>												
80.00	<p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T28N</td></tr> <tr><td>R26E</td><td>R27E</td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td colspan="2">—</td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>from which</p> <p>A juniper, 13 ins. diam., bears S. 13 1/4° E., 114 1/2 lks. dist., mkd. T28N R27E S30 BT.</p> <p>A juniper, 13 ins. diam., bears S. 32 1/4° W., 169 1/2 lks. dist., mkd. T28N R26E S25 BT.</p> <p>A juniper, 15 ins. diam., bears N. 47 3/4° W., 66 1/2 lks. dist., mkd. T28N R26E S24 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 165 lks. S. of a trail road, bears SSE and NNW.</p> <p>Land, rolling to rugged. Soil, rocky clay. Timber, piñon and juniper; brush and native grasses.</p>	T28N		R26E	R27E	S24	S19	—		S25	S30	1991	
T28N													
R26E	R27E												
S24	S19												
—													
S25	S30												
1991													
5.84	<p>North, bet. secs. 19 and 24.</p> <p>Over rugged land.</p> <p>Barbed wire fence, 5 strands, bears E. and W.</p>												

## BOOK 5419

Survey of the East Boundary,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T28N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">1991</td></tr> </table> <p>from which</p> <p style="margin-left: 40px;">A forked piñon, 10 ins. diam. at base, bears S. 70 1/2° E., 75 1/2 lks. dist., mkd. 1/4 S19 BT.</p> <p style="margin-left: 40px;">A piñon, 17 ins. diam., bears S. 55 1/4° W., 87 lks. dist., mkd. 1/4 S24 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T28N		R26E	R27E	1/4		S24	S19	1991			
T28N													
R26E	R27E												
1/4													
S24	S19												
1991													
80.00	<p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T28N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td style="text-align: center;">S13</td><td style="text-align: center;">S18</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">1991</td></tr> </table> <p>from which</p> <p style="margin-left: 40px;">A piñon, 6 ins. diam., bears N. 74 3/4° E., 140 lks. dist., mkd. X BT.</p> <p style="margin-left: 40px;">A forked piñon, 13 ins. diam. at base, bears S. 67 3/4° E., 60 lks. dist., mkd. T28N R27E S19 BT.</p> <p style="margin-left: 40px;">A piñon, 11 ins. diam., bears S. 69 1/2° W., 16 lks. dist., mkd. T28N R26E S24 BT.</p> <p style="margin-left: 40px;">A forked juniper, 26 ins. diam. at base, bears N. 33 1/2° W., 75 1/2 lks. dist., mkd. T28N R26E S13 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T28N		R26E	R27E	S13	S18	-----		S24	S19	1991	
T28N													
R26E	R27E												
S13	S18												
-----													
S24	S19												
1991													

## BOOK 5419

Survey of the East Boundary,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>Cor. is located in a wash, 10 lks. wide, 4 ft. deep, drains SW.</p> <p>Land, rugged. Soil, rocky clay. Timber, juniper; brush and native grasses.</p>												
40.00	<p>North, bet. secs. 13 and 18.</p> <p>Over rugged land.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T28N</td></tr> <tr><td>R26E</td><td>R27E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2">1991</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T28N		R26E	R27E	1/4		S13	S18	1991			
T28N													
R26E	R27E												
1/4													
S13	S18												
1991													
80.00	<p>Point for the cor. of secs. 7, 12, 13, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T28N</td></tr> <tr><td>R26E</td><td>R27E</td></tr> <tr><td>S12</td><td>S 7</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2">1991</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 375 lks. E. of a trail road, bears SSE and NNW.</p> <p>Land, rugged. Soil, sandy clay. Timber, juniper and piñon; brush and native grasses.</p> <p>North, bet. secs. 7 and 12.</p> <p>Over rugged land.</p>	T28N		R26E	R27E	S12	S 7	-----		S13	S18	1991	
T28N													
R26E	R27E												
S12	S 7												
-----													
S13	S18												
1991													



## BOOK 5419

Survey of the East Boundary,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
10.50	Begin descent into badlands.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T28N R26E R27E 1/4 S12   S 7 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 1, 6, 7, and 12.
	Set a magnet, 1 in. long, 7/8 in. diam., in a drill hole, cemented in place, 12 ins. below the surface of the ground.
	from which
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 26°51' E., 113 ft. dist., with brass cap mkd. T28N R27E S7 RM 113 FT. TO COR. 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, to bedrock, for a reference monument, bears N. 78°08' W., 114 ft. dist., with brass cap mkd. T28N R26E S1 RM 114 FT. TO COR. 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	Cor. is located on a steep northerly sandstone slope, bears NE and SW, 12 ft. below the top, where it is impracticable to establish a standard permanent monument.
	<p>Land, rugged. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; brush and native grasses.</p>
	North, bet. secs. 1 and 6.
	Over rugged land.

## BOOK 5419

Survey of the East Boundary,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E R27E 1/4 S 1   S 6 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the 80 1/16 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E R27E 1/16 S 1   S 6 80 1991</p> <p>from which</p> <p style="text-align: center;">A forked juniper, 11 ins. diam. at base, bears N. 63 1/4° E., 141 lks. dist., mkd. 80 1/16 S6 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
90.97	<p>Point for the closing cor. of Tp. 28 N., Rs. 26 and 27 E., at intersection with the Seventh Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R26E S36 ----- S 1   S 6 R26E   R27E T28N CC 1991</p>

## BOOK 5419

Survey of the East Boundary,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>A forked juniper, 11 ins. diam. at base, bears S. 17 1/4° W., 66 lks. dist., mkd. T28N R26E S1 CC BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 29 N., R. 26 E., bears East, 17.56 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. SC T29N R26E 1/4 S36 1990.</p> <p>Land, rugged. Soil, rocky clay. Timber, scattered juniper; brush and native grasses.</p>
	<p style="text-align: center;">Survey of the Subdivisional Lines, T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona</p>
	<p>From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T28N R26E S1 S2 S35 S36 T27N 1990.</p>
	<p>from which</p> <p>A forked juniper, 19 ins. diam. at base, bears N. 52 1/2° E., 173 lks. dist., mkd. T28N R26E S36 BT.</p> <p>A forked piñon, 19 ins. diam. at base, bears S. 42 3/4° E., 133 lks. dist., mkd. T27N R26E S1 BT.</p> <p>A piñon, 6 ins. diam., bears S. 57 1/2° W., 7 lks. dist., mkd. T27N R26E S2 BT.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over rugged land.</p>
25.96	SE cor. of a stucco house, 30 x 25 ft., bears West, 4.56 chs. dist., long side bears NNE.
28.70	Southernmost cor. of a hexagonal hogan, 20 ft. diam., bears West, 13.95 chs. dist.
29.75	SE cor. of a stucco house, 30 x 20 ft., bears West, 14.15 chs. dist., long side bears N.

BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
30.15	Southernmost cor. of a hexagonal hogan, 20 ft. diam., bears West, 12.10 chs. dist.										
30.40	Graded road, 30 lks. wide, bears E. and W.										
31.80	Graded road, 30 lks. wide, bears E. and W.										
40.00	Point for the 1/4 sec. cor. of secs. 35 and 36.  Set a magnet in a 1 x 1 x 2 5/8 ins. white plastic case, 3 ft. below the surface of the ground.  from which  A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 43°54' E., 66.4 ft. dist., with brass cap mkd. T28N R26E 1/4 S36 RM 66.4 FT. TO COR. 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.  A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 52°45' W., 67.0 ft. dist., with brass cap mkd. T28N R26E 1/4 S35 RM 67.0 FT. TO COR. 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.  Cor. is located in a wash, 45 lks. wide, 25 ft. deep, drains SE.										
74.80	Power line, bears ESE and WNW.										
79.30	Trail road, bears SE and NW.										
80.00	Point for the cor. of secs. 25, 26, 35, and 36.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T28N</td> <td style="padding: 0 5px;">R26E</td> </tr> <tr> <td style="padding: 0 5px;">S26</td> <td style="padding: 0 5px;">S25</td> </tr> <tr> <td colspan="2" style="text-align: center;"> </td> </tr> <tr> <td style="padding: 0 5px;">S35</td> <td style="padding: 0 5px;">S36</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table> from which  A forked juniper, 16 ins. diam. at base, bears N. 32 1/4° E., 68 1/2 lks. dist., mkd. T28N R26E S25 BT.	T28N	R26E	S26	S25			S35	S36	1991	
T28N	R26E										
S26	S25										
S35	S36										
1991											

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A piñon, 10 ins. diam., bears N. 43 1/4° W., 139 1/2 lks. dist., mkd. T28N R26E S26 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 95 lks. E. of a trail road, bears SE and NW.</p> <p>Land, rugged. Soil, sandy clay. Timber, piñon and juniper; brush and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°53' W., bet. secs. 25 and 36.</p> <p>Over rolling land.</p>
40.015	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E S25 1/4 — S36 1991</p> <p>from which</p> <p style="text-align: center;">A forked piñon, 12 ins. diam. at base, bears N. 15 1/2° W., 248 1/2 lks. dist., mkd. 1/4 S25 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 60 lks. S. of a graded road, 30 lks. wide, bears ESE and WNW.</p>
80.03	<p>The cor. of secs. 25, 26, 35, and 36.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 25 and 26.</p>

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
14.70	Graded road, 30 lks. wide, bears ENE and WSW.
29.00	Trail road, bears ENE and WSW.
30.00	Top of ridge, descend into rugged land on S. edge of Beautiful Valley.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 3 ins. below the surface of the ground, with brass cap mkd.  <div style="text-align: center;">                     T28N R26E                      1/4                      S26   S25                      1991                 </div> from which  <div style="text-align: center;">                     A forked juniper, 21 ins. diam. at base, bears S. 18° E., 84 lks. dist., mkd. 1/4 S25 BT.                       A piñon, 11 ins. diam., bears S. 11° W., 62 lks. dist., mkd. 1/4 S26 BT.                 </div> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.  Cor. is located on a moderate sandy slope, bears SSE and NNW.
75.79	Barbed wire fence, 5 strands, bears E. and W.
80.00	Point for the cor. of secs. 23, 24, 25, and 26.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">                     T28N R26E                      S23   S24  <hr style="width: 50%; margin: 0 auto;"/>                     S26   S25                      1991                 </div> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.  Cor. is located on the NW slope of a ravine, drains NNE.

## BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.01	<p>Land, rolling to rugged. Soil, clay and sandy clay. Timber, piñon and juniper; brush and native grasses.</p> <hr/> <p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°53' W., bet. secs. 24 and 25.</p> <p>Over rugged land.</p> <p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E S24 1/4 — S25 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 80 lks. S. of a barbed wire fence, 5 strands, bears E. and W.</p>
80.02	<p>The cor. of secs. 23, 24, 25, and 26.</p> <p>Land, rugged. Soil, sandy clay. Timber, scattered juniper and piñon; brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over rugged land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E 1/4 S23   S24 1991</p>

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>from which</p> <p style="padding-left: 40px;">A forked juniper, 8 ins. diam. at base, bears S. 89 3/4° E., 110 1/2 lks. dist., mkd. 1/4 S24 BT.</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears S. 64 3/4° W., 79 lks. dist., mkd. 1/4 S23 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 13, 14, 23, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td style="padding: 0 10px;">T28N</td><td style="padding: 0 10px;">R26E</td></tr> <tr><td style="padding: 0 10px;">S14</td><td style="padding: 0 10px;">S13</td></tr> <tr><td colspan="2" style="text-align: center;"> </td></tr> <tr><td style="padding: 0 10px;">S23</td><td style="padding: 0 10px;">S24</td></tr> <tr><td colspan="2" style="text-align: center;">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on the northerly slope of a meandering ridge, 15 ft. below the top.</p> <p>Land, rugged. Soil, rocky clay. Timber, scattered juniper and piñon; brush and native grasses.</p> <hr style="border: 0.5px solid black;"/> <p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°53' W., bet. secs. 13 and 24.</p> <p>Over rugged land.</p>	T28N	R26E	S14	S13			S23	S24	1991	
T28N	R26E										
S14	S13										
S23	S24										
1991											
40.01	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td style="padding: 0 10px;">T28N</td><td style="padding: 0 10px;">R26E</td></tr> <tr><td style="padding: 0 10px;"></td><td style="padding: 0 10px;">S13</td></tr> <tr><td style="padding: 0 10px;">1/4</td><td style="padding: 0 10px;">—</td></tr> <tr><td style="padding: 0 10px;"></td><td style="padding: 0 10px;">S24</td></tr> <tr><td colspan="2" style="text-align: center;">1991</td></tr> </table> </div>	T28N	R26E		S13	1/4	—		S24	1991	
T28N	R26E										
	S13										
1/4	—										
	S24										
1991											



17  
**BOOK 5419**

Survey of the Subdivisional Lines,  
 T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.02	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on the E. wall of a ravine, drains NNW.</p> <p>The cor. of secs. 13, 14, 23, and 24.</p> <p>Land, rugged.            Soil, rocky clay.            Timber, scattered juniper and piñon; brush and native grasses.</p>
40.00	<p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over rugged land.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;">             T28N R26E              1/4              S14   S13              1991           </div> <p>from which</p> <p style="margin-left: 40px;">A forked juniper, 12 ins. diam. at base, bears              N. 61 1/2° W., 191 1/2 lks. dist., mkd. 1/4 S14 BT.</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 11, 12, 13, and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;">             T28N R26E              S11   S12  <hr style="width: 50%; margin: 0 auto;"/>             S14   S13              1991           </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

## BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rugged. Soil, rocky clay. Timber, scattered juniper; brush and native grasses.</p>
	<p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>N. 89°53' W., bet. secs. 12 and 13.</p>
	<p>Over rugged land.</p>
14.60	<p>Enter rugged land on descent into Beautiful Valley.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R26E S12 1/4 — S13 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
48.70	<p>Bis-Ii-Ah Wash, 150 lks. wide, 12 ft. deep, drains NW.</p>
80.02	<p>The cor. of secs. 11, 12, 13, and 14.</p>
	<p>Land, rolling to rugged. Soil, rocky clay. Timber, scattered juniper; brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 11 and 12.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R26E 1/4 S11   S12 1991</p>

## BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 1, 2, 11, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T28N</td><td>R26E</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S11</td><td>S12</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 275 lks. S. and 285 lks. W. of a trail road, bears SE and NW.</p> <p>Land, rolling. Soil, rocky clay. Timber, scattered juniper; brush and native grasses.</p>	T28N	R26E	S 2	S 1			S11	S12	1991	
T28N	R26E										
S 2	S 1										
S11	S12										
1991											
40.01	<p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°53' W., bet. secs. 1 and 12.</p> <p>Over rugged to rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T28N</td><td>R26E</td></tr> <tr><td>S 1</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S12</td><td></td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T28N	R26E	S 1		1/4	—	S12		1991	
T28N	R26E										
S 1											
1/4	—										
S12											
1991											
80.02	<p>The cor. of secs. 1, 2, 11, and 12.</p>										

## BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rugged to rolling. Soil, sandy clay. Timber, scattered juniper; brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Over rolling land.</p>
22.50	Center shaft of windmill, bears West, 11.85 chs. dist.
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E 1/4 S 2   S 1 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
48.45	Southwesternmost cor. of a hexagonal hogan, 20 ft. diam., bears East, 8 lks. dist.
64.70	Trail road, bears SSE and NNW.
75.40	Telephone line, bears E. and W.
78.15	Trail road, bears E. and W.
80.00	<p>Point for the 80 1/16 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E 1/16 S 2   S 1 80 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
84.55	Trail road, bears SE and NW.
90.79	Point for the closing cor. of secs. 1 and 2, at intersection with the Seventh Standard Parallel North, on the N. bdy. of the Tp.

## BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
26 ins. in the ground, with brass cap mkd.

T29N R26E  
S35

S 2	S 1
T28N R26E	
CC	
1991	

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case  
beneath the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 35,  
T. 29 N., R. 26 E., bears East, 17.59 chs. dist., monumented with  
a stainless steel post, 2 1/2 ins. diam., firmly set, projecting  
4 ins. above the ground, with brass cap mkd. SC T29N R26E 1/4 S35  
1990.

Land, rolling.

Soil, sandy clay.

Timber, scattered juniper; brush and native grasses.

Point for the 1/4 sec. cor. of sec. 1 only, T. 28 N., R. 26 E.,  
at midpoint on the N. bdy. of sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
26 ins. in the ground, with brass cap mkd.

T29N R26E

1/4 S 1
T28N R26E
1991

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case  
beneath the stainless steel post.

From this cor. point, the stan. cor. of secs. 35 and 36,  
T. 29 N., R. 26 E., bears East, 17.575 chs. dist., monumented  
with a stainless steel post, 2 1/2 ins. diam., firmly set,  
projecting 4 ins. above the ground, with brass cap mkd. SC T29N  
R26E S35 S36 1990.

## BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T28N R26E S2 S3 S34 S35 T27N 1990.</p> <p>from which</p> <p>A piñon, 8 ins. diam., bears N. 24 3/4° E., 10 1/2 lks. dist., mkd. T28N R26E S35 BT.</p> <p>A piñon, 10 ins. diam., bears S. 35 1/4° W., 276 1/2 lks. dist., mkd. T27N R26E S3 BT.</p> <p>A piñon, 10 ins. diam., bears N. 67 1/2° W., 199 lks. dist., mkd. T28N R26E S34 BT.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E 1/4 S34   S35 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 170 lks. S. of a graded road, 38 lks. wide, bears ESE on curve to right.</p>
80.00	<p>Point for the cor. of secs. 26, 27, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E S27   S26 ----- S34   S35 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

## BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located 355 lks. S. of a trail road, bears ENE and WSW.</p> <p>Land, rolling. Soil, clay. Timber, scattered piñon and juniper; brush and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>N. 89°53' W., bet. secs. 26 and 35.</p> <p>Over rolling land.</p>
8.15	Center of a hexagonal hogan, 20 ft. diam., bears South, 4.75 chs. dist.
8.50	Graded road, 30 lks. wide, bears N. on curve to left.
9.45	NW cor. of a wood frame house, 30 x 20 ft., bears South, 5.00 chs. dist., long side bears SSW.
12.85	Westernmost cor. of a hexagonal hogan, 20 ft. diam., bears North, 7.30 chs. dist.
13.10	NW cor. of a wood frame house, 30 x 25 ft., bears North, 8.60 chs. dist., long side bears SSW.
13.40	Power line, bears ESE and WNW.
13.80	SE cor. of a wood frame house, 30 x 25 ft., bears North, 6.65 chs. dist., long side bears NNE.
14.20	SE cor. of a stucco house, 35 x 30 ft., bears North, 10.00 chs. dist., long side bears N.
16.58	Southernmost cor. of a hexagonal hogan, 20 ft. diam., bears North, 2.79 chs. dist.
19.09	SE cor. of a wood frame house, 30 x 20 ft., bears North, 0.69 chs. dist., long side bears NNE.
22.04	NW cor. of a wood frame house, 40 x 30 ft., bears South, 1.06 chs. dist., long side bears ESE.
40.01	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

24  
BOOK 54 19

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T28N R26E S26 1/4 — S35 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
48.15	Trail road, bears NNE and SSW.
80.02	The cor. of secs. 26, 27, 34, and 35.  Land, rolling. Soil, clay. Timber, scattered juniper and piñon; brush and native grasses.
	N. 0°01' W., bet. secs. 26 and 27.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T28N R26E 1/4 S27   S26 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
43.90	Trail road, bears ESE and WNW.
80.00	Point for the cor. of secs. 22, 23, 26, and 27.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T28N R26E S22   S23 ———— S27   S26 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.



Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, clay. Timber, scattered piñon and juniper; brush and native grasses.</p> <hr/> <p>From the cor. of secs. 23, 24, 25, and 26. N. 89°53' W., bet. secs. 23 and 26. Over rugged land on ascent.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 23 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E S23 1/4 — S26 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Cor. is located on the S. side of a hill.</p>
52.70	E. edge of Ganado Mesa, thence enter rolling land.
59.10	Trail road, bears SSE and NNW.
80.02	The cor. of secs. 22, 23, 26, and 27.  Land, rugged to rolling. Soil, clay. Timber, scattered piñon and juniper; brush and native grasses.
	<hr/> <p>N. 0°01' W., bet. secs. 22 and 23. Over rolling land.</p>
36.00	Trail road, bears SE and NW.
37.50	Trail road, bears NE and SW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T28N R26E 1/4 S22   S23 1991
	from which  A forked juniper, 10 ins. diam. at base, bears N. 41 1/2° E., 22 1/2 lks. dist., mkd. 1/4 S23 BT.  A piñon, 11 ins. diam., bears N. 88 1/2° W., 152 1/2 lks. dist., mkd. 1/4 S22 BT.  Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
70.20	N. edge of Ganado Mesa, thence enter rugged land on descent.
80.00	Point for the cor. of secs. 14, 15, 22, and 23.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">             T28N R26E              S15   S14              -----              S22   S23              1991           </div> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.  From this cor. point, U. S. Coast and Geodetic Survey first order triangulation station "GANADO 1951", with published latitude of 35°49'24.234" N. and longitude of 109°32'41.511" W., NAD27, bears N. 59°45.3' W., 14.714 chs. dist., monumented with a standard brass disk, 3 1/2 ins. diam., cemented in a concrete collar, 11 ins. diam., firmly set, projecting 1 in. above the ground, with top of disk mkd. GANADO 1951 1972 and a triangle.  Land, rolling to rugged. Soil, clay. Timber, scattered piñon and juniper; brush and native grasses.
	<hr/> From the cor. of secs. 13, 14, 23, and 24.  N. 89°53' W., bet. secs. 14 and 23.  Over rugged land.

27  
BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.01	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E S14 1/4 — S23 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 50 lks. E. of top of a gradually sloping hill.</p>
80.02	<p>The cor. of secs. 14, 15, 22, and 23.</p> <p>Land, rugged. Soil, rocky clay. Timber, scattered piñon and juniper; brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over rugged land on descent into Beautiful Valley.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a magnet, 1 in. long, 7/8 in. diam., in a drill hole, 12 ins. below the surface of bedrock.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 32°46' E., 98.6 ft. dist., with cap mkd. T28N R26E 1/4 S14 RM 98.6 FT. TO COR. 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p style="padding-left: 40px;">A piñon, 13 ins. diam., bears S. 36 1/4° W., 358 lks. dist., mkd. 1/4 S15 BT.</p> <p>Cor. is located on steep SE face of a ridge, bears NE and SW, 240 lks. S. of top, where it is impracticable to establish a permanent standard monument.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14, and 15.</p>

## BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E S10   S11 ----- S15   S14 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on the SE slope of a ridge, bears ENE and WSW, 30 lks. E. of top.</p> <p>Land, rugged. Soil, rocky clay. Timber, scattered juniper and piñon; brush and native grasses.</p>
40.005	<p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>N. 89°54' W., bet. secs. 11 and 14.</p> <p>Over rugged land.</p> <p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E S11 1/4 — S14 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on the E. slope of a ridge, bears N. and S., 50 lks. E. of top.</p>
80.01	<p>The cor. of secs. 10, 11, 14, and 15.</p> <p>Land, rugged. Soil, rocky clay. Timber, juniper; brush and native grasses.</p>

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS															
40.00	<p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over rugged land.</p> <p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>T28N</td><td>R26E</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S10</td><td> </td><td>S11</td></tr> <tr><td colspan="3">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T28N	R26E	1/4		S10		S11	1991						
T28N	R26E														
1/4															
S10		S11													
1991															
80.00	<p>Point for the cor. of secs. 2, 3, 10, and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>T28N</td><td>R26E</td></tr> <tr><td>S 3</td><td> </td><td>S 2</td></tr> <tr><td colspan="3"><hr style="width: 100%;"/></td></tr> <tr><td>S10</td><td> </td><td>S11</td></tr> <tr><td colspan="3">1991</td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A forked juniper, 23 ins. diam. at base, bears S. 2 1/2° W., 124 lks. dist., mkd. T28N R26E S10 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rugged. Soil, rocky clay. Timber, scattered piñon; brush and native grasses.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/>	T28N	R26E	S 3		S 2	<hr style="width: 100%;"/>			S10		S11	1991		
T28N	R26E														
S 3		S 2													
<hr style="width: 100%;"/>															
S10		S11													
1991															
40.005	<p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>N. 89°54' W., bet. secs. 2 and 11.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>														

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T28N R26E S 2 1/4 — S11 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.01	The cor. of secs. 2, 3, 10, and 11.  Land, rolling. Soil, rocky clay. Timber, scattered juniper; brush and native grasses.
	N. 0°01' W., bet. secs. 2 and 3.  Over rolling land.
35.30	Center of a water tank, 8 ft. diam., 12 ft. high, bears West, 15.75 chs. dist.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T28N R26E 1/4 S 3   S 2 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
53.40	Telephone line, bears ENE and WSW.
69.15	Trail road, bears ENE and WSW.
80.00	Point for the 80 1/16 sec. cor. of secs. 2 and 3.  Set a magnet in a 1 x 1 x 2 5/8 ins. white plastic case, 3 ft. below the surface of the ground.

Survey of the Subdivisional Lines,  
 T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 80°37' E., 130.4 ft. dist., with brass cap mkd. T28N R26E 80 1/16 S2 RM 130.4 FT. TO COR. 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 27°11' W., 109.8 ft. dist., with brass cap mkd. T28N R26E 80 1/16 S3 RM 109.8 FT. TO COR. 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in Bis-Ii-Ah Wash, 45 lks. wide, 4 ft. deep, drains NNW.</p>														
90.64	<p>Point for the closing cor. of secs. 2 and 3, at intersection with the Seventh Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T29N R26E</td> </tr> <tr> <td colspan="2">S34</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; height: 5px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 3</td> <td style="padding: 0 5px;">S 2</td> </tr> <tr> <td colspan="2" style="text-align: center;">T28N R26E</td> </tr> <tr> <td colspan="2" style="text-align: center;">CC</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 29 N., R. 26 E., bears East, 17.61 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T29N R26E 1/4 S34 1990.</p> <p>Land, rolling.                  Soil, rocky clay.                  Timber, scattered juniper; brush and native grasses.</p>	T29N R26E		S34				S 3	S 2	T28N R26E		CC		1991	
T29N R26E															
S34															
S 3	S 2														
T28N R26E															
CC															
1991															

## BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Point for the 1/4 sec. cor. of sec. 2 only, T. 28 N., R. 26 E., at midpoint on the N. bdy. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R26E ----- 1/4 S 2 T28N R26E 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 77 lks. N. of a wash, 23 lks. wide, 3 ft. deep, drains WNW.</p> <p>From this cor. point, the stan. cor. of secs. 34 and 35, T. 29 N., R. 26 E., bears East, 17.60 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. SC T29N R26E S34 S35 1990.</p>
	<p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T28N R26E S3 S4 S33 S34 T27N 1990.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E 1/4 S33   S34 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
75.80	<p>Easternmost cor. of a hexagonal hogan, 25 ft. diam., bears West, 6.30 chs. dist.</p>
80.00	<p>Point for the cor. of secs. 27, 28, 33, and 34.</p>



Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS																									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 10px;">T28N R26E</td> <td></td> <td style="padding: 2px 10px;">S27</td> </tr> <tr> <td style="padding: 2px 10px;">S28</td> <td style="border-left: 1px solid black; border-right: 1px solid black; width: 1px;"></td> <td style="padding: 2px 10px;"></td> </tr> <tr> <td style="padding: 2px 10px;">S33</td> <td style="border-left: 1px solid black; border-right: 1px solid black; width: 1px;"></td> <td style="padding: 2px 10px;">S34</td> </tr> <tr> <td colspan="3" style="padding: 2px 10px;">1991</td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A piñon, 7 ins. diam., bears N. 34 1/2° E., 314 lks. dist., mkd. T28N R26E S27 BT.</p> <p style="margin-left: 40px;">A juniper, 11 ins. diam., bears S. 78 1/2° W., 295 lks. dist., mkd. T28N R26E S33 BT.</p> <p style="margin-left: 40px;">A piñon, 10 ins. diam., bears N. 61° W., 186 1/2 lks. dist., mkd. T28N R26E S28 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 450 lks. S. of a trail road, bears SE and NW.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; brush and native grasses.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>N. 89°54' W., bet. secs. 27 and 34.</p> <p>Over rolling land.</p> <p>8.40 Trail road, bears ENE on curve to right.</p> <p>34.80 Trail road, bears SSE and NNW.</p> <p>39.99 Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 10px;">T28N R26E</td> <td></td> <td style="padding: 2px 10px;">S27</td> </tr> <tr> <td style="padding: 2px 10px;">1/4</td> <td style="border-left: 1px solid black; border-right: 1px solid black; width: 1px;"></td> <td style="padding: 2px 10px;">—</td> </tr> <tr> <td style="padding: 2px 10px;"></td> <td style="border-left: 1px solid black; border-right: 1px solid black; width: 1px;"></td> <td style="padding: 2px 10px;">S34</td> </tr> <tr> <td colspan="3" style="padding: 2px 10px;">1991</td> </tr> </table> </div>	T28N R26E		S27	S28			S33		S34	1991			T28N R26E		S27	1/4		—			S34	1991		
T28N R26E		S27																							
S28																									
S33		S34																							
1991																									
T28N R26E		S27																							
1/4		—																							
		S34																							
1991																									

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
73.80	Trail road, bears SE and NW.
79.98	The cor. of secs. 27, 28, 33, and 34.
	Land, rolling. Soil, sandy clay. Timber, piñon and juniper; brush and native grasses.
	N. 0°02' W., bet. secs. 27 and 28.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;">           T28N R26E            1/4            S28   S27            1991         </div>
	from which
	<div style="padding-left: 40px;">           A forked piñon, 12 ins. diam. at base, bears N. 66 1/2° E.,            133 1/2 lks. dist., mkd. 1/4 S27 BT.         </div>
	<div style="padding-left: 40px;">           A forked juniper, 13 ins. diam. at base, bears S. 15° W.,            74 lks. dist., mkd. 1/4 S28 BT.         </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
53.30	N. edge of Ganado Mesa, thence enter rugged land on descent.
80.00	Point for the cor. of secs. 21, 22, 27, and 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;">           T28N R26E            S21   S22            ————            S28   S27            1991         </div>

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p style="margin-left: 40px;">A douglas fir, 7 ins. diam., bears N. 52° E., 38 1/2 lks. dist., mkd. T28N R26E S22 BT.</p> <p style="margin-left: 40px;">A forked piñon, 19 ins. diam. at base, bears S. 55° E., 94 lks. dist., mkd. T28N R26E S27 BT.</p> <p style="margin-left: 40px;">A piñon, 6 ins. diam., bears N. 33 3/4° W., 45 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling to rugged. Soil, rocky clay. Timber, piñon, juniper and douglas fir; brush and native grasses.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>N. 89°54' W., bet. secs. 22 and 27.</p> <p>Over rolling land.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center; margin-left: 100px;">T28N R26E S22 1/4 — S27 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 410 lks. E. of a trail road, bears NE and SW.</p>
58.60	<p>W. edge of Ganado Mesa, bears NNE and SSW, thence enter rugged land on descent.</p>
79.98	<p>The cor. of secs. 21, 22, 27, and 28.</p> <p>Land, rolling to rugged. Soil, rocky clay. Timber, piñon and juniper; brush and native grasses.</p> <hr/>

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over rugged land.</p> <p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T28N R26E 1/4 S21   S22 1991</p> </div> <p>from which</p> <p style="margin-left: 40px;">A juniper, 22 ins. diam., bears N. 84 3/4° E., 79 1/2 lks. dist., mkd. 1/4 S22 BT.</p> <p style="margin-left: 40px;">A piñon, 10 ins. diam., bears S. 31 3/4° W., 194 1/2 lks. dist., mkd. 1/4 S21 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
54.00	<p>Enter rolling land.</p>
80.00	<p>Point for the cor. of secs. 15, 16, 21, and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T28N R26E S16   S15 ----- S21   S22 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rugged to rolling. Soil, rocky clay. Timber, juniper, piñon and douglas fir; brush and native grasses.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>N. 89°54' W., bet. secs. 15 and 22.</p> <p>Over rugged land.</p>

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
15.30	Trail road, bears N. and S.
39.985	<p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E S15 1/4 — S22 1991</p> <p>from which</p> <p style="text-align: center;">A piñon, 8 ins. diam., bears N. 4 1/2° E., 107 1/2 lks. dist., mkd. 1/4 S15 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
79.97	<p>The cor. of secs. 15, 16, 21, and 22.</p> <p>Land, rugged to rolling. Soil, sandy and rocky clay. Timber, juniper and piñon; brush and native grasses.</p> <hr style="border: 0.5px solid black;"/> <p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over rolling land</p>
24.55	Trail road, bears ENE and WSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E 1/4 S16   S15 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
48.00	Wash, 114 lks. wide, 30 ft. deep, drains NW.
80.00	Point for the cor. of secs. 9, 10, 15, and 16.

38  
BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T28N</td><td>R26E</td></tr> <tr><td>S 9</td><td>S10</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S16</td><td>S15</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered juniper; brush and native grasses.</p> <hr/> <p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>N. 89°54' W., bet. secs. 10 and 15.</p> <p>Over rugged land.</p>	T28N	R26E	S 9	S10			S16	S15	1991	
T28N	R26E										
S 9	S10										
S16	S15										
1991											
12.00	E. edge of plateau, bears SSE and NNW, thence enter rolling land.										
39.98	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T28N</td><td>R26E</td></tr> <tr><td></td><td>S10</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S15</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>from which</p> <p style="text-align: center;">A forked piñon, 15 ins. diam. at base, bears S. 38 3/4° W., 64 lks. dist., mkd. 1/4 S15 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T28N	R26E		S10	1/4	—		S15	1991	
T28N	R26E										
	S10										
1/4	—										
	S15										
1991											
58.00	Trail road, bears SE and NW.										
79.96	The cor. of secs. 9, 10, 15, and 16.										

## BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rugged to rolling. Soil, sandy clay. Timber, juniper and piñon; brush and native grasses.</p>
	<p>N. 0°02' W., bet. secs. 9 and 10. Over rolling land.</p>
25.30	Trail road, bears SE and NW.
37.30	Edge of plateau, bears ESE and WNW; thence enter rugged land on descent into Beautiful Valley.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R26E 1/4 S 9   S10 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	Point for the cor. of secs. 3, 4, 9, and 10.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R26E S 4   S 3 ----- S 9   S10 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Land, rolling to rugged. Soil, sandy clay. Timber, scattered juniper; brush and native grasses.</p>
	<p>From the cor. of secs. 2, 3, 10, and 11.</p>
	<p>N. 89°54' W., bet. secs. 3 and 10.</p>

## BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
39.975	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E S 3 1/4 — S10 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
79.95	<p>The cor. of secs. 3, 4, 9, and 10.</p> <p>Land, rolling. Soil, rocky clay. No timber; brush and native grasses.</p>
40.00	<p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E 1/4 S 4   S 3 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the 80 1/16 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E 1/16 S 4   S 3 80 1991</p>



## BOOK 54 19

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS									
90.49	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the closing cor. of secs. 3 and 4, at intersection with the Seventh Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29N R26E S33</p> <hr style="width: 50%; margin: auto;"/> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 4</td> <td style="padding: 0 5px;">S 3</td> </tr> <tr> <td colspan="2" style="text-align: center;">T28N R26E</td> </tr> <tr> <td colspan="2" style="text-align: center;">CC</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 29 N., R. 26 E., bears East, 17.56 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. SC T29N R26E 1/4 S33 1990.</p> <p>Land, rolling. Soil, rocky clay. No timber; brush and native grasses.</p>	S 4	S 3	T28N R26E		CC		1991	
S 4	S 3								
T28N R26E									
CC									
1991									
	<p>Point for the 1/4 sec. cor. of sec. 3 only, T. 28 N., R. 26 E., at midpoint on the N. bdy. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29N R26E</p> <hr style="width: 50%; margin: auto;"/> <p>1/4 S 3 T28N R26E 1991</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>								

## BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, the stan. cor. of secs. 33 and 34, T. 29 N., R. 26 E., bears East, 17.585 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T29N R26E S33 S34 1990.</p>
	<p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T28N R26E S4 S5 S32 S33 T27N 1990.</p>
	<p>from which</p>
	<p>A piñon, 10 ins. diam., bears N 24 3/4° E., 162 lks. dist., mkd. T28N R26E S33 BT.</p>
	<p>A piñon, 10 ins. diam., bears S. 25 1/2° E., 147 lks. dist., mkd. T27N R26E S4 BT.</p>
	<p>N. 0°03' W., bet. secs. 32 and 33.</p>
	<p>Over rolling land.</p>
<p>4.00</p>	<p>W. rim of Ganado Mesa, bears NNE and SSW; thence descend into rugged land.</p>
<p>40.00</p>	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R26E 1/4 S32   S33 1991</p>
	<p>from which</p>
	<p>A piñon, 5 ins. diam., bears N. 86° E., 95 lks. dist., mkd. X BT.</p>
	<p>A juniper, 12 ins. diam., bears N. 53 1/4° W., 125 lks. dist., mkd. 1/4 S32 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located on S. edge of small wash, drains W.</p>
<p>80.00</p>	<p>Point for the cor. of secs. 28, 29, 32, and 33.</p>

## BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T28N</td> <td>R26E</td> </tr> <tr> <td>S29</td> <td>S28</td> </tr> <tr> <td>S32</td> <td>S33</td> </tr> <tr> <td colspan="2">1991</td> </tr> </table> </div> <p>from which</p> <p>A juniper, 21 ins. diam., bears N. 53° E., 218 lks. dist., mkd. T28N R26E S28 BT.</p> <p>A juniper, 16 ins. diam., bears S 46 3/4° E., 256 1/2 lks. dist., mkd. T28N R26E S33 BT.</p> <p>A juniper, 28 ins. diam., bears N. 24 1/2° W., 91 lks. dist., mkd. T28N R26E S29 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on S. edge of a wash, 15 lks. wide, 2 ft. deep, drains NE.</p> <p>Land, rolling to rugged. Soil, clay. Timber, piñon and juniper; brush and native grasses.</p> <hr/> <p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>N. 89°52' W., bet. secs. 28 and 33.</p> <p>Over rolling land.</p> <p>6.55 Trail road, bears NNE and SSW.</p> <p>9.20 W. rim of Ganado Mesa, bears N. and S.; thence descend into rugged land.</p> <p>40.015 Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p>	T28N	R26E	S29	S28	S32	S33	1991	
T28N	R26E								
S29	S28								
S32	S33								
1991									

## BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T28N R26E S28 1/4 — S33 1991</p>
	<p>from which</p> <p style="padding-left: 40px;">A juniper, 7 ins. diam., bears S. 42° W., 78 1/2 lks. dist., mkd. 1/4 S33 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on S. edge of a wash, 23 lks. wide, 3 ft. deep, drains W.</p>
45.94	SE cor. of a log house, 20 x 15 ft., bears North, 2.04 chs. dist., long side bears NNE.
80.03	<p>The cor. of secs. 28, 29, 32, and 33.</p> <p>Land, rolling to rugged. Soil, gravelly clay. Timber, piñon and juniper; brush and native grasses.</p>
40.00	<p>N. 0°03' W., bet. secs. 28 and 29.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
69.35	<p style="text-align: center;">T28N R26E 1/4 S29   S28 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Trail road, bears NE and SW.</p>
80.00	<p>Point for the cor. of secs. 20, 21, 28, and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<div style="text-align: center;"> <table border="1"> <tr><td>T28N</td><td>R26E</td></tr> <tr><td>S20</td><td>S21</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S29</td><td>S28</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, clay. Timber, scattered juniper; brush and native grasses.</p>	T28N	R26E	S20	S21			S29	S28	1991	
T28N	R26E										
S20	S21										
S29	S28										
1991											
40.02	<p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>N. 89°52' W., bet. secs. 21 and 28.</p> <p>Over rugged land.</p> <p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<div style="text-align: center;"> <table border="1"> <tr><td>T28N</td><td>R26E</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">S21</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">1/4 —</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">S28</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">1991</td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears N. 80° W., 100 lks. dist., mkd. 1/4 S21 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Enter rolling land.</p>	T28N	R26E	S21		1/4 —		S28		1991	
T28N	R26E										
S21											
1/4 —											
S28											
1991											
80.04	<p>The cor. of secs. 20, 21, 28, and 29.</p> <p>Land, rolling to rugged. Soil, clay. Timber, piñon and juniper; brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 20 and 21.</p> <p>Over rolling land.</p>										

## BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
5.50	Trail road, bears E and W.										
38.60	Wash, 150 lks. wide, 30 ft. deep, drains W.										
40.00	Point for the 1/4 sec. cor. of secs. 20 and 21.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T28N R26E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S20</td><td>  S21</td></tr> <tr><td colspan="2">1991</td></tr> </table>	T28N R26E		1/4		S20	S21	1991			
T28N R26E											
1/4											
S20	S21										
1991											
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.										
74.95	Trail road, bears E. and W.										
80.00	Point for the cor. of secs. 16, 17, 20, and 21.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T28N R26E</td></tr> <tr><td>S17</td><td>  S16</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S20</td><td>  S21</td></tr> <tr><td colspan="2">1991</td></tr> </table>	T28N R26E		S17	S16	<hr/>		S20	S21	1991	
T28N R26E											
S17	S16										
<hr/>											
S20	S21										
1991											
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.										
	Land, rolling. Soil, clay. Timber, scattered juniper; brush and native grasses.										
	From the cor. of secs. 15, 16, 21, and 22.										
	N. 89°52' W., bet. secs. 16 and 21.										
	Over rolling land.										
9.61	Southeasternmost cor. of a hexagonal log hogan, 10 ft. sides, bears North, 2.24 chs. dist.										
11.46	SE cor. of a wood frame house, 33 x 20 ft., bears North, 1.35 chs. dist., long side bears NNW.										

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
15.36	Southernmost cor. of a hexagonal log hogan, 10 ft. sides, bears North, 1.59 chs. dist.
26.40	Wash, 76 lks. wide, 20 ft. deep, drains N.
28.60	Trail road, bears SSE and NNW.
40.025	Point for the 1/4 sec. cor. of secs. 16 and 21.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">T28N R26E S16 1/4 — S21 1991</div>
80.05	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.  The cor. of secs. 16, 17, 20, and 21.  Land, rolling. Soil, clay. Timber, scattered juniper; brush and native grasses.
	N. 0°03' W., bet. secs. 16 and 17.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 17.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">T28N R26E 1/4 S17   S16 1991</div>
50.50	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.  Bi Keesh Wash, 76 lks. wide, 20 ft. deep, drains WNW.
80.00	Point for the cor. of secs. 8, 9, 16, and 17.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS						
	<div style="text-align: center;"> <table border="1"> <tr><td>T28N R26E</td></tr> <tr><td>S 8   S 9</td></tr> <tr><td>S17   S16</td></tr> <tr><td>1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, clay. Timber, scattered juniper; brush and native grasses.</p>	T28N R26E	S 8   S 9	S17   S16	1991	
T28N R26E						
S 8   S 9						
S17   S16						
1991						
40.035	<p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>N. 89°52' W., bet. secs. 9 and 16.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>					
80.07	<div style="text-align: center;"> <table border="1"> <tr><td>T28N R26E</td></tr> <tr><td>S 9</td></tr> <tr><td>1/4 —</td></tr> <tr><td>S16</td></tr> <tr><td>1991</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 38 lks. W. of the NW bank of a wash, 45 lks. wide, 10 ft. deep, drains SW.</p> <p>The cor. of secs. 8, 9, 16, and 17.</p> <p>Land, rolling. Soil, clay. Timber, scattered juniper; brush and native grasses.</p>	T28N R26E	S 9	1/4 —	S16	1991
T28N R26E						
S 9						
1/4 —						
S16						
1991						
40.00	<p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p>					



## BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T28N R26E 1/4 S 8   S 9 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
54.70	Trail road, bears SSE and NNW.
62.10	Trail road, bears E. and W.
80.00	Point for the cor. of secs. 4, 5, 8, and 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T28N R26E S 5   S 4 ----- S 8   S 9 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	<p>Land, rolling. Soil, clay. Timber, scattered juniper; brush and native grasses.</p>
	From the cor. of secs. 3, 4, 9, and 10.
	N. 89°52' W., bet. secs. 4 and 9.
	Over rugged land ascending from Beautiful Valley.
31.40	W. rim of Beautiful Valley, bears SE and NW; thence enter rolling land.
40.05	Point for the 1/4 sec. cor. of secs. 4 and 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

## BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T28N R26E S 4 1/4 — S 9 1991</p>
80.10	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 4, 5, 8, and 9.</p> <p>Land, rugged to rolling. Soil, clay. Timber, scattered juniper; brush and native grasses.</p>
9.80	<p>N. 0°03' W., bet. secs. 4 and 5.</p> <p>Over rolling land.</p> <p>Trail road, bears NNE and SSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
59.55	<p style="text-align: center;">T28N R26E 1/4 S 5   S 4 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Trail road, bears SE and NW.</p>
80.00	<p>Point for the 80 1/16 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T28N R26E 1/16 S 5   S 4 80 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS																									
82.80	W. rim of Beautiful Valley, bears ESE and WNW; thence descend into rugged land.																								
90.33	<p>Point for the closing cor. of secs. 4 and 5, at intersection with the Seventh Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T29N R26E</td></tr> <tr><td colspan="2">S32</td></tr> <tr><td colspan="2"><hr style="width: 100%;"/></td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 5</td><td style="padding: 0 5px;">S 4</td></tr> <tr><td colspan="2">T28N R26E</td></tr> <tr><td colspan="2">CC</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A juniper, 20 ins. diam., bears S. 58° E., 15 lks. dist., mkd. T28N R26E S4 CC BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the true point for the stan. 1/4 sec. cor. of sec. 32, T. 29 N., R. 26 E., bears East, 17.69 chs. dist., which falls on the edge of a wash; from which the witness cor. to the stan. 1/4 sec. cor. of sec. 32, T. 29 N., R. 26 E., bears East, 1.00 ch. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. WC SC T29N R26E 1/4 S32 1990 and an arrow pointing west.</p> <p>Land, rolling to rugged. Soil, clay. Timber, scattered juniper; brush and native grasses.</p> <hr style="border: 0.5px solid black; margin: 20px 0;"/> <p>Point for the 1/4 sec. cor. of sec. 4 only, T. 28 N., R. 26 E., at midpoint on the N. bdy. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T29N R26E</td></tr> <tr><td colspan="2"><hr style="width: 100%;"/></td></tr> <tr><td colspan="2">1/4 S 4</td></tr> <tr><td colspan="2">T28N R26E</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div>	T29N R26E		S32		<hr style="width: 100%;"/>		S 5	S 4	T28N R26E		CC		1991		T29N R26E		<hr style="width: 100%;"/>		1/4 S 4		T28N R26E		1991	
T29N R26E																									
S32																									
<hr style="width: 100%;"/>																									
S 5	S 4																								
T28N R26E																									
CC																									
1991																									
T29N R26E																									
<hr style="width: 100%;"/>																									
1/4 S 4																									
T28N R26E																									
1991																									

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on the W. slope of a spur ridge, bears N. and S.</p> <p>From this cor. point, the stan. cor. of secs. 32 and 33, T. 29 N., R. 26 E., bears East, 17.625 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. SC T29N R26E S32 S33 1990.</p> <hr/> <p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T28N R26E S5 S6 S31 S32 T27N 1990.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over rolling land.</p>
5.10	Underground waterline, bears SSE and NNW.
28.40	Trail road, bears ESE and WNW.
29.40	Wash, 76 lks. wide, 10 ft. deep, drains WNW.
38.55	Trail road, bears SE and NW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E 1/4 S31   S32 1991</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
44.20	Trail road, bears NNE and SSW.
49.70	Power line, bears SE and NW.
55.97	Northernmost cor. of a wood frame house, 45 x 28 ft., bears West, 2.88 chs. dist., long side bears SW.
57.60	NW cor. of a wood frame house, 45 x 28 ft., bears West, 3.50 chs. dist., long side bears SSW.

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
68.50	Trail road, bears ENE and WSW.										
80.00	<p>Point for the cor. of secs. 29, 30, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 5px;">T28N</td> <td style="padding: 2px 5px;">R26E</td> </tr> <tr> <td style="padding: 2px 5px;">S30</td> <td style="padding: 2px 5px;">S29</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 2px 5px;">S31</td> <td style="border-top: 1px solid black; padding: 2px 5px;">S32</td> </tr> <tr> <td colspan="2" style="padding: 2px 5px;">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, clay. No timber; brush and native grasses.</p> <hr style="border: 0.5px solid black;"/> <p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>N. 89°53' W., bet. secs. 29 and 32.</p> <p>Over rolling land.</p>	T28N	R26E	S30	S29	S31	S32	1991			
T28N	R26E										
S30	S29										
S31	S32										
1991											
39.98	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 5px;">T28N</td> <td style="padding: 2px 5px;">R26E</td> </tr> <tr> <td style="padding: 2px 5px;"></td> <td style="padding: 2px 5px;">S29</td> </tr> <tr> <td style="padding: 2px 5px;">1/4</td> <td style="padding: 2px 5px;">—</td> </tr> <tr> <td style="padding: 2px 5px;"></td> <td style="padding: 2px 5px;">S32</td> </tr> <tr> <td colspan="2" style="padding: 2px 5px;">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	T28N	R26E		S29	1/4	—		S32	1991	
T28N	R26E										
	S29										
1/4	—										
	S32										
1991											
79.96	<p>The cor. of secs. 29, 30, 31, and 32.</p> <p>Land, rolling. Soil, clay. Timber, scattered juniper; brush and native grasses.</p> <hr style="border: 0.5px solid black;"/> <p>N. 89°54' W., bet. secs. 30 and 31.</p>										

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over gently rolling land.
4.68	Barbed wire fence, 7 strands, bears NNE and SSW.
13.51	Barbed wire fence, 7 strands, bears N. and S.
14.50	Power line, bears SSE and NNW.
14.95	Trail road, bears SSE and NNW.
15.90	SE cor. of a stucco house, 20 x 14 ft., bears North, 9.70 chs. dist., long side bears NNE.
17.70	SE cor. of a stucco house, 40 x 32 ft., bears North, 8.15 chs. dist., long side bears NNE.
28.40	Graded road, 30 lks. wide, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  T28N R26E S30 1/4 — S31 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
47.05	Trail road, bears NNE and SSW.
77.74	The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T28N R25E R26E S25 S30 S31 S36 1990.  Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.
	From the cor. of secs. 29, 30, 31, and 32.  N. 0°03' W., bet. secs. 29 and 30.  Over gently rolling land.

## BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
18.80	Trail road, bears E. and W.
23.50	NE cor. of a stucco house, 26 x 22 ft., bears West, 18.15 chs. dist., long side bears WNW.
30.57	NE cor. of a stucco house, 24 x 16 ft., bears West, 19.45 chs. dist., long side bears SSW.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T28N R26E 1/4 S30   S29 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
75.92	Barbed wire fence, 4 strands, bears ESE and WNW.
80.00	Point for the cor. of secs. 19, 20, 29, and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T28N R26E S19   S20 ----- S30   S29 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located in an abandoned cultivated field, 25 lks. E. of W. edge.
	Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.
	From the cor. of secs. 20, 21, 28, and 29.
	N. 89°54' W., bet. secs. 20 and 29.
	Over gently rolling land.

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.975	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E S20 1/4 — S29 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
79.95	<p>The cor. of secs. 19, 20, 29, and 30.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
	<p>N. 89°54' W., bet. secs. 19 and 30.</p> <p>Over gently rolling land.</p>
24.70	<p>Trail road, bears NNE and SSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E S19 1/4 — S30 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
58.40	<p>Northernmost cor. of a wood frame house, 60 x 45 ft., bears South, 17.75 chs. dist., long side bears SE.</p>
67.53	<p>E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.</p>
69.14	<p>Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears NNE and SSW.</p>



## BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
70.65	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.
77.66	<p>The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T28N R25E R26E S19 S24 S25 S30 1990.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.</p> <hr/> <p>From the cor. of secs. 19, 20, 29, and 30. N. 0°03' W., bet. secs. 19 and 20. Over gently rolling land.</p>
11.90	Graded road, 45 lks. wide, bears ESE and WNW.
18.10	Trail road, bears E. and W.
21.00	Wash, 90 lks. wide, 15 ft. deep, drains WSW.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T28N R26E 1/4 S19   S20 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
69.60	Graded road, 30 lks. wide, bears ENE and WSW.
72.94	Intersect the S. side of a wood frame house, 32 x 18 ft., the SE cor. bears ESE, 11 lks. dist., long side bears NNE and SSW.
76.20	Trail road, bears SSE and NNW.
80.00	Point for the cor. of secs. 17, 18, 19, and 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T28N R26E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">S18</td> <td style="padding: 2px;">S17</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">S19</td> <td style="padding: 2px;">S20</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px;">1991</td> </tr> </table>	T28N R26E		S18	S17	S19	S20	1991			
T28N R26E											
S18	S17										
S19	S20										
1991											
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 150 lks. E. of a trail road, bears SSE and NNW.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.</p>										
	<hr/> <p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>N. 89°54' W., bet. secs. 17 and 20.</p> <p>Over gently rolling land.</p>										
29.10	Graded road, 15 lks. wide, bears ESE and WNW.										
39.965	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>										
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T28N R26E</td> </tr> <tr> <td colspan="2" style="text-align: center;">S17</td> </tr> <tr> <td colspan="2" style="text-align: center;">1/4 —</td> </tr> <tr> <td colspan="2" style="text-align: center;">S20</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T28N R26E		S17		1/4 —		S20		1991	
T28N R26E											
S17											
1/4 —											
S20											
1991											
79.93	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 17, 18, 19, and 20.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.</p>										
	<hr/> <p>N. 89°54' W., bet. secs. 18 and 19.</p> <p>Over gently rolling land.</p>										
26.10	Power line, bears NNE and SSW.										

## BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
26.30	Underground waterline, bears NNE and SSW.
34.00	Power line, bears NNE and SSW.
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T28N R26E S18 1/4 — S19 1991
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
48.17	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.
49.73	Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears NNE and SSW.
51.29	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.
77.57	The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T28N R25E R26E S13 S18 S19 S24 1990.
	Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.
	From the cor. of secs. 17, 18, 19, and 20.
	N. 0°03' W., bet. secs. 17 and 18.
	Over gently rolling land.
13.15	Trail road, bears NNE and SSW.
27.55	SE cor. of a wood frame house, 30 x 16 ft., bears West, 18.33 chs. dist., long side bears NNE.
30.40	Trail road, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 18.

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E 1/4 S18   S17 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
68.35	Trail road, bears NNE and SSW.
68.60	Power line, bears NNE and SSW.
80.00	Point for the cor. of secs. 7, 8, 17, and 18.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E S 7   S 8 ----- S18   S17 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.</p>
	<p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>N. 89°53' W., bet secs. 8 and 17.</p> <p>Over rolling land.</p>
39.955	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R26E S 8 1/4 — S17 1991</p>

## BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
74.20	Power line, bears NNE and SSW.
79.91	The cor. of secs. 7, 8, 17, and 18.
	Land, rolling. Soil, sandy clay. No timber; brush and native grasses.
	N. 89°54' W., bet. secs. 7 and 18.
	Over gently rolling land.
28.92	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.
30.44	Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears NNE and SSW.
32.00	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T28N R26E S 7 1/4 — S18 1991</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
77.49	The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T28N R25E R26E S7 S12 S13 S18 1990.
	Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.
	From the cor. of secs. 7, 8, 17, and 18.

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°03' W., bet. secs. 7 and 8.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;">           T28N R26E            1/4            S 7   S 8            1991         </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
63.20	Power line, bears ESE and WNW.
65.20	Graded road, 76 lks. wide, bears E. and W.
80.00	Point for the cor. of secs. 5, 6, 7, and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;">           T28N R26E            S 6   S 5            ————            S 7   S 8            1991         </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Land, rolling.
	Soil, sandy clay.
	No timber; brush and native grasses.
	From the cor. of secs. 4, 5, 8, and 9.
	N. 89°53' W., bet. secs. 5 and 8.
	Over rolling land.
26.83	Intersect the NE side of a concrete block house, 56 x 20 ft., easternmost cor. bears SE, 3 lks. dist., long side bears NE and SW.
29.01	Chainlink fence, bears NE and SW.

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
29.60	Power line, bears NE and SW.
39.95	Point for the 1/4 sec. cor. of secs. 5 and 8.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  T28N R26E S 5 1/4 — S 8 1991  Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
79.90	The cor. of secs. 5, 6, 7, and 8.  Land, rolling. Soil, sandy clay. No timber; brush and native grasses.
<hr/>	
	N. 89°54' W., bet. secs. 6 and 7.  Over gently rolling land.
5.45	Trail road, bears NNE and SSW.
9.54	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.
11.10	Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears NNE and SSW.
12.67	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  T28N R26E S 6 1/4 — S 7 1991  Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
66.35	Trail road, bears NNE and SSW.
77.39	<p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. T28N R25E R26E S1 S6 S7 S12 1990.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; brush and native grasses.</p> <hr style="border: 0.5px solid black;"/> <p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over gently rolling land.</p>
28.60	Trail road, bears NNE and SSW.
39.48	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T28N R26E 1/4 S 6   S 5 1991</p> </div> <p>from which</p> <p style="margin-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 86°12' E., 8.5 ft. dist., with brass cap mkd. T28N R26E 1/4 S5 RM 8.5 FT. TO COR. 1991 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p style="margin-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 86°12' W., 202.4 ft. dist., with brass cap mkd. T28N R26E 1/4 S6 RM 202.4 FT. TO COR. 1991 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>



65  
BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
45.95	Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears NNE and SSW.
52.38	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.
77.90	W. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.
80.00	Point for the 80 1/16 sec. cor. of secs. 5 and 6.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T28N R26E            1/16            S 6   S 5            80            1991         </div> from which  A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 88°50' E., 157.9 ft. dist., with brass cap mkd. T28N R26E 80 1/16 S5 RM 157.9 FT. TO COR. 1991 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.  A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 88°50' W., 56.4 ft. dist., with brass cap mkd. T28N R26E 80 1/16 S6 RM 56.4 FT. TO COR. 1991 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.  Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
82.06	Center of U.S. Highway 191, asphalt pavement, 38 lks. wide, bears SSE and NNW.
86.47	E. right-of-way fence of U.S. Highway 191, barbed wire, 5 strands, parallels highway.

## BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
90.17	<p>Point for the closing cor. of secs. 5 and 6, at intersection with the Seventh Standard Parallel North, the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R26E S31</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S 6   S 5 T28N R26E CC 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 29 N., R. 26 E., bears East, 17.58 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, encircled with a collar of stone, with brass cap mkd. SC T29N R26E 1/4 S31 1990.</p> <p>Land, gently rolling. Soil, sandy clay. Timber, scattered juniper; brush and native grasses.</p>
	<hr/> <p>Point for the 1/4 sec. cor. of sec. 5 only, T. 28 N., R. 26 E., at midpoint on the N. bdy. of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R26E</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1/4 S 5 T28N R26E 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 31 and 32, T. 29 N., R. 26 E., bears East, 17.635 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. SC T29N R26E S31 S32 1990.</p>

## BOOK 5419

Survey of the Subdivisional Lines,  
T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona

## CHAINS

Point for the 1/4 sec. cor. of sec. 6 only, T. 28 N., R. 26 E., at 40.00 chs. westing from the closing cor. of secs. 5 and 6, on the N. bdy. of sec. 6.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T29N R25E

---

1/4 S 6  
T28N R26E  
1991

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

From this cor. point, the stan. cor. of T. 29 N., Rs. 25 and 26 E., bears East, 17.58 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. SC T29N R25E R26E S31 S36 1990.

---

GENERAL DESCRIPTION

---

The area surveyed is within the Navajo Indian Reservation, about 6 miles north of Ganado, Arizona. Ganado Mesa is in the southern portion and Beautiful Valley is in the northeastern portion of the township. The elevation ranges from 5940 feet to 6940 feet above sea level. The soil is mostly clay. There is piñon and juniper on the mesa and brush with native grasses throughout the township. The drainage is generally to the north and west.

U.S. Highway 191 enters the township in section 30 and exits on the north boundary of section 6. There are numerous graded roads and trail roads throughout the township. Residents utilize the township for grazing livestock. There is no evidence of any kind of mining activity.

The mean magnetic declination is 12 1/2° E.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Daniel Bryan	Engineering Technician II
Wilfred Chee	Engineering Technician II
Edward Clarke	Engineering Technician I
Nelson Kinsel	Engineering Technician II
Reuben Mason	Engineering Technician II

## CERTIFICATE OF SURVEY

We, Robin T. Mathews and Leonard R. Sandoval, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 22nd day of November, 1989, we have surveyed the east boundary and the subdivisional lines of Township 28 North, Range 26 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Robin T. Mathews is no longer assigned to this office and is not available for signature.

AUG 30 1994

(Date)

*William F. Oliver*

(Supervisory Cadastral Surveyor)

AUG 30 1994

(Date)

*Leonard R. Sandoval*

(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Arizona State Office  
Phoenix, Arizona

The foregoing field notes of the east boundary and the subdivisional lines of Township 28 North, Range 26 East, Gila and Salt River Meridian, Arizona, executed by Robin T. Mathews and Leonard R. Sandoval, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

OCT 4 1994

(Date)

*James P. Kelley*

(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 28 N., R. 26 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~(Date)~~~~(Chief Cadastral Surveyor of Arizona)~~