

ORIGINAL

BOOK<sup>1</sup> 5422

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

---

SURVEY OF THE

---

EAST BOUNDARY,

---

SECTIONAL GUIDE MERIDIANS, AUXILIARY BASES,

---

AND

---

REMAINING SUBDIVISIONAL LINES

---

OF

---

TOWNSHIP 32 NORTH, RANGE 26 EAST

---

Of the Gila and Salt River Meridian,  
In the State of Arizona

EXECUTED BY

William F. Olver, Supervisory Cadastral Surveyor

---

Under Special Instructions dated November 22, 1989, approved November 22, 1989, and under Supplemental Special Instructions dated January 6, 1992, approved January 6, 1992, which provided for the surveys included under Group Number 715 and assignment instructions dated December 18, 1989.

Survey commenced July 1, 1992

Survey completed March 18, 1993

2  
**BOOK 5422**  
 INDEX DIAGRAM

TOWNSHIP 32 NORTH , RANGE 26 EAST

56	56	37	30	22	18						
6	54	5	36	4	29	3	21	2	17	1	4
53	52	36	14	15	17						
7	52	8	35	9	12	10	20	11	16	12	5
50	49	34	28								
18	48	17	33	16	11	15	14			13	
47	46	10	27								
19	45	20	9	21	26	22	23			24	
44	43	32									
30	41	29	8	28	25	27	26			25	
40	39	30	24								
31	38	32	7	33	23	34	19	35		36	

## BOOK 5422

T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the survey of the east boundary, sectional guide meridians, auxiliary bases, and remaining subdivisional lines of Township 32 North, Range 26 East, Gila and Salt River Meridian, Arizona.

This survey supersedes portions of Townships 5 and 6 North, Range 10 West of the Navajo Special Meridian. The boundaries and subdivisional lines of Townships 5 and 6 North, Range 10 West, Navajo Special Meridian, were surveyed by E. N. Darling in 1869. A portion of the subdivisional lines of Township 5 North, Range 10 West, were dependently resurveyed by B. J. Kinsey in 1933. A portion of the First Standard Parallel North, through Ranges 9 and 10 West, and portions of the east boundary and subdivisional lines, Township 5 North, Range 10 West, were dependently resurveyed by J. L. Warboys in 1940. A portion of the First Standard Parallel North (north boundary) and the subdivisional lines, Township 5 North, Range 10 West, were dependently resurveyed by Leonard R. Sandoval in 1991-92, concurrently under this same group.

The closing corners and 1/4 corners of minimum control on the Eighth Standard Parallel North (north boundary), Gila and Salt River Meridian, and the closing corners at intersection with appropriate section lines, T. 5 N., R. 10 W., Navajo Special Meridian, were established by tying each direction to the controlling corners. For simplicity, only ties to the nearest corner are given in the field notes and shown on the plat.

The south boundary of the township was surveyed by William F. Olver in 1992-93, the west boundary of the township was surveyed by Leonard R. Sandoval in 1990-91, and the Eighth Standard Parallel North (north boundary), through Ranges 25 and 26 East, was surveyed by Leonard R. Sandoval in 1990, all executed concurrently under this same group.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, the Special Instructions dated November 22, 1989, and the Supplemental Special Instructions dated January 6, 1992, for Group No. 715, Arizona.

The directions of all lines were determined by direct hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with a Topcon GTS-3B total station instrument.

## BOOK 5422

T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

## CHAINS

The geographic position of the southeast corner of the township was determined by the technique of differential positioning using the Ashtech M Series Geodetic Positioning System. First order U. S. Coast and Geodetic Survey triangulation stations "BEAUTIFUL 1951" and "LOHALI 1951" were used as the control stations. The geographic coordinates are as follows:

Latitude: 36°07'43.789" N., Longitude: 109°31'32.392" W. NAD27

The mean magnetic declination, as taken from the 1985 magnetic declination map published by U.S. Geological Survey, is 12 1/2° E.

Survey of the East Boundary,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

Beginning at the point for the cor. of T. 32 N., Rs. 26 and 27 E., on the Eighth Standard Parallel North, (north boundary), at 477.87 chs. east of the closing cor. of T. 32 N., Rs. 25 and 26 E.; closing cor. is monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. R25E S36 S1 S6 R25E R26E T32N CC 1991.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T33N R26E	
S36	
S 1	S 6
R26E	R27E
T32N	
1992	

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 33 N., R. 26 E., bears West, 10.89 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. base, 1 1/2 ft. high, with brass cap mkd. SC T33N R26E 1/4 S36 1990.

South, bet. secs. 1 and 6.

Over rolling and broken land.

## BOOK 5422

Survey of the East Boundary,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
4.56	Center of a hexagonal hogan, 20 ft. diam., bears West, 0.28 ch. dist.
40.75	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R26E R27E 1/4 S 1   S 6 1992</p> </div> <p>from which</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears S. 62° E., 1.84 chs. dist., mkd. 1/4 S6 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
41.75	Barbed wire fence, 5 strands, bears ENE and WSW.
77.80	Trail road, bears NE and SW.
80.75	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, in sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <p>T32N R26E   R27E S 1   S 6 ----- S12   S 7 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case in the drill hole beneath the brass tablet.</p>
	<p>Land, rolling and broken. Soil, rocky clay and sand. Timber, juniper and piñon; undergrowth, scattered native grasses.</p>
	South, bet. secs. 7 and 12.
	Over rolling land.
23.40	Barbed wire fence, 5 strands, bears E. and W.

## BOOK 5422

Survey of the East Boundary,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
38.05	Trail road, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T32N R26E R27E 1/4 S12   S 7 1992</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
41.65	Trail road, bears ENE and WSW.
45.31	Point for the closing cor. of secs. 7 and 12, at intersection with the N. bdy. of sec. 1, T. 5 N., R. 10 W., Navajo Special Meridian.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">CC T32N R26E   R27E S12   S 7</p>
	<p style="text-align: center;">T5N R10W S 1 1992</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	From this cor. point, AP 1 on the N. bdy. of sec. 1, T. 5 N., R. 10 W., Navajo Special Meridian, bears N. 89°35' E., 1.59 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 7 ins. above a mound of stone, 5 ft. base, 1 1/2 ft. high, with brass cap mkd. AP1 T5N R10W S1 1992 1940.
	Land, rolling. Soil, rocky clay. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.

7  
**BOOK 5422**

Survey of the First Sectional Guide Meridian,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 14 ins. above the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. T32N R26E S4 S5 S32 S33 T31N 1992.</p> <p>N. 0°03' W., bet. secs. 32 and 33.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T32N R26E  1/4  S32   S33  1992 </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
62.50	<p>Trail road, bears E. and W.</p>
72.10	<p>Trail road, bears ENE and WSW.</p>
77.85	<p>Barbed wire fence, 4 strands, bears E. and W.</p>
80.00	<p>Point for the cor. of secs. 28, 29, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T32N R26E  S29   S28  -----  S32   S33  1992 </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 1.26 chs. E. of a barbed wire fence, 6 strands, bears N. and S., and 2.80 chs. E. of a trail road, bears SSE and NNW.</p>

## BOOK 5422

Survey of the First Sectional Guide Meridian,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, rocky clay. No timber; scattered native grasses.</p>
	<p>N. 0°03' W., bet. secs. 28 and 29.</p>
	<p>Over rolling land.</p>
7.96	<p>Barbed wire fence, 4 strands, bears NNE and SSW.</p>
15.35	<p>Trail road, bears NE and SW.</p>
34.65	<p>Trail road, bears E. and W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R26E 1/4 S29   S28 1992</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
70.84	<p>SE cor. of metal frame building, 78 x 78 ft., bears East, 2.40 chs. dist., sides bear NNE and WNW.</p>
75.73	<p>Center of Navajo Route 7, asphalt pavement, 45 lks. wide, bears ESE and WNW.</p>
80.00	<p>Point for the cor. of secs. 20, 21, 28, and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R26E S20   S21 ----- S29   S28 1992</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located 2.35 chs. S. of a graded road, 38 lks. wide, bears ESE and WNW.</p>



## BOOK 5422

Survey of the First Sectional Guide Meridian,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, rocky clay. No timber; scattered native grasses.</p>
	<p>N. 0°03' W., bet. secs. 20 and 21.</p>
	<p>Over gently rolling land.</p>
21.78	<p>SE cor. of wood frame house, 24 x 16 ft., bears West, 2.30 chs. dist., long side bears N.</p>
31.10	<p>Graded road, 23 lks. wide, bears SE and NW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 44 ins. below the surface of the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R26E 1/4 S20   S21 1992</p>
	<p>from which</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' E., 182 ft. dist., with brass cap mkd. T32N R26E 1/4 S21 RM 182 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°00' E., 114 ft. dist., with brass cap mkd. T32N R26E 1/4 S21 RM 114 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located in a cultivated field.</p>
80.00	<p>Point for the cor. of secs. 16, 17, 20, and 21.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

BOOK 54 22

Survey of the First Sectional Guide Meridian,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>T32N R26E S17   S16 ----- S20   S21 1992</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, rocky and sandy clay. Timber, scattered cottonwood; undergrowth, native grasses.</p>
	<p>Survey of the First Auxiliary Base, T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona</p>
	<p>From the cor. of secs. 16, 17, 20, and 21, hereinbefore described.</p> <p>East, bet. secs. 16 and 21.</p> <p>Over gently rolling land.</p>
12.80	Center of Chinle Wash, 9.10 chs. wide, 1 ft. deep, drains NNW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 36 ins. below the surface of the ground, with brass cap mkd.</p>
	<p>T32N R26E S16 1/4 — S21 1992</p>
	<p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 20°00' E., 60 ft. dist., with brass cap mkd. T32N R26E 1/4 S16 RM 60 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>



Survey of the Second Sectional Guide Meridian,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
24.60	Center of an octagonal hogan, 25 ft. diam., bears West, 2.37 chs. dist.
25.15	Center of an octagonal log hogan, 35 ft. diam., bears West, 7.45 chs. dist.
26.80	Graded road, 30 lks. wide, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center; margin: 10px 0;"> T32N R26E  1/4  S16   S15  1992 </div> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
40.70	S. rim of Slim Canyon, 100 ft. deep, bears E. and W.
47.50	N. rim of Slim Canyon, 100 ft. deep, bears E. and W.
67.30	Trail road, bears E. and W.
72.75	Trail road, bears E. and W.
80.00	Point for the cor. of secs. 9, 10, 15, and 16.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center; margin: 10px 0;"> T32N R26E  S 9   S10  -----  S16   S15  1992 </div> Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.  Land, rolling and broken. Soil, rocky clay. No timber; scattered native grasses.
	N. 0°02' W., bet. secs. 9 and 10.  Over rolling land.

## BOOK 5422

Survey of the Second Sectional Guide Meridian,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R26E 1/4 S 9   S10 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 10 lks. S. of a wash, 8 lks. wide, 1 ft. deep, drains NW.</p>
74.10	Trail road, bears ESE and WNW.
80.00	<p>Point for the cor. of secs. 3, 4, 9, and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R26E S 4   S 3 ----- S 9   S10 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, rocky clay. No timber; scattered native grasses.</p>

Survey of the Second Auxiliary Base,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 3, 4, 9, and 10, hereinbefore described.  East, bet. secs. 3 and 10.  Over rolling and broken land.</p>
21.30	<p>W. rim of canyon, 100 ft. deep, bears N. and S.</p>
33.00	<p>E. rim of canyon, 100 ft. deep, bears SSE and NNW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.  Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, in sandstone bedrock, with top mkd.</p> <div style="text-align: center; margin: 10px 0;"> T32N R26E  S 3  1/4 —  S10  1992 </div> <p>from which</p> <p style="margin-left: 40px;">A piñon, 8 ins. diam., bears N. 59 3/4° W., 66 1/2 lks. dist., mkd. 1/4 S3 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case in the drill hole beneath the brass tablet.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 10, and 11.  Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, in sandstone bedrock, with top mkd.</p> <div style="text-align: center; margin: 10px 0;"> T32N R26E  S 3   S 2  —+—  S10   S11  1992 </div> <p>from which</p> <p style="margin-left: 40px;">The marks X BO, chiseled on a sandstone outcrop, bear S. 38 1/2° W., 1.025 chs. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case in the drill hole beneath the brass tablet.</p> <p>Cor. is located 60 lks. W. and 1.90 chs. N. of NW rim of canyon, 6 chs. wide, 150 ft. deep, bears NNE and SSW.</p>

## BOOK 5422

Survey of the Second Auxiliary Base,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, rocky clay with sandstone outcrops. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p>
40.00	<p>East, bet. secs. 2 and 11.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T32N R26E S 2 1/4 — S11 1992</p> <p>from which</p> <p style="text-align: center;">A piñon, 10 ins. diam., bears S. 27 1/2° E., 72 1/2 lks. dist., mkd. 1/4 S11 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case in the drill hole beneath the brass tablet.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R26E S 2   S 1 —   — S11   S12 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, rocky clay with sandstone outcrops. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p>

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 1, 2, 11, and 12, hereinbefore described.</p> <p>S. 0°01' E., bet. secs. 11 and 12.</p> <p>Over rolling land.</p>
28.45	Trail road, bears E. and W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T32N R26E  1/4  S11   S12  1992 </div>
44.89	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the closing cor. of secs. 11 and 12, at intersection with the N. bdy. of sec. 2, T. 5 N., R. 10 W., Navajo Special Meridian.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> CC  T32N R26E  S11   S12  <hr style="width: 50%; margin: 0 auto;"/> S 2  T5N R10W  1992 </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, angle point 1 on the N. bdy. of sec. 2, T. 5 N., R. 10 W., Navajo Special Meridian, bears N. 88°56' W., 0.18 ch. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 13 ins. above a mound of stone, 3 ft. base, 1 ft. high, and witnessed by a mound of stone, 6 ft. base, 3 ft. high, to the N., with brass cap mkd. AP1 T5N R10W S2 1992 1940.</p>



## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, rocky clay. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p>
39.985	<p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°59' W., bet. secs. 1 and 12.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R26E S 1 1/4 — S12 1992</p>
49.36	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Barbed wire fence, 5 strands, bears NNE and SSW.</p>
79.97	<p>The cor. of secs. 1, 2, 11, and 12, hereinbefore described.</p> <p>Land, rolling. Soil, rocky clay and sand. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p>
35.20	<p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Over rolling and broken land.</p> <p>NW rim of canyon, 6 chs. wide, 60 ft. deep, drains SSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.73	<p style="text-align: center;">T32N R26E 1/4 S 2   S 1 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the closing cor. of secs. 1 and 2, at intersection with the Eighth Standard Parallel North, the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R26E S35 ----- S 2   S 1 T32N R26E CC 1992</p> <p>from which</p> <p style="text-align: center;">A juniper, 8 ins. diam., bears S. 83 1/4° W., 25 lks. dist., mkd. T32N R26E S2 CC BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 33 N., R. 26 E., bears West, 10.94 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T33N R26E 1/4 S35 1990.</p> <p>Land, rolling and broken. Soil, rocky clay. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 1 only, T. 32 N., R. 26 E., at midpoint on the N. bdy. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T33N R26E</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1/4 S 1 T32N R26E 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 35 and 36, T. 33 N., R. 26 E., bears West, 10.915 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T33N R26E S35 S36 1990.</p>
	<p>From the true point for the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp.</p> <p>From this cor. point, the witness cor. to the cor. of secs. 2, 3, 34, and 35, bears West, 1.00 ch. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. WC T32N R26E S2 S3 S34 S35 T31N 1992 and an arrow pointing east.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over rolling land.</p>
32.57	<p>Point for the closing cor. of secs. 34 and 35, at intersection with the S. bdy. of sec. 22, T. 5 N., R. 10 W., Navajo Special Meridian.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5N R10W S22</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S34   S35 T32N R26E CC 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, the cor. of secs. 22, 23, and 26 only, T. 5 N., R. 10 W., Navajo Special Meridian, bears N. 85°37' E., 16.50 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 ft. base, 1 ft. high, with brass cap mkd. T5N R10W S22 S23 S26 1992.</p> <p>Land, rolling. Soil, sand and rocky clay. No timber; scattered native grasses.</p>
	<p>From the cor. of secs. 2, 3, 10, and 11, hereinbefore described.</p> <p>S. 0°01' E., bet. secs. 10 and 11.</p> <p>Over rolling and broken land.</p>
11.10	SE rim of canyon, 150 ft. deep, bears NE and SW.
35.60	Trail road, bears E. and W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R26E 1/4 S10   S11 1992</p>
40.40	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Trail road, bears ENE and WSW.</p>
43.36	<p>Point for the closing cor. of secs. 10 and 11, at intersection with the N. bdy. of sec. 3, T. 5 N., R. 10 W., Navajo Special Meridian.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">CC T32N R26E S10   S11 ----- S 3 T5N R10W 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the AP on the N. bdy. of sec. 3, T. 5 N., R. 10 W., Navajo Special Meridian, bears N. 88°14' W., 0.10 ch. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 13 ins. above ground, and witnessed by a mound of stone, 4 ft. base, 3 ft. high, to the N., with brass cap mkd. AP T5N R10W S3 1992 1940.</p> <p>Land, rolling and broken. Soil, rocky clay. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p>
40.00	<p>From the cor. of secs. 2, 3, 10, and 11, hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R26E 1/4 S 3   S 2 ----- 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>45.15 Trail road, bears E. and W.</p> <p>53.00 Trail road, bears SE and NW.</p> <p>62.15 Trail road, bears SSE and NNW.</p>

## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS							
80.73	<p>Point for the closing cor. of secs. 2 and 3, at intersection with the Eighth Standard Parallel North, the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R26E S34</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 3</td> <td style="padding: 0 5px;">S 2</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T32N R26E</td> <td style="padding: 0 5px;">CC</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1992</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 33 N., R. 26 E., bears West, 10.92 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T33N R26E 1/4 S34 1990.</p> <p>Land, rolling. Soil, rocky clay. Timber, scattered juniper and piñon; undergrowth, scattered native grasses.</p>	S 3	S 2	T32N R26E	CC	1992	
S 3	S 2						
T32N R26E	CC						
1992							
	<p>The point for the 1/4 sec. cor. of sec. 2 only, T. 32 N., R. 26 E., at midpoint on the N. bdy. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R26E</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-top: 1px solid black; padding: 0 5px;">1/4 S 2</td> </tr> <tr> <td style="padding: 0 5px;">T32N R26E</td> </tr> <tr> <td style="text-align: center; padding: 0 5px;">1992</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>	1/4 S 2	T32N R26E	1992			
1/4 S 2							
T32N R26E							
1992							

BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, the stan. cor. of secs. 34 and 35, T. 33 N., R. 26 E., bears West, 10.93 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. SC T33N R26E S34 S35 1990.</p>
	<p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., 12 ins. below the surface of the ground, with brass cap mkd. T32N R26E S3 S4 S33 S34 T31N 1992.</p> <p>from which</p> <p style="padding-left: 40px;">A reference monument bears S. 45°00' W., 270.0 ft. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T31N R26E S4 RM 270.0 FT. TO COR. 1992, and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">A reference monument bears N. 45°00' W., 130.0 ft. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T32N R26E S33 RM 130.0 FT. TO COR. 1992, and an arrow pointing to the cor.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over rolling land.</p>
5.15	Wire mesh and barbed wire fence, bears NNE and SSW.
7.97	SW cor. of stucco house, 26 x 24 ft., bears East, 1.67 chs. dist., long side bears ESE.
9.93	SE cor. of stucco house, 38 x 18 ft., bears West, 1.32 chs. dist., long side bears N.
16.10	Graded road, 33 lks. wide, bears NNE and SSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R26E 1/4 S33   S34 1992</p>

BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>								
47.47	<p>Center of a hexagonal hogan, 25 ft. diam., bears East, 2.22 chs. dist.</p>								
47.90	<p>Power line, bears NNE and SSW.</p>								
48.30	<p>SW cor. of stucco house, 48 x 40 ft., bears East, 1.10 chs. dist., long side bears ESE.</p>								
80.00	<p>Point for the cor. of secs. 27, 28, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>								
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>T32N</td> <td>R26E</td> </tr> <tr> <td>S28</td> <td>S27</td> </tr> <tr> <td>S33</td> <td>S34</td> </tr> <tr> <td colspan="2" style="text-align: center;">1992</td> </tr> </table>	T32N	R26E	S28	S27	S33	S34	1992	
T32N	R26E								
S28	S27								
S33	S34								
1992									
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, rocky clay. No timber; scattered native grasses.</p>								
	<p>East, bet. secs. 27 and 34.</p>								
	<p>Over rolling land.</p>								
10.25	<p>SW cor. of wood frame house, 24 x 16 ft., bears South, 2.69 chs. dist., long side bears NNE.</p>								
18.33	<p>Point for the closing cor. of secs. 27 and 34, at intersection with the W. bdy. of sec. 22, T. 5 N., R. 10 W., Navajo Special Meridian.</p>								
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>								



BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS																			
	<table border="0"> <tr><td>T32N</td><td> </td><td>T5N</td></tr> <tr><td>S27</td><td> </td><td>S22</td></tr> <tr><td>CC —</td><td> </td><td>R10W</td></tr> <tr><td>S34</td><td> </td><td></td></tr> <tr><td>R26E</td><td> </td><td></td></tr> <tr><td></td><td> </td><td>1992</td></tr> </table>	T32N		T5N	S27		S22	CC —		R10W	S34			R26E					1992
T32N		T5N																	
S27		S22																	
CC —		R10W																	
S34																			
R26E																			
		1992																	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the west 1/4 sec. cor. of sec. 22 only, T. 5 N., R. 10 W., Navajo Special Meridian, bears S. 4°11' E., 8.94 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, and witnessed by a mound of stone, 3 ft. base, 1 ft. high, to the W., with brass cap mkd. T5N R10W 1/4 S22 1992 1940.</p> <p>Land, rolling. Soil, rocky clay. No timber; scattered native grasses.</p>																		
	<p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over rolling land.</p>																		
2.99	SE cor. of stucco house, 28 x 12 ft., bears West, 1.10 chs. dist., long side bears NNE.																		
31.83	NE cor. of stucco house, 40 x 24 ft., bears West, 1.30 chs. dist., long side bears SSW.																		
32.31	NE cor. of stucco house, 28 x 16 ft., bears West, 1.45 chs. dist., long side bears SSE.																		
34.10	Point for the closing cor. of secs. 27 and 28, at intersection with the S. bdy. of sec. 16, T. 5 N., R. 10 W., Navajo Special Meridian.																		
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.																		

## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T5N R10W S16 <hr style="width: 10%; margin: auto;"/> S28   S27 T32N R26E CC 1992
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the E 1/16 sec. cor. of sec. 16 only, on the S. bdy. of sec. 16, T. 5 N., R. 10 W., Navajo Special Meridian, bears N. 89°55' W., 4.155 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with the surface of the ground, with brass cap mkd. T5N R10W E 1/16 S16 1992.</p> <p>from which</p> <p style="padding-left: 40px;">SE cor. of a concrete foundation for a wood frame house, bears S. 34 3/4° W., 38 lks. dist.</p> <p style="padding-left: 40px;">NE cor. of the same concrete foundation, bears N. 32 3/4° W., 35 lks. dist.</p> <p>Land, rolling. Soil, rocky clay. No timber; scattered native grasses.</p>
	<p>From the cor. of secs. 15, 16, 21, and 22, hereinbefore described.</p> <p>S. 0°02' E., bet. secs. 21 and 22.</p> <p>Over rolling land.</p>
10.90	Graded road, 27 lks. wide, bears NE and SW.
26.90	Trail road, bears ENE and WSW.
39.30	Trail road, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
45.72	<p style="text-align: center;">T32N R26E 1/4 S21   S22 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Point for the closing cor. of secs. 21 and 22, at intersection with the N. bdy. of sec. 16, T. 5 N., R. 10 W., Navajo Special Meridian.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">CC T32N R26E S21   S22 ----- S16 T5N R10W 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the E 1/16 sec. cor. of sec. 16 only, on the N. bdy. of sec. 16, T. 5 N., R. 10 W., Navajo Special Meridian, bears N. 89°53' W., 0.23 ch. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. base, 16 ins. high, with brass cap mkd. T5N R10W E 1/16 S16 1992.</p> <p>Land, rolling. Soil, rocky clay. No timber; scattered native grasses.</p>
3.30	<p>From the cor. of secs. 15, 16, 21, and 22, hereinbefore described.</p> <p>East, bet. secs. 15 and 22.</p> <p>Over rolling land.</p> <p>Trail road, bears N. and S.</p>
18.80	<p>Graded road, 30 lks. wide, bears NNE and SSW.</p>

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS																			
20.21	<p>Point for the closing cor. of secs. 15 and 22, at intersection with the W. bdy. of sec. 10, T. 5 N., R. 10 W., Navajo Special Meridian.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 2px 5px;">T32N</td> <td style="border-left: 1px solid black; padding: 2px 5px;"></td> <td style="padding: 2px 5px;">T5N</td> </tr> <tr> <td style="padding: 2px 5px;">S15</td> <td style="border-left: 1px solid black; padding: 2px 5px;"></td> <td style="padding: 2px 5px;">S10</td> </tr> <tr> <td style="padding: 2px 5px;">CC ———</td> <td style="border-left: 1px solid black; padding: 2px 5px;"></td> <td style="padding: 2px 5px;">R10W</td> </tr> <tr> <td style="padding: 2px 5px;">S22</td> <td style="border-left: 1px solid black; padding: 2px 5px;"></td> <td style="padding: 2px 5px;"></td> </tr> <tr> <td style="padding: 2px 5px;">R26E</td> <td style="border-left: 1px solid black; padding: 2px 5px;"></td> <td style="padding: 2px 5px;"></td> </tr> <tr> <td colspan="3" style="padding: 2px 5px;">1992</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 10 only, T. 5 N., R. 10 W., Navajo Special Meridian, bears S. 0°42' E., 4.865 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, and witnessed by a mound of stone, 4 ft. base, 1 ft. high, to the W., with brass cap mkd. T5N R10W 1/4 S10 1992 1940.</p> <p>Land, rolling.  Soil, rocky clay.  No timber; scattered native grasses.</p> <hr style="border: 0.5px solid black;"/> <p>From the cor. of secs. 9, 10, 15, and 16, hereinbefore described.  East, bet. secs. 10 and 15.  Over rolling land.</p>	T32N		T5N	S15		S10	CC ———		R10W	S22			R26E			1992		
T32N		T5N																	
S15		S10																	
CC ———		R10W																	
S22																			
R26E																			
1992																			
17.70	Trail road, bears NNE and SSW.																		
21.63	<p>Point for the closing cor. of secs. 10 and 15, at intersection with the W. bdy. of sec. 3, T. 5 N., R. 10 W., Navajo Special Meridian.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>																		

BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS																											
	<div style="text-align: center;"> <table border="0"> <tr> <td>T32N</td> <td> </td> <td>T5N</td> </tr> <tr> <td>S10</td> <td> </td> <td>S 3</td> </tr> <tr> <td>CC ———</td> <td> </td> <td>R10W</td> </tr> <tr> <td>S15</td> <td> </td> <td></td> </tr> <tr> <td>R26E</td> <td> </td> <td></td> </tr> <tr> <td></td> <td> </td> <td>1992</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the west 1/4 sec. cor. of sec. 3 only, T. 5 N., R. 10 W., Navajo Special Meridian, bears S. 2°12' W., 5.245 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T5N R10W 1/4 S3 1992.</p> <p>Land, rolling. Soil, rocky clay. No timber; scattered native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 9, and 10, hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over rolling and broken land.</p> <p>13.70 S. rim of canyon, 50 ft. deep, bears ESE and WNW.</p> <p>24.10 N. rim of canyon, 50 ft. deep, bears NE and SW.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T32N</td> <td>R26E</td> </tr> <tr> <td></td> <td>1/4</td> </tr> <tr> <td>S 4</td> <td>  S 3</td> </tr> <tr> <td></td> <td>1992</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>44.50 Trail road, bears SE and NW.</p> <p>80.74 Point for the closing cor. of secs. 3 and 4, at intersection with the Eighth Standard Parallel North, the N. bdy. of the Tp.</p>	T32N		T5N	S10		S 3	CC ———		R10W	S15			R26E					1992	T32N	R26E		1/4	S 4	S 3		1992
T32N		T5N																									
S10		S 3																									
CC ———		R10W																									
S15																											
R26E																											
		1992																									
T32N	R26E																										
	1/4																										
S 4	S 3																										
	1992																										

## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

## CHAINS

Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, in sandstone bedrock, with top mkd.

T33N R26E  
S33

S 4	S 3
T32N R26E	
CC	
1992	

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case in the drill hole beneath the brass tablet.

From this cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 33 N., R. 26 E., bears West, 10.92 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T33N R26E 1/4 S33 1990.

Land, rolling and broken.  
Soil, rocky clay and sand.  
No timber; scattered native grasses.

The point for the 1/4 sec. cor. of sec. 3 only, T. 32 N., R. 26 E., at midpoint on the N. bdy. of sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T33N R26E  
1/4 S 3  
T32N R26E  
1992

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

From this cor. point, the stan. cor. of secs. 33 and 34, T. 33 N., R. 26 E., bears West, 10.92 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T33N R26E S33 S34 1990.

From the cor. of secs. 27, 28, 33, and 34.

## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	S. 89°59' W., bet. secs. 28 and 33.
	Over gently rolling land.
30.25	SW cor. of stucco house, 56 x 40 ft., bears North, 0.97 ch. dist., long side bears N.
31.60	Power line, bears N. and S.
32.00	Graded road, 38 lks. wide, bears N. and S.
39.99	Point for the 1/4 sec. cor. of secs. 28 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T32N R26E S28 1/4 — S33 1992</p>
	from which
	<p style="text-align: center;">The westernmost cor. of an octagonal hogan, 32 ft. diam., bears S. 39 1/4° E., 1.62 chs. dist.</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
53.40	Trail road, bears ENE and WSW.
57.59	Barbed wire fence, 4 strands, bears N. and S.
58.80	Center of graded landing strip, 1.21 chs. wide, bears N. and S.
59.87	Barbed wire fence, 4 strands, bears N. and S.
60.15	Trail road, bears NNE and SSW.
60.61	Barbed wire fence, 4 strands, bears NNE and SSW.
79.98	The cor. of secs. 28, 29, 32, and 33, hereinbefore described.
	Land, gently rolling.
	Soil, rocky and sandy clay.
	No timber; scattered native grasses.

## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>From the cor. of secs. 20, 21, 28, and 29, hereinbefore described.</p>												
	<p>East, bet. secs. 21 and 28.</p>												
	<p>Over gently rolling land.</p>												
18.09	<p>Point for the closing cor. of secs. 21 and 28, at intersection with the W. bdy. of sec. 16, T. 5 N., R. 10 W., Navajo Special Meridian.</p>												
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. below the surface of the ground, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 5px;">T32N</td> <td style="border-left: 1px solid black; padding-left: 5px;">T5N</td> </tr> <tr> <td style="padding-right: 5px;">S21</td> <td style="border-left: 1px solid black; padding-left: 5px;">S16</td> </tr> <tr> <td style="padding-right: 5px;">CC ———</td> <td style="border-left: 1px solid black; padding-left: 5px;">R10W</td> </tr> <tr> <td style="padding-right: 5px;">S28</td> <td style="border-left: 1px solid black; padding-left: 5px;"></td> </tr> <tr> <td style="padding-right: 5px;">R26E</td> <td style="border-left: 1px solid black; padding-left: 5px;"></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 5px; text-align: center;">1992</td> </tr> </table>	T32N	T5N	S21	S16	CC ———	R10W	S28		R26E			1992
T32N	T5N												
S21	S16												
CC ———	R10W												
S28													
R26E													
	1992												
	<p>from which</p>												
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 55°00' W., 42 ft. dist., with brass cap mkd. T32N R26E S28 CC RM 42 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>												
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' W., 20 ft. dist., with brass cap mkd. T32N R26E S21 CC RM 20 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>												
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>												
	<p>Cor. is located in a graded road, 33 lks. wide, bears NNE and SSW, 1.25 chs. NNE of intersection with a graded road, bears E. and W.</p>												
	<p>From this cor. point, the west 1/4 sec. cor. of sec. 16 only, T. 5 N., R. 10 W., Navajo Special Meridian, bears S. 2°55' W., 5.71 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 8 ins. below the surface of the ground, with brass cap mkd. T5N R10W 1/4 S16 1992.</p>												



Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p style="margin-left: 40px;">A reference monument bears N. 44°58' E., 225.0 ft. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T5N R10W 1/4 S16 RM 225.0 FT. TO COR. 1992, and an arrow pointing to the cor.</p> <p style="margin-left: 40px;">A reference monument bears S. 45°00' E., 200.0 ft. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T5N R10W 1/4 S16 RM 200.0 FT. TO COR. 1992, and an arrow pointing to the cor.</p> <p>Land, gently rolling.  Soil, rocky and sandy clay.  No timber; scattered native grasses.</p> <hr/> <p>From the cor. of secs. 16, 17, 20, and 21, hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over gently rolling land.</p>
25.00	Center of Chinle Wash, 9 chs. wide, 3 ft. deep, drains NNW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R26E  1/4  S17   S16  1992</p>
48.11	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Barbed wire fence, 5 strands, bears ESE and WNW.</p>
70.16	Barbed wire fence, 4 strands, bears ENE and WSW.
71.50	Wash, 3 chs. wide, 5 ft. deep, drains WNW.
72.05	Trail road, bears ENE and WSW.

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
73.80	Barbed wire fence, 5 strands, bears E. and W.										
74.20	Center of water well, 2 ft. square, 4 ft. high, with concrete base, 11 ft. square, bears East, 4.80 chs. dist.										
80.00	<p>Point for the cor. of secs. 8, 9, 16, and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T32N R26E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 8</td> <td style="padding: 2px 5px;">S 9</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; margin-top: 5px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S17</td> <td style="padding: 2px 5px;">S16</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">1992</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling.  Soil, rocky clay and sand.  Timber, saltcedar and russian olive; undergrowth, native grasses.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 9, 10, 15, and 16, hereinbefore described.</p> <p>West, bet. secs. 9 and 16.</p> <p>Over rolling land.</p>	T32N R26E		S 8	S 9			S17	S16	1992	
T32N R26E											
S 8	S 9										
S17	S16										
1992											
35.53	SE cor. of stucco house, 40 x 20 ft., bears North, 0.55 ch. dist., long side bears NNE.										
39.995	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T32N R26E</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">S 9</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">1/4 —</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">S16</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">1992</td> </tr> </table> </div> <p>from which</p> <p style="text-align: center; margin-top: 10px;">An elm, 18 ins. diam., bears N. 50 1/2° E., 34 1/2 lks. dist., mkd. 1/4 S9 BT.</p>	T32N R26E		S 9		1/4 —		S16		1992	
T32N R26E											
S 9											
1/4 —											
S16											
1992											

## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>SW cor. of stucco house, 24 x 22 ft., bears N. 76 1/4° E., 2.11 chs. dist., long side bears NNE.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
40.30	<p>Graded road, 33 lks. wide, bears N. and S.</p>
40.77	<p>Barbed wire fence, 4 strands, bears N. and S.</p>
65.45	<p>Trail road, bears NE and SW.</p>
79.99	<p>The cor. of secs. 8, 9, 16, and 17.</p> <p>Land, rolling. Soil, rocky clay. No timber; scattered native grasses.</p>
	<p>N. 0°03' W., bet. secs. 8 and 9.</p>
	<p>Over gently rolling land.</p>
24.60	<p>Graded road, 33 lks. wide, bears SE and NW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R26E 1/4 S 8   S 9 1992</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 8, and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R26E S 5   S 4 ----- S 8   S 9 1992</p>

## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, rocky and sandy clay. No timber; scattered native grasses.</p>
	<p>From the cor. of secs. 3, 4, 9, and 10, hereinbefore described.</p> <p>N. 89°59' W., bet. secs. 4 and 9.</p>
	<p>Over rolling land.</p>
39.995	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R26E S 4 1/4 — S 9 1992</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
51.60	<p>Trail road, bears SSE and NNW.</p>
79.99	<p>The cor. of secs. 4, 5, 8, and 9.</p>
	<p>Land, rolling. Soil, rocky clay. No timber; scattered native grasses.</p>
	<p>N. 0°03' W., bet. secs. 4 and 5.</p>
	<p>Over rolling land.</p>
17.30	<p>Trail road, bears ENE and WSW.</p>
28.35	<p>SW cor. of wood frame house, 34 x 24 ft., bears West, 4.65 chs. dist., long side bears NNE.</p>
33.80	<p>Wash, 1.52 chs. wide, 8 ft. deep, drains NW.</p>
36.10	<p>Trail road, bears NE and SW.</p>

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R26E  1/4  S 5   S 4  1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
80.73	<p>Point for the closing cor. of secs. 4 and 5, at intersection with the Eighth Standard Parallel North, the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R26E  S32  -----  S 5   S 4  T32N R26E  CC  1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 33 N., R. 26 E., bears West, 10.92 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T33N R26E 1/4 S32 1990.</p> <p>Land, rolling.  Soil, rocky clay.  No timber; scattered native grasses.</p> <hr style="border: 0.5px solid black;"/> <p>The point for the 1/4 sec. cor. of sec. 4 only, T. 32 N., R. 26 E., at midpoint on the N. bdy. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>T33N R26E</p> <hr style="width: 20%; margin: auto;"/> <p>1/4 S 4  T32N R26E  1992</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 32 and 33, T. 33 N., R. 26 E., bears West, 10.92 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T33N R26E S32 S33 1990.</p>
	<p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T32N R26E S5 S6 S31 S32 T31N 1992.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over gently rolling land.</p>
18.40	Cottonwood Wash, 2.27 chs. wide, 6 ft. deep, drains E.
21.25	Trail road, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 32.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T32N R26E  1/4  S31   S32  1992 </p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
45.80	Trail road, bears NNE and SSW.
55.70	Trail road, bears SSE and NNW.
75.90	Underground pipeline, bears ESE and WNW.
80.00	Point for the cor. of secs. 29, 30, 31, and 32.

## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<div style="text-align: center;"> <table border="0"> <tr> <td>T32N</td> <td>R26E</td> </tr> <tr> <td>S30</td> <td>S29</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S31</td> <td>S32</td> </tr> <tr> <td colspan="2" style="text-align: center;">1992</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 2.45 chs. E. of a trail road, bears N. and S.</p> <p>Land, gently rolling. Soil, rocky and sandy clay. No timber; scattered native grasses.</p>	T32N	R26E	S30	S29			S31	S32	1992	
T32N	R26E										
S30	S29										
S31	S32										
1992											
	<p>From the cor. of secs. 28, 29, 32, and 33, hereinbefore described.</p> <p>West, bet. secs. 29 and 32.</p> <p>Over rolling land.</p>										
32.80	Nazlini Wash, 3 chs. wide, 10 ft. deep, drains NNW.										
37.80	Trail road, bears N. and S.										
37.90	Center of a hexagonal hogan, 20 ft. diam., bears South, 3.75 chs. dist.										
40.005	Point for the 1/4 sec. cor. of secs. 29 and 32.										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T32N</td> <td>R26E</td> </tr> <tr> <td></td> <td>S29</td> </tr> <tr> <td></td> <td>1/4 —</td> </tr> <tr> <td></td> <td>S32</td> </tr> <tr> <td colspan="2" style="text-align: center;">1992</td> </tr> </table> </div>	T32N	R26E		S29		1/4 —		S32	1992	
T32N	R26E										
	S29										
	1/4 —										
	S32										
1992											
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>										
40.10	Barbed wire fence, 5 strands, bears NE and SW, on SE edge of Cottonwood Wash, 5 ft. deep, drains NE.										
45.08	Barbed wire fence, 5 strands, bears NE and SW, on NW edge of Cottonwood Wash, 5 ft. deep, drains NE.										

## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
51.30	Graded road, 33 lks. wide, bears N. and S.
64.50	Wash, 30 lks. wide, 6 ft. deep, drains N.
75.80	Trail road, bears SE and NW.
80.01	The cor. of secs. 29, 30, 31, and 32.
	Land, gently rolling. Soil, rocky and sandy clay. No timber; scattered native grasses.
	West, bet. secs. 30 and 31.
	Over gently rolling land.
8.50	Underground pipeline, bears ESE and WNW.
31.40	Trail road, bears NNE and SSW.
37.40	Power line, bears SSE and NNW.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T32N R26E S30 1/4 — S31 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
49.35	Trail road, bears NNE and SSW.
51.00	Graded road, 33 lks. wide, bears ESE and WNW.
67.60	Power line, bears NE and SW.
68.55	Trail road, bears N. and S.
77.80	E. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, bears NE and SW.



## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
78.31	<p>The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T32N R25E R26E S25 S30 S31 S36 1991.</p> <p>from which</p> <p>A reference monument bears S. 45°00' E., 25.0 ft. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T32N R26E S31 RM 25.0 FT. TO COR. 1991, and an arrow pointing to the cor.</p> <p>A reference monument bears N. 45°00' W., 180.0 ft. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T32N R25E S25 RM 180.0 FT. TO COR. 1991, and an arrow pointing to the cor.</p> <p>Land, gently rolling. Soil, rocky and sandy clay. No timber; scattered native grasses.</p>
	<p>From the cor. of secs. 29, 30, 31, and 32.</p>
	<p>N. 0°03' W., bet. secs. 29 and 30.</p>
	<p>Over gently rolling land.</p>
8.41	<p>SE cor. of wood frame house, 36 x 24 ft., bears West, 1.32 chs. dist., long side bears N.</p>
9.86	<p>Center of an octagonal hogan, 24 ft. diam., bears West, 0.91 ch. dist.</p>
22.00	<p>SW cor. of stucco house, 38 x 24, bears East, 1.44 chs. dist., long side bears NNE.</p>
23.90	<p>Graded road, 33 lks. wide, bears ENE and WSW.</p>
38.105	<p>Point selected for the witness cor. to the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	WC T32N R26E 1/4 S30 ↑ S29 1992
	from which  The easternmost cor. of Chinle Primary School Building 3, 225 x 70 ft., bears N. 56° W., 76 1/2 lks. dist., long side bears SW.  The southernmost cor. of Chinle Primary School Building 4, 225 x 70 ft., bears N. 14 1/2° W., 83 1/2 lks. dist., long side bears NW.  Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.  Cor. is located 3 lks. E. of chain link fence, bears NE and SW.
39.11	Intersect SE side of Chinle Primary School Building 4, 225 x 70 ft., 28 lks. NE from southernmost cor., long side bears SE and NW.
40.00	True point for the 1/4 sec. cor. of secs. 29 and 30. The point falls in Chinle Primary School Building 4, where it is impractical to construct a permanent monument.
64.33	Southernmost cor. of Chinle Community Center, 131 x 131 ft., bears West, 0.94 ch. dist., sides bear NE and NW.
73.44	Center of U. S. Highway 191, asphalt pavement, 1.00 ch. wide, bears NE in curve to left.
80.00	Point for the cor. of secs. 19, 20, 29, and 30.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T32N R26E S19   S20 ———— S30   S29 1992

## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>The SE cor. of the Navajo Communications Company building, 54 x 34 ft., bears N. 76° W., 1.01 chs. dist., long side bears N.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, rocky and sandy clay. No timber; scattered native grasses.</p>
	<p>From the cor. of secs. 20, 21, 28, and 29, hereinbefore described.</p>
	<p>West, bet. secs. 20 and 29.</p>
	<p>Over gently rolling land.</p>
9.37	<p>Center of Navajo Route 7, asphalt pavement, 36 lks. wide, bears ESE and WNW.</p>
31.00	<p>E. bank of Nazlini Wash, 10 ft. high, bears N. and S.</p>
40.015	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R26E S20 1/4 — S29 1992</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Cor. is located on a sandy island in Nazlini Wash.</p>
45.80	<p>W. bank of Nazlini Wash, 20 ft. high, bears SSE and NNW.</p>
69.47	<p>Intersect SE side of Chinle High School, an L- shaped building, on a segment 81 lks. long, a cor. bears SW, 25 lks. dist.</p>
71.17	<p>Intersect SW side of same Chinle High School, the southernmost cor. bears SE, 1.39 chs. dist.</p>

## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
74.44	Westernmost cor. of same Chinle High School, bears North, 1.24 chs. dist., sides bear NE and SE.
75.22	Chain link fence, 8 ft. high, bears NNE and SSW.
76.32	Center of U. S. Highway 191, asphalt pavement, 1.06 chs. wide, bears NNE and SSW.
80.03	The cor. of secs. 19, 20, 29, and 30.  Land, gently rolling. Soil, rocky and sandy clay. No timber; scattered native grasses.
	West, bet. secs. 19 and 30.
	Over rolling land.
5.71	Easternmost cor. of Navajo Nation Fleet Management building, 90 x 70 ft., bears South, 0.68 ch. dist., long side bears SW.
24.50	Power line, bears NE and SW.
29.90	Graded road, 30 lks. wide, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T32N R26E S19 1/4 — S30 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
51.46	Barbed wire fence, 6 strands, bears NNE and SSW.
68.17	Barbed wire fence, 6 strands, bears NE and SW.
69.20	Power line, bears N. and S.

## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
78.22	<p>The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T32N R25E R26E S19 S24 S25 S30 1991.</p> <p>Land, gently rolling. Soil, rocky and sandy clay. No timber; scattered native grasses.</p>
	<p>From the cor. of secs. 19, 20, 29, and 30.</p>
	<p>N. 0°03' W., bet. secs. 19 and 20.</p>
	<p>Over gently rolling land.</p>
6.77	<p>Intersect S. side of Navajo Tribal Utilities Authority's east building, SE cor. bears East, 46 lks. dist., long side bears E. and W.</p>
15.76	<p>Center of intersection of Navajo Route 7 and U. S. Highway 191, asphalt pavement, bears East, 2.10 chs. dist., highways extend ENE and NNW.</p>
23.00	<p>Center of U. S. Highway 191, asphalt pavement, 1.03 chs. wide, bears SSE and NNW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 9 ins. below the surface of the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T32N R26E 1/4 S19   S20 1992</p>
	<p>from which</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 35°00' E., 85 ft. dist., with brass cap mkd. T32N R26E 1/4 S20 RM 85 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>The NE cor. of a metal sided building, 70 x 60 ft., bears S. 2° E., 2.19 chs. dist., long side bears SSE.</p>

BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 35°00' W., 95 ft. dist., with brass cap mkd. T32N R26E 1/4 S19 RM 95 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>								
	<p>The SW cor. of metal sided Coca-Cola building, 120 x 75 ft., bears N. 60 1/4° W., 2.93 chs. dist., long side bears NNW.</p>								
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>								
	<p>Cor. is located in the center of a graded road, 83 lks. wide, bears ENE and WSW.</p>								
47.10	<p>Graded road, 42 lks. wide, bears ENE and WSW.</p>								
72.00	<p>Center shaft of windmill, bears East, 0.56 ch. dist.</p>								
80.00	<p>Point for the cor. of secs. 17, 18, 19, and 20.</p>								
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>								
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 2px;">T32N</td> <td style="padding: 2px;">R26E</td> </tr> <tr> <td style="padding: 2px;">S18</td> <td style="padding: 2px;">S17</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 2px;">S19</td> <td style="border-top: 1px solid black; padding: 2px;">S20</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px;">1992</td> </tr> </table>	T32N	R26E	S18	S17	S19	S20	1992	
T32N	R26E								
S18	S17								
S19	S20								
1992									
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>								
	<p>Land, gently rolling. Soil, rocky and sandy clay. No timber; scattered native grasses.</p>								
	<p>From the cor. of secs. 16, 17, 20, and 21, hereinbefore described.</p>								
	<p>West, bet. secs. 17 and 20.</p>								
	<p>Over gently rolling land.</p>								
13.55	<p>Trail road, bears N. and S.</p>								
40.03	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p>								

## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R26E S17 1/4 — S20 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
41.83	Barbed wire fence, 5 strands, bears SSE and NNW.
42.30	Graded road, 38 lks. wide, bears SSE and NNW.
43.13	Barbed wire fence, 5 strands, bears SSE and NNW.
66.90	E. bank of Nazlini Wash, 20 ft. high, bears SE and NW.
76.50	W. bank of Nazlini Wash, 20 ft. deep, bears N. and S.
76.95	Trail road, bears SSE and NNW.
80.06	The cor. of secs. 17, 18, 19, and 20.
	<p>Land, gently rolling. Soil, rocky and sandy clay. Timber, scattered cottonwood; undergrowth, scattered native grasses.</p> <hr/> <p>West, bet. secs. 18 and 19.</p> <p>Over gently rolling land.</p>
10.50	Power line, bears SSE and NNW.
15.29	E. right-of-way fence of U. S. Highway 191, barbed wire, 4 strands, parallels highway.
16.46	Center of U. S. Highway 191, asphalt pavement, 30 lks. wide, bears SSE and NNW.
17.66	W. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
18.20	Power line, bears SSE and NNW.

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
36.20	Graded road, 30 lks. wide, bears WSW on curve to left.
40.00	<p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R26E  S18  1/4 —  S19  1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
54.71	E. fence of Chinle Community Cemetery, NE cor. bears North 2.04 chs. dist.
63.90	Trail road, bears NNE and SSW.
67.95	Trail road, bears N. and S.
72.35	Trail road, bears ENE and WSW.
74.25	Trail road, bears NNE and SSW.
78.12	<p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T32N R25E R26E S13 S18 S19 S24 1991.</p> <p>Land, gently rolling.  Soil, rocky and sandy clay.  No timber; scattered native grasses.</p>
11.85	<p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over gently rolling land.</p>
40.00	<p>Trail road, bears SSE and NNW.</p> <p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a magnet in a 1 x 1 x 2 5/8 ins. white plastic case 36 ins. below the surface of the ground.</p>



BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 55°00' E., 100 ft. dist., with brass cap mkd. T32N R26E 1/4 S17 RM 100 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 55°00' W., 200 ft. dist., with brass cap mkd. T32N R26E 1/4 S18 RM 200 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located in the center of Nazlini Wash, 1.52 chs. wide, 10 ft. deep, drains NNW.</p>										
41.20	Trail road, bears ENE and WSW.										
42.69	Barbed wire fence, 4 strands, bears SSE and NNW.										
80.00	Point for the cor. of secs. 7, 8, 17, and 18.										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="857 1228 1010 1386"> <tr> <td>T32N</td> <td>R26E</td> </tr> <tr> <td>S 7</td> <td>S 8</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> <tr> <td colspan="2" style="text-align: center;">1992</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 1.80 chs. W. of a graded road, 30 lks. wide, bears N. on curve to right.</p> <p>Land, gently rolling. Soil, sandy clay and sand. No timber; scattered native grasses.</p>	T32N	R26E	S 7	S 8	-----		S18	S17	1992	
T32N	R26E										
S 7	S 8										
-----											
S18	S17										
1992											
	<p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>West, bet. secs. 8 and 17.</p>										

## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over gently rolling land.
16.10	Center of Chinle Wash, 4.55 chs. wide, 3 ft. deep, drains N.
40.035	Point for the 1/4 sec. cor. of secs. 8 and 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T32N R26E
	S 8
	1/4 —
	S17
	1992
	from which
	The SW cor. of a wood frame house, 40 x 30 ft., bears S. 84 1/2° E., 3.205 chs. dist., long side bears NNE.
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.07	The cor. of secs. 7, 8, 17, and 18.
	Land, gently rolling.
	Soil, sandy clay and sand.
	No timber; scattered native grasses.
	S. 89°59' W., bet. secs. 7 and 18.
	Over gently rolling land.
10.90	Nazlini Wash, 3.90 chs. wide, 7 ft. deep, drains NNE.
24.86	Chain link fence on S. side of sewage lagoon enclosure, bears ENE and WSW.
33.32	Chain link fence on W. side of sewage lagoon enclosure, bears SSE and NNW.
38.44	E. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
38.70	Power line, bears SSE and NNW.
39.61	Center of U. S. Highway 191, asphalt pavement, 42 lks. wide, bears SSE and NNW.

## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R26E S 7 1/4 — S18 1992</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, for a reference monument, bears N. 45°00' E., 130 ft. dist., with brass cap mkd. T32N R26E 1/4 S7 RM 130 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°00' W., 70 ft. dist., with brass cap mkd. T32N R26E 1/4 S18 RM 70 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
40.78	W. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
41.00	Power line, bears SSE and NNW.
55.35	Intersect E. side of a wood frame house, 32 x 26 ft., NE cor. bears North, 9 lks. dist., long side bears N. and S.
78.03	<p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T32N R25E R26E S7 S12 S13 S18 1991.</p> <p>Land, gently rolling. Soil, rocky and sandy clay. No timber; scattered native grasses.</p>

## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	From the cor. of secs. 7, 8, 17, and 18.										
	N. 0°03' W., bet. secs. 7 and 8.										
	Over gently rolling land.										
36.16	Barbed wire fence, 4 strands, bears ENE and WSW.										
36.90	Graded road, 30 lks. wide, bears ENE and WSW.										
38.50	Power line, bears ENE and WSW.										
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T32N R26E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S 7</td><td style="text-align: center;">S 8</td></tr> <tr><td colspan="2" style="text-align: center;">1992</td></tr> </table>	T32N R26E		1/4		S 7	S 8	1992			
T32N R26E											
1/4											
S 7	S 8										
1992											
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.										
80.00	Point for the cor. of secs. 5, 6, 7, and 8.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T32N R26E</td></tr> <tr><td style="text-align: center;">S 6</td><td style="text-align: center;">S 5</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S 7</td><td style="text-align: center;">S 8</td></tr> <tr><td colspan="2" style="text-align: center;">1992</td></tr> </table>	T32N R26E		S 6	S 5	-----		S 7	S 8	1992	
T32N R26E											
S 6	S 5										
-----											
S 7	S 8										
1992											
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.										
	Land, gently rolling.										
	Soil, rocky and sandy clay.										
	No timber; scattered native grasses.										
	From the cor. of secs. 4, 5, 8, and 9.										
	West, bet. secs. 5 and 8.										
	Over gently rolling land.										

## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
9.65	Graded road, 38 lks. wide, bears N. and S.
10.33	Barbed wire fence, 4 strands, bears N. and S.
32.91	Barbed wire fence, 4 strands, bears N. and S.
40.035	Point for the 1/4 sec. cor. of secs. 5 and 8.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T32N R26E S 5 1/4 — S 8 1992</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
56.40	Center of Chinle Wash, 7.60 chs. wide, 5 ft. deep, drains NNW.
80.07	The cor. of secs. 5, 6, 7, and 8.
	Land, gently rolling. Soil, rocky and sandy clay. Timber, saltcedar; undergrowth, scattered native grasses.
	S. 89°59' W., bet. secs. 6 and 7.
	Over gently rolling land.
8.30	Nazlini Wash, 1.50 chs. wide, 20 ft. deep, drains NE.
24.50	Power line, bears SE and NW.
27.30	Graded road, 38 lks. wide, bears SSE and NNW.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T32N R26E S 6 1/4 — S 7 1992</p>

Survey of the Remaining Subdivisional Lines,  
 T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
61.58	E. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
61.80	Power line, bears SSE and NNW.
62.78	Center of U. S. Highway 191, asphalt pavement, 42 lks. wide, bears SSE and NNW.
63.97	W. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
77.94	The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T32N R25E R26E S1 S6 S7 S12 1991.  Land, gently rolling. Soil, rocky and sandy clay. No timber; scattered native grasses.
	From the cor. of secs. 5, 6, 7, and 8.  N. 0°03' W., bet. secs. 5 and 6.  Over gently rolling land.
5.20	Nazlini Wash, 2.30 chs. wide, 5 ft. deep, drains E.
35.05	Trail road, bears ESE and WNW.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 6.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.  T32N R26E 1/4 S 6   S 5 1992
42.03	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.  NE cor. of log and stucco house, 40 x 20 ft., bears West, 2.81 chs. dist., long side bears SSW.

## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
42.49	Center of an octagonal hogan, 18 ft. diam., bears West, 2.87 chs. dist.
46.18	Center of an octagonal hogan, 24 ft. diam., bears West, 0.92 ch. dist.
59.30	Graded road, 33 lks. wide, bears ESE and WNW.
60.10	Graded road, 33 lks. wide, bears SE and NW.
61.05	Center of concrete water well, 3 x 3 x 4 ft. high, bears West, 1.94 chs. dist.
62.00	Graded road, 36 lks. wide, bears ENE and WSW.
75.20	Trail road, bears SE and NW.
80.73	Point for the closing cor. of secs. 5 and 6, at intersection with the Eighth Standard Parallel North, the N. bdy. of the Tp.
	Set a magnet in a 1 x 1 x 2 5/8 ins. white plastic case 24 ins. below the surface of the ground.
	from which
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 5°00' E., 240 ft. dist., with brass cap mkd. T32N R26E S5 CC RM 240 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 80°00' W., 170 ft. dist., with brass cap mkd. T32N R26E S6 CC RM 170 FT. TO COR. 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 1.50 chs. N. of SW bank of Chinle Wash, 15 chs. wide, 10 ft. deep, drains NW.
	From this cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 33 N., R. 26 E., bears West, 10.84 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T33N R26E 1/4 S31 1990.

## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

## CHAINS

From this same cor. point, the closing cor. of T. 32 N., Rs. 25 and 26 E., bears West, 77.82 chs., hereinbefore described.

Land, gently rolling.  
Soil, rocky and sandy clay.  
Timber, saltcedar; undergrowth, scattered native grasses.

The point for the 1/4 sec. cor. of sec. 5 only, T. 32 N., R. 26 E., at midpoint on the N. bdy. of sec. 5.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T33N R26E

1/4 S 5  
T32N R26E  
1992

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

From this cor. point, the stan. cor. of secs. 31 and 32, T. 33 N., R. 26 E., bears West, 10.88 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T33N R26E S31 S32 1990.

The point for the 1/4 sec. cor. of sec. 6 only, T. 32 N., R. 26 E., at 40.00 chs. westing from the closing cor. of secs. 5 and 6, on the N. bdy. of sec. 6.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.

T33N R26E

1/4 S 6  
T32N R26E  
1992

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.



## BOOK 5422

Survey of the Remaining Subdivisional Lines,  
T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p data-bbox="415 342 1455 470">From this cor. point, the stan. cor. of T. 33 N., Rs. 25 and 26 E., bears West, 10.84 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T33N R25E R26E S31 S36 1990.</p> <hr/> <p data-bbox="699 533 1003 560" style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p data-bbox="415 630 1455 972">Area surveyed is within the Navajo Indian Reservation. The township is located in the vicinity of Chinle, Arizona. The terrain varies from gently rolling in the western portion to rolling and broken in the eastern portion. The elevation ranges from 5400 to 6100 feet above sea level. The soil is mainly clay, varying from sandy to rocky, with some areas of exposed sandstone bedrock. The timber is predominantly scattered juniper, piñon and saltcedar. The undergrowth is mostly scattered native grasses. The drainage is to the northwest, with Chinle and Nazlini Washes being the main drainages emptying northward from the township.</p> <p data-bbox="415 1010 1455 1230">U. S. Highway 191 runs north and south along the west boundary of the township. Navajo Route 7, extends from U. S. Highway 191 easterly through the center of the township. From these roads, there are numerous graded roads and trail roads branching off to residences throughout the township. The township is utilized for commercial activity and grazing sheep, goats, horses and cattle. There is no evidence of mining activity in the township.</p> <p data-bbox="415 1266 1097 1293">The mean magnetic declination is 12 1/2° E.</p> <hr/>
--------	---

BOOK 5422

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD ASSISTANTS

NAMES	CAPACITY
Robert L. Harper	Cadastral Surveyor
Edward Clarke	Surveying Technician
Nelson Kinsel	Surveying Technician

## BOOK 5422

## CERTIFICATE OF SURVEY

I, William F. Olver, Supervisory Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 22nd day of November, 1989, and Supplemental Special Instructions bearing date of the 6th day of January, 1992, I have surveyed the east boundary, sectional guide meridians, auxiliary bases and remaining subdivisional lines of Township 32 North, Range 26 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special and supplemental special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 17, 1994  
(Date)

William F. Olver  
(Supervisory Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Arizona State Office  
Phoenix, Arizona

The foregoing field notes of survey of the east boundary, sectional guide meridians, auxiliary bases, and the remaining subdivisional lines of Township 32 North, Range 26 East, Gila and Salt River Meridian, Arizona, executed by William F. Olver, Supervisory Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

NOV 28 1994  
(Date)

James P. Kelly  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 32 N., R. 26 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~