

ORIGINAL¹ BOOK 5434

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
FIELD NOTES
OF THE

DEPENDENT RESURVEY OF

THE FIFTH STANDARD PARALLEL NORTH (SOUTH BOUNDARY),

THE SEVENTH AUXILIARY GUIDE MERIDIAN EAST (WEST BOUNDARY),

AND A PORTION OF THE SUBDIVISIONAL LINES; AND

THE SUBDIVISION OF SECTIONS 7, 17, AND 22,

AND A METES-AND-BOUNDS SURVEY IN SECTION 7,

TOWNSHIP 21 NORTH, RANGE 29 EAST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

WILLIAM P. CARPENDER,

Cadastral Surveyor

STEPHEN J. MALLOY,

Cadastral Surveyor

KENNETH W. BAYS,

Cadastral Surveyor

Under special instructions dated January 12, 1987, approved February 23, 1987,
supplemental special instructions dated and approved October 13, 1987, supplemental
special instructions dated and approved February 29, 1988, and amended supplemental
special instructions dated and approved January 11, 1989, which provided for the
surveys included under Group Number 685 and assignment instructions dated April 21,
1987, and July 11, 1988.

Survey commenced May 28, 1987

Survey completed June 10, 1993

INDEX DIAGRAM

TOWNSHIP 21 NORTH, RANGE 29 EAST,

22 6 54	5	4	3	2	1
19 7 50	51 8 49	9 43	10 37	11 29	12 25
18 18 46	47 17 44	40 16	15 36	14	13
16 19	20	21	34 22 32	27 23	24
15 30	29	28	27	26	25
13 31 4	32 6	33 8	34 9	35 10	36 11

Subdivision of Sec. 7 pp. 55-61
 Subdivision of Sec. 17 pp. 61-68
 Subdivision of Sec. 22 pp. 68-70
 Metes-and-Bounds Survey, Sec. 7 pp. 70-72

BOOK 5434

T. 21 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of the dependent resurvey of the Fifth Standard Parallel North (south boundary), the Seventh Auxiliary Guide Meridian East (west boundary), and a portion of the subdivisional lines; and the subdivision of sections 7, 17, and 22, and a metes-and-bounds survey in section 7, Township 21 North, Range 29 East, Gila and Salt River Meridian, Arizona.

The township boundaries and subdivisional lines were surveyed by W.R. Fitzgerald in 1882. A portion of the Fifth Standard Parallel North (south boundary) and a portion of the Seventh Auxiliary Guide Meridian East (west boundary) was dependently resurveyed by William Strover in 1910. The southeast corner of the township was remonumented by Ty White in 1947 during the dependent resurvey of the Fifth Standard Parallel North, Township 21 North, Range 30 East. The east boundary was dependently resurveyed by Stephen J. Malloy in 1987-93.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, Special Instructions dated January 12, 1987, Supplemental Special Instructions dated October 13, 1987, Supplemental Special Instructions dated February 29, 1988, and Amended Supplemental Special Instructions dated January 11, 1989, for Group No. 685, Arizona.

Preliminary to the resurvey, the lines of the original survey and resurveys were retraced and search was made for all corners and other calls of the record. Lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of all lines were determined by observations on a U.S.C. & G. S. triangulation network, confirmed by hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with Geodimeter, Hewlett-Packard, Sokkia, and Topcon total stations.

The geographic position of the southeast corner of section 36, as determined from a tie made to U.S.C. & G.S. triangulation station "AHD S 11 1959", located in the NW 1/4 of section 13, T. 21 N., R. 28 E., is as follows:

Latitude: 35°10'05.18" N. Longitude: 109°12'33.45" W. NAD 1927

The mean magnetic declination is 13 1/2° E., as determined from U.S.G.S. Quadrangle "SANDERS, ARIZ.", 1971 edition.

BOOK 5434

T. 21 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

PRELIMINARY STATEMENT

During the course of this survey, wood post or stone corner monuments were found that were marked with the letters "IA" only or "IA" in addition to other corner markings such as grooves, notches, or 1/4.

Investigation of records of the St. Michaels Catholic Mission stored in the archives at the Special Collections Library at the University of Arizona in Tucson, revealed that these corners marked IA were set during the survey of Indian Allotments by the U.S. Indian Service in 1909 and 1910. Letters were found indicating that the surveyors for the Indian Service were corresponding with the GLO office in Santa Fe and that a GLO surveyor, William Strover, was inspecting Indian Allotment surveys in the township and working directly with the Indian Service surveyors while he was performing resurveys in the townships in 1910. Apparently the Indian Service sought to properly reestablish or perpetuate original survey corners.

The Indian Allotment monuments have been accepted locally for many years; moreover, improvements such as fences and roads have been built relying on the Indian Allotment corners as the true corner position.

Accordingly, the Indian Allotment monuments were accepted during the resurvey of this township as the best available evidence of the original corner positions.

Dependent Resurvey of the Fifth Standard Parallel North
(South Boundary), T. 21 N., R. 29 E.,
Gila and Salt River Meridian, Arizona

Restoring the survey executed by W.R. Fitzgerald, in 1882, and the dependent resurveys executed by William Strover, in 1910.

Beginning at the true point for the stan. cor. of Tps. 21 N., Rs. 28 and 29 E., determined at record bearing and dist. from the 1910 witness cor., not remonumented.

BOOK 5434


Dependent Resurvey of the 5th Stan. Par. N. (S. Bdy.),
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS

From the true point, the witness cor. bears South, 1.00 ch. dist., monumented with a sandstone, 24 x 15 x 8 ins., firmly set, 15 ins. in the ground, mkd. with 6 grooves on N., S., E., and W., also SC on E. face. Due to the true point for the stan. cor. of Tps. 21 N., Rs. 28 and 29 E. falling in a wash, the witness cor. will be perpetuated.

At the witness cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Bury the 1910 witness cor. alongside the stainless steel post.

Set a steel fence post near the cor.

The witness cor. is located in a cor. of fences bearing S. and WNW.

From the true point for the stan. cor. of Tps. 21 N., Rs. 28 and 29 E., U.S.C. & G.S. triangulation station "AHD S11 1959", with published latitude of 35°13'13.5018" N. and longitude of 109°19'42.0430 W., NAD 27, bears N. 13°12'51" W. (forward bearing), 288.65 chs. dist., monumented with a standard brass disk, set firmly in a cement slab, 1 ft. sq., projecting 5 ins. above the ground, mkd. U.S. COAST & GEODETIC SURVEY TRIANGULATION STATION AHD S11 1959 and a triangle in the center.

S. 89°53' E., on the south boundary of sec. 31.

Over rolling land, through scattered juniper.

40.11

Point for the stan. 1/4 sec. cor. of sec. 31, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

BOOK 5434

Dependent Resurvey of the 5th Stan. Par. N. (S. Bdy.),
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">S C T21N R29E 1/4 S31 <hr/>1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post</p> <p>Set a steel fence post near the cor.</p>
80.22	<p>The stan. cor. of secs. 31, and 32, monumented with a wood post, 3 ins. square, firmly set, projecting 10 ins. above the ground, mkd. with IA on the N., 5 grooves on the E. and 1 groove on the W. faces. This position has long been locally recognized as the cor. and is accepted as the best available evidence of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S C T21N R29E S31 S32 <hr/>1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Deposit the Indian Allotment post, 36 ins long, alongside the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this cor. a decayed juniper post, 3 ins. diam., 32 ins. long, loose on the ground, bears N. 75°02' W., 5.09 chs. dist.</p>
40.03	<p>S. 89°53' E., on the south boundary of sec. 32.</p> <p>Over rolling land, through scattered juniper.</p> <p>Point for the stan. 1/4 sec. cor. of sec. 32, at proportionate dist.; there is no remaining evidence of the original cor.</p>

BOOK 5434

Dependent Resurvey of the 5th Stan. Par. N. (S. Bdy.),
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S C T21N R29E 1/4 S32 ----- 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post</p> <p>Set a steel fence post near the cor.</p>
80.06	<p>The stan. cor. of secs. 32, and 33, monumented with a wood post, 5 ins. square, firmly set, projecting 6 ins. above the ground, mkd. with IA on the N., 1 groove on E., and 2 grooves on W. faces. This position has long been locally recognized as the cor. and is accepted as the best available evidence of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S C T21N R29E S32 S33 ----- 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post</p> <p>Deposit the Indian Allotment post, 36 ins long, alongside the stainless steel post</p> <p>Set a steel fence post near the cor.</p> <p>The cor is located in a cor. of fences bearing N. and E.</p> <p>From this cor. a juniper post, 3 ins. diam., projecting 24 ins. above the ground, mkd. with 1 groove on the E. and 2 grooves on W. faces, bears N. 89°17' W., 4.92 chs. dist.</p> <hr/>

BOOK 5434

Dependent Resurvey of the 5th Stan. Par. N. (S. Bdy.),
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
	S. 88°40' E., on the south boundary of sec. 33.
	Over rolling land, through scattered juniper.
39.13	Point for the stan. 1/4 sec. cor. of sec. 33, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	S C T21N R29E 1/4 S33 <hr/> 1987
	from which
	A juniper, 8 ins. diam., bears N. 12 1/2° E., 136 lks. dist., mkd. 1/4 S33 SC BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post
	Set a steel fence post near the cor.
	The cor is located 47 lks. S. of a fence, bears E. and W.
	From this cor. a juniper post, 2 ins. diam., projecting 18 ins. above the ground, mkd. with 2 grooves on E. and W. faces, bears N. 82°51' W., 4.11 chs. dist. This post was not similar in character to original or Indian Allotment monuments, and does not relate harmoniously to accepted cor. positions.
78.26	Point for the stan. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	S C T21N R29E S33 S34 <hr/> 1987
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post
	Set a steel fence post near the cor.

BOOK 5434

Dependent Resurvey of the 5th Stan. Par. N. (S. Bdy.),
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS

The cor is located 94 lks. S. of a fence, bears E. and W.

From this cor. a juniper post, 3 ins. diam., projecting 30 ins. above the ground, bears S. $44^{\circ}58'$ W., 8.91 chs. dist.

From this same cor. a juniper post, 4 ins. squared, projecting 18 ins. above the ground, mkd. with 3 grooves on E. and W. faces, bears N. $86^{\circ}18'$ W., 6.05 chs. dist.

From this same cor. a juniper post, 3 ins. diam., projecting 36 ins. above the ground, mkd. with 3 grooves on E. and W. faces, bears N. $73^{\circ}09'$ W., 3.30 chs. dist.

From this same cor. a juniper post, 3 ins. diam., projecting 72 ins. above the ground and wired in a fence, mkd. with 3 grooves on E. and W. faces, bears N. $72^{\circ}36'$ W., 3.27 chs. dist.

These posts were not similar in character to original or Indian Allotment monuments, and do not relate harmoniously to accepted cor. positions.

S. $88^{\circ}40'$ E., on the south boundary of sec. 34.

Over rolling land, through scattered juniper.

39.13 Point for the stan. $1/4$ sec. cor. of sec. 34, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 27 ins. in the ground, with brass cap mkd.

S C
T21N R29E
1/4 S34

1987

from which

A juniper, 7 ins. diam., bears N. 35° E.,
34 lks. dist., mkd. X BT.

A juniper, 34 ins. diam., bears N. 57° W.,
128 lks. dist., mkd. $1/4$ S34 SC BT.

Deposit a magnet in a $1 \times 1 \times 2\frac{5}{8}$ in. white plastic case beneath the stainless steel post

Set a steel fence post near the cor.

The cor is located 1.60 chs. S. of a fence, bears E. and W.

BOOK 5434

Dependent Resurvey of the 5th Stan. Par. N. (S. Bdy.),
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
78.26	<p>Point for the stan. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S C T21N R29E S34 S35</p> <hr style="width: 50%; margin: auto;"/> <p>1987</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post</p> <p>Set a steel fence post near the cor.</p> <p>From this cor. a juniper post, 4 ins. diam., projecting 24 ins. above the ground, mkd. with 4 grooves on the west face, 2 grooves and T21N on the east face, bears N. 26°57' W., 3.25 chs. dist.</p> <p>From this same cor. a juniper post, 4 ins. diam., projecting 24 ins. above the ground, mkd. with 2 grooves on east face, 4 grooves and faint E 4 on west face, bears S. 78°31' W., 3.57 chs. dist.</p> <p>These posts were not similar in character to original or Indian Allotment monuments, and do not relate harmoniously to accepted cor. positions.</p>
39.13	<p>S. 88°40' E., on the south boundary of sec. 35.</p> <p>Over rolling land, through scattered juniper.</p> <p>Point for the stan. 1/4 sec. cor. of sec. 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S C T21N R29E 1/4 S35</p> <hr style="width: 50%; margin: auto;"/> <p>1987</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post</p> <p>Set a steel fence post near the cor.</p>

BOOK 5434

Dependent Resurvey of the 5th Stan. Par. N. (S. Bdy.),
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>The cor is located 58 lks. N. of a fence, bears E. and W.</p> <p>From this cor. a juniper post, 2 ins. diam., projecting 12 ins. above the ground, bears S. 78°23' W., 2.66 chs. dist. This post was not similar in character to original or Indian Allotment monuments, and does not relate harmoniously to accepted cor. positions.</p>
59.65	Ridge, bears N. and S.
78.26	<p>Point for the stan. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S C</p> <p>T21N R29E</p> <p>S35 S36</p> <hr style="width: 50%; margin: auto;"/> <p>1987</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor is located 34 lks. N. of a fence, bears E. and W.</p> <p>From this cor. a juniper post, 4 ins. diam., projecting 24 ins. above the ground, bears S. 78°56' W., 1.79 chs. dist. This post was not similar in character to original or Indian Allotment monuments, and does not relate harmoniously to accepted cor. positions.</p>
39.13	<p>S. 88°40' E., on the south boundary of sec. 36.</p> <p>Over rolling land, through scattered juniper.</p> <p>Point for the stan. 1/4 sec. cor. of sec. 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S C</p> <p>T21N R29E</p> <p>1/4 S36</p> <hr style="width: 50%; margin: auto;"/> <p>1987</p> </div>

BOOK 5434

Dependent Resurvey of the 5th Stan. Par. N. (S. Bdy.),
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A juniper, 9 ins. diam., bears N. 32° E., 28 lks. dist., mkd. 1/4 S36 SC BT.</p> <p>A juniper, 8 ins. diam., bears N. 72° W., 84 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located 15 lks. N. of a fence, bears E. and W.</p> <p>From this cor. a decayed juniper post, 2 ins. diam., projecting 8 ins. above the ground, bears S. 79°35' W., 90 lks. dist. This post was not similar in character to original or Indian Allotment monuments, and does not relate harmoniously to accepted cor. positions.</p>
65.60	Ridge bears N. and S.
78.26	<p>The standard cor. of Tps. 21 N., Rs. 29 and 30 E., monumented with an iron post, 3 ins diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. SC T21N R29E R30E S36 S31 1947.</p> <p>from which the 1947 bearing trees</p> <p>A juniper, 14 ins. diam., bears N. 69° E., 280 lks. dist., mkd. T21N R30E S31 SC BT.</p> <p>A juniper, 10 ins. diam., bears N. 37 1/4° W., 245 1/2 lks. dist., mkd. T21N R29E S36 SC BT.</p> <p>Cor. is located 5 1/2 lks. S. of a fence, bears E. and W., and underneath power lines, bearing N., S. and E.</p> <p>From this cor., U.S.C. & G.S. triangulation station "AHD S11 1959", bears N. 61°48'28" W. (forward bearing), 611.50 chs. dist., hereinbefore described.</p> <hr/>

BOOK 5434

Dependent Resurvey of the 7th Aux. Guide Mer. E. (W. Bdy.),
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">Restoring the survey executed by W. R. Fitzgerald, in 1882</p> <hr style="width: 20%; margin: auto;"/> <p>From the true point for the stan. cor. of Tps. 21 N., Rs. 28 and 29 E.</p> <p>N. 0°34' W., bet. secs. 31 and 36, on the W. bdy. of the Tp.</p> <p>Ascend over rolling land, through scattered juniper.</p> <p>16.47 Point for the S. 1/16 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T21N S 1/16 R28E R29E S36 S31 1989</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located 117 lks. S. of a wash, 20 lks. wide, course WSW.</p> <p>32.94 Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T21N 1/4 R28E R29E S36 S31 1989</p> </div> <p>from which</p> <p style="text-align: center;">A juniper, 14 ins. diam., bears N. 72 1/4° W., 109 lks. dist., mkd. 1/4 S36 BT.</p>

BOOK 5434

Dependent Resurvey of the 7th Aux. Guide Mer. E. (W. Bdy.),
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS

Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case
beneath the stainless steel post.

Set a steel fence post near the cor.

65.88

The cor. of secs. 25, 30, 31, and 36, monumented with a wood
post, 48 ins. long, 5 ins. square, firmly set, projecting 30 ins.
above the ground, mkd. T21N. R29/ S on the NE. face.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T21N	
R28E	R29E
S25	S30
S36	S31
1987	

from which

A juniper, 7 ins. diam., bears S. 71° E.,
11 lks. dist., mkd. T21N R29E S31 BT.

A juniper, 7 ins. diam., bears S. 52 1/4° W.,
30 lks. dist., mkd. T21N R28E S36 BT.

A juniper, 8 ins. diam., bears N. 32° W.,
190 lks. dist., mkd. T21N R28E S25 BT.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case
beneath the stainless steel post.

Bury the original post alongside the stainless steel post.

Set a steel fence post near the cor.

The cor. is located in a line of ancient fence posts, bears W.

BOOK 5434

Dependent Resurvey of the 7th Aux. Guide Mer. E. (W. Bdy.),
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
	N. 0°13' W., bet. secs. 25 and 30.
	Over rolling land, through scattered juniper.
34.50	Desc. rolling N. slope.
36.60	Small saddle, bears E. and W.; asc. S. slope of small knob.
38.70	Top of small knob; desc. steep N. face of knob.
39.90	Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T21N 1/4 R28E R29E S25 S30 1987 </div>
	from which
	<div style="padding-left: 40px;"> A juniper, 7 ins. diam., bears S. 54 1/2° E., 36 lks. dist., mkd. 1/4 S30 BT. </div>
	<div style="padding-left: 40px;"> A juniper, 8 ins. diam., bears S. 67 3/4° W., 82 lks. dist., mkd. 1/4 S25 BT. </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
	The cor. is located on steep N. slope, 7 lks. E. of a barbed wire fence, bears N. and S.
41.40	Base of small knob; gradually desc. over gently rolling land, through scattered juniper.
44.90	Dry wash, 15 lks. wide, course WNW.
71.40	Dry wash, 15 lks. wide, course WSW.
78.70	Dry wash, 140 lks. wide, course W.

BOOK 5434

Dependent Resurvey of the 7th Aux. Guide Mer. E. (W. Bdy.),
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS													
79.80	<p>The cor. of secs. 19, 24, 25 and 30, monumented with a sandstone 22 x 16 x 4 ins., firmly set, projecting 4 ins. above the ground, mkd. IA on E. face, 2 grooves on S. face, and 4 grooves on N. face.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T21N</td></tr> <tr><td style="text-align: center;">R28E</td><td style="text-align: center;">R29E</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S30</td></tr> <tr><td colspan="2" style="text-align: center;">1987</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Bury the Indian Allotment stone alongside the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located at a cor. of fences bearing N., S., and E.</p>	T21N		R28E	R29E	S24	S19	-----		S25	S30	1987	
T21N													
R28E	R29E												
S24	S19												

S25	S30												
1987													
	<p>N. 0°08' W., bet. secs. 19 and 24.</p>												
	<p>Over gently rolling land, along a barbed wire fence.</p>												
20.60	<p>Abandoned road bed, bears NE. and SW.</p>												
39.97	<p>The 1/4 sec. cor. of secs. 19 and 24, determined at calculated dist. from the SE. cor. of lot 210 and the NE. cor. of lot 211, Arizona Park Estates Unit One, as recorded in the Apache County Courthouse, by Earl L. Snyder, R.L.S. 4128, dated January 28, 1963. This position has long been locally recognized as the cor. and is accepted as a careful and faithful determination of the position of the cor.</p> <p>The NE. cor. of lot 211, Arizona Park Estates Unit One, monumented with an open end iron pipe, 1 in. diam., firmly set, flush with ground, bears S. 44°07' W., 53.6 lks. dist.</p> <p>The SE. cor. of lot 210, Arizona Park Estates Unit One, monumented with an open end iron pipe, 1 in. diam., firmly set, flush with ground, bears N. 45°21' W., 53.6 lks. dist.</p>												

BOOK 5434

Dependent Resurvey of the 7th Aux. Guide Mer. E. (W. Bdy.),
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
26 ins. in the ground, with brass cap mkd.

T21N	
1/4	
R28E	R29E
S24	S19
1987	

Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case
beneath the stainless steel post.

Set a steel fence post near the cor.

The cor. is located 2 lks. W. of a barbed wire fence, bears N.
and S., and 22 lks. E. of the intersection of the center lines of
dirt roads, 12 lks. wide, bearing N., S., and W.

N. 0°12' W., beginning new measurement.

Over gently rolling land, along a barbed wire fence.

39.91 The cor. of secs. 13, 18, 19, and 24, monumented with a
sandstone, 18 x 17 x 5 ins., firmly set, 7 ins. below the surface
of the ground, mkd. with 3 grooves on the S. face and 3 grooves
on the N. face.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T21N	
R28E	R29E
S13	S18

S24	S19
1987	

Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case
beneath the stainless steel post.

BOOK 5434

Dependent Resurvey of the 7th Aux. Guide Mer. E. (W. Bdy.),
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
	Deposit the original stone alongside the stainless steel post.
	Set a steel fence post near the cor.
	The cor. is located 21 lks. E. of the intersection of the center lines of dirt roads, 20 lks. wide, bearing N., S., and W., and in a cor. of barbed wire fences bearing N., S., and E.
	N. 0°12' W., bet. secs. 13 and 18.
	Over nearly level land, along a barbed wire fence.
7.20	Bladed gravel road, 30 lks. wide, bears E. and W.
39.96	The 1/4 sec. cor. of secs. 13 and 18, monumented with a wood post, 52 ins. long, 3 ins. square, firmly set, projecting 30 ins. above the ground, mkd. IA on E. face.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T21N 1/4 R28E R29E S13 S18 1987 </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
	Bury the Indian Allotment post alongside the stainless steel post.
	Set a steel fence post near the cor.
	The cor. is located 11 lks. E. of a dirt road, bears N. and S., and in a barbed wire fence, bears N. and S.
	N. 0°11' W., beginning new measurement.
	Over nearly level land, along a barbed wire fence.
26.50	S. bank of Puerco River, bears NE. and SW.

BOOK 5434

Dependent Resurvey of the 7th Aux. Guide Mer. E. (W. Bdy.),
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
40.81	<p>Point for the cor. of secs. 7, 12, 13, and 18, at proportionate dist.; there is no remaining evidence of the original cor. The true point falls in the Puerco River where it is impractical to establish a permanent monument.</p> <hr/> <p>N. 0°11' W., bet. secs. 7 and 12.</p> <p>Across bed of Puerco River.</p>
3.40	<p>N. bank of the Puerco River, bears NE. and SW.</p>
4.30	<p>Point selected for the witness cor. of secs. 7, 12, 13, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div data-bbox="755 846 935 1058" style="text-align: center;"> <pre> WC T21N R28E R29E S12 S7 ----- S13 V S18 1987 </pre> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 3 1/2 ft. high, W. of the witness cor.</p> <p>Set a steel fence post near the witness cor.</p>
4.50	<p>Barbed wire fence, bears NE. and SW.</p>
4.90	<p>A.T.& S.F. Railroad track, bears NE. and SW.</p>
5.10	<p>A.T.& S.F. Railroad track, bears NE. and SW.</p>
6.70	<p>Telephone line, bears NE. and SW.</p>
15.86	<p>Intersect east bound right-of-way of Interstate Highway 40.</p> <p>From this point, an Arizona Highway Dept. right-of-way monument, a brass disk, encased in a concrete cylinder, 6 ins. diam., flush with ground, mkd. STA 1820 X 00 RP 150 EB, bears N. 46°13' E., 65.25 chs. dist.</p>

BOOK 5434

Dependent Resurvey of the 7th Aux. Guide Mer. E. (W. Bdy.),
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
	From this same point, an Arizona Highway Dept. right-of-way monument, a brass disk, encased in a concrete cylinder, 6 ins. diam., flush with ground, mkd. 1753 X 00 RP 2600 WB 1963, bears S. 46°13' W., 36.18 chs. dist.
19.00	Eastbound lanes of Interstate Highway 40, pavement, 60 lks. wide, bear NE and SW
21.30	Westbound lanes of Interstate Highway 40, pavement, 60 lks. wide, bear NE and SW
22.80	Frontage road, paved, 40 lks. wide, bears NE and SW
23.38	Intersect west bound right-of-way of Interstate Highway 40.
	From this point, an Arizona Highway Dept. right-of-way monument, a brass disk, encased in a concrete cylinder, 6 ins. diam., flush with ground, mkd. 1790 X 00 RP 100.0 W.B. 1963, bears N. 46°13' E., 14.69 chs. dist.
	From this same point, an Arizona Highway Dept. right-of-way monument, a brass disk, encased in a concrete cylinder, 6 ins. diam., projecting 1 in. above the ground, mkd. 1780 X 2923 RP 100.0 W.B. 1963, bears S. 46°13' W., 1 lk. dist.
27.20	Power line, bears ENE. and WSW.; ascend over SE. slope.
40.81	Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T21N 1/4 R28E R29E S12 S7 1987 </div>
	from which
	A juniper, 8 ins. diam., bears S. 48 3/4° E., 79.5 lks. dist., mkd. 1/4 S7 BT.
	A pinyon pine, 6 ins. diam., bears S. 7° W., 156 lks. dist., mkd. 1/4 S12 BT.

BOOK 5434

Dependent Resurvey of the 7th Aux. Guide Mer. E. (W. Bdy.),
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS													
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located 9 lks. E. of a barbed wire fence, bears N. and S.</p>												
45.70	Base of rim rock, bears NE. and SW.; asc. steep rocky, SE. slope.												
48.50	Top of rim rock, bears ENE. and WSW.; asc. gradually over rolling mesa top, along a row of ancient fence posts, through scattered juniper.												
81.62	<p>The cor. of secs. 1, 6, 7 and 12, monumented with a sandstone, 10 x 8 x 8 ins., firmly set, projecting 8 ins. above the ground, mkd. with 5 grooves on the S. face, and in a mound of stone, 2 ft. base, to top of stone.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T21N</td></tr> <tr><td>R28E</td><td>R29E</td></tr> <tr><td>S1</td><td>S6</td></tr> <tr><td colspan="2">—</td></tr> <tr><td>S12</td><td>S7</td></tr> <tr><td colspan="2">1987</td></tr> </table> </div> <p>from which</p> <p>A juniper, 6 ins. diam., bears N. 44 3/4° E., 160 lks. dist., mkd. T21N R29E S6 BT.</p> <p>A juniper, 8 ins. diam., bears S. 86 1/2° E., 49 lks. dist., mkd. X at breast height and BT at the base.</p> <p>A juniper, 6 ins. diam., bears N. 59° W., 20 lks. dist., mkd. X at breast height and BT at the base.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Bury the original stone beneath the stainless steel post.</p>	T21N		R28E	R29E	S1	S6	—		S12	S7	1987	
T21N													
R28E	R29E												
S1	S6												
—													
S12	S7												
1987													

BOOK 5434

Dependent Resurvey of the 7th Aux. Guide Mer. E. (W. Bdy.),
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a steel fence post near the cor.</p> <p>The cor. is located approximately 50 lks. E. of a small garbage dump and on a narrow spur sloping ESE.</p> <hr/> <p>N. 0°01' E., bet. secs. 1 and 6.</p> <p>Ascend.</p>
4.40	<p>Graded road, 30 lks. wide, bears E. and W., located on main ridge; descend over broken, eroded terrain, along an ancient fence line.</p>
27.10	<p>Track road, 15 lks. wide, bears E. and WSW.</p>
35.75	<p>Point selected for the witness cor. to the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div data-bbox="850 1003 1029 1192" style="text-align: center;"> <pre> WC T21N 1/4 R28E ↑ R29E S1 S6 1992 </pre> </div>
	<p>from which</p> <p>A pinyon, 9 ins. diam., bears N. 61 1/2° E., 102.5 lks. dist., mkd. X at breast height and BT at base.</p> <p>A juniper, 9 ins. diam., bears S. 32 3/4° w., 279.5 chs. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post near the cor.</p>
	<p>The witness cor. is located on a low ridge, bears ENE. and WSW.</p>
38.70	<p>Enter wash, course E. from N.</p>

BOOK 5434

Dependent Resurvey of the 7th Aux. Guide Mer. E. (W. Bdy.),
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS															
39.75	True point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the original cor. The true point falls in a wash where it is impractical to establish a permanent monument.														
44.80	Leave wash, course S. from W.; ascend.														
53.70	Ridge, bears NE. and W.														
79.50	Point for the cor. of Tps. 21 and 22 N., Rs. 28 and 29 E., at single proportionate dist.; there is no remaining evidence of the original cor.														
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.														
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T22N</td> </tr> <tr> <td style="text-align: center;">R28E</td> <td style="text-align: center;">R29E</td> </tr> <tr> <td style="text-align: center;">S36</td> <td style="text-align: center;">S31</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S1</td> <td style="text-align: center;">S6</td> </tr> <tr> <td colspan="2" style="text-align: center;">T21N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table>	T22N		R28E	R29E	S36	S31	-----		S1	S6	T21N		1991	
T22N															
R28E	R29E														
S36	S31														

S1	S6														
T21N															
1991															
	from which														
	A juniper, 22 ins. diam., bears N. 58 1/2° E., 130.5 lks. dist., mkd. T22N R29E S31 BT.														
	A juniper, 12 ins. diam., bears S. 77 1/2° E., 205 lks. dist., mkd. T21N R29E S6 BT.														
	A juniper, 6 ins. diam., bears S. 38 1/2° W., 144.5 lks. dist., mkd. T21N R28E S1 BT.														
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.														
	Raise a mound of stone, 4 ft. base, 2 ft. high, S. of cor.														
	Set a steel fence post near the cor.														
	From this cor. point, an axle, 1 in. diam., firmly set, projecting 3 ins. above ground, of unknown origin, bears N. 59°11' W., 120 lks. dist.														

BOOK 5434

Dependent Resurvey of the 7th Aux. Guide Mer. E. (W. Bdy.),
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS

From this same cor. point, the cor. of secs. 19, 24, 25, and 30, T. 22 N., Rs. 28 and 29 E., bears N. 0°01'E., 159.00 chs. dist., monumented with a juniper post, 4 ins. square, 45 ins. long, firmly set, projecting 26 ins. above ground, mkd. with 4 grooves on the N., 2 grooves on the S., and IA on the E. faces.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T22N	
R28E	R29E
S24	S19
S25	S30
1992	

from which

A juniper, 7 ins. diam., bears N. 36° E.,
214 lks. dist., mkd. T22N R29E S19 BT.

A juniper, 6 ins. diam., bears S. 47 1/4° E.,
170 lks. dist., mkd. T22N R29E S30 BT.

A juniper, 8 ins. diam., bears S. 4 1/2° W.,
238 lks. dist., mkd. T22N R28E S25 BT.

A juniper, 6 ins. diam., bears N. 60 1/4° W.,
111 1/2 lks. dist., mkd. T22N R28E S24 BT.

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case
beneath the stainless steel post.

Bury the Indian Allotment post alongside the stainless steel
post.

The cor. is located 3 lks. NE. of a cor. of fences bearing N.,
E., and S.

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">Restoring the survey executed by W. R. Fitzgerald, in 1882</p> <hr/> <p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with a brass cap mkd. T21N R29E R30E S12 S7 S13 S18 1993. A steel fence post is set alongside the cor.</p> <p>S. 86°39' W., bet. secs. 12 and 13.</p> <p>Over rolling land.</p>
15.78	<p>Point for a witness point on line bet. secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T21N R29E S12 <hr/>S13 1993</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located on a ridge, bears NNE and SSW.</p>
38.37	<p>Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R29E S12 1/4 — S13 1993</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS									
76.75	<p>The cor. of secs. 11, 12, 13, and 14, monumented with the remnants of a juniper post, 4 ins. square, 30 ins. long, laying loose on the ground, with axe marks on one end, and rotted on the other end.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table data-bbox="867 625 1013 779" style="margin-left: auto; margin-right: auto;"> <tr> <td>T21N</td> <td>R29E</td> </tr> <tr> <td>S11</td> <td>S12</td> </tr> <tr> <td>S14</td> <td>S13</td> </tr> <tr> <td colspan="2" style="text-align: center;">1993</td> </tr> </table> <p>from which</p> <p style="padding-left: 40px;">A juniper, 13 ins. diam., bears N. 42 1/4° E., 116 lks. dist., mkd. T21NR29ES12BT.</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears S. 55 1/2° E., 131 lks. dist., mkd. T21NR28ES13BT.</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears S. 9 1/4° W., 206 lks. dist., mkd. T21NR29ES14BT.</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N. 65 1/4° W., 175 lks. dist., mkd. T21NR29ES11BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Bury the remnants of the original post alongside the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located in dense juniper, 113 lks. S. of a fence, bears E. and W.</p> <p>From this cor., the cor. of secs. 1, 2, 11, and 12, bears N. 0°10'E., 80.00 chs. dist., monumented with a juniper post, 5 ins. square, firmly set, projecting 15 ins. above ground, with faint marks on the N. face, located at a cor. of ancient fence lines bearing N. and W., and is accepted as the best available evidence of the position of the original cor.</p> <p>At the cor. point</p>	T21N	R29E	S11	S12	S14	S13	1993	
T21N	R29E								
S11	S12								
S14	S13								
1993									

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
23 ins. in the ground, with brass cap mkd.

T21N R29E	
S2	S1

S11	S12
1993	

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case
beneath the stainless steel post.

Bury the Indian Allotment post alongside the stainless steel
post.

Set a steel fence post near the cor.

From the point for the cor. of secs. 22, 23, 26, and 27, at
proportionate dist.; there is no remaining evidence of the
original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
25 ins. in the ground, with brass cap mkd.

T21N R29E	
S22	S23

S27	S26
1993	

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case
beneath the stainless steel post.

Set a steel fence post near the cor.

The cor. is located on a spur, bears NE. and SW.

From this cor., the cor. of secs. 19, 24, 25, and 30, on the E.
bdy. of the Tp., bears N. 89°51' E., 156.58 chs. dist.,
monumented with a stainless steel post, 2 1/2 ins. diam., firmly
set, projecting 4 ins. above the ground, with a brass cap mkd.
T21N R29E R30E S24 S19 S25 S30 1993.

From this same cor., the stan. cor. of secs. 34 and 35, on the S.
bdy. of the Tp., bears S. 0°04' E., 156.04 chs. dist.,
hereinbefore described.

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>From this same cor., an aluminum pipe, 2 ins. diam., firmly set in concrete, projecting 13 ins. above the ground, and in a mound of stone, 24 ins. diam., with an aluminum cap mkd. T21N R29E 22 23 27 26 LS8906 1986, established by Keith Shreeve, R.L.S. NO. 8906, in 1986, bears N. 46°12' W., 4.75 chs. dist., established using incorrect control, and is not utilized in the course of this resurvey.</p> <p>N. 2°50' W., bet. secs. 22 and 23.</p> <p>Over rolling land.</p> <p>39.06 Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor., falls on the w. slope of a tailing pile, in a heavily eroded area, where it is impractical to establish a permanent monument.</p> <p>From this cor. point, the point selected for a witness cor. bears N. 69°40' W., 1.785 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC T21N R29E 1/4 S22 S23 1993</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
78.12	<p>The cor. of secs. 14, 15, 22, and 23, monumented with a juniper post, 4 ins. square, 46 ins. long, laying loose on the ground, mkd. T21N on a face, 9 on another face, with other illegible marks on all 4 faces.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T21N R29E S15 S14 ----- S22 S23 1993</p> </div>

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A juniper, 6 ins. diam., bears N. 21 3/4° E., 167 lks. dist., mkd. T21NR29ES14BT.</p> <p>A juniper, 48 ins. diam., bears S. 73° E., 107 lks. dist., mkd. T21NR29ES23BT.</p> <p>A juniper, 5 ins. diam., bears S. 30 1/4° E., 112 lks. dist., mkd. T21NR29ES22BT.</p> <p>A juniper, 7 ins. diam., bears N. 67° E., 145 lks. dist., mkd. T21NR29ES15BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Bury the original post alongside the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located 28 lks. W. of a track road, bears NE. and SW.</p> <p>From this cor., an aluminum pipe, 2 ins. diam., firmly set in concrete, projecting 5 ins. above the ground, with an aluminum cap mkd. T21N R29E 15 14 22 23 LS8906 1986, established by Keith Shreeve, R.L.S. NO. 8906, in 1986, bears N. 19°50' W., 6.61 chs. dist., established using incorrect control, and is not utilized in the course of this resurvey.</p>
39.90	<p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>N. 89°59' W., bet. secs. 11 and 14.</p> <p>Over rolling land, through dense juniper.</p> <p>The 1/4 sec. cor. of secs. 11 and 14, monumented with a juniper post, 42 ins. long, 2 ins. diam., laying loose on the ground, axed flat on one side.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T21N R29E S11 1/4 — S14 1993</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Bury the original post alongside the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located 1 ch. S. of a fence, bears E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°14' W., beginning new measurement.</p>
12.16	<p>Point for a witness point on line bet. secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T21N R29E S11 ——— S14 1993</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located on a ridge, bears NNE and SSW.</p>
21.45	<p>Point for a witness point on line bet. secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T21N R29E S11 ——— S14 1993</p>

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS																					
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located on a ridge, bears NE. and SW.</p>																				
39.98	<p>The cor. of secs. 10, 11, 14, and 15, monumented with a rotted juniper post, 22 ins. long, 5 ins. square, laying loose on the ground, axed on one end, and rotted on the other end.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table data-bbox="868 814 1015 966" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T21N R29E</td></tr> <tr><td>S10</td><td>S11</td></tr> <tr><td colspan="2">— —</td></tr> <tr><td>S15</td><td>S14</td></tr> <tr><td colspan="2">1993</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post</p> <p>Bury the original post alongside the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located 1 lk. N. of a fence, bears E. and W.</p> <p>From this cor., the cor. of secs. 2, 3, 10, and 11, bears North, 79.51 chs. dist., monumented with a juniper post, 4 ins. square, firmly set, projecting 17 ins. above ground, faintly mkd. IA on a face, and is accepted as the best available evidence of the position of the original cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table data-bbox="852 1638 998 1789" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T21N R29E</td></tr> <tr><td>S3</td><td>S2</td></tr> <tr><td colspan="2">— —</td></tr> <tr><td>S10</td><td>S11</td></tr> <tr><td colspan="2">1993</td></tr> </table>	T21N R29E		S10	S11	— —		S15	S14	1993		T21N R29E		S3	S2	— —		S10	S11	1993	
T21N R29E																					
S10	S11																				
— —																					
S15	S14																				
1993																					
T21N R29E																					
S3	S2																				
— —																					
S10	S11																				
1993																					

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A juniper, 7 ins. diam., bears N. 35 1/4° E., 124 lks. dist., mkd. T21NR29ES2BT.</p> <p>A juniper, 14 ins. diam., bears N. 71 1/4° W., 45 lks. dist., mkd. T21NR29ES3BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Bury the Indian Allotment post, 46 ins. long, alongside the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this same cor., the cor. of secs. 14, 15, 22, and 23, bears S. 1°36' W., 77.93 chs. dist.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>N. 89°09' W., bet. secs. 22 and 27.</p> <p>Over rolling land, through scattered juniper.</p> <p>19.68 Point for the E. 1/16 sec. cor. of secs. 23 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R29E S22 E 1/16 — S27 1993</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this cor., an aluminum pipe, 2 ins. diam., firmly set in concrete, projecting 9 ins. above the ground, with an aluminum cap mkd. T21N R29E E1/16 S22 S27 LS8906 1986, established by Keith Shreeve, R.L.S. NO. 8906, in 1986, bears N. 48°17' W., 5.04 chs. dist., established using incorrect control, and is not utilized in the course of this resurvey.</p>

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
25.80	Wash, 15 lks. wide, 4 ft. deep, course NW.
27.10	Track road, 12 lks. wide, bears SE. and NW.
39.36	Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T21N R29E S22 1/4 — S27 1993</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
	From this cor., an aluminum pipe, 2 ins. diam., firmly set in concrete, projecting 14 ins. above the ground, with an aluminum cap mkd. T21N R29E 1/4 S22 S27 LS8906 1986, established by Keith Shreeve, R.L.S. NO. 8906, in 1986, bears N. 50°07' W., 5.32 chs. dist., established using incorrect control, and is not utilized in the course of this resurvey.
78.72	Point for the cor. of secs. 21, 22, 27, and 28, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T21N R29E S21 S22 — — S28 S27 1993</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
	From this cor., the stan. cor. of secs. 33 and 34, on the S. bdy. of the Tp., bears S. 0°15' E., 155.38 chs. dist., hereinbefore described.

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS

From this same cor., the cor. of secs. 20, 21, 28, and 29, bears S. $84^{\circ}35'$ W., 78.83 chs. dist., monumented with a juniper post, 4 ins. square, firmly set, projecting 30 ins. above ground, mkd. IA on the N., 4 grooves on the E., and 2 grooves on the S. faces, and is accepted as the best available evidence of the position of the original cor.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T21N	R29E
S20	S21
S29	S28
1993	

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Bury the Indian Allotment post alongside the stainless steel post.

The cor. is located in a fence, bears N. and S.

From this same cor., an aluminum pipe, 2 ins. diam., firmly set in concrete, projecting 7 ins. above the ground, with an aluminum cap mkd. T21N R29E 21 22 28 27 LS8906 1986, established by Keith Shreeve, R.L.S. NO. 8906, in 1986, bears N. $53^{\circ}11'$ W., 5.90 chs. dist., established using incorrect control, and is not utilized in the course of this resurvey.

N. $3^{\circ}06'$ W., bet. secs. 21 and 22.

Over nearly level land.

38.90

Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

T21N	R29E
1/4	
S21	S22
1993	

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS											
	Set a steel fence post near the cor.										
	From this cor., an aluminum pipe, 2 ins. diam., firmly set in concrete, with an aluminum cap mkd. T21N R29E 1/4 S21 S22 LS8906 1986, established by Keith Shreeve, R.L.S. NO. 8906, in 1986, bears N. 29°36' W., 5.38 chs. dist., established using incorrect control, and is not utilized in the course of this resurvey.										
77.80	The cor. of secs. 15, 16, 21, and 22, monumented with an imbedded mound of decayed stones, 24 ins. diam., 10 ins. high.										
	At the cor. point										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T21N R29E</td> </tr> <tr> <td style="text-align: center;">S16</td> <td style="text-align: center;">S15</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S21</td> <td style="text-align: center;">S22</td> </tr> <tr> <td colspan="2" style="text-align: center;">1993</td> </tr> </table>	T21N R29E		S16	S15	-----		S21	S22	1993	
T21N R29E											
S16	S15										

S21	S22										
1993											
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.										
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.										
	Set a steel fence post near the cor.										
	The cor. is located 50 lks. N. of a wash, 18 lks. wide, 5 ft. deep, course WSW, 70 lks. S. of a wash, 18 lks. wide, 2 ft. deep, course SSE, and 50 lks. W. of a wash, 18 lks. wide, 5 ft. deep, course SW.										
	From this cor., an aluminum pipe, 2 ins. diam., firmly set in concrete, projecting 7 ins. above the ground, with an aluminum cap mkd. T21N R29E 16 15 21 22 LS8906 1986, established by Keith Shreeve, R.L.S. NO. 8906, in 1986, with a rebar alongside, 1/2 in. diam., projecting 12 ins. above the ground, with a tag mkd. 7141, established by Gordon W. McLain, R.L.S. NO. 7141, in 1983, and with a wood post alongside, 3 ins. square, projecting 30 ins. above the ground, with the top sawn flat, of unknown origin, bears N. 7°08' W., 7.43 chs. dist. The aluminum pipe and rebar were set to perpetuate the position of the wood post, which is not similar in character to original or Indian Allotment monuments, and does not relate harmoniously to accepted cor. positions. Therefore this position was established using incorrect control, and is not utilized in the course of this resurvey.										

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>From this same cor., a galvanized iron pipe, 1 in. diam., firmly set, with a cap, 2 ins. diam., mkd. T21N R29E S16 S15 S21 S22 1982 PE 2678, established by Harvey W. Smith, R.L.S. NO. 16198, in 1982, bears N. 85°11' E., 4.21 chs. dist., established using incorrect control and is not utilized in the course of this resurvey.</p>
	<p>From the cor. of secs. 14, 15, 22, and 23.</p>
	<p>N. 89°23' W., bet. secs. 15 and 22.</p>
	<p>Over rolling land, through dense juniper.</p>
19.40	<p>Track road, bears N. and S.</p>
19.76	<p>Point for the E. 1/16 sec. cor. of secs. 15 and 22.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T21N R29E</p>
	<p style="text-align: center;">S15</p>
	<p style="text-align: center;">E 1/16 —</p>
	<p style="text-align: center;">S22</p>
	<p style="text-align: center;">1993</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post near the cor.</p>
	<p>From this cor., an aluminum pipe, 2 ins. diam., firmly set in concrete, projecting 7 ins. above the ground, with an aluminum cap mkd. T21N R29E E1/16 S15 S22 LS8906 1986, established by Keith Shreeve, R.L.S. NO. 8906, in 1986, bears N. 12°35' E., 6.68 chs. dist., established using incorrect control, and is not utilized in the course of this resurvey.</p>
22.10	<p>Spur, bears N. and S.</p>
25.00	<p>Wash, 15 lks. wide, 5 ft. deep, course SE.</p>
28.50	<p>Spur, bears N. and S.</p>
39.52	<p>Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate dist.; there is no remaining evidence of the original cor.</p>

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R29E S15 1/4 — S22 1993</p> <p>from which</p> <p style="text-align: center;">A juniper, 5 ins. diam., bears S. 50 3/4° E., 144 lks. dist., mkd. 1/4S22BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>From this cor., an aluminum pipe, 2 ins. diam., firmly set in concrete, projecting 6 ins. above the ground, with an aluminum cap mkd. T21N R29E S15 S22 1/4 LS8906 1986, established by Keith Shreeve, R.L.S. NO. 8906, in 1986, bears N. 5°36' E., 6.84 chs. dist., established using incorrect control, and is not utilized in the course of this resurvey.</p>
39.70	Track road, bears NNE. and SSW.
79.04	The cor. of secs. 15, 16, 21, and 22.
	<hr/> <p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>S. 89°14' W., bet. secs. 10 and 15.</p> <p>Over rolling land, through moderate juniper, along a fence.</p>
34.30	Spur, bears N. and S.
40.07	<p>The 1/4 sec. cor. of secs. 10 and 15, monumented with a juniper post, 4 ins. square, firmly set, projecting 19 ins. above the ground, mkd. 1/4 on the N. face, and is accepted as the best available evidence of the position of the original cor.</p> <p>At the cor. point</p>

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T21N R29E S10 1/4 — S15 1993</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Bury the Indian Allotment post, 42 ins. long, alongside the stainless steel post.
	Set a steel fence post near the cor.
	The cor. is located 15 lks. SSE. of a cor. of fences bearing E., S., and W.
	<p style="text-align: center;">—————</p> S. 89°37' W., beginning new measurement.
7.50	Spur, bears NE. and SW.
25.70	Point for a witness point on line bet. secs. 10 and 15.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">WP T21N R29E S10 ————— S15 1993</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
	The cor. is located on a ridge, bears NE. and SW.
40.46	The cor. of secs. 9, 10, 15, and 16, monumented with a juniper post, 4 ins. square, 30 ins. long, laying loose on the ground, mkd. IA on a face, 3 grooves on another face, and 4 grooves on another face, and is accepted as the best available evidence of the position of the original cor.

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T21N R29E	
S9	S10

S16	S15
1993	

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case
beneath the stainless steel post.

Bury the Indian Allotment post alongside the stainless steel
post.

Set a steel fence post near the cor.

The cor. is located on a low spur, bears ESE. and WNW., 50 lks.
S. of a dirt road, 15 lks. wide, bears E. and W., and 100 lks. S.
of a fence, bears E. and W.

From this cor., a rebar, 1/2 in. diam., projecting 1 in. above
the ground, in a mound of stone, 24 ins. diam., with a tag mkd.
7141, bears N. 59°36' E., 2.40 chs. dist., established by Gordon
W. McLain, R.L.S. NO. 7141, in 1983, using incorrect control, and
is not utilized in the course of this resurvey.

From this same cor., a galvanized iron pipe, 1 in. diam., firmly
set, projecting 13 ins. above the ground, with a cap mkd. T21N
R29E S9 S10 S16 S15 1982 PE 2678, bears N. 31°14' E., 1.86 chs.
dist., established by Harvey W. Smith, R.L.S. NO. 16198, in 1982,
using incorrect control and is not utilized in the course of this
resurvey.

From this same cor., the 1/4 sec. cor. of secs. 9 and 10, bears
N. 0°39' E., 40.34 chs. dist., monumented with a juniper post,
4 x 5 ins. square, firmly set, projecting 30 ins. above ground,
mkd. IA on the S. face, and is accepted as the best available
evidence of the position of the original cor.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
26 ins. in the ground, with brass cap mkd.

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS

T21N R29E
1/4
S9 | S10
1993

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Bury the Indian Allotment post, 46 ins. long, alongside the stainless steel post.

Set a steel fence post near the cor.

The cor. is located 100 lks. S. of a ridge, bears E. and W.

From this same cor., the cor. of secs. 15, 16, 21, and 22, bears S. 0°31' W., 76.26 chs. dist.

From the cor. of secs. 16, 17, 20, and 21, monumented with a juniper post, 4 ins. square, firmly set, projecting 3 ft. above ground, mkd. IA on the W. face and with 3 grooves on the S. face, with a galvanized iron pipe alongside, 1 in. diam. firmly set, projecting 7 ins. above ground, with brass cap mkd. T21N R29E S17 S16 S20 S21 1982 PE2678. This position has long been locally recognized as the cor. and is accepted as the best available evidence of the position of the cor.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T21N R29E
S17 | S16

S20 | S21
1987

from which

A juniper, 5 ins. diam., bears N. 29 3/4° E.,
239 lks. dist., mkd. T21N R29E S16 BT.

A juniper, 7 ins. diam., bears S. 30 3/4° E.,
305 lks. dist., mkd. T21N R29E S21 BT.

A juniper, 8 ins. diam., bears N. 26 3/4° W.,
92 1/2 lks. dist., mkd. T21N R29E S17 BT.

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Deposit the Indian Allotment post, 57 ins. long, and the iron pipe, 30 ins. long, alongside the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located 8 lks. E. of a barbed wire fence, bears N. and S. N. 0°09' W., bet. secs. 16 and 17.</p> <p>Over rolling land.</p>
20.21	<p>Point for the S. 1/16 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R29E S 1/16 S17 S16 1987</p>
40.42	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located 8 lks. E. of a barbed wire fence, bears N. and S.</p> <p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R29E 1/4 S17 S16 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located 7 lks. E. of a barbed wire fence, bears N. and S.</p>

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS											
80.84	<p>From this cor., an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T21N R29E 1/4 S17 S16 1987 PE 2678, bears N. 89°45' W., 159 lks. dist., established by Harvey W. Smith, R.L.S. NO. 16198, in 1982, using incorrect control and is not utilized in the course of this resurvey.</p> <p>The cor. of secs. 8, 9, 16, and 17, monumented with a wood post, 3 ins. square, firmly set, projecting 11 ins. above the ground, with illegible marks on the S. face, located at a cor. of ancient fence lines bearing N., S., and W. This position has long been locally recognized as the cor. and is accepted as the best available evidence of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <table data-bbox="852 877 998 1033" style="margin-left: auto; margin-right: auto;"> <tr> <td>T21N</td> <td>R29E</td> </tr> <tr> <td>S8</td> <td>S9</td> </tr> <tr> <td colspan="2" style="text-align: center;"> </td> </tr> <tr> <td>S17</td> <td>S16</td> </tr> <tr> <td colspan="2" style="text-align: center;">1987</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Deposit the Indian Allotment post, 43 ins. long, alongside the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located 25 lks. S. of a wash, 20 lks. wide, course WNW., and 191 lks. N. of a cor. of fences bearing NE., S., and W.</p> <p>From this cor., an iron pipe, 1 in. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. T21N R29E S8 S9 S16 S17 1982 PE2678, bears S. 87°18' W., 3.15 chs. dist., established by Harvey W. Smith, R.L.S. NO. 16198, in 1982, using incorrect control and is not utilized in the course of this resurvey.</p> <p>From this same cor., the cor. of secs. 4, 5, 8 and 9, bears N. 3°19' W., 81.02 chs. dist., monumented with a wood post, 5 ins. square, firmly set, projecting 22 ins. above the ground, with IA on the N. face, 5 grooves on the S. face and 4 grooves on the E. face. This position has long been locally recognized as the cor. and is accepted as the best available evidence of the position of the cor.</p> <p>At the cor. point</p>	T21N	R29E	S8	S9			S17	S16	1987	
T21N	R29E										
S8	S9										
S17	S16										
1987											

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS																			
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T21N</td> <td>R29E</td> </tr> <tr> <td>S5</td> <td>S4</td> </tr> <tr> <td>S8</td> <td>S9</td> </tr> <tr> <td colspan="2">1993</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Deposit the Indian Allotment post, 32 ins. long, alongside the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located 2 lks. W. of a cor. of fences bearing E., S., and W.</p> <hr/> <p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>S. 89°40' W., bet. secs. 9 and 16.</p> <p>Over rolling land.</p> <p>3.10 Spur, bears NE. and SW.</p> <p>38.20 Spur, bears NE. and SW.</p> <p>37.49 Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T21N</td> <td>R29E</td> </tr> <tr> <td colspan="2">S9</td> </tr> <tr> <td colspan="2">1/4 —</td> </tr> <tr> <td colspan="2">S16</td> </tr> <tr> <td colspan="2">1993</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located 115 lks. ESE. of a cor. of fences bearing ENE., E., and W., and 165 lks. SW. of a cor. of fences bearing E., WSW., and W.</p>	T21N	R29E	S5	S4	S8	S9	1993		T21N	R29E	S9		1/4 —		S16		1993	
T21N	R29E																		
S5	S4																		
S8	S9																		
1993																			
T21N	R29E																		
S9																			
1/4 —																			
S16																			
1993																			

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
74.98	<p>From this cor., an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. T21N R29E 1/4 S9 S16 1982 PE2678, bears N. 53°37' W., 1.35 chs. dist., established by Harvey W. Smith, R.L.S. NO. 16198, in 1982, using incorrect control and is not utilized in the course of this resurvey.</p> <p>The cor. of secs. 8, 9, 16, and 17.</p>
20.065	<p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>N. 89°57' W., bet. secs. 17 and 20.</p> <p>Over rolling land, through scattered juniper.</p> <p>Point for the E. 1/16 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R29E S17 E 1/16 — S20 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p>
40.13	<p>The 1/4 sec. cor. of secs. 17 and 20, monumented with a wood post, 4 ins. square, firmly set, projecting 3 ft. above the ground, mkd. 1/4 on the N. face and IA on the S. face. This position has long been locally recognized as the cor. and is accepted as the best available evidence of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R29E S17 1/4 — S20 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Deposit the Indian Allotment post, 58 ins. long, alongside the stainless steel post.</p>
	<p>Set a steel fence post near the cor.</p>
	<p>The cor. is located 321 lks. N. of a bladed dirt road, 40 lks. wide, bears ESE and WNW.</p>
	<hr/>
	<p>N. 89°59' W., beginning new measurement.</p>
	<p>Over rolling land, through scattered juniper.</p>
7.15	<p>Graded dirt road, 40 lks. wide, bears WNW and ESE.</p>
20.005	<p>Point for the W. 1/16 sec. cor. of secs. 17 and 20.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T21N R29E S17 W 1/16 — S20 1987</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post near the cor.</p>
40.01	<p>The cor. of secs. 17, 18, 19, and 20, monumented with a steel rebar, 3/4 in. diam., firmly set, projecting 3 ins. above the ground, of unknown origin, located at a cor. of barbed wire fences bearing N. and W. This position is harmoniously related to existing cors., has long been locally recognized, and is accepted as a careful and faithful determination of the position of the cor.</p>
	<p>At the cor. point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T21N R29E S18 S17 — — S19 S20 1987</p>

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
40.14	<p>from which</p> <p>A juniper, 12 ins. diam., bears N. 89 1/4° E., 85 1/2 lks. dist., mkd. T21N R29E S17 BT.</p> <p>A juniper, 6 ins. diam., bears S. 53 1/4° W., 134 1/2 lks. dist., mkd. T21N R29E S19 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Deposit the local rebar, 48 ins. long, alongside the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>S. 89°39' W., bet. secs. 18 and 19.</p> <p>Over rolling land, through scattered juniper, along a fence.</p> <p>The 1/4 sec. cor. of secs. 18 and 19, monumented with a stone, 10 x 3 x 4 ins. above the ground, firmly set, mkd. IA on the S. face, located at a cor. of barbed wire fences bearing N., E., and W. This position has long been locally recognized as the cor. and is accepted as the best available evidence of the position of the cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R29E S18 1/4 — S19 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Deposit the Indian Allotment stone alongside the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <hr/> <p>S. 89°41' W., beginning new measurement.</p> <p>Over rolling land, along a fence.</p>

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
40.25	<p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 17, 18, 19, and 20. North, bet. secs. 17 and 18. Over rolling land, through scattered juniper, along a fence.</p>
4.995	<p>Point for the S-S-S 1/256 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S-S-S 1/256 S18 S17 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located 3 lks. E. of a barbed wire fence, bears N. and S.</p>
10.20	<p>Graded dirt road, 40 lks. wide, bears E. and W.</p>
14.985	<p>Point for the N-S-S 1/256 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N-S-S 1/256 S18 S17 1987</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>Cor. is located 2 lks. E. of a barbed wire fence, bears N. and S.</p>
19.98	<p>Point for the S. 1/16 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T21N R29E S 1/16 S18 S17 1987</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post near the cor.</p>
	<p>Cor. is located 3 lks. E. of a barbed wire fence, bears N. and S.</p>
29.40	<p>Graded dirt road, 40 lks. wide, bears NE and SW.</p>
39.96	<p>The 1/4 sec. cor. of secs. 17 and 18, monumented with a sandstone, 9 x 5 x 4 ins. above ground, firmly set, mkd. A on the W. face, located in a cor. of barbed wire fences bearing N., S., and W. This position has long been locally recognized as the cor. and is accepted as the best available evidence of the position of the cor.</p>
	<p>At the cor. point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T21N R29E 1/4 S18 S17 1987</p>
	<p>from which</p>
	<p style="text-align: center;">A juniper, 8 ins. diam., bears N. 27 3/4° E., 60 lks. dist., mkd. 1/4 S17 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
	<p>Deposit the Indian Allotment stone alongside the stainless steel post.</p>
	<p>Set a steel fence post near the cor.</p>
	<hr style="width: 30%; margin: 0 auto;"/>

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS											
	N. 0°01' E., beginning new measurement.										
	Over rolling land, along a fence.										
40.06	The cor. of secs. 7, 8, 17, and 18, at a cor. of barbed wire fences bearing N., S., E., and W. This position is harmoniously related to other cors., has long been locally recognized as the cor. and is accepted as the best available evidence of the position of the cor.										
	At the cor. point										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T21N R29E</td> </tr> <tr> <td style="text-align: center;">S7</td> <td style="text-align: center;">S8</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S18</td> <td style="text-align: center;">S17</td> </tr> <tr> <td colspan="2" style="text-align: center;">1987</td> </tr> </table>	T21N R29E		S7	S8	-----		S18	S17	1987	
T21N R29E											
S7	S8										

S18	S17										
1987											
	from which										
	A juniper, 5 ins. diam., bears N. 51 1/2° E., 358 lks. dist., mkd. X BT.										
	A juniper, 6 ins. diam., bears S. 43 1/2° W., 128 lks. dist., mkd. T21N R29E S18 BT.										
	A juniper, 8 ins. diam., bears N. 56° W., 240 lks. dist., mkd. T21N R29E S7 BT.										
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.										
	Set a steel fence post near the cor.										
	From the cor. of secs. 8, 9, 16, and 17.										
	S. 89°27' W., bet. secs. 8 and 17.										
	Over rolling land, through scattered juniper.										
38.80	Graded dirt road, 40 lks. wide, bears NNE and SSW.										
39.965	Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the original cor.										

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T21N R29E S8 1/4 — S17 1987</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post near the cor.</p>
	<p>From this cor., a cor. of fences bearing N., E., and W., bears S. 59 1/2° E., 31 lks. dist. .</p>
79.93	<p>The cor. of secs. 7, 8, 17, and 18.</p> <hr/>
	<p>S. 89°39' W., bet. secs. 7 and 18.</p>
	<p>Over nearly level land, along a fence.</p>
40.14	<p>The 1/4 sec. cor. of secs. 7 and 18, at a cor. of old fences bearing N., E., and W., located 10 lks. W. of an old fence, bears S., and 9 lks. E. of a line of ancient fence posts, bears S. This is accepted as the best available evidence of the position of the original cor.</p>
	<p>At the cor. point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T21N R29E S7 1/4 — S18 1993</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>From this cor., a juniper post, 3 x 4 ins. square, firmly set, projecting 11 ins. above the ground, mkd. IA 1/ on the E. face, located in a fence, bears E. and W., 9 lks. W. of a fence, bears N. and S., and 7 lks. E. of an old fence, bears N. and S., bears South, 20.07 chs. dist., not remonumented.</p>

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>From this same cor., a sandstone, 11 x 4 x 9 ins. above the ground, firmly set, mkd. IA on the E. face, with illegible marks on the W. face, located at a cor. of old fences bearing E. and S., 9 lks. W. of an old fence, bears N., and 8 lks. E. of a line of ancient fence posts, bears N., bears South, 40.03 chs. dist., not remonumented.</p> <hr/>
40.54	<p>N. 89°14' W., beginning new measurement.</p> <p>True point for the cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/>
36.90	<p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0°17' E., bet. secs. 7 and 8.</p> <p>Over nearly level land, along a fence.</p> <p>Left bank of the Puerco River, bears E. and W.</p>
40.48	<p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor., falls in the bed of the Puerco River, where it is impractical to establish a permanent monument.</p> <p>From this cor. point, the point selected for a witness cor. bears S. 3°11' W., 4.11 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC T21N R29E 1/4 S7 S8 ↗ 1993</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The witness cor. is located 15 lks. W. of a fence, bears N. and S., and 50 lks. S. of the left bank of the Puerco River, bears E. and W.</p>

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
58.90	Right bank of the Puerco River, bears ENE. and WSW., enter A.T.& S.F. Railroad right-of-way.
60.72	Point for the N. 1/16 sec. cor. of secs. 7 and 8, falls on the southwesterly railroad track, where it is impractical to establish a permanent monument.
61.85	Fence, bears ENE. and WSW.
61.96	Point selected for the witness cor. to the N. 1/16 sec. cor. of secs. 7 and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">WC T21N R29E N 1/16 S7 ↓ S8 1993</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
62.61	Point for a witness point at intersection with the northwesterly A.T.& S.F. Railroad right-of-way line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">WP T21N R29E S7 S8 / ROW 1993</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
	The cor. is located on the NW. side of a drainage ditch, 50 lks. wide, 10 ft. deep, bears ENE. and WSW., and 2 lks. W. of an ancient fence line, bears N. and S.

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS

80.96

The cor. of secs. 5, 6, 7, and 8, at a cor. of ancient fence lines bearing N., S., and W. This is accepted as the best available evidence of the position of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a steel fence post driven into the ground, with brass cap mkd.

T21N R29E	
S6	S5

S7	S8
1993	

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Set a steel fence post near the cor.

From this cor., the 1/4 sec. cor. of secs. 5 and 6, bears N. 0°41' W., 39.31 chs. dist., monumented with a juniper post, 4 ins. square, firmly set, projecting 28 ins. above the ground, mkd. IA on the E., and 1/4 on the W. faces, and is accepted as the best available evidence of the position of the original cor.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T21N R29E	
1/4	
S6	S5
1993	

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Bury the Indian Allotment post, 42 ins. long, alongside the stainless steel post.

Set a steel fence post near the cor.

From this same cor., the cor. of secs. 4, 5, 8, and 9, bears N. 89°28' E., 74.81 chs. dist.

BOOK 5434

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
	N. 89°19' W., bet. secs. 6 and 7.
	Over nearly level land.
11.455	Intersect the southeasterly right-of-way line of U.S. Interstate Highway 40, identical with angle point 5, hereinafter described.
13.90	Center line of the Cedar Point on-ramp to eastbound U.S. Interstate Highway 40, pavement, 40 lks. wide, bears NE. and SW.
14.80	Fence, bears NE. and SW.
16.55	Center line of eastbound U.S. Interstate Highway 40, pavement, 60 lks. wide, bears NE. and SW.
19.00	Center line of westbound U.S. Interstate Highway 40, pavement, 60 lks. wide, bears NE. and SW.
20.485	Point for the E. 1/16 sec. cor. of secs. 6 and 7, falls on the pavement of the Cedar Point off-ramp to westbound U.S. Interstate Highway 40, where it is impractical to establish a permanent monument.
	From this cor. point, the point selected for a witness cor. bears N. 88°28' W., 4.25 chs. dist.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> WC T21N R29E S6 E 1/16 ——— S7 ↘ 1993 </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
20.65	Center line of the Cedar Point off-ramp to westbound U.S. Interstate Highway 40, pavement, 30 lks. wide, bears ENE. and WSW.
22.05	Fence, bears NE. and SW.
23.00	Center line of a frontage road, pavement, 40 lks. wide, bears ENE. and WSW.

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 21 N., R. 29 E., Gila and Salt River Mer., Arizona

CHAINS	
24.70	A cor. of fences bearing ENE., WSW, and W.; ascend over rolling land, through moderate juniper.
40.20	Track road, 15 lks. wide, bears NNE. and S.
40.97	Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T21N R29E S6 1/4 — S7 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
42.00	Wash, 30 lks. wide, 6 ft. deep, course SSE.
81.35	The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., hereinbefore described.
<hr/> Subdivision of Section 7, T. 21 N., R. 29 E., Gila and Salt River Meridian, Arizona <hr/>	
	From the 1/4 cor. sec. cor. of secs. 7 and 18.
	N. 0°18' W., on the N. and S. center line of sec. 7.
	Over nearly level land, along a fence.
21.60	Left bank of the Puerco River, bears NE. and SW.
34.15	Fence on the right bank of the Puerco River, bears NE. and SW.
34.60	A.T.& S.F. Railroad track, bears NE. and SW.
34.85	A.T.& S.F. Railroad track, bears NE. and SW.
35.40	Access road, gravel, 20 lks. wide, bears ENE. and WSW.
35.95	Fence, bears NE. and SW.


BOOK 5434

Subdivision of Section 7, T. 21 N., R. 29 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
36.25	Power pole line, bears ENE. and WSW.; ascend through scattered Juniper.
41.04	Point for the center 1/4 sec. cor. of sec. 7, at intersection with the E. and W. center line of sec. 7.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T21N R29E C1/4 S7 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
48.09	From this point, a rebar, 3/4 in. diam., projecting 2 ins. above the ground, of unknown origin, bears West, 89 lks. dist.
55.10	Southeasterly right-of-way fence of U.S. Interstate Highway 40, bears NE. and SW.
56.15	Frontage road, paved, 30 lks. wide, bears NE. and SW.
56.70	Fence, bears NE. and SW.
58.20	Eastbound U.S. Interstate Highway 40, pavement, 60 lks. wide, bears NE. and SW.
60.75	Westbound U.S. Interstate Highway 40, pavement, 60 lks. wide, bears NE. and SW.
61.36	Point for the center N. 1/16 sec. cor. of sec. 7.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. below the ground, with brass cap mkd.
	T21N R29E C N1/16 S7 C 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	The cor. is located 17 lks. N. of the northwesterly edge of the pavement of the Cedar Point on-ramp to westbound U.S. Interstate Highway 40.

BOOK 5434

Subdivision of Section 7, T. 21 N., R. 29 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
62.30	Fence, bears NE. and SW.
63.00	Frontage road, paved, 40 lks. wide, bears NE. and SW.
79.28	From this point, a rebar, 3/4 in. diam., of unknown origin, bears East, 22 lks. dist.; descend.
81.68	The 1/4 sec. cor. of secs. 6 and 7.
<hr/>	
From the true point for the 1/4 sec. cor. of secs. 7 and 8.	
N. 89°33' W., on the E. and W. center line of sec. 7.	
Across the bed of the Puerco River.	
20.28	Point for the center E. 1/16 sec. cor. of sec. 7, falls in the bed of the Puerco River, where it is impractical to establish a permanent monument.
From this cor. point, the point selected for the witness cor. bears S. 2°00' E., 4.175 chs. dist.	
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.	
<div style="text-align: center;">  <p>WC T21N R29E E1/16 C — C S7 1993</p> </div>	
Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.	
Set a steel fence post near the cor.	
The cor. is located 25 lks. S. of the left bank of the Puerco River, bears E. and W.	
28.30	Right bank of the Puerco River.
29.35	Fence, bears ENE. and WSW.
30.05	A.T. & S.F. Railroad track, bears NE. and SW.
30.45	A.T. & S.F. Railroad track, bears NE. and SW.
31.25	Access road, gravel, 20 lks. wide, bears ENE. and WSW.

BOOK 5434

Subdivision of Section 7, T. 21 N., R. 29 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
32.50	Power line, bears ENE. and WSW.; ascend through scattered juniper.
32.75	Fence, bears ENE. and WSW.
35.00	Wash, 40 lks. wide, 6 ft. deep, course SW.; ascend through scattered juniper.
37.40	Spur, bears N. and S.
40.56	The center 1/4 sec. cor. of sec. 7.
51.30	Spur, bears N. and S.
54.60	Fence, bears NE. and SW.
57.90	Eastbound U.S. Interstate Highway 40, pavement, 60 lks. wide, bears NE. and SW.
60.45	Westbound U.S. Interstate Highway 40, pavement, 60 lks. wide, bears NE. and SW.
61.40	Fence, bears NE. and SW.
61.85	Frontage road, pavement, 40 lks. wide, bears NE. and SW.
62.55	Fence, bears NE. and SW.
63.15	Power line, bears NE. and SW.
71.30	Power line, bears NE. and SW.
77.00	Wash, 35 lks. wide, 6 ft. deep, course SSE.
81.01	The 1/4 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.
	NE 1/4

	From the true point for the center E. 1/16 sec. cor. of sec. 7.
	North, on the N. and S. center line of the NE. 1/4 of sec. 7.
	Across the bed of the Puerco River.
6.05	Right bank of the Puerco River, bears ENE. and WSW.
6.60	Fence, bears ENE. and WSW.

BOOK 5434

Subdivision of Section 7, T. 21 N., R. 29 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
6.85	A.T.& S.F. Railroad track, bears ENE. and WSW.
7.10	A.T.& S.F. Railroad track, bears ENE. and WSW.
7.60	Access road, gravel, 20 lks. wide, bears ENE. and WSW.
8.50	Power line, bears ENE. and WSW.
8.65	Fence, bears ENE. and WSW.
20.28	Point for the NE. 1/16 sec. cor. of sec. 7, at intersection with the E. and W. center line of the NE. 1/4 of sec. 7.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T21N R29E NE 1/16 S7 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
	From this cor., a cor. of fences bearing N. and E., bears S. 75°28' E., 1.05 chs. dist.
28.55	Track road, 15 lks. wide, bears NNE. and SSW.
29.20	Power line, bears NNE. and SSW.
29.56	Point for angle point 1, at intersection with the southeasterly right-of-way of U.S. Interstate Highway 40, hereinafter described.
40.56	True point for the E. 1/16 sec. cor. of secs. 6 and 7.
	From the true point for the N. 1/16 sec. cor. of secs. 7 and 8.
	N. 89°26' W., on the E. and W. center line of the NE. 1/4 of sec. 7.
0.11	A.T.& S.F. Railroad track, bears ENE. and WSW.
0.50	A.T.& S.F. Railroad track, bears ENE. and WSW.
0.90	Access road, gravel, bears ENE. and WSW.

BOOK 5434

Subdivision of Section 7, T. 21 N., R. 29 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
2.84	<p>Point for a witness point at intersection with the northwesterly A.T.& S.F. Railroad right-of-way line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div data-bbox="865 495 1016 678" style="text-align: center;"> <p>WP T21N R29E S7 N—N ROW 1993</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located on the NW. side of a drainage ditch, 50 lks. wide, 10 ft. deep, bears ENE. and WSW., and 2 lks. S. of a fence, bears E. and W.</p>
3.20	Power line, bears ESE. and WNW.
13.80	<p>Point for a witness point on the E. and W. center line of the NE. 1/4 of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div data-bbox="865 1255 1016 1438" style="text-align: center;"> <p>WP T21N R29E S7 N—N 1993</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located on a low ridge, bears N. and S.</p>
20.38	The NE. 1/16 sec. cor. of sec. 7.
34.15	Fence, bears NE. and SW.
35.15	Frontage road, pavement, 40 lks. wide, bears NE. and SW.

BOOK 5434

Subdivision of Section 7, T. 21 N., R. 29 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
35.70	Fence, bears NE. and SW.
37.10	Eastbound U.S. Interstate Highway 40, pavement, 90 lks. wide, bears NE. and SW.
40.00	Westbound U.S. Interstate Highway 40, pavement, 80 lks. wide, bears NE. and SW.
40.76	The center N. 1/16 sec. cor. of sec. 7.
<hr/> Subdivision of Section 17, T. 21 N., R. 29 E., Gila and Salt River Meridian, Arizona <hr/>	
	From the 1/4 sec. cor. of secs. 17 and 20.
	North, on the N. and S. center line of sec. 17.
10.04	Point for the center S-S 1/64 sec. cor. of sec. 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	$ \begin{array}{c} C \\ S-S \ 1/64 \quad \quad S17 \\ C \\ 1987 \end{array} $
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
15.06	Point for the center N-S-S 1/256 sec. cor. of sec. 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	$ \begin{array}{c} C \\ N-S-S \ 1/256 \quad \quad S17 \\ C \\ 1987 \end{array} $
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
20.08	Point for the center S. 1/16 sec. cor. of sec. 17.

BOOK 5434

Subdivision of Section 17, T. 21 N., R. 29 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T21N R29E C S 1/16 S17 C 1987</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A juniper, 7 ins. diam., bears N. 48 1/2° E., 112 1/2 lks. dist., mkd. CS 1/16 S17 BT.</p>
	<p style="padding-left: 40px;">A juniper, 9 ins. diam., bears N. 72 1/2° W., 277 lks. dist., mkd. X BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post near the cor.</p>
40.16	<p>Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E. and W. center line.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T21N R29E C 1/4 S17 1987</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A juniper, 9 ins. diam., bears S. 72° W., 232 1/2 lks. dist., mkd. X BT.</p>
	<p style="padding-left: 40px;">A juniper, 6 ins. diam., bears N. 8 1/4° W., 80 lks. dist., mkd. C 1/4 S17 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post near the cor.</p>
78.10	<p>Graded dirt road, 40 lks. wide, bears NNE AND SSW.</p>
80.41	<p>The 1/4 sec. cor. of secs. 8 and 17.</p> <hr/>

BOOK 5434

Subdivision of Section 17, T. 21 N., R. 29 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	From the 1/4 sec. cor. of secs. 16 and 17.
	S. 89°41' W., on the E. and W. center line of sec. 17
20.025	Point for the center E. 1/16 sec. cor. of sec. 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T21N R29E
	E 1/16
	C———C
	S17
	1987
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
40.05	The center 1/4 sec. cor. of sec. 17.
60.04	Point for the center W. 1/16 sec. cor. of sec. 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T21N R29E
	W 1/16
	C———C
	S17
	1987
	from which
	A juniper, 6 ins. diam., bears N. 31 3/4° W., 99 lks. dist., mkd. CW 1/16 S17 BT.
	A juniper, 5 ins. diam., bears S. 61 3/4° W., 350 lks. dist., mkd. X BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
69.90	Graded dirt road, 40 lks. wide, bears NE. and SW.
80.03	The 1/4 sec. cor. of secs. 17 and 18.

BOOK 5434

Subdivision of Section 17, T. 21 N., R. 29 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	SE 1/4

	From the E. 1/16 sec. cor. of secs. 17 and 20.
	N. 0°05' W., on the N. and S. center line of the SE. 1/4 of sec. 17.
20.145	Point for the SE. 1/16 sec. cor. of sec. 17, at intersection with the E. and W. center line of the SE. 1/4 of sec. 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T21N R29E SE 1/16 S17 1987
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
40.29	The center E. 1/16 sec. cor. of sec. 17.

	From the S. 1/16 sec. cor. of secs. 16 and 17.
	S. 89°52' W., on the E. and W. center line of the SE. 1/4 of sec. 17.
20.05	The SE. 1/16 sec. cor. of sec. 17.
30.07	Point for the center W-SE 1/64 sec. cor. of sec. 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	S17 C-W-SE 1/64 1987
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

BOOK 5434

Subdivision of Section 17, T. 21 N., R. 29 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
40.09	<p>Set a steel fence post near the cor.</p> <p>The center S 1/16 sec. cor. of sec. 17.</p> <hr/>
10.055	<p>From the center W-SE 1/64 sec. cor. of sec. 17</p> <p>S. 0°03' E., on the N. and S. center line of the SW. 1/4 of the SE. 1/4 of sec. 17.</p> <p>Point for the SW-SE 1/64 sec. cor. of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S17 SW-SE 1/64 1987</p> <p>from which</p> <p style="padding-left: 40px;">The shaft of a windmill, bears N. 35 3/4° W., 551 lks. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <hr/>
10.03	<p>S. 89°57' W., on the E. and W. center line of the SW. 1/4 of the SE. 1/4 of sec. 17.</p> <p>The center S-S 1/64 sec. cor. of sec. 17.</p> <hr/>
5.01	<p style="text-align: center;">SW 1/4</p> <hr style="width: 30%; margin: auto;"/> <p>From the W. 1/16 sec. cor. of secs. 17 and 20.</p> <p>North, on the N. and S. center line of the SW 1/4 of sec. 17.</p> <p>Point for the center S-S-SW 1/256 sec. cor. of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

BOOK 5434

Subdivision of Section 17, T. 21 N., R. 29 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	S17 C-S-S-SW 1/256 1987
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post. Set a steel fence post near the cor.
7.70	Graded dirt road, 40 lks. wide, bears ESE. AND WNW.
10.02	Point for the C-S-SW 1/64 sec. cor. of sec. 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	S17 C-S-SW 1/64 1987
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post. Set a steel fence post near the cor.
15.03	Point for the C-N-S-SW 1/256 sec. cor. of sec. 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	S17 C-N-S-SW 1/256 1987
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post. Set a steel fence post near the cor.
20.04	Point for the SW. 1/16 sec. cor. of sec. 17, at intersection with the E. and W. center line of the SW. 1/4 of sec. 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

BOOK 5434

Subdivision of Section 17, T. 21 N., R. 29 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	T21N R29E SW 1/16 S17 1987
	from which
	A juniper, 6 ins. diam., bears S. 56 1/4° E., 94 lks. dist., mkd. X BT.
	A juniper, 10 ins. diam., bears S. 56° W., 161 1/2 lks. dist., mkd. SW 1/16 S17 BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
40.06	The center W. 1/16 sec. cor. of sec. 17. <hr/> From the center S. 1/16 sec. cor. of sec. 17. S. 89°50' W., on the E. and W. center line of the SW. 1/4 of sec. 17.
20.00	The SW. 1/16 sec. cor. of sec. 17.
40.00	The S. 1/16 sec. cor. of secs. 17 and 18. <hr/> From the center S-S 1/64 sec. cor. of sec. 17. S. 89°55' W., on the E. and W. center line of the SE. 1/4 of the SW. 1/4 of sec. 17.
20.005	The center S-SW 1/64 sec. cor. of sec. 17. <hr/> From the center N-S-S 1/256 sec. cor. of sec. 17. S. 89°52' W. on the E. and W. center line of the N. 1/2 of the SE. 1/4 of the SW. 1/4 of sec. 17.
20.00	The center N-S-SW 1/256 sec. cor. of sec. 17. <hr/> S. 89°52' W., on the E. and W. center line of the N. 1/2 of the SW. 1/4 of the SW. 1/4 of sec. 17.

BOOK 5434

Subdivision of Section 17, T. 21 N., R. 29 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
20.00	<p>The N-S-S 1/256 sec. cor. of secs. 17 and 18.</p> <hr/> <p>From the center S-S-SW 1/256 sec. cor. of sec. 17.</p> <p>S. 89°58' W., on the E. and W. center line of the S. 1/2 of the SW. 1/4 of the SW. 1/4 of sec. 17.</p>
20.005	<p>The S-S-S 1/256 sec. cor. of secs. 17 and 18.</p> <hr/> <p style="text-align: center;">Subdivision of Section 22, T. 21 N., R. 29 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 22 and 27.</p> <p>N. 2°59' W., on the N. and S. center line of secs. 22.</p> <p>Over nearly level land.</p>
29.20	<p>Top of a large pile of tailings from an open pit mine.</p>
38.98	<p>Point for the center 1/4 sec. cor. of sec. 22, at intersection with the E. and W. center line of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R29E C1/4 S22 1993</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located on a pile of tailings from an open pit mine.</p> <p>From this cor., an aluminum pipe, 2 ins. diam., firmly set in concrete, with an aluminum cap mkd. T21N R29E S22 C1/4 LS8906 1986, established by Keith Shreeve, R.L.S. NO. 8906, in 1986, bears N. 19°52' W., 5.03 chs. dist., established using incorrect control, and is not utilized in the course of this resurvey.</p>

BOOK 5434

Subdivision of Section 22, T. 21 N., R. 29 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
69.90	Ridge, bears ENE. and WSW.
77.96	The 1/4 sec. cor. of secs. 15 and 22.
19.72	<hr/> <p>From the true point for the 1/4 sec. cor. of secs. 22 and 23. N. 89°16' W., on the E. and W. center line of sec. 22. Across an open pit mine.</p> <p>Point for the center E. 1/16 sec. cor. of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R29E E1/16 C———C S22 1993</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located on top of a large pile of tailings from an open pit mine.</p>
39.44	The center 1/4 sec. cor. of sec. 22.
78.88	The 1/4 sec. cor. of secs. 21 and 22.
24.18	<hr/> <p style="text-align: center;">NE 1/4</p> <hr/> <p>From the center E. 1/16 sec. cor. of sec. 22. N. 2°55' W., on the N. and S. center line of the NE. 1/4 of sec. 22.</p> <p>Point for a witness point on the N. and S. center line of the NE. 1/4 of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>


BOOK 5434

Subdivision of Section 22, T. 21 N., R. 29 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
39.02	<p style="text-align: center;">WP T21N R29E E S22 E 1993</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located on the N. edge of a pile of tailings from an open pit mine, and 45 lks. E. of a track road, bears N. and S.</p> <p>The E. 1/16 sec. cor. of secs. 15 and 22.</p>
4.55 23.40 39.02	<p style="text-align: center;">SE 1/4</p> <hr/> <p>From the E. 1/16 sec. cor. of secs. 22 and 27.</p> <p>N. 2°55' W., on the N. and S. center line of the SE. 1/4 of sec. 22.</p> <p>Graded dirt road, 45 lks. wide, bears E. and W.</p> <p>Dirt road, 35 lks. wide, bears E. and W.</p> <p>The center E. 1/16 sec. cor. of sec. 22.</p>
	<p style="text-align: center;">Metes-and-Bounds Survey, NE. 1/4 of Section 7, T. 21 N., R. 29 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From angle point 1, at the intersection of the N. and S. center line of the NE. 1/4 of sec. 7 with the southeasterly right-of-way line of U.S. Interstate Highway 40.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R29E ROW AP1 S7 1993</p>

BOOK 5434

Metes-and-Bounds Survey, NE. 1/4 of Section 7,
T. 21 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post near the cor.</p> <p>The cor. is located 5 lks. S. of a new right-of-way fence, bears NNE. and SSW.</p> <p>From this cor., a right-of-way monument bears S. 29°51' W., 2.32 chs. dist., an aluminum disk, 3 ins. diam., firmly set in a concrete cylinder, 6 ins. diam., projecting 3 ins. above the ground, mkd. ARIZONA HIGHWAY DEPT. STA 1829X00 RP 385 EB 1964, located 3 lks. SE. of a cor. of right-of-way fences bearing NNE. and WSW.</p> <p>N. 29°51' E., on the southeasterly right-of-way line of U.S. Interstate Highway 40.</p>
10.309	<p>Angle point 2, identical with a right-of-way monument, an aluminum disk, 3 ins. diam., firmly set in concrete, 6 ins. below ground, in a monument box, 12 ins. diam., mkd. ARIZONA HIGHWAY DEPT. STA 1837X00 RP 150 EB 1964, located 55 lks. S. of the center of the Cedar Point on-ramp to U.S. Interstate Highway 40, pavement, 40 lks. wide, bears NE. and SW.</p> <hr/> <p>Thence N. 46°14' E., continuing on the southeasterly right-of-way line of U.S. Interstate Highway 40.</p>
2.652	<p>Angle point 3, identical with a right-of-way monument, a concrete cylinder, 6 ins. diam., firmly set flush with the ground, with the top of the cylinder and the aluminum cap broken off and missing.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, in the concrete cylinder, with top mkd.</p> <div style="text-align: center;"> <p>T21N R29E</p> <p>ROW</p>  <p>AP3</p> <p>S7</p> <p>1993</p> </div> <p>Deposit a magnet in the drill hole beneath the brass tablet.</p> <hr/>

BOOK 5434

Metes-and-Bounds Survey, NE. 1/4 of Section 7,
T. 21 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Thence S. 43°48' E., continuing on the southeasterly right-of-way line of U.S. Interstate Highway 40.</p>
1.287	<p>Angle point 4, identical with a right-of-way monument, an aluminum disk, 3 ins. diam., firmly set in a concrete cylinder, 6 ins. diam., projecting 3 ins. above the ground, mkd. ARIZONA HIGHWAY DEPT. STA 1838X75 RP 235 EB 1964.</p>
	<hr/> <p>Thence N. 46°14' E., continuing on the southeasterly right-of-way line of U.S. Interstate Highway 40.</p>
1.511	<p>Angle point 5, at intersection with the line bet. secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T21N R29E S6</p> <p style="text-align: center;">ROW / AP5 S7 1993</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post near the cor.</p>
	<p>From this cor., a right-of-way monument bears N. 46°14' E., 38.4 lks. dist., an aluminum disk, 3 ins. diam., loosely set in a concrete cylinder, 6 ins. diam., projecting 3 ins. above the ground, mkd. ARIZONA HIGHWAY DEPT. STA 1840X00 RP 235 EB 1964.</p> <hr/>

BOOK 5434

GENERAL DESCRIPTION

CHAINS

This survey is located approximately 60 miles northeast of Holbrook, Arizona. The small town of Sanders, Arizona lies immediately west of the west boundary. The southern boundary of the Navajo Indian Reservation runs through the northern portion of the township.

The terrain consists of rolling land with juniper forest, with a broad, open, nearly level river basin in the northwesterly portion. The average elevation is 6000 feet above sea level.

The Puerco River flows southwesterly across the township, entering in section 4 and leaving in section 18, providing drainage and ground water for the area.

Access is provided by U.S. Interstate Highway 40, U.S. Highway 666, and numerous dirt roads. The Atchinson, Topeka, and Santa Fe Railroad traverses through the township, along the north side of the Puerco River.

There is a large open pit clay mine in southeast portion of the township. Some occupancy in the form of residences, small ranches, and small businesses is found along U.S. Interstate Highway 40, and in the area east of Sander. The remainder of the township is used largely for grazing.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

..
BOOK 5434

FIELD ASSISTANTS

NAMES	CAPACITY
Gary D. Knoff	Crew Chief Surveying Technician
Timothy J. Moore	Crew chief Surveying Technician
Robert J. Lyle	Crew Chief Surveying Technician
Donald L. Brewer	Crew Chief Surveying Technician
Geoffrey A. Graham	Crew Chief Surveying Technician
Robert M. Charboneau	Surveying Technician
Jonathan O. Begay	Student Trainee (Land Surveyor)
Rebecca Ramirez	Surveying Aid
Gordon R. Bubel	Surveying Aid
Mark A. Leonard	Surveying Aid
Stephen M. Koval	Surveying Aid
Bruce J. Olson	Surveying Aid
David G. Jaramillo	Surveying Aid
Robert L. Speisman, II	Surveying Aid
Jimmie James, Jr.	Surveying Aid
Jack E. Arend	Surveying Aid

CERTIFICATE OF SURVEY

BOOK 5434

We, William P. Carpender, Stephen J. Malloy and Kenneth W. Bays, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 23rd day of February, 1987, supplemental special instructions dated October 13, 1987, supplemental special instructions dated February 29, 1988, and amended supplemental special instructions dated January 11, 1989, we have dependently resurveyed the Fifth Standard Parallel North (south boundary), the Seventh Auxiliary Guide Meridian East (west boundary), and a portion of the subdivisional lines; and subdivided sections 7, 17, and 22, and executed a metes-and-bounds survey in section 7, Township 21 North, Range 29 East, of the Gila and Salt River Meridian, in the state of Arizona which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Kenneth W. Bays is no longer assigned to this office and is not available for signature.

MARCH 14, 1995
(Date)

William P. Carpender
(Cadastral Surveyor)

March 16, 1995
(Date)

Step J Malloy
(Supervisory Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the Fifth Standard Parallel North (south boundary), the Seventh Auxiliary Guide Meridian East (west boundary), and a portion of the subdivisional lines; and the subdivision of sections 7, 17, and 22, and a metes-and-bounds survey in section 7, Township 21 North, Range 29 East, Gila and Salt River Meridian, executed by William P. Carpender, Stephen J. Malloy, and Kenneth W. Bays, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

MAR 16 1995

(Date)

Dale C. Wilson
(Acting Chief Cadastral Surveyor of Arizona)

CERTIFICATE OF TRANSCRIPT

I Certify that the foregoing transcript of the field notes of the above-described surveys in T. 21 N., R. 29 E., Gila and Salt River Meridian, Arizona is a true copy of the original field notes.

(Date)

(Acting Chief Cadastral Surveyor of Arizona)