

ORIGINAL

BOOK 5437

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF

A PORTION OF THE FIRST GUIDE MERIDIAN EAST,

THROUGH TOWNSHIP 17 SOUTH,

A PORTION OF THE SOUTH BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES

AND

THE SUBDIVISION OF SECTIONS 25, 35 AND 36

OF

TOWNSHIP 17 SOUTH, RANGE 4 EAST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY
Gordon R. Bubel, Cadastral Surveyor

Under Special Instructions dated July 19, 1994, approved July 19, 1994, which provided for the surveys included under Group Number 779, and assignment instructions dated September 7, 1994.

Survey Commenced September 12, 1994
Survey Completed April 19, 1995

2
BOOK 5437

INDEX DIAGRAM

TOWNSHIP 17 SOUTH, RANGE 4 EAST,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	16	26
				13	25
				14	12
31	32	33	34	14	35
				10	36
				9	8

Subdivision of sec. 25
 Subdivision of sec. 35
 Subdivision of sec. 36

pp. 16-18
 pp. 18-21
 pp. 21-28 pp

BOOK 5437

T. 17 S., R. 4 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the First Guide Meridian East, through Township 17 South, a portion of the south boundary, a portion of the subdivisional lines and the subdivision of sections 25, 35 and 36, Township 17 South, Range 4 East, Gila and Salt River Meridian, Arizona.

The exterior boundaries and a portion of the subdivisional lines were surveyed by William H. Elliott, in 1911.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated July 19, 1994, for Group No. 779, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of all lines were determined by direct hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with a Sokkia SET2BII total station instrument.

The geographic position of the 1/4 sec. cor. of secs. 31 and 36, Ts. 17 S., Rs. 4 and 5 E., on the east boundary of the township, as determined from a tie made to U.S. Coast and Geodetic Survey triangulation station "WAHOO", hereinafter described, is as follows:

Latitude: 31°54'26.87" N. Longitude: 111°52'42.42" W. NAD27

The mean magnetic declination, as taken from quadrangle map SELLS WEST, ARIZ., published in 1979 by U.S. Geological Survey, is 13° E.

BOOK 5437

Dependent Resurvey of a Portion of the First Guide Meridian East,
Through Township 17 South, Gila and Salt River Meridian, Arizona

CHAINS

Restoring the survey executed by
William H. Elliott in 1911

Beginning at the 1/4 sec. cor. of secs. 31 and 36, on the E. bdy of the Tp., monumented with an iron post, 1 ins. diam, firmly set, projecting 16 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. 1/4 S36 S31 1911

Add the marks T17S R4E R5E 1994 on the brass cap.

From this cor. point, U.S.C. & G. Survey triangulation station "WAHOO", with published latitude of 31°55'10.488" N. and longitude of 111°53'12.191" W., NAD27, bears N. 30°12'23" W., (forward bearing), 77.28 chs. dist., monumented with a standard bronze disk, 3 1/2 ins. diam., cemented flush with the surface of a rock outcrop, with top of disk mkd. WAHOO 1936 and a triangle.

N. 0°03' W., bet. secs. 31 and 36.

0.70 Wash, 15 lks. wide, 3 ft. deep, drains NE.

20.04 Point for the N 1/16 sec. cor. of secs. 31 and 36, occupied with an iron pipe, 48 ins. long, 2 1/2 ins. diam., firmly set, projecting 21 ins. above ground, of unknown origin.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.

T17S
N1/16
R4E | R5E
S36 | S31
1994

Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Bury the iron pipe alongside the stainless steel post.

30.06 Point for the N-N 1/64 sec. cor. of secs. 31 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

BOOK 5437

Dependent Resurvey of a Portion of the First Guide Meridian East,
Through Township 17 South, Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T17S R4E R5E N-N 1/64 S36 S31 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 5 lks. E. of a chain link fence, 6 ft. high, bears NNW and SSE.</p>
35.44	Paved road, 38 lks. wide, bears E and W.
40.08	<p>The cor. of secs. 25, 30, 31 and 36, Ts. 17 S., Rs. 4 and 5 E., monumented with an iron post, 3 1/2 ins. diam., firmly set, 4 ins. below the surface of the ground, with brass cap mkd., T17S R4E R5E S30 S31 S36 S25 1911.</p> <p>Add the marks 1994 on the brass cap.</p> <p>Cor. is located 2 chs. E. of the centerline of a paved road 45 lks wide, bears N. and S.</p>
	<hr/> <p>North, bet. secs. 25 and 30.</p>
2.80	Center of wash, 45 lks. wide, 3 ft. deep, drains SE.
17.85	Woven wire fence, 6 ft. high, bears ENE and WSW.
19.25	Center line of AZ. State Highway No. 86, asphalt surfaced, 76 lks. wide, bears ENE and WSW.
20.045	<p>Point for the S 1/16 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T17S R4E R5E S 1/16 S25 S30 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p>

BOOK 5437

Dependent Resurvey of a Portion of the First Guide Meridian East,
Through Township 17 South, Gila and Salt River Meridian, Arizona

CHAINS	
	Cor. located within AZ. Highway No. 86 Right of Way.
20.90	Woven wire fence, 6 ft. high, bears ENE and WSW.
36.35	Barbed wire fence, 3 strand, bears E. and W.
37.40	Left bank of Sells Wash, 6 ft. deep, drains W.
40.09	Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate distance, falls in Sells Wash, where it is impracticable to establish a permanent monument; there is no remaining evidence of the original corner.
	From this point, the point selected for a witness cor., bears N. 8°22' W., 1.82 chs. dist.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	WC T17S R4E R5E 1/4 S25 S30 1994
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
41.50	Right bank of Sells Wash, 8 ft. deep, drains WSW.
59.30	Center of power line, 4 strands, bears E. and W.
75.70	Earthen berm, 30 ft. wide, 10 ft. high, bears NW and SE.
80.18	The cor. of secs. 19, 24, 25 and 30, determined at the center of a depression, containing pieces of concrete and iron.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the First Guide Meridian East,
Through Township 17 South, Gila and Salt River Meridian, Arizona

CHAINS													
	<table style="margin: auto;"> <tr><td colspan="2">T17S</td></tr> <tr><td>R4E</td><td>R5E</td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td colspan="2">— —</td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td colspan="2">1994</td></tr> </table>	T17S		R4E	R5E	S24	S19	— —		S25	S30	1994	
T17S													
R4E	R5E												
S24	S19												
— —													
S25	S30												
1994													
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>Found lying loose nearby; an iron pipe 36 ins. long, 3 ins. diam., with brass cap mkd., T17S R4E R5E S19 S25 S30 S24 1911</p> <p>Remove original monument from area, impracticable to bury.</p> <hr/> <p>N. 0°02' W, bet. secs. 19 and 24.</p> <p>Over nearly level land, medium undergrowth.</p>												
2.80	Earthen berm, 15 ft. wide, 4 ft. high, bears E. and W.												
35.40	Earthen berm, 15 ft. wide, 4 ft. high, bears E. and W.												
40.10	Point for 1/4 sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the original cor.												
	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>												
	<table style="margin: auto;"> <tr><td colspan="2">T17S</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R4E</td><td>R5E</td></tr> <tr><td>S36</td><td>S31</td></tr> <tr><td colspan="2">1994</td></tr> </table>	T17S		1/4		R4E	R5E	S36	S31	1994			
T17S													
1/4													
R4E	R5E												
S36	S31												
1994													
17.40	<p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>Track road, 30 lks. wide, bears NE and SW.</p>												

BOOK 5437

Dependent Resurvey of a Portion of the First Guide Meridian East,
Through Township 17 South, Gila and Salt River Meridian, Arizona

CHAINS	
80.20	<p>The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 3 ins. diam., firmly set, in a 9 ins. x 9 ins. squared concrete form, projecting 3 ins. above ground, with brass cap mkd. T17S R4E R5E S18 S19 S24 S13 1936 1911</p> <p>Add the marks 1994 on the brass cap</p> <p>This cor. point is also utilized, as U.S.C. & G. Survey triangulation station, "G.L.O. STATION No. 21" with published latitude of 31°56'37.784" N. and longitude of 111°52'42.487" W., NAD27.</p>
<p>Dependent Resurvey of a Portion of the South Boundary T. 17 S., R. 4 E., Gila and Salt River Meridian, Arizona</p>	
<p>Restoring the survey executed by William H. Elliott, in 1911</p>	
<p>Beginning at the 1/4 sec. cor. of secs. 1 and 36, Ts. 17 and 18 S., R. 4 E., on the S. bdy. of the Tp., determined from the remains of the original mound of stone, 2 ft. base, 1 1/2 ft. high.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T17S R4E S36 1/4 — S1 T18S 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.</p> <p>Rebuild mound of stone, 3 ft. base, 3 ft. high, N. of cor.</p> <p>Cor. located on gentle S. facing slope.</p> <p>S. 89°57' W., bet. secs. 1 and 36, on the S. bdy. of the Tp.</p>	

BOOK 5437

Dependent Resurvey of a Portion of the South Boundary
T. 17 S., R. 4 E., Gila and Salt River Meridian, Arizona

CHAINS																											
40.15	<p>The cor. of secs. 1, 2, 35 and 36, monumented with an iron post, 3 ins. diam., firmly set, projecting 18 ins. above ground, with a mound of stone to the W., 3 ft. base, 2 ft. high, with brass cap erroneously mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T17S</td><td>R4E</td></tr> <tr><td>S35</td><td>S36</td></tr> <tr><td colspan="2">—</td></tr> <tr><td>S1</td><td>S2</td></tr> <tr><td colspan="2">T18S</td></tr> <tr><td colspan="2">1911</td></tr> </table> </div> <p>Remark the brass cap to read</p> <div style="text-align: center;"> <table border="1"> <tr><td>T17S</td><td>R4E</td></tr> <tr><td>S35</td><td>S36</td></tr> <tr><td colspan="2">—</td></tr> <tr><td>S2</td><td>S1</td></tr> <tr><td colspan="2">T18S</td></tr> <tr><td colspan="2">1911</td></tr> <tr><td colspan="2">1994</td></tr> </table> </div> <p>Cor. located on W. slope of hill.</p>	T17S	R4E	S35	S36	—		S1	S2	T18S		1911		T17S	R4E	S35	S36	—		S2	S1	T18S		1911		1994	
T17S	R4E																										
S35	S36																										
—																											
S1	S2																										
T18S																											
1911																											
T17S	R4E																										
S35	S36																										
—																											
S2	S1																										
T18S																											
1911																											
1994																											
20.03	<p>S. 89°53' W., bet. secs. 2 and 35, on the S. bdy. of the Tp.</p> <p>Point for the E 1/16 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T17S</td><td>R4E</td></tr> <tr><td colspan="2">S35</td></tr> <tr><td colspan="2">E 1/16 —</td></tr> <tr><td colspan="2">S2</td></tr> <tr><td colspan="2">T18S</td></tr> <tr><td colspan="2">1994</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.</p>	T17S	R4E	S35		E 1/16 —		S2		T18S		1994															
T17S	R4E																										
S35																											
E 1/16 —																											
S2																											
T18S																											
1994																											
40.06	<p>Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate dist.; the original iron post, 36 ins. long, 1 ins. diam., with brass cap mkd. 1/4 S35 S2 1911 was found lying loose nearby.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>																										

Dependent Resurvey of a Portion of the South Boundary
T. 17 S., R. 4 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T17S R4E S35 1/4 — S2 T18S 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.</p> <p>Deposit the original iron post inside the stainless steel post.</p> <p>80.12 The cor. of secs. 2, 3, 34 and 35, monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. T17S R4E S35 S2 S3 S34 T18S 1911.</p> <p>Add the marks 1994 on the brass cap.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivisional Lines T. 17 S., R. 4 E., Gila and Salt River Meridian, Arizona</p> <hr/>
	<p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp. hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>20.05 Point for the S 1/16 sec. cor. of secs. 35 and 36.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T17S R4E S 1/16 S35 S36 1994</p>
	<p>Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.</p> <p>40.10 The 1/4 sec. cor. of secs. 35 and 36, monumented with a broken iron post, 1 ins. diam., firmly set, in a concrete cylinder, 2 ft. diam., 6 ins. below the surface of the ground, with remaining fragments of the broken iron post lying nearby, with partially attached brass cap mkd. 1/4 S35 S36.</p> <p>At the cor. point</p>

BOOK 5437

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 17 S., R. 4 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T17S R4E 1/4 S35 S36 1994</p>
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	Remove concrete cylinder from around the iron post, bury remaining iron post and fragments alongside stainless steel post.
	<hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">N. 0°01' E., beginning new measurement.</p>
20.00	Point for the N 1/16 sec. cor. of secs. 35 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T17S R4E N 1/16 S35 S36 1994</p>
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
35.55	Center of graded road, 30 lks. wide, bears E. and W.
37.55	The witness cor. to the cor. of secs. 25, 26, 35 and 36, monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T17S R4E WC S25 S36 S35 S26 1911.
	Add the marks 1994 on the brass cap.
	<hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">N. 0°01' E., beginning new measurement.</p>
0.45	Left bank of Sells Wash, 5 ft. deep, drains WSW.
2.46	True point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance. The corner point falls in Sells Wash, where it is impracticable to establish a permanent monument.
	<hr style="width: 20%; margin: auto;"/>

BOOK 5437

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 17 S., R. 4 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.
	S. 89°51' W., bet. secs. 25 and 36.
	Through the Town of Sells.
2.00	Center line of asphalt surfaced road, 45 lks. wide, bears N. and S.
20.03	Point for the E 1/16 sec. cor. of secs. 25 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T17S R4E S25 E 1/16 — S36 1994</p>
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
36.84	Intersect the E. side of Bashas Supermarket, brick, 177.8 ft. x 81.0 ft., the long side bears N. 8° W., the NE corner bears N. 8° W., 1.05 chs. dist.
40.06	Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist., there is no remaining evidence of the original cor.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, flush with asphalt surface, with top mkd.
	<p style="text-align: center;">T17S R4E S25 1/4 — S36 1994</p>
	from which
	A lamp post base, 10 ins. square, mounted on a concrete pillar, 24 ins. diam., 24 ins. high, bears N. 66 1/4° E., 90 lks. dist., stamped X BO.

BOOK 5437

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 17 S., R. 4 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A lamp post base, 10 ins. square, mounted on a concrete pillar, 24 ins. diam., 24 ins. high, bears S. 24 1/4° W., 2.01 chs. dist., stamped X BO.</p> <p>Cor. is located in parking lot of Bashas Supermarket.</p>
80.12	<p>The true point for the cor. of secs. 25, 26, 35 and 36.</p> <hr/>
	<p>N. 0°03' W., bet. secs. 25 and 26.</p>
4.40	<p>Right bank of Sells Wash, 6 ft. deep, drains WSW.</p>
20.065	<p>Point for the S 1/16 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T17S R4E S 1/16 S25 S26 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.</p>
40.13	<p>The 1/4 sec. cor. of secs. 25 and 26, monumented with an iron pipe, 21 ins. long, 1 3/4 ins. diam., projecting 3 ins. above ground, with attached metal wafer stamped LS 4080, established by Thomas Luckon, and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T17S R4E 1/4 S26 S25 1994</p> <p>Deposit the iron pipe inside the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 17 S., R. 4 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Cor. is located in a barbed wire fence, 4 strands, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03' W., beginning new measurement.</p>										
49.13	Center line of Az. State Highway No. 86, asphalt surfaced, 38 lks. wide, bears ESE and WSW.										
80.19	<p>The cor. of secs. 23, 24, 25 and 26, monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T17S R4E S23 S24 S26 S25 1911.</p> <p>Add the marks 1994 to the brass cap.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 1 ins. diam, firmly set, projecting 11 ins. above ground, with brass cap mkd. 1/4 S34 S35 1911.</p> <p>Add the marks T17S R4E 1994 to the brass cap.</p> <p>N. 0°13' E., bet. secs. 34 and 35.</p> <p>Over nearly level land, through medium undergrowth.</p>										
22.10	Left bank of Sells Wash, 10 ft. deep, drains SW.										
25.00	Right bank of Sells Wash, 10 ft. deep, drains SW.										
38.61	Center of paved road, 38 lks. wide, bears E. and W.										
40.02	<p>Point for the cor. of secs. 26, 27, 34 and 35, determined by three point control; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: 0 auto;"> <tr><td colspan="2">T17S R4E</td></tr> <tr><td>S27</td><td>S26</td></tr> <tr><td colspan="2">— —</td></tr> <tr><td>S34</td><td>S35</td></tr> <tr><td colspan="2">1994</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.</p> <hr/> <p>From the true point for the cor. of secs. 25, 26, 35 and 36.</p>	T17S R4E		S27	S26	— —		S34	S35	1994	
T17S R4E											
S27	S26										
— —											
S34	S35										
1994											

BOOK 5437

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 17 S., R. 4 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>S. 89°50' W., bet. secs. 26 and 35.</p> <p>Over Sells Wash.</p> <p>19.985 True point for the E 1/16 sec. cor. of secs. 26 and 35. The cor. point falls in Sells Wash, where it is impracticable to establish a permanent monument.</p> <p>From this point, the point selected for the witness E 1/16 sec. cor. of secs. 26 and 35 bears N. 20°06' W., 1.11 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WC T17S R4E S26 E1/16 — S35 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 82 lks. S. of right bank of Sells Wash, 6 ft. deep, drains W.</p>
39.97	<p>True point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original cor. The cor. point falls in Sells Wash, where it is impracticable to establish a permanent monument,</p> <p>From this point, the point selected for the witness 1/4 sec. cor. of secs. 26 and 35 bears N. 1°59' E., 1.80 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WC T17S R4E S25 1/4 — S35 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p>

BOOK 5437

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 17 S., R. 4 E., Gila and Salt River Meridian, Arizona

CHAINS 79.94	The cor. of secs. 26, 27, 34 and 35.
	<hr/> <p>N. 0°11' W., bet. secs. 26 and 27.</p> <p>Over nearly level land, through medium undergrowth.</p>
40.02	<p>The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 1 ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd. 1/4 S27 S26 1911.</p> <p>Add the marks T17S R4E 1994 on the brass cap.</p> <p>Cor. is located 18 lks. E. of power line, two wire, bears N. and S.</p> <hr/> <p style="text-align: center;">Subdivision of Section 25 T. 17 S., R. 4 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 36.</p> <p>N. 0°02' W., on the N. and S. centerline of sec. 25.</p>
20.055	<p>Point for the center S 1/16 sec. cor. of sec. 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T17S R4E C S1/16 S25 C 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located on S. slope.</p>
32.20	Center line of Az. State Highway No. 86, asphalt surfaced, 38 lks. wide, bears ESE and WSW.
40.11	<p>Point for the center 1/4 sec. cor. of sec. 25, at intersection with the E. and W. center line of sec. 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

BOOK 5437

Subdivision of Section 25

T. 17 S., R. 4 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T17S R4E C1/4 S25 1994</p>
80.22	<p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>The 1/4 sec. cor. of secs. 24 and 25, monumented with an iron post, 1 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. 1/4 S24 S25 1911.</p> <p>Add the marks T17S R4E 1994 on the brass cap.</p>
40.07	<hr/> <p>From the true point for the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy of the Tp., hereinbefore described.</p> <p>S. 89°53' W., on the E. and W. centerline of sec 25.</p> <p>The center 1/4 sec. cor. of sec. 25.</p>
80.14	<p>The 1/4 sec. cor. of secs. 25 and 26.</p>
40.06	<hr/> <p style="text-align: center;">SE 1/4</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°52' W., on the E. and W. centerline of the SE 1/4 of sec. 31.</p> <p>Through the Town of Sells.</p> <p>The center S 1/16 sec. cor. of sec. 25.</p>
	<hr/> <p style="text-align: center;">SW 1/4</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 25.</p> <p>S. 89°52' W., on the E. and W. centerline of the SW 1/4 of sec. 25.</p>

BOOK 5437

Subdivision of Section 25
T. 17 S., R. 4 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.06	The S 1/16 sec. cor. of secs. 25 and 26.
	<hr/> From the 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°03' E., on the N. and S. centerline of sec. 35.
	Over nearly level land, medium undergrowth.
20.03	Point for the center S 1/16 sec. cor. of sec. 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T17S R4E C S1/16 S35 C 1994</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
40.06	Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E. and W. center line of sec. 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T17S R4E C1/4 S35 1994</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	From this cor., an iron pipe, 2 1/2 ins. diam., firmly set in concrete, projecting 10 ins. above ground, with the mks. INSIDE 1/4, painted on the N. side, of unknown origin, bears N. 89°49' W., 4 lks. dist. Established improperly at midpoint on the E. and W. centerline of sec. 35, and is not utilized in the course of this resurvey.
60.07	Point for the center N 1/16 sec. cor. of sec. 35.

BOOK 5437

Subdivision of Section 35

T. 17 S., R. 4 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T17S R4E C N1/16 S35 C 1994</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
77.10	Left bank of Sells Wash, 6 ft. deep, drains WSW.
79.25	Right bank of Sells Wash, 5 ft. deep, drains WSW.
80.08	The true point for the 1/4 sec. cor. of secs. 26 and 35.
	<hr/>
	From the 1/4 sec. cor. of secs. 35 and 36.
	S. 89°49' W., on the E. and W. centerline of sec. 35.
	Over nearly level land, medium undergrowth.
20.00	Point for the center E 1/16 sec. cor. of sec. 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T17S R4E E1/16 C ——— C S35 1994</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
40.00	The center 1/4 sec. cor. of sec. 35.
80.08	The 1/4 sec. cor. of secs. 34 and 35.
	<hr/>
	NE 1/4
	<hr/>
	From the center E 1/16 sec. cor. of sec. 35.
	N. 0°02' E., on the N. and S. centerline of the NE 1/4 of sec. 35

BOOK 5437

Subdivision of Section 35

T. 17 S., R. 4 E., Gila and Salt River Meridian, Arizona

CHAINS	
19.65	Intersect woven wire fence, 6 ft. high, bears E. and W. Thence across sewage pond.
20.005	True point for the NE 1/16 sec. cor. of sec. 35, at intersection with the E. and W. center line of the NE 1/4 sec. 35. The cor. point falls in a sewage pond, where it is impracticable to establish a permanent monument. From this point, the point selected for the witness NE 1/16 sec. cor. of sec. 35 bears S. 44°07' E., 0.66 chs. dist. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. WC T17S R4E NE 1/16 S35 1994 Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
31.16	Woven wire fence, 6 ft. high, bears E. and W. Leave sewage pond.
40.01	The true point for the E 1/16 sec. cor. of secs. 26 and 35. <hr/>
	From the N 1/16 sec. cor. of secs. 35 and 36.
	S. 89°50' W., on the E. and W. centerline of the NE 1/4 of sec. 35.
19.99	The true point for the NE 1/16 sec. cor. of sec. 35.
39.98	The center N 1/16 sec. cor. of sec. 35. <hr/>
	SE 1/4 <hr/>
	From the E 1/16 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°01' E., on the N. and S. centerline of the SE 1/4 of sec. 35.

BOOK 5437

Subdivision of Section 35
T. 17 S., R. 4 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.04	Point for the SE 1/16 sec. cor. of sec. 35, at intersection with the E. and W. center line of the SE 1/4 of sec. 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T17S R4E SE 1/16 S35 1994
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located on N. slope.
40.08	The center E 1/16 sec. cor. of sec. 35.
	From the S 1/16 sec. cor. of secs. 35 and 36.
	S. 89°51' W., on the E. and W. centerline of the SE 1/4 of sec. 35.
20.015	The SE 1/16 sec. cor. of sec. 35.
40.03	The center S 1/16 sec. cor. of sec. 35.
	Subdivision of Section 36 T. 17 S., R. 4 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 1 and 36, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°04' W., on the N. and S. centerline of sec. 36.
20.06	Point for the center S 1/16 sec. cor. of sec. 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled with a collar of stone, with brass cap mkd.

BOOK 5437

Subdivision of Section 36
T. 17 N., R. 4 E., Gila and Salt River Meridian, Arizona

CHAINS

T17S R4E
C
S1/16 | S36
C
1994

Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

20.35 Center of wash, 15 lks. wide, 1 ft. deep, drains W.

40.12 Point for the center 1/4 sec. cor. of sec. 36, at intersection with the E. and W. center line of sec. 36, occupied by an iron pipe, 21 ins. long, 1 1/2 ins. diam., firmly set, 4 ins. below the surface of the ground, of unknown origin.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T17S R4E
C1/4 S36
1994

Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Deposit the iron pipe inside the stainless steel post.

60.14 Point for the center N 1/16 sec. cor. of sec. 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T17S R4E
C
N1/16 | S36
C
1994

Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Cor. is located 113 lks. W. of the centerline of a paved road, 45 lks. wide, bears NNE and SSW.

BOOK 5437

Subdivision of Section 36

T. 17 N., R. 4 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.16	The 1/4 sec. cor. of secs. 25 and 36. <hr/>
	From the 1/4 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp., hereinbefore described.
	S. 89°54' W., on the E. and W. centerline of sec. 36.
20.025	Point for the center E 1/16 sec. cor. of sec. 36, occupied with an open end iron pipe, 2 1/2 ins. diam., firmly set in concrete, projecting 13 ins. above ground, unknown origin.
	Cemented a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in the end of the iron pipe, with top mkd.
	T17S R4E
	E1/16
	C—C
	S36
	1994
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case inside the iron pipe.
40.05	The center 1/4 sec. cor. of sec. 36.
80.17	The 1/4 sec. cor. of secs. 35 and 36. <hr/>
	NE 1/4 <hr/>
	From the center E 1/16 sec. cor. of sec. 36.
	N. 0°03' W., on the N. and S. centerline of the NE 1/4 of sec. 36.
20.03	Point for the NE 1/16 sec. cor. of sec. 36, at intersection with the E. and W. center line of the NE 1/4 of sec. 36, occupied with an open end iron pipe, 2 1/2 ins. diam., firmly set in concrete, projecting 16 ins. above ground, unknown origin.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.

BOOK 5437

Subdivision of Section 36

T. 17 N., R. 4 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>T17S R4E NE 1/16 S36 1994</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>Bury the iron pipe alongside the stainless steel post.</p>
28.15	Woven wire fence, 6 ft. high, bears E. and W. Thence across playground of Desert Oasis Elementary School.
30.045	Point for the C-N-NE 1/64 sec. cor. of sec. 36, falls in the playground of Desert Oasis Elementary School, not monumented.
33.85	Chain linked fence, 6 ft. high, bears E. and W. Leave playground of Desert Oasis Elementary School.
40.06	The E 1/16 sec. cor. of secs. 25 and 36.
	<hr/> <p>From the N 1/16 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°53' W., on the E. and W. centerline of the NE 1/4 of sec. 36.</p>
20.03	The NE 1/16 sec. cor. of sec. 36.
40.06	The CN 1/16 sec. cor. of sec. 36.
	<hr/> <p>From the N-N 1/64 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°52' W., on the E. and W. centerline of the NE 1/4 of the NE 1/4 of sec. 36.</p>
7.515	<p>Point for the 1/1024 sec. cor. of sec. 36, on the W 1/2 of the E 1/2 of the E. and W. centerline of the NE 1/4 of the NE 1/4 of sec. 36.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, alongside the iron pipe with top mkd.</p>

BOOK 5437

Subdivision of Section 36

T. 17 N., R. 4 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T17S R4E 1/1024 1994</p> <p>Cor. is located 1 lk. NE of a steel woven wire fence corner, set in concrete, 5 ft. high, extending N. and E.</p> <p>From this cor. an iron pipe 1 1/2 ins. diam., firmly set in concrete, projecting 2 ins., above ground, of unknown origin, bears N. 45° W., 0.001 ch. dist.</p>
10.02	<p>Point for the NE-NE 1/64 sec. cor. of sec. 36, at intersection with the calculated N. and S. center line of the NE 1/4 of the NE 1/4 of sec. 36.</p> <p>Chisel an X on a concrete slab.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 28 ins. in the ground, for a reference monument, bears S. 50 1/2° E., 5.6 ft. dist., with cap mkd. RM T17S R4E S36 NE-NE 1/64 5.6 FT TO COR 1994, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p style="padding-left: 40px;">A moly steel nail, 1 in. diam. head, 2 3/4 ins. stem, set flush with pavement, for a reference monument, bears S. 68 1/2° W., 10.24 ft. dist., with top mkd. SURVEY MARK.</p> <p>Cor. is located on a concrete slab of a ramada, 29 X 15 ft.</p>
10.86	<p>Intersect the E. side of Desert Oasis Elementary School maintenance building, brick, 58 x 53 ft., the long side bears N.; the SE corner bears S. 31 lks. dist.</p>
12.525	<p>Point for the 1/1024 sec. cor. of sec. 36, on the E 1/2 of the W 1/2 of the E. and W. centerline of the NE 1/4 of the NE 1/4 of sec. 36; falls in the cafeteria of Desert Oasis Elementary School, not monumented.</p>
20.04	<p>The point for the C-N-NE 1/64 sec. cor. of sec. 36.</p> <hr/>

26
BOOK 5437

Subdivision of Section 36
T. 17 N., R. 4 E., Gila and Salt River Meridian, Arizona

CHAINS	
5.01	<p>From the 1/1024 sec. cor. of sec. 36, on the W 1/2 of the E 1/2 of the E. and W. centerline of the NE 1/4 of the NE 1/4 of sec. 36.</p> <p>N. 0°03' W., on the N. and S. center line of the SW 1/4 of the NE 1/4 of the NE 1/4 of the NE 1/4 of sec. 36.</p> <p>Point for the 1/1024 sec. cor. of sec. 36, on the W 1/2 of the E. and W. centerline of the NE 1/4 of the NE1/4 of the NE 1/4 of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T17S R4E 1/1024 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 11 lks. N. of a fence corner, with woven wire fences, 5 ft. high, extending S. and W.</p> <hr/>
2.505	<p>S. 89° 52' W. on a portion of the E. and W. center line of the NE 1/4 of the NE 1/4 of the NE 1/4.</p> <p>Point for the C-N-NE-NE 1/256 sec. cor. of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T17S R4E S36 C-N-NE-NE 1/256 1994</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 24 lks. N. of a woven wire fence, 5 ft. high, bears E. and W.</p> <hr/>

BOOK 5437

Subdivision of Section 36

T. 17 N., R. 4 E., Gila and Salt River Meridian, Arizona

CHAINS	
2.505	<p>S. 89°52' W. on a portion of the E. and W. center line of the NW 1/4 of the NE 1/4 of the NE 1/4.</p> <p>Point for the 1/1024 sec. cor. of sec. 36, on the E 1/2 of the E. and W. centerline of the NW 1/4 of the NE 1/4 of the NE 1/4 of sec. 36.</p> <p>Set a moly steel nail, 1 in. diam. head, 2 3/4 ins. stem, flush with the pavement surface, with top mkd. SURVEY MARK.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground, for a reference monument, bears N. 48°19' E., 78.5 ft. dist., with cap mkd. RM T17S R4E 1/1024 78.5 FT TO COR 1994, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground, for a reference monument, bears N. 66°02' W., 105.7 ft. dist., with cap mkd. RM T17S R4E 1/1024 105.7 FT TO COR 1994, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.</p> <p>Cor. is located 7 lks. S. of center of paved road, 44 lks. wide, bears N. 85° E. and S. 85° W.</p>
5.01	<p>S. 0°03' E., on the N. and S. center line of the SE 1/4 of the NW 1/4 of the NE 1/4 of the NE 1/4.</p> <p>The 1/1024 sec. cor. of sec. 36, on the E 1/2 of the W 1/2 of the NE 1/4 of the NE 1/4 of sec. 36.</p> <hr/> <p style="text-align: center;">SW 1/4</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 36.</p> <p>S. 89°56' W., on the E. and W. centerline of the SW 1/4 of sec. 36.</p>

BOOK 5437

Subdivision of Section 36
T. 17 N., R. 4 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>40.13</p> <p>40.09</p>	<p>The S 1/16 sec. cor. of secs. 35 and 36.</p> <hr/> <p style="text-align: center;">NW 1/4</p> <hr/> <p>From the center N 1/16 sec. cor. of sec. 36.</p> <p>S. 89°52' W., on the E. and W. centerline of the NW 1/4 of sec. 36.</p> <p>The N 1/16 sec. cor. of secs. 35 and 36.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The land encompassed in this survey is located in and around the Town of Sells, within the Papago Indian Reservation. The land is generally level, with a series of rolling hills in the southern part of the township. Elevations range from 2300 ft. to 2700 ft. above sea level. Sells Wash is the main drainage, crossing the township in a westerly course. The vegetation is mainly creosote and sparse native grasses, with stands of mesquite and palo verde near washes. The soil varies from rocky in the hills, to sandy in the flats and sandy loam near water courses.</p> <p>Access is by way of AZ. Highway No. 86, and numerous paved and unpaved roads in and around Sells.</p>
---	---

BOOK 5437

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Geoffrey A. Graham	Surveying Technician
Jeffrey A. Hill	Surveying Technician
Wallace R. Ott Jr.	Surveying Technician
Mark R. Searles	Surveying Technician

BOOK 5437

CERTIFICATE OF SURVEY

I, Gordon R. Bubel, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 19th day of July, 1994, I have dependently resurveyed a portion of the First Guide Meridian East, through Township 17 South, a portion of the south boundary, portions of the subdivisional lines, and the subdivision of sections 25, 35, and 36 of Township 17 South, Range 4 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

MAY 10, 1995

(Date)

Gordon R. Bubel

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the First Guide Meridian East, through Township 17 South, a portion of the south boundary, a portion of the subdivisional lines and the subdivision of sections 25, 35, and 36 in Township 17 South, Range 4 East, Gila and Salt River Meridian, Arizona, executed by Gordon R. Bubel, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

MAY 15, 1995

(Date)

Jannet A. Tallot

(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 17 S., R. 4 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~MAY 15, 1995~~

~~(Date)~~

~~Jannet A. Tallot~~

~~(Chief Cadastral Surveyor of Arizona)~~