

ORIGINAL

1

BOOK 5442

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE

DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH BOUNDARY

AND A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE METES-AND-BOUNDS SURVEY OF THE

MOUNT NUTT WILDERNESS AREA BOUNDARY

IN TOWNSHIP 20 NORTH, RANGE 19 WEST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY
Olian T. Shockley, Cadastral Surveyor

Under Special Instructions dated October 24, 1991, approved October 24, 1991, which provided for the surveys included under Group Number 738 and assignment instructions dated October 24, 1991.

Survey commenced October 31, 1991
Survey completed May 25, 1993

BOOK 5442

INDEX DIAGRAM

TOWNSHIP 20 NORTH, RANGE 19 WEST,

6	28	5	24	4	3	2	1
27				23			
7	27	8	21	9	10	11	12
26		26		20			
18		17	18	16	8	15	14
				17			
19		20	15	21	7	22	23
			25	13			
30		29	11	28	5	27	26
				11			
31		32	11	33	34	35	36
				4			

BOOK 5442
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the south boundary and a portion of the subdivisional lines, and the metes-and-bounds survey of the Mount Nutt Wilderness Area Boundary, in Township 20 North, Range 19 West, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this resurvey is as follows: The Fifth Standard Parallel North through Range 19 West was surveyed by Omar H. Case in 1872. The Fifth Standard Parallel North through a portion of Range 19 West was resurveyed by Fred W. Rodolf in 1910. A portion of the south boundary and subdivisional lines were surveyed by William B. Alexander in 1910-12. The Fifth Standard Parallel North through a portion of Range 19 West was resurveyed by Guy H. Richardson, Otis Ross, and Hugo Price in 1915. The west boundary was surveyed by Guy H. Richardson in 1915. A portion of the south boundary was retraced and surveyed by Hugo Price in 1915. A portion of the subdivisional lines was resurveyed and surveyed by Guy H. Richardson and Hugo Price in 1915. The south boundary was dependently resurveyed by Dennis K. McKay in 1984-90.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated October 24, 1991, for Group No. 738, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The purpose of this survey was to determine the boundary of Mount Nutt Wilderness Area.

The directions of all lines were determined by direct hour angle observations on the sun and Sirius, and refer to the true meridian. Distances and angles were measured with a Zeiss Elta 3 total station instrument.

The geographic position of the southeast corner of section 33 on the S. bdy. of the Tp., as determined and published by the U.S. Geological Survey, is as follows:

Latitude: 35°04'08.936" N. Longitude: 114°17'52.006" W. NAD27

The mean magnetic declination, as taken from quadrangle map MOUNT NUTT, ARIZ. and SECRET PASS, ARIZ., published in 1967 by U.S. Geological Survey, is 15° E.

BOOK 5442

Dependent Resurvey of a Portion of the South Boundary
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">Restoring the resurvey executed by Dennis K. McKay, in 1984-90</p> <hr/> <p>Beginning at the cor. of secs. 3, 4, 33 and 34, identical with USGS triangulation station "33-T20NR19W", on the S. bdy. of the Tp., monumented with an iron post, 3 ins. diam, firmly set, projecting 36 ins. above ground, supported in a mound of stone, 5 ft. base, to top, with brass cap mkd. T20N R19W S33 S34 S3 S4 T19N 1984 1915.</p> <p>Add the marks 1991 on the brass cap</p> <p>S. 89°45' W., bet. secs. 4 and 33, on the S. bdy. of the Tp.</p> <p>40.26 The 1/4 sec. cor. of secs. 4 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, supported in a mound of stone, 4 ft. base, 12 ins. high, with a mound of stone to the N., 4 ft. base, 5 1/2 ft. high, with brass cap mkd. S33 1/4 S4 1915.</p> <p>Add the marks T20N T19N R19W 1991 on the brass cap</p> <p>Cor. is located on the steep east slope of a mountain.</p> <hr/> <p>S. 89°41' W., beginning new measurement.</p> <p>39.54 The cor. of secs. 4, 5, 32 and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, in a mound of stone, 5 ft. base, 2 ft. high, with brass cap mkd. T20N R19W S32 S33 S4 S5 T19N 1915.</p> <p>Add the marks 1991 on the brass cap</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 34°42' W., 53.9 ft. dist., with cap mkd. T19N R19W RM 53.9 FT TO COR S5 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, to bedrock, for a reference monument, bears N. 28°25' W., 90.0 ft. dist., with cap mkd. T20N R19W RM 90.0 FT TO COR S32 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p>

BOOK 5442

Dependent Resurvey of a Portion of the South Boundary
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS

Cor. is located on a ridge, in a boulder field; and atop a narrow rock formation, 10 X 5 X 12 ft. high.


Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

Restoring the resurvey and survey executed by
Guy H. Richardson and Hugo Price, in 1915

From the cor. of secs. 27, 28, 33, and 34 monumented with a granite stone, 28 x 9 x 6 ins., firmly set, projecting 6 ins. above ground, in a mound of stone, 4 ft. base, 1 ft. high, mkd. with 3 grooves on the E. face and 2 faint grooves on the S. face, with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, alongside the original stone, with brass cap mkd. T20N R19W S28 S27 S34 S33 1915, with a mound of stone to the W., 3 ft. base, 1 ft. high.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.

Add the marks 1991 on the brass cap and bury the orig. stone and the iron post alongside the stainless steel post.

Cor. is located at the base of a gentle E. slope, rises W. to a mountain, 850 ft. high, bears NNW and SSE, in the projection of the S. edge of Quartzite Drive, bears E., and the projection of the W. edge of Kaibab Road, bears N.

N. 0°09' E., bet. secs. 27 and 28, along the W. edge of Kaibab Road.

4.98 Point for a witness point on line bet. secs. 27 and 28.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

BOOK 5442

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">WP T20N R19W S28 S27 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
39.95	<p>The 1/4 sec. cor. of secs. 27 and 28, monumented with a granite stone, 20 x 10 x 7 ins., firmly set, projecting 7 ins. above ground, mkd. 1/4 on W. face, in a mound of stone, 4 ft. base, 1 ft. high, with an iron post, 30 ins. long, 1 in. diam., firmly set, projecting 20 ins. above ground, alongside the original stone, with brass cap mkd. S28 1/4 S27 1915, with a mound of stone to the W., 3 ft. base, 1 ft. high.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T20N R19W 1/4 S28 S27 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Add the marks T20N R19W 1991 on the brass cap and bury the orig. stone and the iron post alongside the stainless steel post.</p> <p>Cor. is located on the W. edge of Kaibab Road, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 0°11' E., beginning new measurement.</p>
30.50	<p>Center of wash, 50 lks. wide, 2 ft. deep, drains SE.</p>
31.60	<p>Center of wash, 6 lks. wide, 1 ft. deep, drains SE.</p>
39.98	<p>The cor. of secs. 21, 22, 27, and 28, monumented with a granite stone, 15 x 9 ins., firmly set, projecting 8 ins. from exposed granite bedrock, mkd. with 3 grooves on the E. face and 2 grooves on the S. face, in a scattered mound of stone. The iron post, set in 1915, 2 ins. diam., 36 ins. long, was found lying loosely nearby, with brass cap mkd. T20N R19W S21 S22 S27 S28 1915.</p> <p>At the cor. point</p>

BOOK 5442

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, in the top of the original granite stone, with top mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T20N</td> <td>R19W</td> </tr> <tr> <td>S21</td> <td>S22</td> </tr> <tr> <td>S28</td> <td>S27</td> </tr> <tr> <td colspan="2">1992</td> </tr> </table> </div> <p>Deposit a magnet, 7/8 in. diam., 1 in. long, in the drill hole, beneath the brass tablet.</p> <p>Remove the marks from the orig. stone and remove the iron post from the area.</p> <p>Cor. is located 70 lks. N. of the top of a low ridge, bears E. and W., in the projection of the west edge of a trail road, bears N., and in the projection of the S. edge of Ash Drive.</p> <hr/>	T20N	R19W	S21	S22	S28	S27	1992	
T20N	R19W								
S21	S22								
S28	S27								
1992									
40.00	<p>N. 0°02' E., bet. secs. 21 and 22, along the W. edge of Kaibab Road.</p> <p>The 1/4 sec. cor. of secs. 21 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 30 ins. above ground, in a mound of stone 4 ft. base, to top, with brass cap mkd. S21 1/4 S22 1915.</p> <p>Add the marks T20N R19W 1991 on the brass cap.</p> <hr/>								
39.99	<p>N. 0°05' E., beginning new measurement.</p> <p>The cor. of secs. 15, 16, 21 and 22, monumented with a granite stone, 20 x 10 x 8 ins., firmly set, projecting 3 ins. above ground, in a mound of stone, 4 ft. base, 1 1/2 ft. high, mkd. with 3 grooves on the E. face and 3 grooves on the S. face, with an iron post, 30 ins. long, 2 ins. diam., firmly set, projecting 6 ins. above ground, alongside the original stone, with brass cap mkd. T20N R19W S16 S15 S21 S22 1915.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								

BOOK 5442

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T20N R19W</td> </tr> <tr> <td>S16</td> <td>S15</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S21</td> <td>S22</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Add the marks 1991 on the brass cap and bury the orig. stone and the iron post alongside the stainless steel post.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 55°27' E., 93.1 ft. dist., with cap mkd. T20N R19W RM 93.1 FT TO COR S15 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Monument is located 1 ch. N. of the N. edge of Aquarius Drive, graded, 39 lks. wide, bears E. and W.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 59°03' E., 140.3 ft. dist., with cap mkd. T20N R19W RM 140.3 FT TO COR S22 1991, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Monument is located 64 lks. S. of the S. edge of Aquarius Drive.</p> <p>Rebuild the supporting mound of stone, 4 ft. base, to top.</p> <p>Cor. is located 14 lks. W. of the center of Kaibab Road, bears N. and S.</p> <hr/> <p>N. 0°08' W., bet. secs. 15 and 16, along the W. edge of Kaibab Road.</p> <p>9.53 Point for a witness point on line bet. secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">WP</td> </tr> <tr> <td>T20N</td> <td>R19W</td> </tr> <tr> <td>S16</td> <td>S15</td> </tr> <tr> <td colspan="2" style="text-align: center;">1992</td> </tr> </table>	T20N R19W		S16	S15			S21	S22	1991		WP		T20N	R19W	S16	S15	1992	
T20N R19W																			
S16	S15																		
S21	S22																		
1991																			
WP																			
T20N	R19W																		
S16	S15																		
1992																			

BOOK 5442

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>29.68</p> <p>39.92</p>	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 14 lks. W. of the W. edge of Kaibab Road, bears N. and S.</p> <p>Point for a witness point on line bet. secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> WP1 T20N R19W S16 S15 1992 </p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 18 lks. W. of the W. edge of Kaibab Road, bears N. and S.</p> <p>The 1/4 sec. cor. of secs. 15 and 16, monumented with a granite stone, 14 x 12 x 8 ins., firmly set, projecting 5 ins. above ground, mkd. 1/4 on W. face, in a mound of stone, 4 ft. base, 1 ft. high, with an iron post, 30 ins. long, 1 in. diam., firmly set, projecting 12 ins. above ground, alongside the original stone, with brass cap mkd. S16 1/4 S15 1915, with a mound of stone to the W., 4 ft. base, 1 ft. high.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;"> T20N R19W 1/4 S16 S15 1991 </p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Add the marks T20N R19W 1991 on the brass cap and bury the orig. stone and the iron post alongside the stainless steel post.</p> <p>Cor. is located 23 lks. W. of the junction of the center of Kaibab Road, bears N. and S., and the center of Ute Drive, bears E.</p> <hr style="width: 20%; margin: 10px auto;"/>
---	---

BOOK 5442

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS																
7.51	<p>N. 0°07' W., beginning new measurement.</p> <p>Point for AP 12, on the Mount Nutt Wilderness Area Bdy.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R19W</p> <table border="0"> <tr> <td>S16</td> <td> </td> <td>S15</td> </tr> <tr> <td colspan="3">/</td> </tr> <tr> <td>AP 12</td> <td> </td> <td></td> </tr> <tr> <td>MNWA</td> <td> </td> <td></td> </tr> <tr> <td colspan="3">1992</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 10 lks. W. of the center of Kaibab Road, bears N. and S., and 16 lks. S. of the S. edge of a trail road, bears N. 74 3/4° W.</p>	S16		S15	/			AP 12			MNWA			1992		
S16		S15														
/																
AP 12																
MNWA																
1992																
40.03	<p>The cor. of secs. 9, 10, 15 and 16, monumented with a granite stone, 20 x 12 x 10 ins., firmly set, projecting 12 ins. above ground, with 3 grooves on E. face, and 4 grooves on S. face, in a mound of stone, 4 ft. base, 6 ins. high, with an iron post, 30 ins. long, 2 ins. diam., firmly set, projecting 6 ins. above ground, in a scattered mound of stone, alongside the original stone, with brass cap mkd. T20N R19W S9 S10 S15 S16 1915, with a mound of stone, 4 ft. base, 4 ft. high, to the W.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R19W</p> <table border="0"> <tr> <td>S9</td> <td> </td> <td>S10</td> </tr> <tr> <td colspan="3">/</td> </tr> <tr> <td>S16</td> <td> </td> <td>S15</td> </tr> <tr> <td colspan="3">1991</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Add the marks 1991 on the brass cap and bury the orig. stone and the iron post alongside the stainless steel post.</p> <p>Cor. is located 20 lks. W. of the center of Kaibab Road, bears N. and S., and 32 lks. S. of the center of Chemehuevi Drive, bears E. and W.</p>	S9		S10	/			S16		S15	1991					
S9		S10														
/																
S16		S15														
1991																

BOOK 5442

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of Tp., hereinbefore described.</p>
	<p>N. 0°01' W., bet. secs. 32 and 33.</p>
39.97	<p>The 1/4 sec. cor. of secs. 32 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, supported in a mound of stone, 4 ft. base, 1 ft. high, with a mound of stone to the W., 4 ft. base, 3 ft. high, with brass cap mkd. S32 1/4 S33 1915.</p> <p>Add the marks T20N R19W 1991 on the brass cap</p> <hr/> <p>N. 0°01' W., beginning new measurement.</p>
40.09	<p>The cor. of secs. 28, 29, 32 and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above ground, supported in a mound of stone, 4 ft. base, 1 ft. high, with a mound of stone to the W., 4 ft. base, 2 ft. high, with brass cap mkd. T20N R19W S29 S28 S33 S32 1915.</p> <p>Add the marks 1991 on the brass cap</p> <p>Cor. is located on a steep NE slope, rises W. to a narrow ridge, 360 ft. high, bears SE and NW.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 89°39' W., bet. secs. 28 and 33.</p>
39.99	<p>The 1/4 sec. cor. of secs. 28 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 36 ins. above ground, supported in a mound of stone, 5 ft. base, 2 ft. high, with brass cap mkd. S28 1/4 S33 1915.</p> <p>Add the marks T20N R19W 1991 on the brass cap</p> <p>Rebuild the supporting mound of stone, 5 ft. base, to top.</p> <hr/> <p>S. 89°40' W., beginning new measurement.</p>
39.72	<p>The cor. of secs. 28, 29, 32 and 33.</p> <hr/> <p>N. 1°49' W., bet. secs. 28 and 29.</p>

BOOK 5442

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

<p>CHAINS 40.03</p>	<p>True point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate dist.; the original witness cor. was found lying disturbed atop the ground, true point falls on top of a rock formation, 120 ft. high, with sheer vertical walls, impracticable to monument.</p> <p>From this point, the point selected for a new witness cor., bears East, 8.08 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. WC T20N R19W 1/4 S29 S28 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Cor. is located 25 lks. E. of the base of a sheer granite cliff, 120 ft. high, bears N. and S., and 92 lks. SSE of the mouth of a cave, 5 ft. high x 9 ft. wide x 7 ft. deep.</p> <p>From the true point, the original iron post, 1 in. diam., 36 ins. long, lying disturbed atop the ground, with brass cap mkd. S29 1/4 S28 WC 1915, bears N. 85°17' E., 7.68 chs. dist. Remove the original iron post.</p>										
<p>80.06</p>	<p>Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T20N</td> <td>R19W</td> </tr> <tr> <td>S20</td> <td>S21</td> </tr> <tr> <td colspan="2" style="text-align: center;">— —</td> </tr> <tr> <td>S29</td> <td>S28</td> </tr> <tr> <td colspan="2" style="text-align: center;">1992</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on the steep NE slope of a mountain, 800 ft. high, bears SE and NW; 35 lks. N. of a wash, 8 lks. wide, 3 ft. deep, drains ENE; and 460 lks. E. of the base of a sheer granite cliff 200 ft. high, bears N. and S.</p> <p>From this cor. point, a rebar, 5/8 in. diam., firmly set, in a mound of stone, 4 ft. base, to top, projecting 12 ins. above ground, with an aluminum cap stamped LS 21061 S20 S21 S28 S29, established by Charles K. Dewald, R.L.S. 21061, in 1990, bears S. 89°57' E., 2.51 chs. dist. Established using improper procedures and is not utilized in the course of this resurvey.</p>	T20N	R19W	S20	S21	— —		S29	S28	1992	
T20N	R19W										
S20	S21										
— —											
S29	S28										
1992											

BOOK 5442

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	From the cor. of secs. 21, 22, 27 and 28.
	S. 89°47' W., bet. secs. 21 and 28, along the S. edge of a trail road.
0.76	A rebar, 1/2 in. diam., firmly set, projecting 6 ins. above ground, with a plastic cap stamped LS 21061, bears N., 106 lks. dist.
1.06	A rebar, 1/2 in. diam., firmly set, projecting 4 ins. above ground, with a plastic cap stamped LS 21061, bears N., 76 lks. dist.
16.59	Point for AP 1, on the Mount Nutt Wilderness Area Bdy.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R19W S21</p> <hr style="width: 50px; margin: 0 auto;"/> <p>AP 1 S28 MNSA 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on the S. edge of a trail road, bears E. and S. 86 3/4° W.</p>
18.52	Point for AP 3, on the Mount Nutt Wilderness Area Bdy.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R19W S21</p> <hr style="width: 50px; margin: 0 auto;"/> <p>S28 AP 3 MNSA 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on the S. edge of a trail road, bears S. 87° E. and W.</p>
24.75	Point for AP 4, on the Mount Nutt Wilderness Area Bdy.

BOOK 5442

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R19W S21</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">/ AP 4 S28 MNWA 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on the S. edge of a trail road, bears E. and S. 73 1/2° W.</p> <p>27.67 Point for AP 6, on the Mount Nutt Wilderness Area Bdy.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R19W S21</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S28 AP 6 / MNWA 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on the S. edge of a trail road, bears S. 70 1/4° E. and W.</p> <p>35.39 Point for AP 7, on the Mount Nutt Wilderness Area Bdy.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R19W S21</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">/ AP 7 S28 MNWA 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on the S. edge of a trail road, bears E. and S. 55 3/4° W.</p>
---------------	---

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

<p>CHAINS 45.01</p>	<p>The 1/4 sec. cor. of secs. 21 and 28, monumented with an iron post, 1 in. diam., 36 ins. long, firmly set, projecting 8 ins. above ground, in a mound of stone, 4 ft. base, 2 ft. high, with brass cap erroneously mkd.</p> <p style="text-align: center;">S20 1/4 ----- S29 1915</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R19W S21 1/4 ——— S28 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Remove the original iron post.</p> <p>Cor. is located 38 lks. W. of a trail road, bears SE and NW.</p> <p>From this cor. point, a rebar, 5/8 in. diam., firmly set, projecting 7 ins. above ground, with an aluminum cap stamped LS 21061 1/4 S21 S28, established by Charles K. Dewald R.L.S. 21061, in 1990, bears S. 89°53' E., 5.03 chs. dist. Established using improper procedures and is not utilized in the course of this resurvey.</p> <p style="text-align: center;">_____</p> <p>S. 89°41' W., beginning new measurement.</p> <p>37.46 The cor. of secs. 20, 21, 28 and 29.</p> <p style="text-align: center;">_____</p> <p>N. 3°30' E., bet. secs. 20 and 21.</p> <p>36.11 Point for a witness point on line bet. secs. 20 and 21..</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>
-------------------------	--

BOOK 5442

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
40.09	<p style="text-align: center;">WP T20N R19W S20 S21 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located in a low saddle atop a ridge, 250 ft. high, bears E. and W.</p> <p>The 1/4 sec. cor. of secs. 20 and 21, monumented with an iron post, 1 in. diam., firmly set, projecting 36 ins. above ground, supported in a mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. S20 1/4 S21 1915.</p> <p>Add the marks T20N R19W 1991 on the brass cap</p> <p>Rebuild the supporting mound of stone, 4 ft. base, to top.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>North, beginning new measurement.</p>
28.76	<p>Point for a witness point on line bet. secs. 20 and 21.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, on the highest point on an exposed rock outcrop, with top mkd.</p> <p style="text-align: center;">WP1 T20N R19W S20 S21 1992</p>
40.04	<p>Deposit a magnet, 7/8 in. diam., 1 in. long, in the drill hole beneath the brass tablet.</p> <p>Cor. is located on a rocky ridge, 280 ft. high, bears E. and W.</p> <p>The cor. of secs. 16, 17, 20 and 21, monumented with an iron post, 2 ins. diam., firmly set, projecting 30 ins. above ground, in a scattered mound of stone, with brass cap mkd. T20N R19W S17 S16 S21 S20 1915.</p> <p>Add the marks 1991 on the brass cap</p> <p>Rebuild the supporting mound of stone, 6 ft. base, to top.</p> <p>Cor. is located on a level bench atop a ridge, 180 ft. high, bears ENE and WSW.</p> <hr style="width: 20%; margin: 10px auto;"/>

BOOK 5442

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	From the cor. of secs. 15, 16, 21 and 22.
	S. 89°46' W., bet. secs. 16 and 21, along a wash and trail road.
13.33	Point for a witness point on line bet. secs. 16 and 21.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled with a collar of stone, with brass cap mkd.
	<p style="text-align: center;">WP T20N R19E S16</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S21 1992</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
	Cor. is located 27 lks. N. of the center of a trail road, bears E and WSW, in curve.
40.05	The 1/4 sec. cor. of secs. 16 and 21, reestablished by Charles K. Dewald, R.L.S. 21061, in 1990, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 6 ins. above ground, in a collar of stone, 5 ft. base, to top, with an aluminum cap stamped LS 21061. This is accepted as a careful and faithful reestablishment of the original cor. position.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T20N R19W S16 1/4 — S21 1992</p>
	Deposit the rebar inside the stainless steel post and a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
	<hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">S. 89°46' W., beginning new measurement.</p>
24.01	Point for a witness point on line bet. secs. 16 and 21.

BOOK 5442

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T20N R19E S16 ----- S21 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located at the base of a hill, and 330 lks. W. of the center of a wash, 3 chs. wide, 8 ft. deep, drains NE.</p>
40.05	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/>
	<p>N. 0°05' W., bet. secs. 16 and 17.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, atop a steel fence post, 5 1/2 ft. long, with brass cap mkd.</p> <p style="text-align: center;">T20N R19W 1/4 S17 S16 1992</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, bears N. 54°10' E., 39.0 ft. dist., with cap mkd. T20N R19W RM 39.0 FT TO COR 1/4 S16 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, bears N. 30°05' W., 48.1 ft. dist., with cap mkd. T20N R19W RM 48.1 FT TO COR 1/4 S17 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>

BOOK 5442

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>63.99</p> <p>78.04</p> <p>80.04</p>	<p>Cor. is located in a wash, 68 lks. wide, 4 ft. deep, drains SE.</p> <p>Point for AP 29, on the Mount Nutt Wilderness Area Bdy.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R19W</p> <p>S17 S16</p> <p>AP 29 </p> <p>MNWA</p> <p>1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 75 lks. N. of the center of a wash, 10 lks. wide, 1 ft. deep, drains E.</p> <p>Point for a witness point on line bet. secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R19W</p> <p>WP</p> <p>S17 S16</p> <p>1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 47 lks. S. of the right bank of Secret Pass Wash.</p> <p>Point for the cor. of secs. 8, 9, 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, atop a steel fence post, 5 1/2 ft. long, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R19W</p> <p>S 8 S 9</p> <hr style="width: 100%;"/> <p>S17 S16</p> <p>1992</p> </div> <p>from which</p>
--	---

BOOK 5442

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, for a reference monument, bears N. 14°25' E., 132.4 ft. dist., with cap mkd. T20N R19W RM 132.4 FT TO COR S9 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Monument is located 110 lks. E. of the left bank of Secret Pass Wash.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, for a reference monument, bears N. 80°04' W., 54.9 ft. dist., with cap mkd. T20N R19W RM 54.9 FT TO COR S8 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Monument is located 30 lks. W. of the right bank of Secret Pass Wash.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located in Secret Pass Wash, 1 ch. wide, 1 ft. deep, drains SE.</p> <p>From this cor. point, a rebar, 5/8 in. diam., 18 ins. long, bent and lying horizontal, 21 ins. below the surface of the ground, with iron wire wrapped 3 ins. below the top, unknown origin, bears SSW, 4.2 lks. dist.</p> <p>From this same cor. point, a galvanized steel pipe, 1 1/4 ins. diam., firmly set, 2 ins below the surface of the ground, unknown origin, bears SE, 7.8 lks. dist. A rebar, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with a plastic cap mkd. HOLMQUIST RLS 25074, reestablished by Rand W. Holmquist, R.L.S. 25074, in 1992, using improper procedures, was found alongside the steel pipe. Subsequent to completion of this survey, Holmquist remonumented this rebar with a brass tablet, 3 ins. diam., in concrete, mkd. HOLMQUIST T20N 8 9 16 17 R19W 1992 RLS 25074.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 89°49' W., bet. secs. 9 and 16, along the S. edge of Chemehuevi Drive.</p> <p>40.00 The 1/4 sec. cor. of secs. 9 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, in a scattered mound of stone, with brass cap mkd. S9 1/4 S16 1915.</p> <p>Add the marks T20N R19W 1991 on the brass cap</p>
--------	---

BOOK 5442

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Rebuild the supporting mound of stone, 4 ft. base, to top.</p> <hr/>
	<p>S. 89°53' W., beginning new measurement.</p>
4.99	<p>A rebar, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with attached aluminum tags mkd. J.T. JORDAN ENG. INC., P.O. DRAWER 69, KINGMAN ARIZ. ARIZ. NO. 1219, 2095, CALIF. NO. 2620, NEVADA NO. 1486 T20N, R19W, S9, UNIT 7, BLOCK J, LOT 9, and J.T. JORDAN ENG. INC., P.O. DRAWER 69, KINGMAN ARIZ. ARIZ. NO. 1219, 2095, CALIF. NO. 2620, NEVADA NO. 1486 T20N, R19W, S9, UNIT 7, BLOCK J, LOT 8, and plastic cap mkd. HOLMQUIST RLS 25074; bears N., 60 lks. dist.</p>
24.99	<p>A rebar, 5/8 in. diam., firmly set, projecting 8 ins. above ground, with attached aluminum tags mkd. J.T. JORDAN ENG. INC., P.O. DRAWER 69, KINGMAN ARIZ. ARIZ. NO. 1219, 2095, CALIF. NO. 2620, NEVADA NO. 1486 T20N, R19W, S9, UNIT 7, BLOCK H, LOT 5, and J.T. JORDAN ENG. INC., P.O. DRAWER 69, KINGMAN ARIZ. ARIZ. NO. 1219, 2095, CALIF. NO. 2620, NEVADA NO. 1486 T20N, R19W, S9, UNIT 7, BLOCK H, LOT 6; bears N., 58 lks. dist.</p>
29.69	<p>A rebar, 5/8 in. diam., firmly set, projecting 10 ins. above ground, bears N., 57 lks. dist.</p>
34.99	<p>A rebar, 5/8 in. diam., firmly set, projecting 1 in. above ground, with plastic cap mkd. HOLMQUIST RLS 25074, bears N., 58 lks. dist.</p>
40.03	<p>The cor. of secs. 8, 9, 16 and 17.</p> <hr/>
	<p>N. 0°01 E., bet. secs. 8 and 9, through Secret Pass Wash, thence along Tom Reed Road.</p>
4.96	<p>A rebar, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with plastic cap mkd. HOLMQUIST RLS 25074, bears E., 67 lks. dist.</p>
9.96	<p>A rebar, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with attached aluminum tags mkd. J.T. JORDAN ENG. INC., P.O. DRAWER 69, KINGMAN ARIZ. ARIZ. NO. 1219, 2095, CALIF. NO. 2620, NEVADA NO. 1486 T20N, R19W, S9, UNIT 7, BLOCK G, LOT 5, and J.T. JORDAN ENG. INC., P.O. DRAWER 69, KINGMAN ARIZ. ARIZ. NO. 1219, 2095, CALIF. NO. 2620, NEVADA NO. 1486 T20N, R19W, S9, UNIT 7, BLOCK G, LOT 4, and plastic cap mkd. HOLMQUIST RLS 25074, bears E., 67 lks. dist.</p>
11.64	<p>Point for a witness point on line bet. secs. 8 and 9.</p>

BOOK 5442

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R19W WP S 8 S 9 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 116 lks. N. of the left bank of Secret Pass Wash.</p>
14.96	<p>A rebar, 5/8 in. diam., firmly set, projecting 5 ins. above ground, with plastic cap mkd. HOLMQUIST RLS 25074, bears E., 66 lks. dist.</p>
19.96	<p>A rebar, 5/8 in. diam., firmly set, projecting 1 in. above ground, with plastic cap mkd. HOLMQUIST RLS 25074, bears E., 65 lks. dist.</p>
24.96	<p>Center of a mound of stone, determined by a well defined hole, with a rebar, 5/8 in. diam., 18 ins. long, lying disturbed atop the ground, alongside, with plastic cap mkd. HOLMQUIST RLS 25074, bears E., 49 lks. dist.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R19E 1/4 S8 S9 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on the E. edge of Tom Reed Road, bears N. and SSW; and 5.35 chs. W. of a sheer cliff face, 300 ft. high, bears N. and S.</p>
80.04	<p>The cor. of secs. 4, 5, 8, and 9, monumented with an iron post, 2 ins. diam., firmly set, projecting 36 ins. above ground, supported in a mound of stone, 4 ft. base, to top, with a mound of stone to the W., 3 ft. base, 2 ft. high, with brass cap mkd. T20N R19W S5 S4 S9 S8 1915.</p>

BOOK 5442

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>39.92</p>	<p>Add the marks 1992 on the brass cap</p> <p>Cor. is located on the W. side of a steep ridge, 300 ft. high, bears NW and SE.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10, monumented with a granite stone, 21 x 12 x 12 ins., firmly set, projecting 6 ins. above ground, in a collar of stone, mkd. with 3 grooves on the E. face and 5 faint grooves on the S. face, with an iron post, 30 ins. long, 2 ins. diam., firmly set, projecting 9 ins. above ground, alongside the original stone, with brass cap mkd. T20N R19W S4 S3 S10 S9 1915.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T20N</td> <td>R19W</td> </tr> <tr> <td>S4</td> <td>S3</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S9</td> <td>S10</td> </tr> <tr> <td colspan="2" style="text-align: center;">1992</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Add the marks 1992 on the brass cap and bury the orig. stone and the iron post alongside the stainless steel post.</p> <p>Cor. is located 21 lks. N. of the center of Hualapai Drive, bears E. and W., and 37 lks. W. of the center of Kaibab Road, bears N. and S.</p> <p>From this cor. point, the cor. of barbed wire fences, 4 strands, extending N. and E., bears NW, 1 1/2 lks. dist.</p> <p>S. 89°47' W., bet. secs. 4 and 9, along the N. edge of Hualapai Drive.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	T20N	R19W	S4	S3			S9	S10	1992	
T20N	R19W										
S4	S3										
S9	S10										
1992											

BOOK 5442

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T20N R19W S 4 1/4 — S 9 1991</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on the outside of a curve, 33 lks. NW of the intersection of Chemehuevi Drive, bears E., and Mockingbird Road, bears S.</p> <p>Thence leave Chemehuevi Drive and begin steep ascent of E. slope of mountain.</p>
78.42	<p>Point for a witness point on line bet. secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to bedrock, in a supporting mound of stone, 6 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">WP T20N R19E S 4 — S 9 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located atop a granite outcrop, on the steep E. slope of a mountain, 4 ft. below the top of a ridge.</p>
79.84	<p>The cor. of secs. 4, 5, 8 and 9.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 4 and 5, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, in a scattered mound of stone, with a mound of stone to the W., 4 ft. base, 2 ft. high, with brass cap mkd. S5 1/4 S4 1915.</p> <p>Add the marks T20N R19W 1991 on the brass cap</p> <p>Rebuild the supporting mound of stone, 4 ft. base, to top.</p> <p>Cor. is located on the gentle S. slope of a mountain; and 3 chs. N. of the center of a wash, 50 lks. wide, 3 ft. deep, drains ESE.</p> <p>N. 0°03' W., bet. secs. 4 and 5.</p>

BOOK 5442

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

<p>CHAINS 40.48</p>	<p>Point for a witness point at intersection with the Mount Nutt Wilderness Area Bdy.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="846 447 1024 636"> <tr> <td colspan="2" style="text-align: center;">WP</td> </tr> <tr> <td style="text-align: center;">T20N</td> <td style="text-align: center;">R19W</td> </tr> <tr> <td style="text-align: center;">S 5</td> <td style="text-align: center;">S 4</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">MN</td> <td style="text-align: center;">WA</td> </tr> <tr> <td colspan="2" style="text-align: center;">1992</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 88 lks. W. of the center of a wash, 18 lks. wide, 2 ft. deep, drains ENE.</p>	WP		T20N	R19W	S 5	S 4	-----		MN	WA	1992	
WP													
T20N	R19W												
S 5	S 4												

MN	WA												
1992													
<p>40.80</p>	<p>The closing cor. of secs. 4 and 5, at intersection with the Fifth Standard Parallel North, monumented with an iron post, 1 in. diam., firmly set, 14 ins. below the surface of the ground, with brass cap mkd. T21N R19W S33 S5 S4 CC T20N R19W 1992 1915 as described in the field notes of the dependent resurvey of a portion of the Fifth Standard Parallel North, T. 21 N., R. 19 W., executed concurrently under this same group.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 33, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. SC T21N R19W 1/4 S33 1992 as described in the field notes of the dependent resurvey of a portion of the Fifth Standard Parallel North, T. 21 N., R. 19 W., executed concurrently under this same group, bears S. 89°56' E., 3.08 chs. dist.</p>												
<p>37.42</p>	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>N. 89°52' W., bet. secs. 20 and 29.</p> <p>The 1/4 sec. cor. of secs. 20 and 29, monumented with an iron post, 1 in. diam., firmly set, projecting 36 ins. above ground, supported in a mound of stone, 4 ft. base, 24 ins. high, with brass cap mkd. S20 1/4 S29 1915.</p> <p>Add the marks T20N R19W 1991 on the brass cap</p> <p>Cor. is located in the center of a narrow, rocky drain, 9 lks. wide, 3 ft. deep, course SE, in a steep ravine.</p>												

BOOK 5442

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 89°45' W., bet. secs. 8 and 17.</p>
39.96	<p>The 1/4 sec. cor. of secs. 8 and 17, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, in a scattered mound of stone, with brass cap mkd. S8 1/4 S17 1915.</p> <p>Add the marks T20N R19W 1991 on the brass cap</p> <p>Rebuild the supporting mound of stone, 4 ft. base, to top.</p> <p>Cor. is located on the gentle NE slope of a mountain.</p> <hr/>
	<p>From the cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 19 ins. above ground, in a scattered mound of stone, with a mound of stone to the W., 3 ft. base, 2 ft. high, with brass cap mkd. T20N R19W S7 S8 S17 S18 1915.</p> <p>Add the marks 1992 on the brass cap</p> <p>Rebuild the supporting mound of stone, 3 ft. base, to top.</p> <p>S. 89°40' W., bet. secs. 7 and 18.</p>
39.92	<p>The 1/4 sec. cor. of secs. 7 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 34 ins. above ground, supported in a mound of stone, 5 ft. base, 2 ft. high, with brass cap mkd. S7 1/4 S18 1915.</p> <p>Add the marks T20N R19W 1992 on the brass cap</p> <p>Rebuild the supporting mound of stone, 5 ft. base, to top.</p> <p>Cor. is located in a narrow canyon, 10 lks. NE of the center of a dry stream bed, 20 lks. wide, 2 ft. deep, drains NW.</p> <hr/>
38.59	<p>S. 89°46' W., beginning new measurement.</p> <p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 24 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. T20N R20W R19W S12 S7 S13 S18 1992 1915 as described in the field notes of the dependent resurvey of a portion of the E. bdy., T. 20 N., R. 20 W., executed concurrently under this same group.</p> <hr/>

BOOK 5442

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0°02' W., bet. secs. 7 and 8.
39.99	The 1/4 sec. cor. of secs. 7 and 8, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, in a mound of stone, 2 ft. base, 1 ft. high, with brass cap mkd. S7 1/4 S8 1915.
	Add the marks T20N R19W 1992 on the brass cap
	Rebuild the mound of stone, 3 ft. base, to top, and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	<hr/>
	N. 0°01' E., beginning new measurement.
40.15	The cor. of secs. 5, 6, 7 and 8, monumented with an iron post, 2 ins. diam., firmly set, supported in a mound of stone, 4 ft. base, 24 ins. high, projecting 27 ins. above ground, with a mound of stone to the W., 3 ft. base, 1 1/2 ft. high, with brass cap mkd. T20N R19W S6 S5 S8 S7 1915.
	Add the marks 1992 on the brass cap
	Cor. is located atop a narrow ridge, 300 ft. high, bears N. and S.
	<hr/>
	S. 89°46' W., bet. secs. 6 and 7.
40.23	The 1/4 sec. cor. of secs. 6 and 7, monumented with an iron post, 1 in. diam., loosely set, projecting 22 ins. above ground, in a scattered mound of stone, with a mound of stone to the N., 3 ft. base, 1 1/2 ft. high, with brass cap mkd. S6 1/4 S7 1915.
	Add the marks T20N R19W 1992 on the brass cap
	Rebuild the supporting mound of stone, 3 ft. base, to top.
	Cor. is located 9 lks. N. of the center of a wash, 30 lks. wide, drains NNE; and 3 1/2 chs. SSW of a spring at the junction of three washes.
	<hr/>
	S. 89°57' W., beginning new measurement.

BOOK 5442



Dependent Resurvey of a Portion of the Subdivisional Lines
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

<p>CHAINS 38.43</p>	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 24 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. T20N R20W R19W S1 S6 S12 S7 1992 1915 as described in the field notes of the dependent resurvey of a portion of the E. bdy., T. 20 N., R. 20 W., executed concurrently under this same group.</p>
	<p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°01' E., bet. secs. 5 and 6.</p>
40.29	<p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p>
77.27	<p>The witness cor. to the closing cor. of secs. 5 and 6, monumented with an iron post, 2 ins. diam., firmly set, projecting 34 ins. above ground, supported in a mound of stone, 3 ft. base, 2 1/2 ft. high, with brass cap erroneously mkd. T20N R19W S31 S32 CC WC S6 S5 1915.</p> <p>Remove the marks S31 and add the marks 1993 on the brass cap</p> <p>Cor. is located 3 lks. W. of the base of a sheer cliff face, 400 ft. high, bears SE and NW; and on the left bank of a dry wash, 70 lks. wide, 3 ft. deep, drains SSE.</p>
81.81	<p>Intersect the Fifth Standard Parallel North.</p> <p>Point for the closing cor. of secs. 5 and 6, falls on the NE face of a sheer cliff, impracticable to monument.</p> <p>From this cor. point, the true point for the stan. 1/4 sec. cor. of sec. 32, T. 21 N., R. 19 W., not monumented, as described in the field notes of the dependent resurvey of a portion of the Fifth Standard Parallel North, T. 21 N., R. 19 W., executed concurrently under this same group, bears S. 88°57' E., 2.59 chs. dist.</p>
	<p style="text-align: center;">Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona</p>
	<p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°44' W., on the line bet. secs. 4 and 33.</p>



Metes-and-Bounds Survey of the
 Mount Nutt Wilderness Area Boundary
 T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS 40.26	The 1/4 sec. cor. of secs. 4 and 33, hereinbefore described. <hr/> S. 89°41' W., on the line bet. secs. 4 and 33.
39.55	The cor. of secs. 4, 5, 32, and 33, hereinbefore described. <hr/> <p style="text-align: center;">In Sec. 32</p> <hr/> N. 0°01' W., on the line bet. secs. 32 and 33.
39.97	The 1/4 sec. cor. of secs. 32 and 33, hereinbefore described. <hr/> N. 0°01' W., on the line bet. secs. 32 and 33.
40.09	The cor. of secs. 28, 29, 32 and 33, hereinbefore described. <hr/> <p style="text-align: center;">In Sec. 28</p> <hr/> N. 89°40' E., on the line bet. secs. 28 and 33.
39.72	The 1/4 sec. cor. of secs. 28 and 33, hereinbefore described. <hr/> N. 89°39' E., on the line bet. secs. 28 and 33.
39.99	The cor. of secs. 27, 28, 33 and 34, hereinbefore described. <hr/> N. 0°09' E., on the line bet. secs. 27 and 28.
4.98	The witness point on line bet. secs. 27 and 28, hereinbefore described.
39.95	The 1/4 sec. cor. of secs. 27 and 28, hereinbefore described. <hr/> N. 0°11' E., on the line bet. secs. 27 and 28.
39.98	The cor. of secs. 21, 22, 27 and 28, hereinbefore described. <hr/> S. 89°47' W., on the line bet. secs. 21 and 28.
16.59	AP 1, on the line bet. secs. 21 and 28, hereinbefore described. <hr/>


Metes-and-Bounds Survey of the
 Mount Nutt Wilderness Area Boundary
 T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
1.04	<p>S. 86°55' W., on line 1-2, along the S. edge of a trail road.</p> <p>Point for AP 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R19W S28</p>  <p>AP 2 MNWA 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 2 lks. S. of the S. edge of a trail road, bears E. and W.</p>
0.90	<p>N. 86°56' W., on line 2-3, along the S. edge of a trail road.</p> <p>AP 3, on line bet. secs. 21 and 28, hereinbefore described.</p>
6.23	<p>S. 89°47' W., on the line bet. secs. 21 and 28.</p> <p>AP 4, hereinbefore described.</p>
1.69	<p>S. 73°38' W., on line 4-5, along the S. edge of a trail road.</p> <p>Point for AP 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R19W S28</p>  <p>AP 5 MNWA 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 19 lks. S. of the S. edge of a trail road, bears ENE and WNW.</p>

Metes-and-Bounds Survey of the
 Mount Nutt Wilderness Area Boundary
 T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	<p>N. 70°11' W., bet. on line 5-6, along the S. edge of a trail road.</p>
1.38	<p>AP 6, on line bet. secs. 21 and 28, hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°47' W., on the line bet. secs. 21 and 28.</p>
7.72	<p>AP 7, hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 55°45' W., on line 7-8, along the S. edge of a trail road.</p>
2.39	<p>Point for AP 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T20N R19W S28  AP 8 MNWA 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on the S. edge of a trail road, bears ENE and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 87°14' W., on line 8-9, along the S. edge of a trail road.</p>
3.15	<p>Point for AP 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T20N R19W S28  AP 9 MNWA 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 9 lks. S. of the S. edge of a trail road, bears E. and WNW.</p> <hr style="width: 20%; margin: 10px auto;"/>

Metes-and-Bounds Survey of the
 Mount Nutt Wilderness Area Boundary
 T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
3.56	<p>N. 78°21' W., on line 9-10, along the S. edge of a trail road.</p> <p>Point for AP 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R19W S28  AP 10 MNWA 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 5 lks. S. of the S. edge of a trail road, bears ENE and NW.</p>
1.26	<p>N. 53°52' W., bet. on line 10-11, along the S. edge of a trail road.</p> <p>Point for AP 11, identical with the 1/4 sec. cor. of secs. 21 and 28, hereinbefore described.</p>
37.46	<p>S. 89°41' W., on the line bet. secs. 21 and 28.</p> <p>The cor. of secs. 20, 21, 28 and 29, hereinbefore described.</p>
	<p style="text-align: center;">In Sec. 20</p>
36.11	<p>N. 3°30' E., on the line bet. secs. 20 and 21.</p> <p>The witness point on line bet. secs. 20 and 21, hereinbefore described.</p>
40.09	<p>The 1/4 sec. cor. of secs. 20 and 21, hereinbefore described.</p>
28.76	<p>North, bet. secs. 20 and 21, beginning new measurement.</p> <p>The witness point on line bet. secs. 20 and 21, hereinbefore described.</p>
40.04	<p>The cor. of secs. 16, 17, 20 and 21, hereinbefore described.</p>

Metes-and-Bounds Survey of the
 Mount Nutt Wilderness Area Boundary
 T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona


CHAINS	In Sec. 16

	N. 89°46' E., on the line bet. secs. 16 and 21.
16.04	The witness point on line bet. secs. 16 and 21, hereinbefore described.
40.05	The 1/4 sec. cor. of secs. 16 and 21, hereinbefore described.



	N. 89°46' E., on the line bet. secs. 16 and 21.
26.72	The witness point on line bet. secs. 16 and 21, hereinbefore described.
40.05	The cor. of secs. 15, 16, 21 and 22, hereinbefore described.

	N. 0°08' W., on the line bet. secs. 15 and 16.
9.53	The witness point on line bet. secs. 15 and 16, hereinbefore described.
29.68	The witness point on line bet. secs. 15 and 16, hereinbefore described.
39.92	The 1/4 sec. cor. of secs. 15 and 16, hereinbefore described.




	N. 0°07' W., on the line bet. secs. 15 and 16.
7.51	AP 12, on the line bet. secs. 15 and 16, hereinbefore described.

	N. 74°46' W., on line 12-13.
1.57	Point for AP 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T20N R19W S16  AP13 MNWA 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.

Metes-and-Bounds Survey of the
 Mount Nutt Wilderness Area Boundary
 T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	<p>Cor. is located 30 lks. S. of the S. edge of a trail road, bears ESE and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 82°01' W., on line 13-14.</p> <p>2.00 Point for AP 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T20N R19W S16</p>  <p>AP14 MNWA 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 33 lks. S. of the S. edge of a trail road, bears ENE and WNW.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 72°17' W., on line 14-15.</p> <p>2.26 Point for AP 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T20N R19W S16</p>  <p>AP15 MNWA 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 33 lks. S. of the S. edge of a trail road, bears E. and WNW.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 73°04' W., on line 15-16.</p> <p>3.18 Point for AP 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
--------	---

Metes-and-Bounds Survey of the
 Mount Nutt Wilderness Area Boundary
 T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T20N R19W S16  AP16 MNWA 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 35 lks. SE of the SE edge of a trail road, bears NE and SW, in curve.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 22°18' W., on line 16-17.</p>
<p>3.23</p>	<p>Point for AP 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R19W S16  AP17 MNWA 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 1 ch. S. of the SE edge of a trail road, bears NE and WSW, in curve.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 80°38' W., on line 17-18.</p>
<p>6.56</p>	<p>Point for AP 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R19W S16  AP18 MNWA 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>



Metes-and-Bounds Survey of the
 Mount Nutt Wilderness Area Boundary
 T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
5.21	<p>Cor. is located 44 lks. S. of the S. edge of a trail road, bears E. and W.</p> <hr style="width: 25%; margin: 10px auto;"/> <p>N. 74°52' W., on line 18-19.</p> <p>Point for AP 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T20N R19W S16 AP19 MNWA 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
3.92	<p>Cor. is located 27 lks. S. of the S. edge of a trail road, bears ENE and WNW.</p> <hr style="width: 25%; margin: 10px auto;"/> <p>N. 76°32' W., on line 19-20.</p> <p>Point for AP 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T20N R19W S16 AP20 MNWA 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
14.05	<p>Cor. is located 31 lks. S. of the S. edge of a trail road, bears E. and W.</p> <hr style="width: 25%; margin: 10px auto;"/> <p>N. 83°40' W., on line 20-21.</p> <p>Point for AP 21.</p>

Metes-and-Bounds Survey of the
 Mount Nutt Wilderness Area Boundary
 T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T20N R19W S16 /</p> <p style="text-align: center;">AP21 MNSA 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 29 lks. S. of the S. edge of a trail road, bears E. and W.</p> <p style="text-align: center;">_____</p> <p>N. 83°32' W., on line 21-22.</p> <p>9.11 Point for AP 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R19W S16 /</p> <p style="text-align: center;">AP22 MNSA 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 31 lks. S. of the S. edge of a trail road, bears E. and W.</p> <p style="text-align: center;">_____</p> <p>N. 79°16' W., on line 22-23.</p> <p>4.14 Point for AP 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R19W S16 /</p> <p style="text-align: center;">AP23 MNSA 1992</p>
--------	---

Metes-and-Bounds Survey of the
 Mount Nutt Wilderness Area Boundary
 T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>8.43</p> <p>2.18</p> <p>7.26</p>	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 35 lks. S. of the S. edge of a trail road, bears ENE and NW.</p> <hr style="width: 25%; margin: 10px auto;"/> <p>N. 53°39' W., on line 23-24.</p> <p>Point for AP 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R19W S16  AP24 MNA 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 32 lks. S. of the S. edge of a trail road, bears ENE and WNW.</p> <hr style="width: 25%; margin: 10px auto;"/> <p>N. 79°53' W., on line 24-25.</p> <p>Point for AP 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R19W S16  AP25 MNA 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 33 lks. S. of the S. edge of a trail road, bears ENE and WNW.</p> <hr style="width: 25%; margin: 10px auto;"/> <p>N. 66°18' W., on line 25-26.</p> <p>Point for AP 26.</p>
---	---




Metes-and-Bounds Survey of the
 Mount Nutt Wilderness Area Boundary
 T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T20N R19W S16 AP26 MNSA 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 32 lks. S. of the S. edge of a trail road, bears ESE and NW.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 59°12' W., on line 26-27.</p> <p>5.34 Point for AP 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T20N R19W S16 AP27 MNSA 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 16 lks. S. of the S. edge of a trail road, bears ENE and W., and 114 lks. SE of Peterson Well.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°09' W., on line 27-28.</p> <p>2.51 Point for AP 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T20N R19W S16 AP28 MNSA 1992</p> </div>
--------	--

Metes-and-Bounds Survey of the
 Mount Nutt Wilderness Area Boundary
 T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 40 lks. WSW of the S. edge of a trail road, bears N. and E., in curve.</p> <hr/> <p>N. 58°10' W., on line 28-29.</p>
6.00	<p>AP 29, on line bet. secs. 16 and 17, hereinbefore described.</p> <hr/> <p>N. 0°05' W., on the line bet. secs. 16 and 17.</p>
14.05	<p>The witness point on line bet. secs. 16 and 17, hereinbefore described.</p>
16.05	<p>The cor. of secs. 8, 9, 16 and 17, hereinbefore described.</p> <hr/> <p style="text-align: center;">In Sec. 8</p> <hr/> <p>N. 0°01' E., on the line bet. secs. 8 and 9.</p>
11.64	<p>The witness point on line bet. secs. 8 and 9, hereinbefore described.</p>
40.02	<p>The 1/4 sec. cor. of secs. 8 and 9, hereinbefore described.</p>
80.04	<p>The cor. of secs. 4, 5, 8 and 9, hereinbefore described.</p> <hr/> <p style="text-align: center;">In Sec. 4</p> <hr/> <p>N. 89°47' E., on the line bet. secs. 4 and 9.</p>
1.42	<p>The witness point on line bet. secs. 4 and 9, hereinbefore described.</p>
39.92	<p>Point for AP 30, identical with the 1/4 sec. cor. of secs. 4 and 9, hereinbefore described.</p> <hr/> <p>N. 43°26' E., on line 30-31.</p>
0.98	<p>Point for AP 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, to bedrock, in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p>

Metes-and-Bounds Survey of the
Mount Nutt Wilderness Area Boundary
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T20N R19W MNWA AP31</p>  <p style="text-align: right;">S 4 1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 48 lks. N. of the N. edge of Hualapai Drive, bears E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°39' E., on line 31-32.</p>
13.95	<p>Point for AP 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R19W MNWA AP32</p>  <p style="text-align: right;">S 4</p> <p style="text-align: center;">1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 46 lks. N. of the N. edge of Hualapai Drive, bears E. and W., and 43 lks. W. of the W. edge of a trail road, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 10°07' W., on line 32-33.</p>
1.90	<p>Point for AP 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R19W MNWA AP33</p>  <p style="text-align: right;">S 4</p> <p style="text-align: center;">1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>

Metes-and-Bounds Survey of the
 Mount Nutt Wilderness Area Boundary
 T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	<p>Cor. is located 44 lks. W. of the W. edge of a trail road, bears SSE and NW.</p> <hr style="width: 25%; margin: 10px auto;"/> <p>N. 31°18' W., on line 33-34.</p> <p>2.99 Point for AP 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T20N R19W MNWA AP34 \ S 4</p> </div> <p style="text-align: center;">1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 45 lks. W. of the W. edge of a trail road, bears N. and SSE.</p> <hr style="width: 25%; margin: 10px auto;"/> <p>N. 14°38' W., on line 34-35.</p> <p>3.55 Point for AP 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T20N R19W MNWA AP35 \ S 4</p> </div> <p style="text-align: center;">1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 52 lks. W. of the W. edge of a trail road, bears N. and S.</p> <hr style="width: 25%; margin: 10px auto;"/> <p>N. 5°10' W., on line 35-36.</p> <p>4.50 Point for AP 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
--------	--

Metes-and-Bounds Survey of the
Mount Nutt Wilderness Area Boundary
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T20N R19W MNWA \ S 4 AP36</p> <p style="text-align: center;">1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 46 lks. W. of the W. edge of a trail road, bears S. and NW.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 10°17' W., on line 36-37.</p>
9.29	<p>Point for AP 37.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R19W MNWA \ S 4 AP37</p> <p style="text-align: center;">1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 46 lks. W. of the W. edge of a trail road, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 17°41' W., on line 37-38.</p>
11.24	<p>Point for AP 38.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R19W MNWA \ S 4 AP38</p> <p style="text-align: center;">1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>

Metes-and-Bounds Survey of the
 Mount Nutt Wilderness Area Boundary
 T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	<p>Cor. is located 42 lks. W. of the W. edge of a trail road, bears NNW and S.</p> <hr style="width: 25%; margin: 10px auto;"/> <p>N. 18°50' W., on line 38-39.</p>
2.56	<p>Point for AP 39.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T20N R19W MNWA AP39 } S 4</p> </div> <p style="text-align: center;">1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 52 lks. W. of the W. edge of a trail road, bears N. and SSE.</p> <hr style="width: 25%; margin: 10px auto;"/> <p>N. 16°07' E., on line 39-40.</p>
3.06	<p>Point for AP 40.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T20N R19W MNWA AP40 } S 4</p> </div> <p style="text-align: center;">1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 45 lks. W. of the W. edge of a trail road, bears N. and S.</p> <hr style="width: 25%; margin: 10px auto;"/> <p>N. 19°02' W., on line 40-41.</p>
4.13	<p>Point for AP 41.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Metes-and-Bounds Survey of the
 Mount Nutt Wilderness Area Boundary
 T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">T20N R19W MNWA AP41 S 4</p> <p style="text-align: center;">1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 44 lks. W. of the W. edge of a trail road, bears SSE and NNW.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 35°25' W., on line 41-42.</p> <p>5.30 Point for AP 42.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R19W MNWA AP42 S 4</p> <p style="text-align: center;">1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 48 lks. W. of the W. edge of a trail road, bears SSE and NNW.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 23°43' W., on line 42-43.</p> <p>3.20 Point for AP 43.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R19W MNWA AP43 S 4</p> <p style="text-align: center;">1992</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
--------	---

Metes-and-Bounds Survey of the
Mount Nutt Wilderness Area Boundary
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona



<p>CHAINS</p> <p>12.53</p>	<p>Cor. is located 49 lks. W. of the W. edge of a trail road, bears SSE and N.</p> <hr/> <p>N. 25°49' W., on line 43-44.</p> <p>Point for AP 44.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R19W MNWA AP44 S 4</p> <p>1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
<p>4.43</p>	<p>Cor. is located 56 lks. W. of the W. edge of a trail road, bears SSE and NNW.</p> <hr/> <p>N. 30°57' W., on line 44-45.</p> <p>Point for AP 45.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R19W MNWA AP45 S 4</p> <p>1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
<p>2.36</p>	<p>Cor. is located 49 lks. W. of the W. edge of a trail road, bears SE and NW.</p> <hr/> <p>N. 7°05' W., on line 45-46.</p> <p>Point for AP 46.</p>

Metes-and-Bounds Survey of the
Mount Nutt Wilderness Area Boundary

T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T20N R19W MNWA AP46 \ S 4</p> <p>1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 46 lks. W. of the W. edge of a trail road, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 18°38' W., on line 46-47.</p> <p>4.16 Point for AP 47.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T20N R19W MNWA AP47 \ S 4</p> <p>1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 50 lks. W. of the W. edge of a trail road, bears SSE and NNW.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 31°31' W., on line 47-48.</p> <p>4.18 Point for AP 48.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T20N R19W MNWA AP48 \ S 4</p> <p>1992</p> </div>
--------	---



Metes-and-Bounds Survey of the
 Mount Nutt Wilderness Area Boundary
 T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 53 lks. W. of the W. edge of a trail road, bears SE and NW.</p> <hr style="width: 25%; margin: 10px auto;"/> <p>N. 39°49' W., on line 48-49.</p>
4.79	<p>Point for AP 49.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T20N R19W MNWA AP49 S 4</p>  <p>1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 45 lks. W. of the center of a trail road, 17 lks. wide, bears SE and NW.</p> <hr style="width: 25%; margin: 10px auto;"/> <p>N. 39°59' W., on line 49-50.</p>
3.11	<p>Point for AP 50, on the southern right-of-way of Shinarump Drive.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T20N R19W S 4 AP50 MNWA</p>  <p>1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 23 lks. S. of a barbed wire fence, 4 strand, bears E. and W., 37 lks. S. of a power line, 2 strand, bears E. and W., 64 lks. S. of a the center of Shinarump Drive, graded gravel, 42 lks. wide, bears E. and W., and 74 lks. W. of the center of a trail road, 17 lks. wide, bears SE and NW.</p> <hr style="width: 25%; margin: 10px auto;"/>


Metes-and-Bounds Survey of the
 Mount Nutt Wilderness Area Boundary
 T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	<p>West, on line 50-51, along the southern right-of-way of Shinarump Drive.</p>
21.02	<p>Point for AP 51, on the southern right-of-way of Shinarump Drive.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T20N R19W S 4</p> <hr style="width: 50px; margin: 0 auto;"/> <p>AP51 MNWA</p> <p>1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 56 lks. S. of the center of Shinarump Drive, graded gravel, 38 lks. wide, bears E. and W.</p> <hr style="width: 200px; margin: 10px auto;"/> <p>N. 89°57' W., on line 51-52, along the southern right-of-way of Shinarump Drive.</p>
3.03	<p>The witness point at intersection with the line bet. 4 and 5, hereinbefore described.</p> <p>From this cor. point, the closing cor. of secs. 4 and 5, bears N. 0°03' W., 0.32 chs. dist., hereinbefore described.</p> <hr style="border: 1px solid black;"/> <div style="text-align: center; margin: 10px 0;"> <p>In Sec. 5</p> <hr style="width: 150px; margin: 0 auto;"/> </div> <p>N. 89°57' W., continuing on line 51-52, beginning new measurement.</p>
0.88	<p>Point for AP 52, on the southern right-of-way of Shinarump Drive, and on the southeast side of a school bus turnout.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T20N R19W S 5</p> <hr style="width: 50px; margin: 0 auto;"/> <p>AP52 MNWA 1992</p> </div>

Metes-and-Bounds Survey of the
Mount Nutt Wilderness Area Boundary
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>6.52</p> <p>1.65</p>	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 3 lks. S. of a barbed wire fence, 4 strands, bears ENE and WSW, and 59 lks. S. of the center of Shinarump Drive, graded gravel, 36 lks. wide, bears E. and W.</p> <hr/> <p>S. 75°24' W., on line 52-53, along the southeast side of a school bus turnout.</p> <p>Point for AP 53, on the southeast side of a school bus turnout.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R19W S 5</p>  <p>AP53 MNWA 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 3 lks. S. of the cor. of barbed wire fences, 4 strands, extending N. and ENE.</p> <hr/> <p>N. 3°36' W., on line 53-54, along the west side of a school bus turnout.</p> <p>Point for AP 54, on the west edge of a school bus turnout, and on the southern right-of-way of Shinarump Drive.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R19W S 5</p>  <p>AP54 MNWA 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
---------------------------------------	--



Metes-and-Bounds Survey of the
Mount Nutt Wilderness Area Boundary
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>29.60</p> <p>0.32</p>	<p>Cor. is located 3 lks. W. of a barbed wire fence, 4 strand, extending N. and S., and 54 lks. S. of the center of Shinarump Drive, graded gravel, 36 lks. wide, bears E. and W.</p> <hr/> <p>N. 89°56' W., on line 54-55, along the southern right-of-way of Shinarump Drive.</p> <p>Point for AP 55.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.; 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R19W</p> <p>S 5</p>  <p>AP55 MNWA 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <hr/> <p>N. 0°38' W., on line 55-56.</p> <p>Point for AP 56, identical with the stan. cor. of secs. 32 and 33, on the Fifth Standard Parallel North, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. SC T21N R19W S32 S33 1992 as described in the field notes of the dependent resurvey of a portion of the Fifth Standard Parallel North, T. 21 N., R. 19 W., executed concurrently under this same group.</p> <hr/> <p style="text-align: center;">In Sec. 7</p> <hr/> <p>From the point for AP 57, identical with AP 22, T. 20 N., R. 20 W., on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. AP22 AP57 T20N R20W MNWA S12 T20N R19W S7 1992 as described in the field notes of the dependent resurvey of a portion of the E. bdy., T. 20 N., R. 20 W., executed concurrently under this same group.</p> <p>From this cor. point, the cor. of secs. 1, 6, 7 and 12, bears N. 0°04' W., 0.71 chs. dist., hereinbefore described.</p> <p>S. 26°26' E., on line 57-58.</p>
--	--

Metes-and-Bounds Survey of the
 Mount Nutt Wilderness Area Boundary
 T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

<p>CHAINS 2.27</p>	<p>Point for AP 58.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 58 lks. E. of the E. edge of a trail road, bears SSE and NNW.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 17°04' E., on line 58-59.</p>
<p>7.26</p>	<p>Point for AP 59.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 32 lks. E. of the E. edge of a trail road, bears WSW and NNW, in curve.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 71°10' W., on line 59-60.</p>
<p>0.94</p>	<p>Point for AP 60.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>

Metes-and-Bounds Survey of the
Mount Nutt Wilderness Area Boundary
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<div style="text-align: center;"> <p>T20N R19W S 7</p>  <p>AP60 MNWA 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 50 lks. W. of the W. edge of a trail road, bears ENE and NNW.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 17°44' W., on line 60-61.</p>
<p>6.75</p>	<p>Point for AP 61.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R19W S 7</p>  <p>AP61 MNWA 1992</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 67 lks. W. of the W. edge of a trail road, bears S. and NNW.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 26°47' W., on line 61-62.</p>
<p>0.44</p>	<p>Point for AP 62, identical with AP 23, T. 20 N., R. 20 W., on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T20N R20W R19W S12 S7 MNWA AP23 AP62 1992 as described in the field notes of the dependent resurvey of a portion of the E. bdy., T. 20 N., R. 20 W., executed concurrently under this same group.</p> <p>From this cor. point, the cor. of secs. 1, 6, 7 and 12, bears N. 0°04' W., 3.17 chs. dist., hereinbefore described.</p>

T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS

Description of
Mount Nutt Wilderness Area Boundary,
T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

The following description is for informational purposes only.

Beginning at the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.

thence S. 89°44' W., on the line bet. secs. 4 and 33, 40.26 chs. dist., to the 1/4 sec. cor. of secs. 4 and 33;
 thence S. 89°41' W., on the line bet. secs. 4 and 33, 39.55 chs. dist., to the cor. of secs. 4, 5, 32 and 33;
 thence N. 0°01' W., on the line bet. secs. 32 and 33, 39.97 chs. dist. to the 1/4 sec. cor. of sec. 32 and 33;
 thence N. 0°01' W., on the line bet. secs. 32 and 33, 40.09 chs. dist. to the cor. of secs. 28, 29, 32 and 33;
 thence N. 89°40' E., on the line bet. secs. 28 and 33, 39.72 chs. dist. to the 1/4 sec. cor. of secs. 28 and 33;
 thence N. 89°39' E., on the line bet. secs. 28 and 33, 39.99 chs. dist. to the cor. of secs. 27, 28, 33 and 34;
 thence N. 0°09' E., on the line bet. secs. 27 and 28, 39.95 chs. dist. to the 1/4 sec. cor. of secs. 27 and 28;
 thence N. 0°11' E., on the line bet. secs. 27 and 28, 39.98 chs. dist. to the cor. of secs. 21, 22, 27 and 28;
 thence S. 89°47' W., on the line bet. secs. 21 and 28, 16.59 chs. dist. to Angle Point 1;
 thence S. 86°55' W., 1.04 chs. dist. to Angle Point 2;
 thence N. 86°56' W., 0.90 chs. dist. to Angle Point 3, on the line bet. secs. 21 and 28;
 thence S. 89°47' W., on the line bet. secs. 21 and 28, 6.23 chs. dist. to Angle Point 4;
 thence S. 73°38' W., 1.69 chs. dist. to Angle Point 5;
 thence N. 70°11' W., 1.38 chs. dist. to Angle Point 6, on the line bet. secs. 21 and 28;
 thence S. 89°47' W., on the line bet. secs. 21 and 28, 7.72 chs. dist. to Angle Point 7;
 thence S. 55°45' W., 2.39 chs. dist. to Angle Point 8;
 thence S. 87°14' W., 3.15 chs. dist. to Angle Point 9;
 thence N. 78°21' W., 3.55 chs. dist. to Angle Point 10;
 thence N. 53°52' W., 1.26 chs. dist. to Angle Point 11, identical with the 1/4 sec. cor. of secs. 21 and 28;
 thence S. 89°41' W., on the line bet. secs. 21 and 28, 37.46 chs. dist. to the cor. of secs. 20, 21, 28 and 29;
 thence N. 3°30' E., on the line bet. secs. 20 and 21, 40.09 chs. dist. to the 1/4 sec. cor. of secs. 20 and 21;
 thence North, on the line bet. secs. 20 and 21, 40.04 chs. dist. to the cor. of secs. 16, 17, 20 and 21;

T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	thence N. 89°46' E., on the line bet. secs. 16 and 21, 40.05 chs. dist. to the 1/4 sec. cor. of secs. 16 and 21;
	thence N. 89°46' E., on the line bet. secs. 16 and 21, 40.05 chs. dist. to the cor. of secs. 15, 16, 21 and 22;
	thence N. 0°08' W., on the line bet. secs. 15 and 16, 39.92 chs. dist. to the 1/4 sec. cor. of secs. 15 and 16;
	thence N. 0°07' W., on the line bet. secs. 15 and 16, 7.51 chs. dist. to Angle Point 12;
	thence N. 74°46' W., 1.57 chs. dist. to Angle Point 13;
	thence N. 82°01' W., 2.00 chs. dist. to Angle Point 14;
	thence N. 72°17' W., 2.26 chs. dist. to Angle Point 15;
	thence S. 73°04' W., 3.18 chs. dist. to Angle Point 16;
	thence S. 22°18' W., 3.23 chs. dist. to Angle Point 17;
	thence S. 80°38' W., 6.56 chs. dist. to Angle Point 18;
	thence N. 74°52' W., 5.21 chs. dist. to Angle Point 19;
	thence N. 76°32' W., 3.92 chs. dist. to Angle Point 20;
	thence N. 83°40' W., 14.05 chs. dist. to Angle Point 21;
	thence N. 83°32' W., 9.11 chs. dist. to Angle Point 22;
	thence N. 79°16' W., 4.14 chs. dist. to Angle Point 23;
	thence N. 53°39' W., 8.43 chs. dist. to Angle Point 24;
	thence N. 79°53' W., 2.18 chs. dist. to Angle Point 25;
	thence N. 66°18' W., 7.26 chs. dist. to Angle Point 26;
	thence N. 59°12' W., 5.34 chs. dist. to Angle Point 27;
	thence N. 89°09' W., 2.51 chs. dist. to Angle Point 28;
	thence N. 58°10' W., 6.00 chs. dist. to Angle Point 29, on the line bet. secs. 16 and 17;
	thence N. 0°05' W., on the line bet. secs. 16 and 17, 16.05 chs. dist. to the cor. of secs. 8, 9, 16 and 17;
	thence N. 0°01' E., on the line bet. secs. 8 and 9, 80.04 chs. dist. to the cor. of secs. 4, 5, 8, and 9.
	thence N. 89°47' E., on the line bet. secs. 4 and 9, 39.92 chs. dist. to Angle Point 30, identical with the 1/4 sec. cor. of secs. 4 and 9;
	thence N. 43°26' E., 0.98 chs. dist. to Angle Point 31;
	thence S. 89°39' E., 13.95 chs. dist. to Angle Point 32;
	thence N. 10°07' W., 1.90 chs. dist. to Angle Point 33;
	thence N. 31°18' W., 2.99 chs. dist. to Angle Point 34;
	thence N. 14°38' W., 3.55 chs. dist. to Angle Point 35;
	thence N. 5°10' W., 4.50 chs. dist. to Angle Point 36;
	thence N. 10°17' W., 9.29 chs. dist. to Angle Point 37;
	thence N. 17°41' W., 11.24 chs. dist. to Angle Point 38;
	thence N. 18°50' W., 2.56 chs. dist. to Angle Point 39;
	thence N. 16°07' E., 3.06 chs. dist. to Angle Point 40;
	thence N. 19°02' W., 4.13 chs. dist. to Angle Point 41;
	thence N. 35°25' W., 5.30 chs. dist. to Angle Point 42;
	thence N. 23°43' W., 3.20 chs. dist. to Angle Point 43;
	thence N. 25°49' W., 12.53 chs. dist. to Angle Point 44;
	thence N. 30°57' W., 4.43 chs. dist. to Angle Point 45;
	thence N. 7°05' W., 2.36 chs. dist. to Angle Point 46;
	thence N. 18°38' W., 4.16 chs. dist. to Angle Point 47;
	thence N. 31°31' W., 4.18 chs. dist. to Angle Point 48;
	thence N. 39°49' W., 4.79 chs. dist. to Angle Point 49;

T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS

thence N. 39°59' W., 3.11 chs. dist. to Angle Point 50;
 thence West, 21.02 chs. dist. to Angle Point 51;
 thence N. 89°57' W., 3.91 chs. dist. to Angle Point 52;
 thence S. 75°24' W., 6.52 chs. dist. to Angle Point 53;
 thence N. 3°36' W., 1.65 chs. dist. to Angle Point 54;
 thence N. 89°56' W., 29.60 chs. dist. to Angle Point 55;
 thence N. 0°38' W., 0.32 chs. dist. to Angle Point 56,
 identical with the stan. cor. of secs. 32 and 33,
 T. 21 N., R. 19 W.

From Angle Point 57, identical with Angle Point 22, T. 20 N.,
 R. 20 W., on the line bet. secs. 7 and 12, on the W. bdy. of the
 Tp.

thence S. 26°26' E., 2.27 chs. dist. to Angle Point 58;
 thence S. 17°04' E., 7.26 chs. dist. to Angle Point 59;
 thence S. 71°10' W., 0.94 chs. dist. to Angle Point 60;
 thence N. 17°44' W., 6.75 chs. dist. to Angle Point 61;
 thence N. 26°47' W., 0.44 chs. dist. to Angle Point 62,
 identical with Angle Point 23, T. 20 N., R. 20 W., on
 the line bet. secs. 7 and 12, on the W. bdy. of the Tp.

GENERAL DESCRIPTION

The land encompassed in this survey is located approximately
 17 miles w. southwest of Kingman, Arizona. The average elevation
 is 3300 ft. above sea level. The land varies from level to
 broken and rugged with numerous sheer cliffs, spires, and exposed
 volcanic outcrops. The vegetation consists of cactus, creosote,
 and sparse native grasses.

Primary access is by way of Arizona State Highway No. 68, thence
 south, 4 3/4 miles on Estrella Road to Shinarump Drive, which
 parallels the Fifth Standard Parallel North to the standard
 corner of section 32 and 33. Secondary access is by way of
 various county and private subdivision roads which parallel
 section lines.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Dallas L. Knoll III	Student Trainee
Cheryl A. Baier	Surveying Technician
Steven J. Buchanan	" "
Ted E. Cazier	" "
Belle A. Craig	" "
Clinton T. Lancaster	" "
Wallace R. Ott, Jr.	" "
Timothy F. Patro	" "
Rebecca N. Ramirez	" "
Mark R. Searles	" "
Ralph Hollins	Surveying Aid
Steven R. Walton, Jr.	" "

BOOK 5442

CERTIFICATE OF SURVEY

I, Olian T. Shockley Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 24th day of October, 1991, I have dependently resurveyed a portion of the south boundary and a portion of the subdivisional lines, and conducted a metes-and-bounds survey of the Mount Nutt Wilderness Area Boundary in Township 20 North, Range 19 West, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

07/31/1995
(Date)

Olian T. Shockley
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the south boundary and a portion of the subdivisional lines, and metes-and-bounds survey of the Mount Nutt Wilderness Area Boundary in Township 20 North, Range 19 West, Gila and Salt River Meridian, Arizona, executed by Olian T. Shockley, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

OCT 4 1995
(Date)

John C. Wilson
(Acting Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 20 N., R. 19 W., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Acting Chief Cadastral Surveyor of Arizona)~~