

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY

AND THE SUBDIVISIONAL LINES,

AND THE SUBDIVISION OF SECTIONS 5, 8 AND 18,

AND METES-AND-BOUNDS SURVEYS

IN SECTIONS 3, 5, 7, 8, 9, 17 AND 18,

TOWNSHIP 20 NORTH, RANGE 27 EAST

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

Joe R. Salazar

Cadastral Surveyor

Under Special Instructions dated January 12, 1987, approved February 17, 1987,
and Supplemental Special Instructions dated February 29, 1988, approved February 29,
1988, which provided for the surveys included under Group Number 686 and assignment
instructions dated October 19, 1992.

Survey commenced July 25, 1993
Survey completed April 23, 1997

INDEX DIAGRAM
TOWNSHIP 20 NORTH, RANGE 27 EAST,

4	6	61	5	43	4	32	3	24	2	15	1
60		58		42		32		23		14	
7	57	8	40	9	31	10	22	11	13	12	
55		55		40		30		21		12	
18	52	17	39	16	29	15	21	14	11	13	
51		51		39		29		20		10	
19	50	20	38	21	28	22	19	23	9	24	
49		48		37		28		19		8	
30	47	29	36	28	26	27	18	26	7	25	
47		46		36		26		17		7	
31	45	32	35	33	25	34	16	35	6	36	

Subdivision of sec. 5 pp. 64-66
 Subdivision of sec. 8 pp. 66-67
 Subdivision of sec. 18 pp. 67-72

Metes-and-Bounds Sur. in sec. 3 pp. 72-73
 Metes-and-Bounds Sur. in sec. 5 pp. 73-75
 Metes-and-bounds Sur. in sec. 7 pp. 75-78
 Metes-and-bounds Sur. in sec. 8 pp. 78-79
 Metes-and-Bounds Sur. in sec. 9 pp. 79
 Metes-and-Bounds Sur. in sec. 17 pp. 79-80
 Metes-and-Bounds Sur. in sec. 18 pp. 80-82

T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the west boundary and the subdivisional lines, and the subdivision of sections 5, 8 and 18 and metes-and-bounds surveys in sections 3, 5, 7, 8, 9, 17 and 18, Township 20 North, Range 27 East, Gila and Salt River Meridian, Arizona.

The Fifth Standard Parallel North through Range 27 East, and the south and west boundaries were surveyed by Frank Follman in 1882. The Fifth Standard Parallel North through Range 28 East and the east boundary were surveyed by W. R. Fitzgerald in 1882. The subdivisional lines were surveyed by Frank Follman in 1883. The Fifth Standard Parallel North through Range 28 East was resurveyed and retraced by William Strover in 1910. The Fifth Standard Parallel North through Range 28 East was dependently resurveyed by William P. Carpender and Stephen J. Malloy in 1987-94. The Fifth Standard Parallel North through Range 27 East was dependently resurveyed concurrently under Group No. 685 by William P. Carpender and Darren R. Breckenridge in 1988-94.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated January 12, 1987, and the Supplemental Special Instructions dated February 29, 1988 for Group No. 686, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of all lines were determined by the technique of static differential positioning using Ashtech models M-XII and MS-XII geodetic units, confirmed by direct hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with a Pentax PTS 3, total station instrument.

The geographic position of the corner of Tps. 19 and 20 N., Rgs. 27 and 28 E., was determined by the technique of static differential positioning using Ashtech models M-XII and MS-XII geodetic units. U. S. Coast and Geodetic Survey triangulation stations "BEACON 54B ECC 1936" AND "DEAD 1936", were used as the control stations. The coordinates refer to the top of the monument and are as follows.

Latitude 35°04'53.443" N. Longitude 109°25'01.279" W. NAD27

T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>The mean magnetic declination, as taken from the quadrangle map CHAMBERS ARIZ. Published in 1971 by the U. S. Geological Survey, is 13 1/2° E.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the West Boundary, T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Restoring the survey executed by Frank Follman, in 1882</p> <hr/> <p>Beginning at the cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T20N R26E R27E S1 S6 S7 S12 1988, as described in the field note record of the dependent resurvey of a portion of the E. bdy., T. 20 N., R. 26 E., executed concurrently under this same group.</p> <p>N. 0°09' E., bet. secs. 1 and 6.</p> <p>Over rolling land</p> <p>39.88 The 1/4 sec. cor. of secs. 1 and 6, reestablished by Lacy Camp Greer, Arizona Registered Land Surveyor No. 5704, monumented with an iron post 2 1/2 ins. diam., 24 ins. long, firmly set 13 ins. in the ground, with brass cap mkd. RLS 5704 T20N R26E R27E 1/4 S1 S6 1971. This is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R26E R27E 1/4 S 1 S 6 1993</p> <p>Bury the iron post alongside the stainless steel post.</p> <p>Deposit a magnet in a plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
--------	--

Dependent Resurvey of a Portion of the West Boundary,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Cor. is located in fence, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°09' E., beginning new measurement.</p> <p>Over rolling land.</p> <p>41.78 Intersect the Fifth Stan. Parallel North, point for the closing cor. of Tps. 20 N., Rs. 26 and 27 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T21N R27E S31</p> <hr style="width: 10%; margin: 0 auto;"/> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">S 1</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S 6</td> </tr> <tr> <td style="padding: 0 5px;">R26E</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">R27E</td> </tr> </table> <p>CC T20N 1993</p> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>From this cor. point, the original closing cor., bears N. 0°09' E., 0.37 chs. dist, monumented with a sandstone, 28 x 13 x 9, firmly set 19 in. in the ground, mkd. with 6 grooves on the E. face, 6 grooves on the W. face and CC on the N. face.</p> <p>Add the marks AM to the sandstone and bury 6 ins. below the ground in place.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 21 N., R. 27 E., bears S. 89° 21' E., 19.01 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. SC T21N R27E 1/4 S31 1988, with a steel fence post alongside the cor.</p> <p>from which the bearing trees mkd. in 1988-94</p> <p style="padding-left: 40px;">A juniper, 11 ins. diam., bears N. 30 1/2° E., 162 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N. 39° W., 203 lks. dist., mkd. 1/4 S31 SC BT.</p> <hr style="width: 80%; margin: 10px auto;"/>	S 1	S 6	R26E	R27E
S 1	S 6				
R26E	R27E				

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">Restoring the survey executed by Frank Follman, in 1883</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T20N R27E S1 S2 S35 S36 T19N 1988, as described and witnessed in the field note record of the dependent resurvey of the N. bdy., T. 19 N., R. 27 E., executed concurrently under this same group.</p> <p>N. 0°43' E., bet. secs. 35 and 36.</p> <p>Over rolling land</p> <p>41.26 Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R27E 1/4 S35 S36 1993</p> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>80.50 Fence, bears ENE. and WSW.</p> <p>82.52 The cor. of secs. 25, 26, 35 and 36, monumented with a juniper post, 33 ins. long, 3 ins. square, lying loose on the ground, mkd. with 1 notch on a face, 1 notch on adjoining face and IA on opposite face, with a spike set below surface of ground. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R27E S26 S25 ----- S35 S36 1993</p> </div>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the juniper post alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with the brass cap mkd. T20N R27E R28E S25 S30 S31 S36 1988, as described in the field note record of the dependent resurvey of the W. bdy., T. 20 N., R. 28 E., executed concurrently under this same group.</p> <p>N. 87°10' W., bet. secs. 25 and 36.</p> <p>Over rolling land.</p>
40.96	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E S25 1/4 — S36 1993</p>
81.91	<p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Cor. is located 2.2 chs. S. of fence, bears ENE. and WSW.</p> <p>Set a steel fence post alongside the cor.</p> <p>The cor. of secs. 25, 26, 35 and 36.</p> <hr/> <p>N. 0°13' W., bet. secs. 25 and 26.</p> <p>Over rolling land.</p>
1.60	<p>Dirt road, bears E. and W.</p>
40.21	<p>The 1/4 sec. cor. of secs. 25 and 26, monumented with a juniper post, 38 ins. long, 4 in. square, lying loose on ground, partially mkd. with a 1 and part of a 4 on a face, with fragmented remains of a sandstone at base.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E 1/4 S26 S25 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the juniper post alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p style="text-align: center;">_____</p> <p>N. 1°28' E., beginning new measurement.</p> <p>Over rolling land.</p>
40.09	<p>Point for the cor. of secs. 23, 24, 25, and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E S23 S24 ----- S26 S25 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p style="text-align: center;">_____</p> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with the brass cap mkd., T20N R27E R28E S19 S24 S25 S30 1988, as described and witnessed in the field note record of the dependent resurvey of the W. bdy., T. 20 N., R. 28 E., executed concurrently under this same group.</p> <p>N. 87°05' W., bet. secs. 24 and 25.</p> <p>Over rolling land.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.64	<p>Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E S24 1/4 — S25 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
81.28	<p>The cor. of secs. 23, 24, 25 and 26.</p> <hr/> <p>N. 0°10' W., bet. secs. 23 and 24.</p> <p>Over rolling land.</p>
40.08	<p>Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E 1/4 S23 S24 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
80.16	<p>Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
41.14	<div style="text-align: center;"> <p>T20N R27E S14 S13 ----- S23 S24 1993</p> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with the brass cap mkd. T20N R27E R28E S13 S18 S19 S24 1989, as described and witnessed in the field note record of the dependent resurvey of the W. bdy., T. 20 N., R. 28 E., executed concurrently under this same group.</p> <p>N. 88°15' W., bet. secs. 13 and 24.</p> <p>Over rolling land.</p> <p>The 1/4 sec. cor. of secs. 13 and 24, monumented with a juniper post, 24 ins. long, 3 ins. square, firmly set 16 ins. in the ground, plainly mkd. with 1/4 on the N. face and IA on the S. face. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R27E S13 1/4 — S24 1993</p> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the juniper post alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>N. 88°24' W., beginning new measurement.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.28	<p>Over rolling land.</p> <p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/>
40.09	<p>N. 1°06' W., bet. secs. 13 and 14.</p> <p>Over rolling land.</p> <p>The 1/4 sec. cor. of secs. 13 and 14, monumented with a juniper post, 30 ins. long, 4 in. square, lying loose on ground, partially mkd. with a 1 and part of a 4 on a face. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E 1/4 S14 S13 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the juniper post alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/>
40.14	<p>N. 0°01' W., beginning new measurement.</p> <p>Over rolling land.</p> <p>The cor. of secs. 11, 12, 13 and 14, monumented with a juniper post, 33 ins. long, 3 in. square, firmly set 24 ins. in the ground, mkd. with 1 notch on E. face, 4 notches on S. face and IA on W. face. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS																					
	<div style="text-align: center;"> <table border="1"> <tr><td>T20N R27E</td><td></td></tr> <tr><td>S11</td><td>S12</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S14</td><td>S13</td></tr> <tr><td colspan="2">1993</td></tr> </table> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the juniper post alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with the brass cap mkd. T20N R27E R28E S7 S12 S13 S18 1989, as described in the field note record of the dependent resurvey of the W. bdy., T. 20 N., R. 28 E., executed concurrently under this same group.</p> <p>N. 89°31' W., bet. secs. 12 and 13.</p> <p>Over rolling land.</p> <p>41.10 Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins below the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T20N R27E</td><td></td></tr> <tr><td>S12</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S13</td><td></td></tr> <tr><td colspan="2">1993</td></tr> </table> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, for a reference monument, bears N. 68°09' E., 55.3 ft. dist., with brass cap mkd. RM T20N R27E 1/4 S12 55.3 FT TO COR 1993, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Set a steel fence post alongside the cor.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam.,</p>	T20N R27E		S11	S12			S14	S13	1993		T20N R27E		S12		1/4	—	S13		1993	
T20N R27E																					
S11	S12																				
S14	S13																				
1993																					
T20N R27E																					
S12																					
1/4	—																				
S13																					
1993																					

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>24 ins. in the ground, for a reference monument, bears S. 54°31' E., 54.2 ft. dist., with brass cap mkd. RM T2ON R27E 1/4 S13 54.2 FT TO COR 1993, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Set a steel fence post alongside the cor.</p> <p>Cor. is located in dirt road, bears N. and S.</p>
82.20	<p>The cor. of secs. 11, 12, 13 and 14.</p> <hr/>
	<p>North, bet. secs. 11 and 12.</p> <p>Over rolling land.</p>
40.58	<p>The 1/4 sec. cor. of secs. 11 and 12, monumented with a broken juniper post, 23 ins. long, 3 ins. square, lying loose on the ground, mkd. with a 1 and a partial 4 on a face and IA on opposite face. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T2ON R27E 1/4 S11 S12 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the juniper post alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/>
40.63	<p>N. 0°01' W., beginning new measurement.</p> <p>Over rolling land.</p> <p>The cor. of secs. 1, 2, 11 and 12, monumented with a juniper post, 33 ins. long, firmly set 24 ins. in the ground, mkd. with 5 notches on S. face and 1 notch and IA on E. face. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T20N R27E</td></tr> <tr><td>S 2</td><td> S 1</td></tr> <tr><td colspan="2">—</td></tr> <tr><td>S11</td><td> S12</td></tr> <tr><td colspan="2">1993</td></tr> </table> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the juniper post alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with the brass cap mkd. T20N R27E R28E S1 S6 S7 S12 1988, as described and witnessed in the field note record of the dependent resurvey of the W. bdy., T. 20 N., R. 28 E., executed concurrently under this same group.</p> <p>N. 89°54' W., bet. secs. 1 and 12.</p> <p>Over rolling land.</p>	T20N R27E		S 2	S 1	—		S11	S12	1993	
T20N R27E											
S 2	S 1										
—											
S11	S12										
1993											
41.19	<p>The 1/4 sec. cor. of secs. 1 and 12, monumented with a juniper post, 3 1/2 ins. square, 33 ins. long, firmly set 13 ins. in the ground, mkd. with 1/4 on N. face and IA on S. face. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T20N R27E</td></tr> <tr><td colspan="2">S1</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td colspan="2">S12</td></tr> <tr><td colspan="2">1993</td></tr> </table> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the juniper post alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/>	T20N R27E		S1		1/4	—	S12		1993	
T20N R27E											
S1											
1/4	—										
S12											
1993											

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>S. 89°57' W., beginning new measurement.</p> <p>Over rolling land.</p>
41.11	<p>The cor. of secs. 1, 2, 11 and 12.</p> <hr/>
	<p>N. 0°04' W., bet. secs. 1 and 2.</p> <p>Over rolling land.</p>
40.89	<p>The 1/4 sec. cor. of secs. 1 and 2, monumented with a juniper post, 5 ins. diam., 25 ins. long, firmly set 9 ins. in the ground, mkd. with a 1/4 and IA on the N. face. This position is accepted as the best available evidence of the original corner.</p>
	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T20N R27E 1/4 S 2 S 1 1993</p>
	<p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p>
	<p>Bury the juniper post alongside the stainless steel post.</p>
	<p>Set a steel fence post alongside the cor.</p> <hr/>
	<p>N. 1°57' E., beginning new measurement.</p> <p>Over rolling land.</p>
39.10	<p>Fence, bears E. and W.</p>
43.90	<p>Point for the closing cor. of secs. 1 and 2, at proportionate dist., from the opposing closing cors., on the Fifth Stan. Parallel North; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T21N R27E S36</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S 2 S 1 T20N R27E CC 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 20 N., R. 27 E., bears S. 89°46' E., 18.72 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T21N R27E 1/4 S36 1988, with a steel fence post alongside the cor.</p> <p>from which the 1988 bearing trees</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears N. 18 1/2° E., 118 lks. dist., mkd. 1/4 S36 SC BT.</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears N. 50 1/4° W., 100 lks. dist., mkd. 1/4 S36 SC BT.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T20N R27E S34 S35 S2 S3 T19N 1988, as described in the field note record of the dependent resurvey of the N. bdy., T. 19 N., R. 27 E., executed concurrently under this same group.</p> <p>N. 0°03' E., bet. secs. 34 and 35.</p> <p>Over rolling land.</p> <p>40.71 Point for 1/4 sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E 1/4 S34 S35 1993</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS											
81.42	<p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>The cor. of secs. 26, 27, 34 and 35, monumented with a juniper post, 3 1/2 ins. diam. 28 ins. long, firmly set 8 ins. in the ground, mkd. with an I on W. side. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T20N</td> <td>R27E</td> </tr> <tr> <td>S27</td> <td>S26</td> </tr> <tr> <td colspan="2" style="text-align: center;">— —</td> </tr> <tr> <td>S34</td> <td>S35</td> </tr> <tr> <td colspan="2" style="text-align: center;">1993</td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the juniper post alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/>	T20N	R27E	S27	S26	— —		S34	S35	1993	
T20N	R27E										
S27	S26										
— —											
S34	S35										
1993											
40.42	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89°57' W., bet. secs. 26 and 35.</p> <p>Over rolling land.</p> <p>Point for 1/4 sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T20N</td> <td>R27E</td> </tr> <tr> <td></td> <td>S26</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S35</td> </tr> <tr> <td colspan="2" style="text-align: center;">1993</td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>	T20N	R27E		S26	1/4	—		S35	1993	
T20N	R27E										
	S26										
1/4	—										
	S35										
1993											

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.84	<p>The cor. of secs. 26, 27, 34 and 35.</p> <hr/> <p>N. 0°24' E., bet. secs. 26 and 27.</p> <p>Over rolling land.</p>
40.96	<p>The 1/4 sec. cor. of secs. 26 and 27, monumented with a sandstone, 24 x 10 x 6 ins., firmly set 22 ins. in the ground, with no visible marks, with the remains of a wooden post alongside. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E 1/4 S27 S26 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the sandstone alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located on spur, bears N. and S., in an abandon fence line, bears N. and S.</p> <hr/> <p>N. 0°15' E., beginning new measurement.</p> <p>Over rolling land.</p>
38.99	<p>The cor. of secs. 22, 23, 26 and 27, monumented with a sandstone, 13 x 7 x 2 ins., loosely set 1 in. in the ground, mkd. with an A on a face. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<div style="text-align: center;"> <table border="1"> <tr><td>T20N R27E</td><td></td></tr> <tr><td>S22</td><td>S23</td></tr> <tr><td colspan="2" style="text-align: center;">—</td></tr> <tr><td>S27</td><td>S26</td></tr> <tr><td colspan="2" style="text-align: center;">1993</td></tr> </table> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the sandstone alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/>	T20N R27E		S22	S23	—		S27	S26	1993	
T20N R27E											
S22	S23										
—											
S27	S26										
1993											
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°49' W., bet. secs. 23 and 26.</p> <p>Over rolling land.</p>										
40.62	<p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										
	<div style="text-align: center;"> <table border="1"> <tr><td>T20N R27E</td><td></td></tr> <tr><td>S23</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S26</td><td></td></tr> <tr><td colspan="2" style="text-align: center;">1993</td></tr> </table> </div>	T20N R27E		S23		1/4	—	S26		1993	
T20N R27E											
S23											
1/4	—										
S26											
1993											
81.23	<p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <p>The cor. of secs. 22, 23, 26 and 27.</p> <hr/>										
	<p>N. 0°27' E., bet. secs. 22 and 23.</p> <p>Over rolling land.</p>										
40.24	<p>Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.48	<p style="text-align: center;">T20N R27E 1/4 S22 S23 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Point for the cor. of secs. 14, 15, 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E S15 S14 ----- S22 S23 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/>
40.18	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°58' W., bet. secs. 14 and 23.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E S14 1/4 — S23 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.36	<p>The cor. of secs. 14, 15, 22 and 23.</p> <hr/> <p>N. 0°11' W., bet. secs. 14 and 15.</p> <p>Over rolling land.</p>
40.24	<p>Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R27E 1/4 S15 S14 1993</p> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
80.48	<p>The cor. of secs. 10, 11, 14 and 15, monumented with a wooden post, 3 ins. square, 25 ins. long, firmly set 7 ins. in the ground, partially mkd. with /4 on the N. face. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R27E S10 S11 ----- S15 S14 1993</p> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the wooden post alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89°46' W., bet. secs. 11 and 14.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.91	<p>Over rolling land.</p> <p>The 1/4 sec. cor. of secs. 11 and 14, monumented with a juniper post, 3 ins. square, 25 ins. long, firmly set 18 ins. in the ground partially mkd. with a /4 on the N. face and illegible marks on the S. face. This position is accepted as the best available evidence of the original cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E S11 1/4 — S14 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the juniper post alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°47' W., beginning new measurement.</p> <p>Over rolling land.</p>
39.93	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°27' E., bet. secs. 10 and 11.</p> <p>Over rolling land.</p>
39.79	<p>Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E 1/4 S10 S11 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS											
79.58	<p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in abandon fence, bears N. and S.</p> <p>The cor. of secs. 2, 3, 10 and 11, monumented with a sandstone, 16 x 10 x 5 ins., loosely set 3 ins. in the ground, plainly mkd., with 5 grooves on the S. face and 2 grooves on the N. face. This position is accepted as the best available evidence of the original cor.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T20N</td> <td>R27E</td> </tr> <tr> <td>S 3</td> <td>S 2</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S10</td> <td>S11</td> </tr> <tr> <td colspan="2" style="text-align: center;">1993</td> </tr> </table> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the sandstone alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/>	T20N	R27E	S 3	S 2			S10	S11	1993	
T20N	R27E										
S 3	S 2										
S10	S11										
1993											
39.63	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89°01' W., bet. secs. 2 and 11.</p> <p>Over rolling land.</p> <p>The 1/4 sec. cor. of secs. 2 and 11, monumented with a wooden post, 4 ins. square, 32 ins. long, firmly set 12 ins. in the ground, partially mkd. with IA on the E. face. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T20N</td> <td>R27E</td> </tr> <tr> <td></td> <td>S 2</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S11</td> </tr> <tr> <td colspan="2" style="text-align: center;">1993</td> </tr> </table>	T20N	R27E		S 2	1/4	—		S11	1993	
T20N	R27E										
	S 2										
1/4	—										
	S11										
1993											

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the wooden post alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>S. 89°05' W., beginning new measurement.</p> <p>Over rolling land.</p>
39.57	<p>The cor. of secs. 2, 3, 10 and 11.</p> <hr/>
	<p>N. 0°05' W., bet. secs. 2 and 3.</p> <p>Over rolling land.</p>
41.70	<p>Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E 1/4 S 3 S 2 1993</p>
	<p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
83.20	<p>Rock ridge, 118 ft. high, bears, E. and W.</p>
85.44	<p>The original closing cor. of secs. 2 and 3, monumented with a sandstone, 15 x 7 x 2, firmly set 1 in. below the ground, mkd. CC on the S. face.</p> <p>Add the marks AM to the sandstone and bury 6 ins. below the ground in place.</p>
85.68	<p>Intersect the Fifth Stan. Parallel North, point for the closing cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T21N R27E S35</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S 3 S 2 T20N R27E CC 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 21 N., R. 27 E., bears N. 89°32' E., 19.51 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. SC T21N R27E 1/4 S35 1988, with a mound of stone 3 ft. base, 2 1/2 ft. high N. of cor. and a fence post alongside the cor.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T20N R27E S3 S4 S33 S34 T19N 1988, as described in the field note record of the dependent resurvey of the N. bdy., T. 19 N., R. 27 E., executed concurrently under this same group.</p> <p>N. 0°30' E., bet. secs. 33 and 34.</p> <p>Over rolling land.</p>
40.81	<p>Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E 1/4 S33 S34 1993</p>
81.62	<p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>The cor. of secs. 27, 28, 33 and 34, monumented with a sandstone, 6 x 5 x 4 ins., firmly set flush with ground, plainly mkd. with 1 groove on the S. face, with the rotted remains of a wood post underneath. This position is accepted as the best available evidence of the original corner.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T20N R27E</td> <td></td> </tr> <tr> <td>S28</td> <td>S27</td> </tr> <tr> <td colspan="2" style="text-align: center;">— —</td> </tr> <tr> <td>S33</td> <td>S34</td> </tr> <tr> <td colspan="2" style="text-align: center;">1993</td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the sandstone alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/>	T20N R27E		S28	S27	— —		S33	S34	1993	
T20N R27E											
S28	S27										
— —											
S33	S34										
1993											
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°57' W., bet. secs. 27 and 34.</p> <p>Over rolling land.</p>										
32.00	Ridge, bears N. and S.										
39.89	<p>Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T20N R27E</td> <td></td> </tr> <tr> <td>S27</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S34</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">1993</td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>	T20N R27E		S27		1/4	—	S34		1993	
T20N R27E											
S27											
1/4	—										
S34											
1993											
45.60	Draw, drains NE.										
79.77	<p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/> <p>N. 5°19' E., bet. secs. 27 and 28.</p>										

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
43.13	<p>Over rolling land.</p> <p>The 1/4 sec. cor. of secs. 27 and 28, monumented with a juniper post, 30 ins. long, 4 ins. square, lying loose on ground, partially mkd. with a 1 and part of a 4 on a face. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R27E 1/4 S28 S27 1993</p> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the juniper post alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 5°56' W., beginning new measurement.</p>
37.73	<p>Over rolling land.</p> <p>The cor. of secs. 21, 22, 27 and 28, monumented with a juniper post, 50 ins. long, 4 ins. square, lying loosely on the ground, previously set 14 ins. in ground, mkd. with illegible grooves on a face and illegible marks on adjoining and opposite faces. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R27E S21 S22 ----- S28 S27 1993</p> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.06	<p>Bury the juniper post alongside the stainless steel post. Set a steel fence post alongside the cor.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27. N. 89°35' W., bet. secs. 22 and 27. Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E S22 1/4 — S27 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
80.12	<p>The cor. of secs. 21, 22, 27 and 28.</p> <hr/> <p>N. 0°03' E., bet. secs. 21 and 22. Over rolling land.</p>
40.15	<p>Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E 1/4 S21 S22 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.30	<p>The cor. of secs. 15, 16, 21 and 22, monumented with a fragmented sandstone, largest piece 4 x 1/2 x 1/4 ins., mkd. with an A on a face. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T20N</td> <td>R27E</td> </tr> <tr> <td>S16</td> <td>S15</td> </tr> <tr> <td>S21</td> <td>S22</td> </tr> <tr> <td colspan="2">1993</td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury sandstone fragments alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°43' W., bet. secs. 15 and 22.</p> <p>Over rolling land.</p>	T20N	R27E	S16	S15	S21	S22	1993			
T20N	R27E										
S16	S15										
S21	S22										
1993											
40.33	<p>Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T20N</td> <td>R27E</td> </tr> <tr> <td></td> <td>S15</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S22</td> </tr> <tr> <td colspan="2">1993</td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>	T20N	R27E		S15	1/4	—		S22	1993	
T20N	R27E										
	S15										
1/4	—										
	S22										
1993											
80.65	<p>The cor. of secs. 15, 16, 21 and 22.</p> <hr/> <p>N. 0°53' E., bet. secs. 15 and 16.</p>										

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
40.46	<p>Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E 1/4 S16 S15 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
78.50	Draw, 20 lks. wide, drains SW.
80.92	<p>Point for the cor. of secs. 9, 10, 15 and 16, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E S 9 S10 ----- S16 S15 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°24' W., bet. secs. 10 and 15.</p> <p>Over rolling land</p>
39.56	<p>Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.13	<p style="text-align: center;">T20N R27E S10 1/4 — S15 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located on N. slope of ridge, bears NE. and SW.</p> <p>The cor. of secs. 9, 10, 15 and 16.</p> <hr/> <p>N. 0°46' E., bet. secs. 9 and 10.</p> <p>Over rolling land.</p>
40.46	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
79.10	<p style="text-align: center;">T20N R27E 1/4 S 9 S10 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Wash, 20 lks. wide, drains SW.</p>
80.92	<p>Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E S 4 S 3 —+— S 9 S10 1993</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.36	<p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 88°25' W., bet. secs. 3 and 10.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E S 3 1/4 — S10 1993</p>
78.71	<p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/> <p>N. 0°52' E., bet. secs. 3 and 4.</p> <p>Over rolling land.</p>
40.46	<p>Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E 1/4 S 4 S 3 1993</p> <p>from which</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A rock outcropping, 6 x 3 x 2 ft. high, bears N. 32° E., 31 1/2 lks. dist., with an XBO chiseled on the top.</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
54.45	<p>Point for a witness point on line bet. secs. 3 and 4, at intersection with the southeasterly right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T20N R27E S 4 S 3 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
66.40	<p>Railroad right-of-way fence, bears NE and SW.</p>
66.90	<p>Point for a witness point on line bet. secs. 3 and 4, at intersection with the northwesterly right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T20N R27E S 4 S 3 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
76.60	<p>Left bank of the Rio Puerco, course SW.</p>
80.60	<p>Right bank of the Rio Puerco, course SW.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS									
82.81	<p>The original closing cor. of secs. 3 and 4, monumented with a sandstone, 12 x 7 x 6 ins., firmly set 10 in. the ground, mkd. with 3 grooves on the E. face and 3 grooves on the W. face and CC on the S. face.</p> <p>Add the marks AM to the sandstone and bury 6 ins. below ground in place.</p>								
82.89	<p>Intersect the Fifth Stan. Parallel North, point for the closing cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T21N R27E S34</p> <hr style="width: 50%; margin: auto;"/> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 4</td> <td style="padding: 0 5px;">S 3</td> </tr> <tr> <td colspan="2" style="text-align: center;">T20N R27E</td> </tr> <tr> <td colspan="2" style="text-align: center;">CC</td> </tr> <tr> <td colspan="2" style="text-align: center;">1993</td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 21 N., R. 27 E., bears N. 89°32' E., 17.90 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. SC T21N R27E 1/4 S34 1988, with a steel fence post alongside the cor.</p>	S 4	S 3	T20N R27E		CC		1993	
S 4	S 3								
T20N R27E									
CC									
1993									
	<p>Point for the 1/4 sec. cor. of sec. 3 only, T. 20 N., R. 27 E., is at midpoint on the N. bdy. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T21N R27E</p> <hr style="width: 50%; margin: auto;"/> <p>1/4 S 3</p> <p>T20N R28E</p> <p>1993</p> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>								

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point the stan. cor. of secs. 34 and 35, T. 21 N., R. 27 E., bears N. 89°32' E., 18.705 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. SC T21N R27E S34 S35 1988, with a steel fence post alongside the cor.</p>
	<p>From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T20N R27E S4 S5 S32 S33 T19N 1987, as described in the field note record of the dependent resurvey of the N. bdy., T. 19 N., R. 27 E., executed concurrently under this same group.</p> <p>N. 0°05' W., bet. secs. 32 and 33.</p> <p>Over rolling land.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R27E 1/4 S32 S33 1993</p> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
80.04	<p>Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R27E S29 S28 ----- S32 S33 1993</p> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.63	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 88°49' W., bet. secs. 28 and 33.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E S28 1/4 — S33 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located on the NE. slope of hill.</p>
81.26	<p>The cor. of secs. 28, 29, 32 and 33.</p> <hr/> <p>N. 0°08' E., bet. secs. 28 and 29.</p> <p>Over rolling land.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E 1/4 S29 S28 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.04	<p>The cor. of secs. 20, 21, 28 and 29, monumented with a rotted wood stub, firmly set 6 ins. below ground, with a decayed wood post, 17 ins. long, 3 ins. diam., and a metal neck of a shovel buried alongside. This position is accepted as the best available evidence of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T20N</td> <td>R27E</td> </tr> <tr> <td>S20</td> <td>S21</td> </tr> <tr> <td>S29</td> <td>S28</td> </tr> <tr> <td colspan="2">1993</td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/>	T20N	R27E	S20	S21	S29	S28	1993			
T20N	R27E										
S20	S21										
S29	S28										
1993											
40.59	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 88°29' W., bet. secs. 21 and 28.</p> <p>Over rolling land.</p> <p>The 1/4 sec. cor. of secs. 21 and 28, monumented with a broken juniper post, 21 ins. long, 4 x 2 ins. on top, lying loose on ground, previously set, 17 ins. in ground, partially mkd. with a / on a face. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T20N</td> <td>R27E</td> </tr> <tr> <td></td> <td>S21</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S28</td> </tr> <tr> <td colspan="2">1993</td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the juniper post alongside the stainless steel post.</p>	T20N	R27E		S21	1/4	—		S28	1993	
T20N	R27E										
	S21										
1/4	—										
	S28										
1993											

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.58	<p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>S. 88°32' W., beginning new measurement.</p> <p>Over rolling land.</p> <p>The cor. of secs. 20, 21, 28 and 29.</p> <hr style="width: 80%; margin: 0 auto;"/>
40.02	<p>N. 0°02' E., bet. secs. 20 and 21.</p> <p>Over rolling land.</p> <p>Dirt road, 16 ft. wide, bears E. and W.</p> <p>Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T20N R27E 1/4 S20 S21 1993 </div>
80.04	<p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>The cor. of secs. 16, 17, 20 and 21, monumented with a decayed wooden post, 42 ins. long, 4 ins. square, lying loosely on the ground, with broken splinters below surface, mkd. with 3 faint grooves on a face and axe marks on adjoining faces. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T20N R27E S17 S16 <hr style="width: 20%; margin: 0 auto;"/> S20 S21 1993 </div>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 88°20' W., bet. secs. 16 and 21.</p> <p>Over rolling land.</p>
40.59	<p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E S16 1/4 — S21 1993</p>
81.18	<p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>N. 2°50' E., bet. secs. 16 and 17.</p> <p>Over rolling land.</p>
41.18	<p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E 1/4 S17 S16 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS											
82.36	<p>Point for the cor. of secs. 8, 9, 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T20N</td><td>R27E</td></tr> <tr><td>S 8</td><td>S 9</td></tr> <tr><td colspan="2" style="text-align: center;">—</td></tr> <tr><td>S17</td><td>S16</td></tr> <tr><td colspan="2" style="text-align: center;">1993</td></tr> </table> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located on W. slope of dike, bears N. and S.</p> <hr/>	T20N	R27E	S 8	S 9	—		S17	S16	1993	
T20N	R27E										
S 8	S 9										
—											
S17	S16										
1993											
	<p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 89°16' W., bet. secs. 9 and 16.</p> <p>Over rolling land.</p>										
39.16	<p>Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T20N</td><td>R27E</td></tr> <tr><td colspan="2" style="text-align: center;">S 9</td></tr> <tr><td colspan="2" style="text-align: center;">1/4 —</td></tr> <tr><td colspan="2" style="text-align: center;">S16</td></tr> <tr><td colspan="2" style="text-align: center;">1993</td></tr> </table> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>	T20N	R27E	S 9		1/4 —		S16		1993	
T20N	R27E										
S 9											
1/4 —											
S16											
1993											
78.32	<p>The cor. of secs. 8, 9, 16 and 17.</p> <hr/> <p>N. 0°41' E., bet. secs. 8 and 9.</p> <p>Over rolling land.</p>										

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
41.13	<p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E 1/4 S 8 S 9 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 68 lks. W. of fence, bears N. and S.</p>
56.12	<p>Point for a witness point on line bet. secs. 8 and 9, at intersection with the southeasterly right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T20N R27E S 8 S 9 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
71.56	<p>Point for a witness point on line bet. secs. 8 and 9, at intersection with the northwesterly right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T20N R27E S 8 S 9 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS											
82.26	<p>The cor. of secs. 4, 5, 8 and 9, monumented with a sandstone, 10 x 6 x 2 1/2 ins., firmly set 6 ins. in the ground, plainly mkd. with 4 grooves on the E. face and 5 grooves on the S. face. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T20N</td><td>R27E</td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td colspan="2" style="text-align: center;">—</td></tr> <tr><td>S 8</td><td>S 9</td></tr> <tr><td colspan="2" style="text-align: center;">1993</td></tr> </table> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the sandstone alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/>	T20N	R27E	S 5	S 4	—		S 8	S 9	1993	
T20N	R27E										
S 5	S 4										
—											
S 8	S 9										
1993											
	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 89°45' W., bet. secs. 4 and 9.</p> <p>Over rolling land.</p>										
39.20	<p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T20N</td><td>R27E</td></tr> <tr><td colspan="2" style="text-align: center;">S 4</td></tr> <tr><td colspan="2" style="text-align: center;">1/4 —</td></tr> <tr><td colspan="2" style="text-align: center;">S 9</td></tr> <tr><td colspan="2" style="text-align: center;">1993</td></tr> </table> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 1 ch. W. of wash, drains N.</p>	T20N	R27E	S 4		1/4 —		S 9		1993	
T20N	R27E										
S 4											
1/4 —											
S 9											
1993											

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
52.84	<p>Point for a witness point on line bet. secs. 4 and 9, at intersection with the southeasterly right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T20N R27E S 4 — S 9 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
67.98	<p>Point for a witness point on line bet. secs. 4 and 9, at intersection with the northwesterly right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T20N R27E S 4 — S 9 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
78.40	<p>The cor. of secs. 4, 5, 8 and 9.</p> <hr/> <p>N. 0°06' W., bet. secs. 4 and 5.</p> <p>Over rolling land.</p>
38.90	<p>Center of McCarrol Rd., a paved road, bears ENE. and WSW.</p>
39.90	<p>Fence, bears E. and W.</p>
40.15	<p>Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate dist.; there is no remaining evidence of the original cor.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E 1/4 S 5 S 4 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
79.00	Rock ledge, bears ENE. and WSW.
82.05	<p>The closing cor. of secs. 4 and 5, on the Fifth Stan. Parallel North, monumented with a reinforcing rod, 1/2 in. diam., 12 ins. long, firmly set 8 ins. in the ground. The monument was set by James D. Thornhill, Arizona Registered Land Surveyor No. 12219, in 1987, is harmoniously related with other identified closing cors. and is accepted as the best available evidence of the original corner position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R27E S33 ----- S 5 S 4 T20N R27E CC 1995</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Cor. is located in fence, bears E. and W.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 21 N., R. 27 E., bears N. 89°41' E., 18.175 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. SC T21N R27E 1/4 S33 1988, with a steel fence post alongside the cor.</p> <p>Cor. is located 1 lk. S. of fence, bears E. and W.</p> <hr/>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Point for the 1/4 sec. cor. of sec. 4 only, T. 20 N., R. 27 E., is at midpoint on the N. bdy. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R27E ----- 1/4 S 4 T20N R27E 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>From this cor. point, the stan. cor. of secs. 33 and 34, T. 21 N., R. 27 E., bears N. 89°41' E., 18.36 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T21N R27E S33 S34 1988, with a steel fence post alongside the cor.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T20N R27E S5 S6 S31 S32 T19N 1994, as described in the field note record of the dependent resurvey of the N. bdy., T. 19 N., R. 27 E., executed concurrently under this same group.</p> <p>N. 0°25' W., bet. secs. 31 and 32.</p> <p>Over rolling land.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E 1/4 S31 S32 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS											
79.98	<p>Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T20N</td> <td>R27E</td> </tr> <tr> <td>S30</td> <td>S29</td> </tr> <tr> <td>S31</td> <td>S32</td> </tr> <tr> <td colspan="2">1993</td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located on the N. bank of wash drains, WSW.</p> <hr/>	T20N	R27E	S30	S29	S31	S32	1993			
T20N	R27E										
S30	S29										
S31	S32										
1993											
40.75	<p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 87°09' W., bet. secs. 29 and 32.</p> <p>Over rolling land.</p> <p>The 1/4 sec. cor. of secs. 29 and 32, monumented with a sandstone, 11 x 9 x 2 1/2 ins., loosely set on the ground, plainly mkd. 1/4 on a face. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T20N</td> <td>R27E</td> </tr> <tr> <td></td> <td>S29</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S32</td> </tr> <tr> <td colspan="2">1993</td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the sandstone alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 1.14 chs. S. of fence, bears E. and W.</p> <hr/>	T20N	R27E		S29	1/4	—		S32	1993	
T20N	R27E										
	S29										
1/4	—										
	S32										
1993											

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>S. 87°33' W., beginning new measurement. Over rolling land.</p>
39.75	<p>The cor. of secs. 29, 30, 31 and 32.</p> <hr/>
	<p>N. 89°40' W., bet. secs. 30 and 31. Over rolling land.</p>
39.75	<p>Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E S30 1/4 — S31 1993</p>
	<p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located on the N. edge of wash, drains NE.</p>
77.98	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T20N R26E R27E S25 S30 S31 S36 1988, as described in the field note record of the dependent resurvey of a portion of the E. bdy., T. 20 N., R. 26 E., executed concurrently under this same group.</p> <hr/>
	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°14' E., bet. secs. 29 and 30. Over rolling land.</p>
39.99	<p>The 1/4 sec. cor. of secs. 29 and 30, monumented with a broken sandstone, 14 x 12 x 2 ins., with base firmly set 3 ins. in the ground, with a broken piece partially mkd. with an A on a face. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E 1/4 S30 S29 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the sandstone alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°24' E., beginning new measurement.</p> <p>Over rolling land.</p>
40.15	<p>The cor. of secs. 19, 20, 29 and 30, monumented with a sandstone, 16 x 15 x 4 ins., firmly set 6 ins. in the ground, mkd. with 5 grooves on the E. face, 2 grooves and an A on the S. face. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E S19 S20 ----- S30 S29 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the sandstone alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>N. 89°41' W., bet. secs. 20 and 29.</p> <p>Over rolling land.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.95	<p>The 1/4 sec. cor. of secs. 20 and 29, monumented with a juniper post, 18 ins. long, 4 ins. square, firmly set 6 ins. in the ground, with no visible marks. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E S20 1/4 — S29 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the juniper post alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p style="text-align: center;">_____</p> <p>N. 89°44' W., beginning new measurement.</p> <p>Over rolling land.</p>
40.20	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p style="text-align: center;">_____</p> <p>N. 89°43' W., bet. secs. 19 and 30.</p> <p>Over rolling land.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E S19 1/4 — S30 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
78.38	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T20N R26E R27E S19 S24 S25 S30 1994, as described in the field note record of the dependent resurvey of a portion of the E. bdy., T. 20 N., R. 26 E., executed concurrently under this same group.</p> <hr/>
	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°02' W., bet. secs. 19 and 20.</p> <p>Over rolling land.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R27E 1/4 S19 S20 1993</p> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
80.04	<p>The cor. of secs. 17, 18, 19 and 20, monumented with a juniper post, 24 ins. long, 4 ins. square, firmly set 9 ins. in the ground, mkd. with 5 grooves on the E. face, 3 grooves and IA on the S. face. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R27E S18 S17 ----- S19 S20 1993</p> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the juniper post alongside the stainless steel post.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.15	<p>Set a steel fence post alongside the cor.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°41' W., bet. secs. 17 and 20.</p> <p>Over rolling land.</p> <p>The 1/4 sec. cor. of secs. 17 and 20, monumented with a juniper post, 24 ins. long, 3 1/2 ins square, firmly set 17 ins. in the ground, with illegible marks on the N. face. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E S17 1/4 — S20 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the juniper post alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr/> <p>N. 89°44' W., beginning new measurement.</p> <p>Over rolling land.</p>
40.07	<p>The cor. of secs. 17, 18, 19 and 20.</p> <hr/> <p>N. 89°00' W., bet. secs. 18 and 19.</p> <p>Over rolling land.</p>
25.80	<p>Left bank of the Rio Puerco, course SW.</p>
33.00	<p>Right bank of the Rio Puerco, course SW.</p>
39.68	<p>Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the original cor.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E S18 1/4 — S19 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
59.52	<p>Point for the W. 1/16 sec. cor. of secs. 18 and 19</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E S18 W1/16 — S19 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
77.60	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T20N R26E R27E S13 S18 S19 S24 1988, as described in the field note record of the dependent resurvey of a portion of the E. bdy., T. 20 N., R. 26 E., executed concurrently under this same group.</p>
	<p>From the cor. of secs. 17, 18, 19 and 20.</p>
	<p>N. 3°52' E., bet. secs. 17 and 18.</p>
	<p>Over rolling land.</p>
1.10	<p>Dirt road, bears NE. and SW.</p>
1.20	<p>Fence, bears NE. and SW.</p>
2.20	<p>Left bank of the Rio Puerco, course SW.</p>
10.90	<p>Right bank of the Rio Puerco, course SW.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
41.16	<p>The 1/4 sec. cor. of secs. 17 and 18, monumented with a sandstone, 12 x 9 x 5 ins., firmly set 11 ins. in the ground, partially mkd. with 1/ on the W. face. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E 1/4 S18 S17 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the sandstone alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 3°42' E., beginning new measurement.</p> <p>Over rolling land.</p>
21.44	<p>Point for the N. 1/16 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E N1/16 S18 S17 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
36.89	<p>Point for a witness point on line bet. secs. 17 and 18, at intersection with the southeasterly right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">WP T20N R27E S18 S17 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
40.64	Fence line, bears NE. and SW.
42.58	<p>Point for a witness point on line bet. secs. 17 and 18, at intersection with the northwesterly right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T20N R27E S18 S17 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
42.88	<p>The cor. of secs. 7, 8, 17 and 18, monumented with a sandstone, 16 x 6 x 5 ins., firmly set 4 ins. in the ground, partially mkd. with 4 notches on the E. face and 4 notches on the S. face. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E S 7 S 8 ----- S18 S17 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the sandstone alongside the stainless steel post.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a steel fence post alongside the cor.
	From the cor. of secs. 8, 9, 16 and 17.
	N. 88°32' W., bet. secs. 8 and 17.
	Over rolling land.
3.40	Left bank of the Rio Puerco, course SSW.
14.00	Right bank of the Rio Puerco, course SSW.
39.37	Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T20N R27E S 8 1/4 — S17 1993</p>
	Deposit a magnet in a white plastic case beneath the stainless steel post.
70.34	Point for a witness point on line bet. secs. 8 and 17, at intersection with the southeasterly right-of-way of the Atchison Topeka and Santa Fe Railway Co.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">WP T20N R27E S 8 — S17 1993</p>
	Deposit a magnet in a white plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
78.75	The cor. of secs. 7, 8, 17 and 18.
	<p style="text-align: center;">S. 88°57' W., bet. secs. 7 and 18.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
1.30	Draw, course SW.
42.04	<p>Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E S 7 1/4 — S18 1993</p>
	<p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
77.45	<p>Point for a witness point on line bet. secs. 7 and 18, at intersection with the southeasterly right-of-way of U. S. Interstate 40.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T20N R27E S 7 — S18 1993</p>
	<p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in southeasterly highway right-of-way fence, bears NE. and SW.</p>
82.40	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with a railroad spike, firmly set flush with pavement in the E. bound lane of U. S. Interstate 40, as described and witnessed in the field note record of the dependent resurvey of a portion of the E. bdy., T. 20 N., R. 26 E., executed concurrently under this same group.</p> <hr/>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°15' W., bet. secs. 7 and 8.</p> <p>Over rolling land.</p>
40.08	<p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E 1/4 S 7 S 8 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
59.68	<p>Point for a witness point on line bet. secs. 7 and 8, at intersection with the southeasterly right-of-way of U. S. Interstate 40.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T20N R27E S 7 S 8 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in the southeasterly highway right-of-way fence, bears NE. and SW.</p>
61.10	Center of E. bound lane of U. S. Interstate 40, bears SW.
65.00	Center of W. bound lane of U. S. Interstate 40, bears NE.
65.60	<p>Point for a witness point on line bet. secs. 7 and 8, at intersection with the northwesterly right-of-way of U. S. Interstate 40.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T20N R27E S 7 S 8 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in the northwesterly highway right-of-way fence, bears NE. and SW.</p> <p>From this cor. point, a highway right-of-way marker, monumented with a 3 in. angle iron, firmly set, projecting 20 ins. above ground, plainly mkd. HWRW on a side, bears S. 51°39' W., 2.80 chs. dist.</p>
80.16	<p>The cor. of secs. 5, 6, 7 and 8, monumented with a sandstone, 16 x 5 x 2 ins., firmly set 4 ins. in the ground, plainly mkd. with 5 grooves on the E. face and 5 grooves on the S. face. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E S 6 S 5 ----- S 7 S 8 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Bury the sandstone alongside the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in fence intersection, bears E., S. and W.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 89°50' W., bet. secs. 5 and 8.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
17.50	Right bank of the Rio Puerco, course SW.
21.70	Left Bank of the Rio Puerco, course SW.
39.96	<p>The 1/4 sec. cor. of secs. 5 and 8, monumented with a sandstone, 15 x 8 x 6 ins., firmly set 7 in. in the ground, plainly mkd. 1/4 on the W. face. This position is accepted as the best available evidence of the original corner.</p>
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T20N R27E S 5 1/4 — S 8 1993</p>
	Deposit a magnet in a white plastic case beneath the stainless steel post.
	Bury the sandstone alongside the stainless steel post.
	Set a steel fence post alongside the cor.
	<p style="text-align: center;">_____</p> <p>N. 89°58' W., beginning new measurement.</p>
	Over rolling land.
13.30	Southeasterly right-of-way fence of U. S. Interstate Highway 40, bears NE. and SW.
18.20	Median of U. S. Interstate Highway 40, bears NE. and SW.
21.62	<p>Point for a witness point on line bet. secs. 5 and 8, at intersection with the northwesterly right-of-way of U. S. Interstate Highway 40.</p>
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">WP T20N R27E S 5 — S 8 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in the northwesterly highway right-of-way fence, bears NE. and SW.</p> <p>From this cor. point, a highway right-of-way marker, monumented with a brass cap, 3 ins. diam., incased in concrete, projecting 3 ins. above the ground, mkd. ARIZONA HIGHWAY DEPT. RP 102 1154+00 1976, bears N 51°39' E., 7.05 chs. dist.</p>
25.31	Point for AP 5 of a metes-and-bounds survey in sec. 5, hereinafter described.
40.08	The cor. of secs. 5, 6, 7 and 8.
	<hr/> <p>S. 89°32' W., bet. secs. 6 and 7.</p> <p>Over rolling land.</p>
42.42	<p>The 1/4 sec. cor. of secs. 6 and 7, monumented by Lacy Camp Greer, Arizona Registered Land Surveyor No. 5704, monumented with an iron post, 1/2 in. diam., 22 ins. long, firmly set 17 ins. in the ground with brass cap mkd. RLS 5704 T20N R27E 1/4 S6 S7 1971. This position is accepted as the best available evidence of the original corner.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E S 6 1/4 — S 7 1993</p> <p>Deposit iron post inside the stainless steel post.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in fence, bears E. and W.</p> <hr/> <p>S. 89°32' W., beginning new measurement.</p> <p>Over rolling land.</p>
38.87	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°07' E., bet. secs. 5 and 6.</p> <p>Over rolling land.</p>
39.60	<p>Draw, drains W.</p>
39.95	<p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E 1/4 S 6 S 5 1993</p>
80.81	<p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Intersect the Fifth Stan. Parallel North, point for the closing cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T21N R27E S32</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S 6 S 5 CC</p> <p style="text-align: center;">T20N R27E 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>From this cor. point the original closing cor., bears N. 0°07' E., 0.98 ch. dist., monumented with a sandstone, 28 x 13 x 9 ins., firmly set 19 in. in the ground, mkd. with 6 grooves on the E. face, 1 groove on the W. face and CC on the N. face</p> <p>Add the marks AM to the sandstone and bury 6 ins. below ground in place.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 21 N., R. 27 E., bears S. 87°32' E., 18.02 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T21N R27E 1/4 S32 1988.</p> <p>from which the bearing trees mkd. in 1988-94</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears N. 6° E., 172 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A juniper, 13 ins. diam., bears N. 76 1/2° W., 190 lks. dist., mkd. 1/4 S32 SC BT.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 5 only, T. 20 N., R. 27 E., is at midpoint on the N. bdy. of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R27E S33</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1/4 S 5 R27E R28E 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a steel fence post alongside the cor.</p> <p>From this cor. point, the stan. cor. of secs. 32 and 33, T. 21 N., R. 27 E., bears N. 87°08' E., 17.97 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T21N R27E S32 S33 1988, with a steel fence post alongside the cor.</p> <p>Cor. is located in a corner of fences, extending N. and E.</p> <hr/> <p>Point for the E 1/16 sec. cor. of sec. 5 only, T. 20 N., R. 27 E., is at midpoint bet. the closing cor. of secs. 4 and 5 and the 1/4 sec. cor. of sec. 5 only, on the N. bdy. of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R27E ----- E 1/16 S 5 T20N R27E 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>From this cor. point, the stan. cor. of secs. 32 and 33, T. 21 N., R. 27 E., bears S. 89°41' W., 1.98 chs. dist., hereinbefore described.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 6 only, at proportionate dist. on the N. bdy. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R27E ----- 1/4 S 6 T20N R27E 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, the stan. cor. of secs. 31 and 32, T. 21 N. R. 27 E., bears N. 88°40' E., 19.84 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T21N R27E S31 S32 1988.</p>
	<p>from which the bearing tree mkd. in 1988-94</p>
	<p>A juniper, 9 ins. diam., bears N. 18° E., 273 lks. dist., mkd. T21N R27E S32 SC BT.</p>
	<p style="text-align: center;">Subdivision of Section 5, T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona</p>
	<p>From the 1/4 sec. cor. of secs. 5 and 8.</p>
	<p>N. 0°02' W., on the N. and S. center line of sec. 5.</p>
	<p>Over rolling land.</p>
40.12	<p>Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E. and W. center line of sec. 5.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T20N R27E C1/4 S 5 1993</p>
	<p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post alongside the cor.</p>
44.83	<p>Intersect line 2-3, of the metes-and-bounds survey in sec. 5.</p>
81.15	<p>The 1/4 sec. cor. of sec. 5 only, on the N. bdy. of the Tp.</p>
	<p>From the 1/4 sec. cor. of secs. 4 and 5.</p>
	<p>S. 89°47' W., on the E. and W. center line of sec. 5.</p>
	<p>Over rolling land.</p>
19.95	<p>Point for the center E 1/16 sec. cor. of sec. 5.</p>

Subdivision of Section 5,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E E1/16 C ————— C S 5 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>39.90 The center 1/4 sec. cor. of sec. 5.</p> <p>45.31 Intersect line 3-4, of the metes-and-bounds survey in sec. 5.</p> <p>79.87 The 1/4 sec. cor. of secs. 5 and 6.</p>
	<p style="text-align: center;"><u>NE 1/4 of section 5</u></p> <p>From the center E 1/16 sec. cor. of sec. 5.</p> <p>N. 0°04' W., on the N. and S. center line of the NE 1/4 of sec. 5.</p> <p>Over rolling land.</p> <p>4.68 Point for AP 2 on the metes-and-bounds survey in sec. 5, hereinafter described.</p> <p>24.50 Point for a witness point on the N. and S. center line of the NE 1/4 of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T20N R27E E S 5 E 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>

Subdivision of Section 5,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
41.86	<p>Cor. is located in fence, bears N. and S.</p> <p>The E 1/16 sec. cor. of sec. 5 only, on the N. bdy. of the Tp.</p>
40.61	<hr/> <p style="text-align: center;">Subdivision of Section 8, T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 8 and 17.</p> <p>N. 0°16' E., on the N. and S. center line of sec. 8.</p> <p>Over rolling land.</p> <p>Point for the center 1/4 sec. cor. of sec. 8, at intersection with the E. and W. center line of sec. 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E C1/4 S 8 1993</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, for a reference monument, bears N. 81°09' E., 28.2 ft. dist., with brass cap mkd. RM T20N R27E C 1/4 S8 28.2 FT TO COR 1993, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Set a steel fence post alongside the cor.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, for a reference monument, bears S. 81°34' W., 32.5 ft. dist., with brass cap mkd. RM T20N R27E C 1/4 S8 32.5 FT TO COR 1993, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Set a steel fence post alongside the cor.</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Cor. is located in dirt road, bears N. and S.</p>
81.15	<p>The 1/4 sec. cor. of secs. 5 and 8.</p>

Subdivision of Section 8
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>From the 1/4 sec. cor. of secs. 8 and 9.</p> <p>N. 89°19' W., on the E. and W. center line of sec. 8.</p> <p>Over rolling land.</p>
39.66	The center 1/4 sec. cor. of sec. 8.
79.38	The 1/4 sec. cor. of secs. 7 and 8.
<hr/> <p>Subdivision of Section 18, T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 18 and 19.</p> <p>N. 2°13' E., on the N. and S. center line of sec. 18.</p> <p>Over rolling land.</p>
20.40	<p>Point for the center S 1/16 sec. cor. of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E C S 1/16 S 18 C 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
40.80	<p>Point for the center 1/4 sec. cor. of sec. 18, at intersection with the E. and W. center line of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E C1/4 S18 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>

Subdivision of Section 18,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
48.72	<p>Point for a witness point, on the N. and S. center line of sec. 18, at intersection with the southeasterly right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP T20N R27E C S18 C 1993</p> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in southeasterly railroad right-of-way fence.</p>
52.52	<p>Point for a witness point, on the N. and S. center line of sec. 18, at intersection with the northwesterly right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Point is occupied with a railroad tie fence post, 6 X 8 ins., firmly set, projecting 52 ins. above ground, set a 60d nail on top of post.</p> <p>Cor. is in fence line bears NE. and SW.</p>
61.63	<p>Point for the center N 1/16 sec. cor. of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R27E C N 1/16 S18 C 1993</p> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
82.46	<p>The 1/4 sec. cor. of secs. 7 and 18.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 17 and 18.</p>

Subdivision of Section 18,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 89°26' W., on the E. and W. center line of sec. 18. Over rolling land.</p>
40.87	<p>The center 1/4 sec. cor. of sec. 18.</p>
52.37	<p>Point for a witness point on the E. and W. center line of sec. 18, at intersection with the southeasterly right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Point is occupied with a railroad rail, firmly set projecting 10 ins. above the ground, with a steel fence post alongside, mkd. the top of rail.</p> <p style="text-align: center;">BLM WP T20N R27E C ————— C S18 1993</p>
57.81	<p>Cor. is located in the southeasterly railroad right-of-way fence.</p> <p>Point for a witness point, on the E. and W. center line of sec. 18, at intersection with the northwesterly right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T20N R27E S18 C ————— C 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in the northwesterly railroad right-of-way fence.</p>
61.30	<p>Point for the center W 1/16 sec. cor. of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 18,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.99	<p style="text-align: center;">T20N R27E W 1/16 C ————— C S18 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>The 1/4 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T20N R26E R27E 1/4 S13 S18 1988, as described in the field note record of the dependent resurvey of a portion of the E. bdy., T. 20 N., R. 26 E., executed concurrently under this same group.</p>
	<p style="text-align: center;"><u>NE 1/4 of Section 18</u></p> <p>From the N. 1/16 sec. cor. of secs. 17 and 18.</p> <p>S. 89°45' W., on the E. and W. center line of the NE 1/4 of sec. 18.</p> <p>Over rolling land.</p>
22.35	<p>Point for a witness point, on the E. and W. center line of the NE 1/4 of sec. 18, at intersection with the southeasterly right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T20N R27E N ————— N S18 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
28.01	<p>Fence line, bears NE. and SW.</p>

Subdivision of Section 18,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
30.65	<p>Point for a witness point, on the E. and W. center line of the NE 1/4 of sec. 18, at intersection with the northwesterly right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T20N R27E N ————— N S18 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
41.45	<p>The center N 1/16 sec. cor. of sec. 18.</p> <hr/> <p style="text-align: center;">SW 1/4 of Section 18</p> <hr/> <p>From the W. 1/16 sec. cor. of secs. 18 and 19.</p> <p>N. 1°23' E., on the N. and S. center line of the NW. 1/4 of sec. 18.</p> <p>Over rolling land.</p>
20.32	<p>Point for the SW 1/16 sec. cor. of sec. 18, at intersection with the E. and W. center line of the SW 1/4 of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E SW 1/16 S18 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p>
34.53	<p>Point for a witness point, on the N. and S. center line of the SW 1/4 of sec. 18, at intersection with the southeasterly right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p>

Subdivision of Section 18,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
<p>38.20</p> <p>40.64</p>	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> WP T20N R27E W S18 W 1993 </p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in the southeasterly railroad right-of-way fence.</p> <p>Fence line on the northwesterly railroad right-of-way.</p> <p>The center W 1/16 sec. cor. of sec. 18.</p>
<p>20.13</p> <p>38.51</p>	<p>From the center S 1/16 sec. cor. of sec. 18.</p> <p>N. 89°13' W., on the E. and W. center line of the SW 1/4 of sec. 18.</p> <p>Over rolling land.</p> <p>The SW 1/16 sec. cor. of sec. 18.</p> <p>The S 1/16 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T20N R26E R27E S1/16 S13 S18 1988, as described in the field note record of the dependent resurvey of a portion of the E. bdy., T. 20 N., R. 26 E., executed concurrently under this same group.</p>
	<p style="text-align: center;">Metes-and-Bounds Surveys in Section 3, T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona</p> <p>From the witness point on line bet. secs. 3 and 4, at intersection with the southeasterly right-of-way of the Atchison Topeka and Santa Fe Railway Co., hereinbefore described.</p> <p>N. 44°42' E., along the southeasterly railway right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Over rolling land.</p>

Metes-and-Bounds Surveys in Section 3,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.34	<p>The witness point on the S. bdy. of sec. 34, T. 21 N., R. 27 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. WP T21N R27E S34 1988, with a steel fence post alongside the cor.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 21 N., R. 27 E., bears S. 89°32' W., 10.05 chs. dist., hereinbefore described.</p>
	<p>From the witness point on line bet. secs. 3 and 4, at intersection with the northwesterly right-of-way of the Atchison Topeka and Santa Fe Railway Co., hereinbefore described.</p> <p>N. 43°30' E., along the northwesterly railway right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Over rolling land.</p>
22.21	<p>The witness point on the S. bdy. of sec. 34, T. 21 N., R. 27 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. WP T21N R27E S34 1988, with a steel fence post alongside the cor.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 21 N., R. 27 E., bears N. 89°32' E., 2.85 chs. dist., hereinbefore described.</p>
	<p style="text-align: center;">Metes-and-Bounds Survey in Section 5, T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona</p>
	<p>From AP1, identical to the E. 1/16 sec. cor. of sec. 5 only, on the N. bdy. of the Tp., hereinbefore described.</p> <p>S. 0°04' E., on line 1-2, identical to the N. and S. center line of the NE 1/4 of sec. 5.</p> <p>Over rolling land, along fence line.</p>
17.36	<p>The witness point on the N. and S. centerline of the NE 1/4 of sec. 5, hereinbefore described.</p>
37.18	<p>Point for AP 2, on the N. and S. centerline of the NE 1/4 of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>



Metes-and-Bounds Survey in Section 5,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<div data-bbox="841 302 1084 485" data-label="Diagram"> </div> <p data-bbox="397 520 1390 583">Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p data-bbox="397 615 1052 646">Set a steel fence post alongside the cor.</p> <p data-bbox="397 678 1354 709">Cor. is located in corner of fences, extending N., S. and W.</p> <hr data-bbox="716 730 1084 741"/> <p data-bbox="397 772 813 804">S. 89°52' W., on line 2-3.</p> <p data-bbox="397 835 971 867">Over rolling land, along fence line.</p>
19.93	Intersect the N. and S. center line of sec. 5.
	From this point, the center 1/4 sec. cor. of sec. 5, bears S. 0°02' E., 4.71 chs. dist., hereinbefore described.
20.00	Point for AP 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div data-bbox="797 1220 992 1402" data-label="Diagram"> </div> <p data-bbox="397 1440 1390 1503">Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p data-bbox="397 1535 1052 1566">Set a steel fence post alongside the cor.</p> <p data-bbox="397 1598 1305 1629">Cor. is located in corner of fences, extending E. and SW.</p> <hr data-bbox="716 1650 1084 1661"/> <p data-bbox="397 1692 1305 1724">S. 48°27' W., on line 3-4 of the metes-and-bounds survey.</p> <p data-bbox="397 1755 971 1787">Over rolling land, along fence line.</p>
7.13	Intersect the E. and W. center line of sec. 5.



Metes-and-Bounds Survey in Section 5,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
42.75	<p>From this point, the center 1/4 sec. cor. of sec. 5, bears N. 89°47' E., 5.41 chs. dist., hereinbefore described.</p> <p>Point for AP 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div data-bbox="803 552 987 709" style="text-align: center;"> <p>T20N R27E S5 AP4 1993</p> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in corner of fences, extending NE. and SSW.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 22°22' E., on line 4-5.</p> <p>Over rolling land, along fence line.</p>
17.81	<p>Point for AP 5 on the line bet. sec. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div data-bbox="795 1283 990 1472" style="text-align: center;"> <p>T20N R27E S5 AP5 S8 1993</p> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in corner of fences, extending SSE., W. and NNW.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">Metes-and-Bounds Surveys in Section 7, T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the point for AP 1.</p>

Metes-and-Bounds Surveys in Section 7,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	 <p>AP1 T20N R27E S7 1993</p>
	<p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post alongside the cor.</p>
	<p>From this cor. point, the cor. of secs. 5, 6, 7 and 8, bears N. 27°26' E., 18.75 chs. dist., hereinbefore described.</p>
	<p>S. 51°38' W., on line 1-2.</p>
	<p>Over rolling land.</p>
2.50	<p>Draw, 90 ft. wide, drains S.</p>
5.30	<p>Point for AP 2.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	 <p>AP2 T20N R27E S7 1993</p>
	<p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p>
	<p>Set a steel fence post alongside the cor.</p>
	<p>_____</p>
	<p>S. 38°22' E., on line 2-3.</p>
	<p>Over rolling land.</p>
3.79	<p>Point for AP 3.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Metes-and-Bounds Surveys in Section 7,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<div style="text-align: center;">  <p>T20N R27E S7 AP3 1993</p> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in the northwesterly highway right-of-way fence, bears SW. and NE.</p> <p>From this cor. point, a highway right-of-way marker, monumented with a 3 in. angle iron, firmly set, projecting 14 ins. above the ground, mkd. HWY RW, bears S. 51°38' W., 66.64 chs. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 51°38' E., on line 3-4.</p> <p>Over rolling land, along northwesterly highway right-of-way fence.</p> <p>1.00 Draw, 50 ft. wide, drains S.</p> <p>5.30 Point for AP 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>T20N R27E S7 AP4 1993</p> </div> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located in the northwesterly highway right-of-way fence, bears SW. and NE.</p> <p>From this cor. point, a highway right-of-way marker, monumented with a brass cap, 3 ins. diam., incased in concrete, projecting 12 ins. above the ground, mkd. ARIZONA HIGHWAY DEPT. RP 102 WB 1129+54.98 1976, bears N. 51°38' E., 1.59 chs. dist.</p> <hr style="width: 20%; margin: 10px auto;"/>

Metes-and-Bounds Surveys in Section 7,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
3.79	<p>N. 38°22' W., on line 4-1 of the metes-and-bounds survey. Over rolling land. AP 1.</p>
19.81	<p>From the witness point on line bet. secs. 7 and 18, at intersection with the southeasterly right-of-way of U. S. Interstate Highway 40, hereinbefore described. N. 51°37' E., along the southeasterly highway right-of-way of U. S. Interstate Highway 40. Over rolling land, along the southeasterly highway right-of-way fence.</p>
49.91	<p>A highway right-of-way marker, monumented with a brass cap, 3 ins. diam., incased in concrete, projecting 4 ins. above the ground, mkd. ARIZONA HIGHWAY DEPT. P.O.T. RP 96 EB 1080+00 1976.</p>
98.43	<p>A highway right-of-way marker, monumented with a brass cap, 3 ins. diam., incased in concrete, projecting 6 ins. above the ground, mkd. ARIZONA HIGHWAY DEPT. P.O.T. RP 96 1099+86.87 1976.</p>
98.43	<p>The witness point on the line bet. secs. 7 and 8, at intersection with the southeasterly right-of-way of U. S. Interstate Highway 40, hereinbefore described.</p>
	<p style="text-align: center;">Metes-and-Bounds Survey in Section 8, T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona.</p>
	<p>From the witness point on line bet. secs. 7 and 8, at intersection with the northwesterly right-of-way of U. S. Interstate Highway 40, hereinbefore described. N. 51°39' E., along the northwesterly highway right-of-way of U. S. Interstate Highway 40. Over rolling land. along northwesterly highway right-of-way fence.</p>

Metes-and-Bounds Survey in Section 8,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
23.45	<p>The witness point on the line bet. secs. 5 and 8, at intersection with the northwesterly right-of-way of U. S. Interstate Highway 40, hereinbefore described.</p>
	<p style="text-align: center;">Metes-and-Bounds Surveys in Section 9, T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona.</p>
	<p>From the witness point on line bet. secs. 8 and 9, at intersection with the southeasterly right-of-way of the Atchison Topeka and Santa Fe Railway Co., hereinbefore described.</p> <p>N. 44°47' E., along the southeasterly right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Over rolling land.</p>
36.70	<p>The witness point on the line bet. secs. 4 and 9, at intersection with southeasterly right-of-way of the Atchison Topeka and Santa Fe Railway Co., hereinbefore described.</p>
	<p>From the witness point on line bet. secs. 8 and 9, at intersection with the northwesterly right-of-way of the Atchison Topeka and Santa Fe Railway Co. hereinbefore described.</p> <p>N. 44°42' E., along the northwesterly right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Over rolling land.</p>
15.00	<p>The witness point on the line bet. secs. 4 and 9, at intersection with northwesterly right-of-way of the Atchison Topeka and Santa Fe Railway Co., hereinbefore described.</p>
	<p style="text-align: center;">Metes-and-Bounds Survey in Section 17, T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona.</p>
	<p>From the witness point on line bet. secs. 17 and 18, at intersection with the southeasterly right-of-way of the Atchison Topeka and Santa Fe Railway Co. hereinbefore described.</p> <p>N. 56°45' E., along the southeasterly right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Over rolling land.</p>

Metes-and-Bounds Survey in Section 17,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
10.51	<p>The witness point on the line bet. secs. 8 and 17, at intersection with the southeasterly right-of-way of the Atchison Topeka and Santa Fe Railway Co., hereinbefore described.</p> <hr/> <p style="text-align: center;">Metes-and-Bounds Surveys in Section 18, T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona.</p> <hr/> <p>From the witness point on line bet. secs. 13 and 18 on the W. bdy. of the Tp., at intersection with the southeasterly right-of-way of the Atchison Topeka and Santa Fe Railway Co., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. WP T20N R26E R27E S13 S18 1988, as described in the field note record of the dependent resurvey of a portion of the E. bdy., T. 20 N., R. 26 E., executed concurrently under this same group.</p> <p>From this cor. point, the S. 1/16 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., bears S. 0°31' W., 1.57 chs. dist., hereinbefore described.</p> <p>N. 56°30' E., along the southeasterly right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Over rolling land.</p>
22.44	<p>The witness point on the N. and S. centerline of the SW. 1/4 of sec. 18, at intersection with the southeasterly right-of-way of the Atchison Topeka and Santa Fe Railway Co., hereinbefore described.</p> <hr/> <p>From the witness point on the E. and W. center line of sec. 18, at intersection with the southeasterly right-of-way of the Atchison Topeka and Santa Fe Railway Co., hereinbefore described.</p> <p>N. 56°31' E., along the southeasterly railway right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Over rolling land.</p>
14.15	<p>The witness point on the N. and S. centerline of sec. 18, at intersection with the southeasterly railway right-of-way of the Atchison Topeka and Santa Fe Railway Co., hereinbefore described.</p> <hr/> <p>From the witness point on the E. and W. center line of the NE 1/4 of sec. 18, at intersection with the southeasterly right-of-way of the Atchison Topeka and Santa Fe Railway Co., hereinbefore described.</p>

Metes-and Bounds Surveys in Section 18,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
28.03	<p>N. 56°23' E., along the southeasterly railway right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Over rolling land.</p> <p>The witness point on the line bet. secs. 17 and 18, at intersection with the southeasterly right-of-way of the Atchison Topeka and Santa Fe Railway Co., hereinbefore described.</p>
	<p>From the point for a witness point on line bet. secs. 13 and 18, on the W. bdy. of the Tp., at intersection with the northwesterly right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T20N R26E R27E S13 S18 1993</p> <p>Deposit a magnet in a white plastic case beneath the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>From this cor. point, the 1/4 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., bears N. 0°31' E., 11.37 chs. dist., hereinbefore described.</p> <p>From this same cor. point, a witness point on line bet. secs. 13 and 18, on the W. bdy. of Tp., bears S. 0°31' W., 3.66 chs. dist., monumented with a stainless steel post 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. WP T20N R26E R27E S13 S18 1988, as described in the field note record of the dependent resurvey of a portion of the E. bdy., T. 20 N., R. 26 E., executed concurrently under this same group.</p> <p>N. 59°15' E., along the northwesterly right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Over rolling land.</p>
21.86	<p>The center W 1/16 sec. cor. of sec. 18, hereinbefore described.</p> <p>From the witness point on the E. and W. center line of sec. 18, at intersection with the northwesterly right-of-way of the Atchison Topeka and Santa Fe Railway Co., hereinbefore described.</p>

Metes-and Bounds Surveys in Section 18,
T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.87	<p>N. 56°25' E., along the northwesterly right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Over rolling land.</p> <p>The witness point on the N. and S. centerline of sec. 18, at intersection with the northwesterly right-of-way of the Atchison Topeka and Santa Fe Railway Co., hereinbefore described.</p>
38.41	<p>From the witness point on the E. and W. center line of the NE. 1/4 of sec. 18, at intersection with the northwesterly right-of-way of the Atchison Topeka and Santa Fe Railway Co., hereinbefore described.</p> <p>N. 56°28' E., along the northwesterly right-of-way of the Atchison Topeka and Santa Fe Railway Co.</p> <p>Over rolling land.</p> <p>The witness point on the line bet. secs. 17 and 18, at intersection with the northwesterly right-of-way of the Atchison Topeka and Santa Fe Railway Co., hereinbefore described.</p>
6.36	<p>From the witness point on line bet. secs. 13 and 18 on the W. bdy. of the Tp., at intersection with the southeasterly right-of-way of U. S. Interstate Highway 40, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. WP T20N R26E R27E S13 S18 1988, as described in the field note record of the dependent resurvey of a portion of the E. bdy., T. 20 N., R. 26 E., executed concurrently under this same group.</p> <p>From this cor. point, the cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., bears N. 0°31' E., 3.85 chs. dist., hereinbefore described.</p> <p>N. 51°40' E., along the southeasterly highway right-of-way of U. S. Interstate Highway 40.</p> <p>Over rolling land.</p> <p>The witness point on the line bet. secs. 7 and 18, at intersection with the southeasterly right-of-way of U. S. Interstate Highway 40, hereinbefore described.</p>

T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	GENERAL DESCRIPTION
	<p>This survey is located approximately 6 miles southwest of the town of Sanders, Arizona.</p> <p>The terrain consists of rolling land with scattered to dense juniper and piñon pine forests scattered throughout the township. The average elevation is 6,500 feet above sea level.</p> <p>Access to the area is by way of U. S. Interstate 40 which traverses the township.</p> <p>Drainage is primarily by the Rio Puerco which drains southwesterly through the township.</p> <p>There is limited occupancy throughout this region and is used primarily for grazing and wood cutting.</p>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
W. William Foster	Surveying Technician
Clinton T. Lancaster	Surveying Technician
Wallace R. Ott, Jr.	Surveying Technician
Timothy F. Patro	Surveying Technician
Michael Searles	Surveying Aid
Jimmy James, Jr.	Surveying Aid
Johnny R. Ramirez	Surveying Aid

CERTIFICATE OF SURVEY

I, Joe R. Salazar, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 12th day of January 1987, and Supplemental Special Instructions bearing date of the 29th day of February, 1988, I have dependently resurveyed a portion of the west boundary and the subdivisional lines, and subdivided sections 5, 8 and 18 and executed metes-and-bounds surveys in sections 3, 5, 7, 8, 9, 17 and 18, in Township 20 North, Range 27 East, Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

MAR 11 1998
(Date)

Joe R. Salazar
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the west boundary and the subdivisional lines and the subdivision of sections 5, 8 and 18 and metes-and-bounds surveys in sections 3, 5, 7, 8, 9, 17 and 18, in Township 20 North, Range 27 East, Gila and Salt River Meridian, Arizona, by Joe R. Salazar, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

04/13/98
(Date)

Lenny A. Lavender
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 20 N., R. 27 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~