

ORIGINAL

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE

SURVEY OF

THE SOUTH, EAST,

WEST AND

NORTH BOUNDARIES,

AND

THE SUBDIVISIONAL LINES,

TOWNSHIP 35 NORTH, RANGE 23 EAST,

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

Jones Curtiss, Cadastral Surveyor

Under Special Instructions dated and approved February 17, 1998, which provided for the surveys included under Group Number 822 and assignment instructions dated February 17, 1998.

Survey Commenced June 9, 1998
Survey Completed August 19, 1998

INDEX DIAGRAM

TOWNSHIP 35 NORTH, RANGE 23 EAST,

GILA AND SALT RIVER MERIDIAN, ARIZONA

24	23	22	21	21	20
19 6	69 5	58 4	49 3	41 2	32 1 14
68	67	57	49	41	32
18 7	67 8	56 9	48 10	40 11	31 12 13
66	65	56	47	39	30
17 18	65 17	55 16	46 15	38 14	30 13 12
64	63	54	45	38	29
16 19	62 20	53 21	45 22	37 23	28 24 11
62	61	52	44	35	28
16 30	60 29	51 28	43 27	34 26	26 25 10
60	59	51	42	34	26
15 31	58 32	50 33	42 34	33 35	25 36 9
8	7	6	6	5	4

T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of the south, east, west and north boundaries, and the subdivisional lines, Township 35 North, Range 23 East, Gila and Salt River Meridian, Arizona.

The Eighth Standard Parallel North, (south boundary), Township 33 North, Range 24 East, was surveyed by Leonard R. Sandoval in 1989-90.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated February 17, 1998, for Group No. 822, Arizona.

The directions of all lines were determined, and distances measured, by the technique of differential positioning using Trimble Navigation 4400 Series Global Positioning System receivers utilizing the Real-Time Kinematic technique.

The geographic position of the southeast corner of the township was determined by the technique of differential positioning using the Ashtech M-Series Geodetic Positioning System. First order U. S. Coast and Geodetic Survey triangulation stations "KAYENTA 1951" and "LOHALI 1951" were used as control stations. The geographic position is as follows:

Lat.: 36°23'22.534" N. Long.: 109°48'35.349" W. NAD83(1992)

The mean magnetic declination is 12 1/2° E.

Survey of the South Boundary,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS															
	<p>Beginning at the point for the cor. of Tps. 34 and 35 N., Rs. 23 and 24 E., established at 12 miles (960.00 chs.) North of the stan. cor. of Tps. 33 N., Rs. 23 and 24 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, encircled with a collar of stone, with brass cap mkd. SC T33N R23E R24E S31 S36 1990.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="836 609 1015 829"> <tr><td colspan="2" style="text-align:center">T35N</td></tr> <tr><td style="text-align:center">R23E</td><td style="text-align:center">R24E</td></tr> <tr><td style="text-align:center">S36</td><td style="text-align:center">S31</td></tr> <tr><td colspan="2" style="text-align:center">-----</td></tr> <tr><td style="text-align:center">S 1</td><td style="text-align:center">S 6</td></tr> <tr><td colspan="2" style="text-align:center">T34N</td></tr> <tr><td colspan="2" style="text-align:center">1998</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>West, bet. secs. 1 and 36.</p> <p>Over rolling and rugged land.</p>	T35N		R23E	R24E	S36	S31	-----		S 1	S 6	T34N		1998	
T35N															
R23E	R24E														
S36	S31														

S 1	S 6														
T34N															
1998															
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="852 1249 998 1438"> <tr><td style="text-align:center">T35N R23E</td></tr> <tr><td style="text-align:center">S36</td></tr> <tr><td style="text-align:center">1/4 —</td></tr> <tr><td style="text-align:center">S 1</td></tr> <tr><td style="text-align:center">T34N</td></tr> <tr><td style="text-align:center">1998</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T35N R23E	S36	1/4 —	S 1	T34N	1998								
T35N R23E															
S36															
1/4 —															
S 1															
T34N															
1998															
80.00	<p>Point for the cor. of secs. 1, 2, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>														

Survey of the South Boundary,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<table border="1" data-bbox="852 289 1003 478"> <tr><td>T35N</td><td>R23E</td></tr> <tr><td>S35</td><td>S36</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td colspan="2">T34N</td></tr> <tr><td colspan="2">1998</td></tr> </table> <p data-bbox="407 512 1419 575">Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p data-bbox="407 606 1357 732">Land, rolling and rugged. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p>	T35N	R23E	S35	S36	<hr/>		S 2	S 1	T34N		1998	
T35N	R23E												
S35	S36												
<hr/>													
S 2	S 1												
T34N													
1998													
40.00	<p data-bbox="407 800 824 827">West, bet. secs. 2 and 35.</p> <p data-bbox="407 863 854 890">Over broken and rugged land.</p> <p data-bbox="407 926 1143 953">Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p data-bbox="407 989 1352 1052">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="852 1087 1003 1276"> <tr><td>T35N</td><td>R23E</td></tr> <tr><td colspan="2">S35</td></tr> <tr><td colspan="2">1/4 —</td></tr> <tr><td colspan="2">S 2</td></tr> <tr><td colspan="2">T34N</td></tr> <tr><td colspan="2">1998</td></tr> </table>	T35N	R23E	S35		1/4 —		S 2		T34N		1998	
T35N	R23E												
S35													
1/4 —													
S 2													
T34N													
1998													
80.00	<p data-bbox="407 1310 1419 1373">Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p data-bbox="407 1409 1127 1436">Point for the cor. of secs. 2, 3, 34, and 35.</p> <p data-bbox="407 1472 1352 1535">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="852 1570 1003 1759"> <tr><td>T35N</td><td>R23E</td></tr> <tr><td>S34</td><td>S35</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td colspan="2">T34N</td></tr> <tr><td colspan="2">1998</td></tr> </table>	T35N	R23E	S34	S35	<hr/>		S 3	S 2	T34N		1998	
T35N	R23E												
S34	S35												
<hr/>													
S 3	S 2												
T34N													
1998													
	<p data-bbox="407 1787 1419 1850">Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>												

Survey of the South Boundary,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>Land, broken and rugged. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, scrub oak and scattered brush and native grasses.</p>												
	<p>West, bet. secs. 3 and 34.</p>												
	<p>Over broken and rugged land.</p>												
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p>												
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T35N</td><td>R23E</td></tr> <tr><td></td><td>S34</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S 3</td></tr> <tr><td></td><td>T34N</td></tr> <tr><td></td><td>1998</td></tr> </table>	T35N	R23E		S34	1/4	—		S 3		T34N		1998
T35N	R23E												
	S34												
1/4	—												
	S 3												
	T34N												
	1998												
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>												
80.00	<p>Point for the cor. of secs. 3, 4, 33, and 34.</p>												
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T35N</td><td>R23E</td></tr> <tr><td>S33</td><td>S34</td></tr> <tr><td colspan="2">—</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td></td><td>T34N</td></tr> <tr><td></td><td>1998</td></tr> </table>	T35N	R23E	S33	S34	—		S 4	S 3		T34N		1998
T35N	R23E												
S33	S34												
—													
S 4	S 3												
	T34N												
	1998												
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>												
	<p>Land, broken and rugged. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, scrub oak and scattered brush and native grasses.</p>												
	<p>West, bet. secs. 4 and 33.</p>												
	<p>Over broken and rugged land.</p>												

Survey of the South Boundary,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E S33 1/4 — S 4 T34N 1998</p> <p>from which</p> <p style="text-align: center;">The marks X BO, chiseled on the face of a sandstone boulder, 12 x 10 x 7 ft., bear N. 22 1/2° W., 28 1/2 lks. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E S32 S33 — — S 5 S 4 T34N 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, broken and rugged. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, scrub oak and scattered brush and native grasses.</p>
	<p>West, bet. secs. 5 and 32.</p> <p>Over broken and rugged land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the South Boundary,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p style="text-align: center;">T35N R23E S32 1/4 — S 5 T34N 1998</p> <p>from which</p> <p style="text-align: center;">The marks X B0, chiseled on the face of a sandstone boulder, 8 x 4 x 4 ft., bear S. 54 3/4° W., 10 lks. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 5, 6, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E S31 S32 — — S 6 S 5 T34N 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, broken and rugged. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, scrub oak and scattered brush and native grasses.</p>
40.00	<p>West, bet. secs. 6 and 31.</p> <p>Over broken and rugged land.</p> <p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the South Boundary,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">T35N R23E S31 1/4 — S 6 T34N 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>61.70 Navajo Route 8066, a graded road, 25 ft. wide, bears NE in curve to right; thence descend abruptly.</p> <p>78.93 Point for the cor. of Tps. 34 and 35 N., Rs. 22 and 23 E., established at 6 miles (480 chs.) West and 12 miles (960 chs.) North of the stan. cor. of Tps. 33 N., Rs. 23 and 24 E.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T35N R22E R23E S36 S31 — — S 1 S 6 T34N 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located atop a sandstone ledge, 10 ft. high, bears SSE and NNW.</p> <p>Land, broken and rugged. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, scrub oak and scattered brush and native grasses.</p> <hr/> <p style="text-align: center;">Survey of the East Boundary, T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 34 and 35 N., Rs. 23 and 24 E., hereinbefore described.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rolling land.</p>
--------	--

Survey of the East Boundary,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
22.20	Graded road, 25 ft. wide, bears ESE and WNW.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T35N R23E R24E 1/4 S36 S31 1998 </div> Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 25, 30, 31, and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T35N R23E R24E S25 S30 ———— S36 S31 1998 </div> Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post. Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.
	North, bet. secs. 25 and 30. Over rolling land.
36.62	S. right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.
38.12	Center of Navajo Route 59, asphalt pavement, 36 ft. wide, bears E. and W.
39.66	N. right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.

Survey of the East Boundary,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R23E R24E 1/4 S25 S30 1998</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
51.80	<p>Apache County Road C580, a graded road, 25 ft. wide, bears SE and NW.</p>
80.00	<p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R23E R24E S24 S19 ----- S25 S30 1998</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 19 and 24.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the East Boundary,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T35N R23E R24E 1/4 S24 S19 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R23E R24E S13 S18 ----- S24 S19 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>North, bet. secs. 13 and 18.</p> <p>Over rolling land.</p>
31.90	<p>Navajo Route 181, a graded road, 25 ft. wide, bears NE and SW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
80.00	<p style="text-align: center;">T35N R23E R24E 1/4 S13 S18 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 7, 12, 13, and 18.</p>

Survey of the East Boundary,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="828 388 1015 588"> <tr><td colspan="2" style="text-align:center">T35N</td></tr> <tr><td style="text-align:center">R23E</td><td style="text-align:center">R24E</td></tr> <tr><td style="text-align:center">S12</td><td style="text-align:center">S 7</td></tr> <tr><td colspan="2" style="text-align:center">-----</td></tr> <tr><td style="text-align:center">S13</td><td style="text-align:center">S18</td></tr> <tr><td colspan="2" style="text-align:center">1998</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>	T35N		R23E	R24E	S12	S 7	-----		S13	S18	1998	
T35N													
R23E	R24E												
S12	S 7												

S13	S18												
1998													
	<p>North, bet. secs. 7 and 12.</p> <p>Over rolling land.</p>												
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="828 1155 1015 1323"> <tr><td colspan="2" style="text-align:center">T35N</td></tr> <tr><td style="text-align:center">R23E</td><td style="text-align:center">R24E</td></tr> <tr><td colspan="2" style="text-align:center">1/4</td></tr> <tr><td style="text-align:center">S12</td><td style="text-align:center">S 7</td></tr> <tr><td colspan="2" style="text-align:center">1998</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T35N		R23E	R24E	1/4		S12	S 7	1998			
T35N													
R23E	R24E												
1/4													
S12	S 7												
1998													
77.40	<p>Apache County Road C503, a graded road, 20 ft. wide, bears ENE and WSW.</p>												
80.00	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="828 1690 1015 1890"> <tr><td colspan="2" style="text-align:center">T35N</td></tr> <tr><td style="text-align:center">R23E</td><td style="text-align:center">R24E</td></tr> <tr><td style="text-align:center">S 1</td><td style="text-align:center">S 6</td></tr> <tr><td colspan="2" style="text-align:center">-----</td></tr> <tr><td style="text-align:center">S12</td><td style="text-align:center">S 7</td></tr> <tr><td colspan="2" style="text-align:center">1998</td></tr> </table>	T35N		R23E	R24E	S 1	S 6	-----		S12	S 7	1998	
T35N													
R23E	R24E												
S 1	S 6												

S12	S 7												
1998													

Survey of the East Boundary,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>North, bet. secs. 1 and 6.</p> <p>Over rolling land.</p>
3.35	<p>SW cor. of a stuccoed house, 36 x 22 ft., bears East, 4.85 chs. dist., long side bears N.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R23E R24E 1/4 S 1 S 6 1998</p> </div>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of Tps. 35 and 36 N., Rs. 23 and 24 E.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T36N R23E R24E S36 S31 ----- S 1 S 6 T35N 1998</p> </div>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the East Boundary,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p style="text-align: center;">Survey of the West Boundary, T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 34 and 35 N., Rs. 22 and 23 E., hereinbefore described.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over broken and rugged land on descent.</p>												
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td colspan="2">T35N</td></tr> <tr><td>R22E</td><td>R23E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S36</td><td>S31</td></tr> <tr><td colspan="2">1998</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T35N		R22E	R23E	1/4		S36	S31	1998			
T35N													
R22E	R23E												
1/4													
S36	S31												
1998													
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td colspan="2">T35N</td></tr> <tr><td>R22E</td><td>R23E</td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td colspan="2">—</td></tr> <tr><td>S36</td><td>S31</td></tr> <tr><td colspan="2">1998</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T35N		R22E	R23E	S25	S30	—		S36	S31	1998	
T35N													
R22E	R23E												
S25	S30												
—													
S36	S31												
1998													

Survey of the West Boundary,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>Land, broken and rugged. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, scrub oak and scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 25 and 30.</p> <p>Over rolling and broken land.</p>												
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T35N</td></tr> <tr><td>R22E</td><td>R23E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td colspan="2" style="text-align: center;">1998</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T35N		R22E	R23E	1/4		S25	S30	1998			
T35N													
R22E	R23E												
1/4													
S25	S30												
1998													
80.00	<p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T35N</td></tr> <tr><td>R22E</td><td>R23E</td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td colspan="2" style="border-top: 1px solid black; text-align: center;">1998</td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td colspan="2" style="text-align: center;">1998</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 19 and 24.</p> <p>Over rolling and broken land.</p>	T35N		R22E	R23E	S24	S19	1998		S25	S30	1998	
T35N													
R22E	R23E												
S24	S19												
1998													
S25	S30												
1998													
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p>												

Survey of the West Boundary,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R22E R23E 1/4 S24 S19 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T35N R22E R23E S13 S18 ----- S24 S19 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over rolling land.</p>
39.75	Trail road, bears E. and W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R22E R23E 1/4 S13 S18 1998</p>

Survey of the West Boundary,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>												
80.00	<p>Point for the cor. of secs. 7, 12, 13, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T35N</td></tr> <tr><td>R22E</td><td>R23E</td></tr> <tr><td>S12</td><td>S 7</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2">1998</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 7 and 12.</p> <p>Over rolling land.</p>	T35N		R22E	R23E	S12	S 7	<hr/>		S13	S18	1998	
T35N													
R22E	R23E												
S12	S 7												
<hr/>													
S13	S18												
1998													
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T35N</td></tr> <tr><td>R22E</td><td>R23E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S12</td><td>S 7</td></tr> <tr><td colspan="2">1998</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T35N		R22E	R23E	1/4		S12	S 7	1998			
T35N													
R22E	R23E												
1/4													
S12	S 7												
1998													
76.00	<p>Graded road, 15 ft. wide, bears E. and W.</p>												
80.00	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												

Survey of the West Boundary,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS																																					
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T35N</td></tr> <tr><td style="text-align: center;">R22E</td><td style="text-align: center;">R23E</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">1998</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over rolling and broken land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T35N</td></tr> <tr><td style="text-align: center;">R22E</td><td style="text-align: center;">R23E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td colspan="2" style="text-align: center;">1998</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>80.00 Point for the cor. of Tps. 35 and 36 N., Rs. 22 and 23 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T36N</td></tr> <tr><td style="text-align: center;">R22E</td><td style="text-align: center;">R23E</td></tr> <tr><td style="text-align: center;">S36</td><td style="text-align: center;">S31</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td colspan="2" style="text-align: center;">T35N</td></tr> <tr><td colspan="2" style="text-align: center;">1998</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T35N		R22E	R23E	S 1	S 6	-----		S12	S 7	1998		T35N		R22E	R23E	1/4		S 1	S 6	1998		T36N		R22E	R23E	S36	S31	-----		S 1	S 6	T35N		1998	
T35N																																					
R22E	R23E																																				
S 1	S 6																																				

S12	S 7																																				
1998																																					
T35N																																					
R22E	R23E																																				
1/4																																					
S 1	S 6																																				
1998																																					
T36N																																					
R22E	R23E																																				
S36	S31																																				

S 1	S 6																																				
T35N																																					
1998																																					

Survey of the West Boundary,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p> <hr/> <p style="text-align: center;">Survey of the North Boundary, T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 35 and 36 N., Rs. 23 and 24 E., hereinbefore described.</p> <p>West, bet. secs. 1 and 36.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E S36 1/4 — S 1 T35N 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
61.90	<p>Trading Post Wash, 30 ft. wide, 15 ft. deep, drains N.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E S35 S36 — — S 2 S 1 T35N 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the North Boundary,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>West, bet. secs. 2 and 35.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E S35 1/4 — S 2 T35N 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E S34 S35 — — S 3 S 2 T35N 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on gradual E. slope of White Top Mesa, bears NNE and SSW.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>West, bet. secs. 3 and 34.</p> <p>Over rolling land atop White Top Mesa.</p>

Survey of the North Boundary,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E S34 1/4 — S 3 T35N 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E S33 S34 — — S 4 S 3 T35N 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
40.00	<p>West, bet. secs. 4 and 33.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E S33 1/4 — S 4 T35N 1998</p>

Survey of the North Boundary,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS													
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.												
40.50	W. rim of White Top Mesa, bears N. and S.; thence descend abruptly to gently rolling land.												
56.48	E. right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.												
57.99	Center of Navajo Route 59, asphalt pavement, 36 ft. wide, bears N. and S.												
59.50	W. right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.												
80.00	Point for the cor. of secs. 4, 5, 32, and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.												
	<table style="margin: auto;"> <tr><td colspan="2">T36N R23E</td></tr> <tr><td>S32</td><td>S33</td></tr> <tr><td colspan="2">— —</td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td colspan="2">T35N</td></tr> <tr><td colspan="2">1998</td></tr> </table>	T36N R23E		S32	S33	— —		S 5	S 4	T35N		1998	
T36N R23E													
S32	S33												
— —													
S 5	S 4												
T35N													
1998													
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.												
	Cor. is located 90 lks. S. of Burro Wash, 25 ft. wide, 2 ft. deep, drains E.												
	Land, gently rolling to broken. Soil, sandy and rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.												
	West, bet. secs. 5 and 32.												
	Over rolling land.												
3.10	Burro Wash, 30 ft. wide, 4 ft. deep, drains ENE.												
39.50	Wash, 3 ft. wide, 2 ft. deep, drains NW.												
40.00	Point for the 1/4 sec. cor. of secs. 5 and 32 Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.												

Survey of the North Boundary,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T36N R23E S32 1/4 — S 5 T35N 1998
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 5, 6, 31, and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, encircled with a collar of stone, with brass cap mkd.
	T36N R23E S31 S32 ———— S 6 S 5 T35N 1998
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
	Cor. is located on SE slope of a prominent spur ridge, bears ENE and WSW, 90 lks. E. of SE rim.
	Land, rolling. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.
	West, bet. secs. 6 and 31.
	Over rolling and broken land across spur ridges.
9.00	NW rim of a prominent spur ridge, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the North Boundary,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T36N R23E S31 1/4 — S 6 T35N 1998
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
78.38	The cor. of Tps. 35 and 36 N., Rs. 22 and 23 E., hereinbefore described. Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.
<hr/> Survey of the Subdivisional lines, T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona <hr/>	
	From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°01' W., bet. secs. 35 and 36.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 35 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T35N R23E 1/4 S35 S36 1998
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
60.90	Graded road, 25 ft. wide, bears ESE and WSW.
80.00	Point for the cor. of secs. 25, 26, 35, and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<table border="1" data-bbox="844 294 998 451"> <tr> <td>T35N</td> <td>R23E</td> </tr> <tr> <td>S26</td> <td>S25</td> </tr> <tr> <td>S35</td> <td>S36</td> </tr> <tr> <td colspan="2" style="text-align: center;">1998</td> </tr> </table> <p data-bbox="402 483 1404 556">Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p data-bbox="402 577 1347 714">Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p>	T35N	R23E	S26	S25	S35	S36	1998			
T35N	R23E										
S26	S25										
S35	S36										
1998											
	<p data-bbox="402 766 1421 840">From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p data-bbox="402 861 836 903">West, bet. secs. 25 and 36.</p> <p data-bbox="402 924 690 966">Over rolling land.</p>										
40.00	<p data-bbox="402 997 1153 1029">Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p data-bbox="402 1050 1339 1123">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>										
	<table border="1" data-bbox="844 1155 998 1312"> <tr> <td>T35N</td> <td>R23E</td> </tr> <tr> <td></td> <td>S25</td> </tr> <tr> <td></td> <td>1/4 —</td> </tr> <tr> <td></td> <td>S36</td> </tr> <tr> <td colspan="2" style="text-align: center;">1998</td> </tr> </table> <p data-bbox="402 1344 1404 1417">Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T35N	R23E		S25		1/4 —		S36	1998	
T35N	R23E										
	S25										
	1/4 —										
	S36										
1998											
80.00	<p data-bbox="402 1438 990 1480">The cor. of secs. 25, 26, 35, and 36.</p> <p data-bbox="402 1501 1347 1638">Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p>										
	<p data-bbox="402 1690 941 1732">N. 0°01' W., bet. secs. 25 and 26.</p> <p data-bbox="402 1753 690 1795">Over rolling land.</p>										
23.40	<p data-bbox="402 1921 1071 1953">Graded road, 20 ft. wide, bears NE and SW.</p>										

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
25.30	Wash, 40 ft. wide, 12 ft. deep, drains E.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T35N R23E 1/4 S26 S25 1998 </div>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
40.70	Power line, bears E. and W.
60.90	SW right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.
63.29	Center of Navajo Route 59, asphalt pavement, 36 ft. wide, bears SE and NW.
64.94	A brass tablet, 3 ins. diam., set in a concrete collar, 6 ins. diam., set 6 ins. below the surface of the ground, bears East, 61 lks. dist., with top mkd. BIA ROADS, and witnessed by an angle iron nearby, with marks POT 692+04.35 visible on a face.
65.69	NE right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.
80.00	Point for the cor. of secs. 23, 24, 25, and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T35N R23E S23 S24 ----- S26 S25 1998 </div>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
	Cor. is located 18 lks. S. of an underground water line, bears SE and NW.

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p>
	<p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>West, bet. secs. 24 and 25.</p>
	<p>Over rolling land.</p>
26.80	<p>Apache County Road C580, a graded road, 25 ft. wide, bears SSE and NNW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 24 and 25. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R23E S24 1/4 — S25 1998</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 23, 24, 25, and 26.</p>
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 23 and 24.</p>
	<p>Over rolling land.</p>
33.70	<p>Navajo Route 181, a graded road, 20 ft. wide, bears NE and SW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T35N R23E 1/4 S23 S24 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 13, 14, 23, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R23E S14 S13 ----- S23 S24 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 13 and 24.</p> <p>Over rolling land.</p>
28.40	<p>Navajo Route 181, a graded road, 20 ft. wide, bears NE and SW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R23E S13 1/4 — S24 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 13, 14, 23, and 24.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/>
40.00	<p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E 1/4 S14 S13 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 11, 12, 13, and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E S11 S12 ----- S14 S13 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 12 and 13.</p> <p>Over rolling land.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E S12 1/4 — S13 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 11, 12, 13, and 14.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over rolling land.</p>
15.00	<p>Apache County Road C503, a graded road, 18 ft. wide, bears NE and SW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E 1/4 S11 S12 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<table style="margin: auto;"> <tr><td colspan="2">T35N R23E</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td colspan="2">— —</td></tr> <tr><td>S11</td><td>S12</td></tr> <tr><td colspan="2">1998</td></tr> </table>	T35N R23E		S 2	S 1	— —		S11	S12	1998	
T35N R23E											
S 2	S 1										
— —											
S11	S12										
1998											
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>										
	<hr/> <p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 1 and 12.</p> <p>Over rolling land.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>										
	<table style="margin: auto;"> <tr><td colspan="2">T35N R23E</td></tr> <tr><td colspan="2">S 1</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td colspan="2">S12</td></tr> <tr><td colspan="2">1998</td></tr> </table>	T35N R23E		S 1		1/4	—	S12		1998	
T35N R23E											
S 1											
1/4	—										
S12											
1998											
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 1, 2, 11, and 12.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>										
	<hr/> <p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Over rolling land.</p>										
11.00	<p>Trading Post Wash, 20 ft. wide, 6 ft. deep, drains NE.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p>										

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E 1/4 S 2 S 1 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over broken and rugged land.</p> <p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T35N R23E 1/4 S34 S35 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the brass tablet.</p>
46.20	<p>Edge of cliff, bears SSE and NNW; thence descend abruptly.</p>
80.00	<p>Point for the cor. of secs. 26, 27, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T35N R23E S27 S26 ----- S34 S35 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, broken and rugged. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, scrub oak and scattered brush and native grasses.</p>
	<p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>West, bet. secs. 26 and 35.</p> <p>Over rolling and broken land.</p>
6.80	Graded road, 25 ft. wide, bears N. and S.
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R23E S26 1/4 — S35 1998</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 26, 27, 34, and 35.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over rolling land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27.

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T35N R23E 1/4 S27 S26 1998</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
52.55	Wash, 25 ft. wide, 10 ft. deep, drains NE.
53.34	S. right-of-way fence of Navajo Route 59 Rough Rock Spur, barbed wire, 5 strands, parallels Spur.
54.56	Center of Navajo Route 59 Rough Rock Spur, asphalt pavement, 36 ft. wide, bears ENE in curve to left.
55.80	N. right-of-way fence of Navajo Route 59 Rough Rock Spur, barbed wire, 5 strands, parallels Spur.
80.00	Point for the cor. of secs. 22, 23, 26, and 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T35N R23E S22 S23 ----- S27 S26 1998</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
	Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.
	From the cor. of secs. 23, 24, 25, and 26.
	West, bet. secs. 23 and 26.
	Over rolling and broken land.
11.68	NE right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
13.58	Center of Navajo Route 59, asphalt pavement, 36 ft. wide, bears SE and NW.
15.54	SW right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.
36.88	A steel fence post serving as cor. of barbed wire fences, 5 strands, at NE cor. of Navajo Housing Authority housing complex, bears North, 35 lks. dist., fences extending ENE, SSE and WSW.
37.43	SE right-of-way fence of Navajo Route 59 Rough Rock Spur, barbed wire, 5 strands, parallels Spur.
39.50	Center of Navajo Route 59 Rough Rock Spur, asphalt pavement, 36 ft. wide, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of the ground, with brass cap mkd.
	T35N R23E S23 1/4 — S26 1998
	from which
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 36°00' E., 94.0 ft. dist., with brass cap mkd. T35N R23E 1/4 S26 RM 94.0 FT. TO COR. 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 36°00' W., 58.0 ft. dist., with brass cap mkd. T35N R23E 1/4 S23 RM 58.0 FT. TO COR. 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post at the 1/4 sec. cor.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Cor. is located 4 lks. W. of the NW edge of asphalt pavement of Navajo Route 59 Rough Rock Spur, bears ENE and WSW; and 1.58 chs. E. of NW right-of-way fence of Navajo Route 59 Rough Rock Spur, barbed wire, 5 strands, parallels Spur.
80.00	The cor. of secs. 22, 23, 26, and 27. Land, rolling. Soil, sandy clay. Timber, sparse piñon and juniper; undergrowth, scattered brush and native grasses.
	N. 0°01' W., bet. secs. 22 and 23. Over rolling land.
35.80	Graded road, 25 ft. wide, bears NNE and SSW.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T35N R23E 1/4 S22 S23 1998
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 14, 15, 22, and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T35N R23E S15 S14 ----- S22 S23 1998
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 13, 14, 23, and 24.</p>
	<p>West, bet. secs. 14 and 23.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R23E S14 1/4 — S23 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
64.71	<p>NE right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.</p>
66.49	<p>Center of Navajo Route 59, asphalt pavement, 36 ft. wide, bears SSE and NNW.</p>
68.23	<p>SW right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.</p>
80.00	<p>The cor. of secs. 14, 15, 22, and 23.</p>
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 14 and 15.</p>
	<p>Over rolling land.</p>
19.09	<p>SW right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.</p>
21.96	<p>Center of Navajo Route 59, asphalt pavement, 36 ft. wide, bears SSE and NNW.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
24.80	NE right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T35N R23E 1/4 S15 S14 1998 </div> Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
67.60	Trading Post Wash, 200 ft. wide, 1 ft. deep, drains NNE.
80.00	Point for the cor. of secs. 10, 11, 14, and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T35N R23E S10 S11 --- --- S15 S14 1998 </div> Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post. Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.
	From the cor. of secs. 11, 12, 13, and 14. West, bet. secs. 11 and 14. Over rolling land.
19.10	Apache County Road C503, a graded road, 25 ft. wide, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T35N R23E S11 1/4 — S14 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
66.00	<p>Trading Post Wash, 200 ft. wide, 1 ft. deep, drains NE.</p>
80.00	<p>The cor. of secs. 10, 11, 14, and 15.</p>
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<hr/>
	<p>N. 0°01' W., bet. secs. 10 and 11.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R23E 1/4 S10 S11 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 10, and 11.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R23E S 3 S 2 ----- S10 S11 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 1, 2, 11, and 12.</p>
	<p>West, bet. secs. 2 and 11.</p>
10.80	<p>Trading Post Wash, 40 ft. wide, 10 ft. deep, drains NNE.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R23E</p>
	<p style="text-align: center;">S 2</p>
	<p style="text-align: center;">1/4 —</p>
	<p style="text-align: center;">S11</p>
	<p style="text-align: center;">1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 2, 3, 10, and 11.</p>
	<p>Land, rolling.</p>
	<p>Soil, sandy clay.</p>
	<p>No timber; scattered brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 2 and 3.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R23E</p>
	<p style="text-align: center;">1/4</p>
	<p style="text-align: center;">S 3 S 2</p>
	<p style="text-align: center;">1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over broken and rugged land on descent.</p> <p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E 1/4 S33 S34 1998</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 27, 28, 33, and 34.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T35N R23E S28 S27 ----- S33 S34 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, broken and rugged. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, scrub oak and scattered brush and native grasses.</p>
	<p>From the cor. of secs. 26, 27, 34, and 35.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	West, bet. secs. 27 and 34. Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T35N R23E S27 1/4 — S34 1998</div>
80.00	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post. The cor. of secs. 27, 28, 33, and 34. Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.
	N. 0°02' W., bet. secs. 27 and 28. Over rolling land.
37.31	SE right-of-way fence of Navajo Route 8066, barbed wire, 5 strands, parallels highway.
38.44	Center of Navajo Route 8066, asphalt pavement, 36 ft. wide, bears NE in curve to right.
39.61	NW right-of-way fence of Navajo Route 8066, barbed wire, 5 strands, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T35N R23E 1/4 S28 S27 1998</div>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS															
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located SE of an area cleared for rodeo grounds.</p>														
76.30	Graded road, 20 ft. wide, bears NNE and SSW.														
80.00	<p>Point for the cor. of secs. 21, 22, 27, and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T35N</td><td>R23E</td></tr> <tr><td>S21</td><td> </td><td>S22</td></tr> <tr><td colspan="3"><hr/></td></tr> <tr><td>S28</td><td> </td><td>S27</td></tr> <tr><td colspan="3">1998</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 1.80 chs. W. of a graded road, 20 ft. wide, bears NNE and SSW.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p>	T35N	R23E	S21		S22	<hr/>			S28		S27	1998		
T35N	R23E														
S21		S22													
<hr/>															
S28		S27													
1998															
40.00	<p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>West, bet. secs. 22 and 27.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T35N</td><td>R23E</td></tr> <tr><td colspan="2">S22</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td colspan="2">S27</td></tr> <tr><td colspan="2">1998</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T35N	R23E	S22		1/4	—	S27		1998					
T35N	R23E														
S22															
1/4	—														
S27															
1998															

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 21, 22, 27, and 28.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over rolling land.</p>
32.00	Trading Post Wash, 36 ft. wide, 12 ft. deep, drains E.
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R23E 1/4 S21 S22 1998</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 15, 16, 21, and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R23E S16 S15 ----- S21 S22 1998</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>West, bet. secs. 15 and 22.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T35N R23E
	S15
	1/4 —
	S22
	1998
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
43.10	Trading Post Wash, 35 ft. wide, 12 ft. deep, drains N.
80.00	The cor. of secs. 15, 16, 21, and 22.
	Land, rolling.
	Soil, sandy clay.
	No timber; scattered brush and native grasses.
	N. 0°02' W., bet. secs. 15 and 16.
	Over rolling land.
12.30	Wash, 100 ft. wide, 15 ft. deep, drains ENE.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T35N R23E
	1/4
	S16 S15
	1998
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
67.20	Apache County Road C579, a graded road, 20 ft. wide, bears ENE and WSW.
80.00	Point for the cor. of secs. 9, 10, 15, and 16.

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a magnet enclosed in a 1 x 1 x 2 ins. white plastic case, 26 ins. below the surface of the ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 40°00' E., 30.0 ft. dist., with brass cap mkd. T35N R23E S15 RM 30.0 FT. TO COR. 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 40°00' W., 40.0 ft. dist., with brass cap mkd. T35N R23E S9 RM 40.0 FT. TO COR. 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on SE bank of a wash, 10 ft. wide, 2 ft. deep, drains NE.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>West, bet. secs. 10 and 15.</p> <p>Over rolling land.</p>
8.46	<p>U. S. Coast and Geodetic Survey first order class II benchmark "F 32", bears South, 4.54 chs. dist., monumented with a standard brass tablet, 3 1/2 ins. diam., set in a concrete collar, 9 ins. square, firmly set, projecting 7 ins. above ground, with top mkd. ELEV 6004.007 F32 1933.</p>
34.05	<p>NE right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.</p>
35.79	<p>Center of Navajo Route 59, asphalt pavement, 36 ft. wide, bears SSE and NNW.</p>
37.58	<p>SW right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E S10 1/4 — S15 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
56.70	Apache County Road C579, a graded road, 20 ft. wide, bears ENE and WSW.
80.00	<p>The cor. of secs. 9, 10, 15, and 16.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E 1/4 S 9 S10 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
46.85	SW right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.
48.66	Center of Navajo Route 59, asphalt pavement, 36 ft. wide, bears SE and NW.
50.52	NW right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.
80.00	Point for the cor. of secs. 3, 4, 9, and 10.

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E S 4 S 3 ----- S 9 S10 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>West, bet. secs. 3 and 10.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E S 3 1/4 — S10 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 3, 4, 9, and 10.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
40.00	<p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T35N R23E 1/4 S 4 S 3 1998</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
80.00	The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described.
	Land, rolling.
	Soil, sandy clay.
	No timber; scattered brush and native grasses.
	From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°03' W., bet. secs. 32 and 33.
	Over broken and rugged land.
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T35N R23E 1/4 S32 S33 1998</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 28, 29, 32, and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T35N R23E S29 S28</p>
	<p style="text-align: center;">S32 S33 1998</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, broken and rugged. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, scrub oak and scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>West, bet. secs. 28 and 33.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T35N R23E S28 1/4 — S33 1998</p> <p>from which</p> <p style="text-align: center;">The marks X B0, chiseled on sandstone bedrock, bear N. 46 1/4° W., 48 lks. dist.</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 28, 29, 32, and 33.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p>
27.60	<p>N. 0°03' W., bet. secs. 28 and 29.</p> <p>Over rolling land.</p> <p>Navajo Route 8066, a graded road, 25 ft. wide, bears ENE and WSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T35N R23E 1/4 S29 S28 1998</p>
	from which
	<p style="text-align: center;">A juniper, 9 ins. diam., bears N. 87 3/4° E., 14 lks. dist., mkd. 1/4 S28 BT.</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
69.90	Graded road, 25 ft. wide, bears SE and NW.
79.00	Graded road, 25 ft. wide, bears NE and SW.
80.00	Point for the cor. of secs. 20, 21, 28, and 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T35N R23E S20 S21 ----- S29 S28 1998</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
	Cor. is located 90 lks. W. of a graded road, 25 ft. wide, bears NE and SW.
	<p>Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p>
	From the cor. of secs. 21, 22, 27, and 28.
	West, bet. secs. 21 and 28.
	Over rolling land.
16.80	Trading Post Wash, 40 ft. wide, 10 ft. deep, drains ENE.

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E S21 1/4 — S28 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
57.10	Apache County Road C579, a graded road, 25 ft. wide, bears SE and NW.
80.00	<p>The cor. of secs. 20, 21, 28, and 29.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 20 and 21.</p> <p>Over rolling land.</p>
29.70	Apache County Road C579, a graded road, 25 ft. wide, bears ESE and WNW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E 1/4 S20 S21 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
79.60	Apache County Road C579, a graded road, 25 ft. wide, bears NE and SW.
80.00	Point for the cor. of secs. 16, 17, 20, and 21.

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of the ground, with brass cap mkd.</p> <table border="1" data-bbox="857 401 1008 554"> <tr> <td>T35N</td> <td>R23E</td> </tr> <tr> <td>S17</td> <td>S16</td> </tr> <tr> <td>S20</td> <td>S21</td> </tr> <tr> <td colspan="2">1998</td> </tr> </table> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°00' W., 50.0 ft. dist., with brass cap mkd. T35N R23E S20 RM 50.0 FT. TO COR. 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' W., 50.0 ft. dist., with brass cap mkd. T35N R23E S17 RM 50.0 FT. TO COR. 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post at the sec. cor.</p> <p>Cor. is located on NW shoulder of Apache County Road C579, a graded road, 25 ft. wide, bears NE and SW.</p> <p>Land, rolling. Soil, sandy clay. Timber, sparse piñon and juniper; undergrowth, scattered brush and native grasses.</p>	T35N	R23E	S17	S16	S20	S21	1998	
T35N	R23E								
S17	S16								
S20	S21								
1998									
	<p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>West, bet. secs. 16 and 21.</p> <p>Over rolling land.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>								

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T35N R23E S16 1/4 — S21 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
75.40	<p>Graded road, 25 ft. wide, bears SSE and NNW.</p>
80.00	<p>The cor. of secs. 16, 17, 20, and 21.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over rolling land.</p>
39.75	<p>Trail road, bears NE and SW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R23E 1/4 S17 S16 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Thence descend over broken land.</p>
80.00	<p>Point for the cor. of secs. 8, 9, 16, and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R23E S 8 S 9 ----- S17 S16 1998</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling to broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>West, bet. secs. 9 and 16.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T35N R23E S 9 1/4 — S16 1998</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on E. edge of wash, 6 ft. wide, 1 ft. deep, drains N.</p> <p>The cor. of secs. 8, 9, 16, and 17.</p> <p>Land, rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.</p>
40.00	<p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">T35N R23E 1/4 S 8 S 9 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>75.70 Graded road, 25 ft. wide, bears ENE and WSW.</p> <p>80.00 Point for the cor. of secs. 4, 5, 8, and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E S 5 S 4 ----- S 8 S 9 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E S 4 1/4 — S 9 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
--------	---

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
54.16	NE right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.
57.79	Center of Navajo Route 59, asphalt pavement, 36 ft. wide, bears ESE in curve to left.
60.35	SW right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.
68.40	Graded road, 20 ft. wide, bears ENE and WSW.
80.00	The cor. of secs. 4, 5, 8, and 9. Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.
	<hr/>
	N. 0°03' W., bet. secs. 4 and 5. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T35N R23E 1/4 S 5 S 4 1998 </div>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
80.00	The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described. Land, rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.
	<hr/>
	From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., hereinbefore described. N. 0°03' W., bet. secs. 31 and 32. Over broken and rugged land on descent.

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E 1/4 S31 S32 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E S30 S29 ----- S31 S32 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, broken and rugged. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, scrub oak and scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>West, bet. secs. 29 and 32.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E S29 1/4 — S32 1998</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
80.00	The cor. of secs. 29, 30, 31, and 32. Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.
	West, bet. secs. 30 and 31. Over rolling and broken land.
32.80	Navajo Route 8066, a graded road, 20 ft. wide, bears NNE in curve to right.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. T35N R23E S30 1/4 — S31 1998
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
78.84	The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., hereinbefore described. Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.
	From the cor. of secs. 29, 30, 31, and 32. N. 0°03' W., bet. secs. 29 and 30. Over rolling and broken land.
23.00	Navajo Route 8066, a graded road, 20 ft. wide, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30.

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E 1/4 S30 S29 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 19, 20, 29, and 30.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T35N R23E S19 S20 ----- S30 S29 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>West, bet. secs. 20 and 29.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T35N R23E S20 1/4 — S29 1998</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>from which</p> <p>The marks X B0, chiseled on sandstone bedrock, bear N. 19 1/4° E., 22 1/2 lks. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 19, 20, 29, and 30.</p> <p>Land, rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p>
40.00	<p>West, bet. secs. 19 and 30.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E S19 1/4 — S30 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
78.75	<p>The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over rolling to broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R23E 1/4 S19 S20 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 17, 18, 19, and 20.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R23E S18 S17 ----- S19 S20 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Land, rolling to broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p>
	<p>From the cor. of secs. 16, 17, 20, and 21.</p>
	<p>West, bet. secs. 17 and 20.</p>
	<p>Over rolling and broken land.</p>
39.70	<p>Burro Wash, 15 ft. wide, 10 ft. deep, drains SW in curve to left.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p>
	<p>Set a magnet enclosed in a 1 x 1 x 2 ins. white plastic case, 26 ins. below the surface of the ground.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 30°00' E., 80.0 ft. dist., with brass cap mkd. T35N R23E 1/4 S17 RM 80.0 FT. TO COR. 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 60°00' E., 60.0 ft. dist., with brass cap mkd. T35N R23E 1/4 S20 RM 60.0 FT. TO COR. 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. falls on the N. edge of Burro Wash, 15 ft. wide, 10 ft. deep, drains W. in curve to right; and 90 lks. E. of same wash, drains NNW in curve to right.</p>
80.00	<p>The cor. of secs. 17, 18, 19, and 20.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p>
40.00	<p>West, bet. secs. 18 and 19.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E S18 1/4 — S19 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
78.66	<p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., hereinbefore described.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p>
<p>40.00</p>	<p>From the cor. of secs. 17, 18, 19, and 20. N. 0°03' W., bet. secs. 17 and 18. Over rolling and broken land. Point for the 1/4 sec. cor. of secs. 17 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E 1/4 S18 S17 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
<p>57.70</p>	<p>Burro Wash, 30 ft. wide, 5 ft. deep, drains W.</p>
<p>80.00</p>	<p>Point for the cor. of secs. 7, 8, 17, and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E S 7 S 8 ----- S18 S17 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p> <p>From the cor. of secs. 8, 9, 16, and 17. West, bet. secs. 8 and 17.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. T35N R23E S 8 1/4 — S17 1998 Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
80.00	The cor. of secs. 7, 8, 17, and 18. Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.
	West, bet. secs. 7 and 18. Over rolling land.
5.70	Burro Wash, 30 ft. wide, 15 ft. deep, drains NW.
39.25	Wash, 25 ft. wide, 3 ft. deep, drains N.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. T35N R23E S 7 1/4 — S18 1998 Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
78.57	The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., hereinbefore described.

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p>
	<p>From the cor. of secs. 7, 8, 17, and 18. N. 0°03' W., bet. secs. 7 and 8. Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E 1/4 S 7 S 8 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
51.60	<p>Burro Wash, 30 ft. wide, 10 ft. deep, drains NE.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 7, and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E S 6 S 5 ----- S 7 S 8 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p> <p>From the cor. of secs. 4, 5, 8, and 9. West, bet. secs. 5 and 8.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
36.20	Trail road, bears ENE and WSW.
39.995	Point for the 1/4 sec. cor. of secs. 5 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. T35N R23E S 5 1/4 — S 8 1998 Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
46.10	Burro Wash, 30 ft. wide, 5 ft. deep, drains NNE.
79.99	The cor. of secs. 5, 6, 7, and 8. Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.
	West, bet. secs. 6 and 7. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. T35N R23E S 6 1/4 — S 7 1998 Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
78.48	The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., hereinbefore described.

Survey of the Subdivisional Lines,
T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p>
	<p>From the cor. of secs. 5, 6, 7, and 8. N. 0°04' W., bet. secs. 5 and 6. Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R23E 1/4 S 6 S 5 1998</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>

T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The area surveyed is within the Navajo Indian Reservation, around the community of Rough Rock, Arizona. The terrain is rolling to rugged land. The most rugged areas are along the south boundary on the north slope of Black Mesa. The drainage is northerly. Principal drainages are Trading Post Wash and Burro Wash.

The elevation varies from 5,700 to 7,400 feet above sea level. The soil is mostly sandy and rocky clay with some sandstone outcrops. The timber is primarily piñon and juniper, ranging from moderate in the southern portion to nonexistent in the northern portion. The undergrowth varies from scrub oak in the southern portion to scattered brush and native grasses elsewhere.

Principal access to the township is provided by Navajo Route 59, which enters the township in section 4 and exits in section 25. There are other paved, graded and trail roads throughout the township. The community of Rough Rock, along with several schools and a few Navajo Housing Authority complexes, are primarily located in sections 26, 27, and 28.

Much of the township is used for grazing of livestock and there is no evidence of current mining activity.

The mean magnetic declination of $12\ 1/2^\circ$ E. was derived from the United States Geological Survey computer program GEOMAGIX utilizing the Regional Magnetic Field Model for Epoch 1995 for the dates of survey.

UNITED STATES
 DEPARTMENT OF THE INTERIOR
 BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Daniel Bryan	Engineering Technician
Wilfred Chee	Engineering Technician
Edward Clarke	Engineering Technician
Reuben Mason	Engineering Technician
Barney Woodie	Engineering Technician

CERTIFICATE OF SURVEY

I, Jones Curtiss, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 17th day of February 1998, I have surveyed the south, east, west and north boundaries, and the subdivisional lines, Township 35 North, Range 23 East, of the Gila and Salt River Meridian, in the state of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

November 18, 1999
(Date)

Jones Curtiss
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the survey of the south, east, west and north boundaries, and the subdivisional lines, Township 35 North, Range 23 East, Gila and Salt River Meridian, Arizona, executed by Jones Curtiss, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

December 1, 1999
(Date)

Kenny D Ravnikar
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 35 N., R. 23 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____~~
~~(Date)~~

~~_____~~
~~(Chief Cadastral Surveyor of Arizona)~~