

# ORIGINAL

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES  
OF THE

---

SURVEY

---

OF

---

THE EAST AND

---

WEST BOUNDARIES,

---

AND

---

THE SUBDIVISIONAL LINES,

---

TOWNSHIP 36 NORTH, RANGE 23 EAST,

---

Of the Gila and Salt River Meridian,  
In the State of Arizona

---

EXECUTED BY

Jones Curtiss, Cadastral Surveyor

---

Under Special Instructions dated and approved February 17, 1998, which provided for the surveys included under Group Number 822 and assignment instructions dated February 17, 1998.

Survey Commenced July 27, 1998

Survey Completed September 8, 1998

INDEX DIAGRAM

TOWNSHIP 36 NORTH, RANGE 23 EAST,

GILA AND SALT RIVER MERIDIAN, ARIZONA

	31	32	33	34	35	36
	62	62	50	40	32	23
14	6	61 5	48 4	39 3	31 2	22 1 8
	60	60	48	39	30	22
13	7	59 8	47 9	38 10	29 11	21 12 7
	58	58	46	37	29	20
12	18	57 17	46 16	37 15	28 14	19 13 6
	56	55	45	36	27	19
11	19	55 20	44 21	35 22	27 23	18 24 5
	54	53	44	35	26	17
10	30	53 29	43 28	34 27	25 26	16 25 4
	52	51	42	33	25	16
9	31	50 32	41 33	32 34	24 35	15 36 4

## T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the survey of the east and west boundaries, and the subdivisional lines, Township 36 North, Range 23 East, Gila and Salt River Meridian, Arizona.

The Ninth Standard Parallel North, (south boundary), Townships 37 North, Ranges 22 and 23 East, and the north boundary of Township 35 North, Range 23 East, were surveyed by Jones Curtiss concurrently under this same group.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated February 17, 1998, for Group No. 822, Arizona.

The directions of all lines were determined, and distances measured, by the technique of differential positioning using Trimble Navigation 4400 Series Global Positioning System receivers utilizing the Real-Time Kinematic technique.

The geographic position of the southeast corner of the township was determined by the technique of differential positioning using the Ashtech M-Series Geodetic Positioning System. First order U. S. Coast and Geodetic Survey triangulation stations "KAYENTA 1951" and "LOHALI 1951" were used as control stations. The geographic position is as follows:

Lat.: 36°28'35.707" N. Long.: 109°48'35.349" W. NAD83(1992)

The mean magnetic declination is 12 1/2° E.

Survey of the East Boundary,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Beginning at the cor. of Tps. 35 and 36 N., Rs. 23 and 24 E., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 35 N., R. 23 E., executed concurrently under this same group.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T36N R23E R24E 1/4 S36   S31 1998</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T36N R23E   R24E S25   S30 ----- S36   S31 1998</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 25 and 30.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p>

Survey of the East Boundary,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E R24E 1/4 S25   S30 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Thence across poorly defined floodplain of Trading Post Wash.</p> <p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E   R24E S24   S19 ----- S25   S30 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling to nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
40.00	<p>North, bet. secs. 19 and 24.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E R24E 1/4 S24   S19 1998</p>

Survey of the East Boundary,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS													
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T36N</td></tr> <tr><td>R23E</td><td>R24E</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2">— —</td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td colspan="2">1998</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over rolling land.</p>	T36N		R23E	R24E	S13	S18	— —		S24	S19	1998	
T36N													
R23E	R24E												
S13	S18												
— —													
S24	S19												
1998													
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T36N</td></tr> <tr><td>R23E</td><td>R24E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2">1998</td></tr> </table> </div>	T36N		R23E	R24E	1/4		S13	S18	1998			
T36N													
R23E	R24E												
1/4													
S13	S18												
1998													
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 7, 12, 13, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												

Survey of the East Boundary,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T36N</td></tr> <tr><td style="text-align: center;">R23E</td><td style="text-align: center;">R24E</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S13</td><td style="text-align: center;">S18</td></tr> <tr><td colspan="2" style="text-align: center;">1998</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>	T36N		R23E	R24E	S12	S 7	-----		S13	S18	1998	
T36N													
R23E	R24E												
S12	S 7												
-----													
S13	S18												
1998													
	<p>North, bet. secs. 7 and 12.</p> <p>Over rolling land.</p>												
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T36N</td></tr> <tr><td style="text-align: center;">R23E</td><td style="text-align: center;">R24E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">1998</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T36N		R23E	R24E	1/4		S12	S 7	1998			
T36N													
R23E	R24E												
1/4													
S12	S 7												
1998													
80.00	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T36N</td></tr> <tr><td style="text-align: center;">R23E</td><td style="text-align: center;">R24E</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">1998</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T36N		R23E	R24E	S 1	S 6	-----		S12	S 7	1998	
T36N													
R23E	R24E												
S 1	S 6												
-----													
S12	S 7												
1998													

Survey of the East Boundary,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>North, bet. secs. 1 and 6.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R23E R24E 1/4 S 1   S 6 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
79.93	<p>Point for the closing cor. of Tps. 36 N., Rs. 23 and 24 E., at intersection with the Ninth Standard Parallel North, on the N. bdy. of the Tp.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T37N R23E S36</p>
	<p style="text-align: center;">S 1   S 6 R23E   R24E T36N CC 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>From this cor. point, the stan. cor. of Tps. 37 N., Rs. 23 and 24 E., bears East, 23.505 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 23 E., executed concurrently under this same group.</p>



Survey of the East Boundary,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 37 N., R. 23 E., bears West, 16.495 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 23 E., executed concurrently under this same group.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p style="text-align: center;">Survey of the West Boundary, T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 35 and 36 N., Rs. 22 and 23 E., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the west boundary, T. 35 N., R. 23 E., executed concurrently under this same group.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R22E R23E 1/4 S36   S31 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
57.60	<p>Graded road, 20 ft. wide, bears NE and SW.</p>
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the West Boundary,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T36N R22E   R23E S25   S30 ----- S36   S31 1998
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.  Land, rolling and broken. Soil, sandy clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.
	North, bet. secs. 25 and 30.  Over rolling land.
30.20	Wash, 50 ft. wide, 1 ft. deep, drains E.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T36N R22E   R23E 1/4 S25   S30 1998
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
44.27	SW right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.
46.02	Center of Navajo Route 59, asphalt pavement, 33 ft. wide, bears ESE and WNW.
47.77	NE right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.
66.34	NE cor. of a stuccoed house, 35 x 25 ft., bears West, 60 lks. dist., long side bears S.
66.73	Center of a stuccoed octagonal hogan, with 8 ft. sides, bears East, 1.01 chs. dist.

Survey of the West Boundary,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS													
70.28	NE cor. of a stuccoed house, 37 x 25 ft., bears West, 11 1/5 lks. dist., long side bears S.												
71.87	Center of a stuccoed octagonal hogan, with 8 ft. sides, bears East, 50 lks. dist.												
76.68	NE cor. of a brick house, 51 x 32 ft., bears West, 50 1/5 lks. dist., long side bears S.												
80.00	Point for the cor. of secs. 19, 24, 25, and 30.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T36N</td></tr> <tr><td style="text-align: center;">R22E</td><td style="text-align: center;">R23E</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S30</td></tr> <tr><td colspan="2" style="text-align: center;">1998</td></tr> </table> from which  NE cor. of an L-shaped stuccoed house, 34 x 30 ft., bears S. 9° W., 2.70 chs. dist., long side bears W.  SE cor. of a wood framed house, 48 x 24 ft., bears N. 12° W., 2.49 chs. dist., long side bears NNE.  Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.  Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.  <hr/> North, bet. secs. 19 and 24.  Over rolling land.	T36N		R22E	R23E	S24	S19	-----		S25	S30	1998	
T36N													
R22E	R23E												
S24	S19												
-----													
S25	S30												
1998													
4.27	Center of a log octagonal hogan, with 8 ft. sides, bears East, 3 lks. dist.												
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.												

Survey of the West Boundary,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T36N R22E R23E 1/4 S24   S19 1998</p>
63.40	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Navajo Route 594, a graded road, 20 ft. wide, bears NE and SW.</p>
80.00	<p>Point for the cor. of secs. 13, 18, 19, and 24.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R22E   R23E S13   S18 ----- S24   S19 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R22E R23E 1/4 S13   S18 1998</p>
50.90	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Foot of S. slope of Sweetwater Mesa, bears NE and SW.</p>

Survey of the West Boundary,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS													
53.30	SE rim of Sweetwater Mesa, bears NE and SW; thence over rolling land atop Sweetwater Mesa.												
79.55	Barbed wire fence, 5 strands, bears NE and SW.												
80.00	Point for the cor. of secs. 7, 12, 13, and 18.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T36N</td></tr> <tr><td style="text-align: center;">R22E</td><td style="text-align: center;">R23E</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S13</td><td style="text-align: center;">S18</td></tr> <tr><td colspan="2" style="text-align: center;">1998</td></tr> </table>	T36N		R22E	R23E	S12	S 7	-----		S13	S18	1998	
T36N													
R22E	R23E												
S12	S 7												
-----													
S13	S18												
1998													
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.												
	Cor. is located 49 lks. W. of a barbed wire fence, 5 strands, bears NE and SW.												
	Land, rolling and broken. Soil, sandy clay. No timber; scattered brush and native grasses.												
	North, bet. secs. 7 and 12.												
	Over rolling land.												
40.00	Point for the 1/4 sec. cor. of secs. 7 and 12.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T36N</td></tr> <tr><td style="text-align: center;">R22E</td><td style="text-align: center;">R23E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">1998</td></tr> </table>	T36N		R22E	R23E	1/4		S12	S 7	1998			
T36N													
R22E	R23E												
1/4													
S12	S 7												
1998													
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.												
80.00	Point for the cor. of secs. 1, 6, 7, and 12.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.												

Survey of the West Boundary,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS																	
	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T36N</td></tr> <tr><td style="text-align: center;">R22E</td><td style="text-align: center;">R23E</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">1998</td></tr> </table>	T36N		R22E	R23E	S 1	S 6	-----		S12	S 7	1998					
T36N																	
R22E	R23E																
S 1	S 6																
-----																	
S12	S 7																
1998																	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over rolling land.</p>																
33.84	Barbed wire fence, 5 strands, bears ESE and WNW.																
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>																
	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T36N</td></tr> <tr><td style="text-align: center;">R22E</td><td style="text-align: center;">R23E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td colspan="2" style="text-align: center;">1998</td></tr> </table>	T36N		R22E	R23E	1/4		S 1	S 6	1998							
T36N																	
R22E	R23E																
1/4																	
S 1	S 6																
1998																	
79.96	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the closing cor. of Tps. 36 N., Rs. 22 and 23 E., at intersection with the Ninth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>																
	<table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T37N R22E</td></tr> <tr><td colspan="2" style="text-align: center;">S36</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td style="text-align: center;">R22E</td><td style="text-align: center;">R23E</td></tr> <tr><td colspan="2" style="text-align: center;">T36N</td></tr> <tr><td colspan="2" style="text-align: center;">CC</td></tr> <tr><td colspan="2" style="text-align: center;">1998</td></tr> </table>	T37N R22E		S36		-----		S 1	S 6	R22E	R23E	T36N		CC		1998	
T37N R22E																	
S36																	
-----																	
S 1	S 6																
R22E	R23E																
T36N																	
CC																	
1998																	

Survey of the West Boundary,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. cor. of Tps. 37 N., Rs. 22 and 23 E., bears East, 21.34 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 22 E., executed concurrently under this same group.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 37 N., R. 22 E., bears West, 18.66 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 22 E., executed concurrently under this same group.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>Survey of the Subdivisional Lines, T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona</p>
	<p>From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 35 N., R. 23 E., executed concurrently under this same group.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E 1/4 S35   S36 1998</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 25, 26, 35, and 36.</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T36N</td><td>R23E</td></tr> <tr><td>S26</td><td>S25</td></tr> <tr><td>S35</td><td>S36</td></tr> <tr><td colspan="2">1998</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush, cacti and native grasses.</p>	T36N	R23E	S26	S25	S35	S36	1998			
T36N	R23E										
S26	S25										
S35	S36										
1998											
	<p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 25 and 36.</p> <p>Over nearly level land across poorly defined floodplain of Trading Post Wash.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T36N</td><td>R23E</td></tr> <tr><td colspan="2">S25</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td colspan="2">S36</td></tr> <tr><td colspan="2">1998</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Thence over rolling land.</p>	T36N	R23E	S25		1/4	—	S36		1998	
T36N	R23E										
S25											
1/4	—										
S36											
1998											
80.00	<p>The cor. of secs. 25, 26, 35, and 36.</p> <p>Land, nearly level to rolling. Soil, sandy clay. No timber; scattered brush, cacti and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 25 and 26.</p>										



Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T36N R23E 1/4 S26   S25 1998</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 23, 24, 25, and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T36N R23E S23   S24 ----- S26   S25 1998</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush, cacti and native grasses.</p>
	From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.
	West, bet. secs. 24 and 25.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 24 and 25.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T36N R23E S24 1/4 — S25 1998</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 23, 24, 25, and 26.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush, cacti and native grasses.</p>
40.00	<p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over rolling land on ascent of SE slope of White Top Mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
80.00	<p style="text-align: center;">T36N R23E 1/4 S23   S24 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Thence over rolling land atop White Top Mesa.</p> <p>Point for the cor. of secs. 13, 14, 23, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R23E S14   S13 —   — S23   S24 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush, cacti, and native grasses.</p>
40.00	<p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 13 and 24.</p> <p>Over rolling to broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E S13 1/4 — S24 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
68.90	<p>E. rim of White Top Mesa, bears SE and NW; thence over rolling land atop White Top Mesa.</p>
80.00	<p>The cor. of secs. 13, 14, 23, and 24.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush, cacti, and native grasses.</p>
15.80	<p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over rolling land atop White Top Mesa.</p> <p>NE rim of White Top Mesa, bears ESE and WNW; thence over broken land on abrupt descent.</p>
18.80	<p>Foot of NE slope of White Top Mesa, bears NE and SW; thence over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p style="text-align: center;">T36N R23E 1/4 S14   S13 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 11, 12, 13, and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
40.00	<p style="text-align: center;">T36N R23E S11   S12 ----- S14   S13 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush, cacti, and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 12 and 13.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
80.00	<p style="text-align: center;">T36N R23E S12 1/4 — S13 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 11, 12, 13, and 14.</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush, cacti, and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over rolling land atop White Top Mesa.</p>
38.50	E. rim of White Top Mesa, bears E. and W.; thence descend abruptly into indentation in E. rim of White Top Mesa.
40.00	<p>True point for the 1/4 sec. cor. of secs. 11 and 12, falls on precipitous slope of White Top Mesa, where it is impracticable to establish a monument.</p> <p>From this cor. point, the point selected for the witness cor. to the 1/4 sec. cor. of secs. 11 and 12, bears N. 45°00' E., 1.515 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 9 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC T36N R23E 1/4 S11   S12 ↙ 1998</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
42.80	E. rim of White Top Mesa, bears NNE and SSW; thence over rolling land atop White Top Mesa.
80.00	<p>Point for the cor. of secs. 1, 2, 11, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T36N R23E S 2   S 1 ----- S11   S12 1998</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush, cacti, and native grasses.</p>
40.00	<p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 1 and 12.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E S 1 1/4 — S12 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
74.70	<p>E. rim of White Top Mesa, bears N. and S.; thence over rolling land atop White Top Mesa.</p>
80.00	<p>The cor. of secs. 1, 2, 11, and 12.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush, cacti, and native grasses.</p>
40.00	<p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Over rolling land atop White Top Mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E 1/4 S 2   S 1 1998</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.93	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the closing cor. of secs. 1 and 2, at intersection with the Ninth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T37N R23E S35 ----- S 2   S 1 T36N R23E CC 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 35 and 36, T. 37 N., R. 23 E., bears East, 23.505 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 23 E., executed concurrently under this same group.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 37 N., R. 23 E., bears West, 16.495 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 23 E., executed concurrently under this same group.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 1 only, T. 36 N., R. 23 E., at midpoint on the N. bdy. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T37N R23E</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1/4 S 1 T36N R23E 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 37 N., R. 23 E., bears East, 23.505 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the stan. cor. of secs. 35 and 36, T. 37 N., R. 23 E., bears West, 16.495 chs. dist.</p> <hr/> <p>From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 35 N., R. 23 E., executed concurrently under this same group.</p> <p>Cor. is located on gradual E. slope of White Top Mesa, bears NNE and SSW.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over rolling land atop White Top Mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E 1/4 S34   S35 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 26, 27, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>



Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<div style="text-align: center;"> <table border="1"> <tr><td>T36N</td><td>R23E</td></tr> <tr><td>S27</td><td>S26</td></tr> <tr><td>S34</td><td>S35</td></tr> <tr><td colspan="2">1998</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush, cacti and native grasses.</p>	T36N	R23E	S27	S26	S34	S35	1998			
T36N	R23E										
S27	S26										
S34	S35										
1998											
40.00	<hr/> <p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>West, bet. secs. 26 and 35.</p> <p>Over rolling land on gradual ascent of White Top Mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>										
80.00	<div style="text-align: center;"> <table border="1"> <tr><td>T36N</td><td>R23E</td></tr> <tr><td>S26</td><td>—</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S35</td><td>—</td></tr> <tr><td colspan="2">1998</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 26, 27, 34, and 35.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush, cacti, and native grasses.</p>	T36N	R23E	S26	—	1/4	—	S35	—	1998	
T36N	R23E										
S26	—										
1/4	—										
S35	—										
1998											
24.70	<hr/> <p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over rolling land atop White Top Mesa.</p> <p>NW rim of White Top Mesa, bears ENE and WSW; thence descend abruptly to rolling land.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p>										

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T36N R23E 1/4 S27   S26 1998</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
67.00	SE rim of spur of White Top Mesa, bears NE and SW; thence over rolling land atop White Top Mesa.
80.00	Point for the cor. of secs. 22, 23, 26, and 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T36N R23E S22   S23 ----- S27   S26 1998</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
	<p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>
	From the cor. of secs. 23, 24, 25, and 26.
	West, bet. secs. 23 and 26.
	Over rolling land on gradual ascent of White Top Mesa.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T36N R23E S23 1/4 — S26 1998</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 22, 23, 26, and 27.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush, cacti, and native grasses.</p>
40.00	<p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over rolling land atop White Top Mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E 1/4 S22   S23 1998</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 14, 15, 22, and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E S15   S14 ----- S22   S23 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush, cacti, and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>West, bet. secs. 14 and 23.</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Over rolling land atop White Top Mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E S14 1/4 — S23 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 14, 15, 22, and 23.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush, cacti, and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 14 and 15.</p>
25.50	<p>Over rolling and broken land across spur ridges on W. edge of White Top Mesa.</p> <p>W. rim of White Top Mesa, bears NE and SW; thence descend abruptly to rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E 1/4 S15   S14 1998</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 10, 11, 14, and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<div style="text-align: center;">           T36N R23E            S10   S11            ---+---            S15   S14            1998         </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>
	<hr/> <p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>West, bet. secs. 11 and 14.</p> <p>Over rolling to broken land.</p>
11.70	E. rim of White Top Mesa, bears ESE and WNW; thence over rolling land atop White Top Mesa.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 14.
	<div style="text-align: center;">           T36N R23E            S11            1/4 —            S14            1998         </div> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<div style="text-align: center;">           T36N R23E            S11            1/4 —            S14            1998         </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
60.00	W. rim of White Top Mesa, bears N. and S.; thence descend abruptly to rolling land.
80.00	The cor. of secs. 10, 11, 14, and 15.
	<p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush, cacti, and native grasses.</p>
	<hr/> <p>N. 0°01' W., bet. secs. 10 and 11.</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling and broken land across spur ridges on W. edge of White Top Mesa.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T36N R23E 1/4 S10   S11 1998
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
	Cor. is located atop a spur ridge of White Top Mesa, bears E. and W.
80.00	Point for the cor. of secs. 2, 3, 10, and 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T36N R23E S 3   S 2 ----- S10   S11 1998
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
	Cor. is located atop White Top Mesa.
	Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.
	From the cor. of secs. 1, 2, 11, and 12.
	West, bet. secs. 2 and 11.
	Over rolling land atop White Top Mesa.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p style="text-align: center;">T36N R23E S 2 1/4 — S11 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 2, 3, 10, and 11.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush, cacti, and native grasses.</p>
40.00	<p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over rolling and broken land atop White Top Mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
79.94	<p style="text-align: center;">T36N R23E 1/4 S 3   S 2 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the closing cor. of secs. 2 and 3, at intersection with the Ninth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T37N R23E S34</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S 3   S 2 T36N R23E CC 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

## CHAINS

From this cor. point, the stan. cor. of secs. 34 and 35, T. 37 N., R. 23 E., bears East, 23.505 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 23 E., executed concurrently under this same group.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 37 N., R. 23 E., bears West, 16.495 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 23 E., executed concurrently under this same group.

Land, rolling.

Soil, sandy clay.

No timber; scattered brush and native grasses.

---

Point for the 1/4 sec. cor. of sec. 2 only, T. 36 N., R. 23 E., at midpoint on the N. bdy. of sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T37N R23E

1/4 S 2

T36N R23E

1998

Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 37 N., R. 23 E., bears East, 23.505 chs. dist.

From this same cor. point, the stan. cor. of secs. 34 and 35, T. 37 N., R. 23 E., bears West, 16.495 chs. dist.

---

From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 35 N., R. 23 E., executed concurrently under this same group.

N. 0°02' W., bet. secs. 33 and 34.

Over rolling land atop White Top Mesa.



Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
29.90	NW rim of White Top Mesa, bears ESE and WNW; thence descend abruptly to rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 33 and 34.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T36N R23E            1/4            S33   S34            1998         </div> Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 27, 28, 33, and 34.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T36N R23E            S28   S27            -----            S33   S34            1998         </div> Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.  Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.
	<hr/> From the cor. of secs. 26, 27, 34, and 35.  West, bet. secs. 27 and 34.  Over rolling land atop White Top Mesa.
13.50	NW rim of White Top Mesa, bears N. and S.; thence descend abruptly to rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T36N R23E S27 1/4 — S34 1998</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 27, 28, 33, and 34.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>
40.00	<p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
80.00	<p style="text-align: center;">T36N R23E 1/4 S28   S27 1998</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 21, 22, 27, and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
80.00	<p style="text-align: center;">T36N R23E S21   S22 —   — S28   S27 1998</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 22, 23, 26, and 27. West, bet. secs. 22 and 27. Over rolling land atop White Top Mesa.</p>
13.20	<p>W. rim of White Top Mesa, bears N. and S.; thence descend abruptly to rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E S22 1/4 — S27 1998</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 21, 22, 27, and 28. Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p> <hr/>
40.00	<p>N. 0°02' W., bet. secs. 21 and 22. Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 21 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E 1/4 S21   S22 1998</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS															
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.														
80.00	Point for the cor. of secs. 15, 16, 21, and 22.														
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.														
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T36N</td><td>R23E</td></tr> <tr><td>S16</td><td> </td><td>S15</td></tr> <tr><td colspan="3" style="border-top: 1px solid black;"></td></tr> <tr><td>S21</td><td> </td><td>S22</td></tr> <tr><td colspan="3" style="text-align: center;">1998</td></tr> </table>	T36N	R23E	S16		S15				S21		S22	1998		
T36N	R23E														
S16		S15													
S21		S22													
1998															
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.														
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush, and native grasses.</p>														
	From the cor. of secs. 14, 15, 22, and 23.														
	West, bet. secs. 15 and 22.														
	Over rolling land atop White Top Mesa.														
5.50	W. rim of White Top Mesa, bears NNE and SSW; thence descend abruptly to rolling land.														
40.00	Point for the 1/4 sec. cor. of secs. 15 and 22.														
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.														
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T36N</td><td>R23E</td></tr> <tr><td colspan="2" style="text-align: center;">S15</td></tr> <tr><td colspan="2" style="text-align: center;">1/4 —</td></tr> <tr><td colspan="2" style="text-align: center;">S22</td></tr> <tr><td colspan="2" style="text-align: center;">1998</td></tr> </table>	T36N	R23E	S15		1/4 —		S22		1998					
T36N	R23E														
S15															
1/4 —															
S22															
1998															
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.														
80.00	The cor. of secs. 15, 16, 21, and 22.														

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E 1/4 S16   S15 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 9, 10, 15, and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E S 9   S10 <hr/>S16   S15 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>West, bet. secs. 10 and 15.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E S10 1/4 — S15 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 9, 10, 15, and 16.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E 1/4 S 9   S10 1998</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 3, 4, 9, and 10.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E S 4   S 3 —   — S 9   S10 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>West, bet. secs. 3 and 10.</p> <p>Over rolling land atop White Top Mesa.</p>
5.70	W. rim of White Top Mesa, bears SSE and NNW; thence descend abruptly to rolling land.
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E S 3 1/4 — S10 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 3, 4, 9, and 10.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E 1/4 S 4   S 3 1998</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS									
79.94	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the closing cor. of secs. 3 and 4, at intersection with the Ninth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T37N R23E S33</p> <hr style="width: 50%; margin: auto;"/> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 4</td> <td style="padding: 0 5px;">S 3</td> </tr> <tr> <td colspan="2" style="text-align: center;">T36N R23E</td> </tr> <tr> <td colspan="2" style="text-align: center;">CC</td> </tr> <tr> <td colspan="2" style="text-align: center;">1998</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 33 and 34, T. 37 N., R. 23 E., bears East, 23.495 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 23 E., executed concurrently under this same group.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 37 N., R. 23 E., bears West, 16.505 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 23 E., executed concurrently under this same group.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr style="border: 0.5px solid black;"/> <p>Point for the 1/4 sec. cor. of sec. 3 only, T. 36 N., R. 23 E., at midpoint on the N. bdy. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>	S 4	S 3	T36N R23E		CC		1998	
S 4	S 3								
T36N R23E									
CC									
1998									



Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>T37N R23E</p> <hr/> <p>1/4 S 3 T36N R23E 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 37 N., R. 23 E., bears East, 23.50 chs. dist.</p> <p>From this same cor. point, the stan. cor. of secs. 33 and 34, T. 37 N., R. 23 E., bears West, 16.50 chs. dist.</p>
	<hr/> <p>From the cor. of secs. 4, 5, 32, and 33, monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 35 N., R. 23 E., executed concurrently under this same group.</p> <p>Cor. is located 90 lks. S. of Burro Wash, 25 ft. wide, 2 ft. deep, drains E.</p> <p>N. 0°03' W., bet. secs. 32 and 33.</p> <p>Over rolling land.</p>
36.99	SW right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.
38.73	Center of Navajo Route 59, asphalt pavement, 33 ft. wide, bears ESE and WNW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below the surface of the ground, with brass cap mkd.</p>
	<p>T36N R23E</p> <p>1/4</p> <p>S32   S33</p> <p>1998</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 85°00' E., 49.0 ft. dist., with brass cap mkd. T36N R23E 1/4 S33 RM 49.0 FT. TO COR. 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 5°00' W., 36.0 ft. dist., with brass cap mkd. T36N R23E 1/4 S32 RM 36.0 FT. TO COR. 1998 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 51 lks. S. of NE right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.</p>								
80.00	Point for the cor. of secs. 28, 29, 32, and 33.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 10px;">T36N</td> <td style="padding: 0 10px;">R23E</td> </tr> <tr> <td style="padding: 0 10px;">S29</td> <td style="padding: 0 10px;">S28</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 10px;">S32</td> <td style="border-top: 1px solid black; padding: 0 10px;">S33</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">1998</td> </tr> </table>	T36N	R23E	S29	S28	S32	S33	1998	
T36N	R23E								
S29	S28								
S32	S33								
1998									
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>								
	<p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>West, bet. secs. 28 and 33.</p> <p>Over rolling land.</p>								
40.00	Point for the 1/4 sec. cor. of secs. 28 and 33.								

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R23E S28 1/4 — S33 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
66.20	<p>Burro Wash, 20 ft. wide, 4 ft. deep, drains ENE.</p>
80.00	<p>The cor. of secs. 28, 29, 32, and 33.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>N. 0°03' W., bet. secs. 28 and 29.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R23E 1/4 S29   S28 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 20, 21, 28, and 29.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R23E S20   S21 ----- S29   S28 1998</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>West, bet. secs. 21 and 28.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E S21 1/4 — S28 1998</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 20, 21, 28, and 29.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
40.00	<p>N. 0°03' W., bet. secs. 20 and 21.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E 1/4 S20   S21 1998</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 16, 17, 20, and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T36N</td><td>R23E</td></tr> <tr><td>S17</td><td>S16</td></tr> <tr><td>S20</td><td>S21</td></tr> <tr><td colspan="2">1998</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>	T36N	R23E	S17	S16	S20	S21	1998			
T36N	R23E										
S17	S16										
S20	S21										
1998											
40.00	<p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>West, bet. secs. 16 and 21.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T36N</td><td>R23E</td></tr> <tr><td>S16</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S21</td><td></td></tr> <tr><td colspan="2">1998</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T36N	R23E	S16		1/4	—	S21		1998	
T36N	R23E										
S16											
1/4	—										
S21											
1998											
55.50	Burro Wash, 30 ft. wide, 2 ft. deep, drains NNE.										
80.00	The cor. of secs. 16, 17, 20, and 21.										

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>N. 0°03' W., bet. secs. 16 and 17.</p>
	<p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R23E 1/4 S17   S16 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 8, 9, 16, and 17.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R23E S 8   S 9 ----- S17   S16 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Land, gently rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 9, 10, 15, and 16.</p>
	<p>West, bet. secs. 9 and 16.</p>
	<p>Over gently rolling land.</p>
33.70	<p>Burro Wash, 40 ft. wide, 4 ft. deep, drains NNW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E S 9 1/4 — S16 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 8, 9, 16, and 17.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>N. 0°03' W., bet. secs. 8 and 9.</p>
	<p>Over rolling land.</p>
9.10	<p>Wash, 25 ft. wide, 4 ft. deep, drains ESE.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E 1/4 S 8   S 9 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
46.00	<p>Navajo Route 594, a graded road, 20 ft. wide, bears NE and SW.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 8, and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, and raise a supporting mound of stone, 3 ft. base, 2 ft. high, E. and downslope of cor., with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<div style="text-align: center;"> <p>T36N R23E S 5   S 4 ----- S 8   S 9 1998</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on steep E. slope of Sweetwater Mesa, bears NNE and SSW, 35 lks. E. of E. rim.</p> <p>Land, rolling. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over rolling land.</p>
30.70	<p>Burro Wash, 30 ft. wide, 4 ft. deep, drains NNW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T36N R23E S 4 1/4 — S 9 1998</p> </div>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 2.30 chs. E. of Navajo Route 594, a graded road, 20 ft. wide, bears NE and SW.</p>
80.00	<p>The cor. of secs. 4, 5, 8, and 9.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>N. 0°03' W., bet. secs. 4 and 5.</p>



Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Over rolling and broken land along E. slope of Sweetwater Mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E 1/4 S 5   S 4 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Thence over rolling land.</p>
79.94	<p>Point for the closing cor. of secs. 4 and 5, at intersection with the Ninth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T37N R23E S 32 ----- S 5   S 4 T36N R23E CC 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. cor. of secs. 32 and 33, T. 37 N., R. 23 E., bears East, 23.495 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 23 E., executed concurrently under this same group.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 37 N., R. 23 E., bears West, 16.505 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 23 E., executed concurrently under this same group.</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>
	<p>Point for the 1/4 sec. cor. of sec. 4 only, T. 36 N., R. 23 E., at midpoint on the N. bdy. of sec. 4.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T37N R23E ----- 1/4 S 4 T36N R23E 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>From this cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 37 N., R. 23 E., bears East, 23.495 chs. dist.</p>
	<p>From this same cor. point, the stan. cor. of secs. 32 and 33, bears West, 16.505 chs. dist.</p>
	<p>From the cor. of secs. 5, 6, 31, and 32, monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 35 N., R. 23 E., executed concurrently under this same group.</p>
	<p>Cor. is located on SE slope of a prominent spur ridge, bears ENE and WSW, 90 lks. E. of SE rim.</p>
	<p>N. 0°03' W., bet. secs. 31 and 32.</p>
	<p>Over rolling and broken land across spur ridges.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R23E 1/4 S31   S32 1998</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS											
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.										
72.09	S. right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.										
73.56	Center of Navajo Route 59, asphalt pavement, 33 ft. wide, bears E. and W.										
75.07	N. right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.										
80.00	Point for the cor. of secs. 29, 30, 31, and 32.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table border="1"> <tr><td>T36N</td><td>R23E</td></tr> <tr><td>S30</td><td>S29</td></tr> <tr><td>S31</td><td>S32</td></tr> <tr><td colspan="2">1998</td></tr> </table> </div>	T36N	R23E	S30	S29	S31	S32	1998			
T36N	R23E										
S30	S29										
S31	S32										
1998											
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.  Land, rolling and broken. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.										
40.00	From the cor. of secs. 28, 29, 32, and 33.  West, bet. secs. 29 and 32.  Over rolling land.  Point for the 1/4 sec. cor. of secs. 29 and 32.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table border="1"> <tr><td>T36N</td><td>R23E</td></tr> <tr><td colspan="2">S29</td></tr> <tr><td colspan="2">1/4 —</td></tr> <tr><td colspan="2">S32</td></tr> <tr><td colspan="2">1998</td></tr> </table> </div>	T36N	R23E	S29		1/4 —		S32		1998	
T36N	R23E										
S29											
1/4 —											
S32											
1998											

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
80.00	<p>The cor. of secs. 29, 30, 31, and 32.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>West, bet. secs. 30 and 31.</p> <p>Over rolling and broken land.</p>
23.02	NE right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.
23.82	A brass tablet, 3 ins. diam., set in a concrete collar, 6 ins. diam., set flush with the surface of the ground, bears North, 1.12 chs. dist., with top mkd. BIA ROADS ELEV., and witnessed by an angle iron set nearby, with marks PT 1083+71.95 visible on a face.
24.76	Center of Navajo Route 59, asphalt pavement, 33 ft. wide, bears SE and NW.
26.36	A brass tablet, 3 ins. diam., set in a concrete collar, 6 ins. diam., set flush with the surface of the ground, bears South, 55 lks. dist., with top mkd. BIA ROADS ELEV., and witnessed by an angle iron set nearby, with marks PT 1083+71.95 visible on a face.
26.70	SW right-of-way fence of Navajo Route 59, barbed wire, 5 strands, parallels highway.
40.00	<p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R23E S30 1/4 — S31 1998</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
66.00	Graded road, 20 ft. wide, bears NNE and SSW.

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
78.29	<p>The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E 1/4 S30   S29 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 19, 20, 29, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E S19   S20 ----- S30   S29 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>West, bet. secs. 20 and 29.</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T36N R23E S20 1/4 — S29 1998</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
80.00	The cor. of secs. 19, 20, 29, and 30.
	Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.
	<hr/>
	West, bet. secs. 19 and 30.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T36N R23E S19 1/4 — S30 1998</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
46.90	Wash, 40 ft. wide, 3 ft. deep, drains N.
78.20	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., hereinbefore described.

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 19, 20, 29, and 30.</p>
	<p>N. 0°03' W., bet. secs. 19 and 20.</p>
	<p>Over gently rolling land.</p>
20.90	<p>Wash, 40 ft. wide, 3 ft. deep, drains ENE.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R23E</p>
	<p style="text-align: center;">1/4</p>
	<p style="text-align: center;">S19   S20</p>
	<p style="text-align: center;">1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 17, 18, 19, and 20.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R23E</p>
	<p style="text-align: center;">S18   S17</p>
	<p style="text-align: center;">S19   S20</p>
	<p style="text-align: center;">1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Land, gently rolling.</p>
	<p>Soil, sandy clay.</p>
	<p>No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 16, 17, 20, and 21.</p>
	<p>West, bet. secs. 17 and 20.</p>
	<p>Over gently rolling land.</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E S17 1/4 — S20 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 17, 18, 19, and 20.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>West, bet. secs. 18 and 19.</p> <p>Over rolling land.</p>
18.15	<p>Pump shaft of a windmill, bears South, 47 lks. dist., mkd. 8T-518.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E S18 1/4 — S19 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
59.60	<p>Navajo Route 594, a graded road, 20 ft. wide, bears NE and SW.</p>
78.11	<p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., hereinbefore described.</p>



Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 17, 18, 19, and 20. N. 0°03' W., bet. secs. 17 and 18. Over rolling land.</p>
39.10	Underground water line, bears NE and SW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E 1/4 S18   S17 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
56.20	Navajo Route 594, a graded road, 20 ft. wide, bears NE and SW; thence ascend SE slope of Sweetwater Mesa.
79.80	SE rim of Sweetwater Mesa, bears ENE and WSW; thence over rolling land atop Sweetwater Mesa.
80.00	<p>Point for the cor. of secs. 7, 8, 17, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E S 7   S 8 ----- S18   S17 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 8, 9, 16, and 17.</p>
	<p>West, bet. secs. 8 and 17.</p>
	<p>Over rolling land.</p>
13.60	<p>Wash, 30 ft. wide, 3 ft. deep, drains NE.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R23E S 8 1/4 — S17 1998</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
47.70	<p>Underground water line, bears NE and SW.</p>
56.90	<p>Navajo Route 594, a graded road, 20 ft. wide, bears NE and SW.</p>
67.20	<p>Foot of SE slope of Sweetwater Mesa, bears NNE and SSW; thence ascend abruptly.</p>
80.00	<p>The cor. of secs. 7, 8, 17, and 18.</p>
	<p>Land, rolling to broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>
	<p>West, bet. secs. 7 and 18.</p>
	<p>Over rolling land atop Sweetwater Mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
78.02	<p style="text-align: center;">T36N R23E S 7 1/4 — S18 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0°03' W., bet. secs. 7 and 8.</p> <p>Over rolling land atop Sweetwater Mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
80.00	<p style="text-align: center;">T36N R23E 1/4 S 7   S 8 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 5, 6, 7, and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R23E S 6   S 5 —   — S 7   S 8 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/>
40.00	<p>From the cor. of secs. 4, 5, 8, and 9. West, bet. secs. 5 and 8. Over rolling and broken land atop Sweetwater Mesa. Point for the 1/4 sec. cor. of secs. 5 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E S 5 1/4 — S 8 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 5, 6, 7, and 8. Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p> <hr/>
40.00	<p>West, bet. secs. 6 and 7. Over rolling land atop Sweetwater Mesa. Point for the 1/4 sec. cor. of secs. 6 and 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R23E S 6 1/4 — S 7 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
43.52	Barbed wire fence, 5 strands, bears N. and S.
77.94	<p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/>
	From the cor. of secs. 5, 6, 7, and 8.
	N. 0°03' W., bet. secs. 5 and 6.
	Over rolling land atop Sweetwater Mesa.
39.11	Barbed wire fence, 5 strands, bears ENE and WSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R23E 1/4 S 6   S 5 1998</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
79.95	<p>Point for the closing cor. of secs. 5 and 6, at intersection with the Ninth Standard Parallel North, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T37N R23E S31</p> <hr/>
	<p style="text-align: center;">S 6   S 5 T36N R23E CC 1998</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, the stan. cor. of secs. 31 and 32, T. 37 N., R. 23 E., bears East, 23.495 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 23 E., executed concurrently under this same group.</p> <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 37 N., R. 23 E., bears West, 16.505 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 23 E., executed concurrently under this same group.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 5 only, T. 36 N., R. 23 E., at midpoint on the N. bdy. of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T37N R23E ----- 1/4 S 5 T36N R23E 1998</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 37 N., R. 23 E., bears East, 23.495 chs. dist.</p> <p>From this same cor. point, the stan. cor. of secs. 31 and 32, T. 37 N., R. 23 E., bears West, 16.505 chs. dist.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 6 only, T. 36 N., R. 23 E., at 40.00 chs. westing from the closing cor. of secs. 5 and 6, on the N. bdy. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS

T37N R23E

1/4 S 6  
T36N R23E  
1998

Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 37 N., R. 23 E., bears East, 23.495 chs. dist.

From this same cor. point, the stan. cor. of Tps. 37 N., Rs. 22 and 23 E., bears West, 16.505 chs. dist., hereinbefore described.

---

T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The area surveyed is within the Navajo Indian Reservation, about 7 miles north of the community of Rough Rock. The terrain is mostly rolling, with broken areas on spur ridges and the slopes of Sweetwater and White Top Mesas. The principal drainage is Burro Wash, which drains northerly through the center of the township.

The elevation varies from 5,500 to 6,100 feet above sea level. The soil is mostly sandy and rocky clay. The vegetation principally consists of scattered brush and native grasses. There is some scattered piñon and juniper on the spur ridges in sections 31 and 32.

Principal access to the township is provided by Navajo Route 59, a paved highway which enters the township in section 30 and exits in section 33. There are graded and trail roads throughout the township.

Much of the township is used for grazing of livestock and there is no evidence of current mining activity.

The mean magnetic declination of  $12\ 1/2^\circ$  E. was derived from the United States Geological Survey computer program GEOMAGIX utilizing the Regional Magnetic Field Model for Epoch 1995 for the dates of survey.



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Daniel Bryan	Engineering Technician
Wilfred Chee	Engineering Technician
Edward Clarke	Engineering Technician
Reuben Mason	Engineering Technician
Barney Woodie	Engineering Technician

CERTIFICATE OF SURVEY

I, Jones Curtiss, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 17th day of February 1998, I have surveyed the east and west boundaries, and the subdivisional lines, Township 36 North, Range 23 East, of the Gila and Salt River Meridian, in the state of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

November 24, 1999  
(Date)

Jones Curtiss  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Arizona State Office  
Phoenix, Arizona

The foregoing field notes of the survey of the east and west boundaries, and the subdivisional lines, Township 36 North, Range 23 East, Gila and Salt River Meridian, Arizona, executed by Jones Curtiss, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

January 7, 2000  
(Date)

Kenny A Rawmbar  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 36 N., R. 23 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~\_\_\_\_\_  
(Date)~~

~~\_\_\_\_\_  
(Chief Cadastral Surveyor of Arizona)~~