

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE

SURVEY

OF

THE EAST AND

NORTH BOUNDARIES,

AND

THE SUBDIVISIONAL LINES,

TOWNSHIP 34 NORTH, RANGE 26 EAST,

Of the Gila and Salt River Meridian,
In the State of Arizona

EXECUTED BY

Jones Curtiss and Leonard R. Sandoval, Cadastral Surveyors

Under Special Instructions dated and approved February 17, 1998, which provided for the surveys included under Group Number 822 and assignment instructions dated February 17, 1998.

Survey Commenced February 16, 1999
Survey Completed April 22, 1999

INDEX DIAGRAM

TOWNSHIP 34 NORTH, RANGE 26 EAST,

GILA AND SALT RIVER MERIDIAN, ARIZONA

14 6 63	13 5 49	12 4 40	11 3 32	10 2 23	9 1 8
62 7 60	61 8 47	48 9 38	39 10 30	31 11 22	23 12 7
59 18 57	58 17 46	46 16 37	38 15 29	30 14 20	21 13 6
57 19 55	56 20 44	45 21 35	36 22 27	28 23 18	20 24 6
54 30 52	54 29 42	43 28 34	35 27 25	26 26 17	18 25 5
52 31 50	51 32 41	42 33 32	33 34 24	25 35 15	16 36 4

T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of the east and north boundaries, and the subdivisional lines, Township 34 North, Range 26 East, Gila and Salt River Meridian, Arizona.

The south and west boundaries of the township were surveyed by Leonard R. Sandoval in 1998-99, concurrently under this same group.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated February 17, 1998, for Group No. 822, Arizona.

The directions of all lines were determined, and distances measured by the technique of differential positioning using Trimble Navigation 4400 and 4700 Series Global Positioning System receivers utilizing Real-Time Kinematic techniques.

The geographic position of the southeast corner of the township was determined by the technique of differential positioning using the Trimble Navigation 4400 and 4700 Series Global Positioning System. First order National Geodetic Survey triangulation stations "BEAUTIFUL 1951" and "LOHALI 1951" were used as control stations. The geographic position is as follows:

Lat.: 36°18'09.397" N. Long.: 109°29'15.877" W. NAD83(1992)

The mean magnetic declination is 12 1/4° E.

Survey of the East Boundary,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Beginning at the cor. of Tps. 33 and 34 N., Rs. 26 and 27 E., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 33 N., R. 26 E., executed concurrently under this same group.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rolling land.</p>
8.65	Trail road, bears E. and W.
30.00	High voltage transmission line, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 36.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T34N R26E R27E 1/4 S36 S31 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 5 lks. E. of a wash, 3 ft. wide, 1 ft. deep, drains NE.</p>
80.00	Point for the cor. of secs. 25, 30, 31, and 36.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T34N R26E R27E S25 S30 ----- S36 S31 1999</p> </div> <p>from which</p> <p style="text-align: center;">A forked juniper, 7 ins. diam. at base, bears S. 55 3/4° W., 24 lks. dist., mkd. T34N R26E S36 BT.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the East Boundary,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy and gravelly clay. Timber, piñon and juniper; undergrowth, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 25 and 30.</p> <p>Over rolling land.</p>
30.40	Tezinie Wash, 70 ft. wide, 3 ft. deep, drains NNW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T34N R26E R27E 1/4 S25 S30 1999 </p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
45.30	Tezinie Wash, 80 ft. wide, 4 ft. deep, drains NE.
53.10	Tezinie Wash, 80 ft. wide, 15 ft. deep, drains NW.
80.00	<p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T34N R26E R27E S24 S19 ----- S25 S30 1999 </p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the East Boundary,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>Land, rolling. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.</p>												
	<p>North, bet. secs. 19 and 24.</p>												
	<p>Over rolling land.</p>												
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p>												
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T34N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table>	T34N		R26E	R27E	1/4		S24	S19	1999			
T34N													
R26E	R27E												
1/4													
S24	S19												
1999													
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>												
44.20	<p>Navajo Route 8084, a graded road, 20 ft. wide, bears E. and W.</p>												
80.00	<p>Point for the cor. of secs. 13, 18, 19, and 24.</p>												
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T34N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td style="text-align: center;">S13</td><td style="text-align: center;">S18</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table>	T34N		R26E	R27E	S13	S18	-----		S24	S19	1999	
T34N													
R26E	R27E												
S13	S18												

S24	S19												
1999													
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>												
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>												
	<p>North, bet. secs. 13 and 18.</p>												
	<p>Over rolling land.</p>												

Survey of the East Boundary,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T34N R26E R27E 1/4 S13 S18 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 7, 12, 13, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T34N R26E R27E S12 S 7 ----- S13 S18 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 7 and 12.</p> <p>Over rolling land.</p>
4.10	Trail road, bears NE and SW.
30.90	Trail road, bears ENE and WSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the East Boundary,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T34N R26E R27E 1/4 S12 S 7 1999
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
65.67	Barbed wire fence, 5 strands, bears ENE and WSW.
80.00	Point for the cor. of secs. 1, 6, 7, and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T34N R26E R27E S 1 S 6 ----- S12 S 7 1999
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
	Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.
	North, bet. secs. 1 and 6.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 6.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T34N R26E R27E 1/4 S 1 S 6 1999
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.

Survey of the East Boundary,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Cor. is located in the fork of a wash, 12 ft. wide, 3 ft. deep, drains NW, and another wash, 12 ft. wide, 2 ft. deep, drains N.</p> <p>From this cor. point, third order National Geodetic Survey triangulation station "HUMP RESET 1955", bears N. 89°01.8' E., 97.310 chs. dist., monumented with a P-K nail, set at the bottom of a drill hole in sandstone bedrock, witnessed by the original U. S. Geological Survey reference marks Nos. 1 and 2.</p> <p>Thence over rolling and broken land.</p>														
80.00	<p>Point for the cor. of Tps. 34 and 35 N., Rs. 26 and 27 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in sandstone bedrock, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="padding: 2px;">T35N</td></tr> <tr><td style="padding: 2px;">R26E</td><td style="padding: 2px;">R27E</td></tr> <tr><td style="padding: 2px;">S36</td><td style="padding: 2px;">S31</td></tr> <tr><td colspan="2" style="border-top: 1px solid black; padding: 2px;"></td></tr> <tr><td style="padding: 2px;">S 1</td><td style="padding: 2px;">S 6</td></tr> <tr><td colspan="2" style="padding: 2px;">T34N</td></tr> <tr><td colspan="2" style="padding: 2px;">1999</td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">The marks X B0, chiseled on sandstone bedrock, bear N. 35 1/4° E., 53 1/2 lks. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p> <p>From this cor. point, an iron pipe, of unknown origin, 2 1/2 ins. diam., firmly set, projecting 13 ins. above ground, bears N. 61°17' E., 3.68 chs. dist., mkd. T35N R26E R27E 1 6 31 36 on the side.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.</p> <hr style="border: 0.5px solid black; margin: 20px 0;"/> <p style="text-align: center;">Survey of the North Boundary, T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona</p> <hr style="border: 0.5px solid black; margin: 20px 0;"/>	T35N		R26E	R27E	S36	S31			S 1	S 6	T34N		1999	
T35N															
R26E	R27E														
S36	S31														
S 1	S 6														
T34N															
1999															

Survey of the North Boundary,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>From the cor. of Tps. 34 and 35 N., Rs. 26 and 27 E., hereinbefore described.</p> <p>West, bet. secs. 1 and 36.</p> <p>Over rolling and broken land.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T35N R26E S36 1/4 — S 1 T34N 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>										
80.00	<p>Point for the cor. of secs. 1, 2, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table border="1" style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2" style="padding: 2px;">T35N R26E</td> </tr> <tr> <td style="padding: 2px;">S35</td> <td style="padding: 2px;">S36</td> </tr> <tr> <td style="padding: 2px;">S 2</td> <td style="padding: 2px;">S 1</td> </tr> <tr> <td colspan="2" style="padding: 2px;">T34N</td> </tr> <tr> <td colspan="2" style="padding: 2px;">1999</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.</p>	T35N R26E		S35	S36	S 2	S 1	T34N		1999	
T35N R26E											
S35	S36										
S 2	S 1										
T34N											
1999											
40.00	<p>West, bet. secs. 2 and 35.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p>										

Survey of the North Boundary,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S35 1/4 — S 2 T34N 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 1.60 chs. E. and 1.11 chs. N. of a barbed wire fence, 5 strands, bears SE and NW, and 18 lks. S. of a trail road, bears ESE and WNW.</p> <p>63.80 Trail road, bears NE in curve to right.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S34 S35 — — S 3 S 2 T34N 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p>
40.00	<p>West, bet. secs. 3 and 34.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the North Boundary,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p style="text-align: center;">T35N R26E S34 1/4 — S 3 T34N 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 3, 4, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S33 S34 — — S 4 S 3 T34N 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p>
40.00	<p>West, bet. secs. 4 and 33.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S33 1/4 — S 4 T34N 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located atop a sandy ridge, bears N. and S.</p>

Survey of the North Boundary,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
80.00	<p>Point for the cor. of secs. 4, 5, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="849 447 995 636"> <tr> <td>T35N</td> <td>R26E</td> </tr> <tr> <td>S32</td> <td>S33</td> </tr> <tr> <td>S 5</td> <td>S 4</td> </tr> <tr> <td colspan="2">T34N</td> </tr> <tr> <td colspan="2">1999</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, clay and sandy clay. No timber; scattered brush and native grasses.</p>	T35N	R26E	S32	S33	S 5	S 4	T34N		1999			
T35N	R26E												
S32	S33												
S 5	S 4												
T34N													
1999													
40.00	<p>West, bet. secs. 5 and 32.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in sandstone bedrock, with brass cap mkd.</p> <table border="1" data-bbox="849 1213 995 1402"> <tr> <td>T35N</td> <td>R26E</td> </tr> <tr> <td></td> <td>S32</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 5</td> </tr> <tr> <td colspan="2">T34N</td> </tr> <tr> <td colspan="2">1999</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, N. of cor.</p>	T35N	R26E		S32	1/4	—		S 5	T34N		1999	
T35N	R26E												
	S32												
1/4	—												
	S 5												
T34N													
1999													
80.00	<p>Point for the cor. of secs. 5, 6, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in sandstone bedrock, with brass cap mkd.</p>												

Survey of the North Boundary,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<div style="text-align: center;"> T35N R26E S31 S32 ----- S 6 S 5 T34N 1999 </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p>West, bet. secs. 6 and 31.</p> <p>Over gently rolling land on descent into Chinle Valley.</p> <p>21.50 Graded road, 15 ft. wide, bears NNE and SSW.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> T35N R26E S31 1/4 — S 6 T34N 1999 </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>48.00 Graded road, 15 ft. wide, bears SSE and NNW.</p> <p>57.20 E. bank of floodplain of Chinle Wash, 15 ft. high, bears N. and S.</p> <p>73.50 Chinle Wash, 130 ft. wide, 3 ft. deep, drains N.</p> <p>73.90 Power line, bears NNE and SSW.</p> <p>76.10 W. bank of floodplain of Chinle Wash, 5 ft. high, bears SSE and NNW.</p>

Survey of the North Boundary,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
78.93	<p>The cor. of Tps. 34 and 35 N., Rs. 25 and 26 E., monumented with a stainless post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 34 N., R. 25 E., executed concurrently under this same group.</p> <p>Cor. is located atop a prominent bare clay hill.</p> <p>Land, gently rolling. Soil, sandy and rocky clay. Timber, cottonwood, Russian olive and saltcedar near Chinle Wash; undergrowth, scattered brush and native grasses.</p> <hr/> <p style="text-align: center;">Survey of the Subdivisional Lines, T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with a brass tablet, 3 1/4 ins. diam., cemented in place in sandstone bedrock, with top mkd. as described in the field notes of the survey of the north boundary, T. 33 N., R. 26 E., executed concurrently under this same group.</p> <p>Cor. is located 1.65 chs. S. and 2.10 chs. W. of SW rim of Jimson Weed Canyon, bears ESE and WNW.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over broken land across Jimson Weed Canyon.</p>
3.30	NE rim of Jimson Weed Canyon, atop sandstone ledge, bears ESE and WNW; thence over rolling land.
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E 1/4 S35 S36 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	Point for the cor. of secs. 25, 26, 35, and 36.

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T34N R26E</td> </tr> <tr> <td>S26</td> <td>S25</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S35</td> <td>S36</td> </tr> <tr> <td colspan="2">1999</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, broken to rolling. Soil, sandy and gravelly clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.</p>	T34N R26E		S26	S25	<hr/>		S35	S36	1999	
T34N R26E											
S26	S25										
<hr/>											
S35	S36										
1999											
	<p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 25 and 36.</p> <p>Over rolling land.</p>										
20.85	Trail road, bears N. and S.										
40.00	Point for the 1/4 sec. cor. of secs. 25 and 36.										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in sandstone bedrock, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T34N R26E</td> </tr> <tr> <td colspan="2">S25</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td colspan="2">S36</td> </tr> <tr> <td colspan="2">1999</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T34N R26E		S25		1/4	—	S36		1999	
T34N R26E											
S25											
1/4	—										
S36											
1999											
43.30	Trail road, bears SE and NW.										
80.00	The cor. of secs. 25, 26, 35, and 36.										

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy and gravelly clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 25 and 26.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E 1/4 S26 S25 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
61.70	<p>SW rim of Tezinie Canyon, atop sandstone ledge, bears ESE and WNW; thence over broken land.</p>
66.30	<p>Tezinie Wash, 18 ft. wide, 5 ft. deep, drains NW.</p>
80.00	<p>Point for the cor. of secs. 23, 24, 25, and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E S23 S24 ----- S26 S25 1999</p>
	<p>from which</p> <p style="text-align: center;">The marks X B0, chiseled on the face of a sandstone ledge, bear N. 34 1/4° E., 56 1/2 lks. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on steep NE slope of Tezinie Canyon, 43 lks. W. of NE rim, bears N. and S.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 24 and 25.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E S24 1/4 — S25 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 23, 24, 25, and 26.</p> <p>Land, rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.</p>
5.30	<p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over rolling and broken land.</p> <p>NE rim of Tezinie Canyon, atop sandstone ledge, bears E. and W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T34N R26E 1/4 S23 S24 1999
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
41.30	Navajo Route 8084, a graded road, 25 ft. wide, bears ENE and WSW.
48.15	The SW cor. of a wood sided house, 61 x 15 ft., bears East, 1.36 chs. dist., long side bears N.
50.50	The center of an octagonal wood sided hogan, 23 ft. diam., bears East, 1.40 chs. dist.
62.60	S. rim of a canyon, atop sandstone ledge, bears ENE and WSW; thence descend into the canyon.
80.00	Point for the cor. of secs. 13, 14, 23, and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T34N R26E S14 S13 ----- S23 S24 1999
	from which
	The marks X B0, chiseled on sandstone bedrock, bear N. 53 1/2° W., 1.695 chs. dist.
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
	Cor. is located atop left bank of a wash, 40 ft. wide, 4 ft. deep, drains W.

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.</p>
	<p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>West, bet. secs. 13 and 24.</p>
	<p>Over rolling and broken land.</p>
17.70	<p>Graded road, 20 ft. wide, bears NE and SW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in sandstone bedrock, with brass cap mkd.</p>
	<p style="text-align: center;">T34N R26E S13 1/4 — S24 1999</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A forked juniper, 14 ins. diam. at base, bears N. 2 1/4° E., 67 1/2 lks. dist., mkd. 1/4 S13 BT.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 13, 14, 23, and 24.</p>
	<p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 13 and 14.</p>
	<p>Over rolling and broken land on ascent from a canyon.</p>
18.70	<p>N. rim of a canyon, atop sandstone ledge, bears ENE and WSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T34N R26E 1/4 S14 S13 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 11, 12, 13, and 14.</p>
	<p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p>
	<p style="text-align: center;">T34N R26E S11 S12 ----- S14 S13 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case in the drill hole beneath the brass tablet.</p>
	<p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>West, bet. secs. 12 and 13.</p>
	<p>Over rolling and broken land.</p>
4.35	<p>Trail road, bears NE and SW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T34N R26E S12 1/4 — S13 1999</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
43.15	Trail road, bears SE and NW.
45.55	Trail road, bears N. and S.
73.85	Trail road, bears ESE and WNW.
80.00	The cor. of secs. 11, 12, 13, and 14. Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.
	N. 0°01' W., bet. secs. 11 and 12. Over rolling and broken land.
3.45	Trail road, bears ESE and WNW.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T34N R26E 1/4 S11 S12 1999 </div>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
63.55	Trail road, bears ESE and WNW.
80.00	Point for the cor. of secs. 1, 2, 11, and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T34N R26E S 2 S 1 <hr style="width: 50%; margin: 0 auto;"/> S11 S12 1999 </div>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>West, bet. secs. 1 and 12.</p>
	<p>Over rolling land.</p>
	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in sandstone bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T34N R26E S 1 1/4 — S12 1999</p>
58.58	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Barbed wire fence, 5 strands, bears SE and NW.</p>
80.00	<p>The cor. of secs. 1, 2, 11, and 12.</p>
	<p>Land, rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 1 and 2.</p>
	<p>Over rolling land.</p>
29.80	<p>Barbed wire fence, 5 strands, bears SE and NW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T34N R26E 1/4 S 2 S 1 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
65.30	<p>Trail road, bears E. and W.</p>
80.00	<p>The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.</p>
	<hr/> <p>From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 33 N., R. 26 E., executed concurrently under this same group.</p> <p>Cor. is located on rocky W. slope of a small hill.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T34N R26E 1/4 S34 S35 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 26, 27, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<div style="text-align: center;"> <table border="1"> <tr><td>T34N</td><td>R26E</td></tr> <tr><td>S27</td><td>S26</td></tr> <tr><td>S34</td><td>S35</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>West, bet. secs. 26 and 35.</p> <p>Over rolling and broken land.</p>	T34N	R26E	S27	S26	S34	S35	1999			
T34N	R26E										
S27	S26										
S34	S35										
1999											
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T34N</td><td>R26E</td></tr> <tr><td>S26</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S35</td><td></td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case in the drill hole beneath the brass tablet.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, N. of cor.</p> <p>Cor. is located on E. rim of Jimson Weed Canyon, atop sandstone ledge, bears N. and S., and 1.70 chs. E. of Jimson Weed Wash, 150 ft. wide, 2 ft. deep, drains NNW.</p>	T34N	R26E	S26		1/4	—	S35		1999	
T34N	R26E										
S26											
1/4	—										
S35											
1999											
80.00	<p>The cor. of secs. 26, 27, 34, and 35.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 26 and 27.</p>										

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling and broken land.
39.70	S. rim of Jimson Weed Canyon, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T34N R26E 1/4 S27 S26 1999</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
	Cor. is located 1.70 chs. S. of Jimson Weed Wash, 25 ft. wide, 4 ft. deep, drains W.
59.62	The SW cor. of a sandstone block house, 23 1/2 x 16 ft., bears East, 1.25 chs. dist., long side bears N.
67.30	Trail road, bears E. at end of curve to left.
80.00	Point for the cor. of secs. 22, 23, 26, and 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T34N R26E S22 S23 ----- S27 S26 1999</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
	Land, rolling and broken.
	Soil, sandy and rocky clay with sandstone outcrops.
	Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.
	From the cor. of secs. 23, 24, 25, and 26.
	West, bet. secs. 23 and 26.

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling and broken land across Tezinie Canyon.
10.40	Tezinie Wash, 24 ft. wide, 16 ft. deep, drains NW.
18.50	SW rim of Tezinie Canyon, atop sandstone ledge, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T34N R26E S23 1/4 — S26 1999</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
80.00	The cor. of secs. 22, 23, 26, and 27.
	Land, rolling and broken.
	Soil, sandy and rocky clay with sandstone outcrops.
	Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.
	N. 0°01' W., bet. secs. 22 and 23.
	Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T34N R26E 1/4 S22 S23 1999</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
	Cor. is located on steep SW slope of Tezinie Canyon.
52.30	Tezinie Wash, 80 ft. wide, 4 ft. deep, drains NW.
80.00	Point for the cor. of secs. 14, 15, 22, and 23.

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T34N</td><td>R26E</td></tr> <tr><td>S15</td><td>S14</td></tr> <tr><td>S22</td><td>S23</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered piñon and juniper; undergrowth, scattered brush and native grasses.</p>	T34N	R26E	S15	S14	S22	S23	1999			
T34N	R26E										
S15	S14										
S22	S23										
1999											
	<hr/>										
	<p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>West, bet. secs. 14 and 23.</p> <p>Over broken land roughly paralleling a canyon.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p>										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in sandstone bedrock, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T34N</td><td>R26E</td></tr> <tr><td>S14</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S23</td><td></td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 2.50 chs. N. of a wash, 40 ft. wide, 5 ft. deep, drains NW in curve to left.</p>	T34N	R26E	S14		1/4	—	S23		1999	
T34N	R26E										
S14											
1/4	—										
S23											
1999											
51.30	<p>Wash, 40 ft. wide, 5 ft. deep, drains NW; thence ascend out of a canyon.</p>										
62.10	<p>W. rim of same canyon, atop sandstone ledge, bears SE and NW.</p>										
68.50	<p>Navajo Route 8084, a graded road, 25 ft. wide, bears SSE and NNW.</p>										
69.80	<p>Power line, bears SE and NW.</p>										

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 14, 15, 22, and 23.</p> <p>Land, broken. Soil, sandy and rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over rolling and broken land.</p>
8.10	Power line, bears SE and NW.
17.20	Navajo Route 8084, a graded road, 25 ft. wide, bears SE and NW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E 1/4 S15 S14 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 2.20 chs. S. of a wash, 25 ft. wide, 5 ft. deep, drains NW; thence ascend abruptly to top of a mesa.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14, and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E S10 S11 ----- S15 S14 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 11, 12, 13, and 14. West, bet. secs. 11 and 14. Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E S11 1/4 — S14 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 10, 11, 14, and 15. Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 10 and 11. Over rolling and broken land.</p>
28.50	<p>Trail road, bears ENE and WSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E 1/4 S10 S11 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Point for the cor. of secs. 2, 3, 10, and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2">T34N R26E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 3</td> <td style="padding: 2px 5px;">S 2</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S10</td> <td style="padding: 2px 5px;">S11</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">1999</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>West, bet. secs. 2 and 11.</p> <p>Over rolling land.</p>	T34N R26E		S 3	S 2	S10	S11	1999			
T34N R26E											
S 3	S 2										
S10	S11										
1999											
25.05	Trail road, bears SE and NW.										
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2">T34N R26E</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 2</td> </tr> <tr> <td style="text-align: center;">1/4</td> <td style="border-bottom: 1px solid black; width: 20px;"></td> </tr> <tr> <td colspan="2" style="text-align: center;">S11</td> </tr> <tr> <td colspan="2" style="text-align: center;">1999</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of cor.</p>	T34N R26E		S 2		1/4		S11		1999	
T34N R26E											
S 2											
1/4											
S11											
1999											
63.78	The SW cor. of a wood sided house, 40 x 14 ft., bears North, 1.44 chs. dist., long side bears N.										
80.00	The cor. of secs. 2, 3, 10, and 11.										

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 2 and 3. Over rolling and broken land.</p>
5.95	Trail road, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T34N R26E 1/4 S 3 S 2 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.
69.95	Trail road, bears ESE and WNW.
80.00	The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., hereinbefore described.
	<p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 33 N., R. 26 E., executed concurrently under this same group.</p>
	Cor. is located on W. edge of a trail road, bears N. in curve to right.
	N. 0°02' W., bet. secs. 33 and 34.
	Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 33 and 34.

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E 1/4 S33 S34 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 27, 28, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E S28 S27 ----- S33 S34 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, sparse juniper; undergrowth, scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>West, bet. secs. 27 and 34.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E S27 1/4 — S34 1999</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS									
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 27, 28, 33, and 34.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, sparse juniper; undergrowth, scattered brush and native grasses.</p>								
40.00	<p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a magnet in a 1 x 1 x 2 ins. white colored plastic case, 24 ins. below the surface of the ground.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°00' E., 65.0 ft. dist., with brass cap mkd. T34N R26E 1/4 S27 RM 65.0 FT. TO COR. 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' W., 65.0 ft. dist., with brass cap mkd. T34N R26E 1/4 S28 RM 65.0 FT. TO COR. 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located in a wash, 15 ft. wide, 2 ft. deep, drains WSW.</p>								
80.00	<p>Point for the cor. of secs. 21, 22, 27, and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T34N R26E</td> </tr> <tr> <td>S21</td> <td>S22</td> </tr> <tr> <td>S28</td> <td>S27</td> </tr> <tr> <td colspan="2">1999</td> </tr> </table> </div>	T34N R26E		S21	S22	S28	S27	1999	
T34N R26E									
S21	S22								
S28	S27								
1999									

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>
	<hr/> <p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>West, bet. secs. 22 and 27.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E S22 1/4 — S27 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
47.70	<p>E. rim of Jimson Weed Canyon, atop sandstone ledge, bears SSE and NNW.</p>
50.70	<p>W. rim of Jimson Weed Canyon, atop sandstone ledge, bears SSE and NNW.</p>
80.00	<p>The cor. of secs. 21, 22, 27, and 28.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. No timber; scattered brush and native grasses.</p>
	<hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over rolling and broken land.</p>
32.30	<p>Jimson Weed Wash, 33 ft. wide, 5 ft. deep, drains W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E 1/4 S21 S22 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 15, 16, 21, and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in sandstone bedrock, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E S16 S15 ----- S21 S22 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>West, bet. secs. 15 and 22.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E S15 1/4 — S22 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
54.70	Tezinie Wash, 30 ft. wide, 5 ft. deep, drains NNW.
80.00	<p>The cor. of secs. 15, 16, 21, and 22.</p> <p>Land, rolling. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>
	<p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E 1/4 S16 S15 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
56.70	Navajo Route 8084, a graded road, 25 ft. wide, bears ESE and WNW.
58.65	Left bank of Tezinie Wash, 15 ft. high, bears ESE and WNW; thence along the bed of Tezinie Wash.
72.70	Right bank of Tezinie Wash, 15 ft. high, bears E. and W.; thence leave Tezinie Wash.
73.85	Trail road, bears ENE and WSW.
80.00	<p>Point for the cor. of secs. 9, 10, 15, and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E S 9 S10 S16 S15 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy clay. Timber, Russian olive and saltcedar along Tezinie Wash; undergrowth, scattered brush and native grasses.</p>
	<p>From the cor. of secs. 10, 11, 14, and 15. West, bet. secs. 10 and 15. Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E S10 1/4 — S15 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post. Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of cor.</p>
76.00	<p>Wash, 60 ft. wide, 7 ft. deep, drains NW.</p>
80.00	<p>The cor. of secs. 9, 10, 15, and 16. Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>
	<p>N. 0°02' W., bet. secs. 9 and 10. Over rolling and broken land.</p>
6.00	<p>Wash, 60 ft. wide, 7 ft. deep, drains NW.</p>
20.80	<p>Graded road, 20 ft. wide, bears E. and W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T34N R26E 1/4 S 9 S10 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
70.90	<p>Graded road, 20 ft. wide, bears ENE and WSW.</p>
76.80	<p>Wash, 40 ft. wide, 3 ft. deep, drains SW.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 9, and 10.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T34N R26E S 4 S 3 ----- S 9 S10 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
	<p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, saltcedar near washes; undergrowth, scattered brush and native grasses.</p>
	<p>From the cor. of secs. 2, 3, 10, and 11.</p>
	<p>West, bet. secs. 3 and 10.</p>
	<p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T34N R26E S 3 1/4 — S10 1999</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
	Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of cor.
	Cor. is located atop prominent rocky ridge, bears SE and NW.
46.15	Graded road, 20 ft. wide, bears NE and SW.
54.70	Same graded road, 20 ft. wide, bears ESE in curve to right.
56.50	Same graded road, 20 ft. wide, bears ENE in curve to right.
76.70	Wash, 60 ft. wide, 4 ft. deep, drains SW.
80.00	The cor. of secs. 3, 4, 9, and 10.
	Land, rolling and broken. Soil, sandy and rocky clay. Timber, saltcedar near wash; undergrowth, scattered brush and native grasses.
	N. 0°02' W., bet. secs. 3 and 4.
	Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T34N R26E 1/4 S 4 S 3 1999</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
80.00	The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described.

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 33 N., R. 26 E., executed concurrently under this same group.</p>
	<p>Cor. is located 1.20 chs. W. of a power line, bears SSE and NNW.</p>
	<p>N. 0°03' W., bet. secs. 32 and 33.</p>
	<p>Over nearly level land.</p>
3.90	<p>Power line, bears SSE and NNW.</p>
9.60	<p>Navajo Route 8086, a graded road, 20 ft. wide, bears SSE and NNW.</p>
34.60	<p>Sheep Dip Creek, a wash, 100 ft. wide, 3 ft. deep, drains NNW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p>
	<p>Set a magnet in a 1 x 1 x 2 ins. white colored plastic case, 24 ins. below the surface of the ground.</p>
	<p>from which</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°00' E., 267.0 ft. dist., with brass cap mkd. T34N R26E 1/4 S33 RM 267.0 FT. TO COR. 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°00' W., 275.0 ft. dist., with brass cap mkd. T34N R26E 1/4 S32 RM 275.0 FT. TO COR. 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Cor. is located on sandy, poorly defined right bank of Sheep Dip Creek, bears SE and NW.</p>
80.00	<p>Point for the cor. of secs. 28, 29, 32, and 33.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E S29 S28 ----- S32 S33 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>West, bet. secs. 28 and 33.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E S28 1/4 — S33 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located near the top of SW slope of a rocky ridge, bears SSE and NNW.</p>
80.00	<p>The cor. of secs. 28, 29, 32, and 33.</p> <p>Land, rolling and broken. Soil, sand and sandy and rocky clay. No timber; scattered brush and native grasses.</p> <p>N. 0°03' W., bet. secs. 28 and 29.</p> <p>Over nearly level land.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E 1/4 S29 S28 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 20, 21, 28, and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E S20 S21 ----- S29 S28 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>West, bet. secs. 21 and 28.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E S21 1/4 — S28 1999</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
	Thence over nearly level land.
59.00	Wash, 35 ft. wide, 3 ft. deep, drains NW.
80.00	The cor. of secs. 20, 21, 28, and 29.
	Land, rolling and broken to nearly level. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.
	N. 0°03' W., bet. secs. 20 and 21.
	Over gently rolling land.
5.70	Wash, 40 ft. wide, 3 ft. deep, drains W.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 21.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T34N R26E 1/4 S20 S21 1999</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
69.30	Jimson Weed Wash, 50 ft. wide, 8 ft. deep, drains NW.
80.00	Point for the cor. of secs. 16, 17, 20, and 21.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below the surface of the ground, with brass cap mkd.
	<p style="text-align: center;">T34N R26E S17 S16 ----- S20 S21 1999</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°00' E., 60.0 ft. dist., with brass cap mkd. T34N R26E S21 RM 60.0 FT. TO COR. 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' W., 60.0 ft. dist., with brass cap mkd. T34N R26E S17 RM 60.0 FT. TO COR. 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post at the sec. cor.</p> <p>Cor. is located on the NW edge of Navajo Route 8084, a graded road, 25 ft. wide, bears NE and SW.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>West, bet. secs. 16 and 21.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T34N R26E S16 1/4 — S21 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 16, 17, 20, and 21.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>
	<p>N. 0°03' W., bet. secs. 16 and 17.</p>
	<p>Over gently rolling land.</p>
12.70	<p>Power line, bears NE and SW.</p>
13.20	<p>Underground water pipeline, bears NE and SW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T34N R26E 1/4 S17 S16 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 8, 9, 16, and 17.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T34N R26E S 8 S 9 ----- S17 S16 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Land, gently rolling. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 9, 10, 15, and 16.</p>
	<p>West, bet. secs. 9 and 16.</p>
	<p>Over rolling land.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
21.40	Tezinie Wash, 140 ft. wide, 7 ft. deep, drains N.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 16. Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd. <div style="text-align: center;">T34N R26E S 9 1/4 — S16 1999</div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case in the drill hole beneath the brass tablet.</p> <p>Cor. is located on an overhanging rock ledge, 1.70 chs. E. of a trail road, bears ESE and WNW.</p>
46.90	Apache County Road C566, a graded road, 20 ft. wide, bears N. and S.
80.00	The cor. of secs. 8, 9, 16, and 17. Land, rolling. Soil, sandy and rocky clay. Timber, cottonwood, Russian olive and saltcedar near Tezinie Wash; undergrowth, scattered brush and native grasses.
	N. 0°03' W., bet. secs. 8 and 9. Over nearly level land.
12.00	Tezinie Wash, 30 ft. wide, 3 ft. deep, drains WSW.
23.23	Barbed wire fence, 4 strands, bears E. and W.; thence enter cultivated fields.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. below the surface of the ground, with brass cap mkd. <div style="text-align: center;">T34N R26E 1/4 S 8 S 9 1999</div>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 10°00' E., 70.0 ft. dist., with brass cap mkd. T34N R26E 1/4 S9 RM 70.0 FT. TO COR. 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 80°00' W., 68.0 ft. dist., with brass cap mkd. T34N R26E 1/4 S8 RM 68.0 FT. TO COR. 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post at the 1/4 sec. cor.</p> <p>Cor. is located in a cultivated field, 1.21 chs. E. and 90 lks. S. of a barbed wire fence, 4 strands, bears NE and SW; and 2.10 chs. S. of a trail road, bears ESE and WNW.</p>								
80.00	<p>Point for the cor. of secs. 4, 5, 8, and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T34N</td> <td style="padding: 0 10px;">R26E</td> </tr> <tr> <td style="padding: 0 10px;">S 5</td> <td style="padding: 0 10px;">S 4</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 10px;">S 8</td> <td style="border-top: 1px solid black; padding: 0 10px;">S 9</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">1999</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 50 lks. S. and 1.90 chs. W. of Apache County Road C566, a graded road, 25 ft. wide, bears ESE and WNW.</p> <p>Land, nearly level. Soil, sandy clay. Timber, cottonwood, Russian olive and saltcedar; undergrowth, scattered brush and native grasses.</p> <hr style="border: 0.5px solid black;"/> <p>From the cor. of secs. 3, 4, 9, and 10.</p>	T34N	R26E	S 5	S 4	S 8	S 9	1999	
T34N	R26E								
S 5	S 4								
S 8	S 9								
1999									

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>West, bet. secs. 4 and 9.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E S 4 1/4 — S 9 1999</p>
	<p>from which</p> <p style="padding-left: 40px;">The northeast cor. of an octagonal stuccoed hogan, 17 ft. diam., bears S. 80° W., 1.465 chs. dist., sides bear SE and WNW.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located in an old sheep corral.</p>
42.57	<p>The center of an octagonal log hogan, 22 ft. diam., bears South, 1.00 ch. dist.</p>
43.00	<p>The northernmost cor. of a wood sided house, 35 x 24 ft., bears South, 1.40 chs. dist., long side bears SW.</p>
50.54	<p>The NE cor. of a wood sided house, 45 x 15 ft., bears South, 1.89 chs. dist., long side bears S.</p>
80.00	<p>The cor. of secs. 4, 5, 8, and 9.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>N. 0°03' W., bet. secs. 4 and 5.</p> <p>Over nearly level land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E 1/4 S 5 S 4 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located at the base of a small hill.</p> <p>Thence over rolling and broken land, entering badlands.</p> <p>The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, nearly level to rolling and broken. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p>
40.00	<p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 33 N., R. 26 E., executed concurrently under this same group.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E 1/4 S31 S32 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T34N R26E S30 S29 ----- S31 S32 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>West, bet. secs. 29 and 32.</p> <p>Over nearly level land.</p>
13.50	<p>Sheep Dip Creek, a wash, 50 ft. wide, 3 ft. deep, drains NW.</p>
39.60	<p>Navajo Route 8086, a graded road, 20 ft. wide, bears SSE and NNW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T34N R26E S29 1/4 — S32 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Thence over rolling land.</p>
80.00	<p>The cor. of secs. 29, 30, 31, and 32.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, nearly level to rolling. Soil, sandy and gravelly clay. Timber, cottonwood, Russian olive and saltcedar near Sheep Dip Creek; undergrowth, scattered brush and native grasses.</p>
	<p>West, bet. secs. 30 and 31.</p>
	<p>Over rolling land on descent into Chinle Valley.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T34N R26E S30 1/4 — S31 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
48.50	<p>Apache County Road C507, a graded road, 20 ft. wide, bears NE and SW.</p>
69.90	<p>Chinle Wash, 200 ft. wide, 3 ft. deep, drains N.</p>
79.38	<p>The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with the brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 34 N., R. 25 E., executed concurrently under this same group.</p>
	<p>Land, rolling. Soil, sandy clay. Timber, cottonwood, Russian olive and saltcedar near Chinle Wash; undergrowth, scattered brush and native grasses.</p>
	<p>From the cor. of secs. 29, 30, 31, and 32.</p>
	<p>N. 0°03' W., bet. secs. 29 and 30.</p>
	<p>Over rolling land.</p>
18.00	<p>Navajo Route 8086, a graded road, 20 ft. wide, bears SE and NW.</p>
27.70	<p>Navajo Route 8084, a graded road, 20 ft. wide, bears E. and W.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
38.73	The center of an octagonal wood sided hogan, 19 ft. diam., bears East, 65 lks. dist.										
39.26	Intersect the SE side of a modular home, 68 x 24 ft., the southernmost cor. bears SW, 2 lks. dist., long side bears NW.										
39.865	Intersect the NE side of same modular home, the southernmost cor. bears SE, 50 lks. dist.										
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30. Chisel an X on concrete sidewalk in front of modular home. from which A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 60°00' E., 145.0 ft. dist., with brass cap mkd. T34N R26E 1/4 S29 RM 145.0 FT. TO COR. 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 30°00' W., 150.0 ft. dist., with brass cap mkd. T34N R26E 1/4 S30 RM 150.0 FT. TO COR. 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. From this cor. point, a rebar, 5/8 in. diam., set flush with the surface of the ground, bears S. 23°57' W., 11.94 chs. dist., with aluminum cap mkd. IHS DEHE.										
77.30	Graded road, 20 ft. wide, bears SE and NW.										
80.00	Point for the cor. of secs. 19, 20, 29, and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T34N</td> <td>R26E</td> </tr> <tr> <td>S19</td> <td>S20</td> </tr> <tr> <td colspan="2" style="text-align: center;">—+—</td> </tr> <tr> <td>S30</td> <td>S29</td> </tr> <tr> <td colspan="2" style="text-align: center;">1999</td> </tr> </table> </div> Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.	T34N	R26E	S19	S20	—+—		S30	S29	1999	
T34N	R26E										
S19	S20										
—+—											
S30	S29										
1999											

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located 1.90 chs. E. of a graded road, bears SE and NW.</p> <p>Land, rolling. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>West, bet. secs. 20 and 29.</p> <p>Over nearly level land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E S20 1/4 — S29 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
50.20	<p>Navajo Route 8084, a graded road, 20 ft. wide, bears NE and SW.</p>
72.30	<p>Sheep Dip Creek, a wash, 60 ft. wide, 2 ft. deep, drains NNW.</p>
80.00	<p>The cor. of secs. 19, 20, 29, and 30.</p>
	<p>Land, nearly level. Soil, sandy clay. Timber, Russian olive and saltcedar; undergrowth, scattered brush and native grasses.</p>
	<p>West, bet. secs. 19 and 30.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T34N R26E S19 1/4 — S30 1999</p>
	<p>from which</p> <p style="padding-left: 40px;">The southernmost cor. of a wood sided extension added to E. side of a stuccoed hogan, bears N. 49 1/2° W., 1.195 chs. dist., sides bear NE and NW.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
72.40	Navajo Route 8086, a graded road, 20 ft. wide, bears SE and NW.
79.29	<p>The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the survey of the east boundary, T. 34 N., R. 25 E., executed concurrently under this same group.</p> <p>Cor. is located 70 lks. E. of the E. bank of a concrete lined canal, 50 ft. wide, 10 ft. deep, bears N. and S.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over nearly level land.</p>
5.20	Sheep Dip Creek, a wash, 60 ft. wide, 1 ft. deep, drains WNW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T34N R26E 1/4 S19 S20 1999</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 17, 18, 19, and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td>T34N</td><td>R26E</td></tr> <tr><td>S18</td><td>S17</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S19</td><td>S20</td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay. Timber, Russian olive and saltcedar; undergrowth, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>West, bet. secs. 17 and 20.</p> <p>Over nearly level land.</p>	T34N	R26E	S18	S17			S19	S20	1999	
T34N	R26E										
S18	S17										
S19	S20										
1999											
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td>T34N</td><td>R26E</td></tr> <tr><td colspan="2" style="text-align: center;">S17</td></tr> <tr><td colspan="2" style="text-align: center;">1/4 —</td></tr> <tr><td colspan="2" style="text-align: center;">S20</td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T34N	R26E	S17		1/4 —		S20		1999	
T34N	R26E										
S17											
1/4 —											
S20											
1999											
80.00	<p>The cor. of secs. 17, 18, 19, and 20.</p>										

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, nearly level. Soil, sandy clay. Timber, scattered Russian olive and saltcedar; undergrowth, scattered brush and native grasses.</p>
	<p>West, bet. secs. 18 and 19.</p>
	<p>Over nearly level land near Many Farms Lake.</p>
11.38	<p>Barbed wire fence, 4 strands, bears SSE and NNW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T34N R26E S18 1/4 — S19 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Cor. is located 60 lks. S. of shore of Many Farms Lake, bears E. and W.</p>
79.20	<p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 34 N., R. 25 E., executed concurrently under this same group.</p>
	<p>Cor. is located 2.65 chs. S. of a trail road, bears ESE and WNW.</p>
	<p>Land, nearly level to rolling and broken at west end. Soil, sandy and rocky clay. Timber, Russian olive and saltcedar; undergrowth, scattered brush and native grasses.</p>
	<p>From the cor. of secs. 17, 18, 19, and 20.</p>
	<p>N. 0°03' W., bet. secs. 17 and 18.</p>
	<p>Over nearly level land.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
14.35	<p>Point selected for a witness point, at the water mark on the shore of Many Farms Lake, a manmade reservoir.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T34N R26E S17 S18 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on well-defined shore of Many Farms Lake, bears ENE and WSW; thence across Many Farms Lake.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18, located in Many Farms Lake, not monumented.</p>
80.00	<p>Point for the cor. of secs. 7, 8, 17, and 18, located in Many Farms Lake, not monumented.</p> <p>Land, nearly level. Soil, sandy clay. Timber, Russian olive and saltcedar; undergrowth, scattered brush and native grasses.</p>
	<p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>West, bet. secs. 8 and 17.</p> <p>Over nearly level land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E S 8 1/4 — S17 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
55.50	<p>Point selected for a witness point, at the water mark on the shore of Many Farms Lake, a manmade reservoir.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T34N R26E S 8 — S17 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on well-defined shore of Many Farms Lake, bears N. and S.; thence across Many Farms Lake.</p>
80.00	<p>Point for the cor. of secs. 7, 8, 17, and 18.</p> <p>Land, nearly level. Soil, sandy clay. Timber, cottonwood, Russian olive and saltcedar; undergrowth, scattered brush and native grasses.</p> <hr/> <p>West, bet. secs. 7 and 18.</p> <p>Over Many Farms Lake.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18, located in Many Farms Lake, not monumented.</p>
63.77	<p>Point selected for a witness point, at the water mark on the shore of Many Farms Lake, a manmade reservoir.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in soft sandstone bedrock, with brass cap mkd.</p> <p style="text-align: center;">WP T34N R26E S 7 — S18 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located on well-defined shore of Many Farms Lake, bears NE and SW; 80 lks. E. of SE rim of a rocky ridge, bears NE and SW.</p> <p>From this cor. point, a brass tablet, 3 3/4 ins. diam., set flush in a concrete collar, 8 ins. diam., firmly set, projecting 6 ins. above ground, bears N. 79°15' W., 7.30 chs. dist., with top mkd. LIMBAUGH ENGINEERING & AERIAL SURVEYS INC. 1913-29 1965.</p> <p>From this same cor. point, a brass tablet, 3 3/4 ins. diam., cemented in sandstone bedrock, bears N. 47°39' E., 13.31 chs. dist., with top mkd. LIMBAUGH ENGINEERING & AERIAL SURVEYS INC. 1913-30 1965.</p>
79.12	<p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 34 N., R. 26 E., executed concurrently under this same group.</p> <p>Cor. is located at base of W. slope of a rocky hill, bears N. and S.</p> <p>Land, lake to rolling and broken. Soil, sandy and rocky clay with sandstone outcrops. Timber, scattered Russian olive and saltcedar; undergrowth, scattered brush and native grasses.</p>
35.60	<p>From the point for the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0°03' W., bet. secs. 7 and 8.</p> <p>Over Many Farms Lake.</p> <p>Point selected for a witness point, at the water mark on the shore of Many Farms Lake, a manmade reservoir.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP T34N R26E S 7 S 8 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Cor. is located on well-defined shore of Many Farms Lake, bears E. and W.; 2.02 chs. S. of a barbed wire fence, 4 strands, bears ESE and WNW.</p> <p>Thence over nearly level land.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E 1/4 S 7 S 8 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Thence over rolling and broken land, entering badlands.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 7, and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E S 6 S 5 ----- S 7 S 8 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 1.05 chs. S. and 1.50 chs. W. of Apache County Road C566, a graded road, 20 ft. wide, bears SE and NW.</p> <p>Land, nearly level to rolling and broken. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>West, bet. secs. 5 and 8.</p> <p>Over rolling and broken land.</p>

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
5.60	Apache County Road C566, a graded road, 25 ft. wide, bears NE in curve to right.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T34N R26E S 5 1/4 — S 8 1999</div> Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post. Cor. is located on W. slope of a small hill.
80.00	The cor. of secs. 5, 6, 7, and 8. Land, rolling and broken. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.
	<hr/> West, bet. secs. 6 and 7. Over rolling and broken land on gradual descent into Chinle Valley.
37.50	Apache County Road C566, a graded road, 20 ft. wide, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T34N R26E S 6 1/4 — S 7 1999</div> Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.

Survey of the Subdivisional Lines,
T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, a brass tablet, 3 3/4 ins. diam., set in a concrete collar, 8 ins. diam., firmly set, projecting 3 ins. above ground, bears S. 5°04' E., 33.67 chs. dist., with top mkd. LIMBAUGH ENGINEERING & AERIAL SURVEYS INC. 1913-31 1965.</p>
45.30	<p>Graded road, 15 ft. wide, bears NNE and SSW.</p>
79.03	<p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 34 N., R. 25 E., executed concurrently under this same group.</p> <p>Cor. is located in floodplain of Chinle Wash, on E. edge of a large clump of saltcedar.</p> <p>Land, rolling and broken. Soil, sandy and gravelly clay. Timber, cottonwood, Russian olive and saltcedar in floodplain of Chinle Wash; undergrowth, scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R26E 1/4 S 6 S 5 1999</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling and broken. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p>

T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>The area surveyed is located just east of the community of Many Farms, Arizona. The terrain varies from nearly level in the western portion to rolling and broken with canyons and mesas in the eastern portion. The drainage is to the northwest, with Sheep Dip Creek, Jimson Weed Wash and Tezinie Wash being the principal drainages; all of which drain into Many Farms Lake. Many Farms Lake is a manmade reservoir located in sections 7, 8, 17 and 18.</p> <p>The elevation varies from 5300 to 5900 feet above sea level. The soil is mostly sandy and rocky clay with some clay badlands and sandstone outcrops. The timber consists of scattered piñon and juniper in the eastern portion, with some cottonwood, Russian olive and saltcedar near washes and Many Farms Lake. Undergrowth principally consists of scattered sagebrush, greasewood, and native grasses.</p> <p>Principal access to the township is provided by Navajo Route 8086, a graded road entering the township in section 33 and exiting in section 19; and Navajo Route 8084, a graded road, entering the township in section 24 and meeting Navajo Route 8086 in section 30. There are trail roads and graded roads throughout the township. Much of the area is used for grazing livestock, with some cultivated fields near Many Farms Lake. There is no mining activity in the township.</p> <p>The mean magnetic declination is $12 \frac{1}{4}^{\circ}$ E, as derived from the United States Geological Survey computer program GEOMAGIX utilizing the Regional Magnetic Field Model for Epoch 1995 for the dates of survey.</p> <hr/>
--------	---

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
William F. Olver	Cadastral Surveyor
Daniel Bryan	Engineering Technician
Wilfred Chee	Engineering Technician
Edward Clarke	Engineering Technician
Reuben Mason	Engineering Technician
Barney Woodie	Engineering Technician

CERTIFICATE OF SURVEY

We, Jones Curtiss and Leonard R. Sandoval, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 17th day of February, 1998, we have surveyed the east and north boundaries, and the subdivisional lines, Township 34 North, Range 26 East, of the Gila and Salt River Meridian, in the state of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

9-25-00
(Date)

Jones Curtiss
(Cadastral Surveyor)

9-19-00
(Date)

Leonard R. Sandoval
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the survey of the east and north boundaries, and the subdivisional lines, Township 34 North, Range 26 East, Gila and Salt River Meridian, Arizona, executed by Jones Curtiss and Leonard R. Sandoval, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

November 28, 2000
(Date)

Henry D. Rowmker
(Chief Cadastral Surveyor of Arizona)

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 34 N., R. 26 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.

(Date)

(Chief Cadastral Surveyor of Arizona)