

**ORIGINAL**

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES  
OF THE

---

SURVEY OF

---

THE SIXTH GUIDE MERIDIAN EAST, (WEST BOUNDARY),

---

THE EAST

---

AND NORTH BOUNDARIES,

---

AND

---

THE SUBDIVISIONAL LINES,

---

TOWNSHIP 35 NORTH, RANGE 25 EAST,

---

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Jones Curtiss, Cadastral Surveyor

---

Under Special Instructions dated and approved February 17, 1998, which provided for the surveys included under Group Number 822 and assignment instructions dated February 17, 1998.

Survey Commenced March 16, 1999

Survey Completed April 28, 1999

## INDEX DIAGRAM

TOWNSHIP 35 NORTH, RANGE 25 EAST,

GILA AND SALT RIVER MERIDIAN, ARIZONA

20 8 6 69	20 5 58	18 4 50	18 3 42	17 2 33	16 1 15
69 7 7 67	68 8 57	57 9 49	50 10 41	42 11 32	32 12 14
67 6 18 65	66 17 55	56 16 47	48 15 39	40 14 29	30 13 13
65 5 19 63	64 20 53	54 21 46	47 22 38	39 23 27	28 24 12
63 4 30 61	62 29 52	53 28 45	45 27 36	37 26 24	26 25 10
61 4 31 59	60 32 51	52 33 43	44 34 34	35 35 21	23 36 9

## T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>The following field notes describe the survey of the Sixth Guide Meridian East, (west boundary), the east and north boundaries, and the subdivisional lines, Township 35 North, Range 25 East, Gila and Salt River Meridian, Arizona.</p> <p>The west boundary of the Navajo Indian Reservation was originally surveyed by Ehud N. Darling in 1869 and dependently resurveyed by Loyd E. Sechrist in 1919-20 and is identified, where possible, for historical purposes only. The south boundary of the township was surveyed by Leonard R. Sandoval concurrently under this same group.</p> <p>The survey was executed in accordance with the specifications as set forth in the <u>Manual of Instructions for the Survey of the Public Lands of the United States, 1973</u>, and the Special Instructions dated February 17, 1998, for Group No. 822, Arizona.</p> <p>The true meridian direction and length of all lines were determined by real time kinematic and static global positioning system observations using Trimble 4400 and 4700 model receivers.</p> <p>Geodetic control was derived from first order U.S. Coast and Geodetic Survey triangulation stations "BEAUTIFUL 1951" and "LOHALI 1951", as published by the National Geodetic Survey, NAD83(1992). The geographic position of the southeast corner of the township is as follows:</p> <p>Latitude: 36°23'22.60" N.                      Longitude: 109°35'42.37" W.</p> <p>The mean magnetic declination is 12 1/4° E.</p>
--------	--

Survey of the Sixth Guide Meridian East, (West Boundary),  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Beginning at the cor. of Tps. 34 and 35 N., Rs. 24 and 25 E., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the Sixth Guide Meridian East, (west boundary), T. 34 N., R. 25 E., executed concurrently under this same group.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rolling land atop Carson Mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R24E R25E 1/4 S36   S31 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R24E   R25E S25   S30 ----- S36   S31 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy and rocky clay. No timber; scattered brush and native grasses.</p>
4.90	<p>North, bet. secs. 25 and 30.</p> <p>Over gently rolling land atop Carson Mesa.</p> <p>Trail road, bears E. and W.</p>

Survey of the Sixth Guide Meridian East, (West Boundary),  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R24E R25E 1/4 S25   S30 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 1.70 chs. S. of a trail road, bears ENE and WSW.</p>
79.30	Trail road, bears E. and W.
80.00	<p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R24E   R25E S24   S19 ----- S25   S30 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p>
	North, bet. secs. 19 and 24.
	Over gently rolling land atop Carson Mesa.
39.30	Graded road, 18 ft. wide, bears NE and SW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Sixth Guide Meridian East, (West Boundary),  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T35N R24E R25E 1/4 S24   S19 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
77.70	Trail road, bears SE and NW.
80.00	Point for the cor. of secs. 13, 18, 19, and 24.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R24E   R25E S13   S18 ----- S24   S19 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p>
	<p>North, bet. secs. 13 and 18.</p>
	<p>Over gently rolling land atop Carson Mesa.</p>
32.10	Graded road, 12 ft. wide, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 18.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R24E R25E 1/4 S13   S18 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Sixth Guide Meridian East, (West Boundary),  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	Cor. is located 3.00 chs. S. of Apache County Road C502, a graded road, 25 ft. wide, bears NE and SW.												
80.00	Point for the cor. of secs. 7, 12, 13, and 18.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.												
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T35N</td></tr> <tr><td style="text-align: center;">R24E</td><td style="text-align: center;">R25E</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S13</td><td style="text-align: center;">S18</td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table>	T35N		R24E	R25E	S12	S 7	-----		S13	S18	1999	
T35N													
R24E	R25E												
S12	S 7												
-----													
S13	S18												
1999													
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.												
	<p>Land, gently rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p>												
	North, bet. secs. 7 and 12.												
	Over gently rolling land atop Carson Mesa.												
3.90	Trail road, bears NNE and SSW.												
10.00	Trail road, bears ENE and WSW.												
37.60	Trail road, bears NE and SW.												
40.00	Point for the 1/4 sec. cor. of secs. 7 and 12.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.												
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T35N</td></tr> <tr><td style="text-align: center;">R24E</td><td style="text-align: center;">R25E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table>	T35N		R24E	R25E	1/4		S12	S 7	1999			
T35N													
R24E	R25E												
1/4													
S12	S 7												
1999													
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.												
80.00	Point for the cor. of secs. 1, 6, 7, and 12.												

Survey of the Sixth Guide Meridian East, (West Boundary),  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T35N</td></tr> <tr><td style="text-align: center;">R24E</td><td style="text-align: center;">R25E</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 15 lks. S. of a trail road, bears E. and W.</p> <p>Land, gently rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p>	T35N		R24E	R25E	S 1	S 6	-----		S12	S 7	1999	
T35N													
R24E	R25E												
S 1	S 6												
-----													
S12	S 7												
1999													
40.00	<p>North, bet. secs. 1 and 6.</p> <p>Over gently rolling land atop Carson Mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T35N</td></tr> <tr><td style="text-align: center;">R24E</td><td style="text-align: center;">R25E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table> <p>from which</p> <p style="margin-left: 40px;">A wood power pole, bears S. 21 3/4° W., 56 lks. dist., with metal tag mkd. 5A-87, with power line extending E. and W.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T35N		R24E	R25E	1/4		S 1	S 6	1999			
T35N													
R24E	R25E												
1/4													
S 1	S 6												
1999													
45.70	<p>Navajo Route 18, a graded road, 20 ft. wide, bears SE and NW.</p>												
80.00	<p>Point for the cor. of Tps. 35 and 36 N., Rs. 24 and 25 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												



Survey of the Sixth Guide Meridian East, (West Boundary),  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS																									
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T36N</td></tr> <tr><td style="text-align: center;">R24E</td><td style="text-align: center;">R25E</td></tr> <tr><td style="text-align: center;">S36</td><td style="text-align: center;">S31</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td colspan="2" style="text-align: center;">T35N</td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p style="text-align: center;">Survey of the East Boundary, T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 34 and 35 N., Rs. 25 and 26 E., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 34 N., R. 25 E., executed concurrently under this same group.</p> <p>Cor. is located atop a prominent bare clay hill.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over gently rolling land entering floodplain of Chinle Wash.</p> <p>20.90 Graded road, 15 ft. wide, bears E. and W.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T35N</td></tr> <tr><td style="text-align: center;">R25E</td><td style="text-align: center;">R26E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S36</td><td style="text-align: center;">S31</td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located in the floodplain of Chinle Wash, 1.40 chs. W. of left bank of Chinle Wash, 3 ft. high, bears NE and SW.</p>	T36N		R24E	R25E	S36	S31	-----		S 1	S 6	T35N		1999		T35N		R25E	R26E	1/4		S36	S31	1999	
T36N																									
R24E	R25E																								
S36	S31																								
-----																									
S 1	S 6																								
T35N																									
1999																									
T35N																									
R25E	R26E																								
1/4																									
S36	S31																								
1999																									

Survey of the East Boundary,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
43.46	Barbed wire fence, 5 strands, bears NNE and SSW.										
54.14	Woven wire and barbed wire fence, bears E. and W.										
70.60	Left bank of Chinle Wash, 1 ft. high, bears SSE and NNW.										
77.60	Left bank of Chinle Wash, 1 ft. high, bears NNE and SSW.										
80.00	Point for the cor. of secs. 25, 30, 31, and 36.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T35N</td> </tr> <tr> <td style="text-align: center;">R25E</td> <td style="text-align: center;">R26E</td> </tr> <tr> <td style="text-align: center;">S25</td> <td style="text-align: center;">S30</td> </tr> <tr> <td style="text-align: center;">S36</td> <td style="text-align: center;">S31</td> </tr> <tr> <td colspan="2" style="text-align: center;">1999</td> </tr> </table>	T35N		R25E	R26E	S25	S30	S36	S31	1999	
T35N											
R25E	R26E										
S25	S30										
S36	S31										
1999											
	from which										
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 33°00' W., 390.0 ft. dist., with brass cap mkd. T35N R25E S36 RM 390.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>										
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 80°00' W., 290.0 ft. dist., with brass cap mkd. T35N R25E S25 RM 290.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>										
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post at the sec. cor.</p>										
	<p>Cor. is located in the floodplain of Chinle Wash.</p>										
	<p>Land, gently rolling. Soil, sand and sandy clay. Timber, cottonwood, Russian olive and saltcedar; undergrowth, scattered brush and native grasses.</p>										
	<hr/> <p>North, bet. secs. 25 and 30.</p>										
	<p>Over gently rolling land in the floodplain of Chinle Wash.</p>										

Survey of the East Boundary,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
8.00	Left bank of Chinle Wash, 2 ft. high, bears SSE and NNW; thence along bed of Chinle Wash.												
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a magnet in a 1 x 1 x 2 5/8 ins. white plastic case, 26 ins. below the surface of the ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 30°00' W., 330.0 ft. dist., with brass cap mkd. T35N R25E 1/4 S25 RM 330.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 80°00' W., 550.0 ft. dist., with brass cap mkd. T35N R25E 1/4 S25 RM 550.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located in Chinle Wash, 350 ft. wide, 1 ft. deep, drains N.; 95 lks. E. of left bank.</p>												
52.50	Left bank of Chinle Wash, 1 ft. high, bears NNE and SSW.												
77.30	W. bank of floodplain of Chinle Wash, 10 ft. high, bears ENE and WSW; thence leave floodplain of Chinle Wash.												
80.00	<p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="padding: 0 10px;">T35N</td> </tr> <tr> <td style="padding: 0 5px;">R25E</td> <td style="border-left: 1px solid black; padding: 0 5px;">R26E</td> </tr> <tr> <td style="padding: 0 5px;">S24</td> <td style="border-left: 1px solid black; padding: 0 5px;">S19</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;">S25</td> <td style="border-left: 1px solid black; padding: 0 5px;">S30</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1999</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 1.10 chs. E. and 1.20 chs. S. of a graded road, 20 ft. wide, bears NE and SW.</p>	T35N		R25E	R26E	S24	S19			S25	S30	1999	
T35N													
R25E	R26E												
S24	S19												
S25	S30												
1999													

Survey of the East Boundary,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, gently rolling. Soil, sand and sandy clay. Timber, cottonwood, Russian olive and saltcedar; undergrowth, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 19 and 24.</p> <p>Over gently rolling land in Chinle Valley.</p>
10.01	Barbed wire fence, 5 strands, bears E. and W.; thence across cultivated field.
20.91	Barbed wire fence, 6 strands, bears E. and W.; thence leave cultivated field.
23.20	Graded road, 20 ft. wide, bears ESE and WNW.
24.00	W. bank of floodplain of Chinle Wash, 12 ft. high, bears ESE and WNW; thence across floodplain of Chinle Wash.
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R25E R26E 1/4 S24   S19 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
69.70	Chinle Wash, 220 ft. wide, 6 ft. deep, drains W.
80.00	<p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R25E   R26E S13   S18 ----- S24   S19 1999</p> </div>

Survey of the East Boundary,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sand and sandy clay. Timber, cottonwood, Russian olive and saltcedar; undergrowth, scattered brush and native grasses.</p>
	<p>North, bet. secs. 13 and 18.</p> <p>Over gently rolling land in the floodplain of Chinle Wash.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R25E R26E 1/4 S13   S18 1999</p> </div>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
43.50	Chinle Wash, 100 ft. wide, 3 ft. deep, drains NE.
67.80	Chinle Wash, 150 ft. wide, 3 ft. deep, drains NNW.
80.00	<p>Point for the cor. of secs. 7, 12, 13, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R25E   R26E S12   S 7 ----- S13   S18 1999</p> </div>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the East Boundary,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, gently rolling. Soil, sand and sandy clay. Timber, cottonwood, Russian olive and saltcedar; undergrowth, scattered brush and native grasses.</p>
	<p>North, bet. secs. 7 and 12.</p>
	<p>Over gently rolling land in the floodplain of Chinle Wash.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R25E R26E 1/4 S12   S 7 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
56.40	<p>Chinle Wash, 75 ft. wide, 7 ft. deep, drains NE.</p>
80.00	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R25E   R26E S 1   S 6 ----- S12   S 7 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Cor. is located in the floodplain of Chinle Wash, 65 lks. E. and 1.35 lks. S. of W. bank of floodplain, 6 ft. high, bears NNE and SSW.</p>

Survey of the East Boundary,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, gently rolling. Soil, sand and sandy clay. Timber, cottonwood, Russian olive and saltcedar; undergrowth, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over nearly level land in Chinle Valley.</p>
12.03	S. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
13.93	Center of U. S. Highway 191, asphalt pavement, 30 ft. wide, bears E. and W.
15.74	N. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R25E R26E 1/4 S 1   S 6 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>From this cor. point, a third order U. S. Geological Survey benchmark, bears N. 5°12' E., 14.44 chs. dist., monumented with a standard brass tablet, 3 1/2 ins. diam., set flush in a concrete collar, 7 ins. square, firmly set, projecting 10 ins. above ground, with top mkd. 1950 5190 34D.</p>
50.40	Graded road, 20 ft. wide, bears E. and W.
77.90	Trail road, bears ESE and WNW.
80.00	<p>Point for the cor. of Tps. 35 and 36 N., Rs. 25 and 26 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the East Boundary,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS															
	<table style="margin: auto;"> <tr><td colspan="2">T36N</td></tr> <tr><td>R25E</td><td>R26E</td></tr> <tr><td>S36</td><td>S31</td></tr> <tr><td colspan="2">— —</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td colspan="2">T35N</td></tr> <tr><td colspan="2">1999</td></tr> </table>	T36N		R25E	R26E	S36	S31	— —		S 1	S 6	T35N		1999	
T36N															
R25E	R26E														
S36	S31														
— —															
S 1	S 6														
T35N															
1999															
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 2.30 chs. E. of a trail road, bears N. and S.</p> <p>Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.</p>														
	<hr/> <p style="text-align: center;">Survey of the North Boundary, T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <hr/>														
	<p>From the cor. of the Tps. 35 and 36 N., Rs. 25 and 26 E., hereinbefore described.</p> <p>West, bet. secs. 1 and 36.</p> <p>Over nearly level land in Chinle Valley.</p>														
37.00	Apache County Road C565, a graded road, 20 ft. wide, bears N. and S.														
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>														
	<table style="margin: auto;"> <tr><td>T36N</td><td>R25E</td></tr> <tr><td></td><td>S36</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S 1</td></tr> <tr><td></td><td>T35N</td></tr> <tr><td></td><td>1999</td></tr> </table>	T36N	R25E		S36	1/4	—		S 1		T35N		1999		
T36N	R25E														
	S36														
1/4	—														
	S 1														
	T35N														
	1999														
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>														
69.80	Graded road, 12 ft. wide, bears SE and NW.														
80.00	Point for the cor. of secs. 1, 2, 35, and 36.														



Survey of the North Boundary,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="846 388 993 573"> <tr><td>T36N</td><td>R25E</td></tr> <tr><td>S35</td><td>S36</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td colspan="2">T35N</td></tr> <tr><td colspan="2">1999</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.</p>	T36N	R25E	S35	S36	<hr/>		S 2	S 1	T35N		1999	
T36N	R25E												
S35	S36												
<hr/>													
S 2	S 1												
T35N													
1999													
	<p>West, bet. secs. 2 and 35.</p> <p>Over rolling and broken land.</p>												
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="846 1150 993 1335"> <tr><td>T36N</td><td>R25E</td></tr> <tr><td>S35</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td colspan="2">S 2</td></tr> <tr><td colspan="2">T35N</td></tr> <tr><td colspan="2">1999</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T36N	R25E	S35		1/4	—	S 2		T35N		1999	
T36N	R25E												
S35													
1/4	—												
S 2													
T35N													
1999													
80.00	<p>Point for the cor. of secs. 2, 3, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="846 1627 993 1812"> <tr><td>T36N</td><td>R25E</td></tr> <tr><td>S34</td><td>S35</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td colspan="2">T35N</td></tr> <tr><td colspan="2">1999</td></tr> </table>	T36N	R25E	S34	S35	<hr/>		S 3	S 2	T35N		1999	
T36N	R25E												
S34	S35												
<hr/>													
S 3	S 2												
T35N													
1999													

Survey of the North Boundary,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>
	<p>West, bet. secs. 3 and 34.</p> <p>Over rolling and broken land.</p>
15.00	Trail road, bears NE and SW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R25E S34 1/4 — S 3 T35N 1999</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 3, 4, 33, and 34.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R25E S33   S34 —   — S 4   S 3 T35N 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sand and sandy clay with sandstone outcrops. No timber; scattered brush and native grasses.</p>
	<p>West, bet. secs. 4 and 33.</p>

Survey of the North Boundary,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 33, falls on steep inaccessible S. slope of sandstone ridge, bears E. and W., where it is impracticable to establish a monument.</p> <p>From this cor. point, the point selected for the witness cor. to the 1/4 sec. cor. of secs. 4 and 33, bears S. 10°00' E., 3.00 chs. dist.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <p>WC T36N R25E S33 1/4 — S 4 T35N 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case in the drill hole beneath the brass tablet.</p> <p>Thence ascend over sandstone ridge, canyon, and broken E. slope of Carson Mesa.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T36N R25E S32   S33 —   — S 5   S 4 T35N 1999</p> </div> <p>from which</p> <p style="text-align: center;">The marks X B0, chiseled on sandstone bedrock, bear N. 30 3/4° E., 2.125 chs. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located atop meandering E. rim of Carson Mesa.</p>

Survey of the North Boundary,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sand and sandy clay with sandstone outcrops. No timber; scattered brush and native grasses.</p>
	<p>West, bet. secs. 5 and 32.</p>
	<p>Over rolling land atop Carson Mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R25E S32 1/4 — S 5 T35N 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Cor. is located on a small sandy knoll.</p>
59.10	<p>Apache County Road C567, a graded road, 18 ft. wide, bears N. and S.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 31, and 32.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R25E S31   S32 —   — S 6   S 5 T35N 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Land, rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p>
	<p>West, bet. secs. 6 and 31.</p>

Survey of the North Boundary,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land atop Carson Mesa.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T36N R25E S31 1/4 — S 6 T35N 1999</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
	Cor. is located 1.40 chs. E. of a trail road, bears SE and NW.
78.39	The cor. of Tps. 35 and 36 N., Rs. 24 and 25 E., hereinbefore described.
	Land, rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.
<hr/> <p>Survey of the Subdivisional Lines, T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the survey of the north boundary, T. 34 N., R. 25 E., executed concurrently under this same group.
	Cor. is located on the S. edge of a cultivated field, 23 lks. N. of a barbed wire fence, 5 strands, bears E. and W., and 1.77 chs. E. of a barbed wire fence, 5 strands, bears N. and S.
	N. 0°01' W., bet. secs. 35 and 36.
	Over nearly level land across cultivated fields in Chinle Valley.
9.90	Woven wire fence, bears E. and W.
10.60	Graded road, 20 ft. wide, bears E. and W.
10.80	Barbed wire fence, 4 strands, bears E. and W.

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
32.48	Barbed wire fence, 6 strands, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 35 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below the surface of the ground, with brass cap mkd.
	<p style="text-align: center;">T35N R25E 1/4 S35   S36 1999</p>
	from which
	<p style="text-align: center;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' E., 263.0 ft. dist., with brass cap mkd. T35N R25E 1/4 S36 RM 263.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p style="text-align: center;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' W., 326.0 ft. dist., with brass cap mkd. T35N R25E 1/4 S35 RM 326.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post at the 1/4 sec. cor.
	Cor. is located in a cultivated field.
43.12	Barbed wire fence, 5 strands, bears E. and W.
76.13	Barbed wire fence, 6 strands, bears E. and W.
80.00	Point for the cor. of secs. 25, 26, 35, and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. below the surface of the ground, with brass cap mkd.
	<p style="text-align: center;">T35N R25E S26   S25 ----- S35   S36 1999</p>

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	from which
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°00' E., 320.0 ft. dist., with brass cap mkd. T35N R25E S36 RM 320.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°00' W., 257.0 ft. dist., with brass cap mkd. T35N R25E S35 RM 257.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post at the sec. cor.</p>
	<p>Cor. is located in a cultivated field.</p>
	<p>From this cor. point, a third order U. S. Geological Survey benchmark, bears S. 73°53' E., 19.12 chs. dist., monumented with a standard brass tablet, 3 1/2 ins. diam., set flush in a concrete collar, 6 ins. diam., firmly set, projecting 2 ins. above ground, with top mkd. 72 0 1967.</p>
	<p>Land, nearly level. Soil, sandy clay. No timber; sparse brush and native grasses.</p>
	<p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>West, bet. secs. 25 and 36.</p>
	<p>Over nearly level land in Chinle Valley.</p>
30.20	<p>Power line, bears NNE and SSW.</p>
36.60	<p>Graded road, 15 ft. wide, bears NNE and SSW.</p>
38.90	<p>Graded road, 20 ft. wide, bears NE and SW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T35N R25E S25 1/4 — S36 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Cor. is located 50 lks. E. of a barbed wire fence, 6 strands, bears NE and SW.</p>
56.90	Power line, bears N. and S.
58.00	Earthen canal, 10 ft. wide, 2 ft. deep, bears N. and S.
58.60	E. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
59.75	Center of U. S. Highway 191, asphalt pavement, 30 ft. wide, bears N. and S.
60.92	W. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
62.20	Concrete canal, 6 ft. wide, 3 ft. deep, bears N. and S.
74.69	Barbed wire fence, 5 strands, bears N. and S.; thence across cultivated field.
80.00	<p>The cor. of secs. 25, 26, 35, and 36.</p> <p>Land, nearly level. Soil, sandy clay. Timber, cottonwood, Russian olive and saltcedar on east end; undergrowth, sparse brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 25 and 26.</p>
	<p>Over nearly level land in Chinle Valley.</p>
7.45	Barbed wire fence, 5 strands, bears E. and W.
18.40	Graded road, 20 ft. wide, bears E. and W.
23.64	Barbed wire fence, 6 strands, bears NNE and SSW.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26.



Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T35N R25E 1/4 S26   S25 1999</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
	Cor. is located 96 lks. S. of a barbed wire fence, 5 strands, bears E. and W.
74.10	Barbed wire fence, 5 strands, bears E. and W.
80.00	Point for the cor. of secs. 23, 24, 25, and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. below the surface of the ground, with brass cap mkd.
	<p style="text-align: center;">T35N R25E S23   S24 ----- S26   S25 1999</p>
	from which
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' E., 423.0 ft. dist., with brass cap mkd. T35N R25E S24 RM 423.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°00' E., 494.0 ft. dist., with brass cap mkd. T35N R25E S25 RM 494.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post at the sec. cor.
	Cor. is located in a cultivated field.

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, nearly level. Soil, sandy clay. No timber; sparse brush and native grasses.</p>
	<p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>West, bet. secs. 24 and 25.</p>
	<p>Over nearly level land across cultivated fields in Chinle Valley.</p>
37.32	<p>Barbed wire fence, 5 strands, bears N. and S.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. below the surface of the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R25E S24 1/4 — S25 1999</p>
	<p>from which</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°00' E., 224.9 ft. dist., with brass cap mkd. T35N R25E 1/4 S25 RM 224.9 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°00' W., 211.0 ft. dist., with brass cap mkd. T35N R25E 1/4 S25 RM 211.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post at the 1/4 sec. cor.</p>
	<p>Cor. is located in a cultivated field, 2.72 chs. E. of a barbed wire fence, 5 strands, bears N. and S.</p>
43.08	<p>The SE cor. of a wood sided house, 68 x 38 ft., bears North, 1.83 chs. dist., long side bears WNW.</p>

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
44.22	The center of an octagonal stuccoed hogan, 19 ft. diam., bears North, 50 lks. dist.
50.29	E. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
51.06	Center of U. S. Highway 191, asphalt pavement, 30 ft. wide, bears N. and S.
52.17	A brass tablet, 3 ins. diam., set flush in a concrete collar, 6 ins. diam., firmly set, projecting 7 ins. above ground, bears North, 22 lks. dist., unmarked.
52.19	W. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
53.00	Concrete canal, 6 ft. wide, 3 ft. deep, bears N. and S.
74.13	Barbed wire fence, 5 strands, bears N. and S.; thence across cultivated field.
80.00	The cor. of secs. 23, 24, 25, and 26.  Land, nearly level. Soil, sandy clay. Timber, scattered cottonwood; undergrowth, sparse brush and native grasses.
	N. 0°01' W., bet. secs. 23 and 24.  Over nearly level land across cultivated fields in Chinle Valley.
5.04	Barbed wire fence, 4 strands, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. below the surface of the ground, with brass cap mkd.
	T35N R25E 1/4 S23   S24 1999

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°00' E., 135.0 ft. dist., with brass cap mkd. T35N R25E 1/4 S24 RM 135.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post. Set a steel fence post nearby</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' W., 119.0 ft. dist., with brass cap mkd. T35N R25E 1/4 S23 RM 119.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post. Set a steel fence post nearby.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post at the 1/4 sec. cor.</p> <p>Cor. is located in a cultivated field.</p> <p>48.35 Woven wire and barbed wire fence, bears E. and W; thence leave cultivated field.</p> <p>80.00 Point for the cor. of secs. 13, 14, 23, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T35N</td> <td style="padding: 0 5px;">R25E</td> </tr> <tr> <td style="padding: 0 5px;">S14</td> <td style="padding: 0 5px;">S13</td> </tr> <tr> <td style="border-left: 1px solid black; border-right: 1px solid black; height: 10px;"></td> <td style="border-left: 1px solid black; border-right: 1px solid black; height: 10px;"></td> </tr> <tr> <td style="padding: 0 5px;">S23</td> <td style="padding: 0 5px;">S24</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1999</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr style="border: 0.5px solid black;"/> <p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 13 and 24.</p>	T35N	R25E	S14	S13			S23	S24	1999	
T35N	R25E										
S14	S13										
S23	S24										
1999											

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over nearly level land in floodplain of Chinle Wash.
19.20	Chinle Wash, 130 ft. wide, 3 ft. deep, drains NNE.
20.40	W. bank of floodplain of Chinle Wash, 12 ft. high, bears NNE and SSW.
32.08	Barbed wire fence, 5 strands, bears NNE and SSW.
38.83	Barbed wire fence, 4 strands, bears NNE and SSW.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T35N R25E S13 1/4 — S24 1999</p>
	from which
	<p style="text-align: center;">The SE cor. of a concrete block house, 25 x 15 ft., bears N. 83 1/4° W., 78 lks. dist., long side bears WNW.</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
	Set a steel fence post nearby.
51.72	E. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
52.50	Center of U. S. Highway 191, asphalt pavement, 30 ft. wide, bears N. and S.
53.26	W. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
80.00	The cor. of secs. 13, 14, 23, and 24.
	Land, nearly level.
	Soil, sandy clay.
	Timber, cottonwood, Russian olive and saltcedar in floodplain of Chinle Wash; undergrowth, scattered brush and native grasses.
	<hr/> <p>N. 0°01' W., bet. secs. 13 and 14.</p>

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over nearly level land in Chinle Valley.
13.30	Navajo Route 18, a graded road, 20 ft. wide, bears ESE and WNW.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T35N R25E            1/4            S14   S13            1999         </div>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.  Cor. is located 70 lks. S. of an underground water line, bears ESE and WNW.
49.00	Apache County Road C508, a graded road, 20 ft. wide, bears SE and NW.
77.00	Apache County Road C508, a graded road, 20 ft. wide, bears ENE and WSW.
80.00	Point for the cor. of secs. 11, 12, 13, and 14.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T35N R25E            S11   S12            -----            S14   S13            1999         </div>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.  Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.
	From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.  West, bet. secs. 12 and 13.

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over nearly level land across floodplain of Chinle Wash.
8.00	Chinle Wash, 150 ft. wide, 3 ft. deep, drains NE.
15.20	W. bank of floodplain of Chinle Wash, 12 ft. high, bears NNE and SSW.
40.00	Point for the 1/4 sec. cor. of secs. 12 and 13.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  T35N R25E S12 1/4 — S13 1999  Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.  From this cor. point, a third order U. S. Geological Survey benchmark, bears S. 76°27' W., 15.45 chs. dist., monumented with a standard brass tablet, 3 1/2 ins. diam., set flush in a concrete collar, 7 ins. diam., firmly set, projecting 8 ins. above ground, with top mkd. 1950 5226 35D.
55.16	E. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway; and a brass tablet, 3 ins. diam., set flush in a concrete collar, 4 ins. diam., firmly set, projecting 8 ins. above ground, bears North, 11 lks. dist., with top mkd. BIA NAVAJO ROADS ELEV. 5227.479 STA 4470+00 19.
55.92	Center of Arizona State Highway 191, asphalt pavement, 30 ft. wide, bears N. and S.
56.68	A brass tablet, 3 ins. diam., set flush in a concrete collar, 4 ins. diam, firmly set, projecting 5 ins. above ground, bears North, 5 lks. dist., with top mkd. BIA NAVAJO ROADS ELEV. STA 4470+00 19.
56.71	W. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
75.00	Apache County Road C508, a graded road, 20 ft. wide, bears ENE and WSW.
80.00	The cor. of secs. 11, 12, 13, and 14.

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, nearly level. Soil, sand and sandy clay. Timber, cottonwood, Russian olive and saltcedar in floodplain of Chinle Wash; undergrowth, scattered brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 11 and 12.</p>
	<p>Over nearly level land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R25E 1/4 S11   S12 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
76.15	<p>The NW cor. of a stuccoed house, 40 x 25 ft., bears East, 4.30 chs. dist., long side bears SSW.</p>
76.60	<p>The center of an octagonal stuccoed hogan, 19 ft. diam., bears East, 5.05 chs. dist.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11, and 12.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R25E S 2   S 1 ----- S11   S12 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.</p>



Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	West, bet. secs. 1 and 12.
	Over nearly level land in Chinle Valley.
33.92	SE right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
36.92	Center of U. S. Highway 191, asphalt pavement, 30 ft. wide, bears NE in curve to right.
38.08	NW right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T35N R25E S 1 1/4 — S12 1999
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
80.00	The cor. of secs. 1, 2, 11, and 12.
	Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.
<hr/>	
	N. 0°01' W., bet. secs. 1 and 2.
	Over nearly level land in Chinle Valley.
3.90	The SW cor. of a stuccoed house, 30 x 20 ft., bears East, 3.05 chs. dist., long side bears N.
31.15	Trail road, bears SSE and NNW.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T35N R25E 1/4 S 2   S 1 1999
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
80.00	The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.  Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.
	<hr/> From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 34 N., R. 25 E., executed concurrently under this same group.  Cor. is located 90 lks. E. of base of E. slope of Carson Mesa, bears NNE and SSW.  N. 0°01' W., bet. secs. 34 and 35.  Over broken land along the E. slope of Carson Mesa.
40.00	Point for the 1/4 sec. cor. of secs. 34 and 35.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T35N R25E 1/4 S34   S35 1999
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.  Cor. is located on the E. slope of Carson Mesa.  From this cor. point, the 44 Mile Cor. of the 1920 resurvey of the W. bdy. of the 1868 Executive Order Navajo Indian Reservation, bears S. 74°55' E., 17.54 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. NIR 44M 1920. Remove and destroy the iron post and the memorial stone from beneath.

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Point for the cor. of secs. 26, 27, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T35N R25E</td> </tr> <tr> <td>S27</td> <td>S26</td> </tr> <tr> <td colspan="2">-----</td> </tr> <tr> <td>S34</td> <td>S35</td> </tr> <tr> <td colspan="2">1999</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on E. slope of Carson Mesa, 1.20 chs. W. of base, bears NNE and SSW.</p> <p>Land, broken land. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>	T35N R25E		S27	S26	-----		S34	S35	1999	
T35N R25E											
S27	S26										
-----											
S34	S35										
1999											
	<p>From the cor. of secs. 25, 26, 35, and 36.</p>										
	<p>West, bet. secs. 26 and 35.</p>										
	<p>Over nearly level land across cultivated field in Chinle Valley.</p>										
3.31	<p>Barbed wire fence, 4 strands, bears N. and S.</p>										
13.59	<p>Barbed wire fence, 4 strands, bears N. and S.</p>										
18.47	<p>Barbed wire fence, 4 strands, bears N. and S.</p>										
23.97	<p>Barbed wire fence, 5 strands, bears SE and NW.</p>										
26.89	<p>Barbed wire fence, 5 strands, bears ESE and WNW.</p>										
35.11	<p>Barbed wire fence, 5 strands, bears N. and S.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. below the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T35N R25E</td> </tr> <tr> <td colspan="2">S26</td> </tr> <tr> <td>1/4</td> <td>---</td> </tr> <tr> <td colspan="2">S35</td> </tr> <tr> <td colspan="2">1999</td> </tr> </table> </div>	T35N R25E		S26		1/4	---	S35		1999	
T35N R25E											
S26											
1/4	---										
S35											
1999											

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' E., 418.0 ft. dist., with brass cap mkd. T35N R25E 1/4 S26 RM 418.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' W., 520.0 ft. dist., with brass cap mkd. T35N R25E 1/4 S26 RM 520.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post at the 1/4 sec. cor.</p> <p>Cor. is located in a cultivated field.</p>
55.22	Barbed wire fence, 5 strands, bears N. and S.; thence leave cultivated field on ascent from Chinle Valley.
56.87	Intersect the E. side of an octagonal stuccoed hogan, 20 1/2 ft. diam., the SE cor. bears South, 1 lk. dist.
58.99	The SE cor. of a stone house, 33 x 15 ft., bears North, 22 lks. dist., long side bears North.
80.00	The cor. of secs. 26, 27, 34, and 35.
	<p>Land, nearly level to rolling. Soil, sandy and rocky clay. Timber, sparse cottonwood; undergrowth, scattered brush and native grasses.</p>
	N. 0°01' W., bet. secs. 26 and 27.
	Over broken land along E. slope of Carson Mesa.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T35N R25E 1/4 S27   S26 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Thence descend abruptly to gently rolling land on W. edge of Chinle Valley.</p>
53.25	<p>Trail road, bears ESE and WNW.</p>
80.00	<p>Point for the cor. of secs. 22, 23, 26, and 27.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R25E S22   S23 ----- S27   S26 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Cor. is located 2.70 chs. E. of base of E. slope of Carson Mesa, bears ESE and WNW.</p>
	<p>Land, broken to gently rolling. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 23, 24, 25, and 26.</p>
	<p>West, bet. secs. 23 and 26.</p>
	<p>Over nearly level land across cultivated field in Chinle Valley.</p>
14.75	<p>Barbed wire fence, 4 strands, bears N. and S.; thence leave cultivated field.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p style="text-align: center;">T35N R25E S23 1/4 — S26 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 1.00 ch. E. of a trail road, bears SE and NW.</p> <p>The cor. of secs. 22, 23, 26, and 27.</p> <p>Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
40.00	<p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over rolling land along W. edge of Chinle Valley.</p> <p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
80.00	<p style="text-align: center;">T35N R25E 1/4 S22   S23 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>From this cor. point, the 46 Mile Cor. of the 1920 resurvey of the W. bdy. of the 1868 Executive Order Navajo Indian Reservation, bears S. 81°33' E., 16.84 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. NIR 46M 1920. Remove and destroy the iron post and the memorial stone from beneath.</p> <p>Point for the cor. of secs. 14, 15, 22, and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<div style="text-align: center;"> <table border="1"> <tr><td>T35N</td><td>R25E</td></tr> <tr><td>S15</td><td>S14</td></tr> <tr><td>S22</td><td>S23</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>	T35N	R25E	S15	S14	S22	S23	1999			
T35N	R25E										
S15	S14										
S22	S23										
1999											
40.00	<hr/> <p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>West, bet. secs. 14 and 23.</p> <p>Over nearly level land in Chinle Valley.</p> <p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>										
80.00	<div style="text-align: center;"> <table border="1"> <tr><td>T35N</td><td>R25E</td></tr> <tr><td>S14</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S23</td><td></td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located in an abandoned eroded road bed, bears SE and NW.</p> <p>The cor. of secs. 14, 15, 22, and 23.</p> <p>Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.</p>	T35N	R25E	S14		1/4	—	S23		1999	
T35N	R25E										
S14											
1/4	—										
S23											
1999											
33.90	<hr/> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over nearly level land in Chinle Valley.</p> <p>Navajo Route 18, a graded road, 16 ft. wide, bears ESE and WNW.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p>										

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R25E 1/4 S15   S14 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>From this cor. point, the 47 Mile Cor. of the 1920 resurvey of the W. bdy. of the 1868 Executive Order Navajo Indian Reservation, bears S. 85°09' E., 16.56 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. NIR 47M 1920. Remove and destroy the iron post and the memorial stone from beneath.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14, and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a steel fence post, with brass cap mkd.</p> <p style="text-align: center;">T35N R25E S10   S11 ----- S15   S14 1999</p> <p>Cor. is located on a bare sand dune.</p> <p>Land, nearly level. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>West, bet. secs. 11 and 14.</p> <p>Over nearly level land in Chinle Valley.</p> <p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>



Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p style="text-align: center;">T35N R25E S11 1/4 — S14 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 10, 11, 14, and 15.</p> <p>Land, nearly level. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p>
12.20	<p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over rolling land on ascent from Chinle Valley.</p> <p>Power line, bears SE and NW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
80.00	<p style="text-align: center;">T35N R25E 1/4 S10   S11 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>From this cor. point, the 48 Mile Cor. of the 1920 resurvey of the W. bdy. of the 1868 Executive Order Navajo Indian Reservation, bears S. 71°28' E., 17.23 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. NIR 48M 1920. Remove and destroy the iron post and the memorial stone from beneath.</p> <p>Point for the cor. of secs. 2, 3, 10, and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<div style="text-align: center;"> <table border="1"> <tr><td>T35N</td><td>R25E</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S10</td><td>S11</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy and rocky clay. No timber; scattered brush and native grasses.</p>	T35N	R25E	S 3	S 2			S10	S11	1999	
T35N	R25E										
S 3	S 2										
S10	S11										
1999											
39.00	<hr/> <p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>West, bet. secs. 2 and 11.</p> <p>Over nearly level to broken land on ascent from Chinle Valley.</p> <p>Rock ledge at top of ascent, bears NE and SW; thence over rolling land.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>										
80.00	<div style="text-align: center;"> <table border="1"> <tr><td>T35N</td><td>R25E</td></tr> <tr><td>S 2</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S11</td><td></td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 2, 3, 10, and 11.</p> <p>Land, nearly level to broken to rolling. Soil, sand, sandy and rocky clay, and rock outcrops. No timber; scattered brush and native grasses.</p>	T35N	R25E	S 2		1/4	—	S11		1999	
T35N	R25E										
S 2											
1/4	—										
S11											
1999											
40.00	<hr/> <p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p>										

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R25E 1/4 S 3   S 2 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy and rocky clay. No timber; scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 34 N., R. 25 E., executed concurrently under this same group.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over rolling land along E. slope of Windy Valley.</p> <p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R25E 1/4 S33   S34 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
51.80	<p>Graded road, 20 ft. wide, bears NNE and SSW.</p>
80.00	<p>Point for the cor. of secs. 27, 28, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<table border="1" style="margin: auto;"> <tr> <td>T35N</td> <td>R25E</td> </tr> <tr> <td>S28</td> <td>S27</td> </tr> <tr> <td>S33</td> <td>S34</td> </tr> <tr> <td colspan="2" style="text-align: center;">1999</td> </tr> </table>	T35N	R25E	S28	S27	S33	S34	1999			
T35N	R25E										
S28	S27										
S33	S34										
1999											
	<p>from which</p> <p>The NE cor. of an octagonal stuccoed hogan, 24 ft. diam., bears S. 8 1/2° W., 1.185 chs. dist., sides bear SSE and WNW.</p> <p>The northernmost cor. of same hogan, bears S. 15 3/4° W., 1.18 chs. dist., sides bear ESE and WSW.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>										
	<hr/> <p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>West, bet. secs. 27 and 34.</p> <p>Over broken land on ascent of E. slope of Carson Mesa.</p>										
9.30	E. rim of Carson Mesa, bears NE and SW; thence continue over rolling land atop Carson Mesa.										
37.15	Trail road, bears N. and S.										
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34.										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <table border="1" style="margin: auto;"> <tr> <td>T35N</td> <td>R25E</td> </tr> <tr> <td></td> <td>S27</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S34</td> </tr> <tr> <td colspan="2" style="text-align: center;">1999</td> </tr> </table> </p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Thence descend E. slope of Windy Valley.</p>	T35N	R25E		S27	1/4	—		S34	1999	
T35N	R25E										
	S27										
1/4	—										
	S34										
1999											

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 27, 28, 33, and 34.</p> <p>Land, broken to rolling. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p> <hr/>
40.00	<p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over rolling land along E. slope of Windy Valley.</p> <p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R25E 1/4 S28   S27 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 21, 22, 27, and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R25E S21   S22 ----- S28   S27 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>West, bet. secs. 22 and 27.</p> <p>Over rolling and broken land on ascent from Chinle Valley.</p>

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
15.70	E. rim of Carson mesa, bears NNE and SSW; thence over rolling land atop Carson Mesa.
37.40	Trail road, bears N. and S.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T35N R25E S22 1/4 — S27 1999
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
	Thence descend into Windy Valley.
80.00	The cor. of secs. 21, 22, 27, and 28.
	Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.
	N. 0°02' W., bet. secs. 21 and 22.
	Over rolling land in Windy Valley.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T35N R25E 1/4 S21   S22 1999
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 15, 16, 21, and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>T35N</td> <td>R25E</td> </tr> <tr> <td>S16</td> <td>S15</td> </tr> <tr> <td>S21</td> <td>S22</td> </tr> <tr> <td colspan="2" style="text-align: center;">1999</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>	T35N	R25E	S16	S15	S21	S22	1999			
T35N	R25E										
S16	S15										
S21	S22										
1999											
40.00	<hr/> <p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>West, bet. secs. 15 and 22.</p> <p>Over rolling land on ascent from Chinle Valley into Windy Valley.</p> <p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>										
80.00	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>T35N</td> <td>R25E</td> </tr> <tr> <td></td> <td>S15</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S22</td> </tr> <tr> <td colspan="2" style="text-align: center;">1999</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 15, 16, 21, and 22.</p> <p>Land, rolling. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>	T35N	R25E		S15	1/4	—		S22	1999	
T35N	R25E										
	S15										
1/4	—										
	S22										
1999											
40.00	<hr/> <p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over rolling land leaving Windy Valley.</p> <p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>										

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p style="text-align: center;">T35N R25E 1/4 S16   S15 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 9, 10, 15, and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in sandstone bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T35N R25E S 9   S10 ----- S16   S15 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay with sandstone outcrops. No timber; scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>West, bet. secs. 10 and 15.</p> <p>Over rolling land on ascent from Chinle Valley.</p> <p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a steel fence post, with brass cap mkd.</p> <p style="text-align: center;">T35N R25E S10 1/4 — S15 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on a bare sand dune.</p>



Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
50.10	Wash, 40 ft. wide, 4 ft. deep, drains ESE.
53.10	Navajo Route 18, a graded road, 16 ft. wide, bears SSE and NNW.
80.00	The cor. of secs. 9, 10, 15, and 16.
	<p>Land, rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p>
	N. 0°02' W., bet. secs. 9 and 10.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T35N R25E 1/4 S 9   S10 1999</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
51.60	Navajo Route 18, a graded road, 20 ft. wide, bears SSE and NNW.
76.80	Wash, 40 ft. wide, 10 ft. deep, drains ESE.
80.00	Point for the cor. of secs. 3, 4, 9, and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a steel fence post, with brass cap mkd.
	<p style="text-align: center;">T35N R25E S 4   S 3 ----- S 9   S10 1999</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
	Cor. is located in a sandy area.

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand and sandy and rocky clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 2, 3, 10, and 11.</p>
	<p>West, bet. secs. 3 and 10.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R25E S 3 1/4 — S10 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 3, 4, 9, and 10.</p>
	<p>Land, rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p>
	<p>N. 0°02' W., bet. secs. 3 and 4.</p>
	<p>Over rolling and broken land.</p>
15.10	<p>Power line, bears SE and NW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R25E 1/4 S 4   S 3 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
52.20	Graded road, 20 ft. wide, bears E. and W.
80.00	The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described.  Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.
	<hr/>
	From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 34 N., R. 25 E., executed concurrently under this same group.  N. 0°03' W., bet. secs. 32 and 33.  Over nearly level land in Windy Valley.
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T35N R25E            1/4            S32   S33            1999         </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
76.20	Trail road, bears ESE and WNW.
80.00	Point for the cor. of secs. 28, 29, 32, and 33.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T35N R25E            S29   S28  <hr style="width: 50%; margin: 0 auto;"/>           S32   S33            1999         </div>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>West, bet. secs. 28 and 33.</p> <p>Over gently rolling land in Windy Valley.</p> <p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R25E S28 1/4 — S33 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 28, 29, 32, and 33.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
40.00	<p>N. 0°03' W., bet. secs. 28 and 29.</p> <p>Over nearly level land in Windy Valley.</p> <p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R25E 1/4 S29   S28 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 20, 21, 28, and 29.</p>

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="849 384 995 541"> <tr> <td colspan="2" data-bbox="849 384 995 411">T35N R25E</td> </tr> <tr> <td data-bbox="849 411 922 459">S20</td> <td data-bbox="922 411 995 459">S21</td> </tr> <tr> <td data-bbox="849 459 922 508">S29</td> <td data-bbox="922 459 995 508">S28</td> </tr> <tr> <td colspan="2" data-bbox="849 508 995 541">1999</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located between boulders near the base of S. slope of a spur of Carson Mesa, bears E. and W.</p> <p>Land, nearly level. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>	T35N R25E		S20	S21	S29	S28	1999			
T35N R25E											
S20	S21										
S29	S28										
1999											
40.00	<p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>West, bet. secs. 21 and 28.</p> <p>Over gently rolling land in Windy Valley.</p> <p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="849 1276 995 1434"> <tr> <td colspan="2" data-bbox="849 1276 995 1304">T35N R25E</td> </tr> <tr> <td colspan="2" data-bbox="849 1304 995 1331">S21</td> </tr> <tr> <td data-bbox="849 1331 922 1379">1/4</td> <td data-bbox="922 1331 995 1379">—</td> </tr> <tr> <td colspan="2" data-bbox="849 1379 995 1407">S28</td> </tr> <tr> <td colspan="2" data-bbox="849 1407 995 1434">1999</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p>	T35N R25E		S21		1/4	—	S28		1999	
T35N R25E											
S21											
1/4	—										
S28											
1999											
80.00	<p>The cor. of secs. 20, 21, 28, and 29.</p> <p>Land, gently rolling. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>										
	<p>N. 0°03' W., bet. secs. 20 and 21.</p>										

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Over broken land across spurs and sandstone cliffs along E. edge of upper level of Carson Mesa.</p>
30.90	<p>E. rim of upper level of Carson Mesa, bears ESE and WNW; thence over rolling land atop Carson Mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T35N R25E 1/4 S20   S21 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case in the drill hole beneath the brass tablet.</p> <p>From this cor. point, a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above ground, bears N. 28°40' W., 17.36 chs. dist., with red plastic cap mkd. ONLA.</p>
80.00	<p>Point for the cor. of secs. 16, 17, 20, and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R25E S17   S16 ----- S20   S21 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, broken to rolling. Soil, sand, sandy and rocky clay, and sandstone outcrops. No timber; scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>West, bet. secs. 16 and 21.</p> <p>Over gently rolling land in Windy Valley.</p> <p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p>

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T35N R25E S16 1/4 — S21 1999</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
41.90	Base of E. slope of upper level of Carson Mesa, bears N. and S.
47.80	E. rim of upper level of Carson Mesa, bears NNE and SSW; thence over rolling land atop Carson Mesa.
80.00	The cor. of secs. 16, 17, 20, and 21.
	<p>Land, gently rolling to broken to rolling. Soil, sand, sandy and rocky clay, and sandstone outcrops. No timber; scattered brush and native grasses.</p>
	<p>N. 0°03' W., bet. secs. 16 and 17. Over rolling and broken land atop Carson Mesa.</p>
40.00	Point for the 1/4 sec. cor. of secs. 16 and 17.
	<p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T35N R25E 1/4 S17   S16 1999</p>
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case in the drill hole beneath the brass tablet.
80.00	Point for the cor. of secs. 8, 9, 16, and 17.
	Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<div style="text-align: center;"> <table border="1"> <tr><td>T35N</td><td>R25E</td></tr> <tr><td>S 8</td><td>S 9</td></tr> <tr><td>S17</td><td>S16</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case in the drill hole beneath the brass tablet.</p> <p>Land, rolling and broken. Soil, sand, sandy and rocky clay, and sandstone outcrops. No timber; scattered brush and native grasses.</p>	T35N	R25E	S 8	S 9	S17	S16	1999			
T35N	R25E										
S 8	S 9										
S17	S16										
1999											
40.00	<p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>West, bet. secs. 9 and 16.</p> <p>Over broken land across sandstone spurs of Carson Mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>										
	<div style="text-align: center;"> <table border="1"> <tr><td>T35N</td><td>R25E</td></tr> <tr><td>S 9</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S16</td><td></td></tr> <tr><td colspan="2">1999</td></tr> </table> </div>	T35N	R25E	S 9		1/4	—	S16		1999	
T35N	R25E										
S 9											
1/4	—										
S16											
1999											
	<p>from which</p> <p style="padding-left: 40px;">The marks X B0, chiseled on the W. face of a sandstone cliff, bear S. 59 1/4° E., 65 lks. dist.</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located atop N. bank of a wash, 15 ft. wide, 6 ft. deep, drains E.; between steep sandstone ridges.</p>										
62.90	<p>E. rim of spur of Carson Mesa, atop sandstone cliff, bears NNE and SSW; thence across Carson Mesa.</p>										
80.00	<p>The cor. of secs. 8, 9, 16, and 17.</p>										



Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sand, sandy and rocky clay, and sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/>
	<p>N. 0°03' W., bet. secs. 8 and 9.</p>
	<p>Over rolling and broken land atop Carson Mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in sandstone bedrock, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R25E 1/4 S 8   S 9 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 8, and 9.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R25E S 5   S 4 ----- S 8   S 9 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Land, rolling and broken. Soil, sand, sandy and rocky clay, and sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 3, 4, 9, and 10.</p>
	<p>West, bet. secs. 4 and 9.</p>
	<p>Over rolling and broken land.</p>
3.80	<p>Wash, 40 ft. wide, 2 ft. deep, drains SSE.</p>
5.30	<p>Navajo Route 18, a graded road, 30 ft. wide, bears NNE and SSW.</p>

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
21.30	Wash, 10 ft. wide, 3 ft. deep, drains ENE.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 9.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T35N R25E                  S 4              1/4 —                  S 9              1999         </div> Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.  Thence ascend E. slope of Carson Mesa.
80.00	The cor. of secs. 4, 5, 8, and 9.  Land, rolling and broken. Soil, sand, sandy clay and sandstone outcrops. No timber; scattered brush and native grasses.
	<hr/> N. 0°03' W., bet. secs. 4 and 5.  Over rolling and broken land atop Carson Mesa.
13.80	Navajo Route 18, a graded road, 30 ft. wide, bears ENE and WSW.
30.10	Power line, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in sandstone bedrock, with brass cap mkd.  <div style="text-align: center;">           T35N R25E                  1/4              S 5   S 4              1999         </div> Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
80.00	The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described.

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sand, sandy clay and sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p>From the true point for the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., falls on an inaccessible area on a narrow sandstone ridge, where it is impracticable to establish a permanent monument.</p> <p>True point is located 1.55 chs. W. of base of E. slope of narrow sandstone ridge, extends S.</p> <p>From this cor. point, the witness cor. to the cor. of secs. 5, 6, 31, and 32, bears S. 45°00' E., 3.00 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 34 N., R. 25 E., executed concurrently under this same group.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over sandstone ridges and canyons along E. rim of upper level of Carson Mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T35N R25E 1/4 S31   S32 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case in the drill hole beneath the brass tablet.</p> <p>Cor. is located on a steep sandstone slope, 1.70 chs. S. of rim of a spur of Carson Mesa, bears ESE and WNW.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in sandstone bedrock, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<div style="text-align: center;"> <table border="1"> <tr> <td>T35N</td> <td>R25E</td> </tr> <tr> <td>S30</td> <td>S29</td> </tr> <tr> <td>S31</td> <td>S32</td> </tr> <tr> <td colspan="2">1999</td> </tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located at bottom of a small sandstone canyon, drains ENE.</p> <p>Land, broken. Soil, sandstone outcrops and sand. No timber; sparse brush and native grasses.</p>	T35N	R25E	S30	S29	S31	S32	1999			
T35N	R25E										
S30	S29										
S31	S32										
1999											
40.00	<hr/> <p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>West, bet. secs. 29 and 32.</p> <p>Over nearly level land in Windy Valley.</p> <p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T35N</td> <td>R25E</td> </tr> <tr> <td></td> <td>S29</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S32</td> </tr> <tr> <td colspan="2">1999</td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">The SE cor. of a wood sided house, 17 1/2 x 16 ft., bears N. 35° W., 2.36 chs. dist., long side bears N.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Thence over rolling and broken land.</p>	T35N	R25E		S29	1/4	—		S32	1999	
T35N	R25E										
	S29										
1/4	—										
	S32										
1999											
80.00	<p>The cor. of secs. 29, 30, 31, and 32.</p>										

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Land, nearly level to rolling and broken. Soil, sand, sandy and rocky clay, and sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p>West, bet. secs. 30 and 31.</p> <p>Over broken and rolling land ascending E. slope of upper level of Carson Mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R25E S30 1/4 — S31 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Thence over rolling land atop Carson Mesa.</p>
78.84	<p>The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, broken and rolling. Soil, sand, sandy and rocky clay, and sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/>
40.00	<p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over broken and rolling land ascending E. slope of upper level of Carson Mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T35N R25E 1/4 S30   S29 1999</p>

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case in the drill hole beneath the brass tablet.</p> <p>Thence over rolling land atop Carson Mesa.</p> <p>Point for the cor. of secs. 19, 20, 29, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T35N</td><td>R25E</td></tr> <tr><td>S19</td><td>S20</td></tr> <tr><td>S30</td><td>S29</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, broken and rolling. Soil, sand, sandy and rocky clay, and sandstone outcrops. No timber; scattered brush and native grasses.</p>	T35N	R25E	S19	S20	S30	S29	1999			
T35N	R25E										
S19	S20										
S30	S29										
1999											
40.00	<p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>West, bet. secs. 20 and 29.</p> <p>Over broken land across sandstone spurs of Carson Mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in place, in a drill hole, in sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T35N</td><td>R25E</td></tr> <tr><td colspan="2">S20</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td colspan="2">S29</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div>	T35N	R25E	S20		1/4	—	S29		1999	
T35N	R25E										
S20											
1/4	—										
S29											
1999											
80.00	<p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case in the drill hole beneath the brass tablet.</p> <p>Thence over rolling land atop Carson Mesa</p> <p>The cor. of secs. 19, 20, 29, and 30.</p>										

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, broken and rolling. Soil, sand, sandy and rocky clay, and sandstone outcrops. No timber; scattered brush and native grasses.</p>
	<hr/>
	<p>West, bet. secs. 19 and 30.</p>
	<p>Over rolling land atop Carson Mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R25E S19 1/4 — S30 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
78.75	<p>The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., hereinbefore described.</p>
	<p>Land, rolling.</p>
	<p>Soil, sand and sandy clay.</p>
	<p>No timber; scattered brush and native grasses.</p>
	<hr/>
	<p>From the cor. of secs. 19, 20, 29, and 30.</p>
	<p>N. 0°03' W., bet. secs. 19 and 20.</p>
	<p>Over rolling land atop Carson Mesa.</p>
24.15	<p>Trail road, bears ESE and WNW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R25E 1/4 S19   S20 1999</p>

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 17, 18, 19, and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T35N</td><td>R25E</td></tr> <tr><td>S18</td><td>S17</td></tr> <tr><td>S19</td><td>S20</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p>	T35N	R25E	S18	S17	S19	S20	1999			
T35N	R25E										
S18	S17										
S19	S20										
1999											
40.00	<p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>West, bet. secs. 17 and 20.</p> <p>Over rolling land atop Carson Mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T35N</td><td>R25E</td></tr> <tr><td>S17</td><td>—</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S20</td><td>—</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div>	T35N	R25E	S17	—	1/4	—	S20	—	1999	
T35N	R25E										
S17	—										
1/4	—										
S20	—										
1999											
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 17, 18, 19, and 20.</p>										



Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand, sandy clay and sandstone outcrops. No timber; scattered brush and native grasses.</p>
	<p>West, bet. secs. 18 and 19.</p>
	<p>Over rolling land atop Carson Mesa.</p>
37.60	<p>Graded road, 20 ft. wide, bears NE and SW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R25E S18 1/4 — S19 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
78.66	<p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., hereinbefore described.</p>
	<p>Land, rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of sec. 17, 18, 19, and 20.</p>
	<p>N. 0°03' W., bet. secs. 17 and 18.</p>
	<p>Over rolling land atop Carson Mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R25E 1/4 S18   S17 1999</p>

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.										
49.80	Trail road, bears ESE and WNW.										
76.20	Trail road, bears SE and NW.										
80.00	Point for the cor. of secs. 7, 8, 17, and 18.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T35N R25E</td></tr> <tr><td>S 7</td><td>S 8</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S18</td><td>S17</td></tr> <tr><td colspan="2">1999</td></tr> </table>	T35N R25E		S 7	S 8	-----		S18	S17	1999	
T35N R25E											
S 7	S 8										
-----											
S18	S17										
1999											
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.										
	Land, rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.										
	From the cor. of secs. 8, 9, 16, and 17.										
	West, bet. secs. 8 and 17.										
	Over rolling land atop Carson Mesa.										
40.00	Point for the 1/4 sec. cor. of secs. 8 and 17.										
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T35N R25E</td></tr> <tr><td colspan="2">S 8</td></tr> <tr><td>1/4</td><td>---</td></tr> <tr><td colspan="2">S17</td></tr> <tr><td colspan="2">1999</td></tr> </table>	T35N R25E		S 8		1/4	---	S17		1999	
T35N R25E											
S 8											
1/4	---										
S17											
1999											
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.										
80.00	The cor. of secs. 7, 8, 17, and 18.										

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sand, sandy clay and sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/>
	<p>West, bet. secs. 7 and 18.</p>
	<p>Over rolling land atop Carson Mesa.</p>
4.10	<p>Trail road, bears SE and NW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R25E S 7 1/4 — S18 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
51.90	<p>Apache County Road C502, a graded road, 20 ft. wide, bears NE and SW.</p>
78.57	<p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., hereinbefore described.</p>
	<p>Land, rolling. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 7, 8, 17, and 18.</p>
	<p>N. 0°03' W., bet. secs. 7 and 8.</p>
	<p>Over rolling land atop Carson Mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T35N R25E 1/4 S 7   S 8 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
43.60	<p>The SE cor. of a stuccoed house, 44 x 25 ft., bears West, 6.25 chs. dist., long side bears NNE.</p>
44.70	<p>The center of an octagonal stuccoed hogan, 20 ft. diam., bears West, 5.30 chs. dist.</p>
71.90	<p>Apache County Road C502, a graded road, 20 ft. wide, bears NE and SW.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 7, and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R25E S 6   S 5 ----- S 7   S 8 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Cor. is located 2.70 chs. S. of Navajo Route 18, a graded road, 20 ft. wide, bears ESE and WNW.</p>
	<p>Land, rolling. Soil, sand and sandy and rocky clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>West, bet. secs. 5 and 8.</p> <p>Over rolling land atop Carson Mesa.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T35N R25E S 5 1/4 — S 8 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 65 lks. S. and 1.10 chs. E. of Navajo Route 18, a graded road, 24 ft. wide, bears ENE and WSW.</p> <p>73.90 Junction of graded roads, 20 ft. wide, with Apache County Road C567 extending NE, Navajo Route 18 extending ESE and WNW, and Apache County Road C502 extending SW.</p> <p>80.00 The cor. of secs. 5, 6, 7, and 8.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p>
	<hr/> <p>West, bet. secs. 6 and 7.</p> <p>Over rolling land atop Carson Mesa.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R25E S 6 1/4 — S 7 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>78.49 The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 5, 6, 7, and 8.</p>

Survey of the Subdivisional Lines,  
T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°03' W., bet. secs. 5 and 6.
	Over rolling land atop Carson Mesa.
34.90	Power line, bears E. and W.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 6.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T35N R25E 1/4 S 6   S 5 1999</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
80.00	The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., hereinbefore described.
	Land, rolling.
	Soil, sand and sandy clay.
	No timber; scattered brush and native grasses.

## T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS

## GENERAL DESCRIPTION

The area surveyed is approximately seven miles north of the community of Many Farms, Arizona. The eastern portion of the township is nearly level land in Chinle Valley and the western portion is nearly level to rolling and broken land on two levels of Carson Mesa. There are numerous sandstone cliffs and ridges extending from section 32 northerly through section 4. The drainage in the western portion is westerly and the eastern portion drains into Chinle Wash, which drains northerly along the east boundary of the township.

The elevation varies from 5200 to 6000 feet above sea level. The soil is mostly sand and sandy and rocky clay, with some sandstone outcrops. The timber is confined mainly to the floodplain of Chinle Wash, and consists of cottonwood, Russian olive, and saltcedar. The remainder of the township is vegetated with scattered brush and native grasses.

Principal access to the township is provided by U. S. Highway 191, asphalt pavement, which enters the township in section 36 and exits in section 1. There are graded roads and trail roads throughout the township. Much of the area is used for grazing livestock. Sections 13, 23, 24, 25, 26, 35, and 36 have numerous cultivated fields. There is no mining activity in the township.

The mean magnetic declination is  $12 \frac{1}{4}^{\circ}$  E., as derived from the United States Geological Survey computer program GEOMAGIX utilizing the Regional Magnetic Field Model for Epoch 1995 for the dates of survey.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD ASSISTANTS

NAMES	CAPACITY
Daniel L. Maxey	Cadastral Surveyor
William F. Olver	Cadastral Surveyor
Daniel Bryan	Engineering Technician
Wilfred Chee	Engineering Technician
Edward Clarke	Engineering Technician
Reuben Mason	Engineering Technician
Barney Woodie	Engineering Technician



CERTIFICATE OF SURVEY

I, Jones Curtiss, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 17th day of February 1998, I have surveyed the Sixth Guide Meridian East, (west boundary), the east and north boundaries, and the subdivisional lines, Township 35 North, Range 25 East, of the Gila and Salt River Meridian, in the state of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

January 2, 2001  
(Date)

Jones Curtiss  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Arizona State Office  
Phoenix, Arizona

The foregoing field notes of the survey of the Sixth Guide Meridian East, (west boundary), the east and north boundaries, and the subdivisional lines, Township 35 North, Range 25 East, Gila and Salt River Meridian, Arizona, executed by Jones Curtiss, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

January 30, 2001  
(Date)

Kenny H. Ravnikar  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 35 N., R. 25 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~\_\_\_\_\_  
(Date)~~

~~\_\_\_\_\_  
(Chief Cadastral Surveyor of Arizona)~~