

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE

SURVEY

OF

THE EAST AND

NORTH BOUNDARIES,

AND

THE SUBDIVISIONAL LINES,

TOWNSHIP 35 NORTH, RANGE 26 EAST,

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Jones Curtiss, Cadastral Surveyor

Under Special Instructions dated and approved February 17, 1998, which provided for the surveys included under Group Number 822 and assignment instructions dated February 17, 1998.

Survey Commenced April 14, 1999

Survey Completed June 22, 1999

INDEX DIAGRAM

TOWNSHIP 35 NORTH, RANGE 26 EAST,

GILA AND SALT RIVER MERIDIAN, ARIZONA

14 6 57	13 5 45	12 4 37	11 3 29	10 2 22	9 1 8
56 7 55	56 8 44	45 9 36	37 10 28	29 11 21	21 12 7
54 18 53	54 17 42	43 16 35	35 15 27	28 14 19	20 13 6
52 19 50	51 20 41	42 21 33	34 22 25	26 23 18	18 24 5
49 30 48	49 29 40	40 28 32	33 27 24	25 26 16	17 25 4
47 31 46	47 32 38	39 33 30	31 34 23	24 35 15	16 36 4

T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of the east and north boundaries, and the subdivisional lines, Township 35 North, Range 26 East, Gila and Salt River Meridian, Arizona.

The south boundary was surveyed by Jones Curtiss and Leonard R. Sandoval concurrently under this same group. The west boundary was surveyed by Jones Curtiss concurrently under this same group.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated February 17, 1998, for Group No. 822, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic and static global positioning system observations using Trimble 4400 and 4700 model receivers.

Geodetic control was derived from first order U.S. Coast and Geodetic Survey triangulation stations "BEAUTIFUL 1951" and "LOHALI 1951", as published by the National Geodetic Survey, NAD83(1992). The geographic position of the southeast corner of the township is as follows:

Latitude: 36°23'22.58" N. Longitude: 109°29'15.88" W.

The mean magnetic declination is 12 1/4° E.

Survey of the East Boundary,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Beginning at the cor. of Tps. 34 and 35 N., Rs. 26 and 27 E., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the survey of the east boundary, T. 34 N., R. 26 E., executed concurrently under this same group.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R26E R27E 1/4 S36 S31 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R26E R27E S25 S30 ----- S36 S31 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, scattered juniper; undergrowth, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 25 and 30.</p> <p>Over rolling land.</p>

Survey of the East Boundary,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
14.90	Apache County Road C492, a graded road, 20 ft. wide, bears SE and NW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R26E R27E 1/4 S25 S30 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located on S. edge of a trail road, bears ENE and WSW.</p>
80.00	<p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R26E R27E S24 S19 ----- S25 S30 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, scattered juniper; undergrowth, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 19 and 24.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the East Boundary,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p style="text-align: center;">T35N R26E R27E 1/4 S24 S19 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E R27E S13 S18 ----- S24 S19 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>
40.00	<p>North, bet. secs. 13 and 18.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
80.00	<p style="text-align: center;">T35N R26E R27E 1/4 S13 S18 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 7, 12, 13, and 18.</p>

Survey of the East Boundary,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T35N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S13</td><td style="text-align: center;">S18</td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>	T35N		R26E	R27E	S12	S 7	-----		S13	S18	1999	
T35N													
R26E	R27E												
S12	S 7												

S13	S18												
1999													
	<p>North, bet. secs. 7 and 12.</p>												
	<p>Over rolling land.</p>												
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p>												
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T35N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table>	T35N		R26E	R27E	1/4		S12	S 7	1999			
T35N													
R26E	R27E												
1/4													
S12	S 7												
1999													
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>												
63.00	<p>Navajo Route 171, a graded road, 20 ft. wide, bears NE and SW.</p>												
80.00	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p>												
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T35N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table>	T35N		R26E	R27E	S 1	S 6	-----		S12	S 7	1999	
T35N													
R26E	R27E												
S 1	S 6												

S12	S 7												
1999													

Survey of the East Boundary,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS															
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>														
	<p>North, bet. secs. 1 and 6.</p> <p>Over gently rolling land.</p>														
14.10	Wash, 20 ft. wide, 3 ft. deep, drains E.														
	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>														
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T35N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table>	T35N		R26E	R27E	1/4		S 1	S 6	1999					
T35N															
R26E	R27E														
1/4															
S 1	S 6														
1999															
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>														
60.90	Agua Sal Wash, 95 ft. wide, 3 ft. deep, drains WSW.														
	<p>Point for the cor. of Tps. 35 and 36 N., Rs. 26 and 27 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>														
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T36N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td style="text-align: center;">S36</td><td style="text-align: center;">S31</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td colspan="2" style="text-align: center;">T35N</td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table>	T36N		R26E	R27E	S36	S31	-----		S 1	S 6	T35N		1999	
T36N															
R26E	R27E														
S36	S31														

S 1	S 6														
T35N															
1999															
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>														

Survey of the East Boundary,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, gently rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p style="text-align: center;">Survey of the North Boundary, T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>West, bet. secs. 1 and 36.</p> <p>Over gently rolling land.</p>
6.90	<p>Agua Sal Wash, 60 ft. wide, 5 ft. deep, drains NNE.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E S36 1/4 — S 1 T35N 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 2.60 chs. E. of Apache County Road C492, a graded road, bears NNE and SSW.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E S35 S36 — — S 2 S 1 T35N 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the North Boundary,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, gently rolling. Soil, sand, clay and sandy clay. No timber; scattered brush and native grasses.</p> <hr/>
	<p>West, bet. secs. 2 and 35.</p> <p>Over rolling land.</p>
37.50	Power line, bears NE and SW.
39.58	SE right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 35.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R26E S35 1/4 — S 2 T35N 1999</p>
	from which
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 44°00' E., 19.7 ft. dist., with brass cap mkd. T35N R26E 1/4 S2 RM 19.7 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 45°00' W., 84.0 ft. dist., with brass cap mkd. T36N R26E 1/4 S35 RM 84.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post at the 1/4 sec. cor.
	Cor. is located 70 lks. E. of center of U. S. Highway 191, and 1.83 chs. E. of NW right-of-way fence, barbed wire, 5 strands, both bear NE and SW.
80.00	Point for the cor. of secs. 2, 3, 34, and 35.

Survey of the North Boundary,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E S34 S35 ----- S 3 S 2 T35N 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<hr/>
	<p>West, bet. secs. 3 and 34.</p>
	<p>Over rolling land.</p>
13.20	<p>Base of E. slope of a mesa, bears SSE and NNW; thence over broken land on ascent.</p>
26.90	<p>E. rim of a mesa, atop rock ledge, bears NNE and SSW; thence over nearly level land atop a mesa.</p>
30.10	<p>W. rim of a mesa, atop rock ledge, bears NNE and SSW; thence over broken land on descent.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in sandstone bedrock, supported in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E S34 1/4 — S 3 T35N 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the North Boundary,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
	<p>From this cor. point, third order U. S. Geological Survey triangulation station "HADES 2", bears S. 36°34.4' E., 12.427 chs. dist., monumented with a rebar, 5/8 in. diam., set 3 ins. below the surface of the ground, and referenced as described in the published recovery sheet.</p>												
45.40	<p>Base of W. slope of a mesa, bears ESE and WNW; thence over rolling land.</p>												
80.00	<p>Point for the cor. of secs. 3, 4, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, to bedrock, encircled with a collar of stone, with brass cap mkd.</p>												
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T36N R26E</td> </tr> <tr> <td style="text-align: center;">S33</td> <td style="text-align: center;">S34</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 4</td> <td style="text-align: center;">S 3</td> </tr> <tr> <td colspan="2" style="text-align: center;">T35N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1999</td> </tr> </table>	T36N R26E		S33	S34	-----		S 4	S 3	T35N		1999	
T36N R26E													
S33	S34												

S 4	S 3												
T35N													
1999													
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>												
	<p>Cor. is located on SE slope of a ridge.</p>												
	<p>Land, broken and rolling with nearly level mesa top. Soil, sandy and rocky clay, and sandstone outcrops. No timber; sparse brush and native grasses.</p>												
	<hr/>												
	<p>West, bet. secs. 4 and 33.</p>												
	<p>Over rolling and broken land.</p>												
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>												
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T36N R26E</td> </tr> <tr> <td colspan="2" style="text-align: center;">S33</td> </tr> <tr> <td style="text-align: center;">1/4</td> <td style="text-align: center;">---</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 4</td> </tr> <tr> <td colspan="2" style="text-align: center;">T35N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1999</td> </tr> </table>	T36N R26E		S33		1/4	---	S 4		T35N		1999	
T36N R26E													
S33													
1/4	---												
S 4													
T35N													
1999													

Survey of the North Boundary,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS													
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on E. slope of a ridge.</p> <p>Point for the cor. of secs. 4, 5, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T36N</td><td>R26E</td></tr> <tr><td>S32</td><td>S33</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td colspan="2">T35N</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, broken and rolling. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p>	T36N	R26E	S32	S33	<hr/>		S 5	S 4	T35N		1999	
T36N	R26E												
S32	S33												
<hr/>													
S 5	S 4												
T35N													
1999													
40.00	<p>West, bet. secs. 5 and 32.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T36N</td><td>R26E</td></tr> <tr><td colspan="2">S32</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td colspan="2">S 5</td></tr> <tr><td colspan="2">T35N</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div>	T36N	R26E	S32		1/4	—	S 5		T35N		1999	
T36N	R26E												
S32													
1/4	—												
S 5													
T35N													
1999													
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 5, 6, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>												

Survey of the North Boundary,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<div style="text-align: center;"> T36N R26E S31 S32 ———— S 6 S 5 T35N 1999 </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p> <hr/> <p>West, bet. secs. 6 and 31.</p> <p>Over rolling and broken land.</p>
5.50	Base of E. slope of a ridge, bears N. and S.; thence over broken land over ridge.
31.20	Bottom of W. slope of a ridge, bears NE and SW; thence over nearly level land.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T36N R26E S31 1/4 ——— S 6 T35N 1999 </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
48.30	Chinle Wash, 30 ft. wide, 3 ft. deep, drains NW.
78.40	The cor. of Tps. 35 and 36 N., Rs. 25 and 26 E., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 35 N., R. 25 E., executed concurrently under this same group.

Survey of the North Boundary,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located 2.10 chs. N. of a trail road, bears ESE and WNW; and 2.30 chs. E. of another trail road, bears N. and S.</p> <p>Land, rolling and broken to nearly level. Soil, sandy and rocky clay. Timber, cottonwood, Russian olive and saltcedar near Chinle Wash; undergrowth, sparse brush and native grasses.</p> <hr/> <p style="text-align: center;">Survey of the Subdivisional Lines, T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 34 N., R. 26 E., executed concurrently under this same group.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E 1/4 S35 S36 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 90 lks. S. of a trail road, bears NE and SW.</p>
80.00	<p>Point for the cor. of secs. 25, 26, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S26 S25 ----- S35 S36 1999</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 25 and 36.</p> <p>Over rolling land.</p>
36.25	Trail road, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 36.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S25 1/4 — S36 1999</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 25, 26, 35, and 36.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
40.00	<p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p style="text-align: center;">T35N R26E 1/4 S26 S25 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 23, 24, 25, and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S23 S24 ----- S26 S25 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 24 and 25.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
43.60	<p style="text-align: center;">T35N R26E S24 1/4 — S25 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Apache County Road C492, a graded road, 22 ft. wide, bears SE and NW.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 23, 24, 25, and 26.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, scattered juniper; undergrowth, scattered brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 23 and 24.</p>
	<p>Over rolling land.</p>
33.40	<p>Apache County Road C492, a graded road, 20 ft. wide, bears SSE and NNW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R26E 1/4 S23 S24 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 13, 14, 23, and 24.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R26E S14 S13 ----- S23 S24 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Cor. is located near top of W. slope of a hill.</p>
	<p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 13 and 24.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S13 1/4 — S24 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 13, 14, 23, and 24.</p> <p>Land, rolling. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p>
40.00	<p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E 1/4 S14 S13 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 1.60 chs. S. of a power line, bears ESE and WNW.</p>
63.50	<p>Apache County Road C492, a graded road, 15 ft. wide, bears NNE and SSW.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Point for the cor. of secs. 11, 12, 13, and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T35N R26E</td></tr> <tr><td>S11</td><td>S12</td></tr> <tr><td colspan="2">—</td></tr> <tr><td>S14</td><td>S13</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 12 and 13.</p> <p>Over rolling land.</p>	T35N R26E		S11	S12	—		S14	S13	1999	
T35N R26E											
S11	S12										
—											
S14	S13										
1999											
40.00	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T35N R26E</td></tr> <tr><td colspan="2">S12</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td colspan="2">S13</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located atop a bare clay ridge, bears E. and W.</p>	T35N R26E		S12		1/4	—	S13		1999	
T35N R26E											
S12											
1/4	—										
S13											
1999											
72.20	<p>Apache County Road C492, a graded road, 18 ft. wide, bears NNE and SSW.</p>										
80.00	<p>The cor. of secs. 11, 12, 13, and 14.</p>										

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 11 and 12.</p>
	<p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R26E 1/4 S11 S12 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Cor. is located on the S. slope of a bare clay hill.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11, and 12.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R26E S 2 S 1 ----- S11 S12 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p>
	<p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>West, bet. secs. 1 and 12.</p>
	<p>Over rolling land.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
9.90	Wash, 25 ft. wide, 3 ft. deep, drains NNW.
18.80	Navajo Route 171, a graded road, 20 ft. wide, bears NNW and SSE.
31.20	Apache County Road C492, a graded road, 20 ft. wide, bears NNE and SSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S 1 1/4 — S12 1999</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Thence over rolling and broken land.</p> <p>The cor. of secs. 1, 2, 11, and 12.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>
40.00	<p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E 1/4 S 2 S 1 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on N. slope of a hill.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 34 N., R. 26 E., executed concurrently under this same group.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E 1/4 S34 S35 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 26, 27, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S27 S26 ----- S34 S35 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>West, bet. secs. 26 and 35.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S26 1/4 — S35 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 26, 27, 34, and 35.</p> <p>Land, rolling. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E 1/4 S27 S26 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 22, 23, 26, and 27.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T35N</td><td>R26E</td></tr> <tr><td>S22</td><td>S23</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S27</td><td>S26</td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>	T35N	R26E	S22	S23			S27	S26	1999	
T35N	R26E										
S22	S23										
S27	S26										
1999											
40.00	<p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>West, bet. secs. 23 and 26.</p> <p>Over rolling land.</p>										
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T35N</td><td>R26E</td></tr> <tr><td></td><td>S23</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S26</td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T35N	R26E		S23	1/4	—		S26	1999	
T35N	R26E										
	S23										
1/4	—										
	S26										
1999											
80.00	<p>The cor. of secs. 22, 23, 26, and 27.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>										
40.00	<p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p>										

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E 1/4 S22 S23 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22, and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S15 S14 ----- S22 S23 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on N. slope of a small clay ridge.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p>
	<hr/> <p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>West, bet. secs. 14 and 23.</p> <p>Over rolling land.</p>
17.00	<p>Apache County Road C492, a graded road, 20 ft. wide, bears N. and S.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T35N R26E S14 1/4 — S23 1999</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 14, 15, 22, and 23.</p> <p>Land, rolling. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p>
	<p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R26E 1/4 S15 S14 1999</p>
72.70	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located atop a small clay hill.</p> <p>Apache County Road C590, a graded road, 20 ft. wide, bears ESE and WNW.</p>
80.00	<p>Point for the cor. of secs. 10, 11, 14, and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R26E S10 S11 — — S15 S14 1999</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p>
40.00	<p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>West, bet. secs. 11 and 14.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S11 1/4 — S14 1999</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 10, 11, 14, and 15.</p> <p>Land, rolling. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p>
40.00	<p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E 1/4 S10 S11 1999</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 2, 3, 10, and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T35N</td><td>R26E</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td>S10</td><td>S11</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p>	T35N	R26E	S 3	S 2	S10	S11	1999			
T35N	R26E										
S 3	S 2										
S10	S11										
1999											
40.00	<p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>West, bet. secs. 2 and 11.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T35N</td><td>R26E</td></tr> <tr><td>S 2</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S11</td><td></td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T35N	R26E	S 2		1/4	—	S11		1999	
T35N	R26E										
S 2											
1/4	—										
S11											
1999											
80.00	<p>The cor. of secs. 2, 3, 10, and 11.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <p>N. 0°01' W., bet. secs. 2 and 3.</p>										

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
39.70	Power line, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T35N R26E 1/4 S 3 S 2 1999</p>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
44.92	S. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
45.83	Center of U. S. Highway 191, asphalt pavement, 25 ft. wide, bears ENE in curve to left.
46.64	N. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
80.00	The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., hereinbefore described,
	<p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>
	<p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 34 N., R. 26 E., executed concurrently under this same group.</p>
	N. 0°02' W., bet. secs. 33 and 34.
	Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 33 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p style="text-align: center;">T35N R26E 1/4 S33 S34 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 27, 28, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S28 S27 ----- S33 S34 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p>
40.00	<p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>West, bet. secs. 27 and 34.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S27 1/4 — S34 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 1.72 chs. E. of a barbed wire fence, 5 strands, bears NNE and SSW.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 27, 28, 33, and 34.</p> <p>Land, rolling. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over rolling and broken land.</p>
8.50	White Water Wash, 20 ft. wide, 5 ft. deep, drains WNW.
18.00	Base of S. slope of a mesa, bears NE and SW.
35.80	S. rim of a mesa, atop rock ledge, bears ESE and WNW; thence over rolling land atop mesa.
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E 1/4 S28 S27 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Thence gradually descend N. slope of a mesa.</p>
80.00	<p>Point for the cor. of secs. 21, 22, 27, and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S21 S22 ----- S28 S27 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27. West, bet. secs. 22 and 27. Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S22 1/4 — S27 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>The cor. of secs. 21, 22, 27, and 28. Land, rolling and broken. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22. Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E 1/4 S21 S22 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
70.80	<p>Wash, 30 ft. wide, 2 ft. deep, drains NW.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
74.30	Wash, 10 ft. wide, 1 ft. deep, drains WSW.										
80.00	<p>Point for the cor. of secs. 15, 16, 21, and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T35N</td><td>R26E</td></tr> <tr><td>S16</td><td>S15</td></tr> <tr><td>S21</td><td>S22</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p>	T35N	R26E	S16	S15	S21	S22	1999			
T35N	R26E										
S16	S15										
S21	S22										
1999											
40.00	<p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>West, bet. secs. 15 and 22.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T35N</td><td>R26E</td></tr> <tr><td colspan="2">S15</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td colspan="2">S22</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located at the base of a bare clay hill.</p>	T35N	R26E	S15		1/4	—	S22		1999	
T35N	R26E										
S15											
1/4	—										
S22											
1999											
80.00	The cor. of secs. 15, 16, 21, and 22.										

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken land. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p>
	<p>N. 0°02' W., bet. secs. 15 and 16.</p>
	<p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R26E 1/4 S16 S15 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 9, 10, 15, and 16.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R26E S 9 S10 ----- S16 S15 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Cor. is located on the NE edge of a wash, 3 ft. wide, 1 ft. deep, drains NW.</p>
	<p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p>
	<p>From the cor. of secs. 10, 11, 14, and 15.</p>
	<p>West, bet. secs. 10 and 15.</p>
	<p>Over rolling land.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
11.30	Apache County Road C590, a graded road, 20 ft. wide, bears N. and S.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 15.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T35N R26E S10 1/4 — S15 1999
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
80.00	The cor. of secs. 9, 10, 15, and 16.
	Land, rolling. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.
	N. 0°02' W., bet. secs. 9 and 10.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35N R26E 1/4 S 9 S10 1999
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
54.80	Power line, bears NE and SW.
63.30	Red Water Wash, 20 ft. wide, 3 ft. deep, drains W.
80.00	Point for the cor. of secs. 3, 4, 9, and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T35N R26E</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td colspan="2">—</td></tr> <tr><td>S 9</td><td>S10</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 10, and 11. West, bet. secs. 3 and 10. Over rolling land.</p>	T35N R26E		S 4	S 3	—		S 9	S10	1999	
T35N R26E											
S 4	S 3										
—											
S 9	S10										
1999											
3.90	Apache County Road C590, a graded road, 20 ft. wide, bears N. and S.										
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T35N R26E</td></tr> <tr><td colspan="2">S 3</td></tr> <tr><td colspan="2">1/4 —</td></tr> <tr><td colspan="2">S10</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 1.30 chs. E. of a trail road, bears NNE and SSW.</p>	T35N R26E		S 3		1/4 —		S10		1999	
T35N R26E											
S 3											
1/4 —											
S10											
1999											
48.30	Power line, bears NE and SW.										
80.00	<p>The cor. of secs. 3, 4, 9, and 10.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 3 and 4.</p>										

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
33.95	S. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
35.85	Center of U. S. Highway 191, asphalt pavement, 25 ft. wide, bears E. and W.
37.75	N. right-of-way fence of Arizona State Highway 191, barbed wire, 5 strands, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T35N R26E 1/4 S 4 S 3 1999</div> Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post. Thence ascend over rolling and broken land.
80.00	The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described. Land, rolling and broken. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.
	From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 34 N., R. 26 E., executed concurrently under this same group. N. 0°03' W., bet. secs. 32 and 33. Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T35N R26E 1/4 S32 S33 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
63.80	<p>White Water Wash, 20 ft. wide, 2 ft. deep, drains NW.</p>
80.00	<p>Point for the cor. of secs. 28, 29, 32, and 33.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R26E S29 S28 ----- S32 S33 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Cor. is located atop a rocky ridge, 25 lks. N. and 45 lks. E. of S. rim, ridge bears SE and NW.</p>
	<p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p>
	<hr/>
	<p>From the cor. of secs. 27, 28, 33, and 34.</p>
	<p>West, bet. secs. 28 and 33.</p>
	<p>Over rolling and broken land.</p>
36.00	<p>White Water Wash, 20 ft. wide, 1 ft. deep, drains WSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R26E S28 1/4 — S33 1999</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
80.00	The cor. of secs. 28, 29, 32, and 33. Land, rolling and broken. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.
	N. 0°03' W., bet. secs. 28 and 29. Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T35N R26E 1/4 S29 S28 1999 </div>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 20, 21, 28, and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T35N R26E S20 S21 ———— S29 S28 1999 </div>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post. Land, rolling and broken. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.
	From the cor. of secs. 21, 22, 27, and 28. West, bet. secs. 21 and 28.

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T35N R26E S21 1/4 — S28 1999</div>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
80.00	The cor. of secs. 20, 21, 28, and 29. Land, rolling. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.
	N. 0°03' W., bet. secs. 20 and 21.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T35N R26E 1/4 S20 S21 1999</div>
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
80.00	Point for the cor. of secs. 16, 17, 20, and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T35N R26E S17 S16 — — S20 S21 1999</div>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p>
	<p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>West, bet. secs. 16 and 21.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S16 1/4 — S21 1999</p>
71.70	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Wash, 60 ft. wide, 3 ft. deep, drains N.</p>
80.00	<p>The cor. of secs. 16, 17, 20, and 21.</p> <p>Land, rolling. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p>
	<p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over rolling land.</p>
11.50	<p>Wash, 55 ft. wide, 3 ft. deep, drains WNW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a magnet enclosed in a 1 x 1 x 2 ins. white plastic case, 24 ins. below the surface of the ground.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 80°00' E., 180.0 ft. dist., with brass cap mkd. T35N R26E 1/4 S16 RM 180.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 10°00' W., 160.0 ft. dist., with brass cap mkd. T35N R26E 1/4 S17 RM 160.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located in Red Water Wash, 60 ft. wide, 6 ft. deep; 30 lks. W. of left bank, and 2.00 chs. S. of right bank, drains SSW in curve to left.</p>										
57.30	Power line, bears NNE and SSW.										
80.00	Point for the cor. of secs. 8, 9, 16, and 17.										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table data-bbox="844 1144 998 1312" style="margin-left: auto; margin-right: auto;"> <tr> <td>T35N</td> <td>R26E</td> </tr> <tr> <td>S 8</td> <td>S 9</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S17</td> <td>S16</td> </tr> <tr> <td colspan="2" style="text-align: center;">1999</td> </tr> </table> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p>	T35N	R26E	S 8	S 9			S17	S16	1999	
T35N	R26E										
S 8	S 9										
S17	S16										
1999											
	<p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>West, bet. secs. 9 and 16.</p> <p>Over rolling land.</p>										
40.00	Point for the 1/4 sec. cor. of secs. 9 and 16.										

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S 9 1/4 — S16 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
52.60	Red Water Wash, 70 ft. wide, 3 ft. deep, drains SSW.
68.20	Power line, bears NNE and SSW.
80.00	The cor. of secs. 8, 9, 16, and 17.
	<p>Land, rolling. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E 1/4 S 8 S 9 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 8, and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S 5 S 4 ----- S 8 S 9 1999</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p>
40.00	<p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S 4 1/4 — S 9 1999</p>
80.00	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 4, 5, 8, and 9.</p> <p>Land, rolling. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p>
40.00	<p>N. 0°03' W., bet. secs. 4 and 5.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E 1/4 S 5 S 4 1999</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
51.30	Center of U. S. Highway 191, asphalt pavement, 25 ft. wide, bears ESE in curve to right.
80.00	The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described.
	Land, rolling and broken. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.
	From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the survey of the north boundary, T. 34 N., R. 26 E., executed concurrently under this same group.
	N. 0°03' W., bet. secs. 31 and 32.
	Over rolling land.
18.15	Trail road, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T35N R26E 1/4 S31 S32 1999
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
51.85	Trail road, bears NE and SW.
77.40	White Water Wash, 70 ft. wide, 2 ft. deep, drains WNW.
80.00	Point for the cor. of secs. 29, 30, 31, and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T35N R26E S30 S29 ----- S31 S32 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>West, bet. secs. 29 and 32.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
80.00	<p style="text-align: center;">T35N R26E S29 1/4 — S32 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 29, 30, 31, and 32.</p> <p>Land, rolling. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p>
32.50	<p>West, bet. secs. 30 and 31.</p> <p>Over gently rolling land across flood plain of White Water Wash.</p> <p>Power line, bears NNE and SSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S30 1/4 — S31 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
71.80	<p>Chinle Wash, 200 ft. wide, 4 ft. deep, drains NNW.</p>
78.84	<p>The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, mkd. and witnessed as described in the field notes of the survey of the east boundary, T. 35 N., R. 25 E., executed concurrently under this same group.</p> <p>Cor. is located in the flood plain of Chinle Wash, 2.40 chs. N. of left bank of Chinle Wash, 1 ft. high, bears NNE and SSW.</p> <p>Land, gently rolling. Soil, sand and sandy clay. Timber, Russian olive and saltcedar near Chinle Wash; undergrowth, scattered brush and native grasses.</p>
40.00	<p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over gently rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E 1/4 S30 S29 1999</p>
62.70	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Power line, bears NNE and SSW.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS											
80.00	<p>Point for the cor. of secs. 19, 20, 29, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T35N</td><td>R26E</td></tr> <tr><td>S19</td><td>S20</td></tr> <tr><td>S30</td><td>S29</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p>	T35N	R26E	S19	S20	S30	S29	1999			
T35N	R26E										
S19	S20										
S30	S29										
1999											
40.00	<p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>West, bet. secs. 20 and 29.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T35N</td><td>R26E</td></tr> <tr><td colspan="2">S20</td></tr> <tr><td colspan="2">1/4 —</td></tr> <tr><td colspan="2">S29</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>	T35N	R26E	S20		1/4 —		S29		1999	
T35N	R26E										
S20											
1/4 —											
S29											
1999											
71.00	<p>Power line, bears NNE and SSW.</p>										
80.00	<p>The cor. of secs. 19, 20, 29, and 30.</p> <p>Land, rolling. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p> <p>West, bet. secs. 19 and 30.</p>										

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over gently rolling land.
24.35	Trail road, bears SSE and NNW.
26.60	White Water Wash, 30 ft. wide, 10 ft. deep, drains NNE.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T35N R26E S19 1/4 — S30 1999
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
68.40	Chinle Wash, 430 ft. wide, 2 ft. deep, drains N.
75.60	W. bank of flood plain of Chinle Wash, 8 ft. high, bears NE and SW.
78.76	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 35 N., R. 25 E., executed concurrently under this same group.
	Cor. is located 2.70 chs. N. of W. bank of flood plain of Chinle Wash, 10 ft. high, bears ENE and WSW; and 1.10 chs. E. and 1.20 chs. S. of a graded road, 20 ft. wide, bears NE and SW.
	Land, gently rolling. Soil, sand and sandy clay. Timber, cottonwood, Russian olive and saltcedar near Chinle Wash; undergrowth, scattered brush and native grasses.
	From the cor. of secs. 19, 20, 29, and 30.
	N. 0°03' W., bet. secs. 19 and 20.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 20.

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E 1/4 S19 S20 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
56.10	Red Water Wash, 120 ft. wide, 4 ft. deep, drains SW.
80.00	Point for the cor. of secs. 17, 18, 19, and 20.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S18 S17 ----- S19 S20 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p>
	<p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>West, bet. secs. 17 and 20.</p> <p>Over gently rolling land.</p>
24.30	Left bank of Red Water Wash, 3 ft. high, bears SSW in curve to right; thence along bed of Red Water Wash.
29.70	Power line, bears NNE and SSW.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 20.
	<p>Set a magnet enclosed in a 1 x 1 x 2 ins. white plastic case, 24 ins. below the surface of the ground.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 30°00' E., 300.0 ft. dist., with brass cap mkd. T35N R26E 1/4 S20 RM 300.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 35°00' W., 200.0 ft. dist., with brass cap mkd. T36N R26E 1/4 S20 RM 200.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on a low island in Red Water Wash, 1.60 chs. N. of left channel, 72 ft. wide, 2 ft. deep, drains WNW; and 90 lks. S. of right channel, 100 ft. wide, 2 ft. deep, drains WNW.</p>
50.80	Right bank of Red Water Wash, 2 ft. high, bears ENE and WSW; thence leave Red Water Wash.
80.00	<p>The cor. of secs. 17, 18, 19, and 20.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; sparse brush and native grasses.</p>
40.00	<p>West, bet. secs. 18 and 19.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor, of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S18 1/4 — S19 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
78.67	<p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 35 N., R. 25 E., executed concurrently under this same group.</p> <p>Land, rolling. Soil, sandy and rocky clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 17, 18, 19, and 20. N. 0°03' W., bet. secs. 17 and 18. Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E 1/4 S18 S17 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 7, 8, 17, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T35N R26E S 7 S 8 ----- S18 S17 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located near base of W. slope of Round Top Ridge.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p>
	<hr/>
	<p>From the cor. of secs. 8, 9, 16, and 17.</p>
	<p>West, bet. secs. 8 and 17.</p>
	<p>Over rolling land.</p>
35.40	<p>Base of E. slope of Round Top Ridge, bears NNE and SSW; thence over broken land on ascent.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R26E S 8 1/4 — S17 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
	<p>Cor. is located on steep E. slope of Round Top Ridge, bears N. and S.; thence over Round Top Ridge.</p>
80.00	<p>The cor. of secs. 7, 8, 17, and 18.</p>
	<p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p>
	<hr/>
	<p>West, bet. secs. 7 and 18.</p>
	<p>Over rolling land on descent into Chinle Valley.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T35N R26E S 7 1/4 — S18 1999
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
78.58	The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 35 N., R. 25 E., executed concurrently under this same group. Land, rolling. Soil, sandy and rocky clay. Timber, cottonwood, Russian olive and saltcedar at west end; undergrowth, scattered brush and native grasses.
	<hr/> From the cor. of secs. 7, 8, 17, and 18. N. 0°03' W., bet. secs. 7 and 8. Over rolling and broken land over spur ridge of Round Top Ridge.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T35N R26E 1/4 S 7 S 8 1999
	Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
47.60	Base of N. slope of spur ridge of Round Top Ridge, bears E. and W.; thence over rolling land.
80.00	Point for the cor. of secs. 5, 6, 7, and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T35N R26E S 6 S 5 ----- S 7 S 8 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p>
40.00	<p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>West, bet. secs. 5 and 8.</p> <p>Over rolling and broken land over Round Top Ridge.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p>
80.00	<p style="text-align: center;">T35N R26E S 5 1/4 — S 8 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 5, 6, 7, and 8.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.</p>
40.00	<p>West, bet. secs. 6 and 7.</p> <p>Over gently rolling land on descent into Chinle Valley.</p> <p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T35N R26E S 6 1/4 — S 7 1999</p>
	<p>Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.</p>
58.00	<p>Chinle Wash, 120 ft. wide, 5 ft. deep, drains NNE.</p>
78.49	<p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 35 N., R. 25 E., executed concurrently under this same group.</p> <p>Cor. is located in the flood plain of Chinle Wash, 65 lks. E. and 1.35 chs. S. of W. bank of flood plain, 6 ft. high, bears NNE and SSW.</p> <p>Land, gently rolling. Soil, sand and sandy clay. Timber, cottonwood, Russian olive and saltcedar near Chinle Wash; undergrowth, scattered brush and native grasses.</p>
	<p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over gently rolling land.</p>
22.86	<p>S. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.</p>
23.19	<p>A brass tablet, 3 ins. diam., set flush in a concrete collar, 6 ins. diam., firmly set, projecting 6 ins. above ground, bears East, 81 lks. dist., with top mkd. ARIZONA HIGHWAY DEPT. 1961; with an angle iron to the E., with marks 113+86.43 HWY RW visible on a face.</p>
24.91	<p>Center of U. S. Highway 191, asphalt pavement, 28 ft. wide, bears ENE in curve to left.</p>
26.69	<p>A brass tablet, 3 ins. diam., set flush in a concrete collar, 6 ins. diam., firmly set, projecting 6 ins. above ground, bears West, 61 1/2 lks. dist., with top mkd. ARIZONA HIGHWAY DEPT. 1961; with an angle iron to the E., with marks 113+86.43 visible on a face.</p>

Survey of the Subdivisional Lines,
T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
26.94	N. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 6. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. T35N R26E 1/4 S 6 S 5 1999 Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post.
62.80	Base of S. slope of a ridge, bears E. and W.; thence over broken land over ridge.
72.30	Base of N. slope of a ridge, bears NE and SW; thence over rolling land.
80.00	The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., hereinbefore described. Land, rolling and broken. Soil, sandy and rocky clay. No timber; sparse brush and native grasses.

T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>The area surveyed is within the Navajo Indian Reservation, approximately six miles northeast of the community of Many Farms, Arizona and six miles southwest of the community of Round Rock. The extreme western portion of the township is in Chinle Valley. The central portion of the township is primarily clay badlands dominated by Round Top Ridge, which extends from section 4 southwesterly into section 17. Red Water Wash and White Water Wash drain westerly into Chinle Wash, which drains northerly along the west boundary of the township. Drainage in the northeastern portion of the township is northeasterly into Agua Sal Wash, which drains northerly through section 1.</p> <p>The elevation varies from 5200 to 5800 feet above sea level. The soil is mostly sandy and rocky clay. The only significant timber, which is cottonwood, Russian olive and saltcedar, is in the flood plains of Chinle Wash and Agua Sal Wash. The majority of the township is vegetated with sparse or scattered brush and native grasses.</p> <p>Principal access to the township is provided by U. S. Highway 191, which enters the township in section 6 and exits in section 2. There are three major graded roads and numerous trail roads providing additional access. Much of the area is used for grazing livestock. There is no mining activity in the township.</p> <p>The mean magnetic declination is $12 \frac{1}{4}^{\circ}$ E., as derived from the United States Geological Survey computer program GEOMAGIX utilizing the Regional Magnetic Field Model for Epoch 1995 for the dates of survey.</p> <hr/>
--------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
William F. Olver	Cadastral Surveyor
Daniel Bryan	Engineering Technician
Wilfred Chee	Engineering Technician
Edward Clarke	Engineering Technician
Reuben Mason	Engineering Technician
Barney Woodie	Engineering Technician

CERTIFICATE OF SURVEY

I, Jones Curtiss, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 17th day of February 1998, I have surveyed the east and north boundaries, and the subdivisional lines, Township 35 North, Range 26 East, of the Gila and Salt River Meridian, in the state of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

January 31, 2001
(Date)

Jones Curtiss
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the survey of the east and north boundaries, and the subdivisional lines, Township 35 North, Range 26 East, Gila and Salt River Meridian, Arizona, executed by Jones Curtiss, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

February 20, 2001
(Date)

Terry D. Rowntree
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 35 N., R. 26 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~