

ORIGINAL

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE

SURVEY OF

THE

EAST

BOUNDARY

AND

THE SUBDIVISIONAL LINES,

TOWNSHIP 36 NORTH, RANGE 26 EAST,

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Leonard R. Sandoval, Cadastral Surveyor

Under Special Instructions dated and approved February 17, 1998, which provided for the surveys included under Group Number 822 and assignment instructions dated February 17, 1998.

Survey Commenced June 22, 1999

Survey Completed July 29, 1999

INDEX DIAGRAM

TOWNSHIP 36 NORTH, RANGE 26 EAST,

GILA AND SALT RIVER MERIDIAN, ARIZONA

| 31 | | 32 | | 33 | | 34 | | 35 | | 36 | |
|----|----|----|----|----|----|----|----|----|----|----|----|
| 64 | | 63 | | 50 | | 41 | | 30 | | 20 | |
| 6 | 62 | 5 | 49 | 4 | 39 | 3 | 29 | 2 | 19 | 1 | 10 |
| 61 | | 61 | | 49 | | 38 | | 28 | | 18 | |
| 7 | 60 | 8 | 48 | 9 | 37 | 10 | 27 | 11 | 18 | 12 | 9 |
| 59 | | 59 | | 47 | | 37 | | 26 | | 17 | |
| 18 | 58 | 17 | 46 | 16 | 36 | 15 | 25 | 14 | 16 | 13 | 8 |
| 57 | | 56 | | 46 | | 35 | | 24 | | 15 | |
| 19 | 55 | 20 | 45 | 21 | 34 | 22 | 24 | 23 | 14 | 24 | 6 |
| 55 | | 54 | | 44 | | 34 | | 23 | | 14 | |
| 30 | 53 | 29 | 43 | 28 | 33 | 27 | 22 | 26 | 13 | 25 | 5 |
| 52 | | 52 | | 42 | | 32 | | 22 | | 12 | |
| 31 | 51 | 32 | 42 | 33 | 31 | 34 | 21 | 35 | 11 | 36 | 4 |

T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of the east boundary and the subdivisional lines, Township 36 North, Range 26 East, Gila and Salt River Meridian, Arizona.

The Ninth Standard Parallel North, (south boundary), Township 37 North, Range 25 East, was surveyed by Jones Curtiss in 1999 under this same group. The Ninth Standard Parallel North, (south boundary), Township 37 North, Range 26 East, was surveyed by Leonard R. Sandoval in 1999 under this same group. The south and west boundaries of the township were surveyed by Jones Curtiss concurrently under this same group.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated February 17, 1998, for Group No. 822, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic and static global positioning system observations using Trimble 4400 and 4700 model receivers.

Geodetic control was derived from first order U. S. Coast and Geodetic Survey triangulation stations "BEAUTIFUL 1951" and "LOHALI 1951", as published by the National Geodetic Survey, NAD83(1992). The geographic position of the southeast corner of the township is as follows:

Latitude: 36°28'35.76" N. Longitude: 109°29'15.88" W.

The mean magnetic declination is 12 1/4° E.

Survey of the East Boundary,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | Beginning at the cor. of Tps. 35 and 36 N., Rs. 26 and 27 E., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 35 N., R. 26 E., executed concurrently under this same group. |
| | North, bet. secs. 31 and 36. |
| | Over nearly level land in flood plain of Agua Sal Wash. |
| 6.20 | Agua Sal Wash, 55 ft. wide, 4 ft. deep, drains NE. |
| 17.10 | Agua Sal Wash, 40 ft. wide, 5 ft. deep, drains NW. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 31 and 36. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T36N R26E R27E 1/4 S36 S31 1999 |
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. |
| | Cor. is located 1.70 chs. E. and 2.20 chs. S. of Agua Sal Wash, 60 ft. wide, 4 ft. deep, drains NE. |
| 49.30 | Agua Sal Wash, 60 ft. wide, 6 ft. deep, drains NW. |
| 74.90 | Agua Sal Wash, 60 ft. wide, 2 ft. deep, drains NNE in curve to left; thence along bed of Agua Sal Wash. |
| 79.70 | Power line, bears ENE and WSW. |
| 80.00 | Point for the cor. of secs. 25, 30, 31, and 36. |
| | Set a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case, 24 ins. below the surface of the ground. |

Survey of the East Boundary,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 50°00' E., 215.0 ft. dist., with brass cap mkd. T36N R27E S30 RM 215.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 40°00' E., 235.0 ft. dist., with brass cap mkd. T36N R27E S31 RM 235.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located in Agua Sal Wash, 60 ft. wide, 2 ft. deep, drains NNW, 15 lks. E. of the left bank.</p> <p>Land, nearly level. Soil, sand and sandy clay. Timber, cottonwood, Russian olive and saltcedar; undergrowth, brush and native grasses.</p> |
| | <p>North, bet. secs. 25 and 30.</p> <p>Over nearly level land in the bed of Agua Sal Wash.</p> |
| 3.50 | Right bank of Agua Sal Wash, 5 ft. high, bears SE and NW; thence over gently rolling land. |
| 29.60 | Graded road, 15 ft. wide, bears ESE and WNW. |
| 31.70 | Power line, bears NE and SW. |
| 33.11 | SE right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway. |
| 34.18 | Center of U. S. Highway 191, asphalt pavement, 27 ft. wide, bears NE and SW. |
| 35.23 | NW right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway. |
| 38.65 | The approximate SW bdy. of an undeveloped homesite, the southernmost cor. bears S. 44°31' E., 35 1/2 lks. dist., monumented with an uncapped rebar, 5/8 in. diam., set flush with the surface of the ground. |

Survey of the East Boundary,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T36N R26E R27E 1/4 S25 S30 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>From this cor. point, the easternmost cor. of an undeveloped homesite, bears N. 76°09' E., 2.58 chs. dist., monumented with a rebar, 5/8 in. diam., set flush with the surface of the ground, with red plastic cap mkd. ONLA.</p> |
| 42.59 | <p>The approximate NW bdy. of an undeveloped homesite, the northernmost cor. bears N. 45°29' E., 40 lks. dist., monumented with an uncapped rebar, 5/8 in. diam., set flush with the surface of the ground.</p> |
| 80.00 | <p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T36N R26E R27E S24 S19 ----- S25 S30 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, nearly level to gently rolling. Soil, sand and sandy and gravelly clay. Timber, cottonwood, Russian olive and saltcedar near Agua Sal Wash; undergrowth, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 19 and 24.</p> |

Survey of the East Boundary,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | | | | | |
|--------|---|------|--|------|------|-----|-----|-------|-----|------|-----|------|--|
| | Over gently rolling land. | | | | | | | | | | | | |
| 40.00 | Point for the 1/4 sec. cor. of secs. 19 and 24. | | | | | | | | | | | | |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. | | | | | | | | | | | | |
| | <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T36N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table> | T36N | | R26E | R27E | 1/4 | | S24 | S19 | 1999 | | | |
| T36N | | | | | | | | | | | | | |
| R26E | R27E | | | | | | | | | | | | |
| 1/4 | | | | | | | | | | | | | |
| S24 | S19 | | | | | | | | | | | | |
| 1999 | | | | | | | | | | | | | |
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. | | | | | | | | | | | | |
| | Cor. is located 2.95 chs. S. of a trail road, bears NE and SW. | | | | | | | | | | | | |
| 59.60 | Power line, bears SE and NW. | | | | | | | | | | | | |
| 70.47 | SW right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway. | | | | | | | | | | | | |
| 71.42 | Center of U. S. Highway 191, asphalt pavement, 27 ft. wide, bears SE and NW. | | | | | | | | | | | | |
| 72.40 | NE right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway. | | | | | | | | | | | | |
| 78.45 | Intersect the S. side of a wood sided house, 36 x 24 ft., the westernmost cor. bears WNW, 24 lks. dist., long side bears ESE and WNW. | | | | | | | | | | | | |
| 80.00 | Point for the cor. of secs. 13, 18, 19, and 24. | | | | | | | | | | | | |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set flush with the surface of the ground, with brass cap mkd. | | | | | | | | | | | | |
| | <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T36N</td></tr> <tr><td style="text-align: center;">R26E</td><td style="text-align: center;">R27E</td></tr> <tr><td style="text-align: center;">S13</td><td style="text-align: center;">S18</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table> | T36N | | R26E | R27E | S13 | S18 | ----- | | S24 | S19 | 1999 | |
| T36N | | | | | | | | | | | | | |
| R26E | R27E | | | | | | | | | | | | |
| S13 | S18 | | | | | | | | | | | | |
| ----- | | | | | | | | | | | | | |
| S24 | S19 | | | | | | | | | | | | |
| 1999 | | | | | | | | | | | | | |
| | from which | | | | | | | | | | | | |
| | <p style="text-align: center;">The northernmost cor. of a wood sided house, 36 x 24 ft., bears S. 1 1/2° W., 1.12 chs. dist., long side bears ESE.</p> | | | | | | | | | | | | |

Survey of the East Boundary,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>A steel manhole cover, 24 ins. diam., bears S. 41° W., 99 1/2 lks. dist., mkd. SEWER.</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p> |
| | <p>North, bet. secs. 13 and 18.</p> <p>Over gently rolling land.</p> |
| 12.20 | Underground sewer line, with a trail road on NE side, both bear SE and NW. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 13 and 18. |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E R27E 1/4 S13 S18 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 35 lks. S. and 50 lks. W. of a trail road, bears SE and NW; thence enter flood plain of Lukachukai Wash.</p> |
| 64.80 | Lukachukai Wash, 75 ft. wide, 4 ft. deep, drains WNW. |
| 80.00 | Point for the cor. of secs. 7, 12, 13, and 18. |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E R27E S12 S 7 ----- S13 S18 1999</p> |

Survey of the East Boundary,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sand and sandy and gravelly clay. Timber, scattered Russian olive and saltcedar near Lukachukai Wash; undergrowth, scattered brush and native grasses.</p> |
| | <p>North, bet. secs. 7 and 12.</p> <p>Over gently rolling land in a flood plain.</p> |
| 24.50 | Red Wash, 60 ft. wide, 3 ft. deep, drains NW. |
| 33.80 | Base of a mesa, bears E. and W.; thence over broken land on ascent of S. slope of a mesa. |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E R27E 1/4 S12 S 7 1999</p> |
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| 49.20 | S. rim of a mesa, bears ENE and WSW; thence over rolling and broken land on descent of N. slope of a mesa. |
| 80.00 | <p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E R27E S 1 S 6 ----- S12 S 7 1999</p> |
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |

Survey of the East Boundary,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Land, gently rolling to broken and rolling. Soil, sand, sandy and gravelly clay and sandstone outcrops. No timber; scattered brush and native grasses.</p> |
| | <p>North, bet. secs. 1 and 6.</p> |
| | <p>Over rolling and broken land on descent of N. slope of a mesa.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E R27E 1/4 S 1 S 6 1999</p> |
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| 72.30 | <p>S. rim of a canyon, bears E. and W.; thence over broken land on abrupt descent into a canyon.</p> |
| 79.86 | <p>True point for the closing cor. of Tps. 36 N., Rs. 26 and 27 E., at intersection with the Ninth Standard Parallel North, on the N. bdy. of the Tp.; the point falls on steep eroding slope, bears SSE and NNW, 60 lks. W. of a wash, 30 ft. wide, 5 ft. deep, drains NW, where it is impracticable to establish a monument.</p> |
| | <p>From this true cor. point, the point selected for the witness cor. to the closing cor. of Tps. 36 N., Rs. 26 and 27 E., bears S. 45°00' W., 0.305 ch. dist.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">WC ↗ T37N R26E S36 ----- S 1 S 6 R26E R27E T36N CC 1999</p> |

Survey of the East Boundary,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|---|---|
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>From this true cor. point, the stan. cor. of Tps. 37 N., Rs. 26 and 27 E., bears East, 29.93 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 26 E., executed under this same group.</p> <p>From this same true cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 37 N., R. 26 E., bears West, 10.07 chs. dist., monumented with a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case, set and witnessed as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 26 E., executed under this same group.</p> <p>Land, rolling and broken. Soil, sandy, gravelly and rocky clay. No timber; scattered brush and native grasses.</p> |
| <hr/> <p style="text-align: center;">Survey of the Subdivisional Lines, T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona</p> <hr/> | |
| | <p>From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 35 N., R. 26 E., executed concurrently under this same group.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over gently rolling land.</p> |
| 26.11 | The center of an octagonal stuccoed hogan, 20 ft. diam., bears West, 34 lks. dist. |
| 35.70 | Power line, bears NE and SW. |
| 37.42 | SE right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway. |
| 38.51 | Center of U. S. Highway 191, asphalt pavement, 27 ft. wide, bears NE and SW. |
| 39.56 | NW right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway. |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E 1/4 S35 S36 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| 80.00 | <p>Point for the cor. of secs. 25, 26, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E S26 S25 ----- S35 S36 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p> |
| | <p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.</p> |
| | <p>West, bet. secs. 25 and 36.</p> |
| | <p>Over rolling land.</p> |
| 33.40 | <p>Power line, bears NE and SW.</p> |
| 35.04 | <p>SE right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.</p> |
| 36.15 | <p>Center of U. S. Highway 191, asphalt pavement, 27 ft. wide, bears NE and SW.</p> |
| 37.28 | <p>NW right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E S25 1/4 — S36 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>From this cor. point, a third order U. S. Geological Survey benchmark, bears N. 43°17' W., 6.22 chs. dist., monumented with a standard brass tablet, 3 1/2 ins. diam., set flush in a concrete collar, 7 ins. diam., firmly set, projecting 18 ins. above ground, with top mkd. 31 D 1950.</p> |
| 80.00 | <p>The cor. of secs. 25, 26, 35, and 36.</p> <p>Land, rolling. Soil, sandy and rocky clay and sandstone outcrops. Timber, cottonwood, Russian olive and saltcedar at E. end; undergrowth, scattered brush and native grasses.</p> |
| | <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over nearly level land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E 1/4 S26 S25 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| 80.00 | <p>Point for the cor. of secs. 23, 24, 25, and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | | | |
|--------|--|------|------|-----|-----|-----|-----|------|--|------|--|
| | <div style="text-align: center;"> <table border="1"> <tr><td>T36N</td><td>R26E</td></tr> <tr><td>S23</td><td>S24</td></tr> <tr><td>S26</td><td>S25</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.</p> | T36N | R26E | S23 | S24 | S26 | S25 | 1999 | | | |
| T36N | R26E | | | | | | | | | | |
| S23 | S24 | | | | | | | | | | |
| S26 | S25 | | | | | | | | | | |
| 1999 | | | | | | | | | | | |
| | <hr/> <p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 24 and 25.</p> <p>Over gently rolling land.</p> | | | | | | | | | | |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> | | | | | | | | | | |
| | <div style="text-align: center;"> <table border="1"> <tr><td>T36N</td><td>R26E</td></tr> <tr><td>S24</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S25</td><td></td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> | T36N | R26E | S24 | | 1/4 | — | S25 | | 1999 | |
| T36N | R26E | | | | | | | | | | |
| S24 | | | | | | | | | | | |
| 1/4 | — | | | | | | | | | | |
| S25 | | | | | | | | | | | |
| 1999 | | | | | | | | | | | |
| 62.20 | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on E. edge of vegetated sand dunes.</p> <p>Agua Sal Wash, 80 ft. wide, 3 ft. deep, drains NNW.</p> | | | | | | | | | | |
| 80.00 | <p>The cor. of secs. 23, 24, 25, and 26.</p> <p>Land, gently rolling. Soil, sand and sandy clay. Timber, cottonwood, Russian olive and saltcedar near Agua Sal Wash; undergrowth, scattered brush and native grasses.</p> | | | | | | | | | | |
| | <hr/> <p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over gently rolling land.</p> | | | | | | | | | | |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 26.00 | Agua Sal Wash, 60 ft. wide, 2 ft. deep, drains WSW. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 23 and 24. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T36N R26E 1/4 S23 S24 1999</p> |
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. |
| | Cor. is located 3.10 chs. E. of Agua Sal Wash, 75 ft. wide, 2 ft. deep, drains N.; at foot of E. slope of vegetated sand dunes forming E. edge of Agua Sal Wash flood plain. |
| 80.00 | Point for the cor. of secs. 13, 14, 23, and 24. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, atop a steel fence post, with brass cap mkd. |
| | <p style="text-align: center;">T36N R26E S14 S13 ----- S23 S24 1999</p> |
| | Cor. is located atop a sparsely vegetated sand dune at E. edge of flood plain of Agua Sal Wash. |
| | <p>Land, gently rolling. Soil, sand and sandy clay. Timber, cottonwood, Russian olive and saltcedar near Agua Sal Wash; undergrowth, brush and native grasses.</p> |
| | From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described. |
| | West, bet. secs. 13 and 24. |
| | Over gently rolling land. |
| 9.81 | NE right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway. |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 11.02 | Center of U. S. Highway 191, asphalt pavement, 27 ft. wide, bears SE and NW. |
| 12.27 | SW right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway. |
| 25.60 | Power line, bears SE and NW. |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E S13 1/4 — S24 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| 80.00 | <p>The cor. of secs. 13, 14, 23, and 24.</p> <p>Land, gently rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses.</p> |
| | <p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over gently rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E 1/4 S14 S13 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| 43.40 | Power line, bears SE and NW. |
| 52.69 | SW right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway. |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | | | | | | | |
|--------|--|------|------|-----|--|-------|--|-----|--|------|--|-----|------|--|--|
| 53.65 | Center of U. S. Highway 191, asphalt pavement, 27 ft. wide, bears SE and NW. | | | | | | | | | | | | | | |
| 54.63 | NE right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway. | | | | | | | | | | | | | | |
| 80.00 | Point for the cor. of secs. 11, 12, 13, and 14. | | | | | | | | | | | | | | |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. | | | | | | | | | | | | | | |
| | <table border="0"> <tr><td>T36N</td><td>R26E</td></tr> <tr><td>S11</td><td> </td><td>S12</td></tr> <tr><td colspan="3" style="border-top: 1px solid black;"></td></tr> <tr><td>S14</td><td> </td><td>S13</td></tr> <tr><td colspan="3" style="text-align: center;">1999</td></tr> </table> | T36N | R26E | S11 | | S12 | | | | S14 | | S13 | 1999 | | |
| T36N | R26E | | | | | | | | | | | | | | |
| S11 | | S12 | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| S14 | | S13 | | | | | | | | | | | | | |
| 1999 | | | | | | | | | | | | | | | |
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. | | | | | | | | | | | | | | |
| | Land, gently rolling. Soil, sand and sandy clay. No timber; scattered brush and native grasses. | | | | | | | | | | | | | | |
| | From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described. | | | | | | | | | | | | | | |
| | West, bet. secs. 12 and 13. | | | | | | | | | | | | | | |
| | Over gently rolling land across a flood plain. | | | | | | | | | | | | | | |
| 27.10 | Lukachukai Wash, 105 ft. wide, 2 ft. deep, drains WNW; thence leave a flood plain. | | | | | | | | | | | | | | |
| 40.00 | Point for the 1/4 sec. cor. of secs. 12 and 13. | | | | | | | | | | | | | | |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. | | | | | | | | | | | | | | |
| | <table border="0"> <tr><td>T36N</td><td>R26E</td></tr> <tr><td colspan="2" style="text-align: center;">S12</td></tr> <tr><td colspan="2" style="text-align: center;">1/4 —</td></tr> <tr><td colspan="2" style="text-align: center;">S13</td></tr> <tr><td colspan="2" style="text-align: center;">1999</td></tr> </table> | T36N | R26E | S12 | | 1/4 — | | S13 | | 1999 | | | | | |
| T36N | R26E | | | | | | | | | | | | | | |
| S12 | | | | | | | | | | | | | | | |
| 1/4 — | | | | | | | | | | | | | | | |
| S13 | | | | | | | | | | | | | | | |
| 1999 | | | | | | | | | | | | | | | |
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. | | | | | | | | | | | | | | |
| 80.00 | The cor. of secs. 11, 12, 13, and 14. | | | | | | | | | | | | | | |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>Land, gently rolling. Soil, sand and sandy and gravelly clay. Timber, cottonwood, Russian olive and saltcedar in flood plain; undergrowth, scattered brush and native grasses.</p> |
| | <p>N. 0°01' W., bet. secs. 11 and 12.</p> |
| | <p>Over nearly level land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E 1/4 S11 S12 1999</p> |
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| 49.30 | <p>Lukachukai Wash, 150 ft. wide, 2 ft. deep, drains W.; thence over rolling land on ascent from valley.</p> |
| 80.00 | <p>Point for the cor. of secs. 1, 2, 11, and 12.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E S 2 S 1 ----- S11 S12 1999</p> |
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| | <p>Cor. is located atop a ridge sloping SW, on S. slope of a mesa.</p> |
| | <p>Land, nearly level to rolling. Soil, sand and sandy, gravelly and rocky clay. Timber, cottonwood, Russian olive and saltcedar near Lukachukai Wash; undergrowth, scattered brush and native grasses.</p> |
| | <p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 40.00 | <p>West, bet. secs. 1 and 12.</p> <p>Over rolling and broken land on ascent of NE slope of a mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E S 1 1/4 — S12 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| 80.00 | <p>Cor. is located 2.50 chs. E. of SW rim of a mesa, bears SE and NW; thence over broken land on descent across S. slope of a mesa.</p> <p>The cor. of secs. 1, 2, 11, and 12.</p> <p>Land, rolling and broken. Soil, sandy, gravelly and rocky clay and sandstone outcrops. No timber; scattered brush and native grasses.</p> |
| 8.40 | <p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Over rolling and broken land on abrupt ascent of S. slope of a mesa.</p> <p>S. rim of spur ridge of a mesa, bears E. and W.</p> |
| 12.70 | <p>N. rim of same spur ridge, bears ENE and WSW; thence over broken land on descent from a spur ridge.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E 1/4 S 2 S 1 1999</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| | <p>Cor. is located on W. slope of a mesa, near base; thence over broken land on ascent of W. slope of spur ridge of a mesa.</p> |
| 48.40 | <p>SW rim of spur ridge of a mesa, bears SE and NW; thence over rolling land atop a spur ridge.</p> |
| 62.95 | <p>S. rim of a canyon, bears E. and W.; thence over broken land on descent into a canyon.</p> |
| 79.85 | <p>Point for the closing cor. of secs. 1 and 2, at intersection with the Ninth Standard Parallel North, on the N. bdy. of the Tp.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T37N R26E S35 ----- S 2 S 1 T36N R26E CC 1999</p> |
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| | <p>From this cor. point, the stan. cor. of secs. 35 and 36, T. 37 N., R. 26 E., bears East, 29.93 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 26 E., executed under this same group.</p> |
| | <p>From this same cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 37 N., R. 26 E., bears West, 10.07 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 26 E., executed under this same group.</p> |
| | <p>Land, rolling and broken. Soil, sandy, gravelly and rocky clay and sandstone outcrops. No timber; scattered brush and native grasses.</p> |
| | <p>Point for the 1/4 sec. cor. of sec. 1 only, T. 36 N., R. 26 E., at midpoint on the N. bdy. of sec. 1.</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T37N R26E</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1/4 S 1 T36N R26E 1999</p> |
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. |
| | From this cor. point, the stan. 1/4 sec. cor. of sec. 36, T. 37 N., R. 26 E., bears East, 29.93 chs. dist., hereinbefore described. |
| | From this same cor. point, the stan. cor. of secs. 35 and 36, T. 37 N., R. 26 E., bears West, 10.07 chs. dist. |
| | From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 35 N., R. 26 E., executed concurrently under this same group. |
| | N. 0°01' W., bet. secs. 34 and 35. |
| | Over rolling land. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 34 and 35. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T36N R26E</p> <p style="text-align: center;">1/4</p> <p style="text-align: center;">S34 S35</p> <p style="text-align: center;">1999</p> |
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. |
| 80.00 | Point for the cor. of secs. 26, 27, 34, and 35. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p style="text-align: center;">T36N R26E S27 S26 ----- S34 S35 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p> <hr/> |
| 40.00 | <p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>West, bet. secs. 26 and 35.</p> <p>Over gently rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> |
| 80.00 | <p style="text-align: center;">T36N R26E S26 1/4 — S35 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 26, 27, 34, and 35.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> |
| 40.00 | <p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over rolling and broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p style="text-align: center;">T36N R26E 1/4 S27 S26 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| 80.00 | <p>Point for the cor. of secs. 22, 23, 26, and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E S22 S23 ----- S27 S26 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy clay. No timber; scattered brush and native grasses.</p> |
| | <p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>West, bet. secs. 23 and 26.</p> <p>Over gently rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E S23 1/4 — S26 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| 80.00 | <p>The cor. of secs. 22, 23, 26, and 27.</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>Land, gently rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> |
| | <p>N. 0°01' W., bet. secs. 22 and 23.</p> |
| | <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E 1/4 S22 S23 1999</p> |
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| 80.00 | <p>Point for the cor. of secs. 14, 15, 22, and 23.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E S15 S14 ----- S22 S23 1999</p> |
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| | <p>Land, rolling. Soil, sandy clay. No timber, scattered brush and native grasses.</p> <hr/> |
| | <p>From the cor. of secs. 13, 14, 23, and 24.</p> |
| | <p>West, bet. secs. 14 and 23.</p> |
| | <p>Over gently rolling land.</p> |
| 8.70 | <p>Agua Sal Wash, 160 ft. wide, 1 ft. deep, drains N.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 7 ins. below the surface of the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E S14 1/4 — S23 1999</p> |
| | <p>from which</p> |
| | <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45°00' E., 100.0 ft. dist., with brass cap mkd. T36N R26E 1/4 S14 RM 100.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| | <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45°00' W., 50.0 ft. dist., with brass cap mkd. T36N R26E 1/4 S23 RM 50.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post at the 1/4 sec. cor.</p> |
| | <p>Cor. is located 50 lks. W. of center of Apache County Road C495, a graded road, 20 ft. wide, bears SE in curve to left.</p> |
| 80.00 | <p>The cor. of secs. 14, 15, 22, and 23.</p> |
| | <p>Land, gently rolling. Soil, sand and sandy clay. Timber, scattered Russian olive and saltcedar near Agua Sal Wash; undergrowth, scattered brush and native grasses.</p> |
| | <p>N. 0°01' W., bet. secs. 14 and 15.</p> |
| | <p>Over rolling land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 80.00 | <p style="text-align: center;">T36N R26E 1/4 S15 S14 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>From this cor. point, second order U. S. Geological Survey triangulation station "ROUND 1949", published by the National Geodetic Survey as an A order station, bears S. 86°43' W., 37.08 chs. dist., monumented with a standard benchmark brass tablet, 3 1/2 ins. diam., set flush in a metal encased concrete collar, 7 ins. diam., firmly set, projecting 5 ins. above ground, with top mkd. ROUND 1949.</p> <p>Point for the cor. of secs. 10, 11, 14, and 15.</p> <p>Set a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case, 24 ins. below the surface of the ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 50°00' E., 70.0 ft. dist., with brass cap mkd. T36N R26E S14 RM 70.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 40°00' W., 70.0 ft. dist., with brass cap mkd. T36N R26E S15 RM 70.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located in a wash, 10 ft. wide, 4 ft. deep, drains E.</p> <p>Land, rolling. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>West, bet. secs. 11 and 14.</p> <p>Over gently rolling land.</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 15.00 | Agua Sal Wash, 42 ft. wide, 2 ft. deep, drains NW. |
| 32.65 | NE right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway. |
| 33.87 | Center of U. S. Highway 191, asphalt pavement, 27 ft. wide, bears SE and NW. |
| 35.09 | SW right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway. |
| 38.15 | Wash, 6 ft. wide, 4 ft. deep, drains NNE. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 11 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T36N R26E S11 1/4 — S14 1999 Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. |
| 44.20 | Power line, bears SE and NW. |
| 46.00 | Power line, bears SE and NW. |
| 80.00 | The cor. of secs. 10, 11, 14, and 15. Land, gently rolling. Soil, sandy and gravelly clay. Timber, Russian olive and saltcedar near Agua Sal Wash; undergrowth, brush and native grasses. |
| | N. 0°01' W., bet. secs. 10 and 11. Over rolling and broken land. |
| 27.10 | Power line, bears SE and NW. |
| 33.94 | SW right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway. |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 35.83 | Center of U. S. Highway 191, asphalt pavement, 27 ft. wide, bears SE and NW. |
| 37.61 | NE right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway. |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E 1/4 S10 S11 1999</p> |
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. |
| 43.10 | Graded road, 15 ft. wide, bears NE and SW. |
| 65.60 | Power line, bears SSE and NNW. |
| 80.00 | <p>Point for the cor. of secs. 2, 3, 10, and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E S 3 S 2 ----- S10 S11 1999</p> |
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. |
| | Cor. is located 2.50 chs. S. and 2.10 chs. E. of a graded road, 15 ft. wide, bears NE and SW. |
| | <p>Land, rolling and broken. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p> |
| | <hr/> <p>From the cor. of secs. 1, 2, 11, and 12.</p> |
| | West, bet. secs. 2 and 11. |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | Over gently rolling land. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 2 and 11. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T36N R26E S 2 1/4 — S11 1999</p> |
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. |
| 54.30 | Lukachukai Wash, 200 ft. wide, 3 ft. deep, drains NNW. |
| 67.10 | A steel water well casing, 5 1/2 ins. diam., bears South, 8.55 chs. dist., projecting 10 ins. above a concrete slab, 4 x 3 ft. |
| 71.70 | Graded road, 15 ft. wide, bears SE and NW. |
| 80.00 | The cor. of secs. 2, 3, 10, and 11. |
| | Land, gently rolling. Soil, sand and sandy and gravelly clay. Timber, Russian olive and saltcedar near Lukachukai Wash; undergrowth, scattered brush and native grasses. |
| | N. 0°01' W., bet. secs. 2 and 3. |
| | Over rolling land on W. edge of Lukachukai Valley. |
| 11.20 | Graded road, 15 ft. wide, bears SE and NW. |
| 18.61 | The easternmost cor. of a wood sided house, 55 x 30 ft., bears West, 79 lks. dist., long side bears SW. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 2 and 3. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T36N R26E 1/4 S 3 S 2 1999</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. |
| 77.00 | SW bank of flood plain of Lukachukai Wash, 7 ft. high, bears SE and NW; thence enter flood plain. |
| 79.84 | Point for the closing cor. of secs. 2 and 3, at intersection with the Ninth Standard Parallel North, on the N. bdy. of the Tp. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T37N R26E S34</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S 3 S 2 T36N R26E CC 1999</p> |
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. |
| | Cor. is located 1.60 chs. E. of W. bank of flood plain of Lukachukai Wash, 8 ft. high, bears SSE and NNW. |
| | From this cor. point, the stan. cor. of secs. 34 and 35, T. 37 N., R. 26 E., bears East, 29.93 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 26 E., executed under this same group. |
| | From this same cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 37 N., R. 26 E., bears West, 10.07 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 26 E., executed under this same group. |
| | Land, rolling. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses. |
| | Point for the 1/4 sec. cor. of sec. 2 only, T. 36 N., R. 26 E., at midpoint on the N. bdy. of sec. 2. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p style="text-align: center;">T37N R26E</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1/4 S 2 T36N R26E 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located on E. edge of Lukachukai Valley, 2.00 chs. W. of base of W. slope of spur ridge of a mesa.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 35, T. 37 N., R. 26 E., bears East, 29.93 chs. dist.</p> <p>From this same cor. point, the stan. cor. of secs. 34 and 35, T. 37 N., R. 26 E., bears West, 10.07 chs. dist.</p> |
| | <p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 35 N., R. 26 E., executed concurrently under this same group.</p> <p>Cor. is located on SE slope of a ridge.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over broken land on ascent of S. slope of spur ridge of a mesa.</p> |
| 30.40 | S. rim of spur ridge of a mesa, bears ENE and WSW; thence over gently rolling to broken land atop a spur ridge. |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E 1/4 S33 S34 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 75 lks. W. of W. rim of a mesa, bears NNE and SSW; thence across another spur ridge.</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | |
|--------|--|-----|-----|-----|-----|
| 48.20 | N. rim of spur ridge of a mesa, bears ESE and WNW; thence across eroded area between ridges. | | | | |
| 70.20 | S. rim of a mesa, bears ESE and WNW; thence over gently rolling land atop a mesa. | | | | |
| 80.00 | <p>Point for the cor. of secs. 27, 28, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T36N R26E</p> <table border="1" style="margin: auto;"> <tr> <td>S28</td> <td>S27</td> </tr> <tr> <td>S33</td> <td>S34</td> </tr> </table> <p>1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located 10 lks. S. and 15 lks. W. of a trail road, bears SE and NW.</p> <p>Land, broken and gently rolling. Soil, sandy, gravelly and rocky clay and sandstone outcrops. No timber; scattered brush and native grasses.</p> | S28 | S27 | S33 | S34 |
| S28 | S27 | | | | |
| S33 | S34 | | | | |
| 40.00 | <hr/> <p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>West, bet. secs. 27 and 34.</p> <p>Over broken land on ascent of E. slope of a mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T36N R26E</p> <p>S27</p> <p>1/4 —</p> <p>S34</p> <p>1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> | | | | |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | Cor. is located 2.20 chs. E. of E. rim of a mesa, bears N. and S.; thence over gently rolling land atop a mesa. |
| 80.00 | The cor. of secs. 27, 28, 33, and 34. |
| | Land, broken to gently rolling. Soil, sandy, gravelly and rocky clay and sandstone outcrops. No timber; scattered brush and native grasses. |
| | N. 0°02' W., bet. secs. 27 and 28. |
| | Over gently rolling land atop a mesa. |
| 12.10 | NE rim of a mesa, bears ESE and WNW; thence over broken land along E. slope of a mesa. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 27 and 28. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T36N R26E 1/4 S28 S27 1999</p> |
| | Deposit a magnet in a 1 x 1 x 2 ins. white colored plastic case beneath the stainless steel post. |
| 69.60 | SE rim of spur ridge of a mesa, bears SE and NW; thence over gently rolling land atop a spur ridge. |
| 80.00 | Point for the cor. of secs. 21, 22, 27, and 28. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T36N R26E S21 S22 ----- S28 S27 1999</p> |
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. |
| | Cor. is located 2.30 chs. S. of NE rim of spur ridge of a mesa, bears ESE and WNW. |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Land, broken to gently rolling. Soil, sandy, gravelly and rocky clay and sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> |
| | <p>From the cor. of secs. 22, 23, 26, and 27.</p> |
| | <p>West, bet. secs. 22 and 27.</p> |
| | <p>Over rolling and broken land.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> |
| | <p>Set a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case, 16 ins. below the surface of the ground.</p> |
| | <p>from which</p> |
| | <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 75°00' E., 90.0 ft. dist., with brass cap mkd. T36N R26E 1/4 S22 RM 90.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| | <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 75°00' W., 90.0 ft. dist., with brass cap mkd. T36N R26E 1/4 S27 RM 90.0 FT TO COR 1999 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| | <p>Cor. is located on E. edge of a wash, 50 ft. wide, 5 ft. deep, drains N.; thence over broken land on ascent of E. slope of spur ridge of a mesa.</p> |
| 76.00 | <p>E. rim of spur ridge of a mesa, bears NNE and SSW; thence over gently rolling land atop spur ridge of a mesa.</p> |
| 80.00 | <p>The cor. of secs. 21, 22, 27, and 28.</p> |
| | <p>Land, rolling and broken to gently rolling. Soil, sandy, gravelly and rocky clay and sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> |
| | <p>N. 0°02' W., bet. secs. 21 and 22.</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | Over broken land across eroded area between spur ridges. |
| 29.80 | SE rim of spur ridge of a mesa, bears NE and SW. |
| 33.30 | N. rim of same spur ridge, bears E. and W.; thence over broken land across eroded area between ridges. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 21 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T36N R26E 1/4 S21 S22 1999 </div> |
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. |
| 58.90 | SE rim of a mesa, bears ENE and WSW; thence over gently rolling land atop a mesa. |
| 80.00 | Point for the cor. of secs. 15, 16, 21, and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T36N R26E S16 S15 ----- S21 S22 1999 </div> |
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. |
| | Land, broken to gently rolling. Soil, sandy, gravelly and rocky clay and sandstone outcrops. No timber; scattered brush and native grasses. |
| | From the cor. of secs. 14, 15, 22, and 23. West, bet. secs. 15 and 22. Over rolling land. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 15 and 22. |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T36N R26E S15 1/4 — S22 1999</p> |
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. |
| | Thence over broken land on ascent of E. slope of a mesa. |
| 74.50 | E. rim of a mesa, bears N. and S.; thence over gently rolling land atop a mesa. |
| 80.00 | The cor. of secs. 15, 16, 21, and 22. |
| | Land, rolling to broken to gently rolling. Soil, sandy, gravelly and rocky clay and sandstone outcrops. No timber; scattered brush and native grasses. |
| | N. 0°02' W., bet. secs. 15 and 16. |
| | Over gently rolling land atop a mesa. |
| 12.45 | Trail road, bears NNE and SSW. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 15 and 16. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T36N R26E 1/4 S16 S15 1999</p> |
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. |
| 80.00 | Point for the cor. of secs. 9, 10, 15, and 16. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p style="text-align: center;">T36N R26E S 9 S10 ----- S16 S15 1999</p> |
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.</p> |
| 36.00 | <p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>West, bet. secs. 10 and 15.</p> <p>Over broken land on ascent of E. slope of a mesa.</p> |
| 38.00 | <p>E. rim of a mesa, bears N. and S.; thence over gently rolling land atop a mesa.</p> |
| 40.00 | <p>Trail road, bears SSE and NNW.</p> |
| | <p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E S10 1/4 — S15 1999</p> |
| 80.00 | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 9, 10, 15, and 16.</p> <p>Land, broken to gently rolling. Soil, sandy, gravelly and rocky clay and sandstone outcrops. No timber; scattered brush and native grasses.</p> |
| | <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over gently rolling land atop a mesa.</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E 1/4 S 9 S10 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| 80.00 | <p>Point for the cor. of secs. 3, 4, 9, and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E S 4 S 3 ----- S 9 S10 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> |
| | <p>From the cor. of secs. 2, 3, 10, and 11.</p> |
| | <p>West, bet. secs. 3 and 10.</p> |
| | <p>Over rolling to broken land on ascent of E. slope of a mesa.</p> |
| 5.30 | <p>Power line, bears SSE and NNW.</p> |
| 29.00 | <p>E. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.</p> |
| 31.11 | <p>Center of U. S. Highway 191, asphalt pavement, 27 ft. wide, bears N. in curve to left.</p> |
| 32.86 | <p>W. right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway.</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 33.00 | E. rim of a mesa, bears N. and S., thence over gently rolling land atop a mesa. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 3 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T36N R26E S 3 1/4 — S10 1999 |
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. |
| | Cor. is located 1.80 chs. E. of a trail road, bears N. and S. |
| | From this cor. point, a third order U. S. Geological Survey benchmark, bears N. 27°52' W., 4.38 chs. dist., monumented with a standard brass tablet, 3 1/2 ins. diam., set flush in a concrete collar, 7 ins. diam., firmly set, projecting 8 ins. above ground, with top mkd. 28 D 5464 1950. |
| 48.40 | Power line, bears SE and NW. |
| 57.20 | Apache County Road C497, a graded road, 25 ft. wide, bears NNE and SSW. |
| 70.60 | Apache County Road C497, a graded road, 25 ft. wide, bears SSE and NNW. |
| 74.30 | Power line, bears N. and S. |
| 80.00 | The cor. of secs. 3, 4, 9, and 10. Land, rolling to broken to gently rolling. Soil, sandy, gravelly and rocky clay and sandstone outcrops. No timber; scattered brush and native grasses. |
| | N. 0°02' W., bet. secs. 3 and 4. |
| | Over gently rolling land atop a mesa. |
| 17.70 | Apache County Road C497, a graded road, 25 ft. wide, bears SSE and NNW. |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 24.30 | Apache County Road C589, a graded road, 25 ft. wide, bears ESE and WNW. |
| 32.80 | Power line, bears ENE and WSW. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 3 and 4. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd. |
| | T36N R26E 1/4 S 4 S 3 1999 |
| | from which |
| | The SW cor. of an octagonal stuccoed hogan, 20 ft. diam., bears N. 39 3/4° E., 1.37 chs. dist., sides bear SE and N. |
| | The SE cor. of a wood sided house, 37 x 33 ft., bears N. 32 1/2° W., 1.66 chs. dist., long side bears W. |
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. |
| 56.70 | Power line, bears SSE and NNW. |
| 74.43 | SW right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway. |
| 75.79 | Center of U. S. Highway 191, asphalt pavement, 27 ft. wide, bears SSE and NNW. |
| 77.21 | NE right-of-way fence of U. S. Highway 191, barbed wire, 5 strands, parallels highway. |
| 79.84 | Point for the closing cor. of secs. 3 and 4, at intersection with the Ninth Standard Parallel North, on the N. bdy. of the Tp. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T37N R26E S33 ----- S 4 S 3 T36N R26E CC 1999 |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.

Cor. is located 1.68 chs. E. of NE right-of-way fence , and 2.66 chs. E. of center of U. S. Highway 191, asphalt pavement, 27 ft. wide, bears SSE and NNW.

From this cor. point, the stan. cor. of secs. 33 and 34, T. 37 N., R. 26 E., bears East, 29.92 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 26 E., executed under this same group.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 37 N., R. 26 E., bears West, 10.08 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 26 E., executed under this same group.

Land, gently rolling.
Soil, sandy and gravelly clay.
No timber; scattered brush and native grasses.

Point for the 1/4 sec. cor. of sec. 3 only, T. 36 N., R. 26 E., at midpoint on the N. bdy. of sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T37N R26E

1/4 S 3
T36N R26E
1999

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 34, T. 37 N., R. 26 E., bears East, 29.925 chs. dist.

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>From this same cor. point, the stan. cor. of secs. 33 and 34, T. 37 N., R. 26 E., bears West, 10.075 chs. dist.</p> |
| | <p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 35 N., R. 26 E., executed concurrently under this same group.</p> |
| | <p>N. 0°03' W., bet. secs. 32 and 33.</p> |
| | <p>Over rolling and broken land on ascent of S. slope of a mesa.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E 1/4 S32 S33 1999</p> |
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| 80.00 | <p>Point for the cor. of secs. 28, 29, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E S29 S28 ----- S32 S33 1999</p> |
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| | <p>Land, rolling and broken. Soil, sandy, gravelly and rocky clay. No timber; sparse brush and native grasses.</p> |
| | <p>From the cor. of secs. 27, 28, 33, and 34.</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | West, bet. secs. 28 and 33. |
| | Over gently rolling land atop a mesa. |
| 29.80 | W. rim of a mesa, bears SSE and NNW; thence over broken land across S. slope of a mesa. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 28 and 33. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T36N R26E S28 1/4 — S33 1999</p> |
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. |
| 80.00 | The cor. of secs. 28, 29, 32, and 33. |
| | Land, gently rolling to broken. |
| | Soil, sandy and rocky clay and sandstone outcrops. |
| | No timber; sparse brush and native grasses. |
| | N. 0°03' W., bet. secs. 28 and 29. |
| | Over broken land on ascent of S. slope of a mesa. |
| 12.40 | S. rim of a mesa, bears NE and SW; thence over gently rolling land atop a mesa. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 28 and 29. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T36N R26E 1/4 S29 S28 1999</p> |
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. |
| 80.00 | Point for the cor. of secs. 20, 21, 28, and 29. |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T36N R26E S20 S21 ----- S29 S28 1999</p> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, broken to gently rolling. Soil, sandy and rocky clay and sandstone outcrops. No timber; scattered brush and native grasses.</p> |
| | <p>From the cor. of secs. 21, 22, 27, and 28.</p> |
| | <p>West, bet. secs. 21 and 28.</p> |
| | <p>Over gently rolling land atop a mesa.</p> |
| 26.65 | <p>Trail road, bears N. and S.</p> |
| 29.90 | <p>Base of E. slope of Round Rock, a sandstone monolith, bears N. and S.; thence over broken land on steep ascent of Round Rock.</p> |
| 40.00 | <p>True point for the 1/4 sec. cor. of secs. 21 and 28, falls on or atop inaccessible vertical sandstone cliff on E. side of Round Rock, a sandstone monolith; where it is impracticable to establish a monument.</p> |
| | <p>From this true cor. point, the point selected for the witness cor. to the 1/4 sec. cor. of secs. 21 and 28, bears N. 80°00' E., 10.00 chs. dist.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> |
| | <div style="text-align: center;"> <p>WC T36N R26E S21 ← 1/4 — S28 1999</p> </div> |
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 66.20 | Base of W. slope of Round Rock, bears NNE and SSW; thence over gently rolling land atop a mesa. |
| 80.00 | <p>The cor. of secs. 20, 21, 28, and 29.</p> <p>Land, gently rolling and broken. Soil, sandy and rocky clay and sandstone monolith. No timber; scattered brush and native grasses.</p> |
| | <hr/> <p>N. 0°03' W., bet. secs. 20 and 21.</p> |
| | Over gently rolling land atop a mesa. |
| 8.20 | Trail road, bears NNE and SSW. |
| 32.80 | Trail road, bears ENE and WSW. |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in bedrock, encircled with a collar of stone, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E 1/4 S20 S21 1999</p> |
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. |
| 80.00 | <p>Point for the cor. of secs. 16, 17, 20, and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E S17 S16 ----- S20 S21 1999</p> |
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Land, gently rolling. Soil, sandy and rocky clay and sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 15, 16, 21, and 22. West, bet. secs. 16 and 21. Over gently rolling land atop a mesa.</p> |
| 6.50 | Trail road, bears NNE and SSW. |
| 28.70 | W. rim of a mesa, bears NE and SW; thence over broken land on descent into eroded area between ridges. |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 16 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E S16 1/4 — S21 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| 68.00 | E. rim of spur ridge of a mesa, bears NNE and SSW; thence over gently rolling land atop a spur ridge. |
| 80.00 | <p>The cor. of secs. 16, 17, 20, and 21. Land, gently rolling and broken. Soil, sandy and rocky clay and sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 16 and 17. Over gently rolling land atop spur ridge of a mesa.</p> |
| 14.70 | N. rim of a spur ridge, bears ENE and WSW; thence over broken land on abrupt descent into eroded area between ridges. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 16 and 17. |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> |
| 70.45 | <p style="text-align: center;">T36N R26E 1/4 S17 S16 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>S. rim of a mesa, bears ENE and WSW; thence over gently rolling land atop a mesa.</p> |
| 80.00 | <p>Point for the cor. of secs. 8, 9, 16, and 17.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E S 8 S 9 ----- S17 S16 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, gently rolling and broken. Soil, sandy and gravelly clay and sandstone outcrops. No timber; scattered brush and native grasses.</p> |
| | <p>From the cor. of secs. 9, 10, 15, and 16.</p> |
| | <p>West, bet. secs. 9 and 16.</p> |
| | <p>Over gently rolling land atop a mesa.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E S 9 1/4 — S16 1999</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. |
| 80.00 | <p>The cor. of secs. 8, 9, 16, and 17.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> |
| | <p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over gently rolling land atop a mesa.</p> |
| 7.50 | S. rim of a ravine, drains WNW; thence across ravine and spur ridge of a mesa. |
| 37.70 | N. rim of spur ridge of a mesa, bears E. and W.; thence over broken land on descent into head of a canyon. |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E 1/4 S 8 S 9 1999</p> |
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located at the head of a canyon, at base of W. slope of a mesa, bears N. and S.: thence over broken land on ascent.</p> |
| 46.00 | SW rim of a mesa, bears NE and SW; thence over gently rolling land atop a mesa. |
| 80.00 | <p>Point for the cor. of secs. 4, 5, 8, and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E S 5 S 4 ----- S 8 S 9 1999</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, gently rolling and broken. Soil, sandy, gravelly and rocky clay and sandstone outcrops. No timber; scattered brush and native grasses.</p> |
| 40.00 | <p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over rolling land atop a mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E S 4 1/4 — S 9 1999</p> |
| 80.00 | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 4, 5, 8, and 9.</p> <p>Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> |
| 40.00 | <p>N. 0°03' W., bet. secs. 4 and 5.</p> <p>Over rolling land atop a mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E 1/4 S 5 S 4 1999</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. |
| 55.15 | Trail road, bears ESE and WNW. |
| 79.84 | Point for the closing cor. of secs. 4 and 5, at intersection with the Ninth Standard Parallel North, on the N. bdy. of the Tp. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T37N R26E S32</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S 5 S 4 T36N R26E CC 1999</p> |
| | Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. |
| | From this cor. point, the stan. cor. of secs. 32 and 33, T. 37 N., R. 26 E., bears East, 29.92 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 26 E., executed under this same group. |
| | From this same cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 37 N., R. 26 E., bears West, 10.08 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 26 E., executed under this same group. |
| | Land, rolling. Soil, sandy clay. No timber; scattered brush and native grasses. |
| | Point for the 1/4 sec. cor. of sec. 4 only, T. 36 N., R. 26 E., at midpoint on the N. bdy. of sec. 4. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 2 ft. base, to top, with brass cap mkd. |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p style="text-align: center;">T37N R26E ----- 1/4 S 4 T36N R26E 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>From this cor. point, the stan. 1/4 sec. cor. of sec. 33, T. 37 N., R. 26 E., bears East, 29.92 chs. dist.</p> <p>From this same cor. point, the stan. cor. of secs. 32 and 33, T. 37 N., R. 26 E., bears West, 10.08 chs. dist.</p> <hr/> <p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the north boundary, T. 35 N., R. 26 E., executed concurrently under this same group.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over nearly level land in Chinle Valley.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E 1/4 S31 S32 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| 80.00 | <p>Point for the cor. of secs. 29, 30, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E S30 S29 ----- S31 S32 1999</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located atop a ridge on S. slope of a mesa, bears NE and WNW.</p> <p>Land, nearly level. Soil, sandy clay. No timber; sparse brush and native grasses.</p> |
| 40.00 | <p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>West, bet. secs. 29 and 32.</p> <p>Over broken land across the S. slope of a mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E S29 1/4 — S32 1999</p> |
| 80.00 | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Thence over rolling and broken land on descent into Chinle Valley.</p> <p>The cor. of secs. 29, 30, 31, and 32.</p> <p>Land, rolling and broken. Soil, sandy, gravelly and rocky clay. No timber; sparse brush and native grasses.</p> |
| 40.00 | <p>West, bet. secs. 30 and 31.</p> <p>Over nearly level land in Chinle Valley.</p> <p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p style="text-align: center;">T36N R26E S30 1/4 — S31 1999</p> |
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| 51.10 | <p>Wash, 25 ft. wide, 4 ft. deep, drains NE.</p> |
| 64.80 | <p>Chinle Wash, 80 ft. wide, 10 ft. deep, drains N.</p> |
| 78.31 | <p>The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 36 N., R. 25 E., executed concurrently under this same group.</p> |
| | <p>Land, nearly level. Soil, sandy clay. Timber, cottonwood, Russian olive and saltcedar near Chinle Wash; undergrowth, sparse brush and native grasses.</p> |
| | <hr/> <p>From the cor. of secs. 29, 30, 31, and 32.</p> |
| | <p>N. 0°03' W., bet. secs. 29 and 30.</p> |
| | <p>Over broken land on ascent of S. slope of spur ridge of a mesa.</p> |
| 22.90 | <p>S. rim of spur ridge of a mesa, bears SSE and NNW; thence over rolling land atop a spur ridge.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E 1/4 S30 S29 1999</p> |
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| | <p>Thence over rolling and broken land across eroded area between spur ridges.</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | | | |
|-----------|---|-----------|--|-----|-----|-----|-----|------|--|------|--|
| 80.00 | <p>Point for the cor. of secs. 19, 20, 29, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T36N R26E</td><td></td></tr> <tr><td>S19</td><td>S20</td></tr> <tr><td>S30</td><td>S29</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy, gravelly and rocky clay and sandstone outcrops. No timber; scattered brush and native grasses.</p> | T36N R26E | | S19 | S20 | S30 | S29 | 1999 | | | |
| T36N R26E | | | | | | | | | | | |
| S19 | S20 | | | | | | | | | | |
| S30 | S29 | | | | | | | | | | |
| 1999 | | | | | | | | | | | |
| | <p>From the cor. of secs. 20, 21, 28, and 29.</p> | | | | | | | | | | |
| | <p>West, bet. secs. 20 and 29.</p> | | | | | | | | | | |
| | <p>Over gently rolling land atop a mesa.</p> | | | | | | | | | | |
| 3.85 | <p>Trail road, bears NNE and SSW.</p> | | | | | | | | | | |
| 22.00 | <p>W. rim of a mesa, bears SSE and NNW; thence over broken land on descent into an eroded area.</p> | | | | | | | | | | |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T36N R26E</td><td></td></tr> <tr><td>S20</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S29</td><td></td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> | T36N R26E | | S20 | | 1/4 | — | S29 | | 1999 | |
| T36N R26E | | | | | | | | | | | |
| S20 | | | | | | | | | | | |
| 1/4 | — | | | | | | | | | | |
| S29 | | | | | | | | | | | |
| 1999 | | | | | | | | | | | |
| 80.00 | <p>The cor. of secs. 19, 20, 29, and 30.</p> | | | | | | | | | | |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 40.00 | <p>Land, gently rolling to broken. Soil, sandy, gravelly and rocky clay and sandstone outcrops. No timber; scattered brush and native grasses.</p> <hr/> <p>West, bet. secs. 19 and 30.</p> <p>Over rolling and broken land across eroded area.</p> <p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E S19 1/4 — S30 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Cor. is located atop W. rim of a rocky clay spur ridge, bears N. and S.; thence descend abruptly to nearly level land in Chinle Valley.</p> |
| 78.22 | <p>The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 36 N., R. 25 E., executed concurrently under this same group.</p> <p>Land, rolling and broken to nearly level. Soil, sandy, gravelly and rocky clay and sandstone outcrops. No timber; sparse brush and native grasses.</p> |
| 40.00 | <hr/> <p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over rolling and broken land across eroded area between spur ridges.</p> <p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E 1/4 S19 S20 1999</p> |
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| | <p>Cor. is located on W. slope of spur ridge of a mesa, 15 lks. W. of W. rim, bears N. and S.</p> |
| 63.00 | <p>S. rim of spur ridge of a mesa, bears ENE and WSW; thence over gently rolling land atop a spur ridge.</p> |
| 80.00 | <p>Point for the cor. of secs. 17, 18, 19, and 20.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E S18 S17 ----- S19 S20 1999</p> |
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| | <p>Cor. is located 20 lks. S. of N. rim of spur ridge of a mesa, bears SE and NW.</p> |
| | <p>Land, rolling and broken to gently rolling. Soil, sandy, gravelly and rocky clay and sandstone outcrops. No timber; sparse brush and native grasses.</p> |
| | <p>From the cor. of secs. 16, 17, 20, and 21.</p> |
| | <p>West, bet. secs. 17 and 20.</p> |
| | <p>Over gently rolling land atop spur ridge of a mesa.</p> |
| 4.60 | <p>W. rim of spur ridge of a mesa, bears SE and NW; thence over broken land across eroded area between spur ridges.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E S17 1/4 — S20 1999</p> |
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| | <p>Cor. is located on E. slope of a narrow spur ridge, bears N. and S.</p> |
| 44.50 | <p>E. rim of a spur ridge, bears NE and SW.</p> |
| 45.70 | <p>W. rim of same spur ridge, bears NNE and SSW: thence over broken and rolling land across head of a narrow canyon and along N. slope of another spur ridge.</p> |
| 80.00 | <p>The cor. of secs. 17, 18, 19, and 20.</p> <p>Land, gently rolling to broken and rolling. Soil, sandy, gravelly and rocky clay and sandstone outcrops. No timber; sparse brush and native grasses.</p> |
| | <p>West, bet. secs. 18 and 19.</p> |
| | <p>Over rolling land atop spur ridge of a mesa.</p> |
| 4.00 | <p>W. rim of spur ridge of a mesa, bears SSE and NNW; thence over broken land on descent into eroded area.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E S18 1/4 — S19 1999</p> |
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>Cor. is located on steep SW slope of a rocky clay spur ridge, bears SE and NW; thence over rolling land across eroded area.</p> |
| 78.13 | <p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 36 N., R. 25 E., executed concurrently under this same group.</p> |
| | <p>Land, rolling and broken. Soil, sandy, gravelly and rocky clay and sandstone outcrops. No timber; sparse brush and native grasses.</p> |
| | <p>From the cor. of secs. 17, 18, 19, and 20. N. 0°03' W., bet. secs. 17 and 18. Over broken land across eroded area.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 17 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E 1/4 S18 S17 1999</p> |
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post. Cor. is located near foot of W. slope of a small ravine, drains N.; thence over rolling land on descent into Chinle Valley.</p> |
| 80.00 | <p>Point for the cor. of secs. 7, 8, 17, and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E S 7 S 8 ----- S18 S17 1999</p> |
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Land, broken to rolling. Soil, sandy, gravelly and rocky clay and sandstone outcrops. No timber; sparse brush and native grasses.</p> |
| | <p>From the cor. of secs. 8, 9, 16, and 17.</p> |
| | <p>West, bet. secs. 8 and 17.</p> |
| | <p>Over gently rolling land atop a mesa.</p> |
| 27.60 | <p>W. rim of a mesa, bears NE and SW; thence over broken land on descent.</p> |
| 36.20 | <p>Base of W. slope of a mesa, bears SE and NW; thence over nearly level land in Chinle Valley.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E S 8 1/4 — S17 1999</p> |
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> |
| 80.00 | <p>The cor. of secs. 7, 8, 17, and 18.</p> <p>Land, gently rolling to broken to nearly level. Soil, sandy, gravelly and rocky clay and sandstone outcrops. No timber; scattered brush and native grasses.</p> |
| | <p>West, bet. secs. 7 and 18.</p> |
| | <p>Over gently rolling land in Chinle Valley.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 78.04 | <p style="text-align: center;">T36N R26E S 7 1/4 — S18 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 36 N., R. 25 E., executed concurrently under this same group.</p> <p>Land, gently rolling. Soil, sandy, gravelly and rocky clay. No timber; scattered brush and native grasses.</p> |
| 40.00 | <p>From the cor. of secs. 7, 8, 17, and 18. N. 0°03' W., bet. secs. 7 and 8. Over nearly level land in Chinle Valley.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| 80.00 | <p style="text-align: center;">T36N R26E 1/4 S 7 S 8 1999</p> <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Point for the cor. of secs. 5, 6, 7, and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E S 6 S 5 — — S 7 S 8 1999</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.</p> |
| 40.00 | <p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>West, bet. secs. 5 and 8.</p> <p>Over gently rolling land atop a mesa.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R26E S 5 1/4 — S 8 1999</p> |
| 47.20 | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>W. rim of a mesa, bears SSE and NNW; thence over broken land on abrupt descent to nearly level land in Chinle Valley.</p> |
| 80.00 | <p>The cor. of secs. 5, 6, 7, and 8.</p> <p>Land, gently rolling to broken to nearly level. Soil, sandy and rocky clay and sandstone outcrops. No timber; scattered brush and native grasses.</p> |
| 40.00 | <p>West, bet. secs. 6 and 7.</p> <p>Over nearly level land in Chinle Valley.</p> <p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p style="text-align: center;">T36N R26E S 6 1/4 — S 7 1999</p> |
| 77.96 | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the east boundary, T. 36 N., R. 25 E., executed concurrently under this same group.</p> <p>Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.</p> |
| 40.00 | <p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over nearly level land in Chinle Valley.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T36N R26E 1/4 S 6 S 5 1999</p> |
| 70.70 | <p>Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.</p> <p>Base of SW slope of a mesa, bears SSE and NNW; thence over broken land on ascent.</p> |
| 75.80 | <p>SW rim of a mesa, bears SE and NW; thence over gently rolling land atop a mesa.</p> |
| 79.83 | <p>Point for the closing cor. of secs. 5 and 6, at intersection with the Ninth Standard Parallel North, on the N. bdy. of the Tp.</p> |

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
20 ins. in the ground, to bedrock, in a mound of stone, 3 ft.
base, to top, with brass cap mkd.

T37N R26E

S31

| | |
|-----|-----|
| S 6 | S 5 |
|-----|-----|

T36N R26E

CC

1999

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic
case beneath the stainless steel post.

Cor. is located 1.70 chs. E. of W. rim of a mesa, bears SSE and
NNW.

From this cor. point, the stan. cor. of secs. 31 and 32,
T. 37 N., R. 26 E., bears East, 29.92 chs. dist., monumented with
a stainless steel post, 2 1/2 ins. diam., with brass cap, set and
mkd. as described in the field notes of the survey of the Ninth
Standard Parallel North, (south boundary), T. 37 N., R. 26 E.,
executed under this same group.

From this same cor. point, the stan. 1/4 sec. cor. of sec. 31,
T. 37 N., R. 26 E., bears West, 10.08 chs. dist., monumented with
a stainless steel post, 2 1/2 ins. diam., with brass cap, set and
mkd. as described in the field notes of the survey of the Ninth
Standard Parallel North, (south boundary), T. 37 N., R. 26 E.,
executed under this same group.

Land, nearly level to broken to gently rolling.
Soil, sandy, gravelly and rocky clay.
No timber; scattered brush and native grasses.

Point for the 1/4 sec. cor. of sec. 5 only, T. 36 N., R. 26 E.,
at midpoint on the N. bdy. of sec. 5.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T37N R26E

| |
|---------|
| 1/4 S 5 |
|---------|

T36N R26E

1999

Survey of the Subdivisional Lines,
T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 32, T. 37 N., R. 26 E., bears East, 29.92 chs. dist.

From this same cor. point, the stan. cor. of secs. 31 and 32, T. 37 N., R. 26 E., bears West, 10.08 chs. dist.

Point for the 1/4 sec. cor. of sec. 6 only, T. 36 N., R. 26 E., at 40 chs. westing from the closing cor. of secs. 5 and 6, on the N. bdy. of sec. 6.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T37N R26E

1/4 S 6
T36N R26E
1999

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.

From this cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 37 N., R. 26 E., bears East, 29.92 chs. dist.

From this same cor. point, the stan. cor. of Tps. 37 N., Rs. 25 and 26 E., bears West, 10.08 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set and mkd. as described in the field notes of the survey of the Ninth Standard Parallel North, (south boundary), T. 37 N., R. 25 E., executed under this same group.

T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona

| | |
|--------|---|
| CHAINS | <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>The area surveyed is located 3 miles northwest of the community of Round Rock, Arizona. The terrain varies from gently rolling land in the valleys of Chinle, Lukachukai and Agua Sal Washes, to rolling and broken land surrounding and atop mesas. There are two prominent sandstone monoliths: Round Rock being in sections 21 and 28, and Little Round Rock being in section 16. The drainage in the west half of the township is primarily westerly into Chinle Wash, which drains northerly along the west boundary. The drainage in the east half is provided by Agua Sal and Lukachukai Washes, which join in section 11, and exit northerly from section 2.</p> <p>The elevation varies from 5100 to 6300 feet above sea level. The soil is mostly sandy, gravelly and rocky clay with sandstone outcrops on the mesas. The timber consists of some cottonwood, Russian olive and saltcedar near the main washes. The principal vegetation consists of scattered brush and native grasses.</p> <p>Principal access to the township is provided by U. S. Highway 191, asphalt pavement, which enters the township in section 35, exits in section 25, reenters in section 24, and exits in section 4. There are a few graded and trail roads providing additional access. Much of the area is used for grazing livestock. There is no mining activity in the township.</p> <p>The mean magnetic declination is $12 \frac{1}{4}^{\circ}$ E, as derived from the United States Geological Survey computer program GEOMAGIX utilizing the Regional Magnetic Field Model for Epoch 1995 for the dates of survey.</p> <hr/> |
|--------|---|

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

| NAMES | CAPACITY |
|------------------|------------------------|
| William F. Olver | Cadastral Surveyor |
| Daniel Bryan | Engineering Technician |
| Wilfred Chee | Engineering Technician |
| Edward Clarke | Engineering Technician |
| Reuben Mason | Engineering Technician |
| Barney Woodie | Engineering Technician |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

CERTIFICATE OF SURVEY

I, Leonard R. Sandoval, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 17th day of February, 1998, I have surveyed the east boundary and the subdivisional lines, Township 36 North, Range 26 East, of the Gila and Salt River Meridian, in the state of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

3-1-01
(Date)

Leonard R. Sandoval
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Arizona State Office
Phoenix, Arizona

The foregoing field notes of the survey of the east boundary and the subdivisional lines, Township 36 North, Range 26 East, Gila and Salt River Meridian, Arizona, executed by Leonard R. Sandoval, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

June 11, 2001
(Date)

Kenny D. Rawnskar
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 36 N., R. 26 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~