

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

**FIELD NOTES
OF THE
DEPENDENT RESURVEY
OF A PORTION OF THE
SOUTH AND EAST BOUNDARIES
AND A PORTION OF THE SUBDIVISIONAL LINES
AND THE SUBDIVISION OF SECTIONS 25 AND 36,
TOWNSHIP 22 NORTH, RANGE 5 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.**

EXECUTED BY

Dale C. Wilson, Cadastral Surveyor, Cadastral Surveyor

**Under Special Instructions dated May 30, 2001, approved May 30, 2001,
which provided for the surveys included under Group No. 872, and
assignment instructions dated May 30, 2001.**

Survey commenced June 19, 2001

Survey completed July 26, 2001

INDEX DIAGRAM

TOWNSHIP 22 NORTH RANGE 5 EAST

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	9 25 5 9
31	32	33	34	35	8 6 36 4 2

Subdivision of Section 25 Pages 10-11
 Subdivision of Section 36 Pages 11-14

T. 22 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the south and east boundaries and a portion of the subdivisional lines and the subdivision of sections 25 and 36, T. 22 N., R. 5 E., Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this resurvey is as follows:

John L. Harris surveyed the south boundary in 1878. Washington O. Secor surveyed the east boundary in 1889. Francis B. Jacobs retraced the south boundary and surveyed the subdivisional lines in 1891-92. Horace M. Muscott and Claude F. Warner dependently resurveyed the south and east boundaries and the subdivisional lines in 1940-41. Charles W. Dryden, Arizona Registered Land Surveyor No. 13010 surveyed U.S. Interstate Highway 40 in 1961.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated May 30, 2001, for Group No. 872, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from U. S. Coast and Geodetic Survey triangulation station DOT 1958, horizontal order B, as published by the National Geodetic Survey, NAD 83 (1992). The geographic position of the cor. Tps. 21 and 22 N., Rs. 5 and 6 E., is as follows:

Latitude: 35° 14' 16.33" N. Longitude: 111° 48' 28.70" W.

The mean magnetic declination is 14½° E.

**Dependent Resurvey of a Portion of the South Boundary,
T. 22 N., R. 5 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
Horace M. Muscott and Claude F. Warner, in 1940-41

**Dependent Resurvey of a Portion of the South Boundary,
T. 22 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Beginning at the cor. of Tps. 21 and 22 N., Rs. 5 and 6 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, in a collar of stone, 2½ ft. base, with brass cap mkd. T22N R5E R6E S36 S31 S1 S6 T21N 1941.</p> <p>from which an original bearing tree</p> <p style="padding-left: 40px;">A pine, 24 ins. diam., bears N. 19½° W., 26 lks. dist., with scribe marks TXXIINRVE XXXVI visible on open blaze.</p> <p>and 1941 bearing trees</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears N. 60° E., 48 lks. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A pine, 16 ins. diam., bears S. 25½° E., 69 lks. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears S. 43½° W., 164 lks. dist., with a healed blaze.</p> <p>Add the marks 2001 to the brass cap.</p> <p>From this cor. point, U.S. Coast and Geodetic Survey triangulation station "DOT 1958" bears S. 10°07'30" E., 66.26 chs. dist., monumented with a brass tablet, set flush in concrete 12 ins. below the surface of the ground, mkd. DOT 1958.</p> <p>S. 89°59' W., bet. secs. 1 and 36, on the S. bdy. of the Tp.</p> <p>Over nearly level land through scattered pine timber.</p>
40.14	<p>The 1/4 sec. cor. of secs. 1 and 36, reestablished by Kenneth A. Krenke, Arizona Registered Land Surveyor No. 14671 in 1998, at proportionate dist. longitudinally and utilizing correlating evidence of the 1961 Charles W. Dryden surveys for alignment; there is no remaining evidence of the 1941 witness cor., monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, in a collar of stone, with brass cap mkd. T22N R5E S36 1/4 S1 T21N 1998 LS 14671. Corner falls on the N. edge of the borrow pit on the N. side of old Route 66, graded, bears SE. and W. This is accepted as a careful and faithful reestablishment of the cor. position.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°58' W., beginning new measurement.</p> <p>Over level land along the N. borrow pit of old Route 66.</p>

**Dependent Resurvey of a Portion of the South Boundary,
T. 22 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS											
20.04	An aluminum cap, 1½ ins. diam., firmly set flush with the surface of the N. edge of asphalt of U.S. Interstate Highway 40, N. frontage road (old Route 66), mkd. L.S. 18215. This monument was set by James A. Folkers, Arizona Registered Land Surveyor No. 18215, in 1994, as the corner of a parcel of private land.										
20.07	Point for the W. 1/16 sec. cor. of secs. 1 and 36, not monumented.										
22.85	Intersect the N. right-of-way of U.S. Interstate Highway 40, at a point S. 2°02' W., 0.36 ch. dist. from station No. 1619+41.71, monumented with a brass disk, 3 ins. diam., set flush in a concrete cylinder, 7 ins. diam., 10 ins. below the surface of the ground.										
30.16	<p>A concrete nail, set flush with the asphalt surface of old Route 66, origin unknown.</p> <p>From this point, a steel reinforcement rod, ½ in. diam., set flush with asphalt, bears North, 0.02 ch. dist., origin unknown.</p> <p>From this same point U.S. Interstate Highway 40, right-of-way station No. 1618+42.76, bears N. 55°02' W., 0.68 ch. dist., monumented with a brass disk, 3 ins. diam., set flush in a concrete cylinder, 7 ins. diam., projecting 2 ins. above ground.</p>										
40.14	<p>The cor. of secs. 1, 2, 35 and 36, determined at record distance from Arizona Highway Department right-of-way monument station No. 1613+19.50, hereinafter described, and on the projection of the section line from the 1/4 sec. cor. of secs. 35 and 36. Charles W. Dryden, Arizona Registered Land Surveyor No. 13010, established this right-of-way monument on the line bet. secs. 35 and 36, in 1961, by establishing the true point for the cor. of secs. 1, 2, 35 and 36 from the 1941 witness cor. which is no longer in existence. This is accepted as a careful and faithful perpetuation of the cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <table border="1" data-bbox="828 1575 1006 1764" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T22N R5E</td> </tr> <tr> <td style="text-align: center;">S35</td> <td style="text-align: center;">S36</td> </tr> <tr> <td style="text-align: center;">S 2</td> <td style="text-align: center;">S 1</td> </tr> <tr> <td colspan="2" style="text-align: center;">T21N</td> </tr> <tr> <td colspan="2" style="text-align: center;">2001</td> </tr> </table> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T22N R5E		S35	S36	S 2	S 1	T21N		2001	
T22N R5E											
S35	S36										
S 2	S 1										
T21N											
2001											

**Dependent Resurvey of a Portion of the South Boundary,
T. 22 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS

Cor. falls in the S. slope of the W. bound grade of U.S. Interstate Highway 40, 38 lks. S. of the S. edge of pavement.

From this cor. point, a steel reinforcement rod, $\frac{1}{2}$ in. diam., firmly set, projecting 4 ins. above the ground, with plastic cap mkd. LS 19344, bears N. $24^{\circ}46'$ E., 0.04 ch. dist. This monument was set by Kirk Pangus, Arizona Registered Land Surveyor No. 19344.

From this same cor. point, the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, bears N. $89^{\circ}57'$ W., 40.07 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, in a mound of stone, 3 ft. base, $\frac{1}{2}$ ft. high with brass cap mkd. S35 $\frac{1}{4}$ S2 1941.

**Dependent Resurvey of a Portion of the East Boundary,
T. 22 N., R. 5 E., Gila and Salt River Meridian, Arizona**

Restoring the resurvey executed by
Horace M. Muscott and Claude F. Warner, in 1940-41

From the cor. of Tps. 21 and 22 N., Rs. 5 and 6 E., hereinbefore described.

N. $1^{\circ}06'$ E., bet. secs. 31 and 36, on the E. bdy. of the Tp.

Over rolling terrain through dense pine timber.

39.92

The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, $2\frac{1}{2}$ ft. base, 1 ft. high, with brass cap mkd. $\frac{1}{4}$ S36 S31 1941.

from which the 1941 bearing trees

A pine, 9 ins. diam., bears N. $79\frac{1}{2}^{\circ}$ E., 125 lks. dist., with scribe marks $\frac{1}{4}$ S31 BT visible on partially opened blaze.

A pine, 12 ins. diam., bears N. 41° W., 75 lks. dist., with a healed blaze. (Record, N. 52° W.)

Add the marks T22N R5E R6E 2001 to the brass cap.

N. $2^{\circ}08'$ E., beginning new measurement.

Over rolling land, through dense pine timber.

**Dependent Resurvey of a Portion of the East Boundary,
T. 22 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.55	<p>The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with a mound of stone, 3 ft. base, 1½ ft. high, to the W., with brass cap mkd. T22N R5E R6E S25 S30 S36 S31 1941.</p> <p>from which the 1941 bearing trees</p> <p>A pine, 18 ins. diam., bears N. 8° E., 54 lks. dist., with scribe marks T22N R6E S30 BT visible on partially healed blaze.</p> <p>A pine, 8 ins. diam., bears S. 83½° E., 29 lks. dist., with scribe marks T22N R visible on partially healed blaze. (Record, 64 lks. dist.)</p> <p>A pine, 5 ins. diam., bears S. 27½° W., 64 lks. dist., with scribe marks T22N R5E S36 BT visible on partially healed blaze. (Record, 29 lks. dist.)</p> <p>A pine, 10 ins. diam., bears N. 55½° W., 27 lks. dist., with scribe marks T22N R5E S25 BT visible on partially opened blaze.</p> <p>Add the marks 2001 to the brass cap</p>
19.66	<p>N. 0°38' E., bet. secs. 25 and 30.</p> <p>Over heavily rolling land through dense pine timber.</p> <p>Point for the S. 1/16 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T22N R5E R6E S 1/16 S25 S30 2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
39.32	<p>Point for the 1/4 sec. cor. of secs. 25 and 30, determined by the method of irregular boundaries; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the East Boundary,
T. 22 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.96	<p align="center">T22N R5E R6E 1/4 S25 S30 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 0°25' E., beginning new measurement.</p> <p>The cor. of secs. 19, 24, 25 and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. T22N R5E R6E S24 S19 S25 S30 1941.</p> <p>from which the 1941 bearing trees</p> <p>A pine stump, 8 ins. diam., bears N. 26½° E., 34 lks. dist., with scribe marks BT visible on open blaze.</p> <p>A pine, 11 ins. diam., bears S. 66½° E., 19 lks. dist., with a healed blaze.</p> <p>A pine, 14 ins. diam., bears S. 31½° W., 64 lks. dist., with a healed blaze.</p> <p>A pine, 11 ins. diam., bears N. 51° W., 51 lks. dist., with a healed blaze.</p> <p>Add the marks 2001 to the brass cap.</p> <hr/> <p align="center">Dependent Resurvey of a Portion of the Subdivisional Lines, T. 22 N., R. 5 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p align="center">Restoring the resurvey executed by Horace M. Muscott and Claude F. Warner, in 1940-41</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 1°05' W., bet. secs. 35 and 36.</p> <p>Over nearly level land, across freeway median.</p>
0.80	<p>Center of pavement, W. bound lane, U.S. Interstate Highway 40, bears N. 60° W., and S. 60° E.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
3.426	Arizona Highway Department right-of-way station 1613+19.50 on the N. right-of-way of U.S. Interstate Highway 40, bears N. 60° W. and S. 67° E., monumented with a brass disk, set flush in the top of a concrete cylinder, 7 ins. diam., firmly set, projecting 4 ins. above ground.
10.045	The S-S 1/64 sec. cor. of secs. 35 and 36, established by Wallace R. Ott, Arizona Registered Land Surveyor No. 9431, in 1989, and recorded in the Coconino County recorder's office in Flagstaff, Az. Book 17, Page 7, monumented with a steel reinforcement rod, 3/4 in. diam., firmly set flush with the ground, with aluminum cap inscribed U.S. DEPARTMENT OF AGRICULTURE FOREST SERVICE and mkd. S-S 1/64 S35 S36 RLS 9431 1989.
14.11	AP 1 of a Tract of land between private and Coconino National Forest, established by Wallace R. Ott, Arizona Registered Land Surveyor No. 9431, in 1989, and recorded in the Coconino County recorder's office in Flagstaff, Az. Book 17, Page 7, monumented with a steel reinforcement rod, 3/4 in. diam., firmly set, 5 ins. below the ground, with aluminum cap inscribed U.S. DEPARTMENT OF AGRICULTURE FOREST SERVICE and mkd. AP1 S35 S36 RLS 9431 1989.
20.09	Point for the S. 1/16 sec. cor. of secs. 35 and 36, not monumented.
40.18	The 1/4 sec. cor. of secs. 35 and 36,, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. 1/4 S35 S36 1941.
	Add the marks T22N R5E 2001 to the brass cap.
	N. 0°46' W., beginning new measurement.
	Over gently rolling land, through scattered pine timber.
40.05	The cor. of secs. 25, 26, 35 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above ground, in a mound of stone, 3½ ft. base, ½ ft. high, with brass cap mkd. T22N R5E S26 S25 S35 S36 1941.
	from which an original bearing tree
	A pine, 39 ins. diam., bears N. 3° E., 38 lks. dist., with a healed blaze.
	from which the 1941 bearing trees
	A pine, 14 ins. diam., bears N. 65½° E., 97 lks. dist., with a healed blaze.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A pine, 16 ins. diam., bears S. 30° E., 54 lks. dist., with a healed blaze.</p> <p>A pine, 20 ins. diam., bears S. 18° W., 178 lks. dist., with a healed blaze.</p> <p>A pine, 17 ins. diam., bears N. 39½° W., 141 lks. dist., with a healed blaze.</p> <p>Add the marks 2001 to the brass cap.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°23' W., bet. secs. 25 and 36.</p> <p>Over rolling land through dense pine timber.</p>
20.93	<p>Point for the E. 1/16 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T22N R5E S25 E 1/16 ——— S36 2001</p> </div>
41.86	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The 1/4 sec. cor. of secs. 25 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above ground, in a mound of stone, 3 ft. base, to top with brass cap mkd. 1/4 S25 S36 1941.</p> <p>from which the 1941 bearing trees</p> <p>A pine, 11 ins. diam., bears S. 61½° E., 56 lks. dist., with a healed blaze.</p> <p>A pine, 10 ins. diam., bears N. 27½° W., 21 lks. dist., with scribe marks S25 BT visible on partially healed blaze.</p> <p>Add the marks T22N R5E 2001 to the brass cap.</p> <hr/> <p>N. 89°31' W., beginning new measurement.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
20.97	<p>Over gently rolling land through scattered pine timber.</p> <p>Point for the W. 1/16 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p align="center">T22N R5E S25 W 1/16 ——— S36 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
41.94	<p>The cor. of secs. 25, 26, 35 and 36.</p> <hr/>
40.09	<p>N. 0°24' E., bet. secs. 25 and 26.</p> <p>Over gently rolling land through scattered pine timber.</p> <p>The 1/4 sec. cor. of secs. 25 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. 1/4 S26 S25 1941.</p> <p>from which a 1941 bearing tree</p> <p align="center">A pine, 27 ins. diam., bears N. 40½° W., 210 lks. dist., with a healed blaze.</p> <p>Add the marks T22N R5E 2001 to the brass cap</p> <hr/>
44.09	<p>From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 85°56' W., bet. secs. 24 and 25.</p> <p>Over gently rolling land through scattered pine timber.</p> <p>The 1/4 sec. cor. of secs. 24 and 25, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd. S24 1/4 S25 1941.</p> <p>from which the remains of the 1941 bearing trees</p> <p align="center">A pine stump, 24 ins. diam., bears S. 7¾° W., 30 lks. dist., with scribe marks 5 BT visible on open blaze.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Add the marks T22N R5E 2001 to the brass cap.</p> <hr/>
	<p style="text-align: center;">Subdivision of Section 25, T. 22 N., R. 5 E., Gila and Salt River Meridian, Arizona</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 25 and 36.</p>
	<p>N. 0°59' W., on the N. and S. center line of sec. 25.</p>
	<p>Over gently rolling land through scattered pine timber.</p>
19.84	<p>Point for the center S. 1/16 sec. cor. of sec. 25, not monumented.</p>
39.68	<p>Point for the center 1/4 sec. cor. of sec. 25 at intersection with the E. and W. center line of sec. 25, not monumented.</p>
81.96	<p>The 1/4 sec. cor. of secs. 24 and 25.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp.</p>
	<p>N. 88°55' W., on the E. and W. center line of sec. 25.</p>
	<p>Over rolling land through dense pine timber.</p>
21.49	<p>Point for the center E. 1/16 sec. cor. of sec. 25, not monumented.</p>
42.98	<p>The point for the center 1/4 sec. cor. of sec. 25.</p>
83.97	<p>The 1/4 sec. cor. of secs. 25 and 26.</p> <hr/>
	<p style="text-align: center;">SE 1/4</p> <hr/>
	<p>From the E. 1/16 sec. cor. of secs. 25 and 36.</p>
	<p>N. 0°11' W., on the N. and S. center line of the SE 1/4 of sec. 25.</p>
	<p>Over gently rolling land through scattered pine timber.</p>
19.75	<p>Point for the SE 1/16 sec. cor. of sec. 25, at intersection with the E. and W. center line of the SE 1/4 of sec. 25.</p>

**Subdivision of Section 25,
T. 22 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.50	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T22N R5E SE 1/16 S25 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The point for the center E. 1/16 sec. cor. of sec. 25.</p> <hr/>
21.21	<p>From the S. 1/16 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp.</p> <p>N. 89°09' W., on the E. and W. center line of the SE 1/4 of sec. 25.</p> <p>Over rolling land through dense pine timber.</p> <p>The SE 1/16 sec. cor. of sec. 25.</p>
42.42	<p>The point for the center S. 1/16 sec. of sec. 25.</p> <hr/>
<p>Subdivision of Section 36, T. 22 N., R. 5 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
10.015	<p>From the 1/4 sec. cor. of secs. 1 and 36, on the S. bdy. of the Tp.</p> <p>N. 0°22' E., on the N. and S. center line of sec. 36.</p> <p>Over flat open prairie.</p> <p>Point for the center S-S 1/64 sec. cor. of sec. 36. Found a steel reinforcement rod, ½ in. diam., 18 ins. long, lying loose nearby.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22N R5E C-S-S 1/64 S36 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Subdivision of Section 36,
T. 22 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Bury the reinforcement rod alongside the stainless steel post.
20.03	Point for the center S. 1/16 sec. cor. of sec. 36, not monumented.
40.06	Point for the center 1/4 sec. cor. of sec. 36, at intersection with the E. and W. center line of sec. 36, occupied with an iron pipe, 1½ ins. diam., firmly set, projecting 1 in. above ground, origin unknown, with a steel reinforcement rod, ½ in. diam., firmly set, projecting 2 ins. above the ground alongside, with a tag mkd. LS 2473. The State Board of Technical Registration lists this LS number to Wilfred Hanson (deceased), his record for this cor. was not located. Not remonumented.
79.89	The 1/4 sec. cor. of secs. 25 and 36.
	<hr/> <p>From the 1/4 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp.</p> <p>N. 89°48' W., on the E. and W. center line of sec. 36.</p> <p>Over rolling land through scattered pine timber.</p>
40.65	The center 1/4 sec. cor. of sec. 36.
61.225	Point for the center W. 1/16 sec. cor. of sec. 36, occupied with an iron pipe, 21 ins. long, 1½ ins. diam., firmly set, projecting 1 in. above ground, origin unknown, with a steel reinforcement rod, 15 ins. long, ½ in. diam., firmly set, projecting 2 ins. above the ground alongside, with a tag mkd. LS 2473. The State Board of Technical Registration lists this LS number to Wilfred Hanson (deceased), his record for this cor. was not located.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T22N R5E W 1/16 C ——— C S36 2001</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Bury the iron pipe and the reinforcement rod alongside the stainless steel post.
81.80	The 1/4 sec. cor. of secs. 35 and 36.

**Subdivision of Section 36,
T. 22 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	SW 1/4
	<hr/> <p>From the point for the W. 1/16 sec. cor. of secs. 1 and 36, on the S. bdy. of the Tp.</p> <p>N. 0°21' W., on the N. and S. center line of the SW 1/4 of sec. 36.</p> <p>Over nearly level land.</p>
10.03	<p>Point for the center S-SW 1/64 sec. cor. of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T22N R5E C-S-SW 1/64 S36 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, a steel reinforcement rod, ½ in. diam., firmly set flush with the ground, with plastic cap mkd. LS 16097, bears S. 29°48' E., 0.05 ch. dist. This monument was set by Gregory L. Allen, Arizona Registered Land Surveyor No. 16097, as the corner of a parcel of private land.</p>
20.06	<p>Point for the SW 1/16 sec. cor. of sec. 36 at intersection with the E. and W. center line of the SW 1/4 of sec. 36, not monumented.</p>
40.12	<p>The center W. 1/16 sec. cor. of sec. 36.</p> <hr/> <p>From the point for the center S. 1/16 sec. cor. of sec. 36.</p> <p>N. 89°53' W., on the E. and W. center line of the SW 1/4 of sec. 36.</p> <p>Over nearly level land.</p>
20.32	<p>The point for the SW 1/16 sec. cor. of sec. 36.</p>
40.64	<p>The point for the S. 1/16 sec. cor. of secs. 35 and 36.</p> <hr/> <p>From the center S-S 1/64 sec. cor. of sec. 36.</p>

**Subdivision of Section 36,
T. 22 N., R. 5 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>N. 89°55' W., on the E. and W. center line of the SE 1/4 of the SW1/4 of sec. 36.</p> <p>Over nearly level land.</p>
1.99	<p>From this point, a steel reinforcement rod, ½ in. diam., firmly set, projecting 5 ins. above ground, with a plastic cap mkd. RLS 16827, bears North, 0.01 ch. dist. This monument was set by Lee Martin Del Giorgio, Arizona Registered Land Surveyor No. 16827, as the corner of a parcel of private land.</p>
3.99	<p>From this point, a steel reinforcement rod, ½ in. diam., firmly set, projecting 5 ins. above ground, with a plastic cap mkd. RLS 18548, bears North, 0.01 ch. dist. This monument was set by Martin H. Martin, Arizona Registered Land Surveyor No. 18548, as the corner of a parcel of private land.</p>
6.99	<p>From this point, a steel reinforcement rod, ½ in. diam., firmly set, projecting 10 ins. above ground, with a plastic cap mkd. RLS 16827, bears North, 0.01 ch. This monument was set by Lee Martin Del Giorgio, Arizona Registered Land Surveyor No. 16827, as the corner of a parcel of private land.</p>
14.11	<p>From this point, a steel reinforcement rod, ½ in. diam., firmly set, projecting 4 ins. above ground, with a plastic cap mkd. RLS 18215, bears South, 0.06 ch. dist. This monument was set by James A. Folkers, Arizona Registered Land Surveyor No. 18215 in 1994, as the corner of a parcel of private land.</p>
20.20	<p>The center S-SW 1/64 sec. cor. of sec. 36.</p> <hr/> <p style="text-align: center;">NW 1/4</p> <hr/> <p>From the center W. 1/16 sec. cor. of sec. 36.</p> <p>N. 0°12' W., on the N. and S. center line of the NW 1/4 of sec. 36.</p>
39.94	<p>The W. 1/16 sec. cor. of secs. 25 and 36.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>The area encompassed by this survey is located 10 miles west of Flagstaff, Arizona, and is referred to locally as Bellemont, Arizona. U. S. Interstate Highway 40 runs NW and SE across the SW cor. of sec. 36. Abandoned U. S. Highway 66 runs E. and W. along the S. bdy. of the Tp. There are numerous Forest Service roads and trails throughout the area. The elevation of this</p>

T. 22 N., R. 5 E., Gila and Salt River Meridian, Arizona

CHAINS

area is between 7,200 and 7,800 feet above sea level. The terrain varies from nearly level in the SW portion to steep and mountainous in the NE portions. The SW 1/4 of sec. 36 is open sage brush with the rest of the area covered with pine timber from scattered stands to very dense thickets.

The principle use of this area is livestock grazing and camping. The Bellemont Travel Center truck stop is located in the S ½ of the S ½ of the SW 1/4 of sec. 36. There is no notable mineral activity.

The mean magnetic declination was observed to be $14\frac{1}{4}^{\circ}$ E.

CERTIFICATE OF SURVEY

I, Dale C. Wilson, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 30th day of May, 2001, I have dependently resurveyed a portion of the south and east boundaries and a portion of the subdivisional lines and subdivided sections 25 and 36, T. 22 N., R. 5 E., Gila and Salt River Meridian, Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

10/16/01

(Date)

Dale C. Wilson

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the south and east boundaries and a portion of the subdivisional lines and the subdivision of sections 25 and 36, T. 22 N., R. 5 E., Gila and Salt River Meridian, Arizona, executed by Dale C. Wilson, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

November 26, 2001

(Date)

Kenny A. Roark

(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 22 N., R. 5 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____~~
(Date)

~~_____~~
(Chief Cadastral Surveyor of Arizona)