

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY OF A  
PORTION OF THE EAST BOUNDARY  
AND A PORTION OF THE SUBDIVISIONAL LINES  
AND  
THE SUBDIVISION OF SECTION 24,  
TOWNSHIP 17 SOUTH, RANGE 23 EAST,  
OF THE GILA AND SALT RIVER MERIDIAN,  
IN THE STATE OF ARIZONA

EXECUTED BY

W. William Foster, Cadastral Surveyor

Under Special Instructions dated September 5, 2001, approved September 5, 2001, which provided for the surveys included under Group No. 877, and assignment instructions dated September 5, 2001.

Survey commenced September 9, 2001

Survey completed September 25, 2001

# INDEX DIAGRAM

TOWNSHIP 17 SOUTH

RANGE 23 EAST

|    |    |    |    |    |             |
|----|----|----|----|----|-------------|
| 6  | 5  | 4  | 3  | 2  | 1           |
| 7  | 8  | 9  | 10 | 11 | 12          |
| 18 | 17 | 16 | 15 | 14 | 13          |
| 19 | 20 | 21 | 22 | 23 | 6<br>5 24 2 |
| 30 | 29 | 28 | 27 | 26 | 4<br>25     |
| 31 | 32 | 33 | 34 | 35 | 36          |

## T. 17 S., R. 23 E., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the dependent resurvey of a portion of the east boundary and a portion of the subdivisional lines and the subdivision of section 24, T. 17 S., R. 23 E., Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this resurvey is as follows:

John A. Rockfellow surveyed the east boundary in 1902. Francis B. Jacobs surveyed a portion of the subdivisional lines in 1902. Dupree R. Averill and Roger F. Wilson resurveyed the west boundary, portions of the north boundary and subdivisional lines and surveyed portions of the south and north boundaries and subdivisional lines in 1925. Louis D. Gilbert remonumented certain original corners on the east boundary in 1970.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated September 5, 2001, for Group No. 877, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 4700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from second order Arizona Department of Transportation triangulation station FARM 1982, as published by the National Geodetic Survey, NAD 83 (1992). The geographic position of the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., is as follows:

Latitude: 31° 56' 03.28" N.      Longitude: 109° 56' 56.25" W.

The mean magnetic declination is 11¼° E.

---

**Dependent Resurvey of a Portion of the East Boundary,  
T. 17 S., R. 23 E., Gila and Salt River Meridian, Arizona**

---

Restoring the survey executed by  
John A. Rockfellow, in 1902

---

Dependent Resurvey of a Portion of the East Boundary,  
T. 17 S., R. 23 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |      |  |      |      |        |     |       |     |      |     |      |  |
|--------|--|------|--|------|------|--------|-----|-------|-----|------|-----|------|--|
|        | <p>Beginning at the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with a granite stone, 18 X 8 X 6 ins., firmly set, projecting 17 ins. above ground, mkd. with 2 notches on the S. and 4 notches on the N. edges.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <table data-bbox="850 638 1029 821" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T17S</td></tr> <tr><td style="text-align: center;">R23E</td><td style="text-align: center;">R24E</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S30</td></tr> <tr><td colspan="2" style="text-align: center;">2001</td></tr> </table> <p>Cor. is located S. 70° W., 6lks. dist. of fence cor., with fences extending N. and E.</p> <p>Deposit a magnet in a white plastic case and the original stone at the base of the stainless steel post.</p> <p>From this cor. point, Arizona Department of Transportation triangulation station FARM 1982, bears N. 57°37' E., 529.26 chs. dist., monumented with a standard brass disk, 3 ins. diam., cemented in a concrete cylinder, 12 ins. diam., firmly set, flush with ground, with top mkd. FARM 1982 and a triangle.</p> <p>N. 0°07' E., bet. secs. 19 and 24, on the E. bdy. of the Tp.</p> <p>Across level ground, through medium undergrowth.</p> | T17S |  | R23E | R24E | S24    | S19 | ----- |     | S25  | S30 | 2001 |  |
| T17S   |  |      |  |      |      |        |     |       |     |      |     |      |  |
| R23E   | R24E   |      |  |      |      |        |     |       |     |      |     |      |  |
| S24    | S19  |      |  |      |      |        |     |       |     |      |     |      |  |
| -----  |  |      |  |      |      |        |     |       |     |      |     |      |  |
| S25    | S30  |      |  |      |      |        |     |       |     |      |     |      |  |
| 2001   |  |      |  |      |      |        |     |       |     |      |     |      |  |
| 20.03  | <p>The S. 1/16 sec. cor. of secs. 19 and 24, established by Ted D. Amox, Arizona Registered Land Surveyor, No. 19315, in 1996, and recorded in the Cochise County Recorder's office in Benson, Az., book 10, page 74, monumented with an iron pipe, 5/8 in. diam., firmly set, projecting 11 ins. above ground, with aluminum cap mkd. RLS 19315. This is accepted as a careful and faithful determination of the corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <table data-bbox="850 1759 1029 1906" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T17S</td></tr> <tr><td style="text-align: center;">R23E</td><td style="text-align: center;">R24E</td></tr> <tr><td colspan="2" style="text-align: center;">S 1/16</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">2001</td></tr> </table>   | T17S |  | R23E | R24E | S 1/16 |     | S24   | S19 | 2001 |     |      |  |
| T17S   |  |      |  |      |      |        |     |       |     |      |     |      |  |
| R23E   | R24E   |      |  |      |      |        |     |       |     |      |     |      |  |
| S 1/16 |  |      |  |      |      |        |     |       |     |      |     |      |  |
| S24    | S19  |      |  |      |      |        |     |       |     |      |     |      |  |
| 2001   |  |      |  |      |      |        |     |       |     |      |     |      |  |

Dependent Resurvey of a Portion of the East Boundary,  
T. 17 S., R. 23 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | <p>Deposit a magnet in a white plastic case and the rebar, 16 ins. long, at the base of the stainless steel post.</p> <p>Cor. is located under a fence, bears N. and S .</p> <p>From this cor. point, a rusted iron pipe, 1 in. diam., firmly set, projecting 8 ins. above ground, bears S. 1°46' W., 0.27 ch. dist., origin unknown.</p> <hr/> <p>N. 0°07' E., beginning new measurement.</p> <p>Across level ground, through medium undergrowth.</p>  |
| 20.03  | <p>The 1/4 sec. cor. of secs. 19 and 24, reestablished at proportionate dist. by Ted D. Amox, Arizona Registered Land Surveyor No. 19315, in 1996, and recorded in the Cochise County Recorder's office in Benson, Az., book 10, page 74, monumented with an iron pipe, 2½ ins. diam., firmly set, flush with ground, with a 2½ in. diam. brass cap seated in the top mkd. 1/4 S24 S19 RLS19315. This is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>Cor. is located 9 lks. W. of fence cor., with fences extending N., E. and S. and 28 lks. N. of corral fence, bears W.</p> <p>From this cor. point, a rusted iron pipe, 1 in. diam., firmly set, flush with ground, bears S. 10°06' E., 0.39 ch. dist., origin unknown.</p> <hr/> <p>N. 0°07' E., beginning new measurement.</p> <p>Across level ground, through medium undergrowth.</p> |
| 20.03  | <p>Point for the N. 1/16 sec. cor. of secs. 19 and 24, not monumented.</p>  |
| 39.52  | <p>A graded road, 45 lks. wide, bears N. 40° E. and S. 40° W.</p>   |
| 40.06  | <p>The cor. of secs. 13, 18, 19 and 24, reestablished by Charles C. Doak, Arizona Registered Surveyor No. 4476, in 1973, monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, in a collar of stone, with brass cap mkd. R23E R24E USFS LS4476 13 18 24 19 T17S 1973.</p> <p>From this cor. point, the cor. of secs. 7, 12, 13 and 18, bears N. 0°06' E., 80.00 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T17S R23E R24E S12 S7 S13 S18 1970.</p>   |

**Dependent Resurvey of a Portion of the East Boundary,  
T. 17 S., R. 23 E., Gila and Salt River Meridian, Arizona**

| CHAINS |   |
|--------|---|
|        | <p>From this same cor. point, a fence cor. bears N., 1.09 chs. dist. with fences extending N. and S. 60° W.</p> <hr/> <p><b>Dependent Resurvey of a Portion of the Subdivisional Lines,<br/>T. 17 S., R. 23 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>Restoring the survey executed by<br/>Francis B. Jacobs, in 1902, and the resurvey executed by<br/>Dupree R. Averill and Roger F. Wilson, in 1925</p> <hr/> <p>From the cor. of secs 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 24 and 25.</p> <p>Over mountainous terrain, through medium timber.</p>   |
| 19.81  | <p>Point for the E. 1/16 sec. cor. of secs. 24 and 25, not monumented.</p>  |
| 39.62  | <p>The 1/4 sec. cor. of secs 24 and 25, monumented with a granite stone, 20 X 10 X 5 ins., firmly set, projecting 12 ins. above ground, mkd. with 1 on the N. face, with an iron post, 1 in. diam., 36 ins. long, firmly set, projecting 18 ins. above ground, with brass cap mkd. 1/4 S24 S25 1925 alongside the stone.</p> <p>from which the remaining 1925 bearing tree</p> <p style="padding-left: 40px;">An oak, 10 ins. diam., dead and down, bears S. 35° W., 64 lks dist., mkd. 1/4 S25 BT on open blaze. (Record: S. 36½° W., 66 lks. dist.)</p> <p>At the corner point</p> <p>Reset the iron post, 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top.</p> <p>Bury the original stone alongside the iron post.</p> <p>Add the marks T17S R23E 2001 to the brass cap.</p> <p>Deposit a magnet in a white plastic case at the base of the iron post.</p> <hr/> <p>N. 89°31' W., beginning new measurement.</p> <p>Over mountainous land, through scattered timber and undergrowth.</p> |

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 23 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
| 39.33  | <p>The cor. of secs. 24 and 25 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above top of mound of stone, 6 ft. base, 2½ ft. high, with brass cap mkd. T17S R23E S23 S26 WC S24 S25 1925.</p> <p>Add the marks 2001 to the brass cap.</p> <p>Cor. located on top of a steep rocky bluff.</p> <hr/>  |
|        | <p>N. 1°04' W., on the W. bdy. of sec. 24.</p> <p>Over mountainous land, through scattered timber and undergrowth.</p>  |
| 39.58  | <p>The 1/4 sec. cor. of sec. 23 only, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above top of mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. 1/4 S23 1925.</p> <p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears. S. 79½° W., 23 lks. dist., mkd. BT in a partially healed blaze.</p> <hr/>  |
|        | <p>N. 1°04' W., beginning new measurement.</p> <p>Over mountainous land through scattered timber and undergrowth.</p>   |
| 0.34   | <p>The witness cor. to the 1/4 sec. cor. of sec. 24 only, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. WC 1/4 S24 1925.</p> <p>from which the remaining 1925 bearing tree</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 9° E., 45 lks. dist., mkd. 1/4 S24 WC BT on partially healed blaze. (Record: S. 12° E.)</p> |
|        | <p>Add the marks T17S R23E 2001 to the brass cap.</p> <p>Cor. is located at foot of steep bluff.</p> <hr/>  |
|        | <p>N. 0°56' W., beginning new measurement.</p> <p>Over mountainous land, through scattered timber and undergrowth.</p>  |
| 0.08   | <p>True point for the 1/4 sec. cor. of sec. 24 only, at proportionate dist.; falls on bluff, impracticable to monument.</p>   |

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 23 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
| 39.49  | <p>From this point, the witness cor. to the cor. of secs. 14 and 23 only, bears S. 89°43' W., 1.37 chs. dist., monumented with iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, in a mound of stone, with brass cap mkd. T17S R23E S14 S23 S24 WC 1925.</p> <p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">An oak, 12 in. diam., bears N. 52° W., 8 lks dist., with healed blaze.</p>  |
| 39.90  | <p>True point for the cor. of secs. 13 and 24 only, determined at record bearing and distance from the witness corner to the cor. of secs. 13 and 24 only, falls on the face of a stone bluff.</p> <p>From this point, the witness corner to the cor. of secs. 13 and 24 only, bears N. 0°03' W., 0.43 ch. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above a mound of stone, with brass cap mkd. T17S R23E S14 S13 S24 WC 1925.</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">An oak, 20 ins. diam., bears N. 71½° E., 69 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">An oak stump, 6 ins. diam., with dead and down tree alongside, bears S. 66½° E., 24 lks. dist., with rotted blaze.</p> <p>Add the marks 2001 to the brass cap.</p> <p>The witness corner is located in a rocky ravine with scattered timber and undergrowth.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°56' W., bet. secs. 13 and 24.</p> <p>Over rolling land, through scattered trees and medium undergrowth.</p> |
| 20.71  | <p>The E. 1/16 sec. cor. of secs. 13 and 24, established by Wallace L. Craig, Arizona Registered Land Surveyor No. 20354, in 2001, and recorded in the Cochise County Recorder's office in Benson, Az., book 17, page 25, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd. E 1/16 13 24 LS20354 2000. This is accepted as a careful and faithful establishment of the cor. position.</p>   |



Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 23 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | <p>from which bearing trees mkd. by Craig</p> <p>A sycamore, 18 ins. diam., bears N. 47° E., 38 lks. dist., with a healed blaze.</p> <p>A canyon hackberry, 18 ins. diam., bears N. 14° W., 25 lks. dist., with scribe marks BT visible on partially opened blaze.</p> <hr/> <p>S. 89°56' W., beginning new measurement.</p> <p>Over rolling land, through scattered trees and medium undergrowth.</p>  |
| 20.71  | <p>The 1/4 sec. cor. of secs. 13 and 24, monumented with a granite stone, 20 x 10 x 8 ins., firmly set, projecting 10 ins. above ground, mkd. 1/4 on the N. face, with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 8 ins. above ground alongside, with brass cap mkd. 1/4 S13 S24 1925.</p> <p>At the corner point</p> <p>Reset the iron post, 28 ins. in the ground.</p> <p>Bury the original stone alongside.</p> <p>Add the marks T17S R23E 2001 to the brass cap.</p> <p>Deposit a magnet in a white plastic case at the base of the iron post.</p> <p>Cor. is located 1 lk. N. of fence cor., with 4 strand barb wire fences extending E. and S.</p> <hr/> |
| 32.17  | <p>N. 89°58' W., beginning new measurement.</p> <p>Over rolling land, gradually ascending.</p> <p>The witness point bet. secs. 13 and 24, monumented with a (+) chiseled on the SE face of bluff and WP chiseled alongside, directly above a mound of stone, 4 ft. base, 2 ft. high at the base of the bluff.</p> <p>from which the 1925 bearing trees</p> <p>An oak, 10 ins. diam., bears N. 5½° E., 47 lks. dist., with a healed blaze.</p>   |

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 23 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
|        | <p>An oak, dead and down, 8 ins. diam., bears S. 17½° W., 25 lks. dist. mkd. with illegible scribe marks on a rotted blaze.</p> <hr/> <p>N. 89°52' W., beginning new measurement.</p>  |
| 6.93   | <p>The true point for the cor. of secs. 13 and 24 only.</p> <hr/>  |
|        | <p style="text-align: center;"><b>Subdivision of Section 24,<br/>T. 17 S., R. 23 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>   |
|        | <p>From the 1/4 sec. cor. of secs. 24 and 25.</p> <p>N. 1°10' W., on the N. and S. centerline of sec. 24.</p> <p>Over rolling land, through medium timber and undergrowth.</p>   |
| 20.105 | <p>Point for the center S 1/16 sec. cor. of sec. 24, not monumented.</p>   |
| 40.21  | <p>Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E. and W. center line of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 3 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T17S R23E<br/>C 1/4 S24<br/>2001</p>   |
|        | <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 5 lks. E. of Cochise Stronghold Road, 33 lks. wide, bears N. 18° E. and S. 26° W.</p> <p>From this cor. point, an aluminum post, 1 in. diam., firmly set, projecting 12 ins. above ground, in an old rusted open end iron pipe, 2 ins. diam., with aluminum cap mkd. C 1/4 S24 LS20354, bears S. 1°58' E., 0.23 ch. dist. This point was established by person(s) unknown and perpetuated by Wallace L. Craig, Arizona Registered Land Surveyor No. 20354, in 2001, and is not adopted in the course of this survey.</p> |
| 60.16  | <p>Point for the center N 1/16 sec. cor. of sec. 24, falls in Cochise Stronghold Road.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 6 ins. below the ground, with brass cap mkd.</p>  |

Subdivision of Section 24,  
T. 17 S., R. 23 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
|        | T17S R23E<br>C<br>N 1/16   S24<br>C<br>2002  |
|        | <p>from which</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 25 ins. in the ground for a reference monument, bears N. 1°33' E., 19.4 ft. dist., with brass cap mkd. RM T17S R23E 1/16 S24 19.4 FT 2002 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for a reference monument, bears S. 89°56' E., 37.2 ft. dist., with brass cap mkd. RM T17S R23E 1/16 S24 37.2 FT and an arrow pointing to the corner.</p> <p>Cor. is located at the intersection of Cochise Stronghold Road, 22 lks. wide, bears N. 38° E. and S. 14° W. with a forest service road, 22 lks. wide, bears N. 50° W. A cattle guard across Cochise Stronghold Road, 12 lks. wide, 22 lks. long, bears N. 53° E., 0.50 ch., dist.</p> |
| 80.11  | <p>The 1/4 sec. cor. of secs. 13 and 24.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy of the Tp.</p> <p>N. 89°49' W., on the E. and W. centerline of sec. 24.</p> <p>Over rolling land, through medium timber and undergrowth.</p>  |
| 20.26  | <p>Point for the center E. 1/16 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">             T17S R23E<br/>                       E 1/16<br/>             C ——— C<br/>                       S24<br/>                       2001           </p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>  |

**Subdivision of Section 24,  
T. 17 S., R. 23 E., Gila and Salt River Meridian, Arizona**

| CHAINS |  |
|--------|--|
|        | <p>From this cor. point, an aluminum post, 1 in. diam., firmly set, in a mound of stone, 3 ft. base, 1 ft. high, with aluminum cap mkd. C-E 1/16 S24 LS20354, bears S. 5°24' E., 0.18 ch. dist. This point was established by person(s) unknown with an iron pipe, ½ in. diam., and perpetuated by Wallace L. Craig, Registered Land Surveyor No. 20354, in 2001, and is not adopted in the course of this survey.</p> <p>from which</p> <p style="padding-left: 40px;">A rock, mkd. B+R, bears N. 89¼° E., 11½ lks. dist.</p>   |
| 40.52  | The center 1/4 sec. cor. of sec. 24.   |
| 79.78  | The true point for the 1/4 sec. cor. of sec. 24 only.  |
|        | <hr/> <p>NE 1/4</p> <hr/>  |
| 19.99  | <p>From the center E 1/16 sec. cor. of sec 24.</p> <p>N. 0°31' W., on the N. and S. centerline of the NE 1/4 of sec. 24.</p> <p>Over rolling land, through scattered timber and under growth.</p> <p>Point for the NE 1/16 sec. cor. of sec. 24, at intersection with the E. and W. centerline of the NE 1/4 of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 17 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T17S R23E<br/>NE 1/16 S24<br/>2002</p> <p>Cor. is located N. 65° W., 10 lks. dist. of fence cor., with 4 strand barb wire fence extending West and 5 strand barb wire fence extending N. 30° E.</p> |
| 39.98  | The E. 1/16 sec. cor. of secs. 13 and 24.  |
|        | <hr/> <p>From the N. 1/16 sec. cor. of secs. 19 and 24 on the E. bdy. of the Tp.</p> <p>N. 89°56' W., on the E. and W. centerline of the NE 1/4 of sec. 24.</p> <p>Over rolling land through scattered cactus and grasses.</p>   |

Subdivision of Section 24,  
T. 17 S., R. 23 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
| 20.485 | The NE 1/16 sec. cor. of sec. 24.   |
| 40.97  | The center N 1/16 sec. cor. of sec. 24.   |
| SE 1/4 |   |
|        | <hr style="width: 30%; margin: auto;"/> <p>From the point for the E. 1/16 sec. cor. of secs. 24 and 25.<br/>N. 0°31' W., on the N. and S. centerline of the SE 1/4 of sec. 24.<br/>Over mountainous land, through scattered timber and undergrowth.</p> |
| 20.07  | Point for the SE 1/16 sec. cor. of sec. 24, at intersection with the E. and W. centerline of the SE 1/4 of sec. 24, not monumented.   |
| 30.09  | Point for the center N-SE 1/64 sec. cor. of sec. 24.<br><br>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.  |
|        | T17S R23E<br>S 24<br>C-N-SE<br>1/64<br>2001   |
|        | Deposit a magnet in a white plastic case at the base of the stainless steel post.   |
| 40.14  | The center E. 1/16 sec. cor. of sec. 24.  |
|        | <hr/> <p>From the S. 1/16 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp.<br/>N. 89°55' W., on the E. and W. centerline of the SE 1/4 of sec. 24.<br/>Over mountainous land, through medium timber and undergrowth.</p>                         |
| 5.01   | Point for the center E-E-SE 1/256 sec. cor. of sec. 24.<br><br>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a collar of stone, with brass cap mkd.  |

Subdivision of Section 24,  
T. 17 S., R. 23 E., Gila and Salt River Meridian, Arizona

| CHAINS |   |
|--------|---|
|        | T17S R23E<br>S 24<br>C-E-E-SE<br>1/256<br>2001  |
|        | Deposit a magnet in a white plastic case at the base of the stainless steel post.   |
|        | Cor. is located 2 lks. W. of fence cor., with 4 strand barb wire fences extending N. and E.                               |
| 20.04  | The point for the SE 1/16 sec. cor. sec. 24.  |
| 40.07  | The point for the center S. 1/16 sec. cor. of sec. 24.  |
|        | <hr/> From the center E-E-SE 1/256 sec. cor. of sec. 24.  |
|        | N. 0°02' W., on the N. and S. centerline of the SE 1/4 of the NE 1/4 of the SE 1/4 of sec. 24.                            |
|        | Over mountainous land, through scattered trees and undergrowth.   |
| 5.01   | Point for the SE-NE-SE 1/256 sec. cor. of sec. 24.  |
|        | Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a collar of stone, with brass cap mkd. |
|        | T17S R23E<br>S 24<br>SE-NE-SE<br>1/256<br>2001  |
|        | Deposit a magnet in a white plastic case at the base of the stainless steel post.   |
|        | <hr/> N. 89°53' W., on the E. and W. centerline of the SE 1/4 of the NE 1/4 of the SE 1/4 of sec. 24.                     |
|        | Over mountainous land, through scattered trees and undergrowth.   |
| 5.025  | Point for the center S-NE-SE 1/256 sec. cor. of sec. 24, not monumented.  |
|        | <hr/> N. 89°53' W., on the E. and W. centerline of the SW 1/4 of the NE 1/4 of the SE 1/4 of sec. 24.                     |
|        | Over mountainous land, through scattered trees and undergrowth.   |

Subdivision of Section 24,  
T. 17 S., R. 23 E., Gila and Salt River Meridian, Arizona

| CHAINS |  |
|--------|--|
| 5.025  | <p>Point for the SW-NE-SE 1/256 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T17S R23E<br/>S 24<br/>SW-NE-SE<br/>1/256<br/>2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 0°22' W., on the N. and S. centerline of the SW 1/4 of the NE 1/4 of the SE 1/4 of sec. 24.</p> <p>Over mountainous land, through scattered trees and undergrowth.</p> |
| 5.02   | <p>Point for the center W-NE-SE 1/256 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T17S R23E<br/>S 24<br/>C-W-NE-SE<br/>1/256<br/>2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 89°52' W., on the E. and W. centerline of the NE 1/4 of the SE 1/4 of sec. 24.</p> <p>Over mountainous land, through scattered trees and undergrowth.</p>       |
| 5.02   | <p>The center N-SE 1/64 sec. cor. of sec. 24.</p> <hr/>  |

## T. 17 S., R. 23 E., Gila and Salt River Meridian, Arizona

| CHAINS | GENERAL DESCRIPTION   |
|--------|---|
|        | <p>The land in section 24 varies from nearly level in the NE 1/4, mountainous in the W 1/2 to rolling in the remainder. The vegetation is dominated by pine, oak, and cottonwood trees, with creosote and bunch grass.</p> <p>A ranch house and other farm buildings are located in the NE 1/4 and the SE 1/4 of the section.</p> <p>Access is by way of Cochise Stronghold Road, which crosses the section southwesterly from the NE 1/4 to the SW 1/4.</p> <p>The mean magnetic declination of <math>11\frac{1}{4}^{\circ}</math> E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.</p> |



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

| NAMES               | CAPACITY                  |
|---------------------|---------------------------|
| Dale C. Wilson      | Supervisory Land Surveyor |
| Richard M. McDonald | Surveying Technician      |
| Brian S. Helfrich   | Surveying Technician      |
| Benjamin P. Boon    | Surveying Technician      |
|                     |                           |
|                     |                           |
|                     |                           |
|                     |                           |
|                     |                           |
|                     |                           |
|                     |                           |
|                     |                           |
|                     |                           |
|                     |                           |
|                     |                           |
|                     |                           |
|                     |                           |
|                     |                           |
|                     |                           |
|                     |                           |
|                     |                           |
|                     |                           |
|                     |                           |
|                     |                           |

CERTIFICATE OF SURVEY

I, W. William Foster, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 5<sup>th</sup> day of September, 2001, I have dependently resurveyed a portion of the east boundary and a portion of the subdivisional lines and subdivided section 24, T. 17 S., R. 23 E., Gila and Salt River Meridian, Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

5/24/2002  
(Date)

W. William Foster  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the east boundary and a portion of the subdivisional lines and the subdivision of section 24, T. 17 S., R. 23 E., Gila and Salt River Meridian, Arizona, executed by W. William Foster, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

August 22, 2002  
(Date)

Kenny D Ravnikar  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 17 S., R. 23 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~\_\_\_\_\_~~  
~~(Date)~~

~~\_\_\_\_\_~~  
~~(Chief Cadastral Surveyor of Arizona)~~