

ORIGINAL

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE
DEPENDENT RESURVEY
OF THE SOUTH, WEST AND NORTH BOUNDARIES
AND THE SUBDIVISIONAL LINES,

TOWNSHIP 27 NORTH, RANGE 15 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

W. William Foster, Cadastral Surveyor

Under Special Instructions dated July 8, 2002, approved July 8, 2002, and Amended Special Instructions dated July 18, 2002, approved July 18, 2002, which provided for the surveys included under Group No. 891, and assignment instructions dated July 8, 2002.

Survey commenced July 17, 2002

Survey completed September 5, 2002

INDEX DIAGRAM

TOWNSHIP 27 NORTH

RANGE 15 EAST

13	12	11	11	10	9
8 6	47 5	38 4	32 3	26 2	20 1
46	46	38	31	25	19
8 7	45 8	37 9	31 10	25 11	19 12
45	44	36	30	24	18
7 18	43 17	36 16	30 15	24 14	18 13
43	43	35	29	23	17
7 19	42 20	35 21	29 22	23 23	16 24
41	41	34	28	22	16
6 30	40 29	33 28	27 27	22 26	15 25
40	40	33	27	21	14
6 31	39 32	32 33	26 34	20 35	13 36
5	4	4	3	2	2

T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of the south, west and north boundaries and the subdivisional lines, T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this resurvey is as follows:

John C. Smith surveyed a portion of the E. bdy. and a portion of the subdivision lines and subdivided certain sections by the three mile method, in 1891. L. D. Chillson surveyed a portion of the south boundary, in 1891. Sidney E. Blout resurveyed portions of south and east boundaries and a portion of the subdivisional lines and surveyed a portion of the south and east boundaries, the north and west boundaries and a portion of the subdivision lines, in 1908-09. The east boundary was dependently resurveyed by Joe R. Salazar, in 2002.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated July 8, 2002, and Amended Special Instructions dated July 18, 2002, for Group No. 891, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 4700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from first order U. S. Coast and Geodetic Survey triangulation stations N 70 1934 and W 70 1934, as published by the National Geodetic Survey, NAD 83 (1992). The geographic position of the southeast corner of the Tp., is as follows:

Latitude: 35° 41' 37.54" N. Longitude: 110° 40' 43.12" W.

The mean magnetic declination is 12½° E.

**Dependent Resurvey of the South Boundary,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Restoring the survey and resurvey executed by Sidney E. Blout, in 1908-09</p> <hr/>
	<p>Beginning at the cor. of Tps. 26 and 27 N., Rs. 15 and 16 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins., above ground, with brass cap mkd. T27N R15E R16E S36 S31 S1 S6 T26N 1908 2002 and witnessed by a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p>
	<p>N. 89°56' W., bet. secs. 1 and 36, on the S. bdy. of the Tp.</p>
	<p>Over rolling land, through scattered sage brush and native grasses.</p>
40.00	<p>The 1/4 sec. cor. of secs. 1 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 19 ins. above ground, in a scattered mound of stone, with brass cap mkd. 1/4 S36 S1 1909. Rebuild the mound of stone, 3 ft. base to top.</p>
	<p>Add the marks T27N R15E T26N 2002 to the brass cap.</p> <hr/>
	<p>N. 89°54' W., beginning new measurement.</p>
	<p>Over rolling land, through scattered sage brush and native grasses.</p>
39.98	<p>The cor. of secs. 1, 2, 35 and 36, monumented with an iron post, 3 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. R15E T27N T26N S35 S36 S2 S1.</p>
	<p>Add the marks 2002 to the brass cap.</p> <hr/>
	<p>N. 89°57' W., bet. secs. 2 and 35.</p>
	<p>Over level land.</p>
19.00	<p>Trail road, 12 ft. wide, bears N. 10° E. and S. 10° W.</p>
23.90	<p>Left bank, Oraibi Wash, 40 ft. high, bears N. 5° E. and S. 5° W.</p>
29.50	<p>Right bank, Oraibi Wash, 40 ft. high, bears N. 5° E. and S. 5° W.</p>
39.97	<p>Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the South Boundary,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T27N R15E S35 1/4 ——— S2 T26N 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Over level land.
79.94	The cor. of secs. 2, 3, 34 and 35, monumented with an iron post, 3 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. R15E T27N T26N S34 S35 S3 S2. Add the marks 2002 to the brass cap.
	N. 89°57' W., bet. secs. 3 and 34. Over level ground, through medium growth of scrub brush.
40.02	The 1/4 sec. cor. of secs. 3 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. 1/4 S34 S3 1909. Add the marks T27N R15E T26N 2002 to the brass cap.
	N. 89°56' W., beginning new measurement. Over level land.
4.41	East Right-of Way fence, barbed wire, 5 strand, bears N. 55° E. and S. 55° W.
7.03	Center line of Navajo-Hopi Road #2, bears N. 51° E. and S. 52° W.
9.45	West Right-of Way fence, barbed wire, 5 strand, bears N. 49° E. and S. 49° W.
40.02	The cor. of secs. 3, 4, 33 and 34, monumented with an iron post, 3 ins. diam., firmly set, flush with the ground, with brass cap mkd. R15E T27N T26N S33 S34 S4 S3. Add the marks 2002 to the brass cap. Cor. is located 3 ft. E. of an imbedded mound of stone.

**Dependent Resurvey of the South Boundary,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.98	<p>N. 89°57' W., bet. secs. 4 and 33.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T27N R15E S33 1/4 ——— S4 T26N 2002 </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>
79.96	<p>The cor. of secs. 4, 5, 32 and 33, monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. R15E T27N T26N S32 S33 S5 S4 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/>
40.01	<p>N. 89°57' W., bet. secs. 5 and 32.</p> <p>Over level to rolling land, through sage brush and native grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T27N R15E S32 1/4 ——— S5 T26N 2002 </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Dependent Resurvey of the South Boundary,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.02	<p>Over level to rolling land, through sage brush and native grasses.</p> <p>The cor. of secs. 5, 6, 31 and 32, monumented with an iron post, 3 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. R15E T27N T26N S31 S32 S6 S5.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/> <p>N. 89°56' W., bet. secs. 6 and 31.</p> <p>Over rolling to level land, through scattered cacti, sage brush and native grasses.</p>
39.97	<p>The 1/4 sec. cor. of secs. 6 and 31, monumented with the remains of the original iron post, 1 in. diam., 20 ins. long, firmly set, 6 ins. below the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R15E S31 1/4 ——— S6 T26N 2002</p> </div> <p>Deposit the remains of the iron post inside the stainless steel post and a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 89°58' W., beginning new measurement.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>
40.20	<p>The cor. of Tps. 26 and 27 N., Rs. 14 and 15 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T27N R14E R15E S36 S31 S1 S6 T26N 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/>

Dependent Resurvey of the West Boundary,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Restoring the survey executed by Sidney E. Blout, in 1908-09</p> <hr/>
	<p>From the cor. of Tps. 26 and 27 N., Rs. 14 and 15 E., hereinbefore described.</p> <p>N. 0°03' E., bet. secs. 31 and 36, on the W. bdy. of the Tp.</p> <p>Over level land, through scattered sage brush and native grasses.</p>
39.99	<p>The 1/4 sec. cor. of secs. 31 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. S36 1/4 S31 1909.</p> <p>Add the marks T27N R14E R15E 2002 to the brass cap.</p> <hr/>
	<p>N. 0°03' E., beginning new measurement.</p> <p>Over level land, through scattered sage brush and native grasses.</p>
40.00	<p>The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T27N R14E R15E S25 S30 S36 S31 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/>
	<p>N. 0°02' E., bet. secs. 25 and 30.</p> <p>Over level land, through scattered sage brush and native grasses.</p>
40.02	<p>The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. S25 1/4 S30 1909.</p> <p>Add the marks T27N R14E R15E 2002 to the brass cap.</p> <hr/>
	<p>North, beginning new measurement.</p> <p>Over level to rolling land, through sage brush and native grasses.</p>
40.02	<p>The cor. of secs. 19, 24, 25 and 30, monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. T27N R14E R15E S24 S19 S25 S30 1909.</p>

**Dependent Resurvey of the West Boundary,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Add the marks 2002 to the brass cap.</p> <hr/> <p>N. 0°01' E., bet. secs. 19 and 24.</p> <p>Over level to rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R14E R15E 1/4 S24 S19 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Over level land, through scattered sage brush and native grasses.</p>
80.00	<p>The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 3 ins. diam., firmly set, 13 ins. below the ground, with brass cap mkd. T27N R14E R15E S13 S18 S24 S19 1909.</p> <p>Left the top of the brass cap exposed.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/>
19.25	<p>N. 0°01' W., bet. secs. 13 and 18.</p> <p>Over level land, through scattered cacti, sage brush and native grasses.</p> <p>Trail road, 10 ft. wide, bears N. 57° E. and S. 57° W.</p>
40.01	<p>The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. S13 1/4 S18 1909.</p> <p>Add the marks T27N R14E R15E 2002 to the brass cap.</p> <hr/> <p>N. 0°01' W., beginning new measurement.</p>

**Dependent Resurvey of the West Boundary,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Over level land, through scattered cacti, sage brush and native grasses.</p> <p>The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R14E R15E S12 S7 S13 S18 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/> <p>N. 0°02' E., bet. secs. 7 and 12.</p> <p>Over rolling to level land, through scattered cacti, sage brush and native grasses.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R14E R15E 1/4 S12 S7 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Over level to rolling land, through scattered cacti, sage brush and native grasses.</p>
80.00	<p>The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R14E R15E S1 S6 S12 S7 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/> <p>N. 0°04' E., bet. secs. 1 and 6.</p> <p>Over rolling land, through scattered cacti, sage brush and native grasses.</p>
40.00	<p>The 1/4 sec. cor. of secs. 1 and 6, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. S1 1/4 S6 1909.</p> <p>Add the marks T27N R14E R15E 2002 to the brass cap.</p> <hr/>

**Dependent Resurvey of the West Boundary,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>N. 0°03' E., beginning new measurement.</p> <p>Over rolling to broken land, through scattered cacti, sage brush and native grasses.</p>												
39.96	<p>The cor. of Tps. 27 and 28 N., Rs. 14 and 15 E., determined from a mound of stone, 3 ft. base, 1 ft. high and witnessed with an imbedded second mound of stone, 3 ft base, 2 ft high, 5 ft. S. of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td colspan="2">T28N</td></tr> <tr><td>R14E</td><td>R15E</td></tr> <tr><td style="border-right: 1px solid black;">S36</td><td>S31</td></tr> <tr><td style="border-right: 1px solid black;">S1</td><td>S6</td></tr> <tr><td colspan="2">T27N</td></tr> <tr><td colspan="2">2002</td></tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of the North Boundary, T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Restoring the survey executed by Sidney E. Blout, in 1908-09</p> <hr/> <p>From the cor. of Tps. 27 and 28 N., Rs. 15 and 16 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. T28N R15E R16E S36 S31 S1 S6 R15E R16E T27N 2001 2002.</p> <p>From this cor. point, U. S. Coast and Geodetic Survey triangulation station N 70 1934, bears N. 27°18' E., 481.49 chs. dist., monumented with a standard brass disk, 3 ins. diam., cemented in a concrete post, 8 ins. square, firmly set, projecting 3 ins. above ground, with top mkd. N 70 1934 and a triangle.</p> <p>N. 89°58' W., bet. secs. 1 and 36, on the N. bdy. of the Tp.</p> <p>Over rolling land, through scattered cacti, sage brush and native grasses.</p>	T28N		R14E	R15E	S36	S31	S1	S6	T27N		2002	
T28N													
R14E	R15E												
S36	S31												
S1	S6												
T27N													
2002													

Dependent Resurvey of the North Boundary,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R15E S36 1/4 ——— S1 T27N 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Over rolling land, through scattered cacti, sage brush and native grasses.</p>
80.00	<p>The cor. of secs. 1, 2, 35 and 36, monumented with an iron post, 3 ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd. R15E T28N T27N S35 S36 S2 S1 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/> <p>N. 89°51' W., bet. secs. 2 and 35.</p> <p>Over rolling land, through scattered cacti, sage brush and native grasses.</p>
32.80	<p>Trail road, 10 ft. wide, bears N. 57° E. and S. 57° W.</p>
39.99	<p>The 1/4 sec. cor. of secs. 2 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. S35 1/4 S2 1909.</p> <p>Add the marks R15E T28N T27N and 2002 to the brass cap.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89°58' W., beginning new measurement.</p> <p>Over rolling land, through scattered cacti, sage brush and native grasses.</p>
40.01	<p>The cor. of secs. 2, 3, 34 and 35, monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. R15E T28N T27N S34 S35 S3 S2 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/>

**Dependent Resurvey of the North Boundary,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.99	<p>N. 89°58' W., bet. secs. 3 and 34.</p> <p>Over rolling land, through scattered cacti, sage brush and native grasses.</p> <p>The 1/4 sec. cor. of secs. 3 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. S34 1/4 S3 1909.</p> <p>Add the marks R15E T28N T27N 2002 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/>
40.01	<p>N. 89°58' W., beginning new measurement.</p> <p>Over rolling land, through scattered cacti, sage brush and native grasses.</p> <p>The cor. of secs. 3, 4, 33 and 34, monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. R15E T28N T27N S33 S34 S4 S3 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <hr style="width: 60%; margin: 10px auto;"/>
40.02	<p>N. 89°57' W., bet. secs. 4 and 33.</p> <p>Over rolling to level land, through scattered cacti, sage brush and native grasses.</p> <p>The 1/4 sec. cor. of secs. 4 and 33, monumented with a bent iron post, 1 in. diam., firmly set, with brass cap mkd. S33 1/4 S4 1909.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T28N R15E S33 1/4 _____ S4 T27N 2002 </div> <p>Bury the iron post alongside the stainless steel post and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>West, beginning new measurement.</p>

Dependent Resurvey of the North Boundary,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over level to rolling land, through scattered cacti, sage brush and native grasses.
8.25	Trail road, 10 ft. wide, bears N. 10° E. and S. 10° W.
40.01	The cor. of secs. 4, 5, 32 and 33, monumented with an iron post, 3 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. R15E T28N T27N S32 S33 S5 S4 1909.
	Add the marks 2002 to the brass cap.
	N. 89°58' W., bet. secs. 5 and 32.
	Over broken to rolling land, through scattered cacti, sage brush and native grasses.
19.20	Dry sandy wash, 25 ft. wide, 2 ft. deep, drains S. 57° E.
39.98	Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T28N R15E S32 1/4 ——— S5 T27N 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Over rolling to broken land, through scattered cacti, sage brush and native grasses.
79.96	Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.
	T28N R15E S31 S32 ——— S6 S5 T27N 2002

**Dependent Resurvey of the North Boundary,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.98	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 89°58' W., bet. secs. 6 and 31.</p> <p>Over rolling to broken land, through scattered cacti, sage brush and native grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T28N R15E S31 1/4 ——— S6 T27N 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Over broken land, through scattered cacti, sage brush and native grasses.</p>
79.34	<p>The cor. of Tps. 27 and 28 N., Rs. 14 and 15 E., hereinbefore described.</p> <hr/> <p align="center">Dependent Resurvey of the Subdivisional Lines, T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p align="center">Restoring the survey and resurvey executed by Sidney E. Blout, in 1908-09</p> <hr/>
39.94	<p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>North, bet. secs. 35 and 36.</p> <p>Over level land, through scattered sage brush and native grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor., falls in Oraibi Wash, impractical to monument.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 35 and 36, bears S. 77°53' W., 3.02 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>W C T27N R15E 1/4 → S35 S36 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Over level land, through scattered sage brush and native grasses.</p>
40.80	Right bank Oraibi Wash, bears N. 45°E. and S. 45°W.
79.88	<p>The cor. of secs. 25, 26, 35 and 36, monumented with an iron post, 2 ins. diam., firmly set, 12 ins. below the ground, with brass cap mkd. T27N R15E S26 S25 S35 S36 1909.</p> <p>Left the top of the brass cap exposed.</p> <p>Add the marks 2002 to the brass cap.</p>
	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. T27N R15E R16E S25 S30 S36 S31 1908 2002.</p> <p>West, bet. secs. 25 and 36.</p> <p>Over level land, through scattered sage brush and native grasses.</p>
33.50	Trail road, 10 ft. wide, bears N. 36° E. and S. 36° W.
39.99	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T27N R15E S25 1/4 ——— S36 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Over level land, through scattered sage brush and native grasses.
45.40	Left bank Oraibi Wash, bears N. 55° E. and S. 55° W.
54.40	Right bank Oraibi Wash, bears N. 67° E. and S. 55° W.
79.98	The cor. of secs. 25, 26, 35 and 36.
<hr/>	
	North, bet. secs. 25 and 26.
	Over level land, through scattered sage brush and native grasses.
36.18	Barbed wire fence, 5 strand, bears N. 45° E. and S. 45° W.
40.00	The 1/4 sec. cor. of secs. 25 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S26 1/4 S25 1909.
	Add the marks T27N R15E 2002 to the brass cap.
<hr/>	
	N. 0°01' W., beginning new measurement.
	Over level land, through scattered sage brush and native grasses.
39.97	The cor. of secs. 23, 24, 25 and 26, monumented with an iron post, 2 ins. diam., loosely set, projecting 18 ins. above ground, with brass cap mkd. T27N R15E S23 S24 S26 S25 1909.
	Reset the iron post, 27 ins. in the ground and add the marks 2002 to the brass cap.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
<hr/>	

Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. T27N R15E R16E S24 S19 S25 S30 1908 2002.</p>
	<p>S. 89°58' W., bet. secs. 24 and 25.</p>
	<p>Over level land, through scattered sage brush and native grasses.</p>
20.90	<p>Left bank Oraibi Wash, bears N. 40° E. and S. 30° E.</p>
30.10	<p>Right bank, Oraibi Wash, bears N. 49° E. and S. 30° E.</p>
39.99	<p>The 1/4 sec. cor. of secs. 24 and 25, monumented with the remains of an iron post, 1 in. diam., firmly set, 10 ins. below the ground.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R15E S24 1/4 ——— S25 2002</p>
	<p>Deposit the remains of iron post inside the stainless steel post and a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/>
	<p>S. 89°59' W., beginning new measurement.</p>
	<p>Over level land, through scattered sage brush and native grasses.</p>
11.90	<p>Trail road, 10 ft. wide, bears N. 12° E. and S. 12° W.</p>
39.97	<p>The cor. of secs. 23, 24, 25 and 26.</p> <hr style="width: 60%; margin: 10px auto;"/>
	<p>N. 0°03' W., bet. secs. 23 and 24.</p>
	<p>Over level land, through scattered sage brush and native grasses.</p>
27.93	<p>East Right-of Way fence, barbed wire, 4 strand, bears N. 45° E. and S. 42° W.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
30.46	Center line of Hopi Road #2, asphalt, 30 ft. wide, bears N. 37° E. and S. 40° W.
32.88	West Right-of Way fence, barbed wire, 4 strand, bears N. 37° E. and S. 40° W.
39.98	The 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. S23 1/4 S24 1909. Add the marks T27N R15E 2002 to the brass cap. <hr style="width: 20%; margin: 10px auto;"/> N. 0°04' W., beginning new measurement. Over level land, through scattered sage brush and native grasses.
39.97	The cor. of secs. 13, 14, 23 and 24, monumented with an iron post, 2 ins., diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T27N R15E S14 S13 S23 S24 190. Add the marks 2002 to the brass cap. <hr style="width: 60%; margin: 10px auto;"/> From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T27N R15E R16E S13 S18 S24 S19 2002. S. 89°55' W., bet. secs. 13 and 24. Over rolling to level land, through scattered sage brush and native grasses.
40.01	Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T27N R15E S13 1/4 ——— S24 2002</div> Deposit a magnet in a white plastic case at the base of the stainless steel post. Over level to rolling land, through scattered sage brush and native grasses.

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
45.30	East Right-of Way fence, barbed wire, 5 strand, bears N. 37° E. and S. 37° W.
47.15	Centerline of Hopi Road #2, asphalt, 30 ft. wide, bears N. 37° E. and S. 37° W.
48.99	West Right-of Way fence, barbed wire, 4 strand, bears N. 37° E. and S. 37° W.
80.02	The cor. of secs. 13, 14, 23 and 24.
	N. 0°02' W., bet. secs. 13 and 14.
	Over rolling to level land, through scattered sage brush and native grasses.
40.01	Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T27N R15E 1/4 S14 S13 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Over rolling to level land, through scattered sage brush, cacti and native grasses.
69.11	Barbed wire fence, 4 strand, bears S. 53° E. and N. 53° W.
80.02	The cor. of secs. 11, 12, 13 and 14, monumented with an iron post, 2 ins. diam., loosely set, projecting 4 ins. above ground, with brass cap mkd. T27N R15E S11 S12 S14 S13 190.
	Reset the iron post, 32 ins. in the ground and add the marks 2002 to the brass cap.
	From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T27N R15E R16E S12 S7 S13 S18 1908 2002.
	S. 89°55' W., bet. secs. 12 and 13.

Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.06	<p>Over rolling land, through scattered sage brush and native grasses.</p> <p>The 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S12 1/4 S13 1909.</p> <p>Add the marks T27N R15E 2002 to the brass cap.</p> <hr/> <p>S. 89°57' W., beginning new measurement.</p>
39.99	<p>Over rolling land, through scattered sage brush and native grasses.</p> <p>The cor. of secs. 11, 12, 13 and 14.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p>
40.00	<p>Over rolling land, through scattered sage brush and native grasses.</p> <p>The 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. S12 1/4 S11 1909.</p> <p>Brass cap oriented incorrectly. Remark the brass cap to reflect correct sections and add the marks T27N R15E 2002 to the brass cap.</p> <hr/> <p>N. 0°01' E., beginning new measurement.</p>
40.04	<p>Over rolling to level land, through scattered cacti, sage brush and native grasses.</p> <p>The cor. of secs. 1, 2, 11 and 12, monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. T27N R15E S2 S1 S11 S12 190.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. T27N R15E R16E S1 S6 S12 S7 1908 2002.</p> <p>S. 89°57' W., bet. secs. 1 and 12.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over level land, through scattered cacti, sage brush and native grasses.
40.02	The 1/4 sec. cor. of secs. 1 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. S1 1/4 S12 1909. Add the marks T27N R15E 2002 to the brass cap. <hr/>
	S. 89°58' W., beginning new measurement.
	Over level land, through scattered cacti, sage brush and native grasses.
40.01	The cor. of secs. 1, 2, 11 and 12. <hr/>
	N. 0°01' E., bet. secs. 1 and 2.
	Over rolling land, through scattered cacti, sage brush and native grasses.
6.35	Trail road, 10 ft. wide, bears S. 36° E. and N. 36° W.
40.00	The 1/4 sec. cor. of secs. 1 and 2, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. S2 1/4 S1 1909. Add the marks T27N R15E 2002 to the brass cap. <hr/>
	N. 0°02' W., beginning new measurement.
	Over rolling land, through scattered cacti, sage brush and native grasses.
40.10	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described. <hr/>
	From the cor. of 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.
	Over rolling land, through scattered cacti, sage brush and native grasses.
	N. 0°02' W., bet. secs. 34 and 35.
40.02	Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.04	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R15E 1/4 S34 S35 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Over rolling land, through scattered cacti, sage brush and native grasses.</p> <p>The cor. of secs. 26, 27, 34 and 35, monumented with a severely rusted and broken iron post, 2 ins. diam., loosely set, projecting 7 ins. above ground, with brass cap mkd. T27N R15E S27 S26 S34 S35 1909.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R15E S27 S26 ----- S34 S35 2002</p> <p>Deposit the iron post remnants inside the stainless steel post. and a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. located on W. bank of dry sandy wash, 25 ft. wide, 2½ ft. deep, drains S. 5° W.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89°50' W., bet. secs. 26 and 35.</p> <p>Over rolling land, through scattered cacti, sage brush and native grasses.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T27N R15E S26 1/4 ——— S35 2002</p>
79.96	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Over rolling land, through scattered cacti, sage brush and native grasses.</p> <p>The cor. of secs. 26, 27, 34 and 35.</p> <hr/>
14.91	<p>N. 0°02' W., bet. secs. 26 and 27.</p> <p>Over rolling land, through scattered cacti, sage brush and native grasses.</p> <p>Dry sandy wash, 15 ft. wide, 2 ft. deep, drains S. 38° E.</p>
40.00	<p>The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. S27 1/4 S26 1909.</p> <p>Add the marks T27N R15E 2002 to the brass cap.</p> <hr/>
40.00	<p>N. 0°03' W., beginning new measurement.</p> <p>Over rolling to broken land, through scattered cacti, sage brush and native grasses.</p> <p>The cor. of secs. 22, 23, 26 and 27, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. T27N R15E S22 S23 S27 S26 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/>
29.11	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°49' W., bet. secs. 23 and 26.</p> <p>Over rolling land, through scattered cacti, sage brush and native grasses.</p>
40.00	<p>Barbed wire fence, 4 strand, bears N. 42° E. and S. 42° W.</p> <p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R15E S23 1/4 ——— S26 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Over rolling land, through scattered cacti, sage brush and native grasses.</p>
80.00	<p>The cor. of secs. 22, 23, 26 and 27.</p> <hr/> <p>N. 0°02' W., bet. secs. 22 and 23.</p> <p>Over rolling land, through scattered cacti, sage brush and native grasses.</p>
36.00	<p>Trail road, 10 ft. wide, bears S. 62° E. and N. 62° W.</p>
40.02	<p>The 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. S22 1/4 S23 1909.</p> <p>Add the marks T27N R15E 2002 to the brass cap.</p> <hr/> <p>N. 0°03' W., beginning new measurement.</p> <p>Over rolling land, through scattered cacti, sage brush and native grasses.</p>
40.01	<p>The cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. T27N R15E S15 S14 S22 S23 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°46' W., bet. secs. 14 and 23.</p> <p>Over rolling land, through scattered cacti, sage brush and native grasses.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.98	<p>Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R15E S14 1/4 ——— S23 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Over rolling land, through scattered cacti, sage brush and native grasses.</p>
79.96	<p>The cor. of secs. 14, 15, 22 and 23.</p> <hr/>
40.00	<p>N. 0°02' W., bet. secs. 14 and 15.</p> <p>Over rolling land, through scattered cacti, sage brush and native grasses.</p>
40.04	<p>The 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. S15 1/4 S14 1909.</p> <p>Add the marks T27N R15E 2002 to the brass cap.</p> <hr/> <p>N. 0°01' E., beginning new measurement.</p> <p>Over rolling land, through scattered cacti, sage brush and native grasses.</p>
40.04	<p>The cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T27N R15E S10 S11 S15 S14 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89°46' W., bet. secs. 11 and 14.</p> <p>Over rolling land, through scattered cacti, sage brush and native grasses.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
35.90	Ascend to edge of mesa, bears N. 24° E. and S. 24° W.
39.98	<p>The 1/4 sec. cor. of secs. 11 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S11 1/4 S14 1909.</p> <p>Add the marks T27N R15E 2002 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°46' W., beginning new measurement.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>
39.94	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>N. 0°03' W., bet. secs. 10 and 11.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>
40.03	<p>The 1/4 sec. cor. of secs. 10 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. S10 1/4 S11 1909.</p> <p>Add the marks T27N R15E 2002 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°02' W., beginning new measurement.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>
15.48	Barbed wire fence, 5 strand, bears N. 45° W. and S. 45° E.
40.02	<p>The cor. of secs. 2, 3, 10 and 11, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T27N R15E S3 S2 S10 S11 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°45' W., bet. secs. 2 and 11.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.96	<p>The 1/4 sec. cor. of secs. 2 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S2 1/4 S11 1909.</p> <p>Add the marks T27N R15E 2002 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°46' W., beginning new measurement.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>
39.99	<p>The cor. of secs. 2, 3, 10 and 11.</p> <hr/> <p>N. 0°04' W., bet. secs. 2 and 3.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>
40.03	<p>The 1/4 sec. cor. of secs. 2 and 3, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S3 1/4 S2 1909.</p> <p>Add the marks T27N R15E 2002 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03' W., beginning new measurement.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>
6.40	<p>Trail road, 10 ft. wide, bears N. 55° E. and S. 55° W.</p>
39.88	<p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over rolling land, through scattered sage brush, cacti and native grasses.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.02	<p style="text-align: center;">T27N R15E 1/4 S33 S34 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Over rolling land, through scattered sage brush, cacti and native grasses.</p> <p>The cor. of secs. 27, 28, 33 and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. T27N R15E S28 S27 S33 S34 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/>
40.01	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°57' W., bet. secs. 27 and 34.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
80.02	<p style="text-align: center;">T27N R15E S27 1/4 ——— S34 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p> <p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/> <p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.01	<p>Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R15E 1/4 S28 S27 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>
46.10	Edge of mesa, bears S. 22° E. and N. 22° W.
80.02	<p>The cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. T27N R15E S21 S22 S28 S27 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89°56' W., bet. secs. 22 and 27.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>
12.60	Dry sandy wash, 30 ft. wide, 1 ft. deep, drains S. 17° W.
24.75	Dry sandy wash, 15 ft. wide, 2 ft. deep, drains S. 13° W.
40.03	<p>The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. S22 1/4 S27 1909.</p> <p>Add the marks T27N R15E 2002 to the brass cap.</p> <hr/> <p>N. 89°56' W., beginning new measurement.</p> <p>Over rolling to level land, through scattered sage brush and native grasses.</p>
39.99	The cor. of secs. 21, 22, 27 and 28.

Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS									
	N. 0°02' W., bet. secs. 21 and 22. Over level land.								
1.50	Edge of mesa, bears N. 45° E. and S. 45° W.								
40.02	The 1/4 sec. cor. of secs. 21 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. S21 1/4 S22 190. Add the marks T27N R15E 2002 to the brass cap.								

	N. 0°01' W., beginning new measurement. Over level land.								
40.00	Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.								
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 2px;">T27N</td> <td style="padding: 2px;">R15E</td> </tr> <tr> <td style="padding: 2px;">S16</td> <td style="padding: 2px;">S15</td> </tr> <tr> <td style="padding: 2px;">S21</td> <td style="padding: 2px;">S22</td> </tr> <tr> <td colspan="2" style="padding: 2px; text-align: center;">2002</td> </tr> </table>	T27N	R15E	S16	S15	S21	S22	2002	
T27N	R15E								
S16	S15								
S21	S22								
2002									
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								

	From the cor. of secs. 14, 15, 22 and 23. N. 89°56' W., bet. secs. 15 and 22. Over level land.								
34.15	Trail road, 10 ft. wide, bears S. 70° E. and N. 70° W.								
40.00	The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., firmly set, flush with the ground, with brass cap mkd. S15 1/4 S22 1909. Add the marks T27N R15E 2002 to the brass cap.								

	N. 89°57' W., beginning new measurement. Over level land.								

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.97	<p>The cor. of secs. 15, 16, 21 and 22.</p> <hr/> <p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over level land, through scattered sage brush and native grasses.</p>
5.75	<p>Right bank, dry sandy wash, bears E. and W.</p>
14.30	<p>Left bank, dry sandy wash, bears S. 30° E. and N. 26° W.</p>
40.00	<p>The 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. S16 1/4 S15 1909.</p> <p>Add the marks T27N R15E 2002 to the brass cap.</p> <hr/> <p>N. 0°01' W., beginning new measurement.</p> <p>Over rolling to level land, through scattered sage brush and native grasses.</p>
6.65	<p>Trail road, 10 ft. wide, bears S. 62° E. and N. 62° W.</p>
40.06	<p>The cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27N R15E S9 S10 S16 S15 1909.</p> <p>Add the marks 2002 to the cap.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°54' W., bet. secs. 10 and 15</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>
40.00	<p>The 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. S10 1/4 S15 1909.</p> <p>Add the marks T27N R15E 2002 to the brass cap.</p> <hr/> <p>N. 89°57' W., beginning new measurement.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.98	<p>The cor. of secs. 9, 10, 15 and 16.</p> <hr/> <p>N. 0°01' W., bet. secs. 9 and 10.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R15E 1/4 S9 S10 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>
70.30	<p>Trail road, 10 ft. wide, bears N. 52° E. and S. 52° W.</p>
80.04	<p>The cor. of secs. 3, 4, 9 and 10, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T27N R15E S4 S3 S9 S10 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/> <p>From the cor. secs. 2, 3, 10 and 11.</p> <p>N. 89°56' W., bet. secs. 3 and 10.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>
21.80	<p>Barbed wire fence, 3 strand, bears S. 38° E. and N. 38° W.</p>
39.96	<p>The 1/4 sec. cor. of secs. 3 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. S3 1/4 S10 1909.</p> <p>Add the marks T27N R15E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 89°55' W., beginning new measurement. Over rolling land, through scattered sage brush, cacti and native grasses.
39.99	The cor. of secs. 3, 4, 9 and 10.
	<hr/>
	N. 0°06' W., bet. secs. 3 and 4. Over rolling land, through scattered sage brush, cacti and native grasses.
7.90	Trail road, 10 ft. wide, bears S. 33° E. and N. 33° W.
14.90	Right bank, dry sandy wash, bears S. 22° E. and N. 22° W.
19.60	Left bank, dry sandy wash, bears S. 22° E. and N. 22° W.
22.95	Trail road, 10 ft. wide, bears S. 9° E. and N. 9° W.
40.03	Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.
	T27N R15E 1/4 S4 S3 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Over rolling land, through scattered sage brush and native grasses.
71.38	Barbed wire fence, 4 strand, bears S. 39° E. and N. 39° W.
79.86	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described.
	<hr/>
	From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°04' W., bet. secs. 32 and 33. Over rolling land, through scattered sage brush and native grasses.

Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.03	<p>The 1/4 sec. cor. of secs. 32 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S32 1/4 S33 1909.</p> <p>Add the marks T27N R15E 2002 to the brass cap.</p> <hr/> <p>N. 0°02' W., beginning new measurement.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>
39.99	<p>The cor. of secs. 28, 29, 32 and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 17 ins. above ground, leaning over, with brass cap mkd. T27N R15E S29 S28 S32 S33 1909.</p> <p>Reset the iron post, 29 ins. in the ground and add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89°57' W., bet. secs. 28 and 33.</p> <p>Over rolling to level land, through scattered sage brush and native grasses.</p>
39.98	<p>The 1/4 sec. cor. of secs. 28 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. S28 1/4 S33 1909.</p> <p>Add the marks T27N R15E 2002 to the brass cap.</p> <hr/> <p>N. 89°59' W., beginning new measurement.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>
40.00	<p>The cor. of secs. 28, 29, 32 and 33.</p> <hr/> <p>N. 0°03' W., bet. secs. 28 and 29.</p> <p>Over rolling to level land, through scattered sage brush and native grasses.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.01	<p>The 1/4 sec. cor. of secs. 28 and 29, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. S29 1/4 S28 1909.</p> <p>Add the marks T27N R15E 2002 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°04' W., beginning new measurement.</p> <p>Over rolling land.</p>
40.03	<p>The cor. of secs. 20, 21, 28 and 29, monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T27N R15E S20 S21 S29 S28 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 89°57' W., bet. secs. 21 and 28.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>
37.20	<p>Trail road, 10 ft. wide, bears N. 43° E. and S. 43° W.</p>
39.99	<p>The 1/4 sec. cor. of secs. 21 and 28, monumented with a bent iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. S21 1/4 S28 1909.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T27N R15E</p> <p>S21</p> <p>1/4 ———</p> <p>S28</p> <p>2002</p> </div> <p>Bury the iron post alongside the stainless steel post and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°57' W., beginning new measurement.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
23.70	Trail road, 10 ft. wide, bears S. 26° E. and N. 26° W.
39.99	The cor. of secs. 20, 21, 28 and 29.
	<hr/>
	N. 0°04' W., bet. secs. 20 and 21.
	Over rolling land, through scattered sage brush, cacti and native grasses.
37.25	Trail road, 10 ft. wide, bears S. 45° E. and N. 37° W.
40.01	The 1/4 sec. cor. of secs. 20 and 21, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. S20 1/4 S21 1909.
	Add the marks T27N R15E 2002 to the brass cap.
	<hr/>
	N. 0°02' W., beginning new measurement.
	Over rolling land, through scattered sage brush and native grasses.
26.35	Trail road, 10 ft. wide, bears N. 14° E. and S. 14° W.
40.03	The cor. of secs. 16, 17, 20 and 21, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T27N R15E S17 S16 S20 S21 1909.
	Add the marks 2002 to the brass cap.
	<hr/>
	From the cor. of secs. 15, 16, 21 and 22.
	N. 89°55' W., bet. secs. 16 and 21.
	Over rolling land, through scattered sage brush and native grasses.
39.98	The 1/4 sec. cor. of secs. 16 and 21, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. S16 1/4 S21 1909.
	Add the marks T27N R15E 2002 to the brass cap.
	<hr/>
	N. 89°57' W., beginning new measurement.
	Over rolling to level land, through scattered sage brush and native grasses.

Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
1.95	Trail road, 10 ft. wide, bears S. 76° E. and N. 76° W.
37.35	Trail road, 10 ft. wide, bears N. 8° E. and S. 8° W.
40.02	The cor. of secs. 16, 17, 20 and 21.
	<hr/>
	N. 0°04' W., bet. secs. 16 and 17.
	Over rolling to level land, through scattered sage brush and native grasses.
40.02	Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.
	T27N R15E 1/4 S17 S16 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Over rolling to level land.
46.74	Well and tank #6-351, bears E., 3.57 chs. dist.
54.40	Trail road, 10 ft. wide, bears S. 39° E. and N. 39° W.
64.60	Dry sandy wash, 15 ft. wide, 3 ft. deep, drains S. 38° E.
80.04	The cor. of secs. 8, 9, 16 and 17, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T27N R15E S8 S9 S17 S16 1909.
	Add the marks 2002 to the brass cap.
	<hr/>
	From the cor. of secs. 9, 10, 15 and 16.
	N. 89°57' W., bet. secs. 9 and 16.
	Over rolling land, through scattered sage brush and native grasses.
40.02	Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate dist., there is no remaining evidence of the original cor.

Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R15E S9 1/4 ——— S16 2002</p> <p>Found 1 in. diam., iron post, 36 ins. long, lying loose nearby with brass cap mkd. S9 1/4 S16 1909.</p> <p>Bury the iron post alongside the stainless steel post and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p> <p>80.04 The cor. of secs. 8, 9, 16 and 17.</p> <hr/>
	<p>N. 0°02' W., bet. secs. 8 and 9.</p> <p>Over rolling land, through scattered sage brush, cacti and native grasses.</p>
39.05	Trail road, 10 ft. wide, bears S. 64° E. and N. 64° W.
39.90	Trail road, 10 ft. wide, bears S. 33° E. and N. 33° W.
40.04	<p>The 1/4 sec. cor. of secs. 8 and 9, monumented with a bent iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. S8 1/4 S9 1909.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 6 ins. below the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R15E 1/4 S8 S9 2002</p> <p>Bury the iron post alongside stainless steel post and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located on E. edge of trail road, bears S. 30° E. and N. 30° W.</p> <hr/>

Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 0°02' W., beginning new measurement.</p> <p>Over rolling land, through scattered sage brush, cacti and native grasses.</p>
40.02	<p>The cor. of secs. 4, 5, 8 and 9, monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T27N R15E S5 S4 S8 S9 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 89°56' W., bet. secs. 4 and 9.</p> <p>Over rolling land, through scattered sage brush, cacti and native grasses.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R15E S4 1/4 ——— S9 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Over rolling land, through scattered sage brush, cacti and native grasses.</p>
44.60	<p>Dry sandy wash, 70 ft. wide, 6 ins. deep, drains S. 17° E.</p>
80.02	<p>The cor. of secs. 4, 5, 8 and 9.</p> <hr/> <p>N. 0°07' W., bet. secs. 4 and 5.</p> <p>Over rolling land, through scattered sage brush, cacti and native grasses.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
<p>68.30</p> <p>79.80</p>	<p style="text-align: center;">T27N R15E 1/4 S5 S4 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Over rolling land, through scattered sage brush, cacti and native grasses.</p> <p>Dry sandy wash, 35 ft. wide, 2 ft deep, drains S. 42° E.</p> <p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/>
<p>40.01</p>	<p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°05' W., bet. secs. 31 and 32.</p> <p>Over level land.</p> <p>The 1/4 sec. cor. of secs. 31 and 32, determined E. of the remains of the original mound of stone, 2 ft. base, 6 ins. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p>
<p>40.02</p>	<p style="text-align: center;">T27N R15E 1/4 S31 S32 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Rebuild mound of stone, 2 ft. base, 2 ft. high.</p> <hr/> <p>North, beginning new measurement.</p> <p>Over level land, through scattered sage brush, cacti and native grasses.</p> <p>The cor. of secs. 29, 30, 31 and 32, monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T27N R15E S30 S29 S31 S32 1909.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Add the marks 2002 to the brass cap.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89°55' W., bet. secs. 29 and 32.</p> <p>Over rolling to level land, through scattered sage brush, cacti and native grasses.</p>
39.99	<p>The 1/4 sec. cor. of secs. 29 and 32, monumented with an iron post, 1 in. diam., firmly set, flush with the ground, with brass cap mkd. S29 1/4 S32 1909.</p> <p>Add the marks T27N R15E 2002 to the brass cap.</p> <hr/> <p>N. 89°57' W., beginning new measurement.</p>
40.00	<p>The cor. of secs. 29, 30, 31 and 32.</p> <hr/> <p>N. 89°59' W., bet. secs. 30 and 31.</p> <p>Over level land.</p>
39.99	<p>The 1/4 sec. cor. of secs. 30 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. S30 1/4 S31 1909.</p> <p>Add the marks T27N R15E 2002 to the brass cap.</p> <hr/> <p>West, beginning new measurement.</p> <p>Over level land.</p>
40.04	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°01' W., bet. secs. 29 and 30.</p> <p>Over level land.</p>
40.02	<p>The 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. S30 1/4 S29 1909.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Add the marks T27N R15E 2002 to the brass cap.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°01' W., beginning new measurement.</p> <p>Over level land.</p>
40.03	<p>The cor. of secs. 19, 20, 29 and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T27N R15E S19 S20 S30 S29 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>N. 89°57' W., bet. secs. 20 and 29.</p> <p>Over rolling land, through scattered sage brush, cacti and native grasses.</p>
36.10	<p>Trail road, 10 ft. wide, bears N. 53° E. and S. 53° W.</p>
39.94	<p>The 1/4 sec. cor. of secs. 20 and 29, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. S20 1/4 S29 1909.</p> <p>Add the marks T27N R15E 2002 to the brass cap.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89°55' W., beginning new measurement.</p> <p>Over rolling land, through scattered sage brush, cacti and native grasses.</p>
39.98	<p>The cor. of secs. 19, 20, 29 and 30.</p> <hr/> <p>N. 89°59' W., bet. secs. 19 and 30.</p> <p>Over rolling land, through scattered sage brush, cacti and native grasses.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.98	<p style="text-align: center;">T27N R15E S19 1/4 ——— S30 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Over rolling land, through scattered sage brush, cacti and native grasses.</p> <p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/>
40.03	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°04' W., bet. secs. 19 and 20.</p> <p>Over level rolling land, through scattered sage brush, cacti and native grasses.</p> <p>Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
80.06	<p style="text-align: center;">T27N R15E 1/4 S19 S20 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Over rolling land, through scattered sage brush, cacti and native grasses.</p> <p>Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27N R15E S18 S17 ——— S19 S20 2002</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°56' W., bet. secs 17 and 20.</p> <p>Over rolling to level land, through scattered sage brush, cacti and native grasses.</p>
39.96	<p>The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. S17 1/4 S20 1909.</p> <p>Add the marks T27N R15E 2002 to the brass cap.</p> <hr/> <p>N. 89°55' W., beginning new measurement.</p> <p>Over rolling to level land, through scattered sage brush, cacti and native grasses.</p>
39.96	<p>The cor. of secs. 17, 18, 19 and 20.</p> <hr/> <p>S. 89°59' W., bet. secs. 18 and 19.</p> <p>Over level land.</p>
40.03	<p>The 1/4 sec. cor. of secs. 18 and 19, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. S18 1/4 S19 1909.</p> <p>Add the marks T27N R15E 2002 to the brass cap.</p> <hr/> <p>S. 89°57' W., beginning new measurement.</p> <p>Over level land.</p>
39.82	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°05' W., bet. secs 17 and 18.</p> <p>Over rolling land, through scattered sage brush, cacti and native grasses.</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
34.80	Trail road, 10 ft. wide, bears N. 59° E. and S. 59° W.
40.03	<p>Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R15E 1/4 S18 S17 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Over rolling land, through scattered sage brush, cacti and native grasses.</p>
80.06	<p>The cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T27N R15E S7 S8 S18 S17 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89°55' W., bet. secs. 8 and 17.</p> <p>Over rolling land, through scattered sage brush, cacti and native grasses.</p>
6.25	Trail road, 10 ft. wide, bears S. 40° E. and N. 13° W.
9.10	Dry sandy wash, 25 ft. wide, 2 ft. deep, drains S. 47° E.
20.30	Trail road, 10 ft. wide, bears S. 8° E. and N. 8° W.
22.80	Trail road, 10 ft. wide, bears S. 68° E. and N. 68° W.
39.97	<p>Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R15E S8 1/4 ——— S17 2002</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the SW cor. of Antonio Rogers house bears N. 51°22' E., 6.83 chs. dist.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>
79.94	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/> <p>S. 89°56' W., bet. secs. 7 and 18.</p> <p>Over level land, through scattered sage brush and native grasses.</p>
7.80	<p>Trail road, 10 ft. wide, bears N. 44° E. and S. 44° W.</p>
40.01	<p>The 1/4 sec. cor. of secs. 7 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. S7 1/4 S18 1909.</p> <p>Add the marks T27N R15E 2002 to the brass cap.</p> <hr/> <p>S. 89°56' W., beginning new measurement.</p>
39.75	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°05' W., bet. secs. 7 and 8.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>
9.75	<p>Trail road, 10 ft. wide, bears N. 27° E. and S. 27° W.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R15E 1/4 S7 S8 2002</p>

**Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>
80.04	<p>The cor. of secs. 5, 6, 7 and 8, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T27N R15E S6 S5 S7 S8 1909.</p> <p>Add the marks 2002 to the brass cap.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 89°56' W., bet. secs. 5 and 8.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>
4.95	Trail road, 10 ft. wide, bears N. 21° E. and S. 21° W.
16.80	Trail road, 10 ft. wide, bears N. 46° E. and S. 46° W.
24.85	Trail road, 10 ft. wide, bears S. 34° E. and N. 34° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R15E S5 1/4 ——— S8 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>
80.00	<p>The cor. of secs. 5, 6, 7 and 8.</p> <hr/> <p>S. 89°54' W., bet. secs. 6 and 7.</p> <p>Over rolling land, through scattered sage brush and native grasses.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.01	<p>Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R15E S6 1/4 ——— S7 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.58	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/>
	<p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°09' W., bet. secs. 5 and 6.</p> <p>Over broken land.</p>
39.99	<p>The 1/4 sec. cor. of secs. 5 and 6, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. S6 1/4 S5 1909.</p> <p>Add the marks T27N R15E 2002 to the brass cap.</p> <hr/> <p>N. 0°04' W., beginning new measurement.</p> <p>Over broken land. through scattered sage brush and native grasses.</p>
39.78	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/>
	<p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>The area surveyed is within the Hopi Indian reservation. The terrain is level to rolling and broken. The drainage is southwesterly, with Oraibi Wash being the principal drainage.</p>

T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona

CHAINS

The elevation varies from 5200 to 5900 feet above sea level. The soil is mostly sandy with some sandstone outcrops. The vegetation principally consists of sage brush and native grasses, with pinon pine sparsely scattered in the NW quadrant of the township.

Principal access to the township is provided by Hopi Route #2. There are numerous trail roads throughout the township. Much of the township is used for grazing of livestock. There is no evidence of current mining activity.

The mean magnetic declination of $12\frac{1}{2}^{\circ}$ E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Richard M. McDonald	Surveying Technician
Mike M. Barnett	Surveying Technician
Mark R. Searles	Surveying Technician
Brian S. Helfrich	Surveying Technician

CERTIFICATE OF SURVEY

I, W. William Foster, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 8th day of July, 2002, and amended special instructions bearing date of the 18th day of July, 2002, I have dependently resurveyed the south, west and north boundaries and the subdivisional lines, T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

6/25/03

(Date)

W. William Foster

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the south, west and north boundaries and the subdivisional lines, T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona, executed by W. William Foster, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

July 24, 2003

(Date)

Kenny D. Ravmkar

(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 27 N., R. 15 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~