

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

**DEPENDENT RESURVEY OF PORTIONS OF
THE EAST, WEST AND NORTH BOUNDARIES
AND A PORTION OF THE SUBDIVISIONAL LINES,
THE SUBDIVISION OF CERTAIN SECTIONS**

AND

METES-AND-BOUNDS SURVEYS IN SECTIONS 20 AND 25,

TOWNSHIP 11 NORTH, RANGE 3 EAST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA.

EXECUTED BY

Stephen K. Hansen and Adrien J. Rodriguez, Cadastral Surveyors

Under Special Instructions dated April 9, 2001, approved April 9, 2001, and Supplemental Special Instructions dated April 10, 2002, approved April 10, 2002, which provided for the surveys included under Group No. 870, and assignment instructions dated April 9, 2001 and October 10, 2001.

Survey commenced April 23, 2001

Survey completed April 10, 2002

INDEX DIAGRAM

TOWNSHIP 11 NORTH RANGE 3 EAST

	16	15	12		12
6	49 5	34 4	25 3	21 2	1 6 19
11 48 7	47 46 8	33 9	26 24 10	21 20 11	19 18 12 4
45 18	44 17	32 16	15	20 14	17 13
19	43 40 20	31 30 21	22	23	24
40 10 30	39 37 29	29 28 28	22 27	26	17 25 2
36 8 31	35 32	27 33	34	35	17 36

Subdivision of Section 1	Pages 50-52
Subdivision of Section 3	Pages 52-54
Subdivision of Section 4	Pages 54-55
Subdivision of Section 7	Pages 55-56
Subdivision of Section 10	Pages 56-58
Subdivision of Section 11	Pages 58-60
Subdivision of Section 12	Pages 61-62
Subdivision of Section 25	Pages 63-64
Subdivision of Section 28	Pages 64-65
Subdivision of Section 30	Pages 65-68
Metes-and-Bounds Survey in Section 20	Page 68
Metes-and-Bounds Survey in Section 25	Pages 69-70

T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of portions of the east, west and north boundaries and a portion of the subdivisional lines, the subdivision of certain sections and metes-and-bounds surveys in sections 20 and 25, T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this resurvey is as follows:

C. Burton Foster surveyed a portion of the west and north boundaries and a portion of the subdivisional lines in 1873. Theodore F. White surveyed a portion of the north and east boundaries in 1881. Lewis Wolfley resurveyed a portion of the east boundary and surveyed a portion of the east and west boundaries and a portion of the subdivisional lines in 1884. Francis B. Jacobs resurveyed portions of the subdivisional lines and surveyed a portion of the subdivisional lines in 1891. R.P.A. Johnson resurveyed a portion of the east boundary and surveyed Homestead Entry Survey Number 324 in 1915. William H. Richards, Jr. resurveyed a portion of the west boundary in 1916. George F. Rigby resurveyed the east boundary, a portion of the south and north boundaries and portions of the subdivisional lines and surveyed a portion of the subdivisional lines in 1917. Francis E. Joy dependently resurveyed a portion of the south boundary in 1933. Theodore Vander Meer and Benjamin J. Mollette dependently resurveyed a portion of the north boundary in 1934. Clarence E. Bilbray dependently resurveyed a portion of the west boundary in 1952.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated April 9, 2001, and Supplemental Special Instructions dated April 10, 2002, for Group No. 870, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 4400 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS

Geodetic control, NAD83(1992), was established utilizing static GPS observations post-processed by the National Geodetic Survey's Online Positioning User Service (OPUS). Three Continuously Operating Reference Stations (CORS), FERNO MESA, FLAGSTAFF and TUCSON were utilized in the post-processing. The geographic position of the cor. of secs. 25 and 36 only, on the E. bdy. of the Tp., is as follows:

Latitude: 34° 17' 45.10" N. Longitude: 111° 59' 11.52" W.

The mean magnetic declination is 12¼° E.

**Dependent Resurvey of a Portion of the East Boundary,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona**

Restoring the resurvey executed by
George F. Rigby, in 1917

Beginning at the cor. of secs. 25 and 36 only, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, in a collar of stone, with a mound of stone, 4 ft. base, 2 ft. high, to the W., with brass cap mkd. T11N S25 S36 R3E 1917.

Add the marks 2002 to the brass cap.

Cor. is located alongside a 4 strand barbed wire fence, bears N. and S.


N. 0°02' W., on the E. bdy. of sec. 25.

Over broken and rocky terrain, through scattering juniper and mesquite.


35.69

Point for AP 4, sec. 25, at intersection with the southerly line of a parcel surveyed by Patrick W. Naville, Arizona Registered Land Surveyor No. 13015, in 1989.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.



Dependent Resurvey of a Portion of the East Boundary,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 18 lks. S. of a wooden fence post, with 5 strand barbed wire fences extending N. 50° E., S. 40° E. and S. 50° W.</p> <p>From this cor. point, a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above ground, with affixed yellow plastic cap mkd. LS 13015, bears N. 47°43' E., 0.075 ch. dist.</p> <p>From this same cor. point, cor. No. 1, Homestead Entry Survey No. 324, bears S. 8°57' E., 0.67 ch. dist., monumented with a limestone, 12 x 9 x 4 ins., firmly set, projecting 9 ins. above ground, mkd. HES 324 on the N. and C on the NE. faces, from which the original bearing object</p> <p style="padding-left: 40px;">A volcanic boulder, 3 x 2 x 2 ft. above the ground, bears S. 43¼° W., 44 lks. dist., mkd. X on top center. (Record: S. 42°38' W.)</p>
36.05	Dirt road, 12 ft. wide, bears N. 50° E. and S. 50° W.
37.29	Point for the 1/4 sec. cor. of sec. 30 only, T. 11 N., R. 4 E., at proportionate dist., falls in open field; there is no remaining evidence of the 1917 cor. Not monumented.
40.03	Point for the 1/4 sec. cor. of sec. 25 only, at proportionate dist., falls in open field; there is no remaining evidence of the 1917 cor. Not monumented.
47.63	<p>Point for AP 1, sec. 25, at intersection with the northerly line of a parcel surveyed by Patrick W. Naville, Arizona Registered Land Surveyor No. 13015, in 1989.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;">  </div> <p>from which</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears S. 20¼° W., 48 lks. dist., mkd. X BT.</p>

**Dependent Resurvey of a Portion of the East Boundary,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 5 lks. W. of a 4 strand barbed wire fence, bears N. and S.</p> <p>From this cor. point, cor. No. 2, Homestead Entry Survey No. 324, bears N. 40°37' E., 0.115 ch. dist., monumented with a volcanic stone, 12 x 6 x 6 ins., firmly set, projecting 6 ins. above ground, with a mound of stone, 3 ft. base, ½ ft. high, to the E., mkd. HES 324 on the E. face, from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 36 ins. diam., bears N. 35¼° E., 237 lks. dist., with illegible scribe marks visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A juniper, 48 ins. diam., bears S. 21¼° W., 283 lks. dist., with a healed blaze.</p>
77.85	<p>The cor. of secs. 19 and 30 only, T. 11 N., R. 4 E., monumented with a volcanic stone, 15 x 12 x 12 ins., firmly set, projecting 12 ins. above ground, with a mound of stone, 4 ft. base, 2 ft. high, to the W., mkd. with 2 notches on S. face and cross X on top. Not remonumented.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 1°15' W., beginning new measurement.</p> <p>Over rolling land, through scattering mesquite and juniper.</p>
2.22	<p>The cor. of secs. 24 and 25 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, in a collar of stone, with a mound of stone, 4 ft. base, 1 ft. high, to the W., with brass cap mkd. T11N S24 S25 R3E 1917, from which the original bearing tree</p> <p style="padding-left: 40px;">A forked juniper, 12 ins. diam., bears S. 16° W., 139 lks. dist., with scribe marks T11N R3E S25 BT visible on partially open blaze. (Record: 136 lks. dist.)</p> <p>Add the marks 2002 to the brass cap.</p> <hr style="width: 30%; margin: 10px auto;"/>
	<p>From the cor. of secs. 7 and 18 only, T. 11 N., R. 4 E., monumented with a mound of stone, 2 ft. base, 1 ft. high, with a mound of stone, 3 ft. base, 2 ft. high, to the E., from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 24 ins. diam., bears S. 27° E., 254 lks. dist., with Roman numeral scribe marks visible on unhealed blaze.</p>

Dependent Resurvey of a Portion of the East Boundary,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A juniper, 28 ins. diam., bears S. $80\frac{1}{2}^{\circ}$ W., 270 lks. dist., with illegible scribe marks visible on unhealed blaze. (Record: S. $81\frac{1}{2}^{\circ}$ W.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R3E R4E S7 S12 S18 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, an iron post, 36 ins. long, 2 ins. diam., lying loosely on the surface of the ground, with brass cap mkd. T11N R3E R4E S7 S18 1917, bears N. $8\frac{1}{2}^{\circ}$ W., 41 lks. dist. The 1917 survey recovered the original cedar post, but did not make mention of setting this iron post. Remove the iron post from the area, impracticable to bury.</p> <p>From this same cor. point, the cor. of secs. 24 and 25 only, bears S. $0^{\circ}05'$ E., 165.10 chs. dist., hereinbefore described.</p> <p>N. $0^{\circ}03'$ E., on the E. bdy. of sec. 12.</p> <p>Over broken and rocky terrain, through scattering mesquite and juniper.</p>
34.88	<p>The $\frac{1}{4}$ sec. cor. of sec. 12 only, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with a mound of stone, $2\frac{1}{2}$ ft. base, 1 ft. high, to the W., with brass cap mkd. $\frac{1}{4}$ S12 1917.</p> <p>Add the marks T11N R3E R4E 2001 to the brass cap.</p> <p>Cor. is located 1 lk. W. of a 4 strand barbed wire fence, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $0^{\circ}03'$ E., beginning new measurement.</p>
5.15	<p>The $\frac{1}{4}$ sec. cor. of sec. 7 only, T. 11 N., R. 4 E., monumented with a volcanic stone, 9 x 8 x 6 ins., firmly set, projecting 6 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, to the E., mkd. $\frac{1}{4}$ on the E. face.</p>

Dependent Resurvey of a Portion of the East Boundary,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E R4E 1/4 S7 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the original stone alongside the stainless steel post, in the mound of stone.</p> <p>Cor. is located 3 lks. E. of a 4 strand barbed wire fence, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°06' W., beginning new measurement.</p>
34.85	<p>The cor. of secs. 1 and 12 only, monumented with an iron post, 2 ins. diam., loosely set, projecting 18 ins. above ground, with brass cap mkd. T11N S1 S12 R3E 1917.</p> <p>Add the marks R4E S7 2001 to the brass cap.</p> <p>Raise a mound of stone, 3 ft. base, to top, around iron post.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°06' W., on the E. bdy. of sec. 1.</p>
5.18	<p>The cor. of secs. 6 and 7 only, T. 11 N., R. 4 E., determined by a hole left in the ground, with a sandstone, 18 x 10 x 5 ins., fallen over because of erosion alongside, mkd. with 5 grooves on the S. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E R4E S6 S1 _____ S7 2001</p>

Dependent Resurvey of a Portion of the East Boundary,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the original stone alongside the stainless steel post, in the mound of stone.</p> <p>Cor. is located 5 lks. W. of a 4 strand barbed wire fence, bears N. and S.</p> <hr/> <p>N. 0°03' E., beginning new measurement.</p> <p>Over rolling rocky hills, through scattering juniper.</p>
34.78	<p>The 1/4 sec. cor. of sec. 1 only, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, in a collar of stone, with a mound of stone, 2½ ft. base, 1 ft. high, to the W., with brass cap mkd. 1/4 S1 1917.</p> <p>Add the marks T11N R3E R4E 2001 to the brass cap.</p> <p>Raise a mound of stone, 3 ft. base, to top, around iron post.</p> <p>Cor. is located 3 lks. E. of a 4 strand barbed wire fence, bears N. and S.</p> <hr/> <p>N. 0°03' E., beginning new measurement.</p>
5.13	<p>The 1/4 sec. cor. of sec. 6 only, T. 11 N., R. 4 E., monumented with a sandstone, 10 x 10 x 6 ins., firmly set, projecting 6 ins. above ground, with a mound of stone, 2½ ft. base, 1½ ft. high, to the E., mkd. 1/4 on E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R3E R4E 1/4 S6 2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the original stone alongside the stainless steel post, in the mound of stone.</p> <p>Cor. is located 2 lks. E. of a 4 strand barbed wire fence, bears N. and S.</p> <hr/> <p>N. 0°49' E., beginning new measurement.</p>

**Dependent Resurvey of a Portion of the East Boundary,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona**

CHAINS															
14.87	Point for the N. 1/16 sec. cor. of sec. 1 only. Not monumented.														
39.91	<p>The cor. of Tps. 11 and 12 N., Rs. 3 and 4 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 20 ins. above ground, in a mound of stone, 3 ft. base, 1½ ft. high, with brass cap mkd. T12N R4E S36 S31 S1 S6 R3E T11N 1917, from which the 1917 bearing tree</p> <p align="center">A juniper, 24 ins. diam., bears N. 72° E., 104 lks. dist., with illegible marks on mostly healed blaze.</p> <p>Add the marks 2001 to the brass cap.</p> <p>Cor. is located 3 lks. E. of a 4 strand barbed wire fence, bears N. and S.</p> <hr/> <p align="center">Dependent Resurvey of a Portion of the West Boundary, T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p align="center">Restoring the resurvey executed by William H. Richards, Jr., in 1916</p> <hr/> <p>From the cor. of Tps. 10 and 11 N., Rs. 2 and 3 E., monumented with a granite stone, 21 x 9 x 7 ins., firmly set, projecting 12 ins. above ground, with a mound of stone, 2 ft. base, ½ ft. high, to the S., mkd. with 6 notches on S. and 6 notches on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T11N</td> </tr> <tr> <td style="text-align: center;">R2E</td> <td style="text-align: center;">R3E</td> </tr> <tr> <td style="text-align: center;">S36</td> <td style="text-align: center;">S31</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S1</td> <td style="text-align: center;">S6</td> </tr> <tr> <td colspan="2" style="text-align: center;">T10N</td> </tr> <tr> <td colspan="2" style="text-align: center;">2001</td> </tr> </table> <p>from which a new bearing tree</p> <p align="center">A juniper, 14 ins. diam., bears N. 22° W., 70 lks. dist., mkd. X BT.</p>	T11N		R2E	R3E	S36	S31	-----		S1	S6	T10N		2001	
T11N															
R2E	R3E														
S36	S31														

S1	S6														
T10N															
2001															

Dependent Resurvey of a Portion of the West Boundary,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 42 lks. W. of a 4 strand barded wire fence, bears N. and S.</p> <p>N. 0°23' W., on the W. bdy. of sec. 31.</p> <p>Over rolling terrain, through scattering mesquite and juniper.</p>
40.48	<p>Point for the 1/4 sec. cor. of sec. 31 only, determined by irregular boundary adjustment; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R2E R3E 1/4 S31 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 5 lks. W. of a 4 strand barbed wire fence, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°53' W., beginning new measurement.</p> <p>Over rolling terrain, through scattering mesquite and juniper.</p>
39.62	<p>The closing cor. of secs. 25 and 36, T. 11 N., R. 2 E., monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above ground, with mound of stone, 2 ft. base, 1 ft. high, to the W., with brass cap mkd. T11N R2E R3E S25 S36 CC 1916.</p> <p>Cor. is located alongside a 4 strand barbed wire fence, bears E. and W.</p>
40.13	<p>The cor. of secs. 30 and 31 only, monumented with a granite stone, 20 x 10 x 5 ins., firmly set, projecting 10 ins. above ground, with a mound of stone, 4 ft. base, 1 ft. high to the W., mkd. with 1 notch on S. and 5 notches on N. faces.</p> <p>At the corner point</p>

**Dependent Resurvey of a Portion of the West Boundary,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R2E R3E S25 S30 S31 2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the original stone alongside the stainless steel post, in the mound of stone.</p> <p>From this cor. point, the SE cor. of a house, 65 x 41 ft., bears N. 28° W., 3.29 chs. dist., long side bears N. 25° E.</p>
	<p>N. 0°25' W., on the W. bdy. of sec. 30.</p> <p>Over rolling terrain, through scattering mesquite and juniper.</p>
19.985	<p>Point for the S. 1/16 sec. cor. of sec. 30 only. Not monumented.</p> <p>From this point, a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with affixed yellow plastic cap mkd. LS 24522, bears S. 62°59' E., 0.045 ch. dist.</p> <p>Point is located 37 lks. E. of the center of Rolling Ridge Drive, dirt, 20 ft. wide, bears N. and S.</p>
39.97	<p>Point for the 1/4 sec. cor. of sec. 30 only, determined by irregular boundary adjustment; there is no remaining evidence of the original cor. Not monumented.</p> <p>From this point, a rebar, 5/8 in. diam., firmly set, 1 in. below the ground, with affixed yellow plastic cap mkd. LS and illegible numbers, bears S. 66°59' E., 0.09 ch. dist.</p> <p>Point is located 50 lks. E. of Rolling Ridge Drive, dirt, 20 ft. wide, bears N. and S.</p>
	<p>N. 0°22' W., beginning new measurement.</p> <p>Over mostly level terrain, through scattering mesquite and juniper.</p>

Dependent Resurvey of a Portion of the West Boundary,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.92	<p>The cor. of secs. 19, 24, 25, and 30, perpetuated by Cadmus L. G. Goss, Arizona Registered Land Surveyor No. 5096, in 1968, as shown on the plat of survey of Cordes Lakes Unit Three Subdivision, monumented with a rebar, $\frac{1}{2}$ in. diam., firmly set, projecting 1 in. above ground, and recorded in Book 13 of Maps and Plats, Page 57, in the Yavapai County Recorders office, Prescott, Arizona, with a metal washer attached at a later date, mkd. LS 15331. A rebar of unknown origin, $\frac{1}{2}$ in. diam., firmly set, projecting 1 in. above ground was found alongside. This position is accepted as a careful and faithful perpetuation of the original cor. position. Not remonumented.</p> <p>Cor. is located alongside a steel fence post, with a 4 strand barbed wire fence extending N. and a 4 ft. high chain link fence extending W. and S.</p> <hr/> <p style="text-align: center;">Restoring the survey executed by Clarence E. Bilbray, in 1952</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 21 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. $\frac{1}{4}$ S12 S7 1952.</p> <p>Add the marks T11N R2E R3E 2001 to the brass cap.</p> <p>N. $0^{\circ}13'$ E., bet. secs. 7 and 12.</p> <p>Over rolling terrain, through scattering mesquite and juniper.</p>
41.16	<p>The cor. of secs. 1, 6, 7, and 12, monumented with an iron post, $2\frac{1}{2}$ ins. diam., loosely set, projecting 24 ins. above ground, in a scattered mound of stone, with brass cap mkd. T11N R2E R3E S1 S6 S12 S7 1952.</p> <p>At the corner point</p> <p>Reset the iron post, 28 ins. long, 16 ins. in the ground, in a mound of stone, 4 ft. base, 1 ft. high.</p> <p>Add the marks 2001 to the brass cap.</p> <p>Deposit a magnet in a white plastic case at the base of the iron post.</p> <hr/>

Dependent Resurvey of a Portion of the North Boundary,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">Restoring the resurvey executed by George F. Rigby, in 1917</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of Tps. 11 and 12 N., Rs. 3 and 4 E., hereinbefore described.</p> <p>N. 89°46' W., bet. secs. 1 and 36, on the N. bdy. of the Tp.</p> <p>Over rolling rocky grassland through scattering juniper.</p>
20.04	<p>Point for the E. 1/16 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T12N R3E S36 E 1/16 ——— S1 T11N 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 3 lks. N. of a 4 strand barbed wire fence, bears E. and W.</p>
40.08	<p>The 1/4 sec. cor. of secs. 1 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. 1/4 S36 S1 1917.</p> <p>Add the marks T12N R3E T11N 2001 to the brass cap.</p> <p>Cor. is located in a 4 strand barbed wire fence, bears E. and W.</p>
	<hr/> <p>From the cor. of secs. 2 and 3 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above ground, with mostly obliterated marks on the brass cap. File the cap and remark so it now reads.</p> <p style="text-align: center;">T12N R3E S35 ————— S3 S2 T11N 2001</p> <p>Cor. is located in a 4 strand barbed wire fence, bears E. and W.</p>

Dependent Resurvey of a Portion of the North Boundary,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS					
4.69	<p>N. 89°36' W., on the N. bdy. of sec. 3.</p> <p>Over rolling rocky grassland through scattering juniper.</p> <p>The cor. of secs. 34 and 35 only, T. 12 N., R. 3 E., monumented with a volcanic stone, 21 x 10 x 8 ins., firmly set, projecting 7 ins. above ground, mkd. with 2 notches on the E. face and 4 notches on the W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p> <table border="1" data-bbox="836 762 1008 840"> <tr> <td>T12N R3E</td> <td></td> </tr> <tr> <td>S34</td> <td>S35</td> </tr> </table> <p>S3 T11N 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the 1917 stone in the mound of stone alongside the stainless steel post.</p> <p>Cor. is located 1½ lks. N. of a 4 strand barbed wire fence, bears E. and W.</p> <hr data-bbox="670 1182 1182 1188"/>	T12N R3E		S34	S35
T12N R3E					
S34	S35				
35.26	<p>N. 89°36' W., beginning new measurement.</p> <p>Point for the 1/4 sec. cor. of sec. 3 only, at proportionate dist.; there is no remaining evidence of the 1917 cor. position.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="862 1478 997 1625"> <tr> <td>T12N R3E</td> </tr> <tr> <td>1/4 S3</td> </tr> <tr> <td>T11N</td> </tr> <tr> <td>2001</td> </tr> </table> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located ½ lk. N. of a cor. of fences, with 4 strand barbed wire fence lines extending E., S. and W.</p>	T12N R3E	1/4 S3	T11N	2001
T12N R3E					
1/4 S3					
T11N					
2001					

Dependent Resurvey of a Portion of the North Boundary,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>The 1917 monument, an iron post, 1 in. diam., 36 ins. long, was found wired to a fence post, S. 45° W., 1½ lks. dist. from the proportionate position, with brass cap mkd. 1/4 S3 1917. Remove the iron post from the area, impracticable to bury.</p> <p>From this cor. point, U. S. Coast and Geodetic Survey triangulation station "SPRING 1958", bears N. 1°06' W., 109.90 chs. dist., monumented with a standard brass disk, 3½ ins. diam., firmly set, in concrete, in a drill hole, in a boulder, 4 x 2 x 1 ft. high, with brass cap mkd. SPRING 1958 and a triangle.</p>
44.72	<p>The 1/4 sec. cor. of sec. 34 only, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with a mound of stone, 2½ ft. base, 1 ft. high, to the N., with brass cap mkd. 1/4 S34 1917.</p> <p>Add the marks T12N R3E T11N 2001 to the brass cap.</p> <p>Cor. is located 1 lk. N. of a 4 strand barbed wire fence, bears E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°34' W., beginning new measurement.</p>
30.54	<p>Point for the 80 1/16 sec. cor. of sec. 3 only.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T12N R3E ————— 1/16 S3 80 T11N 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 4 lks. N. of a 4 strand barbed wire fence, bears E. and W.</p>
44.71	<p>The cor. of secs. 3, 4, 33 and 34, perpetuated by Roger Green, Arizona Registered Land Surveyor No. 18545, in 1987, monumented with an aluminum post, 1 in. diam., firmly set, projecting 6 ins. above ground, in a mound of stone, 4 ft. base, 6 ins. high, with aluminum cap mkd. T12N R3E S33 S34 S4 S3 T11N RLS 18545 1987, with the 1917 stone, 21 x 10 x 7 ins., buried alongside, mkd. with 3 grooves on the E. and W. faces, and recorded in Book 9 of Land Surveys, Page 5, in the Yavapai County Recorders office, Prescott, Arizona. This is accepted as a careful and</p>

Dependent Resurvey of a Portion of the North Boundary,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>faithful perpetuation of the original cor. position. Not remonumented.</p> <p>Cor. is located 14 lks. N. of a 4 strand barbed wire fence, bears E. and W.</p>
	<hr/> <p style="text-align: center;">Restoring the resurvey executed by Theodore Vander Meer and Benjamin J. Mollette, in 1934</p> <hr/> <p>S. 88°39' W., bet. secs. 4 and 33.</p> <p>Over rolling rocky grasslands.</p>
37.50	<p>The witness cor. for the 1/4 sec. cor. of secs. 4 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, in a mound of stone, 4 ft. base, 1 ft. high, with brass cap mkd. 1/4 WC S33 S4 1934.</p> <p>Add the marks T12N R11E T11N 2001 to the brass cap.</p> <p>Cor. is located 1 lk. S. of a 4 strand barbed wire fence, bears E. and W.</p>
	<hr/> <p>S. 88°28' W., beginning new measurement.</p>
1.20	<p>True point for the 1/4 sec. cor. of secs. 4 and 33, falls in a dry creek bed, 1 ch. wide, 3 ft. deep, drains S. 40° W., where it is impracticable to establish a permanent monument.</p>
20.57	<p>Point for the E. 1/16 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T12N R3E S33 W 1/16 ——— S4 T11N 2001</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1½ lks. N. of a 4 strand barbed wire fence, bears E. and W.</p>

**Dependent Resurvey of a Portion of the North Boundary,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.94	<p>The cor. of secs. 4, 5, 32 and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. T12N R3E S32 S33 S5 S4 T11N 1934.</p> <p>Add the marks 2001 to the brass cap.</p> <p>Cor. is located on the S. side of a wooden fence post, with 4 strand barbed wire fence lines extending E., S. and W.</p> <hr/>
	<p>N. 89°32' W., bet. secs. 5 and 32.</p> <p>Over rolling rocky grasslands.</p>
40.23	<p>The 1/4 sec. cor. of secs. 5 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. 1/4 S32 S5 1934.</p> <p>Add the marks T12N R3E T11N 2002 to the brass cap.</p> <p>Cor. is located 4 lks. W. of a steel fence post and 4 lks. E of an aluminum fence post.</p> <p>Cor. is located alongside a 4 strand barbed wire fence, bears E. and W.</p> <hr/>
	<p>N. 89°34' W., bet. secs. 5 and 32.</p> <p>Over rolling rocky grasslands.</p>
40.26	<p>The cor. of secs. 5, 6, 31, and 32, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T12N R3E S31 S32 S6 S5 T11N 1934.</p> <p>Add marks 2001 to the brass cap.</p> <p>Cor. is located 3 lks. SE. of an angle iron fence post, with four strand barbed wire fence lines extending N., E. and W.</p> <hr/>
	<p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona</p> <hr/>
	<p>Restoring the surveys executed by C. Burton Foster, in 1873, Lewis Wolfley, in 1884, Francis B. Jacobs, in 1891, and George F. Rigby, in 1917</p> <hr/>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.67	<p>From the cor. of secs. 25 and 36 only, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°58' W., bet. secs. 25 and 36.</p> <p>Over mountainous land through scattering juniper.</p> <p>The 1/4 sec. cor. of secs. 25 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, in a collar of stone, with a mound of stone, 3 ft. base, 1 ft. high, to the N., with brass cap mkd. 1/4 S25 S36 1917.</p> <p>Add the marks T11N R3E 2002 to the brass cap.</p>
39.69	<p>From the cor. of secs. 24 and 25 only, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°48' W., bet. secs. 24 and 25.</p> <p>Over rolling land, through scattering undergrowth.</p> <p>The 1/4 sec. cor. of secs. 24 and 25, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, in a mound of stone, 2 ft. base, ½ ft. high, with a mound of stone, 2 ft. base, 1½ ft. high, to the N., with brass cap mkd. 1/4 S24 S25 1917.</p> <p>Add the marks T11N R3E 2002 to the brass cap.</p>
39.96	<p>From the 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, with a mound of stone, 2½ ft. base, 1½ ft. high, to the N., with brass cap mkd. 1/4 S12 S13 1917.</p> <p>Add the marks T11N R3E 2001 to the brass cap.</p> <p>Raise a mound of stone, 3 ft. base, to top, around iron post.</p> <p>S. 89°44' W., bet. secs. 12 and 13.</p> <p>Over mountainous land through scattering juniper.</p> <p>The cor. of secs. 11, 12, 13 and 14, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T11N R3E S11 S12 S14 S13 1917, from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears N. 76¼° E., 263 lks. dist., with scribe marks visible on mostly healed blaze. (Record: N. 77° E.)</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Add the marks 2001 to the brass cap</p> <hr/>
	<p>North, bet. secs. 11 and 12.</p>
20.02	<p>Point for the S. 1/16 sec. cor. of secs. 11 and 12.</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T11N R3E</p>
	<p style="text-align: center;">S 1/16</p>
	<p style="text-align: center;">S11 S12</p>
	<p style="text-align: center;">2001</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
40.04	<p>The 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, in a scattered mound of stone, with a mound of stone, 2 ft. base 1½ ft. high, to the N., with brass cap mkd. 1/4 S11 S12 1917.</p>
	<p>Add the marks T11N R3E 2001 to the brass cap.</p>
	<p>Raise a mound of stone, 3 ft. base, to top, around iron post.</p> <hr/>
	<p>North, beginning new measurement.</p>
19.95	<p>Point for the N. 1/16 sec. cor. of secs. 11 and 12.</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T11N R3E</p>
	<p style="text-align: center;">N 1/16</p>
	<p style="text-align: center;">S11 S12</p>
	<p style="text-align: center;">2001</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
39.90	<p>The cor. of secs. 1, 2, 11 and 12, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with a mound of stone, 3 ft. base, 1 ft. high, to the W., with brass cap mkd. T11N R3E S2 S1 S11 S12 1917.</p>
	<p>Add the marks 2001 to the brass cap.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located 1 lk. NE of a wooden fence post, with 4 strand barbed wire fence lines extending S. 50° E. and S. 85° W.</p> <hr/> <p>From the cor. of secs. 1 and 12 only, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°44' W., bet. secs. 1 and 12.</p> <p>Over rocky mountainous land through scattering juniper.</p> <p>39.41 The 1/4 sec. cor. of secs. 1 and 12, monumented with an iron post, 1 in. diam., firmly set, 2 ins. below the ground, bent at the base, with brass cap mkd. 1/4 S1 S12 1917.</p> <p>At the corner point</p> <p>Straighten and reset the iron post, 36 ins. long, 30 ins. in the ground.</p> <p>from which the original bearing tree</p> <p style="padding-left: 40px;">A sycamore, 60 ins. diam., bears S. 35° W., 340 lks. dist., with no discernible blaze.</p> <p>Add the marks T11N R3E 2001 to the brass cap.</p> <p>Cor. is located in a fallow field.</p> <hr/> <p>S. 89°35' W., beginning new measurement.</p>
19.96	Point for the W. 1/16 sec. cor. of secs. 1 and 12. Not monumented.
39.92	The cor. of secs. 1, 2, 11 and 12.
	<hr/> <p>N. 0°16' W., bet. secs. 1 and 2.</p> <p>Over rolling rocky land through scattering juniper and cacti.</p>
20.01	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E S 1/16 S2 S1 2001</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.02	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The 1/4 sec. cor. of secs. 1 and 2, monumented with an iron post, 1 in. diam., loosely set, projecting 18 ins. above ground, in a scattered mound of stone, with a mound of stone, 2½ ft. base, to the W., 1½ ft. high, with brass cap mkd. 1/4 S2 S1 1917.</p> <p>Add the marks T11N R3E 2001 to the brass cap.</p> <p>Raise a mound of stone, 3 ft. base, to top, around iron post.</p>
39.96	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89°59' W., bet. secs. 11 and 14.</p> <p>Over rolling rocky land through scattering juniper.</p> <p>The 1/4 sec. cor. of secs. 11 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, in a scattered mound of stone, with brass cap mkd. 1/4 S11 S14 1917, from which the original bearing trees</p> <p style="padding-left: 40px;">A dead and downed juniper, 16 ins. diam., bears S. 10¾° W., 121 lks. dist., with scribe marks 1/4 S14 BT visible on unhealed blaze.</p> <p style="padding-left: 40px;">A juniper, 18 ins. diam., bears N. 29° W., 51 lks. dist., with scribe marks 1/4 S11 BT visible on unhealed blaze.</p> <p>Add the marks T11N R3E 2001 to the brass cap.</p>
	<p>From the 1/4 sec. cor. of secs. 10 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 3 ft. base, to top, with a mound of stone, 2½ ft. base, 1 ft. high, to the W., with brass cap mkd. 1/4 S10 S11 1917, from which the original bearing tree</p> <p style="padding-left: 40px;">A juniper, 16 ins. diam., bears N. 71½° E., 11 lks. dist., with scribe marks 1/4 S11 BT visible on unhealed blaze.</p> <p>Add the marks T11N R3E 2001 to the brass cap.</p> <p>N. 0°03' W., bet. secs. 10 and 11.</p> <p>Over rolling rocky land through scattering undergrowth.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.01	<p>The cor. of secs. 2, 3, 10 and 11, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above ground, in a collar of stone, with a mound of stone, 3 ft. base, 1 ft. high, to the W., with brass cap mkd. T11N T3E S3 S2 S10 S11 1917.</p> <p>Add the marks 2001 to the brass cap.</p> <hr/>
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°58' W., bet. secs. 2 and 11.</p> <p>Over rolling rocky land through scattering juniper.</p>
20.03	<p>Point for the E. 1/16 sec. cor. of secs. 2 and 11. Not monumented.</p>
40.06	<p>The 1/4 sec. cor. of secs. 2 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with a mound of stone, 2 ft. base, 1 ft. high, to the N., with brass cap mkd. 1/4 S2 S11 1917.</p> <p>Add the marks T11N R3E 2001 to the brass cap.</p> <p>Raise a mound of stone, 3 ft. base, to top, around iron post.</p> <p>Cor. is located in a 4 strand barbed wire fence, bears E. and W.</p> <hr/> <p>West, beginning new measurement.</p>
39.92	<p>The cor. of secs. 2, 3, 10 and 11.</p> <hr/> <p>N. 0°21' W., bet. secs. 2 and 3.</p> <p>Over rolling rocky grassland through scattering undergrowth.</p>
40.32	<p>The 1/4 sec. cor. of secs. 2 and 3, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with a mound of stone, 2½ ft. base, 1 ft. high, to the W., with brass cap mkd. 1/4 S3 S2 1917.</p> <p>Add the marks T11N R3E 2001 to the brass cap.</p> <p>Raise a mound of stone, 3 ft. base, to top, around iron post.</p> <hr/> <p>N. 0°18' W., beginning new measurement.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS																
45.99	<p>The cor. of secs. 2 and 3 only, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 28 and 33 only, monumented with a volcanic stone, 18 x 10 x 7 ins., lying loosely on top of the ground, with a mound of stone, 2½ ft. base, 1 ft. high, to the W., mkd. with 3 notches on the S. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td></td> <td>T11N R3E</td> <td></td> </tr> <tr> <td></td> <td>S28</td> <td> </td> </tr> <tr> <td></td> <td>-----</td> <td> </td> </tr> <tr> <td></td> <td>S33</td> <td> </td> </tr> <tr> <td></td> <td>2002</td> <td></td> </tr> </table> </div> <p>from which a new bearing object</p> <p style="padding-left: 40px;">A volcanic boulder 5 x 4 x 3 ft. above ground, bears N. 37¾° E., 74 lks. dist., mkd. X BO on top.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the original stone in the mound of stone alongside the stainless steel post.</p> <p>From this cor. point, the cor. of secs. 27 and 34 only, bears S. 3°15' E. 0.71 ch. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 24 ins. above ground, in a supporting mound of stone, 3 ft. base, 2½ ft. high, with a mound of stone, 2 ft. base, 1½ ft. high, to the E., with brass cap mkd. T11N S27 S34 R3E 1917.</p> <p>From this same cor. point, the 1/4 sec. cor. of secs. 25 and 36, bears S. 89°53' E., 203.41 chs. dist., hereinbefore described.</p> <p>N. 0°16' W., on the E. bdy. of sec. 28.</p> <p>Over rolling terrain, through scattering juniper.</p>		T11N R3E			S28			-----			S33			2002	
	T11N R3E															
	S28															

	S33															
	2002															
39.29	<p>The 1/4 sec. cor. of sec. 27 only, monumented with an iron post, 1 in. diam., loosely set, projecting 24 ins. above ground, in a collar of stone, with brass cap mkd. 1/4 S27 1917.</p> <hr/> <p>N. 0°16' W., beginning new measurement.</p>															

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona**

CHAINS	
0.53	<p>The 1/4 sec. cor. of sec. 28 only, determined at record bearing and distance from the original bearing tree</p> <p align="center">A juniper, 14 ins. diam., bears S. 30°10' E., 128 lks. dist., with fragmentary scribe marks visible on opened blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 4½ ft. base, to top, with brass cap mkd.</p> <p align="center">T11N R3E 1/4 S28 2001</p> <p>from which a new bearing object</p> <p align="center">A volcanic boulder, 5 x 3 x 1 ft. above ground, bears N. 85¼° W., 205 lks. dist., mkd. X BO on top.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Rebuild mound of stone, 4½ ft. base, 2 ft. high.</p> <p>Cor. falls in 4 strand barbed wire fence extending E. and W.</p> <hr/> <p>N. 0°07' W., beginning new measurement.</p> <p>Over rolling terrain, through scattering juniper.</p>
39.39	<p>The cor. of secs. 22 and 27 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 19 ins. above ground, with a mound of stone, 4 ft. base, 1½ ft. high E. of corner, with brass cap mkd. T11N S22 S27 R3E 1917.</p> <p>Add the marks 2002 to brass cap.</p> <hr/> <p>N. 0°07' W., beginning new measurement.</p>
0.43	<p>The cor. of secs. 21 and 28 only, monumented with a volcanic stone, 24 x 13 x 8 ins., firmly set, projecting 15 ins. above ground, with 2 notches on S. and 3 notches of E. faces.</p> <p>At the corner point</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R3E S21 ----- S28 2002</p> </div> <p>from which a new bearing object</p> <p style="padding-left: 40px;">A volcanic boulder, 9 x 7 x 3 ft., bears S. 34½° W., 36 lks. dist., mkd. X BO on N. side of W. face.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the original stone in the mound of stone, alongside the stainless steel post.</p>
	<p>From the 1/4 sec. cor. of sec. 9 only, bet. secs. 9 and 10, monumented with a volcanic stone, 28 x 12 x 6 ins., loosely set, projecting 10 ins. above ground, no discernable marks, with a mound of stone, 2½ ft. base, 1 ft. high, to the W.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R3E 1/4 S9 2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the original stone in the mound of stone, alongside the stainless steel post.</p> <p>Cor. is located in a 4 strand barbed wire fence, bears N. and S. N. 0°35' E., on the E. bdy. of sec. 9.</p> <p>Over broken rocky land through scattering juniper.</p>
1.11	<p>The 1/4 sec. cor. of sec. 10 only, monumented with an iron post, 1 in. diam., loosely set, projecting 18 ins. above ground, in a scattered mound of stone, with a mound of stone, 2½ ft. base, 1 ft. high, to the E., with brass cap mkd. 1/4 S10 1917.</p> <p>Add the marks T11N R3E 2001 to the brass cap.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS							
	<p>Raise a mound of stone, 3 ft. base, 1½ ft. high, around iron post.</p> <p>Cor. is located 1 lk. W. of a 4 strand barbed wire fence, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°35' E., beginning new measurement.</p>						
19.98	Point for the N. 1/16 of sec. 10 only. Not monumented.						
38.70	<p>The cor. of secs. 4 and 9 only, monumented with a volcanic stone, 18 x 14 x 6 ins., firmly set, projecting 10 ins. above ground, in a scattered mound of stone, with 5 grooves on S. face and 4 grooves on E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T11N R3E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S4</td> <td style="padding: 2px 5px;"> </td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S9</td> <td style="padding: 2px 5px;"> </td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">2001</td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, to the W.</p> <p>Deposit the original stone in the mound of stone.</p> <p>Cor. is located in an ancient wood post fence line, bears S., no remaining wire, and 9 lks. E. of a juniper fence post, with 4 strand barbed wire fence extending S. and W.</p> <hr style="width: 80%; margin: 10px auto;"/>	S4		S9		2001	
S4							
S9							
2001							
1.27	<p>N. 7°21' W., on the E. bdy. of sec. 4.</p> <p>The cor. of secs. 3 and 10 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with an embedded mound of stone to the E., with brass cap mkd. T11N S3 S10 R3E 1917.</p> <p>Add the marks 2001 to the brass cap.</p> <p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, to the E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 7°21' W., beginning new measurement.</p>						

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.23	<p>The 1/4 sec. cor. of sec. 3 only, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with a mound of stone, 3 ft. base, 1 ft. high, to the E., with brass cap mkd. 1/4 S3 1917.</p> <p>Add the marks T11N R3E 2001 to the brass cap.</p> <hr/> <p>N. 7°21' W., beginning new measurement.</p>
0.16	<p>The 1/4 sec. cor. of sec. 4 only, monumented with a volcanic stone, 20 x 8 x 3 ins., firmly set, projecting 8 ins. above ground, with a mound of stone, 2½ ft. base, 1 ft. high, to the E., mkd. 1/4 on the W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E 1/4 S4 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the original stone in the mound of stone, alongside the stainless steel post.</p> <hr/> <p>N. 8°00' W., beginning new measurement.</p>
47.46	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 89°54' W., bet. secs. 3 and 10.</p> <p>Over rolling rocky terrain through scattering undergrowth.</p>
39.99	<p>The 1/4 sec. cor. of secs. 3 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. 1/4 S3 S10 1917.</p> <p>Add the marks T11N R3E 2001 to the brass cap.</p> <p>Raise a mound of stone, 2½ ft. base, 1 ft. high, around the iron post.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located 6 lks. W. of a wooden fence post, with 4 strand barbed wire fence extending N., S. and E.</p> <hr style="width: 30%; margin: 10px auto;"/>
	<p>N. 89°59' W., beginning new measurement.</p>
20.00	<p>Point for the W. 1/16 sec. cor. of secs. 3 and 10. Not monumented.</p>
42.84	<p>The cor. of secs. 3 and 10 only.</p> <hr style="width: 80%; margin: 10px auto;"/>
	<p>From the cor. of secs. 28 and 33 only.</p>
	<p>S. 89°54' W., bet. secs. 28 and 33.</p>
	<p>Over rolling rocky terrain.</p>
40.07	<p>Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T11N R3E S28 1/4 ——— S33 2002</p> </div>
	<p>from which</p>
	<p style="text-align: center;">A forked juniper, 6 ins. diam., bears N. 3½° E., 139 lks. dist., mkd. X BT.</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.20	<p>Point for the cor. of secs. 28, 29, 32, and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T11N R3E S29 S28 ——— S32 S33 2002</p> </div>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A granite boulder, 10 x 5 x 4 ft. above the ground, bears S. 82° E., 98 lks. dist., mkd. X BO.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. falls on top of a hill.</p> <p>From this cor. point, the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., bears S. 0°57' E., 79.69 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. T11N R3E S32 S33 S5 S4 T10N 1933.</p> <p>Add the marks 2002 to brass cap.</p> <p>From this same cor. point, a county monument, monumented with a rebar, firmly set, flush with the ground, with affixed aluminum cap, bears S. 57°17' W., 0.98 ch. dist., mkd. YAVAPAI COUNTY GIS GPS 111032321013 RLS 13190.</p> <p>From this same cor. point, a rebar, ½ in. diam., firmly set, flush with the ground, with affixed yellow plastic cap mkd. LS 24522, bears N. 16°17' W., 1.78 chs. dist.</p>
39.84	<p>N. 0°10' E., bet. secs. 28 and 29.</p> <p>Over rolling terrain through scattering juniper.</p> <p>Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T11N R3E 1/4 S29 S28 2002</p> </div> <p>from which</p> <p style="padding-left: 40px;">A granite boulder, 18 x 12 x 12 ft., 18 ft. above ground, bears S. 88¾° W., 399 lks. dist., mkd. X BO.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona**

CHAINS											
	Cor. falls on N. bank of Agua Fria River, 114 lks. wide, bears S. 80° W. and N. 50° W.										
78.80	Dirt Road, 18 lks. wide, bears S. 80° E. and N. 80° W.										
79.68	Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.										
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.										
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T11N R3E</td> </tr> <tr> <td style="text-align: center;">S20</td> <td style="text-align: center;">S21</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S29</td> <td style="text-align: center;">S28</td> </tr> <tr> <td colspan="2" style="text-align: center;">2002</td> </tr> </table>	T11N R3E		S20	S21	-----		S29	S28	2002	
T11N R3E											
S20	S21										

S29	S28										
2002											
	from which										
	<p style="text-align: center;">A granite boulder 10 x 7 x 6 ft., 7 ft. above ground, bears S. 82¾° W., 5.14 chs. dist., mkd. X BO.</p>										
	Deposit a magnet in a white plastic case at the base of the stainless steel post.										
	Cor. falls in the middle of a dirt tank.										
	Set a steel fence post S. of cor.										
	From the cor. of secs. 21 and 28 only.										
	N. 87°41' W., bet. secs. 21 and 28.										
	Over rolling terrain through scattering juniper.										
39.23	The 1/4 sec. cor. of secs. 21 and 28, monumented with a volcanic stone, 22 x 12 x 6 ins., firmly set, projecting 15 ins. above ground, mkd. 1/4 on N. face, in a mound of stone, 3 ft. base, 1 ft. high.										
	At the corner point										
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.										
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T11N R3E</td> </tr> <tr> <td colspan="2" style="text-align: center;">S21</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">1/4</td> <td style="text-align: center;">S28</td> </tr> <tr> <td colspan="2" style="text-align: center;">2001</td> </tr> </table>	T11N R3E		S21		-----		1/4	S28	2001	
T11N R3E											
S21											

1/4	S28										
2001											

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which a new bearing object</p> <p style="padding-left: 40px;">A volcanic boulder, 3 x 2 x 1 ft., bears N. 6½° E., 42 lks. dist., mkd. X BO on top.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the original stone in the mound of stone, alongside the stainless steel post.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S. 87°36' W. beginning new measurement.</p>
18.48	Barbed wire fence, 5 strand, bears S. 19° E. and N. 19° W.
20.265	<p>Point for the W. 1/16 cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T11N R3E</p> <p style="padding-left: 40px;">S21</p> <p style="padding-left: 20px;">W 1/16 ———</p> <p style="padding-left: 40px;">S28</p> <p style="padding-left: 40px;">2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
21.30	E. bank of Agua Fria River, 48 lks. wide, bears S. 19° E. and N. 19° W.
39.60	Dirt Road, 18 ft. wide, bears S. 23° E. and N. 31° W.
40.53	The cor. of secs. 20, 21, 28 and 29.
	<hr/> <p>N. 7°43' W., bet. secs. 20 and 21.</p> <p>Over rolling terrain through scattering juniper.</p>
40.86	<p>Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T11N R3E</p> <p style="padding-left: 40px;">1/4</p> <p style="padding-left: 20px;">S20 S21</p> <p style="padding-left: 40px;">2002</p> </div>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona**

CHAINS																			
81.72	<p>The cor. of secs. 16, 17, 20, and 21, perpetuated by Bruce Witcher, Arizona Registered Land Surveyor No. 16626, in 1986, as shown on Book 6, Page 23 of Land Surveys, in the Yavapai County Recorders office, Prescott, Arizona, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 3 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with affixed aluminum cap mkd. RLS 16626 T11N S16 S17 S20 S21 R3E 1986. This is accepted as a careful and faithful perpetuation of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <table border="1" data-bbox="846 825 1024 972" style="margin-left: auto; margin-right: auto;"> <tr> <td>T11N</td> <td>R3E</td> </tr> <tr> <td>S17</td> <td>S16</td> </tr> <tr> <td>S20</td> <td>S21</td> </tr> <tr> <td colspan="2" style="text-align: center;">2002</td> </tr> </table> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A forked juniper, 21 ins. diam., bears S. 67¾° E., 124 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears S. 49¼° W., 117 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the rebar inside the stainless steel post.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 16 and 21, monumented with a granite stone, 25 x 9 x 6 ins., firmly set, projecting 14 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, mkd. 1/4 on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <table border="1" data-bbox="862 1755 1008 1902" style="margin-left: auto; margin-right: auto;"> <tr> <td>T11N</td> <td>R3E</td> </tr> <tr> <td></td> <td>S16</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S21</td> </tr> <tr> <td colspan="2" style="text-align: center;">2001</td> </tr> </table>	T11N	R3E	S17	S16	S20	S21	2002		T11N	R3E		S16	1/4	_____		S21	2001	
T11N	R3E																		
S17	S16																		
S20	S21																		
2002																			
T11N	R3E																		
	S16																		
1/4	_____																		
	S21																		
2001																			

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
45.55	<p>from which a new bearing object</p> <p>A granite boulder, 8 x 5 x 3 ft. above ground, bears S. 71½° E., 54 lks. dist., mkd. X BO on top.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the original stone in the mound of stone, alongside the stainless steel post.</p> <p>Cor. is located alongside 4 strand barbed wire fence, bears E. and W.</p> <p>N. 89°23' W., bet. secs. 16 and 21.</p> <p>Over rolling terrain with scattering juniper and cacti.</p> <p>The cor. of secs. 16, 17, 20, and 21.</p>
39.40	<p>N. 0°47' E., bet. secs. 16 and 17.</p> <p>Over rolling terrain with scattering juniper.</p> <p>South bank of Sycamore Creek, 74 lks. wide, bears N. 71° E. and S. 68° W.</p>
40.77	<p>The 1/4 sec. cor. of secs. 16 and 17, reestablished by Bruce Witcher, Arizona Registered Land Surveyor No. 16626, in 1986, and recorded in the Yavapai County Recorders office, Prescott, Arizona, Book 6, Page 23 of Land Surveys, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 8 ins. above ground, in a mound of stone 3 ft. base, 1 ft. high, with affixed aluminum cap mkd. RLS 16626 1/4 S16 S17 T11N R3E 1986. This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R3E 1/4 S17 S16 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the rebar inside the stainless steel post.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona**

CHAINS									
40.76	<p>Set a steel fence post to the N.</p> <hr/> <p>N. 0°47' E., beginning new measurement.</p> <p>The cor. of secs. 8, 9, 16 and 17, determined by verbal testimony of Mr. Albert McDonald, ranch manager for E-Z Ranch and Mr. Lester Smith, owner, who perpetuated the original corner position as identified by Bruce Witcher, Arizona Registered Land Surveyor No. 16626, in 1986, as shown on Book 6, Pages 22 and 23 of Land Surveys, in the Yavapai County Recorders office, Prescott, Arizona. Mr. McDonald and Mr. Smith established reference points 10 ft. E. and 10 ft. N. of the original cor. position in order to preserve it and facilitate construction of a road.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <table border="1" data-bbox="852 982 1019 1136" style="margin-left: auto; margin-right: auto;"> <tr> <td>T11N</td> <td>R3E</td> </tr> <tr> <td>S8</td> <td>S9</td> </tr> <tr> <td>S17</td> <td>S16</td> </tr> <tr> <td colspan="2" style="text-align: center;">2002</td> </tr> </table> <p>from which new bearing objects</p> <p style="padding-left: 40px;">A volcanic boulder, 4 x 3 x 1½ ft. above the ground, bears N. 37½° E., 59 lks. dist., mkd. X BO.</p> <p style="padding-left: 40px;">A volcanic boulder, 5 x 3 x 3 ft. above the ground, bears S. 66° E., 69 lks. dist., mkd. X BO on top.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located at the corner of a dirt road, 18 ft. wide, bears S. and W.</p> <hr/>	T11N	R3E	S8	S9	S17	S16	2002	
T11N	R3E								
S8	S9								
S17	S16								
2002									
45.18	<p>From the cor. of secs. 4 and 9 only.</p> <p>N. 86°54' W., bet. secs. 4 and 9.</p> <p>Over rolling rocky grassland through scattering juniper.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p>								

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E S4 1/4 ——— S9 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
90.36	<p>The cor. of secs. 4, 5, 8 and 9, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 2 ins. above ground, with affixed yellow plastic cap mkd. RLS 16626, at the intersection of ancient fences, with 4 strand barbed wire fences extending N., S. and E., set by Bruce Witcher, Arizona Registered Land Surveyor No. 16626, in 1986, as shown on Book 7, Page 75 of Land Surveys, in the Yavapai County Recorders office, Prescott, Arizona. This is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E S5 S4 ——— S8 S9 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the rebar inside the stainless steel post.</p>
	<p>N. 0°51' E., bet. secs. 4 and 5.</p> <p>Over rolling rocky land through scattering undergrowth.</p>
37.20	<p>East fork of Ash Creek, 20 lks. wide, 1 ft. deep, course N. 60° W.</p>
40.64	<p>The 1/4 sec. cor. of secs. 4 and 5, perpetuated by Bruce Witcher, Arizona Registered Land Surveyor No. 16626, in 1986, as shown on Book 7, Page 75 of Land Surveys, in the Yavapai County Recorders office, Prescott, Arizona, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 3 ins. above ground, in a mound of stone, 2½ ft. base, 1½ ft. high, with</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>affixed aluminum cap mkd. RLS 16626 1/4 T11N S5 S4 R3E 1986. The decayed remnants of a wooden post were found alongside the rebar, in the mound of stone. This is accepted as a careful and faithful perpetuation of the original cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p align="center">T11N R3E 1/4 S5 S4 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the rebar inside the stainless steel post.</p> <p>Cor. is located in a 4 strand barbed wire fence, bears N. and S.</p> <hr/> <p>N. 0°21' E., beginning new measurement.</p>
40.82	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/>
39.70	<p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>N. 88°04' W., bet. secs. 29 and 32.</p> <p>Over rolling terrain through scattering juniper and cacti.</p> <p>The 1/4 sec. cor. of secs. 29 and 32, monumented with a granite stone, 27 x 16 x 10 ins., firmly set, projecting 19 ins. above the ground, with a mound of stone, 2½ ft. base, 1 ft. high, to the S., mkd. 1/4 on the N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p align="center">T11N R3E S29 1/4 ——— S32 2001</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>from which a new bearing object</p> <p>A granite boulder, 8 x 7½ x 5 ft., bears S. 3¾° W., 252 lks. dist., mkd. X BO on top.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the original stone in the mound of stone, alongside the stainless steel post.</p> <p>Cor. is located 45 lks. E. of a dirt road, 8 ft. wide, bears S. 85° E. and N. 45° W.</p> <hr/> <p>S. 89°43' W., beginning new measurement.</p>								
38.60	<p>The cor. of secs. 29, 30, 31, and 32, monumented with a granite stone, 24 x 13 x 10 ins., firmly set, projecting 6 ins. above ground, with a mound of stone, 4 ft. base, 3 ft. high, to the E., mkd. with 5 notches on E. and 1 notch on S faces.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <table data-bbox="846 1136 1019 1283" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T11N R3E</td> </tr> <tr> <td style="text-align: center;">S30</td> <td style="text-align: center;">S29</td> </tr> <tr> <td style="text-align: center;">S31</td> <td style="text-align: center;">S32</td> </tr> <tr> <td colspan="2" style="text-align: center;">2001</td> </tr> </table> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the original stone in the mound of stone, alongside the stainless steel post.</p> <p>Cor. is located 5.25 chs., N. of a dirt road, 8 ft. wide, bears N. 66° E. and S. 66° W.</p> <hr/> <p>N. 89°05' W., bet. secs. 30 and 31.</p> <p>Over rolling terrain though scattering juniper and cacti.</p>	T11N R3E		S30	S29	S31	S32	2001	
T11N R3E									
S30	S29								
S31	S32								
2001									
39.61	<p>The ¼ sec. cor. of secs. 30 and 31, monumented with a granite stone, 25 x 12 x 8 ins., lying loose in a mound of stone, 4 ft. base, 1 ft. high, mkd. ¼ on the N. face.</p> <p>At the corner point</p>								

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 17 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E S30 1/4 ——— S31 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and bury the original stone alongside the stainless steel post.</p> <hr/> <p>N. 88°40' W., beginning new measurement.</p>
21.51	<p>Point for the W. 1/16 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E S30 W 1/16 ——— S31 2002</p> <p>from which</p> <p style="text-align: center;">A granite boulder 8 x 5 x 3 ft., bears S. 0¾° W., 358 lks. dist., mkd. X BO.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 63 lks., S. 50° W., of a 5 strand barbed wire fence cor. with fences extending N. 26° W. and W.</p>
52.83	<p>The cor. of secs. 30 and 31 only, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 0°09' E., bet. secs. 29 and 30.</p> <p>Over rolling terrain though scattering juniper and cacti.</p>
19.86	<p>Point for the S. 1/16 sec. cor. of secs. 29 and 30.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T11N R3E S 1/16 S30 S29 2001</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
21.59	<p>Barbed wire fence, 5 strand, bears S. 82° E. and N. 82° W.</p>
28.05	<p>Dirt road, 12 lks. wide, bears S. 58° W. and N. 85° W.</p>
39.72	<p>The 1/4 sec. cor. of secs. 29 and 30, monumented with a granite stone, 16 x 9 x 5 ins., firmly set, projecting 4 ins. above ground, mkd. 1/4 on the W. face.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T11N R3E 1/4 S30 S29 2001</p>
	<p>from which a new bearing object</p>
	<p style="text-align: center;">A granite boulder, 9 x 7 x 6 ft. above the ground, bears N. 88° E., 371 lks. dist., mkd. X BO on top.</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the original stone in the mound of stone, alongside the stainless steel post.</p>
	<p style="text-align: center;">_____</p> <p>N. 0°18' W., beginning new measurement.</p>
39.33	<p>The cor. of secs. 19, 20, 29 and 30, monumented with a granite stone, 24 x 11 x 4 ins., firmly set, projecting 14 ins. above ground, mkd. with 5 notches on the E. and 2 notches on the S. faces.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 13 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T11N R3E</td></tr> <tr><td>S19</td><td>S20</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S30</td><td>S29</td></tr> <tr><td colspan="2">2001</td></tr> </table> <p>from which a new bearing tree and bearing object</p> <p>A granite boulder, $7\frac{1}{2} \times 4\frac{1}{2} \times 4$ ft. above ground, bears S. $76\frac{3}{4}^\circ$ W., 35 lks. dist, mkd. X BO on top E. face.</p> <p>A juniper, 18 ins. diam., bears N. 13° W., 52 lks. dist., mkd. T11N R3E S19 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T11N R3E		S19	S20	<hr/>		S30	S29	2001	
T11N R3E											
S19	S20										
<hr/>											
S30	S29										
2001											
39.93	<p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>N. $89^\circ 05'$ W., bet. secs. 20 and 29.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 20 and 29, monumented with a granite stone, $15 \times 10 \times 3$ ins, firmly set, projecting 6 ins. above ground, in a mound of stone, 4 ft. base, 1 ft. high., mkd. $\frac{1}{4}$ on the N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T11N R3E</td></tr> <tr><td colspan="2">S20</td></tr> <tr><td>$\frac{1}{4}$</td><td><hr/></td></tr> <tr><td colspan="2">S29</td></tr> <tr><td colspan="2">2001</td></tr> </table> <p>from which a new bearing object</p> <p>A granite boulder, $3 \times 2\frac{1}{2} \times 1\frac{1}{2}$ ft., 3 ft. above ground, bears N. 46° W., 312 lks. dist., mkd. X BO on top.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the original stone in the mound of stone, alongside the stainless steel post.</p> <p>Cor. is located 18 lks. S. of a dirt road, 18 ft. wide, bears N. 84° E. and S. 60° W.</p>	T11N R3E		S20		$\frac{1}{4}$	<hr/>	S29		2001	
T11N R3E											
S20											
$\frac{1}{4}$	<hr/>										
S29											
2001											

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set steel fence post S. of cor.</p> <hr/> <p>S. 89°48' W., beginning new measurement.</p>
38.69	<p>The cor. of secs. 19, 20, 29, and 30.</p> <hr/>
	<p>N. 88°55' W., bet. secs. 19 and 30.</p> <p>Over rolling terrain though scattering juniper and cacti.</p>
39.80	<p>The 1/4 sec. cor. of secs. 19 and 30, monumented with a granite stone, 22 x 7 x 7 ins., firmly set, projecting 5 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, mkd. 1/4 on the N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R3E S19 1/4 ——— S30 2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and bury the original stone alongside the stainless steel post.</p> <p>Cor. is located 182 lks. E. of a 6 wire power line, bears S. 11° E. and N. 11° W.</p> <hr/>
	<p>N. 87°53' W., beginning new measurement.</p>
53.09	<p>The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/>
	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 8°27' W., bet. secs. 19 and 20.</p>
41.72	<p>The 1/4 sec. cor. of secs. 19 and 20, monumented with a granite stone, 28 x 15 x 12 ins., firmly set, in a mound of stone, 3 ft. base, 2 ft. high, no visible marks.</p> <p>At the corner point</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E 1/4 S19 S20 2001</p> <p>from which the original bearing tree and bearing object</p> <p style="text-align: center;">A juniper, 8 ins. diam., bears S. 86½° W., 101 lks. dist., with scribe marks 1/4 S BT visible on partially open blaze. (Record: S. 84°25' W., no dist.)</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the original stone in the mound of stone, alongside the stainless steel post.</p> <p>Remains of an old school house, bears S. 76½° E., 343 lks. dist. more or less.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 9°08' W., beginning new measurement.</p>
38.59	<p>Point for AP 1, sec. 20.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E AP1 S19 S20 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. falls on the N. edge of a dirt road, 12 lks. wide, bears S. 56° E. and N. 56° W.</p>
41.66	<p>Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS

T11N R3E	
S18	S17

S19	S20
2002	

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Cor. is located 1 lk. S. of a fence cor., with fences extending S. 25° W., S. 71° W. and N. 25° W.

From this cor. point, the 1/4 sec. cor. of secs. 18 and 19, bears N. 89°28' W., 39.72 chs. dist., monumented with a volcanic stone, 20 x 20 x 10 ins., firmly set, in a mound of stone, 4½ ft. base, 1 ft. high, mkd. 1/4 on the S. face.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, in a mound of stone, 6 ft. base, to top, with brass cap mkd.

T11N R3E	
S18	
1/4	-----
S19	
2001	

from which a new bearing object

A volcanic stone, 2½ x 2 x ½ ft. above ground, bears N. 85¾° W., 13 lks. dist., mkd. X BO on top.

Deposit a magnet in a white plastic case at the base of the stainless steel post and place the original stone in the mound of stone, alongside the stainless steel post.

From this same cor. point, the cor. of secs. 7, 8, 17 and 18, bears N. 0°27' E., 81.27 chs. dist., hereinafter described.

This control line was fully retraced and careful search was made for evidence of intervening cors. A local cor. for the 1/4 sec. cor. of secs. 17 and 18 was recovered, but not utilized in this survey, monumented with a rebar, 5/8 in. diam., firmly set, flush with ground, with 1½ in. aluminum cap mkd. RLS 16626 1/4 S18 S17 1986. This position was established at proportionate position using improper control.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this same cor. point, an iron pipe, $\frac{5}{8}$ in. diam., firmly set, flush with the ground, origin unknown, bears N. $59^{\circ} 53'$ W., 1.13 chs. dist. This position was used for control for the local $\frac{1}{4}$ sec. cor. of secs. 17 and 18.</p> <hr/> <p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>N. $87^{\circ}48'$ W., bet. secs. 17 and 20.</p> <p>Over rolling terrain though scattering juniper and cacti.</p>
40.68	<p>The $\frac{1}{4}$ sec. cor. of secs. 17 and 20, perpetuated by Bruce Witcher, Arizona Registered Land Surveyor No. 16626, in 1986, as shown on Book 6, Page 23 of Land Surveys, in the Yavapai County Recorders office, Prescott, Arizona, monumented with a rebar, $\frac{5}{8}$ in. diam., 18 ins. long, firmly set, projecting 4 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with affixed aluminum cap mkd. RLS 16626 $\frac{1}{4}$ T11N S17 S20 R3E 1986. This is accepted as a careful and faithful perpetuation of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with an accessory mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, to the N., with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R3E S17 $\frac{1}{4}$ ——— S20 2002</p> </div> <p>from which a new bearing object</p> <p style="text-align: center;">A granite stone, 2 x 2 x $1\frac{1}{2}$ ft., bears S. 17° E., 129 lks. dist, mkd. X BO.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the rebar inside the stainless steel post.</p> <hr/> <p>N. $89^{\circ}29'$ W., beginning new measurement.</p>
34.77	<p>Point for AP 3, sec. 20.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T11N R3E S17</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">AP3 S20 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. falls on the W. bank of the Agua Fria River, 3 chs. wide, bears S. 28° E. and N. 28° W.</p> <p>39.72 The cor. of. secs. 17, 18, 19 and 20.</p> <hr/>
	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 88°49' W., bet. secs. 8 and 17.</p> <p>Over mountainous terrain though scattering juniper and cacti.</p>
40.42	<p>Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T11N R3E S8</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1/4 ——— S17 2002</p> <p>from which</p> <p style="padding-left: 40px;">A volcanic boulder, 4 x 3½ x 3 ft., bears N. 31¼° E., 83 lks. dist., mkd. X BO.</p> <p style="padding-left: 40px;">A volcanic boulder, 5 x 2 x 2 ft., bears N. 56° W., 108 lks. dist., mkd. X BO.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. falls in the middle of a dirt road, 12 ft. wide, bears E. and W.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona**

CHAINS											
80.84	<p>The cor. of secs. 7, 8, 17 and 18, recovered by Bruce Witcher, Arizona Registered Land Surveyor No. 16626, in 1986, as shown on Book 6, Pages 22 and 23 of Land Surveys, in the Yavapai County Recorders office, Prescott, Arizona, and perpetuated by Dale Famas, Arizona Registered Land Surveyor No. 27738, monumented with a rebar, ½ in. diam., 18 ins. long, firmly set, projecting 3 ins. above ground, in a mound of stone, 4 ft. base, 1 ft. high, with affixed yellow plastic cap mkd. FAMAS RLS 27738. This is accepted as a careful and faithful perpetuation of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <table border="1" data-bbox="846 825 1019 972" style="margin-left: auto; margin-right: auto;"> <tr> <td>T11N</td> <td>R3E</td> </tr> <tr> <td>S7</td> <td>S8</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> <tr> <td colspan="2" style="text-align: center;">2002</td> </tr> </table> <p>from which a new bearing object</p> <p style="padding-left: 40px;">A juniper, 7 ins. diam., bears N. 12½° E., 439 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the rebar inside the stainless steel post.</p>	T11N	R3E	S7	S8			S18	S17	2002	
T11N	R3E										
S7	S8										
S18	S17										
2002											
	<p>N. 89°03' W., bet. secs. 7 and 18.</p>										
	<p>Over rolling terrain through scattering juniper and cacti.</p>										
40.29	<p>The ¼ sec. cor. of secs. 7 and 18, monumented with a rebar, ⅝ in. diam., 15 ins. long, firmly set, projecting 5 ins. above ground, origin unknown. This position is harmoniously related to existing cors. and is accepted as the best available evidence of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>										

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T11N R3E S7 1/4 ——— S18 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located alongside wooden 4 stand barbed wire fence cor., with fences extending N., E. and S.</p>
39.92	<p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°14' E., bet. secs. 7 and 8.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
79.84	<p style="text-align: center;">T11N R3E 1/4 S7 S8 2002</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 11 ins. diam., bears S. 21½° W., 328 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 70 lks. E. of a dirt road, 24 lks. wide, course N. and S.</p> <p>The cor. of secs. 5, 6, 7 and 8, monumented with a rebar, ½ in. diam., 18 ins. long, firmly set, projecting 2 ins. above ground, in a mound of stone, 4 ft. base, 1 ft. high, with affixed washer stamped RCE 2398, and recorded by Bruce Witcher, Arizona Registered Land Surveyor No. 16626, in 1986, as shown on Book 6, Pages 21 and 22 of Land Surveys, in the Yavapai County Recorders office, Prescott, Arizona. This position is accepted as the best available evidence of the original cor.</p> <p>At the corner point</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS											
40.31	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 6½ ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T11N</td> <td>R3E</td> </tr> <tr> <td>S6</td> <td>S5</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S7</td> <td>S8</td> </tr> <tr> <td colspan="2">2002</td> </tr> </table> </div> <p>from which new bearing objects</p> <p style="padding-left: 40px;">A volcanic boulder, 2 x 2 x 1 ft., bears S. 60¾° E., 94 lks. dist., mkd. X BO on top.</p> <p style="padding-left: 40px;">A volcanic boulder, 2 x 2 x 1 ft., bears S. 59¼° W., 94 lks. dist., mkd. X BO on top.</p> <p style="padding-left: 40px;">The SE cor. of a trailer, 20 x 16 ft. bears N. 53½° W., 160 lks. dist., long side bears N.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the rebar inside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>N. 89°28' W., bet. secs. 5 and 8.</p> <p>Over rolling terrain through scattering juniper and cacti.</p> <p>The 1/4 sec. cor. bet. secs. 5 and 8, reestablished by Bruce Witcher, Arizona Registered Land Surveyor No. 16626, in 1986, and recorded in the Yavapai County Recorders office, Prescott, Arizona, Book 6, Pages 21 and 22 of Land Surveys, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 8 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with affixed aluminum cap mkd. RLS 16626 1/4 T11N S5 S8 R3E 1986. This position is accepted as a careful and faithful reestablishment of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p>	T11N	R3E	S6	S5			S7	S8	2002	
T11N	R3E										
S6	S5										
S7	S8										
2002											

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T11N R3E S5 1/4 ——— S8 2002</p> <p>from which new bearing objects</p> <p style="padding-left: 40px;">A granite boulder, 5 x 5 x 4 ft., bears N. 49½° E., 73 lks. dist., mkd. X BO on top.</p> <p style="padding-left: 40px;">A granite boulder, 7 x 6 x 4 ft., bears S. 82½° W., 78 lks. dist., mkd. X BO on NE face.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place rebar inside stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89°28'W., beginning new measurement.</p>
40.31	<p>The cor. of secs. 5, 6, 7, and 8.</p> <hr/>
	<p>N. 87°27' W., bet. secs. 6 and 7.</p> <p>Over rolling terrain through scattering juniper and cacti.</p>
41.13	<p>Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T11N R3E S6 1/4 ——— S7 2002</p> <p>from which</p> <p style="padding-left: 40px;">A volcanic boulder, 3 x 2½ x 1½ ft., bears S. 63½° E., 53 lks. dist., mkd. X BO on top.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this point, a rebar, 5/8 in. diam, firmly set, projecting 3 ins. above ground, in a collar of stone, origin unknown, bears N. 46°52' W., 2.36 chs. dist.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.82	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/>
	<p>From the cor. of secs. 5, 6, 7 and 8.</p>
	<p>N. 0°46' E., bet. secs. 5 and 6.</p>
	<p>Over rolling terrain though scattering juniper and cacti.</p>
40.75	<p>The 1/4 sec. cor. of secs. 5 and 6, perpetuated by Bruce Witcher, Arizona Registered Land Surveyor No. 16626, as shown on Book 6, Page 21 of Land Surveys, in the Yavapai County Recorders office, Prescott, Arizona, monumented with a rebar, 5/8 in. diam., firmly set, flush with the ground, in a mound of stone, 3 ft. base, 1 ft. high, with affixed yellow cap mkd. RLS 16626. This is accepted as a careful and faithful perpetuation of the original cor. position.</p>
	<p>At the corner point.</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p align="center">T11N R3E 1/4 S6 S5 2002</p>
	<p>from which a new bearing object</p>
	<p align="center">A volcanic boulder, 3½ x 2 x 1½ ft., bears N. 75¼° E., 64 lks. dist, mkd. X BO on top.</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the rebar inside the stainless steel post.</p>
	<p>From this cor. point, a steel fence post, bears S. 60° E., 5 lks. dist.</p> <hr/>
	<p>N. 0°37' E., beginning new measurement.</p>
40.58	<p>The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/>

Subdivision of Section 1,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 1 and 12.</p> <p>N. 0°03' W., on the N. and S. center line of sec. 1.</p> <p>Over mountainous land through scattering juniper.</p>
19.97	Point for the center S. 1/16 sec. cor. of sec. 1. Not monumented.
39.94	<p>Point for the center 1/4 sec. cor. of sec. 1, at intersection with the E. and W. center line of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E C 1/4 S1 2001</p>
59.99	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the center N. 1/16 sec. cor. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E C N 1/16 S1 C 2001</p>
85.35	<p>The 1/4 sec. cor. of secs. 1 and 36, on the N. bdy. of the Tp.</p> <hr/> <p>From the 1/4 sec. cor. of sec. 1 only, on the E. bdy. of the Tp.</p> <p>S. 89°42' W., on the E. and W. center line of sec. 1.</p> <p>Over rolling rocky land through scattering juniper.</p>
19.46	Point for the center E. 1/16 sec. cor. of sec. 1. Not monumented.
39.46	The center 1/4 sec. cor. of sec. 1.
59.49	Point for the center W. 1/16 sec. cor. of sec. 1.

Subdivision of Section 1,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E W 1/16 C ——— C S1 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.52	<p>The 1/4 sec. cor. of secs. 1 and 2.</p>
	<hr/> <p style="text-align: center;">NE 1/4 of Sec. 1</p> <hr/> <p>From the point for the center E. 1/16 sec. cor. of sec. 1. North, on the N. and S. center line of the NE 1/4 of sec. 1. Over rolling rocky land through scattering juniper.</p>
20.02	<p>Point for the NE 1/16 sec. cor. of sec. 1, at intersection with the E. and W. center line of the NE 1/4 of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E NE 1/16 S1 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
45.22	<p>The E. 1/16 sec. cor. of secs. 1 and 36, on the N. bdy. of the Tp.</p>
	<hr/> <p>From the point for the N. 1/16 sec. cor. of sec. 1 only, on the E. bdy. of the Tp.</p> <p>S. 89°46' W., on the E. and W. center line of the NE 1/4 of sec. 1.</p> <p>Over rolling rocky land through scattering juniper.</p>
19.68	<p>The NE 1/16 sec. cor. of sec. 1.</p>

Subdivision of Section 1,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.70	<p>The center N. 1/16 sec. cor. of sec. 1.</p> <hr/> <p style="text-align: center;">SW 1/4 of Sec. 1</p> <hr style="width: 30%; margin: auto;"/> <p>From the point for the W. 1/16 sec. cor. of secs. 1 and 12. N. 0°10' W., on the N. and S. center line of the SW 1/4 of sec. 1.</p> <p>Over rolling rocky land through scattering juniper.</p>
19.99	<p>Point for the SW 1/16 sec. cor. of sec. 1, at intersection with the E. and W. center line of the SW 1/4 of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E SW 1/16 S1 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
39.98	<p>The center W. 1/16 sec. cor. of sec. 1.</p> <hr/> <p>From the point for the center S. 1/16 sec. cor. of sec. 1. S. 89°39' W., on the E. and W. center line of the SW 1/4 of sec. 1.</p> <p>Over rolling rocky land through scattering juniper.</p>
19.99	<p>The SW 1/16 sec. cor. of sec. 1.</p>
39.98	<p>The S. 1/16 sec. cor. of secs. 1 and 2.</p> <hr/> <p style="text-align: center;">Subdivision of Section 3, T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 10. N. 0°18' W., on the N. and S. center line of sec. 3.</p> <p>Over gently rolling rocky grassland.</p>

Subdivision of Section 3,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.17	<p>Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E. and W. center line of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E C 1/4 S3 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 7 lks. W. of a 4 strand barbed wire fence, bears N. and S.</p>
86.66	<p>The 1/4 sec. cor. of sec. 3 only, on the N. bdy. of the Tp.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 2 and 3.</p> <p>S. 89°41' W., on the E. and W. center line of sec. 3.</p> <p>Over rolling rocky grassland.</p>
39.95	<p>The center 1/4 sec. cor. of sec. 3.</p>
79.95	<p>Point for the center 80 1/16 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E 1/16 C ——— 80 S3 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
87.73	<p>The 1/4 sec. cor. of sec. 3 only, on the W. bdy. of sec. 3.</p> <hr/> <p style="text-align: center;">NW 1/4 of Sec. 3</p> <hr/> <p>From the center 80 1/16 sec. cor. of sec. 3.</p> <p>N. 0°18' W., on the 80 1/16 line of sec. 3.</p> <p>Over rolling rocky grassland.</p>

Subdivision of Section 3,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
47.01	<p>The 80 1/16 sec. cor. of sec. 3, on the N. bdy. of the Tp.</p> <hr/> <p style="text-align: center;">Subdivision of Section 4, T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 4 and 9.</p> <p>N. 3°43' W., on the N. and S. center line of sec. 4.</p> <p>Over rolling rocky land through scattering undergrowth.</p>
41.08	<p>Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E. and W. center line of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 3 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E C 1/4 S4 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
85.13	<p>True point for the 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.</p> <hr/> <p>From the 1/4 sec. cor. of sec. 4 only, on the E. bdy. of sec. 4.</p> <p>N. 87°08' W., on the E. and W. center line of sec. 4.</p> <p>Over rolling rocky grassland through scattering juniper.</p>
42.50	<p>The center 1/4 sec. cor. of sec. 4.</p>
63.44	<p>Point for the center W. 1/16 sec. cor. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E W 1/16 C ——— C S4 2001</p>

**Subdivision of Section 4,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona**

CHAINS	
84.38	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located on the right bank of Ash Creek, 2 chs. wide, 1 ft. deep, course S. 20° E.</p> <p>The 1/4 sec. cor. of secs. 4 and 5.</p> <hr/> <p style="text-align: center;">NW 1/4 of Sec. 4</p> <hr/> <p>From the center W. 1/16 sec. cor. of sec. 4.</p> <p>Over rolling rocky grassland through scattering juniper.</p> <p>N. 1°46' W., on the N. and S. center line of the NW 1/4 of sec. 4.</p>
42.41	<p>The W. 1/16 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.</p> <hr/> <p style="text-align: center;">Subdivision of Section 7, T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 7 and 18.</p> <p>N. 0°21' W., on the N. and S. center line of sec. 7.</p> <p>Over rolling terrain through scattering juniper and cacti.</p>
40.44	<p>Point for the center 1/4 sec. cor. of sec. 7, at intersection with the E. and W. center line of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E C 1/4 S7 2002</p> <p>from which</p> <p style="padding-left: 40px;">A volcanic boulder, 4 x 2 x ½ ft., bears N. 11¼° E., 118 lks. dist, mkd. X BO.</p> <p style="padding-left: 40px;">A volcanic boulder, 2 x 1 x ½ ft., bears N. 55° E., 152 lks. dist, mkd. X BO.</p>

**Subdivision of Section 7,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, a fence cor. bears E., 38 lks. dist., with 4 strand barbed wire fences extending S. 85° E. and S.</p>
81.00	<p>The 1/4 sec. cor. of secs. 6 and 7.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 7 and 8.</p> <p>N. 88°20' W., on the E. and W. center line of sec. 7.</p>
35.42	<p>Power line, bears S. 20° E and N. 20° W.</p>
40.70	<p>The center 1/4 sec. cor. of sec. 7.</p>
80.78	<p>The 1/4 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.</p> <hr/> <p style="text-align: center;">Subdivision of Section 10, T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, in a collar of stone, with a mound of stone, 2½ ft. base, 1 ft. high, to the N., with brass cap mkd. 1/4 S10 S15 1917. Add the marks T11N R3E 2001 to the brass cap.</p> <p>North, on the N. and S. center line of sec. 10.</p> <p>Over mountainous land through scattering undergrowth and cacti.</p>
40.01	<p>Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E. and W. center line of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E C 1/4 S10 2001</p>
59.98	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 5 lks. E. of a 4 strand barbed wire fence, bears N. and S.</p> <p>Point for the center N. 1/16 sec. cor. of sec. 10.</p>

**Subdivision of Section 10,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E C N 1/16 S10 C 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 7 lks. W. of a 4 strand barbed wire fence, bears N. and S.</p>
79.95	<p>The 1/4 sec. cor. of secs. 3 and 10.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 10 and 11.</p> <p>S. 89°59' W., on the E. and W. center line of sec. 10.</p> <p>Over rolling rocky land through scattering undergrowth.</p>
40.03	<p>The center 1/4 sec. cor. of sec. 10.</p>
60.04	<p>Point for the center W. 1/16 sec. cor. of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E W 1/16 C ——— C S10 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
83.10	<p>The 1/4 sec. cor. of sec. 10 only, on the W. bdy. of sec. 10.</p> <hr/> <p style="text-align: center;">NW 1/4 of Sec. 10</p> <hr/> <p>From the center W. 1/16 sec. cor. of sec. 10.</p> <p>N. 0°01' E., on the N. and S. center line of the NW 1/4 of sec. 10.</p>

**Subdivision of Section 10,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona**

CHAINS	
19.98	<p>Over rolling rocky land through scattering undergrowth.</p> <p>Point for the NW 1/16 sec. cor. of sec. 10, at intersection with the E. and W. center line of the NW 1/4 of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E NW 1/16 S10 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
39.96	<p>The point for the W. 1/16 sec. cor. of secs. 3 and 10.</p> <hr/> <p>From the center N. 1/16 sec. cor. of sec. 10.</p> <p>West, on the E. and W. center line of the NW 1/4 of sec. 10.</p> <p>Over rolling rocky land through scattering undergrowth.</p>
20.01	<p>The NW 1/16 sec. cor. of sec. 10.</p>
42.87	<p>The point for the N. 1/16 sec. cor. of sec. 10 only, on the W. bdy. of sec. 10.</p> <hr/> <p style="text-align: center;">Subdivision of Section 11, T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 11 and 14.</p> <p>N. 0°05' W., on the N. and S. center line of sec. 11.</p> <p>Over mountainous land through scattering undergrowth.</p>
19.99	<p>Point for the center S. 1/16 sec. cor. of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E C S 1/16 S11 C 2001</p>

**Subdivision of Section 11,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.98	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E. and W. center line of sec. 11.</p> <p>Set an aluminum rod, 36 ins. long, $\frac{3}{4}$ in. diam., 28 ins. in the ground, in a mound of stone, 2$\frac{1}{2}$ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E C 1/4 S11 2001</p> <p>Deposit a magnet in a white plastic case at the base of the aluminum rod and bury a standard railroad spike beneath the aluminum rod.</p> <p>Cor. is located on the SW side of a juniper tree, 24 ins. diam.</p>
59.96	<p>Point for the center N. 1/16 sec. cor. of sec. 11. Not monumented.</p>
79.94	<p>The 1/4 sec. cor. of secs. 2 and 11.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 11 and 12.</p> <p>S. 89°56' W., on the E. and W. center line of sec. 11.</p> <p>Over mountainous land through scattering undergrowth.</p>
20.00	<p>Point for the center E. 1/16 sec. cor. of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E E 1/16 C ——— C S11 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
40.00	<p>The center 1/4 sec. cor. of sec. 11.</p>
79.94	<p>The 1/4 sec. cor. of secs. 10 and 11.</p> <hr/>

Subdivision of Section 11,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	NE 1/4 of Sec. 11

	From the center E. 1/16 sec. cor. of sec. 11.
	N. 0°03' W., on the N. and S. center line of the NE 1/4 of sec. 11.
	Over mountainous land through scattering undergrowth.
19.97	Point for the NE 1/16 sec. cor. of sec. 11, at intersection with the E. and W. center line of the NE 1/4 of sec. 11.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T11N R3E NE 1/16 S11 2001
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
39.94	The point for the E. 1/16 sec. cor. of secs. 2 and 11.

	From the N. 1/16 sec. cor. of secs. 11 and 12.
	S. 89°59' W., on the E. and W. center line of the NE 1/4 of sec. 11.
	Over mountainous land through scattering undergrowth.
20.02	The NE 1/16 sec. cor. of sec. 11.
40.04	The point for the center N. 1/16 sec. cor. of sec. 11.

	SE 1/4 of Sec. 11

	From the S. 1/16 sec. cor. of secs. 11 and 12.
	S. 89°59' W., on the E. and W. center line of the SE 1/4 of sec. 11.
	Over mountainous land through scattering undergrowth.
39.98	The center S. 1/16 sec. cor. of sec. 11.

**Subdivision of Section 12,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.03	<p>From the 1/4 sec. cor. of secs. 12 and 13.</p> <p>N. 0°02' W., on the N. and S. center line of sec. 12.</p> <p>Over mountainous terrain through scattering juniper.</p> <p>Point for the center 1/4 sec. cor. of sec. 12, at intersection with the E. and W. center line of sec. 12.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E C 1/4 S12 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
60.03	<p>Point for the center N. 1/16 sec. cor. of sec. 12.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E C N 1/16 S12 C 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.03	<p>The 1/4 sec. cor. of secs. 1 and 12.</p> <hr/> <p>From the 1/4 sec. cor. of sec. 12 only, on the E. bdy. of the Tp.</p> <p>S. 89°44' W., on the E. and W. center line of sec. 12.</p> <p>Over mountainous land through scattering juniper.</p>
39.44	<p>The center 1/4 sec. cor. of sec. 12.</p>
59.41	<p>Point for the center W. 1/16 sec. cor. of sec. 12.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

Subdivision of Section 12,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T11N R3E W 1/16 C ——— C S12 2001
79.38	Deposit a magnet in a white plastic case at the base of the stainless steel post. The 1/4 sec. cor. of secs. 11 and 12.
	<hr/> NW 1/4 of Sec. 12 <hr/>
19.97	From the center W. 1/16 sec. cor. of sec. 12. N. 0°01' W., on the N. and S. center line of the NW 1/4 of sec. 12. Over mountainous land through scattering undergrowth. Point for the NW 1/16 sec. cor. of sec. 12, at intersection with the E. and W. center line of the NW 1/4 of sec. 12. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
39.94	T11N R3E NW 1/16 S12 2001
	Deposit a magnet in a white plastic case at the base of the stainless steel post. The point for the W. 1/16 sec. cor. of secs. 1 and 12.
19.96	From the center N. 1/16 sec. cor. of sec. 12. S. 89°40' W., on the E. and W. center line of the NW 1/4 of sec. 12. Over mountainous land through scattering undergrowth. The NW 1/16 sec. cor. of sec. 12.
39.92	The N. 1/16 sec. cor. of secs. 11 and 12.

Subdivision of Section 25,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.94	<p>From the 1/4 sec. cor. of secs. 25 and 36.</p> <p>N. 0°05' W., on the N. and S. center line of sec. 25.</p> <p>Over mountainous terrain through scattering juniper and cacti.</p> <p>Point for the center 1/4 sec. cor. of sec. 25, at intersection with the E. and W. center line of sec. 25.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E C 1/4 S25 2002</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 15 ins. diam., bears N. 79° W., 32 lks. dist., mkd. C 1/4 S25 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.94	<p>The 1/4 sec. cor. of secs. 24 and 25.</p> <hr/> <p>From the 1/4 sec. cor. of sec. 25 only, on the E. bdy. of the Tp.</p> <p>S. 89°51' W., on the E. and W. center line of sec. 25.</p> <p>Over mountainous land through scattering juniper.</p>
6.53	<p>Intersect line 1-2, sec. 25, of the metes-and-bounds survey in sec. 25.</p>
39.70	<p>The center 1/4 sec. cor. of sec. 25.</p>
79.59	<p>The 1/4 sec. cor. of secs. 25 and 26, monumented with an iron post, 1 in. diam, firmly set, projecting 10 ins. above ground, in a scattered mound of stone, 3 ft. base, to top, with brass cap mkd. 1/4 S25 S26 1917, from which the original bearing tree</p> <p style="padding-left: 40px;">A juniper, 21 ins. diam., bears S. 42½° E., 99 lks. dist., with fragmented scribe marks visible on partially opened blaze. (Record: 102 lks. dist.)</p> <p>Add the marks T11N R3E 2002 to the brass cap and rebuild mound of stone, 3 ft. base, to top.</p>

**Subdivision of Section 25,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Cor. is located 46 lks. W. of single iron rail fence, bears S. 15° E. and N. 15° W.</p> <p>Cor. is located 132 lks. S. of a dirt road, 15 ft. wide, bears S. 72° E. and N. 75° W.</p> <hr/> <p style="text-align: center;">Subdivision of Section 28, T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 28 and 33.</p> <p>N. 0°26' E., on the N. and S. center line of sec. 28.</p> <p>Over rolling terrain through scattering juniper and cacti.</p>
39.83	<p>Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E. and W. center line of sec. 28.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E C 1/4 S28 2002</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears N. 37¼° W., 159 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 130 lks. E. of a 4 strand barbed wire fence, bears S. 60° E. and N. 60° W.</p>
81.30	<p>The 1/4 sec. cor. of secs. 21 and 28.</p> <hr/> <p>From the 1/4 sec. cor. of sec. 28 only, on the E. bdy. of sec. 28.</p> <p>S. 89°54' W., on the E. and W. center line of sec. 28.</p> <p>Over rolling terrain through scattering juniper and cacti.</p>
39.59	<p>The center 1/4 sec. cor. of sec. 28.</p>
59.74	<p>Point for the center W. 1/16 sec. cor. of sec. 28.</p>

**Subdivision of Section 28,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.89	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E W 1/16 C ——— C S28 2002</p> <p>Raise mound of stone, 3 ft. base, 1½ ft. high, N. of cor.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The 1/4 sec. cor. of secs. 28 and 29.</p> <hr/> <p style="text-align: center;">NW of 1/4 Sec. 28</p> <hr/> <p>From the center W. 1/16 sec. cor. of sec. 28.</p> <p>N. 0°18' E., on the N. and S. center line of the NW 1/4 of sec. 28.</p> <p>Over rolling terrain through scattering juniper and cacti.</p>
40.65	<p>The W. 1/16 sec. cor. of secs. 21 and 28.</p> <hr/> <p style="text-align: center;">Subdivision of Section 30, T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 30 and 31.</p> <p>N. 0°13' W., on the N. and S. center line of sec. 28.</p> <p>Over rolling terrain through scattering juniper and cacti.</p>
19.99	<p>Point for the center S. 1/16 sec. cor. of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E C S 1/16 S30 C 2002</p>

Subdivision of Section 30,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.98	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 4 lks. W. of a 4 strand barbed wire fence, bears N. and S. and N. 4° W., 41 lks. of a fence cor. with 4 strand barbed wire fences extending N., E., and W.</p> <p>Point for the center 1/4 sec. cor. of sec. 30, at intersection with the E. and W. center line of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R3E C 1/4 S30 2002</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 11 ins. diam., bears S. 15¼° E., 55 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 103 lks. E. of a 4 strand barbed wire fence, bears N. and S. and 145 lks. W of a dirt road, 14 ft. wide, bears S. 48° E. and N. 37° W.</p>
79.16	<p>The 1/4 sec. cor. of secs. 19 and 30.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 29 and 30.</p> <p>N. 88°42' W., on the E. and W. center line of sec. 30.</p> <p>Over rolling terrain through scattering juniper and cacti.</p>
39.87	<p>The center 1/4 sec. cor. of sec. 30.</p>
61.42	<p>Point for the center W. 1/16 sec. cor. of sec. 30. Not monumented.</p> <p>From this point, a rebar, 5/8 in. diam, firmly set, projecting 2 ins. above ground, with affixed yellow plastic cap mkd. LS 24522, bears N. 84°55' W., 2.18 chs. dist.</p>
92.83	<p>The point for the 1/4 sec. cor. of secs. 30 only, on the W. bdy of the Tp.</p> <hr/>

Subdivision of Section 30,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	SE 1/4 of Sec. 30

	From the S. 1/16 sec. cor. of secs. 29 and 30.
	N. 88°53' W., on the E. and W. center line of the SE 1/4 of sec. 30.
	Over rolling terrain through scattering juniper and cacti.
39.74	The point for the center S. 1/16 of sec. 30.

	SW 1/4 of Sec. 30

	From the W. 1/16 sec. cor. of secs. 30 and 31.
	N. 0°17' W. on the N. and S. center line of the SW 1/4 of sec. 30.
	Over rolling terrain through scattering juniper and cacti.
19.99	Point for the SW 1/16 sec. cor. of sec. 30 at intersection with the E. and W. centerline of the SW 1/4 of Sec. 30.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 6 ft. base, to top, with brass cap mkd.
	T11N R3E SW 1/16 S30 2002
	from which
	A volcanic boulder, 2 x 2 x ½ ft. bears S. 53¼° E., 82 lks. dist., mkd. X BO on top.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located N. 15° E., 2 lks. dist., of a steel fence cor., with 4 strand barbed wire fences extending S. and W.
	From this cor. point, a rebar, ⅝ in. diam., firmly set, projecting 3 ins. above ground, with affixed yellow plastic cap mkd. LS 24522, bears N. 84°11' W., 2.19 chs. dist.
39.98	The point for the center W. 1/16 sec. cor. of sec. 30.

**Subdivision of Section 30,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 88°41' W., on the E. and W. center line of the SW 1/4 of sec. 30.
	Over rolling terrain through scattering juniper and cacti.
21.53	The SW 1/16 sec. cor. of sec. 30.
52.89	The point for the S. 1/16 sec. cor. of sec. 30 only, on the W. bdy. of the Tp.
<hr/> Metes-and-Bounds Survey in Section 20, T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona <hr/>	
	From AP 1, sec. 20, on the line bet. secs. 19 and 20, hereinbefore described.
	N. 89°53' E., on line 1-2, sec. 20.
	Over level terrain through scattering mesquite and underbrush.
4.47	Point for AP 2, sec. 20.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.
	T11N R3E AP2 _____ S20 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located S. 38° E., 15 lks. dist. of a mesquite tree fence cor., with 5 strand barbed wire fences extending N. and W. and 105 lks., W. of a 6 strand barbed wire fence, bears S. 29° E. and N. 29° W.
	<hr/> N. 0°05' W., on line 2-3, sec. 20.
	Over level terrain through scattering mesquite and underbrush.
1.60	Desc. 10 ft., over cut bank.
2.98	AP 3, sec. 20., on the line bet. secs. 17 and 20, hereinbefore described.

**Metes-and-Bounds Survey in Section 25,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona**

CHAINS	
10.03	<p>From AP 1, sec. 25, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 40°37' W., on line 1-2, sec. 25.</p> <p>Over rolling terrain through scattering juniper and cacti.</p> <p>Intersect the E. and W. center line of sec. 25.</p> <p>From this point, the 1/4 sec. cor. of sec. 25 only, on the E. bdy. of the Tp., bears N. 89°51' E., 6.53 chs. dist., hereinbefore described.</p>
33.44	<p>Point for AP 2, sec. 25, occupied with a rebar, 5/8 in. diam., firmly set, flush with the ground, with affixed yellow plastic cap mkd. LS 13015.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T11N R3E</p> <p>S25 / AP2 2002</p> </div> <p>from which a new bearing tree</p> <p style="margin-left: 40px;">A juniper, 14 ins. diam., bears S. 40° E., 43 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and place the rebar inside stainless steel post.</p> <hr style="width: 30%; margin: 20px auto;"/>
6.36	<p>S. 0°03' W., on line 2-3, sec. 25.</p> <p>Over rolling terrain through scattering juniper and cacti.</p> <p>Point for AP 3, sec. 25, determined by grant bdy. adjustment from the survey executed by Patrick W. Naville, Arizona Registered Land Surveyor No. 13015, in 1989. A rebar, 3/4 in. diam. found lying loosely on the ground alongside.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p>

Metes-and-Bounds Survey in Section 25,
T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<div data-bbox="873 300 1008 420" style="text-align: center;"> <p>T11N R3E S25 AP3 2002</p> </div> <p>from which</p> <p style="padding-left: 40px;">A juniper, 9 ins. diam., bears S. 32½° E., 38 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, SW of cor.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 47°43' E., on line 3-4, sec. 25.</p> <p>Over rolling terrain through scattering juniper and cacti.</p>
29.44	<p>AP 4, sec. 25, on the E. bdy. of the Tp., hereinbefore described.</p>
	<hr/> <p>GENERAL DESCRIPTION</p> <hr/>
	<p>This survey is located near Cordes Junction, Arizona. Elevations range from about 3000 to 5000 feet above sea level.</p> <p>The land is rolling to mountainous, with scattered juniper and cacti.</p> <p>Access is by way of Interstate 17.</p> <p>The mean magnetic declination of 12¼° E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.</p> <hr/>

CERTIFICATE OF SURVEY

We, Stephen K. Hansen and Adrien J. Rodriguez, Cadastral Surveyors, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 9th day of April, 2001, and supplemental special instructions bearing date of the 10th day of April, 2002, We have dependently resurveyed portions of the east, west and north boundaries and a portion of the subdivisional lines, subdivided certain sections and executed metes-and-bounds surveys in sections 20 and 25, T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

6/06/2003
(Date)

Stephen K. Hansen
(Cadastral Surveyor)

JUNE 11, 2003
(Date)

Adrien J. Rodriguez
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of portions of the east, west and north boundaries and a portion of the subdivisional lines, the subdivision of certain sections and metes-and-bounds surveys in sections 20 and 25, T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona, executed by Stephen K. Hansen and Adrien J. Rodriguez, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

January 23, 2004
(Date)

Lenny A. Pawlik
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 11 N., R. 3 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____~~
~~(Date)~~

~~_____~~
~~(Chief Cadastral Surveyor of Arizona)~~