

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE FIFTH GUIDE MERIDIAN EAST

(EAST BOUNDARY),

THE SOUTH AND WEST BOUNDARIES,

A PORTION OF THE NORTH BOUNDARY

AND

A PORTION OF THE SUBDIVISIONAL LINES,

TOWNSHIP 26 NORTH, RANGE 20 EAST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA.

EXECUTED BY

Geoffrey A. Graham, Cadastral Surveyor

Under Special Instructions dated July 19, 2002, approved July 19, 2002, which provided for the surveys included under Group No. 893, and assignment instructions dated July 19, 2002.

Survey commenced August 7, 2002

Survey completed October 22, 2002

INDEX DIAGRAM

TOWNSHIP 26 NORTH

RANGE 20 EAST

22 19 6	63 5	4	46 3	22 39 2	20 30 1 6
62 18 7	62 61 8	52 52 9	46 45 10	38 37 11	29 29 12 4
60 17 18	60 59 17	51 51 16	45 44 15	36 35 14	28 27 13 3
58 15 19	58 57 20	50 49 21	44 43 22	35 34 23	27 26 24 3
56 14 30	55 55 29	49 48 28	42 41 27	34 32 26	25 25 25 ²
54 13 31	54 53 32	48 47 33	41 40 34	32 31 35	24 23 36
11	10	9	9	8	7

T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the Fifth Guide Meridian East (east boundary), the south and west boundaries, a portion of the north boundary and a portion of the subdivisional lines, T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this resurvey is as follows:

John C. Smith surveyed portions of the north and west boundaries in 1891. In 1908, Sidney E. Blout surveyed the south boundary and resurveyed and completed the east boundary of T. 26 N., R. 19 E. (portion of W. bdy.). In 1910, Sidney E. Blout surveyed the east boundary of T. 25 N., R. 19 E. (portion of W. bdy.), the Fifth Guide Meridian East (E. bdy.), the south boundary and resurveyed and completed the north boundary. Also in 1910, Van L. White surveyed the subdivisional lines. In 1977-78, Kenneth A. Krenke and Marvin T. Koppang dependently resurveyed a portion of the north boundary and a portion of the subdivisional lines. In 1977-79, Shirley B. Hjellum, Kenneth A. Krenke and Marvin T. Koppang dependently resurveyed that portion of the Fifth Guide Meridian East identical with Segment "A" of the Hopi-Navajo Partition Line. Segment "B" of the Hopi-Navajo partition line, crossing the north boundary and through portions of sections 4 and 5, T. 26 N., R. 20 E., was surveyed by Shirley B. Hjellum and Kenneth A. Krenke in 1977-81. The south boundary and a portion of the east boundary of T. 27 N., R. 19 E., was dependently resurveyed by Joe R. Salazar, in 2002.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated July 19, 2002, for Group No. 893, Arizona.

The directions of all lines were determined and distances measured, by the technique of differential positioning using Trimble Navigation 4400 Series Global Positioning System receivers utilizing the Real-Time Kinematic technique.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations processed by the National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS), FERNO MESA, FLAGSTAFF 1 and PIETOWN. The NAD 83 (CORS96) (EPOCH: 2002), geographic position of the southeast corner of the township is as follows:

T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Latitude: 35° 36' 19.00" N. Longitude: 110° 08' 49.05" W.</p> <p>The mean magnetic declination is 11$\frac{3}{4}$° E.</p> <hr/> <p>Dependent Resurvey of a Portion of the Fifth G.M. E. (E. Bdy.), T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>Restoring the resurvey executed by Shirley B. Hjellum, Kenneth A. Krenke and Marvin T. Koppang, in 1977-79</p> <hr/> <p>Beginning at the 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., firmly set in concrete, projecting 10 ins. above ground, with brass cap mkd. T26N R20E R21E S25 1/4 S30 HOPI NAVAJO APA 104 77 1910, from which the original bearing trees</p> <p style="padding-left: 40px;">An 8 ins. diam. branch of a juniper, 15 ins. diam., bears S. 49$\frac{1}{2}$° E., 116 lks. dist., with faint illegible scribe marks visible on partial blaze.</p> <p style="padding-left: 40px;">A juniper, 18 ins. diam., bears S. 69° W., 110 lks. dist., with scribe marks S25 BT visible on partially healed blaze.</p> <p>Add the marks 2002 to the brass cap.</p> <p>This cor. is located in a fence, bears N. and S.</p> <p>N. 0°03' E., bet. secs. 25 and 30.</p> <p>Generally following fence, descend over rolling terrain.</p> <p>40.00 Point for the cor. of secs. 19, 24, 25 and 30, at proportionate dist.; there is no remaining evidence of the 1977 cor., falls in dry wash, 36 ft. wide, 4 ft. deep, drains SW.</p> <p>Set a magnet in a white plastic case, 18 ins. in the ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 57°24' W., 51.8 ft. dist., with brass cap mkd. RM T26N R20E S25 51.8 FT TO COR 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
--------	---

Dependent Resurvey of a Portion of the Fifth Guide Meridian East (E. Bdy.),
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 35°39' W., 44.6 ft. dist., with brass cap mkd. RM T26N R20E S24 44.6 FT TO COR 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
40.00	<p>N. 0°03' E., bet. secs. 19 and 24.</p> <p>Crossing rolling terrain, broken by small washes, generally following fence.</p> <p>The 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., firmly set in concrete, projecting 11 ins. above ground, with brass cap mkd. T26N R20E R21E HOPI S24 ¼ S19 NAVAJO APA 106 78 1910.</p> <p>Add the marks 2002 to the brass cap.</p> <p>This cor. is located in a fence, bears N. and S.</p> <hr/>
40.00	<p>N. 0°04' E., beginning new measurement.</p> <p>Crossing rolling terrain broken by small washes, along fence.</p> <p>The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 3 ins. diam., firmly set in concrete, projecting 14 ins. above ground, with brass cap mkd. T26N R20E R21E S13 S18 HOPI S24 S19 AP-A107 NAVAJO 77 1910.</p> <p>Add the marks 2002 to the brass cap.</p> <p>This cor. is located at cor. of fences, extending E. and S.</p> <hr/>
40.00	<p style="text-align: center;">Restoring the survey executed by Sidney E. Blout, in 1910</p> <hr/> <p>N. 0°03' E., bet. secs. 13 and 18.</p> <p>Begin general ascent over rolling ground broken by small washes.</p> <p>The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. S13 1/4 S18 1910, from which the remains of the original bearing trees</p> <p style="text-align: center;">A pinon pine stump, 14 ins. diam., bears S. 59½° E., 218 lks. dist., no remaining scribe marks.</p>

Dependent Resurvey of a Portion of the Fifth Guide Meridian East (E. Bdy.),
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A burned juniper stump, 15 ins. diam., bears N. $31\frac{1}{2}^{\circ}$ W., 325 lks. dist., with scribe marks BT visible on partial blaze. (Record: N. 32° W., 324 lks. dist.)</p> <p>Add the marks T26N R20E R21E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. $0^{\circ}04'$ E., beginning new measurement.</p> <p>Ascend, leave rolling terrain enter severely erroded and broken land.</p>
39.96	<p>True point for the cor. secs 7, 12, 13 and 18, at proportionate dist.; falls in dry wash, 100 ft. wide, 20 ft. deep, drains S.</p> <hr/>
1.40	<p>N. $0^{\circ}04'$ E., bet. secs. 7 and 12.</p> <p>The witness cor. to the cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. WC T26N R20E R21E S12 S7 S13 S18 1910, from which the remains of the original bearing trees</p> <p>An 8 ins. diam. trunk of a pinon pine, 12 ins. diam., bears N. $18\frac{3}{4}^{\circ}$ E., 107 lks. dist., with scribe marks WC T26N R21E S7 BT visible on open blaze.</p> <p>A juniper, 13 ins. diam., bears S. $46\frac{1}{2}^{\circ}$ E., 114 lks. dist., with scribe marks WC T26N R21E S18 BT visible on partially healed blaze. (Record: 112 lks. dist.)</p> <p>A juniper stump, 18 ins. diam., bears S. $39\frac{1}{2}^{\circ}$ W., 68 lks. dist., with no remaining scribe marks visible.</p> <p>A pinon pine stumphole, 13 ins. diam., bears N. 21° W., 73 lks. dist.</p> <p>Add the marks 2002 and an arrow pointing to the cor. to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>This cor. is located 23 lks. N. of a dry wash, 100 ft. wide, 20 ft. deep, drains S.</p> <hr/> <p>N. $0^{\circ}04'$ E., beginning new measurement.</p>

Dependent Resurvey of a Portion of the Fifth Guide Meridian East (E. Bdy.),
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
38.48	<p>Across severely eroded land broken by many small washes.</p> <p>The 1/4 sec. cor. of secs. 7 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. S12 1/4 S7 1910, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A broken pinon pine trunk, 10 ins. diam., bears S. 73$\frac{3}{4}$° E., 210 lks. dist., with scribe marks BT visible on partial blaze.</p> <p style="padding-left: 40px;">The base of a dead and down pinon pine, 10 ins. diam., bears S. 39$\frac{3}{4}$° W., 15 lks. dist., with scribe marks 1/4 S12 BT visible on weathered blaze.</p> <p>Add the marks T26N R20E R21E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03' E., beginning new measurement.</p> <p>Crossing severely broken spur ridge of mesa.</p>
39.88	<p>The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 3 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. T26N R20E R21E S1 S6 S12 S7 1910, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A dead pinon pine, 12 ins. diam., bears N. 18$\frac{1}{2}$° E., 208 lks. dist., with scribe marks T26N R21E S6 BT visible on weathered blaze. (Record: 211 lks. dist.)</p> <p style="padding-left: 40px;">The base of a dead and down pinon pine, 7 ins. diam., bears S. 59$\frac{1}{4}$° E., 39 lks. dist., with scribe marks T26N R21E S7 BT visible on a weathered blaze.</p> <p style="padding-left: 40px;">A juniper, 9 ins. diam., bears S. 16$\frac{1}{2}$° W., 120 lks. dist., with scribe marks T26N R20E S12 BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A double blazed pinon pine, 11 ins. diam., bears N. 15$\frac{1}{2}$° W., 134 lks. dist., with scribe marks T26N R20E S1 visible on upper blaze and marks BT visible on lower blaze. (Record: 137 lks. dist.)</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p>

Dependent Resurvey of a Portion of the Fifth Guide Meridian East (E. Bdy.),
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Raise supporting mound of stone, 2 ft. base, to top of iron post.</p> <hr/> <p>N. 0°04' W., bet. secs. 1 and 6.</p> <p>Over broken terrain along base of mesa.</p>
40.01	<p>The 1/4 sec. cor. of secs. 1 and 6, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd. S1 1/4 S6 1910, from which the original bearing trees</p> <p style="padding-left: 40px;">A pinon pine, 9 ins. diam., bears S. 42½° E., 94 lks. dist., with scribe marks 1/4 S6 BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A pinon pine, 8 ins. diam., bears S. 39½° W., 114 lks. dist., with scribe marks 1/4 S1 BT visible on partially healed blaze.</p> <p>Reset iron post to project 8 ins. above ground.</p> <p>Add the marks T26N R20E R21E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>Raise a supporting mound of stone, 3 ft. base, to top of iron post.</p> <hr/> <p>N. 0°03' E., beginning new measurement.</p> <p>Crossing severely broken foothills of mesa.</p>
39.78	<p>The cor. of Tps. 26 and 27 N., Rs. 20 and 21 E., monumented with an iron post, 2½ ins. diam., firmly set, projecting 19 ins. above ground, in a substantial supporting mound of stone, 3 ft. base, to top, with brass cap mkd. T27N R20E R21E S36 S31 S1 S6 T26N 1977, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears N. 68° E., 35 lks. dist., with scribe marks T27N R21E S31 BT visible on weathered blaze.</p> <p style="padding-left: 40px;">The base of a dead and down pinon pine, 4 ins. diam., bears S. 60° E., 66 lks. dist., with no scribe marks visible a weathered blaze. (Record: S. 57½° E., 63 lks. dist.)</p>

**Dependent Resurvey of a Portion of the Fifth Guide Meridian East (E. Bdy.),
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS

The base of a dead and down pinon pine, 9 ins. diam., bears S. $14\frac{1}{2}^{\circ}$ W., 171 lks. dist., with scribe marks T26N R20E S1 BT visible on a weathered blaze.

A pinon pine, 8 ins. diam., bears N. $81\frac{1}{2}^{\circ}$ W., 72 lks. dist., with scribe marks T27N R20E S36 BT visible on partially healed blaze.

and the 1977 bearing trees

A juniper, 12 ins. diam., bears S. $10\frac{3}{4}^{\circ}$ E., 46 lks. dist., with scribe marks T26N R21E S6 BT visible on partially healed blaze. (Record: S. 15° E.)

A branch of a juniper, 8 ins. diam., bears S. $59\frac{1}{2}^{\circ}$ W., 29 lks. dist., with scribe marks T26N R20E S1 BT visible on weathered blaze. (Record: S. 64° W.)

Add the marks 2002 to the brass cap.

Set a steel fence post alongside the cor.

This cor. is located on a bend on the right bank of dry wash, 8 ft. wide, 6 ft. deep, drains from S. to W.

**Dependent Resurvey of the South Boundary,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
Sidney E. Blout, in 1910

From the cor. of Tps. 25 and 26 N., Rs. 20 and 21 E., monumented with an iron post, 3 ins. diam., firmly set in concrete, projecting 1 in. above ground, with brass cap mkd. T26N R20E R21E HOPI NAVAJO S36 S31 APA 101 S1 S6 R20E R21E T25N 78 1910, from which the remains of the original bearing tree

A dead juniper, 8 ins. diam., bears S. $68\frac{1}{2}^{\circ}$ W., 78 lks. dist., with scribe marks T25N R20E S1 BT visible on weathered blaze.

Add the marks 2002 to the brass cap.

This cor. is located at cor. fences, extending N., E. and W.

N. $89^{\circ}58'$ W., bet. secs. 1 and 36.

Descend over gently rolling terrain, along fence.

**Dependent Resurvey of the South Boundary,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>The 1/4 sec. cor. of secs. 1 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. S36 1/4 S1 1910.</p> <p>Add the marks T26N R20E T25N 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>This cor. is located in a fence, bears E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°59' W., beginning new measurement.</p> <p>Descend over rolling terrain; along fence.</p>
3.81	<p>A well casing, 8 ins. diam., with windmill and tanks, bears N., 2.61 chs. dist.</p>
40.01	<p>The cor. of secs. 1, 2, 35 and 36, monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. R20E T26N T25N S36 S1 S35 S2 1910.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>This cor. is located in a fence, bears E. and W.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 89°56' W., bet. secs. 2 and 35.</p> <p>Begin gentle ascent over rolling terrain, along fence.</p>
40.01	<p>Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R20E S35 1/4 ——— S2 T25N 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>This cor. is located 1 lk. N. of a fence, bears E. and W.</p>

**Dependent Resurvey of the South Boundary,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
61.15	Center of cattle guard, 24 ft. wide, in graded dirt road, bears N. 62° E. and S. 62° W.
80.02	<p>The cor. of secs. 2, 3, 34 and 35, monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. R20E T26N T5N S35 S2 S34 S3.</p> <p>Add the marks 2 for T25N and 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>This cor. is located in a fence, bears E. and W.</p> <hr/> <p>N. 89°57' W., bet. secs. 3 and 34.</p> <p>Ascend over gently rolling terrain; along fence.</p>
40.01	<p>The 1/4 sec. cor. of secs. 3 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S34 1/4 S3 1910.</p> <p>Add the marks T26N R20E T25N 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>This cor. is located in a fence, bears E. and W.</p> <hr/> <p>N. 89°49' W., beginning new measurement.</p> <p>Over rolling terrain, along fence.</p>
39.98	<p>The cor. of secs. 3, 4, 33 and 34, monumented with an iron post, 3 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. R20E T26N T25N S34 S3 S33 S4 1910.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>This cor. is located at cor. of fences, extending N. 20° E., E. and S. 20° W.</p> <hr/> <p>S. 89°58' W., bet. secs. 4 and 33.</p> <p>Descend over rolling terrain.</p>

**Dependent Resurvey of the South Boundary,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.03	<p>The 1/4 sec. cor. of secs. 4 and 33, monumented with an iron post, 1 in. diam., firmly set in concrete, projecting 11 ins. above ground, with brass cap mkd. S33 1/4 S4 1910.</p> <p>Add the marks T26N R20E T25N 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>An angle iron post is set in same concrete as the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°53' W., beginning new measurement.</p> <p>Descend gradually into flood plain, broken by small washes.</p>
40.03	<p>The cor. of secs. 4, 5, 32 and 33, monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. R20E T26N T25N S33 S4 S32 S5 1910.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 89°55' W., bet. secs. 5 and 32.</p> <p>Crossing nearly level flood plain, broken by small washes.</p>
39.98	<p>The 1/4 sec. cor. of secs. 5 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S32 1/4 S5 1910.</p> <p>Add the marks T26N R20E T25N 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°55' W., beginning new measurement.</p> <p>Crossing nearly level flood plain, broken by small washes.</p>
40.02	<p>The cor. of secs. 5, 6, 31 and 32, monumented with an iron post, 3 ins. diam., firmly set in concrete, projecting 14 ins. above ground, with brass cap mkd. R20E T26N T25N S32 S5 S31 S6 1910.</p> <p>Add the marks 2002 to the brass cap.</p> <p>An angle iron post for cor. of fences, extending N. and W., is set in same concrete as the cor.</p>

**Dependent Resurvey of the South Boundary,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.02	<p>N. 89°58' W., bet. secs. 6 and 31.</p> <p>Crossing flood plain, along fence.</p> <p>Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R20E S31 1/4 ——— S6 T25N 2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>This cor. is located 235 lks. S. of fence, bears S. 88° E. and N. 88° W.</p> <p>Crossing nearly level flood plain, leaving firm ground and entering soft sandy terrain.</p>
78.86	<p>The closing cor. of Tps. 25 and 26 N., R. 20 E., at intersection with the E. bdy. of T. 25 N., R. 19 E., monumented with an iron post, 3 ins. diam., firmly set, 5 ins. below soft sand, with brass cap mkd. T26N CC S6 S1 R19E R20E T25N 1910.</p> <p>Expose iron post to project 5 ins. above ground.</p> <p>Add the marks S31 and 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>From this cor. point, the cor. of secs. 1, 6, 7 and 12, Tps. 25 N., Rs. 19 and 20 E. bears S. 0°01' W., 79.38 chs. dist., monumented with an iron post, 3 ins. diam., firmly set in concrete, projecting 7 ins. above ground, with brass cap mkd. T25N R19E R20E HOPI S1 S6 S12 S7 NAVAJO APA-70 1978.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>This cor. is located in fence, bears E. and W.</p>

Dependent Resurvey of the West Boundary,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS

Restoring the survey executed by
Sidney E. Blout, in 1910

From the closing cor. of Tps. 25 and 26 N., R. 20 E.,
hereinbefore described.

N. 0°01' E., on the E. bdy. of sec. 1, T. 25 N., R. 19 E.

Crossing rolling, soft sandy terrain.

4.62

The closing cor. of T. 25 N., R. 19 E. and T. 26 N., R. 20 E.,
at intersection with the S. bdy. of T. 26 N., R. 19 E.,
monumented with an iron post, 3 ins. diam., firmly set, 17 ins.
below soft sand, with brass cap mkd. T26N R19E R20E S36 S31 CC
S1 R19E R20E T25N 1910.

Add the marks 2002 to the brass cap.

Deposit a magnet in a white plastic case alongside the iron
post.

This cor. is located in fence, bears E. and W.

Impractical to reset iron post above ground due to location in
fence and the soft sandy terrain.

From this cor. point, the 1/4 sec. cor. sec. 36 only, T. 26 N.,
R. 19 E., bears N. 89°59' W., 28.33 chs. dist., monumented with
a basalt stone, 5 X 8 X 13 ins., firmly set, 6 ins. below the
ground, mkd. ¼ on N. face.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins.
in the ground, with brass cap mkd.

T26N R19E
1/4 S36

2002

Bury the original stone, inverted, alongside and deposit a
magnet in a white plastic case at the base of the stainless
steel post.

This cor. is located 1 lk. S. of fence, bears E. and W.

**Dependent Resurvey of the West Boundary,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Restoring the survey executed by Sidney E. Blout, in 1908</p> <hr/>
	<p>From the closing cor. of T. 25 N., R. 19 E. and T. 26 N., R.20 E.</p> <p>S. 89°59' E., on the S. bdy. of sec. 36, T. 26 N., R. 19 E.</p> <p>Crossing rolling, soft sandy terrain.</p>
11.70	<p>The cor. of T. 26 N., R. 19 E. only, monumented with an iron post, 3 ins. diam., firmly set, 5 ins. below ground, with brass cap mkd. T26N R19E R20E S36 S31 S1 S6 R19E R20E T25N.</p> <p>Expose iron post to project 4 ins. above ground.</p> <p>Remove the marks S1 S6 R19E R20E T25N and add the marks 2002 to the brass cap.</p>
	<p>Restoring the survey executed by Sidney E. Blout, in 1908</p> <hr/>
	<p>From the cor. of T. 26 N., R. 19 E. only.</p> <p>N. 0°02' W., on the E. bdy. of sec. 36, T. 26 N., R. 19 E.</p> <p>Leave soft sand and enter firmer terrain.</p>
35.37	<p>Point for the 1/4 sec. cor. of sec. 31 only, T. 26 N., R. 20 E., hereinafter described.</p>
40.06	<p>The 1/4 sec. cor. of sec. 36 only, T. 26 N., R. 19 E., monumented with a basalt stone, 14 X 9 X 7 ins., firmly set, 13 ins. in the ground, mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T26N R19E R20E 1/4 S36 2002 </p> <p>Bury the original stone, inverted, alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>

Dependent Resurvey of the West Boundary,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>N. 0°01' W., beginning new measurement.</p> <p>Crossing nearly level flood plain, broken by small washes.</p>								
35.30	<p>The closing cor. of secs. 30 and 31, T. 26 N., R. 20 E., monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. T26N R19E R20E S30 CC S31 1910.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>Crossing nearly level flood plain, broken by small washes.</p>								
40.02	<p>The cor. of secs. 25 and 36 only, T. 26 N., R. 19 E., monumented with a basalt stone, 14 X 10 X 6 ins., firmly set, 13 ins. in the ground, mkd. with 1 groove on S. face and 5 grooves on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 2px;">T26N</td> <td style="padding: 2px;">T26N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">S25</td> <td style="padding: 2px;">R20E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">S36</td> <td style="padding: 2px;">S30</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">R19E</td> <td style="padding: 2px;">2002</td> </tr> </table> </div> <p>Bury the original stone, inverted, alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T26N	T26N	S25	R20E	S36	S30	R19E	2002
T26N	T26N								
S25	R20E								
S36	S30								
R19E	2002								
	<p>N. 0°02' W., on the E. bdy. of sec. 25, T. 26 N., R. 19 E.</p> <p>Crossing nearly level flood plain, broken by small washes.</p>								
35.26	<p>Point for the 1/4 sec. cor. of sec. 30 only, T. 26 N., R. 20 E., hereinafter described.</p>								
40.01	<p>The 1/4 sec. cor. of sec. 25 only, T. 26 N., R. 19 E., monumented with a basalt stone, 14 X 8 X 6 ins., firmly set, 9 ins. in the ground, mkd. 1/4 on W. face.</p> <p>At the corner point</p>								

Dependent Resurvey of the West Boundary,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R19E R20E 1/4 S25 2002</p> <p>Bury the original stone, inverted, alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 0°02' E., beginning new measurement.</p> <p>Crossing nearly level flood plain, broken by small washes.</p>
35.23	<p>The closing cor. of secs. 19 and 30, T. 26 N., R. 20 E., monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. T26N R19E R20E S19 CC S30 1910.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p>
40.03	<p>The cor. of secs. 24 and 25 only, T. 26 N., R. 19 E., monumented with a basalt stone, 13 X 8 X 5 ins., firmly set, 12 ins. in the ground, mkd. with 2 grooves on S. face and 4 grooves on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N T26N S24 R20E ----- S19 S25 R19E 2002</p> <p>Bury the original stone, inverted, alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 0°01' E., on the E. bdy. of sec. 24, T. 26 N., R. 19 E.</p> <p>Crossing nearly level flood plain, broken by small washes.</p>

Dependent Resurvey of the West Boundary,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS																			
35.20	Point for the 1/4 sec. cor. of sec. 19 only, T. 26 N., R. 20 E., hereinafter described.																		
40.02	The 1/4 sec. cor. of sec. 24 only, T. 26 N., R. 19 E., monumented with a basalt stone, 11 X 9 X 9 ins., firmly set, 10 ins. in the ground, mkd. 1/4 on W. face.																		
	At the corner point																		
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.																		
	<p>T26N R19E R20E 1/4 S24 2002</p>																		
	Bury the original stone, inverted, alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.																		
	<hr style="width: 20%; margin: auto;"/> <p>N. 0°02' E., beginning new measurement.</p>																		
	Crossing nearly level flood plain, broken by small washes.																		
35.18	The closing cor. of secs. 18 and 19, T. 26 N., R. 20 E., monumented with an iron post, 2 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. T26N R19E R20E S18 CC S19 1910.																		
	Add the marks 2002 to the brass cap.																		
	Deposit a magnet in a white plastic case alongside the iron post.																		
40.03	The cor. of secs. 13 and 24 only, T. 26 N., R. 19 E., monumented with a basalt stone, 15 X 9 X 8 ins., firmly set, 14 ins. in the ground, mkd. with 3 grooves on S. face and 3 grooves on N. face.																		
	At the corner point																		
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.																		
	<table border="0"> <tr> <td>T26N</td> <td> </td> <td>T26N</td> </tr> <tr> <td>S13</td> <td> </td> <td>R20E</td> </tr> <tr> <td colspan="3"><hr style="width: 10%; margin: auto;"/></td> </tr> <tr> <td>S24</td> <td> </td> <td>S18</td> </tr> <tr> <td>R19E</td> <td></td> <td></td> </tr> <tr> <td colspan="3" style="text-align: center;">2002</td> </tr> </table>	T26N		T26N	S13		R20E	<hr style="width: 10%; margin: auto;"/>			S24		S18	R19E			2002		
T26N		T26N																	
S13		R20E																	
<hr style="width: 10%; margin: auto;"/>																			
S24		S18																	
R19E																			
2002																			

**Dependent Resurvey of the West Boundary,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Bury the original stone, inverted, alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 0°01' E., on the E. bdy. of sec. 13, T. 26 N., R. 19 E.</p> <p>Beginning gentle ascent, leave flood plain, enter rolling terrain.</p>
23.20	Center of bladed dirt road, 24 ft. wide, bears N. 80° E. and S. 80° W.
35.135	Point for the 1/4 sec. cor. of sec. 18 only, T. 26 N., R. 20 E., hereinafter described.
40.02	<p>The 1/4 sec. cor. of sec. 13 only, T. 26 N., R. 19 E., monumented with a basalt stone, 14 X 9 X 8 ins., firmly set, 4 ins. below the ground, mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R19E R20E 1/4 S13 2002</p> </div> <p>Bury the original stone, inverted, alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>North, beginning new measurement.</p> <p>Ascend over rolling terrain, broken by small washes.</p>
35.10	<p>The closing cor. of secs. 7 and 18, T. 26 N., R. 20 E., monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. T26N R19E R20E S7 CC S18 1910.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p>
40.03	The cor. of secs. 12 and 13 only, T. 26 N., R. 19 E., monumented with a basalt stone, 12 X 9 X 6 ins., firmly set, 10 ins. in the ground, mkd. with 4 grooves on S. face and 2 grooves on N. face.

Dependent Resurvey of the West Boundary,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">T26N</td> <td>T26N</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S12</td> <td>R20E</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S13</td> <td>S7</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">R19E</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;"></td> <td>2002</td> </tr> </table> <p>Bury the original stone, inverted, alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T26N	T26N	S12	R20E	S13	S7	R19E			2002
T26N	T26N										
S12	R20E										
S13	S7										
R19E											
	2002										
	<p>N. 0°04' W., on the E. bdy. of sec. 12, T. 26 N., R. 19 E.</p> <p>Ascend gently over rolling terrain, broken by small washes.</p>										
35.07	<p>Point for the 1/4 sec. cor. of sec. 7 only, T. 26 N., R. 20 E., hereinafter described.</p>										
40.03	<p>The 1/4 sec. cor. for sec. 12 only, T. 26 N., R. 19 E., monumented with a basalt stone, 9 X 9 X 8 ins., firmly set, 8 ins. in the ground, mkd. 1/4 on W. face.</p>										
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">T26N</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">R19E</td> <td>R20E</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">1/4 S12</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;"></td> <td>2002</td> </tr> </table> <p>Bury the original stone, inverted, alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T26N		R19E	R20E	1/4 S12			2002		
T26N											
R19E	R20E										
1/4 S12											
	2002										
35.04	<p>N. 0°02' W., beginning new measurement.</p> <p>Beginning steeper ascent, over rolling terrain.</p> <p>Point for the closing cor. of secs. 6 and 7, T. 26 N., R. 20 E., at proportionate dist.; there is no remaining evidence of the original cor.</p>										

**Dependent Resurvey of the West Boundary,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <pre> T26N R19E R20E S6 S12 ----- CC S7 2002 </pre> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
40.04	<p>The cor. of secs. 1 and 12 only, T. 26 N., R. 19 E., monumented with a basalt stone, 17 X 10 X 7 ins., firmly set, 14 ins. in the ground, mkd. with 5 grooves on S. face and 1 groove on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <pre> T26N T26N S1 R20E ----- S6 S12 R19E 2002 </pre> </div> <p>Bury the original stone, inverted, alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>N. 0°02' W., on the E. bdy. of sec. 1, T. 26 N., R. 19 E.</p> <p>Leave rolling terrain, enter broken land.</p>
34.98	<p>Point for the 1/4 sec. cor. sec. 6 only, T. 26 N., R. 20 E., hereinafter described.</p>
39.99	<p>The 1/4 sec. cor. of sec. 1 only, T. 26 N., R. 19 E., monumented with a sandstone, 15 X 7 X 4 ins., firmly set, 11 ins. in the ground, mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the West Boundary,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
<p>34.77</p> <p>39.96</p>	<p align="center">T26N R19E R20E 1/4 S1 2002</p> <p>Bury the original stone, inverted, alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 0°02' W., beginning new measurement.</p> <p>Crossing severely broken terrain.</p> <p>Point for the closing cor. of Tps. 26 and 27 N., R. 20 E., at proportionate dist.; found original iron post laying loose on ground.</p> <p>Reset the original iron post, 36 ins. long, 3 ins. diam., 34 ins. in the ground, with brass cap mkd. T27N S36 S31 CC S1 S6 R19E R20E T26N 1910.</p> <p>Remove the marks S36 and add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case at the base of the iron post.</p> <p>The cor. of Tps. 26 and 27 N., R. 19 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T27N R19E R20E S36 S31 R19E S1 T26N 2002.</p>
	<p align="center">Dependent Resurvey of a Portion of the North Boundary, T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona</p>
	<p align="center">Restoring the resurvey executed by Kenneth A. Krenke and Marvin T. Koppang, in 1977-79</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 36, on the N. bdy. of the tp., monumented with an iron post, 1 in. diam., firmly set, projecting 17 ins. above ground, with brass cap mkd. S 36 1/4 S1 T27N R20E T26N 77 1910, from which the remains of the original bearing trees</p> <p>A juniper, 10 ins. diam., bears N. 4° E., 17 lks. dist., with scribe marks 1/4 S36 BT visible on partially healed blaze.</p>

Dependent Resurvey of a Portion of the North Boundary,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>The base of a dead and down pinon pine, 10 ins. diam., bears S. $18\frac{1}{2}^{\circ}$ E., 59 lks. dist., with scribe marks $\frac{1}{4}$ S1 BT visible on weathered blaze.</p> <p>and a 1977-78 bearing tree</p> <p>A juniper, 19 ins. diam., bears S. 29° W., 46 lks. dist., with scribe marks $\frac{1}{4}$ S1 BT visible on partially healed blaze. (Record: S. 34° W.)</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>Raise a mound of stone, 5 ft. base, to top of iron post.</p> <p>N. $89^{\circ}58'$ W., bet. secs. 1 and 36.</p> <p>Crossing severely broken terrain.</p>
39.81	<p>The witness cor. to the cor. of secs. 1, 2, 35 and 36, monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. WC R20E T27N S35 S36 S2 S1 T26N 77 1910, from which the original bearing trees</p> <p>A juniper, 8 ins. diam., bears N. $79\frac{3}{4}^{\circ}$ E., 43 lks. dist., with scribe marks T27N R20E visible on weathered blaze.</p> <p>A juniper, 20 ins. diam., bears S. $50\frac{1}{2}^{\circ}$ E., 65 lks. dist., with scribe marks WC T26N R20E S1 BT visible on partially healed blaze. The earth supporting this tree has almost entirely eroded away.</p> <p>A 9 ins. diam. trunk of a juniper, 24 ins. diam., bears S. $2\frac{1}{2}^{\circ}$ W., 147 lks. dist., with scribe marks WC T26N R20E S2 BT visible on partially healed blaze. The earth supporting this tree has almost entirely eroded away.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>A steel fence post is set nearby.</p> <p>This witness cor. is located on the left bank of a steep ravine, drains S. 20° E. To stabilize this cor., I backfill the ravine for 15 ft. with stone and earth.</p> <hr style="width: 20%; margin: 10px auto;"/>

Dependent Resurvey of a Portion of the North Boundary,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
0.10	<p>N. 89°58' W., beginning new measurement.</p> <p>True point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist.; falls on a very steep dirt bank, impracticable to monument.</p>
39.96	<hr/> <p>West, bet. secs. 2 and 35.</p> <p>Leave broken land, enter rolling terrain.</p> <p>The 1/4 sec. cor. of secs. 2 and 35, monumented with an iron post, 2½ ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T27N R20E S35 ¼ S2 T26N 1977, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A juniper root crown, bears N. 15¼° E., 362 lks. dist.</p> <p style="padding-left: 40px;">A juniper, 9 ins. diam., bears S. 75° W., 184 lks. dist., with scribe marks 1/4 S2 BT visible on partially healed blaze. (Record: S. 85° W., 183 lks. dist.)</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>A steel fence post was set nearby.</p> <hr/> <p style="text-align: center;">Restoring the survey executed by Sidney E. Blout, in 1910</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. R20E T27N T26N S32 S5 S31 S6 1910.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>N. 89°56' W., bet. secs. 6 and 31.</p> <p>Descend over rolling terrain, broken by small washes.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the original cor.</p>

**Dependent Resurvey of a Portion of the North Boundary,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
67.42	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R20E S31 1/4 ——— S6 T26N 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Leave rolling terrain, descend through severely broken land.</p> <p>The closing cor. of Tps. 26 and 27 N., R. 20 E., hereinbefore described.</p>
<hr/> <p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
<p>Restoring the survey executed by Van L. White, in 1910</p> <hr/>	
33.70	<p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' E., bet. secs. 35 and 36.</p> <p>Crossing rolling terrain.</p>
40.01	<p>Center of graded dirt road, 30 ft. wide, bears N. 72° E. and S. 72° W.</p>
	<p>The 1/4 sec. cor. of secs. 35 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. S35 1/4 S36 1910.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>North, begining new measurement.</p> <p>Crossing rolling terrain, broken by small washes.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS											
39.99	<p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="844 478 1015 630"> <tr> <td>T26N</td> <td>R20E</td> </tr> <tr> <td>S26</td> <td>S25</td> </tr> <tr> <td>S35</td> <td>S36</td> </tr> <tr> <td colspan="2">2002</td> </tr> </table> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set in concrete, projecting 21 ins. above ground, with brass cap mkd. T26N R20E R21E S25 S30 S36 S31 HOPI NAVAJO APA-103 78 1910, from which the remains of the original bearing trees</p> <p>A pinon pine, 14 ins. diam., bears N. 30½° E., 98 lks. dist., with scribe marks 26N R21E S30 BT visible on partially healed blaze.</p> <p>A stumphole, bears S. 40¼° E., 245 lks. dist.</p> <p>A pinion pine stump, 12 ins. diam., bears N. 38° W., 324 lks. dist., with no visible marks.</p> <p>Add the marks 2002 to the brass cap.</p> <p>This cor. is located in a fence, bears N. and S.</p> <p>N. 89°55' W., bet. secs. 25 and 36.</p> <p>Descend across rolling terrain.</p>	T26N	R20E	S26	S25	S35	S36	2002			
T26N	R20E										
S26	S25										
S35	S36										
2002											
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="828 1690 998 1848"> <tr> <td>T26N</td> <td>R20E</td> </tr> <tr> <td></td> <td>S25</td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td></td> <td>S36</td> </tr> <tr> <td colspan="2">2002</td> </tr> </table>	T26N	R20E		S25	1/4	_____		S36	2002	
T26N	R20E										
	S25										
1/4	_____										
	S36										
2002											

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS							
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 25, 26, 31 and 36.</p> <hr/>						
39.99	<p>North, bet. secs. 25 and 26.</p> <p>Crossing nearly level terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R20E</p> <p>1/4</p> <table border="1" style="margin: auto;"> <tr> <td>S26</td> <td>S25</td> </tr> <tr> <td colspan="2">2002</td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	S26	S25	2002			
S26	S25						
2002							
79.98	<p>Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R20E</p> <table border="1" style="margin: auto;"> <tr> <td>S23</td> <td>S24</td> </tr> <tr> <td>S26</td> <td>S25</td> </tr> <tr> <td colspan="2">2002</td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>	S23	S24	S26	S25	2002	
S23	S24						
S26	S25						
2002							
40.04	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°56' W., bet. secs. 24 and 25.</p> <p>Crossing rolling terrain, broken by small washes.</p> <p>Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>						

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T26N R20E S24 1/4 ——— S25 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.08	<p>The cor. of secs. 23, 24, 25 and 26.</p> <hr/>
	<p>N. 0°01' E., bet. secs. 23 and 24.</p>
	<p>Crossing nearly level terrain.</p>
39.99	<p>The 1/4 sec. cor. of secs. 23 and 24, monumented with a bent iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap missing.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T26N R20E 1/4 S23 S24 2002</p>
	<p>Bury the iron post alongside, and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/>
	<p>N. 0°01' E., beginning new measurement.</p>
	<p>Leave nearly level terrain, enter rolling land.</p>
39.97	<p>The cor. of secs. 13, 14, 23 and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T26N R20E S14 S13 S23 S24 1910, from which the remaining original bearing trees</p>
	<p>A pinon pine, 9 ins. diam., bears N. 20½° E., 158 lks. dist., with scribe marks T26N R20 visible on partially open blaze.</p>
	<p>A pinon pine, 12 ins. diam., bears S. 17¾° E., 101 lks. dist., with scribe marks T26N R20E S24 BT visible on partially open blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A pinon pine, 7 ins. diam., bears N. 50° W., 170 lks. dist., with scribe marks T26N R20E visible on partially open blaze.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>This cor. is located in fence, bears S. 45° E. and N. 45° W.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°57' W., bet. secs. 13 and 24.</p> <p>Crossing rolling terrain broken by small washes.</p>
40.06	<p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R20E S13 1/4 ——— S24 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.12	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/> <p>N. 0°05' E., bet. secs. 13 and 14.</p> <p>Descend through rolling terrain into valley.</p>
39.91	<p>Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R20E 1/4 S14 S13 2002</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS									
79.82	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Ascend, leave valley, enter severely broken terrain.</p> <p>The cor. of secs. 11, 12, 13 and 14, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap missing, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A dead pinon pine, 11 ins. diam., bears N. 52¼° E., 139 lks. dist., with scribe marks T26N R20E T visible on weathered blaze. (Record: N. 53¼° E., 137 lks. dist.)</p> <p style="padding-left: 40px;">The base of a dead and down pinon pine, 8 ins. diam., bears S. 19½° E., 154 lks. dist., with scribe marks T26N R20E S13 BT visible on weathered blaze.</p> <p style="padding-left: 40px;">A pinon pine stump, 8 ins. diam., bears S. 81¼° W., 20 lks. dist., with no scribe marks visible.</p> <p style="padding-left: 40px;">A pinon pine stump, 12 ins. diam., bears N. 29¼° W., 66 lks. dist., with no scribe marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground over a steel fence post, with brass cap mkd.</p> <table border="1" data-bbox="844 1197 1015 1354" style="margin-left: auto; margin-right: auto;"> <tr> <td>T26N</td> <td>R20E</td> </tr> <tr> <td>S11</td> <td>S12</td> </tr> <tr> <td>S14</td> <td>S13</td> </tr> <tr> <td colspan="2" style="text-align: center;">2002</td> </tr> </table> <p>Bury the iron post alongside, and deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T26N	R20E	S11	S12	S14	S13	2002	
T26N	R20E								
S11	S12								
S14	S13								
2002									
40.09	<p>From the true point for the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°56' W., bet. secs. 12 and 13.</p> <p>Crossing severely broken terrain.</p> <p>The 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 1 in. diam., firmly set, flush with the ground, with brass cap mkd. S12 1/4 S13 1910, from which the original bearing trees</p>								

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.98	<p>A juniper, 8 ins. diam., bears S. 30° W., 88 lks. dist., with scribe marks S13 BT visible on partially healed blaze.</p> <p>A pinon pine, 9 ins. diam., bears N. 41½° W., 39 lks. dist., with scribe marks 12 BT visible on partially healed blaze.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>Raise a supporting mound of stone, 4 ft. base, 2 ft. high, on downward slope to stabilize the cor. position.</p> <hr/> <p>S. 89°56' W., beginning new measurement.</p> <p>Crossing severely broken terrain.</p> <p>The cor. of secs. 11, 12, 13 and 14.</p>
39.96	<p>N. 0°04' E., bet. secs. 11 and 12.</p> <p>Ascend, leave severely broken land, enter rolling terrain.</p> <p>The 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. S11 1/4 S12 1910.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 0°06' E., beginning new measurement.</p> <p>Crossing rolling terrain broken by small washes.</p>
39.98	<p>The cor. of secs. 1, 2, 11 and 12, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd. T26N R20E S2 S1 S11 S12 1910.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Raise a supporting mound of stone, 5 ft. base, to top of iron post.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°57' W., bet. secs. 1 and 12.</p> <p>Descend across rolling foothills of mesa.</p>
40.00	<p>The 1/4 sec. cor. of secs. 1 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. S1 1/4 S12 1910, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A juniper stump, 12 ins. diam., bears N. 19½° E., 54 lks. dist., with no scribe marks visible.</p> <p style="padding-left: 40px;">A pinon pine, 10 ins. diam., bears S. 17¼° W., 76 lks. dist., with scribe marks BT visible on partially healed blaze.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>Cor. falls on left bank of wash, bears E. and W.</p> <p>Raise a supporting mound of stone, 5 ft. base, 2 ft. high, on downslope of bank to stabilize the cor. position.</p> <hr/> <p>N. 89°56' W., beginning new measurement.</p> <p>Crossing broken land.</p>
40.02	<p>The cor. of secs. 1, 2, 11 and 12.</p> <hr/> <p>N. 0°08' E., bet. secs. 1 and 2.</p> <p>Crossing severely broken terrain.</p>
39.92	<p>Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.80	<p style="text-align: center;">T26N R20E 1/4 S2 S1 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The true point for the cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described.</p>
39.97	<hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Ascend over rolling terrain.</p>
	<p>The 1/4 sec. cor. of secs. 34 and 35, determined from the remains of the original bearing trees</p> <p style="padding-left: 40px;">A burned juniper stump hole, size indeterminate, bears N. 22½° E., 103 lks. dist., with no scribe marks remaining.</p> <p style="padding-left: 40px;">A juniper trunk, 20 ins. diam., bears N. 41½° W., 80 lks. dist., with scribe marks 1/4 S34 BT visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T26N R20E 1/4 S34 S35 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°02' E., beginning new measurement.</p> <p>Ascend over the broken terrain of the foothills of Stephen's Butte.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.78	<p>The cor. of secs. 26, 27, 34 and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T26N R20E S27 S26 S34 S35 1910, from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 16 ins. diam., bears S. 44½° W., 190 lks. dist., with no scribe marks visible.</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears N. 47½° W., 174 lks. dist., with scribe marks BT visible on weathered blaze.</p> <p>Rebuild original mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>
	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89°54' W., bet. secs. 26 and 35.</p> <p>Crossing rolling terrain, broken by small washes.</p>
40.02	<p>The 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S26 1/4 S35 1910.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>
	<p>S. 89°53' W., beginning new measurement.</p> <p>Ascend the foothills of Stephen's Butte.</p>
1.40	<p>Center of graded dirt road, 28 ft. wide, bears N. 20° E. and S. 20° W.</p>
39.99	<p>The cor. of secs. 26, 27, 34 and 35.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Crossing the broken terrain along Stephen's Butte.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.93	<p>The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. S27 1/4 S26 1910, from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A juniper, 17 ins. diam., bears S. 8½° W., 213 lks. dist., with scribe marks 1/4 S27 BT visible on partially healed blaze. (Record: 217 lks. dist.)</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, to top of iron post.</p> <p>From this cor. point, U. S. Geological Survey triangulation station STEPHEN 1965, bears S. 81°01' W., 33.53 chs. dist., monumented with a standard brass disk, 3 ins. diam., cemented flush with the surface of rock outcrop, with top mkd. STEPHEN 1965 and a triangle.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°02' W., beginning new measurement.</p> <p>Descend the broken foothills of Stephen's Butte.</p>
40.00	<p>The cor. of secs. 22, 23, 26 and 27, monumented with an iron post, 2 ins. diam., firmly set, 12 ins. below the ground, with brass cap mkd. T26N R20E S22 S23 S27 S26 1910, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 16 ins. diam., bears N. 70° E., 31 lks. dist., with scribe marks T26N R20E S visible on partially healed blaze.</p> <p style="padding-left: 40px;">A juniper stump, 18 ins. diam., bears S. 46½° E., 11 lks. dist., with no scribe marks visible.</p> <p style="padding-left: 40px;">A pinon pine stump, 10 ins. diam., bears N. 12¾° W., 114 lks. dist., with scribe marks BT visible on partial blaze.</p> <p>Expose the iron post to project 4 ins. above ground.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 23, 24, 25 and 26.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	S. 89°50' W., bet. secs. 23 and 26.
	Crossing rolling terrain.
39.00	Center of graded dirt road, 28 ft. wide, bears S. 15° E. and N. 10° W.
40.04	The 1/4 sec. cor. of secs. 23 and 26, monumented with a mangled iron post, 1 in. diam., firmly set, with brass cap mkd. S23 1/4 S26 1910.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., flush with the ground, with brass cap mkd.
	<p style="text-align: center;">T26N R20E S23 1/4 ——— S26 2002</p>
	Bury the iron post alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.
	Set steel fence post nearby.
	S. 89°53' W., beginning new measurement.
	Ascend over rolling terrain.
39.99	The cor. of secs. 22, 23, 26 and 27.
	N. 0°01' E., bet. secs. 22 and 23.
	Descend over broken land.
39.98	The 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. S22 1/4 S23 1910.
	Add the marks T26N R20E 2002 to the brass cap.
	Deposit a magnet in a white plastic case alongside the iron post.
	N. 0°02' E., beginning new measurement.
	Ascend, leave broken land, enter rolling terrain.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.99	<p>The cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T26N R20E S15 S14 S22 S23 1910.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p>
	<hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°53' W., bet. secs. 14 and 23.</p> <p>Descend, leave broken land, enter rolling terrain.</p>
39.98	<p>The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. S14 1/4 S23 1910.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p>
	<hr/> <p>S. 89°52' W., beginning new measurement.</p> <p>Crossing rolling terrain, broken by small washes.</p>
14.20	<p>Center of graded dirt road, 24 ft. wide, bears S. 20° E. and N. 20° W.</p>
40.02	<p>The cor. of secs. 14, 15, 22 and 23.</p>
	<hr/> <p>N. 0°02' E., bet. secs. 14 and 15.</p> <p>Ascend over rolling terrain, broken by small washes.</p>
39.95	<p>The 1/4 sec. cor. of secs. 14 and 15, monumented with the rusted remains of an iron post, 1 in. diam., firmly set, 12 ins. below the ground, from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N. 84° E., 195 lks. dist., with scribe marks 1/4 S14 BT visible on weathered partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T26N R20E 1/4 S15 S14 2002</p> <p>Deposit the remains of the iron post inside, and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03' E., beginning new measurement.</p> <p>Descend over rolling terrain, broken by small washes.</p>
27.40	Center of graded dirt road, 18 ft. wide, bears S. 10° W. and N. 25° W.
40.00	<p>The cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T26N R20E S10 S11 S15 S14 1910.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>This cor. is located in fence, bears S. 45° E. and N. 45° W.</p> <hr/> <p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>West, bet. secs. 11 and 14.</p> <p>Crossing broken terrain.</p>
40.06	<p>The 1/4 sec. cor. of secs. 11 and 14, monumented with the rusted remains of an iron post, 1 in. diam., firmly set, 9 ins. below the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R20E S11 1/4 ——— S14 2002</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.98	<p>Deposit the remains of the iron post inside, and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>S. 89°57' W., beginning new measurement.</p> <p>Crossing over rolling terrain, broken by small washes.</p> <p>The cor. of secs. 10, 11, 14 and 15.</p>
39.97	<hr/> <p>N. 0°01' E., bet. secs. 10 and 11.</p> <p>Crossing rolling terrain, broken by many washes.</p> <p>Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R20E 1/4 S10 S11 2002</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 25 ins. in the ground for a reference monument, bears S. 48°30' E., 403.3 ft. dist., with brass cap mkd. RM T26N R20E S11 403.3 FT TO COR 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post. This monument is located on the top and end of a dirt ridge, 12 ft. high, bears N. 45° E.</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 48°30' W., 271.1 ft. dist., with brass cap mkd. RM T26N R20E S10 271.1 FT TO COR 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post. This monument is located at foot of a dirt ridge, bears N. 10° E. and S. 10° W.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>This cor. is located in broad flood plain.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS													
79.94	<p>Ascend over broken terrain.</p> <p>Point for the cor. of secs. 2, 3, 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T26N R20E</td></tr> <tr><td>S3</td><td>S2</td></tr> <tr><td colspan="2">— —</td></tr> <tr><td>S10</td><td>S11</td></tr> <tr><td colspan="2">2002</td></tr> </table> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T26N R20E		S3	S2	— —		S10	S11	2002			
T26N R20E													
S3	S2												
— —													
S10	S11												
2002													
40.05	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89°58' W., bet. secs. 2 and 11.</p> <p>Crossing broken land.</p> <p>Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate dist.; falls in dry wash, impracticable to monument.</p> <p>The original witness cor. to the 1/4 sec. cor. of secs. 2 and 11 was searched for but not recovered.</p> <p>From this point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 2 and 11, bears N. 75°00' E., 2.00 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">WC</td></tr> <tr><td colspan="2">T26N R20E</td></tr> <tr><td colspan="2">S2</td></tr> <tr><td colspan="2">— —</td></tr> <tr><td>1/4</td><td>S11</td></tr> <tr><td>←</td><td>2002</td></tr> </table> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>This witness cor. is located at top of ridge, 8 ft. high, bears S. 65° E. and N. 65° W.</p>	WC		T26N R20E		S2		— —		1/4	S11	←	2002
WC													
T26N R20E													
S2													
— —													
1/4	S11												
←	2002												

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.10	The cor. of secs. 2, 3, 10 and 11.
	N. 0°10' E., bet. secs. 2 and 3.
	Ascend over rolling terrain.
26.20	Center of graded dirt road, 35 ft. wide, bears N. 21° E. and S. 21° W.
39.97	Point for the 1/4 sec. cor of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">T26N R20E 1/4 S3 S2 2002</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.01	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. R20E T27N T26N S35 S2 S34 S3 77 1910, from which the remains of the original bearing trees
	A burned out juniper stump, size indeterminate, bears N. 37° E., 307 lks. dist., with no scribe marks visible.
	A burned out juniper stump, size indeterminate, bears S. 80° W., 225 lks. dist., with no scribe marks visible.
	A 7 ins. diam. branch of a juniper, 24 ins. diam., bears N. 31½° W., 135 lks. dist., with scribe marks R20E S35 BT visible on partially healed blaze.
	and the 1977 bearing trees
	A pinon pine, 9 ins. diam., bears N. 19½° E., 221 lks. dist., with no scribe marks visible on partially healed blaze. (Record: N. 21½° E., 217 lks. dist.)
	A forked pinon pine, 12 ins. diam., bears S. 39° E., 400 lks. dist., with scribe marks T26N R20E S2 BT visible on partially healed blaze. (Record: S. 37° E., 397 lks. dist.)

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A pinon pine, 7 ins. diam., bears S. $70\frac{3}{4}^{\circ}$ W., 240 lks. dist., with scribe marks T26N R20E S3 BT visible on partially healed blaze. (Record: S. $73\frac{1}{2}^{\circ}$ W., 238 lks. dist.)</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. $0^{\circ}10'$ W., bet. secs. 33 and 34.</p> <p>Ascend over rolling terrain.</p>
39.88	<p>The 1/4 sec. cor. of secs. 33 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. S33 1/4 S34 1910, from which the remains of the original bearing trees</p> <p>A juniper stump, 12 ins. diam., bears N. $30\frac{1}{4}^{\circ}$ E., 128 lks. dist., with no scribe marks visible.</p> <p>A burned juniper stump, 12 ins. diam., bears N. 29° W., 110 lks. dist., with no scribe marks visible.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>North, beginning new measurement.</p> <p>Ascend over rolling terrain towards Stephen's Butte.</p>
39.86	<p>The cor. of secs. 27, 28, 33 and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T26N R20E S28 S27 S33 S34 1910, and witnessed by a mound of stone, 3 ft. base, 1 ft. high, 4 ft. W. of cor.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Relocate the original accessory mound to raise a supporting mound of stone, 4 ft. base, 2 ft. high, to stabilize cor. position.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°53' W., bet. secs. 27 and 34.</p> <p>Ascend steep slope crossing Stephen's Butte.</p>
40.09	<p>The 1/4 sec. cor. of secs. 27 and 34, determined from the remains of the original supporting mound of stone and the remaining original bearing tree</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears N. 56° E., 101 lks. dist., with scribe marks BT visible on weathered blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 11 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T26N R20E S27 1/4 ——— S34 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Rebuild original mound of stone, 2 ft. base, 1½ ft. high, N. of cor.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/> <p>N. 89°54' W., beginning new measurement.</p> <p>Crossing Stephen's Butte, and descend steep slope.</p>
40.02	<p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/> <p>N. 0°02' E., bet. secs. 27 and 28.</p> <p>Crossing the broken terrain along Stephen's Butte.</p>
39.93	<p>The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. S28 1/4 S27 1910.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.96	<p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>Relocate the original accessory mound to raise a supporting mound of stone, 4 ft. base, to top of iron post.</p> <hr/> <p>N. 0°03' E., beginning new measurement.</p> <p>Descend the broken terrain along Stephen's Butte.</p> <p>The cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T26N R20E S21 S22 S28 S27 1910, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A juniper stump, 17 ins. diam., bears N. 39° E., 226 lks. dist., with no scribe marks visible.</p> <p style="padding-left: 40px;">A juniper stump, 24 ins. diam., bears S. 8¼° E., 80 lks. dist., with no scribe marks visible.</p> <p style="padding-left: 40px;">A juniper stump, 18 ins. diam., bears S. 58¼° W., 275 lks. dist., with no scribe marks visible.</p> <p style="padding-left: 40px;">A burned juniper root crown, bears N. 31¼° W., 316 lks. dist., with no scribe marks visible.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>
39.99	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89°52'W., bet. secs. 22 and 27.</p> <p>Ascend the broken terrain along Stephen's Butte.</p> <p>The 1/4 sec. cor. of secs. 22 and 27, determined from the original mound of stone and the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 11 ins. diam., bears N. 2¼° E., 68 lks. dist., with scribe marks 1/4 S22 BT visible on weathered blaze. (Record: N. 0¼° W.)</p> <p style="padding-left: 40px;">A juniper, 13 ins. diam., bears S. 23½° E., 37 lks. dist., with scribe marks 1/4 S27 BT visible on weathered blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.01	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T26N R20E S22 1/4 ——— S27 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 89°59' W., beginning new measurement.</p> <p>Descend the broken terrain along Stephen's Butte.</p> <p>The cor. of secs. 21, 22, 27 and 28.</p>
40.00	<p>N. 0°03' E., bet. secs. 21 and 22.</p> <p>Descend through broken land.</p> <p>The 1/4 sec. cor. of secs. 21 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. S21 1/4 S22 1910.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 0°05' E., beginning new measurement.</p> <p>Crossing nearly level terrain, broken by many washes.</p>
39.99	<p>The cor. of secs. 15, 16, 21 and 22, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T26N R20E S16 S15 S21 S22 1910.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>This cor. is located at corner of fences, extending N. 65° E., S. 38° E. and W.</p> <hr/>
	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>West, bet. secs. 15 and 22.</p> <p>Crossing nearly level terrain.</p>
39.96	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. S15 1/4 S22 1910.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 89°49' W., beginning new measurement.</p> <p>Crossing nearly level terrain, broken by many washes.</p>
39.98	<p>The cor. of secs. 15, 16, 21 and 22.</p> <hr/>
	<p>N. 0°02' E., bet. secs. 15 and 16.</p> <p>Crossing nearly level terrain.</p>
39.99	<p>The 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S16 1/4 S15 1910.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>
	<p>N. 0°02' E., beginning new measurement.</p> <p>Ascend over nearly level terrain.</p>
39.98	<p>The cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T26N R20E S9 S10 S16 S15 1910.</p> <p>Add the marks 2002 to the brass cap.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case alongside the iron post.</p>
	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°54' W., bet. secs. 10 and 15.</p> <p>Descend over nearly level terrain.</p>
8.40	<p>Center of graded dirt road, 18 ft. wide, bears S. 31° E. and N. 33° W.</p>
39.97	<p>Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p align="center">T26N R20E S10 1/4 ——— S15 2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.94	<p>The cor. of secs. 9, 10, 15 and 16.</p>
	<p>N. 0°01' E., bet. secs. 9 and 10.</p> <p>Ascend, leave nearly level land, enter rolling terrain.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p align="center">T26N R20E 1/4 S9 S10 2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.98	<p>The cor. of secs. 3, 4, 9 and 10, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T26N R20E S4 S3 S9 S10 1910.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>This cor. is located in fence, bears S. 45° E. and N. 45° W.</p>
	<hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 89°52' W., bet. secs. 3 and 10.</p> <p>Descend over rolling terrain.</p>
3.40	<p>Center of graded dirt road, 24 ft. wide, bears N. 6° E. and S. 17° W.</p>
40.00	<p>The 1/4 sec. cor. of secs. 3 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. S3 1/4 S10 1910.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 89°53' W., beginning new measurement.</p> <p>Descend through broken land.</p>
39.93	<p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/>
	<p>N. 0°12' E., bet. secs. 3 and 4.</p> <p>Ascend over broken terrain.</p>
39.97	<p>The 1/4 sec. cor. of secs. 3 and 4, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. S4 1/4 S3 1910, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A juniper stump, 21 ins. diam., bears N. 41° E., 41 lks. dist., with no scribe marks visible.</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears S. 34° W., 185 lks. dist., with scribe marks 1/4 S BT visible on partially healed blaze.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet in a white plastic case alongside the iron post.</p>
	<hr/> <p>N. 0°09' E., beginning new measurement.</p>
	<p>Ascend over broken terrain.</p>
18.10	<p>Center of graded dirt road, 27 ft. wide, bears N. 55° E. and S. 56° W.</p>
40.01	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp.,</p>
	<p>monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T27N R20E S33 S34 S4 S3 T26N 1977, from which the remains of the original bearing trees</p>
	<p>A juniper stump, 21 ins. diam., bears N. 48° E., 119 lks. dist., with scribe marks S34 BT visible on partial blaze.</p>
	<p>A burned juniper stump, 18 ins. diam., bears S. 10° E., 154 lks. dist., with no marks visible.</p>
	<p>A juniper, 9 ins. diam., bears S. 7° W., 186 lks. dist., with scribe marks T26N R20E S4 BT visible on partially opened blaze.</p>
	<p>A juniper trunk, 15 ins. diam., bears N. 41¼° W., 47 lks. dist., with scribe marks T27N R20E S33 BT visible on partially open blaze.</p>
	<p>and a 1977 bearing tree</p>
	<p>A juniper, 10 ins. diam., bears S. 21½° E., 120 lks. dist., with scribe marks T26N R20E S3 BT visible on partially open blaze.</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>A steel fence post is set nearby.</p>
	<hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p>
	<p>N. 0°02' W., bet. secs. 32 and 33.</p>
	<p>Ascend over rolling terrain, broken by many washes.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.96	<p>The 1/4 sec. cor. of secs. 32 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. S32 1/4 S33 190.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 0°02' W., beginning new measurement.</p> <p>Ascend over rolling terrain, broken by many washes.</p>
39.96	<p>The cor. of secs. 28, 29, 32 and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 17 ins. above ground, with brass cap mkd. T26N R20E S29 S28 S32 S33 1910.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>From the cor of secs. 27, 28, 33 and 34.</p> <p>N. 89°49' W., bet. secs. 28 and 33.</p> <p>Descend over broken land.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R20E S28 1/4 ——— S33 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.98	<p>The cor. of secs. 28, 29, 32 and 33.</p> <hr/> <p>N. 0°02' W., bet. secs. 28 and 29.</p> <p>Crossing rolling terrain, broken by many washes.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
20.26	From this point, an U.S. Geological Survey bench mark, with an aluminum disc, firmly set in concrete form, bears W., 0.78 ch., mkd. 5928 FEET 12DOR 1965.
40.01	<p>The 1/4 sec. cor. of secs. 28 and 29, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. S29 1/4 S28 1910.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>
	<p>N. 0°02' W., beginning new measurement.</p> <p>Crossing rolling terrain, broken by many washes.</p>
40.02	<p>The cor. of secs. 20, 21, 28 and 29, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T26N R20E S20 S21 S29 S28 1910.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>
	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 89°44' W., bet. secs. 21 and 28.</p> <p>Descend over broken terrain.</p>
40.00	<p>The 1/4 sec. cor. of secs. 21 and 28, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. S21 1/4 S28 1910.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>
	<p>N. 89°44' W., beginning new measurement.</p> <p>Descend over rolling terrain, broken by many washes.</p>
40.06	<p>The cor. of secs. 20, 21, 28 and 29.</p> <hr/> <p>N. 0°02' W., bet. secs. 20 and 21.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS											
39.99	<p>Crossing nearly level terrain, broken by many washes.</p> <p>The 1/4 sec. cor. of secs. 20 and 21, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. S20 1/4 S21 1910.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 0°01' W., beginning new measurement.</p>										
39.99	<p>Crossing nearly level terrain, broken by many washes.</p> <p>Point for the cor. of secs. 16, 17, 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table data-bbox="844 966 1006 1123" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T26N R20E</td></tr> <tr><td style="text-align: center;">S17</td><td style="text-align: center;">S16</td></tr> <tr><td style="text-align: center;">S20</td><td style="text-align: center;">S21</td></tr> <tr><td colspan="2" style="text-align: center;">2002</td></tr> </table> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 89°44' W., bet. secs. 16 and 21.</p> <p>Descend nearly level terrain, broken by many washes.</p>	T26N R20E		S17	S16	S20	S21	2002			
T26N R20E											
S17	S16										
S20	S21										
2002											
40.08	<p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <table data-bbox="828 1648 1006 1806" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T26N R20E</td></tr> <tr><td colspan="2" style="text-align: center;">S16</td></tr> <tr><td style="text-align: center;">1/4</td><td style="text-align: center;">_____</td></tr> <tr><td colspan="2" style="text-align: center;">S21</td></tr> <tr><td colspan="2" style="text-align: center;">2002</td></tr> </table> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T26N R20E		S16		1/4	_____	S21		2002	
T26N R20E											
S16											
1/4	_____										
S21											
2002											

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.16	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>N. 0°01' W., bet. secs. 16 and 17.</p> <p>Ascend nearly level terrain, broken by many washes.</p>
39.99	<p>The 1/4 sec. cor. of secs. 16 and 17, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. S17 1/4 S16 1910.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 0°01' E., beginning new measurement.</p> <p>Ascend nearly level terrain, broken by many washes.</p>
39.99	<p>The cor. of secs. 8, 9, 16 and 17, monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. T26N R20E S8 S9 S17 S16 1910.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°43' W., bet. secs. 9 and 16.</p> <p>Descend nearly level terrain, broken by many washes.</p>
40.09	<p>The 1/4 sec. cor. of secs. 9 and 16, monumented with an iron post, 1 in. diam., firmly set, 8 ins. below ground, with brass cap mkd. S9 1/4 S16 1910.</p> <p>Expose the iron post to project 3 ins. above ground.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 89°44' W., beginning new measurement.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.09	<p>Descend nearly level terrain, broken by many washes.</p> <p>The cor of secs. 8, 9, 16 and 17.</p>
39.97	<p>N. 0°05' E., bet. secs. 8 and 9.</p> <p>Ascend nearly level terrain, broken by many washes.</p> <p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p align="center">T26N R20E 1/4 S8 S9 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
69.80	<p>Center of graded dirt road, 27 ft. wide, bears N. 43° E. and S. 40° W.</p>
79.94	<p>The cor. of secs. 4, 5, 8 and 9, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. T26N R20E S5 S4 S8 S9 1910, from which the 1977-78 bearing trees</p> <p align="center">A juniper, 8 ins. diam., bears N. 40¾° E., 130 lks. dist., with scribe marks BT visible on lower open blaze.</p> <p align="center">A juniper, 11 ins. diam., bears N. 19½° W., 108 lks. dist., with illegible scribe marks visible on partially open blaze.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p>
40.04	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 89°46' W., bet. secs. 4 and 9.</p> <p>Descend rolling terrain, broken by many washes.</p> <p>The 1/4 sec. cor. of secs. 4 and 9, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground,</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>with brass cap mkd. S4 1/4 S9 1910.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 89°45' W., beginning new measurement.</p> <p>Descend rolling terrain, broken by many washes.</p>
32.60	Center of graded dirt road, 24 ft. wide, bears N. 40° E. and S. 40° W.
40.04	The cor. of secs. 4, 5, 8 and 9.
	<hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°05' W., bet. secs. 31 and 32, along fence.</p> <p>Ascend nearly level terrain, broken by many washes.</p>
40.00	<p>The 1/4 sec. cor. of secs. 31 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. S31 1/4 S32 1910.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>This cor. is located in fence, bears N. and S.</p> <hr/> <p>N. 0°04' W., beginning new measurement.</p> <p>Ascend nearly level terrain, broken by many washes.</p>
39.98	<p>The cor. of secs. 29, 30, 31 and 32, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T26N R20E S30 S29 S31 S32 1910.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>This cor. is located in fence, bears N. and S.</p> <hr/>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.03	<p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89°52' W., bet. secs. 29 and 32.</p> <p>Descend nearly level terrain, broken by many washes.</p> <p>The 1/4 sec. cor. of secs. 29 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. S29 1/4 S32 1910.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>This cor. is located in fence, bears N. and S.</p> <hr/> <p>N. 89°54' W., beginning new measurement.</p> <p>Descend nearly level terrain, broken by many washes.</p>
40.02	<p>The cor. of secs. 29, 30, 31 and 32.</p> <hr/> <p>N. 89°59' W., bet. secs. 30 and 31.</p> <p>Descend nearly level terrain, broken by many washes.</p>
40.00	<p>The 1/4 sec. cor. of secs. 30 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. S30 1/4 S31 1910.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 89°58' W., beginning new measurement.</p> <p>Descend nearly level terrain, broken by many washes.</p>
27.08	<p>The closing cor. of secs. 30 and 31, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 31 only, T. 26 N., R. 20 E., is at midpoint latitudinally on the W. bdy. of sec. 31.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T26N R19E R20E 1/4 S31 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 36 only, T. 26 N., R. 19 E., bears N. 0°02' W., 4.69 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°05' W., bet. secs. 29 and 30.</p> <p>Ascend nearly level terrain, broken by many washes.</p>
40.02	<p>The 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. S30 1/4 S29 1910.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>This cor. is located in fence, bears N. and S.</p> <hr/> <p>N. 0°04' W., beginning new measurement.</p> <p>Ascend nearly level terrain, broken by many washes.</p>
39.98	<p>The cor. of secs. 19, 20, 29 and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. T26N R20E S19 S20 S30 S29 1910.</p> <p>Reset iron post to project 4 ins. above ground.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>This cor. is located in fence, bears N. and S.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>N. 89°54' W., bet. secs. 20 and 29.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.06	<p>Descend nearly level terrain, broken by many washes.</p> <p>The 1/4 sec. cor. of secs. 20 and 29, monumented with an iron post, 1 in. diam., firmly set, projecting 17 ins. above ground, with brass cap mkd. S20 1/4 S29 1910.</p> <p>Reset iron post to project 6 ins. above ground.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>N. 89°53' W., beginning new measurement.</p> <p>Descend nearly level terrain, broken by many washes.</p>
40.04	<p>The cor. of secs. 19, 20, 29 and 30.</p> <hr/> <p>West, bet. secs. 19 and 30.</p>
39.98	<p>Descend nearly level terrain, broken by many washes.</p> <p>The 1/4 sec. cor. of secs. 19 and 30, monumented with a mangled iron post, 1 in. diam., firmly set, with brass cap mkd. S19 1/4 S30 1910.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R20E S19 1/4 ——— S30 2002</p> <p>Bury the iron post alongside, and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>West, beginning new measurement.</p> <p>Descend nearly level terrain, broken by many washes.</p>
26.98	<p>The closing cor. of secs. 19 and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Point for the 1/4 sec. cor. sec. 30 only, T. 26 N., R. 20 E., is at midpoint on the W. bdy. of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R19E R20E 1/4 S30 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 25 only, T. 26 N., R. 19 E., bears N. 0°02' W., 4.75 chs. dist., hereinbefore described.</p>
40.00	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°05' W., bet. secs. 19 and 20.</p> <p>Ascend nearly level terrain, broken by many washes.</p> <p>The 1/4 sec. cor. of secs. 19 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. S19 1/4 S20 1910.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>This cor. is located in fence, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°04' W., beginning new measurement.</p> <p>Ascend nearly level terrain, broken by many washes.</p>
40.00	<p>The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T26N R20E S18 S17 S19 S20 1910.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>This cor. is located 1 lk. W. of fence, bears N. and S.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.08	<p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°53' W., bet. secs. 17 and 20.</p> <p>Descend nearly level terrain, broken by many washes.</p> <p>Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p align="center">T26N R20E S17 1/4 ——— S20 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.16	<p>The cor. of secs. 17, 18, 19 and 20.</p> <hr/> <p>N. 89°59' W., bet. secs. 18 and 19.</p> <p>Descend nearly level terrain, broken by many washes.</p>
40.00	<p>The 1/4 sec. cor. of secs. 18 and 19, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. S18 1/4 S19 1910.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/> <p>West, beginning new measurement.</p> <p>Descend nearly level terrain, broken by many washes.</p>
26.80	<p>The closing cor. of secs. 18 and 19, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>Point for the 1/4 sec. cor. sec. 19 only, T. 26 N., R. 20 E., is at midpoint on the W. bdy. of sec. 19.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T26N R19E R20E 1/4 S19 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 24 only, T. 26 N., R. 19 E., bears N. 0°01' E., 4.82 chs. dist., hereinbefore described.</p>
	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°05' E., bet. secs. 17 and 18.</p> <p>Ascend nearly level terrain, broken by many washes.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T26N R20E 1/4 S18 S17 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>This cor. is located in fence, bears N. and S.</p>
77.80	<p>Center of cattle guard, 24 ft. wide, in graded dirt road, bears N. 50° E. and S. 50° W.</p>
79.96	<p>The cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. T26N R20E S7 S8 S18 S17 1910.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>This cor. is located at corner of fences, extending N., S., and SW.</p>
	<p>From the cor. of secs. 8, 9, 16 and 17.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.04	<p>N. 89°53' W., bet. secs. 8 and 17.</p> <p>Crossing nearly level terrain, broken by many washes.</p> <p>The 1/4 sec. cor. of secs. 8 and 17, monumented with an iron post, 1 in. diam., firmly set, 10 ins. below ground, with brass cap mkd. S8 1/4 S17 1910.</p> <p>Expose iron post to project 4 ins. above ground.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>
37.60	<p>N. 89°55' W., beginning new measurement.</p> <p>Crossing nearly level land, broken by many washes.</p> <p>Center of graded dirt road, 30 ft. wide, bears N. 51° E. and S. 50° W.</p>
40.01	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/>
39.99	<p>N. 89°59' W., bet. secs. 7 and 18.</p> <p>Descend nearly level terrain, broken by many washes.</p> <p>The 1/4 sec. cor. of secs. 7 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. S7 1/4 S18 1910.</p> <p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <hr/>
26.90	<p>N. 89°58' W., beginning new measurement.</p> <p>Ascend nearly level terrain, broken by many washes.</p> <p>The closing cor. of secs. 7 and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/>
	<p>Point for the 1/4 sec. cor. sec. 18 only, T. 26 N., R. 20 E., is at midpoint on the W. bdy. of sec. 18.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R19E R20E 1/4 S18 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 13 only, T. 26 N., R. 19 E., bears N. 0°01' E., 4.885 chs. dist., hereinbefore described.</p>
	<p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°06' E., bet. secs. 7 and 8.</p> <p>Ascend over rolling terrain, broken by many washes.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R20E 1/4 S7 S8 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>This cor. is located 30 lks. S. of ravine, drains S. 55° W., and in fence, bears N. and S.</p>
79.96	<p>The cor. of secs. 5, 6, 7 and 8, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T26N R20E S6 S5 S7 S8 1910.</p> <p>Add the marks 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>This cor. is located in fence, bears N. and S.</p>
	<p>From the cor. of secs. 4, 5, 8 and 9.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>N 89°53' W., bet. secs. 5 and 8.</p> <p>Crossing rolling terrain, broken by many washes.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R20E S5 1/4 ——— S8 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 5, 6, 7 and 8.</p>
39.70	<p>N. 89°58' W., bet. secs. 6 and 7.</p> <p>Crossing rolling terrain, broken by many washes.</p> <p>The witness cor. to the 1/4 sec. cor. of secs. 6 and 7, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd. WC T26N R20E S6 1/4 S7 190.</p> <p>Reset iron post to project 4 ins. above ground.</p> <p>Add the marks 2002 and an arrow to true point to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, to top of iron post.</p> <p style="text-align: center;">—————</p> <p>N. 89°55' W., beginning new measurement.</p> <p>Crossing broken land.</p>
0.30	<p>True point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist.; falls in ravine, 16 ft. wide, 8 ft. deep, drains S. 22° W.</p>
27.38	<p>The closing cor. of secs. 6 and 7, on the W. bdy. of the Tp., hereinbefore described.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona

CHAINS

Point for the 1/4 sec. cor. sec. 7 only, T. 26 N., R. 20 E., is at midpoint on the W. bdy. of sec. 7.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.

T26N
R19E R20E
| 1/4 S7
2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the 1/4 sec. cor. of sec. 12 only, T. 26 N., R. 19 E., bears N. 0°04' W., 4.96 chs. dist., hereinbefore described.

Point for the 1/4 sec. cor. sec. 6 only, T. 26 N., R. 20 E., is at proportionate dist. on the W. bdy. of sec. 6.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T26N
R19E R20E
| 1/4 S6
2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Raise a mound of stone, 2 ft. base, to top of iron post.

This cor. is located on S. aspect of bare slope.

From this cor. point, the 1/4 sec. cor. of sec. 1 only, T. 26 N., R. 19 E., bears N. 0°02' W., 5.01 chs. dist., hereinbefore described.

From the cor. of secs. 5, 6, 7 and 8.

N. 0°12' E., bet. secs. 5 and 6.

Ascend over broken land to top of low mesa.

39.97

The 1/4 sec. cor. of secs. 5 and 6, monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. S6 1/4 S5 1910 and witnessed by a mound of stone, 3 ft. base, 1 ft. high, W. of cor.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Add the marks T26N R20E 2002 to the brass cap.</p> <p>Deposit a magnet in a white plastic case alongside the iron post.</p> <p>Relocate the original mound to raise a supporting mound of stone, 3 ft. base, to top of iron post.</p> <hr/> <p>N. 0°15' E., beginning new measurement.</p> <p>Descend low mesa, enter broken terrain.</p>
39.76	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p align="center">GENERAL DESCRIPTION</p> <hr/> <p>This survey is located on the Hopi Indian Reservation. Access is provided by three comparatively major graded dirt roads. The road connecting the communities of Tees To and White Cone, passes through the southeast portion of the township, a fork off this road passes northerly through the eastern portion of the township, to Jedito Spring. The third road connects Tees To with Jedito Spring, passing through the northwest portion of the township. A myriad of track roads provide access off these three roads to the majority of the township. Due to the terrain and soil, most of these roads become impassible in wet weather. The only inhabitants of this township are cattle and wildlife. All but one human dwelling has been destroyed. The one remaining is in the south central portion of section 21, and is unoccupied.</p> <p>The general topography of the township slopes from the broken mesa foothills in the north and east down to the nearly level desert in the southwest. Stephen's Butte dominates the township, occupying the bulk of section 27, rising over 500 ft. above the immediate terrain. The elevation ranges from 5790 ft. in the sandy region of the southwest portion to 6570 ft. at the top of Stephen's Butte. The lower elevations used to be vegetated in grasses and sage, but are now mostly covered with various weeds. The higher elevations have a ground cover of grasses and sages and a mixture of juniper and pinon pine.</p> <p>The mean magnetic declination of 11½° E., was derived from the United States Geological Survey computer program GEOMAGIX, utilizing the Regional Magnetic Field Model for Epoch 2000 for the dates of survey.</p>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Dale C. Wilson	Supervisory Land Surveyor
William F. Olver	Supervisory Land Surveyor
Danny A. West	Land Surveyor
Mark R. Searles	Surveying Technician
Mike M. Barnett	Surveying Technician
Christopher R. Higbee	Surveying Technician
Angela D. Meece	Budget Analyst Trainee

CERTIFICATE OF SURVEY

I, Geoffrey A. Graham, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 19th day of July, 2002, I have dependently resurveyed a portion of the Fifth Guide Meridian East (east boundary), the south and west boundaries, a portion of the north boundary and a portion of the subdivisional lines, T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

8-26-2003

(Date)

Geoffrey A. Graham

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the Fifth Guide Meridian East (east boundary), the south and west boundaries, a portion of the north boundary and a portion of the subdivisional lines, T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona, executed by Geoffrey A. Graham, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

March 23, 2004

(Date)

Kenny D. Rowntree

(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 26 N., R. 20 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~