

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE SIXTH STANDARD PARALLEL NORTH, (SOUTH BOUNDARY),

THE SURVEY OF THE EAST, WEST, AND NORTH BOUNDARIES,

AND

THE SUBDIVISIONAL LINES,

OF

TOWNSHIP 25 NORTH, RANGE 23 EAST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA

EXECUTED BY

Jones Curtiss, Cadastral Surveyor

Under Special Instructions dated and approved January 22, 2001, which provided for the surveys included under Group No. 863, and assignment instructions dated January 22, 2001.

Survey commenced December 4, 2001

Survey completed March 6, 2002

INDEX DIAGRAM

TOWNSHIP 25 NORTH, RANGE 23 EAST,
GILA AND SALT RIVER MERIDIAN, ARIZONA

	24	23	22	22	21	
	71	70	58	50	41	20
19	6	69 5	57 4	49 3	40 2	33 1 14
	69	68	57	48	40	32
18	7	67 8	56 9	48 10	39 11	32 12 13
	67	66	56	47	38	31
17	18	65 17	55 16	46 15	38 14	30 13 12
	65	64	54	46	37	30
17	19	63 20	53 21	45 22	36 23	29 24 11
	63	62	53	44	36	28
16	30	61 29	52 28	43 27	35 26	27 25 10
	61	60	51	43	34	26
15	31	59 32	50 33	42 34	33 35	25 36 10
	4	4	5	6	7	8

T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of the Sixth Standard Parallel North, (south boundary), the survey of the east, west, and north boundaries, and the subdivisional lines of T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

The Sixth Standard Parallel North, through Ranges 22 and 23 East, was originally surveyed by Frank Follman in 1883. The Sixth Standard Parallel North, (south boundary), Township 25 North, Range 22 West, was resurveyed by Jones Curtiss, in 2001, concurrently under this same group.

The resurvey and survey were executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated January 22, 2001, for Group No. 863, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from first order U. S. Coast and Geodetic Survey triangulation station "INDIAN 1951" and second order U. S. Geological Survey triangulation station "GREASEWOOD 1972", as published by the National Geodetic Survey, NAD 83 (1992). The geographic position of the southeast corner of township, is as follows:

Latitude: 35°31'04.36" N. Longitude: 109°49'37.08" W.

The mean magnetic declination is 11 1/2° E.

**Dependent Resurvey of the Sixth Stan. Par. North, (S. Bdy.),
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
Frank Follman, in 1883

**Dependent Resurvey of the Sixth Stan. Par. North, (S. Bdy.),
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Beginning at the stan. cor. of Tps. 25 N., Rs. 22 and 23 E., monumented with a stainless post, 2 1/2 ins. diam., with brass cap, set, and mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North, (south boundary), T. 25 N., R. 22 E., executed concurrently under this same group.</p>
	<p>S. 89°55' E., on the S. bdy. of sec. 31.</p>
	<p>Over rolling land.</p>
40.17	<p>Point for the stan. 1/4 sec. cor. of sec. 31, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">SC T 25 N R 23 E 1/4 S 31</p> <hr/> <p align="center">2001</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.34	<p>Point for the stan. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">SC T 25 N R 23 E S 31 S 32</p> <hr/> <p align="center">2001</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>S. 89°55' E., on the S. bdy. of sec. 32.</p>
	<p>Over rolling land.</p>
40.17	<p>Point for the stan. 1/4 sec. cor. of sec. 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Sixth Stan. Par. North, (S. Bdy.),
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">SC T 25 N R 23 E <u>1/4 S 32</u></p> <p style="text-align: center;">2001</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
64.60	<p>Wash, 8 ft. wide, 3 ft. deep, drains S.</p>
80.34	<p>Point for the stan. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T 25 N R 23 E <u>S 32 S 33</u></p> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.35 chs. W. of a trail road, bears N. and S.</p> <hr/>
	<p>S. 89°55' E., on the S. bdy. of sec. 33.</p> <p>Over rolling land.</p>
40.17	<p>Point for the stan. 1/4 sec. cor. of sec. 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T 25 N R 23 E <u>1/4 S 33</u></p> <p style="text-align: center;">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
45.52	<p>N. right-of-way fence of Navajo Route 15, barbed wire, 5 strands, parallels highway.</p>

**Dependent Resurvey of the Sixth Stan. Par. North, (S. Bdy.),
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
48.44	Navajo Route 15, asphalt pavement, 30 ft. wide, bears ENE and WSW.
51.27	S. right-of-way fence of Navajo Route 15, barbed wire, 5 strands, parallels highway.
55.94	Underground gas pipeline, bears ENE and WSW.
58.74	A brass tablet, 3 ins. diam., set flush in a concrete slab, 15 ins. diam., set flush with the surface of the ground, bears North, 3.14 chs. dist., with top mkd. B.I.A. ROADS 19, with an angle iron set nearby, mkd. POT 1209+37.49.
80.34	<p>Point for the stan. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">SC T 25 N R 23 E <u>S 33 S 34</u></p> <p align="center">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>S. 89°55' E., on the S. bdy. of sec. 34.</p> <p>Over rolling land.</p>
40.17	<p>Point for the stan. 1/4 sec. cor. of sec. 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">SC T 25 N R 23 E <u>1/4 S 34</u></p> <p align="center">2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
56.90	Navajo Route 153, a graded road, 38 ft. wide, bears NE and SW.

**Dependent Resurvey of the Sixth Stan. Par. North, (S. Bdy.),
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.34	<p>Point for the stan. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a magnet in a white plastic case, 24 ins. in the ground.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45°00' E., 60.0 ft. dist. with brass cap mkd. SC T25N R23E S35 RM 60.0 FT. TO COR 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45°00' W., 100.0 ft. dist. with brass cap mkd. SC T25N R23E S34 RM 100.0 FT. TO COR 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 38 lks. W. and 18 lks. N., and on the S. slope, of a wash, 15 ft. wide, 7 ft. deep, drains ESE.</p> <p>From this cor. point, a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above ground, bears S. 85°52' W., 5.63 chs. dist., with yellow plastic cap mkd. Navajo Housing Authority Property Cor.</p> <p>From this same cor. point, a rebar, 5/8 ins. diam., firmly set, projecting 4 ins. above ground, bears N. 37°38' W., 1.61 chs. dist., with yellow plastic cap mkd. Navajo Housing Authority Property Cor.</p>
	<hr/> <p>S. 89°55' E., on the S. bdy. of sec. 35.</p>
	<p>Over rolling land.</p>
17.60	<p>Navajo Route 157, a graded road, 34 ft. wide, bears NE and SW.</p>
40.17	<p>Point for the stan. 1/4 sec. cor. of sec. 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">SC T 25 N R 23 E 1/4 S 35</p> <hr/>
	<p align="center">2002</p>

**Dependent Resurvey of the Sixth Stan. Par. North, (S. Bdy.),
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
50.70	Navajo Route 6322, a graded road, 25 ft. wide, bears SSE and NNW.
73.30	Pueblo Colorado Wash, 20 ft. wide, 10 ft. deep, drains SW.
80.34	Point for the stan. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">SC T 25 N R 23 E S 35 S 36</p>
	2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	S. 89°55' E., on the S. bdy. of sec. 36.
	Over rolling land.
40.17	Point for the stan. 1/4 sec. cor. of sec. 36, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p align="center">SC T 25 N R 23 E 1/4 S 36</p>
	2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.34	Point for the stan. cor. of Tps. 25 N., Rs. 23 and 24 E., at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 9 ins. below the surface of the ground, with brass cap mkd.

**Dependent Resurvey of the Sixth Stan. Par. North, (S. Bdy.),
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS

SC
T 25 N
R 23 E R 24 E
S 36 | S 31

2002

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 30°00' E., 100.0 ft. dist. with brass cap mkd. SC T25N R24E S31 RM 100.0 FT. TO COR 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 60°00' W., 50.0 ft. dist. with brass cap mkd. SC T25N R23E S36 RM 50.0 FT. TO COR 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Cor. is located 47 lks. W. of Navajo Route 6322, a graded road, 18 ft. wide, bears NE and SW.

From this cor. point, the stan. cor. of Tps. 25 N., Rs. 24 and 25 E., monumented with a stainless steel post, 2 1/2 ins. diam., with brass cap, set, and mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North, (south boundary), T. 25 N., R. 22 E., executed concurrently under this same group, bears S. 89°55' E., 482.04 chs. dist.

This control line was fully retraced and careful search was made for evidence of intervening cors., none of which was recovered.

From this same cor. point, a sandstone, 9 x 3 ins., firmly set, projecting 16 ins. above ground, with no marks visible, bears S. 10°13' E., 6.20 chs. dist., with a mound of stone, 3 ft. base, 1 ft. high, W., and a wood post alongside with attached tag, mkd. County Surveyors Office. This monument was found in 1995 by the Navajo County Engineering Department and an Arizona Land Survey Corner Record was filed by Gerald K. Wood, AZ. L.S. 22290 attesting to the recovery of this monument during a field visit to determine only an election line between Navajo and Apache counties. This monument is of unknown origin and is not utilized in the course of this resurvey.

**Survey of the East Boundary,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the stan. cor. of Tps. 25 N., Rs. 23 and 24 E., hereinbefore described.</p> <p>North, bet. secs. 31 and 36.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 23 E R 24 E 1/4 S 36 S 31</p> </div> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 23 E R 24 E S 25 S 30 S 36 S 31</p> </div> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 25 and 30.</p> <p>Over rolling land.</p>
17.30	Navajo Route 6322, a graded road, 25 ft. wide, bears SE and NW.
19.00	Navajo Route 28, a graded road, 25 ft. wide, bears E. and W.
24.70	Underground gas pipeline, bears ENE and WSW.

**Survey of the East Boundary,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E R 24 E 1/4 S 25 S 30</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
69.50	E. bank of Pueblo Colorado Wash, 2 ft. high, bears NNE and SSW.
80.00	<p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a magnet in a white plastic case, 24 ins. in the ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45°00' W., 180.0 ft. dist. with brass cap mkd. T25N R23E S25 RM 180.0 FT. TO COR 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45°00' W., 210.0 ft. dist. with brass cap mkd. T25N R23E S24 RM 210.0 FT. TO COR 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located in Pueblo Colorado Wash, 23 lks. E. of W. bank, 1 1/2 ft. high, bears N. and S.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr style="width: 60%; margin-left: 0;"/> <p>North, bet. secs. 19 and 24.</p> <p>Over rolling land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24.

**Survey of the East Boundary,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E R 24 E 1/4 S 24 S 19</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.71 chs. S. of a barbed wire fence, 4 strands, bears ESE and WNW and 2.03 chs. E. of a power line, bears SSE and NNW.</p>
62.66	Navajo Route 15, asphalt pavement, 26 ft. wide, bears NNE and SSW.
80.00	<p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E R 24 E S 13 S 18 S 24 S 19</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the East Boundary,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 25 N R 23 E R 24 E 1/4 S 13 S 18 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
59.40	Graded road, 18 ft. wide, bears SE and NW.
80.00	Point for the cor. of secs. 7, 12, 13, and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 23 E R 24 E S 12 S 7 S 13 S 18 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.
	North, bet. secs. 7 and 12.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 23 E R 24 E 1/4 S 12 S 7 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of the East Boundary,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS																									
80.00	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr><td colspan="4" style="text-align: center;">T 25 N</td></tr> <tr><td style="text-align: center;">R 23 E</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">R 24 E</td><td></td></tr> <tr><td style="text-align: center;">S 1</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">S 6</td><td></td></tr> <tr><td colspan="4" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S 12</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">S 7</td><td></td></tr> </table> <p style="text-align: center;">2002</p> <p>Cor. is located 1.45 chs. N. of the top of a rock ledge, 5 ft. high, bears ENE and WSW and halfway up the S. slope of mesa.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over rolling land.</p>	T 25 N				R 23 E		R 24 E		S 1		S 6		-----				S 12		S 7					
T 25 N																									
R 23 E		R 24 E																							
S 1		S 6																							

S 12		S 7																							
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr><td colspan="4" style="text-align: center;">T 25 N</td></tr> <tr><td style="text-align: center;">R 23 E</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">R 24 E</td><td></td></tr> <tr><td colspan="4" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S 1</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">S 6</td><td></td></tr> </table> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 25 N				R 23 E		R 24 E		1/4				S 1		S 6									
T 25 N																									
R 23 E		R 24 E																							
1/4																									
S 1		S 6																							
80.00	<p>Point for the cor. of Tps. 25 and 26 N., Rs. 23 and 24 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr><td colspan="4" style="text-align: center;">T 26 N</td></tr> <tr><td style="text-align: center;">R 23 E</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">R 24 E</td><td></td></tr> <tr><td style="text-align: center;">S 36</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">S 31</td><td></td></tr> <tr><td colspan="4" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S 1</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">S 6</td><td></td></tr> <tr><td colspan="4" style="text-align: center;">T 25 N</td></tr> </table> <p style="text-align: center;">2002</p>	T 26 N				R 23 E		R 24 E		S 36		S 31		-----				S 1		S 6		T 25 N			
T 26 N																									
R 23 E		R 24 E																							
S 36		S 31																							

S 1		S 6																							
T 25 N																									

**Survey of the East Boundary,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Land, rolling.

Soil, sand and sandy clay.

Timber, sparse juniper; undergrowth, greasewood, scattered brush and native grasses.

**Survey of the West Boundary,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

From the stan. cor. of Tps. 25 N., Rs. 22 and 23 E., hereinbefore described.

North, bet. secs. 31 and 36.

Over rolling and broken land.

40.00 Point for the 1/4 sec. cor. of secs. 31 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N
R 22 E | R 23 E
1/4
S 36 | S 31

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

80.00 Point for the cor. of secs. 25, 30, 31, and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N
R 22 E | R 23 E
S 25 | S 30
S 36 | S 31

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of the West Boundary,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, rocky and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/>
	<p>North, bet. secs. 25 and 30.</p> <p>Over rolling and broken land.</p>
6.90	S. edge of Satan Butte, bears SSE and NNW, thence over rolling land.
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 22 E R 23 E 1/4 S 25 S 30</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
69.60	N. edge of Satan Butte, bears SSE and NNW.
78.40	Bottom of N. slope of Satan Butte, bears ENE and WSW.
80.00	<p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 22 E R 23 E S 24 S 19 S 25 S 30</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, rocky and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/>

**Survey of the West Boundary,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	North, bet. secs. 19 and 24. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 22 E R 23 E 1/4 S 24 S 19 </div> 2002 Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 13, 18, 19, and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 22 E R 23 E S 13 S 18 S 24 S 19 </div> 2002 Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located 85 lks. N. of a barbed wire fence, 5 strands, bears NNE and SSW and 2.35 chs. S. of the same fence, bears ESE and WNW. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.
	North, bet. secs. 13 and 18. Over rolling land.
15.90	Navajo Route 9001, a graded road, 20 ft. wide, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 18.

**Survey of the West Boundary,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 22 E R 23 E 1/4 S 13 S 18</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 7, 12, 13, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 22 E R 23 E S 12 S 7 S 13 S 18</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 1.67 chs. E. of a barbed wire fence, 5 strands, bears NNE and SSW.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>North, bet. secs. 7 and 12.</p> <p>Over rolling land.</p>
3.30	<p>Barbed wire fence, 5 strands, bears NNE and SSW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the West Boundary,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 25 N R 22 E R 23 E 1/4 S 12 S 7 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 1, 6, 7, and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 22 E R 23 E S 1 S 6 S 12 S 7 2002
	Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.
	North, bet. secs. 1 and 6.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 6.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 22 E R 23 E 1/4 S 1 S 6 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of Tps. 25 and 26 N, Rs. 22 and 23 E.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the West Boundary,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 26 N	
R 22 E	R 23 E
S 36	S 31
S 1	S 6
T 25 N	

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Land, rolling.

Soil, sand and sandy clay.

No timber; undergrowth, greasewood, scattered brush and native grasses.

**Survey of the North Boundary,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

From the cor. of Tps. 25 and 26 N., Rs. 23 and 24 E., hereinbefore described.

N. 89°55' W., bet. secs. 1 and 36.

Over rolling and broken land.

40.00 Point for the 1/4 sec. cor. of secs. 1 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 N	R 23 E
S 36	
1/4	_____
S 1	
T 25 N	

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

80.00 Point for the cor. of secs. 1, 2, 35, and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the North Boundary,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table style="margin: auto;"> <tr><td>T 26 N</td><td>R 23 E</td></tr> <tr><td>S 35</td><td>S 36</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td colspan="2">T 25 N</td></tr> </table>	T 26 N	R 23 E	S 35	S 36	S 2	S 1	T 25 N	
T 26 N	R 23 E								
S 35	S 36								
S 2	S 1								
T 25 N									
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Land, rolling and broken. Soil, sand and sandy clay. Timber, light juniper; undergrowth, greasewood, scattered brush and native grasses.								
	<hr/>								
	N. 89°55' W., on the S. bdy. of sec. 35, T. 26 N., R. 23 E.								
	Over rolling land.								
4.90	Top of sandy ridge, bears NE and SW.								
40.00	Point for the 1/4 sec. cor. of sec. 35 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr><td>T 26 N</td><td>R 23 E</td></tr> <tr><td>1/4</td><td>S 35</td></tr> </table>	T 26 N	R 23 E	1/4	S 35				
T 26 N	R 23 E								
1/4	S 35								
	<hr/>								
	T 25 N R 23 E								
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
80.00	Point for the cor. of secs. 34 and 35 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr><td>T 26 N</td><td>R 23 E</td></tr> <tr><td>S 34</td><td>S 35</td></tr> <tr><td>T 25 N</td><td>R 23 E</td></tr> <tr><td colspan="2">S 2</td></tr> </table>	T 26 N	R 23 E	S 34	S 35	T 25 N	R 23 E	S 2	
T 26 N	R 23 E								
S 34	S 35								
T 25 N	R 23 E								
S 2									
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								

**Survey of the North Boundary,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 89°55' W., on the S. bdy. of sec. 34, T. 26 N., R. 23 E.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of sec. 34 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E 1/4 S 34</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">T 25 N R 23 E</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 33 and 34 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E S 33 S 34</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">T 25 N R 23 E S 3</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 89°55' W., on the S. bdy. of sec. 33, T. 26 N., R. 23 E.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of sec. 33 only.</p>

**Survey of the North Boundary,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E 1/4 S 33</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">T 25 N R 23 E</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
68.80	Power line, bears SSE and NNW.
69.40	Underground gas pipeline, bears SSE and NNW.
69.90	Graded road, 26 ft. wide, bears NE and SW.
80.00	Point for the cor. of secs. 32 and 33 only.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E S 32 S 33</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">T 25 N R 23 E S 4</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr style="width: 80%; margin: auto;"/> <p>N. 89°55' W., on the S. bdy. of sec. 32, T. 26 N., R. 23 E.</p> <p>Over rolling land.</p>
40.00	Point for the 1/4 sec. cor. of sec. 32 only.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the North Boundary,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N R 23 E 1/4 S 32 <hr style="width: 10%; margin: 0 auto;"/>
	T 25 N R 23 E 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 31 and 32 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 23 E S 31 S 32 <hr style="width: 10%; margin: 0 auto;"/> T 25 N R 23 E S 5 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.
	N. 89°55' W., on the S. bdy. of sec. 31, T. 26 N., R. 23 E. Over rolling land.
40.00	Point for the 1/4 sec. cor. of sec. 31 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 23 E 1/4 S 31 <hr style="width: 10%; margin: 0 auto;"/> T 25 N R 23 E 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Set a steel fence post alongside the cor.

**Survey of the North Boundary,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Cor. is located in the E. track of a trail road, bears SSE and NNW.
81.52	The cor. of Tps. 25 and 26 N., Rs. 22 and 23 E., hereinbefore described. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.
<hr/> <p>Survey of the Subdivisional Lines, T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the stan. cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described. N. 0°01' W., bet. secs. 35 and 36. Over rolling land.
11.80	Pueblo Colorado Wash, 10 ft. wide, 2 ft. deep, drains SSE.
40.00	Point for the 1/4 sec. cor. of secs. 35 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 25 N R 23 E 1/4 S 35 S 36 2002</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Set a steel fence post alongside the cor.
51.23	Pueblo Colorado Wash, 20 ft. wide, 2 ft. deep, drains SSW.
80.00	Point for the cor. of secs. 25, 26, 35, and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 25 N	R 23 E
S 26	S 25
S 35	S 36

2002

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 30°00' E., 70.0 ft. dist. with brass cap mkd. T25N R23E S36 RM 70.0 FT. TO COR 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 30°00' W., 50.0 ft. dist. with brass cap mkd. T25N R23E S26 RM 50.0 FT. TO COR 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Cor. is located between underground gas pipelines, 12 lks. S. of N. pipeline, bears ENE and WSW, and 33 lks. S. of a trail road, parallels pipelines.

Land, rolling.

Soil, sand and sandy clay.

No timber; undergrowth, greasewood, scattered brush and native grasses.

From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.

N. 89°55' W., bet. secs. 25 and 36.

Over rolling land.

40.17

Point for the 1/4 sec. cor. of secs. 25 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 25 N R 23 E S 25 1/4 ——— S 36 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located 1.35 chs. E. of a trail road, bears NE and SW.
48.40	Pueblo Colorado Wash, 140 ft. wide, 4 ft. deep, drains SW.
80.34	The cor. of secs. 25, 26, 35, and 36.
	Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.
	—————
	N. 0°01' W., bet. secs. 25 and 26.
	Over rolling land.
24.79	Navajo Route 15, asphalt pavement, 25 ft. wide, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 23 E 1/4 S 26 S 25 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 23, 24, 25, and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 23 E S 23 S 24 S 26 S 25 2002

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Land, rolling.

Soil, sand and sandy clay.

No timber; undergrowth, greasewood, scattered brush and native grasses.

From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.

N. 89°55' W., bet. secs. 24 and 25.

Over rolling land.

40.17

Point for the 1/4 sec. cor. of secs. 24 and 25.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N R 23 E

S 24

1/4 ———

S 25

2002

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45°00' E., 54.0 ft. dist. with brass cap mkd. T25N R23E 1/4 S24 RM 54.0 FT. TO COR 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45°00' W., 154.0 ft. dist. with brass cap mkd. T25N R23E 1/4 S24 RM 154.0 FT. TO COR 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Cor. located 1.24 chs. E. of the center of Navajo Route 15, asphalt pavement, 26 ft. wide, and 2.33 chs. W. of a power line, both bear NE and SW.

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, a brass tablet, 3 1/2 ins. diam., set flush in a concrete collar, 6 ins. diam., firmly set, projecting 8 ins. above ground, bears S. 31°40' W., 2.01 chs. dist., with top mkd. B.I.A. ROADS 19, with an angle iron set nearby.</p> <p>From this same cor. point, a brass tablet, 3 1/2 ins. diam., set flush in a concrete collar, 6 ins. diam., firmly set, projecting 7 ins. above ground, bears S. 82°12' W., 2.94 chs. dist., with top mkd. B.I.A. ROADS 19.</p>
80.34	<p>The cor. of secs. 23, 24, 25, and 26.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 25 N R 23 E 1/4 S 23 S 24 2002</p>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 13, 14, 23, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 25 N R 23 E S 14 S 13 S 23 S 24 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 2.06 chs. S. of a trail road, bears ESE and WNW.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°55' W., bet. secs. 13 and 24.</p> <p>Over rolling land.</p>
23.90	Top of ridge, bears NNE and SSW.
40.17	Point for the 1/4 sec. cor. of secs. 13 and 24.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E S 13 1/4 ——— S 24</p> <p style="text-align: center;">2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.34	The cor. of secs. 13, 14, 23, and 24.
	<p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over rolling land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E 1/4 S 14 S 13</p> <p style="text-align: center;">2002</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 27 lks. N. of a trail road, bears NE and SW.</p>								
80.00	<p>Point for the cor. of secs. 11, 12, 13, and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 25 N</td> <td>R 23 E</td> </tr> <tr> <td>S 11</td> <td>S 12</td> </tr> <tr> <td>S 14</td> <td>S 13</td> </tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°55' W., bet. secs. 12 and 13.</p> <p>Over rolling land.</p>	T 25 N	R 23 E	S 11	S 12	S 14	S 13		
T 25 N	R 23 E								
S 11	S 12								
S 14	S 13								
40.17	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 25 N</td> <td>R 23 E</td> </tr> <tr> <td></td> <td>S 12</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 13</td> </tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 25 N	R 23 E		S 12	1/4	—		S 13
T 25 N	R 23 E								
	S 12								
1/4	—								
	S 13								
80.34	<p>The cor. of secs. 11, 12, 13, and 14.</p>								

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E 1/4 S 11 S 12</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E S 2 S 1 S 11 S 12</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°55' W., bet. secs. 1 and 12.</p> <p>Over rolling land.</p>
40.17	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E S 1 1/4 ——— S 12</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.34	<p>The cor. of secs. 1, 2, 11, and 12.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 0°14' E., bet. secs. 1 and 2.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E 1/4 S 2 S 1</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the stan. cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
35.57	Woven wire fence, bears NE and SW.
36.70	Navajo Route 153, a graded road, 38 ft. wide, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 34 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 23 E 1/4 S 34 S 35 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located 1.97 chs. S. of power line, bears ENE and WSW.
44.80	Underground gas pipeline, bears ENE and WSW.
47.43	Navajo Route 15, asphalt pavement, 25 ft. wide, bears ENE and WSW.
61.60	Navajo Route 9001, a graded road, 25 ft. wide, bears SE and NW.
80.00	Point for the cor. of secs. 26, 27, 34, and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 23 E S 27 S 26 ----- S 34 S 35 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.
	From the cor. of secs. 25, 26, 35, and 36. N. 89°55' W., bet. secs. 26 and 35.

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
17.53	Navajo Route 15, asphalt pavement, 25 ft. wide, bears NE and SW.
40.17	Point for the 1/4 sec. cor. of secs. 26 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 23 E S 26 1/4 ——— S 35 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
54.70	Power line, bears SSE and NNW.
55.30	Underground gas pipeline, bears SSE and NNW.
80.34	The cor. of secs. 26, 27, 34, and 35. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.
	----- N. 0°01' W., bet. secs. 26 and 27.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 23 E 1/4 S 27 S 26 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
57.80	Underground gas pipeline, bears SSE and NNW.
59.10	Power line, bears SSE and NNW.

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS									
80.00	<p>Point for the cor. of secs. 22, 23, 26, and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="812 462 1039 567"> <tr> <td>T 25 N</td> <td>R 23 E</td> </tr> <tr> <td>S 22</td> <td>S 23</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> </table> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/>	T 25 N	R 23 E	S 22	S 23	S 27	S 26		
T 25 N	R 23 E								
S 22	S 23								
S 27	S 26								
40.17	<p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>N. 89°55' W., bet. secs. 23 and 26.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="1" data-bbox="812 1249 1039 1375"> <tr> <td>T 25 N</td> <td>R 23 E</td> </tr> <tr> <td></td> <td>S 23</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 26</td> </tr> </table> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 25 N	R 23 E		S 23	1/4	—		S 26
T 25 N	R 23 E								
	S 23								
1/4	—								
	S 26								
80.34	<p>The cor. of secs. 22, 23, 26, and 27.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over rolling land.</p>								

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E 1/4 S 22 S 23</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22, and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E S 15 S 14 S 22 S 23</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>N. 89°55' W., bet. secs. 14 and 23.</p> <p>Over rolling land.</p>
40.17	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E S 14 1/4 ——— S 23</p> <p style="text-align: center;">2002</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.34	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.21 chs. W. of a trail road, bears NNE and SSW.</p> <p>The cor. of secs. 14, 15, 22, and 23.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E 1/4 S 15 S 14</p> <p style="text-align: center;">2002</p>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 10, 11, 14, and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E S 10 S 11 S 15 S 14</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 11, 12, 13, and 14.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 89°55' W., bet. secs. 11 and 14. Over rolling land.
40.17	Point for the 1/4 sec. cor. of secs. 11 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 23 E S 11 1/4 ——— S 14 2002 </div>
80.34	Deposit a magnet in a white plastic case at the base of the stainless steel post. The cor. of secs. 10, 11, 14, and 15. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.

	N. 0°01' W., bet. secs. 10 and 11. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 23 E 1/4 S 10 S 11 2002 </div>
80.00	Deposit a magnet in a white plastic case at the base of the stainless steel post. Point for the cor. of secs. 2, 3, 10, and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 25 N R 23 E S 3 S 2 S 10 S 11 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.
	<hr/> From the cor. of secs. 1, 2, 11, and 12. N. 89°55' W., bet. secs. 2 and 11. Over rolling land.
40.17	Point for the 1/4 sec. cor. of secs. 2 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 23 E S 2 1/4 ——— S 11 2002
80.34	Deposit a magnet in a white plastic case at the base of the stainless steel post. The cor. of secs. 2, 3, 10, and 11. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.
	<hr/> N. 0°01' W., bet. secs. 2 and 3. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p style="text-align: center;">T 25 N R 23 E 1/4 S 3 S 2</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the closing cor. of secs. 2 and 3, at intersection with the S. bdy. of sec. 34, T. 26 N., R. 23 E., identical to the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E S 34 ----- S 3 S 2 T 25 N R 23 E C C</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the cor. of secs. 34 and 35 only, T. 26 N., R. 23 E., bears S. 89°55' E., 0.68 chs. dist., hereinbefore described.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 2 only, T. 25 N., R. 23 E., is at midpoint on the N. bdy. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E ----- 1/4 S 2 T 25 N R 23 E</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 35 only, T. 26 N., R. 23 E., bears S. 89°55' E., 0.34 chs. dist., hereinbefore described.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same cor. point, the cor. of secs. 34 and 35 only, T. 26 N., R. 23 E., bears N. 89°55' W., 39.66 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the stan. cor. of secs. 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over rolling land.</p>
10.30	Underground gas pipeline, bears ENE and WSW.
12.28	S. right-of-way fence of Navajo Route 15, barbed wire, 5 strands, parallels highway.
13.50	Navajo Route 15, asphalt pavement, 35 ft. wide, bears ENE and WSW.
14.72	N. right-of-way fence of Navajo Route 15, barbed wire, 5 strands, parallels highway.
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E 1/4 S 33 S 34</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.97 chs. S. of a power line, bears ENE and WSW.</p>
80.00	<p>Point for the cor. of secs. 27, 28, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 25 N R 23 E S 28 S 27 S 33 S 34 2002 Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located 2.58 chs. S. of a trail road, bears ESE and WNW. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses. <hr/> From the cor. of secs. 26, 27, 34, and 35. N. 89°55' W., bet. secs. 27 and 34. Over rolling land. 13.40 Navajo Route 9001, a graded road, 26 ft. wide, bears SE and NW. 40.17 Point for the 1/4 sec. cor. of secs. 27 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 25 N R 23 E S 27 1/4 ——— S 34 2002 Deposit a magnet in a white plastic case at the base of the stainless steel post. 80.34 The cor. of secs. 27, 28, 33, and 34. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses. <hr/> N. 0°02' W., bet. secs. 27 and 28. Over rolling land.

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E 1/4 S 28 S 27</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
66.30	Navajo Route 9001, a graded road, 26 ft. wide, bears SE and NW.
80.00	<p>Point for the cor. of secs. 21, 22, 27, and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E S 21 S 22 S 28 S 27</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>N. 89°55' W., bet. secs. 22 and 27.</p> <p>Over rolling land.</p>
9.00	Power line, bears SSE and NNW.
9.60	Underground gas pipeline, bears SSE and NNW.
40.17	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 25 N R 23 E S 22 1/4 ——— S 27 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.34	The cor. of secs. 21, 22, 27, and 28. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.

	N. 0°02' W., bet. secs. 21 and 22. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 23 E 1/4 S 21 S 22 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 15, 16, 21, and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 23 E S 16 S 15 ———— S 21 S 22 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 14, 15, 22, and 23. N. 89°55' W., bet. secs. 15 and 22. Over rolling land.</p>
40.17	<p>Point for the 1/4 sec. cor. of secs. 15 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E S 15 1/4 ——— S 22</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
43.70	Power line, bears SSE and NNW.
44.20	Underground gas pipeline, bears SSE and NNW.
80.34	The cor. of secs. 15, 16, 21, and 22.
	<p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 15 and 16. Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E 1/4 S 16 S 15</p> <p style="text-align: center;">2002</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>								
80.00	<p>Point for the cor. of secs. 9, 10, 15, and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 25 N</td><td>R 23 E</td></tr> <tr><td>S 9</td><td>S 10</td></tr> <tr><td>S 16</td><td>S 15</td></tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.44 chs. W. of an underground gas pipeline, and 2.03 chs. W. of power line, both bear SSE and NNW.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>N. 89°55' W., bet. secs. 10 and 15.</p> <p>Over rolling land.</p>	T 25 N	R 23 E	S 9	S 10	S 16	S 15		
T 25 N	R 23 E								
S 9	S 10								
S 16	S 15								
40.17	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 25 N</td><td>R 23 E</td></tr> <tr><td>S 10</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 15</td><td></td></tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 30 lks. E. of a trail road, bears N. and S.</p>	T 25 N	R 23 E	S 10		1/4	—	S 15	
T 25 N	R 23 E								
S 10									
1/4	—								
S 15									
80.34	<p>The cor. of secs. 9, 10, 15, and 16.</p>								

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over rolling land.</p>
3.30	Underground gas pipeline, bears SSE and NNW.
4.70	Power line, bears SSE and NNW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E 1/4 S 9 S 10</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 9, and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E S 4 S 3 S 9 S 10</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>N. 89°55' W., bet. secs. 3 and 10.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
40.17	Point for the 1/4 sec. cor. of secs. 3 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 23 E S 3 1/4 ——— S 10 2002 </div>
80.34	The cor. of secs. 3, 4, 9, and 10. Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses. <hr/>
	N. 0°02' W., bet. secs. 3 and 4. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 23 E 1/4 S 4 S 3 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the closing cor. of secs. 3 and 4, at intersection with the S. bdy. of sec. 33, T. 26 N., R. 23 E., identical to the N. bdy. of the Tp. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 26 N R 23 E
S 33

S 4 | S 3
T 25 N R 23 E
C C

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the cor. of secs. 33 and 34 only, T. 26 N., R. 23 E., bears S. $89^{\circ}55'$ E., 1.02 chs. dist., hereinbefore described.

The point for the 1/4 sec. cor. of sec. 3 only, T. 25 N., R. 23 E., is at midpoint on the N. bdy. of sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 N R 23 E

1/4 S 3
T 25 N R 23 E

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the 1/4 sec. cor. of sec. 34 only, T. 26 N., R. 23 E., bears S. $89^{\circ}55'$ E., 0.85 chs. dist., hereinbefore described.

From this same cor. point, the cor. of secs. 33 and 34 only, T. 26 N., R. 23 E., bears N. $89^{\circ}55'$ W., 39.15 chs. dist., hereinbefore described.

Land, rolling.

Soil, sand and sandy clay.

No timber; undergrowth, greasewood, scattered brush and native grasses.

From the stan. cor. of secs. 32 and 33, on the S. bdy. of the Tp., hereinbefore described.

N. $0^{\circ}03'$ W., bet. secs. 32 and 33.

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	Over rolling land.						
38.20	Wash, 15 ft. wide, 2 ft. deep, drains SW.						
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 25 N</td><td>R 23 E</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S 32</td><td> S 33</td></tr> </table> <p>2002</p> </div>	T 25 N	R 23 E	1/4		S 32	S 33
T 25 N	R 23 E						
1/4							
S 32	S 33						
	Deposit a magnet in a white plastic case at the base of the stainless steel post.						
75.60	Wash, 15 ft. wide, 3 ft. deep, drains SSW.						
80.00	Point for the cor. of secs. 28, 29, 32, and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 25 N</td><td>R 23 E</td></tr> <tr><td>S 29</td><td> S 28</td></tr> <tr><td>S 32</td><td> S 33</td></tr> </table> <p>2002</p> </div>	T 25 N	R 23 E	S 29	S 28	S 32	S 33
T 25 N	R 23 E						
S 29	S 28						
S 32	S 33						
	Deposit a magnet in a white plastic case at the base of the stainless steel post.						
	Cor. is located 1.09 chs. N. of a wash, 10 ft. wide, 3 ft. deep, and 24 lks. E. of same wash, 10 ft. wide, 1 ft. deep, drains SSE, and 3.03 chs. S. of an earthen dike, bears ENE and WSW.						
	Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.						
	From the cor. of secs. 27, 28, 33, and 34. N. 89°55' W., bet. secs. 28 and 33. Over rolling land.						
40.17	Point for the 1/4 sec. cor. of secs. 28 and 33.						

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E S 28 1/4 ——— S 33</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 86 lks. W. of a trail road, and 73 lks. E. of a power line, both bear NNE and SSW.</p>
80.34	<p>The cor. of secs. 28, 29, 32, and 33.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 28 and 29.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E 1/4 S 29 S 28</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 20, 21, 28, and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E S 20 S 21 S 29 S 28</p> <p style="text-align: center;">2002</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>N. 89°55' W., bet. secs. 21 and 28.</p> <p>Over rolling land.</p>
15.00	Navajo Route 9001, a graded road, 26 ft. wide, bears SE and NW.
40.17	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 25 N R 23 E S 21 1/4 ——— S 28</p> <p align="center">2002</p>
80.34	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 20, 21, 28, and 29.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/>
40.00	<p>N. 0°03' W., bet. secs. 20 and 21.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T 25 N R 23 E 1/4 S 20 S 21</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
50.90	Navajo Route 9001, a graded road, 30 ft. wide, bears ENE and WSW.
80.00	<p>Point for the cor. of secs. 16, 17, 20, and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 25 N R 23 E S 17 S 16 S 20 S 21</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 47 lks. N. of a trail road, bears ENE and WSW.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>N. 89°55' W., bet. secs. 16 and 21.</p> <p>Over rolling land.</p>
40.17	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 25 N R 23 E S 16 1/4 ——— S 21</p> <p align="center">2002</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.86 chs. S. of a trail road, bears ENE and WSW.</p> <p>64.80 Graded road, 26 ft. wide, bears N. and S.</p> <p>80.34 The cor. of secs. 16, 17, 20, and 21.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 25 N R 23 E 1/4 S 17 S 16</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 8, 9, 16, and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 25 N R 23 E S 8 S 9 S 17 S 16</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/>
--------	--

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>N. 89°55' W., bet. secs. 9 and 16.</p> <p>Over rolling land.</p>
40.17	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 23 E S 9 1/4 ——— S 16</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
46.40	<p>Graded road, 26 ft. wide, bears NE. and SW.</p>
80.34	<p>The cor. of secs. 8, 9, 16, and 17.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 23 E 1/4 S 8 S 9</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
44.30	<p>Graded road, 25 ft. wide, bears SE and NW.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 8, and 9.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 25 N</td> <td>R 23 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 5</td> <td>S 4</td> </tr> <tr> <td style="border-right: 1px solid black;">S 8</td> <td>S 9</td> </tr> </table> </p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>N. 89°55' W., bet. secs. 4 and 9.</p> <p>Over rolling land.</p>	T 25 N	R 23 E	S 5	S 4	S 8	S 9		
T 25 N	R 23 E								
S 5	S 4								
S 8	S 9								
32.70	Power line, bears SSE and NNW.								
33.30	Underground gas pipeline, bears SSE and NNW.								
40.17	Point for the 1/4 sec. cor. of secs. 4 and 9.								
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 25 N</td> <td>R 23 E</td> </tr> <tr> <td></td> <td style="text-align: center;">S 4</td> </tr> <tr> <td style="text-align: center;">1/4</td> <td style="border-top: 1px solid black; border-bottom: 1px solid black;">—</td> </tr> <tr> <td></td> <td style="text-align: center;">S 9</td> </tr> </table> </p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 25 N	R 23 E		S 4	1/4	—		S 9
T 25 N	R 23 E								
	S 4								
1/4	—								
	S 9								
80.34	<p>The cor. of secs. 4, 5, 8, and 9.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 4 and 5.</p>								

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 23 E 1/4 S 5 S 4 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
65.30	Graded road, 26 ft. wide, bears NE and SW.
80.00	Point for the closing cor. of secs. 4 and 5, at intersection with the S. bdy. of sec. 32, T. 26 N., R. 23 E., identical to the N. bdy. of the Tp. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 23 E S 32 ----- S 5 S 4 T 25 N R 23 E C C 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	From this cor. point, the cor. of secs. 32 and 33 only, T. 26 N., R. 23 E., bears S. 89°55' E., 1.36 chs. dist., hereinbefore described.
	<hr/> The point for the 1/4 sec. cor. of sec. 4 only, T. 25 N., R. 23 E., is at midpoint on the N. bdy. of sec. 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 26 N R 23 E</p> <hr style="width: 10%; margin: auto;"/> <p>1/4 S 4 T 25 N R 23 E</p> <p>2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, the 1/4 sec. cor. of sec. 33 only, T. 26 N., R. 23 E., bears S. 89°55' E., 1.19 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the cor. of secs. 32 and 33 only, T. 26 N., R. 23 E., bears N. 89°55' W., 38.81 chs. dist., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the stan. cor. of secs. 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over rolling and broken land across Satan Butte.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 25 N R 23 E 1/4 S 31 S 32 </p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
40.08	<p>Top of Satan Butte, bears SSE and NNW.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 25 N	R 23 E
S 30	S 29
S 31	S 32

2002

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45°00' E., 62.0 ft. dist. with brass cap mkd. T25N R23E S29 RM 62.0 FT. TO COR 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45°00' W., 190.0 ft. dist. with brass cap mkd. T25N R23E S30 RM 190.0 FT. TO COR 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Land, rolling.

Soil, rocky and sandy clay.

No timber; undergrowth, greasewood, scattered brush and native grasses.

From the cor. of secs. 28, 29, 32, and 33.

N. 89°55' W., bet. secs. 29 and 32.

Over rolling and broken land.

36.10 Top of Satan Butte, bears SSE and NNW.

40.17 Point for the 1/4 sec. cor. of secs. 29 and 32.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N	R 23 E
	S 29
1/4	_____
	S 32

2002

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.34	The cor. of secs. 29, 30, 31, and 32. Land, rolling. Soil, rocky and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.
	<hr/>
	N. 89°55' W., bet. secs. 30 and 31. Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31. Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in a drill hole in volcanic bedrock, with top mkd.
	T 25 N R 23 E S 30 1/4 ——— S 31 2002
	Deposit a magnet in a white plastic case at the base of the brass tablet.
76.90	W. edge of Satan Butte, bears N. and S.
80.25	The cor. of secs. 25, 30, 31, and 36 on the W. bdy. of the Tp., hereinbefore described. Land, rolling. Soil, rocky and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.
	<hr/>
	From the cor. of secs. 29, 30, 31, and 32. N. 0°03' W., bet. secs. 29 and 30. Over rolling and broken land.
13.30	N. edge of Satan Butte, bears E. and W.
23.30	Bottom of N. slope of Satan Butte, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30.

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E 1/4 S 30 S 29</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 19, 20, 29, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E S 19 S 20 S 30 S 29</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 20, 21, 28, and 29. N. 89°55' W., bet. secs. 20 and 29. Over rolling land.</p>
40.17	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E S 20 1/4 ——— S 29</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.34	<p>The cor. of secs. 19, 20, 29, and 30.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 89°55' W., bet. secs. 19 and 30.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E S 19 1/4 ——— S 30</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.16	<p>The cor. of secs. 19, 24, 25, and 30 on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over rolling land.</p>
34.40	<p>Navajo Route 9001, a graded road, 30 ft. wide, bears E. and W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 25 N R 23 E 1/4 S 19 S 20 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 17, 18, 19, and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 23 E S 18 S 17 S 19 S 20 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.
	<hr/> From the cor. of secs. 16, 17, 20, and 21. N. 89°55' W., bet. secs. 17 and 20. Over rolling land.
40.17	Point for the 1/4 sec. cor. of secs. 17 and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 N R 23 E S 17 1/4 ——— S 20 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.34	The cor. of secs. 17, 18, 19, and 20.

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>N. 89°55' W., bet. secs. 18 and 19.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
67.10	Navajo Rt. 9001, a graded road, 25 ft. wide, bears SSE and NNW.
80.07	The cor. of secs. 13, 18, 19, and 24 on the W. bdy. of the Tp., hereinbefore described.
	<p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 N R 23 E 1/4 S 18 S 17</p> <p style="text-align: center;">2002</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
80.00	Point for the cor. of secs. 7, 8, 17, and 18.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 25 N</td> <td>R 23 E</td> </tr> <tr> <td>S 7</td> <td>S 8</td> </tr> <tr> <td>S 18</td> <td>S 17</td> </tr> </table>	T 25 N	R 23 E	S 7	S 8	S 18	S 17		
T 25 N	R 23 E								
S 7	S 8								
S 18	S 17								
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
	Cor. is located 2.14 chs. W. of a trail road, bears SSE and NNW.								
	Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.								
	From the cor. of secs. 8, 9, 16, and 17.								
	N. 89°55' W., bet. secs. 8 and 17.								
	Over rolling land.								
40.17	Point for the 1/4 sec. cor. of secs. 8 and 17.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 25 N</td> <td>R 23 E</td> </tr> <tr> <td>S 8</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 17</td> <td></td> </tr> </table>	T 25 N	R 23 E	S 8		1/4	—	S 17	
T 25 N	R 23 E								
S 8									
1/4	—								
S 17									
	2002								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
80.34	The cor. of secs. 7, 8, 17, and 18.								
	Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.								

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<hr/> <p>N. 89°55' W., bet. secs. 7 and 18.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 23 E</p> <p>S 7</p> <p>1/4 ———</p> <p>S 18</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 76 lks. S. of a power line, bears ENE and WSW.</p>
79.99	<p>The cor. of secs. 7, 12, 13, and 18 on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0°03' W., bet. secs. 7 and 8.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 N R 23 E</p> <p>1/4</p> <p>S 7 S 8</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 7, and 8.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 N	R 23 E
S 6	S 5
S 7	S 8

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Cor. is located 2.76 chs. E. and 86 lks. S. of a wash, 9 ft. wide, 1 ft. deep, drains WSW.

Land, rolling.

Soil, sand and sandy clay.

No timber; undergrowth, greasewood, scattered brush and native grasses.

From the cor. of secs. 4, 5, 8, and 9.

N. 89°55' W., bet. secs. 5 and 8.

Over rolling land.

40.17

Point for the 1/4 sec. cor. of secs. 5 and 8.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below the surface of the ground, with brass cap mkd.

T 25 N	R 23 E
S 5	
1/4	—
S 8	

2002

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 80°00' E., 40.0 ft. dist. with brass cap mkd. T25N R23E S8 RM 40.0 FT. TO COR 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 80°00' W., 60.0 ft. dist. with brass cap mkd. T25N R23E S5 RM 60.0 FT. TO COR 2002 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located on the shoulder and 17 lks. E. of the center of a graded road, bears N. and S.</p>
80.34	<p>The cor. of secs. 5, 6, 7, and 8.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p>
	<hr/> <p>N. 89°55' W., bet. secs. 6 and 7.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 25 N R 23 E S 6 1/4 ——— S 7</p> <p align="center">2002</p>
79.90	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 1, 6, 7, and 12 on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sand and sandy clay. No timber; undergrowth, greasewood, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0°03' W., bet. secs. 5 and 6.</p>

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 6. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 N R 23 E 1/4 S 6 S 5 2002 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the closing cor. of secs. 5 and 6, at intersection with the S. bdy. of sec. 31, T. 26 N., R. 23 E., identical to the N. bdy. of the Tp. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 23 E S 31 ----- S 6 S 5 T 25 N R 23 E C C 2002 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post. From this cor. point, the cor. of secs. 31 and 32 only, T. 26 N., R. 23 E., bears S. 89°55' E., 1.70 chs. dist., hereinbefore described. <hr/> Point for the 1/4 sec. cor. of sec. 5 only, T. 25 N., R. 23 E., is at midpoint on the N. bdy. of sec. 5. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 26 N R 23 E

1/4 S 5
T 25 N R 23 E

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the 1/4 sec. cor. of sec. 32 only, T. 26 N., R. 23 E., bears S. 89°55' E., 1.53 chs. dist., hereinbefore described.

From this same cor. point, the cor. of secs. 31 and 32 only, T. 26 N., R. 23 E., bears N. 89°55' W., 38.47 chs. dist., hereinbefore described.

Point for the 1/4 sec. cor. of sec. 6 only, T. 25 N., R. 23 E., at 40.00 chs. in westing from the closing of secs. 5 and 6, on the N. bdy. of sec. 6.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 N R 23 E

1/4 S 6
T 25 N R 23 E

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the 1/4 sec. cor. of sec. 31 only, T. 26 N., R. 23 E., bears S. 89°55' E., 1.70 chs. dist., hereinbefore described.

From this same cor. point, the cor. of Tps. 25 and 26 N., Rs. 22 and 23 E., bears N. 89°55' W., 39.82 chs. dist., hereinbefore described.

Land, rolling.

Soil, sand and sandy clay.

No timber; undergrowth, greasewood, scattered brush and native grasses.

T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The area surveyed is within the Navajo Indian Reservation and around the community of Greasewood, Arizona. Greasewood Spring Community School, a trading post, a church and Navajo Housing Units are all located in Section 35.

The terrain is mostly rolling and some broken areas. The drainage is southwesterly. The principal drainage is Steamboat Wash, except the southeastern portion of the township where it drains into Pueblo Colorado Wash.

The elevation varies from 5800 to 6400 feet above sea level. The soil is sandy and sandy clay. There is a light stand of pinon and juniper atop the mesa in the northeastern portion of the township. Undergrowth principally consists of scattered brush, cacti, greasewood and native grasses.

Principal access to this township is provided by Navajo Route 15, an asphalt pavement highway, which enters the township in section 33, runs northeasterly into section 35, and thence north-northeast and exits in section 24. There are some major graded roads and trail roads throughout the township. Much of the area is used for grazing livestock. There is no mining activity in the township.

The mean magnetic declination of $11\ 1/2^\circ$ E. was derived from the computer program GEOMAGIX, utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD ASSISTANTS

NAMES	CAPACITY
William F. Olver	Cadastral Surveyor
Daniel Bryan	Engineering Technician
Wilfred Chee	Engineering Technician
Edward Clarke	Engineering Technician
Reuben Mason	Engineering Technician
Barney Woodie	Engineering Technician

CERTIFICATE OF SURVEY

I, Jones Curtiss, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 22nd day of January, 2001, I have dependently resurveyed the Sixth Standard Parallel North, (south boundary), surveyed the east, west, and north boundaries, and the subdivisional lines, T. 25 N., R. 23 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

March 29, 2004
(Date)

Jones Curtiss
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the Sixth Standard Parallel North, (south boundary), the survey of the east, west, and north boundaries, and the subdivisional lines, T. 25 N., R. 23 E., Gila and Salt River Meridian, in the State of Arizona, executed by Jones Curtiss, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

March 30, 2004
(Date)

Kenny D Rownton
(Chief Cadastral Surveyor of Arizona)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 25 N., R. 23 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.

(Date)

(Chief Cadastral Surveyor of Arizona)