

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
SURVEY OF THE
EAST, WEST, AND NORTH BOUNDARIES,
AND
THE SUBDIVISIONAL LINES,
OF
TOWNSHIP 26 NORTH, RANGE 23 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA

EXECUTED BY

Leonard R. Sandoval, Cadastral Surveyor

Under Special Instructions dated and approved January 22, 2001, which provided for the surveys included under Group No. 863, and assignment instructions dated January 22, 2001.

Survey commenced March 4, 2002

Survey completed March 20, 2002

INDEX DIAGRAM

TOWNSHIP 26 NORTH, RANGE 23 EAST,
GILA AND SALT RIVER MERIDIAN, ARIZONA

13	18 6	59	18 5	49	17 4	41	16 3	33	15 2	26	14 1	7
12	59 7	57	58 8	47	48 9	39	40 10	32	33 11	24	25 12	7
11	57 18	55	56 17	46	47 16	38	39 15	30	31 14	23	24 13	6
10	55 19	53	54 20	45	45 21	36	37 22	29	30 23	22	22 24	5
9	53 30	51	52 29	43	44 28	35	36 27	28	28 26	20	21 25	4
8	51 31	49	50 32	42	43 33	34	34 34	26	27 35	19	20 36	3

T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of the east, west, and north boundaries and the subdivisional lines, T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

John G. Evans surveyed the (abandoned) south boundary of the Navajo Indian Reservation through Township 26 North, Range 23 East, in 1884-85.

The south boundary, Township 27 North, Range 25 East, was surveyed by F. C. Miller in 1915 and resurveyed by William F. Olver, Leonard R. Sandoval, and Olian T. Shockley in 1989-90.

The east, west, and north boundaries, Township 25 North, Range 23 East, were surveyed by Jones Curtiss, in 2002, concurrently under this same group.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated January 22, 2001, for Group No. 863, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Geodetic control was derived from Global Positioning System (GPS) static post observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) FERNO MESA CORS ARP, FLAGSTAFF 1 CORS ARP and AZTEC CORS ARP. The NAD 83 (CORS96) (EPOCH: 2002), geographic position of the southeast corner of township, is as follows:

Latitude: 35°36'17.58" N. Longitude: 109°49'37.08" W.

The mean magnetic declination is 11 3/4° E.

**Survey of the East Boundary,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

Beginning at the cor. of Tps. 25 and 26 N., Rs. 23 and 24 E., monumented with a stainless steel post, 2½ ins. diam., with brass cap, set, and mkd. as described in the field notes of the survey of the east boundary, T. 25 N., R. 23 E., executed concurrently under this same group.

North, bet. secs. 31 and 36.

Over rolling land.

**Survey of the East Boundary,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E R 24 E 1/4 S 36 S 31</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E R 24 E S 25 S 30 S 36 S 31</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 47 lks. S. of a wash, 15 ft. wide, 15 ft. deep, drains SW.</p> <p>Land, rolling and broken. Soil, sandy clay. Timber, scattered juniper; undergrowth, brush and native grasses.</p> <hr/> <p>North, bet. secs. 25 and 30.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the East Boundary,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N R 23 E R 24 E 1/4 S 25 S 30 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
56.91	Navajo Route 9031, a graded road, 26 ft. wide, bears E. and W.
80.00	Point for the cor. of secs. 19, 24, 25, and 30.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 23 E R 24 E S 24 S 19 S 25 S 30 2002
	Land, rolling. Soil, sandy clay. Timber, scattered juniper; undergrowth, brush and native grasses.
	North, bet. secs. 19 and 24.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 23 E R 24 E 1/4 S 24 S 19 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 13, 18, 19, and 24.

**Survey of the East Boundary,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 N	
R 23 E	R 24 E
S 13	S 18
S 24	S 19

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Land, rolling.

Soil, sandy clay.

Timber, scattered juniper; undergrowth, brush and native grasses.

North, bet. secs. 13 and 18.

Over rolling land.

40.00

Point for the 1/4 sec. cor. of secs. 13 and 18.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 N	
R 23 E	R 24 E
1/4	
S 13	S 18

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

80.00

Point for the cor. of secs. 7, 12, 13, and 18.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 N	
R 23 E	R 24 E
S 12	S 7
S 13	S 18

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of the East Boundary,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy clay. Timber, scattered juniper; undergrowth, brush and native grasses.</p> <hr/> <p>North, bet. secs. 7 and 12.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 23 E R 24 E 1/4 S 12 S 7</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 23 E R 24 E S 1 S 6 <hr/>S 12 S 7</p> <p>2002</p> </div> <p>Land, gently rolling. Soil, sandy clay. Timber, scattered juniper; undergrowth, brush and native grasses.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the East Boundary,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 26 N
R 23 E | R 24 E
1/4
S 1 | S 6

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Cor. is located 68 lks. N. of a trail road, bears ENE and WSW.

80.00

Point for the cor. of Tps. 26 and 27 N., Rs. 23 and 24 E.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 27 N
R 23 E | R 24 E
S 36 | S 31

S 1 | S 6
T 26 N

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor. point, the cor. of Tps. 26 and 27 N., Rs. 24 and 25 E., bears S. 89°56' E., 481.65 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T27N R24E R25E S36 S31 S1 S6 T26N 1990 1915.

Land, rolling.

Soil, sandy clay.

Timber, scattered juniper; undergrowth, brush and native grasses.

**Survey of the West Boundary,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

From the cor. of Tps. 25 and 26 N., Rs. 22 and 23 E., monumented with a stainless steel post, 2½ ins. diam., with brass cap, set, and mkd. as described in the field notes of the survey of the west boundary, T. 25 N., R. 23 E., executed concurrently under this same group.

North, bet. secs. 31 and 36.

**Survey of the West Boundary,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 36. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 22 E R 23 E 1/4 S 36 S 31 </div> 2002 Deposit a magnet in a white plastic case at the base of the stainless steel post.
56.43	Trail road, bears NE and SW.
80.00	Point for the cor. of secs. 25, 30, 31, and 36. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 22 E R 23 E S 25 S 30 S 36 S 31 </div> 2002 Deposit a magnet in a white plastic case at the base of the stainless steel post. Land, rolling. Soil, sandy clay. No timber; undergrowth, scattered brush and native grasses.
	<hr/> North, bet. secs. 25 and 30. Over rolling land.
6.26	Trail road, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the West Boundary,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N R 22 E R 23 E 1/4 S 25 S 30 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 19, 24, 25, and 30.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 22 E R 23 E S 24 S 19 S 25 S 30 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located 38 lks. N. of a trail road, bears E. and W.
	Land, rolling. Soil, sandy clay. No timber; undergrowth, scattered brush and native grasses.
	North, bet. secs. 19 and 24.
	Over rolling and broken land.
28.20	Top of a bluff, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 22 E R 23 E 1/4 S 24 S 19 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of the West Boundary,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS									
75.64	Wash, 15 ft. wide, 8 ft. deep, drains ENE.								
80.00	Point for the cor. of secs. 13, 18, 19, and 24. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 26 N</td></tr> <tr><td>R 22 E</td><td> R 23 E</td></tr> <tr><td>S 13</td><td> S 18</td></tr> <tr><td>S 24</td><td> S 19</td></tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy and gravelly clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>North, bet. secs. 13 and 18. Over rolling and broken land.</p>	T 26 N		R 22 E	R 23 E	S 13	S 18	S 24	S 19
T 26 N									
R 22 E	R 23 E								
S 13	S 18								
S 24	S 19								
29.35	Wash, 15 ft. wide, 12 ft. deep, drains E.								
40.00	Point for the 1/4 sec. cor. of secs. 13 and 18. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 26 N</td></tr> <tr><td>R 22 E</td><td> R 23 E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 13</td><td> S 18</td></tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 26 N		R 22 E	R 23 E	1/4		S 13	S 18
T 26 N									
R 22 E	R 23 E								
1/4									
S 13	S 18								
80.00	Point for the cor. of secs. 7, 12, 13, and 18. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.								

**Survey of the West Boundary,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS											
	<table style="margin: auto;"> <tr><td colspan="2">T 26 N</td></tr> <tr><td>R 22 E</td><td>R 23 E</td></tr> <tr><td>S 12</td><td>S 7</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 13</td><td>S 18</td></tr> </table>	T 26 N		R 22 E	R 23 E	S 12	S 7	<hr/>		S 13	S 18
T 26 N											
R 22 E	R 23 E										
S 12	S 7										
<hr/>											
S 13	S 18										
	2002										
	Deposit a magnet in a white plastic case at the base of the stainless steel post.										
	Land, rolling and broken. Soil, sandy and gravelly clay. Timber, piñon and juniper; undergrowth, brush and native grasses.										
	<hr/>										
	North, bet. secs. 7 and 12.										
	Over rolling land.										
20.00	Trail road, bears ENE and WSW.										
40.00	Point for the 1/4 sec. cor. of secs. 7 and 12.										
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin: auto;"> <tr><td colspan="2">T 26 N</td></tr> <tr><td>R 22 E</td><td>R 23 E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 12</td><td>S 7</td></tr> </table>	T 26 N		R 22 E	R 23 E	1/4		S 12	S 7		
T 26 N											
R 22 E	R 23 E										
1/4											
S 12	S 7										
	2002										
	Deposit a magnet in a white plastic case at the base of the stainless steel post.										
74.48	Trail road, bears ESE and WNW.										
80.00	Point for the cor. of secs. 1, 6, 7, and 12.										
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin: auto;"> <tr><td colspan="2">T 26 N</td></tr> <tr><td>R 22 E</td><td>R 23 E</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 12</td><td>S 7</td></tr> </table>	T 26 N		R 22 E	R 23 E	S 1	S 6	<hr/>		S 12	S 7
T 26 N											
R 22 E	R 23 E										
S 1	S 6										
<hr/>											
S 12	S 7										
	2002										

**Survey of the West Boundary,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, second order U. S. Geological Survey triangulation station "TOYEI 1972", published by the National Geodetic Survey, bears N. 64°53' W., 68.03 chs. dist., monumented with a standard U. S. Geological Survey brass tablet, 3 ins. diam., cemented in a concrete casting, 2 ins. diam., projecting 8 ins. above ground, with top mkd. TOYEI 1972.</p> <p>From this same cor. point, a corner of an octagonal shaped log hogan, 7½ ft. long per side, bears S. 49°16' E., 1.39 chs. dist.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over rolling and broken land.</p>
14.87	Underground gas pipeline, bears SSE and NNW.
15.44	Trail road, bears SSE and NNW.
16.13	Power line, bears SSE and NNW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 22 E R 23 E 1/4 S 1 S 6 2002</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of Tps. 26 and 27 N., Rs. 22 and 23 E.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the West Boundary,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 27 N	
R 22 E	R 23 E
S 36	S 31
S 1	S 6
T 26 N	

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Land, rolling and broken.

Soil, sandy clay.

Timber, piñon and juniper; undergrowth, brush and native grasses.

**Survey of the North Boundary,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

From the cor. of Tps. 26 and 27 N., Rs. 23 and 24 E., hereinbefore described.

N. 89°55' W., bet. secs. 1 and 36.

Over rolling land.

40.00

Point for the 1/4 sec. cor. of secs. 1 and 36.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 27 N		R 23 E
S 36		
1/4		—
S 1		
T 26 N		

2002

Deposit a magnet in a white plastic case at the base of the stainless steel post.

80.00

Point for the cor. of secs. 1, 2, 35, and 36.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the North Boundary,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS											
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 27 N</td><td>R 23 E</td></tr> <tr><td>S 35</td><td>S 36</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td colspan="2">T 26 N</td></tr> </table>	T 27 N	R 23 E	S 35	S 36	S 2	S 1	T 26 N			
T 27 N	R 23 E										
S 35	S 36										
S 2	S 1										
T 26 N											
	2002										
	Deposit a magnet in a white plastic case at the base of the stainless steel post.										
	Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.										

	N. 89°55' W., bet. secs. 2 and 35.										
	Over rolling land.										
29.42	Apache County Road C286, a graded road, 20 ft. wide, bears NE and SW.										
40.00	Point for the 1/4 sec. cor. of secs. 2 and 35.										
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 27 N</td><td>R 23 E</td></tr> <tr><td colspan="2">S 35</td></tr> <tr><td colspan="2">1/4 _____</td></tr> <tr><td colspan="2">S 2</td></tr> <tr><td colspan="2">T 26 N</td></tr> </table>	T 27 N	R 23 E	S 35		1/4 _____		S 2		T 26 N	
T 27 N	R 23 E										
S 35											
1/4 _____											
S 2											
T 26 N											
	2002										
	Deposit a magnet in a white plastic case at the base of the stainless steel post.										
58.33	Trail road, bears SSE and NNW.										
80.00	Point for the cor. of secs. 2, 3, 34, and 35.										
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 27 N</td><td>R 23 E</td></tr> <tr><td>S 34</td><td>S 35</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td colspan="2">T 26 N</td></tr> </table>	T 27 N	R 23 E	S 34	S 35	S 3	S 2	T 26 N			
T 27 N	R 23 E										
S 34	S 35										
S 3	S 2										
T 26 N											
	2002										

**Survey of the North Boundary,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located on top of a rim, bears ENE and WSW.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 89°55' W., bet. secs. 3 and 34.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 23 E S 34 1/4 ——— S 3 T 26 N 2002</p>
78.46	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 12 lks. N. of a wash, 10 ft. wide, 2 ft. deep, drains SW.</p> <p>Base of a sandstone ledge, 7 ft. high, bears NE and SW.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 23 E S 33 S 34 S 4 S 3 T 26 N 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of the North Boundary,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 89°55' W., bet. secs. 4 and 33.</p> <p>Over nearly level land.</p>
9.32	Navajo Route 9054, a graded road, 25 ft. wide, bears NNE and SSW.
35.87	Steamboat Wash, 40 ft. wide, 15 ft. deep, drains SSE.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 33.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 23 E S 33 1/4 ——— S 4 T 26 N</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
42.20	Wash, 15 ft. wide, 8 ft. deep, drains NNW.
80.00	Point for the cor. of secs. 4, 5, 32, and 33.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 23 E S 32 S 33 S 5 S 4 T 26 N</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, nearly level to rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>

**Survey of the North Boundary,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>N. 89°55' W., bet. secs. 5 and 32.</p> <p>Over rolling and broken land.</p>
28.57	<p>Navajo Route, 9031, a graded road, 25 ft. wide, bears SSE and NNW.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> T 27 N R 23 E S 32 1/4 ——— S 5 T 26 N </p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> T 27 N R 23 E S 31 S 32 S 6 S 5 T 26 N </p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.07 chs. S. of Navajo Route 9031, a graded road, 20 ft. wide, bears ESE and WNW.</p> <p>Land, rolling and broken. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 89°55' W., bet. secs. 6 and 31.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p>

**Survey of the North Boundary,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 N R 23 E S 31 1/4 ——— S 6 T 26 N</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
81.01	<p>The cor. of Tps. 26 and 27 N., Rs. 22 and 23 E., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p style="text-align: center;">Survey of the Subdivisional Lines, T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., with brass cap, set, and mkd. as described in the field notes of the survey of the north boundary, T. 25 N. R. 23 E., executed concurrently under this same group.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E 1/4 S 35 S 36</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 25, 26, 35, and 36.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 26 N</td> <td>R 23 E</td> </tr> <tr> <td>S 26</td> <td>S 25</td> </tr> <tr> <td>S 35</td> <td>S 36</td> </tr> </table> </p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°55' W., bet. secs. 25 and 36.</p> <p>Over rolling and broken land.</p>	T 26 N	R 23 E	S 26	S 25	S 35	S 36		
T 26 N	R 23 E								
S 26	S 25								
S 35	S 36								
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 26 N</td> <td>R 23 E</td> </tr> <tr> <td></td> <td>S 25</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S 36</td> </tr> </table> </p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 26 N	R 23 E		S 25	1/4	—		S 36
T 26 N	R 23 E								
	S 25								
1/4	—								
	S 36								
80.00	<p>The cor. of secs. 25, 26, 35, and 36.</p> <p>Land, rolling and broken. Soil, sandy and gravelly clay. Timber, scattered juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over rolling land.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p>								

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E 1/4 S 26 S 25</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 23, 24, 25, and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E S 23 S 24 S 26 S 25</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°55' W., bet. secs. 24 and 25.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E S 24 1/4 ——— S 25</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
46.46	Navajo Route 9031, a graded road, 20 ft. wide, bears SE and NW.
80.00	The cor. of secs. 23, 24, 25, and 26. Land, rolling. Soil, sandy clay. Timber, scattered juniper; undergrowth, brush and native grasses.

	N. 0°01' W., bet. secs. 23 and 24. Over rolling land.
28.57	Navajo Route 9031, a graded road, 20 ft. wide, bears SE and NW.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 23 E 1/4 S 23 S 24 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 13, 14, 23, and 24. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 23 E S 14 S 13 ----- S 23 S 24 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Land, rolling. Soil, sandy clay. Timber, scattered juniper; undergrowth, brush and native grasses.

	From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>N. 89°55' W., bet. secs. 13 and 24.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E S 13 1/4 ——— S 24</p> <p style="text-align: center;">2002</p>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 13, 14, 23, and 24.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered juniper; undergrowth, brush and native grasses.</p> <hr/>
40.00	<p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E 1/4 S 14 S 13</p> <p style="text-align: center;">2002</p>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 11, 12, 13, and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N R 23 E S 11 S 12 S 14 S 13
	2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling. Soil, sandy clay. Timber, scattered juniper; undergrowth, brush and native grasses.
	From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.
	N. 89°55' W., bet. secs. 12 and 13.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 12 and 13.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 23 E S 12 1/4 ——— S 13
	2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	The cor. of secs. 11, 12, 13, and 14.
	Land, rolling. Soil, sandy clay. Timber, scattered juniper; undergrowth, brush and native grasses.
	N. 0°01' W., bet. secs. 11 and 12.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p style="text-align: center;">T 26 N R 23 E 1/4 S 11 S 12</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E S 2 S 1 S 11 S 12</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°55' W., bet. secs. 1 and 12.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E S 1 1/4 ——— S 12</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 1, 2, 11, and 12.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy clay. Timber, scattered juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E 1/4 S 2 S 1</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.75 chs. N. of a trail road, bears NNE and SSW.</p>
80.00	<p>The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 34 and 35 only, on the S. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., with brass cap, set, and mkd. as described in the field notes of the survey of the north boundary, T. 25 N. R. 23 E., executed concurrently under this same group.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p align="center">T 26 N R 23 E 1/4 S 34 S 35</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 26, 27, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 23 E S 27 S 26 S 34 S 35</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>N. 89°55' W., bet. secs. 26 and 35.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 23 E S 26 1/4 ——— S 35</p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 26, 27, 34, and 35.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy clay. No timber, scattered brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E 1/4 S 27 S 26</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
71.06	<p>Trail road, bears NE and SW.</p>
80.00	<p>Point for the cor. of secs. 22, 23, 26, and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E S 22 S 23 S 27 S 26</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>N. 89°55' W., bet. secs. 23 and 26.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E S 23 1/4 ——— S 26</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
65.33	Trail road, bears ENE and WSW.
80.00	<p>The cor. of secs. 22, 23, 26, and 27.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E 1/4 S 22 S 23</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22, and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E S 15 S 14 S 22 S 23</p> <p style="text-align: center;">2002</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 14, 23, and 24. N. 89°55' W., bet. secs. 14 and 23. Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 23 E S 14 1/4 ——— S 23</p> <p>2002</p> </div>
56.48	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Wash, 12 ft. wide, 10 ft. deep, drains SSE.</p>
62.99	<p>Navajo Route 9031, a graded road, 26 ft. wide, bears SSE and NNW.</p>
80.00	<p>The cor. of secs. 14, 15, 22, and 23.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 14 and 15. Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N R 23 E 1/4 S 15 S 14 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 10, 11, 14, and 15. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 23 E S 10 S 11 S 15 S 14 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located 23 lks. S. of a trail road, bears SE and NW. Land, rolling. Soil, sandy clay. Timber, scattered juniper; undergrowth, brush and native grasses.
	<hr/> From the cor. of secs. 11, 12, 13, and 14. N. 89°55' W., bet. secs. 11 and 14. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 14. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 23 E S 11 1/4 ——— S 14 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
73.16	Navajo Route 9031, a graded road, 26 ft. wide, bears N. and S.
80.00	The cor. of secs. 10, 11, 14, and 15. Land, rolling. Soil, sandy clay. Timber, scattered juniper; undergrowth, brush and native grasses.
	N. 0°01' W., bet. secs. 10 and 11. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 23 E 1/4 S 10 S 11 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
55.86	Navajo Route 9031, a graded road, 26 ft. wide, bears SE and NW.
60.59	Apache County Road C434, a graded road, 26 ft. wide, bears SSE and NNW.
80.00	Point for the cor. of secs. 2, 3, 10, and 11. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 23 E S 3 S 2 S 10 S 11 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>N. 89°55' W., bet. secs. 2 and 11.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E S 2 1/4 ——— S 11</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 2, 3, 10, and 11.</p> <p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E 1/4 S 3 S 2</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 75 lks. S. of Apache County Road C286, a graded road, 18 ft. wide, bears NE and SW.</p>
80.00	<p>The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., hereinbefore described.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 33 and 34 only, on the S. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., with brass cap, set, and mkd. as described in the field notes of the survey of the north boundary, T. 25 N. R. 23 E., executed concurrently under this same group.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over gently rolling land.</p>
12.87	Trail road, bears SSE and NNW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 23 E 1/4 S 33 S 34</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 27, 28, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 23 E S 28 S 27 S 33 S 34</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 26, 27, 34, and 35.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 89°55' W., bet. secs. 27 and 34. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 23 E S 27 1/4 ——— S 34 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
45.81	Trail road, bears NNE and SSW.
80.00	The cor. of secs. 27, 28, 33, and 34. Land, rolling. Soil, sandy clay. No timber, scattered brush and native grasses.
<hr/>	
	N. 0°02' W., bet. secs. 27 and 28. Over rolling land.
14.50	Trail road, bears NE and SW.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 28. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 23 E 1/4 S 28 S 27 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
46.15	Wash, 30 ft. wide, 6 ft. deep, drains SSW.
64.82	Trail road, bears NNE and SSW.
80.00	Point for the cor. of secs. 21, 22, 27, and 28.

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> T 26 N R 23 E S 21 S 22 S 28 S 27 </p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy clay. No timber, scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>N. 89°55' W., bet. secs. 22 and 27.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center"> T 26 N R 23 E S 22 1/4 ——— S 27 </p> <p align="center">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
43.58	<p>Wash, 20 ft. wide, 4 ft. deep, drains SW.</p>
68.01	<p>Trail road, bears NE and SW.</p>
80.00	<p>The cor. of secs. 21, 22, 27, and 28.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T 26 N R 23 E 1/4 S 21 S 22 2002 </div>
80.00	Deposit a magnet in a white plastic case at the base of the stainless steel post. Point for the cor. of secs. 15, 16, 21, and 22. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 23 E S 16 S 15 S 21 S 22 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	From the cor. of secs. 14, 15, 22, and 23. N. 89°55' W., bet. secs. 15 and 22. Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 22. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N R 23 E S 15 1/4 ——— S 22 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
53.25	Trail road, bears N. and S.
80.00	The cor. of secs. 15, 16, 21, and 22. Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	N. 0°02' W., bet. secs. 15 and 16.
	Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 26 N R 23 E 1/4 S 16 S 15 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
52.92	Trail road, bears ESE and WNW.
80.00	Point for the cor. of secs. 9, 10, 15, and 16. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 23 E S 9 S 10 S 16 S 15 2002

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 1.47 chs. S. of a wash, 10 ft. wide, 3 ft. deep, drains WNW.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>N. 89°55' W., bet. secs. 10 and 15.</p> <p>Over rolling and broken land.</p>
19.09	Trail road, bears NE and SW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 23 E</p> <p>S 10</p> <p>1/4 ———</p> <p>S 15</p> <p>2002</p> </div>
76.28	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Wash, 10 ft. wide, 3 ft. deep, drains WNW.</p>
80.00	<p>The cor. of secs. 9, 10, 15, and 16.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N R 23 E 1/4 S 9 S 10 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
49.89	Trail road, bears ENE and WSW.
54.84	S. rim of a canyon, bears ESE and WNW.
69.81	Navajo Route 9031, a graded road, 20 ft. wide, bears ESE and WNW.
71.03	Trail road, bears ENE and WSW.
73.80	Wash, 15 ft. wide, 8 ft. deep, drains SW.
80.00	Point for the cor. of secs. 3, 4, 9, and 10.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 23 E S 4 S 3 ———— S 9 S 10 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located 1.59 chs. S. of a sandstone cliff, 15 ft. high, bears ENE and WSW.
	Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	From the cor. of secs. 2, 3, 10, and 11.
	N. 89°55' W., bet. secs. 3 and 10.
	Over rolling and broken land.
7.90	Apache County Road C434, a graded road, 20 ft. wide, bears SSE and NNW.

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
29.44	SE rim of a narrow canyon, bears ENE and WSW.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 10. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 23 E S 3 1/4 ——— S 10 2002 </div>
80.00	Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located 2.47 chs. E. of a narrow, rocky spur ridge, bears NE and SW. The cor. of secs. 3, 4, 9, and 10. Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
40.00	<hr/> N. 0°02' W., bet. secs. 3 and 4. Over rolling and broken land. Point for the 1/4 sec. cor. of secs. 3 and 4. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 23 E 1/4 S 4 S 3 2002 </div>
43.58	Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located 8 lks. E. of a ditch on a bank, 7 ft. wide, 3 ft. deep, drains N. Rim of a valley, bears ENE and WSW.
63.30	Apache County Road C434, a graded road, 20 ft. wide, bears ESE and WNW.

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
68.33	Trail road, at the base of the valley, bears E. and W.
80.00	The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described. Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	From the cor. of secs. 32 and 33 only, on the S. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., with brass cap, set, and mkd. as described in the field notes of the survey of the north boundary, T. 25 N. R. 23 E., executed concurrently under this same group. N. 0°03' W., bet. secs. 32 and 33. Over nearly level land.
24.34	Underground gas pipeline, bears SSE and NNW.
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 23 E 1/4 S 32 S 33 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 28, 29, 32, and 33. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 23 E S 29 S 28 S 32 S 33 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 27, 28, 33, and 34. N. 89°55' W., bet. secs. 28 and 33. Over gently rolling land.</p>
13.99	Trail road, bears NE and SW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 33. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E S 28 1/4 ——— S 33</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 28, 29, 32, and 33. Land, gently rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 28 and 29. Over nearly level land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E 1/4 S 29 S 28</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS									
70.90	Steamboat Wash, 20 ft. wide, 8 ft. deep, drains WSW.								
80.00	Point for the cor. of secs. 20, 21, 28, and 29. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 26 N</td><td>R 23 E</td></tr> <tr><td>S 20</td><td>S 21</td></tr> <tr><td>S 29</td><td>S 28</td></tr> </table> <p>2002</p> </div>	T 26 N	R 23 E	S 20	S 21	S 29	S 28		
T 26 N	R 23 E								
S 20	S 21								
S 29	S 28								
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.								
	<hr/> From the cor. of secs. 21, 22, 27, and 28. N. 89°55' W., bet. secs. 21 and 28. Over rolling land.								
40.00	Point for the 1/4 sec. cor. of secs. 21 and 28. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 26 N</td><td>R 23 E</td></tr> <tr><td></td><td>S 21</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S 28</td></tr> </table> <p>2002</p> </div>	T 26 N	R 23 E		S 21	1/4	—		S 28
T 26 N	R 23 E								
	S 21								
1/4	—								
	S 28								
	Deposit a magnet in a white plastic case at the base of the stainless steel post.								
73.98	Steamboat Wash, 40 ft. wide, 10 ft. deep, drains SW.								
80.00	The cor. of secs. 20, 21, 28, and 29. Land, rolling and broken. Soil, sandy and gravelly clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.								

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 0°03' W., bet. secs. 20 and 21. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 21. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 23 E 1/4 S 20 S 21 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located 68 lks. S. of a trail road, bears NNE and SSW.
80.00	Point for the cor. of secs. 16, 17, 20, and 21. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 23 E S 17 S 16 S 20 S 21 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located 1.09 chs. N. of Steamboat Wash, 60 ft. wide, 15 ft. deep, drains SW. Land, rolling. Soil, sandy and gravelly clay. No timber; scattered brush and native grasses.
	From the cor. of secs. 15, 16, 21, and 22.
	N. 89°55' W., bet. secs. 16 and 21. Over rolling and broken land.
27.76	Top of a rim, bears NE and SW, thence descend into Steamboat Wash valley.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 21.

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E S 16 1/4 ——— S 21</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
73.08	Steamboat Wash, 100 ft. wide, 15 ft. deep, drains SSW.
80.00	<p>The cor. of secs. 16, 17, 20, and 21.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E 1/4 S 17 S 16</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 8, 9, 16, and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E S 8 S 9 S 17 S 16</p> <p style="text-align: center;">2002</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and gravelly clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>N. 89°55' W., bet. secs. 9 and 16.</p> <p>Over nearly level land, across the Steamboat Wash valley.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 23 E S 9 1/4 — S 16</p> <p align="center">2002</p>
62.52	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Steamboat Wash, 120 ft. wide, 15 ft. deep, drains SSW.</p>
80.00	<p>The cor. of secs. 8, 9, 16, and 17.</p> <p>Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/>
40.00	<p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 26 N R 23 E 1/4 S 8 S 9</p> <p align="center">2002</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 69 lks. N. of a trail road, bears NE and SW and 55 lks. S. of another trail road, bears NE and SW.</p> <p>80.00 Point for the cor. of secs. 4, 5, 8, and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 26 N</td> <td style="padding: 0 10px;">R 23 E</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 5</td> <td style="padding: 0 10px;">S 4</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 8</td> <td style="padding: 0 10px;">S 9</td> </tr> </table> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy and gravelly clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>N. 89°55' W., bet. secs. 4 and 9.</p> <p>Over rolling land.</p> <p>21.30 Base of a rim, bears NNE and SSW, thence across Steamboat Wash valley.</p> <p>25.12 Steamboat Wash, 70 ft. wide, 15 ft. deep, drains S.</p> <p>28.65 Navajo Route 9054, a graded road, 20 ft. wide, bears NE and SW.</p> <p>31.26 Navajo Route 9031, a graded road, 20 ft. wide, bears SE and NW.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 26 N</td> <td style="padding: 0 10px;">R 23 E</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 4</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="padding: 0 10px; border-top: 1px solid black;">S 9</td> </tr> </table> <p>2002</p> </div>	T 26 N	R 23 E	S 5	S 4	S 8	S 9	T 26 N	R 23 E		S 4	1/4	S 9
T 26 N	R 23 E												
S 5	S 4												
S 8	S 9												
T 26 N	R 23 E												
	S 4												
1/4	S 9												

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	The cor. of secs. 4, 5, 8, and 9. Land, rolling to nearly level. Soil, sandy clay. Timber, piñon and juniper on eastern part; undergrowth, brush and native grasses.
	N. 0°02' W., bet. secs. 4 and 5.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 23 E 1/4 S 5 S 4 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located 97 lks. N. of a trail road, bears ENE and WSW.
51.92	Navajo Route 9031, a graded road, 20 ft. wide, bears NNE and SSW.
79.99	The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described. Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	From the cor. of secs. 31 and 32 only, on the S. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., with brass cap, set, and mkd. as described in the field notes of the survey of the north boundary, T. 25 N. R. 23 E., executed concurrently under this same group.
	N. 0°03' W., bet. secs. 31 and 32.
	Over gently rolling land.

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E 1/4 S 31 S 32</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E S 30 S 29 S 31 S 32</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>N. 89°55' W., bet. secs. 29 and 32.</p> <p>Over nearly level land.</p>
23.81	Power line, bears SSE and NNW.
24.36	Underground gas pipeline, bears SSE and NNW.
30.00	Steamboat Wash, 35 ft. wide, 25 ft. deep, drains SSW.
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N R 23 E S 29 1/4 ——— S 32 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	The cor. of secs. 29, 30, 31, and 32. Land, nearly level. Soil, sandy clay. No timber; scattered brush and native grasses.
	<hr/> N. 89°55' W., bet. secs. 30 and 31. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 23 E S 30 1/4 ——— S 31 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
81.44	The cor. of secs. 25, 30, 31, and 36 on the W. bdy. of the Tp., hereinbefore described. Land, gently rolling. Soil, sandy clay. No timber; scattered brush and native grasses.
	<hr/> From the cor. of secs. 29, 30, 31, and 32. N. 0°03' W., bet. secs. 29 and 30. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30.

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E 1/4 S 30 S 29</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 20 lks. N. of a trail road, bears SE and NW, and 1.13 chs. S. of another trail road, bears ENE and WSW.</p>
80.00	<p>Point for the cor. of secs. 19, 20, 29, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E S 19 S 20 S 30 S 29</p> <p style="text-align: center;">2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; scattered brush and native grasses.</p> <hr/> <p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>N. 89°55' W., bet. secs. 20 and 29.</p> <p>Over gently rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 N R 23 E S 20 1/4 ——— S 29</p> <p style="text-align: center;">2002</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
58.82	Power line, bears SSE and NNW.
59.44	Underground gas pipeline, bears SSE and NNW.
80.00	The cor. of secs. 19, 20, 29, and 30. Land, gently rolling. Soil, sandy clay. No timber; scattered brush and native grasses.
	<hr/>
	N. 89°55' W., bet. secs. 19 and 30. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 23 E S 19 1/4 ——— S 30 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
81.35	The cor. of secs. 19, 24, 25, and 30 on the W. bdy. of the Tp., hereinbefore described. Land, rolling. Soil, sandy and gravelly clay. Timber, scattered piñon and juniper; undergrowth, brush and native grasses.
	<hr/>
	From the cor. of secs. 19, 20, 29, and 30. N. 0°03' W., bet. secs. 19 and 20. Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 20. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N R 23 E 1/4 S 19 S 20 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
47.01	Underground gas pipeline, bears SSE and NNW.
48.37	Power line, bears SSE and NNW.
80.00	Point for the cor. of secs. 17, 18, 19, and 20.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 23 E S 18 S 17 S 19 S 20 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located 11 lks. E. and 1.04 chs. S. of a power line, bears NNE and SSW.
	Cor. is also located 63 lks. E. of an underground gas pipeline, bears NNE and SSW.
	Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	<hr/>
	From the cor. of secs. 16, 17, 20, and 21.
	N. 89°55' W., bet. secs. 17 and 20.
	Over rolling and broken land, ascend out of Steamboat Wash valley.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 20.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T 26 N R 23 E S 17 1/4 ——— S 20 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.00	<p>The cor. of secs. 17, 18, 19, and 20.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>
	<p>N. 89°55' W., bet. secs. 18 and 19.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 26 N R 23 E S 18 1/4 ——— S 19 2002</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
81.26	<p>The cor. of secs. 13, 18, 19, and 24 on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/>
	<p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over rolling and broken land.</p>
4.60	<p>Underground gas pipeline, bears N. and S.</p>
13.79	<p>Underground gas pipeline, bears SSE and NNW.</p>

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
15.04	Power line, bears SSE and NNW.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 18. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 23 E 1/4 S 18 S 17 2002 </div>
80.00	Point for the cor. of secs. 7, 8, 17, and 18. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 26 N R 23 E S 7 S 8 S 18 S 17 2002 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	From the cor. of secs. 8, 9, 16, and 17. N. 89°55' W., bet. secs. 8 and 17. Over rolling and broken land, ascend out of Steamboat Wash valley.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 17. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in sandstone, with brass cap mkd. <div style="text-align: center;"> T 26 N R 23 E S 8 1/4 ——— S 17 2002 </div>

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	The cor. of secs. 7, 8, 17, and 18. Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	<hr/>
	N. 89°55' W., bet. secs. 7 and 18. Over rolling and broken land.
25.58	Underground gas pipeline, bears SSE and NNW.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 23 E S 7 1/4 _____ S 18 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post. Cor. is located halfway up the W. slope of a hill.
81.17	The cor. of secs. 7, 12, 13, and 18 on the W. bdy. of the Tp., hereinbefore described. Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	<hr/>
	From the cor. of secs. 7, 8, 17, and 18. N. 0°03' W., bet. secs. 7 and 8. Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 26 N R 23 E 1/4 S 7 S 8 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 5, 6, 7, and 8. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 23 E S 6 S 5 S 7 S 8 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.
	<hr/> From the cor. of secs. 4, 5, 8, and 9. N. 89°55' W., bet. secs. 5 and 8. Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 8. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 26 N R 23 E S 5 1/4 ——— S 8 2002
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	The cor. of secs. 5, 6, 7, and 8.

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>N. 89°55' W., bet. secs. 6 and 7.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 23 E S 6 1/4 ——— S 7</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
74.45	<p>Underground gas pipeline, bears SSE and NNW.</p>
81.08	<p>The cor. of secs. 1, 6, 7, and 12 on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 N R 23 E 1/4 S 6 S 5</p> <p>2002</p> </div>

**Survey of the Subdivisional Lines,
T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.99	<p>The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling and broken. Soil, sandy and rocky clay. Timber, piñon and juniper; undergrowth, brush and native grasses.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>The community of Toyei, Arizona is located about one half mile north of the northwest corner of the township surveyed. The terrain varies from nearly level in the southwest portion of the township to rolling and broken land atop mesas. The main drainage is Steamboat Wash, draining southerly throughout the township.</p> <p>The elevation varies from 6000 to 6500 feet above sea level. The soil is mostly sandy and sandy clay with some areas mixed with gravel and rocks. The timber consists of piñon and juniper. The undergrowth are sagebrush, cacti, greasewood, and native grasses.</p> <p>Principal access to the township is provided by Navajo Route 9031, which enters the township in section 5 and intersects Navajo Route 9054 in section 9 and exits to southeast in section 25. From these main routes there are numerous trail roads throughout the township. There are scattered livestock throughout the township. There is no mining activity in the township.</p> <p>The mean magnetic declination of $11 \frac{3}{4}^{\circ}$ E. was derived from the computer program GEOMAGIX utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.</p> <hr/>

CERTIFICATE OF SURVEY

I, Leonard R. Sandoval, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 22nd day of January, 2001, I have surveyed the east, west, and north boundaries, and the subdivisional lines, T. 26 N., R. 23 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

March 29, 2004
(Date)

Leonard R. Sandoval
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Phoenix, Arizona

The foregoing field notes of the survey of the east, west, and north boundaries, and the subdivisional lines, T. 26 N., R. 23 E., Gila and Salt River Meridian, in the State of Arizona, executed by Leonard R. Sandoval, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

March 30, 2004
(Date)

Lenny D. Pavulak
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 26 N., R. 23 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____~~
~~(Date)~~

~~_____~~
~~(Chief Cadastral Surveyor of Arizona)~~